
python-gitlab Documentation

Release 3.14.0

Gauvain Pocentek, Mika Mäenpää

Apr 11, 2023

TABLE OF CONTENTS

1 Features	3
2 Installation	5
3 Using the docker images	7
3.1 Building the image	7
4 Bug reports	9
5 Gitter Community Chat	11
6 Documentation	13
6.1 Build the docs	13
7 Contributing	15
7.1 Getting started with the CLI	15
7.2 Getting started with the API	20
7.3 Advanced usage	27
7.4 CLI examples	30
7.5 API examples	35
7.6 API reference (gitlab package)	154
7.7 CLI reference (gitlab command)	480
7.8 Lower-level APIs	823
7.9 Changelog	825
7.10 Release notes	865
7.11 FAQ	869
8 Indices and tables	871
Python Module Index	873
Index	875

`python-gitlab` is a Python package providing access to the GitLab server API.

It supports the v4 API of GitLab, and provides a CLI tool (`gitlab`).

**CHAPTER
ONE**

FEATURES

`python-gitlab` enables you to:

- write Pythonic code to manage your GitLab resources.
- pass arbitrary parameters to the GitLab API. Simply follow GitLab's docs on what parameters are available.
- access arbitrary endpoints as soon as they are available on GitLab, by using lower-level API methods.
- use persistent requests sessions for authentication, proxy and certificate handling.
- handle smart retries on network and server errors, with rate-limit handling.
- flexible handling of paginated responses, including lazy iterators.
- automatically URL-encode paths and parameters where needed.
- automatically convert some complex data structures to API attribute types
- merge configuration from config files, environment variables and arguments.

**CHAPTER
TWO**

INSTALLATION

As of 3.0.0, `python-gitlab` is compatible with Python 3.7+.

Use pip to install the latest stable version of `python-gitlab`:

```
$ pip install --upgrade python-gitlab
```

The current development version is available on both [GitHub.com](#) and [GitLab.com](#), and can be installed directly from the git repository:

```
$ pip install git+https://github.com/python-gitlab/python-gitlab.git
```

From GitLab:

```
$ pip install git+https://gitlab.com/python-gitlab/python-gitlab.git
```


USING THE DOCKER IMAGES

python-gitlab provides Docker images in two flavors, based on the Alpine and Debian slim python base images. The default tag is alpine, but you can explicitly use the alias (see below).

The alpine image is smaller, but you may want to use the Debian-based slim tag (currently based on -slim-bullseye) if you are running into issues or need a more complete environment with a bash shell, such as in CI jobs.

The images are published on the GitLab registry, for example:

- `registry.gitlab.com/python-gitlab/python-gitlab:latest` (latest, alpine alias)
- `registry.gitlab.com/python-gitlab/python-gitlab:alpine` (latest alpine)
- `registry.gitlab.com/python-gitlab/python-gitlab:slim-bullseye` (latest slim-bullseye)
- `registry.gitlab.com/python-gitlab/python-gitlab:v3.2.0` (alpine alias)
- `registry.gitlab.com/python-gitlab/python-gitlab:v3.2.0-alpine`
- `registry.gitlab.com/python-gitlab/python-gitlab:v3.2.0-slim-bullseye`

You can run the Docker image directly from the GitLab registry:

```
$ docker run -it --rm registry.gitlab.com/python-gitlab/python-gitlab:latest <command> ..  
→ .
```

For example, to get a project on GitLab.com (without authentication):

```
$ docker run -it --rm registry.gitlab.com/python-gitlab/python-gitlab:latest project get  
→ --id gitlab-org/gitlab
```

You can also mount your own config file:

```
$ docker run -it --rm -v /path/to/python-gitlab.cfg:/etc/python-gitlab.cfg registry.  
→ gitlab.com/python-gitlab/python-gitlab:latest <command> ...
```

3.1 Building the image

To build your own image from this repository, run:

```
$ docker build -t python-gitlab:latest .
```

Run your own image:

```
$ docker run -it --rm python-gitlab:latest <command> ...
```

Build a Debian slim-based image:

```
$ docker build -t python-gitlab:latest --build-arg PYTHON_FLAVOR=slim-bullseye .
```

**CHAPTER
FOUR**

BUG REPORTS

Please report bugs and feature requests at <https://github.com/python-gitlab/python-gitlab/issues>.

**CHAPTER
FIVE**

GITTER COMMUNITY CHAT

We have a [gitter](#) community chat available at <https://gitter.im/python-gitlab/Lobby>, which you can also directly access via the Open Chat button below.

If you have a simple question, the community might be able to help already, without you opening an issue. If you regularly use python-gitlab, we also encourage you to join and participate. You might discover new ideas and use cases yourself!

**CHAPTER
SIX**

DOCUMENTATION

The full documentation for CLI and API is available on [readthedocs](#).

6.1 Build the docs

We use `tox` to manage our environment and build the documentation:

```
pip install tox
tox -e docs
```


CONTRIBUTING

For guidelines for contributing to `python-gitlab`, refer to [CONTRIBUTING.rst](#).

7.1 Getting started with the CLI

`python-gitlab` provides a `gitlab` command-line tool to interact with GitLab servers.

This is especially convenient for running quick ad-hoc commands locally, easily interacting with the API inside GitLab CI, or with more advanced shell scripting when integrating with other tooling.

7.1.1 Configuration

`gitlab` allows setting configuration options via command-line arguments, environment variables, and configuration files.

For a complete list of global CLI options and their environment variable equivalents, see [*CLI reference \(gitlab command\)*](#).

With no configuration provided, `gitlab` will default to unauthenticated requests against [GitLab.com](#).

With no configuration but running inside a GitLab CI job, it will default to authenticated requests using the current job token against the current instance (via `CI_SERVER_URL` and `CI_JOB_TOKEN` environment variables).

Warning: Please note the job token has very limited permissions and can only be used with certain endpoints. You may need to provide a personal access token instead.

When you provide configuration, values are evaluated with the following precedence:

1. Explicitly provided CLI arguments,
2. Environment variables,
3. Configuration files:
 - a. explicitly defined config files:
 - i. via the `--config-file` CLI argument,
 - ii. via the `PYTHON_GITLAB_CFG` environment variable,
 - b. user-specific config file,
 - c. system-level config file,
4. Environment variables always present in CI (`CI_SERVER_URL`, `CI_JOB_TOKEN`).

Additionally, authentication will take the following precedence when multiple options or environment variables are present:

1. Private token,
2. OAuth token,
3. CI job token.

Configuration files

`gitlab` looks up 3 configuration files by default:

The `PYTHON_GITLAB_CFG` environment variable

An environment variable that contains the path to a configuration file.

`/etc/python-gitlab.cfg`

System-wide configuration file

`~/.python-gitlab.cfg`

User configuration file

You can use a different configuration file with the `--config-file` option.

Warning: If the `PYTHON_GITLAB_CFG` environment variable is defined and the target file exists, it will be the only configuration file parsed by `gitlab`.

If the environment variable is defined and the target file cannot be accessed, `gitlab` will fail explicitly.

Configuration file format

The configuration file uses the INI format. It contains at least a `[global]` section, and a specific section for each GitLab server. For example:

```
[global]
default = somewhere
ssl_verify = true
timeout = 5

[somewhere]
url = https://some.whe.re
private_token = vTbFeqJCY3sibBP7BZM
api_version = 4

[elsewhere]
url = http://else.whe.re:8080
private_token = helper: path/to/helper.sh
timeout = 1
```

The `default` option of the `[global]` section defines the GitLab server to use if no server is explicitly specified with the `--gitlab` CLI option.

The `[global]` section also defines the values for the default connection parameters. You can override the values in each GitLab server section.

Table 1: Global options

Option	Possible values	Description
ssl_verify	True, False, or a str	Verify the SSL certificate. Set to <code>False</code> to disable verification, though this will create warnings. Any other value is interpreted as path to a CA_BUNDLE file or directory with certificates of trusted CAs.
timeout	Integer	Number of seconds to wait for an answer before failing.
api_version	4	The API version to use to make queries. Only 4 is available since 1.5.0.
per_page	Integer between 1 and 100	The number of items to return in listing queries. GitLab limits the value at 100.
user_agent	str	A string defining a custom user agent to use when gitlab makes requests.

You must define the `url` in each GitLab server section.

Warning: Note that a url that results in 301/302 redirects will raise an error, so it is highly recommended to use the final destination in the `url` field. For example, if the GitLab server you are using redirects requests from http to https, make sure to use the `https://` protocol in the URL definition.

A URL that redirects using 301/302 (rather than 307/308) will most likely cause malformed POST and PUT requests. python-gitlab will therefore raise a `RedirectionError` when it encounters a redirect which it believes will cause such an error, to avoid confusion between successful GET and failing POST/PUT requests on the same instance.

Only one of `private_token`, `oauth_token` or `job_token` should be defined. If neither are defined an anonymous request will be sent to the Gitlab server, with very limited permissions.

We recommend that you use [Credential helpers](#) to securely store your tokens.

Table 2: GitLab server options

Option	Description
<code>url</code>	URL for the GitLab server. Do NOT use a URL which redirects.
<code>private_token</code>	Your user token. Login/password is not supported. Refer to the official documentation to learn how to obtain a token.
<code>oauth_token</code>	An Oauth token for authentication. The Gitlab server must be configured to support this authentication method.
<code>job_token</code>	Your job token. See the official documentation to learn how to obtain a token.
<code>api_version</code>	GitLab API version to use. Only 4 is available since 1.5.0.

Credential helpers

For all configuration options that contain secrets (for example, `personal_token`, `oauth_token`, `job_token`), you can specify a helper program to retrieve the secret indicated by a `helper:` prefix. This allows you to fetch values from a local keyring store or cloud-hosted vaults such as Bitwarden. Environment variables are expanded if they exist and `~` expands to your home directory.

It is expected that the helper program prints the secret to standard output. To use shell features such as piping to retrieve the value, you will need to use a wrapper script; see below.

Example for a `keyring` helper:

```
[global]
default = somewhere
ssl_verify = true
timeout = 5

[somewhere]
url = http://somewhe.re
private_token = helper: keyring get Service Username
timeout = 1
```

Example for a `pass` helper with a wrapper script:

```
[global]
default = somewhere
ssl_verify = true
timeout = 5

[somewhere]
url = http://somewhe.re
private_token = helper: /path/to/helper.sh
timeout = 1
```

In `/path/to/helper.sh`:

```
#!/bin/bash
pass show path/to/credentials | head -n 1
```

7.1.2 CLI

Objects and actions

The `gitlab` command expects two mandatory arguments. The first one is the type of object that you want to manipulate. The second is the action that you want to perform. For example:

```
$ gitlab project list
```

Use the `--help` option to list the available object types and actions:

```
$ gitlab --help
$ gitlab project --help
```

Some actions require additional parameters. Use the `--help` option to list mandatory and optional arguments for an action:

```
$ gitlab project create --help
```

Optional arguments

Use the following optional arguments to change the behavior of `gitlab`. These options must be defined before the mandatory arguments.

`--verbose, -v`

Outputs detail about retrieved objects. Available for legacy (default) output only.

`--config-file, -c`

Path to a configuration file.

`--gitlab, -g`

ID of a GitLab server defined in the configuration file.

`--output, -o`

Output format. Defaults to a custom format. Can also be `yaml` or `json`.

Important: The [PyYAML package](#) is required to use the `yaml` output option. You need to install it explicitly using `pip install python-gitlab[yaml]`

`--fields, -f`

Comma-separated list of fields to display (`yaml` and `json` output formats only). If not used, all the object fields are displayed.

Example:

```
$ gitlab -o yaml -f id,permissions -g elsewhere -c /tmp/gl.cfg project list
```

Reading values from files

You can make `gitlab` read values from files instead of providing them on the command line. This is handy for values containing new lines for instance:

```
$ cat > /tmp/description << EOF
This is the description of my project.

It is obviously the best project around
EOF
$ gitlab project create --name SuperProject --description @/tmp/description
```

If you want to explicitly pass an argument starting with `@`, you can escape it using `@@`:

```
$ gitlab project-tag list --project-id somenamespace/myproject
...
name: @at-started-tag
...
$ gitlab project-tag delete --project-id somenamespace/myproject --name '@@at-started-tag'
```

7.1.3 Enabling shell completion

To get completion, you'll need to install the package with the extra "completion":

```
pip install python_gitlab[completion]
```

Add the appropriate command below to your shell's config file so that it is run on startup. You will likely have to restart or re-login for the completion to start working.

Bash

```
eval "$(register-python-argcomplete gitlab)"
```

tcsh

```
eval `register-python-argcomplete --shell tcsh gitlab`
```

fish

```
register-python-argcomplete --shell fish gitlab | .
```

Zsh

Warning: Zsh completion support is broken right now in the argcomplete python package. Perhaps it will be fixed in a future release of argcomplete at which point the following instructions will enable completion in zsh.

To activate completions for zsh you need to have bashcompinit enabled in zsh:

```
autoload -U bashcompinit  
bashcompinit
```

Afterwards you can enable completion for gitlab:

```
eval "$(register-python-argcomplete gitlab)"
```

7.2 Getting started with the API

python-gitlab only supports GitLab API v4.

7.2.1 gitlab.Gitlab class

To connect to GitLab.com or another GitLab instance, create a `gitlab.Gitlab` object:

Hint: You can use different types of tokens for authenticated requests against the GitLab API. You will most likely want to use a resource (project/group) access token or a personal access token.

For the full list of available options and how to obtain these tokens, please see <https://docs.gitlab.com/ee/api/index.html#authentication>.

```
import gitlab

# anonymous read-only access for public resources (GitLab.com)
gl = gitlab.Gitlab()

# anonymous read-only access for public resources (self-hosted GitLab instance)
gl = gitlab.Gitlab('https://gitlab.example.com')

# private token or personal token authentication (GitLab.com)
gl = gitlab.Gitlab(private_token='JVNSEs8EwWRx5yDxM5q')

# private token or personal token authentication (self-hosted GitLab instance)
gl = gitlab.Gitlab(url='https://gitlab.example.com', private_token='JVNSEs8EwWRx5yDxM5q
                   ')

# oauth token authentication
gl = gitlab.Gitlab('https://gitlab.example.com', oauth_token='my_long_token_here')

# job token authentication (to be used in CI)
# bear in mind the limitations of the API endpoints it supports:
# https://docs.gitlab.com/ee/ci/jobs/ci_job_token.html
import os
gl = gitlab.Gitlab('https://gitlab.example.com', job_token=os.environ['CI_JOB_TOKEN'])

# Define your own custom user agent for requests
gl = gitlab.Gitlab('https://gitlab.example.com', user_agent='my-package/1.0.0')

# make an API request to create the gl.user object. This is not required but may be_
# useful
# to validate your token authentication. Note that this will not work with job tokens.
gl.auth()

# Enable "debug" mode. This can be useful when trying to determine what
# information is being sent back and forth to the GitLab server.
# Note: this will cause credentials and other potentially sensitive
# information to be printed to the terminal.
gl.enable_debug()
```

You can also use configuration files to create `gitlab.Gitlab` objects:

```
gl = gitlab.Gitlab.from_config('somewhere', ['/tmp/gl.cfg'])
```

See the [Configuration](#) section for more information about configuration files.

Warning: Note that a url that results in 301/302 redirects will raise an error, so it is highly recommended to use the final destination in the `url` field. For example, if the GitLab server you are using redirects requests from http to https, make sure to use the `https://` protocol in the URL definition.

A URL that redirects using 301/302 (rather than 307/308) will most likely cause malformed POST and PUT requests.

`python-gitlab` will therefore raise a `RedirectionError` when it encounters a redirect which it believes will cause such an error, to avoid confusion between successful GET and failing POST/PUT requests on the same instance.

Note on password authentication

GitLab has long removed password-based basic authentication. You can currently still use the [resource owner password credentials](#) flow to obtain an OAuth token.

However, we do not recommend this as it will not work with 2FA enabled, and GitLab is removing ROPC-based flows without client IDs in a future release. We recommend you obtain tokens for automated workflows as linked above or obtain a session cookie from your browser.

For a python example of password authentication using the ROPC-based OAuth2 flow, see [this Ansible snippet](#).

7.2.2 Managers

The `gitlab.Gitlab` class provides managers to access the GitLab resources. Each manager provides a set of methods to act on the resources. The available methods depend on the resource type.

Examples:

```
# list all the projects
projects = gl.projects.list(iterator=True)
for project in projects:
    print(project)

# get the group with id == 2
group = gl.groups.get(2)
for project in group.projects.list(iterator=True):
    print(project)
```

Warning: Calling `list()` without any arguments will by default not return the complete list of items. Use either the `get_all=True` or `iterator=True` parameters to get all the items when using listing methods. See the [Pagination](#) section for more information.

```
# create a new user
user_data = {'email': 'jen@foo.com', 'username': 'jen', 'name': 'Jen'}
user = gl.users.create(user_data)
print(user)
```

Note: `python-gitlab` attempts to sync the required, optional, and mutually exclusive attributes for resource creation and update with the upstream API.

You are encouraged to follow upstream API documentation for each resource to find these - each resource documented here links to the corresponding upstream resource documentation at the top of the page.

The attributes of objects are defined upon object creation, and depend on the GitLab API itself. To list the available information associated with an object use the `attributes` attribute:

```
project = gl.projects.get(1)
print(project.attributes)
```

Some objects also provide managers to access related GitLab resources:

```
# list the issues for a project
project = gl.projects.get(1)
issues = project.issues.list(get_all=True)
```

python-gitlab allows to send any data to the GitLab server when making queries. In case of invalid or missing arguments python-gitlab will raise an exception with the GitLab server error message:

```
>>> gl.projects.list(sort='invalid value')
...
GitlabListError: 400: sort does not have a valid value
```

You can use the `query_parameters` argument to send arguments that would conflict with python or python-gitlab when using them as kwargs:

```
gl.user_activities.list(from='2019-01-01', iterator=True) ## invalid

gl.user_activities.list(query_parameters={'from': '2019-01-01'}, iterator=True) # OK
```

7.2.3 Gitlab Objects

You can update or delete a remote object when it exists locally:

```
# update the attributes of a resource
project = gl.projects.get(1)
project.wall_enabled = False
# don't forget to apply your changes on the server:
project.save()

# delete the resource
project.delete()
```

Some classes provide additional methods, allowing more actions on the GitLab resources. For example:

```
# star a git repository
project = gl.projects.get(1)
project.star()
```

You can print a Gitlab Object. For example:

```
project = gl.projects.get(1)
print(project)
```

(continues on next page)

(continued from previous page)

```
# Or in a prettier format.  
project pprint()  
  
# Or explicitly via `pformat()`. This is equivalent to the above.  
print(project.pformat())
```

You can also extend the object if the parameter isn't explicitly listed. For example, if you want to update a field that has been newly introduced to the Gitlab API, setting the value on the object is accepted:

```
issues = project.issues.list(state='opened')  
for issue in issues:  
    issue.my_super_awesome_feature_flag = "random_value"  
    issue.save()
```

As a dictionary

You can get a dictionary representation copy of the Gitlab Object. Modifications made to the dictionary will have no impact on the GitLab Object.

- `asdict()` method. Returns a dictionary representation of the Gitlab object.
- **attributes property. Returns a dictionary representation of the Gitlab object.** Also returns any relevant parent object attributes.

```
project = gl.projects.get(1)  
project_dict = project.asdict()  
  
# Or a dictionary representation also containing some of the parent attributes  
issue = project.issues.get(1)  
attribute_dict = issue.attributes  
  
# The following will return the same value  
title = issue.title  
title = issue.attributes["title"]
```

Hint: This can be used to access attributes that clash with python-gitlab's own methods or managers. Note that:

`attributes` returns the parent object attributes that are defined in `object._from_parent_attrs`. For example, a `ProjectIssue` object will have a `project_id` key in the dictionary returned from `attributes` but `asdict()` will not.

As JSON

You can get a JSON string representation of the Gitlab Object. For example:

```
project = gl.projects.get(1)  
print(project.to_json())  
# Use arguments supported by ``json.dump()``  
print(project.to_json(sort_keys=True, indent=4))
```

7.2.4 Base types

The `gitlab` package provides some base types.

- `gitlab.Gitlab` is the primary class, handling the HTTP requests. It holds the GitLab URL and authentication information.
- `gitlab.base.RESTObject` is the base class for all the GitLab v4 objects. These objects provide an abstraction for GitLab resources (projects, groups, and so on).
- `gitlab.base.RESTManager` is the base class for v4 objects managers, providing the API to manipulate the resources and their attributes.

7.2.5 Lazy objects

To avoid useless API calls to the server you can create lazy objects. These objects are created locally using a known ID, and give access to other managers and methods.

The following example will only make one API call to the GitLab server to star a project (the previous example used 2 API calls):

```
# star a git repository
project = gl.projects.get(1, lazy=True)  # no API call
project.star()  # API call
```

7.2.6 head() methods

All endpoints that support `get()` and `list()` also support a `head()` method. In this case, the server responds only with headers and not the response JSON or body. This allows more efficient API calls, such as checking repository file size without fetching its content.

Note: In some cases, GitLab may omit specific headers. See more in the [Pagination](#) section.

```
# See total number of personal access tokens for current user
gl.personal_access_tokens.head()
print(headers["X-Total"])

# See returned content-type for project GET endpoint
headers = gl.projects.head("gitlab-org/gitlab")
print(headers["Content-Type"])
```

7.2.7 Pagination

You can use pagination to iterate over long lists. All the `Gitlab` objects listing methods support the `page` and `per_page` parameters:

```
ten_first_groups = gl.groups.list(page=1, per_page=10)
```

Warning: The first page is page 1, not page 0.

By default GitLab does not return the complete list of items. Use the `get_all` parameter to get all the items when using listing methods:

```
all_groups = gl.groups.list(get_all=True)

all_owned_projects = gl.projects.list(owned=True, get_all=True)
```

You can define the `per_page` value globally to avoid passing it to every `list()` method call:

```
gl = gitlab.Gitlab(url, token, per_page=50)
```

GitLab allows to also use keyset pagination. You can supply it to your project listing, but you can also do so globally. Be aware that GitLab then also requires you to only use supported order options. At the time of writing, only `order_by="id"` works.

```
gl = gitlab.Gitlab(url, token, pagination="keyset", order_by="id", per_page=100)
gl.projects.list()
```

Reference: <https://docs.gitlab.com/ce/api/README.html#keyset-based-pagination>

`list()` methods can also return a generator object, by passing the argument `iterator=True`, which will handle the next calls to the API when required. This is the recommended way to iterate through a large number of items:

```
items = gl.groups.list(iterator=True)
for item in items:
    print(item.attributes)
```

The generator exposes extra listing information as received from the server:

- `current_page`: current page number (first page is 1)
- `prev_page`: if `None` the current page is the first one
- `next_page`: if `None` the current page is the last one
- `per_page`: number of items per page
- `total_pages`: total number of pages available. This may be a `None` value.
- `total`: total number of items in the list. This may be a `None` value.

Note: For performance reasons, if a query returns more than 10,000 records, GitLab does not return the `total_pages` or `total` headers. In this case, `total_pages` and `total` will have a value of `None`.

For more information see: https://docs.gitlab.com/ee/user/gitlab_com/index.html#pagination-response-headers

Note: Prior to python-gitlab 3.6.0 the argument `as_list` was used instead of `iterator`. `as_list=False` is the equivalent of `iterator=True`.

Note: If `page` and `iterator=True` are used together, the latter is ignored.

7.2.8 Sudo

If you have the administrator status, you can use `sudo` to act as another user. For example:

```
p = gl.projects.create({'name': 'awesome_project'}, sudo='user1')
```

7.2.9 Attributes in updated objects

When methods manipulate an existing object, such as with `refresh()` and `save()`, the object will only have attributes that were returned by the server. In some cases, such as when the initial request fetches attributes that are needed later for additional processing, this may not be desired:

```
project = gl.projects.get(1, statistics=True)
project.statistics

project.refresh()
project.statistics # AttributeError
```

To avoid this, either copy the object/attributes before calling `refresh()/save()` or subsequently perform another `get()` call as needed, to fetch the attributes you want.

7.3 Advanced usage

7.3.1 Using a custom session

`python-gitlab` relies on `requests.Session` objects to perform all the HTTP requests to the GitLab servers.

You can provide a custom session to create `gitlab.Gitlab` objects:

```
import gitlab
import requests

session = requests.Session()
gl = gitlab.Gitlab(session=session)

# or when instantiating from configuration files
gl = gitlab.Gitlab.from_config('somewhere', ['/tmp/gl.cfg'], session=session)
```

Reference: <https://requests.readthedocs.io/en/latest/user/advanced/#session-objects>

7.3.2 Context manager

You can use `Gitlab` objects as context managers. This makes sure that the `requests.Session` object associated with a `Gitlab` instance is always properly closed when you exit a `with` block:

```
with gitlab.Gitlab(host, token) as gl:
    gl.projects.list()
```

Warning: The context manager will also close the custom `Session` object you might have used to build the `Gitlab` instance.

7.3.3 netrc authentication

python-gitlab reads credentials from `.netrc` files via the `requests` backend by default, which may override authentication headers you set on your client.

For more granular control, you can disable this [*Using a custom session*](#) and explicitly setting `trust_env=False` as described in the `requests` documentation.

```
import gitlab
import requests

session = requests.Session(trust_env=False)
gl = gitlab.Gitlab(session=session)
```

Reference: <https://requests.readthedocs.io/en/latest/user/authentication/#netrc-authentication>

7.3.4 Proxy configuration

python-gitlab accepts the standard `http_proxy`, `https_proxy` and `no_proxy` environment variables via the `requests` backend. Uppercase variables are also supported.

For more granular control, you can also explicitly set proxies by [*Using a custom session*](#) as described in the `requests` documentation.

Reference: <https://requests.readthedocs.io/en/latest/user/advanced/#proxies>

7.3.5 SSL certificate verification

python-gitlab relies on the CA certificate bundle in the `certifi` package that comes with the `requests` library.

If you need python-gitlab to use your system CA store instead, you can provide the path to the CA bundle in the `REQUESTS_CA_BUNDLE` environment variable.

Reference: <https://requests.readthedocs.io/en/latest/user/advanced/#ssl-cert-verification>

7.3.6 Client side certificate

The following sample illustrates how to use a client-side certificate:

```
import gitlab
import requests

session = requests.Session()
session.cert = ('/path/to/client.cert', '/path/to/client.key')
gl = gitlab.Gitlab(url, token, api_version=4, session=session)
```

Reference: <https://requests.readthedocs.io/en/latest/user/advanced/#client-side-certificates>

7.3.7 Rate limits

python-gitlab obeys the rate limit of the GitLab server by default. On receiving a 429 response (Too Many Requests), python-gitlab sleeps for the amount of time in the Retry-After header that GitLab sends back. If GitLab does not return a response with the Retry-After header, python-gitlab will perform an exponential backoff.

If you don't want to wait, you can disable the rate-limiting feature, by supplying the `obey_rate_limit` argument.

```
import gitlab
import requests

gl = gitlab.Gitlab(url, token, api_version=4)
gl.projects.list(get_all=True, obey_rate_limit=False)
```

If you do not disable the rate-limiting feature, you can supply a custom value for `max_retries`; by default, this is set to 10. To retry without bound when throttled, you can set this parameter to -1. This parameter is ignored if `obey_rate_limit` is set to False.

```
import gitlab
import requests

gl = gitlab.Gitlab(url, token, api_version=4)
gl.projects.list(get_all=True, max_retries=-1)
```

Warning: You will get an Exception, if you then go over the rate limit of your GitLab instance.

7.3.8 Transient errors

GitLab server can sometimes return a transient HTTP error. python-gitlab can automatically retry in such case, when `retry_transient_errors` argument is set to True. When enabled, HTTP error codes 500 (Internal Server Error), 502 (502 Bad Gateway), 503 (Service Unavailable), 504 (Gateway Timeout), and Cloudflare errors (520-530) are retried.

Additionally, HTTP error code 409 (Conflict) is retried if the reason is a Resource lock.

It will retry until reaching the `max_retries` value. By default, `retry_transient_errors` is set to False and an exception is raised for these errors.

```
import gitlab
import requests

gl = gitlab.Gitlab(url, token, api_version=4)
gl.projects.list(get_all=True, retry_transient_errors=True)
```

The default `retry_transient_errors` can also be set on the `Gitlab` object and overridden by individual API calls.

```
import gitlab
import requests
gl = gitlab.Gitlab(url, token, api_version=4, retry_transient_errors=True)
gl.projects.list(get_all=True) # retries due to default
                             # value
gl.projects.list(get_all=True, retry_transient_errors=False) # does not retry
```

7.3.9 Timeout

python-gitlab will by default use the `timeout` option from its configuration for all requests. This is passed downwards to the `requests` module at the time of making the HTTP request. However if you would like to override the global timeout parameter for a particular call, you can provide the `timeout` parameter to that API invocation:

```
import gitlab

gl = gitlab.Gitlab(url, token, api_version=4)
gl.projects.import_github(ACCESS_TOKEN, 123456, "root", timeout=120.0)
```

7.3.10 Typing

Generally, python-gitlab is a fully typed package. However, currently you may still need to do some type narrowing on your own, such as for nested API responses and Union return types. For example:

```
from typing import TYPE_CHECKING

import gitlab

gl = gitlab.Gitlab(url, token, api_version=4)
license = gl.get_license()

if TYPE_CHECKING:
    assert isinstance(license["plan"], str)
```

7.4 CLI examples

See also:

For a complete list of objects and actions available, see [CLI reference \(gitlab command\)](#).

7.4.1 CI Lint

Lint a CI YAML configuration from a string:

Note: To see output, you will need to use the `-v/--verbose` flag.

To exit with non-zero on YAML lint failures instead, use the `validate` subcommand shown below.

```
$ gitlab --verbose ci-lint create --content \
"---
test:
  script:
    - echo hello
"'
```

Lint a CI YAML configuration from a file (see [Reading values from files](#)):

```
$ gitlab --verbose ci-lint create --content @.gitlab-ci.yml
```

Validate a CI YAML configuration from a file (lints and exits with non-zero on failure):

```
$ gitlab ci-lint validate --content @.gitlab-ci.yml
```

Lint a project's CI YAML configuration:

```
$ gitlab --verbose project-ci-lint create --project-id group/my-project --content @.gitlab-ci.yml
```

Validate a project's CI YAML configuration (lints and exits with non-zero on failure):

```
$ gitlab project-ci-lint validate --project-id group/my-project --content @.gitlab-ci.yml
```

Lint a project's current CI YAML configuration:

```
$ gitlab --verbose project-ci-lint get --project-id group/my-project
```

Lint a project's current CI YAML configuration on a specific branch:

```
$ gitlab --verbose project-ci-lint get --project-id group/my-project --ref my-branch
```

7.4.2 Projects

List the projects (paginated):

```
$ gitlab project list
```

List all the projects:

```
$ gitlab project list --get-all
```

List all projects of a group:

```
$ gitlab group-project list --get-all --group-id 1
```

List all projects of a group and its subgroups:

```
$ gitlab group-project list --get-all --include-subgroups true --group-id 1
```

Limit to 5 items per request, display the 1st page only

```
$ gitlab project list --page 1 --per-page 5
```

Get a specific project (id 2):

```
$ gitlab project get --id 2
```

7.4.3 Users

Get a specific user by id:

```
$ gitlab user get --id 3
```

Create a user impersonation token (admin-only):

```
gitlab user-impersonation-token create --user-id 2 --name test-token --scopes api,read_user
```

7.4.4 Deploy tokens

Create a deploy token for a project:

```
$ gitlab -v project-deploy-token create --project-id 2 \
--name bar --username root --expires-at "2021-09-09" --scopes "api,read_repository"
```

List deploy tokens for a group:

```
$ gitlab -v group-deploy-token list --group-id 3
```

7.4.5 Personal access tokens

List the current user's personal access tokens (or all users' tokens, if admin):

```
$ gitlab -v personal-access-token list
```

Revoke a personal access token by id:

```
$ gitlab personal-access-token delete --id 1
```

Revoke the personal access token currently used:

```
$ gitlab personal-access-token delete --id self
```

Create a personal access token for a user (admin only):

```
$ gitlab -v user-personal-access-token create --user-id 2 \
--name personal-access-token --expires-at "2023-01-01" --scopes "api,read_repository"
```

7.4.6 Resource access tokens

Create a project access token:

```
$ gitlab -v project-access-token create --project-id 2 \
--name project-token --expires-at "2023-01-01" --scopes "api,read_repository"
```

List project access tokens:

```
$ gitlab -v project-access-token list --project-id 3
```

Revoke a project access token:

```
$ gitlab project-access-token delete --project-id 3 --id 1
```

Create a group access token:

```
$ gitlab -v group-access-token create --group-id 2 \
--name group-token --expires-at "2022-01-01" --scopes "api,read_repository"
```

List group access tokens:

```
$ gitlab -v group-access-token list --group-id 3
```

Revoke a group access token:

```
$ gitlab group-access-token delete --group-id 3 --id 1
```

7.4.7 Packages

List packages for a project:

```
$ gitlab -v project-package list --project-id 3
```

List packages for a group:

```
$ gitlab -v group-package list --group-id 3
```

Get a specific project package by id:

```
$ gitlab -v project-package get --id 1 --project-id 3
```

Delete a specific project package by id:

```
$ gitlab -v project-package delete --id 1 --project-id 3
```

Upload a generic package to a project:

```
$ gitlab generic-package upload --project-id 1 --package-name hello-world \
--package-version v1.0.0 --file-name hello.tar.gz --path /path/to/hello.tar.gz
```

Download a project's generic package:

```
$ gitlab generic-package download --project-id 1 --package-name hello-world \
--package-version v1.0.0 --file-name hello.tar.gz > /path/to/hello.tar.gz
```

7.4.8 Issues

Get a list of issues for this project:

```
$ gitlab project-issue list --project-id 2
```

7.4.9 Snippets

Delete a snippet (id 3):

```
$ gitlab project-snippet delete --id 3 --project-id 2
```

Update a snippet:

```
$ gitlab project-snippet update --id 4 --project-id 2 \
  --code "My New Code"
```

Create a snippet:

```
$ gitlab project-snippet create --project-id 2
Impossible to create object (Missing attribute(s): title, file-name, code)
$ # oops, let's add the attributes:
$ gitlab project-snippet create --project-id 2 --title "the title" \
  --file-name "the name" --code "the code"
```

7.4.10 Commits

Get a specific project commit by its SHA id:

```
$ gitlab project-commit get --project-id 2 --id a43290c
```

Get the signature (e.g. GPG or x509) of a signed commit:

```
$ gitlab project-commit signature --project-id 2 --id a43290c
```

Define the status of a commit (as would be done from a CI tool for example):

```
$ gitlab project-commit-status create --project-id 2 \
  --commit-id a43290c --state success --name ci/jenkins \
  --target-url http://server/build/123 \
  --description "Jenkins build succeeded"
```

Get the merge base for two or more branches, tags or commits:

```
gitlab project repository-merge-base --id 1 --refs bd1324e2f,main,v1.0.0
```

7.4.11 Artifacts

Download the artifacts zip archive of a job:

```
$ gitlab project-job artifacts --id 10 --project-id 1 > artifacts.zip
```

7.4.12 Runners

List owned runners:

```
$ gitlab runner list
```

List owned runners with a filter:

```
$ gitlab runner list --scope active
```

List all runners in the GitLab instance (specific and shared):

```
$ gitlab runner-all list
```

Get a runner's details:

```
$ gitlab -v runner get --id 123
```

7.4.13 Other

Use sudo to act as another user (admin only):

```
$ gitlab project create --name user_project1 --sudo username
```

List values are comma-separated:

```
$ gitlab issue list --labels foo,bar
```

7.5 API examples

7.5.1 Access requests

Users can request access to groups and projects.

When access is granted the user should be given a numerical access level. The following constants are provided to represent the access levels:

- `gitlab.const.AccessLevel.GUEST: 10`
- `gitlab.const.AccessLevel.REPORTER: 20`
- `gitlab.const.AccessLevel.DEVELOPER: 30`
- `gitlab.const.AccessLevel.MAINTAINER: 40`
- `gitlab.const.AccessLevel.OWNER: 50`

References

- v4 API:
 - `gitlab.v4.objects.ProjectAccessRequest`
 - `gitlab.v4.objects.ProjectAccessRequestManager`
 - `gitlab.v4.objects.Project.accessrequests`
 - `gitlab.v4.objects.GroupAccessRequest`
 - `gitlab.v4.objects.GroupAccessRequestManager`
 - `gitlab.v4.objects.Group.accessrequests`
- GitLab API: https://docs.gitlab.com/ce/api/access_requests.html

Examples

List access requests from projects and groups:

```
p_ar = project.accessrequests.list()  
g_ar = group.accessrequests.list()
```

Create an access request:

```
p_ar = project.accessrequests.create()  
g_ar = group.accessrequests.create()
```

Approve an access request:

```
ar.approve()  # defaults to DEVELOPER level  
ar.approve(access_level=gitlab.const.AccessLevel.MAINTAINER)  # explicitly set access_level
```

Deny (delete) an access request:

```
project.accessrequests.delete(user_id)  
group.accessrequests.delete(user_id)  
# or  
ar.delete()
```

7.5.2 Appearance

Reference

- v4 API:
 - `gitlab.v4.objects.ApplicationAppearance`
 - `gitlab.v4.objects.ApplicationAppearanceManager`
 - `gitlab.Gitlab.appearance`
- GitLab API: <https://docs.gitlab.com/ce/api/appearance.html>

Examples

Get the appearance:

```
appearance = gl.appearance.get()
```

Update the appearance:

```
appearance.title = "Test"
appearance.save()
```

7.5.3 Applications

Reference

- v4 API:
 - `gitlab.v4.objects.Applications`
 - `gitlab.v4.objects.ApplicationManager`
 - `gitlab.Gitlab.applications`
- GitLab API: <https://docs.gitlab.com/ce/api/applications.html>

Examples

List all OAuth applications:

```
applications = gl.applications.list()
```

Create an application:

```
gl.applications.create({'name': 'your_app', 'redirect_uri': 'http://application.url',
                        'scopes': 'read_user openid profile email'})
```

Delete an application:

```
gl.applications.delete(app_id)
# or
application.delete()
```

7.5.4 Award Emojis

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssueAwardEmoji`
 - `gitlab.v4.objects.ProjectIssueNoteAwardEmoji`
 - `gitlab.v4.objects.ProjectMergeRequestAwardEmoji`
 - `gitlab.v4.objects.ProjectMergeRequestNoteAwardEmoji`

- *gitlab.v4.objects.ProjectSnippetAwardEmoji*
 - *gitlab.v4.objects.ProjectSnippetNoteAwardEmoji*
 - *gitlab.v4.objects.ProjectIssueAwardEmojiManager*
 - *gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager*
 - *gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager*
 - *gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager*
 - *gitlab.v4.objects.ProjectSnippetAwardEmojiManager*
 - *gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager*
- GitLab API: https://docs.gitlab.com/ce/api/award_emoji.html

Examples

List emojis for a resource:

```
emojis = obj.awardemojis.list()
```

Get a single emoji:

```
emoji = obj.awardemojis.get(emoji_id)
```

Add (create) an emoji:

```
emoji = obj.awardemojis.create({'name': 'tractor'})
```

Delete an emoji:

```
emoji.delete  
# or  
obj.awardemojis.delete(emoji_id)
```

7.5.5 Badges

Badges can be associated with groups and projects.

Reference

- v4 API:
 - *gitlab.v4.objects.GroupBadge*
 - *gitlab.v4.objects.GroupBadgeManager*
 - *gitlab.v4.objects.Group.badges*
 - *gitlab.v4.objects.ProjectBadge*
 - *gitlab.v4.objects.ProjectBadgeManager*
 - *gitlab.v4.objects.Project.badges*
- GitLab API:

- https://docs.gitlab.com/ce/api/group_badges.html
- https://docs.gitlab.com/ce/api/project_badges.html

Examples

List badges:

```
badges = group_or_project.badges.list()
```

Get a badge:

```
badge = group_or_project.badges.get(badge_id)
```

Create a badge:

```
badge = group_or_project.badges.create({'link_url': link, 'image_url': image_link})
```

Update a badge:

```
badge.image_url = new_image_url  
badge.link_url = new_link_url  
badge.save()
```

Delete a badge:

```
badge.delete()
```

Render a badge (preview the generate URLs):

```
output = group_or_project.badges.render(link, image_link)  
print(output['rendered_link_url'])  
print(output['rendered_image_url'])
```

7.5.6 Branches

References

- v4 API:
 - *gitlab.v4.objects.ProjectBranch*
 - *gitlab.v4.objects.ProjectBranchManager*
 - *gitlab.v4.objects.Project.branches*
- GitLab API: <https://docs.gitlab.com/ce/api/branches.html>

Examples

Get the list of branches for a repository:

```
branches = project.branches.list()
```

Get a single repository branch:

```
branch = project.branches.get('main')
```

Create a repository branch:

```
branch = project.branches.create({'branch': 'feature1',
                                  'ref': 'main'})
```

Delete a repository branch:

```
project.branches.delete('feature1')
# or
branch.delete()
```

Delete the merged branches for a project:

```
project.delete_merged_branches()
```

To manage protected branches, see [Protected branches](#).

7.5.7 Migrations (Bulk Imports)

References

- v4 API:
 - `gitlab.v4.objects.BulkImport`
 - `gitlab.v4.objects.BulkImportManager`
 - `gitlab.Gitlab.bulk_imports`
 - `gitlab.v4.objects.BulkImportAllEntity`
 - `gitlab.v4.objects.BulkImportAllEntityManager`
 - `gitlab.Gitlab.bulk_import_entities`
 - `gitlab.v4.objects.BulkImportEntity`
 - `gitlab.v4.objects.BulkImportEntityManager`
 - `gitlab.v4.objects.BulkImport.entities`
- GitLab API: https://docs.gitlab.com/ee/api/bulk_imports.html

Examples

Note: Like the project/group imports and exports, this is an asynchronous operation and you will need to refresh the state from the server to get an accurate migration status. See [Examples](#) in the import/export section for more details and examples.

Start a bulk import/migration of a group and wait for completion:

```
# Create the migration
configuration = {
    "url": "https://gitlab.example.com",
    "access_token": private_token,
}
entity = {
    "source_full_path": "source_group",
    "source_type": "group_entity",
    "destination_slug": "imported-group",
    "destination_namespace": "imported-namespace",
}
migration = gl.bulk_imports.create(
{
    "configuration": configuration,
    "entities": [entity],
}
)

# Wait for the 'finished' status
while migration.status != "finished":
    time.sleep(1)
    migration.refresh()
```

List all migrations:

```
gl.bulk_imports.list()
```

List the entities of all migrations:

```
gl.bulk_import_entities.list()
```

Get a single migration by ID:

```
migration = gl.bulk_imports.get(123)
```

List the entities of a single migration:

```
entities = migration.entities.list()
```

Get a single entity of a migration by ID:

```
entity = migration.entities.get(123)
```

Refresh the state of a migration or entity from the server:

```
migration.refresh()
entity.refresh()

print(migration.status)
print(entity.status)
```

7.5.8 Broadcast messages

You can use broadcast messages to display information on all pages of the gitlab web UI. You must have administration permissions to manipulate broadcast messages.

References

- v4 API:
 - `gitlab.v4.objects.BroadcastMessage`
 - `gitlab.v4.objects.BroadcastMessageManager`
 - `gitlab.Gitlab.broadcastmessages`
- GitLab API: https://docs.gitlab.com/ce/api/broadcast_messages.html

Examples

List the messages:

```
msgs = gl.broadcastmessages.list()
```

Get a single message:

```
msg = gl.broadcastmessages.get(msg_id)
```

Create a message:

```
msg = gl.broadcastmessages.create({'message': 'Important information'})
```

The date format for the `starts_at` and `ends_at` parameters is YYYY-MM-ddThh:mm:ssZ.

Update a message:

```
msg.font = '#444444'
msg.color = '#999999'
msg.save()
```

Delete a message:

```
gl.broadcastmessages.delete(msg_id)
# or
msg.delete()
```

7.5.9 CI Lint

Reference

- v4 API:
 - `gitlab.v4.objects.CiLint`
 - `gitlab.v4.objects.CiLintManager`
 - `gitlab.Gitlab.ci_lint`
 - `gitlab.v4.objects.ProjectCiLint`
 - `gitlab.v4.objects.ProjectCiLintManager`
 - `gitlab.v4.objects.Project.ci_lint`
- GitLab API: <https://docs.gitlab.com/ee/api/lint.html>

Examples

Lint a CI YAML configuration:

```
gitlab_ci_yml = """.
api_test:
  rules:
    - if: $CI_PIPELINE_SOURCE=="merge_request_event"
      changes:
        - src/api/*
deploy:
  extends:
    - .api_test
  rules:
    - when: manual
      allow_failure: true
  script:
    - echo "hello world"
"""
lint_result = gl.ci_lint.create({"content": gitlab_ci_yml})

print(lint_result.status) # Print the status of the CI YAML
print(lint_result.merged_yaml) # Print the merged YAML file
```

Lint a project's CI configuration:

```
lint_result = project.ci_lint.get()
assert lint_result.valid is True # Test that the .gitlab-ci.yml is valid
print(lint_result.merged_yaml) # Print the merged YAML file
```

Lint a CI YAML configuration with a namespace:

```
lint_result = project.ci_lint.create({"content": gitlab_ci_yml})
assert lint_result.valid is True # Test that the .gitlab-ci.yml is valid
print(lint_result.merged_yaml) # Print the merged YAML file
```

Validate a CI YAML configuration (raises `GitlabCiLintError` on failures):

```
# returns None
gl.ci_lint.validate({"content": gitlab_ci_yml})

# raises GitlabCiLintError
gl.ci_lint.validate({"content": "invalid"})
```

Validate a CI YAML configuration with a namespace:

```
# returns None
project.ci_lint.validate({"content": gitlab_ci_yml})

# raises GitLabCiLintError
project.ci_lint.validate({"content": "invalid"})
```

7.5.10 Commits

Commits

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCommit`
 - `gitlab.v4.objects.ProjectCommitManager`
 - `gitlab.v4.objects.Project.commits`

Examples

List the commits for a project:

```
commits = project.commits.list()
```

You can use the `ref_name`, `since` and `until` filters to limit the results:

```
commits = project.commits.list(ref_name='my_branch')
commits = project.commits.list(since='2016-01-01T00:00:00Z')
```

List all commits for a project (see [Pagination](#)) on all branches:

```
commits = project.commits.list(get_all=True, all=True)
```

Create a commit:

```
# See https://docs.gitlab.com/ce/api/commits.html#create-a-commit-with-multiple-files-and-actions
# for actions detail
data = {
    'branch': 'main',
    'commit_message': 'blah blah blah',
    'actions': [
        {
```

(continues on next page)

(continued from previous page)

```

        'action': 'create',
        'file_path': 'README.rst',
        'content': open('path/to/file.rst').read(),
    },
    {
        # Binary files need to be base64 encoded
        'action': 'create',
        'file_path': 'logo.png',
        'content': base64.b64encode(open('logo.png', mode='r+b').read()).decode(),
        'encoding': 'base64',
    }
]
}

commit = project.commits.create(data)

```

Get a commit detail:

```
commit = project.commits.get('e3d5a71b')
```

Get the diff for a commit:

```
diff = commit.diff()
```

Cherry-pick a commit into another branch:

```
commit.cherry_pick(branch='target_branch')
```

Revert a commit on a given branch:

```
commit.revert(branch='target_branch')
```

Get the references the commit has been pushed to (branches and tags):

```
commit.refs() # all references
commit.refs('tag') # only tags
commit.refs('branch') # only branches
```

Get the signature of the commit (if the commit was signed, e.g. with GPG or x509):

```
commit.signature()
```

List the merge requests related to a commit:

```
commit.merge_requests()
```

Commit comments

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCommitComment`
 - `gitlab.v4.objects.ProjectCommitCommentManager`
 - `gitlab.v4.objects.ProjectCommit.comments`
- GitLab API: <https://docs.gitlab.com/ce/api/commits.html>

Examples

Get the comments for a commit:

```
comments = commit.comments.list()
```

Add a comment on a commit:

```
# Global comment
commit = commit.comments.create({'note': 'This is a nice comment'})
# Comment on a line in a file (on the new version of the file)
commit = commit.comments.create({'note': 'This is another comment',
                                 'line': 12,
                                 'line_type': 'new',
                                 'path': 'README.rst'})
```

Commit status

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCommitStatus`
 - `gitlab.v4.objects.ProjectCommitStatusManager`
 - `gitlab.v4.objects.ProjectCommit.statuses`
- GitLab API: <https://docs.gitlab.com/ce/api/commits.html>

Examples

List the statuses for a commit:

```
statuses = commit.statuses.list()
```

Change the status of a commit:

```
commit.statuses.create({'state': 'success'})
```

7.5.11 Deploy keys

Deploy keys

Reference

- v4 API:
 - `gitlab.v4.objects.DeployKey`
 - `gitlab.v4.objects.DeployKeyManager`
 - `gitlab.Gitlab.deploykeys`
- GitLab API: https://docs.gitlab.com/ce/api/deploy_keys.html

Examples

List the deploy keys:

```
keys = gl.deploykeys.list()
```

Deploy keys for projects

Deploy keys can be managed on a per-project basis.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectKey`
 - `gitlab.v4.objects.ProjectKeyManager`
 - `gitlab.v4.objects.Project.keys`
- GitLab API: https://docs.gitlab.com/ce/api/deploy_keys.html

Examples

List keys for a project:

```
keys = project.keys.list()
```

Get a single deploy key:

```
key = project.keys.get(key_id)
```

Create a deploy key for a project:

```
key = project.keys.create({'title': 'jenkins key',
                           'key': open('/home/me/.ssh/id_rsa.pub').read()})
```

Delete a deploy key for a project:

```
key = project.keys.list(key_id)
# or
key.delete()
```

Enable a deploy key for a project:

```
project.keys.enable(key_id)
```

Disable a deploy key for a project:

```
project.keys.delete(key_id)
```

7.5.12 Deploy tokens

Deploy tokens allow read-only access to your repository and registry images without having a user and a password.

Deploy tokens

This endpoint requires admin access.

Reference

- v4 API:
 - [*gitlab.v4.objects.DeployToken*](#)
 - [*gitlab.v4.objects.DeployTokenManager*](#)
 - [*gitlab.Gitlab.deploytokens*](#)
- GitLab API: https://docs.gitlab.com/ce/api/deploy_tokens.html

Examples

Use the `list()` method to list all deploy tokens across the GitLab instance.

```
# List deploy tokens
deploy_tokens = gl.deploytokens.list()
```

Project deploy tokens

This endpoint requires project maintainer access or higher.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectDeployToken`
 - `gitlab.v4.objects.ProjectDeployTokenManager`
 - `gitlab.v4.objects.Project.deploytokens`
- GitLab API: https://docs.gitlab.com/ce/api/deploy_tokens.html#project-deploy-tokens

Examples

List the deploy tokens for a project:

```
deploy_tokens = project.deploytokens.list()
```

Get a deploy token for a project by id:

```
deploy_token = project.deploytokens.get(deploy_token_id)
```

Create a new deploy token to access registry images of a project:

In addition to required parameters `name` and `scopes`, this method accepts the following parameters:

- `expires_at` Expiration date of the deploy token. Does not expire if no value is provided.
- `username` Username for deploy token. Default is `gitlab+deploy-token-{n}`

```
deploy_token = project.deploytokens.create({'name': 'token1', 'scopes': ['read_registry'
˓→'], 'username': '', 'expires_at': ''})
# show its id
print(deploy_token.id)
# show the token value. Make sure you save it, you won't be able to access it again.
print(deploy_token.token)
```

Warning: With GitLab 12.9, even though `username` and `expires_at` are not required, they always have to be passed to the API. You can set them to empty strings, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211878>. Also, the `username`'s value is ignored by the API and will be overridden with `gitlab+deploy-token-{n}`, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211963> These issues were fixed in GitLab 12.10.

Remove a deploy token from the project:

```
deploy_token.delete()
# or
project.deploytokens.delete(deploy_token.id)
```

Group deploy tokens

Reference

- v4 API:
 - `gitlab.v4.objects.GroupDeployToken`
 - `gitlab.v4.objects.GroupDeployTokenManager`
 - `gitlab.v4.objects.Group.deploytokens`
- GitLab API: https://docs.gitlab.com/ce/api/deploy_tokens.html#group-deploy-tokens

Examples

List the deploy tokens for a group:

```
deploy_tokens = group.deploytokens.list()
```

Get a deploy token for a group by id:

```
deploy_token = group.deploytokens.get(deploy_token_id)
```

Create a new deploy token to access all repositories of all projects in a group:

In addition to required parameters `name` and `scopes`, this method accepts the following parameters:

- `expires_at` Expiration date of the deploy token. Does not expire if no value is provided.
- `username` Username for deploy token. Default is `gitlab+deploy-token-{n}`

```
deploy_token = group.deploytokens.create({'name': 'token1', 'scopes': ['read_repository\n↳'], 'username':'', 'expires_at':''})\n# show its id\nprint(deploy_token.id)
```

Warning: With GitLab 12.9, even though `username` and `expires_at` are not required, they always have to be passed to the API. You can set them to empty strings, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211878>. Also, the `username`'s value is ignored by the API and will be overridden with `gitlab+deploy-token-{n}`, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211963> These issues were fixed in GitLab 12.10.

Remove a deploy token from the group:

```
deploy_token.delete()\n# or\ngroup.deploytokens.delete(deploy_token.id)
```

7.5.13 Deployments

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectDeployment`
 - `gitlab.v4.objects.ProjectDeploymentManager`
 - `gitlab.v4.objects.Project.deployments`
- GitLab API: <https://docs.gitlab.com/ce/api/deployments.html>

Examples

List deployments for a project:

```
deployments = project.deployments.list()
```

Get a single deployment:

```
deployment = project.deployments.get(deployment_id)
```

Create a new deployment:

```
deployment = project.deployments.create({
    "environment": "Test",
    "sha": "1agf4gs",
    "ref": "main",
    "tag": False,
    "status": "created",
})
```

Update a deployment:

```
deployment = project.deployments.get(42)
deployment.status = "failed"
deployment.save()
```

Approve a deployment:

```
deployment = project.deployments.get(42)
# `status` must be either "approved" or "rejected".
deployment.approval(status="approved")
```

Reject a deployment:

```
deployment = project.deployments.get(42)
# Using the optional `comment` and `represented_as` arguments
deployment.approval(status="rejected", comment="Fails CI", represented_as="security")
```

Merge requests associated with a deployment

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectDeploymentMergeRequest`
 - `gitlab.v4.objects.ProjectDeploymentMergeRequestManager`
 - `gitlab.v4.objects.ProjectDeployment.mergerequests`
- GitLab API: <https://docs.gitlab.com/ee/api/deployments.html#list-of-merge-requests-associated-with-a-deployment>

Examples

List the merge requests associated with a deployment:

```
deployment = project.deployments.get(42, lazy=True)
mrs = deployment.mergerequests.list()
```

7.5.14 Discussions

Discussions organize the notes in threads. See the [Notes](#) chapter for more information about notes.

Discussions are available for project issues, merge requests, snippets and commits.

Reference

- v4 API:

Issues:

- `gitlab.v4.objects.ProjectIssueDiscussion`
- `gitlab.v4.objects.ProjectIssueDiscussionManager`
- `gitlab.v4.objects.ProjectIssueDiscussionNote`
- `gitlab.v4.objects.ProjectIssueDiscussionNoteManager`
- `gitlab.v4.objects.ProjectIssue.notes`

MergeRequests:

- `gitlab.v4.objects.ProjectMergeRequestDiscussion`
- `gitlab.v4.objects.ProjectMergeRequestDiscussionManager`
- `gitlab.v4.objects.ProjectMergeRequestDiscussionNote`
- `gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager`
- `gitlab.v4.objects.ProjectMergeRequest.notes`

Snippets:

- `gitlab.v4.objects.ProjectSnippetDiscussion`
- `gitlab.v4.objects.ProjectSnippetDiscussionManager`

- `gitlab.v4.objects.ProjectSnippetDiscussionNote`
- `gitlab.v4.objects.ProjectSnippetDiscussionNoteManager`
- `gitlab.v4.objects.ProjectSnippet.notes`
- GitLab API: <https://docs.gitlab.com/ce/api/discussions.html>

Examples

List the discussions for a resource (issue, merge request, snippet or commit):

```
discussions = resource.discussions.list()
```

Get a single discussion:

```
discussion = resource.discussions.get(discussion_id)
```

You can access the individual notes in the discussion through the `notes` attribute. It holds a list of notes in chronological order:

```
# ``resource.notes`` is a DiscussionNoteManager, so we need to get the
# object notes using ``attributes``
for note in discussion.attributes['notes']:
    print(note['body'])
```

Note: The notes are dicts, not objects.

You can add notes to existing discussions:

```
new_note = discussion.notes.create({'body': 'Episode IV: A new note'})
```

You can get and update a single note using the *DiscussionNote resources:

```
discussion = resource.discussions.get(discussion_id)
# Get the latest note's id
note_id = discussion.attributes['notes'][-1]['id']
last_note = discussion.notes.get(note_id)
last_note.body = 'Updated comment'
last_note.save()
```

Create a new discussion:

```
discussion = resource.discussions.create({'body': 'First comment of discussion'})
```

You can comment on merge requests and commit diffs. Provide the `position` dict to define where the comment should appear in the diff:

```
mr_diff = mr.diffs.get(diff_id)
mr.discussions.create({'body': 'Note content',
                      'position': {
                          'base_sha': mr_diff.base_commit_sha,
                          'start_sha': mr_diff.start_commit_sha,
                          'head_sha': mr_diff.head_commit_sha,
```

(continues on next page)

(continued from previous page)

```
'position_type': 'text',
'new_line': 1,
'old_path': 'README.rst',
'new_path': 'README.rst'}
```

}

Resolve / unresolve a merge request discussion:

```
mr_d = mr.discussions.get(d_id)
mr_d.resolved = True # True to resolve, False to unresolve
mr_d.save()
```

Delete a comment:

```
discussions.notes.delete(note_id)
# or
note.delete()
```

7.5.15 Environments

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectEnvironment*
 - *gitlab.v4.objects.ProjectEnvironmentManager*
 - *gitlab.v4.objects.Project.environments*
- GitLab API: <https://docs.gitlab.com/ce/api/environments.html>

Examples

List environments for a project:

```
environments = project.environments.list()
```

Create an environment for a project:

```
environment = project.environments.create({'name': 'production'})
```

Retrieve a specific environment for a project:

```
environment = project.environments.get(112)
```

Update an environment for a project:

```
environment.external_url = 'http://foo.bar.com'
environment.save()
```

Delete an environment for a project:

```
environment = project.environments.delete(environment_id)
# or
environment.delete()
```

Stop an environment:

```
environment.stop()
```

To manage protected environments, see [Protected environments](#).

7.5.16 Events

Events

Reference

- v4 API:
 - [gitlab.v4.objects.Event](#)
 - [gitlab.v4.objects.EventManager](#)
 - [gitlab.Gitlab.events](#)
 - [gitlab.v4.objects.ProjectEvent](#)
 - [gitlab.v4.objects.ProjectEventManager](#)
 - [gitlab.v4.objects.Project.events](#)
 - [gitlab.v4.objects.UserEvent](#)
 - [gitlab.v4.objects.UserEventManager](#)
 - [gitlab.v4.objects.User.events](#)
- GitLab API: <https://docs.gitlab.com/ce/api/events.html>

Examples

You can list events for an entire Gitlab instance (admin), users and projects. You can filter you events you want to retrieve using the `action` and `target_type` attributes. The possible values for these attributes are available on [the gitlab documentation](#).

List all the events (paginated):

```
events = gl.events.list()
```

List the issue events on a project:

```
events = project.events.list(target_type='issue')
```

List the user events:

```
events = project.events.list()
```

Resource state events

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssueResourceStateEvent`
 - `gitlab.v4.objects.ProjectIssueResourceStateEventManager`
 - `gitlab.v4.objects.ProjectIssue.resourcestateevents`
 - `gitlab.v4.objects.ProjectMergeRequestResourceStateEvent`
 - `gitlab.v4.objects.ProjectMergeRequestResourceStateEventManager`
 - `gitlab.v4.objects.ProjectMergeRequest.resourcestateevents`
- GitLab API: https://docs.gitlab.com/ee/api/resource_state_events.html

Examples

You can list and get specific resource state events (via their id) for project issues and project merge requests.

List the state events of a project issue (paginated):

```
state_events = issue.resourcestateevents.list()
```

Get a specific state event of a project issue by its id:

```
state_event = issue.resourcestateevents.get(1)
```

List the state events of a project merge request (paginated):

```
state_events = mr.resourcestateevents.list()
```

Get a specific state event of a project merge request by its id:

```
state_event = mr.resourcestateevents.get(1)
```

7.5.17 Epics

Epics

Reference

- v4 API:
 - `gitlab.v4.objects.GroupEpic`
 - `gitlab.v4.objects.GroupEpicManager`
 - `gitlab.Gitlab.Group.epics`
- GitLab API: <https://docs.gitlab.com/ee/api/epics.html> (EE feature)

Examples

List the epics for a group:

```
epics = groups.epics.list()
```

Get a single epic for a group:

```
epic = group.epics.get(epic_iid)
```

Create an epic for a group:

```
epic = group.epics.create({'title': 'My Epic'})
```

Edit an epic:

```
epic.title = 'New title'
epic.labels = ['label1', 'label2']
epic.save()
```

Delete an epic:

```
epic.delete()
```

Epics issues

Reference

- v4 API:
 - `gitlab.v4.objects.GroupEpicIssue`
 - `gitlab.v4.objects.GroupEpicIssueManager`
 - `gitlab.Gitlab.GroupEpic.issues`
- GitLab API: https://docs.gitlab.com/ee/api/epic_issues.html (EE feature)

Examples

List the issues associated with an issue:

```
ei = epic.issues.list()
```

Associate an issue with an epic:

```
# use the issue id, not its iid
ei = epic.issues.create({'issue_id': 4})
```

Move an issue in the list:

```
ei.move_before_id = epic_issue_id_1
# or
ei.move_after_id = epic_issue_id_2
ei.save()
```

Delete an issue association:

```
ei.delete()
```

7.5.18 Features flags

Reference

- v4 API:
 - `gitlab.v4.objects.Feature`
 - `gitlab.v4.objects.FeatureManager`
 - `gitlab.Gitlab.features`
- GitLab API: <https://docs.gitlab.com/ce/api/features.html>

Examples

List features:

```
features = gl.features.list()
```

Create or set a feature:

```
feature = gl.features.set(feature_name, True)
feature = gl.features.set(feature_name, 30)
feature = gl.features.set(feature_name, True, user=filipowm)
feature = gl.features.set(feature_name, 40, group=mygroup)
```

Delete a feature:

```
feature.delete()
```

7.5.19 Geo nodes

Reference

- v4 API:
 - `gitlab.v4.objects.GeoNode`
 - `gitlab.v4.objects.GeoNodeManager`
 - `gitlab.Gitlab.geonodes`
- GitLab API: https://docs.gitlab.com/ee/api/geo_nodes.html (EE feature)

Examples

List the geo nodes:

```
nodes = gl.geonodes.list()
```

Get the status of all the nodes:

```
status = gl.geonodes.status()
```

Get a specific node and its status:

```
node = gl.geonodes.get(node_id)
node.status()
```

Edit a node configuration:

```
node.url = 'https://secondary.mygitlab.domain'
node.save()
```

Delete a node:

```
node.delete()
```

List the sync failure on the current node:

```
failures = gl.geonodes.current_failures()
```

7.5.20 Groups

Groups

Reference

- v4 API:
 - *gitlab.v4.objects.Group*
 - *gitlab.v4.objects.GroupManager*
 - *gitlab.Gitlab.groups*
- GitLab API: <https://docs.gitlab.com/ce/api/groups.html>

Examples

List the groups:

```
groups = gl.groups.list()
```

Get a group's detail:

```
group = gl.groups.get(group_id)
```

List a group's projects:

```
projects = group.projects.list()
```

List a group's shared projects:

```
projects = group.shared_projects.list()
```

Note: GroupProject and SharedProject objects returned by these two API calls are very limited, and do not provide all the features of Project objects. If you need to manipulate projects, create a new Project object:

```
first_group_project = group.projects.list()[0]
manageable_project = gl.projects.get(first_group_project.id, lazy=True)
```

You can filter and sort the result using the following parameters:

- `archived`: limit by archived status
- `visibility`: limit by visibility. Allowed values are `public`, `internal` and `private`
- `search`: limit to groups matching the given value
- `order_by`: sort by criteria. Allowed values are `id`, `name`, `path`, `created_at`, `updated_at` and `last_activity_at`
- `sort`: sort order: `asc` or `desc`
- `ci_enabled_first`: return CI enabled groups first
- `include_subgroups`: include projects in subgroups

Create a group:

```
group = gl.groups.create({'name': 'group1', 'path': 'group1'})
```

Warning: On GitLab.com, creating top-level groups is currently not permitted using the API. You can only use the API to create subgroups.

Create a subgroup under an existing group:

```
subgroup = gl.groups.create({'name': 'subgroup1', 'path': 'subgroup1', 'parent_id': parent_group_id})
```

Update a group:

```
group.description = 'My awesome group'
group.save()
```

Set the avatar image for a group:

```
# the avatar image can be passed as data (content of the file) or as a file
# object opened in binary mode
group.avatar = open('path/to/file.png', 'rb')
group.save()
```

Remove a group:

```
gl.groups.delete(group_id)
# or
group.delete()
```

Restore a Group marked for deletion (Premium only)::

```
group.restore()
```

Share/unshare the group with a group:

```
group.share(group2.id, gitlab.const.AccessLevel.DEVELOPER)
group.unshare(group2.id)
```

Import / Export

You can export groups from gitlab, and re-import them to create new groups.

Reference

- v4 API:
 - *gitlab.v4.objects.GroupExport*
 - *gitlab.v4.objects.GroupExportManager*
 - *gitlab.v4.objects.Group.exports*
 - *gitlab.v4.objects.GroupImport*
 - *gitlab.v4.objects.GroupImportManager*
 - *gitlab.v4.objects.Group.imports*
 - *gitlab.v4.objects.GroupManager.import_group*
- GitLab API: https://docs.gitlab.com/ce/api/group_import_export.html

Examples

A group export is an asynchronous operation. To retrieve the archive generated by GitLab you need to:

1. Create an export using the API
2. Wait for the export to be done
3. Download the result

Warning: Unlike the Project Export API, GitLab does not provide an `export_status` for Group Exports. It is up to the user to ensure the export is finished.

However, Group Exports only contain metadata, so they are much faster than Project Exports.

```
# Create the export
group = gl.groups.get(my_group)
export = group.exports.create()

# Wait for the export to finish
time.sleep(3)

# Download the result
with open('/tmp/export.tgz', 'wb') as f:
    export.download(streamed=True, action=f.write)
```

Import the group:

```
with open('/tmp/export.tgz', 'rb') as f:
    gl.groups.import_group(f, path='imported-group', name="Imported Group")
```

Subgroups

Reference

- v4 API:
 - `gitlab.v4.objects.GroupSubgroup`
 - `gitlab.v4.objects.GroupSubgroupManager`
 - `gitlab.v4.objects.Group.subgroups`

Examples

List the subgroups for a group:

```
subgroups = group.subgroups.list()
```

Note: The `GroupSubgroup` objects don't expose the same API as the `Group` objects. If you need to manipulate a subgroup as a group, create a new `Group` object:

```
real_group = gl.groups.get(subgroup_id, lazy=True)
real_group.issues.list()
```

Descendant Groups

Reference

- v4 API:
 - `gitlab.v4.objects.GroupDescendantGroup`
 - `gitlab.v4.objects.GroupDescendantGroupManager`
 - `gitlab.v4.objects.Group.descendant_groups`

Examples

List the descendant groups of a group:

```
descendant_groups = group.descendant_groups.list()
```

Note: Like the `GroupSubgroup` objects described above, `GroupDescendantGroup` objects do not expose the same API as the `Group` objects. Create a new `Group` object instead if needed, as shown in the subgroup example.

Group custom attributes

Reference

- v4 API:
 - `gitlab.v4.objects.GroupCustomAttribute`
 - `gitlab.v4.objects.GroupCustomAttributeManager`
 - `gitlab.v4.objects.Group.customattributes`
- GitLab API: https://docs.gitlab.com/ce/api/custom_attributes.html

Examples

List custom attributes for a group:

```
attrs = group.customattributes.list()
```

Get a custom attribute for a group:

```
attr = group.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a group:

```
attr = group.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a group:

```
attr.delete()
# or
group.customattributes.delete(attr_key)
```

Search groups by custom attribute:

```
group.customattributes.set('role': 'admin')
gl.groups.list(custom_attributes={'role': 'admin'})
```

Group members

The following constants define the supported access levels:

- `gitlab.const.AccessLevel.GUEST = 10`
- `gitlab.const.AccessLevel.REPORTER = 20`
- `gitlab.const.AccessLevel.DEVELOPER = 30`
- `gitlab.const.AccessLevel.MAINTAINER = 40`
- `gitlab.const.AccessLevel.OWNER = 50`

Reference

- v4 API:
 - `gitlab.v4.objects.GroupMember`
 - `gitlab.v4.objects.GroupMemberManager`
 - `gitlab.v4.objects.GroupMemberAllManager`
 - `gitlab.v4.objects.GroupBillableMember`
 - `gitlab.v4.objects.GroupBillableMemberManager`
 - `gitlab.v4.objects.Group.members`
 - `gitlab.v4.objects.Group.members_all`
 - `gitlab.v4.objects.Group.billable_members`
- GitLab API: <https://docs.gitlab.com/ce/api/members.html>

Billable group members are only available in GitLab EE.

Examples

List only direct group members:

```
members = group.members.list()
```

List the group members recursively (including inherited members through ancestor groups):

```
members = group.members_all.list(get_all=True)
```

Get only direct group member:

```
members = group.members.get(member_id)
```

Get a member of a group, including members inherited through ancestor groups:

```
members = group.members_all.get(member_id)
```

Add a member to the group:

```
member = group.members.create({'user_id': user_id,
                               'access_level': gitlab.const.AccessLevel.GUEST})
```

Update a member (change the access level):

```
member.access_level = gitlab.const.AccessLevel.DEVELOPER
member.save()
```

Remove a member from the group:

```
group.members.delete(member_id)
# or
member.delete()
```

List billable members of a group (top-level groups only):

```
billable_members = group.billable_members.list()
```

Remove a billable member from the group:

```
group.billable_members.delete(member_id)
# or
billable_member.delete()
```

List memberships of a billable member:

```
billable_member.memberships.list()
```

LDAP group links

Add an LDAP group link to an existing GitLab group:

```
ldap_link = group.ldap_group_links.create({
    'provider': 'ldapmain',
    'group_access': gitlab.const.AccessLevel.DEVELOPER,
    'cn': 'ldap_group_cn'
})
```

List a group's LDAP group links:

```
group.ldap_group_links.list()
```

Remove a link:

```
ldap_link.delete()
# or by explicitly providing the CN or filter
group.ldap_group_links.delete(provider='ldapmain', cn='ldap_group_cn')
group.ldap_group_links.delete(provider='ldapmain', filter='(cn=Common Name)')
```

Sync the LDAP groups:

```
group.ldap_sync()
```

You can use the `ldapgroups` manager to list available LDAP groups:

```
# listing (supports pagination)
ldap_groups = gl.ldapgroups.list()
```

(continues on next page)

(continued from previous page)

```
# filter using a group name
ldap_groups = gl.ldapgroups.list(search='foo')

# list the groups for a specific LDAP provider
ldap_groups = gl.ldapgroups.list(search='foo', provider='ldapmain')
```

SAML group links

Add a SAML group link to an existing GitLab group:

```
saml_link = group.saml_group_links.create({
    "saml_group_name": "<your_saml_group_name>",
    "access_level": <chosen_access_level>
})
```

List a group's SAML group links:

```
group.saml_group_links.list()
```

Get a SAML group link:

```
group.saml_group_links.get("<your_saml_group_name>")
```

Remove a link:

```
saml_link.delete()
```

Groups hooks

Reference

- v4 API:
 - `gitlab.v4.objects.GroupHook`
 - `gitlab.v4.objects.GroupHookManager`
 - `gitlab.v4.objects.Group.hooks`
- GitLab API: <https://docs.gitlab.com/ce/api/groups.html#hooks>

Examples

List the group hooks:

```
hooks = group.hooks.list()
```

Get a group hook:

```
hook = group.hooks.get(hook_id)
```

Create a group hook:

```
hook = group.hooks.create({'url': 'http://my/action/url', 'push_events': 1})
```

Update a group hook:

```
hook.push_events = 0
hook.save()
```

Delete a group hook:

```
group.hooks.delete(hook_id)
# or
hook.delete()
```

Group push rules

Reference

- v4 API:
 - *gitlab.v4.objects.GroupPushRules*
 - *gitlab.v4.objects.GroupPushRulesManager*
 - *gitlab.v4.objects.Group.pushrules*
- GitLab API: <https://docs.gitlab.com/ee/api/groups.html#push-rules>

Examples

Create group push rules (at least one rule is necessary):

```
group.pushrules.create({'deny_delete_tag': True})
```

Get group push rules:

```
pr = group.pushrules.get()
```

Edit group push rules:

```
pr.branch_name_regex = '^((master|develop|support-\d+|release-\d+\...+|hotfix-.+|feature-.+)+)$'
pr.save()
```

Delete group push rules:

```
pr.delete()
```

7.5.21 Group Access Tokens

Get a list of group access tokens

References

- v4 API:
 - `gitlab.v4.objects.GroupAccessToken`
 - `gitlab.v4.objects.GroupAccessTokenManager`
 - `gitlab.Gitlab.group_access_tokens`
- GitLab API: https://docs.gitlab.com/ee/api/group_access_tokens.html

Examples

List group access tokens:

```
access_tokens = gl.groups.get(1, lazy=True).access_tokens.list()
print(access_tokens[0].name)
```

Create group access token:

```
access_token = gl.groups.get(1).access_tokens.create({"name": "test", "scopes": ["api"]})
```

Revoke a group access tokens:

```
gl.groups.get(1).access_tokens.delete(42)
# or
access_token.delete()
```

7.5.22 Invitations

Invitations let you invite or add users to a group or project.

Reference

- v4 API:
 - `gitlab.v4.objects.GroupInvitation`
 - `gitlab.v4.objects.GroupInvitationManager`
 - `gitlab.v4.objects.Group.invitations`
 - `gitlab.v4.objects.ProjectInvitation`
 - `gitlab.v4.objects.ProjectInvitationManager`
 - `gitlab.v4.objects.Project.invitations`
- GitLab API: <https://docs.gitlab.com/ce/api/invitations.html>

Examples

Danger: Creating an invitation with `create()` returns a status response, rather than invitation details, because it allows sending multiple invitations at the same time.

Thus when using several emails, you do not create a real invitation object you can manipulate, because python-gitlab cannot know which email to track as the ID.

In that case, use a `lazy get()` method shown below using a specific email address to create an invitation object you can manipulate.

Create an invitation:

```
invitation = group_or_project.invitations.create(
    {
        "email": "email@example.com",
        "access_level": gitlab.const.AccessLevel.DEVELOPER,
    }
)
```

List invitations for a group or project:

```
invitations = group_or_project.invitations.list()
```

Warning: As mentioned above, GitLab does not provide a real GET endpoint for a single invitation. We can create a lazy object to later manipulate it.

Update an invitation:

```
invitation = group_or_project.invitations.get("email@example.com", lazy=True)
invitation.access_level = gitlab.const.AccessLevel.DEVELOPER
invitation.save()

# or
group_or_project.invitations.update(
    "email@example.com",
    {"access_level": gitlab.const.AccessLevel.DEVELOPER}
)
```

Delete an invitation:

```
invitation = group_or_project.invitations.get("email@example.com", lazy=True)
invitation.delete()

# or
group_or_project.invitations.delete("email@example.com")
```

7.5.23 Issues

Reported issues

Reference

- v4 API:
 - `gitlab.v4.objects.Issue`
 - `gitlab.v4.objects.IssueManager`
 - `gitlab.Gitlab.issues`
- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

Examples

List the issues:

```
issues = gl.issues.list()
```

Use the `state` and `label` parameters to filter the results. Use the `order_by` and `sort` attributes to sort the results:

```
open_issues = gl.issues.list(state='opened')
closed_issues = gl.issues.list(state='closed')
tagged_issues = gl.issues.list(labels=['foo', 'bar'])
```

Note: It is not possible to edit or delete Issue objects. You need to create a `ProjectIssue` object to perform changes:

```
issue = gl.issues.list()[0]
project = gl.projects.get(issue.project_id, lazy=True)
editable_issue = project.issues.get(issue.iid, lazy=True)
editable_issue.title = updated_title
editable_issue.save()
```

Group issues

Reference

- v4 API:
 - `gitlab.v4.objects.GroupIssue`
 - `gitlab.v4.objects.GroupIssueManager`
 - `gitlab.v4.objects.Group.issues`
- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

Examples

List the group issues:

```
issues = group.issues.list()
# Filter using the state, labels and milestone parameters
issues = group.issues.list(milestone='1.0', state='opened')
# Order using the order_by and sort parameters
issues = group.issues.list(order_by='created_at', sort='desc')
```

Note: It is not possible to edit or delete GroupIssue objects. You need to create a ProjectIssue object to perform changes:

```
issue = group.issues.list()[0]
project = gl.projects.get(issue.project_id, lazy=True)
editable_issue = project.issues.get(issue.iid, lazy=True)
editable_issue.title = updated_title
editable_issue.save()
```

Project issues

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssue`
 - `gitlab.v4.objects.ProjectIssueManager`
 - `gitlab.v4.objects.Project.issues`
- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

Examples

List the project issues:

```
issues = project.issues.list()
# Filter using the state, labels and milestone parameters
issues = project.issues.list(milestone='1.0', state='opened')
# Order using the order_by and sort parameters
issues = project.issues.list(order_by='created_at', sort='desc')
```

Get a project issue:

```
issue = project.issues.get(issue_iid)
```

Create a new issue:

```
issue = project.issues.create({'title': 'I have a bug',
                               'description': 'Something useful here.'})
```

Update an issue:

```
issue.labels = ['foo', 'bar']
issue.save()
```

Close / reopen an issue:

```
# close an issue
issue.state_event = 'close'
issue.save()
# reopen it
issue.state_event = 'reopen'
issue.save()
```

Delete an issue (admin or project owner only):

```
project.issues.delete(issue_id)
# or
issue.delete()
```

Assign the issues:

```
issue = gl.issues.list()[0]
issue.assignee_ids = [25, 10, 31, 12]
issue.save()
```

Note: The Gitlab API explicitly references that the *assignee_id* field is deprecated, so using a list of user IDs for *assignee_ids* is how to assign an issue to a user(s).

Subscribe / unsubscribe from an issue:

```
issue.subscribe()
issue.unsubscribe()
```

Move an issue to another project:

```
issue.move(other_project_id)
```

Reorder an issue on a board:

```
issue.reorder(move_after_id=2, move_before_id=3)
```

Make an issue as todo:

```
issue.todo()
```

Get time tracking stats:

```
issue.time_stats()
```

On recent versions of Gitlab the time stats are also returned as an issue object attribute:

```
issue = project.issue.get(iid)
print(issue.attributes['time_stats'])
```

Set a time estimate for an issue:

```
issue.time_estimate('3h30m')
```

Reset a time estimate for an issue:

```
issue.reset_time_estimate()
```

Add spent time for an issue:

```
issue.add_spent_time('3h30m')
```

Reset spent time for an issue:

```
issue.reset_spent_time()
```

Get user agent detail for the issue (admin only):

```
detail = issue.user_agent_detail()
```

Get the list of merge requests that will close an issue when merged:

```
mrs = issue.closed_by()
```

Get the merge requests related to an issue:

```
mrs = issue.related_merge_requests()
```

Get the list of participants:

```
users = issue.participants()
```

Get the list of iteration events:

```
iteration_events = issue.resource_iteration_events.list()
```

Get the list of weight events:

```
weight_events = issue.resource_weight_events.list()
```

Issue links

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssueLink`
 - `gitlab.v4.objects.ProjectIssueLinkManager`
 - `gitlab.v4.objects.ProjectIssue.links`
- GitLab API: https://docs.gitlab.com/ee/api/issue_links.html (EE feature)

Examples

List the issues linked to i1:

```
links = i1.links.list()
```

Link issue i1 to issue i2:

```
data = {
    'target_project_id': i2.project_id,
    'target_issue_iid': i2.iid
}
src_issue, dest_issue = i1.links.create(data)
```

Note: The `create()` method returns the source and destination `ProjectIssue` objects, not a `ProjectIssueLink` object.

Delete a link:

```
i1.links.delete(issue_link_id)
```

Issues statistics

Reference

- v4 API:
 - `gitlab.v4.objects.IssuesStatistics`
 - `gitlab.v4.objects.IssuesStatisticsManager`
 - `gitlab.issues_statistics`
 - `gitlab.v4.objects.GroupIssuesStatistics`
 - `gitlab.v4.objects.GroupIssuesStatisticsManager`
 - `gitlab.v4.objects.Group.issues_statistics`
 - `gitlab.v4.objects.ProjectIssuesStatistics`
 - `gitlab.v4.objects.ProjectIssuesStatisticsManager`
 - `gitlab.v4.objects.Project.issues_statistics`
- GitLab API: https://docs.gitlab.com/ce/api/issues_statistics.htm

Examples

Get statistics of all issues created by the current user:

```
statistics = gl.issues_statistics.get()
```

Get statistics of all issues the user has access to:

```
statistics = gl.issues_statistics.get(scope='all')
```

Get statistics of issues for the user with foobar in the title or the description:

```
statistics = gl.issues_statistics.get(search='foobar')
```

Get statistics of all issues in a group:

```
statistics = group.issues_statistics.get()
```

Get statistics of issues in a group with foobar in the title or the description:

```
statistics = group.issues_statistics.get(search='foobar')
```

Get statistics of all issues in a project:

```
statistics = project.issues_statistics.get()
```

Get statistics of issues in a project with foobar in the title or the description:

```
statistics = project.issues_statistics.get(search='foobar')
```

7.5.24 Iterations

Reference

- v4 API:
 - `gitlab.v4.objects.GroupIteration`
 - `gitlab.v4.objects.GroupIterationManager`
 - `gitlab.v4.objects.Group.iterations`
 - `gitlab.v4.objects.ProjectIterationManager`
 - `gitlab.v4.objects.Project.iterations`
- GitLab API: <https://docs.gitlab.com/ee/api/iterations.html>

Examples

Note: GitLab no longer has project iterations. Using a project endpoint returns the ancestor groups' iterations.

List iterations for a project's ancestor groups:

```
iterations = project.iterations.list()
```

List iterations for a group:

```
iterations = group.iterations.list()
```

7.5.25 Keys

Keys

Reference

- v4 API
 - *gitlab.v4.objects.Key*
 - *gitlab.v4.objects.KeyManager*
 - *gitlab.Gitlab.keys*
- GitLab API: <https://docs.gitlab.com/ce/api/keys.html>

Examples

Get an ssh key by its id (requires admin access):

```
key = gl.keys.get(key_id)
```

Get an ssh key (requires admin access) or a deploy key by its fingerprint:

```
key = gl.keys.get(fingerprint="SHA256:ERJJ/OweAM6jA80jj/gXs4N5fqUaREEJnz/EyfywfXY")
```

7.5.26 Issue boards

Boards

Boards are a visual representation of existing issues for a project or a group. Issues can be moved from one list to the other to track progress and help with priorities.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectBoard`
 - `gitlab.v4.objects.ProjectBoardManager`
 - `gitlab.v4.objects.Project.boards`
 - `gitlab.v4.objects.GroupBoard`
 - `gitlab.v4.objects.GroupBoardManager`
 - `gitlab.v4.objects.Group.boards`
- GitLab API:
 - <https://docs.gitlab.com/ce/api/boards.html>
 - https://docs.gitlab.com/ce/api/group_boards.html

Examples

Get the list of existing boards for a project or a group:

```
# item is a Project or a Group
boards = project_or_group.boards.list()
```

Get a single board for a project or a group:

```
board = project_or_group.boards.get(board_id)
```

Create a board:

```
board = project_or_group.boards.create({'name': 'new-board'})
```

Note: Board creation is not supported in the GitLab CE edition.

Delete a board:

```
board.delete()
# or
project_or_group.boards.delete(board_id)
```

Note: Board deletion is not supported in the GitLab CE edition.

Board lists

Boards are made of lists of issues. Each list is associated to a label, and issues tagged with this label automatically belong to the list.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectBoardList`
 - `gitlab.v4.objects.ProjectBoardListManager`
 - `gitlab.v4.objects.ProjectBoard.lists`
 - `gitlab.v4.objects.GroupBoardList`
 - `gitlab.v4.objects.GroupBoardListManager`
 - `gitlab.v4.objects.GroupBoard.lists`
- GitLab API:
 - <https://docs.gitlab.com/ce/api/boards.html>
 - https://docs.gitlab.com/ce/api/group_boards.html

Examples

List the issue lists for a board:

```
b_lists = board.lists.list()
```

Get a single list:

```
b_list = board.lists.get(list_id)
```

Create a new list:

```
# First get a ProjectLabel
label = get_or_create_label()
# Then use its ID to create the new board list
b_list = board.lists.create({'label_id': label.id})
```

Change a list position. The first list is at position 0. Moving a list will set it at the given position and move the following lists up a position:

```
b_list.position = 2
b_list.save()
```

Delete a list:

```
b_list.delete()
```

7.5.27 Labels

Project labels

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectLabel`
 - `gitlab.v4.objects.ProjectLabelManager`
 - `gitlab.v4.objects.Project.labels`
- GitLab API: <https://docs.gitlab.com/ce/api/labels.html>

Examples

List labels for a project:

```
labels = project.labels.list()
```

Create a label for a project:

```
label = project.labels.create({'name': 'foo', 'color': '#8899aa'})
```

Update a label for a project:

```
# change the name of the label:
label.new_name = 'bar'
label.save()
# change its color:
label.color = '#112233'
label.save()
```

Promote a project label to a group label:

```
label.promote()
```

Delete a label for a project:

```
project.labels.delete(label_id)
# or
label.delete()
```

Manage labels in issues and merge requests:

```
# Labels are defined as lists in issues and merge requests. The labels must
# exist.
issue = p.issues.create({'title': 'issue title',
                         'description': 'issue description',
                         'labels': ['foo']})
issue.labels.append('bar')
issue.save()
```

Label events

Resource label events keep track about who, when, and which label was added or removed to an issuable.

Group epic label events are only available in the EE edition.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssueResourceLabelEvent`
 - `gitlab.v4.objects.ProjectIssueResourceLabelEventManager`
 - `gitlab.v4.objects.ProjectIssue.resourcelabelevents`
 - `gitlab.v4.objects.ProjectMergeRequestResourceLabelEvent`
 - `gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager`
 - `gitlab.v4.objects.ProjectMergeRequest.resourcelabelevents`
 - `gitlab.v4.objects.GroupEpicResourceLabelEvent`
 - `gitlab.v4.objects.GroupEpicResourceLabelEventManager`
 - `gitlab.v4.objects.GroupEpic.resourcelabelevents`
- GitLab API: https://docs.gitlab.com/ee/api/resource_label_events.html

Examples

Get the events for a resource (issue, merge request or epic):

```
events = resource.resourcelabelevents.list()
```

Get a specific event for a resource:

```
event = resource.resourcelabelevents.get(event_id)
```

7.5.28 Notification settings

You can define notification settings globally, for groups and for projects. Valid levels are defined as constants:

- `gitlab.const.NotificationLevel.DISABLED`
- `gitlab.const.NotificationLevel.PARTICIPATING`
- `gitlab.const.NotificationLevel.WATCH`
- `gitlab.const.NotificationLevel.GLOBAL`
- `gitlab.const.NotificationLevel.MENTION`
- `gitlab.const.NotificationLevel.CUSTOM`

You get access to fine-grained settings if you use the `NOTIFICATION_LEVEL_CUSTOM` level.

Reference

- v4 API:
 - `gitlab.v4.objects.NotificationSettings`
 - `gitlab.v4.objects.NotificationSettingsManager`
 - `gitlab.Gitlab.notificationsettings`
 - `gitlab.v4.objects.GroupNotificationSettings`
 - `gitlab.v4.objects.GroupNotificationSettingsManager`
 - `gitlab.v4.objects.Group.notificationsettings`
 - `gitlab.v4.objects.ProjectNotificationSettings`
 - `gitlab.v4.objects.ProjectNotificationSettingsManager`
 - `gitlab.v4.objects.Project.notificationsettings`
- GitLab API: https://docs.gitlab.com/ce/api/notification_settings.html

Examples

Get the notifications settings:

```
# global settings
settings = gl.notificationsettings.get()
# for a group
settings = gl.groups.get(group_id).notificationsettings.get()
# for a project
settings = gl.projects.get(project_id).notificationsettings.get()
```

Update the notifications settings:

```
# use a predefined level
settings.level = gitlab.const.NotificationLevel.WATCH

# create a custom setup
settings.level = gitlab.const.NotificationLevel.CUSTOM
settings.save()  # will create additional attributes, but not mandatory

settings.new_merge_request = True
settings.new_issue = True
settings.new_note = True
settings.save()
```

7.5.29 Merge Trains

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectMergeTrain`
 - `gitlab.v4.objects.ProjectMergeTrainManager`
 - `gitlab.v4.objects.Project.merge_trains`
- GitLab API: https://docs.gitlab.com/ee/api/merge_trains.html

Examples

List merge trains for a project:

```
merge_trains = project.merge_trains.list()
```

List active merge trains for a project:

```
merge_trains = project.merge_trains.list(scope="active")
```

List completed (have been merged) merge trains for a project:

```
merge_trains = project.merge_trains.list(scope="complete")
```

7.5.30 Merge requests

You can use merge requests to notify a project that a branch is ready for merging. The owner of the target project can accept the merge request.

Merge requests are linked to projects, but they can be listed globally or for groups.

Group and global listing

Reference

- v4 API:
 - `gitlab.v4.objects.GroupMergeRequest`
 - `gitlab.v4.objects.GroupMergeRequestManager`
 - `gitlab.v4.objects.Group.mergerequests`
 - `gitlab.v4.objects.MergeRequest`
 - `gitlab.v4.objects.MergeRequestManager`
 - `gitlab.Gitlab.mergerequests`
- GitLab API: https://docs.gitlab.com/ce/api/merge_requests.html

Examples

List the merge requests created by the user of the token on the GitLab server:

```
mrs = gl.mergerequests.list()
```

List the merge requests available on the GitLab server:

```
mrs = gl.mergerequests.list(scope="all")
```

List the merge requests for a group:

```
group = gl.groups.get('mygroup')
mrs = group.mergerequests.list()
```

Note: It is not possible to edit or delete `MergeRequest` and `GroupMergeRequest` objects. You need to create a `ProjectMergeRequest` object to apply changes:

```
mr = group.mergerequests.list()[0]
project = gl.projects.get(mr.project_id, lazy=True)
editable_mr = project.mergerequests.get(mr.iid, lazy=True)
editable_mr.title = updated_title
editable_mr.save()
```

Project merge requests

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectMergeRequest`
 - `gitlab.v4.objects.ProjectMergeRequestManager`
 - `gitlab.v4.objects.Project.mergerequests`
- GitLab API: https://docs.gitlab.com/ce/api/merge_requests.html

Examples

List MRs for a project:

```
mrs = project.mergerequests.list()
```

You can filter and sort the returned list with the following parameters:

- **state:** state of the MR. It can be one of `all`, `merged`, `opened`, `closed` or `locked`
- **order_by:** sort by `created_at` or `updated_at`
- **sort:** sort order (`asc` or `desc`)

You can find a full updated list of parameters here: https://docs.gitlab.com/ee/api/merge_requests.html#list-merge-requests

For example:

```
mrs = project.mergerequests.list(state='merged', order_by='updated_at')
```

Get a single MR:

```
mr = project.mergerequests.get(mr_iid)
```

Create a MR:

```
mr = project.mergerequests.create({'source_branch': 'cool_feature',
                                    'target_branch': 'main',
                                    'title': 'merge cool feature',
                                    'labels': ['label1', 'label2']})
```

Update a MR:

```
mr.description = 'New description'
mr.labels = ['foo', 'bar']
mr.save()
```

Change the state of a MR (close or reopen):

```
mr.state_event = 'close' # or 'reopen'
mr.save()
```

Delete a MR:

```
project.mergerequests.delete(mr_iid)
# or
mr.delete()
```

Accept a MR:

```
mr.merge()
```

Schedule a MR to merge after the pipeline(s) succeed:

```
mr.merge(merge_when_pipeline_succeeds=True)
```

Cancel a MR from merging when the pipeline succeeds:

```
# Cancel a MR from being merged that had been previously set to
# 'merge_when_pipeline_succeeds=True'
mr.cancel_merge_when_pipeline_succeeds()
```

List commits of a MR:

```
commits = mr.commits()
```

List the changes of a MR:

```
changes = mr.changes()
```

List issues that will close on merge:

```
mr.closes_issues()
```

Subscribe to / unsubscribe from a MR:

```
mr.subscribe()  
mr.unsubscribe()
```

Mark a MR as todo:

```
mr.todo()
```

List the diffs for a merge request:

```
diffs = mr.diffs.list()
```

Get a diff for a merge request:

```
diff = mr.diffs.get(diff_id)
```

Get time tracking stats:

```
time_stats = mr.time_stats()
```

On recent versions of Gitlab the time stats are also returned as a merge request object attribute:

```
mr = project.mergerequests.get(id)  
print(mr.attributes['time_stats'])
```

Set a time estimate for a merge request:

```
mr.time_estimate('3h30m')
```

Reset a time estimate for a merge request:

```
mr.reset_time_estimate()
```

Add spent time for a merge request:

```
mr.add_spent_time('3h30m')
```

Reset spent time for a merge request:

```
mr.reset_spent_time()
```

Get user agent detail for the issue (admin only):

```
detail = issue.user_agent_detail()
```

Attempt to rebase an MR:

```
mr.rebase()
```

Clear all approvals of a merge request (possible with project or group access tokens only):

```
mr.reset_approvals()
```

Get status of a rebase for an MR:

```
mr = project.mergerequests.get(mr_id, include_rebase_in_progress=True)
print(mr.rebase_in_progress, mr.merge_error)
```

For more info see: https://docs.gitlab.com/ee/api/merge_requests.html#rebase-a-merge-request

Attempt to merge changes between source and target branch:

```
response = mr.merge_ref()
print(response['commit_id'])
```

Merge Request Pipelines

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectMergeRequestPipeline`
 - `gitlab.v4.objects.ProjectMergeRequestPipelineManager`
 - `gitlab.v4.objects.ProjectMergeRequest.pipelines`
- GitLab API: https://docs.gitlab.com/ee/api/merge_requests.html#list-mr-pipelines

Examples

List pipelines for a merge request:

```
pipelines = mr.pipelines.list()
```

Create a pipeline for a merge request:

```
pipeline = mr.pipelines.create()
```

7.5.31 Merge request approvals settings

Merge request approvals can be defined at the project level or at the merge request level.

References

- v4 API:
 - `gitlab.v4.objects.ProjectApproval`
 - `gitlab.v4.objects.ProjectApprovalManager`
 - `gitlab.v4.objects.ProjectApprovalRule`
 - `gitlab.v4.objects.ProjectApprovalRuleManager`
 - `gitlab.v4.objects.Project.approvals`
 - `gitlab.v4.objects.ProjectMergeRequestApproval`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalManager`
 - `gitlab.v4.objects.ProjectMergeRequest.approvals`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalRule`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager`
 - `gitlab.v4.objects.ProjectMergeRequest.approval_rules`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalState`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalStateManager`
 - `gitlab.v4.objects.ProjectMergeRequest.approval_state`
- GitLab API: https://docs.gitlab.com/ee/api/merge_request_approvals.html

Examples

List project-level MR approval rules:

```
p_mrmas = project.approvalrules.list()
```

Change project-level MR approval rule:

```
p_approvalrule.user_ids = [234]  
p_approvalrule.save()
```

Delete project-level MR approval rule:

```
p_approvalrule.delete()
```

Get project-level or MR-level MR approvals settings:

```
p_mrmas = project.approvals.get()  
  
mr_mrmas = mr.approvals.get()
```

Get MR-level approval state:

```
mr_approval_state = mr.approval_state.get()
```

Change project-level or MR-level MR approvals settings:

```
p_mras.approvals_before_merge = 2
p_mras.save()

mr.approvals.set_approvers(approvals_required=1)
# or
mr_mras.approvals_required = 1
mr_mras.save()
```

Create a new MR-level approval rule or change an existing MR-level approval rule:

```
mr.approvals.set_approvers(approvals_required = 1, approver_ids=[105],
                           approver_group_ids=[653, 654],
                           approval_rule_name="my MR custom approval rule")
```

List MR-level MR approval rules:

```
mr.approval_rules.list()
```

Get a single MR approval rule:

```
approval_rule_id = 123
mr_approvalrule = mr.approval_rules.get(approval_rule_id)
```

Delete MR-level MR approval rule:

```
rules = mr.approval_rules.list()
rules[0].delete()

# or
mr.approval_rules.delete(approval_id)
```

Change MR-level MR approval rule:

```
mr_approvalrule.user_ids = [105]
mr_approvalrule.approvals_required = 2
mr_approvalrule.group_ids = [653, 654]
mr_approvalrule.save()
```

Create a MR-level MR approval rule:

```
mr.approval_rules.create({
    "name": "my MR custom approval rule",
    "approvals_required": 2,
    "rule_type": "regular",
    "user_ids": [105],
    "group_ids": [653, 654],
})
```

7.5.32 Milestones

Project milestones

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectMilestone`
 - `gitlab.v4.objects.ProjectMilestoneManager`
 - `gitlab.v4.objects.Project.milestones`
 - `gitlab.v4.objects.GroupMilestone`
 - `gitlab.v4.objects.GroupMilestoneManager`
 - `gitlab.v4.objects.Group.milestones`
- GitLab API:
 - <https://docs.gitlab.com/ce/api/milestones.html>
 - https://docs.gitlab.com/ce/api/group_milestones.html

Examples

List the milestones for a project or a group:

```
p_milestones = project.milestones.list()
g_milestones = group.milestones.list()
```

You can filter the list using the following parameters:

- `iids`: unique IDs of milestones for the project
- `state`: either `active` or `closed`
- `search`: to search using a string

```
p_milestones = project.milestones.list(state='closed')
g_milestones = group.milestones.list(state='active')
```

Get a single milestone:

```
p_milestone = project.milestones.get(milestone_id)
g_milestone = group.milestones.get(milestone_id)
```

Create a milestone:

```
milestone = project.milestones.create({'title': '1.0'})
```

Edit a milestone:

```
milestone.description = 'v 1.0 release'
milestone.save()
```

Change the state of a milestone (activate / close):

```
# close a milestone
milestone.state_event = 'close'
milestone.save()

# activate a milestone
milestone.state_event = 'activate'
milestone.save()
```

Promote a project milestone:

```
milestone.promote()
```

List the issues related to a milestone:

```
issues = milestone.issues()
```

List the merge requests related to a milestone:

```
merge_requests = milestone.merge_requests()
```

Milestone events

Resource milestone events keep track of what happens to GitLab issues and merge requests.

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectIssueResourceMilestoneEvent*
 - *gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager*
 - *gitlab.v4.objects.ProjectIssue.resourcemilestoneevents*
 - *gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEvent*
 - *gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager*
 - *gitlab.v4.objects.ProjectMergeRequest.resourcemilestoneevents*
- GitLab API: https://docs.gitlab.com/ee/api/resource_milestone_events.html

Examples

Get milestones for a resource (issue, merge request):

```
milestones = resource.resourcemilestoneevents.list()
```

Get a specific milestone for a resource:

```
milestone = resource.resourcemilestoneevents.get(milestone_id)
```

7.5.33 Namespaces

Reference

- v4 API:
 - `gitlab.v4.objects.Namespace`
 - `gitlab.v4.objects.NamespaceManager`
 - `gitlab.Gitlab.namespaces`
- GitLab API: <https://docs.gitlab.com/ce/api/namespaces.html>

Examples

List namespaces:

```
namespaces = gl.namespaces.list()
```

Search namespaces:

```
namespaces = gl.namespaces.list(search='foo')
```

Get a namespace by ID or path:

```
namespace = gl.namespaces.get("my-namespace")
```

Get existence of a namespace by path:

```
namespace = gl.namespaces.exists("new-namespace")

if namespace.exists:
    # get suggestions of namespaces that don't already exist
    print(namespace.suggests)
```

7.5.34 Notes

You can manipulate notes (comments) on group epics, project issues, merge requests and snippets.

Reference

- v4 API:
 - Epics:
 - `gitlab.v4.objects.GroupEpicNote`
 - `gitlab.v4.objects.GroupEpicNoteManager`
 - `gitlab.v4.objects.GroupEpic.notes`
 - Issues:
 - `gitlab.v4.objects.ProjectIssueNote`
 - `gitlab.v4.objects.ProjectIssueNoteManager`

- `gitlab.v4.objects.ProjectIssue.notes`

MergeRequests:

- `gitlab.v4.objects.ProjectMergeRequestNote`
- `gitlab.v4.objects.ProjectMergeRequestNoteManager`
- `gitlab.v4.objects.ProjectMergeRequest.notes`

Snippets:

- `gitlab.v4.objects.ProjectSnippetNote`
- `gitlab.v4.objects.ProjectSnippetNoteManager`
- `gitlab.v4.objects.ProjectSnippet.notes`

- GitLab API: <https://docs.gitlab.com/ce/api/notes.html>

Examples

List the notes for a resource:

```
e_notes = epic.notes.list()  
i_notes = issue.notes.list()  
mr_notes = mr.notes.list()  
s_notes = snippet.notes.list()
```

Get a note for a resource:

```
e_note = epic.notes.get(note_id)  
i_note = issue.notes.get(note_id)  
mr_note = mr.notes.get(note_id)  
s_note = snippet.notes.get(note_id)
```

Create a note for a resource:

```
e_note = epic.notes.create({'body': 'note content'})  
i_note = issue.notes.create({'body': 'note content'})  
mr_note = mr.notes.create({'body': 'note content'})  
s_note = snippet.notes.create({'body': 'note content'})
```

Update a note for a resource:

```
note.body = 'updated note content'  
note.save()
```

Delete a note for a resource:

```
note.delete()
```

7.5.35 Packages

Packages allow you to utilize GitLab as a private repository for a variety of common package managers, as well as GitLab's generic package registry.

Project Packages

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectPackage`
 - `gitlab.v4.objects.ProjectPackageManager`
 - `gitlab.v4.objects.Project.packages`
- GitLab API: <https://docs.gitlab.com/ee/api/packages.html#within-a-project>

Examples

List the packages in a project:

```
packages = project.packages.list()
```

Filter the results by `package_type` or `package_name`

```
packages = project.packages.list(package_type='pypi')
```

Get a specific package of a project by id:

```
package = project.packages.get(1)
```

Delete a package from a project:

```
package.delete()  
# or  
project.packages.delete(package.id)
```

Group Packages

Reference

- v4 API:
 - `gitlab.v4.objects.GroupPackage`
 - `gitlab.v4.objects.GroupPackageManager`
 - `gitlab.v4.objects.Group.packages`
- GitLab API: <https://docs.gitlab.com/ee/api/packages.html#within-a-group>

Examples

List the packages in a group:

```
packages = group.packages.list()
```

Filter the results by `package_type` or `package_name`

```
packages = group.packages.list(package_type='pypi')
```

Project Package Files

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectPackageFile`
 - `gitlab.v4.objects.ProjectPackageManager`
 - `gitlab.v4.objects.ProjectPackage.package_files`
- GitLab API: <https://docs.gitlab.com/ee/api/packages.html#list-package-files>

Examples

List package files for package in project:

```
package = project.packages.get(1)
package_files = package.package_files.list()
```

Delete a package file in a project:

```
package = project.packages.get(1)
file = package.package_files.list()[0]
file.delete()
```

Generic Packages

You can use python-gitlab to upload and download generic packages.

Reference

- v4 API:
 - `gitlab.v4.objects.GenericPackage`
 - `gitlab.v4.objects.GenericPackageManager`
 - `gitlab.v4.objects.Project.generic_packages`
- GitLab API: https://docs.gitlab.com/ee/user/packages/generic_packages

Examples

Upload a generic package to a project:

```
project = gl.projects.get(1, lazy=True)
package = project.generic_packages.upload(
    package_name="hello-world",
    package_version="v1.0.0",
    file_name="hello.tar.gz",
    path="/path/to/local/hello.tar.gz"
)
```

Download a project's generic package:

```
project = gl.projects.get(1, lazy=True)
package = project.generic_packages.download(
    package_name="hello-world",
    package_version="v1.0.0",
    file_name="hello.tar.gz",
)
```

Hint: You can use the Packages API described above to find packages and retrieve the metadata you need download them.

7.5.36 Pages domains

Admin

References

- v4 API:
 - `gitlab.v4.objects.PagesDomain`
 - `gitlab.v4.objects.PagesDomainManager`
 - `gitlab.Gitlab.pagesdomains`
- GitLab API: https://docs.gitlab.com/ce/api/pages_domains.html#list-all-pages-domains

Examples

List all the existing domains (admin only):

```
domains = gl.pagesdomains.list()
```

Project pages domain

References

- v4 API:
 - `gitlab.v4.objects.ProjectPagesDomain`
 - `gitlab.v4.objects.ProjectPagesDomainManager`
 - `gitlab.v4.objects.Project.pagesdomains`
- GitLab API: https://docs.gitlab.com/ce/api/pages_domains.html#list-pages-domains

Examples

List domains for a project:

```
domains = project.pagesdomains.list()
```

Get a single domain:

```
domain = project.pagesdomains.get('d1.example.com')
```

Create a new domain:

```
domain = project.pagesdomains.create({'domain': 'd2.example.com'})
```

Update an existing domain:

```
domain.certificate = open('d2.crt').read()
domain.key = open('d2.key').read()
domain.save()
```

Delete an existing domain:

```
domain.delete
# or
project.pagesdomains.delete('d2.example.com')
```

7.5.37 Personal Access Tokens

References

- v4 API:
 - `gitlab.v4.objects.PersonalAccessToken`
 - `gitlab.v4.objects.PersonalAccessTokenManager`
 - `gitlab.Gitlab.personal_access_tokens`
 - `gitlab.v4.objects.UserPersonalAccessToken`
 - `gitlab.v4.objects.UserPersonalAccessTokenManager`
 - `gitlab.Gitlab.User.personal_access_tokens`

- GitLab API:
 - https://docs.gitlab.com/ee/api/personal_access_tokens.html
 - <https://docs.gitlab.com/ee/api/users.html#create-a-personal-access-token>

Examples

List personal access tokens:

```
access_tokens = gl.personal_access_tokens.list()
print(access_tokens[0].name)
```

List personal access tokens from other user_id (admin only):

```
access_tokens = gl.personal_access_tokens.list(user_id=25)
```

Get a personal access token by id:

```
gl.personal_access_tokens.get(123)
```

Get the personal access token currently used:

```
gl.personal_access_tokens.get("self")
```

Revoke a personal access token fetched via list:

```
access_token = access_tokens[0]
access_token.delete()
```

Revoke a personal access token by id:

```
gl.personal_access_tokens.delete(123)
```

Revoke the personal access token currently used:

```
gl.personal_access_tokens.delete("self")
```

Create a personal access token for a user (admin only):

```
user = gl.users.get(25, lazy=True)
access_token = user.personal_access_tokens.create({"name": "test", "scopes": "api"})
```

Note: As you can see above, you can only create personal access tokens via the Users API, but you cannot revoke these objects directly. This is because the create API uses a different endpoint than the list and revoke APIs. You need to fetch the token via the list API first to revoke it.

As of 14.2, GitLab does not provide a GET API for single personal access tokens. You must use the list method to retrieve single tokens.

7.5.38 Pipelines and Jobs

Project pipelines

A pipeline is a group of jobs executed by GitLab CI.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectPipeline`
 - `gitlab.v4.objects.ProjectPipelineManager`
 - `gitlab.v4.objects.Project.pipelines`
- GitLab API: <https://docs.gitlab.com/ce/api/pipelines.html>

Examples

List pipelines for a project:

```
pipelines = project.pipelines.list()
```

Get a pipeline for a project:

```
pipeline = project.pipelines.get(pipeline_id)
```

Get variables of a pipeline:

```
variables = pipeline.variables.list()
```

Create a pipeline for a particular reference with custom variables:

```
pipeline = project.pipelines.create({'ref': 'main', 'variables': [{  
    'key': 'MY_VARIABLE',  
    'value': 'hello'}]})
```

Retry the failed builds for a pipeline:

```
pipeline.retry()
```

Cancel builds in a pipeline:

```
pipeline.cancel()
```

Delete a pipeline:

```
pipeline.delete()
```

Triggers

Triggers provide a way to interact with the GitLab CI. Using a trigger a user or an application can run a new build/job for a specific commit.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectTrigger`
 - `gitlab.v4.objects.ProjectTriggerManager`
 - `gitlab.v4.objects.Project.triggers`
- GitLab API: https://docs.gitlab.com/ce/api/pipeline_triggers.html

Examples

List triggers:

```
triggers = project.triggers.list()
```

Get a trigger:

```
trigger = project.triggers.get(trigger_token)
```

Create a trigger:

```
trigger = project.triggers.create({'description': 'mytrigger'})
```

Remove a trigger:

```
project.triggers.delete(trigger_token)
# or
trigger.delete()
```

Full example with wait for finish:

```
def get_or_create_trigger(project):
    trigger_description = 'my_trigger_id'
    for t in project.triggers.list():
        if t.description == trigger_description:
            return t
    return project.triggers.create({'description': trigger_description})

trigger = get_or_create_trigger(project)
pipeline = project.trigger_pipeline('main', trigger.token, variables={"DEPLOY_ZONE": "us-west1"})
while pipeline.finished_at is None:
    pipeline.refresh()
    time.sleep(1)
```

You can trigger a pipeline using token authentication instead of user authentication. To do so create an anonymous Gitlab instance and use lazy objects to get the associated project:

```
gl = gitlab.Gitlab(URL)  # no authentication
project = gl.projects.get(project_id, lazy=True)  # no API call
project.trigger_pipeline('main', trigger_token)
```

Reference: <https://docs.gitlab.com/ee/ci/triggers/#trigger-token>

Pipeline schedules

You can schedule pipeline runs using a cron-like syntax. Variables can be associated with the scheduled pipelines.

Reference

- v4 API
 - `gitlab.v4.objects.ProjectPipelineSchedule`
 - `gitlab.v4.objects.ProjectPipelineScheduleManager`
 - `gitlab.v4.objects.Project.pipelineschedules`
 - `gitlab.v4.objects.ProjectPipelineScheduleVariable`
 - `gitlab.v4.objects.ProjectPipelineScheduleVariableManager`
 - `gitlab.v4.objects.ProjectPipelineSchedule.variables`
 - `gitlab.v4.objects.ProjectPipelineSchedulePipeline`
 - `gitlab.v4.objects.ProjectPipelineSchedulePipelineManager`
 - `gitlab.v4.objects.ProjectPipelineSchedule.pipelines`
- GitLab API: https://docs.gitlab.com/ce/api/pipeline_schedules.html

Examples

List pipeline schedules:

```
scheds = project.pipelineschedules.list()
```

Get a single schedule:

```
sched = project.pipelineschedules.get(schedule_id)
```

Create a new schedule:

```
sched = project.pipelineschedules.create({
    'ref': 'main',
    'description': 'Daily test',
    'cron': '0 1 * * *'})
```

Update a schedule:

```
sched.cron = '1 2 * * *'
sched.save()
```

Take ownership of a schedule:

```
sched.take_ownership()
```

Trigger a pipeline schedule immediately:

```
sched = projects.pipelineschedules.get(schedule_id)
sched.play()
```

Delete a schedule:

```
sched.delete()
```

List schedule variables:

```
# note: you need to use get() to retrieve the schedule variables. The
# attribute is not present in the response of a list() call
sched = projects.pipelineschedules.get(schedule_id)
vars = sched.attributes['variables']
```

Create a schedule variable:

```
var = sched.variables.create({'key': 'foo', 'value': 'bar'})
```

Edit a schedule variable:

```
var.value = 'new_value'
var.save()
```

Delete a schedule variable:

```
var.delete()
```

List all pipelines triggered by a pipeline schedule:

```
pipelines = sched.pipelines.list()
```

Jobs

Jobs are associated to projects, pipelines and commits. They provide information on the jobs that have been run, and methods to manipulate them.

Reference

- v4 API
 - `gitlab.v4.objects.ProjectJob`
 - `gitlab.v4.objects.ProjectJobManager`
 - `gitlab.v4.objects.Project.jobs`
- GitLab API: <https://docs.gitlab.com/ce/api/jobs.html>

Examples

Jobs are usually automatically triggered, but you can explicitly trigger a new job:

```
project.trigger_build('main', trigger_token,
                      {'extra_var1': 'foo', 'extra_var2': 'bar'})
```

List jobs for the project:

```
jobs = project.jobs.list()
```

Get a single job:

```
project.jobs.get(job_id)
```

List the jobs of a pipeline:

```
project = gl.projects.get(project_id)
pipeline = project.pipelines.get(pipeline_id)
jobs = pipeline.jobs.list()
```

Note: Job methods (play, cancel, and so on) are not available on `ProjectPipelineJob` objects. To use these methods create a `ProjectJob` object:

```
pipeline_job = pipeline.jobs.list()[0]
job = project.jobs.get(pipeline_job.id, lazy=True)
job.retry()
```

Get the artifacts of a job:

```
build_or_job.artifacts()
```

Get the artifacts of a job by its name from the latest successful pipeline of a branch or tag:

```
project.artifacts.download(ref_name='main', job='build')
```

Attention: An older method `project.artifacts()` is deprecated and will be removed in a future version.

Warning: Artifacts are entirely stored in memory in this example.

You can download artifacts as a stream. Provide a callable to handle the stream:

```
with open("archive.zip", "wb") as f:
    build_or_job.artifacts(streamed=True, action=f.write)
```

You can also directly stream the output into a file, and unzip it afterwards:

```
zipfn = "__artifacts.zip"
with open(zipfn, "wb") as f:
```

(continues on next page)

(continued from previous page)

```
build_or_job.artifacts(streamed=True, action=f.write)
subprocess.run(["unzip", "-bo", zipfn])
os.unlink(zipfn)
```

Or, you can also use the underlying response iterator directly:

```
artifact_bytes_iterator = build_or_job.artifacts(iterator=True)
```

This can be used with frameworks that expect an iterator (such as FastAPI/Starlette's `StreamingResponse`) to forward a download from GitLab without having to download the entire content server-side first:

```
@app.get("/download_artifact")
def download_artifact():
    artifact_bytes_iterator = build_or_job.artifacts(iterator=True)
    return StreamingResponse(artifact_bytes_iterator, media_type="application/zip")
```

Delete all artifacts of a project that can be deleted:

```
project.artifacts.delete()
```

Get a single artifact file:

```
build_or_job.artifact('path/to/file')
```

Get a single artifact file by branch and job:

```
project.artifacts.raw('branch', 'path/to/file', 'job')
```

Attention: An older method `project.artifact()` is deprecated and will be removed in a future version.

Mark a job artifact as kept when expiration is set:

```
build_or_job.keep_artifacts()
```

Delete the artifacts of a job:

```
build_or_job.delete_artifacts()
```

Get a job log file / trace:

```
build_or_job.trace()
```

Warning: Traces are entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Cancel/retry a job:

```
build_or_job.cancel()
build_or_job.retry()
```

Play (trigger) a job:

```
build_or_job.play()
```

Erase a job (artifacts and trace):

```
build_or_job.erase()
```

Pipeline bridges

Get a list of bridge jobs (including child pipelines) for a pipeline.

Reference

- v4 API
 - *gitlab.v4.objects.ProjectPipelineBridge*
 - *gitlab.v4.objects.ProjectPipelineBridgeManager*
 - *gitlab.v4.objects.ProjectPipeline.bridges*
- GitLab API: <https://docs.gitlab.com/ee/api/jobs.html#list-pipeline-bridges>

Examples

List bridges for the pipeline:

```
bridges = pipeline.bridges.list()
```

Pipeline test report

Get a pipeline's complete test report.

Reference

- v4 API
 - *gitlab.v4.objects.ProjectPipelineTestReport*
 - *gitlab.v4.objects.ProjectPipelineTestReportManager*
 - *gitlab.v4.objects.ProjectPipeline.test_report*
- GitLab API: <https://docs.gitlab.com/ee/api/pipelines.html#get-a-pipelines-test-report>

Examples

Get the test report for a pipeline:

```
test_report = pipeline.test_report.get()
```

Pipeline test report summary

Get a pipeline's test report summary.

Reference

- v4 API
 - *gitlab.v4.objects.ProjectPipelineTestReportSummary*
 - *gitlab.v4.objects.ProjectPipelineTestReportSummaryManager*
 - *gitlab.v4.objects.ProjectPipeline.test_report_summary*
- GitLab API: <https://docs.gitlab.com/ee/api/pipelines.html#get-a-pipelines-test-report-summary>

Examples

Get the test report summary for a pipeline:

```
test_report_summary = pipeline.test_report_summary.get()
```

7.5.39 Projects

Projects

Reference

- v4 API:
 - *gitlab.v4.objects.Project*
 - *gitlab.v4.objects.ProjectManager*
 - *gitlab.Gitlab.projects*
- GitLab API: <https://docs.gitlab.com/ce/api/projects.html>

Examples

List projects:

```
projects = gl.projects.list()
```

The API provides several filtering parameters for the listing methods:

- `archived`: if `True` only archived projects will be returned
- `visibility`: returns only projects with the specified visibility (can be `public`, `internal` or `private`)
- `search`: returns project matching the given pattern

Results can also be sorted using the following parameters:

- `order_by`: sort using the given argument. Valid values are `id`, `name`, `path`, `created_at`, `updated_at` and `last_activity_at`. The default is to sort by `created_at`
- `sort`: sort order (`asc` or `desc`)

```
# List all projects (default 20)
projects = gl.projects.list(get_all=True)
# Archived projects
projects = gl.projects.list(archived=True)
# Limit to projects with a defined visibility
projects = gl.projects.list.visibility='public')

# List owned projects
projects = gl.projects.list(owned=True)

# List starred projects
projects = gl.projects.list(starred=True)

# Search projects
projects = gl.projects.list(search='keyword')
```

Note: To list the starred projects of another user, see the [Users API docs](#).

Note: Fetching a list of projects, doesn't include all attributes of all projects. To retrieve all attributes, you'll need to fetch a single project

Get a single project:

```
# Get a project by ID
project_id = 851
project = gl.projects.get(project_id)

# Get a project by name with namespace
project_name_with_namespace = "namespace/project_name"
project = gl.projects.get(project_name_with_namespace)
```

Create a project:

```
project = gl.projects.create({'name': 'project1'})
```

Create a project for a user (admin only):

```
alice = gl.users.list(username='alice')[0]
user_project = alice.projects.create({'name': 'project'})
user_projects = alice.projects.list()
```

Create a project in a group:

```
# You need to get the id of the group, then use the namespace_id attribute
# to create the group
group_id = gl.groups.list(search='my-group')[0].id
project = gl.projects.create({'name': 'myrepo', 'namespace_id': group_id})
```

List a project's groups:

```
# Get a list of ancestor/parent groups for a project.
groups = project.groups.list()
```

Update a project:

```
project.snippets_enabled = 1
project.save()
```

Set the avatar image for a project:

```
# the avatar image can be passed as data (content of the file) or as a file
# object opened in binary mode
project.avatar = open('path/to/file.png', 'rb')
project.save()
```

Delete a project:

```
gl.projects.delete(project_id)
# or
project.delete()
```

Restore a project marked for deletion (Premium only):

```
project.restore()
```

Fork a project:

```
fork = project.forks.create({})
# fork to a specific namespace
fork = project.forks.create({'namespace': 'myteam'})
```

Get a list of forks for the project:

```
forks = project.forks.list()
```

Create/delete a fork relation between projects (requires admin permissions):

```
project.create_fork_relation(source_project.id)
project.delete_fork_relation()
```

Get languages used in the project with percentage value:

```
languages = project.languages()
```

Star/unstar a project:

```
project.star()
project.unstar()
```

Archive/unarchive a project:

```
project.archive()
project.unarchive()
```

Start the housekeeping job:

```
project.housekeeping()
```

List the repository tree:

```
# list the content of the root directory for the default branch
items = project.repository_tree()

# list the content of a subdirectory on a specific branch
items = project.repository_tree(path='docs', ref='branch1')
```

Get the content and metadata of a file for a commit, using a blob sha:

```
items = project.repository_tree(path='docs', ref='branch1')
file_info = p.repository_blob(items[0]['id'])
content = base64.b64decode(file_info['content'])
size = file_info['size']
```

Update a project submodule:

```
items = project.update_submodule(
    submodule="foo/bar",
    branch="main",
    commit_sha="4c3674f66071e30b3311dac9b9ccc90502a72664",
    commit_message="Message", # optional
)
```

Get the repository archive:

```
tgz = project.repository_archive()

# get the archive for a branch/tag/commit
tzg = project.repository_archive(sha='4567abc')

# get the archive in a different format
zip = project.repository_archive(format='zip')
```

Note: For the formats available, refer to <https://docs.gitlab.com/ce/api/repositories.html#get-file-archive>

Warning: Archives are entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Get the content of a file using the blob id:

```
# find the id for the blob (simple search)
id = [d['id'] for d in p.repository_tree() if d['name'] == 'README.rst'][0]

# get the content
file_content = p.repository_raw_blob(id)
```

Warning: Blobs are entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Get a snapshot of the repository:

```
tar_file = project.snapshot()
```

Warning: Snapshots are entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Compare two branches, tags or commits:

```
result = project.repository_compare('main', 'branch1')

# get the commits
for commit in result['commits']:
    print(commit)

# get the diffs
for file_diff in result['diffs']:
    print(file_diff)
```

Get the merge base for two or more branches, tags or commits:

```
commit = project.repository_merge_base(['main', 'v1.2.3', 'bd1324e2f'])
```

Get a list of contributors for the repository:

```
contributors = project.repository_contributors()
```

Get a list of users for the repository:

```
users = p.users.list()

# search for users
users = p.users.list(search='pattern')
```

Start the pull mirroring process (EE edition):

```
project.mirror_pull()
```

Get a project's pull mirror details (EE edition):

```
mirror_pull_details = project.mirror_pull_details()
```

Import / Export

You can export projects from gitlab, and re-import them to create new projects or overwrite existing ones.

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectExport*
 - *gitlab.v4.objects.ProjectExportManager*
 - *gitlab.v4.objects.Project.exports*
 - *gitlab.v4.objects.ProjectImport*
 - *gitlab.v4.objects.ProjectImportManager*
 - *gitlab.v4.objects.Project.imports*
 - *gitlab.v4.objects.ProjectManager.import_project*
- GitLab API: https://docs.gitlab.com/ce/api/project_import_export.html

Examples

A project export is an asynchronous operation. To retrieve the archive generated by GitLab you need to:

1. Create an export using the API
2. Wait for the export to be done
3. Download the result

```
# Create the export
p = gl.projects.get(my_project)
export = p.exports.create()

# Wait for the 'finished' status
export.refresh()
while export.export_status != 'finished':
    time.sleep(1)
    export.refresh()

# Download the result
with open('/tmp/export.tgz', 'wb') as f:
    export.download(streamed=True, action=f.write)
```

You can export and upload a project to an external URL (see upstream documentation for more details):

```
project.exports.create(
{
    "upload":
    {
        "url": "http://localhost:8080",
        "method": "POST"
    }
}
)
```

You can also get the status of an existing export, regardless of whether it was created via the API or the Web UI:

```
project = gl.projects.get(my_project)

# Gets the current export status
export = project.exports.get()
```

Import the project into the current user's namespace:

```
with open('/tmp/export.tgz', 'rb') as f:
    output = gl.projects.import_project(
        f, path='my_new_project', name='My New Project'
    )

# Get a ProjectImport object to track the import status
project_import = gl.projects.get(output['id'], lazy=True).imports.get()
while project_import.import_status != 'finished':
    time.sleep(1)
    project_import.refresh()
```

Import the project into a namespace and override parameters:

```
with open('/tmp/export.tgz', 'rb') as f:
    output = gl.projects.import_project(
        f,
        path='my_new_project',
        name='My New Project',
        namespace='my-group',
        override_params={'visibility': 'private'},
    )
```

Import the project using file stored on a remote URL:

```
output = gl.projects.remote_import(
    url="https://whatever.com/url/file.tar.gz",
    path="my_new_remote_project",
    name="My New Remote Project",
    namespace="my-group",
    override_params={'visibility': 'private'},
)
```

Import the project using file stored on AWS S3:

```
output = gl.projects.remote_import_s3(  
    path="my_new_remote_project",  
    region="aws-region",  
    bucket_name="aws-bucket-name",  
    file_key="aws-file-key",  
    access_key_id="aws-access-key-id",  
    secret_access_key="secret-access-key",  
    name="My New Remote Project",  
    namespace="my-group",  
    override_params={'visibility': 'private'},  
)
```

Project custom attributes

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCustomAttribute`
 - `gitlab.v4.objects.ProjectCustomAttributeManager`
 - `gitlab.v4.objects.Project.customattributes`
- GitLab API: https://docs.gitlab.com/ce/api/custom_attributes.html

Examples

List custom attributes for a project:

```
attrs = project.customattributes.list()
```

Get a custom attribute for a project:

```
attr = project.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a project:

```
attr = project.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a project:

```
attr.delete()  
# or  
project.customattributes.delete(attr_key)
```

Search projects by custom attribute:

```
project.customattributes.set('type', 'internal')  
gl.projects.list(custom_attributes={'type': 'internal'})
```

Project files

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectFile`
 - `gitlab.v4.objects.ProjectFileManager`
 - `gitlab.v4.objects.Project.files`
- GitLab API: https://docs.gitlab.com/ce/api/repository_files.html

Examples

Get a file:

```
f = project.files.get(file_path='README.rst', ref='main')

# get the base64 encoded content
print(f.content)

# get the decoded content
print(f.decode())
```

Get file details from headers, without fetching its entire content:

```
headers = project.files.head('README.rst', ref='main')

# Get the file size:
# For a full list of headers returned, see upstream documentation.
# https://docs.gitlab.com/ee/api/repository_files.html#get-file-from-repository
print(headers["X-Gitlab-Size"])
```

Get a raw file:

```
raw_content = project.files.raw(file_path='README.rst', ref='main')
print(raw_content)

with open('/tmp/raw-download.txt', 'wb') as f:
    project.files.raw(file_path='README.rst', ref='main', streamed=True, action=f.write)
```

Create a new file:

```
f = project.files.create({'file_path': 'testfile.txt',
                           'branch': 'main',
                           'content': file_content,
                           'author_email': 'test@example.com',
                           'author_name': 'yourname',
                           'commit_message': 'Create testfile'})
```

Update a file. The entire content must be uploaded, as plain text or as base64 encoded text:

```
f.content = 'new content'
f.save(branch='main', commit_message='Update testfile')

# or for binary data
# Note: decode() is required with python 3 for data serialization. You can omit
# it with python 2
f.content = base64.b64encode(open('image.png').read()).decode()
f.save(branch='main', commit_message='Update testfile', encoding='base64')
```

Delete a file:

```
f.delete(commit_message='Delete testfile', branch='main')
# or
project.files.delete(file_path='testfile.txt', commit_message='Delete testfile', branch=
↪'main')
```

Get file blame:

```
b = project.files.blame(file_path='README.rst', ref='main')
```

Project tags

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectTag*
 - *gitlab.v4.objects.ProjectTagManager*
 - *gitlab.v4.objects.Project.tags*
- GitLab API: <https://docs.gitlab.com/ce/api/tags.html>

Examples

List the project tags:

```
tags = project.tags.list()
```

Get a tag:

```
tag = project.tags.get('1.0')
```

Create a tag:

```
tag = project.tags.create({'tag_name': '1.0', 'ref': 'main'})
```

Delete a tag:

```
project.tags.delete('1.0')
# or
tag.delete()
```

Project snippets

The snippet visibility can be defined using the following constants:

- `gitlab.const.Visibility.PRIVATE`
- `gitlab.const.Visibility.INTERNAL`
- `gitlab.const.Visibility.PUBLIC`

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectSnippet`
 - `gitlab.v4.objects.ProjectSnippetManager`
 - `gitlab.v4.objects.Project.files`
- GitLab API: https://docs.gitlab.com/ce/api/project_snippets.html

Examples

List the project snippets:

```
snippets = project.snippets.list()
```

Get a snippet:

```
snippet = project.snippets.get(snippet_id)
```

Get the content of a snippet:

```
print(snippet.content())
```

Warning: The snippet content is entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Create a snippet:

```
snippet = project.snippets.create({'title': 'sample 1',
                                    'file_name': 'foo.py',
                                    'code': 'import gitlab',
                                    'visibility_level':
                                    gitlab.const.Visibility.PRIVATE})
```

Update a snippet:

```
snippet.code = 'import gitlab\nimport whatever'
snippet.save
```

Delete a snippet:

```
project.snippets.delete(snippet_id)
# or
snippet.delete()
```

Get user agent detail (admin only):

```
detail = snippet.user_agent_detail()
```

Notes

See *Notes*.

Project members

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectMember`
 - `gitlab.v4.objects.ProjectMemberManager`
 - `gitlab.v4.objects.ProjectMemberAllManager`
 - `gitlab.v4.objects.Project.members`
 - `gitlab.v4.objects.Project.members_all`
- GitLab API: <https://docs.gitlab.com/ce/api/members.html>

Examples

List only direct project members:

```
members = project.members.list()
```

List the project members recursively (including inherited members through ancestor groups):

```
members = project.members_all.list(get_all=True)
```

Search project members matching a query string:

```
members = project.members.list(query='bar')
```

Get only direct project member:

```
member = project.members.get(user_id)
```

Get a member of a project, including members inherited through ancestor groups:

```
members = project.members_all.get(member_id)
```

Add a project member:

```
member = project.members.create({'user_id': user.id, 'access_level':
                                gitlab.const.AccessLevel.DEVELOPER})
```

Modify a project member (change the access level):

```
member.access_level = gitlab.const.AccessLevel.MAINTAINER
member.save()
```

Remove a member from the project team:

```
project.members.delete(user.id)
# or
member.delete()
```

Share/unshare the project with a group:

```
project.share(group.id, gitlab.const.AccessLevel.DEVELOPER)
project.unshare(group.id)
```

Project hooks

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectHook`
 - `gitlab.v4.objects.ProjectHookManager`
 - `gitlab.v4.objects.Project.hooks`
- GitLab API: <https://docs.gitlab.com/ce/api/projects.html#hooks>

Examples

List the project hooks:

```
hooks = project.hooks.list()
```

Get a project hook:

```
hook = project.hooks.get(hook_id)
```

Create a project hook:

```
hook = project.hooks.create({'url': 'http://my/action/url', 'push_events': 1})
```

Update a project hook:

```
hook.push_events = 0
hook.save()
```

Delete a project hook:

```
project.hooks.delete(hook_id)
# or
hook.delete()
```

Project Integrations

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIntegration`
 - `gitlab.v4.objects.ProjectIntegrationManager`
 - `gitlab.v4.objects.Project.integrations`
- GitLab API: <https://docs.gitlab.com/ce/api/integrations.html>

Examples

Danger: Since GitLab 13.12, `get()` calls to project integrations return a `404 Not Found` response until they have been activated the first time.

To avoid this, we recommend using `lazy=True` to prevent making the initial call when activating new integrations unless they have previously already been activated.

Configure and enable an integration for the first time:

```
integration = project.integrations.get('asana', lazy=True)

integration.api_key = 'randomkey'
integration.save()
```

Get an existing integration:

```
integration = project.integrations.get('asana')
# display its status (enabled/disabled)
print(integration.active)
```

List active project integrations:

```
integration = project.integrations.list()
```

List the code names of available integrations (doesn't return objects):

```
integrations = project.integrations.available()
```

Disable an integration:

```
integration.delete()
```

File uploads

Reference

- v4 API:
 - `gitlab.v4.objects.Project.upload`
- Gitlab API: <https://docs.gitlab.com/ce/api/projects.html#upload-a-file>

Examples

Upload a file into a project using a filesystem path:

```
project.upload("filename.txt", filepath="/some/path/filename.txt")
```

Upload a file into a project without a filesystem path:

```
project.upload("filename.txt", filedatal="Raw data")
```

Upload a file and comment on an issue using the uploaded file's markdown:

```
uploaded_file = project.upload("filename.txt", filedatal="data")
issue = project.issues.get(issue_id)
issue.notes.create({
    "body": "See the attached file: {}".format(uploaded_file["markdown"])
})
```

Upload a file and comment on an issue while using custom markdown to reference the uploaded file:

```
uploaded_file = project.upload("filename.txt", filedatal="data")
issue = project.issues.get(issue_id)
issue.notes.create({
    "body": "See the [attached file]({})".format(uploaded_file["url"])
})
```

Project push rules

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectPushRules`
 - `gitlab.v4.objects.ProjectPushRulesManager`
 - `gitlab.v4.objects.Project.pushrules`
- GitLab API: <https://docs.gitlab.com/ee/api/projects.html#push-rules>

Examples

Create project push rules (at least one rule is necessary):

```
project.pushrules.create({'deny_delete_tag': True})
```

Get project push rules:

```
pr = project.pushrules.get()
```

Edit project push rules:

```
pr.branch_name_regex = '^(\main|develop|support-\d+|release-\d+\.\.+|hotfix-\.\.+|feature-\.\.+)$'  
pr.save()
```

Delete project push rules:

```
pr.delete()
```

Project protected tags

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectProtectedTag`
 - `gitlab.v4.objects.ProjectProtectedTagManager`
 - `gitlab.v4.objects.Project.protectedtags`
- GitLab API: https://docs.gitlab.com/ce/api/protected_tags.html

Examples

Get a list of protected tags from a project:

```
protected_tags = project.protectedtags.list()
```

Get a single protected tag or wildcard protected tag:

```
protected_tag = project.protectedtags.get('v*')
```

Protect a single repository tag or several project repository tags using a wildcard protected tag:

```
project.protectedtags.create({'name': 'v*', 'create_access_level': '40'})
```

Unprotect the given protected tag or wildcard protected tag.:

```
protected_tag.delete()
```

Additional project statistics

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectAdditionalStatistics`
 - `gitlab.v4.objects.ProjectAdditionalStatisticsManager`
 - `gitlab.v4.objects.Project.additionalstatistics`
- GitLab API: https://docs.gitlab.com/ce/api/project_statistics.html

Examples

Get all additional statistics of a project:

```
statistics = project.additionalstatistics.get()
```

Get total fetches in last 30 days of a project:

```
total_fetches = project.additionalstatistics.get().fetches['total']
```

Project storage

This endpoint requires admin access.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectStorage`
 - `gitlab.v4.objects.ProjectStorageManager`
 - `gitlab.v4.objects.Project.storage`
- GitLab API: <https://docs.gitlab.com/ee/api/projects.html#get-the-path-to-repository-storage>

Examples

Get the repository storage details for a project:

```
storage = project.storage.get()
```

Get the repository storage disk path:

```
disk_path = project.storage.get().disk_path
```

7.5.40 Project Access Tokens

Get a list of project access tokens

References

- v4 API:
 - `gitlab.v4.objects.ProjectAccessToken`
 - `gitlab.v4.objects.ProjectAccessTokenManager`
 - `gitlab.Gitlab.project_access_tokens`
- GitLab API: https://docs.gitlab.com/ee/api/project_access_tokens.html

Examples

List project access tokens:

```
access_tokens = gl.projects.get(1, lazy=True).access_tokens.list()  
print(access_tokens[0].name)
```

Create project access token:

```
access_token = gl.projects.get(1).access_tokens.create({"name": "test", "scopes": ["api  
←"]})
```

Revoke a project access tokens:

```
gl.projects.get(1).access_tokens.delete(42)  
# or  
access_token.delete()
```

7.5.41 Protected branches

You can define a list of protected branch names on a repository. Names can use wildcards (*).

References

- v4 API:
 - `gitlab.v4.objects.ProjectProtectedBranch`
 - `gitlab.v4.objects.ProjectProtectedBranchManager`
 - `gitlab.v4.objects.Project.protectedbranches`
- GitLab API: https://docs.gitlab.com/ce/api/protected_branches.html#protected-branches-api

Examples

Get the list of protected branches for a project:

```
p_branches = project.protectedbranches.list()
```

Get a single protected branch:

```
p_branch = project.protectedbranches.get('main')
```

Create a protected branch:

```
p_branch = project.protectedbranches.create({
    'name': '*-stable',
    'merge_access_level': gitlab.const.AccessLevel.DEVELOPER,
    'push_access_level': gitlab.const.AccessLevel.MAINTAINER
})
```

Create a protected branch with more granular access control:

```
p_branch = project.protectedbranches.create({
    'name': '*-stable',
    'allowed_to_push': [{"user_id": 99}, {"user_id": 98}],
    'allowed_to_merge': [{"group_id": 653}],
    'allowed_to_unprotect': [{"access_level": gitlab.const.AccessLevel.MAINTAINER}]
})
```

Delete a protected branch:

```
project.protectedbranches.delete('*-stable')
# or
p_branch.delete()
```

7.5.42 Protected environments

You can list and manage protected environments in a project.

References

- v4 API:
 - [gitlab.v4.objects.ProjectProtectedEnvironment](#)
 - [gitlab.v4.objects.ProjectProtectedEnvironmentManager](#)
 - [gitlab.v4.objects.Project.protected_environment](#)
- GitLab API: https://docs.gitlab.com/ee/api/protected_environments.html

Examples

Get the list of protected environments for a project:

```
p_environments = project.protected_environments.list()
```

Get a single protected environment:

```
p_environment = project.protected_environments.get('production')
```

Protect an existing environment:

```
p_environment = project.protected_environments.create(  
    {  
        'name': 'production',  
        'deploy_access_levels': [  
            {'access_level': 40}  
        ],  
    }  
)
```

Unprotect a protected environment:

```
p_environment = project.protected_environments.delete('production')  
# or  
p_environment.delete()
```

7.5.43 Releases

Project releases

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectRelease`
 - `gitlab.v4.objects.ProjectReleaseManager`
 - `gitlab.v4.objects.Project.releases`
- Gitlab API: <https://docs.gitlab.com/ee/api/releases/index.html>

Examples

Get a list of releases from a project:

```
project = gl.projects.get(project_id, lazy=True)  
release = project.releases.list()
```

Get a single release:

```
release = project.releases.get('v1.2.3')
```

Edit a release:

```
release.name = "Demo Release"
release.description = "release notes go here"
release.save()
```

Create a release for a project tag:

```
release = project.releases.create({'name':'Demo Release', 'tag_name':'v1.2.3',
                                   'description':'release notes go here'})
```

Delete a release:

```
# via its tag name from project attributes
release = project.releases.delete('v1.2.3')

# delete object directly
release.delete()
```

Note: The Releases API is one of the few working with CI_JOB_TOKEN, but the project can't be fetched with the token. Thus use *lazy* for the project as in the above example.

Also be aware that most of the capabilities of the endpoint were not accessible with CI_JOB_TOKEN until Gitlab version 14.5.

Project release links

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectReleaseLink`
 - `gitlab.v4.objects.ProjectReleaseLinkManager`
 - `gitlab.v4.objects.ProjectRelease.links`
- Gitlab API: <https://docs.gitlab.com/ee/api/releases/links.html>

Examples

Get a list of releases from a project:

```
links = release.links.list()
```

Get a single release link:

```
link = release.links.get(1)
```

Create a release link for a release:

```
link = release.links.create({"url": "https://example.com/asset", "name": "asset"})
```

Delete a release link:

```
# via its ID from release attributes
release.links.delete(1)

# delete object directly
link.delete()
```

7.5.44 Runners

Runners are external processes used to run CI jobs. They are deployed by the administrator and registered to the GitLab instance.

Shared runners are available for all projects. Specific runners are enabled for a list of projects.

Global runners (admin)

Reference

- v4 API:
 - `gitlab.v4.objects.Runner`
 - `gitlab.v4.objects.RunnerManager`
 - `gitlab.Gitlab.runners`
 - `gitlab.v4.objects.RunnerAll`
 - `gitlab.v4.objects.RunnerAllManager`
 - `gitlab.Gitlab.runners_all`
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

Examples

Use the `runners.list()` and `runners_all.list()` methods to list runners. `runners.list()` - Get a list of specific runners available to the user `runners_all.list()` - Get a list of all runners in the GitLab instance (specific and shared). Access is restricted to users with administrator access.

Both methods accept a `scope` parameter to filter the list. Allowed values for this parameter are:

- `active`
- `paused`
- `online`
- `specific` (`runners_all.list()` only)
- `shared` (`runners_all.list()` only)

Note: The returned objects hold minimal information about the runners. Use the `get()` method to retrieve detail about a runner.

Runners returned via `runners_all.list()` also cannot be manipulated directly. You will need to use the `get()` method to create an editable object.

```
# List owned runners
runners = gl.runners.list()

# List owned runners with a filter
runners = gl.runners.list(scope='active')

# List all runners in the GitLab instance (specific and shared), using a filter
runners = gl.runners_all.list(scope='paused')
```

Get a runner's detail:

```
runner = gl.runners.get(runner_id)
```

Register a new runner:

```
runner = gl.runners.create({'token': secret_token})
```

Update a runner:

```
runner = gl.runners.get(runner_id)
runner.tag_list.append('new_tag')
runner.save()
```

Remove a runner:

```
gl.runners.delete(runner_id)
# or
runner.delete()
```

Remove a runner by its authentication token:

```
gl.runners.delete(token="runner-auth-token")
```

Verify a registered runner token:

```
try:
    gl.runners.verify(runner_token)
    print("Valid token")
except GitlabVerifyError:
    print("Invalid token")
```

Project/Group runners

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectRunner`
 - `gitlab.v4.objects.ProjectRunnerManager`
 - `gitlab.v4.objects.Project.runners`
 - `gitlab.v4.objects.GroupRunner`
 - `gitlab.v4.objects.GroupRunnerManager`

- *gitlab.v4.objects.Group.runners*
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

Examples

List the runners for a project:

```
runners = project.runners.list()
```

Enable a specific runner for a project:

```
p_runner = project.runners.create({'runner_id': runner.id})
```

Disable a specific runner for a project:

```
project.runners.delete(runner.id)
```

Runner jobs

Reference

- v4 API:
 - *gitlab.v4.objects.RunnerJob*
 - *gitlab.v4.objects.RunnerJobManager*
 - *gitlab.v4.objects.Runner.jobs*
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

Examples

List for jobs for a runner:

```
jobs = runner.jobs.list()
```

Filter the list using the jobs status:

```
# status can be 'running', 'success', 'failed' or 'canceled'  
active_jobs = runner.jobs.list(status='running')
```

7.5.45 Project Remote Mirrors

Remote Mirrors allow you to set up push mirroring for a project.

References

- v4 API:
 - `gitlab.v4.objects.ProjectRemoteMirror`
 - `gitlab.v4.objects.ProjectRemoteMirrorManager`
 - `gitlab.v4.objects.Project.remote_mirrors`
- GitLab API: https://docs.gitlab.com/ce/api/remote_mirrors.html

Examples

Get the list of a project's remote mirrors:

```
mirrors = project.remote_mirrors.list()
```

Create (and enable) a remote mirror for a project:

```
mirror = project.remote_mirrors.create({'url': 'https://gitlab.com/example.git',
                                         'enabled': True})
```

Update an existing remote mirror's attributes:

```
mirror.enabled = False
mirror.only_protected_branches = True
mirror.save()
```

7.5.46 Registry Repositories

References

- v4 API:
 - `gitlab.v4.objects.ProjectRegistryRepository`
 - `gitlab.v4.objects.ProjectRegistryRepositoryManager`
 - `gitlab.v4.objects.Project.repositories`
- GitLab API: https://docs.gitlab.com/ce/api/container_registry.html

Examples

Get the list of container registry repositories associated with the project:

```
repositories = project.repositories.list()
```

Get the list of all project container registry repositories in a group:

```
repositories = group.registry_repositories.list()
```

Delete repository:

```
project.repositories.delete(id=x)
# or
repository = repositories.pop()
repository.delete()
```

7.5.47 Registry Repository Tags

References

- v4 API:
 - `gitlab.v4.objects.ProjectRegistryTag`
 - `gitlab.v4.objects.ProjectRegistryTagManager`
 - `gitlab.v4.objects.Repository.tags`
- Gitlab API: https://docs.gitlab.com/ce/api/container_registry.html

Examples

Get the list of repository tags in given registry:

```
repositories = project.repositories.list()
repository = repositories.pop()
tags = repository.tags.list()
```

Get specific tag:

```
repository.tags.get(id=tag_name)
```

Delete tag:

```
repository.tags.delete(id=tag_name)
# or
tag = repository.tags.get(id=tag_name)
tag.delete()
```

Delete tag in bulk:

```
repository.tags.delete_in_bulk(keep_n=1)
# or
repository.tags.delete_in_bulk(older_than="1m")
# or
repository.tags.delete_in_bulk(name_regex="v.+", keep_n=2)
```

Note: Delete in bulk is asynchronous operation and may take a while. Refer to: https://docs.gitlab.com/ce/api/container_registry.html#delete-repository-tags-in-bulk

7.5.48 Resource Groups

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectResourceGroup`
 - `gitlab.v4.objects.ProjectResourceGroupManager`
 - `gitlab.v4.objects.Project.resource_groups`
 - `gitlab.v4.objects.ProjectResourceGroupUpcomingJob`
 - `gitlab.v4.objects.ProjectResourceGroupUpcomingJobManager`
 - `gitlab.v4.objects.ProjectResourceGroup.upcoming_jobs`
- Gitlab API: https://docs.gitlab.com/ee/api/resource_groups.html

Examples

List resource groups for a project:

```
project = gl.projects.get(project_id, lazy=True)
resource_group = project.resource_groups.list()
```

Get a single resource group:

```
resource_group = project.resource_groups.get("production")
```

Edit a resource group:

```
resource_group.process_mode = "oldest_first"
resource_group.save()
```

List upcoming jobs for a resource group:

```
upcoming_jobs = resource_group.upcoming_jobs.list()
```

7.5.49 Search API

You can search for resources at the top level, in a project or in a group. Searches are based on a scope (issues, merge requests, and so on) and a search string. The following constants are provided to represent the possible scopes:

- Shared scopes (global, group and project):
 - `gitlab.const.SearchScope.PROJECTS`: projects
 - `gitlab.const.SearchScope.ISSUES`: issues
 - `gitlab.const.SearchScope.MERGE_REQUESTS`: merge_requests
 - `gitlab.const.SearchScope.MILESTONES`: milestones
 - `gitlab.const.SearchScope.WIKI_BLOBS`: wiki_blobs
 - `gitlab.const.SearchScope.COMMITS`: commits
 - `gitlab.const.SearchScope.BLOBS`: blobs

- `gitlab.const.SearchScope.USERS`: users
- specific global scope:
 - `gitlab.const.SearchScope.GLOBAL_SNIPPET_TITLES`: `snippet_titles`
- specific project scope:
 - `gitlab.const.SearchScope.PROJECT_NOTES`: `notes`

Reference

- v4 API:
 - `gitlab.Gitlab.search`
 - `gitlab.v4.objects.Group.search`
 - `gitlab.v4.objects.Project.search`
- GitLab API: <https://docs.gitlab.com/ce/api/search.html>

Examples

Search for issues matching a specific string:

```
# global search
gl.search(gitlab.const.SearchScope.ISSUES, 'regression')

# group search
group = gl.groups.get('mygroup')
group.search(gitlab.const.SearchScope.ISSUES, 'regression')

# project search
project = gl.projects.get('myproject')
project.search(gitlab.const.SearchScope.ISSUES, 'regression')
```

The `search()` methods implement the pagination support:

```
# get lists of 10 items, and start at page 2
gl.search(gitlab.const.SearchScope.ISSUES, search_str, page=2, per_page=10)

# get a generator that will automatically make required API calls for
# pagination
for item in gl.search(gitlab.const.SearchScope.ISSUES, search_str, iterator=True):
    do_something(item)
```

The search API doesn't return objects, but dicts. If you need to act on objects, you need to create them explicitly:

```
for item in gl.search(gitlab.const.SearchScope.ISSUES, search_str, iterator=True):
    issue_project = gl.projects.get(item['project_id'], lazy=True)
    issue = issue_project.issues.get(item['iid'])
    issue.state = 'closed'
    issue.save()
```

7.5.50 Secure Files

secure files

References

- v4 API:
 - `gitlab.v4.objects.ProjectSecureFile`
 - `gitlab.v4.objects.ProjectSecureFileManager`
 - `gitlab.v4.objects.Project.secure_files`
- GitLab API: https://docs.gitlab.com/ee/api/secure_files.html

Examples

Get a project secure file:

```
secure_files = gl.projects.get(1, lazy=True).secure_files.get(1)
print(secure_files.name)
```

List project secure files:

```
secure_files = gl.projects.get(1, lazy=True).secure_files.list()
print(secure_files[0].name)
```

Create project secure file:

```
secure_file = gl.projects.get(1).secure_files.create({"name": "test", "file": "secure.txt"})
```

Download a project secure file:

```
content = secure_file.download()
print(content)
with open("/tmp/secure.txt", "wb") as f:
    secure_file.download(streamed=True, action=f.write)
```

Remove a project secure file:

```
gl.projects.get(1).secure_files.delete(1)
# or
secure_file.delete()
```

7.5.51 Settings

Reference

- v4 API:
 - `gitlab.v4.objects.ApplicationSettings`
 - `gitlab.v4.objects.ApplicationSettingsManager`
 - `gitlab.Gitlab.settings`
- GitLab API: <https://docs.gitlab.com/ce/api/settings.html>

Examples

Get the settings:

```
settings = gl.settings.get()
```

Update the settings:

```
settings.signin_enabled = False  
settings.save()
```

7.5.52 Snippets

Reference

- v4 API:
 - `gitlab.v4.objects.Snippet`
 - `gitlab.v4.objects.SnippetManager`
 - `gitlab.Gitlab.snippets`
- GitLab API: <https://docs.gitlab.com/ce/api/snippets.html>

Examples

List snippets owned by the current user:

```
snippets = gl.snippets.list()
```

List the public snippets:

```
public_snippets = gl.snippets.public()
```

Get a snippet:

```
snippet = gl.snippets.get(snippet_id)  
# get the content  
content = snippet.content()
```

Warning: Blobs are entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Create a snippet:

```
snippet = gl.snippets.create({'title': 'snippet1',
                             'file_name': 'snippet1.py',
                             'content': open('snippet1.py').read()})
```

Update the snippet attributes:

```
snippet.visibility_level = gitlab.const.Visibility.PUBLIC
snippet.save()
```

To update a snippet code you need to create a ProjectSnippet object:

```
snippet = gl.snippets.get(snippet_id)
project = gl.projects.get(snippet.project_id, lazy=True)
editable_snippet = project.snippets.get(snippet.id)
editable_snippet.code = new_snippet_content
editable_snippet.save()
```

Delete a snippet:

```
gl.snippets.delete(snippet_id)
# or
snippet.delete()
```

Get user agent detail (admin only):

```
detail = snippet.user_agent_detail()
```

7.5.53 Statistics

Reference

- v4 API:
 - [gitlab.v4.objects.ApplicationStatistics](#)
 - [gitlab.v4.objects.ApplicationStatisticsManager](#)
 - [gitlab.Gitlab.statistics](#)
- GitLab API: <https://docs.gitlab.com/ee/api/statistics.html>

Examples

Get the statistics:

```
statistics = gl.statistics.get()
```

7.5.54 System hooks

Reference

- v4 API:
 - `gitlab.v4.objects.Hook`
 - `gitlab.v4.objects.HookManager`
 - `gitlab.Gitlab.hooks`
- GitLab API: https://docs.gitlab.com/ce/api/system_hooks.html

Examples

List the system hooks:

```
hooks = gl.hooks.list()
```

Create a system hook:

```
gl.hooks.get(hook_id)
```

Test a system hook. The returned object is not usable (it misses the hook ID):

```
hook = gl.hooks.create({'url': 'http://your.target.url'})
```

Delete a system hook:

```
gl.hooks.delete(hook_id)  
# or  
hook.delete()
```

7.5.55 Templates

You can request templates for different type of files:

- License files
- .gitignore files
- GitLab CI configuration files
- Dockerfiles

License templates

Reference

- v4 API:
 - `gitlab.v4.objects.License`
 - `gitlab.v4.objects.LicenseManager`
 - `gitlab.Gitlab.licenses`
- GitLab API: <https://docs.gitlab.com/ce/api/templates/licenses.html>

Examples

List known license templates:

```
licenses = gl.licenses.list()
```

Generate a license content for a project:

```
license = gl.licenses.get('apache-2.0', project='foobar', fullname='John Doe')
print(license.content)
```

.gitignore templates

Reference

- v4 API:
 - `gitlab.v4.objects.Gitignore`
 - `gitlab.v4.objects.GitignoreManager`
 - `gitlab.Gitlab.gitignores`
- GitLab API: <https://docs.gitlab.com/ce/api/templates/gitignores.html>

Examples

List known gitignore templates:

```
gitignores = gl.gitignores.list()
```

Get a gitignore template:

```
gitignore = gl.gitignores.get('Python')
print(gitignore.content)
```

GitLab CI templates

Reference

- v4 API:
 - `gitlab.v4.objects.Gitlabciyml`
 - `gitlab.v4.objects.GitlabciymlManager`
 - `gitlab.Gitlab.gitlabciymls`
- GitLab API: https://docs.gitlab.com/ce/api/templates/gitlab_ci_ymls.html

Examples

List known GitLab CI templates:

```
gitlabciymls = gl.gitlabciymls.list()
```

Get a GitLab CI template:

```
gitlabciyml = gl.gitlabciymls.get('Pelican')
print(gitlabciyml.content)
```

Dockerfile templates

Reference

- v4 API:
 - `gitlab.v4.objects.Dockerfile`
 - `gitlab.v4.objects.DockerfileManager`
 - `gitlab.Gitlab.gitlabciymls`
- GitLab API: Not documented.

Examples

List known Dockerfile templates:

```
dockerfiles = gl.dockerfiles.list()
```

Get a Dockerfile template:

```
dockerfile = gl.dockerfiles.get('Python')
print(dockerfile.content)
```

7.5.56 Todos

Reference

- v4 API:
 - Todo
 - TodoManager
 - `gitlab.Gitlab.todos`
- GitLab API: <https://docs.gitlab.com/ce/api/todos.html>

Examples

List active todos:

```
todos = gl.todos.list()
```

You can filter the list using the following parameters:

- `action`: can be assigned, mentioned, build_failed, marked, or approval_required
- `author_id`
- `project_id`
- `state`: can be pending or done
- `type`: can be Issue or MergeRequest

For example:

```
todos = gl.todos.list(project_id=1)
todos = gl.todos.list(state='done', type='Issue')
```

Mark a todo as done:

```
todos = gl.todos.list(project_id=1)
todos[0].mark_as_done()
```

Mark all the todos as done:

```
gl.todos.mark_all_as_done()
```

7.5.57 Topics

Topics can be used to categorize projects and find similar new projects.

Reference

- v4 API:
 - `gitlab.v4.objects.Topic`
 - `gitlab.v4.objects.TopicManager`
 - `gitlab.Gitlab.topics`
- GitLab API: <https://docs.gitlab.com/ce/api/topics.html>

This endpoint requires admin access for creating, updating and deleting objects.

Examples

List project topics on the GitLab instance:

```
topics = gl.topics.list()
```

Get a specific topic by its ID:

```
topic = gl.topics.get(topic_id)
```

Create a new topic:

```
topic = gl.topics.create({"name": "my-topic", "title": "my title"})
```

Update a topic:

```
topic.description = "My new topic"  
topic.save()  
  
# or  
gl.topics.update(topic_id, {"description": "My new topic"})
```

Delete a topic:

```
topic.delete()  
  
# or  
gl.topics.delete(topic_id)
```

Merge a source topic into a target topic:

```
gl.topics.merge(topic_id, target_topic_id)
```

7.5.58 Users and current user

The Gitlab API exposes user-related method that can be manipulated by admins only.

The currently logged-in user is also exposed.

Users

References

- v4 API:
 - `gitlab.v4.objects.User`
 - `gitlab.v4.objects.UserManager`
 - `gitlab.Gitlab.users`
- GitLab API:
 - <https://docs.gitlab.com/ce/api/users.html>
 - <https://docs.gitlab.com/ee/api/projects.html#list-projects-starred-by-a-user>

Examples

Get the list of users:

```
users = gl.users.list()
```

Search users whose username match a given string:

```
users = gl.users.list(search='foo')
```

Get a single user:

```
# by ID
user = gl.users.get(user_id)
# by username
user = gl.users.list(username='root')[0]
```

Create a user:

```
user = gl.users.create({'email': 'john@doe.com',
                       'password': 's3cur3s3cr3T',
                       'username': 'jdoe',
                       'name': 'John Doe'})
```

Update a user:

```
user.name = 'Real Name'
user.save()
```

Delete a user:

```
gl.users.delete(user_id)
# or
user.delete()
```

Block/Unblock a user:

```
user.block()
user.unblock()
```

Activate/Deactivate a user:

```
user.activate()
user.deactivate()
```

Ban/Unban a user:

```
user.ban()
user.unban()
```

Follow/Unfollow a user:

```
user.follow()
user.unfollow()
```

Set the avatar image for a user:

```
# the avatar image can be passed as data (content of the file) or as a file
# object opened in binary mode
user.avatar = open('path/to/file.png', 'rb')
user.save()
```

Set an external identity for a user:

```
user.provider = 'oauth2_generic'
user.extern_uid = '3'
user.save()
```

Delete an external identity by provider name:

```
user.identityproviders.delete('oauth2_generic')
```

Get the followers of a user

```
user.followers_users.list()
```

Get the followings of a user

```
user.following_users.list()
```

List a user's starred projects

```
user.starred_projects.list()
```

If the GitLab instance has new user account approval enabled some users may have `user.state == 'blocked_pending_approval'`. Administrators can approve and reject such users:

```
user.approve()
user.reject()
```

User custom attributes

References

- v4 API:
 - `gitlab.v4.objects.UserCustomAttribute`
 - `gitlab.v4.objects.UserCustomAttributeManager`
 - `gitlab.v4.objects.User.customattributes`
- GitLab API: https://docs.gitlab.com/ce/api/custom_attributes.html

Examples

List custom attributes for a user:

```
attrs = user.customattributes.list()
```

Get a custom attribute for a user:

```
attr = user.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a user:

```
attr = user.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a user:

```
attr.delete()  
# or  
user.customattributes.delete(attr_key)
```

Search users by custom attribute:

```
user.customattributes.set('role', 'QA')  
gl.users.list(custom_attributes={'role': 'QA'})
```

User impersonation tokens

References

- v4 API:
 - `gitlab.v4.objects.UserImpersonationToken`
 - `gitlab.v4.objects.UserImpersonationTokenManager`
 - `gitlab.v4.objects.User.impersonationtokens`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#get-all-impersonation-tokens-of-a-user>

List impersonation tokens for a user:

```
i_t = user.impersonationtokens.list(state='active')
i_t = user.impersonationtokens.list(state='inactive')
```

Get an impersonation token for a user:

```
i_t = user.impersonationtokens.get(i_t_id)
```

Create and use an impersonation token for a user:

```
i_t = user.impersonationtokens.create({'name': 'token1', 'scopes': ['api']})
# use the token to create a new gitlab connection
user_gl = gitlab.Gitlab(gitlab_url, private_token=i_t.token)
```

Revoke (delete) an impersonation token for a user:

```
i_t.delete()
```

User projects

References

- v4 API:
 - `gitlab.v4.objects.UserProject`
 - `gitlab.v4.objects.UserProjectManager`
 - `gitlab.v4.objects.User.projects`
- GitLab API: <https://docs.gitlab.com/ee/api/projects.html#list-user-projects>

List visible projects in the user's namespace:

```
projects = user.projects.list()
```

Note: Only the projects in the user's namespace are returned. Projects owned by the user in any group or subgroups are not returned. An empty list is returned if a profile is set to private.

User memberships

References

- v4 API:
 - `gitlab.v4.objects.UserMembership`
 - `gitlab.v4.objects.UserMembershipManager`
 - `gitlab.v4.objects.User.memberships`
- GitLab API: <https://docs.gitlab.com/ee/api/users.html#user-memberships>

List direct memberships for a user:

```
memberships = user.memberships.list()
```

List only direct project memberships:

```
memberships = user.memberships.list(type='Project')
```

List only direct group memberships:

```
memberships = user.memberships.list(type='Namespace')
```

Note: This endpoint requires admin access.

Current User

References

- v4 API:
 - *gitlab.v4.objects.CurrentUser*
 - *gitlab.v4.objects.CurrentUserManager*
 - *gitlab.Gitlab.user*
- GitLab API: <https://docs.gitlab.com/ce/api/users.html>

Examples

Get the current user:

```
gl.auth()
current_user = gl.user
```

GPG keys

References

You can manipulate GPG keys for the current user and for the other users if you are admin.

- v4 API:
 - *gitlab.v4.objects.CurrentUserGPGKey*
 - *gitlab.v4.objects.CurrentUserGPGKeyManager*
 - *gitlab.v4.objects.CurrentUser.gpgkeys*
 - *gitlab.v4.objects.UserGPGKey*
 - *gitlab.v4.objects.UserGPGKeyManager*
 - *gitlab.v4.objects.User.gpgkeys*
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-all-gpg-keys>

Examples

List GPG keys for a user:

```
gpgkeys = user.gpgkeys.list()
```

Get a GPG gpgkey for a user:

```
gpgkey = user.gpgkeys.get(key_id)
```

Create a GPG gpgkey for a user:

```
# get the key with `gpg --export -a GPG_KEY_ID`
k = user.gpgkeys.create({'key': public_key_content})
```

Delete a GPG gpgkey for a user:

```
user.gpgkeys.delete(key_id)
# or
gpgkey.delete()
```

SSH keys

References

You can manipulate SSH keys for the current user and for the other users if you are admin.

- v4 API:
 - `gitlab.v4.objects.CurrentUserKey`
 - `gitlab.v4.objects.CurrentUserKeyManager`
 - `gitlab.v4.objects.CurrentUser.keys`
 - `gitlab.v4.objects.UserKey`
 - `gitlab.v4.objects.UserKeyManager`
 - `gitlab.v4.objects.User.keys`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-ssh-keys>

Examples

List SSH keys for a user:

```
keys = user.keys.list()
```

Create an SSH key for a user:

```
key = user.keys.create({'title': 'my_key',
                       'key': open('/home/me/.ssh/id_rsa.pub').read()})
```

Get an SSH key for a user by id:

```
key = user.keys.get(key_id)
```

Delete an SSH key for a user:

```
user.keys.delete(key_id)
# or
key.delete()
```

Status

References

You can manipulate the status for the current user and you can read the status of other users.

- v4 API:
 - `gitlab.v4.objects.CurrentUserStatus`
 - `gitlab.v4.objects.CurrentUserStatusManager`
 - `gitlab.v4.objects.CurrentUser.status`
 - `gitlab.v4.objects.UserStatus`
 - `gitlab.v4.objects.UserStatusManager`
 - `gitlab.v4.objects.User.status`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#user-status>

Examples

Get current user status:

```
status = user.status.get()
```

Update the status for the current user:

```
status = user.status.get()
status.message = "message"
status.emoji = "thumbsup"
status.save()
```

Get the status of other users:

```
gl.users.get(1).status.get()
```

Emails

References

You can manipulate emails for the current user and for the other users if you are admin.

- v4 API:
 - `gitlab.v4.objects.CurrentUserEmail`
 - `gitlab.v4.objects.CurrentUserEmailManager`
 - `gitlab.v4.objects.CurrentUser.emails`
 - `gitlab.v4.objects.UserEmail`
 - `gitlab.v4.objects.UserEmailManager`
 - `gitlab.v4.objects.User.emails`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-emails>

Examples

List emails for a user:

```
emails = user.emails.list()
```

Get an email for a user:

```
email = user.emails.get(email_id)
```

Create an email for a user:

```
k = user.emails.create({'email': 'foo@bar.com'})
```

Delete an email for a user:

```
user.emails.delete(email_id)
# or
email.delete()
```

Users activities

References

- admin only
- v4 API:
 - `gitlab.v4.objects.UserActivities`
 - `gitlab.v4.objects.UserActivitiesManager`
 - `gitlab.Gitlab.user_activities`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#get-user-activities-admin-only>

Examples

Get the users activities:

```
activities = gl.user_activities.list(
    query_parameters={'from': '2018-07-01'},
    get_all=True,
)
```

7.5.59 CI/CD Variables

You can configure variables at the instance-level (admin only), or associate variables to projects and groups, to modify pipeline/job scripts behavior.

Warning: Please always follow GitLab's [rules for CI/CD variables](#), especially for values in masked variables. If you do not, your variables may silently fail to save.

Instance-level variables

This endpoint requires admin access.

Reference

- v4 API
 - `gitlab.v4.objects.Variable`
 - `gitlab.v4.objects.VariableManager`
 - `gitlab.Gitlab.variables`
- GitLab API
 - https://docs.gitlab.com/ce/api/instance_level_ci_variables.html

Examples

List all instance variables:

```
variables = gl.variables.list()
```

Get an instance variable by key:

```
variable = gl.variables.get('key_name')
```

Create an instance variable:

```
variable = gl.variables.create({'key': 'key1', 'value': 'value1'})
```

Update a variable value:

```
variable.value = 'new_value'  
variable.save()
```

Remove a variable:

```
gl.variables.delete('key_name')  
# or  
variable.delete()
```

Projects and groups variables

Reference

- v4 API
 - `gitlab.v4.objects.ProjectVariable`
 - `gitlab.v4.objects.ProjectVariableManager`
 - `gitlab.v4.objects.Project.variables`
 - `gitlab.v4.objects.GroupVariable`
 - `gitlab.v4.objects.GroupVariableManager`
 - `gitlab.v4.objects.Group.variables`
- GitLab API
 - https://docs.gitlab.com/ce/api/instance_level_ci_variables.html
 - https://docs.gitlab.com/ce/api/project_level_variables.html
 - https://docs.gitlab.com/ce/api/group_level_variables.html

Examples

List variables:

```
p_variables = project.variables.list()  
g_variables = group.variables.list()
```

Get a variable:

```
p_var = project.variables.get('key_name')  
g_var = group.variables.get('key_name')
```

Create a variable:

```
var = project.variables.create({'key': 'key1', 'value': 'value1'})  
var = group.variables.create({'key': 'key1', 'value': 'value1'})
```

Update a variable value:

```
var.value = 'new_value'
var.save()
# or
project.variables.update("key1", {"value": "new_value"})
```

Remove a variable:

```
project.variables.delete('key_name')
group.variables.delete('key_name')
# or
var.delete()
```

7.5.60 Sidekiq metrics

Reference

- v4 API:
 - *gitlab.v4.objects.SidekiqManager*
 - *gitlab.Gitlab.sidekiq*
- GitLab API: https://docs.gitlab.com/ce/api/sidekiq_metrics.html

Examples

```
gl.sidekiq.queue_metrics()
gl.sidekiq.process_metrics()
gl.sidekiq.job_stats()
gl.sidekiq.compound_metrics()
```

7.5.61 Wiki pages

References

- v4 API:
 - *gitlab.v4.objects.ProjectWiki*
 - *gitlab.v4.objects.ProjectWikiManager*
 - *gitlab.v4.objects.Project.wikis*
 - *gitlab.v4.objects.GroupWiki*
 - *gitlab.v4.objects.GroupWikiManager*
 - *gitlab.v4.objects.Group.wikis*
- GitLab API for Projects: <https://docs.gitlab.com/ce/api/wikis.html>
- GitLab API for Groups: https://docs.gitlab.com/ee/api/group_wikis.html

Examples

Get the list of wiki pages for a project. These do not contain the contents of the wiki page. You will need to call `get(slug)` to retrieve the content by accessing the `content` attribute:

```
pages = project.wikis.list()
```

Get the list of wiki pages for a group. These do not contain the contents of the wiki page. You will need to call `get(slug)` to retrieve the content by accessing the `content` attribute:

```
pages = group.wikis.list()
```

Get a single wiki page for a project:

```
page = project.wikis.get(page_slug)
```

Get a single wiki page for a group:

```
page = group.wikis.get(page_slug)
```

Get the contents of a wiki page:

```
print(page.content)
```

Create a wiki page on a project level:

```
page = project.wikis.create({'title': 'Wiki Page 1',
                             'content': open(a_file).read()})
```

Update a wiki page:

```
page.content = 'My new content'
page.save()
```

Delete a wiki page:

```
page.delete()
```

7.5.62 Clusters (DEPRECATED)

Warning: Cluster support was deprecated in GitLab 14.5 and disabled by default as of GitLab 15.0

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCluster`
 - `gitlab.v4.objects.ProjectClusterManager`
 - `gitlab.v4.objects.Project.clusters`
 - `gitlab.v4.objects.GroupCluster`

- `gitlab.v4.objects.GroupClusterManager`
- `gitlab.v4.objects.Group.clusters`
- GitLab API: https://docs.gitlab.com/ee/api/project_clusters.html
- GitLab API: https://docs.gitlab.com/ee/api/group_clusters.html

Examples

List clusters for a project:

```
clusters = project.clusters.list()
```

Create an cluster for a project:

```
cluster = project.clusters.create(
{
    "name": "cluster1",
    "platform_kubernetes_attributes": {
        "api_url": "http://url",
        "token": "tokenval",
    },
})
```

Retrieve a specific cluster for a project:

```
cluster = project.clusters.get(cluster_id)
```

Update an cluster for a project:

```
cluster.platform_kubernetes_attributes = {"api_url": "http://newurl"}
cluster.save()
```

Delete an cluster for a project:

```
cluster = project.clusters.delete(cluster_id)
# or
cluster.delete()
```

List clusters for a group:

```
clusters = group.clusters.list()
```

Create an cluster for a group:

```
cluster = group.clusters.create(
{
    "name": "cluster1",
    "platform_kubernetes_attributes": {
        "api_url": "http://url",
        "token": "tokenval",
    },
})
```

Retrieve a specific cluster for a group:

```
cluster = group.clusters.get(cluster_id)
```

Update an cluster for a group:

```
cluster.platform_kubernetes_attributes = {"api_url": "http://newurl"}  
cluster.save()
```

Delete an cluster for a group:

```
cluster = group.clusters.delete(cluster_id)  
# or  
cluster.delete()
```

7.6 API reference (gitlab package)

7.6.1 Module contents

Wrapper for the GitLab API.

```
class gitlab.Gitlab(url: Optional[str] = None, private_token: Optional[str] = None, oauth_token:  
Optional[str] = None, job_token: Optional[str] = None, ssl_verify: Union[bool, str] =  
True, http_username: Optional[str] = None, http_password: Optional[str] = None,  
timeout: Optional[float] = None, api_version: str = '4', per_page: Optional[int] = None,  
pagination: Optional[str] = None, order_by: Optional[str] = None, user_agent: str =  
'python-gitlab/3.14.0', retry_transient_errors: bool = False, keep_base_url: bool = False,  
**kwargs: Any)
```

Bases: `object`

Represents a GitLab server connection.

Parameters

- **url** (`Optional[str]`) – The URL of the GitLab server (defaults to <https://gitlab.com>).
- **private_token** (`Optional[str]`) – The user private token
- **oauth_token** (`Optional[str]`) – An oauth token
- **job_token** (`Optional[str]`) – A CI job token
- **ssl_verify** (`Union[bool, str]`) – Whether SSL certificates should be validated. If the value is a string, it is the path to a CA file used for certificate validation.
- **timeout** (`Optional[float]`) – Timeout to use for requests to the GitLab server.
- **http_username** (`Optional[str]`) – Username for HTTP authentication
- **http_password** (`Optional[str]`) – Password for HTTP authentication
- **api_version** (`str`) – Gitlab API version to use (support for 4 only)
- **pagination** (`Optional[str]`) – Can be set to ‘keyset’ to use keyset pagination
- **order_by** (`Optional[str]`) – Set order_by globally
- **user_agent** (`str`) – A custom user agent to use for making HTTP requests.
- **retry_transient_errors** (`bool`) – Whether to retry after 500, 502, 503, 504 or 52x responses. Defaults to False.

- **keep_base_url** (*bool*) – keep user-provided base URL for pagination if it differs from response headers
- **session** (*requests.Session*) – HTTP Requests Session
- **backend** (*RequestsBackend*) – Backend that will be used to make http requests
- **per_page** (*Optional[int]*) –
- **kwargs** (*Any*) –

property api_url: str

The computed API base URL.

property api_version: str

The API version used (4 only).

appearance

See [ApplicationAppearanceManager](#)

applications

See [ApplicationManager](#)

audit_events

See [AuditEventManager](#)

auth() → None

Performs an authentication using private token. Warns the user if a potentially misconfigured URL is detected on the client or server side.

The *user* attribute will hold a *gitlab.objects.CurrentUser* object on success.

Return type

None

broadcastmessages

See [BroadcastMessageManager](#)

bulk_import_entities

See [BulkImportAllEntityManager](#)

bulk_imports

See [BulkImportManager](#)

ci_lint

See [CiLintManager](#)

deploykeys

See [DeployKeyManager](#)

deploytokens

See [DeployTokenManager](#)

dockerfiles

See [DockerfileManager](#)

static enable_debug() → None**Return type**

None

events

See [EventManager](#)

features

See [FeatureManager](#)

classmethod from_config(*gitlab_id: Optional[str] = None*, *config_files: Optional[List[str]] = None*,
***kwargs: Any*) → [Gitlab](#)

Create a Gitlab connection from configuration files.

Parameters

- **gitlab_id** (*Optional[str]*) – ID of the configuration section.
- **list[str]** (*config_files*) – List of paths to configuration files.
- **config_files** (*Optional[List[str]]*) –
- **kwargs** (*Any*) –

Return type

[Gitlab](#)

kwargs:

`session`: `requests.Session`: Custom requests Session

Returns

A Gitlab connection.

Raises

[gitlab.config.GitlabDataError](#) – If the configuration is not correct.

Parameters

- **gitlab_id** (*Optional[str]*) –
- **config_files** (*Optional[List[str]]*) –
- **kwargs** (*Any*) –

Return type

[Gitlab](#)

geonodes

See [GeoNodeManager](#)

get_license(***kwargs: Any*) → `Dict[str, Union[str, Dict[str, str]]]`

Retrieve information about the current license.

Parameters

***kwargs* (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Returns

The current license information

Return type

`Dict[str, Union[str, Dict[str, str]]]`

gitignores

See [GitignoreManager](#)

gitlabciymls

See [GitlabciymlManager](#)

groups

See [GroupManager](#)

headers

Headers that will be used in request to GitLab

hooks

See [HookManager](#)

http_delete(path: str, **kwargs: Any) → Response

Make a DELETE request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The requests object.

Raises

[GitlabHttpError](#) – When the return code is not 2xx

Return type

Response

http_get(path: str, query_data: Optional[Dict[str, Any]] = None, streamed: bool = False, raw: bool = False, **kwargs: Any) → Union[Dict[str, Any], Response]

Make a GET request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **streamed (bool)** – Whether the data should be streamed
- **raw (bool)** – If True do not try to parse the output as json
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

A requests result object is streamed is True or the content type is not json. The parsed json data otherwise.

Raises

- [GitlabHttpError](#) – When the return code is not 2xx
- [GitlabParsingError](#) – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

http_head(*path: str, query_data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → requests.structures.CaseInsensitiveDict[Any]

Make a HEAD request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo, page, per_page)

Returns

A requests.header object

Raises

GitlabHttpError – When the return code is not 2xx

Return type

requests.structures.CaseInsensitiveDict[Any]

http_list(*path: str, query_data: Optional[Dict[str, Any]] = None, *, as_list: Optional[bool] = None, iterator: Optional[bool] = None, **kwargs: Any*) → Union[[GitlabList](#), List[Dict[str, Any]]]

Make a GET request to the Gitlab server for list-oriented queries.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **iterator (Optional[bool])** – Indicate if should return a generator (True)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo, page, per_page)
- **as_list (Optional[bool])** –

Returns

A list of the objects returned by the server. If *iterator* is True and no pagination-related arguments (*page, per_page, get_all*) are defined then a [GitlabList](#) object (generator) is returned instead. This object will make API calls when needed to fetch the next items from the server.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[[GitlabList](#), List[Dict[str, Any]]]

http_patch(*path: str, *, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Union[Dict[str, Any], bytes]] = None, raw: bool = False, **kwargs: Any*) → Union[Dict[str, Any], Response]

Make a PATCH request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **post_data (Optional[Union[Dict[str, Any], bytes]])** – Data to send in the body (will be converted to json by default)
- **raw (bool)** – If True, do not convert post_data to json

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The parsed json returned by the server.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

http_post(*path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Dict[str, Any]] = None, raw: bool = False, files: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *Union[Dict[str, Any], Response]*

Make a POST request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **post_data (Optional[Dict[str, Any]])** – Data to send in the body (will be converted to json by default)
- **raw (bool)** – If True, do not convert post_data to json
- **files (Optional[Dict[str, Any]])** – The files to send to the server
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The parsed json returned by the server if json is return, else the raw content

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

http_put(*path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Union[Dict[str, Any], bytes]] = None, raw: bool = False, files: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *Union[Dict[str, Any], Response]*

Make a PUT request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **post_data (Optional[Union[Dict[str, Any], bytes]])** – Data to send in the body (will be converted to json by default)
- **raw (bool)** – If True, do not convert post_data to json
- **files (Optional[Dict[str, Any]])** – The files to send to the server
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The parsed json returned by the server.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

```
http_request(verb: str, path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Union[Dict[str, Any], bytes]] = None, raw: bool = False, streamed: bool = False, files: Optional[Dict[str, Any]] = None, timeout: Optional[float] = None, obey_rate_limit: bool = True, retry_transient_errors: Optional[bool] = None, max_retries: int = 10, **kwargs: Any) → Response
```

Make an HTTP request to the Gitlab server.

Parameters

- **verb (str)** – The HTTP method to call ('get', 'post', 'put', 'delete')
- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projecs')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **post_data (Optional[Union[Dict[str, Any], bytes]])** – Data to send in the body (will be converted to json by default)
- **raw (bool)** – If True, do not convert post_data to json
- **streamed (bool)** – Whether the data should be streamed
- **files (Optional[Dict[str, Any]])** – The files to send to the server
- **timeout (Optional[float])** – The timeout, in seconds, for the request
- **obey_rate_limit (bool)** – Whether to obey 429 Too Many Requests responses. Defaults to True.
- **retry_transient_errors (Optional[bool])** – Whether to retry after 500, 502, 503, 504 or 52x responses. Defaults to False.
- **max_retries (int)** – Max retries after 429 or transient errors, set to -1 to retry forever. Defaults to 10.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

A requests result object.

Raises

GitlabHttpError – When the return code is not 2xx

Return type

Response

issues

See [IssueManager](#)

issues_statistics

See [IssuesStatisticsManager](#)

keys

See [KeyManager](#)

ldapgroups

See [LDAPGroupManager](#)

licenses

See [LicenseManager](#)

lint(*content*: str, ***kwargs*: Any) → Tuple[bool, List[str]]

Validate a gitlab CI configuration.

Parameters

- **content** (str) – The .gitlab-ci.yml content
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabVerifyError** – If the validation could not be done

Returns

(True, []) if the file is valid, (False, errors(list)) otherwise

Return type

Tuple[bool, List[str]]

markdown(*text*: str, *gfm*: bool = False, *project*: Optional[str] = None, ***kwargs*: Any) → str

Render an arbitrary Markdown document.

Parameters

- **text** (str) – The markdown text to render
- **gfm** (bool) – Render text using GitLab Flavored Markdown. Default is False
- **project** (Optional[str]) – Full path of a project used a context when *gfm* is True
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMarkdownError** – If the server cannot perform the request

Returns

The HTML rendering of the markdown text.

Return type

str

classmethod merge_config(*options*: Dict[str, Any], *gitlab_id*: Optional[str] = None, *config_files*: Optional[List[str]] = None) → [Gitlab](#)

Create a Gitlab connection by merging configuration with the following precedence:

1. Explicitly provided CLI arguments,
2. Environment variables,
3. Configuration files:
 - a. explicitly defined config files:

- i. via the `-config-file` CLI argument,
 - ii. via the `PYTHON_GITLAB_CFG` environment variable,
 - b. user-specific config file,
 - c. system-level config file,
4. Environment variables always present in CI (`CI_SERVER_URL`, `CI_JOB_TOKEN`).

Parameters

- **options** (`Dict[str, Any]`) – A dictionary of explicitly provided key-value options.
- **gitlab_id** (`Optional[str]`) – ID of the configuration section.
- **config_files** (`Optional[List[str]]`) – List of paths to configuration files.

Returns

A Gitlab connection.

Return type

`(gitlab.Gitlab)`

Raises

`gitlab.config.GitlabDataError` – If the configuration is not correct.

mergerequests

See `MergeRequestManager`

namespaces

See `NamespaceManager`

notificationsettings

See `NotificationSettingsManager`

pagesdomains

See `PagesDomainManager`

personal_access_tokens

See `PersonalAccessTokenManager`

projects

See `ProjectManager`

registry_repositories

See `RegistryRepositoryManager`

runners

See `RunnerManager`

runners_all

See `RunnerManager`

search(`scope: str, search: str, **kwargs: Any`) → Union[`GitlabList`, `List[Dict[str, Any]]`]

Search GitLab resources matching the provided string.'

Parameters

- **scope** (`str`) – Scope of the search
- **search** (`str`) – Search string
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSearchError** – If the server failed to perform the request

Returns

A list of dicts describing the resources found.

Return type

Union[GitlabList, List[Dict[str, Any]]]

set_license(*license: str, **kwargs: Any*) → *Dict[str, Any]*

Add a new license.

Parameters

- **license (str)** – The license string
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPostError** – If the server cannot perform the request

Returns

The new license information

Return type

Dict[str, Any]

settings

See *ApplicationSettingsManager*

sidekiq

See *SidekiqManager*

snippets

See *SnippetManager*

ssl_verify

Whether SSL certificates should be validated

statistics

See *ApplicationStatisticsManager*

timeout

Timeout to use for requests to gitlab server

todos

See *TodoManager*

topics

See *TopicManager*

property url: str

The user-provided server URL.

user_activities

See *UserActivitiesManager*

users

See [UserManager](#)

variables

See [VariableManager](#)

version() → Tuple[str, str]

Returns the version and revision of the gitlab server.

Note that self.version and self.revision will be set on the gitlab object.

Returns

The server version and server revision.

(‘unknown’, ‘unknown’) if the server doesn’t perform as expected.

Return type

Tuple[str, str]

exception `gitlab.GitlabActivateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabAttachFileError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabAuthenticationError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: [GitlabError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabBanError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabBlockError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabBuildCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabCancelError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabBuildEraseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabBuildPlayError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabBuildRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabRetryError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabCherryPickError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabCiLintError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabConnectionError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabCreateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabDeactivateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabDeleteError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabDeploymentApprovalError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: `Exception`

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabFollowError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabGetError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabGroupTransferError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: `GitlabOperationError`

Parameters

- `error_message` (`Union[str, bytes]`) –
- `response_code` (`Optional[int]`) –
- `response_body` (`Optional[bytes]`) –

Return type

`None`

exception `gitlab.GitlabHeadError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- `error_message` (`Union[str, bytes]`) –
- `response_code` (`Optional[int]`) –
- `response_body` (`Optional[bytes]`) –

Return type

`None`

exception `gitlab.GitlabHousekeepingError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- `error_message` (`Union[str, bytes]`) –
- `response_code` (`Optional[int]`) –
- `response_body` (`Optional[bytes]`) –

Return type

`None`

exception `gitlab.GitlabHttpError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabError`

Parameters

- `error_message` (`Union[str, bytes]`) –
- `response_code` (`Optional[int]`) –
- `response_body` (`Optional[bytes]`) –

Return type

`None`

exception `gitlab.GitlabImportError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabInvitationError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabJobCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabCancelError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabJobEraseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabJobPlayError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabJobRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabLicenseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
class gitlab.GitlabList(gl: Gitlab, url: str, query_data: Dict[str, Any], get_next: bool = True, **kwargs: Any)
```

Bases: *object*

Generator representing a list of remote objects.

The object handles the links returned by a query to the API, and will call the API again when needed.

Parameters

- **gl** (*Gitlab*) –
- **url** (*str*) –
- **query_data** (*Dict[str, Any]*) –
- **get_next** (*bool*) –
- **kwargs** (*Any*) –

property current_page: int

The current page number.

next() → *Dict[str, Any]***Return type**
*Dict[str, Any]***property next_page: Optional[int]**

The next page number.

If None, the current page is the last.

property per_page: Optional[int]

The number of items per page.

property prev_page: Optional[int]

The previous page number.

If None, the current page is the first.

property total: Optional[int]

The total number of items.

property total_pages: Optional[int]

The total number of pages.

exception gitlab.GitlabListError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception gitlab.GitlabMRApprovalError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception gitlab.GitlabMRClosedError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception gitlab.GitlabMRForbiddenError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabMROnBuildSuccessError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabMRRebaseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabMRResetApprovalError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabMarkdownError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –

- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabOperationError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabOwnershipError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabParsingError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabPipelineCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabCancelError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabPipelinePlayError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabPipelineRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabProjectDeployKeyError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabPromoteError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabProtectError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabRenderError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabRepairError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabRestoreError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabRevertError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabSearchError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabSetError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabStopError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabSubscribeError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabTimeTrackingError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabTodoError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabTopicMergeError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabTransferProjectError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUnbanError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUnblockError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUnfollowError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUnsubscribeError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabUpdateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabUploadError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabUserApproveError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabUserRejectError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –

- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabVerifyError(error_message: Union[str, bytes] = '', response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.RedirectError(error_message: Union[str, bytes] = '', response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
class gitlab.Gitlab(url: Optional[str] = None, private_token: Optional[str] = None, oauth_token: Optional[str] = None, job_token: Optional[str] = None, ssl_verify: Union[bool, str] = True, http_username: Optional[str] = None, http_password: Optional[str] = None, timeout: Optional[float] = None, api_version: str = '4', per_page: Optional[int] = None, pagination: Optional[str] = None, order_by: Optional[str] = None, user_agent: str = 'python-gitlab/3.14.0', retry_transient_errors: bool = False, keep_base_url: bool = False, **kwargs: Any)
```

Bases: *object*

Represents a GitLab server connection.

Parameters

- **url** (*Optional[str]*) – The URL of the GitLab server (defaults to <https://gitlab.com>).
- **private_token** (*Optional[str]*) – The user private token
- **oauth_token** (*Optional[str]*) – An oauth token
- **job_token** (*Optional[str]*) – A CI job token
- **ssl_verify** (*Union[bool, str]*) – Whether SSL certificates should be validated. If the value is a string, it is the path to a CA file used for certificate validation.
- **timeout** (*Optional[float]*) – Timeout to use for requests to the GitLab server.
- **http_username** (*Optional[str]*) – Username for HTTP authentication
- **http_password** (*Optional[str]*) – Password for HTTP authentication

- **api_version** (*str*) – Gitlab API version to use (support for 4 only)
- **pagination** (*Optional[str]*) – Can be set to ‘keyset’ to use keyset pagination
- **order_by** (*Optional[str]*) – Set order_by globally
- **user_agent** (*str*) – A custom user agent to use for making HTTP requests.
- **retry_transient_errors** (*bool*) – Whether to retry after 500, 502, 503, 504 or 52x responses. Defaults to False.
- **keep_base_url** (*bool*) – keep user-provided base URL for pagination if it differs from response headers
- **session** (*requests.Session*) – HTTP Requests Session
- **backend** (*RequestsBackend*) – Backend that will be used to make http requests
- **per_page** (*Optional[int]*) –
- **kwargs** (*Any*) –

property api_url: str

The computed API base URL.

property api_version: str

The API version used (4 only).

appearance

See [ApplicationAppearanceManager](#)

applications

See [ApplicationManager](#)

audit_events

See [AuditEventManager](#)

auth() → None

Performs an authentication using private token. Warns the user if a potentially misconfigured URL is detected on the client or server side.

The *user* attribute will hold a *gitlab.objects.CurrentUser* object on success.

Return type

None

broadcastmessages

See [BroadcastMessageManager](#)

bulk_import_entities

See [BulkImportAllEntityManager](#)

bulk_imports

See [BulkImportManager](#)

ci_lint

See [CiLintManager](#)

deploykeys

See [DeployKeyManager](#)

deploytokens

See [DeployTokenManager](#)

dockerfiles

See [DockerfileManager](#)

static enable_debug() → None**Return type**

None

events

See [EventManager](#)

features

See [FeatureManager](#)

classmethod from_config(gitlab_id: Optional[str] = None, config_files: Optional[List[str]] = None, **kwargs: Any) → Gitlab

Create a Gitlab connection from configuration files.

Parameters

- **gitlab_id** (*Optional[str]*) – ID of the configuration section.
- **list[str]** (*config_files*) – List of paths to configuration files.
- **config_files** (*Optional[List[str]]*) –
- **kwargs** (*Any*) –

Return type

Gitlab

kwargs:

session requests.Session: Custom requests Session

Returns

A Gitlab connection.

Raises

[gitlab.config.GitlabDataError](#) – If the configuration is not correct.

Parameters

- **gitlab_id** (*Optional[str]*) –
- **config_files** (*Optional[List[str]]*) –
- **kwargs** (*Any*) –

Return type

Gitlab

geonodes

See [GeoNodeManager](#)

get_license(kwargs: Any) → Dict[str, Union[str, Dict[str, str]]]**

Retrieve information about the current license.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Returns

The current license information

Return type

Dict[str, Union[Dict[str, str], Dict[str, str]]]

gitignores

See [GitignoreManager](#)

gitlabciymls

See [GitlabciymlManager](#)

groups

See [GroupManager](#)

headers

Headers that will be used in request to GitLab

hooks

See [HookManager](#)

http_delete(path: str, **kwargs: Any) → Response

Make a DELETE request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The requests object.

Raises

GitlabHttpError – When the return code is not 2xx

Return type

Response

http_get(path: str, query_data: Optional[Dict[str, Any]] = None, streamed: bool = False, raw: bool = False, **kwargs: Any) → Union[Dict[str, Any], Response]

Make a GET request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **streamed (bool)** – Whether the data should be streamed
- **raw (bool)** – If True do not try to parse the output as json
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

A requests result object is streamed is True or the content type is not json. The parsed json data otherwise.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

http_head(*path: str, query_data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → requests.structures.CaseInsensitiveDict[Any]

Make a HEAD request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo, page, per_page)

Returns

A requests.header object

Raises

- **GitlabHttpError** – When the return code is not 2xx

Return type

requests.structures.CaseInsensitiveDict[Any]

http_list(*path: str, query_data: Optional[Dict[str, Any]] = None, *, as_list: Optional[bool] = None, iterator: Optional[bool] = None, **kwargs: Any*) → Union[[GitlabList](#), List[Dict[str, Any]]]

Make a GET request to the Gitlab server for list-oriented queries.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **iterator (Optional[bool])** – Indicate if should return a generator (True)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo, page, per_page)
- **as_list (Optional[bool])** –

Returns

A list of the objects returned by the server. If *iterator* is True and no pagination-related arguments (*page*, *per_page*, *get_all*) are defined then a [GitlabList](#) object (generator) is returned instead. This object will make API calls when needed to fetch the next items from the server.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[GitlabList, List[Dict[str, Any]]]

http_patch(*path: str*, *, *query_data: Optional[Dict[str, Any]] = None*, *post_data: Optional[Union[Dict[str, Any], bytes]] = None*, *raw: bool = False*, ***kwargs: Any*) → *Union[Dict[str, Any], Response]*

Make a PATCH request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **post_data (Optional[Union[Dict[str, Any], bytes]])** – Data to send in the body (will be converted to json by default)
- **raw (bool)** – If True, do not convert post_data to json
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The parsed json returned by the server.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

http_post(*path: str*, *query_data: Optional[Dict[str, Any]] = None*, *post_data: Optional[Dict[str, Any]] = None*, *raw: bool = False*, *files: Optional[Dict[str, Any]] = None*, ***kwargs: Any*) → *Union[Dict[str, Any], Response]*

Make a POST request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **post_data (Optional[Dict[str, Any]])** – Data to send in the body (will be converted to json by default)
- **raw (bool)** – If True, do not convert post_data to json
- **files (Optional[Dict[str, Any]])** – The files to send to the server
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The parsed json returned by the server if json is return, else the raw content

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

```
http_put(path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Union[Dict[str, Any], bytes]] = None, raw: bool = False, files: Optional[Dict[str, Any]] = None, **kwargs: Any) → Union[Dict[str, Any], Response]
```

Make a PUT request to the Gitlab server.

Parameters

- **path** (str) – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data** (Optional[Dict[str, Any]]) – Data to send as query parameters
- **post_data** (Optional[Union[Dict[str, Any], bytes]]) – Data to send in the body (will be converted to json by default)
- **raw** (bool) – If True, do not convert post_data to json
- **files** (Optional[Dict[str, Any]]) – The files to send to the server
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The parsed json returned by the server.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

```
http_request(verb: str, path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Union[Dict[str, Any], bytes]] = None, raw: bool = False, streamed: bool = False, files: Optional[Dict[str, Any]] = None, timeout: Optional[float] = None, obey_rate_limit: bool = True, retry_transient_errors: Optional[bool] = None, max_retries: int = 10, **kwargs: Any) → Response
```

Make an HTTP request to the Gitlab server.

Parameters

- **verb** (str) – The HTTP method to call ('get', 'post', 'put', 'delete')
- **path** (str) – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data** (Optional[Dict[str, Any]]) – Data to send as query parameters
- **post_data** (Optional[Union[Dict[str, Any], bytes]]) – Data to send in the body (will be converted to json by default)
- **raw** (bool) – If True, do not convert post_data to json
- **streamed** (bool) – Whether the data should be streamed
- **files** (Optional[Dict[str, Any]]) – The files to send to the server
- **timeout** (Optional[float]) – The timeout, in seconds, for the request
- **obey_rate_limit** (bool) – Whether to obey 429 Too Many Request responses. Defaults to True.
- **retry_transient_errors** (Optional[bool]) – Whether to retry after 500, 502, 503, 504 or 52x responses. Defaults to False.

- **max_retries** (*int*) – Max retries after 429 or transient errors, set to -1 to retry forever. Defaults to 10.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

A requests result object.

Raises

GitlabHttpError – When the return code is not 2xx

Return type

Response

issues

See [IssueManager](#)

issues_statistics

See [IssuesStatisticsManager](#)

keys

See [KeyManager](#)

ldapgroups

See [LDAPGroupManager](#)

licenses

See [LicenseManager](#)

lint(*content: str, **kwargs: Any*) → Tuple[bool, List[str]]

Validate a gitlab CI configuration.

Parameters

- **content** (*str*) – The .gitlab-ci.yml content
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabVerifyError** – If the validation could not be done

Returns

(True, []) if the file is valid, (False, errors(list)) otherwise

Return type

Tuple[bool, List[str]]

markdown(*text: str, gfm: bool = False, project: Optional[str] = None, **kwargs: Any*) → str

Render an arbitrary Markdown document.

Parameters

- **text** (*str*) – The markdown text to render
- **gfm** (*bool*) – Render text using GitLab Flavored Markdown. Default is False
- **project** (*Optional[str]*) – Full path of a project used a context when *gfm* is True
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMarkdownError** – If the server cannot perform the request

Returns

The HTML rendering of the markdown text.

Return type

str

classmethod **merge_config**(*options: Dict[str, Any]*, *gitlab_id: Optional[str] = None*, *config_files: Optional[List[str]] = None*) → *Gitlab*

Create a Gitlab connection by merging configuration with the following precedence:

1. Explicitly provided CLI arguments,
2. Environment variables,
3. **Configuration files:**
 - a. **explicitly defined config files:**
 - i. via the *-config-file* CLI argument,
 - ii. via the *PYTHON_GITLAB_CFG* environment variable,
 - b. user-specific config file,
 - c. system-level config file,
4. Environment variables always present in CI (CI_SERVER_URL, CI_JOB_TOKEN).

Parameters

- **options** (*Dict[str, Any]*) – A dictionary of explicitly provided key-value options.
- **gitlab_id** (*Optional[str]*) – ID of the configuration section.
- **config_files** (*Optional[List[str]]*) – List of paths to configuration files.

Returns

A Gitlab connection.

Return type

(*gitlab.Gitlab*)

Raises

gitlab.config.GitlabDataError – If the configuration is not correct.

mergerequests

See *MergeRequestManager*

namespaces

See *NamespaceManager*

notificationsettings

See *NotificationSettingsManager*

pagesdomains

See *PagesDomainManager*

personal_access_tokens

See *PersonalAccessTokenManager*

projects

See [ProjectManager](#)

registry_repositories

See [RegistryRepositoryManager](#)

runners

See [RunnerManager](#)

runners_all

See [RunnerManager](#)

search(scope: str, search: str, **kwargs: Any) → Union[GitlabList, List[Dict[str, Any]]]

Search GitLab resources matching the provided string.'

Parameters

- **scope (str)** – Scope of the search
- **search (str)** – Search string
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSearchError** – If the server failed to perform the request

Returns

A list of dicts describing the resources found.

Return type

Union[GitlabList, List[Dict[str, Any]]]

set_license(license: str, **kwargs: Any) → Dict[str, Any]

Add a new license.

Parameters

- **license (str)** – The license string
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPostError** – If the server cannot perform the request

Returns

The new license information

Return type

Dict[str, Any]

settings

See [ApplicationSettingsManager](#)

sidekiq

See [SidekiqManager](#)

snippets

See [SnippetManager](#)

ssl_verify

Whether SSL certificates should be validated

statistics

See [ApplicationStatisticsManager](#)

timeout

Timeout to use for requests to gitlab server

todos

See [TodoManager](#)

topics

See [TopicManager](#)

property url: str

The user-provided server URL.

user: Optional[objects.CurrentUser]**user_activities**

See [UserActivitiesManager](#)

users

See [UserManager](#)

variables

See [VariableManager](#)

version() → Tuple[str, str]

Returns the version and revision of the gitlab server.

Note that self.version and self.revision will be set on the gitlab object.

Returns**The server version and server revision.**

(‘unknown’, ‘unknown’) if the server doesn’t perform as expected.

Return type

Tuple[str, str]

class gitlab.GitlabList(gl: Gitlab, url: str, query_data: Dict[str, Any], get_next: bool = True, **kwargs: Any)

Bases: `object`

Generator representing a list of remote objects.

The object handles the links returned by a query to the API, and will call the API again when needed.

Parameters

- **gl (Gitlab) –**
- **url (str) –**
- **query_data (Dict[str, Any]) –**
- **get_next (bool) –**
- **kwargs (Any) –**

```
property current_page: int
    The current page number.

next() → Dict[str, Any]

    Return type
    Dict[str, Any]

property next_page: Optional[int]
    The next page number.

    If None, the current page is the last.

property per_page: Optional[int]
    The number of items per page.

property prev_page: Optional[int]
    The previous page number.

    If None, the current page is the first.

property total: Optional[int]
    The total number of items.

property total_pages: Optional[int]
    The total number of pages.
```

7.6.2 Subpackages

gitlab.v4 package

Submodules

gitlab.v4.objects module

```
class gitlab.v4.objects.Application(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:
    bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ApplicationAppearance(manager: RESTManager, attrs: Dict[str, Any], *,
    created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –

```
    • attrs (Dict[str, Any]) –
    • created_from_list (bool) –
    • lazy (bool) –

manager: RESTManager

class gitlab.v4.objects.ApplicationAppearanceManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: GetWithoutIdMixin, UpdateMixin, RESTManager
```

Object Creation

Object update

Optional attributes for object update:

- `title`
- `description`
- `logo`
- `header_logo`
- `favicon`
- `new_project_guidelines`
- `header_message`
- `footer_message`
- `message_background_color`
- `message_font_color`
- `email_header_and_footer_enabled`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(***kwargs: Any*) → *ApplicationAppearance*

Retrieve a single object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ApplicationAppearance

gitlab: *Gitlab*

```
update(id: Optional[Union[int, str]] = None, new_data: Optional[Dict[str, Any]] = None, **kwargs: Any)
       → Dict[str, Any]
```

Update an object on the server.

Parameters

- **id** (*Optional[Union[int, str]]*) – ID of the object to update (can be None if not required)
- **new_data** (*Optional[Dict[str, Any]]*) – the update data for the object
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The new object data (*not* a RESTObject)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server cannot perform the request

Return type

Dict[str, Any]

```
class gitlab.v4.objects.ApplicationManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, CreateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- name
- redirect_uri
- scopes

Optional attributes for object create:

- confidential

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.ApplicationSettings(manager: RESTManager, attrs: Dict[str, Any], *,
                                             created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

```
manager: RESTManager

class gitlab.v4.objects.ApplicationSettingsManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: GetWithoutIdMixin, UpdateMixin, RESTManager
```

Object Creation

Object update

Optional attributes for object update:

- id
- default_projects_limit
- signup_enabled
- password_authentication_enabled_for_web
- gravatar_enabled
- sign_in_text
- created_at
- updated_at
- home_page_url
- default_branch_protection
- restricted_visibility_levels
- max_attachment_size
- session_expire_delay
- default_project_visibility
- default_snippet_visibility
- default_group_visibility
- outbound_local_requests_whitelist
- disabled_oauth_sign_in_sources
- domain_whitelist
- domain_blacklist_enabled
- domain_blacklist
- domain_allowlist
- domain_denylist_enabled
- domain_denylist
- external_authorization_service_enabled
- external_authorization_service_url
- external_authorization_service_default_label
- external_authorization_service_timeout
- import_sources

- user_oauth_applications
- after_sign_out_path
- container_registry_token_expire_delay
- repository_storages
- plantuml_enabled
- plantuml_url
- terminal_max_session_time
- polling_interval_multiplier
- rsa_key_restriction
- dsa_key_restriction
- ecdsa_key_restriction
- ed25519_key_restriction
- first_day_of_week
- enforce_terms
- terms
- performance_bar_allowed_group_id
- instance_statistics_visibility_private
- user_show_add_ssh_key_message
- file_template_project_id
- local_markdown_version
- asset_proxy_enabled
- asset_proxy_url
- asset_proxy_whitelist
- asset_proxy_allowlist
- geo_node_allowed_ips
- allow_local_requests_from_hooks_and_services
- allow_local_requests_from_web_hooks_and_services
- allow_local_requests_from_system_hooks

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → ApplicationSettings`

Retrieve a single object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ApplicationSettings

gitlab: `Gitlab`

update(*id*: *Optional[Union[int, str]]* = *None*, *new_data*: *Optional[Dict[str, Any]]* = *None*, ***kwargs*: *Any*)
→ Dict[str, Any]

Update an object on the server.

Parameters

- **id**(*Optional[Union[int, str]]*) – ID of the object to update (can be None if not required)
- **new_data**(*Optional[Dict[str, Any]]*) – the update data for the object
- ****kwargs**(*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The new object data (*not* a RESTObject)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server cannot perform the request

Return type

Dict[str, Any]

class gitlab.v4.objects.ApplicationStatistics(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)

Bases: `RESTObject`

Parameters

- **manager**(`RESTManager`) –
- **attrs**(`Dict[str, Any]`) –
- **created_from_list**(`bool`) –
- **lazy**(`bool`) –

manager: `RESTManager`

class gitlab.v4.objects.ApplicationStatisticsManager(gl: Gitlab, parent: Optional[RESTObject] = None)

Bases: `GetWithoutIdMixin, RESTManager`

Object Creation**Object update****Parameters**

- **gl**(`Gitlab`) –

- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → ApplicationStatistics**
Retrieve a single object.

Parameters
****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns
The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type
ApplicationStatistics

gitlab: *Gitlab*

class gitlab.v4.objects.AuditEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

class gitlab.v4.objects.AuditEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: *RetrieveMixin, RESTManager*

Object listing filters

- `created_after`
- `created_before`
- `entity_type`
- `entity_id`

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → AuditEvent
Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[AuditEvent](#)

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.BroadcastMessage(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: [SaveMixin](#), [ObjectDeleteMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: [RESTManager](#)

```
class gitlab.v4.objects.BroadcastMessageManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: [CRUDMixin](#), [RESTManager](#)

Object Creation

Required attributes for object create:

- **message**

Optional attributes for object create:

- **starts_at**
- **ends_at**
- **color**
- **font**
- **target_access_levels**

Object update

Optional attributes for object update:

- **message**
- **starts_at**
- **ends_at**
- **color**

- `font`
- `target_access_levels`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → BroadcastMessage`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`BroadcastMessage`

`gitlab: Gitlab`

`class gitlab.v4.objects.BulkImport(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RefreshMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`entities: BulkImportEntityManager`

`class gitlab.v4.objects.BulkImportAllEntity(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

```
manager: RESTManager

class gitlab.v4.objects.BulkImportAllEntityManager(gl: Gitlab, parent: Optional[RESTObject] = None)
    Bases: ListMixin, RESTManager

Object listing filters

- sort
- status

Object Creation
Object update

    Parameters

- gl (Gitlab) –
- parent (Optional[RESTObject]) –


gitlab: Gitlab

class gitlab.v4.objects.BulkImportEntity(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
    Bases: RefreshMixin, RESTObject

    Parameters

- manager (RESTManager) –
- attrs (Dict[str, Any]) –
- created_from_list (bool) –
- lazy (bool) –


manager: RESTManager

class gitlab.v4.objects.BulkImportEntityManager(gl: Gitlab, parent: Optional[RESTObject] = None)
    Bases: RetrieveMixin, RESTManager

Object listing filters

- sort
- status

Object Creation
Object update

    Parameters

- gl (Gitlab) –
- parent (Optional[RESTObject]) –

get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → BulkImportEntity
    Retrieve a single object.

    Parameters

- id (Union[str, int]) – ID of the object to retrieve

```

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

BulkImportEntity

gitlab: *Gitlab*

class `gitlab.v4.objects.BulkImportManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: *CreateMixin, RetrieveMixin, RESTManager*

Object listing filters

- sort
- status

Object Creation

Required attributes for object create:

- configuration
- entities

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *BulkImport*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

BulkImport

gitlab: *Gitlab*

```
class gitlab.v4.objects.CiLint(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.CiLintManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CreateMixin, RESTManager*

Object Creation

Required attributes for object create:

- **content**

Optional attributes for object create:

- **include_merged_yaml**
- **include_jobs**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

validate(*args: Any, **kwargs: Any) → None

Raise an error if the CI Lint results are not valid.

This is a custom python-gitlab method to wrap lint endpoints.

Parameters

- **args** (*Any*) –
- **kwargs** (*Any*) –

Return type

None

```
class gitlab.v4.objects.CurrentUser(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –

- `created_from_list (bool) –`
- `lazy (bool) –`

`emails: CurrentUserEmailManager`

`gpgkeys: CurrentUserGPGKeyManager`

`keys: CurrentUserKeyManager`

`status: CurrentUserStatusManager`

`class gitlab.v4.objects.CurrentUserEmail(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

`manager: RESTManager`

`class gitlab.v4.objects.CurrentUserEmailManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, CreateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- `email`

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → CurrentUserEmail`

Retrieve a single object.

Parameters

- `id (Union[str, int]) –` ID of the object to retrieve
- `lazy (bool) –` If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

CurrentUserEmail

gitlab: *Gitlab***class** gitlab.v4.objects.CurrentUserGPGKey(*manager: RESTManager*, *attrs: Dict[str, Any]*, *,
created_from_list: bool = False, *lazy: bool = False*)Bases: *ObjectDeleteMixin, RESTObject***Parameters**

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager***class** gitlab.v4.objects.CurrentUserGPGKeyManager(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)Bases: *RetrieveMixin, CreateMixin, DeleteMixin, RESTManager***Object Creation**

Required attributes for object create:

- key

Object update**Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *CurrentUserGPGKey*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

CurrentUserGPGKey

gitlab: *Gitlab*

```
class gitlab.v4.objects.CurrentUserKey(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.CurrentUserKeyManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, CreateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- **title**
- **key**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *CurrentUserKey*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

CurrentUserKey

gitlab: *Gitlab*

```
class gitlab.v4.objects.CurrentUserManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin, RESTManager*

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → CurrentUser`

Retrieve a single object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`CurrentUser`

`gitlab: Gitlab`

`class gitlab.v4.objects.CurrentUserStatus(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.CurrentUserStatusManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `GetWithoutIdMixin, UpdateMixin, RESTManager`

Object Creation**Object update**

Optional attributes for object update:

- `emoji`
- `message`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → CurrentUserStatus`

Retrieve a single object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

CurrentUserStatus

gitlab: `Gitlab`

```
class gitlab.v4.objects.DeployKey(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                    bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.DeployKeyManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `ListMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

```
class gitlab.v4.objects.DeployToken(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                    bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.DeployTokenManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `ListMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional*[`RESTObject`]) –

gitlab: `Gitlab`

```
class gitlab.v4.objects.Dockerfile(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.DockerfileManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, RESTManager`

Object Creation**Object update****Parameters**

- **gl** (`Gitlab`) –
- **parent** (*Optional*[`RESTObject`]) –

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → `Dockerfile`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`Dockerfile`

gitlab: `Gitlab`

```
class gitlab.v4.objects.Event(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.EventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- **action**
- **target_type**
- **before**
- **after**
- **sort**

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.Feature(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.FeatureManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, DeleteMixin, RESTManager*

Object Creation

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`gitlab: Gitlab`

`set(name: str, value: Union[bool, int], feature_group: Optional[str] = None, user: Optional[str] = None, group: Optional[str] = None, project: Optional[str] = None, **kwargs: Any) → Feature`

Create or update the object.

Parameters

- `name (str) –` The value to set for the object
- `value (Union[bool, int]) –` The value to set for the object
- `feature_group (Optional[str]) –` A feature group name
- `user (Optional[str]) –` A GitLab username
- `group (Optional[str]) –` A GitLab group
- `project (Optional[str]) –` A GitLab project in form group/project
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabSetError` – If an error occurred

Returns

The created/updated attribute

Return type

Feature

`class gitlab.v4.objects.GenericPackage(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

`manager: RESTManager`

`class gitlab.v4.objects.GenericPackageManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RESTManager`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

```
download(package_name: str, package_version: str, file_name: str, streamed: bool = False, action: Optional[Callable[[bytes], None]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]
```

Download a generic package.

Parameters

- **package_name** (*str*) – The package name.
- **package_version** (*str*) – The package version.
- **file_name** (*str*) – The name of the file in the registry
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[[bytes], None]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The package content if streamed is False, None otherwise

Return type

Optional[Union[bytes, Iterator[Any]]]

gitlab: *Gitlab*

```
upload(package_name: str, package_version: str, file_name: str, path: Union[str, Path], **kwargs: Any) → GenericPackage
```

Upload a file as a generic package.

Parameters

- **package_name** (*str*) – The package name. Must follow generic package name regex rules
- **package_version** (*str*) – The package version. Must follow semantic version regex rules
- **file_name** (*str*) – The name of the file as uploaded in the registry
- **path** (*Union[str, Path]*) – The path to a local file to upload
- **kwargs** (*Any*) –

Raises

- **GitlabConnectionError** – If the server cannot be reached
- **GitlabUploadError** – If the file upload fails
- **GitlabUploadError** – If filepath cannot be read

Returns

An object storing the metadata of the uploaded package.

Return type

GenericPackage

https://docs.gitlab.com/ee/user/packages/generic_packages/

```
class gitlab.v4.objects.GeoNode(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

repair(kwargs: Any) → None**

Repair the OAuth authentication of the geo node.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabRepairError** – If the server failed to perform the request

Return type

None

status(kwargs: Any) → Dict[str, Any]**

Get the status of the geo node.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The status of the geo node

Return type

Dict[str, Any]

```
class gitlab.v4.objects.GeoNodeManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, UpdateMixin, DeleteMixin, RESTManager*

Object Creation**Object update**

Optional attributes for object update:

- `enabled`
- `url`

- `files_max_capacity`
- `repos_max_capacity`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`current_failures(**kwargs: Any) → List[Dict[str, Any]]`

Get the list of failures on the current geo node.

Parameters

- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

Returns

The list of failures

Return type

`List[Dict[str, Any]]`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GeoNode`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GeoNode`

`gitlab: Gitlab`

`status(**kwargs: Any) → List[Dict[str, Any]]`

Get the status of all the geo nodes.

Parameters

- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

Returns

The status of all the geo nodes

Return type

List[Dict[str, Any]]

```
class gitlab.v4.objects.Gitignore(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
    bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GitignoreManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, RESTManager*

Object Creation**Object update****Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *Gitignore*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Gitignore

gitlab: *Gitlab*

```
class gitlab.v4.objects.Gitlabciyml(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
    bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.GitlabciymlManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `RetrieveMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int], lazy: bool = False, **kwargs: Any`) → `Gitlabciyml`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`Gitlabciyml`

gitlab: `Gitlab`

class `gitlab.v4.objects.Group`(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

access_tokens: `GroupAccessTokenManager`

accessrequests: `GroupAccessRequestManager`

`add_ldap_group_link(cn: str, group_access: int, provider: str, **kwargs: Any) → None`

Add an LDAP group link.

Parameters

- `cn (str)` – CN of the LDAP group
- `group_access (int)` – Minimum access level for members of the LDAP group
- `provider (str)` – LDAP provider for the LDAP group
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

Return type

None

`audit_events: GroupAuditEventManager`

`badges: GroupBadgeManager`

`billable_members: GroupBillableMemberManager`

`boards: GroupBoardManager`

`clusters: GroupClusterManager`

`customattributes: GroupCustomAttributeManager`

`delete_ldap_group_link(cn: str, provider: Optional[str] = None, **kwargs: Any) → None`

Delete an LDAP group link.

Parameters

- `cn (str)` – CN of the LDAP group
- `provider (Optional[str])` – LDAP provider for the LDAP group
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server cannot perform the request

Return type

None

`deploytokens: GroupDeployTokenManager`

`descendant_groups: GroupDescendantGroupManager`

`epics: GroupEpicManager`

`exports: GroupExportManager`

`hooks: GroupHookManager`

`imports: GroupImportManager`

```
invitations: GroupInvitationManager
issues: GroupIssueManager
issues_statistics: GroupIssuesStatisticsManager
iterations: GroupIterationManager
labels: GroupLabelManager
ldap_group_links: GroupLDAPGroupLinkManager
```

ldap_sync(kwargs: Any) → None**

Sync LDAP groups.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Return type

None

```
members: GroupMemberManager
```

```
members_all: GroupMemberAllManager
```

```
mergerequests: GroupMergeRequestManager
```

```
milestones: GroupMilestoneManager
```

```
notificationsettings: GroupNotificationSettingsManager
```

```
packages: GroupPackageManager
```

```
projects: GroupProjectManager
```

```
pushrules: GroupPushRulesManager
```

```
registry_repositories: GroupRegistryRepositoryManager
```

restore(kwargs: Any) → None**

Restore a group marked for deletion..

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabRestoreError** – If the server failed to perform the request

Return type

None

```
runners: GroupRunnerManager
```

```
saml_group_links: GroupSAMLGroupLinkManager
```

search(*scope: str, search: str, **kwargs: Any*) → Union[*GitlabList*, List[Dict[str, Any]]]

Search the group resources matching the provided string.

Parameters

- **scope (str)** – Scope of the search
- **search (str)** – Search string
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSearchError** – If the server failed to perform the request

Returns

A list of dicts describing the resources found.

Return type

Union[*GitlabList*, List[Dict[str, Any]]]

share(*group_id: int, group_access: int, expires_at: Optional[str] = None, **kwargs: Any*) → None

Share the group with a group.

Parameters

- **group_id (int)** – ID of the group.
- **group_access (int)** – Access level for the group.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)
- **expires_at (Optional[str])** –
- ****kwargs** –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server failed to perform the request

Returns

Group

Return type

None

shared_projects: *SharedProjectManager*

subgroups: *GroupSubgroupManager*

transfer(*group_id: Optional[int] = None, **kwargs: Any*) → None

Transfer the group to a new parent group or make it a top-level group.

Requires GitLab 14.6.

Parameters

- **group_id (Optional[int])** – ID of the new parent group. When not specified, the group to transfer is instead turned into a top-level group.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGroupTransferError** – If the group could not be transferred

Return type

None

transfer_project(*project_id*: int, ***kwargs*: Any) → None

Transfer a project to this group.

Parameters

- **to_project_id** – ID of the project to transfer
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)
- **project_id (int)** –
- ****kwargs** –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTransferProjectError** – If the project could not be transferred

Return type

None

unshare(*group_id*: int, ***kwargs*: Any) → None

Delete a shared group link within a group.

Parameters

- **group_id (int)** – ID of the group.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server failed to perform the request

Return type

None

variables: *GroupVariableManager*

wikis: *GroupWikiManager*

class gitlab.v4.objects.GroupAccessRequest(*manager*: RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False, *lazy*: bool = False)

Bases: *AccessRequestMixin*, *ObjectDeleteMixin*, *RESTObject*

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupAccessRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, CreateMixin, DeleteMixin, RESTManager
```

Object Creation

Object update

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

gitlab: Gitlab

```
class gitlab.v4.objects.GroupAccessToken(manager: RESTManager, attrs: Dict[str, Any], *,
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: ObjectDeleteMixin, RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: RESTManager

```
class gitlab.v4.objects.GroupAccessTokenManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: ListMixin, CreateMixin, DeleteMixin, RESTManager

Object Creation

Required attributes for object create:

- name
- scopes

Optional attributes for object create:

- access_level
- expires_at

Object update

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

gitlab: Gitlab

```
class gitlab.v4.objects.GroupAuditEvent(manager: RESTManager, attrs: Dict[str, Any], *,
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –

```
    • created_from_list (bool) –
    • lazy (bool) –
manager: RESTManager

class gitlab.v4.objects.GroupAuditEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: RetrieveMixin, RESTManager

Object listing filters
    • created_after
    • created_before

Object Creation

Object update

Parameters
    • gl (Gitlab) –
    • parent (Optional[RESTObject]) –
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupAuditEvent
    Retrieve a single object.

Parameters
    • id (Union[str, int]) – ID of the object to retrieve
    • lazy (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
    • **kwargs (Any) – Extra options to send to the server (e.g. sudo)

Returns
    The generated RESTObject.

Raises
    • GitlabAuthenticationError – If authentication is not correct
    • GitlabGetError – If the server cannot perform the request

Return type
    GroupAuditEvent

gitlab: Gitlab

class gitlab.v4.objects.GroupBadge(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
Bases: SaveMixin, ObjectDeleteMixin, RESTObject

Parameters
    • manager (RESTManager) –
    • attrs (Dict[str, Any]) –
    • created_from_list (bool) –
    • lazy (bool) –
manager: RESTManager
```

```
class gitlab.v4.objects.GroupBadgeManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: BadgeRenderMixin, CRUDMixin, RESTManager
```

Object Creation

Required attributes for object create:

- `link_url`
- `image_url`

Object update

Optional attributes for object update:

- `link_url`
- `image_url`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupBadge`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupBadge`

`gitlab: Gitlab`

```
class gitlab.v4.objects.GroupBillableMember(manager: RESTManager, attrs: Dict[str, Any], *,
                                             created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

memberships: *GroupBillableMemberMembershipManager*

```
class gitlab.v4.objects.GroupBillableMemberManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, DeleteMixin, RESTManager*

Object listing filters

- `search`
- `sort`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupBillableMemberMembership(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

manager: *RESTManager*

```
class gitlab.v4.objects.GroupBillableMemberMembershipManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object Creation

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupBoard(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`

- `created_from_list (bool) –`
- `lazy (bool) –`

`lists: GroupBoardListManager`

`class gitlab.v4.objects.GroupBoardList(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

`manager: RESTManager`

`class gitlab.v4.objects.GroupBoardListManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object Creation

Mutually exclusive attributes for object create:

- `label_id`
- `assignee_id`
- `milestone_id`

Object update

Required attributes for object update:

- `position`

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupBoardList`

Retrieve a single object.

Parameters

- `id (Union[str, int]) –` ID of the object to retrieve
- `lazy (bool) –` If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type
GroupBoardList

gitlab: [Gitlab](#)

class [gitlab.v4.objects.GroupBoardManager](#)(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: [CRUDMixin](#), [RESTManager](#)

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** ([Optional\[RESTObject\]](#)) –

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → [GroupBoard](#)

Retrieve a single object.

Parameters

- **id** ([Union\[str, int\]](#)) – ID of the object to retrieve
- **lazy** ([bool](#)) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** ([Any](#)) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type

[GroupBoard](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.GroupCluster](#)(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: [SaveMixin](#), [ObjectDeleteMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –
- **lazy** ([bool](#)) –

manager: [RESTManager](#)

```
class gitlab.v4.objects.GroupClusterManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- name
- platform_kubernetes_attributes

Optional attributes for object create:

- domain
- enabled
- managed
- environment_scope

Object update

Optional attributes for object update:

- name
- domain
- management_project_id
- platform_kubernetes_attributes
- environment_scope

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

create(*data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → [GroupCluster](#)

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – Parameters to send to the server to create the resource
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo or ‘ref_name’, ‘stage’, ‘name’, ‘all’)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Returns

A new instance of the manage object class build with
the data sent by the server

Return type

[GroupCluster](#)

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupCluster
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`GroupCluster`

gitlab: `Gitlab`

```
class gitlab.v4.objects.GroupCustomAttribute(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.GroupCustomAttributeManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, SetMixin, DeleteMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupCustomAttribute
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.

- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupCustomAttribute

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupDeployToken(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupDeployTokenManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, CreateMixin, DeleteMixin, RESTManager*

Object listing filters

- scopes

Object Creation

Required attributes for object create:

- name
- scopes

Optional attributes for object create:

- expires_at
- username

Object update**Parameters**

- **gl** (*Gitlab*) –
- **parent** (Optional[*RESTObject*]) –

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → *GroupDeployToken*

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve

- **lazy (bool)** – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupDeployToken

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.GroupDescendantGroup(manager: RESTManager, attrs: Dict[str, Any], *,  
                                              created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

manager: [RESTManager](#)

```
class gitlab.v4.objects.GroupDescendantGroupManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                    None)
```

Bases: *GroupSubgroupManager*

This manager inherits from GroupSubgroupManager as descendant groups share all attributes with subgroups, except the path and object class.

Object listing filters

- skip_groups
- all_available
- search
- order_by
- sort
- statistics
- owned
- with_custom_attributes
- min_access_level

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

```
class gitlab.v4.objects.GroupEpic(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, SaveMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

issues: `GroupEpicIssueManager`

notes: `GroupEpicNoteManager`

resourceLabelEvents: `GroupEpicResourceLabelEventManager`

```
class gitlab.v4.objects.GroupEpicAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.GroupEpicAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `NoUpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `GroupEpicAwardEmoji`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupEpicAwardEmoji

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupEpicDiscussionNote(manager: RESTManager, attrs: Dict[str, Any], *,  
                                                created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupEpicDiscussionNoteManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                       None)
```

Bases: *GetMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at

Object update

Required attributes for object update:

- body

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *GroupEpicDiscussionNote*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupEpicDiscussionNote

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupEpicIssue(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, SaveMixin, RESTObject*

Parameters

- **manager** (*GroupEpicIssueManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *GroupEpicIssueManager*

save(kwargs: Any) → None**

Save the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server cannot perform the request

Return type

None

```
class gitlab.v4.objects.GroupEpicIssueManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- **issue_id**

Object update

Optional attributes for object update:

- `move_before_id`
- `move_after_id`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → GroupEpicIssue`

Create a new object.

Parameters

- `data (Optional[Dict[str, Any]])` – Parameters to send to the server to create the resource
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

Returns

A new instance of the `manage` object class build with the data sent by the server

Return type

`GroupEpicIssue`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupEpicManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object listing filters

- `author_id`
- `labels`
- `order_by`
- `sort`
- `search`

Object Creation

Required attributes for object create:

- `title`

Optional attributes for object create:

- `labels`
- `description`
- `start_date`
- `end_date`

Object update

Optional attributes for object update:

- `title`
- `labels`
- `description`
- `start_date`
- `end_date`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupEpic`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupEpic`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupEpicNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`awardemojis: GroupEpicNoteAwardEmojiManager`

```
class gitlab.v4.objects.GroupEpicNoteAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *,  
                                               created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupEpicNoteAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                       None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *GroupEpicNoteAwardEmoji*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupEpicNoteAwardEmoji

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupEpicNoteManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at

Object update

Required attributes for object update:

- body

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → `GroupEpicNote`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`GroupEpicNote`

gitlab: `Gitlab`

class `gitlab.v4.objects.GroupEpicResourceLabelEvent`(*manager*: `RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`, *lazy*: `bool = False`)

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.GroupEpicResourceLabelEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupEpicResourceLabelEvent
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupEpicResourceLabelEvent

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupExport(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *DownloadMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupExportManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin, CreateMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –

- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → GroupExport**
Retrieve a single object.

Parameters
****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns
The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type
GroupExport

gitlab: *Gitlab*

class gitlab.v4.objects.GroupHook(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

class gitlab.v4.objects.GroupHookManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- url

Optional attributes for object create:

- push_events
- issues_events
- confidential_issues_events
- merge_requests_events
- tag_push_events
- note_events
- confidential_note_events
- job_events
- pipeline_events
- wiki_page_events

- deployment_events
- releases_events
- subgroup_events
- enable_ssl_verification
- token

Object update

Required attributes for object update:

- url

Optional attributes for object update:

- push_events
- issues_events
- confidential_issues_events
- merge_requests_events
- tag_push_events
- note_events
- confidential_note_events
- job_events
- pipeline_events
- wiki_page_events
- deployment_events
- releases_events
- subgroup_events
- enable_ssl_verification
- token

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [GroupHook](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupHook

gitlab: *Gitlab***class** gitlab.v4.objects.GroupImport(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)Bases: *RESTObject***Parameters**

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager***class** gitlab.v4.objects.GroupImportManager(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)Bases: *GetWithoutIdMixin, RESTManager***Object Creation****Object update****Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → GroupImport**

Retrieve a single object.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupImport

gitlab: *Gitlab***class** gitlab.v4.objects.GroupInvitation(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)Bases: *SaveMixin, ObjectDeleteMixin, RESTObject***Parameters**

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.GroupInvitationManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: InvitationMixin, RESTManager
```

Object listing filters

- `query`

Object Creation

Required attributes for object create:

- `access_level`

Optional attributes for object create:

- `expires_at`
- `invite_source`
- `tasks_to_be_done`
- `tasks_project_id`

Mutually exclusive attributes for object create:

- `email`
- `user_id`

Object update

Optional attributes for object update:

- `access_level`
- `expires_at`

Parameters

- `gl` (`Gitlab`) –
- `parent` (`Optional[RESTObject]`) –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `GroupInvitation`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupInvitation

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupIssue(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                    bool = False, lazy: bool = False)
```

Bases: *RESTObject***Parameters**

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupIssueManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager***Object listing filters**

- state
- labels
- milestone
- order_by
- sort
- iids
- author_id
- assignee_id
- my_reaction_emoji
- search
- created_after
- created_before
- updated_after
- updated_before

Object Creation**Object update****Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupIssuesStatistics(manager: RESTManager, attrs: Dict[str, Any], *,  
                                              created_from_list: bool = False, lazy: bool = False)
```

Bases: *RefreshMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupIssuesStatisticsManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                   None)
```

Bases: *GetWithoutIdMixin, RESTManager*

Object listing filters

- iids

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → GroupIssuesStatistics**

Retrieve a single object.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupIssuesStatistics

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupIteration(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –

- `created_from_list (bool) –`
- `lazy (bool) –`

manager: `RESTManager`

class `gitlab.v4.objects.GroupIterationManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)
Bases: `ListMixin, RESTManager`

Object listing filters

- `state`
- `search`
- `include_ancestors`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

gitlab: `Gitlab`

class `gitlab.v4.objects.GroupLDAPGroupLink`(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)
Bases: `RESTObject`

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

delete(kwargs: Any) → None**
Delete the LDAP group link from the server.

Parameters
`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server cannot perform the request

Return type
None

manager: `RESTManager`

class `gitlab.v4.objects.GroupLDAPGroupLinkManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)
Bases: `ListMixin, CreateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- provider
- group_access

Mutually exclusive attributes for object create:

- cn
- filter

Object update

Parameters

- gl ([Gitlab](#)) –
- parent (*Optional[RESTObject]*) –

class `gitlab.v4.objects.GroupLabel`(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *SubscribableMixin, SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- manager ([GroupLabelManager](#)) –
- attrs (*Dict[str, Any]*) –
- created_from_list (*bool*) –
- lazy (*bool*) –

manager: *GroupLabelManager*

save(kwargs: Any) → None**

Saves the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct.
- **GitlabUpdateError** – If the server cannot perform the request.

Return type

None

class `gitlab.v4.objects.GroupLabelManager`(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: *RetrieveMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- name
- color

Optional attributes for object create:

- description
- priority

Object update

Required attributes for object update:

- `name`

Optional attributes for object update:

- `new_name`
- `color`
- `description`
- `priority`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupLabel`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupLabel`

`gitlab: Gitlab`

`update(name: Optional[str], new_data: Optional[Dict[str, Any]] = None, **kwargs: Any) → Dict[str, Any]`

Update a Label on the server.

Parameters

- `name (Optional[str])` – The name of the label
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)
- `new_data (Optional[Dict[str, Any]])` –
- `**kwargs` –

Return type

`Dict[str, Any]`

```
class gitlab.v4.objects.GroupManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: CRUDMixin, RESTManager
```

Object listing filters

- skip_groups
- all_available
- search
- order_by
- sort
- statistics
- owned
- with_custom_attributes
- min_access_level
- top_level_only

Object Creation

Required attributes for object create:

- name
- path

Optional attributes for object create:

- description
- membership_lock
- visibility
- share_with_group_lock
- require_two_factor_authentication
- two_factor_grace_period
- project_creation_level
- auto_devops_enabled
- subgroup_creation_level
- emails_disabled
- avatar
- mentions_disabled
- lfs_enabled
- request_access_enabled
- parent_id
- default_branch_protection
- shared_runners_minutes_limit
- extra_shared_runners_minutes_limit

Object update

Optional attributes for object update:

- name
- path
- description
- membership_lock
- share_with_group_lock
- visibility
- require_two_factor_authentication
- two_factor_grace_period
- project_creation_level
- auto_devops_enabled
- subgroup_creation_level
- emails_disabled
- avatar
- mentions_disabled
- lfs_enabled
- request_access_enabled
- default_branch_protection
- file_template_project_id
- shared_runners_minutes_limit
- extra_shared_runners_minutes_limit
- prevent_forking_outside_group
- shared_runners_setting

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → `Group`

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`Group`

`gitlab: Gitlab`

`import_group(file: BinaryIO, path: str, name: str, parent_id: Optional[Union[int, str]] = None, **kwargs: Any) → Union[Dict[str, Any], Response]`

Import a group from an archive file.

Parameters

- **file (BinaryIO)** – Data or file object containing the group
- **path (str)** – The path for the new group to be imported.
- **name (str)** – The name for the new group.
- **parent_id (Optional[Union[int, str]])** – ID of a parent group that the group will be imported into.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabImportError** – If the server failed to perform the request

Returns

A representation of the import status.

Return type

`Union[Dict[str, Any], Response]`

`class gitlab.v4.objects.GroupMember(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

`manager: RESTManager`

`class gitlab.v4.objects.GroupMemberAll(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –

- `created_from_list (bool) –`
- `lazy (bool) –`

manager: `RESTManager`

class `gitlab.v4.objects.GroupMemberAllManager(gl: Gitlab, parent: Optional[RESTObject] = None)`
Bases: `RetrieveMixin, RESTManager`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

get(`id: Union[str, int], lazy: bool = False, **kwargs: Any`) → `GroupMemberAll`

Retrieve a single object.

Parameters

- `id (Union[str, int]) –` ID of the object to retrieve
- `lazy (bool) –` If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupMemberAll`

gitlab: `Gitlab`

class `gitlab.v4.objects.GroupMemberManager(gl: Gitlab, parent: Optional[RESTObject] = None)`
Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `access_level`
- `user_id`

Optional attributes for object create:

- `expires_at`
- `tasks_to_be_done`

Object update

Required attributes for object update:

- `access_level`

Optional attributes for object update:

- `expires_at`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupMember`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupMember`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupMergeRequest(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.GroupMergeRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `ListMixin, RESTManager`

Object listing filters

- `state`
- `order_by`
- `sort`
- `milestone`
- `view`

- labels
- created_after
- created_before
- updated_after
- updated_before
- scope
- author_id
- assignee_id
- approver_ids
- approved_by_ids
- my_reaction_emoji
- source_branch
- target_branch
- search
- wip

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.GroupMilestone(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`issues(**kwargs: Any) → RESTObjectList`

List issues related to this milestone.

Parameters

- `all` – If True, return all the items, without pagination
- `per_page` – Number of items to retrieve per request
- `page` – ID of the page to return (starts with page 1)
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

The list of issues

Return type

`RESTObjectList`

`manager: RESTManager`

`merge_requests(**kwargs: Any) → RESTObjectList`

List the merge requests related to this milestone.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

The list of merge requests

Return type

`RESTObjectList`

`class gitlab.v4.objects.GroupMilestoneManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object listing filters

- `iids`
- `state`
- `search`

Object Creation

Required attributes for object create:

- `title`

Optional attributes for object create:

- `description`
- `due_date`
- `start_date`

Object update

Optional attributes for object update:

- `title`
- `description`

- `due_date`
- `start_date`
- `state_event`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupMilestone`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupMilestone`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupNotificationSettings(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `NotificationSettings`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.GroupNotificationSettingsManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `NotificationSettingsManager`

Object Creation

Object update

Optional attributes for object update:

- `level`

- notification_email
- new_note
- new_issue
- reopen_issue
- close_issue
- reassign_issue
- new_merge_request
- reopen_merge_request
- close_merge_request
- reassign_merge_request
- merge_merge_request

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → GroupNotificationSettings`

Retrieve a single object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupNotificationSettings`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupPackage(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.GroupPackageManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- `exclude_subgroups`
- `order_by`
- `sort`
- `package_type`
- `package_name`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`gitlab: Gitlab`

```
class gitlab.v4.objects.GroupProject(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

`manager: RESTManager`

```
class gitlab.v4.objects.GroupProjectManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- `archived`
- `visibility`
- `order_by`
- `sort`
- `search`
- `simple`
- `owned`
- `starred`
- `with_custom_attributes`
- `include_subgroups`
- `with_issues_enabled`

- `with_merge_requests_enabled`
- `with_shared`
- `min_access_level`
- `with_security_reports`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`gitlab: Gitlab`

```
class gitlab.v4.objects.GroupPushRules(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

`manager: RESTManager`

```
class gitlab.v4.objects.GroupPushRulesManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `GetWithoutIdMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager`

Object Creation

Optional attributes for object create:

- `deny_delete_tag`
- `member_check`
- `prevent_secrets`
- `commit_message_regex`
- `commit_message_negative_regex`
- `branch_name_regex`
- `author_email_regex`
- `file_name_regex`
- `max_file_size`
- `commit_committer_check`
- `reject_unsigned_commits`

Object update

Optional attributes for object update:

- deny_delete_tag
- member_check
- prevent_secrets
- commit_message_regex
- commit_message_negative_regex
- branch_name_regex
- author_email_regex
- file_name_regex
- max_file_size
- commit_committer_check
- reject_unsigned_commits

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → GroupPushRules`

Retrieve a single object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupPushRules`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupRegistryRepositoryManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `ListMixin, RESTManager`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.GroupRunner(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –
- **lazy** ([bool](#)) –

manager: [RESTManager](#)

```
class gitlab.v4.objects.GroupRunnerManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: [ListMixin](#), [RESTManager](#)

Object listing filters

- scope
- tag_list

Object Creation

Required attributes for object create:

- runner_id

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** ([Optional\[RESTObject\]](#)) –

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.GroupSAMLGroupLink(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: [ObjectDeleteMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –
- **lazy** ([bool](#)) –

manager: [RESTManager](#)

```
class gitlab.v4.objects.GroupSAMLGroupLinkManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: [NoUpdateMixin](#), [RESTManager](#)

Object Creation

Required attributes for object create:

- saml_group_name
- access_level

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupSAMLGroupLink`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupSAMLGroupLink`

`class gitlab.v4.objects.GroupSubgroup(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

`class gitlab.v4.objects.GroupSubgroupManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `ListMixin, RESTManager`

Object listing filters

- `skip_groups`
- `all_available`
- `search`
- `order_by`
- `sort`
- `statistics`
- `owned`
- `with_custom_attributes`

- `min_access_level`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

```
class gitlab.v4.objects.GroupVariable(manager: RESTManager, attrs: Dict[str, Any], *,  
created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.GroupVariableManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `key`
- `value`

Optional attributes for object create:

- `protected`
- `variable_type`
- `masked`

Object update

Required attributes for object update:

- `key`
- `value`

Optional attributes for object update:

- `protected`
- `variable_type`
- `masked`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → GroupVariable

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupVariable

gitlab: Gitlab

class gitlab.v4.objects.GroupWiki(*manager*: RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False, *lazy*: bool = False)

Bases: SaveMixin, ObjectDeleteMixin, RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: RESTManager

class gitlab.v4.objects.GroupWikiManager(*gl*: Gitlab, *parent*: Optional[RESTObject] = None)

Bases: CRUDMixin, RESTManager

Object listing filters

- with_content

Object Creation

Required attributes for object create:

- title
- content

Optional attributes for object create:

- format

Object update

Optional attributes for object update:

- title
- content

- `format`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupWiki`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupWiki`

`gitlab: Gitlab`

`class gitlab.v4.objects.Hook(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.HookManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `NoUpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `url`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → Hook
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`Hook`

gitlab: `Gitlab`

```
class gitlab.v4.objects.Issue(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.IssueManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, RESTManager`

Object listing filters

- `state`
- `labels`
- `milestone`
- `scope`
- `author_id`
- `assignee_id`
- `my_reaction_emoji`
- `iids`
- `order_by`
- `sort`
- `search`

- `created_after`
- `created_before`
- `updated_after`
- `updated_before`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → Issue`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`Issue`

`gitlab: Gitlab`

`class gitlab.v4.objects.IssuesStatistics(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RefreshMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.IssuesStatisticsManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `GetWithoutIdMixin, RESTManager`

Object listing filters

- `iids`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(**kwargs: Any) → IssuesStatistics`

Retrieve a single object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`IssuesStatistics`

`gitlab: Gitlab`

`class gitlab.v4.objects.Key(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

`manager: RESTManager`

`class gitlab.v4.objects.KeyManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `GetMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Optional[Union[int, str]] = None, lazy: bool = False, **kwargs: Any) → Key`

Retrieve a single object.

Parameters

- **id** (`Optional[Union[int, str]]`) – ID of the object to retrieve

- **lazy (bool)** – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Key

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.LDAPGroup(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                bool = False, lazy: bool = False)
```

Bases: [RESTObject](#)

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

manager: [RESTManager](#)

```
class gitlab.v4.objects.LDAPGroupManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: [RESTManager](#)

Object listing filters

- search
- provider

Object Creation

Object update

Parameters

- **gl (Gitlab)** –
- **parent (Optional[RESTObject])** –

gitlab: [Gitlab](#)

list(kwargs: Any) → Union[List[LDAPGroup], RESTObjectList]**

Retrieve a list of objects.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)

- **iterator** – If set to True and no pagination option is defined, return a generator instead of a list
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The list of objects, or a generator if *iterator* is True

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server cannot perform the request

Return type

Union[`List[LDAPGroup]`, `RESTObjectList`*]*

```
class gitlab.v4.objects.License(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

manager: `RESTManager`

```
class gitlab.v4.objects.LicenseManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin`, `RESTManager`

Object listing filters

- popular

Object Creation**Object update****Parameters**

- **gl (Gitlab)** –
- **parent (Optional[RESTObject])** –

get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → License

Retrieve a single object.

Parameters

- **id (Union[str, int])** – ID of the object to retrieve
- **lazy (bool)** – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[License](#)

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.MergeRequest(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                bool = False, lazy: bool = False)
```

Bases: [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –
- **lazy** ([bool](#)) –

manager: [RESTManager](#)

```
class gitlab.v4.objects.MergeRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: [ListMixin](#), [RESTManager](#)

Object listing filters

- **state**
- **order_by**
- **sort**
- **milestone**
- **view**
- **labels**
- **with_labels_details**
- **with_merge_status_recheck**
- **created_after**
- **created_before**
- **updated_after**
- **updated_before**
- **scope**
- **author_id**
- **author_username**
- **assignee_id**
- **approver_ids**
- **approved_by_ids**
- **reviewer_id**
- **reviewer_username**

- `my_reaction_emoji`
- `source_branch`
- `target_branch`
- `search`
- `in`
- `wip`
- `not`
- `environment`
- `deployed_before`
- `deployed_after`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.Namespace(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.NamespaceManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, RESTManager`

Object listing filters

- `search`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

exists(*namespace*: str, ***kwargs*: Any) → Namespace

Get existence of a namespace by path.

Parameters

- **namespace** (str) – The path to the namespace.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

Data on namespace existence returned from the server.

Return type

Namespace

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → Namespace

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Namespace

gitlab: Gitlab

class gitlab.v4.objects.NotificationSettings(*manager*: RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False, *lazy*: bool = False)

Bases: SaveMixin, RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: RESTManager

```
class gitlab.v4.objects.NotificationSettingsManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `GetWithoutIdMixin, UpdateMixin, RESTManager`

Object Creation

Object update

Optional attributes for object update:

- `level`
- `notification_email`
- `new_note`
- `new_issue`
- `reopen_issue`
- `close_issue`
- `reassign_issue`
- `new_merge_request`
- `reopen_merge_request`
- `close_merge_request`
- `reassign_merge_request`
- `merge_merge_request`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → NotificationSettings`

Retrieve a single object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`NotificationSettings`

`gitlab: Gitlab`

```
class gitlab.v4.objects.PagesDomain(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class gitlab.v4.objects.PagesDomainManager(`gl: Gitlab, parent: Optional[RESTObject] = None`)
Bases: `ListMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

class gitlab.v4.objects.PersonalAccessToken(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)
Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class gitlab.v4.objects.PersonalAccessTokenManager(`gl: Gitlab, parent: Optional[RESTObject] = None`)
Bases: `DeleteMixin, RetrieveMixin, RESTManager`

Object listing filters

- `user_id`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int], lazy: bool = False, **kwargs: Any`) → `PersonalAccessToken`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve

- **lazy (bool)** – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

PersonalAccessToken

gitlab: *Gitlab*

```
class gitlab.v4.objects.Project(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RefreshMixin, SaveMixin, ObjectDeleteMixin, RepositoryMixin, RESTObject*

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

access_tokens: *ProjectAccessTokenManager*

accessrequests: *ProjectAccessRequestManager*

additionalstatistics: *ProjectAdditionalStatisticsManager*

approvalrules: *ProjectApprovalRuleManager*

approvals: *ProjectApprovalManager*

archive(kwargs: Any) → None**

Archive a project.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server failed to perform the request

Return type

None

artifact(*args: Any, **kwargs: Any) → Optional[bytes]

Parameters

- **args (Any)** –
- **kwargs (Any)** –

Return type

Optional[bytes]

artifacts: *ProjectArtifactManager*

audit_events: *ProjectAuditEventManager*

badges: *ProjectBadgeManager*

boards: *ProjectBoardManager*

branches: *ProjectBranchManager*

ci_lint: *ProjectCiLintManager*

clusters: *ProjectClusterManager*

commits: *ProjectCommitManager*

create_fork_relation(*forked_from_id: int*, *kwargs: Any*) → None**

Create a forked from/to relation between existing projects.

Parameters

- **forked_from_id (*int*)** – The ID of the project that was forked from
- ****kwargs (*Any*)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the relation could not be created

Return type

None

customattributes: *ProjectCustomAttributeManager*

delete_fork_relation(*kwargs: Any*) → None**

Delete a forked relation between existing projects.

Parameters

****kwargs (*Any*)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server failed to perform the request

Return type

None

deployments: *ProjectDeploymentManager*

deploytokens: *ProjectDeployTokenManager*

environments: *ProjectEnvironmentManager*

events: *ProjectEventManager*

exports: *ProjectExportManager*

```
files: ProjectFileManager
forks: ProjectForkManager
generic_packages: GenericPackageManager
groups: ProjectGroupManager
hooks: ProjectHookManager
housekeeping(**kwargs: Any) → None
```

Start the housekeeping task.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabHousekeepingError** – If the server failed to perform the request

Return type

None

```
imports: ProjectImportManager
```

```
integrations: ProjectIntegrationManager
```

```
invitations: ProjectInvitationManager
```

```
issues: ProjectIssueManager
```

```
issues_statistics: ProjectIssuesStatisticsManager
```

```
iterations: ProjectIterationManager
```

```
jobs: ProjectJobManager
```

```
keys: ProjectKeyManager
```

```
labels: ProjectLabelManager
```

```
languages(**kwargs: Any) → Union[Dict[str, Any], Response]
```

Get languages used in the project with percentage value.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Return type

Union[Dict[str, Any], Response]

```
members: ProjectMemberManager
```

```
members_all: ProjectMemberAllManager
```

```
merge_trains: ProjectMergeTrainManager
```

`mergerequests: ProjectMergeRequestManager`

`milestones: ProjectMilestoneManager`

`mirror_pull(**kwargs: Any) → None`

Start the pull mirroring process for the project.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server failed to perform the request

Return type

`None`

`mirror_pull_details(**kwargs: Any) → Dict[str, Any]`

Get a project's pull mirror details.

Introduced in GitLab 15.5.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

Returns

`dict` of the parsed json returned by the server

Return type

`Dict[str, Any]`

`notes: ProjectNoteManager`

`notificationsettings: ProjectNotificationSettingsManager`

`packages: ProjectPackageManager`

`pagesdomains: ProjectPagesDomainManager`

`pipelines: ProjectPipelineManager`

`pipelineschedules: ProjectPipelineScheduleManager`

`protected_environments: ProjectProtectedEnvironmentManager`

`protectedbranches: ProjectProtectedBranchManager`

`protectedtags: ProjectProtectedTagManager`

`pushrules: ProjectPushRulesManager`

`releases: ProjectReleaseManager`

`remote_mirrors: ProjectRemoteMirrorManager`

repositories: *ProjectRegistryRepositoryManager*

resource_groups: *ProjectResourceGroupManager*

restore(kwargs: Any) → None**

Restore a project marked for deletion.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabRestoreError** – If the server failed to perform the request

Return type

None

runners: *ProjectRunnerManager*

search(scope: str, search: str, **kwargs: Any) → Union[GitlabList, List[Dict[str, Any]]]

Search the project resources matching the provided string.'

Parameters

- **scope (str)** – Scope of the search
- **search (str)** – Search string
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSearchError** – If the server failed to perform the request

Returns

A list of dicts describing the resources found.

Return type

Union[GitlabList, List[Dict[str, Any]]]

secure_files: *ProjectSecureFileManager*

services: *ProjectServiceManager*

share(group_id: int, group_access: int, expires_at: Optional[str] = None, **kwargs: Any) → None

Share the project with a group.

Parameters

- **group_id (int)** – ID of the group.
- **group_access (int)** – Access level for the group.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)
- **expires_at (Optional[str])** –
- ****kwargs** –

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabCreateError** – If the server failed to perform the request

Return type

None

snapshot(*wiki: bool = False*, *streamed: bool = False*, *action: Optional[Callable[[bytes], None]] = None*, *chunk_size: int = 1024*, **, iterator: bool = False*, ***kwargs: Any*) → *Optional[Union[bytes, Iterator[Any]]]*

Return a snapshot of the repository.

Parameters

- **wiki** (*bool*) – If True return the wiki repository
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment.
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[[bytes], None]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the content could not be retrieved

Returns

The uncompressed tar archive of the repository

Return type

Optional[Union[bytes, Iterator[Any]]]

snippets: *ProjectSnippetManager*

star(***kwargs: Any*) → *None*

Star a project.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server failed to perform the request

Return type

None

storage: *ProjectStorageManager*

tags: *ProjectTagManager*

transfer(*to_namespace: Union[int, str]*, ***kwargs: Any*) → *None*

Transfer a project to the given namespace ID

Parameters

- **to_namespace** (*Union[int, str]*) – ID or path of the namespace to transfer the

- **to** (*project*) –
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTransferProjectError** – If the project could not be transferred

Return type

None

transfer_project(**args*: *Any*, ***kwargs*: *Any*) → None**Parameters**

- **args** (*Any*) –
- **kwargs** (*Any*) –

Return type

None

trigger_pipeline(*ref*: *str*, *token*: *str*, *variables*: *Optional[Dict[str, Any]]* = *None*, ***kwargs*: *Any*) → *ProjectPipeline*

Trigger a CI build.

See <https://gitlab.com/help/ci/triggers/README.md#trigger-a-build>**Parameters**

- **ref** (*str*) – Commit to build; can be a branch name or a tag
- **token** (*str*) – The trigger token
- **variables** (*Optional[Dict[str, Any]]*) – Variables passed to the build script
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server failed to perform the request

Return type*ProjectPipeline***triggers:** *ProjectTriggerManager***unarchive**(***kwargs*: *Any*) → None

Unarchive a project.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server failed to perform the request

Return type

None

unshare(*group_id*: int, ***kwargs*: Any) → None

Delete a shared project link within a group.

Parameters

- **group_id** (int) – ID of the group.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server failed to perform the request

Return type

None

unstar(***kwargs*: Any) → None

Unstar a project.

Parameters

- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server failed to perform the request

Return type

None

upload(*filename*: str, *filedata*: Optional[bytes] = None, *filepath*: Optional[str] = None, ***kwargs*: Any) → Dict[str, Any]

Upload the specified file into the project.

Note: Either *filedata* or *filepath* *MUST* be specified.

Parameters

- **filename** (str) – The name of the file being uploaded
- **filedata** (Optional[bytes]) – The raw data of the file being uploaded
- **filepath** (Optional[str]) – The path to a local file to upload (optional)
- **kwargs** (Any) –

Raises

- **GitlabConnectionError** – If the server cannot be reached
- **GitlabUploadError** – If the file upload fails
- **GitlabUploadError** – If *filedata* and *filepath* are not specified
- **GitlabUploadError** – If both *filedata* and *filepath* are specified

Returns

- **alt** - The alternate text for the upload
- **url** - The direct url to the uploaded file

- `markdown` - Markdown for the uploaded file

Return type

A dict with the keys

`users: ProjectUserManager`

`variables: ProjectVariableManager`

`wikis: ProjectWikiManager`

`class gitlab.v4.objects.ProjectAccessRequest(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `AccessRequestMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectAccessRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `ListMixin, CreateMixin, DeleteMixin, RESTManager`

Object Creation**Object update****Parameters**

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectAccessToken(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectAccessTokenManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `ListMixin, CreateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- name
- scopes

Optional attributes for object create:

- access_level
- expires_at

Object update

Parameters

- gl ([Gitlab](#)) –
- parent (*Optional[RESTObject]*) –

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.ProjectAdditionalStatistics(manager: RESTManager, attrs: Dict[str, Any],  
*, created_from_list: bool = False, lazy: bool =  
False)
```

Bases: [RefreshMixin](#), [RESTObject](#)

Parameters

- manager ([RESTManager](#)) –
- attrs (*Dict[str, Any]*) –
- created_from_list (*bool*) –
- lazy (*bool*) –

manager: [RESTManager](#)

```
class gitlab.v4.objects.ProjectAdditionalStatisticsManager(gl: Gitlab, parent:  
Optional[RESTObject] = None)
```

Bases: [GetWithoutIdMixin](#), [RESTManager](#)

Object Creation

Object update

Parameters

- gl ([Gitlab](#)) –
- parent (*Optional[RESTObject]*) –

get(**kwargs: Any) → [ProjectAdditionalStatistics](#)

Retrieve a single object.

Parameters

**kwargs (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type

ProjectAdditionalStatistics

gitlab: *Gitlab***class** gitlab.v4.objects.ProjectApproval(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)Bases: *SaveMixin, RESTObject***Parameters**

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager***class** gitlab.v4.objects.ProjectApprovalManager(*gl: Gitlab, parent: Optional[RESTObject] = None*)Bases: *GetWithoutIdMixin, UpdateMixin, RESTManager***Object Creation****Object update**

Optional attributes for object update:

- approvals_before_merge
- reset_approvals_on_push
- disable_overriding_approvers_per_merge_request
- merge_requests_author_approval
- merge_requests_disable_committers_approval

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → ProjectApproval**

Retrieve a single object.

Parameters****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)**Returns**

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectApproval

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectApprovalRule(manager: RESTManager, attrs: Dict[str, Any], *,  
                                             created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectApprovalRuleManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                   None)
```

Bases: *ListMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- `name`
- `approvals_required`

Optional attributes for object create:

- `user_ids`
- `group_ids`
- `protected_branch_ids`

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectArtifact(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Dummy object to manage custom actions on artifacts

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectArtifactManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
delete(**kwargs: Any) → None
```

Delete the project's artifacts on the server.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

None

```
download(ref_name: str, job: str, streamed: bool = False, action: Optional[Callable[[bytes], None]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]
```

Get the job artifacts archive from a specific tag or branch.

Parameters

- **ref_name** (*str*) – Branch or tag name in repository. HEAD or SHA references
- **supported.** (*are not*) –
- **job** (*str*) – The name of the job.
- **job_token** – Job token for multi-project pipeline triggers.
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[[bytes], None]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns

The artifacts if *streamed* is False, *None* otherwise.

Return type

Optional[Union[bytes, Iterator[Any]]]

gitlab: *Gitlab*

```
raw(ref_name: str, artifact_path: str, job: str, streamed: bool = False, action: Optional[Callable[[bytes], None]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]
```

Download a single artifact file from a specific tag or branch from within the job's artifacts archive.

Parameters

- **ref_name** (*str*) – Branch or tag name in repository. HEAD or SHA references are not supported.
- **artifact_path** (*str*) – Path to a file inside the artifacts archive.
- **job** (*str*) – The name of the job.
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[[bytes], None]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns

The artifact if *streamed* is False, None otherwise.

Return type

Optional[Union[bytes, Iterator[Any]]]

```
class gitlab.v4.objects.ProjectAudit(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ProjectAuditEvent*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectAuditEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –

- `created_from_list (bool) –`
- `lazy (bool) –`

manager: `RESTManager`

class `gitlab.v4.objects.ProjectAuditEventManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `RetrieveMixin, RESTManager`

Object listing filters

- `created_after`
- `created_before`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

get(`id: Union[str, int], lazy: bool = False, **kwargs: Any`) → `ProjectAuditEvent`

Retrieve a single object.

Parameters

- `id (Union[str, int]) –` ID of the object to retrieve
- `lazy (bool) –` If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectAuditEvent`

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectAuditManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `ProjectAuditEventManager`

Object listing filters

- `created_after`
- `created_before`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`

- **parent** (*Optional[RESTObject]*) –
gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectBadge`(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectBadgeManager`(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: `BadgeRenderMixin, CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `link_url`
- `image_url`

Object update

Optional attributes for object update:

- `link_url`
- `image_url`

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → `ProjectBadge`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type
ProjectBadge

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectBoard`(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

lists: `ProjectBoardListManager`

class `gitlab.v4.objects.ProjectBoardList`(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectBoardListManager`(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: `CRUDMixin, RESTManager`

Object Creation

Mutually exclusive attributes for object create:

- `label_id`
- `assignee_id`
- `milestone_id`

Object update

Required attributes for object update:

- `position`

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectBoardList`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectBoardList`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectBoardManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectBoard`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectBoard`

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectBranch(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectBranchManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- **branch**
- **ref**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectBranch*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectBranch

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectCiLint(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectCiLintManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin*, *CreateMixin*, *RESTManager*

Object Creation

Required attributes for object create:

- **content**

Optional attributes for object create:

- **dry_run**
- **include_jobs**
- **ref**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → ProjectCiLint**

Retrieve a single object.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectCiLint

gitlab: Gitlab

validate(*args: Any, **kwargs: Any) → None

Raise an error if the Project CI Lint results are not valid.

This is a custom python-gitlab method to wrap lint endpoints.

Parameters

- **args** (*Any*) –
- **kwargs** (*Any*) –

Return type

None

```
class gitlab.v4.objects.ProjectCluster(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectClusterManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- **name**
- **platform_kubernetes_attributes**

Optional attributes for object create:

- **domain**
- **enabled**
- **managed**
- **environment_scope**

Object update

Optional attributes for object update:

- **name**
- **domain**
- **management_project_id**
- **platform_kubernetes_attributes**
- **environment_scope**

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

create(*data*: *Optional[Dict[str, Any]]* = *None*, ***kwargs*: *Any*) → *ProjectCluster*

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – Parameters to send to the server to create the resource
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo or ‘ref_name’, ‘stage’, ‘name’, ‘all’)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Returns

A new instance of the manage object class build with
the data sent by the server

Return type

ProjectCluster

get(*id*: *Union[str, int]*, *lazy*: *bool* = *False*, ***kwargs*: *Any*) → *ProjectCluster*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don’t request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectCluster

gitlab: *Gitlab*

class gitlab.v4.objects.ProjectCommit(*manager*: *RESTManager*, *attrs*: *Dict[str, Any]*, *,
created_from_list: *bool* = *False*, *lazy*: *bool* = *False*)

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

cherry_pick(*branch: str, **kwargs: Any*) → None

Cherry-pick a commit into a branch.

Parameters

- **branch (str)** – Name of target branch
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCherryPickError** – If the cherry-pick could not be performed

Return type

None

comments: *ProjectCommitCommentManager*

diff(***kwargs: Any*) → Union[*GitlabList*, List[Dict[str, Any]]]

Generate the commit diff.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the diff could not be retrieved

Returns

The changes done in this commit

Return type

Union[*GitlabList*, List[Dict[str, Any]]]

discussions: *ProjectCommitDiscussionManager*

merge_requests(***kwargs: Any*) → Union[*GitlabList*, List[Dict[str, Any]]]

List the merge requests related to the commit.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the references could not be retrieved

Returns

The merge requests related to the commit.

Return type

Union[*GitlabList*, List[Dict[str, Any]]]

refs(*type: str = 'all', **kwargs: Any*) → Union[*GitlabList*, List[Dict[str, Any]]]

List the references the commit is pushed to.

Parameters

- **type (str)** – The scope of references ('branch', 'tag' or 'all')
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the references could not be retrieved

Returns

The references the commit is pushed to.

Return type

Union[GitlabList, List[Dict[str, Any]]]

revert(*branch: str, **kwargs: Any*) → *Union[Dict[str, Any], Response]*

Revert a commit on a given branch.

Parameters

- **branch (str)** – Name of target branch
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabRevertError** – If the revert could not be performed

Returns

The new commit data (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

signature(***kwargs: Any*) → *Union[Dict[str, Any], Response]*

Get the signature of the commit.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the signature could not be retrieved

Returns

The commit's signature data

Return type

Union[Dict[str, Any], Response]

statuses: *ProjectCommitStatusManager*

class *gitlab.v4.objects.ProjectCommitComment*(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *RESTObject*

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

```
manager: RESTManager

class gitlab.v4.objects.ProjectCommitCommentManager(gl: Gitlab, parent: Optional[RESTObject] = None)

Bases: ListMixin, CreateMixin, RESTManager
```

Object Creation

Required attributes for object create:

- note

Optional attributes for object create:

- path
- line
- line_type

Object update

Parameters

- gl (Gitlab) –
- parent (Optional[RESTObject]) –

gitlab: Gitlab

```
class gitlab.v4.objects.ProjectCommitDiscussion(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: RESTObject

Parameters

- manager (RESTManager) –
- attrs (Dict[str, Any]) –
- created_from_list (bool) –
- lazy (bool) –

notes: ProjectCommitDiscussionNoteManager

```
class gitlab.v4.objects.ProjectCommitDiscussionManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: RetrieveMixin, CreateMixin, RESTManager

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at

Object update

Parameters

- gl (Gitlab) –
- parent (Optional[RESTObject]) –

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → ProjectCommitDiscussion

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectCommitDiscussion

gitlab: Gitlab

class gitlab.v4.objects.ProjectCommitDiscussionNote(*manager*: RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False, *lazy*: bool = False)

Bases: SaveMixin, ObjectDeleteMixin, RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: RESTManager

class gitlab.v4.objects.ProjectCommitDiscussionNoteManager(*gl*: Gitlab, *parent*: Optional[RESTObject] = None)

Bases: GetMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at
- position

Object update

Required attributes for object update:

- body

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [ProjectCommitDiscussionNote](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type

[ProjectCommitDiscussionNote](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.ProjectCommitManager](#)(*gl: Gitlab, parent: Optional[RESTObject] = None*)
Bases: [RetrieveMixin](#), [CreateMixin](#), [RESTManager](#)

Object listing filters

- `ref_name`
- `since`
- `until`
- `path`
- `with_stats`
- `first_parent`
- `order`
- `trailers`

Object Creation

Required attributes for object create:

- `branch`
- `commit_message`
- `actions`

Optional attributes for object create:

- `author_email`
- `author_name`

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [ProjectCommit](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[ProjectCommit](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.ProjectCommitStatus](#)(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)

Bases: [RefreshMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: [RESTManager](#)

class [gitlab.v4.objects.ProjectCommitStatusManager](#)(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)

Bases: [ListMixin](#), [CreateMixin](#), [RESTManager](#)

Object Creation

Required attributes for object create:

- **state**

Optional attributes for object create:

- **description**
- **name**
- **context**
- **ref**

- `target_url`
- `coverage`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → ProjectCommitStatus`

Create a new object.

Parameters

- `data (Optional[Dict[str, Any]])` – Parameters to send to the server to create the resource
- `**kwargs (Any)` – Extra options to send to the server (e.g. `sudo` or `'ref_name'`, `'stage'`, `'name'`, `'all'`)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

Returns

A new instance of the `manage` object class build with the data sent by the server

Return type

`ProjectCommitStatus`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectCustomAttribute(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectCustomAttributeManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, SetMixin, DeleteMixin, RESTManager`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –

- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectCustomAttribute*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectCustomAttribute

gitlab: *Gitlab*

class *gitlab.v4.objects.ProjectDeployToken*(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

class *gitlab.v4.objects.ProjectDeployTokenManager*(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)

Bases: *RetrieveMixin, CreateMixin, DeleteMixin, RESTManager*

Object listing filters

- **scopes**

Object Creation

Required attributes for object create:

- **name**
- **scopes**

Optional attributes for object create:

- **expires_at**
- **username**

Object update

Parameters

- **g1** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [ProjectDeployToken](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[ProjectDeployToken](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.ProjectDeployment](#)(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)

Bases: [SaveMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

approval(*status: str*, *comment: Optional[str] = None*, *represented_as: Optional[str] = None*, ***kwargs: Any*) → *Dict[str, Any]*

Approve or reject a blocked deployment.

Parameters

- **status** (*str*) – Either “approved” or “rejected”
- **comment** (*Optional[str]*) – A comment to go with the approval
- **represented_as** (*Optional[str]*) – The name of the User/Group/Role to use for the approval, when the user belongs to multiple approval rules.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMRAApprovalError** – If the approval failed

Returns

A dict containing the result.

Return type

Dict[str, Any]

<https://docs.gitlab.com/ee/api/deployments.html#approve-or-reject-a-blocked-deployment>

mergerequests: *ProjectDeploymentMergeRequestManager*

```
class gitlab.v4.objects.ProjectDeploymentManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: RetrieveMixin, CreateMixin, UpdateMixin, RESTManager
```

Object listing filters

- `order_by`
- `sort`
- `updated_after`
- `updated_before`
- `environment`
- `status`

Object Creation

Required attributes for object create:

- `sha`
- `ref`
- `tag`
- `status`
- `environment`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → *ProjectDeployment*

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

ProjectDeployment

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectDeploymentMergeRequest(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `MergeRequest`

Parameters

- `manager` (`RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –
- `lazy` (`bool`) –

`manager: RESTManager`

```
class gitlab.v4.objects.ProjectDeploymentMergeRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `MergeRequestManager`

Object listing filters

- `state`
- `order_by`
- `sort`
- `milestone`
- `view`
- `labels`
- `with_labels_details`
- `with_merge_status_recheck`
- `created_after`
- `created_before`
- `updated_after`
- `updated_before`
- `scope`
- `author_id`
- `author_username`
- `assignee_id`
- `approver_ids`
- `approved_by_ids`
- `reviewer_id`
- `reviewer_username`
- `my_reaction_emoji`
- `source_branch`

- `target_branch`
- `search`
- `in`
- `wip`
- `not`
- `environment`
- `deployed_before`
- `deployed_after`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectEnvironment(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`stop(**kwargs: Any) → Union[Dict[str, Any], Response]`

Stop the environment.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabStopError` – If the operation failed

Returns

A dict of the result.

Return type

`Union[Dict[str, Any], Response]`

```
class gitlab.v4.objects.ProjectEnvironmentManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager`

Object listing filters

- `name`

- `search`
- `states`

Object Creation

Required attributes for object create:

- `name`

Optional attributes for object create:

- `external_url`

Object update

Optional attributes for object update:

- `name`
- `external_url`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectEnvironment`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectEnvironment`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `Event`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectEventManager`(`gl: Gitlab`, `parent: Optional[RESTObject] = None`)

Bases: `EventManager`

Object listing filters

- `action`
- `target_type`
- `before`
- `after`
- `sort`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectExport`(`manager: RESTManager`, `attrs: Dict[str, Any]`, *, `created_from_list: bool = False`, `lazy: bool = False`)

Bases: `DownloadMixin`, `RefreshMixin`, `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectExportManager`(`gl: Gitlab`, `parent: Optional[RESTObject] = None`)

Bases: `GetWithoutIdMixin`, `CreateMixin`, `RESTManager`

Object Creation

Optional attributes for object create:

- `description`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(kwargs: Any) → ProjectExport**

Retrieve a single object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectExport

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectFile(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*ProjectFileManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

branch: str

commit_message: str

decode() → bytes

Returns the decoded content of the file.

Returns

The decoded content.

Return type

bytes

delete(*branch: str, commit_message: str, **kwargs: Any*) → None

Delete the file from the server.

Parameters

- **branch** (*str*) – Branch from which the file will be removed
- **commit_message** (*str*) – Commit message for the deletion
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

None

file_path: str

manager: *ProjectFileManager*

save(*branch: str, commit_message: str, **kwargs: Any*) → None

Save the changes made to the file to the server.

The object is updated to match what the server returns.

Parameters

- **branch (str)** – Branch in which the file will be updated
- **commit_message (str)** – Message to send with the commit
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server cannot perform the request

Return type

None

class gitlab.v4.objects.ProjectFileManager(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: *GetMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- `file_path`
- `branch`
- `content`
- `commit_message`

Optional attributes for object create:

- `encoding`
- `author_email`
- `author_name`

Object update

Required attributes for object update:

- `file_path`
- `branch`
- `content`
- `commit_message`

Optional attributes for object update:

- `encoding`
- `author_email`
- `author_name`

Parameters

- `gl (Gitlab)` –

- **parent** (*Optional[RESTObject]*) –

blame(*file_path*: str, *ref*: str, ***kwargs*: Any) → List[Dict[str, Any]]

Return the content of a file for a commit.

Parameters

- **file_path** (str) – Path of the file to retrieve
- **ref** (str) – Name of the branch, tag or commit
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns

A list of commits/lines matching the file

Return type

List[Dict[str, Any]]

create(*data*: *Optional[Dict[str, Any]]* = None, ***kwargs*: Any) → ProjectFile

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – parameters to send to the server to create the resource
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

a new instance of the managed object class built with
the data sent by the server

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Return type

ProjectFile

delete(*file_path*: str, *branch*: str, *commit_message*: str, ***kwargs*: Any) → None

Delete a file on the server.

Parameters

- **file_path** (str) – Path of the file to remove
- **branch** (str) – Branch from which the file will be removed
- **commit_message** (str) – Commit message for the deletion
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

None

get(*file_path*: str, *ref*: str, ***kwargs*: Any) → [ProjectFile](#)

Retrieve a single file.

Parameters

- **file_path** (str) – Path of the file to retrieve
- **ref** (str) – Name of the branch, tag or commit
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the file could not be retrieved

Returns

The generated RESTObject

Return type

[ProjectFile](#)

gitlab: [Gitlab](#)

raw(*file_path*: str, *ref*: str, *streamed*: bool = False, *action*: Optional[Callable[..., Any]] = None, *chunk_size*: int = 1024, *, *iterator*: bool = False, ***kwargs*: Any) → Optional[Union[bytes, Iterator[Any]]]

Return the content of a file for a commit.

Parameters

- **ref** (str) – ID of the commit
- **filepath** – Path of the file to return
- **streamed** (bool) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (bool) – If True directly return the underlying response iterator
- **action** (Optional[Callable[..., Any]]) – Callable responsible of dealing with chunk of data
- **chunk_size** (int) – Size of each chunk
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)
- **file_path** (str) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the file could not be retrieved

Returns

The file content

Return type

Optional[Union[bytes, Iterator[Any]]]

update(*file_path*: str, *new_data*: Optional[Dict[str, Any]] = None, ***kwargs*: Any) → Dict[str, Any]

Update an object on the server.

Parameters

- **id** – ID of the object to update (can be None if not required)
- **new_data** (*Optional[Dict[str, Any]]*) – the update data for the object
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)
- **file_path** (*str*) –

Returns

The new object data (*not* a RESTObject)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server cannot perform the request

Return type

Dict[str, Any]

class gitlab.v4.objects.ProjectFork(*manager*: RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False, *lazy*: bool = False)

Bases: *RESTObject*

Parameters

- **manager** (RESTManager) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: RESTManager

class gitlab.v4.objects.ProjectForkManager(*gl*: Gitlab, *parent*: *Optional[RESTObject]* = None)

Bases: *CreateMixin, ListMixin, RESTManager*

Object listing filters

- **archived**
- **visibility**
- **order_by**
- **sort**
- **search**
- **simple**
- **owned**
- **membership**
- **starred**
- **statistics**
- **with_custom_attributes**

- `with_issues_enabled`
- `with_merge_requests_enabled`

Object Creation

Optional attributes for object create:

- `namespace`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → ProjectFork`

Creates a new object.

Parameters

- `data (Optional[Dict[str, Any]])` – Parameters to send to the server to create the resource
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

Returns

A new instance of the managed object class build with the data sent by the server

Return type

`ProjectFork`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectHook(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectHookManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `url`

Optional attributes for object create:

- `push_events`
- `issues_events`
- `confidential_issues_events`
- `merge_requests_events`
- `tag_push_events`
- `note_events`
- `job_events`
- `pipeline_events`
- `wiki_page_events`
- `enable_ssl_verification`
- `token`

Object update

Required attributes for object update:

- `url`

Optional attributes for object update:

- `push_events`
- `issues_events`
- `confidential_issues_events`
- `merge_requests_events`
- `tag_push_events`
- `note_events`
- `job_events`
- `pipeline_events`
- `wiki_events`
- `enable_ssl_verification`
- `token`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectHook`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.

- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectHook

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectImport(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: `RefreshMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectImportManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `GetWithoutIdMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(kwargs: Any) → ProjectImport**

Retrieve a single object.

Parameters

- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectImport

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectIntegration(manager: RESTManager, attrs: Dict[str, Any], *,  
    created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager` (`RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –
- `lazy` (`bool`) –

`manager:` `RESTManager`

```
class gitlab.v4.objects.ProjectIntegrationManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `GetMixin, UpdateMixin, DeleteMixin, ListMixin, RESTManager`

Object Creation

Object update

Parameters

- `gl` (`Gitlab`) –
- `parent` (`Optional[RESTObject]`) –

`available()` → `List[str]`

List the services known by python-gitlab.

Returns

The list of service code names.

Return type

`List[str]`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectIntegration`

Retrieve a single object.

Parameters

- `id` (`Union[str, int]`) – ID of the object to retrieve
- `lazy` (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectIntegration`

`gitlab:` `Gitlab`

```
class gitlab.v4.objects.ProjectInvitation(manager: RESTManager, attrs: Dict[str, Any], *,  
    created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin`, `ObjectDeleteMixin`, `RESTObject`

Parameters

- `manager` (`RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –
- `lazy` (`bool`) –

`manager:` `RESTManager`

```
class gitlab.v4.objects.ProjectInvitationManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `InvitationMixin`, `RESTManager`

Object listing filters

- `query`

Object Creation

Required attributes for object create:

- `access_level`

Optional attributes for object create:

- `expires_at`
- `invite_source`
- `tasks_to_be_done`
- `tasks_project_id`

Mutually exclusive attributes for object create:

- `email`
- `user_id`

Object update

Optional attributes for object update:

- `access_level`
- `expires_at`

Parameters

- `gl` (`Gitlab`) –
- `parent` (`Optional[RESTObject]`) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectInvitation
```

Retrieve a single object.

Parameters

- `id` (`Union[str, int]`) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectInvitation

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectIssue(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                     bool = False, lazy: bool = False)  
  
Bases:     UserAgentDetailMixin, SubscribableMixin, TodoMixin, TimeTrackingMixin,  
           ParticipantsMixin, SaveMixin, ObjectDeleteMixin, RESTObject
```

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

awardemojis: *ProjectIssueAwardEmojiManager*

closed_by(**kwargs: Any) → Dict[str, Any]

List merge requests that will close the issue when merged.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the merge requests could not be retrieved

Returns

The list of merge requests.

Return type

Dict[str, Any]

discussions: *ProjectIssueDiscussionManager*

links: *ProjectIssueLinkManager*

move(to_project_id: int, **kwargs: Any) → None

Move the issue to another project.

Parameters

- **to_project_id** (*int*) – ID of the target project
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the issue could not be moved

Return type

None

notes: *ProjectIssueNoteManager*

related_merge_requests(kwargs: Any) → Dict[str, Any]**

List merge requests related to the issue.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the merge requests could not be retrieved

Returns

The list of merge requests.

Return type

Dict[str, Any]

reorder(move_after_id: Optional[int] = None, move_before_id: Optional[int] = None, **kwargs: Any) → None

Reorder an issue on a board.

Parameters

- **move_after_id (Optional[int])** – ID of an issue that should be placed after this issue
- **move_before_id (Optional[int])** – ID of an issue that should be placed before this issue
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the issue could not be reordered

Return type

None

resource_iteration_events: ProjectIssueResourceIterationEventManager

resource_weight_events: ProjectIssueResourceWeightEventManager

resourcelabelevents: ProjectIssueResourceLabelEventManager

resourcemilestoneevents: ProjectIssueResourceMilestoneEventManager

resourcestateevents: ProjectIssueResourceStateEventManager

```
class gitlab.v4.objects.ProjectIssueAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectIssueAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, `**kwargs`: `Any`) → *ProjectIssueAwardEmoji*

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectIssueAwardEmoji`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectIssueDiscussion(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

notes: `ProjectIssueDiscussionNoteManager`

```
class gitlab.v4.objects.ProjectIssueDiscussionManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, CreateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `body`

Optional attributes for object create:

- `created_at`

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectIssueDiscussion
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectIssueDiscussion`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectIssueDiscussionNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –

```
    • attrs (Dict[str, Any]) –
    • created_from_list (bool) –
    • lazy (bool) –

manager: RESTManager

class gitlab.v4.objects.ProjectIssueDiscussionNoteManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: GetMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager
```

Object Creation

Required attributes for object create:

- `body`

Optional attributes for object create:

- `created_at`

Object update

Required attributes for object update:

- `body`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectIssueDiscussionNote
```

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectIssueDiscussionNote`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectIssueLink(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectIssueLinkManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, CreateMixin, DeleteMixin, RESTManager
```

Object Creation

Required attributes for object create:

- `target_project_id`
- `target_issue_iid`

Object update

Parameters

- `gl` (`Gitlab`) –
- `parent` (`Optional[RESTObject]`) –

create(`data: Dict[str, Any], **kwargs: Any`) → `Tuple[RESTObject, RESTObject]`

Create a new object.

Parameters

- `data` (`Dict[str, Any]`) – parameters to send to the server to create the resource
- `**kwargs` (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The source and target issues

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

Return type

`Tuple[RESTObject, RESTObject]`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectIssueManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: CRUDMixin, RESTManager
```

Object listing filters

- `iids`
- `state`
- `labels`
- `milestone`
- `scope`
- `author_id`

- assignee_id
- my_reaction_emoji
- order_by
- sort
- search
- created_after
- created_before
- updated_after
- updated_before

Object Creation

Required attributes for object create:

- title

Optional attributes for object create:

- description
- confidential
- assignee_ids
- assignee_id
- milestone_id
- labels
- created_at
- due_date
- merge_request_to_resolve_discussions_of
- discussion_to_resolve

Object update

Optional attributes for object update:

- title
- description
- confidential
- assignee_ids
- assignee_id
- milestone_id
- labels
- state_event
- updated_at
- due_date
- discussion_locked

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectIssue`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectIssue`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectIssueNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`awardemojis: ProjectIssueNoteAwardEmojiManager`

`class gitlab.v4.objects.ProjectIssueNoteAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager(gl: Gitlab, parent:  
Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin*, *RESTManager*

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectIssueNoteAwardEmoji
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIssueNoteAwardEmoji

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectIssueNoteManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin*, *RESTManager*

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at

Object update

Required attributes for object update:

- body

Parameters

- **gl** (*Gitlab*) –

- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectIssueNote*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIssueNote

gitlab: *Gitlab*

class gitlab.v4.objects.ProjectIssueResourceIterationEvent(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

class gitlab.v4.objects.ProjectIssueResourceIterationEventManager(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)

Bases: *RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectIssueResourceIterationEvent*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIssueResourceIterationEvent

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectIssueResourceLabelEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectIssueResourceLabelEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, RESTManager*

Object Creation**Object update****Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectIssueResourceLabelEvent*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIssueResourceLabelEvent

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectIssueResourceMilestoneEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `ProjectIssueResourceMilestoneEvent`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIssueResourceMilestoneEvent

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectIssueResourceStateEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectIssueResourceStateManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin*, *RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectIssueResourceStateEvent*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIssueResourceStateEvent

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectIssueResourceWeightEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

```
    • manager (RESTManager) –
    • attrs (Dict[str, Any]) –
    • created_from_list (bool) –
    • lazy (bool) –

manager: RESTManager

class gitlab.v4.objects.ProjectIssueResourceWeightEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int], lazy: bool = False, **kwargs: Any`) → `ProjectIssueResourceWeightEvent`

 Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

 The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectIssueResourceWeightEvent`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectIssuesStatistics(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `RefreshMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectIssuesStatisticsManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `GetWithoutIdMixin, RESTManager`

Object listing filters

- `iids`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → ProjectIssuesStatistics`

Retrieve a single object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectIssuesStatistics`

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectIterationManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `ListMixin, RESTManager`

Object listing filters

- `state`
- `search`
- `include_ancestors`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectJob(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `RefreshMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

artifact(*path*: str, *streamed*: bool = `False`, *action*: `Optional[Callable[..., Any]]` = `None`, *chunk_size*: int = 1024, *, *iterator*: bool = `False`, ***kwargs*: Any) → `Optional[Union[bytes, Iterator[Any]]]`

Get a single artifact file from within the job's artifacts archive.

Parameters

- **path** (str) – Path of the artifact
- **streamed** (bool) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (bool) – If True directly return the underlying response iterator
- **action** (`Optional[Callable[..., Any]]`) – Callable responsible of dealing with chunk of data
- **chunk_size** (int) – Size of each chunk
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns

The artifacts if *streamed* is `False`, `None` otherwise.

Return type

`Optional[Union[bytes, Iterator[Any]]]`

artifacts(*streamed*: bool = `False`, *action*: `Optional[Callable[..., Any]]` = `None`, *chunk_size*: int = 1024, *, *iterator*: bool = `False`, ***kwargs*: Any) → `Optional[Union[bytes, Iterator[Any]]]`

Get the job artifacts.

Parameters

- **streamed** (bool) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (bool) – If True directly return the underlying response iterator
- **action** (`Optional[Callable[..., Any]]`) – Callable responsible of dealing with chunk of data
- **chunk_size** (int) – Size of each chunk
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns

The artifacts if *streamed* is `False`, `None` otherwise.

Return type

Optional[Union[bytes, Iterator[Any]]]

cancel(kwargs: Any) → Dict[str, Any]**

Cancel the job.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabJobCancelError** – If the job could not be canceled

Return type

Dict[str, Any]

delete_artifacts(kwargs: Any) → None**

Delete artifacts of a job.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the request could not be performed

Return type

None

erase(kwargs: Any) → None**

Erase the job (remove job artifacts and trace).

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabJobEraseError** – If the job could not be erased

Return type

None

keep_artifacts(kwargs: Any) → None**

Prevent artifacts from being deleted when expiration is set.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the request could not be performed

Return type

None

manager: RESTManager

play(kwargs: Any) → None**

Trigger a job explicitly.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabJobPlayError** – If the job could not be triggered

Return type

None

retry(kwargs: Any) → Dict[str, Any]**

Retry the job.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabJobRetryError** – If the job could not be retried

Return type

Dict[str, Any]

trace(streamed: bool = False, action: Optional[Callable[..., Any]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Dict[str, Any]

Get the job trace.

Parameters

- **streamed (bool)** – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment

- **iterator (bool)** – If True directly return the underlying response iterator

- **action (Optional[Callable[..., Any]])** – Callable responsible of dealing with chunk of data

- **chunk_size (int)** – Size of each chunk

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabGetError** – If the artifacts could not be retrieved

Returns

The trace

Return type

Dict[str, Any]

class gitlab.v4.objects.ProjectJobManager(gl: Gitlab, parent: Optional[RESTObject] = None)

Bases: *RetrieveMixin, RESTManager*

Object listing filters

- scope

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectJob`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectJob`

gitlab: `Gitlab`

`class gitlab.v4.objects.ProjectKey(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

`class gitlab.v4.objects.ProjectKeyManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `title`
- `key`

Optional attributes for object create:

- `can_push`

Object update

Optional attributes for object update:

- `title`
- `can_push`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`enable(key_id: int, **kwargs: Any) → Union[Dict[str, Any], Response]`

Enable a deploy key for a project.

Parameters

- `key_id (int)` – The ID of the key to enable
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabProjectDeployKeyError` – If the key could not be enabled

Returns

A dict of the result.

Return type

`Union[Dict[str, Any], Response]`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectKey`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectKey`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectLabel(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `PromoteMixin, SubscribableMixin, SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`ProjectLabelManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `ProjectLabelManager`

save(`**kwargs: Any`) → `None`

Saves the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct.
- **GitlabUpdateError** – If the server cannot perform the request.

Return type

`None`

class `gitlab.v4.objects.ProjectLabelManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- `name`
- `color`

Optional attributes for object create:

- `description`
- `priority`

Object update

Required attributes for object update:

- `name`

Optional attributes for object update:

- `new_name`
- `color`
- `description`
- `priority`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → ProjectLabel

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectLabel

gitlab: Gitlab

update(*name*: Optional[str], *new_data*: Optional[Dict[str, Any]] = None, ***kwargs*: Any) → Dict[str, Any]

Update a Label on the server.

Parameters

- **name** (Optional[str]) – The name of the label
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)
- **new_data** (Optional[Dict[str, Any]]) –
- ****kwargs** –

Return type

Dict[str, Any]

class gitlab.v4.objects.ProjectManager(*gl*: Gitlab, *parent*: Optional[RESTObject] = None)

Bases: CRUDMixin, RESTManager

Object listing filters

- archived
- id_after
- id_before
- last_activity_after
- last_activity_before
- membership
- min_access_level
- order_by
- owned
- repository_checksum_failed
- repository_storage

- `search_namespaces`
- `search`
- `simple`
- `sort`
- `starred`
- `statistics`
- `topic`
- `visibility`
- `wiki_checksum_failed`
- `with_custom_attributes`
- `with_issues_enabled`
- `with_merge_requests_enabled`
- `with_programming_language`

Object Creation

Optional attributes for object create:

- `name`
- `path`
- `allow_merge_on_skipped_pipeline`
- `only_allow_merge_if_all_status_checks_passed`
- `analytics_access_level`
- `approvals_before_merge`
- `auto_cancel_pending_pipelines`
- `auto_devops_deploy_strategy`
- `auto_devops_enabled`
- `autoclose_referenced_issues`
- `avatar`
- `build_coverage_regex`
- `build_git_strategy`
- `build_timeout`
- `builds_access_level`
- `ci_config_path`
- `container_expiration_policy_attributes`
- `container_registry_access_level`
- `container_registry_enabled`
- `default_branch`
- `description`

- emails_disabled
- external_authorization_classification_label
- forking_access_level
- group_with_project_templates_id
- import_url
- initialize_with_readme
- issues_access_level
- issues_enabled
- jobs_enabled
- lfs_enabled
- merge_method
- merge_pipelines_enabled
- merge_requests_access_level
- merge_requests_enabled
- mirror_trigger_builds
- mirror
- namespace_id
- operations_access_level
- only_allow_merge_if_all_discussions_are_resolved
- only_allow_merge_if_pipeline_succeeds
- packages_enabled
- pages_access_level
- requirements_access_level
- printing_merge_request_link_enabled
- public_builds
- releases_access_level
- environments_access_level
- feature_flags_access_level
- infrastructure_access_level
- monitor_access_level
- remove_source_branch_after_merge
- repository_access_level
- repository_storage
- request_access_enabled
- resolve_outdated_diff_discussions
- security_and_compliance_access_level

- shared_runners_enabled
- show_default_award_emojis
- snippets_access_level
- snippets_enabled
- squash_option
- tag_list
- topics
- template_name
- template_project_id
- use_custom_template
- visibility
- wiki_access_level
- wiki_enabled

Object update

Optional attributes for object update:

- allow_merge_on_skipped_pipeline
- only_allow_merge_if_all_status_checks_passed
- analytics_access_level
- approvals_before_merge
- auto_cancel_pending_pipelines
- auto_devops_deploy_strategy
- auto_devops_enabled
- autoclose_referenced_issues
- avatar
- build_coverage_regex
- build_git_strategy
- build_timeout
- builds_access_level
- ci_config_path
- ci_default_git_depth
- ci_forward_deployment_enabled
- ci_allow_fork_pipelines_to_run_in_parent_project
- ci_separated_caches
- container_expiration_policy_attributes
- container_registry_access_level
- container_registry_enabled

- default_branch
- description
- emails_disabled
- enforce_auth_checks_on_uploads
- external_authorization_classification_label
- forking_access_level
- import_url
- issues_access_level
- issues_enabled
- issues_template
- jobs_enabled
- keep_latest_artifact
- lfs_enabled
- merge_commit_template
- merge_method
- merge_pipelines_enabled
- merge_requests_access_level
- merge_requests_enabled
- merge_requests_template
- merge_trains_enabled
- mirror_overwrites_diverged_branches
- mirror_trigger_builds
- mirror_user_id
- mirror
- mr_default_target_self
- name
- operations_access_level
- only_allow_merge_if_all_discussions_are_resolved
- only_allow_merge_if_pipeline_succeeds
- only_mirror_protected_branches
- packages_enabled
- pages_access_level
- requirements_access_level
- restrict_user_defined_variables
- path
- public_builds

- `releases_access_level`
- `environments_access_level`
- `feature_flags_access_level`
- `infrastructure_access_level`
- `monitor_access_level`
- `remove_source_branch_after_merge`
- `repository_access_level`
- `repository_storage`
- `request_access_enabled`
- `resolve_outdated_diff_discussions`
- `security_and_compliance_access_level`
- `service_desk_enabled`
- `shared_runners_enabled`
- `show_default_award_emojis`
- `snippets_access_level`
- `snippets_enabled`
- `issue_branch_template`
- `squash_commit_template`
- `squash_option`
- `suggestion_commit_message`
- `tag_list`
- `topics`
- `visibility`
- `wiki_access_level`
- `wiki_enabled`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → Project`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Project

gitlab: `Gitlab`

```
import_bitbucket_server(bitbucket_server_url: str, bitbucket_server_username: str,  
                        personal_access_token: str, bitbucket_server_project: str,  
                        bitbucket_server_repo: str, new_name: Optional[str] = None,  
                        target_namespace: Optional[str] = None, **kwargs: Any) → Union[Dict[str,  
                        Any], Response]
```

Import a project from BitBucket Server to Gitlab (schedule the import)

This method will return when an import operation has been safely queued, or an error has occurred. After triggering an import, check the `import_status` of the newly created project to detect when the import operation has completed.

Note: This request may take longer than most other API requests. So this method will specify a 60 second default timeout if none is specified. A timeout can be specified via kwargs to override this functionality.

Parameters

- **bitbucket_server_url** (`str`) – Bitbucket Server URL
- **bitbucket_server_username** (`str`) – Bitbucket Server Username
- **personal_access_token** (`str`) – Bitbucket Server personal access token/password
- **bitbucket_server_project** (`str`) – Bitbucket Project Key
- **bitbucket_server_repo** (`str`) – Bitbucket Repository Name
- **new_name** (`Optional[str]`) – New repository name (Optional)
- **target_namespace** (`Optional[str]`) – Namespace to import repository into. Supports subgroups like /namespace/subgroup (Optional)
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns

A representation of the import status.

Return type

`Union[Dict[str, Any], Response]`

Example:

```

gl = gitlab.Gitlab_from_config()
print("Triggering import")
result = gl.projects.import_bitbucket_server(
    bitbucket_server_url="https://some.server.url",
    bitbucket_server_username="some_bitbucket_user",
    personal_access_token="my_password_or_access_token",
    bitbucket_server_project="my_project",
    bitbucket_server_repo="my_repo",
    new_name="gl_project_name",
    target_namespace="gl_project_path"
)
project = gl.projects.get(ret['id'])
print("Waiting for import to complete")
while project.import_status == u'started':
    time.sleep(1.0)
    project = gl.projects.get(project.id)
print("BitBucket import complete")

```

import_github(*personal_access_token: str, repo_id: int, target_namespace: str, new_name: Optional[str] = None, github_hostname: Optional[str] = None, optional_stages: Optional[Dict[str, bool]] = None, **kwargs: Any*) → Union[Dict[str, Any], Response]

Import a project from Github to Gitlab (schedule the import)

This method will return when an import operation has been safely queued, or an error has occurred. After triggering an import, check the `import_status` of the newly created project to detect when the import operation has completed.

Note: This request may take longer than most other API requests. So this method will specify a 60 second default timeout if none is specified. A timeout can be specified via `kwargs` to override this functionality.

Parameters

- **personal_access_token** (*str*) – GitHub personal access token
- **repo_id** (*int*) – Github repository ID
- **target_namespace** (*str*) – Namespace to import repo into
- **new_name** (*Optional[str]*) – New repo name (Optional)
- **github_hostname** (*Optional[str]*) – Custom GitHub Enterprise hostname. Do not set for GitHub.com. (Optional)
- **optional_stages** (*Optional[Dict[str, bool]]*) – Additional items to import. (Optional)
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns

A representation of the import status.

Return type*Union[Dict[str, Any], Response]*

Example:

```
gl = gitlab.Gitlab_from_config()
print("Triggering import")
result = gl.projects.import_github(ACCESS_TOKEN,
                                    123456,
                                    "my-group/my-subgroup")
project = gl.projects.get(result['id'])
print("Waiting for import to complete")
while project.import_status == u'started':
    time.sleep(1.0)
    project = gl.projects.get(project.id)
print("Github import complete")
```

import_project(file: str, path: str, name: Optional[str] = None, namespace: Optional[str] = None, overwrite: bool = False, override_params: Optional[Dict[str, Any]] = None, **kwargs: Any) → Union[Dict[str, Any], Response]

Import a project from an archive file.

Parameters

- **file** (str) – Data or file object containing the project
- **path** (str) – Name and path for the new project
- **name** (Optional[str]) – The name of the project to import. If not provided, defaults to the path of the project.
- **namespace** (Optional[str]) – The ID or path of the namespace that the project will be imported to
- **overwrite** (bool) – If True overwrite an existing project with the same path
- **override_params** (Optional[Dict[str, Any]]) – Set the specific settings for the project
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabImportError** – If the server failed to perform the request

Returns

A representation of the import status.

Return type*Union[Dict[str, Any], Response]*

remote_import(url: str, path: str, name: Optional[str] = None, namespace: Optional[str] = None, overwrite: bool = False, override_params: Optional[Dict[str, Any]] = None, **kwargs: Any) → Union[Dict[str, Any], Response]

Import a project from an archive file stored on a remote URL.

Parameters

- **url** (str) – URL for the file containing the project data to import

- **path** (*str*) – Name and path for the new project
- **name** (*Optional[str]*) – The name of the project to import. If not provided, defaults to the path of the project.
- **namespace** (*Optional[str]*) – The ID or path of the namespace that the project will be imported to
- **overwrite** (*bool*) – If True overwrite an existing project with the same path
- **override_params** (*Optional[Dict[str, Any]]*) – Set the specific settings for the project
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabImportError** – If the server failed to perform the request

Returns

A representation of the import status.

Return type

Union[Dict[str, Any], Response]

```
remote_import_s3(path: str, region: str, bucket_name: str, file_key: str, access_key_id: str,
                  secret_access_key: str, name: Optional[str] = None, namespace: Optional[str] = None,
                  overwrite: bool = False, override_params: Optional[Dict[str, Any]] = None, **kwargs:
                  Any) → Union[Dict[str, Any], Response]
```

Import a project from an archive file stored on AWS S3.

Parameters

- **region** (*str*) – AWS S3 region name where the file is stored
- **bucket_name** (*str*) – AWS S3 bucket name where the file is stored
- **file_key** (*str*) – AWS S3 file key to identify the file.
- **access_key_id** (*str*) – AWS S3 access key ID.
- **secret_access_key** (*str*) – AWS S3 secret access key.
- **path** (*str*) – Name and path for the new project
- **name** (*Optional[str]*) – The name of the project to import. If not provided, defaults to the path of the project.
- **namespace** (*Optional[str]*) – The ID or path of the namespace that the project will be imported to
- **overwrite** (*bool*) – If True overwrite an existing project with the same path
- **override_params** (*Optional[Dict[str, Any]]*) – Set the specific settings for the project
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabImportError** – If the server failed to perform the request

Returns

A representation of the import status.

Return type

Union[Dict[str, Any], Response]

```
class gitlab.v4.objects.ProjectMember(manager: RESTManager, attrs: Dict[str, Any], *,  
created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectMemberAll(manager: RESTManager, attrs: Dict[str, Any], *,  
created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectMemberAllManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectMemberAll*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMemberAll

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectMemberManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: CRUDMixin, RESTManager
```

Object Creation

Required attributes for object create:

- access_level
- user_id

Optional attributes for object create:

- expires_at
- tasks_to_be_done

Object update

Required attributes for object update:

- access_level

Optional attributes for object update:

- expires_at

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectMember*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMember

gitlab: Gitlab

```
class gitlab.v4.objects.ProjectMergeRequest(manager: RESTManager, attrs: Dict[str, Any], *,  
                                             created_from_list: bool = False, lazy: bool = False)  
Bases: SubscribableMixin, TodoMixin, TimeTrackingMixin, ParticipantsMixin, SaveMixin,  
ObjectDeleteMixin, RESTObject
```

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

approval_rules: ProjectMergeRequestApprovalRuleManager

approval_state: ProjectMergeRequestApprovalStateManager

approvals: ProjectMergeRequestApprovalManager

approve(sha: Optional[str] = None, **kwargs: Any) → Dict[str, Any]

Approve the merge request.

Parameters

- **sha** (Optional[str]) – Head SHA of MR
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMRApiApprovalError** – If the approval failed

Returns

A dict containing the result.

Return type

Dict[str, Any]

https://docs.gitlab.com/ee/api/merge_request_approvals.html#approve-merge-request

awardemojis: ProjectMergeRequestAwardEmojiManager

cancel_merge_when_pipeline_succeeds(**kwargs: Any) → Dict[str, str]

Cancel merge when the pipeline succeeds.

Parameters

- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMROnBuildSuccessError** – If the server could not handle the request

Returns

dict of the parsed json returned by the server

Return type

Dict[str, str]

changes(**kwargs: Any) → Union[Dict[str, Any], Response]

List the merge request changes.

Parameters

• ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

List of changes

Return type

Union[Dict[str, Any], Response]

closes_issues(**kwargs: Any) → RESTObjectList

List issues that will close on merge.”

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

List of issues

Return type

RESTObjectList

commits(**kwargs: Any) → RESTObjectList

List the merge request commits.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

The list of commits

Return type

RESTObjectList

diffs: *ProjectMergeRequestDiffManager*
discussions: *ProjectMergeRequestDiscussionManager*
merge(*merge_commit_message: Optional[str] = None*, *should_remove_source_branch: Optional[bool] = None*, *merge_when_pipeline_succeeds: Optional[bool] = None*, ***kwargs: Any*) → *Dict[str, Any]*
Accept the merge request.

Parameters

- **merge_commit_message** (*Optional[str]*) – Commit message
- **should_remove_source_branch** (*Optional[bool]*) – If True, removes the source branch
- **merge_when_pipeline_succeeds** (*Optional[bool]*) – Wait for the build to succeed, then merge
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMRClosedError** – If the merge failed

Return type

Dict[str, Any]

merge_ref(***kwargs: Any*) → *Union[Dict[str, Any], Response]*

**Attempt to merge changes between source and target branches into
refs/merge-requests/:iid/merge.**

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabGetError** – If cannot be merged

Return type

Union[Dict[str, Any], Response]

notes: *ProjectMergeRequestNoteManager*

pipelines: *ProjectMergeRequestPipelineManager*

rebase(***kwargs: Any*) → *Union[Dict[str, Any], Response]*

Attempt to rebase the source branch onto the target branch

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMRRebaseError** – If rebasing failed

Return type

Union[Dict[str, Any], Response]

reset_approvals(kwargs: Any) → Union[Dict[str, Any], Response]**

Clear all approvals of the merge request.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMRResetApprovalError** – If reset approval failed

Return type

Union[Dict[str, Any], Response]

resourcelabelevents: *ProjectMergeRequestResourceLabelEventManager*

resourcemilestoneevents: *ProjectMergeRequestResourceMilestoneEventManager*

resourcestateevents: *ProjectMergeRequestResourceStateEventManager*

unapprove(kwargs: Any) → None**

Unapprove the merge request.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMRApprovalError** – If the unapproval failed

Return type

None

https://docs.gitlab.com/ee/api/merge_request_approvals.html#unapprove-merge-request

```
class gitlab.v4.objects.ProjectMergeRequestApproval(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, RESTObject*

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectMergeRequestApprovalManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin, UpdateMixin, RESTManager*

Object Creation

Object update

Required attributes for object update:

- `approvals_required`

Parameters

- `g1 (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → ProjectMergeRequestApproval`

Retrieve a single object.

Parameters

- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectMergeRequestApproval`

`gitlab: Gitlab`

`set_approvers(approvals_required: int, approver_ids: Optional[List[int]] = None, approver_group_ids: Optional[List[int]] = None, approval_rule_name: str = 'name', **kwargs: Any) → RESTObject`

Change MR-level allowed approvers and approver groups.

Parameters

- `approvals_required (int)` – The number of required approvals for this rule
- `approver_ids (Optional[List[int]])` – User IDs that can approve MRs
- `approver_group_ids (Optional[List[int]])` – Group IDs whose members can approve MRs
- `approval_rule_name (str)` –
- `kwargs (Any)` –

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server failed to perform the request

Return type

`RESTObject`

`class gitlab.v4.objects.ProjectMergeRequestApprovalRule(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –

- `created_from_list (bool) –`
- `lazy (bool) –`

`approval_rule_id: int`

`id: int`

`merge_request_iid: int`

`save(**kwargs: Any) → None`

Save the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server cannot perform the request

Return type

None

`class gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `id`
- `merge_request_iid`
- `name`
- `approvals_required`

Optional attributes for object create:

- `approval_project_rule_id`
- `user_ids`
- `group_ids`

Object update

Required attributes for object update:

- `id`
- `merge_request_iid`
- `approval_rule_id`
- `name`
- `approvals_required`

Optional attributes for object update:

- `user_ids`

- `group_ids`

Parameters

- `g1 (Gitlab)` –
- `parent (Optional[RESTObject])` –

`create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → RESTObject`

Create a new object.

Parameters

- `data (Optional[Dict[str, Any]])` – Parameters to send to the server to create the resource
- `**kwargs (Any)` – Extra options to send to the server (e.g. `sudo` or `'ref_name'`, `'stage'`, `'name'`, `'all'`)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

Returns

A new instance of the `manage` object class build with
the data sent by the server

Return type

`RESTObject`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestApprovalRule`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. `sudo`)

Returns

The generated `RESTObject`.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectMergeRequestApprovalRule`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectMergeRequestApprovalState(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectMergeRequestApprovalStateManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `GetWithoutIdMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(kwargs: Any) → ProjectMergeRequestApprovalState**

Retrieve a single object.

Parameters

- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectMergeRequestApprovalState`

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectMergeRequestAwardEmoji`(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager(gl: Gitlab, parent:  
                           Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestAwardEmoji
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMergeRequestAwardEmoji

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestDiff(manager: RESTManager, attrs: Dict[str, Any], *,  
                                               created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectMergeRequestDiffManager(gl: Gitlab, parent: Optional[RESTObject] =  
                           None)
```

Bases: *RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional*[`RESTObject`]) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestDiff`

Retrieve a single object.

Parameters

- **id** (*Union*[`str`, `int`]) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectMergeRequestDiff`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectMergeRequestDiscussion(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

`notes: ProjectMergeRequestDiscussionNoteManager`

`class gitlab.v4.objects.ProjectMergeRequestDiscussionManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, CreateMixin, UpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `body`

Optional attributes for object create:

- `created_at`
- `position`

Object update

Required attributes for object update:

- resolved

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestDiscussion`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectMergeRequestDiscussion`

gitlab: `Gitlab`

`class gitlab.v4.objects.ProjectMergeRequestDiscussionNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

`class gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `GetMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- `created_at`

Object update

Required attributes for object update:

- `body`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestDiscussionNote`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectMergeRequestDiscussionNote`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectMergeRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object listing filters

- `state`
- `order_by`
- `sort`
- `milestone`
- `view`
- `labels`
- `created_after`
- `created_before`
- `updated_after`
- `updated_before`

- scope
- iids
- author_id
- assignee_id
- approver_ids
- approved_by_ids
- my_reaction_emoji
- source_branch
- target_branch
- search
- wip

Object Creation

Required attributes for object create:

- source_branch
- target_branch
- title

Optional attributes for object create:

- allow_collaboration
- allow_maintainer_to_push
- approvals_before_merge
- assignee_id
- assignee_ids
- description
- labels
- milestone_id
- remove_source_branch
- reviewer_ids
- squash
- target_project_id

Object update

Optional attributes for object update:

- target_branch
- assignee_id
- title
- description
- state_event

- labels
- milestone_id
- remove_source_branch
- discussion_locked
- allow_maintainer_to_push
- squash
- reviewer_ids

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional*[[RESTObject](#)]) –

get(*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) → [ProjectMergeRequest](#)

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[ProjectMergeRequest](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.ProjectMergeRequestNote](#)(*manager*: [RESTManager](#), *attrs*: *Dict*[*str*, *Any*], *, *created_from_list*: *bool* = *False*, *lazy*: *bool* = *False*)

Bases: [SaveMixin](#), [ObjectDeleteMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

awardemojis: [ProjectMergeRequestNoteAwardEmojiManager](#)

```
class gitlab.v4.objects.ProjectMergeRequestNoteAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → `ProjectMergeRequestNoteAwardEmoji`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectMergeRequestNoteAwardEmoji`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectMergeRequestNoteManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- body

Object update

Required attributes for object update:

- body

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectMergeRequestNote*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMergeRequestNote

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestPipeline(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectMergeRequestPipelineManager(gl: Gitlab, parent:  
                                         Optional[RESTObject] = None)  
    Bases: CreateMixin, ListMixin, RESTManager  
  
Object Creation  
  
Object update  
  
    Parameters  
        • gl (Gitlab) –  
        • parent (Optional[RESTObject]) –  
  
    gitlab: Gitlab  
  
class gitlab.v4.objects.ProjectMergeRequestResourceLabelEvent(manager: RESTManager, attrs:  
                                                               Dict[str, Any], *, created_from_list:  
                                                               bool = False, lazy: bool = False)  
    Bases: RESTObject  
  
    Parameters  
        • manager (RESTManager) –  
        • attrs (Dict[str, Any]) –  
        • created_from_list (bool) –  
        • lazy (bool) –  
  
    manager: RESTManager  
  
class gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager(gl: Gitlab, parent:  
                                         Optional[RESTObject] = None)  
    Bases: RetrieveMixin, RESTManager  
  
Object Creation  
  
Object update  
  
    Parameters  
        • gl (Gitlab) –  
        • parent (Optional[RESTObject]) –  
  
    get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestResourceLabelEvent  
        Retrieve a single object.  
  
    Parameters  
        • id (Union[str, int]) – ID of the object to retrieve  
        • lazy (bool) – If True, don't request the server, but create a shallow object giving  
          access to the managers. This is useful if you want to avoid useless calls to the API.  
        • **kwargs (Any) – Extra options to send to the server (e.g. sudo)  
  
    Returns  
        The generated RESTObject.  
  
    Raises  
        • GitlabAuthenticationError – If authentication is not correct
```

- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMergeRequestResourceLabelEvent

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEvent(manager: RESTManager,  
                     attrs: Dict[str, Any], *,  
                     created_from_list: bool =  
                         False, lazy: bool = False)
```

Bases: `RESTObject`**Parameters**

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager(gl: Gitlab, parent:  
                           Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, RESTManager`**Object Creation****Object update****Parameters**

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `ProjectMergeRequestResourceMilestoneEvent`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

ReturnsThe generated `RESTObject`.**Raises**

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMergeRequestResourceMilestoneEvent

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestResourceStateEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectMergeRequestResourceEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin*, *RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id*: *Union[str, int]*, *lazy*: *bool* = *False*, ***kwargs*: *Any*) → *ProjectMergeRequestResourceStateEvent*
Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated *RESTObject*.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMergeRequestResourceStateEvent

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectMergeTrain(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

gitlab.v4.objects.ProjectMergeTrainManager(`gl: Gitlab, parent: Optional[RESTObject] = None`)
Bases: `ListMixin, RESTManager`

Object listing filters

- `scope`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

gitlab.v4.objects.ProjectMilestone(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)
Bases: `PromoteMixin, SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

issues(kwargs: Any) → RESTObjectList**

List issues related to this milestone.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

The list of issues

Return type
`RESTObjectList`

```
manager: RESTManager  
merge_requests(**kwargs: Any) → RESTObjectList
```

List the merge requests related to this milestone.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

The list of merge requests

Return type

RESTObjectList

```
class gitlab.v4.objects.ProjectMilestoneManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object listing filters

- **iids**
- **state**
- **search**

Object Creation

Required attributes for object create:

- **title**

Optional attributes for object create:

- **description**
- **due_date**
- **start_date**
- **state_event**

Object update

Optional attributes for object update:

- **title**
- **description**
- **due_date**
- **start_date**
- **state_event**

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → `ProjectMilestone`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectMilestone`

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectNote`(*manager*: `RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`, *lazy*: `bool = False`)

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectNoteManager`(*gl*: `Gitlab`, *parent*: `Optional[RESTObject] = None`)

Bases: `RetrieveMixin, RESTManager`

Object Creation

Required attributes for object create:

- body

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectNote`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectNote`

gitlab: `Gitlab`

`class gitlab.v4.objects.ProjectNotificationSettings(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `NotificationSettings`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

`class gitlab.v4.objects.ProjectNotificationSettingsManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `NotificationSettingsManager`

Object Creation

Object update

Optional attributes for object update:

- `level`
- `notification_email`
- `new_note`
- `new_issue`
- `reopen_issue`
- `close_issue`
- `reassign_issue`

- `new_merge_request`
- `reopen_merge_request`
- `close_merge_request`
- `reassign_merge_request`
- `merge_merge_request`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → ProjectNotificationSettings`

Retrieve a single object.

Parameters

- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectNotificationSettings`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectPackage(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`package_files: ProjectPackageManager`

`class gitlab.v4.objects.ProjectPackageFile(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

```
manager: RESTManager

class gitlab.v4.objects.ProjectPackageManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: DeleteMixin, ListMixin, RESTManager

Object Creation
Object update

Parameters
• gl (Gitlab) –
• parent (Optional[RESTObject]) –

gitlab: Gitlab

class gitlab.v4.objects.ProjectPackageManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, GetMixin, DeleteMixin, RESTManager

Object listing filters
• order_by
• sort
• package_type
• package_name

Object Creation
Object update

Parameters
• gl (Gitlab) –
• parent (Optional[RESTObject]) –

get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectPackage
Retrieve a single object.

Parameters
• id (Union[str, int]) – ID of the object to retrieve
• lazy (bool) – If True, don't request the server, but create a shallow object giving
access to the managers. This is useful if you want to avoid useless calls to the API.
• **kwargs (Any) – Extra options to send to the server (e.g. sudo)

Returns
The generated RESTObject.

Raises
• GitlabAuthenticationError – If authentication is not correct
• GitlabGetError – If the server cannot perform the request

Return type
ProjectPackage

gitlab: Gitlab
```

```
class gitlab.v4.objects.ProjectPagesDomain(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager` (`RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –
- `lazy` (`bool`) –

`manager:` `RESTManager`

```
class gitlab.v4.objects.ProjectPagesDomainManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `domain`

Optional attributes for object create:

- `certificate`
- `key`

Object update

Optional attributes for object update:

- `certificate`
- `key`

Parameters

- `gl` (`Gitlab`) –
- `parent` (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectPagesDomain`

Retrieve a single object.

Parameters

- `id` (`Union[str, int]`) – ID of the object to retrieve
- `lazy` (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectPagesDomain`

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectPipeline(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RefreshMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

bridges: `ProjectPipelineBridgeManager`

cancel(kwargs: Any) → Union[Dict[str, Any], Response]**

Cancel the job.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPipelineCancelError** – If the request failed

Return type

`Union[Dict[str, Any], Response]`

jobs: `ProjectPipelineJobManager`

retry(kwargs: Any) → Union[Dict[str, Any], Response]**

Retry the job.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPipelineRetryError** – If the request failed

Return type

`Union[Dict[str, Any], Response]`

test_report: `ProjectPipelineTestReportManager`

test_report_summary: `ProjectPipelineTestReportSummaryManager`

variables: `ProjectPipelineVariableManager`

class `gitlab.v4.objects.ProjectPipelineBridge(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

gitlab.v4.objects.ProjectPipelineBridgeManager(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `ListMixin, RESTManager`

Object listing filters

- `scope`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

gitlab.v4.objects.ProjectPipelineJob(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

gitlab.v4.objects.ProjectPipelineJobManager(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `ListMixin, RESTManager`

Object listing filters

- `scope`
- `include_retried`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectPipelineManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: RetrieveMixin, CreateMixin, DeleteMixin, RESTManager
```

Object listing filters

- scope
- status
- source
- ref
- sha
- yaml_errors
- name
- username
- order_by
- sort

Object Creation

Required attributes for object create:

- ref

Object update

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

```
create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → ProjectPipeline
```

Creates a new object.

Parameters

- **data** (Optional[Dict[str, Any]]) – Parameters to send to the server to create the resource
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Returns

A new instance of the managed object class build with
the data sent by the server

Return type

ProjectPipeline

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectPipeline
```

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve

- **lazy (bool)** – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectPipeline

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectPipelineSchedule(manager: RESTManager, attrs: Dict[str, Any], *,  
                                               created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

pipelines: *ProjectPipelineSchedulePipelineManager*

play(kwargs: Any) → Dict[str, Any]**

Trigger a new scheduled pipeline, which runs immediately. The next scheduled run of this pipeline is not affected.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPipelinePlayError** – If the request failed

Return type

Dict[str, Any]

take_ownership(kwargs: Any) → None**

Update the owner of a pipeline schedule.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabOwnershipError** – If the request failed

Return type

None

```
variables: ProjectPipelineScheduleVariableManager

class gitlab.v4.objects.ProjectPipelineScheduleManager(gl: Gitlab, parent: Optional[RESTObject] = None)

Bases: CRUDMixin, RESTManager
```

Object Creation

Required attributes for object create:

- description
- ref
- cron

Optional attributes for object create:

- cron_timezone
- active

Object update

Optional attributes for object update:

- description
- ref
- cron
- cron_timezone
- active

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → ProjectPipelineSchedule

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectPipelineSchedule

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectPipelineSchedulePipeline(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectPipelineSchedulePipelineManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectPipelineScheduleVariable(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectPipelineScheduleVariableManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CreateMixin, UpdateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- **key**
- **value**

Object update

Required attributes for object update:

- key
- value

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectPipelineTestReport(manager: RESTManager, attrs: Dict[str, Any], *,  
                                                created_from_list: bool = False, lazy: bool =  
                                                False)
```

Bases: `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.ProjectPipelineTestReportManager(gl: Gitlab, parent: Optional[RESTObject]  
= None)
```

Bases: `GetWithoutIdMixin, RESTManager`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → ProjectPipelineTestReport`

Retrieve a single object.

Parameters

- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectPipelineTestReport`

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectPipelineTestReportSummary(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectPipelineTestReportSummaryManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → ProjectPipelineTestReportSummary**

Retrieve a single object.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectPipelineTestReportSummary

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectPipelineVariable(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: [RESTManager](#)

```
class gitlab.v4.objects.ProjectPipelineVariableManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: [ListMixin](#), [RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** ([Optional\[RESTObject\]](#)) –

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.ProjectProtectedBranch(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: [ObjectDeleteMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –
- **lazy** ([bool](#)) –

manager: [RESTManager](#)

```
class gitlab.v4.objects.ProjectProtectedBranchManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: [NoUpdateMixin](#), [RESTManager](#)

Object Creation

Required attributes for object create:

- name

Optional attributes for object create:

- push_access_level
- merge_access_level
- unprotect_access_level
- allow_force_push
- allowed_to_push
- allowed_to_merge
- allowed_to_unprotect
- code_owner_approval_required

Object update

Parameters

- **gl** ([Gitlab](#)) –

- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectProtectedBranch*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectProtectedBranch

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectProtectedEnvironment(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectProtectedEnvironmentManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, CreateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- `name`
- `deploy_access_levels`

Optional attributes for object create:

- `required_approval_count`
- `approval_rules`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectProtectedEnvironment`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectProtectedEnvironment`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectProtectedTag(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectProtectedTagManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `NoUpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `name`

Optional attributes for object create:

- `create_access_level`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectProtectedTag`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectProtectedTag`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectPushRules(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectPushRulesManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `GetWithoutIdMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager`

Object Creation

Optional attributes for object create:

- `author_email_regex`
- `branch_name_regex`
- `commit_committer_check`
- `commit_message_negative_regex`
- `commit_message_regex`
- `deny_delete_tag`
- `file_name_regex`
- `max_file_size`
- `member_check`
- `prevent_secrets`

- `reject_unsigned_commits`

Object update

Optional attributes for object update:

- `author_email_regex`
- `branch_name_regex`
- `commit_committer_check`
- `commit_message_negative_regex`
- `commit_message_regex`
- `deny_delete_tag`
- `file_name_regex`
- `max_file_size`
- `member_check`
- `prevent_secrets`
- `reject_unsigned_commits`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → ProjectPushRules`

Retrieve a single object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectPushRules`

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectRegistryRepository(manager: RESTManager, attrs: Dict[str, Any], *,  
                                                created_from_list: bool = False, lazy: bool =  
                                                False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –

- **lazy** (*bool*) –

tags: *ProjectRegistryTagManager*

gitlab.v4.objects.ProjectRegistryRepositoryManager(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: *DeleteMixin, ListMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

gitlab.v4.objects.ProjectRegistryTag(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

gitlab.v4.objects.ProjectRegistryTagManager(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: *DeleteMixin, RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

delete_in_bulk(*name_regex_delete: str, **kwargs: Any*) → *None*

 Delete Tag in bulk

Parameters

- **name_regex_delete** (*str*) – The regex of the name to delete. To delete all tags specify ***.
- **keep_n** – The amount of latest tags of given name to keep.
- **name_regex_keep** – The regex of the name to keep. This value overrides any matches from *name_regex*.
- **older_than** – Tags to delete that are older than the given time, written in human readable form 1h, 1d, 1month.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

None

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → ProjectRegistryTag

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectRegistryTag

gitlab: Gitlab

class gitlab.v4.objects.ProjectRelease(*manager*: RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False, *lazy*: bool = False)

Bases: SaveMixin, RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

links: ProjectReleaseLinkManager

class gitlab.v4.objects.ProjectReleaseLink(*manager*: RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False, *lazy*: bool = False)

Bases: ObjectDeleteMixin, SaveMixin, RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: RESTManager

```
class gitlab.v4.objects.ProjectReleaseLinkManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: CRUDMixin, RESTManager
```

Object Creation

Required attributes for object create:

- name
- url

Optional attributes for object create:

- filepath
- link_type

Object update

Optional attributes for object update:

- name
- url
- filepath
- link_type

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectReleaseLink
```

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectReleaseLink

gitlab: Gitlab

```
class gitlab.v4.objects.ProjectReleaseManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: CRUDMixin, RESTManager
```

Object listing filters

- order_by

- `sort`
- `include_html_description`

Object Creation

Required attributes for object create:

- `tag_name`

Optional attributes for object create:

- `name`
- `description`
- `ref`
- `assets`

Object update

Optional attributes for object update:

- `name`
- `description`
- `milestones`
- `released_at`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectRelease`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectRelease`

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectRemoteMirror(manager: RESTManager, attrs: Dict[str, Any], *,  
                                             created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectRemoteMirrorManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                 None)
```

Bases: *ListMixin, CreateMixin, UpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- `url`

Optional attributes for object create:

- `enabled`
- `only_protected_branches`

Object update

Optional attributes for object update:

- `enabled`
- `only_protected_branches`

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectResourceGroup(manager: RESTManager, attrs: Dict[str, Any], *,  
                                              created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

upcoming_jobs: *ProjectResourceGroupUpcomingJobManager*

```
class gitlab.v4.objects.ProjectResourceGroupManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, UpdateMixin, RESTManager*

Object listing filters

- `order_by`
- `sort`
- `include_html_description`

Object Creation

Object update

Optional attributes for object update:

- `process_mode`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectResourceGroup
```

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectResourceGroup`

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectResourceGroupUpcomingJob(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

```
manager: RESTManager

class gitlab.v4.objects.ProjectResourceGroupUpcomingJobManager(gl: Gitlab, parent:
    Optional[RESTObject] = None)
Bases: ListMixin, RESTManager

Object Creation
Object update

    Parameters
        • gl (Gitlab) –
        • parent (Optional[RESTObject]) –

gitlab: Gitlab

class gitlab.v4.objects.ProjectRunner(manager: RESTManager, attrs: Dict[str, Any], *,
    created_from_list: bool = False, lazy: bool = False)
Bases: ObjectDeleteMixin, RESTObject

    Parameters
        • manager (RESTManager) –
        • attrs (Dict[str, Any]) –
        • created_from_list (bool) –
        • lazy (bool) –

manager: RESTManager

class gitlab.v4.objects.ProjectRunnerManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: CreateMixin, DeleteMixin, ListMixin, RESTManager

Object listing filters
    • scope
    • tag_list

Object Creation
Required attributes for object create:
    • runner_id

Object update

    Parameters
        • gl (Gitlab) –
        • parent (Optional[RESTObject]) –

gitlab: Gitlab

class gitlab.v4.objects.ProjectSecureFile(manager: RESTManager, attrs: Dict[str, Any], *,
    created_from_list: bool = False, lazy: bool = False)
Bases: ObjectDeleteMixin, RESTObject

    Parameters
        • manager (RESTManager) –
```

- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

download(*streamed: bool = False, action: Optional[Callable[[bytes], None]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any*) → *Optional[Union[bytes, Iterator[Any]]]*

Download the secure file.

Parameters

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[[bytes], None]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns

The artifacts if *streamed* is False, None otherwise.

Return type

Optional[Union[bytes, Iterator[Any]]]

manager: [RESTManager](#)

class gitlab.v4.objects.ProjectSecureFileManager(*gl: Gitlab, parent: Optional[RESTObject] = None*)
Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- **name**
- **file**

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → [ProjectSecureFile](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectSecureFile

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectService(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *ProjectIntegration*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectServiceManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ProjectIntegrationManager*

Object Creation**Object update****Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ****kwargs: Any**) → *ProjectService*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectService

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectSnippet(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *UserAgentDetailMixin, SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

awardemojis: *ProjectSnippetAwardEmojiManager*

content (`streamed: bool = False, action: Optional[Callable[..., Any]] = None, chunk_size: int = 1024, *,
iterator: bool = False, **kwargs: Any`) → `Optional[Union[bytes, Iterator[Any]]]`

Return the content of a snippet.

Parameters

- **streamed** (`bool`) – If True the data will be processed by chunks of `chunk_size` and each chunk is passed to `action` for treatment.
- **iterator** (`bool`) – If True directly return the underlying response iterator
- **action** (`Optional[Callable[..., Any]]`) – Callable responsible of dealing with chunk of data
- **chunk_size** (`int`) – Size of each chunk
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the content could not be retrieved

Returns

The snippet content

Return type

`Optional[Union[bytes, Iterator[Any]]]`

discussions: *ProjectSnippetDiscussionManager*

notes: *ProjectSnippetNoteManager*

```
class gitlab.v4.objects.ProjectSnippetAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *,  
                                                created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectSnippetAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectSnippetAwardEmoji
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectSnippetAwardEmoji

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectSnippetDiscussion(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

notes: *ProjectSnippetDiscussionNoteManager*

```
class gitlab.v4.objects.ProjectSnippetDiscussionManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, CreateMixin, RESTManager*

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectSnippetDiscussion*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectSnippetDiscussion

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectSnippetDiscussionNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectSnippetDiscussionNoteManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetMixin*, *CreateMixin*, *UpdateMixin*, *DeleteMixin*, *RESTManager*

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at

Object update

Required attributes for object update:

- body

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectSnippetDiscussionNote
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectSnippetDiscussionNote

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectSnippetManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin*, *RESTManager*

Object Creation

Required attributes for object create:

- title
- file_name
- content
- visibility

Optional attributes for object create:

- `description`

Object update

Optional attributes for object update:

- `title`
- `file_name`
- `content`
- `visibility`
- `description`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectSnippet`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectSnippet`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectSnippetNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`awardemojis: ProjectSnippetNoteAwardEmojiManager`

```
class gitlab.v4.objects.ProjectSnippetNoteAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- `name`

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(*id*: `Union[str, int]`, `lazy`: `bool = False`, `**kwargs`: `Any`) → `ProjectSnippetNoteAwardEmoji`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. `sudo`)

Returns

The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectSnippetNoteAwardEmoji`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectSnippetNoteManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- body

Object update

Required attributes for object update:

- body

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectSnippetNote`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectSnippetNote`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectStorage(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RefreshMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectStorageManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `GetWithoutIdMixin, RESTManager`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –

- **parent** (*Optional[RESTObject]*) –

get(***kwargs: Any*) → *ProjectStorage*
Retrieve a single object.

Parameters
****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns
The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type
ProjectStorage

gitlab: *Gitlab*

class *gitlab.v4.objects.ProjectTag*(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

class *gitlab.v4.objects.ProjectTagManager*(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- **tag_name**
- **ref**

Optional attributes for object create:

- **message**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *ProjectTag*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve

- **lazy (bool)** – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectTag

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.ProjectTrigger(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: [SaveMixin](#), [ObjectDeleteMixin](#), [RESTObject](#)

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

manager: [RESTManager](#)

```
class gitlab.v4.objects.ProjectTriggerManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: [CRUDMixin](#), [RESTManager](#)

Object Creation

Required attributes for object create:

- **description**

Object update

Required attributes for object update:

- **description**

Parameters

- **gl (Gitlab)** –
- **parent (Optional[RESTObject])** –

get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectTrigger

Retrieve a single object.

Parameters

- **id (Union[str, int])** – ID of the object to retrieve
- **lazy (bool)** – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.

- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectTrigger

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectUser(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectUserManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- **search**
- **skip_users**

Object Creation**Object update****Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectVariable(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectVariableManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)
Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `key`
- `value`

Optional attributes for object create:

- `protected`
- `variable_type`
- `masked`
- `environment_scope`

Object update

Required attributes for object update:

- `key`
- `value`

Optional attributes for object update:

- `protected`
- `variable_type`
- `masked`
- `environment_scope`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `ProjectVariable`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

ProjectVariable

gitlab: *Gitlab***class** gitlab.v4.objects.ProjectWiki(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)Bases: *SaveMixin, ObjectDeleteMixin, RESTObject***Parameters**

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager***class** gitlab.v4.objects.ProjectWikiManager(*gl: Gitlab, parent: Optional[RESTObject] = None*)Bases: *CRUDMixin, RESTManager***Object listing filters**

- *with_content*

Object Creation

Required attributes for object create:

- *title*
- *content*

Optional attributes for object create:

- *format*

Object update

Optional attributes for object update:

- *title*
- *content*
- *format*

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectWiki*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectWiki

gitlab: `Gitlab`

```
class gitlab.v4.objects.RegistryRepository(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.RegistryRepositoryManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `GetMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `RegistryRepository`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`RegistryRepository`

```
gitlab: Gitlab

class gitlab.v4.objects.RepositoryMixin
    Bases: object

    delete_merged_branches(**kwargs: Any) → None
        Delete merged branches.

        Parameters
        **kwargs (Any) – Extra options to send to the server (e.g. sudo)

        Raises
        • GitlabAuthenticationError – If authentication is not correct
        • GitlabDeleteError – If the server failed to perform the request

        Return type
        None

    repository_archive(sh: Optional[str] = None, streamed: bool = False, action: Optional[Callable[[...], Any]] = None, chunk_size: int = 1024, format: Optional[str] = None, path: Optional[str] = None, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]
        Return an archive of the repository.

        Parameters
        • sh (Optional[str]) – ID of the commit (default branch by default)
        • streamed (bool) – If True the data will be processed by chunks of chunk_size and each chunk is passed to action for treatment
        • iterator (bool) – If True directly return the underlying response iterator
        • action (Optional[Callable[[...], Any]]) – Callable responsible of dealing with chunk of data
        • chunk_size (int) – Size of each chunk
        • format (Optional[str]) – file format (tar.gz by default)
        • path (Optional[str]) – The subpath of the repository to download (all files by default)
        • **kwargs (Any) – Extra options to send to the server (e.g. sudo)

        Raises
        • GitlabAuthenticationError – If authentication is not correct
        • GitlabListError – If the server failed to perform the request

        Returns
        The binary data of the archive

        Return type
        Optional[Union[bytes, Iterator[Any]]]

    repository_blob(sh: str, **kwargs: Any) → Union[Dict[str, Any], Response]
        Return a file by blob SHA.

        Parameters
        • sh (str) – ID of the blob
```

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The blob content and metadata

Return type

Union[Dict[str, Any], Response]

repository_compare(*from_*: str, *to*: str, ****kwargs**: Any) → Union[Dict[str, Any], Response]

Return a diff between two branches/commits.

Parameters

- **from** – Source branch/SHA
- **to (str)** – Destination branch/SHA
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)
- **from_ (str)** –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The diff

Return type

Union[Dict[str, Any], Response]

repository_contributors(****kwargs**: Any) → Union[[GitlabList](#), List[Dict[str, Any]]]

Return a list of contributors for the project.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **iterator** – If set to True and no pagination option is defined, return a generator instead of a list
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The contributors

Return type

Union[GitlabList, List[Dict[str, Any]]]

repository_merge_base(*refs*: *List[str]*, ***kwargs*: *Any*) → *Union[Dict[str, Any], Response]*

Return a diff between two branches/commits.

Parameters

- **refs** (*List[str]*) – The refs to find the common ancestor of. Multiple refs can be passed.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The common ancestor commit (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

repository_raw_blob(*sha*: *str*, *streamed*: *bool* = *False*, *action*: *Optional[Callable[..., Any]]* = *None*, *chunk_size*: *int* = *1024*, *, *iterator*: *bool* = *False*, ***kwargs*: *Any*) → *Optional[Union[bytes, Iterator[Any]]]*

Return the raw file contents for a blob.

Parameters

- **sha** (*str*) – ID of the blob
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[..., Any]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The blob content if streamed is False, None otherwise

Return type

Optional[Union[bytes, Iterator[Any]]]

repository_tree(*path*: *str* = '', *ref*: *str* = '', *recursive*: *bool* = *False*, ***kwargs*: *Any*) → *Union[GitlabList, List[Dict[str, Any]]]*

Return a list of files in the repository.

Parameters

- **path** (*str*) – Path of the top folder (/ by default)
- **ref** (*str*) – Reference to a commit or branch
- **recursive** (*bool*) – Whether to get the tree recursively

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **iterator** – If set to True and no pagination option is defined, return a generator instead of a list
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The representation of the tree

Return type

Union[GitlabList, List[Dict[str, Any]]]

update_submodule(*submodule: str, branch: str, commit_sha: str, **kwargs: Any*) → *Union[Dict[str, Any], Response]*

Update a project submodule

Parameters

- **submodule (str)** – Full path to the submodule
- **branch (str)** – Name of the branch to commit into
- **commit_sha (str)** – Full commit SHA to update the submodule to
- **commit_message** – Commit message. If no message is provided, a default one will be set (optional)
- **kwargs (Any)** –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPutError** – If the submodule could not be updated

Return type

Union[Dict[str, Any], Response]

class `gitlab.v4.objects.Runner`(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

jobs: `RunnerJobManager`

```
class gitlab.v4.objects.RunnerAll(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
    bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.RunnerAllManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- scope
- type
- status
- paused
- tag_list

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.RunnerJob(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
    bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.RunnerJobManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- status

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.RunnerManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object listing filters

- `scope`
- `type`
- `status`
- `paused`
- `tag_list`

Object Creation

Required attributes for object create:

- `token`

Optional attributes for object create:

- `description`
- `info`
- `active`
- `locked`
- `run_untagged`
- `tag_list`
- `access_level`
- `maximum_timeout`

Object update

Optional attributes for object update:

- `description`
- `active`
- `tag_list`
- `run_untagged`
- `locked`
- `access_level`
- `maximum_timeout`

Parameters

- **g1** (`Gitlab`) –
- **parent** (*Optional*[`RESTObject`]) –

all(*scope*: *Optional*[`str`] = `None`, ***kwargs*: `Any`) → `List[Runner]`

List all the runners.

Parameters

- **scope** (*Optional*[`str`]) – The scope of runners to show, one of: specific, shared, active, paused, online
- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **iterator** – If set to True and no pagination option is defined, return a generator instead of a list
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns

A list of runners matching the scope.

Return type

`List[Runner]`

get(*id*: *Union*[`str`, `int`], *lazy*: `bool` = `False`, ***kwargs*: `Any`) → `Runner`

Retrieve a single object.

Parameters

- **id** (*Union*[`str`, `int`]) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`Runner`

gitlab: `Gitlab`

verify(*token*: `str`, ***kwargs*: `Any`) → `None`

Validates authentication credentials for a registered Runner.

Parameters

- **token** (*str*) – The runner’s authentication token
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabVerifyError** – If the server failed to verify the token

Return type

None

```
class gitlab.v4.objects.SharedProject(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.SharedProjectManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- `archived`
- `visibility`
- `order_by`
- `sort`
- `search`
- `simple`
- `starred`
- `with_issues_enabled`
- `with_merge_requests_enabled`
- `min_access_level`
- `with_custom_attributes`

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.SidekiqManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RESTManager*

Manager for the Sidekiq methods.

This manager doesn't actually manage objects but provides helper function for the sidekiq metrics API.

Object Creation

Object update

Parameters

- **gl (Gitlab)** –
- **parent (Optional[RESTObject])** –

```
compound_metrics(**kwargs: Any) → Union[Dict[str, Any], Response]
```

Return all available metrics and statistics.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the information couldn't be retrieved

Returns

All available Sidekiq metrics and statistics

Return type

Union[Dict[str, Any], Response]

gitlab: *Gitlab*

```
job_stats(**kwargs: Any) → Union[Dict[str, Any], Response]
```

Return statistics about the jobs performed.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the information couldn't be retrieved

Returns

Statistics about the Sidekiq jobs performed

Return type

Union[Dict[str, Any], Response]

```
process_metrics(**kwargs: Any) → Union[Dict[str, Any], Response]
```

Return the registered sidekiq workers.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the information couldn't be retrieved

Returns

Information about the register Sidekiq worker

Return type

Union[Dict[str, Any], Response]

queue_metrics(kwargs: Any) → Union[Dict[str, Any], Response]**

Return the registered queues information.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the information couldn't be retrieved

Returns

Information about the Sidekiq queues

Return type

Union[Dict[str, Any], Response]

class gitlab.v4.objects.Snippet(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)

Bases: *UserAgentDetailMixin, SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

content(streamed: bool = False, action: Optional[Callable[..., Any]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]

Return the content of a snippet.

Parameters

- **streamed (bool)** – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment.
- **iterator (bool)** – If True directly return the underlying response iterator
- **action (Optional[Callable[..., Any]])** – Callable responsible of dealing with chunk of data
- **chunk_size (int)** – Size of each chunk
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the content could not be retrieved

Returns

The snippet content

Return type

Optional[Union[bytes, Iterator[Any]]]

manager: *RESTManager*

class `gitlab.v4.objects.SnippetManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- `title`
- `file_name`
- `content`

Optional attributes for object create:

- `lifetime`
- `visibility`

Object update

Optional attributes for object update:

- `title`
- `file_name`
- `content`
- `visibility`

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *Snippet*

Retrieve a single object.

Parameters

- `id (Union[str, int]) –` ID of the object to retrieve
- `lazy (bool) –` If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

Snippet

gitlab: *Gitlab*

public(***kwargs: Any*) → Union[*RESTObjectList*, List[*RESTObject*]]

List all the public snippets.

Parameters

- **all** – If True the returned object will be a list
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

GitlabListError – If the list could not be retrieved

Returns

A generator for the snippets list

Return type

Union[*RESTObjectList*, List[*RESTObject*]]

class gitlab.v4.objects.StarredProject(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)

Bases: *RESTObject*

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

manager: *RESTManager*

class gitlab.v4.objects.StarredProjectManager(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)

Bases: *ListMixin, RESTManager*

Object listing filters

- **archived**
- **membership**
- **min_access_level**
- **order_by**
- **owned**
- **search**
- **simple**
- **sort**
- **starred**
- **statistics**
- **visibility**
- **with_custom_attributes**
- **with_issues_enabled**
- **with_merge_requests_enabled**

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.Todo(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`mark_as_done(**kwargs: Any) → Dict[str, Any]`

Mark the todo as done.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabTodoError` – If the server failed to perform the request

Returns

A dict with the result

Return type

`Dict[str, Any]`

```
class gitlab.v4.objects.TodoManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `ListMixin, DeleteMixin, RESTManager`

Object listing filters

- `action`
- `author_id`
- `project_id`
- `state`
- `type`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –

- **parent** (*Optional[RESTObject]*) –

gitlab: [Gitlab](#)

mark_all_as_done(***kwargs*: *Any*) → *None*
Mark all the todos as done.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTodoError** – If the server failed to perform the request

Returns
The number of todos marked done

Return type
None

class [gitlab.v4.objects.Topic](#)(*manager*: RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False, *lazy*: bool = False)

Bases: [SaveMixin](#), [ObjectDeleteMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: [RESTManager](#)

class [gitlab.v4.objects.TopicManager](#)(*gl*: Gitlab, *parent*: *Optional[RESTObject]* = None)

Bases: [CRUDMixin](#), [RESTManager](#)

Object Creation

Required attributes for object create:

- name

Optional attributes for object create:

- avatar
- description
- title

Object update

Optional attributes for object update:

- avatar
- description
- name

Parameters

- **g1** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [Topic](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[Topic](#)

gitlab: [Gitlab](#)

merge(*source_topic_id: Union[int, str]*, *target_topic_id: Union[int, str]*, ***kwargs: Any*) → *Dict[str, Any]*

Merge two topics, assigning all projects to the target topic.

Parameters

- **source_topic_id** (*Union[int, str]*) – ID of source project topic
- **target_topic_id** (*Union[int, str]*) – ID of target project topic
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTopicMergeError** – If the merge failed

Returns

The merged topic data (*not* a RESTObject)

Return type

Dict[str, Any]

class gitlab.v4.objects.User(*manager: RESTManager*, *attrs: Dict[str, Any]*, **, created_from_list: bool = False*, *lazy: bool = False*)

Bases: [SaveMixin](#), [ObjectDeleteMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

activate(kwargs: Any) → Union[Dict[str, Any], Response]**

Activate the user.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabActivateError** – If the user could not be activated

Returns

Whether the user status has been changed

Return type

Union[Dict[str, Any], Response]

approve(kwargs: Any) → Union[Dict[str, Any], Response]**

Approve a user creation request.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUserApproveError** – If the user could not be activated

Returns

The new object data (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

ban(kwargs: Any) → Union[Dict[str, Any], Response]**

Ban the user.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabBanError** – If the user could not be banned

Returns

Whether the user has been banned

Return type

Union[Dict[str, Any], Response]

block(kwargs: Any) → Optional[bool]**

Block the user.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabBlockError** – If the user could not be blocked

Returns

Whether the user status has been changed

Return type

Optional[bool]

customattributes: *UserCustomAttributeManager*

deactivate(kwargs: Any) → Union[Dict[str, Any], Response]**

Deactivate the user.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeactivateError** – If the user could not be deactivated

Returns

Whether the user status has been changed

Return type

Union[Dict[str, Any], Response]

emails: *UserEmailManager*

events: *UserEventManager*

follow(kwargs: Any) → Union[Dict[str, Any], Response]**

Follow the user.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabFollowError** – If the user could not be followed

Returns

The new object data (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

followers_users: *UserFollowersManager*

following_users: *UserFollowingManager*

gpgkeys: *UserGPGKeyManager*

identityproviders: *UserIdentityProviderManager*

impersonationtokens: *UserImpersonationTokenManager*

keys: *UserKeyManager*

memberships: *UserMembershipManager*

personal_access_tokens: *UserPersonalAccessTokenManager*

projects: *UserProjectManager*

reject(kwargs: Any) → Union[Dict[str, Any], Response]**

Reject a user creation request.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUserRejectError** – If the user could not be rejected

Returns

The new object data (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

starred_projects: *StarredProjectManager*

status: *UserStatusManager*

unban(kwargs: Any) → Union[Dict[str, Any], Response]**

Unban the user.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUnbanError** – If the user could not be unbanned

Returns

Whether the user has been unbanned

Return type

Union[Dict[str, Any], Response]

unblock(kwargs: Any) → Optional[bool]**

Unblock the user.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUnblockError** – If the user could not be unblocked

Returns

Whether the user status has been changed

Return type

Optional[bool]

unfollow(kwargs: Any) → Union[Dict[str, Any], Response]**

Unfollow the user.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUnfollowError** – If the user could not be followed

Returns

The new object data (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

```
class gitlab.v4.objects.UserActivities(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.UserActivitiesManager(gl: Gitlab, parent: Optional[RESTObject] = None)  
Bases: ListMixin, RESTManager
```

Object Creation**Object update****Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.UserCustomAttribute(manager: RESTManager, attrs: Dict[str, Any], *,  
                                             created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.UserCustomAttributeManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                None)
```

Bases: *RetrieveMixin, SetMixin, DeleteMixin, RESTManager*

Object Creation**Object update**

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → UserCustomAttribute`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

UserCustomAttribute

`gitlab: Gitlab`

`class gitlab.v4.objects.UserEmail(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.UserEmailManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, CreateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- `email`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → UserEmail
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`UserEmail`

gitlab: `Gitlab`

```
class gitlab.v4.objects.UserEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                bool = False, lazy: bool = False)
```

Bases: `Event`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.UserEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `EventManager`

Object listing filters

- `action`
- `target_type`
- `before`
- `after`
- `sort`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.UserGPGKey(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.UserGPGKeyManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, CreateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- **key**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *UserGPGKey*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

UserGPGKey

gitlab: *Gitlab*

```
class gitlab.v4.objects.UserIdentityProviderManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *DeleteMixin, RESTManager*

Manager for user identities.

This manager does not actually manage objects but enables functionality for deletion of user identities by provider.

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional[RESTObject]*) –

gitlab: `Gitlab`

```
class gitlab.v4.objects.UserImpersonationToken(manager: RESTManager, attrs: Dict[str, Any], *,  
                                               created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.UserImpersonationTokenManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                       None)
```

Bases: *NoUpdateMixin, RESTManager*

Object listing filters

- `state`

Object Creation

Required attributes for object create:

- `name`
- `scopes`

Optional attributes for object create:

- `expires_at`

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, `lazy = False`, `**kwargs: Any`) → `UserImpersonationToken`

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

UserImpersonationToken

gitlab: *Gitlab*

```
class gitlab.v4.objects.UserKey(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.UserKeyManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, CreateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- **title**
- **key**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *UserKey*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

UserKey

gitlab: `Gitlab`

```
class gitlab.v4.objects.UserManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object listing filters

- active
- blocked
- username
- extern_uid
- provider
- external
- search
- custom_attributes
- status
- two_factor

Object Creation

Optional attributes for object create:

- email
- username
- name
- password
- reset_password
- skype
- linkedin
- twitter
- projects_limit
- extern_uid
- provider
- bio
- admin
- can_create_group

- website_url
- skip_confirmation
- external
- organization
- location
- avatar
- public_email
- private_profile
- color_scheme_id
- theme_id

Object update

Required attributes for object update:

- email
- username
- name

Optional attributes for object update:

- password
- skype
- linkedin
- twitter
- projects_limit
- extern_uid
- provider
- bio
- admin
- can_create_group
- website_url
- skip_reconfirmation
- external
- organization
- location
- avatar
- public_email
- private_profile
- color_scheme_id
- theme_id

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional*[`RESTObject`]) –

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → `User`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`User`

gitlab: `Gitlab`

class `gitlab.v4.objects.UserMembership`(*manager*: `RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`, *lazy*: `bool = False`)

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.UserMembershipManager`(*gl*: `Gitlab`, *parent*: *Optional*[`RESTObject`] = `None`)

Bases: `RetrieveMixin, RESTManager`

Object listing filters

- `type`

Object Creation**Object update****Parameters**

- **gl** (`Gitlab`) –
- **parent** (*Optional*[`RESTObject`]) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → UserMembership
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`UserMembership`

gitlab: `Gitlab`

```
class gitlab.v4.objects.UserPersonalAccessToken(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.UserPersonalAccessTokenManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `CreateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `name`
- `scopes`

Optional attributes for object create:

- `expires_at`

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

```
gitlab: Gitlab

class gitlab.v4.objects.UserProject(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:
                                         bool = False, lazy: bool = False)
Bases: RESTObject

Parameters
• manager (RESTManager) –
• attrs (Dict[str, Any]) –
• created_from_list (bool) –
• lazy (bool) –

manager: RESTManager

class gitlab.v4.objects.UserProjectManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, CreateMixin, RESTManager

Object listing filters
• archived
• visibility
• order_by
• sort
• search
• simple
• owned
• membership
• starred
• statistics
• with_issues_enabled
• with_merge_requests_enabled
• with_custom_attributes
• with_programming_language
• wiki_checksum_failed
• repository_checksum_failed
• min_access_level
• id_after
• id_before
```

Object Creation

Required attributes for object create:

- name

Optional attributes for object create:

- `default_branch`
- `issues_enabled`
- `wall_enabled`
- `merge_requests_enabled`
- `wiki_enabled`
- `snippets_enabled`
- `squash_option`
- `public`
- `visibility`
- `description`
- `builds_enabled`
- `public_builds`
- `import_url`
- `only_allow_merge_if_build_succeeds`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

`list(**kwargs: Any) → Union[RESTObjectList, List[RESTObject]]`

Retrieve a list of objects.

Parameters

- `all` – If True, return all the items, without pagination
- `per_page` – Number of items to retrieve per request
- `page` – ID of the page to return (starts with page 1)
- `iterator` – If set to True and no pagination option is defined, return a generator instead of a list
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The list of objects, or a generator if `iterator` is True

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the server cannot perform the request

Return type

`Union[RESTObjectList, List[RESTObject]]`

```
class gitlab.v4.objects.UserStatus(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.UserStatusManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → UserStatus**

Retrieve a single object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

UserStatus

gitlab: *Gitlab*

```
class gitlab.v4.objects.Variable(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.VariableManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: CRUDMixin, RESTManager
```

Object Creation

Required attributes for object create:

- key
- value

Optional attributes for object create:

- protected
- variable_type
- masked

Object update

Required attributes for object update:

- key
- value

Optional attributes for object update:

- protected
- variable_type
- masked

Parameters

- **gl** ([Gitlab](#)) –
- **parent** ([Optional\[RESTObject\]](#)) –

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → [Variable](#)

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[Variable](#)

gitlab: [Gitlab](#)

Module contents

7.6.3 Submodules

7.6.4 gitlab.base module

```
class gitlab.base.RESTManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: object

Base class for CRUD operations on objects.

Derived class must define `_path` and `_obj_cls`.

`_path`: Base URL path on which requests will be sent (e.g. ‘/projects’) `_obj_cls`: The class of objects that will be created

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`gitlab: Gitlab`

`property parent_attrs: Optional[Dict[str, Any]]`

`property path: Optional[str]`

```
class gitlab.base.RESTObject(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: object

Represents an object built from server data.

It holds the attributes known from the server, and the updated attributes in another. This allows smart updates, if the object allows it.

You can redefine `_id_attr` in child classes to specify which attribute must be used as the unique ID. `None` means that the object can be updated without ID in the url.

Likewise, you can define a `_repr_attr` in subclasses to specify which attribute should be added as a human-readable identifier when called in the object’s `__repr__()` method.

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

`asdict(*, with_parentAttrs: bool = False) → Dict[str, Any]`

Parameters

`with_parentAttrs (bool) –`

Return type

`Dict[str, Any]`

`property attributes: Dict[str, Any]`

property encoded_id: Optional[Union[int, str]]

Ensure that the ID is url-encoded so that it can be safely used in a URL path

get_id() → Optional[Union[int, str]]

Returns the id of the resource.

Return type

Optional[Union[int, str]]

manager: [RESTManager](#)

pformat() → str

Return type

str

pprint() → None

Return type

None

to_json(*, with_parent_attrs: bool = False, **kwargs: Any) → str

Parameters

- **with_parent_attrs (bool) –**
- **kwargs (Any) –**

Return type

str

class gitlab.base.RESTObjectList(manager: RESTManager, obj_cls: Type[RESTObject], _list: GitlabList)

Bases: object

Generator object representing a list of RESTObject's.

This generator uses the Gitlab pagination system to fetch new data when required.

Note: you should not instantiate such objects, they are returned by calls to RESTManager.list()

Parameters

- **manager (RESTManager) –** Manager to attach to the created objects
- **obj_cls (Type[RESTObject]) –** Type of objects to create from the json data
- **_list (GitlabList) –** A GitlabList object

property current_page: int

The current page number.

next() → RESTObject

Return type

RESTObject

property next_page: Optional[int]

The next page number.

If None, the current page is the last.

property per_page: Optional[int]

The number of items per page.

```
property prev_page: Optional[int]
    The previous page number.
    If None, the current page is the first.
property total: Optional[int]
    The total number of items.
property total_pages: Optional[int]
    The total number of pages.
```

7.6.5 gitlab.cli module

```
class gitlab.cli.VerticalHelpFormatter(prog, indent_increment=2, max_help_position=24, width=None)
Bases: HelpFormatter
format_help() → str

    Return type
        str

gitlab.cli.cls_to_gitlab_resource(cls: RESTObject) → str

    Parameters
        cls (RESTObject) –

    Return type
        str

gitlab.cli.die(msg: str, e: Optional[Exception] = None) → None

    Parameters
        • msg (str) –
        • e (Optional[Exception]) –

    Return type
        None

gitlab.cli.docs() → ArgumentParser
Provide a statically generated parser for sphinx only, so we don't need to provide dummy gitlab config for readthe-
docs.

    Return type
        ArgumentParser

gitlab.cli.gitlab_resource_to_cls(gitlab_resource: str, namespace: module) → Type[RESTObject]

    Parameters
        • gitlab_resource (str) –
        • namespace (module) –

    Return type
        Type[RESTObject]
```

`gitlab.cli.main()` → None

Return type

None

`gitlab.cli.register_custom_action(cls_names: Union[str, Tuple[str, ...]], mandatory: Tuple[str, ...] = (), optional: Tuple[str, ...] = (), custom_action: Optional[str] = None) → Callable[[_F], __F]`

Parameters

- `cls_names (Union[str, Tuple[str, ...]])` –
- `mandatory (Tuple[str, ...])` –
- `optional (Tuple[str, ...])` –
- `custom_action (Optional[str])` –

Return type

`Callable[[_F], __F]`

7.6.6 gitlab.config module

`exception gitlab.config.ConfigError`

Bases: `Exception`

`exception gitlab.config.GitlabConfigHelperError`

Bases: `ConfigError`

`exception gitlab.config.GitlabConfigMissingError`

Bases: `ConfigError`

`class gitlab.config.GitlabConfigParser(gitlab_id: Optional[str] = None, config_files: Optional[List[str]] = None)`

Bases: `object`

Parameters

- `gitlab_id (Optional[str])` –
- `config_files (Optional[List[str]])` –

`exception gitlab.config.GitlabDataError`

Bases: `ConfigError`

`exception gitlab.config.GitlabIDError`

Bases: `ConfigError`

7.6.7 gitlab.const module

```
class gitlab.const.AccessLevel(value)
    Bases: IntEnum

    An enumeration.

    ADMIN: int = 60
    DEVELOPER: int = 30
    GUEST: int = 10
    MAINTAINER: int = 40
    MINIMAL_ACCESS: int = 5
    NO_ACCESS: int = 0
    OWNER: int = 50
    REPORTER: int = 20

class gitlab.const.NotificationLevel(value)
    Bases: GitlabEnum

    An enumeration.

    CUSTOM: str = 'custom'
    DISABLED: str = 'disabled'
    GLOBAL: str = 'global'
    MENTION: str = 'mention'
    PARTICIPATING: str = 'participating'
    WATCH: str = 'watch'

class gitlab.const.SearchScope(value)
    Bases: GitlabEnum

    An enumeration.

    BLOBS: str = 'blobs'
    COMMITS: str = 'commits'
    GLOBAL_SNIPPET_TITLES: str = 'snippet_titles'
    ISSUES: str = 'issues'
    MERGE_REQUESTS: str = 'merge_requests'
    MILESTONES: str = 'milestones'
    PROJECTS: str = 'projects'
    PROJECT_NOTES: str = 'notes'
```

```
USERS: str = 'users'

WIKI_BLOBS: str = 'wiki_blobs'

class gitlab.const.Visibility(value)

Bases: GitlabEnum

An enumeration.

INTERNAL: str = 'internal'

PRIVATE: str = 'private'

PUBLIC: str = 'public'
```

7.6.8 gitlab.exceptions module

```
exception gitlab.exceptions.GitlabActivateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabAttachFileError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabAuthenticationError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBanError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBlockError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBuildCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabCancelError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBuildEraseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBuildPlayError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBuildRetryError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabCancelError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes]  
                                              = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabCherryPickError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabCiLintError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabConnectionError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabCreateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabDeactivateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabDeleteError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabDeploymentApprovalError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [Exception](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabFollowError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabGetError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabGroupTransferError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabHeadError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabHousekeepingError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabHttpError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabImportError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabInvitationError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabJobCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabCancelError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabJobEraseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabJobPlayError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabJobRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabLicenseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabListError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabMRApiApprovalError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabMRClosedError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabMRForbiddenError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabMROnBuildSuccessError(error_message: Union[str, bytes] = "",  
                                                       response_code: Optional[int] = None,  
                                                       response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabMRRebaseError(error_message: Union[str, bytes] = "", response_code:  
                                               Optional[int] = None, response_body:  
                                               Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabMRResetApprovalError(error_message: Union[str, bytes] = "",  
                                                       response_code: Optional[int] = None,  
                                                       response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabMarkdownError(error_message: Union[str, bytes] = "", response_code:  
                                               Optional[int] = None, response_body:  
                                               Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabOperationError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: [GitlabError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabOwnershipError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabParsingError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes]  
                                              = None)
```

Bases: [GitlabError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabPipelineCancelError(error_message: Union[str, bytes] = "",  
                                                       response_code: Optional[int] = None,  
                                                       response_body: Optional[bytes] = None)
```

Bases: [GitlabCancelError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabPipelinePlayError(error_message: Union[str, bytes] = "",  
                                                 response_code: Optional[int] = None,  
                                                 response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabPipelineRetryError(error_message: Union[str, bytes] = "",  
                                                 response_code: Optional[int] = None,  
                                                 response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabProjectDeployKeyError(error_message: Union[str, bytes] = "",  
                                                       response_code: Optional[int] = None,  
                                                       response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabPromoteError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes]  
                                              = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabProtectError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabRenderError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabRepairError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabRestoreError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabRevertError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabSearchError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabSetError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabStopError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabSubscribeError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabTimeTrackingError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabTodoError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabTopicMergeError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabTransferProjectError(error_message: Union[str, bytes] = "",  
                                                       response_code: Optional[int] = None,  
                                                       response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUnbanError(error_message: Union[str, bytes] = "", response_code:  
                                             Optional[int] = None, response_body: Optional[bytes] =  
                                             None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUnblockError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes] =  
                                              None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUnfollowError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUnsubscribeError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUpdateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUploadError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUserApproveError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUserRejectError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabVerifyError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes]  
                                              = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.RedirectError(error_message: Union[str, bytes] = "", response_code:  
                                         Optional[int] = None, response_body: Optional[bytes] =  
                                         None)
```

Bases: *GitlabError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

7.6.9 gitlab.mixins module

```
class gitlab.mixins.AccessRequestMixin
```

Bases: object

```
approve(access_level: int = 30, **kwargs: Any) → None
```

Approve an access request.

Parameters

- **access_level (int)** – The access level for the user
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server fails to perform the request

Return type

None

manager: *RESTManager*

```
class gitlab.mixins.BadgeRenderMixin
```

Bases: object

```
render(link_url: str, image_url: str, **kwargs: Any) → Dict[str, Any]
```

Preview link_url and image_url after interpolation.

Parameters

- **link_url (str)** – URL of the badge link
- **image_url (str)** – URL of the badge image
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabRenderError** – If the rendering failed

Returns

The rendering properties

Return type

Dict[str, Any]

```
class gitlab.mixins.CRUDMixin
```

Bases: *GetMixin, ListMixin, CreateMixin, UpdateMixin, DeleteMixin*

gitlab: *Gitlab*

```
class gitlab.mixins.CreateMixin
```

Bases: object

```
create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → RESTObject
```

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – parameters to send to the server to create the resource
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

A new instance of the managed object class built with
the data sent by the server

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Return type

`RESTObject`

gitlab: `Gitlab`

```
class gitlab.mixins.DeleteMixin
```

Bases: `object`

```
delete(id: Optional[Union[int, str]] = None, **kwargs: Any) → None
```

Delete an object on the server.

Parameters

- **id** (*Optional[Union[int, str]]*) – ID of the object to delete
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

`None`

gitlab: `Gitlab`

```
class gitlab.mixins.DownloadMixin
```

Bases: `object`

```
download(streamed: bool = False, action: Optional[Callable[[bytes], None]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]
```

Download the archive of a resource export.

Parameters

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[[bytes], None]]*) – Callable responsible of dealing with chunk of data

- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The blob content if streamed is False, None otherwise

Return type

Optional[Union[bytes, Iterator[Any]]]

manager: *RESTManager*

class gitlab.mixins.GetMixin

Bases: HeadMixin, object

get(*id: Union[str, int]*, *lazy: bool = False*, ****kwargs: Any**) → *RESTObject*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

RESTObject

gitlab: *Gitlab*

class gitlab.mixins.GetWithoutIdMixin

Bases: HeadMixin, object

get(****kwargs: Any**) → *RESTObject*

Retrieve a single object.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

```
Return type  
RESTObject

gitlab: Gitlab

class gitlab.mixins.ListMixin
Bases: HeadMixin, object

gitlab: Gitlab

list(**kwargs: Any) → Union[RESTObjectList, List[RESTObject]]
Retrieve a list of objects.

Parameters
• all – If True, return all the items, without pagination
• per_page – Number of items to retrieve per request
• page – ID of the page to return (starts with page 1)
• iterator – If set to True and no pagination option is defined, return a generator instead of a list
• **kwargs (Any) – Extra options to send to the server (e.g. sudo)

Returns
The list of objects, or a generator if iterator is True

Raises
• GitlabAuthenticationError – If authentication is not correct
• GitlabListError – If the server cannot perform the request

Return type
Union[RESTObjectList, List[RESTObject]]

class gitlab.mixins.NoUpdateMixin
Bases: GetMixin, ListMixin, CreateMixin, DeleteMixin

gitlab: Gitlab

class gitlab.mixins.ObjectDeleteMixin
Bases: object

Mixin for RESTObject's that can be deleted.

delete(**kwargs: Any) → None
Delete the object from the server.

Parameters
**kwargs (Any) – Extra options to send to the server (e.g. sudo)

Raises
• GitlabAuthenticationError – If authentication is not correct
• GitlabDeleteError – If the server cannot perform the request

Return type
None

manager: RESTManager
```

```
class gitlab.mixins.ParticipantsMixin
    Bases: object

    manager: RESTManager

    participants(**kwargs: Any) → Dict[str, Any]
        List the participants.

        Parameters
            • all – If True, return all the items, without pagination
            • per_page – Number of items to retrieve per request
            • page – ID of the page to return (starts with page 1)
            • **kwargs (Any) – Extra options to send to the server (e.g. sudo)

        Raises
            • GitlabAuthenticationError – If authentication is not correct
            • GitlabListError – If the list could not be retrieved

        Returns
            The list of participants

        Return type
            Dict[str, Any]

class gitlab.mixins.RefreshMixin
    Bases: object

    manager: RESTManager

    refresh(**kwargs: Any) → None
        Refresh a single object from server.

        Parameters
            **kwargs (Any) – Extra options to send to the server (e.g. sudo)

        Return type
            None

        Returns None (updates the object)

        Raises
            • GitlabAuthenticationError – If authentication is not correct
            • GitlabGetError – If the server cannot perform the request

        Parameters
            kwargs (Any) –

        Return type
            None

class gitlab.mixins.RetrieveMixin
    Bases: ListMixin, GetMixin

    gitlab: Gitlab
```

class gitlab.mixins.SaveMixin

Bases: object

Mixin for RESTObject's that can be updated.

manager: RESTManager

save(kwargs: Any) → Optional[Dict[str, Any]]**

Save the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

**kwargs (Any) – Extra options to send to the server (e.g. sudo)

Returns

The new object data (*not* a RESTObject)

Raises

- GitlabAuthenticationError – If authentication is not correct
- GitlabUpdateError – If the server cannot perform the request

Return type

Optional[Dict[str, Any]]

class gitlab.mixins.SetMixin

Bases: object

gitlab: Gitlab

set(key: str, value: str, **kwargs: Any) → RESTObject

Create or update the object.

Parameters

- key (str) – The key of the object to create/update
- value (str) – The value to set for the object
- **kwargs (Any) – Extra options to send to the server (e.g. sudo)

Raises

- GitlabAuthenticationError – If authentication is not correct
- GitlabSetError – If an error occurred

Returns

The created/updated attribute

Return type

RESTObject

class gitlab.mixins.SubscribableMixin

Bases: object

manager: RESTManager

subscribe(kwargs: Any) → None**

Subscribe to the object notifications.

Parameters

**kwargs (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSubscribeError** – If the subscription cannot be done

Return type

None

unsubscribe(kwargs: Any) → None**

Unsubscribe from the object notifications.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUnsubscribeError** – If the unsubscription cannot be done

Return type

None

class gitlab.mixins.TimeTrackingMixin

Bases: object

add_spent_time(duration: str, **kwargs: Any) → Dict[str, Any]

Add time spent working on the object.

Parameters

- **duration (str)** – Duration in human format (e.g. 3h30)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTimeTrackingError** – If the time tracking update cannot be done

Return type

Dict[str, Any]

manager: RESTManager

reset_spent_time(kwargs: Any) → Dict[str, Any]**

Resets the time spent working on the object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTimeTrackingError** – If the time tracking update cannot be done

Return type

Dict[str, Any]

reset_time_estimate(kwargs: Any) → Dict[str, Any]**

Resets estimated time for the object to 0 seconds.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTimeTrackingError** – If the time tracking update cannot be done

Return type

Dict[str, Any]

time_estimate(duration: str, **kwargs: Any) → Dict[str, Any]

Set an estimated time of work for the object.

Parameters

- **duration (str)** – Duration in human format (e.g. 3h30)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTimeTrackingError** – If the time tracking update cannot be done

Return type

Dict[str, Any]

time_stats(kwargs: Any) → Dict[str, Any]**

Get time stats for the object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTimeTrackingError** – If the time tracking update cannot be done

Return type

Dict[str, Any]

class gitlab.mixins.TodoMixin

Bases: `object`

manager: `RESTManager`

todo(kwargs: Any) → None**

Create a todo associated to the object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTodoError** – If the todo cannot be set

Return type

`None`

```
class gitlab.mixins.UpdateMixin
    Bases: object
    gitlab: Gitlab
    update(id: Optional[Union[int, str]] = None, new_data: Optional[Dict[str, Any]] = None, **kwargs: Any) → Dict[str, Any]
        Update an object on the server.

    Parameters
        • id (Optional[Union[int, str]]) – ID of the object to update (can be None if not required)
        • new_data (Optional[Dict[str, Any]]) – the update data for the object
        • **kwargs (Any) – Extra options to send to the server (e.g. sudo)

    Returns
        The new object data (not a RESTObject)

    Raises
        • GitlabAuthenticationError – If authentication is not correct
        • GitlabUpdateError – If the server cannot perform the request

    Return type
        Dict[str, Any]

class gitlab.mixins.UserAgentDetailMixin
    Bases: object
    manager: RESTManager
    user_agent_detail(**kwargs: Any) → Dict[str, Any]
        Get the user agent detail.

    Parameters
        • **kwargs (Any) – Extra options to send to the server (e.g. sudo)

    Raises
        • GitlabAuthenticationError – If authentication is not correct
        • GitlabGetError – If the server cannot perform the request

    Returns
        Dict[str, Any]
```

7.6.10 gitlab.utils module

```
class gitlab.utils.EncodedId(value: Union[str, int, EncodedId])
    Bases: str
    A custom str class that will return the URL-encoded value of the string.

    • Using it recursively will only url-encode the value once.
    • Can accept either str or int as input value.
    • Can be used in an f-string and output the URL-encoded string.
```

Reference to documentation on why this is necessary.

See:

<https://docs.gitlab.com/ee/api/index.html#namespaced-path-encoding>
<https://docs.gitlab.com/ee/api/index.html#path-parameters>

Parameters

`value (Union[str, int, EncodedId]) –`

Return type

`EncodedId`

`gitlab.utils.copy_dict(*, src: Dict[str, Any], dest: Dict[str, Any]) → None`

Parameters

- `src (Dict[str, Any]) –`
- `dest (Dict[str, Any]) –`

Return type

`None`

`gitlab.utils.get_content_type(content_type: Optional[str]) → str`

Parameters

`content_type (Optional[str]) –`

Return type

`str`

`gitlab.utils.remove_none_from_dict(data: Dict[str, Any]) → Dict[str, Any]`

Parameters

`data (Dict[str, Any]) –`

Return type

`Dict[str, Any]`

`gitlab.utils.response_content(response: Response, streamed: bool, action: Optional[Callable[[bytes], None]], chunk_size: int, *, iterator: bool) → Optional[Union[bytes, Iterator[Any]]]`

Parameters

- `response (Response) –`
- `streamed (bool) –`
- `action (Optional[Callable[[bytes], None]]) –`
- `chunk_size (int) –`
- `iterator (bool) –`

Return type

`Optional[Union[bytes, Iterator[Any]]]`

```
gitlab.utils.warn(message: str, *, category: Optional[Type[Warning]] = None, source: Optional[Any] = None) → None
```

This `warnings.warn` wrapper function attempts to show the location causing the warning in the user code that called the library.

It does this by walking up the stack trace to find the first frame located outside the `gitlab/` directory. This is helpful to users as it shows them their code that is causing the warning.

Parameters

- **message** (`str`) –
- **category** (`Optional[Type[Warning]]`) –
- **source** (`Optional[Any]`) –

Return type

`None`

7.7 CLI reference (gitlab command)

Warning: The following is a complete, auto-generated list of subcommands available via the `gitlab` command-line tool. Some of the actions may currently not work as expected or lack functionality available via the API.

Please see the existing [list of CLI related issues](#), or open a new one if it is not already listed there.

7.7.1 gitlab

GitLab API Command Line Interface

```
usage: gitlab [-h] [--version] [-v] [-d] [-c CONFIG_FILE] [-g GITLAB]
              [-o {json,legacy,yaml}] [-f FIELDS] [--server-url SERVER_URL]
              [--ssl-verify SSL_VERIFY] [--timeout TIMEOUT]
              [--api-version API_VERSION] [--per-page PER_PAGE]
              [--pagination PAGINATION] [--order-by ORDER_BY]
              [--user-agent USER_AGENT]
              [--private-token PRIVATE_TOKEN | --oauth-token OAUTH_TOKEN | --job-token
               ↵JOB_TOKEN]
              application
              application-appearance
              application-settings
              application-statistics
              audit-event
              broadcast-message
              bulk-import
              bulk-import-all-entity
              bulk-import-entity
              ci-lint
              current-user
              current-user-email
              current-user-gpg-key
              current-user-key
              current-user-status
```

(continues on next page)

(continued from previous page)

```
deploy-key
deploy-token
dockerfile
event
feature
generic-package
geo-node
gitignore
gitlabciyml
group
group-access-request
group-access-token
group-audit-event
group-badge
group-billable-member
group-billable-member-membership
group-board
group-board-list
group-cluster
group-custom-attribute
group-deploy-token
group-descendant-group
group-epic
group-epic-award-emoji
group-epic-discussion-note
group-epic-issue
group-epic-note
group-epic-note-award-emoji
group-epic-resource-label-event
group-export
group-hook
group-import
group-invitation
group-issue
group-issues-statistics
group-iteration
group-ldap-group-link
group-label
group-member
group-member-all
group-merge-request
group-milestone
group-notification-settings
group-package
group-project
group-push-rules
group-runner
group-saml-group-link
group-subgroup
group-variable
group-wiki
hook
```

(continues on next page)

(continued from previous page)

```
issue
issues-statistics
key
ldap-group
license
merge-request
namespace
notification-settings
pages-domain
personal-access-token
project
project-access-request
project-access-token
project-additional-statistics
project-approval
project-approval-rule
project-artifact
project-audit-event
project-badge
project-board
project-board-list
project-branch
project-ci-lint
project-cluster
project-commit
project-commit-comment
project-commit-discussion
project-commit-discussion-note
project-commit-status
project-custom-attribute
project-deploy-token
project-deployment
project-deployment-merge-request
project-environment
project-event
project-export
project-file
project-fork
project-hook
project-import
project-integration
project-invitation
project-issue
project-issue-award-emoji
project-issue-discussion
project-issue-discussion-note
project-issue-link
project-issue-note
project-issue-note-award-emoji
project-issue-resource-iteration-event
project-issue-resource-label-event
project-issue-resource-milestone-event
```

(continues on next page)

(continued from previous page)

```
project-issue-resource-state-event
project-issue-resource-weight-event
project-issues-statistics
project-job
project-key
project-label
project-member
project-member-all
project-merge-request
project-merge-request-approval
project-merge-request-approval-rule
project-merge-request-approval-state
project-merge-request-award-emoji
project-merge-request-diff
project-merge-request-discussion
project-merge-request-discussion-note
project-merge-request-note
project-merge-request-note-award-emoji
project-merge-request-pipeline
project-merge-request-resource-label-event
project-merge-request-resource-milestone-event
project-merge-request-resource-state-event
project-merge-train
project-milestone
project-note
project-notification-settings
project-package
project-package-file
project-pages-domain
project-pipeline
project-pipeline-bridge
project-pipeline-job
project-pipeline-schedule
project-pipeline-schedule-pipeline
project-pipeline-schedule-variable
project-pipeline-test-report
project-pipeline-test-report-summary
project-pipeline-variable
project-protected-branch
project-protected-environment
project-protected-tag
project-push-rules
project-registry-repository
project-registry-tag
project-release
project-release-link
project-remote-mirror
project-resource-group
project-resource-group-upcoming-job
project-runner
project-secure-file
project-service
```

(continues on next page)

(continued from previous page)

```
project-snippet
project-snippet-award-emoji
project-snippet-discussion
project-snippet-discussion-note
project-snippet-note
project-snippet-note-award-emoji
project-storage
project-tag
project-trigger
project-user
project-variable
project-wiki
registry-repository
runner
runner-all
runner-job
shared-project
snippet
starred-project
todo
topic
user
user-activities
user-custom-attribute
user-email
user-event
user-gpg-key
user-impersonation-token
user-key
user-membership
user-personal-access-token
user-project
user-status
variable
...
```

-h, --help

show this help message and exit

--version

Display the version.

-v, --verbose, --fancy

Verbose mode (legacy format only) [env var: GITLAB_VERBOSE]

-d, --debug

Debug mode (display HTTP requests) [env var: GITLAB_DEBUG]

-c <config_file>, --config-file <config_file>

Configuration file to use. Can be used multiple times. [env var: PYTHON_GITLAB_CFG]

-g <gitlab>, --gitlab <gitlab>

Which configuration section should be used. If not defined, the default selection will be used.

```

-o {json,legacy,yaml}, --output {json,legacy,yaml}
    Output format (v4 only): json|legacy|yaml
-f <fields>, --fields <fields>
    Fields to display in the output (comma separated). Not used with legacy output
--server-url <server_url>
    GitLab server URL [env var: GITLAB_URL]
--ssl-verify <ssl_verify>
    Whether SSL certificates should be validated. [env var: GITLAB_SSL_VERIFY]
--timeout <timeout>
    Timeout to use for requests to the GitLab server. [env var: GITLAB_TIMEOUT]
--api-version <api_version>
    GitLab API version [env var: GITLAB_API_VERSION]
--per-page <per_page>
    Number of entries to return per page in the response. [env var: GITLAB_PER_PAGE]
--pagination <pagination>
    Whether to use keyset or offset pagination [env var: GITLAB_PAGINATION]
--order-by <order_by>
    Set order_by globally [env var: GITLAB_ORDER_BY]
--user-agent <user_agent>
    The user agent to send to GitLab with the HTTP request. [env var: GITLAB_USER_AGENT]
--private-token <private_token>
    GitLab private access token [env var: GITLAB_PRIVATE_TOKEN]
--oauth-token <oauth_token>
    GitLab OAuth token [env var: GITLAB_OAUTH_TOKEN]
--job-token <job_token>
    GitLab CI job token [env var: CI_JOB_TOKEN]

```

gitlab application

```
usage: gitlab application [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab application create

```
usage: gitlab application create [-h] [--sudo SUDO] --name NAME --redirect-uri
                                REDIRECT_URI --scopes SCOPES
                                [--confidential CONFIDENTIAL]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--name <name>
--redirect-uri <redirect_uri>
--scopes <scopes>
--confidential <confidential>
```

gitlab application delete

```
usage: gitlab application delete [-h] [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>
```

gitlab application list

```
usage: gitlab application list [-h] [--sudo SUDO] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab application-appearance

```
usage: gitlab application-appearance [-h] {get,update} ...
```

```
-h, --help
    show this help message and exit
```

gitlab application-appearance get

```
usage: gitlab application-appearance get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab application-appearance update

```
usage: gitlab application-appearance update [-h] [--sudo SUDO] [--title TITLE]
                                             [--description DESCRIPTION]
                                             [--logo LOGO]
                                             [--header-logo HEADER_LOGO]
                                             [--favicon FAVICON]
                                             [--new-project-guidelines NEW_PROJECT_
                                              ↵GUIDELINES]
                                             [--header-message HEADER_MESSAGE]
                                             [--footer-message FOOTER_MESSAGE]
                                             [--message-background-color MESSAGE_
                                              ↵BACKGROUND_COLOR]
                                             [--message-font-color MESSAGE_FONT_COLOR]
                                             [--email-header-and-footer-enabled EMAIL_
                                              ↵HEADER_AND_FOOTER_ENABLED]
```

-h, --help

show this help message and exit

--sudo <sudo>

--title <title>

--description <description>

--logo <logo>

--header-logo <header_logo>

--favicon <favicon>

--new-project-guidelines <new_project_guidelines>

--header-message <header_message>

--footer-message <footer_message>

--message-background-color <message_background_color>

--message-font-color <message_font_color>

--email-header-and-footer-enabled <email_header_and_footer_enabled>

gitlab application-settings

```
usage: gitlab application-settings [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab application-settings get

```
usage: gitlab application-settings get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab application-settings update

```
usage: gitlab application-settings update [-h] [--sudo SUDO] [--id ID]
                                         [--default-projects-limit DEFAULT_PROJECTS_
                                         ↵LIMIT]
                                         [--signup-enabled SIGNUP_ENABLED]
                                         [--password-authentication-enabled-for-web_
                                         ↵PASSWORD_AUTHENTICATION_ENABLED_FOR_WEB]
                                         [--gravatar-enabled GRAVATAR_ENABLED]
                                         [--sign-in-text SIGN_IN_TEXT]
                                         [--created-at CREATED_AT]
                                         [--updated-at UPDATED_AT]
                                         [--home-page-url HOME_PAGE_URL]
                                         [--default-branch-protection DEFAULT_BRANCH_
                                         ↵PROTECTION]
                                         [--restricted-visibility-levels RESTRICTED_
                                         ↵VISIBILITY_LEVELS]
                                         [--max-attachment-size MAX_ATTACHMENT_SIZE]
                                         [--session-expire-delay SESSION_EXPIRE_DELAY]
                                         [--default-project-visibility DEFAULT_PROJECT_
                                         ↵VISIBILITY]
                                         [--default-snippet-visibility DEFAULT_SNIPPET_
                                         ↵VISIBILITY]
                                         [--default-group-visibility DEFAULT_GROUP_
                                         ↵VISIBILITY]
                                         [--outbound-local-requests-whitelist OUTBOUND_
                                         ↵LOCAL_REQUESTS_WHITELIST]
                                         [--disabled-oauth-sign-in-sources DISABLED_
                                         ↵OAUTH_SIGN_IN_SOURCES]
                                         [--domain-whitelist DOMAIN_WHITELIST]
                                         [--domain-blacklist-enabled DOMAIN_BLACKLIST_
                                         ↵ENABLED]
                                         [--domain-blacklist DOMAIN_BLACKLIST]
                                         [--domain-allowlist DOMAIN_ALLOWLIST]
                                         [--domain-denylist-enabled DOMAIN_DENYLIST_
```

(continues on next page)

(continued from previous page)

↳ ENABLED]	[--domain-denylist DOMAIN_DENYLIST] [--external-authorization-service-enabled]
↳ EXTERNAL_AUTHORIZATION_SERVICE_ENABLED]	[--external-authorization-service-url EXTERNAL_
↳ AUTHORIZATION_SERVICE_URL]	[--external-authorization-service-default-
↳ label EXTERNAL_AUTHORIZATION_SERVICE_DEFAULT_LABEL]	[--external-authorization-service-timeout_
↳ EXTERNAL_AUTHORIZATION_SERVICE_TIMEOUT]	[--import-sources IMPORT_SOURCES] [--user-oauth-applications USER_OAUTH_
↳ APPLICATIONS]	[--after-sign-out-path AFTER_SIGN_OUT_PATH] [--container-registry-token-expire-delay_
↳ CONTAINER_REGISTRY_TOKEN_EXPIRE_DELAY]	[--repository-storages REPOSITORY_STORAGES] [--plantuml-enabled PLANTUML_ENABLED] [--plantuml-url PLANTUML_URL] [--terminal-max-session-time TERMINAL_MAX_
↳ SESSION_TIME]	[--polling-interval-multiplier POLLING_
↳ INTERVAL_MULTIPLIER]	[--rsa-key-restriction RSA_KEY_RESTRICTION] [--dsa-key-restriction DSA_KEY_RESTRICTION] [--ecdsa-key-restriction ECDSA_KEY_RESTRICTION] [--ed25519-key-restriction ED25519_KEY_
↳ RESTRICTION]	[--first-day-of-week FIRST_DAY_OF_WEEK] [--enforce-terms ENFORCE_TERMS] [--terms TERMS] [--performance-bar-allowed-group-id_
↳ PERFORMANCE_BAR_ALLOWED_GROUP_ID]	[--instance-statistics-visibility-private_
↳ INSTANCE_STATISTICS_VISIBILITY_PRIVATE]	[--user-show-add-ssh-key-message USER_SHOW_ADD_
↳ SSH_KEY_MESSAGE]	[--file-template-project-id FILE_TEMPLATE_
↳ PROJECT_ID]	[--local-markdown-version LOCAL_MARKDOWN_
↳ VERSION]	[--asset-proxy-enabled ASSET_PROXY_ENABLED] [--asset-proxy-url ASSET_PROXY_URL] [--asset-proxy-whitelist ASSET_PROXY_WHITELIST] [--asset-proxy-allowlist ASSET_PROXY_ALLOWLIST] [--geo-node-allowed-ips GEO_NODE_ALLOWED_IPS] [--allow-local-requests-from-hooks-and-
↳ services ALLOW_LOCAL_REQUESTS_FROM_HOOKS_AND_SERVICES]	[--allow-local-requests-from-web-hooks-and-
↳ services ALLOW_LOCAL_REQUESTS_FROM_WEB_HOOKS_AND_SERVICES]	[--allow-local-requests-from-system-hooks_
↳ ALLOW_LOCAL_REQUESTS_FROM_SYSTEM_HOOKS]	

```
-h, --help
    show this help message and exit

--sudo <sudo>

--id <id>

--default-projects-limit <default_projects_limit>

--signup-enabled <signup_enabled>

--password-authentication-enabled-for-web <password_authentication_enabled_for_web>

--gravatar-enabled <gravatar_enabled>

--sign-in-text <sign_in_text>

--created-at <created_at>

--updated-at <updated_at>

--home-page-url <home_page_url>

--default-branch-protection <default_branch_protection>

--restricted-visibility-levels <restricted_visibility_levels>

--max-attachment-size <max_attachment_size>

--session-expire-delay <session_expire_delay>

--default-project-visibility <default_project_visibility>

--default-snippet-visibility <default_snippet_visibility>

--default-group-visibility <default_group_visibility>

--outbound-local-requests-whitelist <outbound_local_requests_whitelist>

--disabled-oauth-sign-in-sources <disabled_oauth_sign_in_sources>

--domain-whitelist <domain_whitelist>

--domain-blacklist-enabled <domain_blacklist_enabled>

--domain-blacklist <domain_blacklist>

--domain-allowlist <domain_allowlist>

--domain-denylist-enabled <domain_denylist_enabled>

--domain-denylist <domain_denylist>

--external-authorization-service-enabled <external_authorization_service_enabled>

--external-authorization-service-url <external_authorization_service_url>

--external-authorization-service-default-label <external_authorization_service_default_label>

--external-authorization-service-timeout <external_authorization_service_timeout>
```

```
--import-sources <import_sources>
--user-oauth-applications <user_oauth_applications>
--after-sign-out-path <after_sign_out_path>
--container-registry-token-expire-delay <container_registry_token_expire_delay>
--repository-storages <repository_storages>
--plantuml-enabled <plantuml_enabled>
--plantuml-url <plantuml_url>
--terminal-max-session-time <terminal_max_session_time>
--polling-interval-multiplier <polling_interval_multiplier>
--rsa-key-restriction <rsa_key_restriction>
--dsa-key-restriction <dsa_key_restriction>
--ecdsa-key-restriction <ecdsa_key_restriction>
--ed25519-key-restriction <ed25519_key_restriction>
--first-day-of-week <first_day_of_week>
--enforce-terms <enforce_terms>
--terms <terms>
--performance-bar-allowed-group-id <performance_bar_allowed_group_id>
--instance-statistics-visibility-private <instance_statistics_visibility_private>
--user-show-add-ssh-key-message <user_show_add_ssh_key_message>
--file-template-project-id <file_template_project_id>
--local-markdown-version <local_markdown_version>
--asset-proxy-enabled <asset_proxy_enabled>
--asset-proxy-url <asset_proxy_url>
--asset-proxy-whitelist <asset_proxy_whitelist>
--asset-proxy-allowlist <asset_proxy_allowlist>
--geo-node-allowed-ips <geo_node_allowed_ips>
--allow-local-requests-from-hooks-and-services <allow_local_requests_from_hooks_and_services>
--allow-local-requests-from-web-hooks-and-services <allow_local_requests_from_web_hooks_and_services>
--allow-local-requests-from-system-hooks <allow_local_requests_from_system_hooks>
```

gitlab application-statistics

```
usage: gitlab application-statistics [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab application-statistics get

```
usage: gitlab application-statistics get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab audit-event

```
usage: gitlab audit-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab audit-event get

```
usage: gitlab audit-event get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab audit-event list

```
usage: gitlab audit-event list [-h] [--sudo SUDO]
                               [--created-after CREATED_AFTER]
                               [--created-before CREATED_BEFORE]
                               [--entity-type ENTITY_TYPE]
                               [--entity-id ENTITY_ID] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--created-after <created_after>

```
--created-before <created_before>
--entity-type <entity_type>
--entity-id <entity_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab broadcast-message

```
usage: gitlab broadcast-message [-h] {list,get,create,update,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab broadcast-message create

```
usage: gitlab broadcast-message create [-h] [--sudo SUDO] --message MESSAGE
                                         [--starts-at STARTS_AT]
                                         [--ends-at ENDS_AT] [--color COLOR]
                                         [--font FONT]
                                         [--target-access-levels TARGET_ACCESS_LEVELS]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--message <message>
--starts-at <starts_at>
--ends-at <ends_at>
--color <color>
--font <font>
--target-access-levels <target_access_levels>
```

gitlab broadcast-message delete

```
usage: gitlab broadcast-message delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab broadcast-message get

```
usage: gitlab broadcast-message get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab broadcast-message list

```
usage: gitlab broadcast-message list [-h] [--sudo SUDO] [--page PAGE]
                                     [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab broadcast-message update

```
usage: gitlab broadcast-message update [-h] [--sudo SUDO] --id ID
                                         [--message MESSAGE]
                                         [--starts-at STARTS_AT]
                                         [--ends-at ENDS_AT] [--color COLOR]
                                         [--font FONT]
                                         [--target-access-levels TARGET_ACCESS_LEVELS]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>
--message <message>
--starts-at <starts_at>
--ends-at <ends_at>
--color <color>
--font <font>
--target-access-levels <target_access_levels>
```

gitlab bulk-import

```
usage: gitlab bulk-import [-h] {list,get,create} ...
```

```
-h, --help
    show this help message and exit
```

gitlab bulk-import create

```
usage: gitlab bulk-import create [-h] [--sudo SUDO] --configuration
                                 CONFIGURATION --entities ENTITIES
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--configuration <configuration>
--entities <entities>
```

gitlab bulk-import get

```
usage: gitlab bulk-import get [-h] [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>
```

gitlab bulk-import list

```
usage: gitlab bulk-import list [-h] [--sudo SUDO] [--sort SORT]
                               [--status STATUS] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--sort <sort>

--status <status>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab bulk-import-all-entity

```
usage: gitlab bulk-import-all-entity [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab bulk-import-all-entity list

```
usage: gitlab bulk-import-all-entity list [-h] [--sudo SUDO] [--sort SORT]
                                         [--status STATUS] [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--sort <sort>

--status <status>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab bulk-import-entity

```
usage: gitlab bulk-import-entity [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab bulk-import-entity get

```
usage: gitlab bulk-import-entity get [-h] [--sudo SUDO] --bulk-import-id
                                     BULK_IMPORT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--bulk-import-id <bulk_import_id>****--id <id>****gitlab bulk-import-entity list**

```
usage: gitlab bulk-import-entity list [-h] [--sudo SUDO] --bulk-import-id
                                       BULK_IMPORT_ID [--sort SORT]
                                       [--status STATUS] [--page PAGE]
                                       [--per-page PER_PAGE] [--get-all]
                                       [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--bulk-import-id <bulk_import_id>****--sort <sort>****--status <status>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab ci-lint

```
usage: gitlab ci-lint [-h] {create,validate} ...
```

-h, --help

show this help message and exit

gitlab ci-lint create

```
usage: gitlab ci-lint create [-h] [--sudo SUDO] --content CONTENT
                             [--include-merged-yaml INCLUDE_MERGED_YAML]
                             [--include-jobs INCLUDE_JOBS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--content <content>

--include-merged-yaml <include_merged_yaml>

--include-jobs <include_jobs>

gitlab ci-lint validate

```
usage: gitlab ci-lint validate [-h] --content CONTENT
                               [--include-merged-yaml INCLUDE_MERGED_YAML]
                               [--include-jobs INCLUDE_JOBS]
```

-h, --help

show this help message and exit

--content <content>

--include-merged-yaml <include_merged_yaml>

--include-jobs <include_jobs>

gitlab current-user

```
usage: gitlab current-user [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab current-user get

```
usage: gitlab current-user get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>**gitlab current-user-email**

```
usage: gitlab current-user-email [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab current-user-email create

```
usage: gitlab current-user-email create [-h] [--sudo SUDO] --email EMAIL
```

-h, --help

show this help message and exit

--sudo <sudo>**--email <email>****gitlab current-user-email delete**

```
usage: gitlab current-user-email delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--id <id>****gitlab current-user-email get**

```
usage: gitlab current-user-email get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--id <id>**

gitlab current-user-email list

```
usage: gitlab current-user-email list [-h] [--sudo SUDO] [--page PAGE]
                                     [--per-page PER_PAGE] [--get-all]
                                     [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab current-user-gpg-key

```
usage: gitlab current-user-gpg-key [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab current-user-gpg-key create

```
usage: gitlab current-user-gpg-key create [-h] [--sudo SUDO] --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

gitlab current-user-gpg-key delete

```
usage: gitlab current-user-gpg-key delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-gpg-key get

```
usage: gitlab current-user-gpg-key get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-gpg-key list

```
usage: gitlab current-user-gpg-key list [-h] [--sudo SUDO] [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab current-user-key

```
usage: gitlab current-user-key [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab current-user-key create

```
usage: gitlab current-user-key create [-h] [--sudo SUDO] --title TITLE --key
                                         KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--title <title>

--key <key>

gitlab current-user-key delete

```
usage: gitlab current-user-key delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-key get

```
usage: gitlab current-user-key get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-key list

```
usage: gitlab current-user-key list [-h] [--sudo SUDO] [--page PAGE]
                                    [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab current-user-status

```
usage: gitlab current-user-status [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab current-user-status get

```
usage: gitlab current-user-status get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab current-user-status update

```
usage: gitlab current-user-status update [-h] [--sudo SUDO] [--emoji EMOJI]
                                         [--message MESSAGE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--emoji <emoji>

--message <message>

gitlab deploy-key

```
usage: gitlab deploy-key [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab deploy-key list

```
usage: gitlab deploy-key list [-h] [--sudo SUDO] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab deploy-token

```
usage: gitlab deploy-token [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab deploy-token list

```
usage: gitlab deploy-token list [-h] [--sudo SUDO] [--page PAGE]
                                 [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab dockerfile

```
usage: gitlab dockerfile [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab dockerfile get

```
usage: gitlab dockerfile get [-h] [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--name <name>

gitlab dockerfile list

```
usage: gitlab dockerfile list [-h] [--sudo SUDO] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab event

```
usage: gitlab event [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab event list

```
usage: gitlab event list [-h] [--sudo SUDO] [--action ACTION]
                           [--target-type TARGET_TYPE] [--before BEFORE]
                           [--after AFTER] [--sort SORT] [--page PAGE]
                           [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--action <action>

--target-type <target_type>

--before <before>

--after <after>

--sort <sort>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab feature

```
usage: gitlab feature [-h] {list,delete} ...
```

-h, --help

show this help message and exit

gitlab feature delete

```
usage: gitlab feature delete [-h] [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--name <name>

gitlab feature list

```
usage: gitlab feature list [-h] [--sudo SUDO] [--page PAGE]
                           [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab generic-package

```
usage: gitlab generic-package [-h] {upload,download} ...
```

-h, --help

show this help message and exit

gitlab generic-package download

```
usage: gitlab generic-package download [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --package-name
                                       PACKAGE_NAME --package-version
                                       PACKAGE_VERSION --file-name FILE_NAME
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--package-name <package_name>

--package-version <package_version>

--file-name <file_name>

gitlab generic-package upload

```
usage: gitlab generic-package upload [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --package-name PACKAGE_NAME
                                       --package-version PACKAGE_VERSION
                                       --file-name FILE_NAME --path PATH
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--package-name <package_name>

--package-version <package_version>

--file-name <file_name>

--path <path>

gitlab geo-node

```
usage: gitlab geo-node [-h]
  list
  get
  update
  delete
  repair
  status
  current-failures
  ...
```

-h, --help

show this help message and exit

gitlab geo-node current-failures

```
usage: gitlab geo-node current-failures [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab geo-node delete

```
usage: gitlab geo-node delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab geo-node get

```
usage: gitlab geo-node get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab geo-node list

```
usage: gitlab geo-node list [-h] [--sudo SUDO] [--page PAGE]
                            [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab geo-node repair

```
usage: gitlab geo-node repair [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab geo-node status

```
usage: gitlab geo-node status [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab geo-node update

```
usage: gitlab geo-node update [-h] [--sudo SUDO] --id ID [--enabled ENABLED]
                               [--url URL]
                               [--files-max-capacity FILES_MAX_CAPACITY]
                               [--repos-max-capacity REPOS_MAX_CAPACITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

```
--enabled <enabled>
--url <url>
--files-max-capacity <files_max_capacity>
--repos-max-capacity <repos_max_capacity>
```

gitlab gitignore

```
usage: gitlab gitignore [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab gitignore get

```
usage: gitlab gitignore get [-h] [--sudo SUDO] --name NAME
```

-h, --help
show this help message and exit
--sudo <sudo>
--name <name>

gitlab gitignore list

```
usage: gitlab gitignore list [-h] [--sudo SUDO] [--page PAGE]
                             [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help
show this help message and exit
--sudo <sudo>
--page <page>
--per-page <per_page>
--get-all
Return all items from the server, without pagination.
--all
Deprecated. Use --get-all instead.

gitlab gitlabciyml

```
usage: gitlab gitlabciyml [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab gitlabciyml get

```
usage: gitlab gitlabciyml get [-h] [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--name <name>

gitlab gitlabciyml list

```
usage: gitlab gitlabciyml list [-h] [--sudo SUDO] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab group

```
usage: gitlab group [-h]
    list
    get
    create
    update
    delete
    transfer-project
    transfer
    search
    add-ldap-group-link
    delete-ldap-group-link
```

(continues on next page)

(continued from previous page)

```
ldap-sync  
share  
unshare  
restore  
...
```

-h, --help

show this help message and exit

gitlab group add-ldap-group-link

```
usage: gitlab group add-ldap-group-link [-h] --id ID --cn CN --group-access  
GROUP_ACCESS --provider PROVIDER
```

-h, --help

show this help message and exit

--id <id>

--cn <cn>

--group-access <group_access>

--provider <provider>

gitlab group create

```
usage: gitlab group create [-h] [--sudo SUDO] --name NAME --path PATH  
[--description DESCRIPTION]  
[--membership-lock MEMBERSHIP_LOCK]  
[--visibility VISIBILITY]  
[--share-with-group-lock SHARE_WITH_GROUP_LOCK]  
[--require-two-factor-authentication REQUIRE_TWO_FACTOR_  
AUTHENTICATION]  
[--two-factor-grace-period TWO_FACTOR_GRACE_PERIOD]  
[--project-creation-level PROJECT_CREATION_LEVEL]  
[--auto-devops-enabled AUTO_DEVOPS_ENABLED]  
[--subgroup-creation-level SUBGROUP_CREATION_LEVEL]  
[--emails-disabled EMAILS_DISABLED]  
[--avatar AVATAR]  
[--mentions-disabled MENTIONS_DISABLED]  
[--lfs-enabled LFS_ENABLED]  
[--request-access-enabled REQUEST_ACCESS_ENABLED]  
[--parent-id PARENT_ID]  
[--default-branch-protection DEFAULT_BRANCH_PROTECTION]  
[--shared-runners-minutes-limit SHARED_RUNNERS_MINUTES_LIMIT]  
[--extra-shared-runners-minutes-limit EXTRA_SHARED_RUNNERS_  
MINUTES_LIMIT]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--name <name>
--path <path>
--description <description>
--membership-lock <membership_lock>
--visibility <visibility>
--share-with-group-lock <share_with_group_lock>
--require-two-factor-authentication <require_two_factor_authentication>
--two-factor-grace-period <two_factor_grace_period>
--project-creation-level <project_creation_level>
--auto-devops-enabled <auto_devops_enabled>
--subgroup-creation-level <subgroup_creation_level>
--emails-disabled <emails_disabled>
--avatar <avatar>
--mentions-disabled <mentions_disabled>
--lfs-enabled <lfs_enabled>
--request-access-enabled <request_access_enabled>
--parent-id <parent_id>
--default-branch-protection <default_branch_protection>
--shared-runners-minutes-limit <shared_runners_minutes_limit>
--extra-shared-runners-minutes-limit <extra_shared_runners_minutes_limit>
```

gitlab group delete

```
usage: gitlab group delete [-h] [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>
```

gitlab group delete-ldap-group-link

```
usage: gitlab group delete-ldap-group-link [-h] --id ID --cn CN  
                                         [--provider PROVIDER]
```

-h, --help

show this help message and exit

--id <id>

--cn <cn>

--provider <provider>

gitlab group get

```
usage: gitlab group get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab group ldap-sync

```
usage: gitlab group ldap-sync [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab group list

```
usage: gitlab group list [-h] [--sudo SUDO] [--skip-groups SKIP_GROUPS]  
                         [--all-available ALL_AVAILABLE] [--search SEARCH]  
                         [--order-by ORDER_BY] [--sort SORT]  
                         [--statistics STATISTICS] [--owned OWNED]  
                         [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]  
                         [--min-access-level MIN_ACCESS_LEVEL]  
                         [--top-level-only TOP_LEVEL_ONLY] [--page PAGE]  
                         [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--skip-groups <skip_groups>

```
--all-available <all_available>
--search <search>
--order-by <order_by>
--sort <sort>
--statistics <statistics>
--owned <owned>
--with-custom-attributes <with_custom_attributes>
--min-access-level <min_access_level>
--top-level-only <top_level_only>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group restore

```
usage: gitlab group restore [-h] --id ID
```

```
-h, --help
    show this help message and exit
--id <id>
```

gitlab group search

```
usage: gitlab group search [-h] --id ID --scope SCOPE --search SEARCH
```

```
-h, --help
    show this help message and exit
--id <id>
--scope <scope>
--search <search>
```

gitlab group share

```
usage: gitlab group share [-h] --id ID --group-id GROUP_ID --group-access
                           GROUP_ACCESS [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--id <id>

--group-id <group_id>

--group-access <group_access>

--expires-at <expires_at>

gitlab group transfer

```
usage: gitlab group transfer [-h] --id ID [--group-id GROUP_ID]
```

-h, --help

show this help message and exit

--id <id>

--group-id <group_id>

gitlab group transfer-project

```
usage: gitlab group transfer-project [-h] --id ID --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--id <id>

--project-id <project_id>

gitlab group unshare

```
usage: gitlab group unshare [-h] --id ID --group-id GROUP_ID
```

-h, --help

show this help message and exit

--id <id>

--group-id <group_id>

gitlab group update

```
usage: gitlab group update [-h] [--sudo SUDO] --id ID [--name NAME]
                           [--path PATH] [--description DESCRIPTION]
                           [--membership-lock MEMBERSHIP_LOCK]
                           [--share-with-group-lock SHARE_WITH_GROUP_LOCK]
                           [--visibility VISIBILITY]
                           [--require-two-factor-authentication REQUIRE_TWO_FACTOR_
                           AUTHENTICATION]
                           [--two-factor-grace-period TWO_FACTOR_GRACE_PERIOD]
                           [--project-creation-level PROJECT_CREATION_LEVEL]
                           [--auto-devops-enabled AUTO_DEVOPS_ENABLED]
                           [--subgroup-creation-level SUBGROUP_CREATION_LEVEL]
                           [--emails-disabled EMAILS_DISABLED]
                           [--avatar AVATAR]
                           [--mentions-disabled MENTIONS_DISABLED]
                           [--lfs-enabled LFS_ENABLED]
                           [--request-access-enabled REQUEST_ACCESS_ENABLED]
                           [--default-branch-protection DEFAULT_BRANCH_PROTECTION]
                           [--file-template-project-id FILE_TEMPLATE_PROJECT_ID]
                           [--shared-runners-minutes-limit SHARED_RUNNERS_MINUTES_LIMIT]
                           [--extra-shared-runners-minutes-limit EXTRA_SHARED_RUNNERS_
                           MINUTES_LIMIT]
                           [--prevent-forking-outside-group PREVENT_FORKING_OUTSIDE_
                           GROUP]
                           [--shared-runners-setting SHARED_RUNNERS_SETTING]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

--name <name>

--path <path>

--description <description>

--membership-lock <membership_lock>

--share-with-group-lock <share_with_group_lock>

--visibility <visibility>

--require-two-factor-authentication <require_two_factor_authentication>

--two-factor-grace-period <two_factor_grace_period>

--project-creation-level <project_creation_level>

--auto-devops-enabled <auto_devops_enabled>

--subgroup-creation-level <subgroup_creation_level>

```
--emails-disabled <emails_disabled>
--avatar <avatar>
--mentions-disabled <mentions_disabled>
--lfs-enabled <lfs_enabled>
--request-access-enabled <request_access_enabled>
--default-branch-protection <default_branch_protection>
--file-template-project-id <file_template_project_id>
--shared-runners-minutes-limit <shared_runners_minutes_limit>
--extra-shared-runners-minutes-limit <extra_shared_runners_minutes_limit>
--prevent-forking-outside-group <prevent_forking_outside_group>
--shared-runners-setting <shared_runners_setting>
```

gitlab group-access-request

```
usage: gitlab group-access-request [-h] {list,create,delete,approve} ...
```

-h, --help

show this help message and exit

gitlab group-access-request approve

```
usage: gitlab group-access-request approve [-h] --group-id GROUP_ID
                                         [--sudo SUDO] --id ID
                                         [--access-level ACCESS_LEVEL]
```

-h, --help

show this help message and exit

--group-id <group_id>

--sudo <sudo>

--id <id>

--access-level <access_level>

gitlab group-access-request create

```
usage: gitlab group-access-request create [-h] [--sudo SUDO] --group-id GROUP_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-access-request delete

```
usage: gitlab group-access-request delete [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-access-request list

```
usage: gitlab group-access-request list [-h] [--sudo SUDO] --group-id GROUP_ID  
[--page PAGE] [--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-access-token

```
usage: gitlab group-access-token [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab group-access-token create

```
usage: gitlab group-access-token create [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --name NAME --scopes SCOPES
                                         [--access-level ACCESS_LEVEL]
                                         [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

--scopes <scopes>

--access-level <access_level>

--expires-at <expires_at>

gitlab group-access-token delete

```
usage: gitlab group-access-token delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-access-token list

```
usage: gitlab group-access-token list [-h] [--sudo SUDO] --group-id GROUP_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-audit-event

```
usage: gitlab group-audit-event [-h] {list,get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-audit-event get

```
usage: gitlab group-audit-event get [-h] [--sudo SUDO] --group-id GROUP_ID
                                    --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-audit-event list

```
usage: gitlab group-audit-event list [-h] [--sudo SUDO] --group-id GROUP_ID
                                      [--created-after CREATED_AFTER]
                                      [--created-before CREATED_BEFORE]
                                      [--page PAGE] [--per-page PER_PAGE]
                                      [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--created-after <created_after>
```

```
--created-before <created_before>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-badge

```
usage: gitlab group-badge [-h] {list,get,create,update,delete,render} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-badge create

```
usage: gitlab group-badge create [-h] [--sudo SUDO] --group-id GROUP_ID
                                 --link-url LINK_URL --image-url IMAGE_URL
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--link-url <link_url>
--image-url <image_url>
```

gitlab group-badge delete

```
usage: gitlab group-badge delete [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                 ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-badge get

```
usage: gitlab group-badge get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-badge list

```
usage: gitlab group-badge list [-h] [--sudo SUDO] --group-id GROUP_ID  
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]  
                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-badge render

```
usage: gitlab group-badge render [-h] --group-id GROUP_ID [--sudo SUDO] --id  
                                 ID --link-url LINK_URL --image-url IMAGE_URL
```

-h, --help

show this help message and exit

--group-id <group_id>

--sudo <sudo>

--id <id>

--link-url <link_url>

--image-url <image_url>

gitlab group-badge update

```
usage: gitlab group-badge update [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                 ID [--link-url LINK_URL]
                                 [--image-url IMAGE_URL]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

--link-url <link_url>

--image-url <image_url>

gitlab group-billable-member

```
usage: gitlab group-billable-member [-h] {list,delete} ...
```

-h, --help

show this help message and exit

gitlab group-billable-member delete

```
usage: gitlab group-billable-member delete [-h] [--sudo SUDO] --group-id
                                         GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-billable-member list

```
usage: gitlab group-billable-member list [-h] [--sudo SUDO] --group-id
                                         GROUP_ID [--search SEARCH]
                                         [--sort SORT] [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--search <search>
--sort <sort>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-billable-member-membership

```
usage: gitlab group-billable-member-membership [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab group-billable-member-membership list

```
usage: gitlab group-billable-member-membership list [-h] [--sudo SUDO]
                                                    --group-id GROUP_ID
                                                    --user-id USER_ID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--get-all] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--user-id <user_id>

--page <page>

--per-page <per_page>

--get-all
Return all items from the server, without pagination.

--all
Deprecated. Use --get-all instead.

gitlab group-board

```
usage: gitlab group-board [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-board create

```
usage: gitlab group-board create [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                  NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

gitlab group-board delete

```
usage: gitlab group-board delete [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                  ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-board get

```
usage: gitlab group-board get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-board list

```
usage: gitlab group-board list [-h] [--sudo SUDO] --group-id GROUP_ID
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]
                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-board update

```
usage: gitlab group-board update [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                  ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-board-list

```
usage: gitlab group-board-list [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-board-list create

```
usage: gitlab group-board-list create [-h] [--sudo SUDO] --group-id GROUP_ID  
                                      --board-id BOARD_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

gitlab group-board-list delete

```
usage: gitlab group-board-list delete [-h] [--sudo SUDO] --group-id GROUP_ID  
                                      --board-id BOARD_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--id <id>

gitlab group-board-list get

```
usage: gitlab group-board-list get [-h] [--sudo SUDO] --group-id GROUP_ID  
                                      --board-id BOARD_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--id <id>

gitlab group-board-list list

```
usage: gitlab group-board-list list [-h] [--sudo SUDO] --group-id GROUP_ID
                                    --board-id BOARD_ID [--page PAGE]
                                    [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-board-list update

```
usage: gitlab group-board-list update [-h] [--sudo SUDO] --group-id GROUP_ID
                                       --board-id BOARD_ID --id ID --position
                                       POSITION
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--id <id>

--position <position>

gitlab group-cluster

```
usage: gitlab group-cluster [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-cluster create

```
usage: gitlab group-cluster create [-h] [--sudo SUDO] --group-id GROUP_ID
                                  --name NAME
                                  --platform-kubernetes-attributes
                                  PLATFORM_KUBERNETES_ATTRIBUTES
                                  [--domain DOMAIN] [--enabled ENABLED]
                                  [--managed MANAGED]
                                  [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

--platform-kubernetes-attributes <platform_kubernetes_attributes>

--domain <domain>

--enabled <enabled>

--managed <managed>

--environment-scope <environment_scope>

gitlab group-cluster delete

```
usage: gitlab group-cluster delete [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-cluster get

```
usage: gitlab group-cluster get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-cluster list

```
usage: gitlab group-cluster list [-h] [--sudo SUDO] --group-id GROUP_ID
                                 [--page PAGE] [--per-page PER_PAGE]
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-cluster update

```
usage: gitlab group-cluster update [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID [--name NAME] [--domain DOMAIN]
                                   [--management-project-id MANAGEMENT_PROJECT_ID]
                                   [--platform-kubernetes-attributes PLATFORM_KUBERNETES_
                                   ATTRIBUTES]
                                   [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

--name <name>

--domain <domain>

--management-project-id <management_project_id>

--platform-kubernetes-attributes <platform_kubernetes_attributes>

--environment-scope <environment_scope>

gitlab group-custom-attribute

```
usage: gitlab group-custom-attribute [-h] {list,get,delete} ...
```

-h, --help

show this help message and exit

gitlab group-custom-attribute delete

```
usage: gitlab group-custom-attribute delete [-h] [--sudo SUDO] --group-id
                                             GROUP_ID --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

gitlab group-custom-attribute get

```
usage: gitlab group-custom-attribute get [-h] [--sudo SUDO] --group-id
                                         GROUP_ID --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

gitlab group-custom-attribute list

```
usage: gitlab group-custom-attribute list [-h] [--sudo SUDO] --group-id
                                         GROUP_ID [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-deploy-token

```
usage: gitlab group-deploy-token [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab group-deploy-token create

```
usage: gitlab group-deploy-token create [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --name NAME --scopes SCOPES
                                         [--expires-at EXPIRES_AT]
                                         [--username USERNAME]
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--name <name>****--scopes <scopes>****--expires-at <expires_at>****--username <username>****gitlab group-deploy-token delete**

```
usage: gitlab group-deploy-token delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--id <id>**

gitlab group-deploy-token get

```
usage: gitlab group-deploy-token get [-h] [--sudo SUDO] --group-id GROUP_ID  
                                     --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-deploy-token list

```
usage: gitlab group-deploy-token list [-h] [--sudo SUDO] --group-id GROUP_ID  
                                      [--scopes SCOPES] [--page PAGE]  
                                      [--per-page PER_PAGE] [--get-all]  
                                      [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--scopes <scopes>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-descendant-group

```
usage: gitlab group-descendant-group [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-descendant-group list

```
usage: gitlab group-descendant-group list [-h] [--sudo SUDO] --group-id
                                         GROUP_ID [--skip-groups SKIP_GROUPS]
                                         [--all-available ALL_AVAILABLE]
                                         [--search SEARCH]
                                         [--order-by ORDER_BY] [--sort SORT]
                                         [--statistics STATISTICS]
                                         [--owned OWNED]
                                         [--with-custom-attributes WITH_CUSTOM_
                                         ↵ATTRIBUTES]
                                         [--min-access-level MIN_ACCESS_LEVEL]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--skip-groups <skip_groups>

--all-available <all_available>

--search <search>

--order-by <order_by>

--sort <sort>

--statistics <statistics>

--owned <owned>

--with-custom-attributes <with_custom_attributes>

--min-access-level <min_access_level>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-epic

```
usage: gitlab group-epic [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-epic create

```
usage: gitlab group-epic create [-h] [--sudo SUDO] --group-id GROUP_ID --title
                                TITLE [--labels LABELS]
                                [--description DESCRIPTION]
                                [--start-date START_DATE]
                                [--end-date END_DATE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--title <title>

--labels <labels>

--description <description>

--start-date <start_date>

--end-date <end_date>

gitlab group-epic delete

```
usage: gitlab group-epic delete [-h] [--sudo SUDO] --group-id GROUP_ID --iid
                                 IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--iid <iid>

gitlab group-epic get

```
usage: gitlab group-epic get [-h] [--sudo SUDO] --group-id GROUP_ID --iid IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--iid <iid>

gitlab group-epic list

```
usage: gitlab group-epic list [-h] [--sudo SUDO] --group-id GROUP_ID
                               [--author-id AUTHOR_ID] [--labels LABELS]
                               [--order-by ORDER_BY] [--sort SORT]
                               [--search SEARCH] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--author-id <author_id>

--labels <labels>

--order-by <order_by>

--sort <sort>

--search <search>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-epic update

```
usage: gitlab group-epic update [-h] [--sudo SUDO] --group-id GROUP_ID --iid
                                IID [--title TITLE] [--labels LABELS]
                                [--description DESCRIPTION]
                                [--start-date START_DATE]
                                [--end-date END_DATE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--iid <iid>

--title <title>

--labels <labels>

--description <description>

--start-date <start_date>

--end-date <end_date>

gitlab group-epic-award-emoji

```
usage: gitlab group-epic-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab group-epic-award-emoji create

```
usage: gitlab group-epic-award-emoji create [-h] [--sudo SUDO] --group-id
                                              GROUP_ID --epic-iid EPIC_IID
                                              --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--name <name>

gitlab group-epic-award-emoji delete

```
usage: gitlab group-epic-award-emoji delete [-h] [--sudo SUDO] --group-id
                                             GROUP_ID --epic-iid EPIC_IID --id
                                             ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--id <id>

gitlab group-epic-award-emoji get

```
usage: gitlab group-epic-award-emoji get [-h] [--sudo SUDO] --group-id
                                         GROUP_ID --epic-iid EPIC_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--id <id>

gitlab group-epic-award-emoji list

```
usage: gitlab group-epic-award-emoji list [-h] [--sudo SUDO] --group-id
                                            GROUP_ID --epic-iid EPIC_IID
                                            [--page PAGE] [--per-page PER_PAGE]
                                            [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-epic-discussion-note

```
usage: gitlab group-epic-discussion-note [-h] {get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-epic-discussion-note create

```
usage: gitlab group-epic-discussion-note create [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-id EPIC_ID
                                                --discussion-id DISCUSSION_ID
                                                --body BODY
                                                [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-id <epic_id>

--discussion-id <discussion_id>

--body <body>

--created-at <created_at>

gitlab group-epic-discussion-note delete

```
usage: gitlab group-epic-discussion-note delete [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-id EPIC_ID
                                                --discussion-id DISCUSSION_ID
                                                --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-id <epic_id>

```
--discussion-id <discussion_id>  
--id <id>
```

gitlab group-epic-discussion-note get

```
usage: gitlab group-epic-discussion-note get [-h] [--sudo SUDO] --group-id  
      GROUP_ID --epic-id EPIC_ID  
      --discussion-id DISCUSSION_ID  
      --id ID
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--group-id <group_id>  
--epic-id <epic_id>  
--discussion-id <discussion_id>  
--id <id>
```

gitlab group-epic-discussion-note update

```
usage: gitlab group-epic-discussion-note update [-h] [--sudo SUDO] --group-id  
      GROUP_ID --epic-id EPIC_ID  
      --discussion-id DISCUSSION_ID  
      --id ID --body BODY
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--group-id <group_id>  
--epic-id <epic_id>  
--discussion-id <discussion_id>  
--id <id>  
--body <body>
```

gitlab group-epic-issue

```
usage: gitlab group-epic-issue [-h] {list,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-epic-issue create

```
usage: gitlab group-epic-issue create [-h] [--sudo SUDO] --group-id GROUP_ID  
--epic-iid EPIC_IID --issue-id ISSUE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--issue-id <issue_id>

gitlab group-epic-issue delete

```
usage: gitlab group-epic-issue delete [-h] [--sudo SUDO] --group-id GROUP_ID  
--epic-iid EPIC_IID --epic-issue-id  
EPIC_ISSUE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--epic-issue-id <epic_issue_id>

gitlab group-epic-issue list

```
usage: gitlab group-epic-issue list [-h] [--sudo SUDO] --group-id GROUP_ID  
--epic-iid EPIC_IID [--page PAGE]  
[--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

```
--epic-iid <epic_iid>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-epic-issue update

```
usage: gitlab group-epic-issue update [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --epic-iid EPIC_IID --epic-issue-id
                                      EPIC_ISSUE_ID
                                      [--move-before-id MOVE_BEFORE_ID]
                                      [--move-after-id MOVE_AFTER_ID]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--epic-iid <epic_iid>
--epic-issue-id <epic_issue_id>
--move-before-id <move_before_id>
--move-after-id <move_after_id>
```

gitlab group-epic-note

```
usage: gitlab group-epic-note [-h] {list,get,create,update,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-epic-note create

```
usage: gitlab group-epic-note create [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --epic-id EPIC_ID --body BODY
                                      [--created-at CREATED_AT]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
```

```
--group-id <group_id>
--epic-id <epic_id>
--body <body>
--created-at <created_at>
```

gitlab group-epic-note delete

```
usage: gitlab group-epic-note delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --epic-id EPIC_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--epic-id <epic_id>
--id <id>
```

gitlab group-epic-note get

```
usage: gitlab group-epic-note get [-h] [--sudo SUDO] --group-id GROUP_ID
                                   --epic-id EPIC_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--epic-id <epic_id>
--id <id>
```

gitlab group-epic-note list

```
usage: gitlab group-epic-note list [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --epic-id EPIC_ID [--page PAGE]
                                      [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

--epic-id <epic_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-epic-note update

```
usage: gitlab group-epic-note update [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --epic-id EPIC_ID --id ID --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-id <epic_id>

--id <id>

--body <body>

gitlab group-epic-note-award-emoji

```
usage: gitlab group-epic-note-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab group-epic-note-award-emoji create

```
usage: gitlab group-epic-note-award-emoji create [-h] [--sudo SUDO] --group-id
                                                 GROUP_ID --epic-iid EPIC_IID
                                                 --note-id NOTE_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--note-id <note_id>

--name <name>

gitlab group-epic-note-award-emoji delete

```
usage: gitlab group-epic-note-award-emoji delete [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --note-id NOTE_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--note-id <note_id>

--id <id>

gitlab group-epic-note-award-emoji get

```
usage: gitlab group-epic-note-award-emoji get [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --note-id NOTE_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--note-id <note_id>

--id <id>

gitlab group-epic-note-award-emoji list

```
usage: gitlab group-epic-note-award-emoji list [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --note-id NOTE_ID [--page PAGE]
                                                [--per-page PER_PAGE]
                                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

```
--note-id <note_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-epic-resource-label-event

```
usage: gitlab group-epic-resource-label-event [-h] {list,get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-epic-resource-label-event get

```
usage: gitlab group-epic-resource-label-event get [-h] [--sudo SUDO]
                                                --group-id GROUP_ID
                                                --epic-id EPIC_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--epic-id <epic_id>
--id <id>
```

gitlab group-epic-resource-label-event list

```
usage: gitlab group-epic-resource-label-event list [-h] [--sudo SUDO]
                                                 --group-id GROUP_ID
                                                 --epic-id EPIC_ID
                                                 [--page PAGE]
                                                 [--per-page PER_PAGE]
                                                 [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

```
--epic-id <epic_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-export

```
usage: gitlab group-export [-h] {get,create,download} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-export create

```
usage: gitlab group-export create [-h] [--sudo SUDO] --group-id GROUP_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

gitlab group-export download

```
usage: gitlab group-export download [-h] --group-id GROUP_ID [--sudo SUDO]
```

```
-h, --help
    show this help message and exit
--group-id <group_id>
--sudo <sudo>
```

gitlab group-export get

```
usage: gitlab group-export get [-h] [--sudo SUDO] --group-id GROUP_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

gitlab group-hook

```
usage: gitlab group-hook [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-hook create

```
usage: gitlab group-hook create [-h] [--sudo SUDO] --group-id GROUP_ID --url
                                URL [--push-events PUSH_EVENTS]
                                [--issues-events ISSUES_EVENTS]
                                [--confidential-issues-events CONFIDENTIAL_ISSUES_EVENTS]
                                [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                [--tag-push-events TAG_PUSH_EVENTS]
                                [--note-events NOTE_EVENTS]
                                [--confidential-note-events CONFIDENTIAL_NOTE_EVENTS]
                                [--job-events JOB_EVENTS]
                                [--pipeline-events PIPELINE_EVENTS]
                                [--wiki-page-events WIKI_PAGE_EVENTS]
                                [--deployment-events DEPLOYMENT_EVENTS]
                                [--releases-events RELEASES_EVENTS]
                                [--subgroup-events SUBGROUP_EVENTS]
                                [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                [--token TOKEN]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--url <url>

--push-events <push_events>

--issues-events <issues_events>

--confidential-issues-events <confidential_issues_events>

--merge-requests-events <merge_requests_events>

--tag-push-events <tag_push_events>

--note-events <note_events>

--confidential-note-events <confidential_note_events>

--job-events <job_events>

--pipeline-events <pipeline_events>

--wiki-page-events <wiki_page_events>

```
--deployment-events <deployment_events>
--releases-events <releases_events>
--subgroup-events <subgroup_events>
--enable-ssl-verification <enable_ssl_verification>
--token <token>
```

gitlab group-hook delete

```
usage: gitlab group-hook delete [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-hook get

```
usage: gitlab group-hook get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-hook list

```
usage: gitlab group-hook list [-h] [--sudo SUDO] --group-id GROUP_ID
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]
                               [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--page <page>
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-hook update

```
usage: gitlab group-hook update [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
                                --url URL [--push-events PUSH_EVENTS]
                                [--issues-events ISSUES_EVENTS]
                                [--confidential-issues-events CONFIDENTIAL_ISSUES_EVENTS]
                                [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                [--tag-push-events TAG_PUSH_EVENTS]
                                [--note-events NOTE_EVENTS]
                                [--confidential-note-events CONFIDENTIAL_NOTE_EVENTS]
                                [--job-events JOB_EVENTS]
                                [--pipeline-events PIPELINE_EVENTS]
                                [--wiki-page-events WIKI_PAGE_EVENTS]
                                [--deployment-events DEPLOYMENT_EVENTS]
                                [--releases-events RELEASES_EVENTS]
                                [--subgroup-events SUBGROUP_EVENTS]
                                [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                [--token TOKEN]
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--id <id>****--url <url>****--push-events <push_events>****--issues-events <issues_events>****--confidential-issues-events <confidential_issues_events>****--merge-requests-events <merge_requests_events>****--tag-push-events <tag_push_events>****--note-events <note_events>****--confidential-note-events <confidential_note_events>****--job-events <job_events>****--pipeline-events <pipeline_events>****--wiki-page-events <wiki_page_events>**

```
--deployment-events <deployment_events>
--releases-events <releases_events>
--subgroup-events <subgroup_events>
--enable-ssl-verification <enable_ssl_verification>
--token <token>
```

gitlab group-import

```
usage: gitlab group-import [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab group-import get

```
usage: gitlab group-import get [-h] [--sudo SUDO] --group-id GROUP_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-invitation

```
usage: gitlab group-invitation [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-invitation create

```
usage: gitlab group-invitation create [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --access-level ACCESS_LEVEL
                                      [--expires-at EXPIRES_AT]
                                      [--invite-source INVITE_SOURCE]
                                      [--tasks-to-be-done TASKS_TO_BE_DONE]
                                      [--tasks-project-id TASKS_PROJECT_ID]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

```
--access-level <access_level>
--expires-at <expires_at>
--invite-source <invite_source>
--tasks-to-be-done <tasks_to_be_done>
--tasks-project-id <tasks_project_id>
```

gitlab group-invitation delete

```
usage: gitlab group-invitation delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --email EMAIL
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--email <email>

gitlab group-invitation get

```
usage: gitlab group-invitation get [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --email EMAIL
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--email <email>

gitlab group-invitation list

```
usage: gitlab group-invitation list [-h] [--sudo SUDO] --group-id GROUP_ID
                                      [--query QUERY] [--page PAGE]
                                      [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--query <query>

```
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-invitation update

```
usage: gitlab group-invitation update [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --email EMAIL
                                      [--access-level ACCESS_LEVEL]
                                      [--expires-at EXPIRES_AT]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--email <email>
--access-level <access_level>
--expires-at <expires_at>
```

gitlab group-issue

```
usage: gitlab group-issue [-h] {list} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-issue list

```
usage: gitlab group-issue list [-h] [--sudo SUDO] --group-id GROUP_ID
                               [--state STATE] [--labels LABELS]
                               [--milestone MILESTONE] [--order-by ORDER_BY]
                               [--sort SORT] [--iids IIDS]
                               [--author-id AUTHOR_ID]
                               [--assignee-id ASSIGNEE_ID]
                               [--my-reaction-emoji MY_REACTION_EMOJI]
                               [--search SEARCH]
                               [--created-after CREATED_AFTER]
                               [--created-before CREATED_BEFORE]
                               [--updated-after UPDATED_AFTER]
                               [--updated-before UPDATED_BEFORE] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--state <state>
--labels <labels>
--milestone <milestone>
--order-by <order_by>
--sort <sort>
--iids <iids>
--author-id <author_id>
--assignee-id <assignee_id>
--my-reaction-emoji <my_reaction_emoji>
--search <search>
--created-after <created_after>
--created-before <created_before>
--updated-after <updated_after>
--updated-before <updated_before>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-issues-statistics

```
usage: gitlab group-issues-statistics [-h] {get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-issues-statistics get

```
usage: gitlab group-issues-statistics get [-h] [--sudo SUDO] --group-id GROUP_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-iteration

```
usage: gitlab group-iteration [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-iteration list

```
usage: gitlab group-iteration list [-h] [--sudo SUDO] --group-id GROUP_ID  
                                  [--state STATE] [--search SEARCH]  
                                  [--include-ancestors INCLUDE_ANCESTORS]  
                                  [--page PAGE] [--per-page PER_PAGE]  
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--state <state>

--search <search>

--include-ancestors <include_ancestors>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-label

```
usage: gitlab group-label [-h]
    list
    get
    create
    update
    delete
    subscribe
    unsubscribe
    ...
```

-h, --help

show this help message and exit

gitlab group-label create

```
usage: gitlab group-label create [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                  NAME --color COLOR
                                  [--description DESCRIPTION]
                                  [--priority PRIORITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

--color <color>

--description <description>

--priority <priority>

gitlab group-label delete

```
usage: gitlab group-label delete [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                  NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

gitlab group-label get

```
usage: gitlab group-label get [-h] [--sudo SUDO] --group-id GROUP_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

gitlab group-label list

```
usage: gitlab group-label list [-h] [--sudo SUDO] --group-id GROUP_ID  
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]  
                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-label subscribe

```
usage: gitlab group-label subscribe [-h] --group-id GROUP_ID [--sudo SUDO]  
                                    --name NAME
```

-h, --help

show this help message and exit

--group-id <group_id>

--sudo <sudo>

--name <name>

gitlab group-label unsubscribe

```
usage: gitlab group-label unsubscribe [-h] --group-id GROUP_ID [--sudo SUDO]
                                      --name NAME
```

-h, --help

show this help message and exit

--group-id <group_id>

--sudo <sudo>

--name <name>

gitlab group-label update

```
usage: gitlab group-label update [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                 NAME [--new-name NEW_NAME] [--color COLOR]
                                 [--description DESCRIPTION]
                                 [--priority PRIORITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

--new-name <new_name>

--color <color>

--description <description>

--priority <priority>

gitlab group-ldap-group-link

```
usage: gitlab group-ldap-group-link [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab group-ldap-group-link create

```
usage: gitlab group-ldap-group-link create [-h] [--sudo SUDO] --group-id
                                         GROUP_ID --provider PROVIDER
                                         --group-access GROUP_ACCESS
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--provider <provider>

--group-access <group_access>

gitlab group-ldap-group-link delete

```
usage: gitlab group-ldap-group-link delete [-h] [--sudo SUDO] --group-id
                                         GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-ldap-group-link list

```
usage: gitlab group-ldap-group-link list [-h] [--sudo SUDO] --group-id
                                         GROUP_ID [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-member

```
usage: gitlab group-member [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-member create

```
usage: gitlab group-member create [-h] [--sudo SUDO] --group-id GROUP_ID
                                  --access-level ACCESS_LEVEL --user-id
                                  USER_ID [--expires-at EXPIRES_AT]
                                  [--tasks-to-be-done TASKS_TO_BE_DONE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--access-level <access_level>

--user-id <user_id>

--expires-at <expires_at>

--tasks-to-be-done <tasks_to_be_done>

gitlab group-member delete

```
usage: gitlab group-member delete [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                  ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-member get

```
usage: gitlab group-member get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--group-id <group_id>
--id <id>
```

gitlab group-member list

```
usage: gitlab group-member list [-h] [--sudo SUDO] --group-id GROUP_ID
                                 [--page PAGE] [--per-page PER_PAGE]
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-member update

```
usage: gitlab group-member update [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID --access-level ACCESS_LEVEL
                                   [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

--access-level <access_level>

--expires-at <expires_at>

gitlab group-member-all

```
usage: gitlab group-member-all [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab group-member-all get

```
usage: gitlab group-member-all get [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-member-all list

```
usage: gitlab group-member-all list [-h] [--sudo SUDO] --group-id GROUP_ID
                                    [--page PAGE] [--per-page PER_PAGE]
                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-merge-request

```
usage: gitlab group-merge-request [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-merge-request list

```
usage: gitlab group-merge-request list [-h] [--sudo SUDO] --group-id GROUP_ID
                                         [--state STATE] [--order-by ORDER_BY]
                                         [--sort SORT] [--milestone MILESTONE]
                                         [--view VIEW] [--labels LABELS]
                                         [--created-after CREATED_AFTER]
                                         [--created-before CREATED_BEFORE]
                                         [--updated-after UPDATED_AFTER]
                                         [--updated-before UPDATED_BEFORE]
                                         [--scope SCOPE] [--author-id AUTHOR_ID]
                                         [--assignee-id ASSIGNEE_ID]
                                         [--approver-ids APPROVER_IDS]
                                         [--approved-by-ids APPROVED_BY_IDS]
                                         [--my-reaction-emoji MY_REACTION_EMOJI]
                                         [--source-branch SOURCE_BRANCH]
                                         [--target-branch TARGET_BRANCH]
                                         [--search SEARCH] [--wip WIP]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--state <state>

--order-by <order_by>

--sort <sort>

--milestone <milestone>

--view <view>

--labels <labels>

--created-after <created_after>

--created-before <created_before>

--updated-after <updated_after>

--updated-before <updated_before>

```
--scope <scope>
--author-id <author_id>
--assignee-id <assignee_id>
--approver-ids <approver_ids>
--approved-by-ids <approved_by_ids>
--my-reaction-emoji <my_reaction_emoji>
--source-branch <source_branch>
--target-branch <target_branch>
--search <search>
--wip <wip>
--page <page>
--per-page <per_page>
--get-all
```

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-milestone

```
usage: gitlab group-milestone [-h]
  list
  get
  create
  update
  delete
  issues
  merge-requests
  ...
  
```

-h, --help

show this help message and exit

gitlab group-milestone create

```
usage: gitlab group-milestone create [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --title TITLE [--description DESCRIPTION]
                                      [--due-date DUE_DATE]
                                      [--start-date START_DATE]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--title <title>
--description <description>
--due-date <due_date>
--start-date <start_date>
```

gitlab group-milestone delete

```
usage: gitlab group-milestone delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-milestone get

```
usage: gitlab group-milestone get [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-milestone issues

```
usage: gitlab group-milestone issues [-h] --group-id GROUP_ID [--sudo SUDO]
                                      --id ID
```

```
-h, --help
    show this help message and exit
--group-id <group_id>
--sudo <sudo>
--id <id>
```

gitlab group-milestone list

```
usage: gitlab group-milestone list [-h] [--sudo SUDO] --group-id GROUP_ID
                                  [--iids IIDS] [--state STATE]
                                  [--search SEARCH] [--page PAGE]
                                  [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--iids <iids>

--state <state>

--search <search>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-milestone merge-requests

```
usage: gitlab group-milestone merge-requests [-h] --group-id GROUP_ID
                                              [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--group-id <group_id>

--sudo <sudo>

--id <id>

gitlab group-milestone update

```
usage: gitlab group-milestone update [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --id ID [--title TITLE]
                                      [--description DESCRIPTION]
                                      [--due-date DUE_DATE]
                                      [--start-date START_DATE]
                                      [--state-event STATE_EVENT]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
--title <title>
--description <description>
--due-date <due_date>
--start-date <start_date>
--state-event <state_event>
```

gitlab group-notification-settings

```
usage: gitlab group-notification-settings [-h] {get,update} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-notification-settings get

```
usage: gitlab group-notification-settings get [-h] [--sudo SUDO] --group-id
                                              GROUP_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

gitlab group-notification-settings update

```
usage: gitlab group-notification-settings update [-h] [--sudo SUDO] --group-id
                                                 GROUP_ID [--level LEVEL]
                                                 [--notification-email NOTIFICATION_
                                                 ↵EMAIL]
                                                 [--new-note NEW_NOTE]
                                                 [--new-issue NEW_ISSUE]
                                                 [--reopen-issue REOPEN_ISSUE]
                                                 [--close-issue CLOSE_ISSUE]
                                                 [--reassign-issue REASSIGN_ISSUE]
                                                 [--new-merge-request NEW_MERGE_REQUEST]
                                                 [--reopen-merge-request REOPEN_MERGE_
                                                 ↵REQUEST]
```

(continues on next page)

(continued from previous page)

↳ REQUEST]	[--close-merge-request CLOSE_MERGE_
↳ MERGE_REQUEST]	[--reassign-merge-request REASSIGN_
↳ REQUEST]	[--merge-merge-request MERGE_MERGE_

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--level <level>****--notification-email <notification_email>****--new-note <new_note>****--new-issue <new_issue>****--reopen-issue <reopen_issue>****--close-issue <close_issue>****--reassign-issue <reassign_issue>****--new-merge-request <new_merge_request>****--reopen-merge-request <reopen_merge_request>****--close-merge-request <close_merge_request>****--reassign-merge-request <reassign_merge_request>****--merge-merge-request <merge_merge_request>****gitlab group-package**

usage: gitlab group-package [-h] {list} ...

-h, --help

show this help message and exit

gitlab group-package list

```
usage: gitlab group-package list [-h] [--sudo SUDO] --group-id GROUP_ID
                                 [--exclude-subgroups EXCLUDE_SUBGROUPS]
                                 [--order-by ORDER_BY] [--sort SORT]
                                 [--package-type PACKAGE_TYPE]
                                 [--package-name PACKAGE_NAME] [--page PAGE]
                                 [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--exclude-subgroups <exclude_subgroups>
--order-by <order_by>
--sort <sort>
--package-type <package_type>
--package-name <package_name>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-project

```
usage: gitlab group-project [-h] {list} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-project list

```
usage: gitlab group-project list [-h] [--sudo SUDO] --group-id GROUP_ID
                                  [--archived ARCHIVED]
                                  [--visibility VISIBILITY]
                                  [--order-by ORDER_BY] [--sort SORT]
                                  [--search SEARCH] [--simple SIMPLE]
                                  [--owned OWNED] [--starred STARRED]
                                  [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                  [--include-subgroups INCLUDE_SUBGROUPS]
                                  [--with-issues-enabled WITH_ISSUES_ENABLED]
                                  [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
→ENABLED]
                                  [--with-shared WITH_SHARED]
                                  [--min-access-level MIN_ACCESS_LEVEL]
                                  [--with-security-reports WITH_SECURITY_REPORTS]
                                  [--page PAGE] [--per-page PER_PAGE]
                                  [--get-all] [--all]
```

```
-h, --help
    show this help message and exit

--sudo <sudo>

--group-id <group_id>

--archived <archived>

--visibility <visibility>

--order-by <order_by>

--sort <sort>

--search <search>

--simple <simple>

--owned <owned>

--starred <starred>

--with-custom-attributes <with_custom_attributes>

--include-subgroups <include_subgroups>

--with-issues-enabled <with_issues_enabled>

--with-merge-requests-enabled <with_merge_requests_enabled>

--with-shared <with_shared>

--min-access-level <min_access_level>

--with-security-reports <with_security_reports>

--page <page>

--per-page <per_page>

--get-all
    Return all items from the server, without pagination.

--all
    Deprecated. Use --get-all instead.
```

gitlab group-push-rules

```
usage: gitlab group-push-rules [-h] {get,create,update,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-push-rules create

```
usage: gitlab group-push-rules create [-h] [--sudo SUDO] --group-id GROUP_ID
                                      [--deny-delete-tag DENY_DELETE_TAG]
                                      [--member-check MEMBER_CHECK]
                                      [--prevent-secrets PREVENT_SECRETS]
                                      [--commit-message-regex COMMIT_MESSAGE_REGEX]
                                      [--commit-message-negative-regex COMMIT_MESSAGE_
                                       NEGATIVE_REGEX]
                                      [--branch-name-regex BRANCH_NAME_REGEX]
                                      [--author-email-regex AUTHOR_EMAIL_REGEX]
                                      [--file-name-regex FILE_NAME_REGEX]
                                      [--max-file-size MAX_FILE_SIZE]
                                      [--commit-committer-check COMMIT_COMMITTER_CHECK]
                                      [--reject-unsigned-commits REJECT_UNSIGNED_COMMITS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--deny-delete-tag <deny_delete_tag>

--member-check <member_check>

--prevent-secrets <prevent_secrets>

--commit-message-regex <commit_message_regex>

--commit-message-negative-regex <commit_message_negative_regex>

--branch-name-regex <branch_name_regex>

--author-email-regex <author_email_regex>

--file-name-regex <file_name_regex>

--max-file-size <max_file_size>

--commit-committer-check <commit_committer_check>

--reject-unsigned-commits <reject_unsigned_commits>

gitlab group-push-rules delete

```
usage: gitlab group-push-rules delete [-h] [--sudo SUDO] --group-id GROUP_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-push-rules get

```
usage: gitlab group-push-rules get [-h] [--sudo SUDO] --group-id GROUP_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-push-rules update

```
usage: gitlab group-push-rules update [-h] [--sudo SUDO] --group-id GROUP_ID
                                      [--deny-delete-tag DENY_DELETE_TAG]
                                      [--member-check MEMBER_CHECK]
                                      [--prevent-secrets PREVENT_SECRETS]
                                      [--commit-message-regex COMMIT_MESSAGE_REGEX]
                                      [--commit-message-negative-regex COMMIT_MESSAGE_
                                       NEGATIVE_REGEX]
                                      [--branch-name-regex BRANCH_NAME_REGEX]
                                      [--author-email-regex AUTHOR_EMAIL_REGEX]
                                      [--file-name-regex FILE_NAME_REGEX]
                                      [--max-file-size MAX_FILE_SIZE]
                                      [--commit-committer-check COMMIT_COMMITTER_CHECK]
                                      [--reject-unsigned-commits REJECT_UNSIGNED_COMMITS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--deny-delete-tag <deny_delete_tag>

--member-check <member_check>

--prevent-secrets <prevent_secrets>

--commit-message-regex <commit_message_regex>

--commit-message-negative-regex <commit_message_negative_regex>

--branch-name-regex <branch_name_regex>

--author-email-regex <author_email_regex>

--file-name-regex <file_name_regex>

--max-file-size <max_file_size>

--commit-committer-check <commit_committer_check>

--reject-unsigned-commits <reject_unsigned_commits>

gitlab group-runner

```
usage: gitlab group-runner [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-runner list

```
usage: gitlab group-runner list [-h] [--sudo SUDO] --group-id GROUP_ID
                                [--scope SCOPE] [--tag-list TAG_LIST]
                                [--page PAGE] [--per-page PER_PAGE]
                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--scope <scope>

--tag-list <tag_list>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-saml-group-link

```
usage: gitlab group-saml-group-link [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab group-saml-group-link create

```
usage: gitlab group-saml-group-link create [-h] [--sudo SUDO] --group-id
                                             GROUP_ID --saml-group-name
                                             SAML_GROUP_NAME --access-level
                                             ACCESS_LEVEL
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--saml-group-name <saml_group_name>
--access-level <access_level>
```

gitlab group-saml-group-link delete

```
usage: gitlab group-saml-group-link delete [-h] [--sudo SUDO] --group-id
                                             GROUP_ID --name NAME
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--name <name>
```

gitlab group-saml-group-link get

```
usage: gitlab group-saml-group-link get [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --name NAME
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--name <name>
```

gitlab group-saml-group-link list

```
usage: gitlab group-saml-group-link list [-h] [--sudo SUDO] --group-id
                                           GROUP_ID [--page PAGE]
                                           [--per-page PER_PAGE] [--get-all]
                                           [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--page <page>
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-subgroup

```
usage: gitlab group-subgroup [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-subgroup list

```
usage: gitlab group-subgroup list [-h] [--sudo SUDO] --group-id GROUP_ID
                                  [--skip-groups SKIP_GROUPS]
                                  [--all-available ALL_AVAILABLE]
                                  [--search SEARCH] [--order-by ORDER_BY]
                                  [--sort SORT] [--statistics STATISTICS]
                                  [--owned OWNED]
                                  [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                  [--min-access-level MIN_ACCESS_LEVEL]
                                  [--page PAGE] [--per-page PER_PAGE]
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--skip-groups <skip_groups>

--all-available <all_available>

--search <search>

--order-by <order_by>

--sort <sort>

--statistics <statistics>

--owned <owned>

--with-custom-attributes <with_custom_attributes>

--min-access-level <min_access_level>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-variable

```
usage: gitlab group-variable [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-variable create

```
usage: gitlab group-variable create [-h] [--sudo SUDO] --group-id GROUP_ID
                                   --key KEY --value VALUE
                                   [--protected PROTECTED]
                                   [--variable-type VARIABLE_TYPE]
                                   [--masked MASKED]
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--key <key>****--value <value>****--protected <protected>****--variable-type <variable_type>****--masked <masked>****gitlab group-variable delete**

```
usage: gitlab group-variable delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                   --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--key <key>**

gitlab group-variable get

```
usage: gitlab group-variable get [-h] [--sudo SUDO] --group-id GROUP_ID --key  
                                 KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

gitlab group-variable list

```
usage: gitlab group-variable list [-h] [--sudo SUDO] --group-id GROUP_ID  
                                 [--page PAGE] [--per-page PER_PAGE]  
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-variable update

```
usage: gitlab group-variable update [-h] [--sudo SUDO] --group-id GROUP_ID  
                                 --key KEY --value VALUE  
                                 [--protected PROTECTED]  
                                 [--variable-type VARIABLE_TYPE]  
                                 [--masked MASKED]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

```
--value <value>
--protected <protected>
--variable-type <variable_type>
--masked <masked>
```

gitlab group-wiki

```
usage: gitlab group-wiki [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-wiki create

```
usage: gitlab group-wiki create [-h] [--sudo SUDO] --group-id GROUP_ID --title
                                TITLE --content CONTENT [--format FORMAT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--title <title>

--content <content>

--format <format>

gitlab group-wiki delete

```
usage: gitlab group-wiki delete [-h] [--sudo SUDO] --group-id GROUP_ID --slug
                                 SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--slug <slug>

gitlab group-wiki get

```
usage: gitlab group-wiki get [-h] [--sudo SUDO] --group-id GROUP_ID --slug
                             SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--slug <slug>

gitlab group-wiki list

```
usage: gitlab group-wiki list [-h] [--sudo SUDO] --group-id GROUP_ID
                               [--with-content WITH_CONTENT] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--with-content <with_content>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab group-wiki update

```
usage: gitlab group-wiki update [-h] [--sudo SUDO] --group-id GROUP_ID --slug
                                 SLUG [--title TITLE] [--content CONTENT]
                                 [--format FORMAT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--slug <slug>

```
--title <title>
--content <content>
--format <format>
```

gitlab hook

```
usage: gitlab hook [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab hook create

```
usage: gitlab hook create [-h] [--sudo SUDO] --url URL
```

-h, --help

show this help message and exit

--sudo <sudo>

--url <url>

gitlab hook delete

```
usage: gitlab hook delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab hook get

```
usage: gitlab hook get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab hook list

```
usage: gitlab hook list [-h] [--sudo SUDO] [--page PAGE] [--per-page PER_PAGE]
                        [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab issue

```
usage: gitlab issue [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab issue get

```
usage: gitlab issue get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab issue list

```
usage: gitlab issue list [-h] [--sudo SUDO] [--state STATE] [--labels LABELS]
                         [--milestone MILESTONE] [--scope SCOPE]
                         [--author-id AUTHOR_ID] [--assignee-id ASSIGNEE_ID]
                         [--my-reaction-emoji MY_REACTION_EMOJI] [--iids IIDS]
                         [--order-by ORDER_BY] [--sort SORT] [--search SEARCH]
                         [--created-after CREATED_AFTER]
                         [--created-before CREATED_BEFORE]
                         [--updated-after UPDATED_AFTER]
                         [--updated-before UPDATED_BEFORE] [--page PAGE]
                         [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--state <state>
--labels <labels>
--milestone <milestone>
--scope <scope>
--author-id <author_id>
--assignee-id <assignee_id>
--my-reaction-emoji <my_reaction_emoji>
--iids <iids>
--order-by <order_by>
--sort <sort>
--search <search>
--created-after <created_after>
--created-before <created_before>
--updated-after <updated_after>
--updated-before <updated_before>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab issues-statistics

```
usage: gitlab issues-statistics [-h] {get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab issues-statistics get

```
usage: gitlab issues-statistics get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab key

```
usage: gitlab key [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab key get

```
usage: gitlab key get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab ldap-group

```
usage: gitlab ldap-group [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab ldap-group list

```
usage: gitlab ldap-group list [-h] [--sudo SUDO] [--search SEARCH]
                               [--provider PROVIDER] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--search <search>

--provider <provider>

--page <page>

```
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab license

```
usage: gitlab license [-h] {list,get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab license get

```
usage: gitlab license get [-h] [--sudo SUDO] --key KEY [--project PROJECT]
                           [--fullname FULLNAME]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--key <key>
--project <project>
--fullname <fullname>
```

gitlab license list

```
usage: gitlab license list [-h] [--sudo SUDO] [--popular POPULAR]
                           [--page PAGE] [--per-page PER_PAGE] [--get-all]
                           [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--popular <popular>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab merge-request

```
usage: gitlab merge-request [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab merge-request list

```
usage: gitlab merge-request list [-h] [--sudo SUDO] [--state STATE]
                                 [--order-by ORDER_BY] [--sort SORT]
                                 [--milestone MILESTONE] [--view VIEW]
                                 [--labels LABELS]
                                 [--with-labels-details WITH_LABELS_DETAILS]
                                 [--with-merge-status-recheck WITH_MERGE_STATUS_RECHECK]
                                 [--created-after CREATED_AFTER]
                                 [--created-before CREATED_BEFORE]
                                 [--updated-after UPDATED_AFTER]
                                 [--updated-before UPDATED_BEFORE]
                                 [--scope SCOPE] [--author-id AUTHOR_ID]
                                 [--author-username AUTHOR_USERNAME]
                                 [--assignee-id ASSIGNEE_ID]
                                 [--approver-ids APPROVER_IDS]
                                 [--approved-by-ids APPROVED_BY_IDS]
                                 [--reviewer-id REVIEWER_ID]
                                 [--reviewer-username REVIEWER_USERNAME]
                                 [--my-reaction-emoji MY_REACTION_EMOJI]
                                 [--source-branch SOURCE_BRANCH]
                                 [--target-branch TARGET_BRANCH]
                                 [--search SEARCH] [--in IN] [--wip WIP]
                                 [--not NOT] [--environment ENVIRONMENT]
                                 [--deployed-before DEPLOYED_BEFORE]
                                 [--deployed-after DEPLOYED_AFTER]
                                 [--page PAGE] [--per-page PER_PAGE]
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--state <state>

--order-by <order_by>

--sort <sort>

--milestone <milestone>

--view <view>

--labels <labels>

--with-labels-details <with_labels_details>

```
--with-merge-status-recheck <with_merge_status_recheck>
--created-after <created_after>
--created-before <created_before>
--updated-after <updated_after>
--updated-before <updated_before>
--scope <scope>
--author-id <author_id>
--author-username <author_username>
--assignee-id <assignee_id>
--approver-ids <approver_ids>
--approved-by-ids <approved_by_ids>
--reviewer-id <reviewer_id>
--reviewer-username <reviewer_username>
--my-reaction-emoji <my_reaction_emoji>
--source-branch <source_branch>
--target-branch <target_branch>
--search <search>
--in <in>
--wip <wip>
--not <not>
--environment <environment>
--deployed-before <deployed_before>
--deployed-after <deployed_after>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab namespace

```
usage: gitlab namespace [-h] {list,get,exists} ...
```

-h, --help

show this help message and exit

gitlab namespace exists

```
usage: gitlab namespace exists [-h] --id ID --namespace NAMESPACE --parent-id  
                               PARENT_ID
```

-h, --help

show this help message and exit

--id <id>

--namespace <namespace>

--parent-id <parent_id>

gitlab namespace get

```
usage: gitlab namespace get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab namespace list

```
usage: gitlab namespace list [-h] [--sudo SUDO] [--search SEARCH]  
                           [--page PAGE] [--per-page PER_PAGE] [--get-all]  
                           [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--search <search>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab notification-settings

```
usage: gitlab notification-settings [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab notification-settings get

```
usage: gitlab notification-settings get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab notification-settings update

```
usage: gitlab notification-settings update [-h] [--sudo SUDO] [--level LEVEL]
                                            [--notification-email NOTIFICATION_EMAIL]
                                            [--new-note NEW_NOTE]
                                            [--new-issue NEW_ISSUE]
                                            [--reopen-issue REOPEN_ISSUE]
                                            [--close-issue CLOSE_ISSUE]
                                            [--reassign-issue REASSIGN_ISSUE]
                                            [--new-merge-request NEW_MERGE_REQUEST]
                                            [--reopen-merge-request REOPEN_MERGE_REQUEST]
                                            [--close-merge-request CLOSE_MERGE_REQUEST]
                                            [--reassign-merge-request REASSIGN_MERGE_
                                            REQUEST]
                                            [--merge-merge-request MERGE_MERGE_REQUEST]
```

-h, --help

show this help message and exit

--sudo <sudo>

--level <level>

--notification-email <notification_email>

--new-note <new_note>

--new-issue <new_issue>

--reopen-issue <reopen_issue>

--close-issue <close_issue>

--reassign-issue <reassign_issue>

--new-merge-request <new_merge_request>

```
--reopen-merge-request <reopen_merge_request>
--close-merge-request <close_merge_request>
--reassign-merge-request <reassign_merge_request>
--merge-merge-request <merge_merge_request>
```

gitlab pages-domain

```
usage: gitlab pages-domain [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab pages-domain list

```
usage: gitlab pages-domain list [-h] [--sudo SUDO] [--page PAGE]
                                 [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab personal-access-token

```
usage: gitlab personal-access-token [-h] {list,get,delete} ...
```

-h, --help

show this help message and exit

gitlab personal-access-token delete

```
usage: gitlab personal-access-token delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab personal-access-token get

```
usage: gitlab personal-access-token get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab personal-access-token list

```
usage: gitlab personal-access-token list [-h] [--sudo SUDO]
                                         [--user-id USER_ID] [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project

```
usage: gitlab project [-h]
    list
    get
    create
    update
    delete
    artifacts
    update-submodule
    repository-tree
    repository-blob
    repository-raw-blob
    repository-compare
    repository-contributors
    repository-archive
    repository-merge-base
```

(continues on next page)

(continued from previous page)

```
delete-merged-branches
create-fork-relation
delete-fork-relation
languages
star
unstar
archive
unarchive
share
unshare
trigger-pipeline
housekeeping
upload
restore
snapshot
search
mirror-pull
mirror-pull-details
transfer
transfer-project
artifact
    ...
```

-h, --help

show this help message and exit

gitlab project archive

```
usage: gitlab project archive [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project artifact

```
usage: gitlab project artifact [-h] --id ID --ref-name REF_NAME
                               --artifact-path ARTIFACT_PATH --job JOB
```

-h, --help

show this help message and exit

--id <id>

--ref-name <ref_name>

--artifact-path <artifact_path>

--job <job>

gitlab project artifacts

```
usage: gitlab project artifacts [-h] --id ID --ref-name REF_NAME --job JOB
                               [--job-token JOB_TOKEN]
```

-h, --help

show this help message and exit

--id <id>

--ref-name <ref_name>

--job <job>

--job-token <job_token>

gitlab project create

```
usage: gitlab project create [-h] [--sudo SUDO] [--name NAME] [--path PATH]
                             [--allow-merge-on-skipped-pipeline ALLOW_MERGE_ON_SKIPPED_
                             PIPELINE]
                             [--only-allow-merge-if-all-status-checks-passed ONLY_ALLOW_
                             MERGE_IF_ALL_STATUS_CHECKS_PASSED]
                             [--analytics-access-level ANALYTICS_ACCESS_LEVEL]
                             [--approvals-before-merge APPROVALS_BEFORE_MERGE]
                             [--auto-cancel-pending-pipelines AUTO_CANCEL_PENDING_
                             PIPELINES]
                             [--auto-devops-deploy-strategy AUTO_DEVOPS_DEPLOY_STRATEGY]
                             [--auto-devops-enabled AUTO_DEVOPS_ENABLED]
                             [--autoclose-referenced-issues AUTOCLOSE_REFERENCED_ISSUES]
                             [--avatar AVATAR]
                             [--build-coverage-regex BUILD_COVERAGE_REGEX]
                             [--build-git-strategy BUILD_GIT_STRATEGY]
                             [--build-timeout BUILD_TIMEOUT]
                             [--builds-access-level BUILDS_ACCESS_LEVEL]
                             [--ci-config-path CI_CONFIG_PATH]
                             [--container-expiration-policy-attributes CONTAINER_
                             EXPIRATION_POLICY_ATTRIBUTES]
                             [--container-registry-access-level CONTAINER_REGISTRY_
                             ACCESS_LEVEL]
                             [--container-registry-enabled CONTAINER_REGISTRY_ENABLED]
                             [--default-branch DEFAULT_BRANCH]
                             [--description DESCRIPTION]
                             [--emails-disabled EMAILS_DISABLED]
                             [--external-authorization-classification-label EXTERNAL_
                             AUTHORIZATION_CLASSIFICATION_LABEL]
                             [--forking-access-level FORKING_ACCESS_LEVEL]
                             [--group-with-project-templates-id GROUP_WITH_PROJECT_
                             TEMPLATES_ID]
                             [--import-url IMPORT_URL]
                             [--initialize-with-readme INITIALIZE_WITH_README]
                             [--issues-access-level ISSUES_ACCESS_LEVEL]
                             [--issues-enabled ISSUES_ENABLED]
```

(continues on next page)

(continued from previous page)

```

[--jobs-enabled JOBS_ENABLED]
[--lfs-enabled LFS_ENABLED]
[--merge-method MERGE_METHOD]
[--merge-pipelines-enabled MERGE_PIPELINES_ENABLED]
[--merge-requests-access-level MERGE_REQUESTS_ACCESS_LEVEL]
[--merge-requests-enabled MERGE_REQUESTS_ENABLED]
[--mirror-trigger-builds MIRROR_TRIGGER_BUILDUPS]
[--mirror MIRROR] [--namespace-id NAMESPACE_ID]
[--operations-access-level OPERATIONS_ACCESS_LEVEL]
[--only-allow-merge-if-all-discussions-are-resolved ONLY_
↳ ALLOW_MERGE_IF_ALL_DISCUSSIONS_ARE_RESOLVED]
    [--only-allow-merge-if-pipeline-succeeds ONLY_ALLOW_MERGE_
↳ IF_PIPELINE_SUCCEEDS]
        [--packages-enabled PACKAGES_ENABLED]
        [--pages-access-level PAGES_ACCESS_LEVEL]
        [--requirements-access-level REQUIREMENTS_ACCESS_LEVEL]
        [--printing-merge-request-link-enabled PRINTING_MERGE_
↳ REQUEST_LINK_ENABLED]
            [--public-builds PUBLIC_BUILDUPS]
            [--releases-access-level RELEASES_ACCESS_LEVEL]
            [--environments-access-level ENVIRONMENTS_ACCESS_LEVEL]
            [--feature-flags-access-level FEATURE_FLAGS_ACCESS_LEVEL]
            [--infrastructure-access-level INFRASTRUCTURE_ACCESS_LEVEL]
            [--monitor-access-level MONITOR_ACCESS_LEVEL]
            [--remove-source-branch-after-merge REMOVE_SOURCE_BRANCH_
↳ AFTER_MERGE]
                [--repository-access-level REPOSITORY_ACCESS_LEVEL]
                [--repository-storage REPOSITORY_STORAGE]
                [--request-access-enabled REQUEST_ACCESS_ENABLED]
                [--resolve-outdated-diff-discussions RESOLVE_OUTDATED_DIFF_
↳ DISCUSSIONS]
                    [--security-and-compliance-access-level SECURITY_AND_
↳ COMPLIANCE_ACCESS_LEVEL]
                        [--shared-runners-enabled SHARED_RUNNERS_ENABLED]
                        [--show-default-award-emojis SHOW_DEFAULT_AWARD_EMOJIS]
                        [--snippets-access-level SNIPPETS_ACCESS_LEVEL]
                        [--snippets-enabled SNIPPETS_ENABLED]
                        [--squash-option SQUASH_OPTION]
                        [--tag-list TAG_LIST] [--topics TOPICS]
                        [--template-name TEMPLATE_NAME]
                        [--template-project-id TEMPLATE_PROJECT_ID]
                        [--use-custom-template USE_CUSTOM_TEMPLATE]
                        [--visibility VISIBILITY]
                        [--wiki-access-level WIKI_ACCESS_LEVEL]
                        [--wiki-enabled WIKI_ENABLED]

```

-h, --help

show this help message and exit

--sudo <sudo>**--name <name>**

```
--path <path>
--allow-merge-on-skipped-pipeline <allow_merge_on_skipped_pipeline>
--only-allow-merge-if-all-status-checks-passed <only_allow_merge_if_all_status_checks_passed>
--analytics-access-level <analytics_access_level>
--approvals-before-merge <approvals_before_merge>
--auto-cancel-pending-pipelines <auto_cancel_pending_pipelines>
--auto-devops-deploy-strategy <auto_devops_deploy_strategy>
--auto-devops-enabled <auto_devops_enabled>
--autoclose-referenced-issues <autoclose_referenced_issues>
--avatar <avatar>
--build-coverage-regex <build_coverage_regex>
--build-git-strategy <build_git_strategy>
--build-timeout <build_timeout>
--builds-access-level <builds_access_level>
--ci-config-path <ci_config_path>
--container-expiration-policy-attributes <container_expiration_policy_attributes>
--container-registry-access-level <container_registry_access_level>
--container-registry-enabled <container_registry_enabled>
--default-branch <default_branch>
--description <description>
--emails-disabled <emails_disabled>
--external-authorization-classification-label <external_authorization_classification_label>
--forking-access-level <forking_access_level>
--group-with-project-templates-id <group_with_project_templates_id>
--import-url <import_url>
--initialize-with-readme <initialize_with_readme>
--issues-access-level <issues_access_level>
--issues-enabled <issues_enabled>
--jobs-enabled <jobs_enabled>
--lfs-enabled <lfs_enabled>
--merge-method <merge_method>
```

```
--merge-pipelines-enabled <merge_pipelines_enabled>
--merge-requests-access-level <merge_requests_access_level>
--merge-requests-enabled <merge_requests_enabled>
--mirror-trigger-builds <mirror_trigger_builds>
--mirror <mirror>
--namespace-id <namespace_id>
--operations-access-level <operations_access_level>
--only-allow-merge-if-all-discussions-are-resolved <only_allow_merge_if_all_discussions_are_resolved>
--only-allow-merge-if-pipeline-succeeds <only_allow_merge_if_pipeline_succeeds>
--packages-enabled <packages_enabled>
--pages-access-level <pages_access_level>
--requirements-access-level <requirements_access_level>
--printing-merge-request-link-enabled <printing_merge_request_link_enabled>
--public-builds <public_builds>
--releases-access-level <releases_access_level>
--environments-access-level <environments_access_level>
--feature-flags-access-level <feature_flags_access_level>
--infrastructure-access-level <infrastructure_access_level>
--monitor-access-level <monitor_access_level>
--remove-source-branch-after-merge <remove_source_branch_after_merge>
--repository-access-level <repository_access_level>
--repository-storage <repository_storage>
--request-access-enabled <request_access_enabled>
--resolve-outdated-diff-discussions <resolve_outdated_diff_discussions>
--security-and-compliance-access-level <security_and_compliance_access_level>
--shared-runners-enabled <shared_runners_enabled>
--show-default-award-emojis <show_default_award_emojis>
--snippets-access-level <snippets_access_level>
--snippets-enabled <snippets_enabled>
--squash-option <squash_option>
--tag-list <tag_list>
```

```
--topics <topics>
--template-name <template_name>
--template-project-id <template_project_id>
--use-custom-template <use_custom_template>
--visibility <visibility>
--wiki-access-level <wiki_access_level>
--wiki-enabled <wiki_enabled>
```

gitlab project create-fork-relation

```
usage: gitlab project create-fork-relation [-h] --id ID --forked-from-id
                                         FORKED_FROM_ID
```

-h, --help

show this help message and exit

--id <id>

--forked-from-id <forked_from_id>

gitlab project delete

```
usage: gitlab project delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab project delete-fork-relation

```
usage: gitlab project delete-fork-relation [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project delete-merged-branches

```
usage: gitlab project delete-merged-branches [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project get

```
usage: gitlab project get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab project housekeeping

```
usage: gitlab project housekeeping [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project languages

```
usage: gitlab project languages [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project list

```
usage: gitlab project list [-h] [--sudo SUDO] [--archived ARCHIVED]
                           [--id-after ID_AFTER] [--id-before ID_BEFORE]
                           [--last-activity-after LAST_ACTIVITY_AFTER]
                           [--last-activity-before LAST_ACTIVITY_BEFORE]
                           [--membership MEMBERSHIP]
                           [--min-access-level MIN_ACCESS_LEVEL]
                           [--order-by ORDER_BY] [--owned OWNED]
                           [--repository-checksum-failed REPOSITORY_CHECKSUM_FAILED]
                           [--repository-storage REPOSITORY_STORAGE]
```

(continues on next page)

(continued from previous page)

```
[--search-namespaces SEARCH_NAMESPACES]
[--search SEARCH] [--simple SIMPLE] [--sort SORT]
[--starred STARRED] [--statistics STATISTICS]
[--topic TOPIC] [--visibility VISIBILITY]
[--wiki-checksum-failed WIKI_CHECKSUM_FAILED]
[--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
[--with-issues-enabled WITH_ISSUES_ENABLED]
[--with-merge-requests-enabled WITH_MERGE_REQUESTS_ENABLED]
[--with-programming-language WITH_PROGRAMMING_LANGUAGE]
[--page PAGE] [--per-page PER_PAGE] [--get-all]
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--archived <archived>****--id-after <id_after>****--id-before <id_before>****--last-activity-after <last_activity_after>****--last-activity-before <last_activity_before>****--membership <membership>****--min-access-level <min_access_level>****--order-by <order_by>****--owned <owned>****--repository-checksum-failed <repository_checksum_failed>****--repository-storage <repository_storage>****--search-namespaces <search_namespaces>****--search <search>****--simple <simple>****--sort <sort>****--starred <starred>****--statistics <statistics>****--topic <topic>****--visibility <visibility>****--wiki-checksum-failed <wiki_checksum_failed>****--with-custom-attributes <with_custom_attributes>**

```
--with-issues-enabled <with_issues_enabled>
--with-merge-requests-enabled <with_merge_requests_enabled>
--with-programming-language <with_programming_language>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project mirror-pull

```
usage: gitlab project mirror-pull [-h] --id ID
```

```
-h, --help
    show this help message and exit
--id <id>
```

gitlab project mirror-pull-details

```
usage: gitlab project mirror-pull-details [-h] --id ID
```

```
-h, --help
    show this help message and exit
--id <id>
```

gitlab project repository-archive

```
usage: gitlab project repository-archive [-h] --id ID [--sha SHA]
                                         [--format FORMAT]
```

```
-h, --help
    show this help message and exit
--id <id>
--sha <sha>
--format <format>
```

gitlab project repository-blob

```
usage: gitlab project repository-blob [-h] --id ID --sha SHA
```

-h, --help

show this help message and exit

--id <id>

--sha <sha>

gitlab project repository-compare

```
usage: gitlab project repository-compare [-h] --id ID --from- FROM_ --to TO
```

-h, --help

show this help message and exit

--id <id>

--from- <from_>

--to <to>

gitlab project repository-contributors

```
usage: gitlab project repository-contributors [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project repository-merge-base

```
usage: gitlab project repository-merge-base [-h] --id ID --refs REFS
```

-h, --help

show this help message and exit

--id <id>

--refs <refs>

gitlab project repository-raw-blob

```
usage: gitlab project repository-raw-blob [-h] --id ID --sha SHA
```

-h, --help

show this help message and exit

--id <id>

--sha <sha>

gitlab project repository-tree

```
usage: gitlab project repository-tree [-h] --id ID [--path PATH] [--ref REF]
                                      [--recursive RECURSIVE]
```

-h, --help

show this help message and exit

--id <id>

--path <path>

--ref <ref>

--recursive <recursive>

gitlab project restore

```
usage: gitlab project restore [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project search

```
usage: gitlab project search [-h] --id ID --scope SCOPE --search SEARCH
```

-h, --help

show this help message and exit

--id <id>

--scope <scope>

--search <search>

gitlab project share

```
usage: gitlab project share [-h] --id ID --group-id GROUP_ID --group-access
                           GROUP_ACCESS [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--id <id>

--group-id <group_id>

--group-access <group_access>

--expires-at <expires_at>

gitlab project snapshot

```
usage: gitlab project snapshot [-h] --id ID [--wiki WIKI]
```

-h, --help

show this help message and exit

--id <id>

--wiki <wiki>

gitlab project star

```
usage: gitlab project star [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project transfer

```
usage: gitlab project transfer [-h] --id ID --to-namespace TO_NAMESPACE
```

-h, --help

show this help message and exit

--id <id>

--to-namespace <to_namespace>

gitlab project transfer-project

```
usage: gitlab project transfer-project [-h] --id ID --to-namespace  
TO_NAMESPACE
```

-h, --help

show this help message and exit

--id <id>

--to-namespace <to_namespace>

gitlab project trigger-pipeline

```
usage: gitlab project trigger-pipeline [-h] --id ID --ref REF --token TOKEN
```

-h, --help

show this help message and exit

--id <id>

--ref <ref>

--token <token>

gitlab project unarchive

```
usage: gitlab project unarchive [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project unshare

```
usage: gitlab project unshare [-h] --id ID --group-id GROUP_ID
```

-h, --help

show this help message and exit

--id <id>

--group-id <group_id>

gitlab project unstar

```
usage: gitlab project unstar [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project update

```
usage: gitlab project update [-h] [--sudo SUDO] --id ID
                             [--allow-merge-on-skipped-pipeline ALLOW_MERGE_ON_SKIPPED_
                             ↵PIPELINE]
                             [--only-allow-merge-if-all-status-checks-passed ONLY_ALLOW_
                             ↵MERGE_IF_ALL_STATUS_CHECKS_PASSED]
                             [--analytics-access-level ANALYTICS_ACCESS_LEVEL]
                             [--approvals-before-merge APPROVALS_BEFORE_MERGE]
                             [--auto-cancel-pending-pipelines AUTO_CANCEL_PENDING_
                             ↵PIPELINES]
                             [--auto-devops-deploy-strategy AUTO_DEVOPS_DEPLOY_STRATEGY]
                             [--auto-devops-enabled AUTO_DEVOPS_ENABLED]
                             [--autoclose-referenced-issues AUTOCLOSE_REFERENCED_ISSUES]
                             [--avatar AVATAR]
                             [--build-coverage-regex BUILD_COVERAGE_REGEX]
                             [--build-git-strategy BUILD_GIT_STRATEGY]
                             [--build-timeout BUILD_TIMEOUT]
                             [--builds-access-level BUILDS_ACCESS_LEVEL]
                             [--ci-config-path CI_CONFIG_PATH]
                             [--ci-default-git-depth CI_DEFAULT_GIT_DEPTH]
                             [--ci-forward-deployment-enabled CI_FORWARD_DEPLOYMENT_
                             ↵ENABLED]
                             [--ci-allow-fork-pipelines-to-run-in-parent-project CI_
                             ↵ALLOW_FORK_PIPELINES_TO_RUN_IN_PARENT_PROJECT]
                             [--ci-separated-caches CI_SEPARATED_CACHES]
                             [--container-expiration-policy-attributes CONTAINER_
                             ↵EXPIRATION_POLICY_ATTRIBUTES]
                             [--container-registry-access-level CONTAINER_REGISTRY_
                             ↵ACCESS_LEVEL]
                             [--container-registry-enabled CONTAINER_REGISTRY_ENABLED]
                             [--default-branch DEFAULT_BRANCH]
                             [--description DESCRIPTION]
                             [--emails-disabled EMAILS_DISABLED]
                             [--enforce-auth-checks-on-uploads ENFORCE_AUTH_CHECKS_ON_
                             ↵UPLOADS]
                             [--external-authorization-classification-label EXTERNAL_
                             ↵AUTHORIZATION_CLASSIFICATION_LABEL]
                             [--forking-access-level FORKING_ACCESS_LEVEL]
                             [--import-url IMPORT_URL]
                             [--issues-access-level ISSUES_ACCESS_LEVEL]
                             [--issues-enabled ISSUES_ENABLED]
                             [--issues-template ISSUES_TEMPLATE]
```

(continues on next page)

(continued from previous page)

```

[--jobs-enabled JOBS_ENABLED]
[--keep-latest-artifact KEEP_LATEST_ARTIFACT]
[--lfs-enabled LFS_ENABLED]
[--merge-commit-template MERGE_COMMIT_TEMPLATE]
[--merge-method MERGE_METHOD]
[--merge-pipelines-enabled MERGE_PIPELINES_ENABLED]
[--merge-requests-access-level MERGE_REQUESTS_ACCESS_LEVEL]
[--merge-requests-enabled MERGE_REQUESTS_ENABLED]
[--merge-requests-template MERGE_REQUESTS_TEMPLATE]
[--merge-trains-enabled MERGE_TRAINS_ENABLED]
[--mirror-overwrites-diverged-branches MIRROR_OVERWRITES_]

↳ DIVERGED_BRANCHES]
    [--mirror-trigger-builds MIRROR_TRIGGER_BUILDS]
    [--mirror-user-id MIRROR_USER_ID]
    [--mirror MIRROR]
    [--mr-default-target-self MR_DEFAULT_TARGET_SELF]
    [--name NAME]
    [--operations-access-level OPERATIONS_ACCESS_LEVEL]
    [--only-allow-merge-if-all-discussions-are-resolved ONLY_]

↳ ALLOW_MERGE_IF_ALL_DISCUSSIONS_ARE_RESOLVED]
    [--only-allow-merge-if-pipeline-succeeds ONLY_ALLOW_MERGE_]

↳ IF_PIPELINE_SUCCEEDS]
    [--only-mirror-protected-branches ONLY_MIRROR_PROTECTED_]

↳ BRANCHES]
    [--packages-enabled PACKAGES_ENABLED]
    [--pages-access-level PAGES_ACCESS_LEVEL]
    [--requirements-access-level REQUIREMENTS_ACCESS_LEVEL]
    [--restrict-user-defined-variables RESTRICT_USER_DEFINED_]

↳ VARIABLES]
    [--path PATH] [--public-builds PUBLIC_BUILD]
    [--releases-access-level RELEASES_ACCESS_LEVEL]
    [--environments-access-level ENVIRONMENTS_ACCESS_LEVEL]
    [--feature-flags-access-level FEATURE_FLAGS_ACCESS_LEVEL]
    [--infrastructure-access-level INFRASTRUCTURE_ACCESS_LEVEL]
    [--monitor-access-level MONITOR_ACCESS_LEVEL]
    [--remove-source-branch-after-merge REMOVE_SOURCE_BRANCH_]

↳ AFTER_MERGE]
    [--repository-access-level REPOSITORY_ACCESS_LEVEL]
    [--repository-storage REPOSITORY_STORAGE]
    [--request-access-enabled REQUEST_ACCESS_ENABLED]
    [--resolve-outdated-diff-discussions RESOLVE_OUTDATED_DIFF_]

↳ DISCUSSIONS]
    [--security-and-compliance-access-level SECURITY_AND_]

↳ COMPLIANCE_ACCESS_LEVEL]
    [--service-desk-enabled SERVICE_DESK_ENABLED]
    [--shared-runners-enabled SHARED_RUNNERS_ENABLED]
    [--show-default-award-emojis SHOW_DEFAULT_AWARD_EMOJIS]
    [--snippets-access-level SNIPPETS_ACCESS_LEVEL]
    [--snippets-enabled SNIPPETS_ENABLED]
    [--issue-branch-template ISSUE_BRANCH_TEMPLATE]
    [--squash-commit-template SQUASH_COMMIT_TEMPLATE]
    [--squash-option SQUASH_OPTION]

```

(continues on next page)

(continued from previous page)

```
[--suggestion-commit-message SUGGESTION_COMMIT_MESSAGE]
[--tag-list TAG_LIST] [--topics TOPICS]
[--visibility VISIBILITY]
[--wiki-access-level WIKI_ACCESS_LEVEL]
[--wiki-enabled WIKI_ENABLED]
```

-h, --help

show this help message and exit

--sudo <sudo>**--id <id>****--allow-merge-on-skipped-pipeline <allow_merge_on_skipped_pipeline>****--only-allow-merge-if-all-status-checks-passed <only_allow_merge_if_all_status_checks_passed>****--analytics-access-level <analytics_access_level>****--approvals-before-merge <approvals_before_merge>****--auto-cancel-pending-pipelines <auto_cancel_pending_pipelines>****--auto-devops-deploy-strategy <auto_devops_deploy_strategy>****--auto-devops-enabled <auto_devops_enabled>****--autoclose-referenced-issues <autoclose_referenced_issues>****--avatar <avatar>****--build-coverage-regex <build_coverage_regex>****--build-git-strategy <build_git_strategy>****--build-timeout <build_timeout>****--builds-access-level <builds_access_level>****--ci-config-path <ci_config_path>****--ci-default-git-depth <ci_default_git_depth>****--ci-forward-deployment-enabled <ci_forward_deployment_enabled>****--ci-allow-fork-pipelines-to-run-in-parent-project <ci_allow_fork_pipelines_to_run_in_parent_project>****--ci-separated-caches <ci_separated_caches>****--container-expiration-policy-attributes <container_expiration_policy_attributes>****--container-registry-access-level <container_registry_access_level>****--container-registry-enabled <container_registry_enabled>****--default-branch <default_branch>****--description <description>**

```
--emails-disabled <emails_disabled>
--enforce-auth-checks-on-uploads <enforce_auth_checks_on_uploads>
--external-authorization-classification-label <external_authorization_classification_label>
--forking-access-level <forking_access_level>
--import-url <import_url>
--issues-access-level <issues_access_level>
--issues-enabled <issues_enabled>
--issues-template <issues_template>
--jobs-enabled <jobs_enabled>
--keep-latest-artifact <keep_latest_artifact>
--lfs-enabled <lfs_enabled>
--merge-commit-template <merge_commit_template>
--merge-method <merge_method>
--merge-pipelines-enabled <merge_pipelines_enabled>
--merge-requests-access-level <merge_requests_access_level>
--merge-requests-enabled <merge_requests_enabled>
--merge-requests-template <merge_requests_template>
--merge-trains-enabled <merge_trains_enabled>
--mirror-overwrites-diverged-branches <mirror_overwrites_diverged_branches>
--mirror-trigger-builds <mirror_trigger_builds>
--mirror-user-id <mirror_user_id>
--mirror <mirror>
--mr-default-target-self <mr_default_target_self>
--name <name>
--operations-access-level <operations_access_level>
--only-allow-merge-if-all-discussions-are-resolved <only_allow_merge_if_all_discussions_are_resolved>
--only-allow-merge-if-pipeline-succeeds <only_allow_merge_if_pipeline_succeeds>
--only-mirror-protected-branches <only_mirror_protected_branches>
--packages-enabled <packages_enabled>
--pages-access-level <pages_access_level>
--requirements-access-level <requirements_access_level>
```

```
--restrict-user-defined-variables <restrict_user_defined_variables>
--path <path>
--public-builds <public_builds>
--releases-access-level <releases_access_level>
--environments-access-level <environments_access_level>
--feature-flags-access-level <feature_flags_access_level>
--infrastructure-access-level <infrastructure_access_level>
--monitor-access-level <monitor_access_level>
--remove-source-branch-after-merge <remove_source_branch_after_merge>
--repository-access-level <repository_access_level>
--repository-storage <repository_storage>
--request-access-enabled <request_access_enabled>
--resolve-outdated-diff-discussions <resolve_outdated_diff_discussions>
--security-and-compliance-access-level <security_and_compliance_access_level>
--service-desk-enabled <service_desk_enabled>
--shared-runners-enabled <shared_runners_enabled>
--show-default-award-emojis <show_default_award_emojis>
--snippets-access-level <snippets_access_level>
--snippets-enabled <snippets_enabled>
--issue-branch-template <issue_branch_template>
--squash-commit-template <squash_commit_template>
--squash-option <squash_option>
--suggestion-commit-message <suggestion_commit_message>
--tag-list <tag_list>
--topics <topics>
--visibility <visibility>
--wiki-access-level <wiki_access_level>
--wiki-enabled <wiki_enabled>
```

gitlab project update-submodule

```
usage: gitlab project update-submodule [-h] --id ID --submodule SUBMODULE  
                                      --branch BRANCH --commit-sha COMMIT_SHA
```

-h, --help

show this help message and exit

--id <id>

--submodule <submodule>

--branch <branch>

--commit-sha <commit_sha>

gitlab project upload

```
usage: gitlab project upload [-h] --id ID --filename FILENAME --filepath  
                           FILEPATH
```

-h, --help

show this help message and exit

--id <id>

--filename <filename>

--filepath <filepath>

gitlab project-access-request

```
usage: gitlab project-access-request [-h] {list,create,delete,approve} ...
```

-h, --help

show this help message and exit

gitlab project-access-request approve

```
usage: gitlab project-access-request approve [-h] --project-id PROJECT_ID  
                                           [--sudo SUDO] --id ID  
                                           [--access-level ACCESS_LEVEL]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--access-level <access_level>

gitlab project-access-request create

```
usage: gitlab project-access-request create [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-access-request delete

```
usage: gitlab project-access-request delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-access-request list

```
usage: gitlab project-access-request list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID [--page PAGE]  
                                         [--per-page PER_PAGE] [--get-all]  
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-access-token

```
usage: gitlab project-access-token [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-access-token create

```
usage: gitlab project-access-token create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --name NAME --scopes
                                         SCOPES [--access-level ACCESS_LEVEL]
                                         [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--scopes <scopes>

--access-level <access_level>

--expires-at <expires_at>

gitlab project-access-token delete

```
usage: gitlab project-access-token delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-access-token list

```
usage: gitlab project-access-token list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-additional-statistics

```
usage: gitlab project-additional-statistics [-h] {get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-additional-statistics get

```
usage: gitlab project-additional-statistics get [-h] [--sudo SUDO]
                                               --project-id PROJECT_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
```

gitlab project-approval

```
usage: gitlab project-approval [-h] {get,update} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-approval get

```
usage: gitlab project-approval get [-h] [--sudo SUDO] --project-id PROJECT_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
```

gitlab project-approval update

```
usage: gitlab project-approval update [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID
                                      [--approvals-before-merge APPROVALS_BEFORE_MERGE]
                                      [--reset-approvals-on-push RESET_APPROVALS_ON_PUSH]
                                      [--disable-overriding-approvers-per-merge-request
                                       ↵DISABLE_OVERRIDING_APPROVERS_PER_MERGE_REQUEST]
                                      [--merge-requests-author-approval MERGE_REQUESTS_
                                       ↵AUTHOR_APPROVAL]
                                      [--merge-requests-disable-committers-approval
                                       ↵MERGE_REQUESTS_DISABLE_COMMITTERS_APPROVAL]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--approvals-before-merge <approvals_before_merge>

--reset-approvals-on-push <reset_approvals_on_push>

--disable-overriding-approvers-per-merge-request <disable_overriding_approvers_per_merge_request>

--merge-requests-author-approval <merge_requests_author_approval>

--merge-requests-disable-committers-approval <merge_requests_disable_committers_approval>

gitlab project-approval-rule

```
usage: gitlab project-approval-rule [-h] {list,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-approval-rule create

```
usage: gitlab project-approval-rule create [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --name NAME
                                             --approvals-required
                                             APPROVALS_REQUIRED
                                             [--user-ids USER_IDS]
                                             [--group-ids GROUP_IDS]
                                             [--protected-branch-ids PROTECTED_BRANCH_IDS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--name <name>
--approvals-required <approvals_required>
--user-ids <user_ids>
--group-ids <group_ids>
--protected-branch-ids <protected_branch_ids>
```

gitlab project-approval-rule delete

```
usage: gitlab project-approval-rule delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-approval-rule list

```
usage: gitlab project-approval-rule list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all
Return all items from the server, without pagination.

--all
Deprecated. Use --get-all instead.

gitlab project-approval-rule update

```
usage: gitlab project-approval-rule update [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-artifact

```
usage: gitlab project-artifact [-h] {delete,download,raw} ...
```

-h, --help

show this help message and exit

gitlab project-artifact delete

```
usage: gitlab project-artifact delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --ref-name REF_NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--ref-name <ref_name>

gitlab project-artifact download

```
usage: gitlab project-artifact download [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --ref-name REF_NAME  
                                         --job JOB [--job-token JOB_TOKEN]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--ref-name <ref_name>

--job <job>

--job-token <job_token>

gitlab project-artifact raw

```
usage: gitlab project-artifact raw [-h] --project-id PROJECT_ID [--sudo SUDO]
                                  --ref-name REF_NAME --artifact-path
                                  ARTIFACT_PATH --job JOB
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--ref-name <ref_name>

--artifact-path <artifact_path>

--job <job>

gitlab project-audit-event

```
usage: gitlab project-audit-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-audit-event get

```
usage: gitlab project-audit-event get [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-audit-event list

```
usage: gitlab project-audit-event list [-h] [--sudo SUDO] --project-id
                                       PROJECT_ID
                                       [--created-after CREATED_AFTER]
                                       [--created-before CREATED_BEFORE]
                                       [--page PAGE] [--per-page PER_PAGE]
                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--created-after <created_after>
--created-before <created_before>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-badge

```
usage: gitlab project-badge [-h] {list,get,create,update,delete,render} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-badge create

```
usage: gitlab project-badge create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --link-url LINK_URL --image-url IMAGE_URL
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--link-url <link_url>
--image-url <image_url>
```

gitlab project-badge delete

```
usage: gitlab project-badge delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-badge get

```
usage: gitlab project-badge get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                               --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-badge list

```
usage: gitlab project-badge list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 [--page PAGE] [--per-page PER_PAGE]  
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-badge render

```
usage: gitlab project-badge render [-h] --project-id PROJECT_ID [--sudo SUDO]  
                                   --id ID --link-url LINK_URL --image-url  
                                   IMAGE_URL
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--link-url <link_url>

--image-url <image_url>

gitlab project-badge update

```
usage: gitlab project-badge update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --id ID [--link-url LINK_URL]
                                  [--image-url IMAGE_URL]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--link-url <link_url>

--image-url <image_url>

gitlab project-board

```
usage: gitlab project-board [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-board create

```
usage: gitlab project-board create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-board delete

```
usage: gitlab project-board delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-board get

```
usage: gitlab project-board get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                               --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-board list

```
usage: gitlab project-board list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 [--page PAGE] [--per-page PER_PAGE]  
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-board update

```
usage: gitlab project-board update [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-board-list

```
usage: gitlab project-board-list [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-board-list create

```
usage: gitlab project-board-list create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --board-id BOARD_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

gitlab project-board-list delete

```
usage: gitlab project-board-list delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --board-id BOARD_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

--id <id>

gitlab project-board-list get

```
usage: gitlab project-board-list get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --board-id BOARD_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

--id <id>

gitlab project-board-list list

```
usage: gitlab project-board-list list [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --board-id BOARD_ID
                                      [--page PAGE] [--per-page PER_PAGE]
                                      [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-board-list update

```
usage: gitlab project-board-list update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --board-id BOARD_ID --id ID
                                         --position POSITION
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

--id <id>

--position <position>

gitlab project-branch

```
usage: gitlab project-branch [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-branch create

```
usage: gitlab project-branch create [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   --branch BRANCH --ref REF
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--branch <branch>

--ref <ref>

gitlab project-branch delete

```
usage: gitlab project-branch delete [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-branch get

```
usage: gitlab project-branch get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-branch list

```
usage: gitlab project-branch list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  [--page PAGE] [--per-page PER_PAGE]
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-ci-lint

```
usage: gitlab project-ci-lint [-h] {get,create,validate} ...
```

-h, --help

show this help message and exit

gitlab project-ci-lint create

```
usage: gitlab project-ci-lint create [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --content CONTENT
                                     [--dry-run DRY_RUN]
                                     [--include-jobs INCLUDE_JOBS] [--ref REF]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--content <content>

--dry-run <dry_run>

--include-jobs <include_jobs>

--ref <ref>

gitlab project-ci-lint get

```
usage: gitlab project-ci-lint get [-h] [--sudo SUDO] --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-ci-lint validate

```
usage: gitlab project-ci-lint validate [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --content CONTENT
                                         [--dry-run DRY_RUN]
                                         [--include-jobs INCLUDE_JOBS]
                                         [--ref REF]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--content <content>

--dry-run <dry_run>

--include-jobs <include_jobs>

--ref <ref>

gitlab project-cluster

```
usage: gitlab project-cluster [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-cluster create

```
usage: gitlab project-cluster create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --name NAME
                                         --platform-kubernetes-attributes
                                         PLATFORM_KUBERNETES_ATTRIBUTES
                                         [--domain DOMAIN] [--enabled ENABLED]
                                         [--managed MANAGED]
                                         [--environment-scope ENVIRONMENT_SCOPE]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--name <name>
--platform-kubernetes-attributes <platform_kubernetes_attributes>
--domain <domain>
--enabled <enabled>
--managed <managed>
--environment-scope <environment_scope>
```

gitlab project-cluster delete

```
usage: gitlab project-cluster delete [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-cluster get

```
usage: gitlab project-cluster get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-cluster list

```
usage: gitlab project-cluster list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  [--page PAGE] [--per-page PER_PAGE]
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab project-cluster update

```
usage: gitlab project-cluster update [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --id ID [--name NAME]
                                     [--domain DOMAIN]
                                     [--management-project-id MANAGEMENT_PROJECT_ID]
                                     [--platform-kubernetes-attributes PLATFORM_
                                     ↵KUBERNETES_ATTRIBUTES]
                                     [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--name <name>

--domain <domain>

--management-project-id <management_project_id>

--platform-kubernetes-attributes <platform_kubernetes_attributes>

--environment-scope <environment_scope>

gitlab project-commit

```
usage: gitlab project-commit [-h]
    list
    get
    create
    diff
    cherry-pick
    refs
    merge-requests
    revert
    signature
    ...
    ...
```

-h, --help

show this help message and exit

gitlab project-commit cherry-pick

```
usage: gitlab project-commit cherry-pick [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --id ID --branch BRANCH
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--branch <branch>

gitlab project-commit create

```
usage: gitlab project-commit create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                    --branch BRANCH --commit-message
                                    COMMIT_MESSAGE --actions ACTIONS
                                    [--author-email AUTHOR_EMAIL]
                                    [--author-name AUTHOR_NAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--branch <branch>

--commit-message <commit_message>

--actions <actions>

```
--author-email <author_email>  
--author-name <author_name>
```

gitlab project-commit diff

```
usage: gitlab project-commit diff [-h] --project-id PROJECT_ID [--sudo SUDO]  
                                 --id ID
```

```
-h, --help  
    show this help message and exit  
--project-id <project_id>  
--sudo <sudo>  
--id <id>
```

gitlab project-commit get

```
usage: gitlab project-commit get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 --id ID
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>  
--id <id>
```

gitlab project-commit list

```
usage: gitlab project-commit list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 [--ref-name REF_NAME] [--since SINCE]  
                                 [--until UNTIL] [--path PATH]  
                                 [--with-stats WITH_STATS]  
                                 [--first-parent FIRST_PARENT]  
                                 [--order ORDER] [--trailers TRAILERS]  
                                 [--page PAGE] [--per-page PER_PAGE]  
                                 [--get-all] [--all]
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>  
--ref-name <ref_name>
```

```
--since <since>
--until <until>
--path <path>
--with-stats <with_stats>
--first-parent <first_parent>
--order <order>
--trailers <trailers>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-commit merge-requests

```
usage: gitlab project-commit merge-requests [-h] --project-id PROJECT_ID
                                            [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>
```

gitlab project-commit refs

```
usage: gitlab project-commit refs [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID [--type TYPE]
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>
--type <type>
```

gitlab project-commit revert

```
usage: gitlab project-commit revert [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID --branch BRANCH
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--branch <branch>

gitlab project-commit signature

```
usage: gitlab project-commit signature [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-commit-comment

```
usage: gitlab project-commit-comment [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab project-commit-comment create

```
usage: gitlab project-commit-comment create [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --commit-id COMMIT_ID
                                             --note NOTE [--path PATH]
                                             [--line LINE]
                                             [--line-type LINE_TYPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--commit-id <commit_id>
--note <note>
--path <path>
--line <line>
--line-type <line_type>
```

gitlab project-commit-comment list

```
usage: gitlab project-commit-comment list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --commit-id COMMIT_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-commit-discussion

```
usage: gitlab project-commit-discussion [-h] {list,get,create} ...
```

-h, --help

show this help message and exit

gitlab project-commit-discussion create

```
usage: gitlab project-commit-discussion create [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --commit-id
                                               COMMIT_ID --body BODY
                                               [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--commit-id <commit_id>
--body <body>
--created-at <created_at>
```

gitlab project-commit-discussion get

```
usage: gitlab project-commit-discussion get [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --commit-id COMMIT_ID
                                             --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--commit-id <commit_id>
--id <id>
```

gitlab project-commit-discussion list

```
usage: gitlab project-commit-discussion list [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --commit-id COMMIT_ID
                                              [--page PAGE]
                                              [--per-page PER_PAGE] [--get-all]
                                              [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--commit-id <commit_id>
--page <page>
--per-page <per_page>
--get-all
```

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-commit-discussion-note

```
usage: gitlab project-commit-discussion-note [-h]
  get
  create
  update
  delete} ...
```

-h, --help

show this help message and exit

gitlab project-commit-discussion-note create

```
usage: gitlab project-commit-discussion-note create [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --commit-id COMMIT_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --body BODY
                                                    [--created-at CREATED_AT]
                                                    [--position POSITION]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--discussion-id <discussion_id>

--body <body>

--created-at <created_at>

--position <position>

gitlab project-commit-discussion-note delete

```
usage: gitlab project-commit-discussion-note delete [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --commit-id COMMIT_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--commit-id <commit_id>
--discussion-id <discussion_id>
--id <id>
```

gitlab project-commit-discussion-note get

```
usage: gitlab project-commit-discussion-note get [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --commit-id COMMIT_ID
                                                --discussion-id DISCUSSION_ID
                                                --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--discussion-id <discussion_id>

--id <id>

gitlab project-commit-discussion-note update

```
usage: gitlab project-commit-discussion-note update [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --commit-id COMMIT_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --id ID
                                                    --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--discussion-id <discussion_id>

--id <id>

--body <body>

gitlab project-commit-status

```
usage: gitlab project-commit-status [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab project-commit-status create

```
usage: gitlab project-commit-status create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --commit-id COMMIT_ID
                                         --state STATE
                                         [--description DESCRIPTION]
                                         [--name NAME] [--context CONTEXT]
                                         [--ref REF]
                                         [--target-url TARGET_URL]
                                         [--coverage COVERAGE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--state <state>

--description <description>

--name <name>

--context <context>

--ref <ref>

--target-url <target_url>

--coverage <coverage>

gitlab project-commit-status list

```
usage: gitlab project-commit-status list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --commit-id COMMIT_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--commit-id <commit_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-custom-attribute

```
usage: gitlab project-custom-attribute [-h] {list,get,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-custom-attribute delete

```
usage: gitlab project-custom-attribute delete [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --key KEY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--key <key>
```

gitlab project-custom-attribute get

```
usage: gitlab project-custom-attribute get [-h] [--sudo SUDO] --project-id
                                            PROJECT_ID --key KEY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--key <key>
```

gitlab project-custom-attribute list

```
usage: gitlab project-custom-attribute list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-deploy-token

```
usage: gitlab project-deploy-token [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-deploy-token create

```
usage: gitlab project-deploy-token create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --name NAME --scopes  
SCOPES [--expires-at EXPIRES_AT]  
[--username USERNAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--scopes <scopes>

--expires-at <expires_at>

--username <username>

gitlab project-deploy-token delete

```
usage: gitlab project-deploy-token delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-deploy-token get

```
usage: gitlab project-deploy-token get [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-deploy-token list

```
usage: gitlab project-deploy-token list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID [--scopes SCOPES]  
                                         [--page PAGE] [--per-page PER_PAGE]  
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--scopes <scopes>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-deployment

```
usage: gitlab project-deployment [-h] {list,get,create,update,approval} ...
```

-h, --help

show this help message and exit

gitlab project-deployment approval

```
usage: gitlab project-deployment approval [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --id ID --status
                                         STATUS [--comment COMMENT]
                                         [--represented-as REPRESENTED_AS]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--status <status>

--comment <comment>

--represented-as <represented_as>

gitlab project-deployment create

```
usage: gitlab project-deployment create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --sha SHA --ref REF --tag
                                         TAG --status STATUS --environment
                                         ENVIRONMENT
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--sha <sha>

--ref <ref>

--tag <tag>

--status <status>

--environment <environment>

gitlab project-deployment get

```
usage: gitlab project-deployment get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-deployment list

```
usage: gitlab project-deployment list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--order-by ORDER_BY]  
[--sort SORT]  
[--updated-after UPDATED_AFTER]  
[--updated-before UPDATED_BEFORE]  
[--environment ENVIRONMENT]  
[--status STATUS] [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--order-by <order_by>

--sort <sort>

--updated-after <updated_after>

--updated-before <updated_before>

--environment <environment>

--status <status>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-deployment update

```
usage: gitlab project-deployment update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--id <id>****gitlab project-deployment-merge-request**

```
usage: gitlab project-deployment-merge-request [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-deployment-merge-request list

```
usage: gitlab project-deployment-merge-request list [-h] [--sudo SUDO]
                                                    --deployment-id
                                                    DEPLOYMENT_ID --project-id
                                                    PROJECT_ID [--state STATE]
                                                    [--order-by ORDER_BY]
                                                    [--sort SORT]
                                                    [--milestone MILESTONE]
                                                    [--view VIEW]
                                                    [--labels LABELS]
                                                    [--with-labels-details WITH_LABELS_
                                                    ↵DETAILS]
                                                    [--with-merge-status-recheck WITH_
                                                    ↵MERGE_STATUS_RECHECK]
                                                    [--created-after CREATED_AFTER]
                                                    [--created-before CREATED_BEFORE]
                                                    [--updated-after UPDATED_AFTER]
                                                    [--updated-before UPDATED_BEFORE]
                                                    [--scope SCOPE]
                                                    [--author-id AUTHOR_ID]
                                                    [--author-username AUTHOR_USERNAME]
                                                    [--assignee-id ASSIGNEE_ID]
                                                    [--approver-ids APPROVER_IDS]
                                                    [--approved-by-ids APPROVED_BY_IDS]
                                                    [--reviewer-id REVIEWER_ID]
                                                    [--reviewer-username REVIEWER_
                                                    ↵USERNAME]
                                                    [--my-reaction-emoji MY_REACTION_
                                                    ↵EMOJI]
```

(continues on next page)

(continued from previous page)

```
[--source-branch SOURCE_BRANCH]
[--target-branch TARGET_BRANCH]
[--search SEARCH]
[--in IN] [--wip WIP]
[--not NOT]
[--environment ENVIRONMENT]
[--deployed-before DEPLOYED_BEFORE]
[--deployed-after DEPLOYED_AFTER]
[--page PAGE]
[--per-page PER_PAGE]
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--deployment-id <deployment_id>****--project-id <project_id>****--state <state>****--order-by <order_by>****--sort <sort>****--milestone <milestone>****--view <view>****--labels <labels>****--with-labels-details <with_labels_details>****--with-merge-status-recheck <with_merge_status_recheck>****--created-after <created_after>****--created-before <created_before>****--updated-after <updated_after>****--updated-before <updated_before>****--scope <scope>****--author-id <author_id>****--author-username <author_username>****--assignee-id <assignee_id>****--approver-ids <approver_ids>****--approved-by-ids <approved_by_ids>****--reviewer-id <reviewer_id>**

```
--reviewer-username <reviewer_username>
--my-reaction-emoji <my_reaction_emoji>
--source-branch <source_branch>
--target-branch <target_branch>
--search <search>
--in <in>
--wip <wip>
--not <not>
--environment <environment>
--deployed-before <deployed_before>
--deployed-after <deployed_after>
--page <page>
--per-page <per_page>
--get-all
```

Return all items from the server, without pagination.

```
--all
```

Deprecated. Use --get-all instead.

gitlab project-environment

```
usage: gitlab project-environment [-h]
    list
    get
    create
    update
    delete
    stop} ...
```

```
-h, --help
```

show this help message and exit

gitlab project-environment create

```
usage: gitlab project-environment create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --name NAME
                                         [--external-url EXTERNAL_URL]
```

```
-h, --help
```

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--name <name>
--external-url <external_url>
```

gitlab project-environment delete

```
usage: gitlab project-environment delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-environment get

```
usage: gitlab project-environment get [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-environment list

```
usage: gitlab project-environment list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--name NAME]
                                         [--search SEARCH] [--states STATES]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--name <name>
```

```
--search <search>
--states <states>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-environment stop

```
usage: gitlab project-environment stop [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>
```

gitlab project-environment update

```
usage: gitlab project-environment update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID [--name NAME]
                                         [--external-url EXTERNAL_URL]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
--name <name>
--external-url <external_url>
```

gitlab project-event

```
usage: gitlab project-event [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-event list

```
usage: gitlab project-event list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 [--action ACTION] [--target-type TARGET_TYPE]
                                 [--before BEFORE] [--after AFTER]
                                 [--sort SORT] [--page PAGE]
                                 [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--action <action>

--target-type <target_type>

--before <before>

--after <after>

--sort <sort>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-export

```
usage: gitlab project-export [-h] {get,create,download} ...
```

-h, --help

show this help message and exit

gitlab project-export create

```
usage: gitlab project-export create [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  [--description DESCRIPTION]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--description <description>

gitlab project-export download

```
usage: gitlab project-export download [-h] --project-id PROJECT_ID  
                                     [--sudo SUDO]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

gitlab project-export get

```
usage: gitlab project-export get [-h] [--sudo SUDO] --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-file

```
usage: gitlab project-file [-h] {get,create,update,delete,raw,blame} ...
```

-h, --help

show this help message and exit

gitlab project-file blame

```
usage: gitlab project-file blame [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --file-path FILE_PATH --ref REF
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--ref <ref>

gitlab project-file create

```
usage: gitlab project-file create [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --file-path FILE_PATH --branch BRANCH
                                   --content CONTENT --commit-message
                                   COMMIT_MESSAGE [--encoding ENCODING]
                                   [--author-email AUTHOR_EMAIL]
                                   [--author-name AUTHOR_NAME]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--branch <branch>

--content <content>

--commit-message <commit_message>

--encoding <encoding>

--author-email <author_email>

--author-name <author_name>

gitlab project-file delete

```
usage: gitlab project-file delete [-h] --project-id PROJECT_ID [--sudo SUDO]
                                  --file-path FILE_PATH --branch BRANCH
                                  --commit-message COMMIT_MESSAGE
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--branch <branch>

--commit-message <commit_message>

gitlab project-file get

```
usage: gitlab project-file get [-h] --project-id PROJECT_ID [--sudo SUDO]
                               --file-path FILE_PATH --ref REF
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--ref <ref>

gitlab project-file raw

```
usage: gitlab project-file raw [-h] --project-id PROJECT_ID [--sudo SUDO]
                               --file-path FILE_PATH --ref REF
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--ref <ref>

gitlab project-file update

```
usage: gitlab project-file update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --file-path FILE_PATH --branch BRANCH
                                  --content CONTENT --commit-message
                                  COMMIT_MESSAGE [--encoding ENCODING]
                                  [--author-email AUTHOR_EMAIL]
                                  [--author-name AUTHOR_NAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--file-path <file_path>

--branch <branch>

--content <content>

--commit-message <commit_message>

--encoding <encoding>

--author-email <author_email>

--author-name <author_name>

gitlab project-fork

```
usage: gitlab project-fork [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab project-fork create

```
usage: gitlab project-fork create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  [--namespace NAMESPACE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--namespace <namespace>

gitlab project-fork list

```
usage: gitlab project-fork list [-h] [--sudo SUDO] --project-id PROJECT_ID
                               [--archived ARCHIVED]
                               [--visibility VISIBILITY]
                               [--order-by ORDER_BY] [--sort SORT]
                               [--search SEARCH] [--simple SIMPLE]
                               [--owned OWNED] [--membership MEMBERSHIP]
                               [--starred STARRED] [--statistics STATISTICS]
                               [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                               [--with-issues-enabled WITH_ISSUES_ENABLED]
                               [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
→ENABLED]
                               [--page PAGE] [--per-page PER_PAGE]
                               [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--archived <archived>

--visibility <visibility>

--order-by <order_by>

--sort <sort>

--search <search>

--simple <simple>

--owned <owned>

--membership <membership>

--starred <starred>

--statistics <statistics>

--with-custom-attributes <with_custom_attributes>

--with-issues-enabled <with_issues_enabled>

--with-merge-requests-enabled <with_merge_requests_enabled>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-hook

```
usage: gitlab project-hook [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-hook create

```
usage: gitlab project-hook create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --url URL [--push-events PUSH_EVENTS]
                                  [--issues-events ISSUES_EVENTS]
                                  [--confidential-issues-events CONFIDENTIAL_ISSUES_
                                   EVENTS]
                                  [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                  [--tag-push-events TAG_PUSH_EVENTS]
                                  [--note-events NOTE_EVENTS]
                                  [--job-events JOB_EVENTS]
                                  [--pipeline-events PIPELINE_EVENTS]
                                  [--wiki-page-events WIKI_PAGE_EVENTS]
                                  [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                  [--token TOKEN]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--url <url>

--push-events <push_events>

--issues-events <issues_events>

--confidential-issues-events <confidential_issues_events>

--merge-requests-events <merge_requests_events>

--tag-push-events <tag_push_events>

--note-events <note_events>

--job-events <job_events>

--pipeline-events <pipeline_events>

--wiki-page-events <wiki_page_events>

--enable-ssl-verification <enable_ssl_verification>

--token <token>

gitlab project-hook delete

```
usage: gitlab project-hook delete [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-hook get

```
usage: gitlab project-hook get [-h] [--sudo SUDO] --project-id PROJECT_ID --id  
                               ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-hook list

```
usage: gitlab project-hook list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                [--page PAGE] [--per-page PER_PAGE]  
                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-hook update

```
usage: gitlab project-hook update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --id ID --url URL
                                  [--push-events PUSH_EVENTS]
                                  [--issues-events ISSUES_EVENTS]
                                  [--confidential-issues-events CONFIDENTIAL_ISSUES_
←EVENTS]
                                  [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                  [--tag-push-events TAG_PUSH_EVENTS]
                                  [--note-events NOTE_EVENTS]
                                  [--job-events JOB_EVENTS]
                                  [--pipeline-events PIPELINE_EVENTS]
                                  [--wiki-events WIKI_EVENTS]
                                  [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                  [--token TOKEN]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--url <url>

--push-events <push_events>

--issues-events <issues_events>

--confidential-issues-events <confidential_issues_events>

--merge-requests-events <merge_requests_events>

--tag-push-events <tag_push_events>

--note-events <note_events>

--job-events <job_events>

--pipeline-events <pipeline_events>

--wiki-events <wiki_events>

--enable-ssl-verification <enable_ssl_verification>

--token <token>

gitlab project-import

```
usage: gitlab project-import [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-import get

```
usage: gitlab project-import get [-h] [--sudo SUDO] --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-integration

```
usage: gitlab project-integration [-h] {list,get,update,delete,available} ...
```

-h, --help

show this help message and exit

gitlab project-integration available

```
usage: gitlab project-integration available [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --slug SLUG
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--slug <slug>

gitlab project-integration delete

```
usage: gitlab project-integration delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-integration get

```
usage: gitlab project-integration get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-integration list

```
usage: gitlab project-integration list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-integration update

```
usage: gitlab project-integration update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-invitation

```
usage: gitlab project-invitation [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-invitation create

```
usage: gitlab project-invitation create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --access-level ACCESS_LEVEL
                                         [--expires-at EXPIRES_AT]
                                         [--invite-source INVITE_SOURCE]
                                         [--tasks-to-be-done TASKS_TO_BE_DONE]
                                         [--tasks-project-id TASKS_PROJECT_ID]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--access-level <access_level>

--expires-at <expires_at>

--invite-source <invite_source>

--tasks-to-be-done <tasks_to_be_done>

--tasks-project-id <tasks_project_id>

gitlab project-invitation delete

```
usage: gitlab project-invitation delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --email EMAIL
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--email <email>

gitlab project-invitation get

```
usage: gitlab project-invitation get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --email EMAIL
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--email <email>

gitlab project-invitation list

```
usage: gitlab project-invitation list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--query QUERY] [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--query <query>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-invitation update

```
usage: gitlab project-invitation update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --email EMAIL  
[--access-level ACCESS_LEVEL]  
[--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--email <email>
--access-level <access_level>
--expires-at <expires_at>
```

gitlab project-issue

```
usage: gitlab project-issue [-h]
    list
    get
    create
    update
    delete
    user-agent-detail
    subscribe
    unsubscribe
    todo
    time-stats
    time-estimate
    reset-time-estimate
    add-spent-time
    reset-spent-time
    participants
    move
    reorder
    related-merge-requests
    closed-by
    ...
    ...
```

-h, --help

show this help message and exit

gitlab project-issue add-spent-time

```
usage: gitlab project-issue add-spent-time [-h] --project-id PROJECT_ID
                                            [--sudo SUDO] --iid IID --duration
                                            DURATION
```

-h, --help

show this help message and exit

```
--project-id <project_id>
--sudo <sudo>
--iid <iid>
--duration <duration>
```

gitlab project-issue closed-by

```
usage: gitlab project-issue closed-by [-h] --project-id PROJECT_ID  
                                     [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue create

```
usage: gitlab project-issue create [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   --title TITLE [--description DESCRIPTION]  
                                   [--confidential CONFIDENTIAL]  
                                   [--assignee-ids ASSIGNEE_IDS]  
                                   [--assignee-id ASSIGNEE_ID]  
                                   [--milestone-id MILESTONE_ID]  
                                   [--labels LABELS] [--created-at CREATED_AT]  
                                   [--due-date DUE_DATE]  
                                   [--merge-request-to-resolve-discussions-of MERGE_  
→REQUEST_TO_RESOLVE_DISCUSSIONS_OF]  
                                   [--discussion-to-resolve DISCUSSION_TO_RESOLVE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--title <title>

--description <description>

--confidential <confidential>

--assignee-ids <assignee_ids>

--assignee-id <assignee_id>

--milestone-id <milestone_id>

--labels <labels>

--created-at <created_at>

--due-date <due_date>

--merge-request-to-resolve-discussions-of <merge_request_to_resolve_discussions_of>

--discussion-to-resolve <discussion_to_resolve>

gitlab project-issue delete

```
usage: gitlab project-issue delete [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  --iid IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iid <iid>

gitlab project-issue get

```
usage: gitlab project-issue get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 --iid IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iid <iid>

gitlab project-issue list

```
usage: gitlab project-issue list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 [--iids IIDS] [--state STATE]  
                                 [--labels LABELS] [--milestone MILESTONE]  
                                 [--scope SCOPE] [--author-id AUTHOR_ID]  
                                 [--assignee-id ASSIGNEE_ID]  
                                 [--my-reaction-emoji MY_REACTION_EMOJI]  
                                 [--order-by ORDER_BY] [--sort SORT]  
                                 [--search SEARCH]  
                                 [--created-after CREATED_AFTER]  
                                 [--created-before CREATED_BEFORE]  
                                 [--updated-after UPDATED_AFTER]  
                                 [--updated-before UPDATED_BEFORE]  
                                 [--page PAGE] [--per-page PER_PAGE]  
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iids <iids>

```
--state <state>
--labels <labels>
--milestone <milestone>
--scope <scope>
--author-id <author_id>
--assignee-id <assignee_id>
--my-reaction-emoji <my_reaction_emoji>
--order-by <order_by>
--sort <sort>
--search <search>
--created-after <created_after>
--created-before <created_before>
--updated-after <updated_after>
--updated-before <updated_before>
--page <page>
--per-page <per_page>
--get-all
```

Return all items from the server, without pagination.

```
--all
```

Deprecated. Use --get-all instead.

gitlab project-issue move

```
usage: gitlab project-issue move [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --iid IID --to-project-id TO_PROJECT_ID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
--to-project-id <to_project_id>
```

gitlab project-issue participants

```
usage: gitlab project-issue participants [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue related-merge-requests

```
usage: gitlab project-issue related-merge-requests [-h] --project-id  
                                                 PROJECT_ID [--sudo SUDO]  
                                                 --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue reorder

```
usage: gitlab project-issue reorder [-h] --project-id PROJECT_ID [--sudo SUDO]  
                                    --iid IID --move-after-id MOVE_AFTER_ID  
                                    --move-before-id MOVE_BEFORE_ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--move-after-id <move_after_id>

--move-before-id <move_before_id>

gitlab project-issue reset-spent-time

```
usage: gitlab project-issue reset-spent-time [-h] --project-id PROJECT_ID  
                                              [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue reset-time-estimate

```
usage: gitlab project-issue reset-time-estimate [-h] --project-id PROJECT_ID  
                                                [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue subscribe

```
usage: gitlab project-issue subscribe [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue time-estimate

```
usage: gitlab project-issue time-estimate [-h] --project-id PROJECT_ID  
                                            [--sudo SUDO] --iid IID --duration  
                                            DURATION
```

-h, --help

show this help message and exit

--project-id <project_id>

```
--sudo <sudo>
--iid <iid>
--duration <duration>
```

gitlab project-issue time-stats

```
usage: gitlab project-issue time-stats [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --iid IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-issue todo

```
usage: gitlab project-issue todo [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --iid IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-issue unsubscribe

```
usage: gitlab project-issue unsubscribe [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --iid IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-issue update

```
usage: gitlab project-issue update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --iid IID [--title TITLE]
                                  [--description DESCRIPTION]
                                  [--confidential CONFIDENTIAL]
                                  [--assignee-ids ASSIGNEE_IDS]
                                  [--assignee-id ASSIGNEE_ID]
                                  [--milestone-id MILESTONE_ID]
                                  [--labels LABELS]
                                  [--state-event STATE_EVENT]
                                  [--updated-at UPDATED_AT]
                                  [--due-date DUE_DATE]
                                  [--discussion-locked DISCUSSION_LOCKED]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iid <iid>

--title <title>

--description <description>

--confidential <confidential>

--assignee-ids <assignee_ids>

--assignee-id <assignee_id>

--milestone-id <milestone_id>

--labels <labels>

--state-event <state_event>

--updated-at <updated_at>

--due-date <due_date>

--discussion-locked <discussion_locked>

gitlab project-issue user-agent-detail

```
usage: gitlab project-issue user-agent-detail [-h] --project-id PROJECT_ID
                                              [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

```
--sudo <sudo>
--iid <iid>
```

gitlab project-issue-award-emoji

```
usage: gitlab project-issue-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-issue-award-emoji create

```
usage: gitlab project-issue-award-emoji create [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --issue-iid
                                               ISSUE_IID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--name <name>

gitlab project-issue-award-emoji delete

```
usage: gitlab project-issue-award-emoji delete [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --issue-iid
                                               ISSUE_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-award-emoji get

```
usage: gitlab project-issue-award-emoji get [-h] [--sudo SUDO] --project-id  
                                PROJECT_ID --issue-iid ISSUE_IID  
                                --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-award-emoji list

```
usage: gitlab project-issue-award-emoji list [-h] [--sudo SUDO] --project-id  
                                PROJECT_ID --issue-iid ISSUE_IID  
                                [--page PAGE]  
                                [--per-page PER_PAGE] [--get-all]  
                                [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issue-discussion

```
usage: gitlab project-issue-discussion [-h] {list,get,create} ...
```

-h, --help

show this help message and exit

gitlab project-issue-discussion create

```
usage: gitlab project-issue-discussion create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --issue-iid ISSUE_IID  
--body BODY  
[--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--body <body>

--created-at <created_at>

gitlab project-issue-discussion get

```
usage: gitlab project-issue-discussion get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --issue-iid ISSUE_IID  
--id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-discussion list

```
usage: gitlab project-issue-discussion list [-h] [--sudo SUDO] --project-id  
PROJECT_ID --issue-iid ISSUE_IID  
[--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

```
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-issue-discussion-note

```
usage: gitlab project-issue-discussion-note [-h]
  get
  create
  update
  delete} ...
```

-h, --help
show this help message and exit

gitlab project-issue-discussion-note create

```
usage: gitlab project-issue-discussion-note create [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --discussion-id
                                                 DISCUSSION_ID --body BODY
                                                 [--created-at CREATED_AT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--discussion-id <discussion_id>

--body <body>

--created-at <created_at>

gitlab project-issue-discussion-note delete

```
usage: gitlab project-issue-discussion-note delete [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --discussion-id
                                                 DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--discussion-id <discussion_id>

--id <id>

gitlab project-issue-discussion-note get

```
usage: gitlab project-issue-discussion-note get [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --issue-iid ISSUE_IID
                                                --discussion-id DISCUSSION_ID
                                                --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--discussion-id <discussion_id>

--id <id>

gitlab project-issue-discussion-note update

```
usage: gitlab project-issue-discussion-note update [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --discussion-id
                                                 DISCUSSION_ID --id ID
                                                 --body BODY
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--discussion-id <discussion_id>
--id <id>
--body <body>
```

gitlab project-issue-link

```
usage: gitlab project-issue-link [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-issue-link create

```
usage: gitlab project-issue-link create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --issue-iid ISSUE_IID
                                         --target-project-id TARGET_PROJECT_ID
                                         --target-issue-iid TARGET_ISSUE_IID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--target-project-id <target_project_id>
--target-issue-iid <target_issue_iid>
```

gitlab project-issue-link delete

```
usage: gitlab project-issue-link delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --issue-iid ISSUE_IID
                                         --issue-link-id ISSUE_LINK_ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--issue-link-id <issue_link_id>
```

gitlab project-issue-link list

```
usage: gitlab project-issue-link list [-h] [--sudo SUDO] --project-id  
PROJECT_ID --issue-iid ISSUE_IID  
[--page PAGE] [--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issue-note

```
usage: gitlab project-issue-note [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-issue-note create

```
usage: gitlab project-issue-note create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --issue-iid ISSUE_IID  
--body BODY [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--body <body>

--created-at <created_at>

gitlab project-issue-note delete

```
usage: gitlab project-issue-note delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --issue-iid ISSUE_IID --id
                                         ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-note get

```
usage: gitlab project-issue-note get [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --issue-iid ISSUE_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-note list

```
usage: gitlab project-issue-note list [-h] [--sudo SUDO] --project-id
                                       PROJECT_ID --issue-iid ISSUE_IID
                                       [--page PAGE] [--per-page PER_PAGE]
                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issue-note update

```
usage: gitlab project-issue-note update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --issue-iid ISSUE_IID --id
                                         ID --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--issue-iid <issue_iid>****--id <id>****--body <body>****gitlab project-issue-note-award-emoji**

```
usage: gitlab project-issue-note-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-issue-note-award-emoji create

```
usage: gitlab project-issue-note-award-emoji create [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --note-id NOTE_ID --name
                                                 NAME
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--issue-iid <issue_iid>****--note-id <note_id>****--name <name>**

gitlab project-issue-note-award-emoji delete

```
usage: gitlab project-issue-note-award-emoji delete [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --note-id NOTE_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--note-id <note_id>

--id <id>

gitlab project-issue-note-award-emoji get

```
usage: gitlab project-issue-note-award-emoji get [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --note-id NOTE_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--note-id <note_id>

--id <id>

gitlab project-issue-note-award-emoji list

```
usage: gitlab project-issue-note-award-emoji list [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --note-id NOTE_ID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--note-id <note_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-issue-resource-iteration-event

```
usage: gitlab project-issue-resource-iteration-event [-h] {list,get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-issue-resource-iteration-event get

```
usage: gitlab project-issue-resource-iteration-event get [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID
                                                       --issue-iid ISSUE_IID
                                                       --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--id <id>
```

gitlab project-issue-resource-iteration-event list

```
usage: gitlab project-issue-resource-iteration-event list [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID
                                                       --issue-iid
                                                       ISSUE_IID
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issue-resource-label-event

```
usage: gitlab project-issue-resource-label-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-issue-resource-label-event get

```
usage: gitlab project-issue-resource-label-event get [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-resource-label-event list

```
usage: gitlab project-issue-resource-label-event list [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --issue-iid ISSUE_IID
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--issue-iid <issue_iid>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issue-resource-milestone-event

```
usage: gitlab project-issue-resource-milestone-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-issue-resource-milestone-event get

```
usage: gitlab project-issue-resource-milestone-event get [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID
                                                       --issue-iid ISSUE_IID
                                                       --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--issue-iid <issue_iid>****--id <id>**

gitlab project-issue-resource-milestone-event list

```
usage: gitlab project-issue-resource-milestone-event list [-h] [--sudo SUDO]
                           --project-id
                           PROJECT_ID
                           --issue-iid
                           ISSUE_IID
                           [--page PAGE]
                           [--per-page PER_PAGE]
                           [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab project-issue-resource-state-event

```
usage: gitlab project-issue-resource-state-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-issue-resource-state-event get

```
usage: gitlab project-issue-resource-state-event get [-h] [--sudo SUDO]
                           --project-id PROJECT_ID
                           --issue-iid ISSUE_IID
                           --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-resource-state-event list

```
usage: gitlab project-issue-resource-state-event list [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --issue-iid ISSUE_IID
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issue-resource-weight-event

```
usage: gitlab project-issue-resource-weight-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-issue-resource-weight-event get

```
usage: gitlab project-issue-resource-weight-event get [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --issue-iid ISSUE_IID
                                                       --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-resource-weight-event list

```
usage: gitlab project-issue-resource-weight-event list [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --issue-iid ISSUE_IID
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issues-statistics

```
usage: gitlab project-issues-statistics [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-issues-statistics get

```
usage: gitlab project-issues-statistics get [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-job

```
usage: gitlab project-job [-h]
  list
  get
  cancel
  retry
  play
  erase
  keep-artifacts
  delete-artifacts
  artifacts
  artifact
  trace
  ...
  ...
```

-h, --help

show this help message and exit

gitlab project-job artifact

```
usage: gitlab project-job artifact [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job artifacts

```
usage: gitlab project-job artifacts [-h] --project-id PROJECT_ID [--sudo SUDO]
                                    --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job cancel

```
usage: gitlab project-job cancel [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job delete-artifacts

```
usage: gitlab project-job delete-artifacts [-h] --project-id PROJECT_ID
                                            [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job erase

```
usage: gitlab project-job erase [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job get

```
usage: gitlab project-job get [-h] [--sudo SUDO] --project-id PROJECT_ID --id
                               ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>  
--id <id>
```

gitlab project-job keep-artifacts

```
usage: gitlab project-job keep-artifacts [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --id ID
```

```
-h, --help  
    show this help message and exit  
--project-id <project_id>  
--sudo <sudo>  
--id <id>
```

gitlab project-job list

```
usage: gitlab project-job list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                               [--scope SCOPE] [--page PAGE]  
                               [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>  
--scope <scope>  
--page <page>  
--per-page <per_page>  
--get-all  
    Return all items from the server, without pagination.  
--all  
    Deprecated. Use --get-all instead.
```

gitlab project-job play

```
usage: gitlab project-job play [-h] --project-id PROJECT_ID [--sudo SUDO] --id  
                                ID
```

```
-h, --help  
    show this help message and exit  
--project-id <project_id>
```

```
--sudo <sudo>
--id <id>
```

gitlab project-job retry

```
usage: gitlab project-job retry [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --id ID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>
```

gitlab project-job trace

```
usage: gitlab project-job trace [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --id ID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>
```

gitlab project-key

```
usage: gitlab project-key [-h] {list,get,create,update,delete,enable} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-key create

```
usage: gitlab project-key create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --title TITLE --key KEY [--can-push CAN_PUSH]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
```

```
--title <title>
--key <key>
--can-push <can_push>
```

gitlab project-key delete

```
usage: gitlab project-key delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-key enable

```
usage: gitlab project-key enable [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --id ID --key-id KEY_ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--key-id <key_id>

gitlab project-key get

```
usage: gitlab project-key get [-h] [--sudo SUDO] --project-id PROJECT_ID --id
                               ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-key list

```
usage: gitlab project-key list [-h] [--sudo SUDO] --project-id PROJECT_ID
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]
                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab project-key update

```
usage: gitlab project-key update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --id ID [--title TITLE] [--can-push CAN_PUSH]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--title <title>

--can-push <can_push>

gitlab project-label

```
usage: gitlab project-label [-h]
    list
    get
    create
    update
    delete
    subscribe
    unsubscribe
    ...
```

-h, --help

show this help message and exit

gitlab project-label create

```
usage: gitlab project-label create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --name NAME --color COLOR
                                  [--description DESCRIPTION]
                                  [--priority PRIORITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--color <color>

--description <description>

--priority <priority>

gitlab project-label delete

```
usage: gitlab project-label delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-label get

```
usage: gitlab project-label get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-label list

```
usage: gitlab project-label list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 [--page PAGE] [--per-page PER_PAGE]
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-label subscribe

```
usage: gitlab project-label subscribe [-h] --project-id PROJECT_ID
                                      [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--name <name>

gitlab project-label unsubscribe

```
usage: gitlab project-label unsubscribe [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--name <name>

gitlab project-label update

```
usage: gitlab project-label update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --name NAME [--new-name NEW_NAME]
                                  [--color COLOR] [--description DESCRIPTION]
                                  [--priority PRIORITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--new-name <new_name>

--color <color>

--description <description>

--priority <priority>

gitlab project-member

```
usage: gitlab project-member [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-member create

```
usage: gitlab project-member create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                    --access-level ACCESS_LEVEL --user-id
                                    USER_ID [--expires-at EXPIRES_AT]
                                    [--tasks-to-be-done TASKS_TO_BE_DONE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--access-level <access_level>

--user-id <user_id>

--expires-at <expires_at>

--tasks-to-be-done <tasks_to_be_done>

gitlab project-member delete

```
usage: gitlab project-member delete [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-member get

```
usage: gitlab project-member get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-member list

```
usage: gitlab project-member list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   [--page PAGE] [--per-page PER_PAGE]  
                                   [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-member update

```
usage: gitlab project-member update [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  --id ID --access-level ACCESS_LEVEL  
                                  [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--access-level <access_level>

--expires-at <expires_at>

gitlab project-member-all

```
usage: gitlab project-member-all [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-member-all get

```
usage: gitlab project-member-all get [-h] [--sudo SUDO] --project-id  
                                     PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-member-all list

```
usage: gitlab project-member-all list [-h] [--sudo SUDO] --project-id  
                                      PROJECT_ID [--page PAGE]  
                                      [--per-page PER_PAGE] [--get-all]  
                                      [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-merge-request

```
usage: gitlab project-merge-request [-h]
    list
    get
    create
    update
    delete
    subscribe
    unsubscribe
    todo
    time-stats
    time-estimate
    reset-time-estimate
    add-spent-time
    reset-spent-time
    participants
    cancel-merge-when-pipeline-succeeds
    closes-issues
    commits
    changes
    approve
    unapprove
    rebase
    reset-approvals
    merge-ref
    merge
    ...
```

-h, --help

show this help message and exit

gitlab project-merge-request add-spent-time

```
usage: gitlab project-merge-request add-spent-time [-h] --project-id  
                                                PROJECT_ID [--sudo SUDO]  
                                                --iid IID --duration  
                                                DURATION
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--duration <duration>

gitlab project-merge-request approve

```
usage: gitlab project-merge-request approve [-h] --project-id PROJECT_ID  
                                              [--sudo SUDO] --iid IID  
                                              [--sha SHA]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--sha <sha>

gitlab project-merge-request cancel-merge-when-pipeline-succeeds

```
usage: gitlab project-merge-request cancel-merge-when-pipeline-succeeds  
      [-h] --project-id PROJECT_ID [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request changes

```
usage: gitlab project-merge-request changes [-h] --project-id PROJECT_ID
                                            [--sudo SUDO] --iid IID
                                            [--access-raw-diffs ACCESS_RAW_DIFFS]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--access-raw-diffs <access_raw_diffs>

gitlab project-merge-request closes-issues

```
usage: gitlab project-merge-request closes-issues [-h] --project-id PROJECT_ID
                                                 [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request commits

```
usage: gitlab project-merge-request commits [-h] --project-id PROJECT_ID
                                             [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request create

```
usage: gitlab project-merge-request create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --source-branch
                                         SOURCE_BRANCH --target-branch
                                         TARGET_BRANCH --title TITLE
                                         [--allow-collaboration ALLOW_COLLABORATION]
                                         [--allow-maintainer-to-push ALLOW_MAINTAINER_
                                         ↵TO_PUSH]
                                         [--approvals-before-merge APPROVALS_BEFORE_
                                         ↵MERGE]
                                         [--assignee-id ASSIGNEE_ID]
                                         [--assignee-ids ASSIGNEE_IDS]
                                         [--description DESCRIPTION]
                                         [--labels LABELS]
                                         [--milestone-id MILESTONE_ID]
                                         [--remove-source-branch REMOVE_SOURCE_BRANCH]
                                         [--reviewer-ids REVIEWER_IDS]
                                         [--squash SQUASH]
                                         [--target-project-id TARGET_PROJECT_ID]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--source-branch <source_branch>****--target-branch <target_branch>****--title <title>****--allow-collaboration <allow_collaboration>****--allow-maintainer-to-push <allow_maintainer_to_push>****--approvals-before-merge <approvals_before_merge>****--assignee-id <assignee_id>****--assignee-ids <assignee_ids>****--description <description>****--labels <labels>****--milestone-id <milestone_id>****--remove-source-branch <remove_source_branch>****--reviewer-ids <reviewer_ids>****--squash <squash>****--target-project-id <target_project_id>**

gitlab project-merge-request delete

```
usage: gitlab project-merge-request delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --iid IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iid <iid>

gitlab project-merge-request get

```
usage: gitlab project-merge-request get [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --iid IID  
                                         [--render-html RENDER_HTML]  
                                         [--include-diverged-commits-count INCLUDE_  
                                         ↵DIVERGED_COMMITS_COUNT]  
                                         [--include-rebase-in-progress INCLUDE_REBASE_IN_  
                                         ↵PROGRESS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iid <iid>

--render-html <render_html>

--include-diverged-commits-count <include_diverged_commits_count>

--include-rebase-in-progress <include_rebase_in_progress>

gitlab project-merge-request list

```
usage: gitlab project-merge-request list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID [--state STATE]  
                                         [--order-by ORDER_BY] [--sort SORT]  
                                         [--milestone MILESTONE] [--view VIEW]  
                                         [--labels LABELS]  
                                         [--created-after CREATED_AFTER]  
                                         [--created-before CREATED_BEFORE]  
                                         [--updated-after UPDATED_AFTER]  
                                         [--updated-before UPDATED_BEFORE]  
                                         [--scope SCOPE] [-iids IIDS]  
                                         [--author-id AUTHOR_ID]  
                                         [--assignee-id ASSIGNEE_ID]
```

(continues on next page)

(continued from previous page)

```
[--approver-ids APPROVER_IDS]
[--approved-by-ids APPROVED_BY_IDS]
[--my-reaction-emoji MY_REACTION_EMOJI]
[--source-branch SOURCE_BRANCH]
[--target-branch TARGET_BRANCH]
[--search SEARCH] [--wip WIP]
[--page PAGE] [--per-page PER_PAGE]
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--state <state>****--order-by <order_by>****--sort <sort>****--milestone <milestone>****--view <view>****--labels <labels>****--created-after <created_after>****--created-before <created_before>****--updated-after <updated_after>****--updated-before <updated_before>****--scope <scope>****--iids <iids>****--author-id <author_id>****--assignee-id <assignee_id>****--approver-ids <approver_ids>****--approved-by-ids <approved_by_ids>****--my-reaction-emoji <my_reaction_emoji>****--source-branch <source_branch>****--target-branch <target_branch>****--search <search>****--wip <wip>**

```
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-merge-request merge

```
usage: gitlab project-merge-request merge [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --iid IID
                                         [--merge-commit-message MERGE_COMMIT_MESSAGE]
                                         [--should-remove-source-branch SHOULD_REMOVE_
                                         ↵SOURCE_BRANCH]
                                         [--merge-when-pipeline-succeeds MERGE_WHEN_
                                         ↵PIPELINE_SUCCEEDS]
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
--merge-commit-message <merge_commit_message>
--should-remove-source-branch <should_remove_source_branch>
--merge-when-pipeline-succeeds <merge_when_pipeline_succeeds>
```

gitlab project-merge-request merge-ref

```
usage: gitlab project-merge-request merge-ref [-h] --project-id PROJECT_ID
                                              [--sudo SUDO] --iid IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-merge-request participants

```
usage: gitlab project-merge-request participants [-h] --project-id PROJECT_ID  
                                                [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request rebase

```
usage: gitlab project-merge-request rebase [-h] --project-id PROJECT_ID  
                                            [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request reset-approvals

```
usage: gitlab project-merge-request reset-approvals [-h] --project-id  
                                                 PROJECT_ID [--sudo SUDO]  
                                                 --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request reset-spent-time

```
usage: gitlab project-merge-request reset-spent-time [-h] --project-id  
                                                 PROJECT_ID [--sudo SUDO]  
                                                 --iid IID
```

-h, --help

show this help message and exit

```
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-merge-request reset-time-estimate

```
usage: gitlab project-merge-request reset-time-estimate [-h] --project-id
                                                       PROJECT_ID
                                                       [--sudo SUDO] --iid
                                                       IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-merge-request subscribe

```
usage: gitlab project-merge-request subscribe [-h] --project-id PROJECT_ID
                                               [--sudo SUDO] --iid IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-merge-request time-estimate

```
usage: gitlab project-merge-request time-estimate [-h] --project-id PROJECT_ID
                                                   [--sudo SUDO] --iid IID
                                                   --duration DURATION
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
--duration <duration>
```

gitlab project-merge-request time-stats

```
usage: gitlab project-merge-request time-stats [-h] --project-id PROJECT_ID  
                                              [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request todo

```
usage: gitlab project-merge-request todo [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request unapprove

```
usage: gitlab project-merge-request unapprove [-h] --project-id PROJECT_ID  
                                              [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request unsubscribe

```
usage: gitlab project-merge-request unsubscribe [-h] --project-id PROJECT_ID  
                                                 [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

```
--sudo <sudo>  
--iid <iid>
```

gitlab project-merge-request update

```
usage: gitlab project-merge-request update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --iid IID  
[--target-branch TARGET_BRANCH]  
[--assignee-id ASSIGNEE_ID]  
[--title TITLE]  
[--description DESCRIPTION]  
[--state-event STATE_EVENT]  
[--labels LABELS]  
[--milestone-id MILESTONE_ID]  
[--remove-source-branch REMOVE_SOURCE_BRANCH]  
[--discussion-locked DISCUSSION_LOCKED]  
[--allow-maintainer-to-push ALLOW_MAINTAINER_  
→ TO_PUSH]  
[--squash SQUASH]  
[--reviewer-ids REVIEWER_IDS]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--iid <iid>
```

```
--target-branch <target_branch>
```

```
--assignee-id <assignee_id>
```

```
--title <title>
```

```
--description <description>
```

```
--state-event <state_event>
```

```
--labels <labels>
```

```
--milestone-id <milestone_id>
```

```
--remove-source-branch <remove_source_branch>
```

```
--discussion-locked <discussion_locked>
```

```
--allow-maintainer-to-push <allow_maintainer_to_push>
```

```
--squash <squash>
```

```
--reviewer-ids <reviewer_ids>
```

gitlab project-merge-request-approval

```
usage: gitlab project-merge-request-approval [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-approval get

```
usage: gitlab project-merge-request-approval get [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --mr-iid MR_IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

gitlab project-merge-request-approval update

```
usage: gitlab project-merge-request-approval update [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID
                                                    --approvals-required
                                                    APPROVALS_REQUIRED
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--approvals-required <approvals_required>

gitlab project-merge-request-approval-rule

```
usage: gitlab project-merge-request-approval-rule [-h]
  list
  get
  create
  update
  delete
  ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-approval-rule create

```
usage: gitlab project-merge-request-approval-rule create [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID --id ID
                                                       --merge-request-iid
                                                       MERGE_REQUEST_IID
                                                       --name NAME
                                                       --approvals-required
                                                       APPROVALS_REQUIRED
                                                       [--approval-project-rule-id,
                                                       APPROVAL_PROJECT_RULE_ID]
                                                       [--user-ids USER_IDS]
                                                       [--group-ids GROUP_IDS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

--merge-request-iid <merge_request_iid>

--name <name>

--approvals-required <approvals_required>

--approval-project-rule-id <approval_project_rule_id>

--user-ids <user_ids>

--group-ids <group_ids>

gitlab project-merge-request-approval-rule delete

```
usage: gitlab project-merge-request-approval-rule delete [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--mr-iid <mr_iid>
--id <id>
```

gitlab project-merge-request-approval-rule get

```
usage: gitlab project-merge-request-approval-rule get [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--mr-iid <mr_iid>
```

```
--id <id>
```

gitlab project-merge-request-approval-rule list

```
usage: gitlab project-merge-request-approval-rule list [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--mr-iid <mr_iid>
```

```
--page <page>
```

```
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-approval-rule update

```
usage: gitlab project-merge-request-approval-rule update [-h] [--sudo SUDO]
                           --project-id
                           PROJECT_ID --mr-iid
                           MR_IID --id ID
                           --merge-request-iid
                           MERGE_REQUEST_IID
                           --approval-rule-id
                           APPROVAL_RULE_ID
                           --name NAME
                           --approvals-required
                           APPROVALS_REQUIRED
                           [--user-ids USER_IDS]
                           [--group-ids GROUP_IDS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

--merge-request-iid <merge_request_iid>

--approval-rule-id <approval_rule_id>

--name <name>

--approvals-required <approvals_required>

--user-ids <user_ids>

--group-ids <group_ids>

gitlab project-merge-request-approval-state

```
usage: gitlab project-merge-request-approval-state [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-approval-state get

```
usage: gitlab project-merge-request-approval-state get [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-award-emoji

```
usage: gitlab project-merge-request-award-emoji [-h]
                                              list
                                              get
                                              create
                                              delete} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-award-emoji create

```
usage: gitlab project-merge-request-award-emoji create [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --name
                                                       NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--name <name>

gitlab project-merge-request-award-emoji delete

```
usage: gitlab project-merge-request-award-emoji delete [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-award-emoji get

```
usage: gitlab project-merge-request-award-emoji get [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-award-emoji list

```
usage: gitlab project-merge-request-award-emoji list [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

```
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-merge-request-diff

```
usage: gitlab project-merge-request-diff [-h] {list,get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-merge-request-diff get

```
usage: gitlab project-merge-request-diff get [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --mr-iid MR_IID --id
                                              ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--id <id>
```

gitlab project-merge-request-diff list

```
usage: gitlab project-merge-request-diff list [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --mr-iid MR_IID
                                               [--page PAGE]
                                               [--per-page PER_PAGE]
                                               [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--page <page>
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-discussion

```
usage: gitlab project-merge-request-discussion [-h]
  list
  get
  create
  update} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-discussion create

```
usage: gitlab project-merge-request-discussion create [-h] [--sudo SUDO]
                                                      --project-id PROJECT_ID
                                                      --mr-iid MR_IID --body
                                                      BODY
                                                      [--created-at CREATED_AT]
                                                      [--position POSITION]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--body <body>

--created-at <created_at>

--position <position>

gitlab project-merge-request-discussion get

```
usage: gitlab project-merge-request-discussion get [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--mr-iid <mr_iid>
--id <id>
```

gitlab project-merge-request-discussion list

```
usage: gitlab project-merge-request-discussion list [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-discussion update

```
usage: gitlab project-merge-request-discussion update [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --id ID
                                                       --resolved RESOLVED
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

--resolved <resolved>

gitlab project-merge-request-discussion-note

```
usage: gitlab project-merge-request-discussion-note [-h]
  get
  create
  update
  delete
  ...
  ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-discussion-note create

```
usage: gitlab project-merge-request-discussion-note create [-h] [--sudo SUDO]
  --project-id
  PROJECT_ID --mr-iid
  MR_IID
  --discussion-id
  DISCUSSION_ID
  --body BODY
  [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--discussion-id <discussion_id>

--body <body>

--created-at <created_at>

gitlab project-merge-request-discussion-note delete

```
usage: gitlab project-merge-request-discussion-note delete [-h] [--sudo SUDO]
  --project-id
  PROJECT_ID --mr-iid
  MR_IID
  --discussion-id
  DISCUSSION_ID --id
  ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--mr-iid <mr_iid>
--discussion-id <discussion_id>
--id <id>
```

gitlab project-merge-request-discussion-note get

```
usage: gitlab project-merge-request-discussion-note get [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID --discussion-id
                                                       DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--discussion-id <discussion_id>

--id <id>

gitlab project-merge-request-discussion-note update

```
usage: gitlab project-merge-request-discussion-note update [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID
                                                       --discussion-id
                                                       DISCUSSION_ID --id
                                                       ID --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--discussion-id <discussion_id>

--id <id>

--body <body>

gitlab project-merge-request-note

```
usage: gitlab project-merge-request-note [-h]
  list
  get
  create
  update
  delete} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-note create

```
usage: gitlab project-merge-request-note create [-h] [--sudo SUDO]
                                               --project-id PROJECT_ID
                                               --mr-iid MR_IID --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--body <body>

gitlab project-merge-request-note delete

```
usage: gitlab project-merge-request-note delete [-h] [--sudo SUDO]
                                               --project-id PROJECT_ID
                                               --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-note get

```
usage: gitlab project-merge-request-note get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --mr-iid MR_IID --id  
ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-note list

```
usage: gitlab project-merge-request-note list [-h] [--sudo SUDO] --project-id  
PROJECT_ID --mr-iid MR_IID  
[--page PAGE]  
[--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-note update

```
usage: gitlab project-merge-request-note update [-h] [--sudo SUDO]  
--project-id PROJECT_ID  
--mr-iid MR_IID --id ID --body  
BODY
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--id <id>
--body <body>
```

gitlab project-merge-request-note-award-emoji

```
usage: gitlab project-merge-request-note-award-emoji [-h]
    list
    get
    create
    delete
    ...
    ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-note-award-emoji create

```
usage: gitlab project-merge-request-note-award-emoji create
    [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --note-id
    NOTE_ID --name NAME
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--note-id <note_id>
--name <name>
```

gitlab project-merge-request-note-award-emoji delete

```
usage: gitlab project-merge-request-note-award-emoji delete
    [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --note-id
    NOTE_ID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
--mr-iid <mr_iid>
--note-id <note_id>
--id <id>
```

gitlab project-merge-request-note-award-emoji get

```
usage: gitlab project-merge-request-note-award-emoji get [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID --note-id
                                                       NOTE_ID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--mr-iid <mr_iid>
```

```
--note-id <note_id>
```

```
--id <id>
```

gitlab project-merge-request-note-award-emoji list

```
usage: gitlab project-merge-request-note-award-emoji list [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID --note-id
                                                       NOTE_ID
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--mr-iid <mr_iid>
```

```
--note-id <note_id>
```

```
--page <page>
```

```
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-pipeline

```
usage: gitlab project-merge-request-pipeline [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-pipeline create

```
usage: gitlab project-merge-request-pipeline create [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

gitlab project-merge-request-pipeline list

```
usage: gitlab project-merge-request-pipeline list [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-resource-label-event

```
usage: gitlab project-merge-request-resource-label-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-resource-label-event get

```
usage: gitlab project-merge-request-resource-label-event get
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--mr-iid <mr_iid>****--id <id>****gitlab project-merge-request-resource-label-event list**

```
usage: gitlab project-merge-request-resource-label-event list
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID
      [--page PAGE] [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--mr-iid <mr_iid>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-resource-milestone-event

```
usage: gitlab project-merge-request-resource-milestone-event
      [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-resource-milestone-event get

```
usage: gitlab project-merge-request-resource-milestone-event get
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-resource-milestone-event list

```
usage: gitlab project-merge-request-resource-milestone-event list
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID
      [--page PAGE] [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-resource-state-event

```
usage: gitlab project-merge-request-resource-state-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-resource-state-event get

```
usage: gitlab project-merge-request-resource-state-event get
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-resource-state-event list

```
usage: gitlab project-merge-request-resource-state-event list
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID
      [--page PAGE] [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-train

```
usage: gitlab project-merge-train [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-merge-train list

```
usage: gitlab project-merge-train list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--scope SCOPE]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--scope <scope>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-milestone

```
usage: gitlab project-milestone [-h]
    list
    get
    create
    update
    delete
    issues
    merge-requests
    ...

```

-h, --help

show this help message and exit

gitlab project-milestone create

```
usage: gitlab project-milestone create [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --title TITLE
                                      [--description DESCRIPTION]
                                      [--due-date DUE_DATE]
                                      [--start-date START_DATE]
                                      [--state-event STATE_EVENT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--title <title>

--description <description>

--due-date <due_date>

--start-date <start_date>

--state-event <state_event>

gitlab project-milestone delete

```
usage: gitlab project-milestone delete [-h] [--sudo SUDO] --project-id
                                       PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-milestone get

```
usage: gitlab project-milestone get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                    --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-milestone issues

```
usage: gitlab project-milestone issues [-h] --project-id PROJECT_ID  
                                     [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-milestone list

```
usage: gitlab project-milestone list [-h] [--sudo SUDO] --project-id  
                                     PROJECT_ID [--iids IIDS] [--state STATE]  
                                     [--search SEARCH] [--page PAGE]  
                                     [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iids <iids>

--state <state>

--search <search>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-milestone merge-requests

```
usage: gitlab project-milestone merge-requests [-h] --project-id PROJECT_ID  
                                              [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

```
--sudo <sudo>  
--id <id>
```

gitlab project-milestone update

```
usage: gitlab project-milestone update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID [--title TITLE]  
[--description DESCRIPTION]  
[--due-date DUE_DATE]  
[--start-date START_DATE]  
[--state-event STATE_EVENT]
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>  
--id <id>  
--title <title>  
--description <description>  
--due-date <due_date>  
--start-date <start_date>  
--state-event <state_event>
```

gitlab project-note

```
usage: gitlab project-note [-h] {list,get} ...
```

```
-h, --help  
    show this help message and exit
```

gitlab project-note get

```
usage: gitlab project-note get [-h] [--sudo SUDO] --project-id PROJECT_ID --id  
ID
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>  
--id <id>
```

gitlab project-note list

```
usage: gitlab project-note list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--page PAGE] [--per-page PER_PAGE]
                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-notification-settings

```
usage: gitlab project-notification-settings [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab project-notification-settings get

```
usage: gitlab project-notification-settings get [-h] [--sudo SUDO]
                                               --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-notification-settings update

```
usage: gitlab project-notification-settings update [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 [--level LEVEL]
                                                 [--notification-email NOTIFICATION_
                                                 ↪EMAIL]
                                                 [--new-note NEW_NOTE]
                                                 [--new-issue NEW_ISSUE]
```

(continues on next page)

(continued from previous page)

↳REQUEST]	[--reopen-issue REOPEN_ISSUE] [--close-issue CLOSE_ISSUE] [--reassign-issue REASSIGN_ISSUE] [--new-merge-request NEW_MERGE_
↳REQUEST]	[--reopen-merge-request REOPEN_MERGE_
↳REQUEST]	[--close-merge-request CLOSE_MERGE_
↳MERGE_REQUEST]	[--reassign-merge-request REASSIGN_
↳REQUEST]	[--merge-merge-request MERGE_MERGE_

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--level <level>****--notification-email <notification_email>****--new-note <new_note>****--new-issue <new_issue>****--reopen-issue <reopen_issue>****--close-issue <close_issue>****--reassign-issue <reassign_issue>****--new-merge-request <new_merge_request>****--reopen-merge-request <reopen_merge_request>****--close-merge-request <close_merge_request>****--reassign-merge-request <reassign_merge_request>****--merge-merge-request <merge_merge_request>****gitlab project-package**

usage: gitlab project-package [-h] {list,get,delete} ...

-h, --help

show this help message and exit

gitlab project-package delete

```
usage: gitlab project-package delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-package get

```
usage: gitlab project-package get [-h] [--sudo SUDO] --project-id PROJECT_ID  
--id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-package list

```
usage: gitlab project-package list [-h] [--sudo SUDO] --project-id PROJECT_ID  
[--order-by ORDER_BY] [--sort SORT]  
[--package-type PACKAGE_TYPE]  
[--package-name PACKAGE_NAME] [--page PAGE]  
[--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--order-by <order_by>

--sort <sort>

--package-type <package_type>

--package-name <package_name>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-package-file

```
usage: gitlab project-package-file [-h] {list,delete} ...
```

-h, --help

show this help message and exit

gitlab project-package-file delete

```
usage: gitlab project-package-file delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --package-id PACKAGE_ID  
                                         --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--package-id <package_id>****--id <id>****gitlab project-package-file list**

```
usage: gitlab project-package-file list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --package-id PACKAGE_ID  
                                         [--page PAGE] [--per-page PER_PAGE]  
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--package-id <package_id>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use `--get-all` instead.

gitlab project-pages-domain

```
usage: gitlab project-pages-domain [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-pages-domain create

```
usage: gitlab project-pages-domain create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --domain DOMAIN
                                         [--certificate CERTIFICATE]
                                         [--key KEY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--domain <domain>

--certificate <certificate>

--key <key>

gitlab project-pages-domain delete

```
usage: gitlab project-pages-domain delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --domain DOMAIN
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--domain <domain>

gitlab project-pages-domain get

```
usage: gitlab project-pages-domain get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --domain DOMAIN
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--domain <domain>

gitlab project-pages-domain list

```
usage: gitlab project-pages-domain list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-pages-domain update

```
usage: gitlab project-pages-domain update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --domain DOMAIN  
[--certificate CERTIFICATE]  
[--key KEY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--domain <domain>

```
--certificate <certificate>
--key <key>
```

gitlab project-pipeline

```
usage: gitlab project-pipeline [-h] {list,get,create,delete,cancel,retry} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline cancel

```
usage: gitlab project-pipeline cancel [-h] --project-id PROJECT_ID
                                     [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-pipeline create

```
usage: gitlab project-pipeline create [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --ref REF
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--ref <ref>

gitlab project-pipeline delete

```
usage: gitlab project-pipeline delete [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-pipeline get

```
usage: gitlab project-pipeline get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-pipeline list

```
usage: gitlab project-pipeline list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                    [--scope SCOPE] [--status STATUS]  
                                    [--source SOURCE] [--ref REF] [--sha SHA]  
                                    [--yaml-errors YAML_ERRORS] [--name NAME]  
                                    [--username USERNAME]  
                                    [--order-by ORDER_BY] [--sort SORT]  
                                    [--page PAGE] [--per-page PER_PAGE]  
                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--scope <scope>

--status <status>

--source <source>

--ref <ref>

--sha <sha>

--yaml-errors <yaml_errors>

--name <name>

--username <username>

--order-by <order_by>

--sort <sort>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-pipeline retry

```
usage: gitlab project-pipeline retry [-h] --project-id PROJECT_ID  
[--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-pipeline-bridge

```
usage: gitlab project-pipeline-bridge [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-bridge list

```
usage: gitlab project-pipeline-bridge list [-h] [--sudo SUDO] --project-id  
PROJECT_ID --pipeline-id  
PIPELINE_ID [--scope SCOPE]  
[--page PAGE] [--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-id <pipeline_id>

--scope <scope>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-pipeline-job

```
usage: gitlab project-pipeline-job [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-job list

```
usage: gitlab project-pipeline-job list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --pipeline-id PIPELINE_ID
                                         [--scope SCOPE]
                                         [--include-retried INCLUDE_RETRIED]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--pipeline-id <pipeline_id>****--scope <scope>****--include-retried <include_retried>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-pipeline-schedule

```
usage: gitlab project-pipeline-schedule [-h]
  list
  get
  create
  update
  delete
  take-ownership
  play
  ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-schedule create

```
usage: gitlab project-pipeline-schedule create [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --description
                                               DESCRIPTION --ref REF --cron
                                               CRON
                                               [--cron-timezone CRON_TIMEZONE]
                                               [--active ACTIVE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--description <description>

--ref <ref>

--cron <cron>

--cron-timezone <cron_timezone>

--active <active>

gitlab project-pipeline-schedule delete

```
usage: gitlab project-pipeline-schedule delete [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-pipeline-schedule get

```
usage: gitlab project-pipeline-schedule get [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>  
--id <id>
```

gitlab project-pipeline-schedule list

```
usage: gitlab project-pipeline-schedule list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all
Return all items from the server, without pagination.

--all
Deprecated. Use --get-all instead.

gitlab project-pipeline-schedule play

```
usage: gitlab project-pipeline-schedule play [-h] --project-id PROJECT_ID  
[--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-pipeline-schedule take-ownership

```
usage: gitlab project-pipeline-schedule take-ownership [-h] --project-id  
PROJECT_ID  
[--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

```
--sudo <sudo>
--id <id>
```

gitlab project-pipeline-schedule update

```
usage: gitlab project-pipeline-schedule update [-h] [--sudo SUDO] --project-id
PROJECT_ID --id ID
[--description DESCRIPTION]
[--ref REF] [--cron CRON]
[--cron-timezone CRON_TIMEZONE]
[--active ACTIVE]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--id <id>
```

```
--description <description>
```

```
--ref <ref>
```

```
--cron <cron>
```

```
--cron-timezone <cron_timezone>
```

```
--active <active>
```

gitlab project-pipeline-schedule-pipeline

```
usage: gitlab project-pipeline-schedule-pipeline [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-schedule-pipeline list

```
usage: gitlab project-pipeline-schedule-pipeline list [-h] [--sudo SUDO]
--project-id PROJECT_ID
--pipeline-schedule-id PIPELINE_SCHEDULE_ID
[--page PAGE]
[--per-page PER_PAGE]
[--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--pipeline-schedule-id <pipeline_schedule_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-pipeline-schedule-variable

```
usage: gitlab project-pipeline-schedule-variable [-h]
        create
        update
        delete} ...
```

-h, --help
show this help message and exit

gitlab project-pipeline-schedule-variable create

```
usage: gitlab project-pipeline-schedule-variable create [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID
                                                       --pipeline-schedule-id
                                                       PIPELINE_SCHEDULE_ID
                                                       --key KEY --value
                                                       VALUE
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--pipeline-schedule-id <pipeline_schedule_id>
--key <key>
--value <value>
```

gitlab project-pipeline-schedule-variable delete

```
usage: gitlab project-pipeline-schedule-variable delete [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID
                                                       --pipeline-schedule-id
                                                       PIPELINE_SCHEDULE_ID
                                                       --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-schedule-id <pipeline_schedule_id>

--key <key>

gitlab project-pipeline-schedule-variable update

```
usage: gitlab project-pipeline-schedule-variable update [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID
                                                       --pipeline-schedule-id
                                                       PIPELINE_SCHEDULE_ID
                                                       --key KEY --value
                                                       VALUE
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-schedule-id <pipeline_schedule_id>

--key <key>

--value <value>

gitlab project-pipeline-test-report

```
usage: gitlab project-pipeline-test-report [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-test-report get

```
usage: gitlab project-pipeline-test-report get [-h] [--sudo SUDO] --project-id  
                                              PROJECT_ID --pipeline-id  
                                              PIPELINE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-id <pipeline_id>

gitlab project-pipeline-test-report-summary

```
usage: gitlab project-pipeline-test-report-summary [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-test-report-summary get

```
usage: gitlab project-pipeline-test-report-summary get [-h] [--sudo SUDO]  
                                              --project-id PROJECT_ID  
                                              --pipeline-id  
                                              PIPELINE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-id <pipeline_id>

gitlab project-pipeline-variable

```
usage: gitlab project-pipeline-variable [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-variable list

```
usage: gitlab project-pipeline-variable list [-h] [--sudo SUDO] --project-id  
PROJECT_ID --pipeline-id  
PIPELINE_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-id <pipeline_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-protected-branch

```
usage: gitlab project-protected-branch [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-protected-branch create

```
usage: gitlab project-protected-branch create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --name NAME  
[--push-access-level PUSH_ACCESS_LEVEL]  
[--merge-access-level MERGE_ACCESS_LEVEL]  
[--unprotect-access-level UNPROTECT_ACCESS_  
LEVEL]  
[--allow-force-push ALLOW_FORCE_PUSH]  
[--allowed-to-push ALLOWED_TO_PUSH]  
[--allowed-to-merge ALLOWED_TO_MERGE]  
[--allowed-to-unprotect ALLOWED_TO_  
UNPROTECT]  
[--code-owner-approval-required CODE_OWNER_  
APPROVAL_REQUIRED]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--name <name>
--push-access-level <push_access_level>
--merge-access-level <merge_access_level>
--unprotect-access-level <unprotect_access_level>
--allow-force-push <allow_force_push>
--allowed-to-push <allowed_to_push>
--allowed-to-merge <allowed_to_merge>
--allowed-to-unprotect <allowed_to_unprotect>
--code-owner-approval-required <code_owner_approval_required>
```

gitlab project-protected-branch delete

```
usage: gitlab project-protected-branch delete [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-protected-branch get

```
usage: gitlab project-protected-branch get [-h] [--sudo SUDO] --project-id
                                            PROJECT_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-protected-branch list

```
usage: gitlab project-protected-branch list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-protected-environment

```
usage: gitlab project-protected-environment [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-protected-environment create

```
usage: gitlab project-protected-environment create [-h] [--sudo SUDO]  
--project-id PROJECT_ID  
--name NAME  
--deploy-access-levels  
DEPLOY_ACCESS_LEVELS  
[--required-approval-count REQUIRED_  
APPROVAL_COUNT]  
[--approval-rules APPROVAL_RULES]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--deploy-access-levels <deploy_access_levels>

```
--required-approval-count <required_approval_count>
--approval-rules <approval_rules>
```

gitlab project-protected-environment delete

```
usage: gitlab project-protected-environment delete [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --name NAME
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--name <name>
```

gitlab project-protected-environment get

```
usage: gitlab project-protected-environment get [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID --name
                                                NAME
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--name <name>
```

gitlab project-protected-environment list

```
usage: gitlab project-protected-environment list [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 [--page PAGE]
                                                 [--per-page PER_PAGE]
                                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--page <page>
```

```
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-protected-tag

```
usage: gitlab project-protected-tag [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-protected-tag create

```
usage: gitlab project-protected-tag create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --name NAME
                                         [--create-access-level CREATE_ACCESS_LEVEL]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--create-access-level <create_access_level>

gitlab project-protected-tag delete

```
usage: gitlab project-protected-tag delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-protected-tag get

```
usage: gitlab project-protected-tag get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-protected-tag list

```
usage: gitlab project-protected-tag list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-push-rules

```
usage: gitlab project-push-rules [-h] {get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-push-rules create

```
usage: gitlab project-push-rules create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID
                                         [--author-email-regex AUTHOR_EMAIL_REGEX]
                                         [--branch-name-regex BRANCH_NAME_REGEX]
                                         [--commit-committer-check COMMIT_COMMITTER_CHECK]
                                         [--commit-message-negative-regex COMMIT_MESSAGE_
                                         ↵NEGATIVE_REGEX]
                                         [--commit-message-regex COMMIT_MESSAGE_REGEX]
                                         [--deny-delete-tag DENY_DELETE_TAG]
                                         [--file-name-regex FILE_NAME_REGEX]
                                         [--max-file-size MAX_FILE_SIZE]
                                         [--member-check MEMBER_CHECK]
                                         [--prevent-secrets PREVENT_SECRETS]
                                         [--reject-unsigned-commits REJECT_UNSIGNED_
                                         ↵COMMITS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--author-email-regex <author_email_regex>

--branch-name-regex <branch_name_regex>

--commit-committer-check <commit_committer_check>

--commit-message-negative-regex <commit_message_negative_regex>

--commit-message-regex <commit_message_regex>

--deny-delete-tag <deny_delete_tag>

--file-name-regex <file_name_regex>

--max-file-size <max_file_size>

--member-check <member_check>

--prevent-secrets <prevent_secrets>

--reject-unsigned-commits <reject_unsigned_commits>

gitlab project-push-rules delete

```
usage: gitlab project-push-rules delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>  
--project-id <project_id>
```

gitlab project-push-rules get

```
usage: gitlab project-push-rules get [-h] [--sudo SUDO] --project-id  
PROJECT_ID
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>
```

gitlab project-push-rules update

```
usage: gitlab project-push-rules update [-h] [--sudo SUDO] --project-id  
PROJECT_ID  
[--author-email-regex AUTHOR_EMAIL_REGEX]  
[--branch-name-regex BRANCH_NAME_REGEX]  
[--commit-committer-check COMMIT_COMMITTER_CHECK]  
[--commit-message-negative-regex COMMIT_MESSAGE_  
NEGATIVE_REGEX]  
[--commit-message-regex COMMIT_MESSAGE_REGEX]  
[--deny-delete-tag DENY_DELETE_TAG]  
[--file-name-regex FILE_NAME_REGEX]  
[--max-file-size MAX_FILE_SIZE]  
[--member-check MEMBER_CHECK]  
[--prevent-secrets PREVENT_SECRETS]  
[--reject-unsigned-commits REJECT_UNSIGNED_  
COMMITTS]
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>  
--author-email-regex <author_email_regex>  
--branch-name-regex <branch_name_regex>  
--commit-committer-check <commit_committer_check>  
--commit-message-negative-regex <commit_message_negative_regex>  
--commit-message-regex <commit_message_regex>  
--deny-delete-tag <deny_delete_tag>  
--file-name-regex <file_name_regex>
```

```
--max-file-size <max_file_size>
--member-check <member_check>
--prevent-secrets <prevent_secrets>
--reject-unsigned-commits <reject_unsigned_commits>
```

gitlab project-registry-repository

```
usage: gitlab project-registry-repository [-h] {list,delete} ...
```

-h, --help

show this help message and exit

gitlab project-registry-repository delete

```
usage: gitlab project-registry-repository delete [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID --id
                                                 ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-registry-repository list

```
usage: gitlab project-registry-repository list [-h] [--sudo SUDO] --project-id
                                                PROJECT_ID [--page PAGE]
                                                [--per-page PER_PAGE]
                                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-registry-tag

```
usage: gitlab project-registry-tag [-h] {list,get,delete,delete-in-bulk} ...
```

-h, --help

show this help message and exit

gitlab project-registry-tag delete

```
usage: gitlab project-registry-tag delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --repository-id
                                         REPOSITORY_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--repository-id <repository_id>

--name <name>

gitlab project-registry-tag delete-in-bulk

```
usage: gitlab project-registry-tag delete-in-bulk [-h] --project-id PROJECT_ID
                                                 --repository-id
                                                 REPOSITORY_ID [--sudo SUDO]
                                                 --name NAME
                                                 --name-regex-delete
                                                 NAME_REGEX_DELETE
                                                 [--keep-n KEEP_N]
                                                 [--name-regex-keep NAME_REGEX_KEEP]
                                                 [--older-than OLDER_THAN]
```

-h, --help

show this help message and exit

--project-id <project_id>

--repository-id <repository_id>

--sudo <sudo>

--name <name>

--name-regex-delete <name_regex_delete>

--keep-n <keep_n>

--name-regex-keep <name_regex_keep>

--older-than <older_than>

gitlab project-registry-tag get

```
usage: gitlab project-registry-tag get [-h] [--sudo SUDO] --project-id  
                                      PROJECT_ID --repository-id  
                                      REPOSITORY_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--repository-id <repository_id>

--name <name>

gitlab project-registry-tag list

```
usage: gitlab project-registry-tag list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --repository-id  
                                         REPOSITORY_ID [--page PAGE]  
                                         [--per-page PER_PAGE] [--get-all]  
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--repository-id <repository_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-release

```
usage: gitlab project-release [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-release create

```
usage: gitlab project-release create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --tag-name TAG_NAME  
[--name NAME] [--description DESCRIPTION]  
[--ref REF] [--assets ASSETS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--name <name>

--description <description>

--ref <ref>

--assets <assets>

gitlab project-release delete

```
usage: gitlab project-release delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --tag-name TAG_NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

gitlab project-release get

```
usage: gitlab project-release get [-h] [--sudo SUDO] --project-id PROJECT_ID  
--tag-name TAG_NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

gitlab project-release list

```
usage: gitlab project-release list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  [--order-by ORDER_BY] [--sort SORT]
                                  [--include-html-description INCLUDE_HTML_DESCRIPTION]
                                  [--page PAGE] [--per-page PER_PAGE]
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--order-by <order_by>

--sort <sort>

--include-html-description <include_html_description>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-release update

```
usage: gitlab project-release update [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --tag-name TAG_NAME
                                      [--name NAME] [--description DESCRIPTION]
                                      [--milestones MILESTONES]
                                      [--released-at RELEASED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--name <name>

--description <description>

--milestones <milestones>

--released-at <released_at>

gitlab project-release-link

```
usage: gitlab project-release-link [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-release-link create

```
usage: gitlab project-release-link create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --tag-name TAG_NAME
                                         --name NAME --url URL
                                         [--filepath FILEPATH]
                                         [--link-type LINK_TYPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--name <name>

--url <url>

--filepath <filepath>

--link-type <link_type>

gitlab project-release-link delete

```
usage: gitlab project-release-link delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --tag-name TAG_NAME --id
                                         ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--id <id>

gitlab project-release-link get

```
usage: gitlab project-release-link get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --tag-name TAG_NAME --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--id <id>

gitlab project-release-link list

```
usage: gitlab project-release-link list [-h] [--sudo SUDO] --project-id  
PROJECT_ID --tag-name TAG_NAME  
[--page PAGE] [--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-release-link update

```
usage: gitlab project-release-link update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --tag-name TAG_NAME --id  
ID [--name NAME] [--url URL]  
[--filepath FILEPATH]  
[--link-type LINK_TYPE]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--tag-name <tag_name>
--id <id>
--name <name>
--url <url>
--filepath <filepath>
--link-type <link_type>
```

gitlab project-remote-mirror

```
usage: gitlab project-remote-mirror [-h] {list,create,update} ...
```

-h, --help

show this help message and exit

gitlab project-remote-mirror create

```
usage: gitlab project-remote-mirror create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --url URL
                                         [--enabled ENABLED]
                                         [--only-protected-branches ONLY_PROTECTED_
                                         BRANCHES]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--url <url>

--enabled <enabled>

--only-protected-branches <only_protected_branches>

gitlab project-remote-mirror list

```
usage: gitlab project-remote-mirror list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-remote-mirror update

```
usage: gitlab project-remote-mirror update [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --id ID
                                             [--enabled ENABLED]
                                             [--only-protected-branches ONLY_PROTECTED_
                                             BRANCHES]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
--enabled <enabled>
--only-protected-branches <only_protected_branches>
```

gitlab project-resource-group

```
usage: gitlab project-resource-group [-h] {list,get,update} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-resource-group get

```
usage: gitlab project-resource-group get [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --key KEY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--key <key>
```

gitlab project-resource-group list

```
usage: gitlab project-resource-group list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--order-by ORDER_BY]
                                         [--sort SORT]
                                         [--include-html-description INCLUDE_HTML_
                                         ↵DESCRIPTION]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--order-by <order_by>****--sort <sort>****--include-html-description <include_html_description>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab project-resource-group update

```
usage: gitlab project-resource-group update [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --key KEY
                                             [--process-mode PROCESS_MODE]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--key <key>****--process-mode <process_mode>**

gitlab project-resource-group-upcoming-job

```
usage: gitlab project-resource-group-upcoming-job [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-resource-group-upcoming-job list

```
usage: gitlab project-resource-group-upcoming-job list [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --resource-group-key
                                                       RESOURCE_GROUP_KEY
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--resource-group-key <resource_group_key>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-runner

```
usage: gitlab project-runner [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-runner create

```
usage: gitlab project-runner create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                     --runner-id RUNNER_ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--runner-id <runner_id>
```

gitlab project-runner delete

```
usage: gitlab project-runner delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--id <id>
```

gitlab project-runner list

```
usage: gitlab project-runner list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   [--scope SCOPE] [--tag-list TAG_LIST]
                                   [--page PAGE] [--per-page PER_PAGE]
                                   [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--scope <scope>
```

```
--tag-list <tag_list>
```

```
--page <page>
```

```
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-secure-file

```
usage: gitlab project-secure-file [-h] {list,get,create,delete,download} ...
```

-h, --help

show this help message and exit

gitlab project-secure-file create

```
usage: gitlab project-secure-file create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --name NAME --file FILE
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--file <file>

gitlab project-secure-file delete

```
usage: gitlab project-secure-file delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-secure-file download

```
usage: gitlab project-secure-file download [-h] --project-id PROJECT_ID  
[--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-secure-file get

```
usage: gitlab project-secure-file get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-secure-file list

```
usage: gitlab project-secure-file list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-service

```
usage: gitlab project-service [-h] {list,get,update,delete,available} ...
```

-h, --help

show this help message and exit

gitlab project-service available

```
usage: gitlab project-service available [-h] --project-id PROJECT_ID  
                                      [--sudo SUDO] --slug SLUG
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--slug <slug>

gitlab project-service delete

```
usage: gitlab project-service delete [-h] [--sudo SUDO] --project-id  
                                     PROJECT_ID --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-service get

```
usage: gitlab project-service get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-service list

```
usage: gitlab project-service list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                    [--page PAGE] [--per-page PER_PAGE]  
                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-service update

```
usage: gitlab project-service update [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --slug SLUG
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--slug <slug>
```

gitlab project-snippet

```
usage: gitlab project-snippet [-h]
  list
  get
  create
  update
  delete
  user-agent-detail
  content
  ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-snippet content

```
usage: gitlab project-snippet content [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>
```

gitlab project-snippet create

```
usage: gitlab project-snippet create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --title TITLE --file-name  
FILE_NAME --content CONTENT --visibility  
VISIBILITY [--description DESCRIPTION]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--title <title>

--file-name <file_name>

--content <content>

--visibility <visibility>

--description <description>

gitlab project-snippet delete

```
usage: gitlab project-snippet delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-snippet get

```
usage: gitlab project-snippet get [-h] [--sudo SUDO] --project-id PROJECT_ID  
--id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-snippet list

```
usage: gitlab project-snippet list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  [--page PAGE] [--per-page PER_PAGE]
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab project-snippet update

```
usage: gitlab project-snippet update [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --id ID [--title TITLE]
                                      [--file-name FILE_NAME]
                                      [--content CONTENT]
                                      [--visibility VISIBILITY]
                                      [--description DESCRIPTION]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--title <title>

--file-name <file_name>

--content <content>

--visibility <visibility>

--description <description>

gitlab project-snippet user-agent-detail

```
usage: gitlab project-snippet user-agent-detail [-h] --project-id PROJECT_ID  
                                                [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-snippet-award-emoji

```
usage: gitlab project-snippet-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-snippet-award-emoji create

```
usage: gitlab project-snippet-award-emoji create [-h] [--sudo SUDO]  
                                                --project-id PROJECT_ID  
                                                --snippet-id SNIPPET_ID  
                                                --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--name <name>

gitlab project-snippet-award-emoji delete

```
usage: gitlab project-snippet-award-emoji delete [-h] [--sudo SUDO]  
                                                --project-id PROJECT_ID  
                                                --snippet-id SNIPPET_ID --id  
                                                ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--snippet-id <snippet_id>
--id <id>
```

gitlab project-snippet-award-emoji get

```
usage: gitlab project-snippet-award-emoji get [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --snippet-id
                                              SNIPPET_ID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--snippet-id <snippet_id>
```

```
--id <id>
```

gitlab project-snippet-award-emoji list

```
usage: gitlab project-snippet-award-emoji list [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --snippet-id
                                               SNIPPET_ID [--page PAGE]
                                               [--per-page PER_PAGE]
                                               [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--snippet-id <snippet_id>
```

```
--page <page>
```

```
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-snippet-discussion

```
usage: gitlab project-snippet-discussion [-h] {list,get,create} ...
```

-h, --help

show this help message and exit

gitlab project-snippet-discussion create

```
usage: gitlab project-snippet-discussion create [-h] [--sudo SUDO]
                                               --project-id PROJECT_ID
                                               --snippet-id SNIPPET_ID --body
                                               BODY [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--body <body>

--created-at <created_at>

gitlab project-snippet-discussion get

```
usage: gitlab project-snippet-discussion get [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --snippet-id
                                              SNIPPET_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--id <id>

gitlab project-snippet-discussion list

```
usage: gitlab project-snippet-discussion list [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --snippet-id
                                              SNIPPET_ID [--page PAGE]
                                              [--per-page PER_PAGE]
                                              [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--snippet-id <snippet_id>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab project-snippet-discussion-note

```
usage: gitlab project-snippet-discussion-note [-h]
  get
  create
  update
  delete} ...
```

-h, --help

show this help message and exit

gitlab project-snippet-discussion-note create

```
usage: gitlab project-snippet-discussion-note create [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --snippet-id SNIPPET_ID
                                                 --discussion-id
                                                 DISCUSSION_ID --body BODY
                                                 [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>**

```
--snippet-id <snippet_id>
--discussion-id <discussion_id>
--body <body>
--created-at <created_at>
```

gitlab project-snippet-discussion-note delete

```
usage: gitlab project-snippet-discussion-note delete [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--discussion-id <discussion_id>

--id <id>

gitlab project-snippet-discussion-note get

```
usage: gitlab project-snippet-discussion-note get [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--discussion-id <discussion_id>

--id <id>

gitlab project-snippet-discussion-note update

```
usage: gitlab project-snippet-discussion-note update [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --id ID
                                                    --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--discussion-id <discussion_id>

--id <id>

--body <body>

gitlab project-snippet-note

```
usage: gitlab project-snippet-note [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-snippet-note create

```
usage: gitlab project-snippet-note create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --snippet-id SNIPPET_ID
                                         --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--body <body>

gitlab project-snippet-note delete

```
usage: gitlab project-snippet-note delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --snippet-id SNIPPET_ID  
                                         --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--id <id>

gitlab project-snippet-note get

```
usage: gitlab project-snippet-note get [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --snippet-id SNIPPET_ID --id  
                                         ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--id <id>

gitlab project-snippet-note list

```
usage: gitlab project-snippet-note list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --snippet-id SNIPPET_ID  
                                         [--page PAGE] [--per-page PER_PAGE]  
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-snippet-note update

```
usage: gitlab project-snippet-note update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --snippet-id SNIPPET_ID
                                         --id ID --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--snippet-id <snippet_id>****--id <id>****--body <body>****gitlab project-snippet-note-award-emoji**

```
usage: gitlab project-snippet-note-award-emoji [-h]
      list
      get
      create
      delete} ...
```

-h, --help

show this help message and exit

gitlab project-snippet-note-award-emoji create

```
usage: gitlab project-snippet-note-award-emoji create [-h] [--sudo SUDO]
                                         --project-id PROJECT_ID
                                         --snippet-id SNIPPET_ID
                                         --note-id NOTE_ID --name
                                         NAME
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--snippet-id <snippet_id>**

```
--note-id <note_id>  
--name <name>
```

gitlab project-snippet-note-award-emoji delete

```
usage: gitlab project-snippet-note-award-emoji delete [-h] [--sudo SUDO]  
          --project-id PROJECT_ID  
          --snippet-id SNIPPET_ID  
          --note-id NOTE_ID --id  
          ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--snippet-id <snippet_id>
```

```
--note-id <note_id>
```

```
--id <id>
```

gitlab project-snippet-note-award-emoji get

```
usage: gitlab project-snippet-note-award-emoji get [-h] [--sudo SUDO]  
          --project-id PROJECT_ID  
          --snippet-id SNIPPET_ID  
          --note-id NOTE_ID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--snippet-id <snippet_id>
```

```
--note-id <note_id>
```

```
--id <id>
```

gitlab project-snippet-note-award-emoji list

```
usage: gitlab project-snippet-note-award-emoji list [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --snippet-id SNIPPET_ID
                                                 --note-id NOTE_ID
                                                 [--page PAGE]
                                                 [--per-page PER_PAGE]
                                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--note-id <note_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-storage

```
usage: gitlab project-storage [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-storage get

```
usage: gitlab project-storage get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-tag

```
usage: gitlab project-tag [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-tag create

```
usage: gitlab project-tag create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --tag-name TAG_NAME --ref REF
                                 [--message MESSAGE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--ref <ref>

--message <message>

gitlab project-tag delete

```
usage: gitlab project-tag delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-tag get

```
usage: gitlab project-tag get [-h] [--sudo SUDO] --project-id PROJECT_ID
                               --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-tag list

```
usage: gitlab project-tag list [-h] [--sudo SUDO] --project-id PROJECT_ID
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]
                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-trigger

```
usage: gitlab project-trigger [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-trigger create

```
usage: gitlab project-trigger create [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --description DESCRIPTION
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--description <description>

gitlab project-trigger delete

```
usage: gitlab project-trigger delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-trigger get

```
usage: gitlab project-trigger get [-h] [--sudo SUDO] --project-id PROJECT_ID  
--id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-trigger list

```
usage: gitlab project-trigger list [-h] [--sudo SUDO] --project-id PROJECT_ID  
[--page PAGE] [--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-trigger update

```
usage: gitlab project-trigger update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID --description  
DESCRIPTION
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--description <description>

gitlab project-user

```
usage: gitlab project-user [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-user list

```
usage: gitlab project-user list [-h] [--sudo SUDO] --project-id PROJECT_ID  
[--search SEARCH] [--skip-users SKIP_USERS]  
[--page PAGE] [--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--search <search>

--skip-users <skip_users>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-variable

```
usage: gitlab project-variable [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-variable create

```
usage: gitlab project-variable create [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --key KEY --value VALUE
                                      [--protected PROTECTED]
                                      [--variable-type VARIABLE_TYPE]
                                      [--masked MASKED]
                                      [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--key <key>

--value <value>

--protected <protected>

--variable-type <variable_type>

--masked <masked>

--environment-scope <environment_scope>

gitlab project-variable delete

```
usage: gitlab project-variable delete [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--key <key>

gitlab project-variable get

```
usage: gitlab project-variable get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--key <key>

gitlab project-variable list

```
usage: gitlab project-variable list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                    [--page PAGE] [--per-page PER_PAGE]  
                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-variable update

```
usage: gitlab project-variable update [-h] [--sudo SUDO] --project-id  
                                      PROJECT_ID --key KEY --value VALUE  
                                      [--protected PROTECTED]  
                                      [--variable-type VARIABLE_TYPE]  
                                      [--masked MASKED]  
                                      [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--key <key>
--value <value>
--protected <protected>
--variable-type <variable_type>
--masked <masked>
--environment-scope <environment_scope>
```

gitlab project-wiki

```
usage: gitlab project-wiki [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-wiki create

```
usage: gitlab project-wiki create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --title TITLE --content CONTENT
                                  [--format FORMAT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--title <title>

--content <content>

--format <format>

gitlab project-wiki delete

```
usage: gitlab project-wiki delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-wiki get

```
usage: gitlab project-wiki get [-h] [--sudo SUDO] --project-id PROJECT_ID
                               --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-wiki list

```
usage: gitlab project-wiki list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 [--with-content WITH_CONTENT] [--page PAGE]
                                 [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--with-content <with_content>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-wiki update

```
usage: gitlab project-wiki update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --slug SLUG [--title TITLE]
                                   [--content CONTENT] [--format FORMAT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

```
--title <title>
--content <content>
--format <format>
```

gitlab registry-repository

```
usage: gitlab registry-repository [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab registry-repository get

```
usage: gitlab registry-repository get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab runner

```
usage: gitlab runner [-h] {list,get,create,update,delete,all,verify} ...
```

-h, --help

show this help message and exit

gitlab runner all

```
usage: gitlab runner all [-h] --id ID [--scope SCOPE]
```

-h, --help

show this help message and exit

--id <id>

--scope <scope>

gitlab runner create

```
usage: gitlab runner create [-h] [--sudo SUDO] --token TOKEN
                            [--description DESCRIPTION] [--info INFO]
                            [--active ACTIVE] [--locked LOCKED]
                            [--run-untagged RUN_UNTAGGED]
                            [--tag-list TAG_LIST]
                            [--access-level ACCESS_LEVEL]
                            [--maximum-timeout MAXIMUM_TIMEOUT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--token <token>

--description <description>

--info <info>

--active <active>

--locked <locked>

--run-untagged <run_untagged>

--tag-list <tag_list>

--access-level <access_level>

--maximum-timeout <maximum_timeout>

gitlab runner delete

```
usage: gitlab runner delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab runner get

```
usage: gitlab runner get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab runner list

```
usage: gitlab runner list [-h] [--sudo SUDO] [--scope SCOPE] [--type TYPE]
                           [--status STATUS] [--paused PAUSED]
                           [--tag-list TAG_LIST] [--page PAGE]
                           [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--scope <scope>

--type <type>

--status <status>

--paused <paused>

--tag-list <tag_list>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab runner update

```
usage: gitlab runner update [-h] [--sudo SUDO] --id ID
                            [--description DESCRIPTION] [--active ACTIVE]
                            [--tag-list TAG_LIST]
                            [--run-untagged RUN_UNTAGGED] [--locked LOCKED]
                            [--access-level ACCESS_LEVEL]
                            [--maximum-timeout MAXIMUM_TIMEOUT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

--description <description>

--active <active>

--tag-list <tag_list>

--run-untagged <run_untagged>

```
--locked <locked>
--access-level <access_level>
--maximum-timeout <maximum_timeout>
```

gitlab runner verify

```
usage: gitlab runner verify [-h] --id ID --token TOKEN
```

```
-h, --help
    show this help message and exit
--id <id>
--token <token>
```

gitlab runner-all

```
usage: gitlab runner-all [-h] {list} ...
```

```
-h, --help
    show this help message and exit
```

gitlab runner-all list

```
usage: gitlab runner-all list [-h] [--sudo SUDO] [--scope SCOPE] [--type TYPE]
                               [--status STATUS] [--paused PAUSED]
                               [--tag-list TAG_LIST] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--scope <scope>
--type <type>
--status <status>
--paused <paused>
--tag-list <tag_list>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab runner-job

```
usage: gitlab runner-job [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab runner-job list

```
usage: gitlab runner-job list [-h] [--sudo SUDO] --runner-id RUNNER_ID
                               [--status STATUS] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--runner-id <runner_id>

--status <status>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab shared-project

```
usage: gitlab shared-project [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab shared-project list

```
usage: gitlab shared-project list [-h] [--sudo SUDO] --group-id GROUP_ID
                                   [--archived ARCHIVED]
                                   [--visibility VISIBILITY]
                                   [--order-by ORDER_BY] [--sort SORT]
                                   [--search SEARCH] [--simple SIMPLE]
                                   [--starred STARRED]
                                   [--with-issues-enabled WITH_ISSUES_ENABLED]
                                   [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
                                   ↵ENABLED]
                                   [--min-access-level MIN_ACCESS_LEVEL]
```

(continues on next page)

(continued from previous page)

```
[--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
[--page PAGE] [--per-page PER_PAGE]
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--archived <archived>****--visibility <visibility>****--order-by <order_by>****--sort <sort>****--search <search>****--simple <simple>****--starred <starred>****--with-issues-enabled <with_issues_enabled>****--with-merge-requests-enabled <with_merge_requests_enabled>****--min-access-level <min_access_level>****--with-custom-attributes <with_custom_attributes>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab snippet

```
usage: gitlab snippet [-h]
  list
  get
  create
  update
  delete
  user-agent-detail
  content
  public
  ...
```

-h, --help

show this help message and exit

gitlab snippet content

```
usage: gitlab snippet content [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab snippet create

```
usage: gitlab snippet create [-h] [--sudo SUDO] --title TITLE --file-name
                             FILE_NAME --content CONTENT [--lifetime LIFETIME]
                             [--visibility VISIBILITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--title <title>

--file-name <file_name>

--content <content>

--lifetime <lifetime>

--visibility <visibility>

gitlab snippet delete

```
usage: gitlab snippet delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab snippet get

```
usage: gitlab snippet get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab snippet list

```
usage: gitlab snippet list [-h] [--sudo SUDO] [--page PAGE]
                           [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab snippet public

```
usage: gitlab snippet public [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab snippet update

```
usage: gitlab snippet update [-h] [--sudo SUDO] --id ID [--title TITLE]
                             [--file-name FILE_NAME] [--content CONTENT]
                             [--visibility VISIBILITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

```
--title <title>
--file-name <file_name>
--content <content>
--visibility <visibility>
```

gitlab snippet user-agent-detail

```
usage: gitlab snippet user-agent-detail [-h] --id ID
```

-h, --help
show this help message and exit

--id <id>

gitlab starred-project

```
usage: gitlab starred-project [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab starred-project list

```
usage: gitlab starred-project list [-h] [--sudo SUDO] --user-id USER_ID
                                   [--archived ARCHIVED]
                                   [--membership MEMBERSHIP]
                                   [--min-access-level MIN_ACCESS_LEVEL]
                                   [--order-by ORDER_BY] [--owned OWNED]
                                   [--search SEARCH] [--simple SIMPLE]
                                   [--sort SORT] [--starred STARRED]
                                   [--statistics STATISTICS]
                                   [--visibility VISIBILITY]
                                   [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                   [--with-issues-enabled WITH_ISSUES_ENABLED]
                                   [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
                                   ↵ENABLED]
                                   [--page PAGE] [--per-page PER_PAGE]
                                   [--get-all] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--archived <archived>

```
--membership <membership>
--min-access-level <min_access_level>
--order-by <order_by>
--owned <owned>
--search <search>
--simple <simple>
--sort <sort>
--starred <starred>
--statistics <statistics>
--visibility <visibility>
--with-custom-attributes <with_custom_attributes>
--with-issues-enabled <with_issues_enabled>
--with-merge-requests-enabled <with_merge_requests_enabled>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab todo

```
usage: gitlab todo [-h] {list,delete,mark-as-done,mark-all-as-done} ...
```

```
-h, --help
    show this help message and exit
```

gitlab todo delete

```
usage: gitlab todo delete [-h] [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>
```

gitlab todo list

```
usage: gitlab todo list [-h] [--sudo SUDO] [--action ACTION]
                        [--author-id AUTHOR_ID] [--project-id PROJECT_ID]
                        [--state STATE] [--type TYPE] [--page PAGE]
                        [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--action <action>

--author-id <author_id>

--project-id <project_id>

--state <state>

--type <type>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab todo mark-all-as-done

```
usage: gitlab todo mark-all-as-done [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab todo mark-as-done

```
usage: gitlab todo mark-as-done [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab topic

```
usage: gitlab topic [-h] {list,get,create,update,delete,merge} ...
```

-h, --help

show this help message and exit

gitlab topic create

```
usage: gitlab topic create [-h] [--sudo SUDO] --name NAME [--avatar AVATAR]
                           [--description DESCRIPTION] [--title TITLE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--name <name>

--avatar <avatar>

--description <description>

--title <title>

gitlab topic delete

```
usage: gitlab topic delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab topic get

```
usage: gitlab topic get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab topic list

```
usage: gitlab topic list [-h] [--sudo SUDO] [--page PAGE]
                         [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab topic merge

```
usage: gitlab topic merge [-h] --id ID --source-topic-id SOURCE_TOPIC_ID
                          --target-topic-id TARGET_TOPIC_ID
```

-h, --help

show this help message and exit

--id <id>

--source-topic-id <source_topic_id>

--target-topic-id <target_topic_id>

gitlab topic update

```
usage: gitlab topic update [-h] [--sudo SUDO] --id ID [--avatar AVATAR]
                           [--description DESCRIPTION] [--name NAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

--avatar <avatar>

--description <description>

--name <name>

gitlab user

```
usage: gitlab user [-h]
  list
  get
  create
  update
  delete
  block
  follow
  unfollow
  unblock
  deactivate
  activate
  approve
  reject
  ban
  unban
  ...
```

-h, --help

show this help message and exit

gitlab user activate

```
usage: gitlab user activate [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user approve

```
usage: gitlab user approve [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user ban

```
usage: gitlab user ban [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user block

```
usage: gitlab user block [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user create

```
usage: gitlab user create [-h] [--sudo SUDO] [--email EMAIL]
                           [--username USERNAME] [--name NAME]
                           [--password PASSWORD]
                           [--reset-password RESET_PASSWORD] [--skype SKYPE]
                           [--linkedin LINKEDIN] [--twitter TWITTER]
                           [--projects-limit PROJECTS_LIMIT]
                           [--extern-uid EXTERN_UID] [--provider PROVIDER]
                           [--bio BIO] [--admin ADMIN]
                           [--can-create-group CAN_CREATE_GROUP]
                           [--website-url WEBSITE_URL]
                           [--skip-confirmation SKIP_CONFIRMATION]
                           [--external EXTERNAL] [--organization ORGANIZATION]
                           [--location LOCATION] [--avatar AVATAR]
                           [--public-email PUBLIC_EMAIL]
                           [--private-profile PRIVATE_PROFILE]
                           [--color-scheme-id COLOR_SCHEME_ID]
                           [--theme-id THEME_ID]
```

-h, --help

show this help message and exit

--sudo <sudo>

--email <email>

--username <username>

--name <name>

--password <password>

--reset-password <reset_password>

--skype <skype>

--linkedin <linkedin>

--twitter <twitter>

--projects-limit <projects_limit>

--extern-uid <extern_uid>

--provider <provider>

```
--bio <bio>
--admin <admin>
--can-create-group <can_create_group>
--website-url <website_url>
--skip-confirmation <skip_confirmation>
--external <external>
--organization <organization>
--location <location>
--avatar <avatar>
--public-email <public_email>
--private-profile <private_profile>
--color-scheme-id <color_scheme_id>
--theme-id <theme_id>
```

gitlab user deactivate

```
usage: gitlab user deactivate [-h] --id ID
```

-h, --help
show this help message and exit
--id <id>

gitlab user delete

```
usage: gitlab user delete [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit
--sudo <sudo>
--id <id>

gitlab user follow

```
usage: gitlab user follow [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user get

```
usage: gitlab user get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab user list

```
usage: gitlab user list [-h] [--sudo SUDO] [--active ACTIVE]
                        [--blocked BLOCKED] [--username USERNAME]
                        [--extern-uid EXTERN_UID] [--provider PROVIDER]
                        [--external EXTERNAL] [--search SEARCH]
                        [--custom-attributes CUSTOM_ATTRIBUTES]
                        [--status STATUS] [--two-factor TWO_FACTOR]
                        [--page PAGE] [--per-page PER_PAGE] [--get-all]
                        [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--active <active>

--blocked <blocked>

--username <username>

--extern-uid <extern_uid>

--provider <provider>

--external <external>

--search <search>

--custom-attributes <custom_attributes>

--status <status>

```
--two-factor <two_factor>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab user reject

```
usage: gitlab user reject [-h] --id ID
```

```
-h, --help
    show this help message and exit
--id <id>
```

gitlab user unban

```
usage: gitlab user unban [-h] --id ID
```

```
-h, --help
    show this help message and exit
--id <id>
```

gitlab user unblock

```
usage: gitlab user unblock [-h] --id ID
```

```
-h, --help
    show this help message and exit
--id <id>
```

gitlab user unfollow

```
usage: gitlab user unfollow [-h] --id ID
```

```
-h, --help
    show this help message and exit
--id <id>
```

gitlab user update

```
usage: gitlab user update [-h] [--sudo SUDO] --id ID --email EMAIL --username
                          USERNAME --name NAME [--password PASSWORD]
                          [--skype SKYPE] [--linkedin LINKEDIN]
                          [--twitter TWITTER]
                          [--projects-limit PROJECTS_LIMIT]
                          [--extern-uid EXTERN_UID] [--provider PROVIDER]
                          [--bio BIO] [--admin ADMIN]
                          [--can-create-group CAN_CREATE_GROUP]
                          [--website-url WEBSITE_URL]
                          [--skip-reconfirmation SKIP_RECONFIRMATION]
                          [--external EXTERNAL] [--organization ORGANIZATION]
                          [--location LOCATION] [--avatar AVATAR]
                          [--public-email PUBLIC_EMAIL]
                          [--private-profile PRIVATE_PROFILE]
                          [--color-scheme-id COLOR_SCHEME_ID]
                          [--theme-id THEME_ID]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

--email <email>

--username <username>

--name <name>

--password <password>

--skype <skype>

--linkedin <linkedin>

--twitter <twitter>

--projects-limit <projects_limit>

--extern-uid <extern_uid>

--provider <provider>

--bio <bio>

--admin <admin>

--can-create-group <can_create_group>

--website-url <website_url>

--skip-reconfirmation <skip_reconfirmation>

--external <external>

```
--organization <organization>
--location <location>
--avatar <avatar>
--public-email <public_email>
--private-profile <private_profile>
--color-scheme-id <color_scheme_id>
--theme-id <theme_id>
```

gitlab user-activities

```
usage: gitlab user-activities [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab user-activities list

```
usage: gitlab user-activities list [-h] [--sudo SUDO] [--page PAGE]
                                   [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab user-custom-attribute

```
usage: gitlab user-custom-attribute [-h] {list,get,delete} ...
```

-h, --help

show this help message and exit

gitlab user-custom-attribute delete

```
usage: gitlab user-custom-attribute delete [-h] [--sudo SUDO] --user-id
                                         USER_ID --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--key <key>

gitlab user-custom-attribute get

```
usage: gitlab user-custom-attribute get [-h] [--sudo SUDO] --user-id USER_ID
                                         --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--key <key>

gitlab user-custom-attribute list

```
usage: gitlab user-custom-attribute list [-h] [--sudo SUDO] --user-id USER_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab user-email

```
usage: gitlab user-email [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab user-email create

```
usage: gitlab user-email create [-h] [--sudo SUDO] --user-id USER_ID --email  
                                EMAIL
```

-h, --help

show this help message and exit

--sudo <sudo>**--user-id <user_id>****--email <email>****gitlab user-email delete**

```
usage: gitlab user-email delete [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--user-id <user_id>****--id <id>****gitlab user-email get**

```
usage: gitlab user-email get [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--user-id <user_id>****--id <id>**

gitlab user-email list

```
usage: gitlab user-email list [-h] [--sudo SUDO] --user-id USER_ID
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]
                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab user-event

```
usage: gitlab user-event [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab user-event list

```
usage: gitlab user-event list [-h] [--sudo SUDO] --user-id USER_ID
                               [--action ACTION] [--target-type TARGET_TYPE]
                               [--before BEFORE] [--after AFTER] [--sort SORT]
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]
                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--action <action>

--target-type <target_type>

--before <before>

--after <after>

--sort <sort>

```
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab user-gpg-key

```
usage: gitlab user-gpg-key [-h] {list,get,create,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab user-gpg-key create

```
usage: gitlab user-gpg-key create [-h] [--sudo SUDO] --user-id USER_ID --key
                                  KEY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--user-id <user_id>
--key <key>
```

gitlab user-gpg-key delete

```
usage: gitlab user-gpg-key delete [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--user-id <user_id>
--id <id>
```

gitlab user-gpg-key get

```
usage: gitlab user-gpg-key get [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-gpg-key list

```
usage: gitlab user-gpg-key list [-h] [--sudo SUDO] --user-id USER_ID  
                                [--page PAGE] [--per-page PER_PAGE]  
                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab user-impersonation-token

```
usage: gitlab user-impersonation-token [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab user-impersonation-token create

```
usage: gitlab user-impersonation-token create [-h] [--sudo SUDO] --user-id  
                                              USER_ID --name NAME --scopes  
                                              SCOPES [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--user-id <user_id>
--name <name>
--scopes <scopes>
--expires-at <expires_at>
```

gitlab user-impersonation-token delete

```
usage: gitlab user-impersonation-token delete [-h] [--sudo SUDO] --user-id
                                               USER_ID --id ID
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--user-id <user_id>
--id <id>
```

gitlab user-impersonation-token get

```
usage: gitlab user-impersonation-token get [-h] [--sudo SUDO] --user-id
                                              USER_ID --id ID
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--user-id <user_id>
--id <id>
```

gitlab user-impersonation-token list

```
usage: gitlab user-impersonation-token list [-h] [--sudo SUDO] --user-id
                                              USER_ID [--state STATE]
                                              [--page PAGE]
                                              [--per-page PER_PAGE] [--get-all]
                                              [--all]
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--user-id <user_id>
```

```
--state <state>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab user-key

```
usage: gitlab user-key [-h] {list,get,create,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab user-key create

```
usage: gitlab user-key create [-h] [--sudo SUDO] --user-id USER_ID --title
                               TITLE --key KEY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--user-id <user_id>
--title <title>
--key <key>
```

gitlab user-key delete

```
usage: gitlab user-key delete [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--user-id <user_id>
--id <id>
```

gitlab user-key get

```
usage: gitlab user-key get [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-key list

```
usage: gitlab user-key list [-h] [--sudo SUDO] --user-id USER_ID [--page PAGE]
                            [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab user-membership

```
usage: gitlab user-membership [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab user-membership get

```
usage: gitlab user-membership get [-h] [--sudo SUDO] --user-id USER_ID
                                  --source-id SOURCE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--user-id <user_id>
--source-id <source_id>
```

gitlab user-membership list

```
usage: gitlab user-membership list [-h] [--sudo SUDO] --user-id USER_ID
                                  [--type TYPE] [--page PAGE]
                                  [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--type <type>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab user-personal-access-token

```
usage: gitlab user-personal-access-token [-h] {create} ...
```

-h, --help

show this help message and exit

gitlab user-personal-access-token create

```
usage: gitlab user-personal-access-token create [-h] [--sudo SUDO] --user-id
                                                USER_ID --name NAME --scopes
                                                SCOPES
                                                [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--name <name>

--scopes <scopes>

--expires-at <expires_at>

gitlab user-project

```
usage: gitlab user-project [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab user-project create

```
usage: gitlab user-project create [-h] [--sudo SUDO] --user-id USER_ID --name
                                  NAME [--default-branch DEFAULT_BRANCH]
                                  [--issues-enabled ISSUES_ENABLED]
                                  [--wall-enabled WALL_ENABLED]
                                  [--merge-requests-enabled MERGE_REQUESTS_ENABLED]
                                  [--wiki-enabled WIKI_ENABLED]
                                  [--snippets-enabled SNIPPETS_ENABLED]
                                  [--squash-option SQUASH_OPTION]
                                  [--public PUBLIC] [--visibility VISIBILITY]
                                  [--description DESCRIPTION]
                                  [--builds-enabled BUILDS_ENABLED]
                                  [--public-builds PUBLIC_BUILDS]
                                  [--import-url IMPORT_URL]
                                  [--only-allow-merge-if-build-succeeds ONLY_ALLOW_MERGE_
                                  ↪IF_BUILD_SUCCEEDS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--name <name>

--default-branch <default_branch>

--issues-enabled <issues_enabled>

--wall-enabled <wall_enabled>

--merge-requests-enabled <merge_requests_enabled>

--wiki-enabled <wiki_enabled>

--snippets-enabled <snippets_enabled>

--squash-option <squash_option>

--public <public>

--visibility <visibility>

--description <description>

--builds-enabled <builds_enabled>

```
--public-builds <public_builds>
--import-url <import_url>
--only-allow-merge-if-build-succeeds <only_allow_merge_if_build_succeeds>
```

gitlab user-project list

```
usage: gitlab user-project list [-h] [--sudo SUDO] --user-id USER_ID
                                 [--archived ARCHIVED]
                                 [--visibility VISIBILITY]
                                 [--order-by ORDER_BY] [--sort SORT]
                                 [--search SEARCH] [--simple SIMPLE]
                                 [--owned OWNED] [--membership MEMBERSHIP]
                                 [--starred STARRED] [--statistics STATISTICS]
                                 [--with-issues-enabled WITH_ISSUES_ENABLED]
                                 [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
                                 ↵ENABLED]
                                 [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                 [--with-programming-language WITH_PROGRAMMING_LANGUAGE]
                                 [--wiki-checksum-failed WIKI_CHECKSUM_FAILED]
                                 [--repository-checksum-failed REPOSITORY_CHECKSUM_FAILED]
                                 [--min-access-level MIN_ACCESS_LEVEL]
                                 [--id-after ID_AFTER] [--id-before ID_BEFORE]
                                 [--page PAGE] [--per-page PER_PAGE]
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--user-id <user_id>
--archived <archived>
--visibility <visibility>
--order-by <order_by>
--sort <sort>
--search <search>
--simple <simple>
--owned <owned>
--membership <membership>
--starred <starred>
--statistics <statistics>
--with-issues-enabled <with_issues_enabled>
```

```
--with-merge-requests-enabled <with_merge_requests_enabled>
--with-custom-attributes <with_custom_attributes>
--with-programming-language <with_programming_language>
--wiki-checksum-failed <wiki_checksum_failed>
--repository-checksum-failed <repository_checksum_failed>
--min-access-level <min_access_level>
--id-after <id_after>
--id-before <id_before>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab user-status

```
usage: gitlab user-status [-h] {get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab user-status get

```
usage: gitlab user-status get [-h] [--sudo SUDO] --user-id USER_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--user-id <user_id>
```

gitlab variable

```
usage: gitlab variable [-h] {list,get,create,update,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab variable create

```
usage: gitlab variable create [-h] [--sudo SUDO] --key KEY --value VALUE
                               [--protected PROTECTED]
                               [--variable-type VARIABLE_TYPE]
                               [--masked MASKED]
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

--value <value>

--protected <protected>

--variable-type <variable_type>

--masked <masked>

gitlab variable delete

```
usage: gitlab variable delete [-h] [--sudo SUDO] --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

gitlab variable get

```
usage: gitlab variable get [-h] [--sudo SUDO] --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

gitlab variable list

```
usage: gitlab variable list [-h] [--sudo SUDO] [--page PAGE]
                           [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab variable update

```
usage: gitlab variable update [-h] [--sudo SUDO] --key KEY --value VALUE
                               [--protected PROTECTED]
                               [--variable-type VARIABLE_TYPE]
                               [--masked MASKED]
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

--value <value>

--protected <protected>

--variable-type <variable_type>

--masked <masked>

7.8 Lower-level APIs

python-gitlab's API levels provide different degrees of convenience, control and stability.

7.8.1 Main interface - Gitlab, managers and objects

As shown in previous sections and examples, the high-level API interface wraps GitLab's API endpoints and makes them available from the `Gitlab` instance via managers that create objects you can manipulate.

This is what most users will want to use, as it covers most of GitLab's API endpoints, and allows you to write idiomatic Python code when interacting with the API.

7.8.2 Lower-level API - HTTP methods

Danger: At this point, `python-gitlab` will no longer take care of URL-encoding and other transformations needed to correctly pass API parameter types. You have to construct these correctly yourself.

However, you still benefit from many of the client's [Features](#) such as authentication, requests and retry handling.

Important: If you've found yourself at this section because of an endpoint not yet implemented in the library - please consider opening a pull request implementing the resource or at least filing an issue so we can track progress.

High-quality pull requests for standard endpoints that pass CI and include unit tests and documentation are easy to review, and can land quickly with monthly releases. If you ask, we can also trigger a new release, so you and everyone benefits from the contribution right away!

Managers and objects call specific HTTP methods to fetch or send data to the server. These methods can be invoked directly to access endpoints not currently implemented by the client. This essentially gives you some level of usability for any endpoint the moment it is available on your GitLab instance.

These methods can be accessed directly via the `Gitlab` instance (e.g. `gl.http_get()`), or via an object's manager (e.g. `project.manager.gitlab.http_get()`), if the `Gitlab` instance is not available in the current context.

For example, if you'd like to access GitLab's [undocumented latest pipeline endpoint](#), you can do so by calling `http_get()` with the path to the endpoint:

```
>>> gl = gitlab.Gitlab(private_token=private_token)
>>>
>>> pipeline = gl.http_get("/projects/gitlab-org%2Fgitlab/pipelines/latest")
>>> pipeline["id"]
449070256
```

The available methods are:

- `http_get()`
- `http_post()`
- `http_put()`
- `http_patch()`
- `http_delete()`
- `http_list()` (a wrapper around `http_get` handling pagination, including with lazy generators)
- `http_head()` (only returns the header dictionary)

7.8.3 Lower-lower-level API - HTTP requests

Important: This is mostly intended for internal use in python-gitlab and may have a less stable interface than higher-level APIs. To lessen the chances of a change to the interface impacting your code, we recommend using keyword arguments when calling the interfaces.

At the lowest level, HTTP methods call `http_request()`, which performs the actual request and takes care of details such as timeouts, retries, and handling rate-limits.

This method can be invoked directly to or customize this behavior for a single request, or to call custom HTTP methods not currently implemented in the library - while still making use of all of the client's options and authentication methods.

For example, if for whatever reason you want to fetch allowed methods for an endpoint at runtime:

```
>>> gl = gitlab.Gitlab(private_token=private_token)
>>>
>>> response = gl.http_request(verb="OPTIONS", path="/projects")
>>> response.headers["Allow"]
'OPTIONS, GET, POST, HEAD'
```

Or get the total number of a user's events with a customized HEAD request:

```
>>> response = gl.http_request(
    verb="HEAD",
    path="/events",
    query_params={"sudo": "some-user"},
    timeout=10
)
>>> response.headers["X-Total"]
'123'
```

7.9 Changelog

7.9.1 v3.14.0 (2023-04-11)

Feature

- **projects:** Allow importing additional items from GitHub ([ce84f2e](#))
- **objects:** Support fetching PATs via id or `self` endpoint ([19b38bd](#))
- Add `resource_weight_event` for `ProjectIssue` ([6e5ef55](#))
- **backends:** Use PEP544 protocols for structural subtyping ([#2442](#)) ([4afeaff](#))
- **client:** Add `http_patch` method ([#2471](#)) ([f711d9e](#))
- **cli:** Add setting of `allow_force_push` for protected branch ([929e07d](#))

Fix

- **cli:** Warn user when no fields are displayed ([8bf53c8](#))
- **client:** Properly parse content-type when charset is present ([76063c3](#))
- Support int for parent_id in import_group ([90f96ac](#))
- **cli:** Add ability to escape at-prefixed parameter (#2513) ([4f7c784](#))
- **cli:** Display items when iterator is returned ([33a04e7](#))
- Typo fixed in docs ([ee5f444](#))

Documentation

- **objects:** Fix typo in pipeline schedules ([3057f45](#))
- **advanced:** Clarify netrc, proxy behavior with requests ([1da7c53](#))
- Fix update badge behaviour ([3d7ca1c](#))
- **advanced:** Fix typo in Gitlab examples ([1992790](#))

7.9.2 v3.13.0 (2023-01-30)

Feature

- **group:** Add support for group restore API ([9322db6](#))
- **client:** Automatically retry on HTTP 409 Resource lock ([dcde76a](#))
- **api:** Add support for bulk imports API ([043de2d](#))
- **api:** Add support for resource groups ([5f8b8f5](#))
- **api:** Support listing pipelines triggered by pipeline schedules ([865fa41](#))
- Allow filtering pipelines by source ([b6c0872](#))
- **client:** Bootstrap the http backends concept (#2391) ([91a665f](#))
- Add resource iteration events (see https://docs.gitlab.com/ee/api/resource_iteration_events.html) ([ef5feb4](#))
- Allow passing kwargs to Gitlab class when instantiating with `from_config` (#2392) ([e88d34e](#))
- Add `keep_base_url` when getting configuration from file ([50a0301](#))

Fix

- **client:** Regression - do not automatically get_next if page=# and ([585e3a8](#))
- Change return value to “None” in case getattr returns None to prevent error ([3f86d36](#))
- **deps:** Bump requests-toolbelt to fix deprecation warning ([faf842e](#))
- Use the ProjectIterationManager within the Project object ([44f05dc](#))
- **api:** Make description optional for releases ([5579750](#))

Documentation

- **faq:** Describe and group common errors ([4c9a072](#))

7.9.3 v3.12.0 (2022-11-28)

Feature

- Add support for SAML group links ([#2367](#)) ([1020ce9](#))
- **groups:** Add LDAP link manager and deprecate old API endpoints ([3a61f60](#))
- **groups:** Add support for listing ldap_group_links ([#2371](#)) ([ad7c8fa](#))
- Implement secure files API ([d0a0348](#))
- **ci:** Re-Run Tests on PR Comment workflow ([@34cde3](#))
- **api:** Add support for getting a project's pull mirror details ([@60cf0e1](#))
- **api:** Add support for remote project import from AWS S3 ([#2357](#)) ([892281e](#))
- **api:** Add support for remote project import ([#2348](#)) ([e5dc72d](#))
- **api:** Add application statistics ([6fcf3b6](#))

Fix

- **cli:** Enable debug before doing auth ([65abb85](#))
- **cli:** Expose missing mr_default_target_self project attribute ([12aea32](#))
- Use POST method and return dict in cancel_merge_when_pipeline_succeeds() ([#2350](#)) ([bd82d74](#))

Documentation

- Use the term “log file” for getting a job log file ([9d2b1ad](#))
- **groups:** Describe GitLab.com group creation limitation ([9bd433a](#))
- **api:** Pushrules remove saying None is returned when not found ([c3600b4](#))

7.9.4 v3.11.0 (2022-10-28)

Feature

- **build:** Officially support Python 3.11 ([74f66c7](#))
- **api:** Add support for topics merge API ([9a6d197](#))

Fix

- Remove `project.approvals.set_approvals()` method ([91f08f0](#))
- Use epic id instead of iid for epic notes ([97cae38](#))
- **cli:** Handle list response for json/yaml output ([9b88132](#))
- Intermittent failure in `test_merge_request_reset_approvals` ([3dde36e](#))

Documentation

- **advanced:** Add hint on type narrowing ([a404152](#))
- Add minimal docs about the `enable_debug()` method ([b4e9ab7](#))
- **commits:** Fix commit create example for binary content ([bcc1eb4](#))
- **readme:** Add a basic feature list ([b4d53f1](#))
- **api:** Describe use of lower-level methods ([b7a6874](#))
- **api:** Describe the `list()` and `all()` runners' functions ([b6cc3f2](#))
- **api:** Update `merge_requests.rst`: `mr_id` to `mr_iid` ([b32234d](#))

7.9.5 v3.10.0 (2022-09-28)

Feature

- Add `reset_approvals` api ([88693ff](#))
- Add support for deployment approval endpoint ([9c9eeb9](#))

Fix

- **cli:** Add missing attributes for creating MRs ([1714d0a](#))
- **cli:** Add missing attribute for MR changes ([20c46a0](#))

7.9.6 v3.9.0 (2022-08-28)

Feature

- Add support for `merge_base` API ([dd4fb5d](#))

7.9.7 v3.8.1 (2022-08-10)

Fix

- **client:** Do not assume user attrs returned for auth() ([a07547c](#))

7.9.8 v3.8.0 (2022-08-04)

Feature

- **client:** Warn user on misconfigured URL in auth() ([0040b43](#))
- Support downloading archive subpaths ([cadb0e5](#))

Fix

- **client:** Ensure encoded query params are never duplicated ([1398426](#))
- Optionally keep user-provided base URL for pagination ([#2149](#)) ([e2ea8b8](#))

Documentation

- Describe self-revoking personal access tokens ([5ea48fc](#))

7.9.9 v3.7.0 (2022-07-28)

Feature

- Allow sort/ordering for project releases ([b1dd284](#))
- **cli:** Add a custom help formatter ([005ba93](#))
- Add support for iterations API ([194ee01](#))
- **groups:** Add support for shared projects API ([66461ba](#))
- **issues:** Add support for issue reorder API ([8703324](#))
- **namespaces:** Add support for namespace existence API ([4882cb2](#))
- Add support for group and project invitations API ([7af3d340](#))
- **projects:** Add support for project restore API ([4794ecc](#))
- Add support for filtering jobs by scope ([0e1c0dd](#))
- Add `asdict()` and `to_json()` methods to Gitlab Objects ([08ac071](#))
- **api:** Add support for instance-level registry repositories ([284d739](#))
- **groups:** Add support for group-level registry repositories ([70148c6](#))
- Add ‘merge_pipelines_enabled’ project attribute ([fc33c93](#))
- Support validating CI lint results ([3b1ede4](#))
- **cli:** Add support for global CI lint ([3f67c4b](#))
- **objects:** Add Project CI Lint support ([b213dd3](#))

- Add support for group push rules ([b5cdc09](#))
- **api:** Add support for get for a MR approval rule ([89c18c6](#))

Fix

- Support array types for most resources ([d9126cd](#))
- Use the [] after key names for array variables in `params` ([1af44ce](#))
- **runners:** Fix listing for /runners/all ([c6dd57c](#))
- **config:** Raise error when gitlab id provided but no config section found ([1ef7018](#))
- **config:** Raise error when gitlab id provided but no config file found ([ac46c1c](#))
- Add `get_all` param (and `--get-all`) to allow passing `all` to API ([7c71d5d](#))
- Results returned by `attributes` property to show updates ([e5afffc8](#))
- Enable epic notes ([5fc3216](#))
- **cli:** Remove irrelevant MR approval rule list filters ([0daec5f](#))
- Ensure path elements are escaped ([5d9c198](#))

Documentation

- **cli:** Showcase use of token scopes ([4a6f8d6](#))
- **projects:** Document export with upload to URL ([03f5484](#))
- Describe fetching existing export status ([9c5b8d5](#))
- **authors:** Add John ([e2afb84](#))
- Document CI Lint usage ([d5de4b1](#))
- **users:** Add docs about listing a user's projects ([065a1a5](#))
- Update return type of pushrules ([53cbecc](#))
- Describe ROPC flow in place of password authentication ([91c17b7](#))
- **readme:** Remove redundant -v that breaks the command ([c523e18](#))

7.9.10 v3.6.0 (2022-06-28)

Feature

- **downloads:** Allow streaming downloads access to response iterator (#1956) ([b644721](#))
- **api:** Support head() method for get and list endpoints ([ce9216c](#))
- **api:** Implement HEAD method ([90635a7](#))
- **users:** Add approve and reject methods to User ([f57139d](#))
- **api:** Convert gitlab.const to Enums ([c3c6086](#))
- Add support for Protected Environments ([1dc9d0f](#))
- **users:** Add ban and unban methods ([0d44b11](#))

- **docker:** Provide a Debian-based slim image ([384031c](#))
- Support mutually exclusive attributes and consolidate validation to fix board lists (#2037) ([3fa330c](#))
- **client:** Introduce `iterator=True` and deprecate `as_list=False` in `list()` ([cdc6605](#))

Fix

- **base:** Do not fail `repr()` on lazy objects ([1efb123](#))
- **cli:** Project-merge-request-approval-rule ([15a242c](#))
- **cli:** Fix project export download for CLI ([5d14867](#))

Documentation

- **api:** Add separate section for advanced usage ([22ae101](#))
- **api:** Document usage of `head()` methods ([f555bfb](#))
- **projects:** Provide more detailed import examples ([8f8611a](#))
- **projects:** Document 404 gotcha with unactivated integrations ([522ecff](#))
- **variables:** Instruct users to follow GitLab rules for values ([194b6be](#))
- **api:** Stop linking to python-requests.org ([49c7e83](#))
- **api:** Fix incorrect docs for `merge_request_approvals` (#2094) ([5583eaa](#))
- **api-usage:** Add import `os` in example ([2194a44](#))
- Drop deprecated `setuptools build_sphinx` ([048d66a](#))
- **usage:** Refer to upstream docs instead of custom attributes ([ae7d3b0](#))
- **ext:** Fix rendering for `RequiredOptional` dataclass ([4d431e5](#))
- Documentation updates to reflect addition of mutually exclusive attributes ([24b720e](#))
- Use `as_list=False` or `all=True` in Getting started ([de8c6e8](#))

7.9.11 v3.5.0 (2022-05-28)

Feature

- **objects:** Support get project storage endpoint ([8867ee5](#))
- Display human-readable attribute in `repr()` if present ([6b47c26](#))
- **ux:** Display `project.name_with_namespace` on project `repr` ([e598762](#))

Fix

- **cli:** Changed default allow_abbrev value to fix arguments collision problem (#2013) ([d68cacf](#))
- Duplicate subparsers being added to argparse ([f553fd3](#))

Documentation

- Update issue example and extend API usage docs ([aad71d2](#))
- **CONTRIBUTING.rst:** Fix link to conventional-changelog commit format documentation ([2373a4f](#))
- Add missing Admin access const value ([3e0d4d9](#))
- **merge_requests:** Add new possible merge request state and link to the upstream docs ([e660fa8](#))

7.9.12 v3.4.0 (2022-04-28)

Feature

- Emit a warning when using a list() method returns max ([1339d64](#))
- **objects:** Support getting project/group deploy tokens by id ([fcd37fe](#))
- **user:** Support getting user SSH key by id ([6f93c05](#))
- **api:** Re-add topic delete endpoint ([d1d96bd](#))

Fix

- Add ChunkedEncodingError to list of retryable exceptions ([7beb20f](#))
- Avoid passing redundant arguments to API ([3431887](#))
- **cli:** Add missing filters for project commit list ([149d244](#))
- Add 52x range to retry transient failures and tests ([c3ef1b5](#))
- Also retry HTTP-based transient errors ([3b49e4d](#))

Documentation

- **api-docs:** Docs fix for application scopes ([e1ad93d](#))

7.9.13 v3.3.0 (2022-03-28)

Feature

- **object:** Add pipeline test report summary support ([a97e0cf](#))

Fix

- Support RateLimit-Reset header ([4060146](#))

Documentation

- Fix typo and incorrect style ([2828b10](#))
- Add pipeline test report summary support ([d78afb3](#))
- **chore:** Include docs .js files in sdist ([3010b40](#))

7.9.14 v3.2.0 (2022-02-28)

Feature

- **merge_request_approvals:** Add support for deleting MR approval rules ([85a734f](#))
- **artifacts:** Add support for project artifacts delete API ([c01c034](#))
- **mixins:** Allow deleting resources without IDs ([0717517](#))
- **objects:** Add a complete artifacts manager ([c8c2fa7](#))

Fix

- **services:** Use slug for id_attr instead of custom methods ([e30f39d](#))
- Remove custom delete method for labels ([0841a2a](#))

Documentation

- Enable gitter chat directly in docs ([bd1ecdd](#))
- Add delete methods for runners and project artifacts ([5e711fd](#))
- Add retry_transient infos ([bb1f054](#))
- Add transient errors retry info ([b7a1266](#))
- **artifacts:** Deprecate artifacts() and artifact() methods ([64d01ef](#))
- Revert “chore: add temporary banner for v3” ([#1864](#)) ([7a13b9b](#))

7.9.15 v3.1.1 (2022-01-28)

Fix

- **cli:** Make ‘per_page’ and ‘page’ type explicit ([d493a5e](#))
- **cli:** Make ‘timeout’ type explicit ([bbb7df5](#))
- **cli:** Allow custom methods in managers ([8dfed0c](#))
- **objects:** Make resource access tokens and repos available in CLI ([e0a3a41](#))

Documentation

- Enhance release docs for CI_JOB_TOKEN usage ([5d973de](#))
- **changelog:** Add missing changelog items ([01755fb](#))

7.9.16 v3.1.0 (2022-01-14)

Feature

- add support for Group Access Token API ([c01b7c4](#))
- Add support for Groups API method `transfer()` ([0007006](#))
- **api:** Add `project.transfer()` and deprecate `transfer_project()` ([259668a](#))
- **api:** Return result from `SaveMixin.save()` ([e6258a4](#))

Fix

- **cli:** Add missing list filters for environments ([6f64d40](#))
- Use url-encoded ID in all paths ([12435d7](#))
- **members:** Use new *All objects for *AllManager managers ([755e0a3](#))
- **api:** Services: add missing `lazy` parameter ([888f332](#))
- broken URL for FAQ about attribute-error-list ([1863f30](#))
- remove default arguments for `mergerequests.merge()` ([8e589c4](#))
- remove custom URL encoding ([3d49e5e](#))

Documentation

- **cli:** make examples more easily navigable by generating TOC ([f33c523](#))
- update project access token API reference link ([73ae955](#))

7.9.17 v3.0.0 (2022-01-05)

Feature

- **docker:** Remove custom entrypoint from image ([80754a1](#))
- **cli:** Allow options from args and environment variables ([ca58008](#))
- **api:** Support file format for repository archive ([83dcabf](#))
- Add support for `squash_option` in Projects ([a246ce8](#))
- **cli:** Do not require config file to run CLI ([92a893b](#))
- **api:** Add support for Topics API ([e7559bf](#))
- Add delete on `package_file` object ([124667b](#))
- Add support for `projects.groups.list()` ([68ff595](#))

- **api:** Add support for epic notes ([7f4edb5](#))
- Remove support for Python 3.6, require 3.7 or higher ([414009d](#))
- **api:** Add project milestone promotion ([f068520](#))
- **api:** Add merge trains ([fd73a73](#))
- **api:** Add merge request approval state ([f41b093](#))
- **api:** Add project label promotion ([6d7c88a](#))
- **objects:** Support delete package files API ([4518046](#))
- **objects:** List starred projects of a user ([47a5606](#))
- **build:** Officially support and test python 3.10 ([c042ddc](#))
- **objects:** Support Create and Revoke personal access token API ([e19314d](#))
- Default to gitlab.com if no URL given ([8236281](#))
- Allow global retry_transient_errors setup ([3b1d3a4](#))

Fix

- Handle situation where GitLab does not return values ([cb824a4](#))
- Stop encoding ‘.’ to ‘%2E’ ([702e41d](#))
- **build:** Do not include docs in wheel package ([68a97ce](#))
- **api:** Delete invalid ‘project-runner get’ command (#1628) ([905781b](#))
- **api:** Replace deprecated attribute in delete_in_bulk() (#1536) ([c59fbdb](#))
- **objects:** Rename confusing to_project_id argument ([ce4bc0d](#))
- Raise error if there is a 301/302 redirection ([d56a434](#))
- **build:** Do not package tests in wheel ([969dccc](#))

Breaking

- The gitlab CLI will now accept CLI arguments and environment variables for its global options in addition to configuration file options. This may change behavior for some workflows such as running inside GitLab CI and with certain environment variables configured. ([ca58008](#))
- stop encoding ‘.’ to ‘%2E’. This could potentially be a breaking change for users who have incorrectly configured GitLab servers which don’t handle period ‘.’ characters correctly. ([702e41d](#))
- A config file is no longer needed to run the CLI. python-gitlab will default to https://gitlab.com with no authentication if there is no config file provided. python-gitlab will now also only look for configuration in the provided PYTHON_GITLAB_CFG path, instead of merging it with user- and system-wide config files. If the environment variable is defined and the file cannot be opened, python-gitlab will now explicitly fail. ([92a893b](#))
- As of python-gitlab 3.0.0, Python 3.6 is no longer supported. Python 3.7 or higher is required. ([414009d](#))
- As of python-gitlab 3.0.0, the default branch for development has changed from master to main. ([545f8ed](#))
- remove deprecated branch protect methods in favor of the more complete protected branches API. ([9656a16](#))
- The deprecated name_regex attribute has been removed in favor of name_regex_delete. (see <https://gitlab.com/gitlab-org/gitlab/-/commit/ce99813cf54>) ([c59fbdb](#))

- rename confusing `to_project_id` argument in `transfer_project` to `project_id` (`--project-id` in CLI). This is used for the source project, not for the target namespace. ([ce4bc0d](#))
- remove deprecated constants defined in `gitlab.v4.objects`, and use only `gitlab.const` module ([3f320af](#))
- remove deprecated tag release API. This was removed in GitLab 14.0 ([2b8a94a](#))
- remove deprecated `project.issuesstatistics` in favor of `project.issues_statistics` ([ca7777e](#))
- remove deprecated `members.all()` method in favor of `members_all.list()` ([4d7b848](#))
- remove deprecated `pipelines()` methods in favor of `pipelines.list()` ([c4f5ec6](#))
- python-gitlab will now default to `gitlab.com` if no URL is given ([8236281](#))
- raise error if there is a 301/302 redirection ([d56a434](#))

Documentation

- Switch to Furo and refresh introduction pages ([ee6b024](#))
- Correct documentation for updating discussion note ([ee66f4a](#))
- Rename documentation files to match names of code files ([ee3f865](#))
- **project:** Remove redundant encoding parameter ([fed613f](#))
- Use annotations for return types ([79e785e](#))
- Update docs to use `gitlab.const` for constants ([b3b0b5f](#))
- Only use type annotations for documentation ([b7dde0d](#))
- Add links to the GitLab API docs ([e3b5d27](#))
- Fix API delete key example ([b31bb05](#))
- **pipelines:** Document `take_ownership` method ([69461f6](#))
- **api:** Document the update method for project variables ([7992911](#))
- **api:** Clarify job token usage with `auth()` ([3f423ef](#))
- Fix a few typos ([7ea4ddc](#))
- Consolidate changelogs and remove v3 API docs ([90da8ba](#))
- Correct documented return type ([acabf63](#))

7.9.18 v2.10.1 (2021-08-28)

Fix

- **mixins:** Improve deprecation warning ([57e0187](#))
- **deps:** Upgrade requests to 2.25.0 (see CVE-2021-33503) ([ce995b2](#))

Documentation

- **mergequests:** Gl.mergequests.list documentation was missleading ([5b5a7bc](#))

7.9.19 v2.10.0 (2021-07-28)

Feature

- **api:** Add merge_ref for merge requests ([1e24ab2](#))
- **api:** Add name_regex_keep attribute in delete_in_bulk() ([e49ff3f](#))

Fix

- **api:** Do not require Release name for creation ([98cd03b](#))

Documentation

- **readme:** Move contributing docs to CONTRIBUTING.rst ([edf49a3](#))
- Add example for mr.merge_ref ([b30b8ac](#))
- **project:** Add example on getting a single project using name with namespace ([ef16a97](#))

7.9.20 v2.9.0 (2021-06-28)

Feature

- **release:** Allow to update release ([b4c4787](#))
- **api:** Add group hooks ([4a7e9b8](#))
- **api:** Remove responsibility for API inconsistencies for MR reviewers ([3d985ee](#))
- **api:** Add MR pipeline manager and deprecate pipelines() method ([954357c](#))
- **api:** Add support for creating/editing reviewers in project merge requests ([676d1f6](#))

Documentation

- **tags:** Remove deprecated functions ([1b1a827](#))
- **release:** Add update example ([6254a5f](#))
- Make Gitlab class usable for intersphinx ([8753add](#))

7.9.21 v2.8.0 (2021-06-10)

Feature

- Add keys endpoint (a81525a)
- **objects:** Add support for Group wikis (#1484) (74f5e62)
- **objects:** Add support for generic packages API (79d88bd)
- **api:** Add deployment mergerequests interface (fbcbc0d4)
- **objects:** Support all issues statistics endpoints (f731707)
- **objects:** Add support for descendant groups API (1b70580)
- **objects:** Add pipeline test report support (ee9f96e)
- **objects:** Add support for billable members (fb0b083)
- Add feature to get inherited member for project/group (e444b39)
- Add code owner approval as attribute (fdc46ba)
- Indicate that we are a typed package (e4421ca)
- Add support for lists of integers to ListAttribute (115938b)

Fix

- Catch invalid type used to initialize RESTObject (c7bcc25)
- Functional project service test (#1500) (093db9d)
- Ensure kwargs are passed appropriately for ObjectDeleteMixin (4e690c2)
- **cli:** Add missing list filter for jobs (b3d1c26)
- Change mr.merge() to use ‘post_data’ (cb6a3c6)
- **cli:** Fix parsing CLI objects to classnames (4252070)
- **objects:** Return server data in cancel/retry methods (9fed061)
- **objects:** Add missing group attributes (d20ff4f)
- **objects:** Allow lists for filters for in all objects (603a351)
- Iids not working as a list in projects.issues.list() (45f806c)
- Add a check to ensure the MRO is correct (565d548)

Documentation

- Fix typo in http_delete docstring (5226f09)
- **api:** Add behavior in local attributes when updating objects (38f65e8)
- Fail on warnings during sphinx build (cbd4d52)

7.9.22 v2.7.1 (2021-04-26)

- fix(files): do not url-encode file paths twice

7.9.23 v2.7.0 (2021-04-25)

Bug Fixes

- update user's bool data and avatar (3ba27ffb)
- argument type was not a tuple as expected (062f8f6a)
- correct some type-hints in gitlab/mixins.py (8bd31240)
- only append kwargs as query parameters (b9ecc9a8)
- only add query_parameters to GitlabList once (1386)
- checking if RESTManager._from_parentAttrs is set (8224b406)
- handling config value in _get_values_from_helper (9dfb4cd9)
- let the homedir be expanded in path of helper (fc7387a0)
- make secret helper more user friendly (fc2798fc)
- linting issues and test (b04dd2c0)
- handle tags like debian/2%2.6-21 as identifiers (b4dac5ce)
- remove duplicate class definitions in v4/objects/users.py (7c4e6259)
- wrong variable name (15ec41ca)
- tox pep8 target, so that it can run (f518e87b)
- undefined name errors (48ec9e0f)
- extend wait timeout for test_delete_user() (19fde8ed)
- test_update_group() dependency on ordering (e78a8d63)
- honor parameter value passed (c2f8f0e7)
- **objects:** add single get endpoint for instance audit events (c3f0a6f1)
- **types:** prevent **dir** from producing duplicates (5bf7525d)

Features

- add ProjectPackageFile (#1372)
- add option to add a helper to lookup token (8ecf5592)
- add project audit endpoint (6660dbef)
- add personal access token API (2bb16fac)
- add import from bitbucket server (ff3013a2)
- **api,cli:** make user agent configurable (4bb201b9)
- **issues:** add missing get verb to IssueManager (f78ebe06)
- **objects:**

- add support for resource state events API (d4799c40)
- add support for group audit events API (2a0fbdf9)
- add Release Links API support (28d75181)
- **projects:** add project access token api (1becef02)
- **users:** add follow/unfollow API (e456869d)

Documentation

- correct ProjectFile.decode() documentation (b180bafcd)
- update doc for token helper (3ac6fa12)
- better real life token lookup example (9ef83118)

7.9.24 v2.6.0 (2021-01-29)

Features

- support multipart uploads (2fa3004d)
- add MINIMAL_ACCESS constant (49eb3ca7)
- unit tests added (f37ebf5f)
- added support for pipeline bridges (05cbdc22)
- adds support for project merge request approval rules (#1199) (c6fbf399)
- **api:**
 - added wip filter param for merge requests (d6078f80)
 - added wip filter param for merge requests (aa6e80d5)
 - add support for user identity provider deletion (e78e1215)
- **tests:** test label getter (a41af902)

Bug Fixes

- docs changed using the consts (650b65c3)
- typo (9baa9053)
- **api:**
 - use RetrieveMixin for ProjectLabelManager (1a143952)
 - add missing runner access_level param (92669f2e)
- **base:** really refresh object (e1e0d8cb), closes (#1155)
- **cli:**
 - write binary data to stdout buffer (0733ec6c)
 - add missing args for project lists (c73e2374)

7.9.25 v2.5.0 (2020-09-01)

Features

- add support to resource milestone events (88f8cc78), closes #1154
- add share/unshare group with group (7c6e541d)
- add support for instance variables (4492fc42)
- add support for Packages API (71495d12)
- add endpoint for latest ref artifacts (b7a07fca)

Bug Fixes

- wrong reconfirmation parameter when updating user's email (b5c267e1)
- tests fail when using REUSE_CONTAINER option (0078f899, closes #1146)
- implement Gitlab's behavior change for owned=True (99777991)

7.9.26 v2.4.0 (2020-07-09)

Bug Fixes

- do not check if kwargs is none (a349b90e)
- make query kwargs consistent between call in init and next (72ffa016)
- pass kwargs to subsequent queries in gitlab list (1d011ac7)
- **merge:** parse arguments as query_data (878098b7)

Features

- add NO_ACCESS const (dab4d0a1)
- add masked parameter for variables command (b6339bf8)

7.9.27 v2.3.1 (2020-06-09)

- revert keyset pagination by default

7.9.28 v2.3.0 (2020-06-08)

Features

- add group runners api (49439916)
- add play command to project pipeline schedules (07b99881)
- allow an environment variable to specify config location (401e702a)
- **api:** added support in the GroupManager to upload Group avatars (28eb7eab)

- **services:** add project service list API (fc522218)
- **types:** add `dir` to RESTObject to expose attributes (cad134c0)

Bug Fixes

- use keyset pagination by default for /projects > 50000 (f86ef3bb)
- **config:** fix duplicate code (ee2df6f1), closes (#1094)
- **project:** add missing project parameters (ad8c67d6)

7.9.29 v2.2.0 (2020-04-07)

Bug Fixes

- add missing import_project param (9b16614b)
- **types:** do not split single value string in ListAttribute (a26e5858)

Features

- add commit GPG signature API (da7a8097)
- add create from template args to ProjectManager (f493b73e)
- add remote mirrors API (#1056) (4cfaa2fd)
- add Gitlab Deploy Token API (01de524c)
- add Group Import/Export API (#1037) (6cb9d923)

7.9.30 v2.1.2 (2020-03-09)

Bug Fixes

- Fix regression, when using keyset pagination with merge requests. Related to <https://github.com/python-gitlab/python-gitlab/issues/1044>

7.9.31 v2.1.1 (2020-03-09)

Bug Fixes

users: update user attributes

This change was made to mitigate an issue in Gitlab (again). Fix available in: https://gitlab.com/gitlab-org/gitlab-/merge_requests/26792

7.9.32 v2.1.0 (2020-03-08)

Bug Fixes

- do not require empty data dict for create() (99d959f7)
- remove trailing slashes from base URL (#913) (2e396e4a)
- return response with commit data (b77b945c)
- remove null values from features POST data, because it fails with HTTP 500 (1ec1816d)
- **docs:**
 - fix typo in user memberships example (33889bcb)
 - update to new set approvers call for # of approvers (8e0c5262)
 - update docs and tests for set_approvers (2cf12c79)
- **objects:**
 - add default name data and use http post (70c0cfb6)
 - update set_approvers function call (65ecadcf)
 - update to new gitlab api for path, and args (e512cddd)

Features

- add support for user memberships API (#1009) (c313c2b0)
- add support for commit revert API (#991) (5298964e)
- add capability to control GitLab features per project or group (7f192b4f)
- use keyset pagination by default for all=True (99b4484d)
- add support for GitLab OAuth Applications API (4e12356d)

7.9.33 v2.0.1 (2020-02-05)

Changes

- **users:** update user attributes

This change was made to mitigate an issue in GitLab. See: <https://gitlab.com/gitlab-org/gitlab/issues/202070>

7.9.34 v2.0.0 (2020-01-26)

This releases drops support for python < 3.6

Bug Fixes

- **projects:** adjust snippets to match the API (e104e213)

Features

- add global order_by option to ease pagination (d1879253)
- support keyset pagination globally (0b71ba4d)
- add appearance API (4c4ac5ca)
- add autocompletion support (973cb8b9)

7.9.35 v1.15.0 (2019-12-16)

Bug Fixes

- ignore all parameter, when as_list=True 137d72b3, closes #962

Features

- allow cfg timeout to be overridden via kwargs e9a8289a
- add support for /import/github aa4d41b7
- nicer stacktrace 697cda24
- retry transient HTTP errors 59fe2714, closes #970
- access project's issues statistics 482e57ba, closes #966
- adding project stats db0b00a9, closes #967
- add variable_type/protected to projects ci variables 4724c50e
- add variable_type to groups ci variables 0986c931

7.9.36 v1.14.0 (2019-12-07)

Bug Fixes

- added missing attributes for project approvals 460ed63c
- **labels:** ensure label.save() works 727f5361
- **project-fork:**
 - copy create fix from ProjectPipelineManager 516307f1
 - correct path computation for project-fork list 44a7c278

Features

- add audit endpoint 2534020b
- add project and group clusters ebd053e7
- add support for include_subgroups filter abcd83f

7.9.37 v1.13.0 (2019-11-02)

Features

- add users activate, deactivate functionality (32ad6692)
- send python-gitlab version as user-agent (c22d49d0)
- add deployment creation (ca256a07), closes [#917]
- **auth:** remove deprecated session auth (b751cdf4)
- **doc:** remove refs to api v3 in docs (6beeaa99)
- **test:** unused unittest2, type -> isinstance (33b18012)

Bug Fixes

- **projects:** support approval_rules endpoint for projects (2cef2bb4)

7.9.38 v1.12.1 (2019-10-07)

Bug Fixes

fix: fix not working without auth provided

7.9.39 v1.12.0 (2019-10-06)

Features

- add support for job token
- **project:**
 - implement update_submodule
 - add file blame api
- **user:** add status api

Bug Fixes

- **cli:** fix cli command user-project list
- **labels:** don't mangle label name on update
- **todo:** mark_all_as_done doesn't return anything

7.9.40 v1.11.0 (2019-08-31)

Features

- add methods to retrieve an individual project environment
- group labels with subscriptable mixin

Bug Fixes

- projects: avatar uploading for projects
- remove empty list default arguments
- remove empty dict default arguments
- add project and group label update without id to fix cli

7.9.41 v1.10.0 (2019-07-22)

Features

- add mr rebase method bc4280c2
- get artifact by ref and job cda11745
- add support for board update 908d79fa, closes #801
- add support for issue.related_merge_requests 90a36315, closes #794

Bug Fixes

- improve pickle support b4b5decb
- **cli:**
 - allow –recursive parameter in repository tree 7969a78c, closes #718, #731
 - don't fail when the short print attr value is None 8d1552a0, closes #717, #727
 - fix update value for key not working b7662039

7.9.42 v1.9.0 (2019-06-19)

Features

- implement artifacts deletion
- add endpoint to get the variables of a pipeline
- delete ProjectPipeline
- implement **eq** and **hash** methods
- Allow runpy invocation of CLI tool (python -m gitlab)
- add project releases api
- merged new release & registry apis

Bug Fixes

- convert # to %23 in URLs
- pep8 errors
- use python2 compatible syntax for super
- Make MemberManager.all() return a list of objects
-
- Re-enable command specific help messages
- dont ask for id attr if this is *Manager originating custom action
- fix -/_ replacement for *Manager custom actions
- fix repository_id marshaling in cli
- register cli action for delete_in_bulk

7.9.43 v1.8.0 (2019-02-22)

- docs(setup): use proper readme on PyPI
- docs(readme): provide commit message guidelines
- fix(api): make reset_time_estimate() work again
- fix: handle empty ‘Retry-After’ header from GitLab
- fix: remove decode() on error_message string
- chore: release tags to PyPI automatically
- fix(api): avoid parameter conflicts with python and gitlab
- fix(api): Don’t try to parse raw downloads
- feat: Added approve & unapprove method for Mergerequests
- fix all kwarg behaviour

7.9.44 v1.7.0 (2018-12-09)

- **docs:** Fix the owned/starred usage documentation
- **docs:** Add a warning about http to https redirects
- Fix the https redirection test
- **docs:** Add a note about GroupProject limited API
- Add missing comma in ProjectIssueManager _create_attrs
- More flexible docker image
- Add project protected tags management
- **cli:** Print help and usage without config file
- Rename MASTER_ACCESS to MAINTAINER_ACCESS
- **docs:** Add docs build information
- Use docker image with current sources
- **docs:** Add PyYAML requirement notice
- Add Gitter badge to README
- **docs:** Add an example of pipeline schedule vars listing
- **cli:** Exit on config parse error, instead of crashing
- Add support for resource label events
- **docs:** Fix the milestone filetring doc (iid -> iids)
- **docs:** Fix typo in custom attributes example
- Improve error message handling in exceptions
- Add support for members all() method
- Add access control options to protected branch creation

7.9.45 v1.6.0 (2018-08-25)

- **docs:** Don't use hardcoded values for ids
- **docs:** Improve the snippets examples
- **cli:** Output: handle bytes in API responses
- **cli:** Fix the case where we have nothing to print
- Project import: fix the override_params parameter
- Support group and global MR listing
- Implement MR.pipelines()
- MR: add the squash attribute for create/update
- Added support for listing forks of a project
- **docs:** Add/update notes about read-only objects
- Raise an exception on https redirects for PUT/POST

- **docs:** Add a FAQ
- **cli:** Fix the project-export download

7.9.46 v1.5.1 (2018-06-23)

- Fix the ProjectPipelineJob base class (regression)

7.9.47 v1.5.0 (2018-06-22)

- Drop API v3 support
- Drop GetFromListMixin
- Update the sphinx extension for v4 objects
- Add support for user avatar upload
- Add support for project import/export
- Add support for the search API
- Add a global per_page config option
- Add support for the discussions API
- Add support for merged branches deletion
- Add support for Project badges
- Implement user_agent_detail for snippets
- Implement commit.refs()
- Add commit.merge_requests() support
- Deployment: add list filters
- Deploy key: add missing attributes
- Add support for environment stop()
- Add feature flags deletion support
- Update some group attributes
- Issues: add missing attributes and methods
- Fix the participants() decorator
- Add support for group boards
- Implement the markdown rendering API
- Update MR attributes
- Add pipeline listing filters
- Add missing project attributes
- Implement runner jobs listing
- Runners can be created (registered)
- Implement runner token validation
- Update the settings attributes

- Add support for the gitlab CI lint API
- Add support for group badges
- Fix the IssueManager path to avoid redirections
- time_stats(): use an existing attribute if available
- Make ProjectCommitStatus.create work with CLI
- Tests: default to python 3
- ProjectPipelineJob was defined twice
- Silence logs/warnings in unittests
- Add support for MR approval configuration (EE)
- Change post_data default value to None
- Add geo nodes API support (EE)
- Add support for issue links (EE)
- Add support for LDAP groups (EE)
- Add support for board creation/deletion (EE)
- Add support for Project.pull_mirror (EE)
- Add project push rules configuration (EE)
- Add support for the EE license API
- Add support for the LDAP groups API (EE)
- Add support for epics API (EE)
- Fix the non-verbose output of ProjectCommitComment

7.9.48 v1.4.0 (2018-05-19)

- Require requests>=2.4.2
- ProjectKeys can be updated
- Add support for unsharing projects (v3/v4)
- **cli:** fix listing for json and yaml output
- Fix typos in documentation
- Introduce RefreshMixin
- **docs:** Fix the time tracking examples
- **docs:** Commits: add an example of binary file creation
- **cli:** Allow to read args from files
- Add support for recursive tree listing
- **cli:** Restore the –help option behavior
- Add basic unit tests for v4 CLI
- **cli:** Fix listing of strings
- Support downloading a single artifact file

- Update docs copyright years
- Implement attribute types to handle special cases
- **docs:** fix GitLab reference for notes
- Expose additional properties for Gitlab objects
- Fix the impersonation token deletion example
- feat: obey the rate limit
- Fix URL encoding on branch methods
- **docs:** add a code example for listing commits of a MR
- **docs:** update service.available() example for API v4
- **tests:** fix functional tests for python3
- api-usage: bit more detail for listing with all
- More efficient .get() for group members
- Add docs for the `files` arg in `http_*`
- Deprecate GetFromListMixin

7.9.49 v1.3.0 (2018-02-18)

- Add support for pipeline schedules and schedule variables
- Clarify information about supported python version
- Add manager for jobs within a pipeline
- Fix wrong tag example
- Update the groups documentation
- Add support for MR participants API
- Add support for getting list of user projects
- Add Gitlab and User events support
- Make trigger_pipeline return the pipeline
- Config: support api_version in the global section
- Gitlab can be used as context manager
- Default to API v4
- Add a simplified example for streamed artifacts
- Add documentation about labels update

7.9.50 v1.2.0 (2018-01-01)

- Add mattermost service support
- Add users custom attributes support
- **doc:** Fix project.triggers.create example with v4 API
- Oauth token support
- Remove deprecated objects/methods
- Rework authentication args handling
- Add support for oauth and anonymous auth in config/CLI
- Add support for impersonation tokens API
- Add support for user activities
- Update user docs with gitlab URLs
- **docs:** Bad arguments in projects file documentation
- Add support for user_agent_detail (issues)
- Add a SetMixin
- Add support for project housekeeping
- Expected HTTP response for subscribe is 201
- Update pagination docs for ProjectCommit
- Add doc to get issue from iid
- Make todo() raise GitlabTodoError on error
- Add support for award emojis
- Update project services docs for v4
- Avoid sending empty update data to issue.save
- **docstrings:** Explicitly document pagination arguments
- **docs:** Add a note about password auth being removed from GitLab
- Submanagers: allow having undefined parameters
- ProjectFile.create(): don't modify the input data
- Update testing tools for /session removal
- Update groups tests
- Allow per_page to be used with generators
- Add groups listing attributes
- Add support for subgroups listing
- Add supported python versions in setup.py
- Add support for pagesdomains
- Add support for features flags
- Add support for project and group custom variables
- Add support for user/group/project filter by custom attribute

- Respect content of REQUESTS_CA_BUNDLE and *_proxy envvars

7.9.51 v1.1.0 (2017-11-03)

- Fix trigger variables in v4 API
- Make the delete() method handle / in ids
- **docs:** update the file upload samples
- Tags release description: support / in tag names
- **docs:** improve the labels usage documentation
- Add support for listing project users
- ProjectFileManager.create: handle / in file paths
- Change ProjectUser and GroupProject base class
- **docs:** document get_create_attrs in the API tutorial
- Document the Gitlab session parameter
- ProjectFileManager: custom update() method
- Project: add support for printing_merge_request_link_enabled attr
- Update the ssl_verify docstring
- Add support for group milestones
- Add support for GPG keys
- Add support for wiki pages
- Update the repository_blob documentation
- Fix the CLI for objects without ID (API v4)
- Add a contributed Dockerfile
- Pagination generators: expose more information
- Module's base objects serialization
- **doc:** Add sample code for client-side certificates

7.9.52 v1.0.2 (2017-09-29)

- **docs:** remove example usage of submanagers
- Properly handle the labels attribute in ProjectMergeRequest
- ProjectFile: handle / in path for delete() and save()

7.9.53 v1.0.1 (2017-09-21)

- Tags can be retrieved by ID
- Add the server response in GitlabError exceptions
- Add support for project file upload
- Minor typo fix in “Switching to v4” documentation
- Fix password authentication for v4
- Fix the labels attrs on MR and issues
- Exceptions: use a proper error message
- Fix http_get method in get artifacts and job trace
- CommitStatus: sha is parent attribute
- Fix a couple listing calls to allow proper pagination
- Add missing doc file

7.9.54 v1.0.0 (2017-09-08)

- Support for API v4. See <http://python-gitlab.readthedocs.io/en/master/switching-to-v4.html>
- Support SSL verification via internal CA bundle
- Docs: Add link to gitlab docs on obtaining a token
- Added dependency injection support for Session
- Fixed repository_compare examples
- Fix changelog and release notes inclusion in sdist
- Missing expires_at in GroupMembers update
- Add lower-level methods for Gitlab()

7.9.55 v0.21.2 (2017-06-11)

- Install doc: use sudo for system commands
- **v4:** Make MR work properly
- Remove extraAttrs argument from _raw_list
- **v4:** Make project issues work properly
- Fix urlencode() usage (python 2/3) (#268)
- Fixed spelling mistake (#269)
- Add new event types to ProjectHook

7.9.56 v0.21.1 (2017-05-25)

- Fix the manager name for jobs in the Project class
- Fix the docs

7.9.57 v0.21 (2017-05-24)

- Add time_stats to ProjectMergeRequest
- Update User options for creation and update (#246)
- Add milestone.merge_requests() API
- Fix docs typo (s/correspnding/corresponding/)
- Support milestone start date (#251)
- Add support for priority attribute in labels (#256)
- Add support for nested groups (#257)
- Make GroupProjectManager a subclass of ProjectManager (#255)
- Available services: return a list instead of JSON (#258)
- MR: add support for time tracking features (#248)
- Fixed repository_tree and repository_blob path encoding (#265)
- Add ‘search’ attribute to projects.list()
- Initial gitlab API v4 support
- Reorganise the code to handle v3 and v4 objects
- Allow 202 as delete return code
- Deprecate parameter related methods in gitlab.Gitlab

7.9.58 v0.20 (2017-03-25)

- Add time tracking support (#222)
- Improve changelog (#229, #230)
- Make sure that manager objects are never overwritten (#209)
- Include chanlog and release notes in docs
- Add DeployKey{,Manager} classes (#212)
- Add support for merge request notes deletion (#227)
- Properly handle extra args when listing with all=True (#233)
- Implement pipeline creation API (#237)
- Fix spent_time methods
- Add ‘delete source branch’ option when creating MR (#241)
- Provide API wrapper for cherry picking commits (#236)
- Stop listing if recursion limit is hit (#234)

7.9.59 v0.19 (2017-02-21)

- Update project.archive() docs
- Support the scope attribute in runners.list()
- Add support for project runners
- Add support for commit creation
- Fix install doc
- Add builds-email and pipelines-email services
- Deploy keys: rework enable/disable
- Document the dynamic aspect of objects
- Add pipeline_events to ProjectHook attrs
- Add due_date attribute to ProjectIssue
- Handle settings.domain_whitelist, partly
- {Project,Group}Member: support expires_at attribute

7.9.60 v0.18 (2016-12-27)

- Fix JIRA service editing for GitLab 8.14+
- Add jira_issue_transition_id to the JIRA service optional fields
- Added support for Snippets (new API in Gitlab 8.15)
- **docs:** update pagination section
- **docs:** artifacts example: open file in wb mode
- **CLI:** ignore empty arguments
- **CLI:** Fix wrong use of arguments
- **docs:** Add doc for snippets
- Fix duplicated data in API docs
- Update known attributes for projects
- sudo: always use strings

7.9.61 v0.17 (2016-12-02)

- README: add badges for pypi and RTD
- Fix ProjectBuild.play (raised error on success)
- Pass kwargs to the object factory
- Add .tox to ignore to respect default tox settings
- Convert response list to single data source for iid requests
- Add support for boards API
- Add support for Gitlab.version()

- Add support for broadcast messages API
- Add support for the notification settings API
- Don't overwrite attributes returned by the server
- Fix bug when retrieving changes for merge request
- Feature: enable / disable the deploy key in a project
- Docs: add a note for python 3.5 for file content update
- ProjectHook: support the token attribute
- Rework the API documentation
- Fix docstring for http_{username,password}
- Build managers on demand on GitlabObject's
- API docs: add managers doc in GitlabObject's
- Sphinx ext: factorize the build methods
- Implement __repr__ for gitlab objects
- Add a 'report a bug' link on doc
- Remove deprecated methods
- Implement merge requests diff support
- Make the manager objects creation more dynamic
- Add support for templates API
- Add attr 'created_at' to ProjectIssueNote
- Add attr 'updated_at' to ProjectIssue
- CLI: add support for project all --all
- Add support for triggering a new build
- Rework requests arguments (support latest requests release)
- Fix should_remove_source_branch

7.9.62 v0.16 (2016-10-16)

- Add the ability to fork to a specific namespace
- JIRA service - add api_url to optional attributes
- Fix bug: Missing coma concatenates array values
- docs: branch protection notes
- Create a project in a group
- Add only_allow_merge_if_build_succeeds option to project objects
- Add support for --all in CLI
- Fix examples for file modification
- Use the plural merge_requests URL everywhere
- Rework travis and tox setup

- Workaround gitlab setup failure in tests
- Add ProjectBuild.erase()
- Implement ProjectBuild.play()

7.9.63 v0.15.1 (2016-10-16)

- docs: improve the pagination section
- Fix and test pagination
- ‘path’ is an existing gitlab attr, don’t use it as method argument

7.9.64 v0.15 (2016-08-28)

- Add a basic HTTP debug method
- Run more tests in travis
- Fix fork creation documentation
- Add more API examples in docs
- Update the ApplicationSettings attributes
- Implement the todo API
- Add sidekiq metrics support
- Move the constants at the gitlab root level
- Remove methods marked as deprecated 7 months ago
- Refactor the Gitlab class
- Remove _get_list_or_object() and its tests
- Fix canGet attribute (typo)
- Remove unused ProjectTagReleaseManager class
- Add support for project services API
- Add support for project pipelines
- Add support for access requests
- Add support for project deployments

7.9.65 v0.14 (2016-08-07)

- Remove ‘next_url’ from kwargs before passing it to the cls constructor.
- List projects under group
- Add support for subscribe and unsubscribe in issues
- Project issue: doc and CLI for (un)subscribe
- Added support for HTTP basic authentication
- Add support for build artifacts and trace

- –title is a required argument for ProjectMilestone
- Commit status: add optional context url
- Commit status: optional get attrs
- Add support for commit comments
- Issues: add optional listing parameters
- Issues: add missing optional listing parameters
- Project issue: proper update attributes
- Add support for project-issue move
- Update ProjectLabel attributes
- Milestone: optional listing attrs
- Add support for namespaces
- Add support for label (un)subscribe
- MR: add (un)subscribe support
- Add note_events to project hooks attributes
- Add code examples for a bunch of resources
- Implement user emails support
- Project: add VISIBILITY_* constants
- Fix the Project.archive call
- Implement archive/unarchive for a project
- Update ProjectSnippet attributes
- Fix ProjectMember update
- Implement sharing project with a group
- Implement CLI for project archive/unarchive/share
- Implement runners global API
- Gitlab: add managers for build-related resources
- Implement ProjectBuild.keep_artifacts
- Allow to stream the downloads when appropriate
- Groups can be updated
- Replace Snippet.Content() with a new content() method
- CLI: refactor _die()
- Improve commit statuses and comments
- Add support from listing group issues
- Added a new project attribute to enable the container registry.
- Add a contributing section in README
- Add support for global deploy key listing
- Add support for project environments

- MR: get list of changes and commits
- Fix the listing of some resources
- MR: fix updates
- Handle empty messages from server in exceptions
- MR (un)subscribe: don't fail if state doesn't change
- MR merge(): update the object

7.9.66 v0.13 (2016-05-16)

- Add support for MergeRequest validation
- MR: add support for cancel_merge_when_build_succeeds
- MR: add support for closes_issues
- Add “external” parameter for users
- Add deletion support for issues and MR
- Add missing group creation parameters
- Add a Session instance for all HTTP requests
- Enable updates on ProjectIssueNotes
- Add support for Project raw_blob
- Implement project compare
- Implement project contributors
- Drop the next_url attribute when listing
- Remove unnecessary canUpdate property from ProjectIssuesNote
- Add new optional attributes for projects
- Enable deprecation warnings for gitlab only
- Rework merge requests update
- Rework the Gitlab.delete method
- ProjectFile: file_path is required for deletion
- Rename some methods to better match the API URLs
- Deprecate the file_* methods in favor of the files manager
- Implement star/unstar for projects
- Implement list/get licenses
- Manage optional parameters for list() and get()

7.9.67 v0.12.2 (2016-03-19)

- Add new ProjectHook attributes
- Add support for user block/unblock
- Fix GitlabObject creation in _custom_list
- Add support for more CLI subcommands
- Add some unit tests for CLI
- Add a coverage tox env
- Define `GitlabObject.as_dict()` to dump object as a dict
- Define `GitlabObject.__eq__()` and `__ne__()` equivalence methods
- Define UserManager.search() to search for users
- Define UserManager.get_by_username() to get a user by username
- Implement “user search” CLI
- Improve the doc for UserManager
- CLI: implement user get-by-username
- Re-implement _custom_list in the Gitlab class
- Fix the ‘invalid syntax’ error on Python 3.2
- Gitlab.update(): use the proper attributes if defined

7.9.68 v0.12.1 (2016-02-03)

- Fix a broken upload to pypi

7.9.69 v0.12 (2016-02-03)

- Improve documentation
- Improve unit tests
- Improve test scripts
- Skip BaseManager attributes when encoding to JSON
- Fix the json() method for python 3
- Add Travis CI support
- Add a decode method for ProjectFile
- Make connection exceptions more explicit
- Fix ProjectLabel get and delete
- Implement ProjectMilestone.issues()
- ProjectTag supports deletion
- Implement setting release info on a tag
- Implement project triggers support

- Implement project variables support
- Add support for application settings
- Fix the ‘password’ requirement for User creation
- Add sudo support
- Fix project update
- Fix Project.tree()
- Add support for project builds

7.9.70 v0.11.1 (2016-01-17)

- Fix discovery of parents object attrs for managers
- Support setting commit status
- Support deletion without getting the object first
- Improve the documentation

7.9.71 v0.11 (2016-01-09)

- functional_tests.sh: support python 2 and 3
- Add a get method for GitlabObject
- CLI: Add the -g short option for --gitlab
- Provide a create method for GitlabObject’s
- Rename the _created attribute _from_api
- More unit tests
- CLI: fix error when arguments are missing (python 3)
- Remove deprecated methods
- Implement managers to get access to resources
- Documentation improvements
- Add fork project support
- Deprecate the “old” Gitlab methods
- Add support for groups search

7.9.72 v0.10 (2015-12-29)

- Implement pagination for list() (#63)
- Fix url when fetching a single MergeRequest
- Add support to update MergeRequestNotes
- API: Provide a Gitlab.from_config method
- setup.py: require requests>=1 (#69)

- Fix deletion of object not using ‘id’ as ID (#68)
- Fix GET/POST for project files
- Make ‘confirm’ an optional attribute for user creation
- Python 3 compatibility fixes
- Add support for group members update (#73)

7.9.73 v0.9.2 (2015-07-11)

- CLI: fix the update and delete subcommands (#62)

7.9.74 v0.9.1 (2015-05-15)

- Fix the setup.py script

7.9.75 v0.9 (2015-05-15)

- Implement argparse library for parsing argument on CLI
- Provide unit tests and (a few) functional tests
- Provide PEP8 tests
- Use tox to run the tests
- CLI: provide a –config-file option
- Turn the gitlab module into a proper package
- Allow projects to be updated
- Use more pythonic names for some methods
- Deprecate some Gitlab object methods:
 - raw* methods should never have been exposed; replace them with _raw_* methods
 - setCredentials and setToken are replaced with set_credentials and set_token
- Sphinx: don’t hardcode the version in conf.py

7.9.76 v0.8 (2014-10-26)

- Better python 2.6 and python 3 support
- Timeout support in HTTP requests
- Gitlab.get() raised GitlabListError instead of GitlabGetError
- Support api-objects which don’t have id in api response
- Add ProjectLabel and ProjectFile classes
- Moved url attributes to separate list
- Added list for delete attributes

7.9.77 v0.7 (2014-08-21)

- Fix license classifier in `setup.py`
- Fix encoding error when printing to redirected output
- Fix encoding error when updating with redirected output
- Add support for UserKey listing and deletion
- Add support for branches creation and deletion
- Support state_event in ProjectMilestone (#30)
- Support namespace/name for project id (#28)
- Fix handling of boolean values (#22)

7.9.78 v0.6 (2014-01-16)

- IDs can be unicode (#15)
- ProjectMember: constructor should not create a User object
- Add support for extra parameters when listing all projects (#12)
- Projects listing: explicitly define arguments for pagination

7.9.79 v0.5 (2013-12-26)

- Add SSH key for user
- Fix comments
- Add support for project events
- Support creation of projects for users
- Project: add methods for create/update/delete files
- Support projects listing: search, all, owned
- System hooks can't be updated
- Project.archive(): download tarball of the project
- Define new optional attributes for user creation
- Provide constants for access permissions in groups

7.9.80 v0.4 (2013-09-26)

- Fix strings encoding (Closes #6)
- Allow to get a project commit (GitLab 6.1)
- ProjectMergeRequest: fix Note() method
- Gitlab 6.1 methods: diff, blob (commit), tree, blob (project)
- Add support for Gitlab 6.1 group members

7.9.81 v0.3 (2013-08-27)

- Use PRIVATE-TOKEN header for passing the auth token
- provide an AUTHORS file
- cli: support ssl_verify config option
- Add ssl_verify option to Gitlab object. Defaults to True
- Correct url for merge requests API.

7.9.82 v0.2 (2013-08-08)

- provide a pip requirements.txt
- drop some debug statements

7.9.83 v0.1 (2013-07-08)

- Initial release

7.10 Release notes

Prior to version 2.0.0 and GitHub Releases, a summary of changes was maintained in release notes. They are available below for historical purposes. For the list of current releases, including breaking changes, please see the changelog.

7.10.1 Changes from 1.8 to 1.9

- ProjectMemberManager.all() and GroupMemberManager.all() now return a list of ProjectMember and GroupMember objects respectively, instead of a list of dicts.

7.10.2 Changes from 1.7 to 1.8

- You can now use the `query_parameters` argument in method calls to define arguments to send to the GitLab server. This allows to avoid conflicts between python-gitlab and GitLab server variables, and allows to use the python reserved keywords as GitLab arguments.

The following examples make the same GitLab request with the 2 syntaxes:

```
projects = gl.projects.list(owned=True, starred=True)
projects = gl.projects.list(query_parameters={'owned': True, 'starred': True})
```

The following example only works with the new parameter:

```
activities = gl.user_activities.list(
    query_parameters={'from': '2019-01-01'},
    all=True)
```

- Additionally the `all` parameter is not sent to the GitLab anymore.

7.10.3 Changes from 1.5 to 1.6

- When python-gitlab detects HTTP redirections from http to https it will raise a `RedirectionError` instead of a cryptic error.

Make sure to use an `https://` protocol in your GitLab URL parameter if the server requires it.

7.10.4 Changes from 1.4 to 1.5

- APIv3 support has been removed. Use the 1.4 release/branch if you need v3 support.
- GitLab EE features are now supported: Geo nodes, issue links, LDAP groups, project/group boards, project mirror pulling, project push rules, EE license configuration, epics.
- The `GetFromListMixin` class has been removed. The `get()` method is not available anymore for the following managers:
 - `UserKeyManager`
 - `DeployKeyManager`
 - `GroupAccessRequestManager`
 - `GroupIssueManager`
 - `GroupProjectManager`
 - `GroupSubgroupManager`
 - `IssueManager`
 - `ProjectCommitStatusManager`
 - `ProjectEnvironmentManager`
 - `ProjectLabelManager`
 - `ProjectPipelineJobManager`
 - `ProjectAccessRequestManager`
 - `TodoManager`
- `ProjectPipelineJob` do not inherit from `ProjectJob` anymore and thus can only be listed.

7.10.5 Changes from 1.3 to 1.4

- 1.4 is the last release supporting the v3 API, and the related code will be removed in the 1.5 version.

If you are using a GitLab server version that does not support the v4 API you can:

- upgrade the server (recommended)
- make sure to use version 1.4 of python-gitlab (`pip install python-gitlab==1.4`)

See also the [Switching to GitLab API v4 documentation](#).

- python-gitlab now handles the server rate limiting feature. It will pause for the required time when reaching the limit ([documentation](#))
- The `GetFromListMixin.get()` method is deprecated and will be removed in the next python-gitlab version. The goal of this mixin/method is to provide a way to get an object by looping through a list for GitLab objects that don't support the GET method. The method is [broken](#) and conflicts with the GET method now supported by some GitLab objects.

You can implement your own method with something like:

```
def get_from_list(self, id):
    for obj in self.list(as_list=False):
        if obj.get_id() == id:
            return obj
```

- The GroupMemberManager, NamespaceManager and ProjectBoardManager managers now use the GET API from GitLab instead of the GetFromListMixin.get() method.

7.10.6 Changes from 1.2 to 1.3

- gitlab.Gitlab objects can be used as context managers in a `with` block.

7.10.7 Changes from 1.1 to 1.2

- python-gitlab now respects the `*_proxy`, REQUESTS_CA_BUNDLE and CURL_CA_BUNDLE environment variables (#352)
- The following deprecated methods and objects have been removed:
 - `gitlab.v3.object` Key and KeyManager objects: use DeployKey and DeployKeyManager instead
 - `gitlab.v3.objects`.Project `archive_` and `unarchive_` methods
 - `gitlab.Gitlab` `credentials_auth`, `token_auth`, `set_url`, `set_token` and `set_credentials` methods. Once a Gitlab object has been created its URL and authentication information cannot be updated: create a new Gitlab object if you need to use new information
- The `todo()` method raises a `GitlabTodoError` exception on error

7.10.8 Changes from 1.0.2 to 1.1

- The `ProjectUser` class doesn't inherit from `User` anymore, and the `GroupProject` class doesn't inherit from `Project` anymore. The Gitlab API doesn't provide the same set of features for these objects, so python-gitlab objects shouldn't try to workaround that.

You can create `User` or `Project` objects from `ProjectUser` and `GroupProject` objects using the `id` attribute:

```
for gr_project in group.projects.list():
    # lazy object creation avoids a Gitlab API request
    project = gl.projects.get(gr_project.id, lazy=True)
    project.default_branch = 'develop'
    project.save()
```

7.10.9 Changes from 0.21 to 1.0.0

1.0.0 brings a stable python-gitlab API for the v4 Gitlab API. v3 is still used by default.

v4 is mostly compatible with the v3, but some important changes have been introduced. Make sure to read [Switching to GitLab API v4](#).

The development focus will be v4 from now on. v3 has been deprecated by GitLab and will disappear from python-gitlab at some point.

7.10.10 Changes from 0.20 to 0.21

- Initial support for the v4 API (experimental)

The support for v4 is stable enough to be tested, but some features might be broken. Please report issues to <https://github.com/python-gitlab/python-gitlab/issues/>

Be aware that the python-gitlab API for v4 objects might change in the next releases.

Warning: Consider defining explicitly which API version you want to use in the configuration files or in your `gitlab.Gitlab` instances. The default will change from v3 to v4 soon.

- Several methods have been deprecated in the `gitlab.Gitlab` class:
 - `credentials_auth()` is deprecated and will be removed. Call `auth()`.
 - `token_auth()` is deprecated and will be removed. Call `auth()`.
 - `set_url()` is deprecated, create a new `Gitlab` instance if you need an updated URL.
 - `set_token()` is deprecated, use the `private_token` argument of the `Gitlab` constructor.
 - `set_credentials()` is deprecated, use the `email` and `password` arguments of the `Gitlab` constructor.
- The service listing method (`ProjectServiceManager.list()`) now returns a python list instead of a JSON string.

7.10.11 Changes from 0.19 to 0.20

- The `projects` attribute of `Group` objects is not a list of `Project` objects anymore. It is a `Manager` object giving access to `GroupProject` objects. To get the list of projects use:

```
group.projects.list()
```

Documentation: http://python-gitlab.readthedocs.io/en/stable/gl_objects/groups.html#examples

Related issue: <https://github.com/python-gitlab/python-gitlab/issues/209>

- The `Key` objects are deprecated in favor of the new `DeployKey` objects. They are exactly the same but the name makes more sense.

Documentation: http://python-gitlab.readthedocs.io/en/stable/gl_objects/deploy_keys.html

Related issue: <https://github.com/python-gitlab/python-gitlab/issues/212>

7.11 FAQ

7.11.1 General

I cannot edit the merge request / issue I've just retrieved.

It is likely that you used a `MergeRequest`, `GroupMergeRequest`, `Issue` or `GroupIssue` object. These objects cannot be edited. But you can create a new `ProjectMergeRequest` or `ProjectIssue` object to apply changes. For example:

```
issue = gl.issues.list()[0]
project = gl.projects.get(issue.project_id, lazy=True)
editable_issue = project.issues.get(issue.id, lazy=True)
# you can now edit the object
```

See the [merge requests example](#) and the [issues examples](#).

How can I clone the repository of a project?

`python-gitlab` does not provide an API to clone a project. You have to use a git library or call the `git` command.

The git URI is exposed in the `ssh_url_to_repo` attribute of `Project` objects.

Example:

```
import subprocess

project = gl.projects.create(data) # or gl.projects.get(project_id)
print(project.attributes) # displays all the attributes
git_url = project.ssh_url_to_repo
subprocess.call(['git', 'clone', git_url])
```

Not all items are returned from the API

If you've passed `all=True` (or `--all` via the CLI) to the API and still cannot see all items returned, use `get_all=True` (or `--get-all` via the CLI) instead. See [Pagination](#) for more details.

7.11.2 Common errors

AttributeError when accessing object attributes retrieved via `list()`

Fetching a list of objects does not always include all attributes in the objects. To retrieve an object with all attributes, use a `get()` call.

Example with projects:

```
for projects in gl.projects.list():
    # Retrieve project object with all attributes
    project = gl.projects.get(project.id)
```

AttributeError when accessing attributes after save() or refresh()

You are most likely trying to access an attribute that was not returned by the server on the second request. Please look at the documentation in [*Attributes in updated objects*](#) to see how to avoid this.

TypeError when accessing object attributes

When you encounter errors such as `object is not iterable` or `object is not subscriptable` when trying to access object attributes returned from the server, you are most likely trying to access an attribute that is shadowed by python-gitlab's own methods or managers.

You can use the object's `attributes` dictionary to access it directly instead. See the [*Gitlab Objects*](#) section for more details on how attributes are exposed.

**CHAPTER
EIGHT**

INDICES AND TABLES

- genindex
- modindex
- search

PYTHON MODULE INDEX

g

`gitlab.base`, 447
`gitlab.cli`, 449
`gitlab.config`, 450
`gitlab.const`, 451
`gitlab.exceptions`, 452
`gitlab.mixins`, 470
`gitlab.utils`, 478
`gitlab.v4`, 447
`gitlab.v4.objects`, 192

INDEX

Symbols

--access-level
 gitlab-group-access-request-approve
 command line option, 518
 gitlab-group-access-token-create
 command line option, 520
 gitlab-group-invitation-create command
 line option, 552
 gitlab-group-invitation-update command
 line option, 554
 gitlab-group-member-create command line
 option, 561
 gitlab-group-member-update command line
 option, 562
 gitlab-group-saml-group-link-create
 command line option, 575
 gitlab-project-access-request-approve
 command line option, 610
 gitlab-project-access-token-create
 command line option, 612
 gitlab-project-invitation-create
 command line option, 659
 gitlab-project-invitation-update
 command line option, 661
 gitlab-project-member-create command
 line option, 693
 gitlab-project-member-update command
 line option, 695
 gitlab-runner-create command line
 option, 791
 gitlab-runner-update command line
 option, 793

--access-raw-diffs
 gitlab-project-merge-request-changes
 command line option, 698

--action
 gitlab-event-list command line option,
 505
 gitlab-project-event-list command line
 option, 648
 gitlab-todo-list command line option, 800
 gitlab-user-event-list command line
 option, 812

--actions
 gitlab-project-commit-create command
 line option, 629

--active
 gitlab-project-pipeline-schedule-create
 command line option, 740
 gitlab-project-pipeline-schedule-update
 command line option, 742
 gitlab-runner-create command line
 option, 791
 gitlab-runner-update command line
 option, 792
 gitlab-user-list command line option, 806

--admin
 gitlab-user-create command line option,
 805
 gitlab-user-update command line option,
 808

--after
 gitlab-event-list command line option,
 505
 gitlab-project-event-list command line
 option, 648
 gitlab-user-event-list command line
 option, 812

--after-sign-out-path
 gitlab-application-settings-update
 command line option, 491

--all
 gitlab-application-list command line
 option, 486
 gitlab-audit-event-list command line
 option, 493
 gitlab-broadcast-message-list command
 line option, 494
 gitlab-bulk-import-all-entity-list
 command line option, 496
 gitlab-bulk-import-entity-list command
 line option, 497
 gitlab-bulk-import-list command line
 option, 496

gitlab-current-user-email-list command
 line option, 500

gitlab-current-user-gpg-key-list
 command line option, 501

gitlab-current-user-key-list command
 line option, 502

gitlab-deploy-key-list command line
 option, 503

gitlab-deploy-token-list command line
 option, 504

gitlab-dockerfile-list command line
 option, 505

gitlab-event-list command line option,
 506

gitlab-feature-list command line option,
 506

gitlab-geo-node-list command line
 option, 509

gitlab-gitignore-list command line
 option, 510

gitlab-gitlabciyml-list command line
 option, 511

gitlab-group-access-request-list
 command line option, 519

gitlab-group-access-token-list command
 line option, 521

gitlab-group-audit-event-list command
 line option, 522

gitlab-group-badge-list command line
 option, 523

gitlab-group-billable-member-list
 command line option, 525

gitlab-group-billable-member-membership-list
 command line option, 525

gitlab-group-board-list command line
 option, 527

gitlab-group-board-list-list command
 line option, 529

gitlab-group-cluster-list command line
 option, 531

gitlab-group-custom-attribute-list
 command line option, 533

gitlab-group-deploy-token-list command
 line option, 534

gitlab-group-descendant-group-list
 command line option, 535

gitlab-group-epic-award-emoji-list
 command line option, 540

gitlab-group-epic-issue-list command
 line option, 543

gitlab-group-epic-list command line
 option, 537

gitlab-group-epic-note-award-emoji-list
 command line option, 547

gitlab-group-epic-note-list command
 line option, 545

gitlab-group-epic-resource-label-event-list
 command line option, 548

gitlab-group-hook-list command line
 option, 551

gitlab-group-invitation-list command
 line option, 554

gitlab-group-issue-list command line
 option, 555

gitlab-group-iteration-list command
 line option, 556

gitlab-group-label-list command line
 option, 558

gitlab-group-ldap-group-link-list
 command line option, 560

gitlab-group-list command line option,
 515

gitlab-group-member-all-list command
 line option, 563

gitlab-group-member-list command line
 option, 562

gitlab-group-merge-request-list command
 line option, 565

gitlab-group-milestone-list command
 line option, 567

gitlab-group-package-list command line
 option, 570

gitlab-group-project-list command line
 option, 571

gitlab-group-runner-list command line
 option, 574

gitlab-group-saml-group-link-list
 command line option, 576

gitlab-group-subgroup-list command line
 option, 577

gitlab-group-variable-list command line
 option, 578

gitlab-group-wiki-list command line
 option, 580

gitlab-hook-list command line option, 582

gitlab-issue-list command line option,
 583

gitlab-ldap-group-list command line
 option, 585

gitlab-license-list command line option,
 585

gitlab-merge-request-list command line
 option, 587

gitlab-namespace-list command line
 option, 588

gitlab-pages-domain-list command line
 option, 590

gitlab-personal-access-token-list

```
    command line option, 591
gitlab-project-access-request-list
    command line option, 611
gitlab-project-access-token-list
    command line option, 613
gitlab-project-approval-rule-list
    command line option, 615
gitlab-project-audit-event-list command
    line option, 618
gitlab-project-badge-list command line
    option, 619
gitlab-project-board-list command line
    option, 621
gitlab-project-board-list-list command
    line option, 623
gitlab-project-branch-list command line
    option, 625
gitlab-project-cluster-list command
    line option, 628
gitlab-project-commit-comment-list
    command line option, 633
gitlab-project-commit-discussion-list
    command line option, 634
gitlab-project-commit-list command line
    option, 631
gitlab-project-commit-status-list
    command line option, 638
gitlab-project-custom-attribute-list
    command line option, 639
gitlab-project-deploy-token-list
    command line option, 640
gitlab-project-deployment-list command
    line option, 642
gitlab-project-deployment-merge-request-list
    command line option, 645
gitlab-project-environment-list command
    line option, 647
gitlab-project-event-list command line
    option, 648
gitlab-project-fork-list command line
    option, 653
gitlab-project-hook-list command line
    option, 655
gitlab-project-integration-list command
    line option, 658
gitlab-project-invitation-list command
    line option, 660
gitlab-project-issue-award-emoji-list
    command line option, 670
gitlab-project-issue-discussion-list
    command line option, 672
gitlab-project-issue-link-list command
    line option, 675
gitlab-project-issue-list command line
    option, 664
gitlab-project-issue-note-award-emoji-list
    command line option, 679
gitlab-project-issue-note-list command
    line option, 677
gitlab-project-issue-iteration-event-list
    command line option, 680
gitlab-project-issue-resource-label-event-list
    command line option, 681
gitlab-project-issue-resource-milestone-event-list
    command line option, 682
gitlab-project-issue-resource-state-event-list
    command line option, 683
gitlab-project-issue-resource-weight-event-list
    command line option, 684
gitlab-project-job-list command line
    option, 687
gitlab-project-key-list command line
    option, 690
gitlab-project-label-list command line
    option, 692
gitlab-project-list command line option,
    600
gitlab-project-member-all-list command
    line option, 696
gitlab-project-member-list command line
    option, 694
gitlab-project-merge-request-approval-rule-list
    command line option, 709
gitlab-project-merge-request-award-emoji-list
    command line option, 713
gitlab-project-merge-request-diff-list
    command line option, 714
gitlab-project-merge-request-discussion-list
    command line option, 715
gitlab-project-merge-request-list
    command line option, 702
gitlab-project-merge-request-note-award-emoji-list
    command line option, 722
gitlab-project-merge-request-note-list
    command line option, 719
gitlab-project-merge-request-pipeline-list
    command line option, 722
gitlab-project-merge-request-resource-label-event-list
    command line option, 723
gitlab-project-merge-request-resource-milestone-event-
    command line option, 724
gitlab-project-merge-request-resource-state-event-list
    command line option, 725
gitlab-project-merge-train-list command
    line option, 726
gitlab-project-milestone-list command
    line option, 728
gitlab-project-note-list command line
```

```
    option, 730
gitlab-project-package-file-list
    command line option, 733
gitlab-project-package-list command
    line option, 733
gitlab-project-pages-domain-list
    command line option, 735
gitlab-project-pipeline-bridge-list
    command line option, 738
gitlab-project-pipeline-job-list
    command line option, 739
gitlab-project-pipeline-list command
    line option, 738
gitlab-project-pipeline-schedule-list
    command line option, 741
gitlab-project-pipeline-schedule-pipeline-list
    command line option, 743
gitlab-project-pipeline-variable-list
    command line option, 746
gitlab-project-protected-branch-list
    command line option, 748
gitlab-project-protected-environment-list
    command line option, 750
gitlab-project-protected-tag-list
    command line option, 751
gitlab-project-registry-repository-list
    command line option, 754
gitlab-project-registry-tag-list
    command line option, 756
gitlab-project-release-link-list
    command line option, 760
gitlab-project-release-list command
    line option, 758
gitlab-project-remote-mirror-list
    command line option, 762
gitlab-project-resource-group-list
    command line option, 763
gitlab-project-resource-group-upcoming-job-list
    command line option, 764
gitlab-project-runner-list command line
    option, 765
gitlab-project-secure-file-list command
    line option, 767
gitlab-project-service-list command
    line option, 769
gitlab-project-snippet-award-emoji-list
    command line option, 773
gitlab-project-snippet-discussion-list
    command line option, 775
gitlab-project-snippet-list command
    line option, 771
gitlab-project-snippet-note-award-emoji-list
    command line option, 781
gitlab-project-snippet-note-list
```

```
    command line option, 779
gitlab-project-tag-list command line
    option, 783
gitlab-project-trigger-list command
    line option, 784
gitlab-project-user-list command line
    option, 785
gitlab-project-variable-list command
    line option, 787
gitlab-project-wiki-list command line
    option, 789
gitlab-runner-all-list command line
    option, 793
gitlab-runner-job-list command line
    option, 794
gitlab-runner-list command line option, 792
gitlab-shared-project-list command line
    option, 795
gitlab-snippet-list command line option, 797
gitlab-starred-project-list command
    line option, 799
gitlab-todo-list command line option, 800
gitlab-topic-list command line option, 802
gitlab-user-activities-list command
    line option, 809
gitlab-user-custom-attribute-list
    command line option, 810
gitlab-user-email-list command line
    option, 812
gitlab-user-event-list command line
    option, 813
gitlab-user-gpg-key-list command line
    option, 814
gitlab-user-impersonation-token-list
    command line option, 816
gitlab-user-key-list command line
    option, 817
gitlab-user-list command line option, 807
gitlab-user-membership-list command
    line option, 818
gitlab-user-project-list command line
    option, 821
gitlab-variable-list command line
    option, 823
--all-available
gitlab-group-descendant-group-list
    command line option, 535
gitlab-group-list command line option, 514
gitlab-group-subgroup-list command line
    option, 576
```

```
--allow-collaboration
    gitlab-project-merge-request-create
        command line option, 699
--allow-force-push
    gitlab-project-protected-branch-create
        command line option, 747
--allow-local-requests-from-hooks-and-services
    gitlab-application-settings-update
        command line option, 491
--allow-local-requests-from-system-hooks
    gitlab-application-settings-update
        command line option, 491
--allow-local-requests-from-web-hooks-and-services
    gitlab-application-settings-update
        command line option, 491
--allow-maintainer-to-push
    gitlab-project-merge-request-create
        command line option, 699
    gitlab-project-merge-request-update
        command line option, 706
--allow-merge-on-skipped-pipeline
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--allowed-to-merge
    gitlab-project-protected-branch-create
        command line option, 747
--allowed-to-push
    gitlab-project-protected-branch-create
        command line option, 747
--allowed-to-unprotect
    gitlab-project-protected-branch-create
        command line option, 747
--analytics-access-level
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--api-version
    gitlab command line option, 485
--approval-project-rule-id
    gitlab-project-merge-request-approval-rule-create
        command line option, 708
--approval-rule-id
    gitlab-project-merge-request-approval-rule-update
        command line option, 710
--approval-rules
    gitlab-project-protected-environment-create
        command line option, 749
--approvals-before-merge
    gitlab-project-approval-update command
        line option, 614
    gitlab-project-create command line
        option, 595
    gitlab-project-merge-request-create
        command line option, 699
    gitlab-project-merge-request-approval-rule-create
        command line option, 708
    gitlab-project-merge-request-approval-rule-update
        command line option, 710
    gitlab-project-merge-request-approval-update
        command line option, 707
--approved-by-ids
    gitlab-group-merge-request-list command
        line option, 565
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-merge-request-list
        command line option, 644
    gitlab-project-merge-request-list
        command line option, 701
--approver-ids
    gitlab-group-merge-request-list command
        line option, 565
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-merge-request-list
        command line option, 644
    gitlab-project-merge-request-list
        command line option, 701
--archived
    gitlab-group-project-list command line
        option, 571
    gitlab-project-fork-list command line
        option, 653
    gitlab-project-list command line option,
        599
    gitlab-shared-project-list command line
        option, 795
    gitlab-starred-project-list command
        line option, 798
    gitlab-user-project-list command line
        option, 820
--artifact-path
    gitlab-project-artifact command line
        option, 592
    gitlab-project-artifact-raw command
        line option, 617
--asset-proxy-allowlist
    gitlab-application-settings-update
        command line option, 491
--asset-proxy-enabled
```

```
gitlab-application-settings-update
    command line option, 491
--asset-proxy-url
    gitlab-application-settings-update
        command line option, 491
--asset-proxy-whitelist
    gitlab-application-settings-update
        command line option, 491
--assets
    gitlab-project-release-create command
        line option, 757
--assignee-id
    gitlab-group-issue-list command line
        option, 555
    gitlab-group-merge-request-list command
        line option, 565
    gitlab-issue-list command line option,
        583
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-merge-request-list
        command line option, 644
    gitlab-project-issue-create command
        line option, 662
    gitlab-project-issue-list command line
        option, 664
    gitlab-project-issue-update command
        line option, 668
    gitlab-project-merge-request-create
        command line option, 699
    gitlab-project-merge-request-list
        command line option, 701
    gitlab-project-merge-request-update
        command line option, 706
--assignee-ids
    gitlab-project-issue-create command
        line option, 662
    gitlab-project-issue-update command
        line option, 668
    gitlab-project-merge-request-create
        command line option, 699
--author-email
    gitlab-project-commit-create command
        line option, 629
    gitlab-project-file-create command line
        option, 650
    gitlab-project-file-update command line
        option, 652
--author-email-regex
    gitlab-group-push-rules-create command
        line option, 572
    gitlab-group-push-rules-update command
        line option, 573
    gitlab-project-push-rules-create
        command line option, 752
    gitlab-project-push-rules-update
        command line option, 753
--author-id
    gitlab-group-epic-list command line
        option, 537
    gitlab-group-issue-list command line
        option, 555
    gitlab-group-merge-request-list command
        line option, 565
    gitlab-issue-list command line option,
        583
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-merge-request-list
        command line option, 644
    gitlab-project-issue-list command line
        option, 664
    gitlab-project-merge-request-list
        command line option, 701
    gitlab-todo-list command line option, 800
--author-name
    gitlab-project-commit-create command
        line option, 630
    gitlab-project-file-create command line
        option, 650
    gitlab-project-file-update command line
        option, 652
--author-username
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-merge-request-list
        command line option, 644
--auto-cancel-pending-pipelines
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--auto-devops-deploy-strategy
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--auto-devops-enabled
    gitlab-group-create command line option,
        513
    gitlab-group-update command line option,
        517
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--autoclose-referenced-issues
    gitlab-project-create command line
```

```

    option, 595
gitlab-project-update command line
    option, 607
--avatar
    gitlab-group-create command line option,
        513
    gitlab-group-update command line option,
        518
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
    gitlab-topic-create command line option,
        801
    gitlab-topic-update command line option,
        802
    gitlab-user-create command line option,
        805
    gitlab-user-update command line option,
        809
--before
    gitlab-event-list command line option,
        505
    gitlab-project-event-list command line
        option, 648
    gitlab-user-event-list command line
        option, 812
--bio
    gitlab-user-create command line option,
        804
    gitlab-user-update command line option,
        808
--blocked
    gitlab-user-list command line option, 806
--board-id
    gitlab-group-board-list-create command
        line option, 528
    gitlab-group-board-list-delete command
        line option, 528
    gitlab-group-board-list-get command
        line option, 528
    gitlab-group-board-list-list command
        line option, 529
    gitlab-group-board-list-update command
        line option, 529
    gitlab-project-board-list-create
        command line option, 622
    gitlab-project-board-list-delete
        command line option, 622
    gitlab-project-board-list-get command
        line option, 622
    gitlab-project-board-list-list command
        line option, 623
    gitlab-project-board-list-update
        command line option, 623
--body
    gitlab-group-epic-discussion-note-create
        command line option, 540
    gitlab-group-epic-discussion-note-update
        command line option, 541
    gitlab-group-epic-note-create command
        line option, 544
    gitlab-group-epic-note-update command
        line option, 545
    gitlab-project-commit-discussion-create
        command line option, 634
    gitlab-project-commit-discussion-note-create
        command line option, 635
    gitlab-project-commit-discussion-note-update
        command line option, 636
    gitlab-project-issue-discussion-create
        command line option, 671
    gitlab-project-issue-discussion-note-create
        command line option, 672
    gitlab-project-issue-discussion-note-update
        command line option, 674
    gitlab-project-issue-note-create
        command line option, 675
    gitlab-project-issue-note-update
        command line option, 677
    gitlab-project-merge-request-discussion-create
        command line option, 714
    gitlab-project-merge-request-discussion-note-create
        command line option, 716
    gitlab-project-merge-request-discussion-note-update
        command line option, 717
    gitlab-project-merge-request-note-create
        command line option, 718
    gitlab-project-merge-request-note-update
        command line option, 720
    gitlab-project-snippet-discussion-create
        command line option, 774
    gitlab-project-snippet-discussion-note-create
        command line option, 776
    gitlab-project-snippet-discussion-note-update
        command line option, 777
    gitlab-project-snippet-note-create
        command line option, 777
    gitlab-project-snippet-note-update
        command line option, 779
--branch
    gitlab-project-branch-create command
        line option, 624
    gitlab-project-commit-cherry-pick
        command line option, 629
    gitlab-project-commit-create command
        line option, 629
    gitlab-project-commit-revert command
        line option, 629

```

```
    line option, 632
gitlab-project-file-create command line
    option, 650
gitlab-project-file-delete command line
    option, 651
gitlab-project-file-update command line
    option, 652
gitlab-project-update-submodule command
    line option, 610
--branch-name-regex
    gitlab-group-push-rules-create command
        line option, 572
    gitlab-group-push-rules-update command
        line option, 573
    gitlab-project-push-rules-create
        command line option, 752
    gitlab-project-push-rules-update
        command line option, 753
--build-coverage-regex
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--build-git-strategy
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--build-timeout
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--builds-access-level
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--builds-enabled
    gitlab-user-project-create command line
        option, 819
--bulk-import-id
    gitlab-bulk-import-entity-get command
        line option, 497
    gitlab-bulk-import-entity-list command
        line option, 497
--can-create-group
    gitlab-user-create command line option,
        805
    gitlab-user-update command line option,
        808
--can-push
    gitlab-project-key-create command line
        option, 689
gitlab-project-key-update command line
    option, 690
--certificate
    gitlab-project-pages-domain-create
        command line option, 734
    gitlab-project-pages-domain-update
        command line option, 735
--ci-allow-fork-pipelines-to-run-in-parent-project
    gitlab-project-update command line
        option, 607
--ci-config-path
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--ci-default-git-depth
    gitlab-project-update command line
        option, 607
--ci-forward-deployment-enabled
    gitlab-project-update command line
        option, 607
--ci-separated-caches
    gitlab-project-update command line
        option, 607
--close-issue
    gitlab-group-notification-settings-update
        command line option, 569
    gitlab-notification-settings-update
        command line option, 589
    gitlab-project-notification-settings-update
        command line option, 731
--close-merge-request
    gitlab-group-notification-settings-update
        command line option, 569
    gitlab-notification-settings-update
        command line option, 590
    gitlab-project-notification-settings-update
        command line option, 731
--cn
    gitlab-group-add-ldap-group-link
        command line option, 512
    gitlab-group-delete-ldap-group-link
        command line option, 514
--code-owner-approval-required
    gitlab-project-protected-branch-create
        command line option, 747
--color
    gitlab-broadcast-message-create command
        line option, 493
    gitlab-broadcast-message-update command
        line option, 495
    gitlab-group-label-create command line
        option, 557
    gitlab-group-label-update command line
```

```

        option, 559
gitlab-project-label-create command
    line option, 691
gitlab-project-label-update command
    line option, 693
--color-scheme-id
    gitlab-user-create command line option,
        805
    gitlab-user-update command line option,
        809
--comment
    gitlab-project-deployment-approval
        command line option, 641
--commit-committer-check
    gitlab-group-push-rules-create command
        line option, 572
    gitlab-group-push-rules-update command
        line option, 573
    gitlab-project-push-rules-create
        command line option, 752
    gitlab-project-push-rules-update
        command line option, 753
--commit-id
    gitlab-project-commit-comment-create
        command line option, 632
    gitlab-project-commit-comment-list
        command line option, 633
    gitlab-project-commit-discussion-create
        command line option, 634
    gitlab-project-commit-discussion-get
        command line option, 634
    gitlab-project-commit-discussion-list
        command line option, 634
    gitlab-project-commit-discussion-note-create
        command line option, 635
    gitlab-project-commit-discussion-note-delete
        command line option, 635
    gitlab-project-commit-discussion-note-get
        command line option, 636
    gitlab-project-commit-discussion-note-update
        command line option, 636
    gitlab-project-commit-status-create
        command line option, 637
    gitlab-project-commit-status-list
        command line option, 638
--commit-message
    gitlab-project-commit-create command
        line option, 629
    gitlab-project-file-create command line
        option, 650
    gitlab-project-file-delete command line
        option, 651
    gitlab-project-file-update command line
        option, 652
--commit-message-negative-regex
gitlab-group-push-rules-create command
    line option, 572
gitlab-group-push-rules-update command
    line option, 573
gitlab-project-push-rules-create
    command line option, 752
gitlab-project-push-rules-update
    command line option, 753
--commit-message-regex
gitlab-group-push-rules-create command
    line option, 572
gitlab-group-push-rules-update command
    line option, 573
gitlab-project-push-rules-create
    command line option, 752
gitlab-project-push-rules-update
    command line option, 753
--commit-sha
    gitlab-project-update-submodule command
        line option, 610
--confidential
    gitlab-application-create command line
        option, 486
    gitlab-project-issue-create command
        line option, 662
    gitlab-project-issue-update command
        line option, 668
--confidential-issues-events
    gitlab-group-hook-create command line
        option, 549
    gitlab-group-hook-update command line
        option, 551
    gitlab-project-hook-create command line
        option, 654
    gitlab-project-hook-update command line
        option, 656
--confidential-note-events
    gitlab-group-hook-create command line
        option, 549
    gitlab-group-hook-update command line
        option, 551
--config-file
    gitlab command line option, 484
--configuration
    gitlab-bulk-import-create command line
        option, 495
--container-expiration-policy-attributes
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--container-registry-access-level
    gitlab-project-create command line

```

```
    option, 595
gitlab-project-update command line
    option, 607
--container-registry-enabled
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--container-registry-token-expire-delay
    gitlab-application-settings-update
        command line option, 491
--content
    gitlab-ci-lint-create command line
        option, 498
    gitlab-ci-lint-validate command line
        option, 498
    gitlab-group-wiki-create command line
        option, 579
    gitlab-group-wiki-update command line
        option, 581
    gitlab-project-ci-lint-create command
        line option, 625
    gitlab-project-ci-lint-validate command
        line option, 626
    gitlab-project-file-create command line
        option, 650
    gitlab-project-file-update command line
        option, 652
    gitlab-project-snippet-create command
        line option, 770
    gitlab-project-snippet-update command
        line option, 771
    gitlab-project-wiki-create command line
        option, 788
    gitlab-project-wiki-update command line
        option, 790
    gitlab-snippet-create command line
        option, 796
    gitlab-snippet-update command line
        option, 798
--context
    gitlab-project-commit-status-create
        command line option, 637
--coverage
    gitlab-project-commit-status-create
        command line option, 637
--create-access-level
    gitlab-project-protected-tag-create
        command line option, 750
--created-after
    gitlab-audit-event-list command line
        option, 492
    gitlab-group-audit-event-list command
        line option, 521
gitlab-group-issue-list command line
    option, 555
gitlab-group-merge-request-list command
    line option, 564
gitlab-issue-list command line option,
    583
gitlab-merge-request-list command line
    option, 587
gitlab-project-audit-event-list command
    line option, 618
gitlab-project-deployment-merge-request-list
    command line option, 644
gitlab-project-issue-list command line
    option, 664
gitlab-project-merge-request-list
    command line option, 701
--created-at
    gitlab-application-settings-update
        command line option, 490
    gitlab-group-epic-discussion-note-create
        command line option, 540
    gitlab-group-epic-note-create command
        line option, 544
    gitlab-project-commit-discussion-create
        command line option, 634
    gitlab-project-commit-discussion-note-create
        command line option, 635
    gitlab-project-issue-create command
        line option, 662
    gitlab-project-issue-discussion-create
        command line option, 671
    gitlab-project-issue-discussion-note-create
        command line option, 672
    gitlab-project-issue-note-create
        command line option, 675
    gitlab-project-merge-request-discussion-create
        command line option, 714
    gitlab-project-merge-request-discussion-note-create
        command line option, 716
    gitlab-project-snippet-discussion-create
        command line option, 774
    gitlab-project-snippet-discussion-note-create
        command line option, 776
--created-before
    gitlab-audit-event-list command line
        option, 492
    gitlab-group-audit-event-list command
        line option, 521
    gitlab-group-issue-list command line
        option, 555
    gitlab-group-merge-request-list command
        line option, 564
    gitlab-issue-list command line option,
        583
```

```

gitlab-merge-request-list command line
    option, 587
gitlab-project-audit-event-list command
    line option, 618
gitlab-project-deployment-merge-request-list
    command line option, 644
gitlab-project-issue-list command line
    option, 664
gitlab-project-merge-request-list
    command line option, 701
--cron
    gitlab-project-pipeline-schedule-create
        command line option, 740
    gitlab-project-pipeline-schedule-update
        command line option, 742
--cron-timezone
    gitlab-project-pipeline-schedule-create
        command line option, 740
    gitlab-project-pipeline-schedule-update
        command line option, 742
--custom-attributes
    gitlab-user-list command line option, 806
--debug
    gitlab command line option, 484
--default-branch
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
    gitlab-user-project-create command line
        option, 819
--default-branch-protection
    gitlab-application-settings-update
        command line option, 490
    gitlab-group-create command line option,
        513
    gitlab-group-update command line option,
        518
--default-group-visibility
    gitlab-application-settings-update
        command line option, 490
--default-project-visibility
    gitlab-application-settings-update
        command line option, 490
--default-projects-limit
    gitlab-application-settings-update
        command line option, 490
--default-snippet-visibility
    gitlab-application-settings-update
        command line option, 490
--deny-delete-tag
    gitlab-group-push-rules-create command
        line option, 572
    gitlab-group-push-rules-update command
        line option, 573
gitlab-project-push-rules-create
    command line option, 752
gitlab-project-push-rules-update
    command line option, 753
--deploy-access-levels
    gitlab-project-protected-environment-create
        command line option, 748
--deployed-after
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-merge-request-list
        command line option, 645
--deployed-before
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-merge-request-list
        command line option, 645
--deployment-events
    gitlab-group-hook-create command line
        option, 549
    gitlab-group-hook-update command line
        option, 551
--deployment-id
    gitlab-project-deployment-merge-request-list
        command line option, 644
--description
    gitlab-application-appearance-update
        command line option, 487
    gitlab-group-create command line option,
        513
    gitlab-group-epic-create command line
        option, 536
    gitlab-group-epic-update command line
        option, 538
    gitlab-group-label-create command line
        option, 557
    gitlab-group-label-update command line
        option, 559
    gitlab-group-milestone-create command
        line option, 566
    gitlab-group-milestone-update command
        line option, 568
    gitlab-group-update command line option,
        517
    gitlab-project-commit-status-create
        command line option, 637
    gitlab-project-create command line
        option, 595
    gitlab-project-export-create command
        line option, 649
    gitlab-project-issue-create command
        line option, 662
    gitlab-project-issue-update command
        line option, 663

```

```
    line option, 668
gitlab-project-label-create command
    line option, 691
gitlab-project-label-update command
    line option, 693
gitlab-project-merge-request-create
    command line option, 699
gitlab-project-merge-request-update
    command line option, 706
gitlab-project-milestone-create command
    line option, 727
gitlab-project-milestone-update command
    line option, 729
gitlab-project-pipeline-schedule-create
    command line option, 740
gitlab-project-pipeline-schedule-update
    command line option, 742
gitlab-project-release-create command
    line option, 757
gitlab-project-release-update command
    line option, 758
gitlab-project-snippet-create command
    line option, 770
gitlab-project-snippet-update command
    line option, 771
gitlab-project-trigger-create command
    line option, 783
gitlab-project-trigger-update command
    line option, 785
gitlab-project-update command line
    option, 607
gitlab-runner-create command line
    option, 791
gitlab-runner-update command line
    option, 792
gitlab-topic-create command line option,
    801
gitlab-topic-update command line option,
    802
gitlab-user-project-create command line
    option, 819
--disable-overriding-approvers-per-merge-request
gitlab-project-approval-update command
    line option, 614
--disabled-oauth-sign-in-sources
gitlab-application-settings-update
    command line option, 490
--discussion-id
gitlab-group-epic-discussion-note-create
    command line option, 540
gitlab-group-epic-discussion-note-delete
    command line option, 540
gitlab-group-epic-discussion-note-get
    command line option, 541
gitlab-group-epic-discussion-note-update
    command line option, 541
gitlab-project-commit-discussion-note-create
    command line option, 635
gitlab-project-commit-discussion-note-delete
    command line option, 636
gitlab-project-commit-discussion-note-get
    command line option, 636
gitlab-project-commit-discussion-note-update
    command line option, 636
gitlab-project-issue-discussion-note-create
    command line option, 672
gitlab-project-issue-discussion-note-delete
    command line option, 673
gitlab-project-issue-discussion-note-get
    command line option, 673
gitlab-project-issue-discussion-note-update
    command line option, 674
gitlab-project-merge-request-discussion-note-create
    command line option, 716
gitlab-project-merge-request-discussion-note-delete
    command line option, 717
gitlab-project-merge-request-discussion-note-get
    command line option, 717
gitlab-project-merge-request-discussion-note-update
    command line option, 717
gitlab-project-snippet-discussion-note-create
    command line option, 776
gitlab-project-snippet-discussion-note-delete
    command line option, 776
gitlab-project-snippet-discussion-note-get
    command line option, 776
gitlab-project-snippet-discussion-note-update
    command line option, 777
--discussion-locked
gitlab-project-issue-update command
    line option, 668
gitlab-project-merge-request-update
    command line option, 706
--discussion-to-resolve
gitlab-project-issue-create command
    line option, 662
--domain
gitlab-group-cluster-create command
    line option, 530
gitlab-group-cluster-update command
    line option, 531
gitlab-project-cluster-create command
    line option, 627
gitlab-project-cluster-update command
    line option, 628
gitlab-project-pages-domain-create
    command line option, 734
gitlab-project-pages-domain-delete
```

```

        command line option, 734
gitlab-project-pages-domain-get command
    line option, 735
gitlab-project-pages-domain-update
    command line option, 735
--domain-allowlist
    gitlab-application-settings-update
        command line option, 490
--domain-blacklist
    gitlab-application-settings-update
        command line option, 490
--domain-blacklist-enabled
    gitlab-application-settings-update
        command line option, 490
--domain-denylist
    gitlab-application-settings-update
        command line option, 490
--domain-denylist-enabled
    gitlab-application-settings-update
        command line option, 490
--domain-whitelist
    gitlab-application-settings-update
        command line option, 490
--dry-run
    gitlab-project-ci-lint-create command
        line option, 625
    gitlab-project-ci-lint-validate command
        line option, 626
--dsa-key-restriction
    gitlab-application-settings-update
        command line option, 491
--due-date
    gitlab-group-milestone-create command
        line option, 566
    gitlab-group-milestone-update command
        line option, 568
    gitlab-project-issue-create command
        line option, 662
    gitlab-project-issue-update command
        line option, 668
    gitlab-project-milestone-create command
        line option, 727
    gitlab-project-milestone-update command
        line option, 729
--duration
    gitlab-project-issue-add-spent-time
        command line option, 661
    gitlab-project-issue-time-estimate
        command line option, 667
    gitlab-project-merge-request-add-spent-time
        command line option, 697
    gitlab-project-merge-request-time-estimate
        command line option, 704
--ecdsa-key-restriction
gitlab-application-settings-update
    command line option, 491
--ed25519-key-restriction
    gitlab-application-settings-update
        command line option, 491
--email
    gitlab-current-user-email-create
        command line option, 499
    gitlab-group-invitation-delete command
        line option, 553
    gitlab-group-invitation-get command
        line option, 553
    gitlab-group-invitation-update command
        line option, 554
    gitlab-project-invitation-delete
        command line option, 659
    gitlab-project-invitation-get command
        line option, 660
    gitlab-project-invitation-update
        command line option, 660
    gitlab-user-create command line option,
        804
    gitlab-user-email-create command line
        option, 811
    gitlab-user-update command line option,
        808
--email-header-and-footer-enabled
    gitlab-application-appearance-update
        command line option, 487
--emails-disabled
    gitlab-group-create command line option,
        513
    gitlab-group-update command line option,
        517
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 607
--emoji
    gitlab-current-user-status-update
        command line option, 503
--enable-ssl-verification
    gitlab-group-hook-create command line
        option, 550
    gitlab-group-hook-update command line
        option, 552
    gitlab-project-hook-create command line
        option, 654
    gitlab-project-hook-update command line
        option, 656
--enabled
    gitlab-geo-node-update command line
        option, 509
    gitlab-group-cluster-create command

```

```
    line option, 530
gitlab-project-cluster-create command
    line option, 627
gitlab-project-remote-mirror-create
    command line option, 761
gitlab-project-remote-mirror-update
    command line option, 762
--encoding
    gitlab-project-file-create command line
        option, 650
    gitlab-project-file-update command line
        option, 652
--end-date
    gitlab-group-epic-create command line
        option, 536
    gitlab-group-epic-update command line
        option, 538
--ends-at
    gitlab-broadcast-message-create command
        line option, 493
    gitlab-broadcast-message-update command
        line option, 495
--enforce-auth-checks-on-uploads
    gitlab-project-update command line
        option, 608
--enforce-terms
    gitlab-application-settings-update
        command line option, 491
--entities
    gitlab-bulk-import-create command line
        option, 495
--entity-id
    gitlab-audit-event-list command line
        option, 493
--entity-type
    gitlab-audit-event-list command line
        option, 493
--environment
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-create
        command line option, 641
    gitlab-project-deployment-list command
        line option, 642
    gitlab-project-deployment-merge-request-list
        command line option, 645
--environment-scope
    gitlab-group-cluster-create command
        line option, 530
    gitlab-group-cluster-update command
        line option, 531
    gitlab-project-cluster-create command
        line option, 627
    gitlab-project-cluster-update command
        line option, 628
gitlab-project-variable-create command
    line option, 786
gitlab-project-variable-update command
    line option, 788
--environments-access-level
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
--epic-id
    gitlab-group-epic-discussion-note-create
        command line option, 540
    gitlab-group-epic-discussion-note-delete
        command line option, 540
    gitlab-group-epic-discussion-note-get
        command line option, 541
    gitlab-group-epic-discussion-note-update
        command line option, 541
    gitlab-group-epic-note-create command
        line option, 544
    gitlab-group-epic-note-delete command
        line option, 544
    gitlab-group-epic-note-get command line
        option, 544
    gitlab-group-epic-note-list command
        line option, 544
    gitlab-group-epic-note-update command
        line option, 545
    gitlab-group-epic-resource-label-event-get
        command line option, 547
    gitlab-group-epic-resource-label-event-list
        command line option, 547
--epic-iid
    gitlab-group-epic-award-emoji-create
        command line option, 538
    gitlab-group-epic-award-emoji-delete
        command line option, 539
    gitlab-group-epic-award-emoji-get
        command line option, 539
    gitlab-group-epic-award-emoji-list
        command line option, 539
    gitlab-group-epic-issue-create command
        line option, 542
    gitlab-group-epic-issue-delete command
        line option, 542
    gitlab-group-epic-issue-list command
        line option, 542
    gitlab-group-epic-issue-update command
        line option, 543
    gitlab-group-epic-note-award-emoji-create
        command line option, 545
    gitlab-group-epic-note-award-emoji-delete
        command line option, 546
```

gitlab-group-emoji-command command line option, 546
 gitlab-group-emoji-list command line option, 546
--epic-issue-id
 gitlab-group-epic-issue-delete command line option, 542
 gitlab-group-epic-issue-update command line option, 543
--exclude-subgroups
 gitlab-group-package-list command line option, 570
--expires-at
 gitlab-group-access-token-create command line option, 520
 gitlab-group-deploy-token-create command line option, 533
 gitlab-group-invitation-create command line option, 553
 gitlab-group-invitation-update command line option, 554
 gitlab-group-member-create command line option, 561
 gitlab-group-member-update command line option, 562
 gitlab-group-share command line option, 516
 gitlab-project-access-token-create command line option, 612
 gitlab-project-deploy-token-create command line option, 639
 gitlab-project-invitation-create command line option, 659
 gitlab-project-invitation-update command line option, 661
 gitlab-project-member-create command line option, 693
 gitlab-project-member-update command line option, 695
 gitlab-project-share command line option, 603
 gitlab-user-impersonation-token-create command line option, 815
 gitlab-user-personal-access-token-create command line option, 818
--extern-uid
 gitlab-user-create command line option, 804
 gitlab-user-list command line option, 806
 gitlab-user-update command line option, 808
--external
 gitlab-user-create command line option, 805
 gitlab-user-list command line option, 806
 gitlab-user-update command line option, 808
--fields
 gitlab command line option, 484
--favicon
 gitlab-application-appearance-update command line option, 487
--feature-flags-access-level
 gitlab-project-create command line option, 596
 gitlab-project-update command line option, 609
--file
 gitlab-project-secure-file-create command line option, 766
--file-name
 gitlab-generic-package-download command line option, 507
 gitlab-generic-package-upload command line option, 507
 gitlab-project-snippet-create command line option, 770
 gitlab-project-snippet-update command line option, 771

```
gitlab-snippet-create command line
    option, 796
gitlab-snippet-update command line
    option, 798
--file-name-regex
    gitlab-group-push-rules-create command
        line option, 572
    gitlab-group-push-rules-update command
        line option, 573
    gitlab-project-push-rules-create
        command line option, 752
    gitlab-project-push-rules-update
        command line option, 753
--file-path
    gitlab-project-file-blame command line
        option, 650
    gitlab-project-file-create command line
        option, 650
    gitlab-project-file-delete command line
        option, 651
    gitlab-project-file-get command line
        option, 651
    gitlab-project-file-raw command line
        option, 651
    gitlab-project-file-update command line
        option, 652
--file-template-project-id
    gitlab-application-settings-update
        command line option, 491
    gitlab-group-update command line option,
        518
--filename
    gitlab-project-upload command line
        option, 610
--filepath
    gitlab-project-release-link-create
        command line option, 759
    gitlab-project-release-link-update
        command line option, 761
    gitlab-project-upload command line
        option, 610
--files-max-capacity
    gitlab-geo-node-update command line
        option, 510
--first-day-of-week
    gitlab-application-settings-update
        command line option, 491
--first-parent
    gitlab-project-commit-list command line
        option, 631
--font
    gitlab-broadcast-message-create command
        line option, 493
    gitlab-broadcast-message-update command
        line option, 495
    gitlab-application-appearance-update
        command line option, 487
--forked-from-id
    gitlab-project-create-fork-relation
        command line option, 597
--forking-access-level
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 608
--format
    gitlab-group-wiki-create command line
        option, 579
    gitlab-group-wiki-update command line
        option, 581
    gitlab-project-repository-archive
        command line option, 600
    gitlab-project-wiki-create command line
        option, 788
    gitlab-project-wiki-update command line
        option, 790
--from-
    gitlab-project-repository-compare
        command line option, 601
--fullname
    gitlab-license-get command line option,
        585
--geo-node-allowed-ips
    gitlab-application-settings-update
        command line option, 491
--get-all
    gitlab-application-list command line
        option, 486
    gitlab-audit-event-list command line
        option, 493
    gitlab-broadcast-message-list command
        line option, 494
    gitlab-bulk-import-all-entity-list
        command line option, 496
    gitlab-bulk-import-entity-list command
        line option, 497
    gitlab-bulk-import-list command line
        option, 496
    gitlab-current-user-email-list command
        line option, 500
    gitlab-current-user-gpg-key-list
        command line option, 501
    gitlab-current-user-key-list command
        line option, 502
    gitlab-deploy-key-list command line
        option, 503
    gitlab-deploy-token-list command line
```

option, 504
gitlab-dockerfile-list command line option, 505
gitlab-event-list command line option, 505
gitlab-feature-list command line option, 506
gitlab-geo-node-list command line option, 509
gitlab-gitignore-list command line option, 510
gitlab-gitlabciyml-list command line option, 511
gitlab-group-access-request-list command line option, 519
gitlab-group-access-token-list command line option, 521
gitlab-group-audit-event-list command line option, 522
gitlab-group-badge-list command line option, 523
gitlab-group-billable-member-list command line option, 525
gitlab-group-billable-member-membership-list command line option, 525
gitlab-group-board-list command line option, 527
gitlab-group-board-list-list command line option, 529
gitlab-group-cluster-list command line option, 531
gitlab-group-custom-attribute-list command line option, 532
gitlab-group-deploy-token-list command line option, 534
gitlab-group-descendant-group-list command line option, 535
gitlab-group-emoji-list command line option, 539
gitlab-group-epic-issue-list command line option, 543
gitlab-group-epic-list command line option, 537
gitlab-group-epic-note-award-emoji-list command line option, 547
gitlab-group-epic-note-list command line option, 545
gitlab-group-epic-resource-label-event-list command line option, 548
gitlab-group-hook-list command line option, 550
gitlab-group-invitation-list command line option, 554
gitlab-group-issue-list command line option, 555
gitlab-group-iteration-list command line option, 556
gitlab-group-label-list command line option, 558
gitlab-group-ldap-group-link-list command line option, 560
gitlab-group-list command line option, 515
gitlab-group-member-all-list command line option, 563
gitlab-group-member-list command line option, 562
gitlab-group-merge-request-list command line option, 565
gitlab-group-milestone-list command line option, 567
gitlab-group-package-list command line option, 570
gitlab-group-project-list command line option, 571
gitlab-group-runner-list command line option, 574
gitlab-group-saml-group-link-list command line option, 575
gitlab-group-subgroup-list command line option, 576
gitlab-group-variable-list command line option, 578
gitlab-group-wiki-list command line option, 580
gitlab-hook-list command line option, 582
gitlab-issue-list command line option, 583
gitlab-ldap-group-list command line option, 585
gitlab-license-list command line option, 585
gitlab-merge-request-list command line option, 587
gitlab-namespace-list command line option, 588
gitlab-pages-domain-list command line option, 590
gitlab-personal-access-token-list command line option, 591
gitlab-project-access-request-list command line option, 611
gitlab-project-access-token-list command line option, 613
gitlab-project-approval-rule-list command line option, 615
gitlab-project-audit-event-list command line option, 618

gitlab-project-badge-list command line option, 619
gitlab-project-board-list command line option, 621
gitlab-project-board-list-list command line option, 623
gitlab-project-branch-list command line option, 625
gitlab-project-cluster-list command line option, 628
gitlab-project-commit-comment-list command line option, 633
gitlab-project-commit-discussion-list command line option, 634
gitlab-project-commit-list command line option, 631
gitlab-project-commit-status-list command line option, 638
gitlab-project-custom-attribute-list command line option, 639
gitlab-project-deploy-token-list command line option, 640
gitlab-project-deployment-list command line option, 642
gitlab-project-deployment-merge-request-list command line option, 645
gitlab-project-environment-list command line option, 647
gitlab-project-event-list command line option, 648
gitlab-project-fork-list command line option, 653
gitlab-project-hook-list command line option, 655
gitlab-project-integration-list command line option, 658
gitlab-project-invitation-list command line option, 660
gitlab-project-issue-award-emoji-list command line option, 670
gitlab-project-issue-discussion-list command line option, 672
gitlab-project-issue-link-list command line option, 675
gitlab-project-issue-list command line option, 664
gitlab-project-issue-note-award-emoji-list command line option, 679
gitlab-project-issue-note-list command line option, 676
gitlab-project-issue-resource-iteration-event-list command line option, 680
gitlab-project-issue-resource-label-event-list command line option, 681
gitlab-project-issue-resource-milestone-event-list command line option, 682
gitlab-project-issue-resource-state-event-list command line option, 683
gitlab-project-issue-resource-weight-event-list command line option, 684
gitlab-project-job-list command line option, 687
gitlab-project-key-list command line option, 690
gitlab-project-label-list command line option, 692
gitlab-project-list command line option, 600
gitlab-project-member-all-list command line option, 696
gitlab-project-member-list command line option, 694
gitlab-project-merge-request-approval-rule-list command line option, 709
gitlab-project-merge-request-award-emoji-list command line option, 713
gitlab-project-merge-request-diff-list command line option, 713
gitlab-project-merge-request-discussion-list command line option, 715
gitlab-project-merge-request-list command line option, 702
gitlab-project-merge-request-note-award-emoji-list command line option, 721
gitlab-project-merge-request-note-list command line option, 719
gitlab-project-merge-request-pipeline-list command line option, 722
gitlab-project-merge-request-resource-label-event-list command line option, 723
gitlab-project-merge-request-resource-milestone-event-list command line option, 724
gitlab-project-merge-request-resource-state-event-list command line option, 725
gitlab-project-merge-train-list command line option, 726
gitlab-project-milestone-list command line option, 728
gitlab-project-note-list command line option, 730
gitlab-project-package-file-list command line option, 733
gitlab-project-package-list command line option, 732
gitlab-project-pages-domain-list command line option, 735
gitlab-project-pipeline-bridge-list command line option, 738

```

gitlab-project-pipeline-job-list command line option, 739
gitlab-project-pipeline-list command line option, 737
gitlab-project-pipeline-schedule-list command line option, 741
gitlab-project-pipeline-schedule-pipeline-listgitlab-runner-list command line option, 792
gitlab-project-pipeline-variable-list command line option, 746
gitlab-project-protected-branch-list command line option, 748
gitlab-project-protected-environment-list command line option, 749
gitlab-project-protected-tag-list command line option, 751
gitlab-project-registry-repository-list command line option, 754
gitlab-project-registry-tag-list command line option, 756
gitlab-project-release-link-list command line option, 760
gitlab-project-release-list command line option, 758
gitlab-project-remote-mirror-list command line option, 762
gitlab-project-resource-group-list command line option, 763
gitlab-project-resource-group-upcoming-job-list command line option, 764
gitlab-project-runner-list command line option, 765
gitlab-project-secure-file-list command line option, 767
gitlab-project-service-list command line option, 769
gitlab-project-snippet-award-emoji-list command line option, 773
gitlab-project-snippet-discussion-list command line option, 775
gitlab-project-snippet-list command line option, 771
gitlab-project-snippet-note-award-emoji-list command line option, 781
gitlab-project-snippet-note-list command line option, 778
gitlab-project-tag-list command line option, 783
gitlab-project-trigger-list command line option, 784
gitlab-project-user-list command line option, 785
gitlab-project-variable-list command line option, 787
gitlab-project-wiki-list command line option, 789
gitlab-runner-all-list command line option, 793
gitlab-runner-job-list command line option, 794
gitlab-shared-project-list command line option, 795
gitlab-snippet-list command line option, 797
gitlab-starred-project-list command line option, 799
gitlab-todo-list command line option, 800
gitlab-topic-list command line option, 802
gitlab-user-activities-list command line option, 809
gitlab-user-custom-attribute-list command line option, 810
gitlab-user-email-list command line option, 812
gitlab-user-event-list command line option, 813
gitlab-user-gpg-key-list command line option, 814
gitlab-user-impersonation-token-list command line option, 816
gitlab-user-key-list command line option, 817
gitlab-user-list command line option, 807
gitlab-user-membership-list command line option, 818
gitlab-user-project-list command line option, 821
gitlab-variable-list command line option, 823
--gitlab gitlab command line option, 484
--gravatar-enabled gitlab-application-settings-update command line option, 490
--group-access gitlab-group-add-ldap-group-link command line option, 512
gitlab-group-ldap-group-link-create command line option, 560
gitlab-group-share command line option, 516
gitlab-project-share command line option, 603
--group-id gitlab-group-access-request-approve

```

```
    command line option, 518
gitlab-group-access-request-create
    command line option, 519
gitlab-group-access-request-delete
    command line option, 519
gitlab-group-access-request-list
    command line option, 519
gitlab-group-access-token-create
    command line option, 520
gitlab-group-access-token-delete
    command line option, 520
gitlab-group-access-token-list command
    line option, 521
gitlab-group-audit-event-get command
    line option, 521
gitlab-group-audit-event-list command
    line option, 521
gitlab-group-badge-create command line
    option, 522
gitlab-group-badge-delete command line
    option, 522
gitlab-group-badge-get command line
    option, 523
gitlab-group-badge-list command line
    option, 523
gitlab-group-badge-render command line
    option, 523
gitlab-group-badge-update command line
    option, 524
gitlab-group-billable-member-delete
    command line option, 524
gitlab-group-billable-member-list
    command line option, 525
gitlab-group-billable-member-membership-list
    command line option, 525
gitlab-group-board-create command line
    option, 526
gitlab-group-board-delete command line
    option, 526
gitlab-group-board-get command line
    option, 526
gitlab-group-board-list command line
    option, 527
gitlab-group-board-list-create command
    line option, 528
gitlab-group-board-list-delete command
    line option, 528
gitlab-group-board-list-get command
    line option, 528
gitlab-group-board-list-list command
    line option, 529
gitlab-group-board-list-update command
    line option, 529
gitlab-group-board-update command line
    option, 527
gitlab-group-cluster-create command
    line option, 530
gitlab-group-cluster-delete command
    line option, 530
gitlab-group-cluster-get command line
    option, 530
gitlab-group-cluster-list command line
    option, 531
gitlab-group-cluster-update command
    line option, 531
gitlab-group-custom-attribute-delete
    command line option, 532
gitlab-group-custom-attribute-get
    command line option, 532
gitlab-group-custom-attribute-list
    command line option, 532
gitlab-group-deploy-token-create
    command line option, 533
gitlab-group-deploy-token-delete
    command line option, 533
gitlab-group-deploy-token-get command
    line option, 534
gitlab-group-deploy-token-list command
    line option, 534
gitlab-group-descendant-group-list
    command line option, 535
gitlab-group-epic-award-emoji-create
    command line option, 538
gitlab-group-epic-award-emoji-delete
    command line option, 539
gitlab-group-epic-award-emoji-get
    command line option, 539
gitlab-group-epic-award-emoji-list
    command line option, 539
gitlab-group-epic-create command line
    option, 536
gitlab-group-epic-delete command line
    option, 536
gitlab-group-epic-discussion-note-create
    command line option, 540
gitlab-group-epic-discussion-note-delete
    command line option, 540
gitlab-group-epic-discussion-note-get
    command line option, 541
gitlab-group-epic-discussion-note-update
    command line option, 541
gitlab-group-epic-get command line
    option, 537
gitlab-group-epic-issue-create command
    line option, 542
gitlab-group-epic-issue-delete command
    line option, 542
gitlab-group-epic-issue-list command
```

```

    line option, 542
gitlab-group-epic-issue-update command
    line option, 543
gitlab-group-epic-list command line
    option, 537
gitlab-group-epic-note-award-emoji-create
    command line option, 545
gitlab-group-epic-note-award-emoji-delete
    command line option, 546
gitlab-group-epic-note-award-emoji-get
    command line option, 546
gitlab-group-epic-note-award-emoji-list
    command line option, 546
gitlab-group-epic-note-create command
    line option, 543
gitlab-group-epic-note-delete command
    line option, 544
gitlab-group-epic-note-get command line
    option, 544
gitlab-group-epic-note-list command
    line option, 544
gitlab-group-epic-note-update command
    line option, 545
gitlab-group-epic-resource-label-event-get
    command line option, 547
gitlab-group-epic-resource-label-event-list
    command line option, 547
gitlab-group-epic-update command line
    option, 538
gitlab-group-export-create command line
    option, 548
gitlab-group-export-download command
    line option, 548
gitlab-group-export-get command line
    option, 548
gitlab-group-hook-create command line
    option, 549
gitlab-group-hook-delete command line
    option, 550
gitlab-group-hook-get command line
    option, 550
gitlab-group-hook-list command line
    option, 550
gitlab-group-hook-update command line
    option, 551
gitlab-group-import-get command line
    option, 552
gitlab-group-invitation-create command
    line option, 552
gitlab-group-invitation-delete command
    line option, 553
gitlab-group-invitation-get command
    line option, 553
gitlab-group-invitation-list command
    line option, 553
gitlab-group-invitation-update command
    line option, 554
gitlab-group-issue-list command line
    option, 555
gitlab-group-issues-statistics-get
    command line option, 556
gitlab-group-iteration-list command
    line option, 556
gitlab-group-label-create command line
    option, 557
gitlab-group-label-delete command line
    option, 557
gitlab-group-label-get command line
    option, 558
gitlab-group-label-list command line
    option, 558
gitlab-group-label-subscribe command
    line option, 558
gitlab-group-label-unsubscribe command
    line option, 559
gitlab-group-label-update command line
    option, 559
gitlab-group-ldap-group-link-create
    command line option, 560
gitlab-group-ldap-group-link-delete
    command line option, 560
gitlab-group-ldap-group-link-list
    command line option, 560
gitlab-group-member-all-get command
    line option, 563
gitlab-group-member-all-list command
    line option, 563
gitlab-group-member-create command line
    option, 561
gitlab-group-member-delete command line
    option, 561
gitlab-group-member-get command line
    option, 561
gitlab-group-member-list command line
    option, 562
gitlab-group-member-update command line
    option, 562
gitlab-group-merge-request-list command
    line option, 564
gitlab-group-milestone-create command
    line option, 566
gitlab-group-milestone-delete command
    line option, 566
gitlab-group-milestone-get command line
    option, 566
gitlab-group-milestone-issues command
    line option, 566
gitlab-group-milestone-list command
    line option, 566

```

```
    line option, 567
gitlab-group-milestone-merge-requests
    command line option, 567
gitlab-group-milestone-update command
    line option, 568
gitlab-group-notification-settings-get
    command line option, 568
gitlab-group-notification-settings-update
    command line option, 569
gitlab-group-package-list command line
    option, 570
gitlab-group-project-list command line
    option, 571
gitlab-group-push-rules-create command
    line option, 572
gitlab-group-push-rules-delete command
    line option, 572
gitlab-group-push-rules-get command
    line option, 573
gitlab-group-push-rules-update command
    line option, 573
gitlab-group-runner-list command line
    option, 574
gitlab-group-saml-group-link-create
    command line option, 575
gitlab-group-saml-group-link-delete
    command line option, 575
gitlab-group-saml-group-link-get
    command line option, 575
gitlab-group-saml-group-link-list
    command line option, 575
gitlab-group-share command line option,
    516
gitlab-group-subgroup-list command line
    option, 576
gitlab-group-transfer command line
    option, 516
gitlab-group-unshare command line
    option, 516
gitlab-group-variable-create command
    line option, 577
gitlab-group-variable-delete command
    line option, 577
gitlab-group-variable-get command line
    option, 578
gitlab-group-variable-list command line
    option, 578
gitlab-group-variable-update command
    line option, 578
gitlab-group-wiki-create command line
    option, 579
gitlab-group-wiki-delete command line
    option, 579
gitlab-group-wiki-get command line
    option, 580
gitlab-group-wiki-list command line
    option, 580
gitlab-group-wiki-update command line
    option, 580
gitlab-project-share command line
    option, 603
gitlab-project-unshare command line
    option, 604
gitlab-shared-project-list command line
    option, 795
--group-ids
    gitlab-project-approval-rule-create
        command line option, 615
    gitlab-project-merge-request-approval-rule-create
        command line option, 708
    gitlab-project-merge-request-approval-rule-update
        command line option, 710
--group-with-project-templates-id
    gitlab-project-create command line
        option, 595
--header-logo
    gitlab-application-appearance-update
        command line option, 487
--header-message
    gitlab-application-appearance-update
        command line option, 487
--help
    gitlab command line option, 484
    gitlab-application command line option,
        485
    gitlab-application-appearance command
        line option, 486
    gitlab-application-appearance-get
        command line option, 487
    gitlab-application-appearance-update
        command line option, 487
    gitlab-application-create command line
        option, 485
    gitlab-application-delete command line
        option, 486
    gitlab-application-list command line
        option, 486
    gitlab-application-settings command
        line option, 488
    gitlab-application-settings-get command
        line option, 488
    gitlab-application-settings-update
        command line option, 489
    gitlab-application-statistics command
        line option, 492
    gitlab-application-statistics-get
        command line option, 492
    gitlab-audit-event command line option,
```

```

    492
gitlab-audit-event-get command line
    option, 492
gitlab-audit-event-list command line
    option, 492
gitlab-broadcast-message command line
    option, 493
gitlab-broadcast-message-create command
    line option, 493
gitlab-broadcast-message-delete command
    line option, 494
gitlab-broadcast-message-get command
    line option, 494
gitlab-broadcast-message-list command
    line option, 494
gitlab-broadcast-message-update command
    line option, 494
gitlab-bulk-import command line option,
    495
gitlab-bulk-import-all-entity command
    line option, 496
gitlab-bulk-import-all-entity-list
    command line option, 496
gitlab-bulk-import-create command line
    option, 495
gitlab-bulk-import-entity command line
    option, 497
gitlab-bulk-import-entity-get command
    line option, 497
gitlab-bulk-import-entity-list command
    line option, 497
gitlab-bulk-import-get command line
    option, 495
gitlab-bulk-import-list command line
    option, 496
gitlab-ci-lint command line option, 498
gitlab-ci-lint-create command line
    option, 498
gitlab-ci-lint-validate command line
    option, 498
gitlab-current-user command line option,
    498
gitlab-current-user-email command line
    option, 499
gitlab-current-user-email-create
    command line option, 499
gitlab-current-user-email-delete
    command line option, 499
gitlab-current-user-email-get command
    line option, 499
gitlab-current-user-email-list command
    line option, 500
gitlab-current-user-get command line
    option, 499
gitlab-current-user-gpg-key command
    line option, 500
gitlab-current-user-gpg-key-create
    command line option, 500
gitlab-current-user-gpg-key-delete
    command line option, 500
gitlab-current-user-gpg-key-get command
    line option, 501
gitlab-current-user-gpg-key-list
    command line option, 501
gitlab-current-user-key command line
    option, 501
gitlab-current-user-key-create command
    line option, 501
gitlab-current-user-key-delete command
    line option, 502
gitlab-current-user-key-get command
    line option, 502
gitlab-current-user-key-list command
    line option, 502
gitlab-current-user-status command line
    option, 502
gitlab-current-user-status-get command
    line option, 503
gitlab-current-user-status-update
    command line option, 503
gitlab-deploy-key command line option,
    503
gitlab-deploy-key-list command line
    option, 503
gitlab-deploy-token command line option,
    504
gitlab-deploy-token-list command line
    option, 504
gitlab-dockerfile command line option,
    504
gitlab-dockerfile-get command line
    option, 504
gitlab-dockerfile-list command line
    option, 505
gitlab-event command line option, 505
gitlab-event-list command line option,
    505
gitlab-feature command line option, 506
gitlab-feature-delete command line
    option, 506
gitlab-feature-list command line option,
    506
gitlab-generic-package command line
    option, 507
gitlab-generic-package-download command
    line option, 507
gitlab-generic-package-upload command
    line option, 507

```

gitlab-geo-node command line option, 508
gitlab-geo-node-current-failures
 command line option, 508
gitlab-geo-node-delete command line
 option, 508
gitlab-geo-node-get command line option,
 508
gitlab-geo-node-list command line
 option, 509
gitlab-geo-node-repair command line
 option, 509
gitlab-geo-node-status command line
 option, 509
gitlab-geo-node-update command line
 option, 509
gitlab-gitignore command line option, 510
gitlab-gitignore-get command line
 option, 510
gitlab-gitignore-list command line
 option, 510
gitlab-gitlabciyml command line option,
 511
gitlab-gitlabciyml-get command line
 option, 511
gitlab-gitlabciyml-list command line
 option, 511
gitlab-group command line option, 512
gitlab-group-access-request command
 line option, 518
gitlab-group-access-request-approve
 command line option, 518
gitlab-group-access-request-create
 command line option, 519
gitlab-group-access-request-delete
 command line option, 519
gitlab-group-access-request-list
 command line option, 519
gitlab-group-access-token command line
 option, 520
gitlab-group-access-token-create
 command line option, 520
gitlab-group-access-token-delete
 command line option, 520
gitlab-group-access-token-list command
 line option, 520
gitlab-group-add-ldap-group-link
 command line option, 512
gitlab-group-audit-event command line
 option, 521
gitlab-group-audit-event-get command
 line option, 521
gitlab-group-audit-event-list command
 line option, 521
gitlab-group-badge command line option,
 522
gitlab-group-badge-create command line
 option, 522
gitlab-group-badge-delete command line
 option, 522
gitlab-group-badge-get command line
 option, 523
gitlab-group-badge-list command line
 option, 523
gitlab-group-badge-render command line
 option, 523
gitlab-group-badge-update command line
 option, 524
gitlab-group-billable-member command
 line option, 524
gitlab-group-billable-member-delete
 command line option, 524
gitlab-group-billable-member-list
 command line option, 524
gitlab-group-billable-member-membership
 command line option, 525
gitlab-group-billable-member-membership-list
 command line option, 525
gitlab-group-board command line option,
 526
gitlab-group-board-create command line
 option, 526
gitlab-group-board-delete command line
 option, 526
gitlab-group-board-get command line
 option, 526
gitlab-group-board-list command line
 option, 527
gitlab-group-board-list-create command
 line option, 528
gitlab-group-board-list-delete command
 line option, 528
gitlab-group-board-list-get command
 line option, 528
gitlab-group-board-list-list command
 line option, 529
gitlab-group-board-list-update command
 line option, 529
gitlab-group-board-update command line
 option, 527
gitlab-group-cluster command line
 option, 529
gitlab-group-cluster-create command
 line option, 530
gitlab-group-cluster-delete command
 line option, 530
gitlab-group-cluster-get command line
 option, 530
gitlab-group-cluster-list command line

```
    option, 531
gitlab-group-cluster-update command
    line option, 531
gitlab-group-create command line option,
    512
gitlab-group-custom-attribute command
    line option, 532
gitlab-group-custom-attribute-delete
    command line option, 532
gitlab-group-custom-attribute-get
    command line option, 532
gitlab-group-custom-attribute-list
    command line option, 532
gitlab-group-delete command line option,
    513
gitlab-group-delete-ldap-group-link
    command line option, 514
gitlab-group-deploy-token command line
    option, 533
gitlab-group-deploy-token-create
    command line option, 533
gitlab-group-deploy-token-delete
    command line option, 533
gitlab-group-deploy-token-get command
    line option, 534
gitlab-group-deploy-token-list command
    line option, 534
gitlab-group-descendant-group command
    line option, 534
gitlab-group-descendant-group-list
    command line option, 535
gitlab-group-epic command line option,
    536
gitlab-group-epic-award-emoji command
    line option, 538
gitlab-group-epic-award-emoji-create
    command line option, 538
gitlab-group-epic-award-emoji-delete
    command line option, 539
gitlab-group-epic-award-emoji-get
    command line option, 539
gitlab-group-epic-award-emoji-list
    command line option, 539
gitlab-group-epic-create command line
    option, 536
gitlab-group-epic-delete command line
    option, 536
gitlab-group-epic-discussion-note
    command line option, 540
gitlab-group-epic-discussion-note-create
    command line option, 540
gitlab-group-epic-discussion-note-delete
    command line option, 540
gitlab-group-epic-discussion-note-get
    command line option, 541
gitlab-group-epic-discussion-note-update
    command line option, 541
gitlab-group-epic-get command line
    option, 537
gitlab-group-epic-issue command line
    option, 542
gitlab-group-epic-issue-create command
    line option, 542
gitlab-group-epic-issue-delete command
    line option, 542
gitlab-group-epic-issue-list command
    line option, 542
gitlab-group-epic-issue-update command
    line option, 543
gitlab-group-epic-list command line
    option, 537
gitlab-group-epic-note command line
    option, 543
gitlab-group-epic-note-award-emoji
    command line option, 545
gitlab-group-epic-note-award-emoji-create
    command line option, 545
gitlab-group-epic-note-award-emoji-delete
    command line option, 546
gitlab-group-epic-note-award-emoji-get
    command line option, 546
gitlab-group-epic-note-award-emoji-list
    command line option, 546
gitlab-group-epic-note-create command
    line option, 543
gitlab-group-epic-note-delete command
    line option, 544
gitlab-group-epic-note-get command line
    option, 544
gitlab-group-epic-note-list command
    line option, 544
gitlab-group-epic-note-update command
    line option, 545
gitlab-group-epic-resource-label-event
    command line option, 547
gitlab-group-epic-resource-label-event-get
    command line option, 547
gitlab-group-epic-resource-label-event-list
    command line option, 547
gitlab-group-epic-update command line
    option, 538
gitlab-group-export command line option,
    548
gitlab-group-export-create command line
    option, 548
gitlab-group-export-download command
    line option, 548
gitlab-group-export-get command line
```

option, 548
gitlab-group-get command line option, 514
gitlab-group-hook command line option,
549
gitlab-group-hook-create command line
option, 549
gitlab-group-hook-delete command line
option, 550
gitlab-group-hook-get command line
option, 550
gitlab-group-hook-list command line
option, 550
gitlab-group-hook-update command line
option, 551
gitlab-group-import command line option,
552
gitlab-group-import-get command line
option, 552
gitlab-group-invitation command line
option, 552
gitlab-group-invitation-create command
line option, 552
gitlab-group-invitation-delete command
line option, 553
gitlab-group-invitation-get command
line option, 553
gitlab-group-invitation-list command
line option, 553
gitlab-group-invitation-update command
line option, 554
gitlab-group-issue command line option,
554
gitlab-group-issue-list command line
option, 554
gitlab-group-issues-statistics command
line option, 555
gitlab-group-issues-statistics-get
command line option, 556
gitlab-group-iteration command line
option, 556
gitlab-group-iteration-list command
line option, 556
gitlab-group-label command line option,
557
gitlab-group-label-create command line
option, 557
gitlab-group-label-delete command line
option, 557
gitlab-group-label-get command line
option, 558
gitlab-group-label-list command line
option, 558
gitlab-group-label-subscribe command
line option, 558
gitlab-group-label-unsubscribe command
line option, 559
gitlab-group-label-update command line
option, 559
gitlab-group-ldap-group-link command
line option, 559
gitlab-group-ldap-group-link-create
command line option, 560
gitlab-group-ldap-group-link-delete
command line option, 560
gitlab-group-ldap-group-link-list
command line option, 560
gitlab-group-ldap-sync command line
option, 514
gitlab-group-list command line option,
514
gitlab-group-member command line option,
561
gitlab-group-member-all command line
option, 563
gitlab-group-member-all-get command
line option, 563
gitlab-group-member-all-list command
line option, 563
gitlab-group-member-create command line
option, 561
gitlab-group-member-delete command line
option, 561
gitlab-group-member-get command line
option, 561
gitlab-group-member-list command line
option, 562
gitlab-group-member-update command line
option, 562
gitlab-group-merge-request command line
option, 564
gitlab-group-merge-request-list command
line option, 564
gitlab-group-milestone command line
option, 565
gitlab-group-milestone-create command
line option, 565
gitlab-group-milestone-delete command
line option, 566
gitlab-group-milestone-get command line
option, 566
gitlab-group-milestone-issues command
line option, 566
gitlab-group-milestone-list command
line option, 567
gitlab-group-milestone-merge-requests
command line option, 567
gitlab-group-milestone-update command
line option, 567

gitlab-group-notification-settings
 command line option, 568
gitlab-group-notification-settings-get
 command line option, 568
gitlab-group-notification-settings-update
 command line option, 569
gitlab-group-package command line
 option, 569
gitlab-group-package-list command line
 option, 569
gitlab-group-project command line
 option, 570
gitlab-group-project-list command line
 option, 570
gitlab-group-push-rules command line
 option, 571
gitlab-group-push-rules-create command
 line option, 572
gitlab-group-push-rules-delete command
 line option, 572
gitlab-group-push-rules-get command
 line option, 573
gitlab-group-push-rules-update command
 line option, 573
gitlab-group-restore command line
 option, 515
gitlab-group-runner command line option,
 574
gitlab-group-runner-list command line
 option, 574
gitlab-group-saml-group-link command
 line option, 574
gitlab-group-saml-group-link-create
 command line option, 574
gitlab-group-saml-group-link-delete
 command line option, 575
gitlab-group-saml-group-link-get
 command line option, 575
gitlab-group-saml-group-link-list
 command line option, 575
gitlab-group-search command line option,
 515
gitlab-group-share command line option,
 516
gitlab-group-subgroup command line
 option, 576
gitlab-group-subgroup-list command line
 option, 576
gitlab-group-transfer command line
 option, 516
gitlab-group-transfer-project command
 line option, 516
gitlab-group-unshare command line
 option, 516

gitlab-group-update command line option,
 517
gitlab-group-variable command line
 option, 577
gitlab-group-variable-create command
 line option, 577
gitlab-group-variable-delete command
 line option, 577
gitlab-group-variable-get command line
 option, 578
gitlab-group-variable-list command line
 option, 578
gitlab-group-variable-update command
 line option, 578
gitlab-group-wiki command line option,
 579
gitlab-group-wiki-create command line
 option, 579
gitlab-group-wiki-delete command line
 option, 579
gitlab-group-wiki-get command line
 option, 580
gitlab-group-wiki-list command line
 option, 580
gitlab-group-wiki-update command line
 option, 580
gitlab-hook command line option, 581
gitlab-hook-create command line option,
 581
gitlab-hook-delete command line option,
 581
gitlab-hook-get command line option, 581
gitlab-hook-list command line option, 582
gitlab-issue command line option, 582
gitlab-issue-get command line option, 582
gitlab-issue-list command line option,
 582
gitlab-issues-statistics command line
 option, 583
gitlab-issues-statistics-get command
 line option, 584
gitlab-key command line option, 584
gitlab-key-get command line option, 584
gitlab-ldap-group command line option,
 584
gitlab-ldap-group-list command line
 option, 584
gitlab-license command line option, 585
gitlab-license-get command line option,
 585
gitlab-license-list command line option,
 585
gitlab-merge-request command line
 option, 586

gitlab-merge-request-list command line
 option, 586
gitlab-namespace command line option, 588
gitlab-namespace-exists command line
 option, 588
gitlab-namespace-get command line
 option, 588
gitlab-namespace-list command line
 option, 588
gitlab-notification-settings command
 line option, 589
gitlab-notification-settings-get
 command line option, 589
gitlab-notification-settings-update
 command line option, 589
gitlab-pages-domain command line option,
 590
gitlab-pages-domain-list command line
 option, 590
gitlab-personal-access-token command
 line option, 590
gitlab-personal-access-token-delete
 command line option, 590
gitlab-personal-access-token-get
 command line option, 591
gitlab-personal-access-token-list
 command line option, 591
gitlab-project command line option, 592
gitlab-project-access-request command
 line option, 610
gitlab-project-access-request-approve
 command line option, 610
gitlab-project-access-request-create
 command line option, 611
gitlab-project-access-request-delete
 command line option, 611
gitlab-project-access-request-list
 command line option, 611
gitlab-project-access-token command
 line option, 612
gitlab-project-access-token-create
 command line option, 612
gitlab-project-access-token-delete
 command line option, 612
gitlab-project-access-token-list
 command line option, 612
gitlab-project-additional-statistics
 command line option, 613
gitlab-project-additional-statistics-get
 command line option, 613
gitlab-project-approval command line
 option, 613
gitlab-project-approval-get command
 line option, 613

gitlab-project-approval-rule command
 line option, 614
gitlab-project-approval-rule-create
 command line option, 614
gitlab-project-approval-rule-delete
 command line option, 615
gitlab-project-approval-rule-list
 command line option, 615
gitlab-project-approval-rule-update
 command line option, 616
gitlab-project-approval-update command
 line option, 614
gitlab-project-archive command line
 option, 592
gitlab-project-artifact command line
 option, 592, 616
gitlab-project-artifact-delete command
 line option, 616
gitlab-project-artifact-download
 command line option, 616
gitlab-project-artifact-raw command
 line option, 617
gitlab-project-artifacts command line
 option, 593
gitlab-project-audit-event command line
 option, 617
gitlab-project-audit-event-get command
 line option, 617
gitlab-project-audit-event-list command
 line option, 617
gitlab-project-badge command line
 option, 618
gitlab-project-badge-create command
 line option, 618
gitlab-project-badge-delete command
 line option, 618
gitlab-project-badge-get command line
 option, 619
gitlab-project-badge-list command line
 option, 619
gitlab-project-badge-render command
 line option, 619
gitlab-project-badge-update command
 line option, 620
gitlab-project-board command line
 option, 620
gitlab-project-board-create command
 line option, 620
gitlab-project-board-delete command
 line option, 620
gitlab-project-board-get command line
 option, 621
gitlab-project-board-list command line
 option, 621, 622

gitlab-project-board-list-create
 command line option, 622
gitlab-project-board-list-delete
 command line option, 622
gitlab-project-board-list-get command
 line option, 622
gitlab-project-board-list-list command
 line option, 623
gitlab-project-board-list-update
 command line option, 623
gitlab-project-board-update command
 line option, 621
gitlab-project-branch command line
 option, 623
gitlab-project-branch-create command
 line option, 624
gitlab-project-branch-delete command
 line option, 624
gitlab-project-branch-get command line
 option, 624
gitlab-project-branch-list command line
 option, 625
gitlab-project-ci-lint command line
 option, 625
gitlab-project-ci-lint-create command
 line option, 625
gitlab-project-ci-lint-get command line
 option, 626
gitlab-project-ci-lint-validate command
 line option, 626
gitlab-project-cluster command line
 option, 626
gitlab-project-cluster-create command
 line option, 626
gitlab-project-cluster-delete command
 line option, 627
gitlab-project-cluster-get command line
 option, 627
gitlab-project-cluster-list command
 line option, 628
gitlab-project-cluster-update command
 line option, 628
gitlab-project-commit command line
 option, 629
gitlab-project-commit-cherry-pick
 command line option, 629
gitlab-project-commit-comment command
 line option, 632
gitlab-project-commit-comment-create
 command line option, 632
gitlab-project-commit-comment-list
 command line option, 633
gitlab-project-commit-create command
 line option, 629

gitlab-project-commit-diff command line
 option, 630
gitlab-project-commit-discussion
 command line option, 633
gitlab-project-commit-discussion-create
 command line option, 633
gitlab-project-commit-discussion-get
 command line option, 634
gitlab-project-commit-discussion-list
 command line option, 634
gitlab-project-commit-discussion-note
 command line option, 635
gitlab-project-commit-discussion-note-create
 command line option, 635
gitlab-project-commit-discussion-note-delete
 command line option, 635
gitlab-project-commit-discussion-note-get
 command line option, 636
gitlab-project-commit-discussion-note-update
 command line option, 636
gitlab-project-commit-get command line
 option, 630
gitlab-project-commit-list command line
 option, 630
gitlab-project-commit-merge-requests
 command line option, 631
gitlab-project-commit-refs command line
 option, 631
gitlab-project-commit-revert command
 line option, 632
gitlab-project-commit-signature command
 line option, 632
gitlab-project-commit-status command
 line option, 637
gitlab-project-commit-status-create
 command line option, 637
gitlab-project-commit-status-list
 command line option, 637
gitlab-project-create command line
 option, 594
gitlab-project-create-fork-relation
 command line option, 597
gitlab-project-custom-attribute command
 line option, 638
gitlab-project-custom-attribute-delete
 command line option, 638
gitlab-project-custom-attribute-get
 command line option, 638
gitlab-project-custom-attribute-list
 command line option, 639
gitlab-project-delete command line
 option, 597
gitlab-project-delete-fork-relation
 command line option, 597

gitlab-project-delete-merged-branches
 command line option, 598
gitlab-project-deploy-token command
 line option, 639
gitlab-project-deploy-token-create
 command line option, 639
gitlab-project-deploy-token-delete
 command line option, 640
gitlab-project-deploy-token-get command
 line option, 640
gitlab-project-deploy-token-list
 command line option, 640
gitlab-project-deployment command line
 option, 641
gitlab-project-deployment-approval
 command line option, 641
gitlab-project-deployment-create
 command line option, 641
gitlab-project-deployment-get command
 line option, 642
gitlab-project-deployment-list command
 line option, 642
gitlab-project-deployment-merge-request
 command line option, 643
gitlab-project-deployment-merge-request-list
 command line option, 644
gitlab-project-deployment-update
 command line option, 643
gitlab-project-environment command line
 option, 645
gitlab-project-environment-create
 command line option, 645
gitlab-project-environment-delete
 command line option, 646
gitlab-project-environment-get command
 line option, 646
gitlab-project-environment-list command
 line option, 646
gitlab-project-environment-stop command
 line option, 647
gitlab-project-environment-update
 command line option, 647
gitlab-project-event command line
 option, 648
gitlab-project-event-list command line
 option, 648
gitlab-project-export command line
 option, 648
gitlab-project-export-create command
 line option, 649
gitlab-project-export-download command
 line option, 649
gitlab-project-export-get command line
 option, 649
gitlab-project-file command line option,
 649
gitlab-project-file-blame command line
 option, 650
gitlab-project-file-create command line
 option, 650
gitlab-project-file-delete command line
 option, 651
gitlab-project-file-get command line
 option, 651
gitlab-project-file-raw command line
 option, 651
gitlab-project-file-update command line
 option, 652
gitlab-project-fork command line option,
 652
gitlab-project-fork-create command line
 option, 652
gitlab-project-fork-list command line
 option, 653
gitlab-project-get command line option,
 598
gitlab-project-hook command line option,
 654
gitlab-project-hook-create command line
 option, 654
gitlab-project-hook-delete command line
 option, 655
gitlab-project-hook-get command line
 option, 655
gitlab-project-hook-list command line
 option, 655
gitlab-project-hook-update command line
 option, 656
gitlab-project-housekeeping command
 line option, 598
gitlab-project-import command line
 option, 657
gitlab-project-import-get command line
 option, 657
gitlab-project-integration command line
 option, 657
gitlab-project-integration-available
 command line option, 657
gitlab-project-integration-delete
 command line option, 657
gitlab-project-integration-get command
 line option, 658
gitlab-project-integration-list command
 line option, 658
gitlab-project-integration-update
 command line option, 658
gitlab-project-invitation command line
 option, 659

gitlab-project-invitation-create
 command line option, 659
gitlab-project-invitation-delete
 command line option, 659
gitlab-project-invitation-get command
 line option, 660
gitlab-project-invitation-list command
 line option, 660
gitlab-project-invitation-update
 command line option, 660
gitlab-project-issue command line
 option, 661
gitlab-project-issue-add-spent-time
 command line option, 661
gitlab-project-issue-award-emoji
 command line option, 669
gitlab-project-issue-award-emoji-create
 command line option, 669
gitlab-project-issue-award-emoji-delete
 command line option, 669
gitlab-project-issue-award-emoji-get
 command line option, 670
gitlab-project-issue-award-emoji-list
 command line option, 670
gitlab-project-issue-closed-by command
 line option, 662
gitlab-project-issue-create command
 line option, 662
gitlab-project-issue-delete command
 line option, 663
gitlab-project-issue-discussion command
 line option, 670
gitlab-project-issue-discussion-create
 command line option, 671
gitlab-project-issue-discussion-get
 command line option, 671
gitlab-project-issue-discussion-list
 command line option, 671
gitlab-project-issue-discussion-note
 command line option, 672
gitlab-project-issue-discussion-note-create
 command line option, 672
gitlab-project-issue-discussion-note-delete
 command line option, 673
gitlab-project-issue-discussion-note-get
 command line option, 673
gitlab-project-issue-discussion-note-update
 command line option, 673
gitlab-project-issue-get command line
 option, 663
gitlab-project-issue-link command line
 option, 674
gitlab-project-issue-link-create
 command line option, 674

gitlab-project-issue-link-delete
 command line option, 674
gitlab-project-issue-link-list command
 line option, 675
gitlab-project-issue-list command line
 option, 663
gitlab-project-issue-move command line
 option, 664
gitlab-project-issue-note command line
 option, 675
gitlab-project-issue-note-award-emoji
 command line option, 677
gitlab-project-issue-note-award-emoji-create
 command line option, 677
gitlab-project-issue-note-award-emoji-delete
 command line option, 678
gitlab-project-issue-note-award-emoji-get
 command line option, 678
gitlab-project-issue-note-award-emoji-list
 command line option, 678
gitlab-project-issue-note-create
 command line option, 675
gitlab-project-issue-note-delete
 command line option, 676
gitlab-project-issue-note-get command
 line option, 676
gitlab-project-issue-note-list command
 line option, 676
gitlab-project-issue-note-update
 command line option, 677
gitlab-project-issue-participants
 command line option, 665
gitlab-project-issue-related-merge-requests
 command line option, 665
gitlab-project-issue-reorder command
 line option, 665
gitlab-project-issue-reset-spent-time
 command line option, 666
gitlab-project-issue-reset-time-estimate
 command line option, 666
gitlab-project-issue-resource-iteration-event
 command line option, 679
gitlab-project-issue-resource-iteration-event-get
 command line option, 679
gitlab-project-issue-resource-iteration-event-list
 command line option, 679
gitlab-project-issue-resource-label-event
 command line option, 680
gitlab-project-issue-resource-label-event-get
 command line option, 680
gitlab-project-issue-resource-label-event-list
 command line option, 680
gitlab-project-issue-resource-milestone-event
 command line option, 681

gitlab-project-issue-resource-milestone-event command line option, 681
gitlab-project-issue-resource-milestone-event command line option, 682
gitlab-project-issue-resource-state-event command line option, 682
gitlab-project-issue-resource-state-event-get command line option, 682
gitlab-project-issue-resource-state-event-list command line option, 683
gitlab-project-issue-resource-weight-event command line option, 683
gitlab-project-issue-resource-weight-event-get command line option, 683
gitlab-project-issue-resource-weight-event-list command line option, 684
gitlab-project-issue-subscribe command line option, 666
gitlab-project-issue-time-estimate command line option, 666
gitlab-project-issue-time-stats command line option, 667
gitlab-project-issue-todo command line option, 667
gitlab-project-issue-unsubscribe command line option, 667
gitlab-project-issue-update command line option, 668
gitlab-project-issue-user-agent-detail command line option, 668
gitlab-project-issues-statistics command line option, 684
gitlab-project-issues-statistics-get command line option, 684
gitlab-project-job command line option, 685
gitlab-project-job-artifact command line option, 685
gitlab-project-job-artifacts command line option, 685
gitlab-project-job-cancel command line option, 686
gitlab-project-job-delete-artifacts command line option, 686
gitlab-project-job-erase command line option, 686
gitlab-project-job-get command line option, 686
gitlab-project-job-keep-artifacts command line option, 687
gitlab-project-job-list command line option, 687
gitlab-project-job-play command line option, 687
gitlab-project-job-retry command line option, 688
gitlab-project-job-trace command line option, 688
gitlab-project-key command line option, 688
gitlab-project-key-create command line option, 688
gitlab-project-key-delete command line option, 689
gitlab-project-key-enable command line option, 689
gitlab-project-key-get command line option, 689
gitlab-project-key-list command line option, 690
gitlab-project-key-update command line option, 690
gitlab-project-label command line option, 690
gitlab-project-label-create command line option, 691
gitlab-project-label-delete command line option, 691
gitlab-project-label-get command line option, 691
gitlab-project-label-list command line option, 692
gitlab-project-label-subscribe command line option, 692
gitlab-project-label-unsubscribe command line option, 692
gitlab-project-label-update command line option, 693
gitlab-project-languages command line option, 598
gitlab-project-list command line option, 599
gitlab-project-member command line option, 693
gitlab-project-member-all command line option, 695
gitlab-project-member-all-get command line option, 695
gitlab-project-member-all-list command line option, 695
gitlab-project-member-create command line option, 693
gitlab-project-member-delete command line option, 694
gitlab-project-member-get command line option, 694
gitlab-project-member-list command line option, 694

```

gitlab-project-member-update command
    line option, 695
gitlab-project-merge-request command
    line option, 696
gitlab-project-merge-request-add-spent-time
    command line option, 697
gitlab-project-merge-request-approval
    command line option, 707
gitlab-project-merge-request-approval-get
    command line option, 707
gitlab-project-merge-request-approval-rule
    command line option, 707
gitlab-project-merge-request-approval-rule-create
    command line option, 708
gitlab-project-merge-request-approval-rule-delete
    command line option, 708
gitlab-project-merge-request-approval-rule-get
    command line option, 709
gitlab-project-merge-request-approval-rule-list
    command line option, 709
gitlab-project-merge-request-approval-state
    command line option, 710
gitlab-project-merge-request-approval-state-get
    command line option, 711
gitlab-project-merge-request-approval-update
    command line option, 707
gitlab-project-merge-request-approve
    command line option, 697
gitlab-project-merge-request-award-emoji
    command line option, 711
gitlab-project-merge-request-award-emoji-create
    command line option, 711
gitlab-project-merge-request-award-emoji-delete
    command line option, 712
gitlab-project-merge-request-award-emoji-get
    command line option, 712
gitlab-project-merge-request-award-emoji-list
    command line option, 712
gitlab-project-merge-request-cancel-merge-whengitlab-project-merge-request-note-award-emoji-get
    command line option, 697
gitlab-project-merge-request-changes
    command line option, 698
gitlab-project-merge-request-closes-issues
    command line option, 698
gitlab-project-merge-request-commits
    command line option, 698
gitlab-project-merge-request-create
    command line option, 699
gitlab-project-merge-request-delete
    command line option, 700
gitlab-project-merge-request-diff
    command line option, 713
gitlab-project-merge-request-diff-get
    command line option, 713
gitlab-project-merge-request-diff-list
    command line option, 713
gitlab-project-merge-request-discussion
    command line option, 714
gitlab-project-merge-request-discussion-create
    command line option, 714
gitlab-project-merge-request-discussion-get
    command line option, 714
gitlab-project-merge-request-discussion-list
    command line option, 715
gitlab-project-merge-request-discussion-note
    command line option, 716
gitlab-project-merge-request-discussion-note-create
    command line option, 716
gitlab-project-merge-request-discussion-note-delete
    command line option, 716
gitlab-project-merge-request-discussion-note-get
    command line option, 717
gitlab-project-merge-request-discussion-note-update
    command line option, 717
gitlab-project-merge-request-list
    command line option, 701
gitlab-project-merge-request-merge
    command line option, 702
gitlab-project-merge-request-merge-ref
    command line option, 702
gitlab-project-merge-request-note
    command line option, 718
gitlab-project-merge-request-note-award-emoji
    command line option, 720
gitlab-project-merge-request-note-award-emoji-create
    command line option, 720
gitlab-project-merge-request-note-award-emoji-delete
    command line option, 720
gitlab-project-merge-request-note-award-emoji-get
    command line option, 721
gitlab-project-merge-request-note-award-emoji-list
    command line option, 721
gitlab-project-merge-request-note-create
    command line option, 718
gitlab-project-merge-request-note-delete
    command line option, 718
gitlab-project-merge-request-note-get
    command line option, 719
gitlab-project-merge-request-note-list
    command line option, 719
gitlab-project-merge-request-note-update
    command line option, 719

```

gitlab-project-merge-request-participants command line option, 703
gitlab-project-merge-request-pipeline command line option, 722
gitlab-project-merge-request-pipeline-create command line option, 722
gitlab-project-merge-request-pipeline-list command line option, 722
gitlab-project-merge-request-rebase command line option, 703
gitlab-project-merge-request-reset-approvals command line option, 703
gitlab-project-merge-request-reset-spent-time command line option, 703
gitlab-project-merge-request-reset-time-estimate command line option, 704
gitlab-project-merge-request-resource-label-event command line option, 723
gitlab-project-merge-request-resource-label-event command line option, 723
gitlab-project-merge-request-resource-label-event command line option, 723
gitlab-project-merge-request-resource-milestone command line option, 724
gitlab-project-merge-request-resource-state-event command line option, 725
gitlab-project-merge-request-resource-state-event command line option, 725
gitlab-project-merge-request-resource-state-event command line option, 725
gitlab-project-merge-request-state-event command line option, 725
gitlab-project-merge-request-subscribe command line option, 704
gitlab-project-merge-request-time-estimate command line option, 704
gitlab-project-merge-request-time-stats command line option, 705
gitlab-project-merge-request-todo command line option, 705
gitlab-project-merge-request-unapprove command line option, 705
gitlab-project-merge-request-unsubscribe command line option, 705
gitlab-project-merge-request-update command line option, 706
gitlab-project-merge-train command line option, 726
gitlab-project-merge-train-list command line option, 726
gitlab-project-milestone command line option, 726
gitlab-project-milestone-create command line option, 727
gitlab-project-milestone-delete command line option, 727
gitlab-project-milestone-get command line option, 727
gitlab-project-milestone-issues command line option, 728
gitlab-project-milestone-list command line option, 728
gitlab-project-milestone-merge-requests command line option, 728
gitlab-project-milestone-update command line option, 729
gitlab-project-mirror-pull command line option, 600
gitlab-project-mirror-pull-details command line option, 600
gitlab-project-note command line option, 729
gitlab-project-note-get command line option, 729
gitlab-project-note-list command line option, 730
gitlab-project-notification-settings command line option, 730
gitlab-project-notification-settings-get command line option, 730
gitlab-project-notification-settings-update command line option, 731
gitlab-project-package command line option, 731
gitlab-project-package-delete command line option, 732
gitlab-project-package-file command line option, 733
gitlab-project-package-file-delete command line option, 733
gitlab-project-package-file-list command line option, 733
gitlab-project-package-get command line option, 732
gitlab-project-package-list command line option, 732
gitlab-project-pages-domain command line option, 734
gitlab-project-pages-domain-create command line option, 734
gitlab-project-pages-domain-delete command line option, 734
gitlab-project-pages-domain-get command line option, 735
gitlab-project-pages-domain-list command line option, 735

gitlab-project-pages-domain-update
 command line option, 735

gitlab-project-pipeline command line
 option, 736

gitlab-project-pipeline-bridge command
 line option, 738

gitlab-project-pipeline-bridge-list
 command line option, 738

gitlab-project-pipeline-cancel command
 line option, 736

gitlab-project-pipeline-create command
 line option, 736

gitlab-project-pipeline-delete command
 line option, 736

gitlab-project-pipeline-get command
 line option, 737

gitlab-project-pipeline-job command
 line option, 739

gitlab-project-pipeline-job-list
 command line option, 739

gitlab-project-pipeline-list command
 line option, 737

gitlab-project-pipeline-retry command
 line option, 738

gitlab-project-pipeline-schedule
 command line option, 739

gitlab-project-pipeline-schedule-create
 command line option, 740

gitlab-project-pipeline-schedule-delete
 command line option, 740

gitlab-project-pipeline-schedule-get
 command line option, 740

gitlab-project-pipeline-schedule-list
 command line option, 741

gitlab-project-pipeline-schedule-pipeline
 command line option, 742

gitlab-project-pipeline-schedule-pipeline-list
 command line option, 742

gitlab-project-pipeline-schedule-play
 command line option, 741

gitlab-project-pipeline-schedule-take-ownership
 command line option, 741

gitlab-project-pipeline-schedule-update
 command line option, 742

gitlab-project-pipeline-schedule-variable
 command line option, 743

gitlab-project-pipeline-schedule-variable-create
 command line option, 743

gitlab-project-pipeline-schedule-variable-delete
 command line option, 744

gitlab-project-pipeline-schedule-variable-update
 command line option, 744

gitlab-project-pipeline-test-report
 command line option, 744

gitlab-project-pipeline-test-report-get
 command line option, 745

gitlab-project-pipeline-test-report-summary
 command line option, 745

gitlab-project-pipeline-test-report-summary-get
 command line option, 745

gitlab-project-pipeline-variable
 command line option, 745

gitlab-project-pipeline-variable-list
 command line option, 746

gitlab-project-protected-branch command
 line option, 746

gitlab-project-protected-branch-create
 command line option, 746

gitlab-project-protected-branch-delete
 command line option, 747

gitlab-project-protected-branch-get
 command line option, 747

gitlab-project-protected-branch-list
 command line option, 748

gitlab-project-protected-environment
 command line option, 748

gitlab-project-protected-environment-create
 command line option, 748

gitlab-project-protected-environment-delete
 command line option, 749

gitlab-project-protected-environment-get
 command line option, 749

gitlab-project-protected-environment-list
 command line option, 749

gitlab-project-protected-tag command
 line option, 750

gitlab-project-protected-tag-create
 command line option, 750

gitlab-project-protected-tag-delete
 command line option, 750

gitlab-project-protected-tag-get
 command line option, 751

gitlab-project-protected-tag-list
 command line option, 751

gitlab-project-push-rules command line
 option, 751

gitlab-project-push-rules-create
 command line option, 752

gitlab-project-push-rules-delete
 command line option, 752

gitlab-project-push-rules-get command
 line option, 753

gitlab-project-push-rules-update
 command line option, 753

gitlab-project-registry-repository
 command line option, 754

gitlab-project-registry-repository-delete
 command line option, 754

```
gitlab-project-registry-repository-list
    command line option, 754
gitlab-project-registry-tag command
    line option, 755
gitlab-project-registry-tag-delete
    command line option, 755
gitlab-project-registry-tag-delete-in-bulk
    command line option, 755
gitlab-project-registry-tag-get command
    line option, 756
gitlab-project-registry-tag-list
    command line option, 756
gitlab-project-release command line
    option, 756
gitlab-project-release-create command
    line option, 757
gitlab-project-release-delete command
    line option, 757
gitlab-project-release-get command line
    option, 757
gitlab-project-release-link command
    line option, 759
gitlab-project-release-link-create
    command line option, 759
gitlab-project-release-link-delete
    command line option, 759
gitlab-project-release-link-get command
    line option, 760
gitlab-project-release-link-list
    command line option, 760
gitlab-project-release-link-update
    command line option, 760
gitlab-project-release-list command
    line option, 758
gitlab-project-release-update command
    line option, 758
gitlab-project-remote-mirror command
    line option, 761
gitlab-project-remote-mirror-create
    command line option, 761
gitlab-project-remote-mirror-list
    command line option, 761
gitlab-project-remote-mirror-update
    command line option, 762
gitlab-project-repository-archive
    command line option, 600
gitlab-project-repository-blob command
    line option, 601
gitlab-project-repository-compare
    command line option, 601
gitlab-project-repository-contributors
    command line option, 601
gitlab-project-repository-merge-base
    command line option, 601
gitlab-project-repository-raw-blob
    command line option, 602
gitlab-project-repository-tree command
    line option, 602
gitlab-project-resource-group command
    line option, 762
gitlab-project-resource-group-get
    command line option, 762
gitlab-project-resource-group-list
    command line option, 763
gitlab-project-resource-group-upcoming-job
    command line option, 764
gitlab-project-resource-group-upcoming-job-list
    command line option, 764
gitlab-project-resource-group-update
    command line option, 763
gitlab-project-restore command line
    option, 602
gitlab-project-runner command line
    option, 764
gitlab-project-runner-create command
    line option, 764
gitlab-project-runner-delete command
    line option, 765
gitlab-project-runner-list command line
    option, 765
gitlab-project-search command line
    option, 602
gitlab-project-secure-file command line
    option, 766
gitlab-project-secure-file-create
    command line option, 766
gitlab-project-secure-file-delete
    command line option, 766
gitlab-project-secure-file-download
    command line option, 766
gitlab-project-secure-file-get command
    line option, 767
gitlab-project-secure-file-list command
    line option, 767
gitlab-project-service command line
    option, 767
gitlab-project-service-available
    command line option, 768
gitlab-project-service-delete command
    line option, 768
gitlab-project-service-get command line
    option, 768
gitlab-project-service-list command
    line option, 768
gitlab-project-service-update command
    line option, 769
gitlab-project-share command line
    option, 603
```

gitlab-project-snapshot command line
 option, 603
gitlab-project-snippet command line
 option, 769
gitlab-project-snippet-award-emoji
 command line option, 772
gitlab-project-snippet-award-emoji-create
 command line option, 772
gitlab-project-snippet-award-emoji-delete
 command line option, 772
gitlab-project-snippet-award-emoji-get
 command line option, 773
gitlab-project-snippet-award-emoji-list
 command line option, 773
gitlab-project-snippet-content command
 line option, 769
gitlab-project-snippet-create command
 line option, 770
gitlab-project-snippet-delete command
 line option, 770
gitlab-project-snippet-discussion
 command line option, 774
gitlab-project-snippet-discussion-create
 command line option, 774
gitlab-project-snippet-discussion-get
 command line option, 774
gitlab-project-snippet-discussion-list
 command line option, 775
gitlab-project-snippet-discussion-note
 command line option, 775
gitlab-project-snippet-discussion-note-create
 command line option, 775
gitlab-project-snippet-discussion-note-delete
 command line option, 776
gitlab-project-snippet-discussion-note-get
 command line option, 776
gitlab-project-snippet-discussion-note-update
 command line option, 777
gitlab-project-snippet-get command line
 option, 770
gitlab-project-snippet-list command
 line option, 771
gitlab-project-snippet-note command
 line option, 777
gitlab-project-snippet-note-award-emoji
 command line option, 779
gitlab-project-snippet-note-award-emoji-create
 command line option, 779
gitlab-project-snippet-note-award-emoji-delete
 command line option, 780
gitlab-project-snippet-note-award-emoji-get
 command line option, 780
gitlab-project-snippet-note-award-emoji-list
 command line option, 781

gitlab-project-snippet-note-create
 command line option, 777
gitlab-project-snippet-note-delete
 command line option, 778
gitlab-project-snippet-note-get command
 line option, 778
gitlab-project-snippet-note-list
 command line option, 778
gitlab-project-snippet-note-update
 command line option, 779
gitlab-project-snippet-update command
 line option, 771
gitlab-project-snippet-user-agent-detail
 command line option, 772
gitlab-project-star command line option,
 603
gitlab-project-storage command line
 option, 781
gitlab-project-storage-get command line
 option, 781
gitlab-project-tag command line option,
 782
gitlab-project-tag-create command line
 option, 782
gitlab-project-tag-delete command line
 option, 782
gitlab-project-tag-get command line
 option, 782
gitlab-project-tag-list command line
 option, 783
gitlab-project-transfer command line
 option, 603
gitlab-project-transfer-project command
 line option, 604
gitlab-project-trigger command line
 option, 783
gitlab-project-trigger-create command
 line option, 783
gitlab-project-trigger-delete command
 line option, 784
gitlab-project-trigger-get command line
 option, 784
gitlab-project-trigger-list command
 line option, 784
gitlab-project-trigger-pipeline command
 line option, 604
gitlab-project-trigger-update command
 line option, 785
gitlab-project-unarchive command line
 option, 604
gitlab-project-unshare command line
 option, 604
gitlab-project-unstar command line
 option, 605

gitlab-project-update command line
 option, 607
gitlab-project-update-submodule command
 line option, 610
gitlab-project-upload command line
 option, 610
gitlab-project-user command line option,
 785
gitlab-project-user-list command line
 option, 785
gitlab-project-variable command line
 option, 786
gitlab-project-variable-create command
 line option, 786
gitlab-project-variable-delete command
 line option, 786
gitlab-project-variable-get command
 line option, 787
gitlab-project-variable-list command
 line option, 787
gitlab-project-variable-update command
 line option, 787
gitlab-project-wiki command line option,
 788
gitlab-project-wiki-create command line
 option, 788
gitlab-project-wiki-delete command line
 option, 788
gitlab-project-wiki-get command line
 option, 789
gitlab-project-wiki-list command line
 option, 789
gitlab-project-wiki-update command line
 option, 789
gitlab-registry-repository command line
 option, 790
gitlab-registry-repository-get command
 line option, 790
gitlab-runner command line option, 790
gitlab-runner-all command line option,
 790, 793
gitlab-runner-all-list command line
 option, 793
gitlab-runner-create command line
 option, 791
gitlab-runner-delete command line
 option, 791
gitlab-runner-get command line option,
 791
gitlab-runner-job command line option,
 794
gitlab-runner-job-list command line
 option, 794
gitlab-runner-list command line option,
 792
gitlab-runner-update command line
 option, 792
gitlab-runner-verify command line
 option, 793
gitlab-shared-project command line
 option, 794
gitlab-shared-project-list command line
 option, 795
gitlab-snippet command line option, 795
gitlab-snippet-content command line
 option, 796
gitlab-snippet-create command line
 option, 796
gitlab-snippet-delete command line
 option, 796
gitlab-snippet-get command line option,
 797
gitlab-snippet-list command line option,
 797
gitlab-snippet-public command line
 option, 797
gitlab-snippet-update command line
 option, 797
gitlab-snippet-user-agent-detail
 command line option, 798
gitlab-starred-project command line
 option, 798
gitlab-starred-project-list command
 line option, 798
gitlab-todo command line option, 799
gitlab-todo-delete command line option,
 799
gitlab-todo-list command line option, 800
gitlab-todo-mark-all-as-done command
 line option, 800
gitlab-todo-mark-as-done command line
 option, 800
gitlab-topic command line option, 801
gitlab-topic-create command line option,
 801
gitlab-topic-delete command line option,
 801
gitlab-topic-get command line option, 801
gitlab-topic-list command line option,
 802
gitlab-topic-merge command line option,
 802
gitlab-topic-update command line option,
 802
gitlab-user command line option, 803
gitlab-user-activate command line
 option, 803
gitlab-user-activities command line

```
    option, 809
gitlab-user-activities-list command
    line option, 809
gitlab-user-approve command line option,
    803
gitlab-user-ban command line option, 803
gitlab-user-block command line option,
    804
gitlab-user-create command line option,
    804
gitlab-user-custom-attribute command
    line option, 809
gitlab-user-custom-attribute-delete
    command line option, 810
gitlab-user-custom-attribute-get
    command line option, 810
gitlab-user-custom-attribute-list
    command line option, 810
gitlab-user-deactivate command line
    option, 805
gitlab-user-delete command line option,
    805
gitlab-user-email command line option,
    811
gitlab-user-email-create command line
    option, 811
gitlab-user-email-delete command line
    option, 811
gitlab-user-email-get command line
    option, 811
gitlab-user-email-list command line
    option, 812
gitlab-user-event command line option,
    812
gitlab-user-event-list command line
    option, 812
gitlab-user-follow command line option,
    806
gitlab-user-get command line option, 806
gitlab-user-gpg-key command line option,
    813
gitlab-user-gpg-key-create command line
    option, 813
gitlab-user-gpg-key-delete command line
    option, 813
gitlab-user-gpg-key-get command line
    option, 814
gitlab-user-gpg-key-list command line
    option, 814
gitlab-user-impersonation-token command
    line option, 814
gitlab-user-impersonation-token-create
    command line option, 814
gitlab-user-impersonation-token-delete
    command line option, 815
gitlab-user-impersonation-token-get
    command line option, 815
gitlab-user-impersonation-token-list
    command line option, 815
gitlab-user-key command line option, 816
gitlab-user-key-create command line
    option, 816
gitlab-user-key-delete command line
    option, 816
gitlab-user-key-get command line option,
    817
gitlab-user-key-list command line
    option, 817
gitlab-user-list command line option, 806
gitlab-user-membership command line
    option, 817
gitlab-user-membership-get command line
    option, 817
gitlab-user-membership-list command
    line option, 818
gitlab-user-personal-access-token
    command line option, 818
gitlab-user-personal-access-token-create
    command line option, 818
gitlab-user-project command line option,
    819
gitlab-user-project-create command line
    option, 819
gitlab-user-project-list command line
    option, 820
gitlab-user-reject command line option,
    807
gitlab-user-status command line option,
    821
gitlab-user-status-get command line
    option, 821
gitlab-user-unban command line option,
    807
gitlab-user-unblock command line option,
    807
gitlab-user-unfollow command line
    option, 807
gitlab-user-update command line option,
    808
gitlab-variable command line option, 821
gitlab-variable-create command line
    option, 822
gitlab-variable-delete command line
    option, 822
gitlab-variable-get command line option,
    822
gitlab-variable-list command line
    option, 823
```

```
gitlab-variable-update command line
    option, 823
--home-page-url
    gitlab-application-settings-update
        command line option, 490
--id
    gitlab-application-delete command line
        option, 486
    gitlab-application-settings-update
        command line option, 490
    gitlab-audit-event-get command line
        option, 492
    gitlab-broadcast-message-delete command
        line option, 494
    gitlab-broadcast-message-get command
        line option, 494
    gitlab-broadcast-message-update command
        line option, 495
    gitlab-bulk-import-entity-get command
        line option, 497
    gitlab-bulk-import-get command line
        option, 495
    gitlab-current-user-email-delete
        command line option, 499
    gitlab-current-user-email-get command
        line option, 499
    gitlab-current-user-gpg-key-delete
        command line option, 500
    gitlab-current-user-gpg-key-get command
        line option, 501
    gitlab-current-user-key-delete command
        line option, 502
    gitlab-current-user-key-get command
        line option, 502
    gitlab-geo-node-current-failures
        command line option, 508
    gitlab-geo-node-delete command line
        option, 508
    gitlab-geo-node-get command line option,
        508
    gitlab-geo-node-repair command line
        option, 509
    gitlab-geo-node-status command line
        option, 509
    gitlab-geo-node-update command line
        option, 509
    gitlab-group-access-request-approve
        command line option, 518
    gitlab-group-access-request-delete
        command line option, 519
    gitlab-group-access-token-delete
        command line option, 520
    gitlab-group-add-ldap-group-link
        command line option, 512
    gitlab-group-audit-event-get command
        line option, 521
    gitlab-group-badge-delete command line
        option, 522
    gitlab-group-badge-get command line
        option, 523
    gitlab-group-badge-render command line
        option, 523
    gitlab-group-badge-update command line
        option, 524
    gitlab-group-billable-member-delete
        command line option, 524
    gitlab-group-board-delete command line
        option, 526
    gitlab-group-board-get command line
        option, 526
    gitlab-group-board-list-delete command
        line option, 528
    gitlab-group-board-list-get command
        line option, 528
    gitlab-group-board-list-update command
        line option, 529
    gitlab-group-board-update command line
        option, 527
    gitlab-group-cluster-delete command
        line option, 530
    gitlab-group-cluster-get command line
        option, 530
    gitlab-group-cluster-update command
        line option, 531
    gitlab-group-delete command line option,
        513
    gitlab-group-delete-ldap-group-link
        command line option, 514
    gitlab-group-deploy-token-delete
        command line option, 533
    gitlab-group-deploy-token-get command
        line option, 534
    gitlab-group-epic-award-emoji-delete
        command line option, 539
    gitlab-group-epic-award-emoji-get
        command line option, 539
    gitlab-group-epic-discussion-note-delete
        command line option, 541
    gitlab-group-epic-discussion-note-get
        command line option, 541
    gitlab-group-epic-discussion-note-update
        command line option, 541
    gitlab-group-epic-note-award-emoji-delete
        command line option, 546
    gitlab-group-epic-note-award-emoji-get
        command line option, 546
    gitlab-group-epic-note-delete command
        line option, 544
```

```

gitlab-group-epic-note-get command line
    option, 544
gitlab-group-epic-note-update command
    line option, 545
gitlab-group-epic-resource-label-event-get
    command line option, 547
gitlab-group-get command line option, 514
gitlab-group-hook-delete command line
    option, 550
gitlab-group-hook-get command line
    option, 550
gitlab-group-hook-update command line
    option, 551
gitlab-group-ldap-group-link-delete
    command line option, 560
gitlab-group-ldap-sync command line
    option, 514
gitlab-group-member-all-get command
    line option, 563
gitlab-group-member-delete command line
    option, 561
gitlab-group-member-get command line
    option, 562
gitlab-group-member-update command line
    option, 562
gitlab-group-milestone-delete command
    line option, 566
gitlab-group-milestone-get command line
    option, 566
gitlab-group-milestone-issues command
    line option, 566
gitlab-group-milestone-merge-requests
    command line option, 567
gitlab-group-milestone-update command
    line option, 568
gitlab-group-restore command line
    option, 515
gitlab-group-search command line option,
    515
gitlab-group-share command line option,
    516
gitlab-group-transfer command line
    option, 516
gitlab-group-transfer-project command
    line option, 516
gitlab-group-unshare command line
    option, 516
gitlab-group-update command line option,
    517
gitlab-hook-delete command line option,
    581
gitlab-hook-get command line option, 581
gitlab-issue-get command line option, 582
gitlab-key-get command line option, 584
gitlab-namespace-exists command line
    option, 588
gitlab-namespace-get command line
    option, 588
gitlab-personal-access-token-delete
    command line option, 590
gitlab-personal-access-token-get
    command line option, 591
gitlab-project-access-request-approve
    command line option, 610
gitlab-project-access-request-delete
    command line option, 611
gitlab-project-access-token-delete
    command line option, 612
gitlab-project-approval-rule-delete
    command line option, 615
gitlab-project-approval-rule-update
    command line option, 616
gitlab-project-archive command line
    option, 592
gitlab-project-artifact command line
    option, 592
gitlab-project-artifacts command line
    option, 593
gitlab-project-audit-event-get command
    line option, 617
gitlab-project-badge-delete command
    line option, 618
gitlab-project-badge-get command line
    option, 619
gitlab-project-badge-render command
    line option, 619
gitlab-project-badge-update command
    line option, 620
gitlab-project-board-delete command
    line option, 620
gitlab-project-board-get command line
    option, 621
gitlab-project-board-list-delete
    command line option, 622
gitlab-project-board-list-get command
    line option, 622
gitlab-project-board-list-update
    command line option, 623
gitlab-project-board-update command
    line option, 621
gitlab-project-cluster-delete command
    line option, 627
gitlab-project-cluster-get command line
    option, 627
gitlab-project-cluster-update command
    line option, 628
gitlab-project-commit-cherry-pick
    command line option, 629

```

gitlab-project-commit-diff command line option, 630
gitlab-project-commit-discussion-get command line option, 634
gitlab-project-commit-discussion-note-delete command line option, 636
gitlab-project-commit-discussion-note-get command line option, 636
gitlab-project-commit-discussion-note-update command line option, 636
gitlab-project-commit-get command line option, 630
gitlab-project-commit-merge-requests command line option, 631
gitlab-project-commit-refs command line option, 631
gitlab-project-commit-revert command line option, 632
gitlab-project-commit-signature command line option, 632
gitlab-project-create-fork-relation command line option, 597
gitlab-project-delete command line option, 597
gitlab-project-delete-fork-relation command line option, 597
gitlab-project-delete-merged-branches command line option, 598
gitlab-project-deploy-token-delete command line option, 640
gitlab-project-deploy-token-get command line option, 640
gitlab-project-deployment-approval command line option, 641
gitlab-project-deployment-get command line option, 642
gitlab-project-deployment-update command line option, 643
gitlab-project-environment-delete command line option, 646
gitlab-project-environment-get command line option, 646
gitlab-project-environment-stop command line option, 647
gitlab-project-environment-update command line option, 647
gitlab-project-get command line option, 598
gitlab-project-hook-delete command line option, 655
gitlab-project-hook-get command line option, 655
gitlab-project-hook-update command line option, 656
gitlab-project-housekeeping command line option, 598
gitlab-project-issue-award-emoji-delete command line option, 669
gitlab-project-issue-award-emoji-get command line option, 670
gitlab-project-issue-discussion-get command line option, 671
gitlab-project-issue-discussion-note-delete command line option, 673
gitlab-project-issue-discussion-note-get command line option, 673
gitlab-project-issue-discussion-note-update command line option, 674
gitlab-project-issue-note-award-emoji-delete command line option, 678
gitlab-project-issue-note-award-emoji-get command line option, 678
gitlab-project-issue-note-delete command line option, 676
gitlab-project-issue-note-get command line option, 676
gitlab-project-issue-note-update command line option, 677
gitlab-project-issue-resource-iteration-event-get command line option, 679
gitlab-project-issue-resource-label-event-get command line option, 680
gitlab-project-issue-resource-milestone-event-get command line option, 681
gitlab-project-issue-resource-state-event-get command line option, 682
gitlab-project-issue-resource-weight-event-get command line option, 683
gitlab-project-job-artifact command line option, 685
gitlab-project-job-artifacts command line option, 685
gitlab-project-job-cancel command line option, 686
gitlab-project-job-delete-artifacts command line option, 686
gitlab-project-job-erase command line option, 686
gitlab-project-job-get command line option, 687
gitlab-project-job-keep-artifacts command line option, 687
gitlab-project-job-play command line option, 688
gitlab-project-job-retry command line option, 688
gitlab-project-job-trace command line option, 688

```

gitlab-project-key-delete command line
    option, 689
gitlab-project-key-enable command line
    option, 689
gitlab-project-key-get command line
    option, 689
gitlab-project-key-update command line
    option, 690
gitlab-project-languages command line
    option, 598
gitlab-project-member-all-get command
    line option, 695
gitlab-project-member-delete command
    line option, 694
gitlab-project-member-get command line
    option, 694
gitlab-project-member-update command
    line option, 695
gitlab-project-merge-request-approval-rule-create
    command line option, 708
gitlab-project-merge-request-approval-rule-delete
    command line option, 709
gitlab-project-merge-request-approval-rule-get
    command line option, 709
gitlab-project-merge-request-approval-rule-update
    command line option, 710
gitlab-project-merge-request-approval-state-get
    command line option, 711
gitlab-project-merge-request-award-emoji-delete
    command line option, 712
gitlab-project-merge-request-award-emoji-get
    command line option, 712
gitlab-project-merge-request-diff-get
    command line option, 713
gitlab-project-merge-request-discussion-get
    command line option, 715
gitlab-project-merge-request-discussion-note-delete
    command line option, 717
gitlab-project-merge-request-discussion-note-get
    command line option, 717
gitlab-project-merge-request-discussion-note-update
    command line option, 717
gitlab-project-merge-request-note-award-emoji-delete
    command line option, 721
gitlab-project-merge-request-note-award-emoji-get
    command line option, 721
gitlab-project-merge-request-note-award-emoji-update
    command line option, 720
gitlab-project-merge-request-resource-label-event-get
    command line option, 723
gitlab-project-merge-request-resource-milestone-event-
    command line option, 724
gitlab-project-merge-request-resource-state-event-get
    command line option, 725
gitlab-project-milestone-delete command
    line option, 727
gitlab-project-milestone-get command
    line option, 727
gitlab-project-milestone-issues command
    line option, 728
gitlab-project-milestone-merge-requests
    command line option, 729
gitlab-project-milestone-update command
    line option, 729
gitlab-project-mirror-pull command line
    option, 600
gitlab-project-mirror-pull-details
    command line option, 600
gitlab-project-note-get command line
    option, 729
gitlab-project-package-delete command
    line option, 732
gitlab-project-package-file-delete
    command line option, 733
gitlab-project-package-get command line
    option, 732
gitlab-project-pipeline-cancel command
    line option, 736
gitlab-project-pipeline-delete command
    line option, 736
gitlab-project-pipeline-get command
    line option, 737
gitlab-project-pipeline-retry command
    line option, 738
gitlab-project-pipeline-schedule-delete
    command line option, 740
gitlab-project-pipeline-schedule-get
    command line option, 741
gitlab-project-pipeline-schedule-play
    command line option, 741
gitlab-project-pipeline-schedule-take-ownership
    command line option, 742
gitlab-project-pipeline-schedule-update
    command line option, 742
gitlab-project-registry-repository-delete
    command line option, 754
gitlab-project-release-link-delete
    command line option, 759
gitlab-project-release-link-get command
    line option, 760
gitlab-project-release-link-update
    command line option, 761

```

gitlab-project-remote-mirror-update
 command line option, 762
gitlab-project-repository-archive
 command line option, 600
gitlab-project-repository-blob command
 line option, 601
gitlab-project-repository-compare
 command line option, 601
gitlab-project-repository-contributors
 command line option, 601
gitlab-project-repository-merge-base
 command line option, 601
gitlab-project-repository-raw-blob
 command line option, 602
gitlab-project-repository-tree command
 line option, 602
gitlab-project-restore command line
 option, 602
gitlab-project-runner-delete command
 line option, 765
gitlab-project-search command line
 option, 602
gitlab-project-secure-file-delete
 command line option, 766
gitlab-project-secure-file-download
 command line option, 766
gitlab-project-secure-file-get command
 line option, 767
gitlab-project-share command line
 option, 603
gitlab-project-snapshot command line
 option, 603
gitlab-project-snippet-award-emoji-delete
 command line option, 773
gitlab-project-snippet-award-emoji-get
 command line option, 773
gitlab-project-snippet-content command
 line option, 769
gitlab-project-snippet-delete command
 line option, 770
gitlab-project-snippet-discussion-get
 command line option, 774
gitlab-project-snippet-discussion-note-delete
 command line option, 776
gitlab-project-snippet-discussion-note-get
 command line option, 776
gitlab-project-snippet-discussion-note-update
 command line option, 777
gitlab-project-snippet-get command line
 option, 770
gitlab-project-snippet-note-award-emoji-delete
 command line option, 780
gitlab-project-snippet-note-award-emoji-get
 command line option, 780

gitlab-project-snippet-note-delete
 command line option, 778
gitlab-project-snippet-note-get command
 line option, 778
gitlab-project-snippet-note-update
 command line option, 779
gitlab-project-snippet-update command
 line option, 771
gitlab-project-snippet-user-agent-detail
 command line option, 772
gitlab-project-star command line option,
 603
gitlab-project-storage-get command line
 option, 781
gitlab-project-transfer command line
 option, 603
gitlab-project-transfer-project command
 line option, 604
gitlab-project-trigger-delete command
 line option, 784
gitlab-project-trigger-get command line
 option, 784
gitlab-project-trigger-pipeline command
 line option, 604
gitlab-project-trigger-update command
 line option, 785
gitlab-project-unarchive command line
 option, 604
gitlab-project-unshare command line
 option, 604
gitlab-project-unstar command line
 option, 605
gitlab-project-update command line
 option, 607
gitlab-project-update-submodule command
 line option, 610
gitlab-project-upload command line
 option, 610
gitlab-registry-repository-get command
 line option, 790
gitlab-runner-all command line option,
 790
gitlab-runner-delete command line
 option, 791
gitlab-runner-get command line option,
 791
gitlab-runner-update command line
 option, 792
gitlab-runner-verify command line
 option, 793
gitlab-snippet-content command line
 option, 796
gitlab-snippet-delete command line
 option, 796

```

gitlab-snippet-get command line option,           807
    gitlab-snippet-public command line
        option, 797
    gitlab-snippet-update command line
        option, 797
    gitlab-snippet-user-agent-detail
        command line option, 798
gitlab-todo-delete command line option,          799
gitlab-todo-mark-all-as-done command
    line option, 800
gitlab-todo-mark-as-done command line
    option, 800
gitlab-topic-delete command line option,          801
gitlab-topic-get command line option,             801
gitlab-topic-merge command line option,           802
gitlab-topic-update command line option,          802
gitlab-user-activate command line
    option, 803
gitlab-user-approve command line option,          803
gitlab-user-ban command line option,              803
gitlab-user-block command line option,            804
gitlab-user-deactivate command line
    option, 805
gitlab-user-delete command line option,            805
gitlab-user-email-delete command line
    option, 811
gitlab-user-email-get command line
    option, 811
gitlab-user-follow command line option,           806
gitlab-user-get command line option,              806
gitlab-user-gpg-key-delete command line
    option, 813
gitlab-user-gpg-key-get command line
    option, 814
gitlab-user-impersonation-token-delete
    command line option, 815
gitlab-user-impersonation-token-get
    command line option, 815
gitlab-user-key-delete command line
    option, 816
gitlab-user-key-get command line option,           817
gitlab-user-reject command line option,            807
gitlab-user-unban command line option,

```

```
gitlab-project-issue-update command  
    line option, 668  
gitlab-project-issue-user-agent-detail  
    command line option, 669  
gitlab-project-merge-request-add-spent-time  
    command line option, 697  
gitlab-project-merge-request-approve  
    command line option, 697  
gitlab-project-merge-request-cancel-merge-when-pipeline-squashed  
    command line option, 697  
gitlab-project-merge-request-changes  
    command line option, 698  
gitlab-project-merge-request-closes-issues  
    command line option, 698  
gitlab-project-merge-request-commits  
    command line option, 698  
gitlab-project-merge-request-delete  
    command line option, 700  
gitlab-project-merge-request-get  
    command line option, 700  
gitlab-project-merge-request-merge  
    command line option, 702  
gitlab-project-merge-request-merge-ref  
    command line option, 702  
gitlab-project-merge-request-participants  
    command line option, 703  
gitlab-project-merge-request-rebase  
    command line option, 703  
gitlab-project-merge-request-reset-approvals  
    command line option, 703  
gitlab-project-merge-request-reset-spent-time  
    command line option, 704  
gitlab-project-merge-request-reset-time-estimate  
    command line option, 704  
gitlab-project-merge-request-subscribe  
    command line option, 704  
gitlab-project-merge-request-time-estimate  
    command line option, 704  
gitlab-project-merge-request-time-stats  
    command line option, 705  
gitlab-project-merge-request-todo  
    command line option, 705  
gitlab-project-merge-request-unapprove  
    command line option, 705  
gitlab-project-merge-request-unsubscribe  
    command line option, 706  
gitlab-project-merge-request-update  
    command line option, 706  
--iids  
    gitlab-group-issue-list command line  
        option, 555  
    gitlab-group-milestone-list command  
        line option, 567  
    gitlab-issue-list command line option,  
        583  
gitlab-project-issue-list command line  
    option, 663  
gitlab-project-merge-request-list  
    command line option, 701  
gitlab-project-milestone-list command  
    line option, 728  
    --image-url  
gitlab-project-badge-create command line  
    option, 522  
gitlab-group-badge-render command line  
    option, 523  
gitlab-group-badge-update command line  
    option, 524  
gitlab-project-badge-create command  
    line option, 618  
gitlab-project-badge-render command  
    line option, 619  
gitlab-project-badge-update command  
    line option, 620  
    --import-sources  
        gitlab-application-settings-update  
            command line option, 490  
    --import-url  
        gitlab-project-create command line  
            option, 595  
        gitlab-project-update command line  
            option, 608  
gitlab-user-project-create command line  
    option, 820  
gitlab-merge-request-list command line  
    option, 587  
gitlab-project-deployment-merge-request-list  
    command line option, 645  
    --include-ancestors  
        gitlab-group-iteration-list command  
            line option, 556  
    --include-diverged-commits-count  
        gitlab-project-merge-request-get  
            command line option, 700  
    --include-html-description  
        gitlab-project-release-list command  
            line option, 758  
    gitlab-project-resource-group-list  
        command line option, 763  
    --include-jobs  
        gitlab-ci-lint-create command line  
            option, 498  
        gitlab-ci-lint-validate command line  
            option, 498  
        gitlab-project-ci-lint-create command  
            line option, 625  
        gitlab-project-ci-lint-validate command
```

```

    line option, 626
--include-merged-yaml
    gitlab-ci-lint-create command line
        option, 498
    gitlab-ci-lint-validate command line
        option, 498
--include-rebase-in-progress
    gitlab-project-merge-request-get
        command line option, 700
--include-retried
    gitlab-project-pipeline-job-list
        command line option, 739
--include-subgroups
    gitlab-group-project-list command line
        option, 571
--info
    gitlab-runner-create command line
        option, 791
--infrastructure-access-level
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
--initialize-with-readme
    gitlab-project-create command line
        option, 595
--instance-statistics-visibility-private
    gitlab-application-settings-update
        command line option, 491
--invite-source
    gitlab-group-invitation-create command
        line option, 553
    gitlab-project-invitation-create
        command line option, 659
--issue-branch-template
    gitlab-project-update command line
        option, 609
--issue-id
    gitlab-group-epic-issue-create command
        line option, 542
--issue-iid
    gitlab-project-issue-award-emoji-create
        command line option, 669
    gitlab-project-issue-award-emoji-delete
        command line option, 669
    gitlab-project-issue-award-emoji-get
        command line option, 670
    gitlab-project-issue-award-emoji-list
        command line option, 670
    gitlab-project-issue-discussion-create
        command line option, 671
    gitlab-project-issue-discussion-get
        command line option, 671
    gitlab-project-issue-discussion-list
        command line option, 671
    gitlab-project-issue-discussion-note-create
        command line option, 672
    gitlab-project-issue-discussion-note-delete
        command line option, 673
    gitlab-project-issue-discussion-note-get
        command line option, 673
    gitlab-project-issue-discussion-note-update
        command line option, 674
    gitlab-project-issue-link-create
        command line option, 674
    gitlab-project-issue-link-delete
        command line option, 674
    gitlab-project-issue-link-list command
        line option, 675
    gitlab-project-issue-note-award-emoji-create
        command line option, 677
    gitlab-project-issue-note-award-emoji-delete
        command line option, 678
    gitlab-project-issue-note-award-emoji-get
        command line option, 678
    gitlab-project-issue-note-award-emoji-list
        command line option, 679
    gitlab-project-issue-note-create
        command line option, 675
    gitlab-project-issue-note-delete
        command line option, 676
    gitlab-project-issue-note-get command
        line option, 676
    gitlab-project-issue-note-list command
        line option, 676
    gitlab-project-issue-note-update
        command line option, 677
    gitlab-project-issue-resource-iteration-event-get
        command line option, 679
    gitlab-project-issue-resource-iteration-event-list
        command line option, 680
    gitlab-project-issue-resource-label-event-get
        command line option, 680
    gitlab-project-issue-resource-label-event-list
        command line option, 681
    gitlab-project-issue-resource-milestone-event-get
        command line option, 681
    gitlab-project-issue-resource-milestone-event-list
        command line option, 682
    gitlab-project-issue-resource-state-event-get
        command line option, 682
    gitlab-project-issue-resource-state-event-list
        command line option, 683
    gitlab-project-issue-resource-weight-event-get
        command line option, 683
    gitlab-project-issue-resource-weight-event-list
        command line option, 684
--issue-link-id

```

```
gitlab-project-issue-link-delete
    command line option, 674
--issues-access-level
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 608
--issues-enabled
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 608
    gitlab-user-project-create command line
        option, 819
--issues-events
    gitlab-group-hook-create command line
        option, 549
    gitlab-group-hook-update command line
        option, 551
    gitlab-project-hook-create command line
        option, 654
    gitlab-project-hook-update command line
        option, 656
--issues-template
    gitlab-project-update command line
        option, 608
--job
    gitlab-project-artifact command line
        option, 592
    gitlab-project-artifact-download
        command line option, 616
    gitlab-project-artifact-raw command
        line option, 617
    gitlab-project-artifacts command line
        option, 593
--job-events
    gitlab-group-hook-create command line
        option, 549
    gitlab-group-hook-update command line
        option, 551
    gitlab-project-hook-create command line
        option, 654
    gitlab-project-hook-update command line
        option, 656
--job-token
    gitlab command line option, 485
    gitlab-project-artifact-download
        command line option, 616
    gitlab-project-artifacts command line
        option, 593
--jobs-enabled
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 608
--keep-latest-artifact
    gitlab-project-update command line
        option, 608
--keep-n
    gitlab-project-registry-tag-delete-in-bulk
        command line option, 755
--key
    gitlab-current-user-gpg-key-create
        command line option, 500
    gitlab-current-user-key-create command
        line option, 501
gitlab-group-custom-attribute-delete
    command line option, 532
gitlab-group-custom-attribute-get
    command line option, 532
gitlab-group-variable-create command
    line option, 577
gitlab-group-variable-delete command
    line option, 577
gitlab-group-variable-get command line
    option, 578
gitlab-group-variable-update command
    line option, 578
gitlab-license-get command line option,
    585
gitlab-project-custom-attribute-delete
    command line option, 638
gitlab-project-custom-attribute-get
    command line option, 638
gitlab-project-key-create command line
    option, 689
gitlab-project-pages-domain-create
    command line option, 734
gitlab-project-pages-domain-update
    command line option, 736
gitlab-project-pipeline-schedule-variable-create
    command line option, 743
gitlab-project-pipeline-schedule-variable-delete
    command line option, 744
gitlab-project-pipeline-schedule-variable-update
    command line option, 744
gitlab-project-resource-group-get
    command line option, 762
gitlab-project-resource-group-update
    command line option, 763
gitlab-project-variable-create command
    line option, 786
gitlab-project-variable-delete command
    line option, 786
gitlab-project-variable-get command
    line option, 787
gitlab-project-variable-update command
    line option, 787
```

```

gitlab-user-custom-attribute-delete
    command line option, 810
gitlab-user-custom-attribute-get
    command line option, 810
gitlab-user-gpg-key-create command line
    option, 813
gitlab-user-key-create command line
    option, 816
gitlab-variable-create command line
    option, 822
gitlab-variable-delete command line
    option, 822
gitlab-variable-get command line option,
    822
gitlab-variable-update command line
    option, 823
--key-id
    gitlab-project-key-enable command line
        option, 689
--labels
    gitlab-group-epic-create command line
        option, 536
    gitlab-group-epic-list command line
        option, 537
    gitlab-group-epic-update command line
        option, 538
    gitlab-group-issue-list command line
        option, 555
    gitlab-group-merge-request-list command
        line option, 564
    gitlab-issue-list command line option,
        583
    gitlab-merge-request-list command line
        option, 586
    gitlab-project-deployment-merge-request-list
        command line option, 644
    gitlab-project-issue-create command
        line option, 662
    gitlab-project-issue-list command line
        option, 664
    gitlab-project-issue-update command
        line option, 668
    gitlab-project-merge-request-create
        command line option, 699
    gitlab-project-merge-request-list
        command line option, 701
    gitlab-project-merge-request-update
        command line option, 706
--last-activity-after
    gitlab-project-list command line option,
        599
--last-activity-before
    gitlab-project-list command line option,
        599
--level
    gitlab-group-notification-settings-update
        command line option, 569
    gitlab-notification-settings-update
        command line option, 589
    gitlab-project-notification-settings-update
        command line option, 731
--lfs-enabled
    gitlab-group-create command line option,
        513
    gitlab-group-update command line option,
        518
    gitlab-project-create command line
        option, 595
    gitlab-project-update command line
        option, 608
--lifetime
    gitlab-snippet-create command line
        option, 796
--line
    gitlab-project-commit-comment-create
        command line option, 633
--line-type
    gitlab-project-commit-comment-create
        command line option, 633
--link-type
    gitlab-project-release-link-create
        command line option, 759
    gitlab-project-release-link-update
        command line option, 761
--link-url
    gitlab-group-badge-create command line
        option, 522
    gitlab-group-badge-render command line
        option, 523
    gitlab-group-badge-update command line
        option, 524
    gitlab-project-badge-create command
        line option, 618
    gitlab-project-badge-render command
        line option, 619
    gitlab-project-badge-update command
        line option, 620
--linkedin
    gitlab-user-create command line option,
        804
    gitlab-user-update command line option,
        808
--local-markdown-version
    gitlab-application-settings-update
        command line option, 491
--location
    gitlab-user-create command line option,
        805

```

```
gitlab-user-update command line option,  
    809  
--locked  
    gitlab-runner-create command line  
        option, 791  
    gitlab-runner-update command line  
        option, 792  
--logo  
    gitlab-application-appearance-update  
        command line option, 487  
--managed  
    gitlab-group-cluster-create command  
        line option, 530  
    gitlab-project-cluster-create command  
        line option, 627  
--management-project-id  
    gitlab-group-cluster-update command  
        line option, 531  
    gitlab-project-cluster-update command  
        line option, 628  
--masked  
    gitlab-group-variable-create command  
        line option, 577  
    gitlab-group-variable-update command  
        line option, 579  
    gitlab-project-variable-create command  
        line option, 786  
    gitlab-project-variable-update command  
        line option, 788  
    gitlab-variable-create command line  
        option, 822  
    gitlab-variable-update command line  
        option, 823  
--max-attachment-size  
    gitlab-application-settings-update  
        command line option, 490  
--max-file-size  
    gitlab-group-push-rules-create command  
        line option, 572  
    gitlab-group-push-rules-update command  
        line option, 573  
    gitlab-project-push-rules-create  
        command line option, 752  
    gitlab-project-push-rules-update  
        command line option, 753  
--maximum-timeout  
    gitlab-runner-create command line  
        option, 791  
    gitlab-runner-update command line  
        option, 793  
--member-check  
    gitlab-group-push-rules-create command  
        line option, 572  
    gitlab-group-push-rules-update command  
        line option, 573  
--membership  
    gitlab-project-fork-list command line  
        option, 653  
    gitlab-project-list command line option,  
        599  
    gitlab-starred-project-list command  
        line option, 798  
    gitlab-user-project-list command line  
        option, 820  
--membership-lock  
    gitlab-group-create command line option,  
        513  
    gitlab-group-update command line option,  
        517  
--mentions-disabled  
    gitlab-group-create command line option,  
        513  
    gitlab-group-update command line option,  
        518  
--merge-access-level  
    gitlab-project-protected-branch-create  
        command line option, 747  
--merge-commit-message  
    gitlab-project-merge-request-merge  
        command line option, 702  
--merge-commit-template  
    gitlab-project-update command line  
        option, 608  
--merge-merge-request  
    gitlab-group-notification-settings-update  
        command line option, 569  
    gitlab-notification-settings-update  
        command line option, 590  
    gitlab-project-notification-settings-update  
        command line option, 731  
--merge-method  
    gitlab-project-create command line  
        option, 595  
    gitlab-project-update command line  
        option, 608  
--merge-pipelines-enabled  
    gitlab-project-create command line  
        option, 595  
    gitlab-project-update command line  
        option, 608  
--merge-request-iid  
    gitlab-project-merge-request-approval-rule-create  
        command line option, 708  
    gitlab-project-merge-request-approval-rule-update
```

```

    command line option, 710
--merge-request-to-resolve-discussions-of
    gitlab-project-issue-create command
        line option, 662
--merge-requests-access-level
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 608
--merge-requests-author-approval
    gitlab-project-approval-update command
        line option, 614
--merge-requests-disable-committers-approval
    gitlab-project-approval-update command
        line option, 614
--merge-requests-enabled
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 608
    gitlab-user-project-create command line
        option, 819
--merge-requests-events
    gitlab-group-hook-create command line
        option, 549
    gitlab-group-hook-update command line
        option, 551
    gitlab-project-hook-create command line
        option, 654
    gitlab-project-hook-update command line
        option, 656
--merge-requests-template
    gitlab-project-update command line
        option, 608
--merge-trains-enabled
    gitlab-project-update command line
        option, 608
--merge-when-pipeline-succeeds
    gitlab-project-merge-request-merge
        command line option, 702
--message
    gitlab-broadcast-message-create command
        line option, 493
    gitlab-broadcast-message-update command
        line option, 495
    gitlab-current-user-status-update
        command line option, 503
    gitlab-project-tag-create command line
        option, 782
--message-background-color
    gitlab-application-appearance-update
        command line option, 487
--message-font-color
    gitlab-application-appearance-update
        command line option, 487
--milestone
    gitlab-group-issue-list command line
        option, 555
    gitlab-group-merge-request-list command
        line option, 564
    gitlab-issue-list command line option,
        583
    gitlab-merge-request-list command line
        option, 586
    gitlab-project-deployment-merge-request-list
        command line option, 644
    gitlab-project-issue-list command line
        option, 664
    gitlab-project-merge-request-list
        command line option, 701
--milestone-id
    gitlab-project-issue-create command
        line option, 662
    gitlab-project-issue-update command
        line option, 668
    gitlab-project-merge-request-create
        command line option, 699
    gitlab-project-merge-request-update
        command line option, 706
--milestones
    gitlab-project-release-update command
        line option, 758
--min-access-level
    gitlab-group-descendant-group-list
        command line option, 535
    gitlab-group-list command line option,
        515
    gitlab-group-project-list command line
        option, 571
    gitlab-group-subgroup-list command line
        option, 576
    gitlab-project-list command line option,
        599
    gitlab-shared-project-list command line
        option, 795
    gitlab-starred-project-list command
        line option, 799
    gitlab-user-project-list command line
        option, 821
--mirror
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 608
--mirror-overwrites-diverged-branches
    gitlab-project-update command line
        option, 608
--mirror-trigger-builds

```

```
gitlab-project-create command line
    option, 596
gitlab-project-update command line
    option, 608
--mirror-user-id
    gitlab-project-update command line
        option, 608
--monitor-access-level
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
--move-after-id
    gitlab-group-epic-issue-update command
        line option, 543
    gitlab-project-issue-reorder command
        line option, 665
--move-before-id
    gitlab-group-epic-issue-update command
        line option, 543
    gitlab-project-issue-reorder command
        line option, 665
--mr-default-target-self
    gitlab-project-update command line
        option, 608
--mr-iid
    gitlab-project-merge-request-approval-get
        command line option, 707
    gitlab-project-merge-request-approval-rule-create
        command line option, 708
    gitlab-project-merge-request-approval-rule-del
        command line option, 709
    gitlab-project-merge-request-approval-rule-get
        command line option, 709
    gitlab-project-merge-request-approval-rule-list
        command line option, 709
    gitlab-project-merge-request-approval-rule-update
        command line option, 710
    gitlab-project-merge-request-approval-state-get
        command line option, 711
    gitlab-project-merge-request-approval-update
        command line option, 707
    gitlab-project-merge-request-award-emoji-create
        command line option, 711
    gitlab-project-merge-request-award-emoji-delete
        command line option, 712
    gitlab-project-merge-request-award-emoji-get
        command line option, 712
    gitlab-project-merge-request-award-emoji-list
        command line option, 712
    gitlab-project-merge-request-diff-get
        command line option, 713
    gitlab-project-merge-request-diff-list
        command line option, 713
gitlab-project-merge-request-discussion-create
    command line option, 714
gitlab-project-merge-request-discussion-get
    command line option, 715
gitlab-project-merge-request-discussion-list
    command line option, 715
gitlab-project-merge-request-discussion-note-create
    command line option, 716
gitlab-project-merge-request-discussion-note-delete
    command line option, 717
gitlab-project-merge-request-discussion-note-get
    command line option, 717
gitlab-project-merge-request-discussion-note-update
    command line option, 717
gitlab-project-merge-request-discussion-update
    command line option, 715
gitlab-project-merge-request-note-award-emoji-create
    command line option, 720
gitlab-project-merge-request-note-award-emoji-delete
    command line option, 721
gitlab-project-merge-request-note-award-emoji-get
    command line option, 721
gitlab-project-merge-request-note-award-emoji-list
    command line option, 721
gitlab-project-merge-request-note-create
    command line option, 718
gitlab-project-merge-request-note-delete
    command line option, 718
gitlab-project-merge-request-note-get
    command line option, 719
gitlab-project-merge-request-note-list
    command line option, 719
gitlab-project-merge-request-note-update
    command line option, 720
gitlab-project-merge-request-pipeline-create
    command line option, 722
gitlab-project-merge-request-pipeline-list
    command line option, 722
gitlab-project-merge-request-resource-label-event-get
    command line option, 723
gitlab-project-merge-request-resource-label-event-list
    command line option, 723
gitlab-project-merge-request-resource-milestone-event-
    command line option, 724
gitlab-project-merge-request-resource-milestone-event-
    command line option, 724
gitlab-project-merge-request-state-event-get
    command line option, 725
gitlab-project-merge-request-state-event-list
    command line option, 725
--my-reaction-emoji
    gitlab-group-issue-list command line
        option, 555
    gitlab-group-merge-request-list command
```

```

    line option, 565
gitlab-issue-list command line option,
    583
gitlab-merge-request-list command line
    option, 587
gitlab-project-deployment-merge-request-list
    command line option, 645
gitlab-project-issue-list command line
    option, 664
gitlab-project-merge-request-list
    command line option, 701
--name
    gitlab-application-create command line
        option, 486
    gitlab-dockerfile-get command line
        option, 504
    gitlab-feature-delete command line
        option, 506
    gitlab-gitignore-get command line
        option, 510
    gitlab-gitlabciyml-get command line
        option, 511
    gitlab-group-access-token-create
        command line option, 520
    gitlab-group-board-create command line
        option, 526
    gitlab-group-cluster-create command
        line option, 530
    gitlab-group-cluster-update command
        line option, 531
    gitlab-group-create command line option,
        513
    gitlab-group-deploy-token-create
        command line option, 533
    gitlab-group-epic-award-emoji-create
        command line option, 538
    gitlab-group-epic-note-award-emoji-create
        command line option, 545
    gitlab-group-label-create command line
        option, 557
    gitlab-group-label-delete command line
        option, 557
    gitlab-group-label-get command line
        option, 558
    gitlab-group-label-subscribe command
        line option, 558
    gitlab-group-label-unsubscribe command
        line option, 559
    gitlab-group-label-update command line
        option, 559
    gitlab-group-saml-group-link-delete
        command line option, 575
    gitlab-group-saml-group-link-get
        command line option, 575
gitlab-group-update command line option,
    517
gitlab-project-access-token-create
    command line option, 612
gitlab-project-approval-rule-create
    command line option, 614
gitlab-project-board-create command
    line option, 620
gitlab-project-branch-delete command
    line option, 624
gitlab-project-branch-get command line
    option, 624
gitlab-project-cluster-create command
    line option, 627
gitlab-project-cluster-update command
    line option, 628
gitlab-project-commit-status-create
    command line option, 637
gitlab-project-create command line
    option, 594
gitlab-project-deploy-token-create
    command line option, 639
gitlab-project-environment-create
    command line option, 646
gitlab-project-environment-list command
    line option, 646
gitlab-project-environment-update
    command line option, 647
gitlab-project-issue-award-emoji-create
    command line option, 669
gitlab-project-issue-note-award-emoji-create
    command line option, 677
gitlab-project-label-create command
    line option, 691
gitlab-project-label-delete command
    line option, 691
gitlab-project-label-get command line
    option, 691
gitlab-project-label-subscribe command
    line option, 692
gitlab-project-label-unsubscribe
    command line option, 692
gitlab-project-label-update command
    line option, 693
gitlab-project-merge-request-approval-rule-create
    command line option, 708
gitlab-project-merge-request-approval-rule-update
    command line option, 710
gitlab-project-merge-request-award-emoji-create
    command line option, 711
gitlab-project-merge-request-note-award-emoji-create
    command line option, 720
gitlab-project-pipeline-list command
    line option, 737

```

```
gitlab-project-protected-branch-create
    command line option, 747
gitlab-project-protected-branch-delete
    command line option, 747
gitlab-project-protected-branch-get
    command line option, 747
gitlab-project-protected-environment-create
    command line option, 748
gitlab-project-protected-environment-delete
    command line option, 749
gitlab-project-protected-environment-get
    command line option, 749
gitlab-project-protected-tag-create
    command line option, 750
gitlab-project-protected-tag-delete
    command line option, 750
gitlab-project-protected-tag-get
    command line option, 751
gitlab-project-registry-tag-delete
    command line option, 755
gitlab-project-registry-tag-delete-in-bulk
    command line option, 755
gitlab-project-registry-tag-get command
    line option, 756
gitlab-project-release-create command
    line option, 757
gitlab-project-release-link-create
    command line option, 759
gitlab-project-release-link-update
    command line option, 761
gitlab-project-release-update command
    line option, 758
gitlab-project-secure-file-create
    command line option, 766
gitlab-project-snippet-award-emoji-create
    command line option, 772
gitlab-project-snippet-note-award-emoji-create
    command line option, 780
gitlab-project-tag-delete command line
    option, 782
gitlab-project-tag-get command line
    option, 782
gitlab-project-update command line
    option, 608
gitlab-topic-create command line option,
    801
gitlab-topic-update command line option,
    802
gitlab-user-create command line option,
    804
gitlab-user-impersonation-token-create
    command line option, 815
gitlab-user-personal-access-token-create
    command line option, 818
gitlab-user-project-create command line
    option, 819
gitlab-user-update command line option,
    808
--name-regex-delete
gitlab-project-registry-tag-delete-in-bulk
    command line option, 755
--name-regex-keep
gitlab-project-registry-tag-delete-in-bulk
    command line option, 755
--namespace
gitlab-namespace-exists command line
    option, 588
gitlab-project-fork-create command line
    option, 652
--namespace-id
gitlab-project-create command line
    option, 596
--new-issue
gitlab-group-notification-settings-update
    command line option, 569
gitlab-notification-settings-update
    command line option, 589
gitlab-project-notification-settings-update
    command line option, 731
--new-merge-request
gitlab-group-notification-settings-update
    command line option, 569
gitlab-notification-settings-update
    command line option, 589
gitlab-project-notification-settings-update
    command line option, 731
--new-name
gitlab-group-label-update command line
    option, 559
gitlab-project-label-update command
    line option, 693
--new-note
gitlab-group-notification-settings-update
    command line option, 569
gitlab-notification-settings-update
    command line option, 589
gitlab-project-notification-settings-update
    command line option, 731
--new-project-guidelines
gitlab-application-appearance-update
    command line option, 487
--not
gitlab-merge-request-list command line
    option, 587
gitlab-project-deployment-merge-request-list
    command line option, 645
--note
gitlab-project-commit-comment-create
```

```

    command line option, 633
--note-events
    gitlab-group-hook-create command line
        option, 549
    gitlab-group-hook-update command line
        option, 551
    gitlab-project-hook-create command line
        option, 654
    gitlab-project-hook-update command line
        option, 656
--note-id
    gitlab-group-epic-note-award-emoji-create --only-allow-merge-if-build-succeeds
        command line option, 545
    gitlab-group-epic-note-award-emoji-delete --only-allow-merge-if-pipeline-succeeds
        command line option, 546
    gitlab-group-epic-note-award-emoji-get --only-protected-branches
        command line option, 546
    gitlab-group-epic-note-award-emoji-list --gitlab-project-create command line
        option, 595
    gitlab-project-issue-note-award-emoji-createonly-mirror-protected-branches
        command line option, 677
    gitlab-project-issue-note-award-emoji-delete --gitlab-project-update command line
        command line option, 678
    gitlab-project-issue-note-award-emoji-get --gitlab-project-remote-mirror-create
        command line option, 678
    gitlab-project-issue-note-award-emoji-list --gitlab-project-remote-mirror-update
        command line option, 679
    gitlab-project-merge-request-note-award-emojioperations-access-level
        command line option, 720
    gitlab-project-merge-request-note-award-emoji-delete --gitlab-project-create command line
        command line option, 721
    gitlab-project-merge-request-note-award-emoji-get --gitlab-project-update command line
        command line option, 721
    gitlab-project-merge-request-note-award-emoji-list --gitlab-project-commit-list command line
        command line option, 721
    gitlab-project-snippet-note-award-emoji-creater-by
        command line option, 779
    gitlab-project-snippet-note-award-emoji-deletegitlab-group-descendant-group-list
        command line option, 780
    gitlab-project-snippet-note-award-emoji-get --gitlab-group-epic-list command line
        command line option, 780
    gitlab-project-snippet-note-award-emoji-list --gitlab-group-issue-list command line
        command line option, 781
--notification-email
    gitlab-group-notification-settings-update --gitlab-group-list command line option,
        515
    gitlab-notification-settings-update --gitlab-group-merge-request-list command
        line option, 564
    gitlab-project-notification-settings-update --gitlab-group-package-list command line
        option, 570
--oauth-token
    gitlab command line option, 485
--older-than
    gitlab-project-registry-tag-delete-in-bulk --gitlab-group-project-list command line
        option, 571
    gitlab-group-subgroup-list command line
        option, 576
    gitlab-issue-list command line option,

```

583
gitlab-merge-request-list command line
option, 586
gitlab-project-deployment-list command
line option, 642
gitlab-project-deployment-merge-request-list
command line option, 644
gitlab-project-fork-list command line
option, 653
gitlab-project-issue-list command line
option, 664
gitlab-project-list command line option,
599
gitlab-project-merge-request-list
command line option, 701
gitlab-project-package-list command
line option, 732
gitlab-project-pipeline-list command
line option, 737
gitlab-project-release-list command
line option, 758
gitlab-project-resource-group-list
command line option, 763
gitlab-shared-project-list command line
option, 795
gitlab-starred-project-list command
line option, 799
gitlab-user-project-list command line
option, 820
--organization
gitlab-user-create command line option,
805
gitlab-user-update command line option,
808
--outbound-local-requests-whitelist
gitlab-application-settings-update
command line option, 490
--output
gitlab command line option, 484
--owned
gitlab-group-descendant-group-list
command line option, 535
gitlab-group-list command line option,
515
gitlab-group-project-list command line
option, 571
gitlab-group-subgroup-list command line
option, 576
gitlab-project-fork-list command line
option, 653
gitlab-project-list command line option,
599
gitlab-starred-project-list command
line option, 799
gitlab-user-project-list command line
option, 820
--package-id
gitlab-project-package-file-delete
command line option, 733
gitlab-project-package-file-list
command line option, 733
--package-name
gitlab-generic-package-download command
line option, 507
gitlab-generic-package-upload command
line option, 507
gitlab-group-package-list command line
option, 570
gitlab-project-package-list command
line option, 732
--package-type
gitlab-group-package-list command line
option, 570
gitlab-project-package-list command
line option, 732
--package-version
gitlab-generic-package-download command
line option, 507
gitlab-generic-package-upload command
line option, 507
--packages-enabled
gitlab-project-create command line
option, 596
gitlab-project-update command line
option, 608
--page
gitlab-application-list command line
option, 486
gitlab-audit-event-list command line
option, 493
gitlab-broadcast-message-list command
line option, 494
gitlab-bulk-import-all-entity-list
command line option, 496
gitlab-bulk-import-entity-list command
line option, 497
gitlab-bulk-import-list command line
option, 496
gitlab-current-user-email-list command
line option, 500
gitlab-current-user-gpg-key-list
command line option, 501
gitlab-current-user-key-list command
line option, 502
gitlab-deploy-key-list command line
option, 503
gitlab-deploy-token-list command line
option, 504

gitlab-dockerfile-list command line option, 505
 gitlab-event-list command line option, 505
 gitlab-feature-list command line option, 506
 gitlab-geo-node-list command line option, 509
 gitlab-gitignore-list command line option, 510
 gitlab-gitlabciyml-list command line option, 511
 gitlab-group-access-request-list command line option, 519
 gitlab-group-access-token-list command line option, 521
 gitlab-group-audit-event-list command line option, 522
 gitlab-group-badge-list command line option, 523
 gitlab-group-billable-member-list command line option, 525
 gitlab-group-billable-member-membership-list command line option, 525
 gitlab-group-board-list command line option, 527
 gitlab-group-board-list-list command line option, 529
 gitlab-group-cluster-list command line option, 531
 gitlab-group-custom-attribute-list command line option, 532
 gitlab-group-deploy-token-list command line option, 534
 gitlab-group-descendant-group-list command line option, 535
 gitlab-group-emoji-list command line option, 539
 gitlab-group-epic-issue-list command line option, 543
 gitlab-group-epic-list command line option, 537
 gitlab-group-epic-note-award-emoji-list command line option, 547
 gitlab-group-epic-note-list command line option, 545
 gitlab-group-epic-resource-label-event-list command line option, 548
 gitlab-group-hook-list command line option, 550
 gitlab-group-invitation-list command line option, 553
 gitlab-group-issue-list command line option, 555
 gitlab-group-iteration-list command line option, 556
 gitlab-group-label-list command line option, 558
 gitlab-group-ldap-group-link-list command line option, 560
 gitlab-group-list command line option, 515
 gitlab-group-member-all-list command line option, 563
 gitlab-group-member-list command line option, 562
 gitlab-group-merge-request-list command line option, 565
 gitlab-group-milestone-list command line option, 567
 gitlab-group-package-list command line option, 570
 gitlab-group-project-list command line option, 571
 gitlab-group-runner-list command line option, 574
 gitlab-group-saml-group-link-list command line option, 575
 gitlab-group-subgroup-list command line option, 576
 gitlab-group-variable-list command line option, 578
 gitlab-group-wiki-list command line option, 580
 gitlab-hook-list command line option, 582
 gitlab-issue-list command line option, 583
 gitlab-ldap-group-list command line option, 584
 gitlab-license-list command line option, 585
 gitlab-merge-request-list command line option, 587
 gitlab-namespace-list command line option, 588
 gitlab-pages-domain-list command line option, 590
 gitlab-personal-access-token-list command line option, 591
 gitlab-project-access-request-list command line option, 611
 gitlab-project-access-token-list command line option, 613
 gitlab-project-approval-rule-list command line option, 615
 gitlab-project-audit-event-list command line option, 618
 gitlab-project-badge-list command line

```
    option, 619
gitlab-project-board-list command line
    option, 621
gitlab-project-board-list-list command
    line option, 623
gitlab-project-branch-list command line
    option, 625
gitlab-project-cluster-list command
    line option, 628
gitlab-project-commit-comment-list
    command line option, 633
gitlab-project-commit-discussion-list
    command line option, 634
gitlab-project-commit-list command line
    option, 631
gitlab-project-commit-status-list
    command line option, 638
gitlab-project-custom-attribute-list
    command line option, 639
gitlab-project-deploy-token-list
    command line option, 640
gitlab-project-deployment-list command
    line option, 642
gitlab-project-deployment-merge-request-list
    command line option, 645
gitlab-project-environment-list command
    line option, 647
gitlab-project-event-list command line
    option, 648
gitlab-project-fork-list command line
    option, 653
gitlab-project-hook-list command line
    option, 655
gitlab-project-integration-list command
    line option, 658
gitlab-project-invitation-list command
    line option, 660
gitlab-project-issue-award-emoji-list
    command line option, 670
gitlab-project-issue-discussion-list
    command line option, 671
gitlab-project-issue-link-list command
    line option, 675
gitlab-project-issue-list command line
    option, 664
gitlab-project-issue-note-award-emoji-list
    command line option, 679
gitlab-project-issue-note-list command
    line option, 676
gitlab-project-issue-resource-iteration-event-d.gitlab-project-pages-domain-list
    command line option, 680
gitlab-project-issue-resource-label-event-listgitlab-project-pipeline-bridge-list
    command line option, 681
gitlab-project-issue-resource-milestone-event-d.gitlab-project-pipeline-job-list
```

```

    command line option, 739
gitlab-project-pipeline-list command
    line option, 737
gitlab-project-pipeline-schedule-list
    command line option, 741
gitlab-project-pipeline-schedule-pipeline-listgitlab-runner-list command line option,
    command line option, 743
gitlab-project-pipeline-variable-list
    command line option, 746
gitlab-project-protected-branch-list
    command line option, 748
gitlab-project-protected-environment-list
    command line option, 749
gitlab-project-protected-tag-list
    command line option, 751
gitlab-project-registry-repository-list
    command line option, 754
gitlab-project-registry-tag-list
    command line option, 756
gitlab-project-release-link-list
    command line option, 760
gitlab-project-release-list command
    line option, 758
gitlab-project-remote-mirror-list
    command line option, 762
gitlab-project-resource-group-list
    command line option, 763
gitlab-project-resource-group-upcoming-job-list
    command line option, 764
gitlab-project-runner-list command line
    option, 765
gitlab-project-secure-file-list command
    line option, 767
gitlab-project-service-list command
    line option, 769
gitlab-project-snippet-award-emoji-list
    command line option, 773
gitlab-project-snippet-discussion-list
    command line option, 775
gitlab-project-snippet-list command
    line option, 771
gitlab-project-snippet-note-award-emoji-list
    command line option, 781
gitlab-project-snippet-note-list
    command line option, 778
gitlab-project-tag-list command line
    option, 783
gitlab-project-trigger-list command
    line option, 784
gitlab-project-user-list command line
    option, 785
gitlab-project-variable-list command
    line option, 787
gitlab-project-wiki-list command line
    option, 789
gitlab-runner-all-list command line
    option, 793
gitlab-runner-job-list command line
    option, 794
gitlab-runner-list command line option,
    792
gitlab-shared-project-list command line
    option, 795
gitlab-snippet-list command line option,
    797
gitlab-starred-project-list command
    line option, 799
gitlab-todo-list command line option, 800
gitlab-topic-list command line option,
    802
gitlab-user-activities-list command
    line option, 809
gitlab-user-custom-attribute-list
    command line option, 810
gitlab-user-email-list command line
    option, 812
gitlab-user-event-list command line
    option, 812
gitlab-user-gpg-key-list command line
    option, 814
gitlab-user-impersonation-token-list
    command line option, 816
gitlab-user-key-list command line
    option, 817
gitlab-user-list command line option, 807
gitlab-user-membership-list command
    line option, 818
gitlab-user-project-list command line
    option, 821
gitlab-variable-list command line
    option, 823
--pages-access-level
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 608
--pagination
    gitlab command line option, 485
--parent-id
    gitlab-group-create command line option,
        513
    gitlab-namespace-exists command line
        option, 588
--password
    gitlab-user-create command line option,
        804
    gitlab-user-update command line option,
        808

```

```
--password-authentication-enabled-for-web  
    gitlab-application-settings-update  
        command line option, 490  
--path  
    gitlab-generic-package-upload command  
        line option, 507  
    gitlab-group-create command line option,  
        513  
    gitlab-group-update command line option,  
        517  
    gitlab-project-commit-comment-create  
        command line option, 633  
    gitlab-project-commit-list command line  
        option, 631  
    gitlab-project-create command line  
        option, 594  
    gitlab-project-repository-tree command  
        line option, 602  
    gitlab-project-update command line  
        option, 609  
--paused  
    gitlab-runner-all-list command line  
        option, 793  
    gitlab-runner-list command line option,  
        792  
--per-page  
    gitlab command line option, 485  
    gitlab-application-list command line  
        option, 486  
    gitlab-audit-event-list command line  
        option, 493  
    gitlab-broadcast-message-list command  
        line option, 494  
    gitlab-bulk-import-all-entity-list  
        command line option, 496  
    gitlab-bulk-import-entity-list command  
        line option, 497  
    gitlab-bulk-import-list command line  
        option, 496  
    gitlab-current-user-email-list command  
        line option, 500  
    gitlab-current-user-gpg-key-list  
        command line option, 501  
    gitlab-current-user-key-list command  
        line option, 502  
    gitlab-deploy-key-list command line  
        option, 503  
    gitlab-deploy-token-list command line  
        option, 504  
    gitlab-dockerfile-list command line  
        option, 505  
    gitlab-event-list command line option,  
        505  
    gitlab-feature-list command line option,  
        506  
gitlab-geo-node-list command line  
    option, 509  
gitlab-gitignore-list command line  
    option, 510  
gitlab-gitlabciyaml-list command line  
    option, 511  
gitlab-group-access-request-list  
    command line option, 519  
gitlab-group-access-token-list command  
    line option, 521  
gitlab-group-audit-event-list command  
    line option, 522  
gitlab-group-badge-list command line  
    option, 523  
gitlab-group-billable-member-list  
    command line option, 525  
gitlab-group-billable-member-membership-list  
    command line option, 525  
gitlab-group-board-list command line  
    option, 527  
gitlab-group-board-list-list command  
    line option, 529  
gitlab-group-cluster-list command line  
    option, 531  
gitlab-group-custom-attribute-list  
    command line option, 532  
gitlab-group-deploy-token-list command  
    line option, 534  
gitlab-group-descendant-group-list  
    command line option, 535  
gitlab-group-epic-award-emoji-list  
    command line option, 539  
gitlab-group-epic-issue-list command  
    line option, 543  
gitlab-group-epic-list command line  
    option, 537  
gitlab-group-epic-note-award-emoji-list  
    command line option, 547  
gitlab-group-epic-note-list command  
    line option, 545  
gitlab-group-epic-resource-label-event-list  
    command line option, 548  
gitlab-group-hook-list command line  
    option, 550  
gitlab-group-invitation-list command  
    line option, 554  
gitlab-group-issue-list command line  
    option, 555  
gitlab-group-iteration-list command  
    line option, 556  
gitlab-group-label-list command line  
    option, 558  
gitlab-group-ldap-group-link-list
```

command line option, 560
gitlab-group-list command line option, 515
gitlab-group-member-all-list command line option, 563
gitlab-group-member-list command line option, 562
gitlab-group-merge-request-list command line option, 565
gitlab-group-milestone-list command line option, 567
gitlab-group-package-list command line option, 570
gitlab-group-project-list command line option, 571
gitlab-group-runner-list command line option, 574
gitlab-group-saml-group-link-list command line option, 575
gitlab-group-subgroup-list command line option, 576
gitlab-group-variable-list command line option, 578
gitlab-group-wiki-list command line option, 580
gitlab-hook-list command line option, 582
gitlab-issue-list command line option, 583
gitlab-ldap-group-list command line option, 584
gitlab-license-list command line option, 585
gitlab-merge-request-list command line option, 587
gitlab-namespace-list command line option, 588
gitlab-pages-domain-list command line option, 590
gitlab-personal-access-token-list command line option, 591
gitlab-project-access-request-list command line option, 611
gitlab-project-access-token-list command line option, 613
gitlab-project-approval-rule-list command line option, 615
gitlab-project-audit-event-list command line option, 618
gitlab-project-badge-list command line option, 619
gitlab-project-board-list command line option, 621
gitlab-project-board-list-list command line option, 623

gitlab-project-branch-list command line option, 625
gitlab-project-cluster-list command line option, 628
gitlab-project-commit-comment-list command line option, 633
gitlab-project-commit-discussion-list command line option, 634
gitlab-project-commit-list command line option, 631
gitlab-project-commit-status-list command line option, 638
gitlab-project-custom-attribute-list command line option, 639
gitlab-project-deploy-token-list command line option, 640
gitlab-project-deployment-list command line option, 642
gitlab-project-deployment-merge-request-list command line option, 645
gitlab-project-environment-list command line option, 647
gitlab-project-event-list command line option, 648
gitlab-project-fork-list command line option, 653
gitlab-project-hook-list command line option, 655
gitlab-project-integration-list command line option, 658
gitlab-project-invitation-list command line option, 660
gitlab-project-issue-award-emoji-list command line option, 670
gitlab-project-issue-discussion-list command line option, 672
gitlab-project-issue-link-list command line option, 675
gitlab-project-issue-list command line option, 664
gitlab-project-issue-note-award-emoji-list command line option, 679
gitlab-project-issue-note-list command line option, 676
gitlab-project-issue-resource-iteration-event-list command line option, 680
gitlab-project-issue-resource-label-event-list command line option, 681
gitlab-project-issue-resource-milestone-event-list command line option, 682
gitlab-project-issue-resource-state-event-list command line option, 683
gitlab-project-issue-resource-weight-event-list command line option, 684

gitlab-project-job-list command line
 option, 687
gitlab-project-key-list command line
 option, 690
gitlab-project-label-list command line
 option, 692
gitlab-project-list command line option,
 600
gitlab-project-member-all-list command
 line option, 696
gitlab-project-member-list command line
 option, 694
gitlab-project-merge-request-approval-rule-list
 command line option, 709
gitlab-project-merge-request-award-emoji-list gitlab-project-release-link-list
 command line option, 712
gitlab-project-merge-request-diff-list
 command line option, 713
gitlab-project-merge-request-discussion-list
 command line option, 715
gitlab-project-merge-request-list
 command line option, 702
gitlab-project-merge-request-note-award-emoji
 command line option, 721
gitlab-project-merge-request-note-list
 command line option, 719
gitlab-project-merge-request-pipeline-list
 command line option, 722
gitlab-project-merge-request-resource-label-event
 command line option, 723
gitlab-project-merge-request-resource-milestone
 command line option, 724
gitlab-project-merge-request-resource-state-event
 command line option, 725
gitlab-project-merge-train-list command
 line option, 726
gitlab-project-milestone-list command
 line option, 728
gitlab-project-note-list command line
 option, 730
gitlab-project-package-file-list
 command line option, 733
gitlab-project-package-list command
 line option, 732
gitlab-project-pages-domain-list
 command line option, 735
gitlab-project-pipeline-bridge-list
 command line option, 738
gitlab-project-pipeline-job-list
 command line option, 739
gitlab-project-pipeline-list command
 line option, 737
gitlab-project-pipeline-schedule-list
 command line option, 741

gitlab-project-pipeline-schedule-pipeline-list
 command line option, 743
gitlab-project-pipeline-variable-list
 command line option, 746
gitlab-project-protected-branch-list
 command line option, 748
gitlab-project-protected-environment-list
 command line option, 749
gitlab-project-protected-tag-list
 command line option, 751
gitlab-project-registry-repository-list
 command line option, 754
gitlab-project-registry-tag-list
 command line option, 756
gitlab-project-release-link-list
 command line option, 760
gitlab-project-release-list command
 line option, 758
gitlab-project-remote-mirror-list
 command line option, 762
gitlab-project-resource-group-list
 command line option, 763
gitlab-project-resource-group-upcoming-job-list
 command line option, 764
gitlab-project-runner-list command line
 option, 765
gitlab-project-secure-file-list command
 line option, 767
gitlab-project-service-list command
 line option, 769
gitlab-project-snippet-award-emoji-list
 command line option, 773
gitlab-project-snippet-discussion-list
 command line option, 775
gitlab-project-snippet-list command
 line option, 771
gitlab-project-snippet-note-award-emoji-list
 command line option, 781
gitlab-project-snippet-note-list
 command line option, 778
gitlab-project-tag-list command line
 option, 783
gitlab-project-trigger-list command
 line option, 784
gitlab-project-user-list command line
 option, 785
gitlab-project-variable-list command
 line option, 787
gitlab-project-wiki-list command line
 option, 789
gitlab-runner-all-list command line
 option, 793
gitlab-runner-job-list command line
 option, 794

```

gitlab-runner-list command line option,
    792
gitlab-shared-project-list command line
    option, 795
gitlab-snippet-list command line option,
    797
gitlab-starred-project-list command
    line option, 799
gitlab-todo-list command line option, 800
gitlab-topic-list command line option,
    802
gitlab-user-activities-list command
    line option, 809
gitlab-user-custom-attribute-list
    command line option, 810
gitlab-user-email-list command line
    option, 812
gitlab-user-event-list command line
    option, 813
gitlab-user-gpg-key-list command line
    option, 814
gitlab-user-impersonation-token-list
    command line option, 816
gitlab-user-key-list command line
    option, 817
gitlab-user-list command line option, 807
gitlab-user-membership-list command
    line option, 818
gitlab-user-project-list command line
    option, 821
gitlab-variable-list command line
    option, 823
--performance-bar-allowed-group-id
    gitlab-application-settings-update
        command line option, 491
--pipeline-events
    gitlab-group-hook-create command line
        option, 549
    gitlab-group-hook-update command line
        option, 551
    gitlab-project-hook-create command line
        option, 654
    gitlab-project-hook-update command line
        option, 656
--pipeline-id
    gitlab-project-pipeline-bridge-list
        command line option, 738
    gitlab-project-pipeline-job-list
        command line option, 739
    gitlab-project-pipeline-test-report-get
        command line option, 745
    gitlab-project-pipeline-test-report-summary-get
        command line option, 745
    gitlab-project-pipeline-variable-list
        command line option, 746
--pipeline-schedule-id
    gitlab-project-pipeline-schedule-pipeline-list
        command line option, 743
    gitlab-project-pipeline-schedule-variable-create
        command line option, 743
    gitlab-project-pipeline-schedule-variable-delete
        command line option, 744
    gitlab-project-pipeline-schedule-variable-update
        command line option, 744
--plantuml-enabled
    gitlab-application-settings-update
        command line option, 491
--plantuml-url
    gitlab-application-settings-update
        command line option, 491
--platform-kubernetes-attributes
    gitlab-group-cluster-create command
        line option, 530
    gitlab-group-cluster-update command
        line option, 531
    gitlab-project-cluster-create command
        line option, 627
    gitlab-project-cluster-update command
        line option, 628
--polling-interval-multiplier
    gitlab-application-settings-update
        command line option, 491
--popular
    gitlab-license-list command line option,
        585
--position
    gitlab-group-board-list-update command
        line option, 529
    gitlab-project-board-list-update
        command line option, 623
    gitlab-project-commit-discussion-note-create
        command line option, 635
    gitlab-project-merge-request-discussion-create
        command line option, 714
--prevent-forking-outside-group
    gitlab-group-update command line option,
        518
--prevent-secrets
    gitlab-group-push-rules-create command
        line option, 572
    gitlab-group-push-rules-update command
        line option, 573
    gitlab-project-push-rules-create
        command line option, 752
    gitlab-project-push-rules-update
        command line option, 754
    --printing-merge-request-link-enabled
        gitlab-project-create command line

```

```
    option, 596
--priority
    gitlab-group-label-create command line
        option, 557
    gitlab-group-label-update command line
        option, 559
    gitlab-project-label-create command
        line option, 691
    gitlab-project-label-update command
        line option, 693
--private-profile
    gitlab-user-create command line option,
        805
    gitlab-user-update command line option,
        809
--private-token
    gitlab command line option, 485
--process-mode
    gitlab-project-resource-group-update
        command line option, 763
--project
    gitlab-license-get command line option,
        585
--project-creation-level
    gitlab-group-create command line option,
        513
    gitlab-group-update command line option,
        517
--project-id
    gitlab-generic-package-download command
        line option, 507
    gitlab-generic-package-upload command
        line option, 507
    gitlab-group-transfer-project command
        line option, 516
    gitlab-project-access-request-approve
        command line option, 610
    gitlab-project-access-request-create
        command line option, 611
    gitlab-project-access-request-delete
        command line option, 611
    gitlab-project-access-request-list
        command line option, 611
    gitlab-project-access-token-create
        command line option, 612
    gitlab-project-access-token-delete
        command line option, 612
    gitlab-project-access-token-list
        command line option, 613
    gitlab-project-additional-statistics-get
        command line option, 613
    gitlab-project-approval-get command
        line option, 613
    gitlab-project-approval-rule-create
        command line option, 614
    gitlab-project-approval-rule-delete
        command line option, 615
    gitlab-project-approval-rule-list
        command line option, 615
    gitlab-project-approval-rule-update
        command line option, 616
    gitlab-project-approval-update command
        line option, 614
    gitlab-project-artifact-delete command
        line option, 616
    gitlab-project-artifact-download
        command line option, 616
    gitlab-project-artifact-raw command
        line option, 617
    gitlab-project-audit-event-get command
        line option, 617
    gitlab-project-audit-event-list command
        line option, 618
    gitlab-project-badge-create command
        line option, 618
    gitlab-project-badge-delete command
        line option, 618
    gitlab-project-badge-get command line
        option, 619
    gitlab-project-badge-list command line
        option, 619
    gitlab-project-badge-render command
        line option, 619
    gitlab-project-badge-update command
        line option, 620
    gitlab-project-board-create command
        line option, 620
    gitlab-project-board-delete command
        line option, 620
    gitlab-project-board-get command line
        option, 621
    gitlab-project-board-list command line
        option, 621
    gitlab-project-board-list-create
        command line option, 622
    gitlab-project-board-list-delete
        command line option, 622
    gitlab-project-board-list-get command
        line option, 622
    gitlab-project-board-list-list command
        line option, 623
    gitlab-project-board-list-update
        command line option, 623
    gitlab-project-board-update command
        line option, 621
    gitlab-project-branch-create command
        line option, 624
    gitlab-project-branch-delete command
```

```
    line option, 624
gitlab-project-branch-get command line
    option, 624
gitlab-project-branch-list command line
    option, 625
gitlab-project-ci-lint-create command
    line option, 625
gitlab-project-ci-lint-get command line
    option, 626
gitlab-project-ci-lint-validate command
    line option, 626
gitlab-project-cluster-create command
    line option, 627
gitlab-project-cluster-delete command
    line option, 627
gitlab-project-cluster-get command line
    option, 627
gitlab-project-cluster-list command
    line option, 628
gitlab-project-cluster-update command
    line option, 628
gitlab-project-commit-cherry-pick
    command line option, 629
gitlab-project-commit-comment-create
    command line option, 632
gitlab-project-commit-comment-list
    command line option, 633
gitlab-project-commit-create command
    line option, 629
gitlab-project-commit-diff command line
    option, 630
gitlab-project-commit-discussion-create
    command line option, 634
gitlab-project-commit-discussion-get
    command line option, 634
gitlab-project-commit-discussion-list
    command line option, 634
gitlab-project-commit-discussion-note-create
    command line option, 635
gitlab-project-commit-discussion-note-delete
    command line option, 635
gitlab-project-commit-discussion-note-get
    command line option, 636
gitlab-project-commit-discussion-note-update
    command line option, 636
gitlab-project-commit-get command line
    option, 630
gitlab-project-commit-list command line
    option, 630
gitlab-project-commit-merge-requests
    command line option, 631
gitlab-project-commit-refs command line
    option, 631
gitlab-project-commit-revert command
    line option, 632
gitlab-project-commit-signature command
    line option, 632
gitlab-project-commit-status-create
    command line option, 637
gitlab-project-commit-status-list
    command line option, 637
gitlab-project-custom-attribute-delete
    command line option, 638
gitlab-project-custom-attribute-get
    command line option, 638
gitlab-project-custom-attribute-list
    command line option, 639
gitlab-project-deploy-token-create
    command line option, 639
gitlab-project-deploy-token-delete
    command line option, 640
gitlab-project-deploy-token-get command
    line option, 640
gitlab-project-deploy-token-list
    command line option, 640
gitlab-project-deployment-approval
    command line option, 641
gitlab-project-deployment-create
    command line option, 641
gitlab-project-deployment-get command
    line option, 642
gitlab-project-deployment-list command
    line option, 642
gitlab-project-deployment-merge-request-list
    command line option, 644
gitlab-project-deployment-update
    command line option, 643
gitlab-project-environment-create
    command line option, 646
gitlab-project-environment-delete
    command line option, 646
gitlab-project-environment-get command
    line option, 646
gitlab-project-environment-list command
    line option, 646
gitlab-project-environment-stop command
    line option, 647
gitlab-project-environment-update
    command line option, 647
gitlab-project-event-list command line
    option, 648
gitlab-project-export-create command
    line option, 649
gitlab-project-export-download command
    line option, 649
gitlab-project-export-get command line
    option, 649
gitlab-project-file-blame command line
```

```
    option, 650
gitlab-project-file-create command line
    option, 650
gitlab-project-file-delete command line
    option, 651
gitlab-project-file-get command line
    option, 651
gitlab-project-file-raw command line
    option, 651
gitlab-project-file-update command line
    option, 652
gitlab-project-fork-create command line
    option, 652
gitlab-project-fork-list command line
    option, 653
gitlab-project-hook-create command line
    option, 654
gitlab-project-hook-delete command line
    option, 655
gitlab-project-hook-get command line
    option, 655
gitlab-project-hook-list command line
    option, 655
gitlab-project-hook-update command line
    option, 656
gitlab-project-import-get command line
    option, 657
gitlab-project-integration-available
    command line option, 657
gitlab-project-integration-delete
    command line option, 657
gitlab-project-integration-get command
    line option, 658
gitlab-project-integration-list command
    line option, 658
gitlab-project-integration-update
    command line option, 658
gitlab-project-invitation-create
    command line option, 659
gitlab-project-invitation-delete
    command line option, 659
gitlab-project-invitation-get command
    line option, 660
gitlab-project-invitation-list command
    line option, 660
gitlab-project-invitation-update
    command line option, 660
gitlab-project-issue-add-spent-time
    command line option, 661
gitlab-project-issue-award-emoji-create
    command line option, 669
gitlab-project-issue-award-emoji-delete
    command line option, 669
gitlab-project-issue-award-emoji-get
    command line option, 670
gitlab-project-issue-award-emoji-list
    command line option, 670
gitlab-project-issue-closed-by command
    line option, 662
gitlab-project-issue-create command
    line option, 662
gitlab-project-issue-delete command
    line option, 663
gitlab-project-issue-discussion-create
    command line option, 671
gitlab-project-issue-discussion-get
    command line option, 671
gitlab-project-issue-discussion-list
    command line option, 671
gitlab-project-issue-discussion-note-create
    command line option, 672
gitlab-project-issue-discussion-note-delete
    command line option, 673
gitlab-project-issue-discussion-note-get
    command line option, 673
gitlab-project-issue-discussion-note-update
    command line option, 674
gitlab-project-issue-get command line
    option, 663
gitlab-project-issue-link-create
    command line option, 674
gitlab-project-issue-link-delete
    command line option, 674
gitlab-project-issue-link-list command
    line option, 675
gitlab-project-issue-list command line
    option, 663
gitlab-project-issue-move command line
    option, 664
gitlab-project-issue-note-award-emoji-create
    command line option, 677
gitlab-project-issue-note-award-emoji-delete
    command line option, 678
gitlab-project-issue-note-award-emoji-get
    command line option, 678
gitlab-project-issue-note-award-emoji-list
    command line option, 679
gitlab-project-issue-note-create
    command line option, 675
gitlab-project-issue-note-delete
    command line option, 676
gitlab-project-issue-note-get command
    line option, 676
gitlab-project-issue-note-list command
    line option, 676
gitlab-project-issue-note-update
    command line option, 677
gitlab-project-issue-participants
```

```
    command line option, 665
gitlab-project-issue-related-merge-requests      option, 686
    command line option, 665
gitlab-project-issue-reorder command               gitlab-project-job-get command line
    line option, 665                                option, 686
gitlab-project-issue-reset-spent-time           gitlab-project-job-keep-artifacts
    command line option, 666                           command line option, 687
gitlab-project-issue-reset-time-estimate        gitlab-project-job-list command line
    command line option, 666                           option, 687
gitlab-project-issue-resource-iteration-event   gitlab-project-job-play command line
    command line option, 679                           option, 687
gitlab-project-issue-resource-iteration-event   gitlab-project-job-retry command line
    command line option, 680                           option, 688
gitlab-project-issue-resource-label-event-get   gitlab-project-job-trace command line
    command line option, 680                           option, 688
gitlab-project-issue-resource-label-event-list  gitlab-project-key-create command line
    command line option, 681                           option, 688
gitlab-project-issue-resource-milestone-event   gitlab-project-key-delete command line
    command line option, 681                           option, 689
gitlab-project-issue-resource-milestone-event   gitlab-project-key-enable command line
    command line option, 681                           option, 689
gitlab-project-issue-resource-milestone-event   gitlab-project-key-get command line
    command line option, 682                           option, 689
gitlab-project-issue-resource-state-event-get  gitlab-project-key-list command line
    command line option, 682                           option, 690
gitlab-project-issue-resource-state-event-list  gitlab-project-key-update command line
    command line option, 683                           option, 690
gitlab-project-issue-resource-weight-event-get  gitlab-project-label-create command
    command line option, 683                           line option, 691
gitlab-project-issue-resource-weight-event-list  gitlab-project-label-delete command
    command line option, 684                           line option, 691
gitlab-project-issue-subscribe command           gitlab-project-label-get command line
    line option, 666                                 option, 691
gitlab-project-issue-time-estimate             gitlab-project-label-list command line
    command line option, 666                           option, 692
gitlab-project-issue-time-stats command         gitlab-project-label-subscribe command
    line option, 667                                 line option, 692
gitlab-project-issue-todo command               gitlab-project-label-unsubscribe
    line option, 667                               command line option, 692
gitlab-project-issue-unsubscribe              gitlab-project-label-update command
    command line option, 667                           line option, 693
gitlab-project-issue-update command            gitlab-project-member-all-get command
    line option, 668                                 line option, 695
gitlab-project-issue-user-agent-detail        gitlab-project-member-all-list command
    command line option, 668                           line option, 695
gitlab-project-issues-statistics-get          gitlab-project-member-create command
    command line option, 684                           line option, 693
gitlab-project-job-artifact command           gitlab-project-member-delete command
    line option, 685                                 line option, 694
gitlab-project-job-artifacts command          gitlab-project-member-get command line
    line option, 685                               option, 694
gitlab-project-job-cancel command line        gitlab-project-member-list command line
    option, 686                                 option, 694
gitlab-project-job-delete-artifacts          gitlab-project-member-update command
    command line option, 686                           line option, 695
gitlab-project-job-erase command line
```

```
    command line option, 697
gitlab-project-merge-request-approval-get      command line option, 717
    command line option, 707
gitlab-project-merge-request-approval-rule-create
    command line option, 708
gitlab-project-merge-request-approval-rule-delete
    command line option, 708
gitlab-project-merge-request-approval-rule-getgitlab-project-merge-request-list
    command line option, 709
gitlab-project-merge-request-approval-rule-listgitlab-project-merge-request-merge
    command line option, 709
gitlab-project-merge-request-approval-rule-updatelab-project-merge-request-ref
    command line option, 710
gitlab-project-merge-request-approval-state-getgitlab-project-merge-request-note-award-emoji-create
    command line option, 711
gitlab-project-merge-request-approval-updategitlab-project-merge-request-note-award-emoji-delete
    command line option, 707
gitlab-project-merge-request-approve          gitlab-project-merge-request-note-award-emoji-get
    command line option, 697
gitlab-project-merge-request-award-emoji-createlab-project-merge-request-note-award-emoji-list
    command line option, 711
gitlab-project-merge-request-award-emoji-deletelab-project-merge-request-note-create
    command line option, 712
gitlab-project-merge-request-award-emoji-get  gitlab-project-merge-request-note-delete
    command line option, 712
gitlab-project-merge-request-award-emoji-list gitlab-project-merge-request-note-get
    command line option, 712
gitlab-project-merge-request-cancel-merge-whengitlab-project-merge-request-note-list
    command line option, 697
gitlab-project-merge-request-changes         gitlab-project-merge-request-note-update
    command line option, 698
gitlab-project-merge-request-closes-issues   gitlab-project-merge-request-participants
    command line option, 698
gitlab-project-merge-request-commits        gitlab-project-merge-request-pipeline-create
    command line option, 698
gitlab-project-merge-request-create         gitlab-project-merge-request-pipeline-list
    command line option, 699
gitlab-project-merge-request-delete         gitlab-project-merge-request-rebase
    command line option, 700
gitlab-project-merge-request-diff-get       gitlab-project-merge-request-reset-approvals
    command line option, 713
gitlab-project-merge-request-diff-list      gitlab-project-merge-request-reset-spent-time
    command line option, 713
gitlab-project-merge-request-discussion-creategitlab-project-merge-request-reset-time-estimate
    command line option, 714
gitlab-project-merge-request-discussion-get  gitlab-project-merge-request-resource-label-event-get
    command line option, 714
gitlab-project-merge-request-discussion-list gitlab-project-merge-request-resource-label-event-list
    command line option, 715
gitlab-project-merge-request-discussion-note-create
    command line option, 716
gitlab-project-merge-request-discussion-note-delete
    command line option, 716
gitlab-project-merge-request-discussion-note-getgitlab-project-merge-request-resource-milestone-event-
    command line option, 716
gitlab-project-merge-request-discussion-note-getgitlab-project-merge-request-resource-milestone-event-
    command line option, 724
gitlab-project-merge-request-discussion-note-getgitlab-project-merge-request-resource-state-event-get
```

```

    command line option, 725
gitlab-project-merge-request-resource-state-event command
    command line option, 725
gitlab-project-merge-request-subscribe
    command line option, 704
gitlab-project-merge-request-time-estimate
    command line option, 704
gitlab-project-merge-request-time-stats
    command line option, 705
gitlab-project-merge-request-todo
    command line option, 705
gitlab-project-merge-request-unapprove
    command line option, 705
gitlab-project-merge-request-unsubscribe
    command line option, 705
gitlab-project-merge-request-update
    command line option, 706
gitlab-project-merge-train-list command
    line option, 726
gitlab-project-milestone-create command
    line option, 727
gitlab-project-milestone-delete command
    line option, 727
gitlab-project-milestone-get command
    line option, 727
gitlab-project-milestone-issues command
    line option, 728
gitlab-project-milestone-list command
    line option, 728
gitlab-project-milestone-merge-requests
    command line option, 728
gitlab-project-milestone-update command
    line option, 729
gitlab-project-note-get command line
    option, 729
gitlab-project-note-list command line
    option, 730
gitlab-project-notification-settings-get
    command line option, 730
gitlab-project-notification-settings-update
    command line option, 731
gitlab-project-package-delete command
    line option, 732
gitlab-project-package-file-delete
    command line option, 733
gitlab-project-package-file-list
    command line option, 733
gitlab-project-package-get command line
    option, 732
gitlab-project-package-list command
    line option, 732
gitlab-project-pages-domain-create
    command line option, 734
gitlab-project-pages-domain-delete
    command line option, 734
gitlab-project-project-pages-domain-get command
    line option, 735
gitlab-project-pages-domain-list
    command line option, 735
gitlab-project-pages-domain-update
    command line option, 735
gitlab-project-pipeline-bridge-list
    command line option, 738
gitlab-project-pipeline-cancel command
    line option, 736
gitlab-project-pipeline-create command
    line option, 736
gitlab-project-pipeline-delete command
    line option, 736
gitlab-project-pipeline-get command
    line option, 737
gitlab-project-pipeline-job-list
    command line option, 739
gitlab-project-pipeline-list command
    line option, 737
gitlab-project-pipeline-retry command
    line option, 738
gitlab-project-pipeline-schedule-create
    command line option, 740
gitlab-project-pipeline-schedule-delete
    command line option, 740
gitlab-project-pipeline-schedule-get
    command line option, 740
gitlab-project-pipeline-schedule-list
    command line option, 741
gitlab-project-pipeline-schedule-pipeline-list
    command line option, 743
gitlab-project-pipeline-schedule-play
    command line option, 741
gitlab-project-pipeline-schedule-take-ownership
    command line option, 741
gitlab-project-pipeline-schedule-update
    command line option, 742
gitlab-project-pipeline-schedule-variable-create
    command line option, 743
gitlab-project-pipeline-schedule-variable-delete
    command line option, 744
gitlab-project-pipeline-schedule-variable-update
    command line option, 744
gitlab-project-pipeline-test-report-get
    command line option, 745
gitlab-project-pipeline-test-report-summary-get
    command line option, 745
gitlab-project-pipeline-variable-list
    command line option, 746
gitlab-project-protected-branch-create
    command line option, 747
gitlab-project-protected-branch-delete
    command line option, 747

```

command line option, 747
gitlab-project-protected-branch-get
 command line option, 747
gitlab-project-protected-branch-list
 command line option, 748
gitlab-project-protected-environment-create
 command line option, 748
gitlab-project-protected-environment-delete
 command line option, 749
gitlab-project-protected-environment-get
 command line option, 749
gitlab-project-protected-environment-list
 command line option, 749
gitlab-project-protected-tag-create
 command line option, 750
gitlab-project-protected-tag-delete
 command line option, 750
gitlab-project-protected-tag-get
 command line option, 751
gitlab-project-protected-tag-list
 command line option, 751
gitlab-project-push-rules-create
 command line option, 752
gitlab-project-push-rules-delete
 command line option, 753
gitlab-project-push-rules-get command
 line option, 753
gitlab-project-push-rules-update
 command line option, 753
gitlab-project-registry-repository-delete
 command line option, 754
gitlab-project-registry-repository-list
 command line option, 754
gitlab-project-registry-tag-delete
 command line option, 755
gitlab-project-registry-tag-delete-in-bulk
 command line option, 755
gitlab-project-registry-tag-get command
 line option, 756
gitlab-project-registry-tag-list
 command line option, 756
gitlab-project-release-create command
 line option, 757
gitlab-project-release-delete command
 line option, 757
gitlab-project-release-get command line
 option, 757
gitlab-project-release-link-create
 command line option, 759
gitlab-project-release-link-delete
 command line option, 759
gitlab-project-release-link-get command
 line option, 760
gitlab-project-release-link-list
 command line option, 760
gitlab-project-release-link-update
 command line option, 761
gitlab-project-release-list command
 line option, 758
gitlab-project-release-update command
 line option, 758
gitlab-project-remote-mirror-create
 command line option, 761
gitlab-project-remote-mirror-list
 command line option, 762
gitlab-project-remote-mirror-update
 command line option, 762
gitlab-project-resource-group-get
 command line option, 762
gitlab-project-resource-group-list
 command line option, 763
gitlab-project-resource-group-upcoming-job-list
 command line option, 764
gitlab-project-resource-group-update
 command line option, 763
gitlab-project-runner-create command
 line option, 765
gitlab-project-runner-delete command
 line option, 765
gitlab-project-runner-list command line
 option, 765
gitlab-project-secure-file-create
 command line option, 766
gitlab-project-secure-file-delete
 command line option, 766
gitlab-project-secure-file-download
 command line option, 766
gitlab-project-secure-file-get command
 line option, 767
gitlab-project-secure-file-list command
 line option, 767
gitlab-project-service-available
 command line option, 768
gitlab-project-service-delete command
 line option, 768
gitlab-project-service-get command line
 option, 768
gitlab-project-service-list command
 line option, 768
gitlab-project-service-update command
 line option, 769
gitlab-project-snippet-award-emoji-create
 command line option, 772
gitlab-project-snippet-award-emoji-delete
 command line option, 772
gitlab-project-snippet-award-emoji-get
 command line option, 773
gitlab-project-snippet-award-emoji-list

```

    command line option, 773
gitlab-project-snippet-content command
    line option, 769
gitlab-project-snippet-create command
    line option, 770
gitlab-project-snippet-delete command
    line option, 770
gitlab-project-snippet-discussion-create
    command line option, 774
gitlab-project-snippet-discussion-get
    command line option, 774
gitlab-project-snippet-discussion-list
    command line option, 775
gitlab-project-snippet-discussion-note-create gitlab-project-user-list command line
    command line option, 775
gitlab-project-snippet-discussion-note-delete gitlab-project-variable-create command
    command line option, 776
gitlab-project-snippet-discussion-note-get    gitlab-project-variable-delete command
    command line option, 776
gitlab-project-snippet-discussion-note-update gitlab-project-variable-get command
    command line option, 777
gitlab-project-snippet-get command line
    option, 770
gitlab-project-snippet-list command
    line option, 771
gitlab-project-snippet-note-award-emoji-creategitlab-project-wiki-create command line
    command line option, 779
gitlab-project-snippet-note-award-emoji-deletegitlab-project-wiki-delete command line
    command line option, 780
gitlab-project-snippet-note-award-emoji-get    gitlab-project-wiki-get command line
    command line option, 780
gitlab-project-snippet-note-award-emoji-list  gitlab-project-wiki-list command line
    command line option, 781
gitlab-project-snippet-note-create
    command line option, 777
gitlab-project-snippet-note-delete
    command line option, 778
gitlab-project-snippet-note-get command
    line option, 778
gitlab-project-snippet-note-list
    command line option, 778
gitlab-project-snippet-note-update
    command line option, 779
gitlab-project-snippet-update command
    line option, 771
gitlab-project-snippet-user-agent-detail
    command line option, 772
gitlab-project-storage-get command line
    option, 781
gitlab-project-tag-create command line
    option, 782
gitlab-project-tag-delete command line
    option, 782
gitlab-project-tag-get command line
    option, 782
gitlab-project-tag-list command line
    option, 783
gitlab-project-trigger-create command
    line option, 783
gitlab-project-trigger-delete command
    line option, 784
gitlab-project-trigger-get command line
    option, 784
gitlab-project-trigger-list command
    line option, 784
gitlab-project-trigger-update command
    line option, 785
gitlab-project-variable-create command
    line option, 786
gitlab-project-variable-delete command
    line option, 786
gitlab-project-variable-get command
    line option, 787
gitlab-project-variable-list command
    line option, 787
gitlab-project-variable-update command
    line option, 787
gitlab-project-wiki-create command line
    option, 788
gitlab-project-wiki-delete command line
    option, 788
gitlab-project-wiki-get command line
    option, 789
gitlab-project-wiki-list command line
    option, 789
gitlab-project-wiki-update command line
    option, 789
gitlab-todo-list command line option, 800
--projects-limit
gitlab-user-create command line option,
    804
gitlab-user-update command line option,
    808
--protected
gitlab-group-variable-create command
    line option, 577
gitlab-group-variable-update command
    line option, 579
gitlab-project-variable-create command
    line option, 786
gitlab-project-variable-update command
    line option, 788
gitlab-variable-create command line
    option, 822
gitlab-variable-update command line
    option, 823

```

```
--protected-branch-ids
    gitlab-project-approval-rule-create
        command line option, 615
--provider
    gitlab-group-add-ldap-group-link
        command line option, 512
    gitlab-group-delete-ldap-group-link
        command line option, 514
    gitlab-group-ldap-group-link-create
        command line option, 560
    gitlab-ldap-group-list command line
        option, 584
    gitlab-user-create command line option,
        804
    gitlab-user-list command line option, 806
    gitlab-user-update command line option,
        808
--public
    gitlab-user-project-create command line
        option, 819
--public-builds
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
    gitlab-user-project-create command line
        option, 819
--public-email
    gitlab-user-create command line option,
        805
    gitlab-user-update command line option,
        809
--push-access-level
    gitlab-project-protected-branch-create
        command line option, 747
--push-events
    gitlab-group-hook-create command line
        option, 549
    gitlab-group-hook-update command line
        option, 551
    gitlab-project-hook-create command line
        option, 654
    gitlab-project-hook-update command line
        option, 656
--query
    gitlab-group-invitation-list command
        line option, 553
    gitlab-project-invitation-list command
        line option, 660
--reassign-issue
    gitlab-group-notification-settings-update
        command line option, 569
    gitlab-notification-settings-update
        command line option, 589
    gitlab-project-notification-settings-update
        command line option, 731
--reassign-merge-request
    gitlab-group-notification-settings-update
        command line option, 569
    gitlab-notification-settings-update
        command line option, 590
    gitlab-project-notification-settings-update
        command line option, 731
--recursive
    gitlab-project-repository-tree command
        line option, 602
--redirect-uri
    gitlab-application-create command line
        option, 486
--ref
    gitlab-project-branch-create command
        line option, 624
    gitlab-project-ci-lint-create command
        line option, 625
    gitlab-project-ci-lint-validate command
        line option, 626
    gitlab-project-commit-status-create
        command line option, 637
    gitlab-project-deployment-create
        command line option, 641
    gitlab-project-file-blame command line
        option, 650
    gitlab-project-file-get command line
        option, 651
    gitlab-project-file-raw command line
        option, 651
    gitlab-project-pipeline-create command
        line option, 736
    gitlab-project-pipeline-list command
        line option, 737
    gitlab-project-pipeline-schedule-create
        command line option, 740
    gitlab-project-pipeline-schedule-update
        command line option, 742
    gitlab-project-release-create command
        line option, 757
    gitlab-project-repository-tree command
        line option, 602
    gitlab-project-tag-create command line
        option, 782
    gitlab-project-trigger-pipeline command
        line option, 604
--ref-name
    gitlab-project-artifact command line
        option, 592
    gitlab-project-artifact-delete command
        line option, 616
    gitlab-project-artifact-download
```

```

    command line option, 616
gitlab-project-artifact-raw command
    line option, 617
gitlab-project-artifacts command line
    option, 593
gitlab-project-commit-list command line
    option, 630
--refs
    gitlab-project-repository-merge-base
        command line option, 601
--reject-unsigned-commits
    gitlab-group-push-rules-create command
        line option, 572
    gitlab-group-push-rules-update command
        line option, 573
    gitlab-project-push-rules-create
        command line option, 752
    gitlab-project-push-rules-update
        command line option, 754
--released-at
    gitlab-project-release-update command
        line option, 758
--releases-access-level
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
--releases-events
    gitlab-group-hook-create command line
        option, 550
    gitlab-group-hook-update command line
        option, 552
--remove-source-branch
    gitlab-project-merge-request-create
        command line option, 699
    gitlab-project-merge-request-update
        command line option, 706
--remove-source-branch-after-merge
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
--render-html
    gitlab-project-merge-request-get
        command line option, 700
--reopen-issue
    gitlab-group-notification-settings-update
        command line option, 569
    gitlab-notification-settings-update
        command line option, 589
    gitlab-project-notification-settings-update
        command line option, 731
--reopen-merge-request
    gitlab-group-notification-settings-update
        command line option, 569
    gitlab-notification-settings-update
        command line option, 589
    gitlab-project-notification-settings-update
        command line option, 731
--repo
    gitlab-project-repository-merge-base
        command line option, 569
    gitlab-notification-settings-update
        command line option, 589
    gitlab-project-notification-settings-update
        command line option, 731
--repos-max-capacity
    gitlab-geo-node-update command line
        option, 510
--repository-access-level
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
--repository-checksum-failed
    gitlab-project-list command line option,
        599
    gitlab-user-project-list command line
        option, 821
--repository-id
    gitlab-project-registry-tag-delete
        command line option, 755
    gitlab-project-registry-tag-delete-in-bulk
        command line option, 755
    gitlab-project-registry-tag-get command
        line option, 756
    gitlab-project-registry-tag-list
        command line option, 756
--repository-storage
    gitlab-project-create command line
        option, 596
    gitlab-project-list command line option,
        599
    gitlab-project-update command line
        option, 609
--repository-storages
    gitlab-application-settings-update
        command line option, 491
--represented-as
    gitlab-project-deployment-approval
        command line option, 641
--request-access-enabled
    gitlab-group-create command line option,
        513
    gitlab-group-update command line option,
        518
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
--require-two-factor-authentication
    gitlab-group-create command line option,
        513
    gitlab-group-update command line option,
        517

```

```
--required-approval-count          --runner-id
    gitlab-project-protected-environment-create command line option, 748      gitlab-project-runner-create command
                                         line option, 765
--requirements-access-level        gitlab-runner-job-list command line
    gitlab-project-create command line      option, 794
                                         option, 596
    gitlab-project-update command line      --saml-group-name
                                         option, 608      gitlab-group-saml-group-link-create
                                         command line option, 575
--reset-approvals-on-push         --scope
    gitlab-project-approval-update command      gitlab-group-merge-request-list command
                                         line option, 614      line option, 564
                                         gitlab-group-runner-list command line
--reset-password                  option, 574
    gitlab-user-create command line option,      gitlab-group-search command line option,
                                         804      515
--resolve-outdated-diff-discussions gitlab-issue-list command line option,
                                         gitlab-project-deployment-merge-request-list
                                         option, 596      command line option, 644
                                         gitlab-project-issue-list command line
                                         option, 609      option, 664
                                         gitlab-project-job-list command line
                                         option, 764      option, 687
                                         gitlab-project-merge-request-list
                                         command line option, 701
                                         gitlab-project-merge-train-list command
                                         line option, 726
                                         gitlab-project-pipeline-bridge-list
                                         command line option, 738
                                         gitlab-project-pipeline-job-list
                                         command line option, 739
                                         gitlab-project-pipeline-list command
                                         line option, 737
                                         gitlab-project-runner-list command line
                                         option, 765
                                         gitlab-project-search command line
                                         option, 602
                                         gitlab-runner-all command line option,
                                         790
                                         gitlab-runner-all-list command line
                                         option, 793
                                         gitlab-runner-list command line option,
                                         792
                                         --scopes
                                         gitlab-application-create command line
                                         option, 486
                                         gitlab-group-access-token-create
                                         command line option, 520
                                         gitlab-group-deploy-token-create
                                         command line option, 533
                                         gitlab-group-deploy-token-list command
                                         line option, 534
```

```

gitlab-project-access-token-create
    command line option, 612
gitlab-project-deploy-token-create
    command line option, 639
gitlab-project-deploy-token-list
    command line option, 640
gitlab-user-impersonation-token-create
    command line option, 815
gitlab-user-personal-access-token-create
    command line option, 818
--search
    gitlab-group-billable-member-list
        command line option, 525
    gitlab-group-descendant-group-list
        command line option, 535
    gitlab-group-epic-list command line
        option, 537
    gitlab-group-issue-list command line
        option, 555
    gitlab-group-iteration-list command
        line option, 556
    gitlab-group-list command line option,
        515
    gitlab-group-merge-request-list command
        line option, 565
    gitlab-group-milestone-list command
        line option, 567
    gitlab-group-project-list command line
        option, 571
    gitlab-group-search command line option,
        515
    gitlab-group-subgroup-list command line
        option, 576
    gitlab-issue-list command line option,
        583
    gitlab-ldap-group-list command line
        option, 584
    gitlab-merge-request-list command line
        option, 587
    gitlab-namespace-list command line
        option, 588
    gitlab-project-deployment-merge-request-list
        command line option, 645
    gitlab-project-environment-list command
        line option, 646
    gitlab-project-fork-list command line
        option, 653
    gitlab-project-issue-list command line
        option, 664
    gitlab-project-list command line option,
        599
    gitlab-project-merge-request-list
        command line option, 701
    gitlab-project-milestone-list command
        line option, 728
gitlab-project-search command line
    option, 602
gitlab-project-user-list command line
    option, 785
gitlab-shared-project-list command line
    option, 795
gitlab-starred-project-list command
    line option, 799
gitlab-user-list command line option, 806
gitlab-user-project-list command line
    option, 820
--search-namespaces
    gitlab-project-list command line option,
        599
--security-and-compliance-access-level
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
--server-url
    gitlab command line option, 485
--service-desk-enabled
    gitlab-project-update command line
        option, 609
--session-expire-delay
    gitlab-application-settings-update
        command line option, 490
--sha
    gitlab-project-deployment-create
        command line option, 641
    gitlab-project-merge-request-approve
        command line option, 697
    gitlab-project-pipeline-list command
        line option, 737
    gitlab-project-repository-archive
        command line option, 600
    gitlab-project-repository-blob command
        line option, 601
    gitlab-project-repository-raw-blob
        command line option, 602
share-with-group-lock
    gitlab-group-create command line option,
        513
    gitlab-group-update command line option,
        517
--shared-runners-enabled
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
--shared-runners-minutes-limit
    gitlab-group-create command line option,
        513

```

```
gitlab-group-update command line option,  
      518  
--shared-runners-setting  
    gitlab-group-update command line option,  
      518  
--should-remove-source-branch  
  gitlab-project-merge-request-merge  
    command line option, 702  
--show-default-award-emojis  
  gitlab-project-create command line  
    option, 596  
  gitlab-project-update command line  
    option, 609  
--sign-in-text  
  gitlab-application-settings-update  
    command line option, 490  
--signup-enabled  
  gitlab-application-settings-update  
    command line option, 490  
--simple  
  gitlab-group-project-list command line  
    option, 571  
  gitlab-project-fork-list command line  
    option, 653  
  gitlab-project-list command line option,  
    599  
  gitlab-shared-project-list command line  
    option, 795  
  gitlab-starred-project-list command  
    line option, 799  
  gitlab-user-project-list command line  
    option, 820  
--since  
  gitlab-project-commit-list command line  
    option, 630  
--skip-confirmation  
  gitlab-user-create command line option,  
    805  
--skip-groups  
  gitlab-group-descendant-group-list  
    command line option, 535  
  gitlab-group-list command line option,  
    514  
  gitlab-group-subgroup-list command line  
    option, 576  
--skip-reconfirmation  
  gitlab-user-update command line option,  
    808  
--skip-users  
  gitlab-project-user-list command line  
    option, 785  
--skype  
  gitlab-user-create command line option,  
    804  
gitlab-user-update command line option,  
      808  
--slug  
  gitlab-group-wiki-delete command line  
    option, 579  
  gitlab-group-wiki-get command line  
    option, 580  
  gitlab-group-wiki-update command line  
    option, 580  
  gitlab-project-integration-available  
    command line option, 657  
  gitlab-project-integration-delete  
    command line option, 657  
  gitlab-project-integration-get command  
    line option, 658  
  gitlab-project-integration-update  
    command line option, 658  
  gitlab-project-service-available  
    command line option, 768  
  gitlab-project-service-delete command  
    line option, 768  
  gitlab-project-service-get command line  
    option, 768  
  gitlab-project-service-update command  
    line option, 769  
  gitlab-project-wiki-delete command line  
    option, 788  
  gitlab-project-wiki-get command line  
    option, 789  
  gitlab-project-wiki-update command line  
    option, 789  
--snippet-id  
  gitlab-project-snippet-award-emoji-create  
    command line option, 772  
  gitlab-project-snippet-award-emoji-delete  
    command line option, 773  
  gitlab-project-snippet-award-emoji-get  
    command line option, 773  
  gitlab-project-snippet-award-emoji-list  
    command line option, 773  
  gitlab-project-snippet-discussion-create  
    command line option, 774  
  gitlab-project-snippet-discussion-get  
    command line option, 774  
  gitlab-project-snippet-discussion-list  
    command line option, 775  
  gitlab-project-snippet-discussion-note-create  
    command line option, 775  
  gitlab-project-snippet-discussion-note-delete  
    command line option, 776  
  gitlab-project-snippet-discussion-note-get  
    command line option, 776  
  gitlab-project-snippet-discussion-note-update  
    command line option, 777
```

```

gitlab-project-snippet-note-award-emoji-create    option, 571
    command line option, 779
gitlab-project-snippet-note-award-emoji-delete   option, 576
    command line option, 780
gitlab-project-snippet-note-award-emoji-get      command line option, 780
gitlab-project-snippet-note-award-emoji-list     command line option, 781
gitlab-project-snippet-note-create               command line option, 777
gitlab-project-snippet-note-delete              command line option, 778
gitlab-project-snippet-note-get command line
    option, 778
gitlab-project-snippet-note-list                command line option, 778
gitlab-project-snippet-note-update              command line option, 779
--snippets-access-level
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
--snippets-enabled
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
    gitlab-user-project-create command line
        option, 819
--sort
    gitlab-bulk-import-all-entity-list
        command line option, 496
    gitlab-bulk-import-entity-list command
        line option, 497
    gitlab-bulk-import-list command line
        option, 496
    gitlab-event-list command line option,
        505
    gitlab-group-billable-member-list
        command line option, 525
    gitlab-group-descendant-group-list
        command line option, 535
    gitlab-group-epic-list command line
        option, 537
    gitlab-group-issue-list command line
        option, 555
    gitlab-group-list command line option,
        515
    gitlab-group-merge-request-list command
        line option, 564
    gitlab-group-package-list command line
        option, 570
    gitlab-group-project-list command line
        option, 571
gitlab-group-subgroup-list command line
gitlab-issue-list command line option,
    583
gitlab-merge-request-list command line
    option, 586
gitlab-project-deployment-list command
    line option, 642
gitlab-project-deployment-merge-request-list
    command line option, 644
gitlab-project-event-list command line
    option, 648
gitlab-project-fork-list command line
    option, 653
gitlab-project-issue-list command line
    option, 664
gitlab-project-list command line option,
    599
gitlab-project-merge-request-list
    command line option, 701
gitlab-project-package-list command
    line option, 732
gitlab-project-pipeline-list command
    line option, 737
gitlab-project-release-list command
    line option, 758
gitlab-project-resource-group-list
    command line option, 763
gitlab-shared-project-list command line
    option, 795
gitlab-starred-project-list command
    line option, 799
gitlab-user-event-list command line
    option, 812
gitlab-user-project-list command line
    option, 820
--source
    gitlab-project-pipeline-list command
        line option, 737
--source-branch
    gitlab-group-merge-request-list command
        line option, 565
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-merge-request-list
        command line option, 645
    gitlab-project-merge-request-create
        command line option, 699
    gitlab-project-merge-request-list
        command line option, 701
--source-id
    gitlab-user-membership-get command line
        option, 818

```

```
--source-topic-id
    gitlab-topic-merge command line option,
        802
--squash
    gitlab-project-merge-request-create
        command line option, 699
    gitlab-project-merge-request-update
        command line option, 706
--squash-commit-template
    gitlab-project-update command line
        option, 609
--squash-option
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
    gitlab-user-project-create command line
        option, 819
--ssl-verify
    gitlab command line option, 485
--starred
    gitlab-group-project-list command line
        option, 571
    gitlab-project-fork-list command line
        option, 653
    gitlab-project-list command line option,
        599
    gitlab-shared-project-list command line
        option, 795
    gitlab-starred-project-list command
        line option, 799
    gitlab-user-project-list command line
        option, 820
--start-date
    gitlab-group-epic-create command line
        option, 536
    gitlab-group-epic-update command line
        option, 538
    gitlab-group-milestone-create command
        line option, 566
    gitlab-group-milestone-update command
        line option, 568
    gitlab-project-milestone-create command
        line option, 727
    gitlab-project-milestone-update command
        line option, 729
--starts-at
    gitlab-broadcast-message-create command
        line option, 493
    gitlab-broadcast-message-update command
        line option, 495
--state
    gitlab-group-issue-list command line
        option, 555
gitlab-group-iteration-list command
    line option, 556
gitlab-group-merge-request-list command
    line option, 564
gitlab-group-milestone-list command
    line option, 567
gitlab-issue-list command line option,
    583
gitlab-merge-request-list command line
    option, 586
gitlab-project-commit-status-create
    command line option, 637
gitlab-project-deployment-merge-request-list
    command line option, 644
gitlab-project-issue-list command line
    option, 663
gitlab-project-merge-request-list
    command line option, 701
gitlab-project-milestone-list command
    line option, 728
gitlab-todo-list command line option, 800
gitlab-user-impersonation-token-list
    command line option, 815
--state-event
    gitlab-group-milestone-update command
        line option, 568
    gitlab-project-issue-update command
        line option, 668
    gitlab-project-merge-request-update
        command line option, 706
    gitlab-project-milestone-create command
        line option, 727
    gitlab-project-milestone-update command
        line option, 729
--states
    gitlab-project-environment-list command
        line option, 647
--statistics
    gitlab-group-descendant-group-list
        command line option, 535
    gitlab-group-list command line option,
        515
    gitlab-group-subgroup-list command line
        option, 576
    gitlab-project-fork-list command line
        option, 653
    gitlab-project-list command line option,
        599
    gitlab-starred-project-list command
        line option, 799
    gitlab-user-project-list command line
        option, 820
--status
    gitlab-bulk-import-all-entity-list
```

```

    command line option, 496
gitlab-bulk-import-entity-list command
    line option, 497
gitlab-bulk-import-list command line
    option, 496
gitlab-project-deployment-approval
    command line option, 641
gitlab-project-deployment-create
    command line option, 641
gitlab-project-deployment-list command
    line option, 642
gitlab-project-pipeline-list command
    line option, 737
gitlab-runner-all-list command line
    option, 793
gitlab-runner-job-list command line
    option, 794
gitlab-runner-list command line option,
    792
gitlab-user-list command line option, 806
--subgroup-creation-level
    gitlab-group-create command line option,
        513
    gitlab-group-update command line option,
        517
--subgroup-events
    gitlab-group-hook-create command line
        option, 550
    gitlab-group-hook-update command line
        option, 552
--submodule
    gitlab-project-update-submodule command
        line option, 610
--sudo
    gitlab-application-appearance-get
        command line option, 487
    gitlab-application-appearance-update
        command line option, 487
    gitlab-application-create command line
        option, 485
    gitlab-application-delete command line
        option, 486
    gitlab-application-list command line
        option, 486
    gitlab-application-settings-get command
        line option, 488
    gitlab-application-settings-update
        command line option, 490
    gitlab-application-statistics-get
        command line option, 492
    gitlab-audit-event-get command line
        option, 492
    gitlab-audit-event-list command line
        option, 492
gitlab-broadcast-message-create command
    line option, 493
gitlab-broadcast-message-delete command
    line option, 494
gitlab-broadcast-message-get command
    line option, 494
gitlab-broadcast-message-list command
    line option, 494
gitlab-broadcast-message-update command
    line option, 495
gitlab-bulk-import-all-entity-list
    command line option, 496
gitlab-bulk-import-create command line
    option, 495
gitlab-bulk-import-entity-get command
    line option, 497
gitlab-bulk-import-entity-list command
    line option, 497
gitlab-bulk-import-get command line
    option, 495
gitlab-bulk-import-list command line
    option, 496
gitlab-ci-lint-create command line
    option, 498
gitlab-current-user-email-create
    command line option, 499
gitlab-current-user-email-delete
    command line option, 499
gitlab-current-user-email-get command
    line option, 499
gitlab-current-user-email-list command
    line option, 500
gitlab-current-user-get command line
    option, 499
gitlab-current-user-gpg-key-create
    command line option, 500
gitlab-current-user-gpg-key-delete
    command line option, 500
gitlab-current-user-gpg-key-get command
    line option, 501
gitlab-current-user-gpg-key-list
    command line option, 501
gitlab-current-user-key-create command
    line option, 501
gitlab-current-user-key-delete command
    line option, 502
gitlab-current-user-key-get command
    line option, 502
gitlab-current-user-key-list command
    line option, 502
gitlab-current-user-status-get command
    line option, 503
gitlab-current-user-status-update
    command line option, 503

```

gitlab-deploy-key-list command line
 option, 503
gitlab-deploy-token-list command line
 option, 504
gitlab-dockerfile-get command line
 option, 504
gitlab-dockerfile-list command line
 option, 505
gitlab-event-list command line option,
 505
gitlab-feature-delete command line
 option, 506
gitlab-feature-list command line option,
 506
gitlab-generic-package-download command
 line option, 507
gitlab-generic-package-upload command
 line option, 507
gitlab-geo-node-delete command line
 option, 508
gitlab-geo-node-get command line option,
 508
gitlab-geo-node-list command line
 option, 509
gitlab-geo-node-update command line
 option, 509
gitlab-gitignore-get command line
 option, 510
gitlab-gitignore-list command line
 option, 510
gitlab-gitlabciyml-get command line
 option, 511
gitlab-gitlabciyml-list command line
 option, 511
gitlab-group-access-request-approve
 command line option, 518
gitlab-group-access-request-create
 command line option, 519
gitlab-group-access-request-delete
 command line option, 519
gitlab-group-access-request-list
 command line option, 519
gitlab-group-access-token-create
 command line option, 520
gitlab-group-access-token-delete
 command line option, 520
gitlab-group-access-token-list command
 line option, 520
gitlab-group-audit-event-get command
 line option, 521
gitlab-group-audit-event-list command
 line option, 521
gitlab-group-badge-create command line
 option, 522
gitlab-group-badge-delete command line
 option, 522
gitlab-group-badge-get command line
 option, 523
gitlab-group-badge-list command line
 option, 523
gitlab-group-badge-render command line
 option, 523
gitlab-group-badge-update command line
 option, 524
gitlab-group-billable-member-delete
 command line option, 524
gitlab-group-billable-member-list
 command line option, 524
gitlab-group-billable-member-membership-list
 command line option, 525
gitlab-group-board-create command line
 option, 526
gitlab-group-board-delete command line
 option, 526
gitlab-group-board-get command line
 option, 526
gitlab-group-board-list command line
 option, 527
gitlab-group-board-list-create command
 line option, 528
gitlab-group-board-list-delete command
 line option, 528
gitlab-group-board-list-get command
 line option, 528
gitlab-group-board-list-list command
 line option, 529
gitlab-group-board-list-update command
 line option, 529
gitlab-group-board-update command line
 option, 527
gitlab-group-cluster-create command
 line option, 530
gitlab-group-cluster-delete command
 line option, 530
gitlab-group-cluster-get command line
 option, 530
gitlab-group-cluster-list command line
 option, 531
gitlab-group-cluster-update command
 line option, 531
gitlab-group-create command line option,
 512
gitlab-group-custom-attribute-delete
 command line option, 532
gitlab-group-custom-attribute-get
 command line option, 532
gitlab-group-custom-attribute-list
 command line option, 532

gitlab-group-delete command line option, 513
gitlab-group-deploy-token-create command line option, 533
gitlab-group-deploy-token-delete command line option, 533
gitlab-group-deploy-token-get command line option, 534
gitlab-group-deploy-token-list command line option, 534
gitlab-group-descendant-group-list command line option, 535
gitlab-group-epic-award-emoji-create command line option, 538
gitlab-group-epic-award-emoji-delete command line option, 539
gitlab-group-epic-award-emoji-get command line option, 539
gitlab-group-epic-award-emoji-list command line option, 539
gitlab-group-epic-create command line option, 536
gitlab-group-epic-delete command line option, 536
gitlab-group-epic-discussion-note-create command line option, 540
gitlab-group-epic-discussion-note-delete command line option, 540
gitlab-group-epic-discussion-note-get command line option, 541
gitlab-group-epic-discussion-note-update command line option, 541
gitlab-group-epic-get command line option, 537
gitlab-group-epic-issue-create command line option, 542
gitlab-group-epic-issue-delete command line option, 542
gitlab-group-epic-issue-list command line option, 542
gitlab-group-epic-issue-update command line option, 543
gitlab-group-epic-list command line option, 537
gitlab-group-epic-note-award-emoji-create command line option, 545
gitlab-group-epic-note-award-emoji-delete command line option, 546
gitlab-group-epic-note-award-emoji-get command line option, 546
gitlab-group-epic-note-award-emoji-list command line option, 546
gitlab-group-epic-note-create command line option, 543
gitlab-group-epic-note-delete command line option, 544
gitlab-group-epic-note-get command line option, 544
gitlab-group-epic-note-list command line option, 544
gitlab-group-epic-note-update command line option, 545
gitlab-group-epic-resource-label-event-get command line option, 547
gitlab-group-epic-resource-label-event-list command line option, 547
gitlab-group-epic-update command line option, 538
gitlab-group-export-create command line option, 548
gitlab-group-export-download command line option, 548
gitlab-group-export-get command line option, 548
gitlab-group-get command line option, 514
gitlab-group-hook-create command line option, 549
gitlab-group-hook-delete command line option, 550
gitlab-group-hook-get command line option, 550
gitlab-group-hook-list command line option, 550
gitlab-group-hook-update command line option, 551
gitlab-group-import-get command line option, 552
gitlab-group-invitation-create command line option, 552
gitlab-group-invitation-delete command line option, 553
gitlab-group-invitation-get command line option, 553
gitlab-group-invitation-list command line option, 553
gitlab-group-invitation-update command line option, 554
gitlab-group-issue-list command line option, 555
gitlab-group-issues-statistics-get command line option, 556
gitlab-group-iteration-list command line option, 556
gitlab-group-label-create command line option, 557
gitlab-group-label-delete command line option, 557
gitlab-group-label-get command line

```
    option, 558
gitlab-group-label-list command line
    option, 558
gitlab-group-label-subscribe command
    line option, 558
gitlab-group-label-unsubscribe command
    line option, 559
gitlab-group-label-update command line
    option, 559
gitlab-group-ldap-group-link-create
    command line option, 560
gitlab-group-ldap-group-link-delete
    command line option, 560
gitlab-group-ldap-group-link-list
    command line option, 560
gitlab-group-list command line option,
    514
gitlab-group-member-all-get command
    line option, 563
gitlab-group-member-all-list command
    line option, 563
gitlab-group-member-create command line
    option, 561
gitlab-group-member-delete command line
    option, 561
gitlab-group-member-get command line
    option, 561
gitlab-group-member-list command line
    option, 562
gitlab-group-member-update command line
    option, 562
gitlab-group-merge-request-list command
    line option, 564
gitlab-group-milestone-create command
    line option, 565
gitlab-group-milestone-delete command
    line option, 566
gitlab-group-milestone-get command line
    option, 566
gitlab-group-milestone-issues command
    line option, 566
gitlab-group-milestone-list command
    line option, 567
gitlab-group-milestone-merge-requests
    command line option, 567
gitlab-group-milestone-update command
    line option, 568
gitlab-group-notification-settings-get
    command line option, 568
gitlab-group-notification-settings-update
    command line option, 569
gitlab-group-package-list command line
    option, 570
gitlab-group-project-list command line
    option, 571
gitlab-group-push-rules-create command
    line option, 572
gitlab-group-push-rules-delete command
    line option, 572
gitlab-group-push-rules-get command
    line option, 573
gitlab-group-push-rules-update command
    line option, 573
gitlab-group-runner-list command line
    option, 574
gitlab-group-saml-group-link-create
    command line option, 574
gitlab-group-saml-group-link-delete
    command line option, 575
gitlab-group-saml-group-link-get
    command line option, 575
gitlab-group-saml-group-link-list
    command line option, 575
gitlab-group-subgroup-list command line
    option, 576
gitlab-group-update command line option,
    517
gitlab-group-variable-create command
    line option, 577
gitlab-group-variable-delete command
    line option, 577
gitlab-group-variable-get command line
    option, 578
gitlab-group-variable-list command line
    option, 578
gitlab-group-variable-update command
    line option, 578
gitlab-group-wiki-create command line
    option, 579
gitlab-group-wiki-delete command line
    option, 579
gitlab-group-wiki-get command line
    option, 580
gitlab-group-wiki-list command line
    option, 580
gitlab-group-wiki-update command line
    option, 580
gitlab-hook-create command line option,
    581
gitlab-hook-delete command line option,
    581
gitlab-hook-get command line option, 581
gitlab-hook-list command line option, 582
gitlab-issue-get command line option, 582
gitlab-issue-list command line option,
    583
gitlab-issues-statistics-get command
    line option, 584
```

gitlab-key-get command line option, 584
gitlab-ldap-group-list command line option, 584
gitlab-license-get command line option, 585
gitlab-license-list command line option, 585
gitlab-merge-request-list command line option, 586
gitlab-namespace-get command line option, 588
gitlab-namespace-list command line option, 588
gitlab-notification-settings-get command line option, 589
gitlab-notification-settings-update command line option, 589
gitlab-pages-domain-list command line option, 590
gitlab-personal-access-token-delete command line option, 590
gitlab-personal-access-token-get command line option, 591
gitlab-personal-access-token-list command line option, 591
gitlab-project-access-request-approve command line option, 610
gitlab-project-access-request-create command line option, 611
gitlab-project-access-request-delete command line option, 611
gitlab-project-access-request-list command line option, 611
gitlab-project-access-token-create command line option, 612
gitlab-project-access-token-delete command line option, 612
gitlab-project-access-token-list command line option, 612
gitlab-project-additional-statistics-get command line option, 613
gitlab-project-approval-get command line option, 613
gitlab-project-approval-rule-create command line option, 614
gitlab-project-approval-rule-delete command line option, 615
gitlab-project-approval-rule-list command line option, 615
gitlab-project-approval-rule-update command line option, 616
gitlab-project-approval-update command line option, 614
gitlab-project-artifact-delete command line option, 616
gitlab-project-artifact-download command line option, 616
gitlab-project-artifact-raw command line option, 617
gitlab-project-audit-event-get command line option, 617
gitlab-project-audit-event-list command line option, 617
gitlab-project-badge-create command line option, 618
gitlab-project-badge-delete command line option, 618
gitlab-project-badge-get command line option, 619
gitlab-project-badge-list command line option, 619
gitlab-project-badge-render command line option, 619
gitlab-project-badge-update command line option, 620
gitlab-project-board-create command line option, 620
gitlab-project-board-delete command line option, 620
gitlab-project-board-get command line option, 621
gitlab-project-board-list command line option, 621
gitlab-project-board-list-create command line option, 622
gitlab-project-board-list-delete command line option, 622
gitlab-project-board-list-get command line option, 622
gitlab-project-board-list-list command line option, 623
gitlab-project-board-list-update command line option, 623
gitlab-project-board-update command line option, 621
gitlab-project-branch-create command line option, 624
gitlab-project-branch-delete command line option, 624
gitlab-project-branch-get command line option, 624
gitlab-project-branch-list command line option, 625
gitlab-project-ci-lint-create command line option, 625
gitlab-project-ci-lint-get command line option, 626
gitlab-project-ci-lint-validate command

```
    line option, 626
gitlab-project-cluster-create command
    line option, 627
gitlab-project-cluster-delete command
    line option, 627
gitlab-project-cluster-get command line
    option, 627
gitlab-project-cluster-list command
    line option, 628
gitlab-project-cluster-update command
    line option, 628
gitlab-project-commit-cherry-pick
    command line option, 629
gitlab-project-commit-comment-create
    command line option, 632
gitlab-project-commit-comment-list
    command line option, 633
gitlab-project-commit-create command
    line option, 629
gitlab-project-commit-diff command line
    option, 630
gitlab-project-commit-discussion-create
    command line option, 633
gitlab-project-commit-discussion-get
    command line option, 634
gitlab-project-commit-discussion-list
    command line option, 634
gitlab-project-commit-discussion-note-create
    command line option, 635
gitlab-project-commit-discussion-note-delete
    command line option, 635
gitlab-project-commit-discussion-note-get
    command line option, 636
gitlab-project-commit-discussion-note-update
    command line option, 636
gitlab-project-commit-get command line
    option, 630
gitlab-project-commit-list command line
    option, 630
gitlab-project-commit-merge-requests
    command line option, 631
gitlab-project-commit-refs command line
    option, 631
gitlab-project-commit-revert command
    line option, 632
gitlab-project-commit-signature command
    line option, 632
gitlab-project-commit-status-create
    command line option, 637
gitlab-project-commit-status-list
    command line option, 637
gitlab-project-create command line
    option, 594
gitlab-project-custom-attribute-delete
    command line option, 638
gitlab-project-custom-attribute-get
    command line option, 638
gitlab-project-custom-attribute-list
    command line option, 639
gitlab-project-delete command line
    option, 597
gitlab-project-deploy-token-create
    command line option, 639
gitlab-project-deploy-token-delete
    command line option, 640
gitlab-project-deploy-token-get command
    line option, 640
gitlab-project-deploy-token-list
    command line option, 640
gitlab-project-deployment-approval
    command line option, 641
gitlab-project-deployment-create
    command line option, 641
gitlab-project-deployment-get command
    line option, 642
gitlab-project-deployment-list command
    line option, 642
gitlab-project-deployment-merge-request-list
    command line option, 644
gitlab-project-deployment-update
    command line option, 643
gitlab-project-environment-create
    command line option, 645
gitlab-project-environment-delete
    command line option, 646
gitlab-project-environment-get command
    line option, 646
gitlab-project-environment-list command
    line option, 646
gitlab-project-environment-stop command
    line option, 647
gitlab-project-environment-update
    command line option, 647
gitlab-project-event-list command line
    option, 648
gitlab-project-export-create command
    line option, 649
gitlab-project-export-download command
    line option, 649
gitlab-project-export-get command line
    option, 649
gitlab-project-file-blame command line
    option, 650
gitlab-project-file-create command line
    option, 650
gitlab-project-file-delete command line
    option, 651
gitlab-project-file-get command line
```

```
    option, 651
gitlab-project-file-raw command line
    option, 651
gitlab-project-file-update command line
    option, 652
gitlab-project-fork-create command line
    option, 652
gitlab-project-fork-list command line
    option, 653
gitlab-project-get command line option,
    598
gitlab-project-hook-create command line
    option, 654
gitlab-project-hook-delete command line
    option, 655
gitlab-project-hook-get command line
    option, 655
gitlab-project-hook-list command line
    option, 655
gitlab-project-hook-update command line
    option, 656
gitlab-project-import-get command line
    option, 657
gitlab-project-integration-available
    command line option, 657
gitlab-project-integration-delete
    command line option, 657
gitlab-project-integration-get command
    line option, 658
gitlab-project-integration-list command
    line option, 658
gitlab-project-integration-update
    command line option, 658
gitlab-project-invitation-create
    command line option, 659
gitlab-project-invitation-delete
    command line option, 659
gitlab-project-invitation-get command
    line option, 660
gitlab-project-invitation-list command
    line option, 660
gitlab-project-invitation-update
    command line option, 660
gitlab-project-issue-add-spent-time
    command line option, 661
gitlab-project-issue-award-emoji-create
    command line option, 669
gitlab-project-issue-award-emoji-delete
    command line option, 669
gitlab-project-issue-award-emoji-get
    command line option, 670
gitlab-project-issue-award-emoji-list
    command line option, 670
gitlab-project-issue-closed-by command
    line option, 662
gitlab-project-issue-create command
    line option, 662
gitlab-project-issue-delete command
    line option, 663
gitlab-project-issue-discussion-create
    command line option, 671
gitlab-project-issue-discussion-get
    command line option, 671
gitlab-project-issue-discussion-list
    command line option, 671
gitlab-project-issue-discussion-note-create
    command line option, 672
gitlab-project-issue-discussion-note-delete
    command line option, 673
gitlab-project-issue-discussion-note-get
    command line option, 673
gitlab-project-issue-discussion-note-update
    command line option, 673
gitlab-project-issue-get command line
    option, 663
gitlab-project-issue-link-create
    command line option, 674
gitlab-project-issue-link-delete
    command line option, 674
gitlab-project-issue-link-list command
    line option, 675
gitlab-project-issue-list command line
    option, 663
gitlab-project-issue-move command line
    option, 664
gitlab-project-issue-note-award-emoji-create
    command line option, 677
gitlab-project-issue-note-award-emoji-delete
    command line option, 678
gitlab-project-issue-note-award-emoji-get
    command line option, 678
gitlab-project-issue-note-award-emoji-list
    command line option, 678
gitlab-project-issue-note-create
    command line option, 675
gitlab-project-issue-note-delete
    command line option, 676
gitlab-project-issue-note-get command
    line option, 676
gitlab-project-issue-note-list command
    line option, 676
gitlab-project-issue-note-update
    command line option, 677
gitlab-project-issue-participants
    command line option, 665
gitlab-project-issue-related-merge-requests
    command line option, 665
gitlab-project-issue-reorder command
```

line option, 665
gitlab-project-issue-reset-spent-time command line option, 666
gitlab-project-issue-reset-time-estimate command line option, 666
gitlab-project-issue-resource-iteration-event command line option, 679
gitlab-project-issue-resource-iteration-event command line option, 680
gitlab-project-issue-resource-label-event-get gitlab-project-key-create command line option, 680
gitlab-project-issue-resource-label-event-listgitlab-project-key-delete command line option, 681
gitlab-project-issue-resource-milestone-event gitlab-project-key-enable command line option, 681
gitlab-project-issue-resource-milestone-event gitlab-project-key-get command line option, 682
gitlab-project-issue-resource-state-event-get gitlab-project-key-list command line option, 682
gitlab-project-issue-resource-state-event-listgitlab-project-key-update command line option, 683
gitlab-project-issue-resource-weight-event-getgitlab-project-label-create command line option, 683
gitlab-project-issue-resource-weight-event-listgitlab-project-label-delete command line option, 684
gitlab-project-issue-subscribe command line option, 666
gitlab-project-issue-time-estimate command line option, 666
gitlab-project-issue-time-stats command line option, 667
gitlab-project-issue-todo command line option, 667
gitlab-project-issue-unsubscribe command line option, 667
gitlab-project-issue-update command line option, 668
gitlab-project-issue-user-agent-detail command line option, 668
gitlab-project-issues-statistics-get command line option, 684
gitlab-project-job-artifact command line option, 685
gitlab-project-job-artifacts command line option, 685
gitlab-project-job-cancel command line option, 686
gitlab-project-job-delete-artifacts command line option, 686
gitlab-project-job-erase command line option, 686
gitlab-project-job-get command line option, 686
gitlab-project-job-keep-artifacts command line option, 687
gitlab-project-job-list command line option, 687
gitlab-project-job-play command line option, 687
gitlab-project-job-retry command line option, 688
gitlab-project-job-trace command line option, 688
gitlab-project-key-create command line option, 688
gitlab-project-key-delete command line option, 689
gitlab-project-key-enable command line option, 689
gitlab-project-key-get command line option, 689
gitlab-project-key-list command line option, 690
gitlab-project-key-update command line option, 690
gitlab-project-label-create command line option, 691
gitlab-project-label-delete command line option, 691
gitlab-project-label-get command line option, 691
gitlab-project-label-list command line option, 692
gitlab-project-label-subscribe command line option, 692
gitlab-project-label-unsubscribe command line option, 692
gitlab-project-label-update command line option, 693
gitlab-project-list command line option, 599
gitlab-project-member-all-get command line option, 695
gitlab-project-member-all-list command line option, 695
gitlab-project-member-create command line option, 693
gitlab-project-member-delete command line option, 694
gitlab-project-member-get command line option, 694
gitlab-project-member-list command line option, 694
gitlab-project-member-update command line option, 695
gitlab-project-merge-request-add-spent-time command line option, 697
gitlab-project-merge-request-approval-get

```

    command line option, 707
gitlab-project-merge-request-approval-rule-create command line option, 708
gitlab-project-merge-request-approval-rule-del command line option, 708
gitlab-project-merge-request-approval-rule-get command line option, 709
gitlab-project-merge-request-approval-rule-list command line option, 709
gitlab-project-merge-request-approval-rule-update command line option, 710
gitlab-project-merge-request-approval-state-get command line option, 711
gitlab-project-merge-request-approval-update command line option, 707
gitlab-project-merge-request-approve command line option, 697
gitlab-project-merge-request-award-emoji-create command line option, 711
gitlab-project-merge-request-award-emoji-delete command line option, 712
gitlab-project-merge-request-award-emoji-list gitlab-project-merge-request-note-award-emoji-create
    command line option, 720
gitlab-project-merge-request-note-award-emoji-delete command line option, 720
gitlab-project-merge-request-note-award-emoji-get command line option, 721
gitlab-project-merge-request-note-award-emoji-list command line option, 721
gitlab-project-merge-request-note-create command line option, 718
gitlab-project-merge-request-note-delete command line option, 718
gitlab-project-merge-request-note-get command line option, 719
gitlab-project-merge-request-cancel-merge-wherewhen command line option, 697
gitlab-project-merge-request-changes command line option, 698
gitlab-project-merge-request-closes-issues command line option, 698
gitlab-project-merge-request-commits command line option, 698
gitlab-project-merge-request-create command line option, 699
gitlab-project-merge-request-delete command line option, 700
gitlab-project-merge-request-diff-get command line option, 713
gitlab-project-merge-request-diff-list command line option, 713
gitlab-project-merge-request-discussion-create command line option, 714
gitlab-project-merge-request-discussion-get command line option, 714
gitlab-project-merge-request-discussion-list command line option, 715
gitlab-project-merge-request-discussion-note-create command line option, 716
gitlab-project-merge-request-discussion-note-del command line option, 716
gitlab-project-merge-request-discussion-note-get command line option, 717
gitlab-project-merge-request-discussion-note-updatemerge request note update command line option, 717
gitlab-project-merge-request-discussion-update command line option, 715
gitlab-project-merge-request-get command line option, 700
gitlab-project-merge-request-list command line option, 701
gitlab-project-merge-request-merge command line option, 702
gitlab-project-merge-request-merge-ref command line option, 702
gitlab-project-merge-request-note-award-emoji-create command line option, 720
gitlab-project-merge-request-note-award-emoji-delete command line option, 720
gitlab-project-merge-request-note-award-emoji-list command line option, 721
gitlab-project-merge-request-note-create command line option, 718
gitlab-project-merge-request-note-delete command line option, 718
gitlab-project-merge-request-note-get command line option, 719
gitlab-project-merge-request-note-list command line option, 719
gitlab-project-merge-request-note-update command line option, 719
gitlab-project-merge-request-participants command line option, 703
gitlab-project-merge-request-pipeline-create command line option, 722
gitlab-project-merge-request-pipeline-list command line option, 722
gitlab-project-merge-request-rebase command line option, 703
gitlab-project-merge-request-reset-approvals command line option, 703
gitlab-project-merge-request-reset-spent-time command line option, 704
gitlab-project-merge-request-reset-time-estimate command line option, 704
gitlab-project-merge-request-resource-label-event-get command line option, 723
gitlab-project-merge-request-resource-label-event-list command line option, 723
gitlab-project-merge-request-resource-milestone-event-command line option, 724
gitlab-project-merge-request-resource-milestone-event-command line option, 724
gitlab-project-merge-request-resource-state-event-get command line option, 725
gitlab-project-merge-request-resource-state-event-list command line option, 725

```

```
    command line option, 725
gitlab-project-merge-request-subscribe
    command line option, 704
gitlab-project-merge-request-time-estimate
    command line option, 704
gitlab-project-merge-request-time-stats
    command line option, 705
gitlab-project-merge-request-todo
    command line option, 705
gitlab-project-merge-request-unapprove
    command line option, 705
gitlab-project-merge-request-unsubscribe
    command line option, 705
gitlab-project-merge-request-update
    command line option, 706
gitlab-project-merge-train-list command
    line option, 726
gitlab-project-milestone-create command
    line option, 727
gitlab-project-milestone-delete command
    line option, 727
gitlab-project-milestone-get command
    line option, 727
gitlab-project-milestone-issues command
    line option, 728
gitlab-project-milestone-list command
    line option, 728
gitlab-project-milestone-merge-requests
    command line option, 728
gitlab-project-milestone-update command
    line option, 729
gitlab-project-note-get command line
    option, 729
gitlab-project-note-list command line
    option, 730
gitlab-project-notification-settings-get
    command line option, 730
gitlab-project-notification-settings-update
    command line option, 731
gitlab-project-package-delete command
    line option, 732
gitlab-project-package-file-delete
    command line option, 733
gitlab-project-package-file-list
    command line option, 733
gitlab-project-package-get command line
    option, 732
gitlab-project-package-list command
    line option, 732
gitlab-project-pages-domain-create
    command line option, 734
gitlab-project-pages-domain-delete
    command line option, 734
gitlab-project-pages-domain-get command
    line option, 735
gitlab-project-pages-domain-list
    command line option, 735
gitlab-project-pages-domain-update
    command line option, 735
gitlab-project-pipeline-bridge-list
    command line option, 738
gitlab-project-pipeline-cancel command
    line option, 736
gitlab-project-pipeline-create command
    line option, 736
gitlab-project-pipeline-delete command
    line option, 736
gitlab-project-pipeline-get command
    line option, 737
gitlab-project-pipeline-job-list
    command line option, 739
gitlab-project-pipeline-list command
    line option, 737
gitlab-project-pipeline-retry command
    line option, 738
gitlab-project-pipeline-schedule-create
    command line option, 740
gitlab-project-pipeline-schedule-delete
    command line option, 740
gitlab-project-pipeline-schedule-get
    command line option, 740
gitlab-project-pipeline-schedule-list
    command line option, 741
gitlab-project-pipeline-schedule-pipeline-list
    command line option, 742
gitlab-project-pipeline-schedule-play
    command line option, 741
gitlab-project-pipeline-schedule-take-ownership
    command line option, 741
gitlab-project-pipeline-schedule-update
    command line option, 742
gitlab-project-pipeline-schedule-variable-create
    command line option, 743
gitlab-project-pipeline-schedule-variable-delete
    command line option, 744
gitlab-project-pipeline-schedule-variable-update
    command line option, 744
gitlab-project-pipeline-test-report-get
    command line option, 745
gitlab-project-pipeline-test-report-summary-get
    command line option, 745
gitlab-project-pipeline-variable-list
    command line option, 746
gitlab-project-protected-branch-create
    command line option, 746
gitlab-project-protected-branch-delete
    command line option, 747
gitlab-project-protected-branch-get
```

```
    command line option, 747
gitlab-project-protected-branch-list
    command line option, 748
gitlab-project-protected-environment-create
    command line option, 748
gitlab-project-protected-environment-delete
    command line option, 749
gitlab-project-protected-environment-get
    command line option, 749
gitlab-project-protected-environment-list
    command line option, 749
gitlab-project-protected-tag-create
    command line option, 750
gitlab-project-protected-tag-delete
    command line option, 750
gitlab-project-protected-tag-get
    command line option, 751
gitlab-project-protected-tag-list
    command line option, 751
gitlab-project-push-rules-create
    command line option, 752
gitlab-project-push-rules-delete
    command line option, 752
gitlab-project-push-rules-get command
    line option, 753
gitlab-project-push-rules-update
    command line option, 753
gitlab-project-registry-repository-delete
    command line option, 754
gitlab-project-registry-repository-list
    command line option, 754
gitlab-project-registry-tag-delete
    command line option, 755
gitlab-project-registry-tag-delete-in-bulk
    command line option, 755
gitlab-project-registry-tag-get command
    line option, 756
gitlab-project-registry-tag-list
    command line option, 756
gitlab-project-release-create command
    line option, 757
gitlab-project-release-delete command
    line option, 757
gitlab-project-release-get command line
    option, 757
gitlab-project-release-link-create
    command line option, 759
gitlab-project-release-link-delete
    command line option, 759
gitlab-project-release-link-get command
    line option, 760
gitlab-project-release-link-list
    command line option, 760
gitlab-project-release-link-update
    command line option, 760
gitlab-project-release-list command
    line option, 758
gitlab-project-release-update command
    line option, 758
gitlab-project-remote-mirror-create
    command line option, 761
gitlab-project-remote-mirror-list
    command line option, 761
gitlab-project-remote-mirror-update
    command line option, 762
gitlab-project-resource-group-get
    command line option, 762
gitlab-project-resource-group-list
    command line option, 763
gitlab-project-resource-group-upcoming-job-list
    command line option, 764
gitlab-project-resource-group-update
    command line option, 763
gitlab-project-runner-create command
    line option, 764
gitlab-project-runner-delete command
    line option, 765
gitlab-project-runner-list command line
    option, 765
gitlab-project-secure-file-create
    command line option, 766
gitlab-project-secure-file-delete
    command line option, 766
gitlab-project-secure-file-download
    command line option, 766
gitlab-project-secure-file-get command
    line option, 767
gitlab-project-secure-file-list command
    line option, 767
gitlab-project-service-available
    command line option, 768
gitlab-project-service-delete command
    line option, 768
gitlab-project-service-get command line
    option, 768
gitlab-project-service-list command
    line option, 768
gitlab-project-service-update command
    line option, 769
gitlab-project-snippet-award-emoji-create
    command line option, 772
gitlab-project-snippet-award-emoji-delete
    command line option, 772
gitlab-project-snippet-award-emoji-get
    command line option, 773
gitlab-project-snippet-award-emoji-list
    command line option, 773
gitlab-project-snippet-content command
```

line option, 769
gitlab-project-snippet-create command
 line option, 770
gitlab-project-snippet-delete command
 line option, 770
gitlab-project-snippet-discussion-create
 command line option, 774
gitlab-project-snippet-discussion-get
 command line option, 774
gitlab-project-snippet-discussion-list
 command line option, 775
gitlab-project-snippet-discussion-note-create
 command line option, 775
gitlab-project-snippet-discussion-note-delete
 command line option, 776
gitlab-project-snippet-discussion-note-get
 command line option, 776
gitlab-project-snippet-discussion-note-update
 command line option, 777
gitlab-project-snippet-get command line
 option, 770
gitlab-project-snippet-list command
 line option, 771
gitlab-project-snippet-note-award-emoji-create
 command line option, 779
gitlab-project-snippet-note-award-emoji-delete
 command line option, 780
gitlab-project-snippet-note-award-emoji-get
 command line option, 780
gitlab-project-snippet-note-award-emoji-list
 command line option, 781
gitlab-project-snippet-note-create
 command line option, 777
gitlab-project-snippet-note-delete
 command line option, 778
gitlab-project-snippet-note-get command line
 option, 778
gitlab-project-snippet-note-list
 command line option, 778
gitlab-project-snippet-note-update
 command line option, 779
gitlab-project-snippet-update command line
 option, 771
gitlab-project-snippet-user-agent-detail
 command line option, 772
gitlab-project-storage-get command line
 option, 781
gitlab-project-tag-create command line
 option, 782
gitlab-project-tag-delete command line
 option, 782
gitlab-project-tag-get command line
 option, 782
gitlab-project-tag-list command line
 option, 783
gitlab-project-trigger-create command
 line option, 783
gitlab-project-trigger-delete command
 line option, 784
gitlab-project-trigger-get command line
 option, 784
gitlab-project-trigger-list command
 line option, 784
gitlab-project-trigger-update command
 line option, 785
gitlab-project-update command line
 option, 607
gitlab-project-user-list command line
 option, 785
gitlab-project-variable-create command
 line option, 786
gitlab-project-variable-delete command
 line option, 786
gitlab-project-variable-get command
 line option, 787
gitlab-project-variable-list command
 line option, 787
gitlab-project-variable-update command
 line option, 787
gitlab-project-wiki-create command line
 option, 788
gitlab-project-wiki-delete command line
 option, 788
gitlab-project-wiki-get command line
 option, 789
gitlab-project-wiki-list command line
 option, 789
gitlab-project-wiki-update command line
 option, 789
gitlab-registry-repository-get command line
 option, 790
gitlab-runner-all-list command line
 option, 793
gitlab-runner-create command line
 option, 791
gitlab-runner-delete command line
 option, 791
gitlab-runner-get command line option,
 791
gitlab-runner-job-list command line
 option, 794
gitlab-runner-list command line option,
 792
gitlab-runner-update command line
 option, 792
gitlab-shared-project-list command line
 option, 795
gitlab-snippet-create command line

```

    option, 796
gitlab-snippet-delete command line
    option, 796
gitlab-snippet-get command line option,
    797
gitlab-snippet-list command line option,
    797
gitlab-snippet-update command line
    option, 797
gitlab-starred-project-list command
    line option, 798
gitlab-todo-delete command line option,
    799
gitlab-todo-list command line option, 800
gitlab-topic-create command line option,
    801
gitlab-topic-delete command line option,
    801
gitlab-topic-get command line option, 801
gitlab-topic-list command line option,
    802
gitlab-topic-update command line option,
    802
gitlab-user-activities-list command
    line option, 809
gitlab-user-create command line option,
    804
gitlab-user-custom-attribute-delete
    command line option, 810
gitlab-user-custom-attribute-get
    command line option, 810
gitlab-user-custom-attribute-list
    command line option, 810
gitlab-user-delete command line option,
    805
gitlab-user-email-create command line
    option, 811
gitlab-user-email-delete command line
    option, 811
gitlab-user-email-get command line
    option, 811
gitlab-user-email-list command line
    option, 812
gitlab-user-event-list command line
    option, 812
gitlab-user-get command line option, 806
gitlab-user-gpg-key-create command line
    option, 813
gitlab-user-gpg-key-delete command line
    option, 813
gitlab-user-gpg-key-get command line
    option, 814
gitlab-user-gpg-key-list command line
    option, 814
gitlab-user-impersonation-token-create
    command line option, 814
gitlab-user-impersonation-token-delete
    command line option, 815
gitlab-user-impersonation-token-get
    command line option, 815
gitlab-user-impersonation-token-list
    command line option, 815
gitlab-user-key-create command line
    option, 816
gitlab-user-key-delete command line
    option, 816
gitlab-user-key-get command line option,
    817
gitlab-user-key-list command line
    option, 817
gitlab-user-list command line option, 806
gitlab-user-membership-get command line
    option, 817
gitlab-user-membership-list command
    line option, 818
gitlab-user-personal-access-token-create
    command line option, 818
gitlab-user-project-create command line
    option, 819
gitlab-user-project-list command line
    option, 820
gitlab-user-status-get command line
    option, 821
gitlab-user-update command line option,
    808
gitlab-variable-create command line
    option, 822
gitlab-variable-delete command line
    option, 822
gitlab-variable-get command line option,
    822
gitlab-variable-list command line
    option, 823
gitlab-variable-update command line
    option, 823
--suggestion-commit-message
gitlab-project-update command line
    option, 609
--tag
    gitlab-project-deployment-create
        command line option, 641
--tag-list
    gitlab-group-runner-list command line
        option, 574
    gitlab-project-create command line
        option, 596
    gitlab-project-runner-list command line
        option, 765

```

```
gitlab-project-update command line
    option, 609
gitlab-runner-all-list command line
    option, 793
gitlab-runner-create command line
    option, 791
gitlab-runner-list command line option,
    792
gitlab-runner-update command line
    option, 792
--tag-name
    gitlab-project-release-create command
        line option, 757
    gitlab-project-release-delete command
        line option, 757
    gitlab-project-release-get command line
        option, 757
    gitlab-project-release-link-create
        command line option, 759
    gitlab-project-release-link-delete
        command line option, 759
    gitlab-project-release-link-get command
        line option, 760
    gitlab-project-release-link-list
        command line option, 760
    gitlab-project-release-link-update
        command line option, 761
    gitlab-project-release-update command
        line option, 758
    gitlab-project-tag-create command line
        option, 782
--tag-push-events
    gitlab-group-hook-create command line
        option, 549
    gitlab-group-hook-update command line
        option, 551
    gitlab-project-hook-create command line
        option, 654
    gitlab-project-hook-update command line
        option, 656
--target-access-levels
    gitlab-broadcast-message-create command
        line option, 493
    gitlab-broadcast-message-update command
        line option, 495
--target-branch
    gitlab-group-merge-request-list command
        line option, 565
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-merge-request-list
        command line option, 645
    gitlab-project-merge-request-create
        command line option, 699
gitlab-project-merge-request-list
    command line option, 701
gitlab-project-merge-request-update
    command line option, 706
--target-issue-iid
    gitlab-project-issue-link-create
        command line option, 674
--target-project-id
    gitlab-project-issue-link-create
        command line option, 674
    gitlab-project-merge-request-create
        command line option, 699
--target-topic-id
    gitlab-topic-merge command line option,
    802
--target-type
    gitlab-event-list command line option,
    505
    gitlab-project-event-list command line
        option, 648
    gitlab-user-event-list command line
        option, 812
--target-url
    gitlab-project-commit-status-create
        command line option, 637
--tasks-project-id
    gitlab-group-invitation-create command
        line option, 553
    gitlab-project-invitation-create
        command line option, 659
--tasks-to-be-done
    gitlab-group-invitation-create command
        line option, 553
    gitlab-group-member-create command line
        option, 561
    gitlab-project-invitation-create
        command line option, 659
    gitlab-project-member-create command
        line option, 693
--template-name
    gitlab-project-create command line
        option, 597
--template-project-id
    gitlab-project-create command line
        option, 597
--terminal-max-session-time
    gitlab-application-settings-update
        command line option, 491
--terms
    gitlab-application-settings-update
        command line option, 491
--theme-id
    gitlab-user-create command line option,
    805
```

```

gitlab-user-update command line option,
    809
--timeout
    gitlab command line option, 485
--title
    gitlab-application-appearance-update
        command line option, 487
    gitlab-current-user-key-create command
        line option, 501
    gitlab-group-epic-create command line
        option, 536
    gitlab-group-epic-update command line
        option, 538
    gitlab-group-milestone-create command
        line option, 566
    gitlab-group-milestone-update command
        line option, 568
    gitlab-group-wiki-create command line
        option, 579
    gitlab-group-wiki-update command line
        option, 580
    gitlab-project-issue-create command
        line option, 662
    gitlab-project-issue-update command
        line option, 668
    gitlab-project-key-create command line
        option, 688
    gitlab-project-key-update command line
        option, 690
    gitlab-project-merge-request-create
        command line option, 699
    gitlab-project-merge-request-update
        command line option, 706
    gitlab-project-milestone-create command
        line option, 727
    gitlab-project-milestone-update command
        line option, 729
    gitlab-project-snippet-create command
        line option, 770
    gitlab-project-snippet-update command
        line option, 771
    gitlab-project-wiki-create command line
        option, 788
    gitlab-project-wiki-update command line
        option, 789
    gitlab-snippet-create command line
        option, 796
    gitlab-snippet-update command line
        option, 797
    gitlab-topic-create command line option,
        801
    gitlab-user-key-create command line
        option, 816
--to
    gitlab-project-repository-compare
        command line option, 601
--to-namespace
    gitlab-project-transfer command line
        option, 603
    gitlab-project-transfer-project command
        line option, 604
--to-project-id
    gitlab-project-issue-move command line
        option, 664
--token
    gitlab-group-hook-create command line
        option, 550
    gitlab-group-hook-update command line
        option, 552
    gitlab-project-hook-create command line
        option, 654
    gitlab-project-hook-update command line
        option, 656
    gitlab-project-trigger-pipeline command
        line option, 604
    gitlab-runner-create command line
        option, 791
    gitlab-runner-verify command line
        option, 793
--top-level-only
    gitlab-group-list command line option,
        515
--topic
    gitlab-project-list command line option,
        599
--topics
    gitlab-project-create command line
        option, 596
    gitlab-project-update command line
        option, 609
--trailers
    gitlab-project-commit-list command line
        option, 631
--twitter
    gitlab-user-create command line option,
        804
    gitlab-user-update command line option,
        808
--two-factor
    gitlab-user-list command line option, 806
--two-factor-grace-period
    gitlab-group-create command line option,
        513
    gitlab-group-update command line option,
        517
--type
    gitlab-project-commit-refs command line
        option, 631

```

```
gitlab-runner-all-list command line
    option, 793
gitlab-runner-list command line option,
    792
gitlab-todo-list command line option, 800
gitlab-user-membership-list command
    line option, 818
--unprotect-access-level
    gitlab-project-protected-branch-create
        command line option, 747
--until
    gitlab-project-commit-list command line
        option, 631
--updated-after
    gitlab-group-issue-list command line
        option, 555
    gitlab-group-merge-request-list command
        line option, 564
    gitlab-issue-list command line option,
        583
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-list command
        line option, 642
    gitlab-project-deployment-merge-request-list
        command line option, 644
    gitlab-project-issue-list command line
        option, 664
    gitlab-project-merge-request-list
        command line option, 701
--updated-at
    gitlab-application-settings-update
        command line option, 490
    gitlab-project-issue-update command
        line option, 668
--updated-before
    gitlab-group-issue-list command line
        option, 555
    gitlab-group-merge-request-list command
        line option, 564
    gitlab-issue-list command line option,
        583
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-list command
        line option, 642
    gitlab-project-deployment-merge-request-list
        command line option, 644
    gitlab-project-issue-list command line
        option, 664
    gitlab-project-merge-request-list
        command line option, 701
--url
    gitlab-geo-node-update command line
        option, 510
gitlab-group-hook-create command line
    option, 549
gitlab-group-hook-update command line
    option, 551
gitlab-hook-create command line option,
    581
gitlab-project-hook-create command line
    option, 654
gitlab-project-hook-update command line
    option, 656
gitlab-project-release-link-create
    command line option, 759
gitlab-project-release-link-update
    command line option, 761
gitlab-project-remote-mirror-create
    command line option, 761
--use-custom-template
    gitlab-project-create command line
        option, 597
--user-agent
    gitlab command line option, 485
--user-id
    gitlab-group-billable-member-membership-list
        command line option, 525
    gitlab-group-member-create command line
        option, 561
    gitlab-personal-access-token-list
        command line option, 591
    gitlab-project-member-create command
        line option, 693
    gitlab-starred-project-list command
        line option, 798
    gitlab-user-custom-attribute-delete
        command line option, 810
    gitlab-user-custom-attribute-get
        command line option, 810
    gitlab-user-custom-attribute-list
        command line option, 810
    gitlab-user-email-create command line
        option, 811
    gitlab-user-email-delete command line
        option, 811
    gitlab-user-email-get command line
        option, 811
    gitlab-user-email-list command line
        option, 812
    gitlab-user-event-list command line
        option, 812
    gitlab-user-gpg-key-create command line
        option, 813
    gitlab-user-gpg-key-delete command line
        option, 813
    gitlab-user-gpg-key-get command line
```

```

        option, 814
gitlab-user-gpg-key-list command line
    option, 814
gitlab-user-impersonation-token-create
    command line option, 815
gitlab-user-impersonation-token-delete
    command line option, 815
gitlab-user-impersonation-token-get
    command line option, 815
gitlab-user-impersonation-token-list
    command line option, 815
gitlab-user-key-create command line
    option, 816
gitlab-user-key-delete command line
    option, 816
gitlab-user-key-get command line option,
    817
gitlab-user-key-list command line
    option, 817
gitlab-user-membership-get command line
    option, 817
gitlab-user-membership-list command
    line option, 818
gitlab-user-personal-access-token-create
    command line option, 818
gitlab-user-project-create command line
    option, 819
gitlab-user-project-list command line
    option, 820
gitlab-user-status-get command line
    option, 821
--user-ids
    gitlab-project-approval-rule-create
        command line option, 615
    gitlab-project-merge-request-approval-rule-creation
        command line option, 708
    gitlab-project-merge-request-approval-rule-update
        command line option, 710
--user-oauth-applications
    gitlab-application-settings-update
        command line option, 491
--user-show-add-ssh-key-message
    gitlab-application-settings-update
        command line option, 491
--username
    gitlab-group-deploy-token-create
        command line option, 533
    gitlab-project-deploy-token-create
        command line option, 639
    gitlab-project-pipeline-list command
        line option, 737
    gitlab-user-create command line option,
        804
    gitlab-user-list command line option, 806
--value
    gitlab-group-variable-create command
        line option, 577
    gitlab-group-variable-update command
        line option, 578
    gitlab-project-pipeline-schedule-variable-create
        command line option, 743
    gitlab-project-pipeline-schedule-variable-update
        command line option, 744
    gitlab-project-variable-create command
        line option, 786
    gitlab-project-variable-update command
        line option, 788
    gitlab-variable-create command line
        option, 822
    gitlab-variable-update command line
        option, 823
--variable-type
    gitlab-group-variable-create command
        line option, 577
    gitlab-group-variable-update command
        line option, 579
    gitlab-project-variable-create command
        line option, 786
    gitlab-project-variable-update command
        line option, 788
    gitlab-variable-create command line
        option, 822
    gitlab-variable-update command line
        option, 823
--verbose
    gitlab command line option, 484
    gitlab command line option, 484
--verbose
    gitlab-group-merge-request-list command
        line option, 564
    gitlab-merge-request-list command line
        option, 586
    gitlab-project-deployment-merge-request-list
        command line option, 644
    gitlab-project-merge-request-list
        command line option, 701
--visibility
    gitlab-group-create command line option,
        513
    gitlab-group-project-list command line
        option, 571
    gitlab-group-update command line option,
        517
    gitlab-project-create command line
        option, 597

```

```
gitlab-project-fork-list command line
    option, 653
gitlab-project-list command line option,
    599
gitlab-project-snippet-create command
    line option, 770
gitlab-project-snippet-update command
    line option, 771
gitlab-project-update command line
    option, 609
gitlab-shared-project-list command line
    option, 795
gitlab-snippet-create command line
    option, 796
gitlab-snippet-update command line
    option, 798
gitlab-starred-project-list command
    line option, 799
gitlab-user-project-create command line
    option, 819
gitlab-user-project-list command line
    option, 820
--wall-enabled
    gitlab-user-project-create command line
        option, 819
--website-url
    gitlab-user-create command line option,
        805
    gitlab-user-update command line option,
        808
--wiki
    gitlab-project-snapshot command line
        option, 603
--wiki-access-level
    gitlab-project-create command line
        option, 597
    gitlab-project-update command line
        option, 609
--wiki-checksum-failed
    gitlab-project-list command line option,
        599
    gitlab-user-project-list command line
        option, 821
--wiki-enabled
    gitlab-project-create command line
        option, 597
    gitlab-project-update command line
        option, 609
    gitlab-user-project-create command line
        option, 819
--wiki-events
    gitlab-project-hook-update command line
        option, 656
--wiki-page-events
    gitlab-group-hook-create command line
        option, 549
    gitlab-group-hook-update command line
        option, 551
    gitlab-project-hook-create command line
        option, 654
--wip
    gitlab-group-merge-request-list command
        line option, 565
    gitlab-merge-request-list command line
        option, 587
    gitlab-project-deployment-merge-request-list
        command line option, 645
    gitlab-project-merge-request-list
        command line option, 701
--with-content
    gitlab-group-wiki-list command line
        option, 580
    gitlab-project-wiki-list command line
        option, 789
--with-custom-attributes
    gitlab-group-descendant-group-list
        command line option, 535
    gitlab-group-list command line option,
        515
    gitlab-group-project-list command line
        option, 571
    gitlab-group-subgroup-list command line
        option, 576
    gitlab-project-fork-list command line
        option, 653
    gitlab-project-list command line option,
        599
    gitlab-shared-project-list command line
        option, 795
    gitlab-starred-project-list command
        line option, 799
    gitlab-user-project-list command line
        option, 821
--with-issues-enabled
    gitlab-group-project-list command line
        option, 571
    gitlab-project-fork-list command line
        option, 653
    gitlab-project-list command line option,
        599
    gitlab-shared-project-list command line
        option, 795
    gitlab-starred-project-list command
        line option, 799
    gitlab-user-project-list command line
        option, 820
--with-labels-details
    gitlab-merge-request-list command line
```

```

        option, 586
gitlab-project-deployment-merge-request-list
    command line option, 644
--with-merge-requests-enabled
    gitlab-group-project-list command line
        option, 571
    gitlab-project-fork-list command line
        option, 653
    gitlab-project-list command line option,
        600
    gitlab-shared-project-list command line
        option, 795
    gitlab-starred-project-list command
        line option, 799
    gitlab-user-project-list command line
        option, 820
--with-merge-status-recheck
    gitlab-merge-request-list command line
        option, 586
gitlab-project-deployment-merge-request-list
    command line option, 644
--with-programming-language
    gitlab-project-list command line option,
        600
    gitlab-user-project-list command line
        option, 821
--with-security-reports
    gitlab-group-project-list command line
        option, 571
--with-shared
    gitlab-group-project-list command line
        option, 571
--with-stats
    gitlab-project-commit-list command line
        option, 631
--yaml-errors
    gitlab-project-pipeline-list command
        line option, 737
-c
    gitlab command line option, 484
-d
    gitlab command line option, 484
-f
    gitlab command line option, 485
-g
    gitlab command line option, 484
-h
    gitlab command line option, 484
    gitlab-application command line option,
        485
    gitlab-application-appearance command
        line option, 486
    gitlab-application-appearance-get
        command line option, 487
gitlab-application-appearance-update
    command line option, 487
gitlab-application-create command line
    option, 485
gitlab-application-delete command line
    option, 486
gitlab-application-list command line
    option, 486
gitlab-application-settings command
    line option, 488
gitlab-application-settings-get command
    line option, 488
gitlab-application-settings-update
    command line option, 489
gitlab-application-statistics command
    line option, 492
gitlab-application-statistics-get
    command line option, 492
gitlab-audit-event command line option,
    492
gitlab-audit-event-get command line
    option, 492
gitlab-audit-event-list command line
    option, 492
gitlab-broadcast-message command line
    option, 493
gitlab-broadcast-message-create command
    line option, 493
gitlab-broadcast-message-delete command
    line option, 494
gitlab-broadcast-message-get command
    line option, 494
gitlab-broadcast-message-list command
    line option, 494
gitlab-broadcast-message-update command
    line option, 494
gitlab-bulk-import command line option,
    495
gitlab-bulk-import-all-entity command
    line option, 496
gitlab-bulk-import-all-entity-list
    command line option, 496
gitlab-bulk-import-create command line
    option, 495
gitlab-bulk-import-entity command line
    option, 497
gitlab-bulk-import-entity-get command
    line option, 497
gitlab-bulk-import-entity-list command
    line option, 497
gitlab-bulk-import-get command line
    option, 495
gitlab-bulk-import-list command line
    option, 496

```

gitlab-ci-lint command line option, 498
gitlab-ci-lint-create command line option, 498
gitlab-ci-lint-validate command line option, 498
gitlab-current-user command line option, 498
gitlab-current-user-email command line option, 499
gitlab-current-user-email-create command line option, 499
gitlab-current-user-email-delete command line option, 499
gitlab-current-user-email-get command line option, 499
gitlab-current-user-email-list command line option, 500
gitlab-current-user-get command line option, 499
gitlab-current-user-gpg-key command line option, 500
gitlab-current-user-gpg-key-create command line option, 500
gitlab-current-user-gpg-key-delete command line option, 500
gitlab-current-user-gpg-key-get command line option, 501
gitlab-current-user-gpg-key-list command line option, 501
gitlab-current-user-key command line option, 501
gitlab-current-user-key-create command line option, 501
gitlab-current-user-key-delete command line option, 502
gitlab-current-user-key-get command line option, 502
gitlab-current-user-key-list command line option, 502
gitlab-current-user-status command line option, 502
gitlab-current-user-status-get command line option, 503
gitlab-current-user-status-update command line option, 503
gitlab-deploy-key command line option, 503
gitlab-deploy-key-list command line option, 503
gitlab-deploy-token command line option, 504
gitlab-deploy-token-list command line option, 504
gitlab-dockerfile command line option, 504
gitlab-dockerfile-get command line option, 504
gitlab-dockerfile-list command line option, 505
gitlab-event command line option, 505
gitlab-event-list command line option, 505
gitlab-feature command line option, 506
gitlab-feature-delete command line option, 506
gitlab-feature-list command line option, 506
gitlab-generic-package command line option, 507
gitlab-generic-package-download command line option, 507
gitlab-generic-package-upload command line option, 507
gitlab-geo-node command line option, 508
gitlab-geo-node-current-failures command line option, 508
gitlab-geo-node-delete command line option, 508
gitlab-geo-node-get command line option, 508
gitlab-geo-node-list command line option, 509
gitlab-geo-node-repair command line option, 509
gitlab-geo-node-status command line option, 509
gitlab-geo-node-update command line option, 509
gitlab-gitignore command line option, 510
gitlab-gitignore-get command line option, 510
gitlab-gitignore-list command line option, 510
gitlab-gitlabciyml command line option, 511
gitlab-gitlabciyml-get command line option, 511
gitlab-gitlabciyml-list command line option, 511
gitlab-group command line option, 512
gitlab-group-access-request command line option, 518
gitlab-group-access-request-approve command line option, 518
gitlab-group-access-request-create command line option, 519
gitlab-group-access-request-delete command line option, 519

gitlab-group-access-request-list
 command line option, 519
gitlab-group-access-token command line
 option, 520
gitlab-group-access-token-create
 command line option, 520
gitlab-group-access-token-delete
 command line option, 520
gitlab-group-access-token-list command
 line option, 520
gitlab-group-add-ldap-group-link
 command line option, 512
gitlab-group-audit-event command line
 option, 521
gitlab-group-audit-event-get command
 line option, 521
gitlab-group-audit-event-list command
 line option, 521
gitlab-group-badge command line option,
 522
gitlab-group-badge-create command line
 option, 522
gitlab-group-badge-delete command line
 option, 522
gitlab-group-badge-get command line
 option, 523
gitlab-group-badge-list command line
 option, 523
gitlab-group-badge-render command line
 option, 523
gitlab-group-badge-update command line
 option, 524
gitlab-group-billable-member command
 line option, 524
gitlab-group-billable-member-delete
 command line option, 524
gitlab-group-billable-member-list
 command line option, 524
gitlab-group-billable-member-membership
 command line option, 525
gitlab-group-billable-member-membership-list
 command line option, 525
gitlab-group-board command line option,
 526
gitlab-group-board-create command line
 option, 526
gitlab-group-board-delete command line
 option, 526
gitlab-group-board-get command line
 option, 526
gitlab-group-board-list command line
 option, 527
gitlab-group-board-list-create command
 line option, 528
gitlab-group-board-list-delete command
 line option, 528
gitlab-group-board-list-get command
 line option, 528
gitlab-group-board-list-list command
 line option, 529
gitlab-group-board-list-update command
 line option, 529
gitlab-group-board-update command line
 option, 527
gitlab-group-cluster command line
 option, 529
gitlab-group-cluster-create command
 line option, 530
gitlab-group-cluster-delete command
 line option, 530
gitlab-group-cluster-get command line
 option, 530
gitlab-group-cluster-list command line
 option, 531
gitlab-group-cluster-update command
 line option, 531
gitlab-group-create command line option,
 512
gitlab-group-custom-attribute command
 line option, 532
gitlab-group-custom-attribute-delete
 command line option, 532
gitlab-group-custom-attribute-get
 command line option, 532
gitlab-group-custom-attribute-list
 command line option, 532
gitlab-group-delete command line option,
 513
gitlab-group-delete-ldap-group-link
 command line option, 514
gitlab-group-deploy-token command line
 option, 533
gitlab-group-deploy-token-create
 command line option, 533
gitlab-group-deploy-token-delete
 command line option, 533
gitlab-group-deploy-token-get command
 line option, 534
gitlab-group-deploy-token-list command
 line option, 534
gitlab-group-descendant-group command
 line option, 534
gitlab-group-descendant-group-list
 command line option, 535
gitlab-group-epic command line option,
 536
gitlab-group-epic-award-emoji command
 line option, 538

gitlab-group-epic-award-emoji-create
 command line option, 538
gitlab-group-epic-award-emoji-delete
 command line option, 539
gitlab-group-epic-award-emoji-get
 command line option, 539
gitlab-group-epic-award-emoji-list
 command line option, 539
gitlab-group-epic-create command line
 option, 536
gitlab-group-epic-delete command line
 option, 536
gitlab-group-epic-discussion-note
 command line option, 540
gitlab-group-epic-discussion-note-create
 command line option, 540
gitlab-group-epic-discussion-note-delete
 command line option, 540
gitlab-group-epic-discussion-note-get
 command line option, 541
gitlab-group-epic-discussion-note-update
 command line option, 541
gitlab-group-epic-get command line
 option, 537
gitlab-group-epic-issue command line
 option, 542
gitlab-group-epic-issue-create command
 line option, 542
gitlab-group-epic-issue-delete command
 line option, 542
gitlab-group-epic-issue-list command
 line option, 542
gitlab-group-epic-issue-update command
 line option, 543
gitlab-group-epic-list command line
 option, 537
gitlab-group-epic-note command line
 option, 543
gitlab-group-epic-note-award-emoji
 command line option, 545
gitlab-group-epic-note-award-emoji-create
 command line option, 545
gitlab-group-epic-note-award-emoji-delete
 command line option, 546
gitlab-group-epic-note-award-emoji-get
 command line option, 546
gitlab-group-epic-note-award-emoji-list
 command line option, 546
gitlab-group-epic-note-create command
 line option, 543
gitlab-group-epic-note-delete command
 line option, 544
gitlab-group-epic-note-get command line
 option, 544

gitlab-group-epic-note-list command
 line option, 544
gitlab-group-epic-note-update command
 line option, 545
gitlab-group-epic-resource-label-event
 command line option, 547
gitlab-group-epic-resource-label-event-get
 command line option, 547
gitlab-group-epic-resource-label-event-list
 command line option, 547
gitlab-group-epic-update command line
 option, 538
gitlab-group-export command line option,
 548
gitlab-group-export-create command line
 option, 548
gitlab-group-export-download command
 line option, 548
gitlab-group-export-get command line
 option, 548
gitlab-group-get command line option, 514
gitlab-group-hook command line option,
 549
gitlab-group-hook-create command line
 option, 549
gitlab-group-hook-delete command line
 option, 550
gitlab-group-hook-get command line
 option, 550
gitlab-group-hook-list command line
 option, 550
gitlab-group-hook-update command line
 option, 551
gitlab-group-import command line option,
 552
gitlab-group-import-get command line
 option, 552
gitlab-group-invitation command line
 option, 552
gitlab-group-invitation-create command
 line option, 552
gitlab-group-invitation-delete command
 line option, 553
gitlab-group-invitation-get command
 line option, 553
gitlab-group-invitation-list command
 line option, 553
gitlab-group-invitation-update command
 line option, 554
gitlab-group-issue command line option,
 554
gitlab-group-issue-list command line
 option, 554
gitlab-group-issues-statistics command

```

    line option, 555
gitlab-group-issues-statistics-get
    command line option, 556
gitlab-group-iteration command line
    option, 556
gitlab-group-iteration-list command
    line option, 556
gitlab-group-label command line option,
    557
gitlab-group-label-create command line
    option, 557
gitlab-group-label-delete command line
    option, 557
gitlab-group-label-get command line
    option, 558
gitlab-group-label-list command line
    option, 558
gitlab-group-label-subscribe command
    line option, 558
gitlab-group-label-unsubscribe command
    line option, 559
gitlab-group-label-update command line
    option, 559
gitlab-group-ldap-group-link command
    line option, 559
gitlab-group-ldap-group-link-create
    command line option, 560
gitlab-group-ldap-group-link-delete
    command line option, 560
gitlab-group-ldap-group-link-list
    command line option, 560
gitlab-group-ldap-sync command line
    option, 514
gitlab-group-list command line option,
    514
gitlab-group-member command line option,
    561
gitlab-group-member-all command line
    option, 563
gitlab-group-member-all-get command
    line option, 563
gitlab-group-member-all-list command
    line option, 563
gitlab-group-member-create command line
    option, 561
gitlab-group-member-delete command line
    option, 561
gitlab-group-member-get command line
    option, 561
gitlab-group-member-list command line
    option, 562
gitlab-group-member-update command line
    option, 562
gitlab-group-merge-request command line
    option, 564
gitlab-group-merge-request-list command
    line option, 564
gitlab-group-milestone command line
    option, 565
gitlab-group-milestone-create command
    line option, 565
gitlab-group-milestone-delete command
    line option, 566
gitlab-group-milestone-get command line
    option, 566
gitlab-group-milestone-issues command
    line option, 566
gitlab-group-milestone-list command
    line option, 567
gitlab-group-milestone-merge-requests
    command line option, 567
gitlab-group-milestone-update command
    line option, 567
gitlab-group-notification-settings
    command line option, 568
gitlab-group-notification-settings-get
    command line option, 568
gitlab-group-notification-settings-update
    command line option, 569
gitlab-group-package command line
    option, 569
gitlab-group-package-list command line
    option, 569
gitlab-group-project command line
    option, 570
gitlab-group-project-list command line
    option, 570
gitlab-group-push-rules command line
    option, 571
gitlab-group-push-rules-create command
    line option, 572
gitlab-group-push-rules-delete command
    line option, 572
gitlab-group-push-rules-get command
    line option, 573
gitlab-group-push-rules-update command
    line option, 573
gitlab-group-restore command line
    option, 515
gitlab-group-runner command line option,
    574
gitlab-group-runner-list command line
    option, 574
gitlab-group-saml-group-link command
    line option, 574
gitlab-group-saml-group-link-create
    command line option, 574
gitlab-group-saml-group-link-delete

```

```
    command line option, 575
gitlab-group-saml-group-link-get
    command line option, 575
gitlab-group-saml-group-link-list
    command line option, 575
gitlab-group-search command line option,
    515
gitlab-group-share command line option,
    516
gitlab-group-subgroup command line
    option, 576
gitlab-group-subgroup-list command line
    option, 576
gitlab-group-transfer command line
    option, 516
gitlab-group-transfer-project command
    line option, 516
gitlab-group-unshare command line
    option, 516
gitlab-group-update command line option,
    517
gitlab-group-variable command line
    option, 577
gitlab-group-variable-create command
    line option, 577
gitlab-group-variable-delete command
    line option, 577
gitlab-group-variable-get command line
    option, 578
gitlab-group-variable-list command line
    option, 578
gitlab-group-variable-update command
    line option, 578
gitlab-group-wiki command line option,
    579
gitlab-group-wiki-create command line
    option, 579
gitlab-group-wiki-delete command line
    option, 579
gitlab-group-wiki-get command line
    option, 580
gitlab-group-wiki-list command line
    option, 580
gitlab-group-wiki-update command line
    option, 580
gitlab-hook command line option, 581
gitlab-hook-create command line option,
    581
gitlab-hook-delete command line option,
    581
gitlab-hook-get command line option, 581
gitlab-hook-list command line option, 582
gitlab-issue command line option, 582
gitlab-issue-get command line option, 582
gitlab-issue-list command line option,
    582
gitlab-issues-statistics command line
    option, 583
gitlab-issues-statistics-get command
    line option, 584
gitlab-key command line option, 584
gitlab-key-get command line option, 584
gitlab-ldap-group command line option,
    584
gitlab-ldap-group-list command line
    option, 584
gitlab-license command line option, 585
gitlab-license-get command line option,
    585
gitlab-license-list command line option,
    585
gitlab-merge-request command line
    option, 586
gitlab-merge-request-list command line
    option, 586
gitlab-namespace command line option, 588
gitlab-namespace-exists command line
    option, 588
gitlab-namespace-get command line
    option, 588
gitlab-namespace-list command line
    option, 588
gitlab-notification-settings command
    line option, 589
gitlab-notification-settings-get
    command line option, 589
gitlab-notification-settings-update
    command line option, 589
gitlab-pages-domain command line option,
    590
gitlab-pages-domain-list command line
    option, 590
gitlab-personal-access-token command
    line option, 590
gitlab-personal-access-token-delete
    command line option, 590
gitlab-personal-access-token-get
    command line option, 591
gitlab-personal-access-token-list
    command line option, 591
gitlab-project command line option, 592
gitlab-project-access-request command
    line option, 610
gitlab-project-access-request-approve
    command line option, 610
gitlab-project-access-request-create
    command line option, 611
gitlab-project-access-request-delete
```

```

    command line option, 611
gitlab-project-access-request-list
    command line option, 611
gitlab-project-access-token command
    line option, 612
gitlab-project-access-token-create
    command line option, 612
gitlab-project-access-token-delete
    command line option, 612
gitlab-project-access-token-list
    command line option, 612
gitlab-project-additional-statistics
    command line option, 613
gitlab-project-additional-statistics-get
    command line option, 613
gitlab-project-approval command line
    option, 613
gitlab-project-approval-get command
    line option, 613
gitlab-project-approval-rule command
    line option, 614
gitlab-project-approval-rule-create
    command line option, 614
gitlab-project-approval-rule-delete
    command line option, 615
gitlab-project-approval-rule-list
    command line option, 615
gitlab-project-approval-rule-update
    command line option, 616
gitlab-project-approval-update command
    line option, 614
gitlab-project-archive command line
    option, 592
gitlab-project-artifact command line
    option, 592, 616
gitlab-project-artifact-delete command
    line option, 616
gitlab-project-artifact-download
    command line option, 616
gitlab-project-artifact-raw command
    line option, 617
gitlab-project-artifacts command line
    option, 593
gitlab-project-audit-event command line
    option, 617
gitlab-project-audit-event-get command
    line option, 617
gitlab-project-audit-event-list command
    line option, 617
gitlab-project-badge command line
    option, 618
gitlab-project-badge-create command
    line option, 618
gitlab-project-badge-delete command
    line option, 618
gitlab-project-badge-get command line
    option, 619
gitlab-project-badge-list command line
    option, 619
gitlab-project-badge-render command
    line option, 619
gitlab-project-badge-update command
    line option, 620
gitlab-project-board command line
    option, 620
gitlab-project-board-create command
    line option, 620
gitlab-project-board-delete command
    line option, 620
gitlab-project-board-get command line
    option, 621
gitlab-project-board-list command line
    option, 621, 622
gitlab-project-board-list-create
    command line option, 622
gitlab-project-board-list-delete
    command line option, 622
gitlab-project-board-list-get command
    line option, 622
gitlab-project-board-list-list command
    line option, 623
gitlab-project-board-list-update
    command line option, 623
gitlab-project-board-update command
    line option, 621
gitlab-project-branch command line
    option, 623
gitlab-project-branch-create command
    line option, 624
gitlab-project-branch-delete command
    line option, 624
gitlab-project-branch-get command line
    option, 624
gitlab-project-branch-list command line
    option, 625
gitlab-project-ci-lint command line
    option, 625
gitlab-project-ci-lint-create command
    line option, 625
gitlab-project-ci-lint-get command line
    option, 626
gitlab-project-ci-lint-validate command
    line option, 626
gitlab-project-cluster command line
    option, 626
gitlab-project-cluster-create command
    line option, 626
gitlab-project-cluster-delete command
    line option, 626

```

```
    line option, 627
gitlab-project-cluster-get command line
    option, 627
gitlab-project-cluster-list command
    line option, 628
gitlab-project-cluster-update command
    line option, 628
gitlab-project-commit command line
    option, 629
gitlab-project-commit-cherry-pick
    command line option, 629
gitlab-project-commit-comment command
    line option, 632
gitlab-project-commit-comment-create
    command line option, 632
gitlab-project-commit-comment-list
    command line option, 633
gitlab-project-commit-create command
    line option, 629
gitlab-project-commit-diff command line
    option, 630
gitlab-project-commit-discussion
    command line option, 633
gitlab-project-commit-discussion-create
    command line option, 633
gitlab-project-commit-discussion-get
    command line option, 634
gitlab-project-commit-discussion-list
    command line option, 634
gitlab-project-commit-discussion-note
    command line option, 635
gitlab-project-commit-discussion-note-create
    command line option, 635
gitlab-project-commit-discussion-note-delete
    command line option, 635
gitlab-project-commit-discussion-note-get
    command line option, 636
gitlab-project-commit-discussion-note-update
    command line option, 636
gitlab-project-commit-get command line
    option, 630
gitlab-project-commit-list command line
    option, 630
gitlab-project-commit-merge-requests
    command line option, 631
gitlab-project-commit-refs command line
    option, 631
gitlab-project-commit-revert command
    line option, 632
gitlab-project-commit-signature command
    line option, 632
gitlab-project-commit-status command
    line option, 637
gitlab-project-commit-status-create
    command line option, 637
gitlab-project-commit-status-list
    command line option, 637
gitlab-project-create command line
    option, 594
gitlab-project-create-fork-relation
    command line option, 597
gitlab-project-custom-attribute command
    line option, 638
gitlab-project-custom-attribute-delete
    command line option, 638
gitlab-project-custom-attribute-get
    command line option, 638
gitlab-project-custom-attribute-list
    command line option, 639
gitlab-project-delete command line
    option, 597
gitlab-project-delete-fork-relation
    command line option, 597
gitlab-project-delete-merged-branches
    command line option, 598
gitlab-project-deploy-token command
    line option, 639
gitlab-project-deploy-token-create
    command line option, 639
gitlab-project-deploy-token-delete
    command line option, 640
gitlab-project-deploy-token-get command
    line option, 640
gitlab-project-deploy-token-list
    command line option, 640
gitlab-project-deployment command line
    option, 641
gitlab-project-deployment-approval
    command line option, 641
gitlab-project-deployment-create
    command line option, 641
gitlab-project-deployment-get command
    line option, 642
gitlab-project-deployment-list command
    line option, 642
gitlab-project-deployment-merge-request
    command line option, 643
gitlab-project-deployment-merge-request-list
    command line option, 644
gitlab-project-deployment-update
    command line option, 643
gitlab-project-environment command line
    option, 645
gitlab-project-environment-create
    command line option, 645
gitlab-project-environment-delete
    command line option, 646
gitlab-project-environment-get command
```

line option, 646
gitlab-project-environment-list command line option, 646
gitlab-project-environment-stop command line option, 647
gitlab-project-environment-update command line option, 647
gitlab-project-event command line option, 648
gitlab-project-event-list command line option, 648
gitlab-project-export command line option, 648
gitlab-project-export-create command line option, 649
gitlab-project-export-download command line option, 649
gitlab-project-export-get command line option, 649
gitlab-project-file command line option, 649
gitlab-project-file-blame command line option, 650
gitlab-project-file-create command line option, 650
gitlab-project-file-delete command line option, 651
gitlab-project-file-get command line option, 651
gitlab-project-file-raw command line option, 651
gitlab-project-file-update command line option, 652
gitlab-project-fork command line option, 652
gitlab-project-fork-create command line option, 652
gitlab-project-fork-list command line option, 653
gitlab-project-get command line option, 598
gitlab-project-hook command line option, 654
gitlab-project-hook-create command line option, 654
gitlab-project-hook-delete command line option, 655
gitlab-project-hook-get command line option, 655
gitlab-project-hook-list command line option, 655
gitlab-project-hook-update command line option, 656
gitlab-project-housekeeping command line option, 598
gitlab-project-import command line option, 657
gitlab-project-import-get command line option, 657
gitlab-project-integration command line option, 657
gitlab-project-integration-available command line option, 657
gitlab-project-integration-delete command line option, 657
gitlab-project-integration-get command line option, 658
gitlab-project-integration-list command line option, 658
gitlab-project-integration-update command line option, 658
gitlab-project-invitation command line option, 659
gitlab-project-invitation-create command line option, 659
gitlab-project-invitation-delete command line option, 659
gitlab-project-invitation-get command line option, 660
gitlab-project-invitation-list command line option, 660
gitlab-project-invitation-update command line option, 660
gitlab-project-issue command line option, 661
gitlab-project-issue-add-spent-time command line option, 661
gitlab-project-issue-award-emoji command line option, 669
gitlab-project-issue-award-emoji-create command line option, 669
gitlab-project-issue-award-emoji-delete command line option, 669
gitlab-project-issue-award-emoji-get command line option, 670
gitlab-project-issue-award-emoji-list command line option, 670
gitlab-project-issue-closed-by command line option, 662
gitlab-project-issue-create command line option, 662
gitlab-project-issue-delete command line option, 663
gitlab-project-issue-discussion command line option, 670
gitlab-project-issue-discussion-create command line option, 671
gitlab-project-issue-discussion-get

```
    command line option, 671
gitlab-project-issue-discussion-list
    command line option, 671
gitlab-project-issue-discussion-note
    command line option, 672
gitlab-project-issue-discussion-note-create
    command line option, 672
gitlab-project-issue-discussion-note-delete
    command line option, 673
gitlab-project-issue-discussion-note-get
    command line option, 673
gitlab-project-issue-discussion-note-update
    command line option, 673
gitlab-project-issue-get command line
    option, 663
gitlab-project-issue-link command line
    option, 674
gitlab-project-issue-link-create
    command line option, 674
gitlab-project-issue-link-delete
    command line option, 674
gitlab-project-issue-link-list command
    line option, 675
gitlab-project-issue-list command line
    option, 663
gitlab-project-issue-move command line
    option, 664
gitlab-project-issue-note command line
    option, 675
gitlab-project-issue-note-award-emoji
    command line option, 677
gitlab-project-issue-note-award-emoji-create
    command line option, 677
gitlab-project-issue-note-award-emoji-delete
    command line option, 678
gitlab-project-issue-note-award-emoji-get
    command line option, 678
gitlab-project-issue-note-award-emoji-list
    command line option, 678
gitlab-project-issue-note-create
    command line option, 675
gitlab-project-issue-note-delete
    command line option, 676
gitlab-project-issue-note-get command
    line option, 676
gitlab-project-issue-note-list command
    line option, 676
gitlab-project-issue-note-update
    command line option, 677
gitlab-project-issue-participants
    command line option, 665
gitlab-project-issue-related-merge-requests
    command line option, 665
gitlab-project-issue-reorder command
    line option, 665
gitlab-project-issue-reset-spent-time
    command line option, 666
gitlab-project-issue-reset-time-estimate
    command line option, 666
gitlab-project-issue-resource-iteration-event
    command line option, 679
gitlab-project-issue-resource-iteration-event-get
    command line option, 679
gitlab-project-issue-resource-iteration-event-list
    command line option, 679
gitlab-project-issue-resource-label-event
    command line option, 680
gitlab-project-issue-resource-label-event-get
    command line option, 680
gitlab-project-issue-resource-label-event-list
    command line option, 680
gitlab-project-issue-resource-milestone-event
    command line option, 681
gitlab-project-issue-resource-milestone-event-get
    command line option, 681
gitlab-project-issue-resource-milestone-event-list
    command line option, 682
gitlab-project-issue-resource-state-event
    command line option, 682
gitlab-project-issue-resource-state-event-get
    command line option, 682
gitlab-project-issue-resource-state-event-list
    command line option, 683
gitlab-project-issue-resource-weight-event
    command line option, 683
gitlab-project-issue-resource-weight-event-get
    command line option, 683
gitlab-project-issue-resource-weight-event-list
    command line option, 684
gitlab-project-issue-subscribe command
    line option, 666
gitlab-project-issue-time-estimate
    command line option, 666
gitlab-project-issue-time-stats command
    line option, 667
gitlab-project-issue-todo command line
    option, 667
gitlab-project-issue-unsubscribe
    command line option, 667
gitlab-project-issue-update command
    line option, 668
gitlab-project-issue-user-agent-detail
    command line option, 668
gitlab-project-issues-statistics
    command line option, 684
gitlab-project-issues-statistics-get
    command line option, 684
gitlab-project-job command line option,
```

685
gitlab-project-job-artifact command
line option, 685
gitlab-project-job-artifacts command
line option, 685
gitlab-project-job-cancel command line
option, 686
gitlab-project-job-delete-artifacts
command line option, 686
gitlab-project-job-erase command line
option, 686
gitlab-project-job-get command line
option, 686
gitlab-project-job-keep-artifacts
command line option, 687
gitlab-project-job-list command line
option, 687
gitlab-project-job-play command line
option, 687
gitlab-project-job-retry command line
option, 688
gitlab-project-job-trace command line
option, 688
gitlab-project-key command line option,
688
gitlab-project-key-create command line
option, 688
gitlab-project-key-delete command line
option, 689
gitlab-project-key-enable command line
option, 689
gitlab-project-key-get command line
option, 689
gitlab-project-key-list command line
option, 690
gitlab-project-key-update command line
option, 690
gitlab-project-label command line
option, 690
gitlab-project-label-create command
line option, 691
gitlab-project-label-delete command
line option, 691
gitlab-project-label-get command line
option, 691
gitlab-project-label-list command line
option, 692
gitlab-project-label-subscribe command
line option, 692
gitlab-project-label-unsubscribe
command line option, 692
gitlab-project-label-update command
line option, 693
gitlab-project-languages command line
option, 598
gitlab-project-list command line option,
599
gitlab-project-member command line
option, 693
gitlab-project-member-all command line
option, 695
gitlab-project-member-all-get command
line option, 695
gitlab-project-member-all-list command
line option, 695
gitlab-project-member-create command
line option, 693
gitlab-project-member-delete command
line option, 694
gitlab-project-member-get command line
option, 694
gitlab-project-member-list command line
option, 694
gitlab-project-member-update command
line option, 695
gitlab-project-merge-request command
line option, 696
gitlab-project-merge-request-add-spent-time
command line option, 697
gitlab-project-merge-request-approval
command line option, 707
gitlab-project-merge-request-approval-get
command line option, 707
gitlab-project-merge-request-approval-rule
command line option, 707
gitlab-project-merge-request-approval-rule-create
command line option, 708
gitlab-project-merge-request-approval-rule-delete
command line option, 708
gitlab-project-merge-request-approval-rule-get
command line option, 709
gitlab-project-merge-request-approval-rule-list
command line option, 709
gitlab-project-merge-request-approval-rule-update
command line option, 710
gitlab-project-merge-request-approval-state
command line option, 710
gitlab-project-merge-request-approval-state-get
command line option, 711
gitlab-project-merge-request-approval-update
command line option, 707
gitlab-project-merge-request-approve
command line option, 697
gitlab-project-merge-request-award-emoji
command line option, 711
gitlab-project-merge-request-award-emoji-create
command line option, 711
gitlab-project-merge-request-award-emoji-delete

```
    command line option, 712
gitlab-project-merge-request-award-emoji-get gitlab-project-merge-request-note-award-emoji-create
    command line option, 712
gitlab-project-merge-request-award-emoji-list gitlab-project-merge-request-note-award-emoji-delete
    command line option, 712
gitlab-project-merge-request-cancel-merge-whengitlab-project-merge-request-note-award-emoji-get
    command line option, 697
gitlab-project-merge-request-changes
    command line option, 698
gitlab-project-merge-request-closes-issues
    command line option, 698
gitlab-project-merge-request-commits
    command line option, 698
gitlab-project-merge-request-create
    command line option, 699
gitlab-project-merge-request-delete
    command line option, 700
gitlab-project-merge-request-diff
    command line option, 713
gitlab-project-merge-request-diff-get
    command line option, 713
gitlab-project-merge-request-diff-list
    command line option, 713
gitlab-project-merge-request-discussion
    command line option, 714
gitlab-project-merge-request-discussion-creategitlab-project-merge-request-pipeline-list
    command line option, 714
gitlab-project-merge-request-discussion-get gitlab-project-merge-request-rebase
    command line option, 714
gitlab-project-merge-request-discussion-list gitlab-project-merge-request-reset-approvals
    command line option, 715
gitlab-project-merge-request-discussion-note gitlab-project-merge-request-reset-spent-time
    command line option, 716
gitlab-project-merge-request-discussion-note-creatagitlab-project-merge-request-reset-time-estimate
    command line option, 716
gitlab-project-merge-request-discussion-note-deletagitlab-project-merge-request-resource-label-event
    command line option, 716
gitlab-project-merge-request-discussion-note-updatagitlab-project-merge-request-resource-label-event-get
    command line option, 717
gitlab-project-merge-request-discussion-note-updatagitlab-project-merge-request-resource-label-event-list
    command line option, 717
gitlab-project-merge-request-discussion-updategitlab-project-merge-request-resource-milestone-event
    command line option, 715
gitlab-project-merge-request-get
    command line option, 700
gitlab-project-merge-request-list
    command line option, 701
gitlab-project-merge-request-merge
    command line option, 702
gitlab-project-merge-request-merge-ref
    command line option, 702
gitlab-project-merge-request-note
    command line option, 718
gitlab-project-merge-request-note-award-emoji gitlab-project-merge-request-subscribe
    command line option, 720
gitlab-project-merge-request-note-award-emoji-create
    command line option, 720
gitlab-project-merge-request-note-award-emoji-delete
    command line option, 720
gitlab-project-merge-request-note-award-emoji-get
    command line option, 721
gitlab-project-merge-request-note-award-emoji-list
    command line option, 721
gitlab-project-merge-request-note-create
    command line option, 718
gitlab-project-merge-request-note-delete
    command line option, 718
gitlab-project-merge-request-note-get
    command line option, 719
gitlab-project-merge-request-note-list
    command line option, 719
gitlab-project-merge-request-note-update
    command line option, 719
gitlab-project-merge-request-participants
    command line option, 703
gitlab-project-merge-request-pipeline
    command line option, 722
gitlab-project-merge-request-pipeline-create
    command line option, 722
gitlab-project-merge-request-pipeline-list
    command line option, 722
gitlab-project-merge-request-rebase
    command line option, 703
gitlab-project-merge-request-reset-approvals
    command line option, 703
gitlab-project-merge-request-reset-spent-time
    command line option, 703
gitlab-project-merge-request-reset-time-estimate
    command line option, 704
gitlab-project-merge-request-resource-label-event
    command line option, 723
gitlab-project-merge-request-resource-label-event-get
    command line option, 723
gitlab-project-merge-request-resource-label-event-list
    command line option, 723
gitlab-project-merge-request-resource-milestone-event
    command line option, 724
gitlab-project-merge-request-resource-milestone-event-
    command line option, 724
gitlab-project-merge-request-resource-state-event
    command line option, 725
gitlab-project-merge-request-resource-state-event-get
    command line option, 725
gitlab-project-merge-request-resource-state-event-list
    command line option, 725
```

```

    command line option, 704
gitlab-project-merge-request-time-estimate
    command line option, 704
gitlab-project-merge-request-time-stats
    command line option, 705
gitlab-project-merge-request-todo
    command line option, 705
gitlab-project-merge-request-unapprove
    command line option, 705
gitlab-project-merge-request-unsubscribe
    command line option, 705
gitlab-project-merge-request-update
    command line option, 706
gitlab-project-merge-train command line
    option, 726
gitlab-project-merge-train-list command
    line option, 726
gitlab-project-milestone command line
    option, 726
gitlab-project-milestone-create command
    line option, 727
gitlab-project-milestone-delete command
    line option, 727
gitlab-project-milestone-get command
    line option, 727
gitlab-project-milestone-issues command
    line option, 728
gitlab-project-milestone-list command
    line option, 728
gitlab-project-milestone-merge-requests
    command line option, 728
gitlab-project-milestone-update command
    line option, 729
gitlab-project-mirror-pull command line
    option, 600
gitlab-project-mirror-pull-details
    command line option, 600
gitlab-project-note command line option,
    729
gitlab-project-note-get command line
    option, 729
gitlab-project-note-list command line
    option, 730
gitlab-project-notification-settings
    command line option, 730
gitlab-project-notification-settings-get
    command line option, 730
gitlab-project-notification-settings-update
    command line option, 731
gitlab-project-package command line
    option, 731
gitlab-project-package-delete command
    line option, 732
gitlab-project-package-file command
    line option, 733
gitlab-project-package-file-delete
    command line option, 733
gitlab-project-package-file-list
    command line option, 733
gitlab-project-package-get command line
    option, 732
gitlab-project-package-list command
    line option, 732
gitlab-project-pages-domain command
    line option, 734
gitlab-project-pages-domain-create
    command line option, 734
gitlab-project-pages-domain-delete
    command line option, 734
gitlab-project-pages-domain-get command
    line option, 735
gitlab-project-pages-domain-list
    command line option, 735
gitlab-project-pages-domain-update
    command line option, 735
gitlab-project-pipeline command line
    option, 736
gitlab-project-pipeline-bridge command
    line option, 738
gitlab-project-pipeline-bridge-list
    command line option, 738
gitlab-project-pipeline-cancel command
    line option, 736
gitlab-project-pipeline-create command
    line option, 736
gitlab-project-pipeline-delete command
    line option, 736
gitlab-project-pipeline-get command
    line option, 737
gitlab-project-pipeline-job command
    line option, 739
gitlab-project-pipeline-job-list
    command line option, 739
gitlab-project-pipeline-list command
    line option, 737
gitlab-project-pipeline-retry command
    line option, 738
gitlab-project-pipeline-schedule
    command line option, 739
gitlab-project-pipeline-schedule-create
    command line option, 740
gitlab-project-pipeline-schedule-delete
    command line option, 740
gitlab-project-pipeline-schedule-get
    command line option, 740
gitlab-project-pipeline-schedule-list
    command line option, 741
gitlab-project-pipeline-schedule-pipeline

```

```
    command line option, 742
gitlab-project-pipeline-schedule-pipeline-listgitlab-project-protected-tag-get
    command line option, 742
gitlab-project-pipeline-schedule-play
    command line option, 741
gitlab-project-pipeline-schedule-take-ownershipgitlab-project-push-rules command line
    command line option, 741
gitlab-project-pipeline-schedule-update
    command line option, 742
gitlab-project-pipeline-schedule-variable
    command line option, 743
gitlab-project-pipeline-schedule-variable-creatgitlab-project-push-rules-create
    command line option, 743
gitlab-project-pipeline-schedule-variable-deletgitlab-project-push-rules-delete
    command line option, 744
gitlab-project-pipeline-schedule-variable-updagitlab-project-push-rules-get command
    command line option, 744
line option, 753
gitlab-project-pipeline-test-report
    command line option, 744
gitlab-project-pipeline-test-report-get
    command line option, 745
gitlab-project-pipeline-test-report-summary
    command line option, 745
gitlab-project-pipeline-test-report-summary-gegitlab-project-registry-repository
    command line option, 745
gitlab-project-pipeline-variable
    command line option, 745
gitlab-project-pipeline-variable-list
    command line option, 746
gitlab-project-protected-branch command
    line option, 746
gitlab-project-protected-branch-create
    command line option, 746
gitlab-project-protected-branch-delete
    command line option, 747
gitlab-project-protected-branch-get
    command line option, 747
gitlab-project-protected-branch-list
    command line option, 748
gitlab-project-protected-environment
    command line option, 748
gitlab-project-protected-environment-create
    command line option, 748
gitlab-project-protected-environment-delete
    command line option, 749
gitlab-project-protected-environment-get
    command line option, 749
gitlab-project-protected-environment-list
    command line option, 749
gitlab-project-protected-tag command
    line option, 750
gitlab-project-protected-tag-create
    command line option, 750
gitlab-project-protected-tag-delete
    command line option, 750
gitlab-project-protected-tag-get
    command line option, 751
gitlab-project-protected-tag-list
    command line option, 751
gitlab-project-push-rules command line
    option, 751
gitlab-project-push-rules-create
    command line option, 752
gitlab-project-push-rules-delete
    command line option, 752
gitlab-project-push-rules-get command
    line option, 753
gitlab-project-push-rules-update
    command line option, 753
gitlab-project-registry-repository
    command line option, 754
gitlab-project-registry-repository-delete
    command line option, 754
gitlab-project-registry-repository-list
    command line option, 754
gitlab-project-registry-tag command
    line option, 755
gitlab-project-registry-tag-delete
    command line option, 755
gitlab-project-registry-tag-delete-in-bulk
    command line option, 755
gitlab-project-registry-tag-get command
    line option, 756
gitlab-project-registry-tag-list
    command line option, 756
gitlab-project-release command line
    option, 756
gitlab-project-release-create command
    line option, 757
gitlab-project-release-delete command
    line option, 757
gitlab-project-release-get command line
    option, 757
gitlab-project-release-link command
    line option, 759
gitlab-project-release-link-create
    command line option, 759
gitlab-project-release-link-delete
    command line option, 759
gitlab-project-release-link-get command
    line option, 760
gitlab-project-release-link-list
    command line option, 760
gitlab-project-release-link-update
    command line option, 760
gitlab-project-release-list command
    line option, 758
gitlab-project-release-update command
```

```

    line option, 758
gitlab-project-remote-mirror command
    line option, 761
gitlab-project-remote-mirror-create
    command line option, 761
gitlab-project-remote-mirror-list
    command line option, 761
gitlab-project-remote-mirror-update
    command line option, 762
gitlab-project-repository-archive
    command line option, 600
gitlab-project-repository-blob command
    line option, 601
gitlab-project-repository-compare
    command line option, 601
gitlab-project-repository-contributors
    command line option, 601
gitlab-project-repository-merge-base
    command line option, 601
gitlab-project-repository-raw-blob
    command line option, 602
gitlab-project-repository-tree command
    line option, 602
gitlab-project-resource-group command
    line option, 762
gitlab-project-resource-group-get
    command line option, 762
gitlab-project-resource-group-list
    command line option, 763
gitlab-project-resource-group-upcoming-job
    command line option, 764
gitlab-project-resource-group-upcoming-job-list
    command line option, 764
gitlab-project-resource-group-update
    command line option, 763
gitlab-project-restore command line
    option, 602
gitlab-project-runner command line
    option, 764
gitlab-project-runner-create command
    line option, 764
gitlab-project-runner-delete command
    line option, 765
gitlab-project-runner-list command line
    option, 765
gitlab-project-search command line
    option, 602
gitlab-project-secure-file command line
    option, 766
gitlab-project-secure-file-create
    command line option, 766
gitlab-project-secure-file-delete
    command line option, 766
gitlab-project-secure-file-download
    command line option, 766
gitlab-project-secure-file-get command
    line option, 767
gitlab-project-secure-file-list command
    line option, 767
gitlab-project-service command line
    option, 767
gitlab-project-service-available
    command line option, 768
gitlab-project-service-delete command
    line option, 768
gitlab-project-service-get command line
    option, 768
gitlab-project-service-list command
    line option, 768
gitlab-project-service-update command
    line option, 769
gitlab-project-share command line
    option, 603
gitlab-project-snapshot command line
    option, 603
gitlab-project-snippet command line
    option, 769
gitlab-project-snippet-award-emoji
    command line option, 772
gitlab-project-snippet-award-emoji-create
    command line option, 772
gitlab-project-snippet-award-emoji-delete
    command line option, 772
gitlab-project-snippet-award-emoji-get
    command line option, 773
gitlab-project-snippet-award-emoji-list
    command line option, 773
gitlab-project-snippet-content command
    line option, 769
gitlab-project-snippet-create command
    line option, 770
gitlab-project-snippet-delete command
    line option, 770
gitlab-project-snippet-discussion
    command line option, 774
gitlab-project-snippet-discussion-create
    command line option, 774
gitlab-project-snippet-discussion-get
    command line option, 774
gitlab-project-snippet-discussion-list
    command line option, 775
gitlab-project-snippet-discussion-note
    command line option, 775
gitlab-project-snippet-discussion-note-create
    command line option, 775
gitlab-project-snippet-discussion-note-delete
    command line option, 776
gitlab-project-snippet-discussion-note-get
    command line option, 776

```

```
    command line option, 776
gitlab-project-snippet-discussion-note-update command line option, 777
gitlab-project-snippet-get command line option, 770
gitlab-project-snippet-list command line option, 771
gitlab-project-snippet-note command line option, 777
gitlab-project-snippet-note-award-emoji command line option, 779
gitlab-project-snippet-note-award-emoji-create command line option, 779
gitlab-project-snippet-note-award-emoji-delete command line option, 780
gitlab-project-snippet-note-award-emoji-get command line option, 780
gitlab-project-snippet-note-award-emoji-list command line option, 781
gitlab-project-snippet-note-create command line option, 777
gitlab-project-snippet-note-delete command line option, 778
gitlab-project-snippet-note-get command line option, 778
gitlab-project-snippet-note-list command line option, 778
gitlab-project-snippet-note-update command line option, 779
gitlab-project-snippet-update command line option, 771
gitlab-project-snippet-user-agent-detail command line option, 772
gitlab-project-star command line option, 603
gitlab-project-storage command line option, 781
gitlab-project-storage-get command line option, 781
gitlab-project-tag command line option, 782
gitlab-project-tag-create command line option, 782
gitlab-project-tag-delete command line option, 782
gitlab-project-tag-get command line option, 782
gitlab-project-tag-list command line option, 783
gitlab-project-transfer command line option, 603
gitlab-project-transfer-project command line option, 604
gitlab-project-trigger command line option, 783
gitlab-project-trigger-create command line option, 783
gitlab-project-trigger-delete command line option, 784
gitlab-project-trigger-get command line option, 784
gitlab-project-trigger-list command line option, 784
gitlab-project-trigger-pipeline command line option, 604
gitlab-project-trigger-update command line option, 785
gitlab-project-unarchive command line option, 604
gitlab-project-unshare command line option, 604
gitlab-project-unstar command line option, 605
gitlab-project-update command line option, 607
gitlab-project-update-submodule command line option, 610
gitlab-project-upload command line option, 610
gitlab-project-user command line option, 785
gitlab-project-user-list command line option, 785
gitlab-project-variable command line option, 786
gitlab-project-variable-create command line option, 786
gitlab-project-variable-delete command line option, 786
gitlab-project-variable-get command line option, 787
gitlab-project-variable-list command line option, 787
gitlab-project-variable-update command line option, 787
gitlab-project-wiki command line option, 788
gitlab-project-wiki-create command line option, 788
gitlab-project-wiki-delete command line option, 788
gitlab-project-wiki-get command line option, 789
gitlab-project-wiki-list command line option, 789
gitlab-project-wiki-update command line option, 789
gitlab-registry-repository command line
```

option, 790
gitlab-registry-repository-get command line option, 790
gitlab-runner command line option, 790
gitlab-runner-all command line option, 790, 793
gitlab-runner-all-list command line option, 793
gitlab-runner-create command line option, 791
gitlab-runner-delete command line option, 791
gitlab-runner-get command line option, 791
gitlab-runner-job command line option, 794
gitlab-runner-job-list command line option, 794
gitlab-runner-list command line option, 792
gitlab-runner-update command line option, 792
gitlab-runner-verify command line option, 793
gitlab-shared-project command line option, 794
gitlab-shared-project-list command line option, 795
gitlab-snippet command line option, 795
gitlab-snippet-content command line option, 796
gitlab-snippet-create command line option, 796
gitlab-snippet-delete command line option, 796
gitlab-snippet-get command line option, 797
gitlab-snippet-list command line option, 797
gitlab-snippet-public command line option, 797
gitlab-snippet-update command line option, 797
gitlab-snippet-user-agent-detail command line option, 798
gitlab-starred-project command line option, 798
gitlab-starred-project-list command line option, 798
gitlab-todo command line option, 799
gitlab-todo-delete command line option, 799
gitlab-todo-list command line option, 800
gitlab-todo-mark-all-as-done command line option, 800
gitlab-todo-mark-as-done command line option, 800
gitlab-topic command line option, 801
gitlab-topic-create command line option, 801
gitlab-topic-delete command line option, 801
gitlab-topic-get command line option, 801
gitlab-topic-list command line option, 802
gitlab-topic-merge command line option, 802
gitlab-topic-update command line option, 802
gitlab-user command line option, 803
gitlab-user-activate command line option, 803
gitlab-user-activities command line option, 809
gitlab-user-activities-list command line option, 809
gitlab-user-approve command line option, 803
gitlab-user-ban command line option, 803
gitlab-user-block command line option, 804
gitlab-user-create command line option, 804
gitlab-user-custom-attribute command line option, 809
gitlab-user-custom-attribute-delete command line option, 810
gitlab-user-custom-attribute-get command line option, 810
gitlab-user-custom-attribute-list command line option, 810
gitlab-user-deactivate command line option, 805
gitlab-user-delete command line option, 805
gitlab-user-email command line option, 811
gitlab-user-email-create command line option, 811
gitlab-user-email-delete command line option, 811
gitlab-user-email-get command line option, 811
gitlab-user-email-list command line option, 812
gitlab-user-event command line option, 812
gitlab-user-event-list command line

```
    option, 812
gitlab-user-follow command line option,
    806
gitlab-user-get command line option, 806
gitlab-user-gpg-key command line option,
    813
gitlab-user-gpg-key-create command line
    option, 813
gitlab-user-gpg-key-delete command line
    option, 813
gitlab-user-gpg-key-get command line
    option, 814
gitlab-user-gpg-key-list command line
    option, 814
gitlab-user-impersonation-token command
    line option, 814
gitlab-user-impersonation-token-create
    command line option, 814
gitlab-user-impersonation-token-delete
    command line option, 815
gitlab-user-impersonation-token-get
    command line option, 815
gitlab-user-impersonation-token-list
    command line option, 815
gitlab-user-key command line option, 816
gitlab-user-key-create command line
    option, 816
gitlab-user-key-delete command line
    option, 816
gitlab-user-key-get command line option,
    817
gitlab-user-key-list command line
    option, 817
gitlab-user-list command line option, 806
gitlab-user-membership command line
    option, 817
gitlab-user-membership-get command line
    option, 817
gitlab-user-membership-list command
    line option, 818
gitlab-user-personal-access-token
    command line option, 818
gitlab-user-personal-access-token-create
    command line option, 818
gitlab-user-project command line option,
    819
gitlab-user-project-create command line
    option, 819
gitlab-user-project-list command line
    option, 820
gitlab-user-reject command line option,
    807
gitlab-user-status command line option,
    821
gitlab-user-status-get command line
    option, 821
gitlab-user-unban command line option,
    807
gitlab-user-unblock command line option,
    807
gitlab-user-unfollow command line
    option, 807
gitlab-user-update command line option,
    808
gitlab-variable command line option, 821
gitlab-variable-create command line
    option, 822
gitlab-variable-delete command line
    option, 822
gitlab-variable-get command line option,
    822
gitlab-variable-list command line
    option, 823
gitlab-variable-update command line
    option, 823
-o gitlab command line option, 484
-v gitlab command line option, 484
```

A

access_tokens (*gitlab.v4.objects.Group attribute*), 216
access_tokens (*gitlab.v4.objects.Project attribute*), 275
AccessLevel (*class in gitlab.const*), 451
AccessRequestMixin (*class in gitlab.mixins*), 470
accessrequests (*gitlab.v4.objects.Group attribute*),
 216
accessrequests (*gitlab.v4.objects.Project attribute*),
 275
activate() (*gitlab.v4.objects.User method*), 429
add_ldap_group_link() (*gitlab.v4.objects.Group method*), 216
add_spent_time() (*gitlab.mixins.TimeTrackingMixin method*), 476
additionalstatistics (*gitlab.v4.objects.Project attribute*), 275
ADMIN (*gitlab.const.AccessLevel attribute*), 451
all() (*gitlab.v4.objects.RunnerManager method*), 421
api_url (*gitlab.Gitlab property*), 182
api_version (*gitlab.Gitlab property*), 182
appearance (*gitlab.Gitlab attribute*), 182
Application (*class in gitlab.v4.objects*), 192
ApplicationAppearance (*class in gitlab.v4.objects*),
 192
ApplicationAppearanceManager (*class in gitlab.v4.objects*), 193
ApplicationManager (*class in gitlab.v4.objects*), 194
applications (*gitlab.Gitlab attribute*), 182

B

ApplicationSettings (*class in gitlab.v4.objects*), 194
 ApplicationSettingsManager (*class in gitlab.v4.objects*), 195
 ApplicationStatistics (*class in gitlab.v4.objects*), 197
 ApplicationStatisticsManager (*class in gitlab.v4.objects*), 197
 approval() (*gitlab.v4.objects.ProjectDeployment method*), 305
 approval_rule_id (*gitlab.v4.objects.ProjectMergeRequestApprovalRule attribute*), 359
 approval_rules (*gitlab.v4.objects.ProjectMergeRequest attribute*), 354
 approval_state (*gitlab.v4.objects.ProjectMergeRequest attribute*), 354
 approvalrules (*gitlab.v4.objects.Project attribute*), 275
 approvals (*gitlab.v4.objects.Project attribute*), 275
 approvals (*gitlab.v4.objects.ProjectMergeRequest attribute*), 354
 approve() (*gitlab.mixins.AccessRequestMixin method*), 470
 approve() (*gitlab.v4.objects.ProjectMergeRequest method*), 354
 approve() (*gitlab.v4.objects.User method*), 430
 archive() (*gitlab.v4.objects.Project method*), 275
 artifact() (*gitlab.v4.objects.Project method*), 275
 artifact() (*gitlab.v4.objects.ProjectJob method*), 336
 artifacts (*gitlab.v4.objects.Project attribute*), 276
 artifacts() (*gitlab.v4.objects.ProjectJob method*), 336
 asdict() (*gitlab.base.RESTObject method*), 447
 attributes (*gitlab.base.RESTObject property*), 447
 audit_events (*gitlab.Gitlab attribute*), 182
 audit_events (*gitlab.v4.objects.Group attribute*), 217
 audit_events (*gitlab.v4.objects.Project attribute*), 276
 AuditEvent (*class in gitlab.v4.objects*), 198
 AuditEventManager (*class in gitlab.v4.objects*), 198
 auth() (*gitlab.Gitlab method*), 182
 available() (*gitlab.v4.objects.ProjectIntegrationManager method*), 319
 awardemojis (*gitlab.v4.objects.GroupEpicNote attribute*), 235
 awardemojis (*gitlab.v4.objects.ProjectIssue attribute*), 321
 awardemojis (*gitlab.v4.objects.ProjectIssueNote attribute*), 328
 awardemojis (*gitlab.v4.objects.ProjectMergeRequest attribute*), 354
 awardemojis (*gitlab.v4.objects.ProjectMergeRequestNote attribute*), 367
 awardemojis (*gitlab.v4.objects.ProjectSnippet attribute*), 402
 awardemojis (*gitlab.v4.objects.ProjectSnippetNote attribute*), 406
 BadgeRenderMixin (*class in gitlab.mixins*), 470
 badges (*gitlab.v4.objects.Group attribute*), 217
 badges (*gitlab.v4.objects.Project attribute*), 276
 ban() (*gitlab.v4.objects.User method*), 430
 billable_members (*gitlab.v4.objects.Group attribute*), 217
 blame() (*gitlab.v4.objects.ProjectFileManager method*), 313
 BLOBS (*gitlab.const.SearchScope attribute*), 451
 block() (*gitlab.v4.objects.User method*), 430
 boards (*gitlab.v4.objects.Group attribute*), 217
 boards (*gitlab.v4.objects.Project attribute*), 276
 branch (*gitlab.v4.objects.ProjectFile attribute*), 311
 branches (*gitlab.v4.objects.Project attribute*), 276
 bridges (*gitlab.v4.objects.ProjectPipeline attribute*), 380
 BroadcastMessage (*class in gitlab.v4.objects*), 199
 BroadcastMessageManager (*class in gitlab.v4.objects*), 199
 broadcastmessages (*gitlab.Gitlab attribute*), 182
 bulk_import_entities (*gitlab.Gitlab attribute*), 182
 bulk_imports (*gitlab.Gitlab attribute*), 182
 BulkImport (*class in gitlab.v4.objects*), 200
 BulkImportAllEntity (*class in gitlab.v4.objects*), 200
 BulkImportAllEntityManager (*class in gitlab.v4.objects*), 201
 BulkImportEntity (*class in gitlab.v4.objects*), 201
 BulkImportEntityManager (*class in gitlab.v4.objects*), 201
 BulkImportManager (*class in gitlab.v4.objects*), 202

C

cancel() (*gitlab.v4.objects.ProjectJob method*), 337
 cancel() (*gitlab.v4.objects.ProjectPipeline method*), 380
 cancel_merge_when_pipeline_succeeds() (*gitlab.v4.objects.ProjectMergeRequest method*), 354
 changes() (*gitlab.v4.objects.ProjectMergeRequest method*), 354
 cherry_pick() (*gitlab.v4.objects.ProjectCommit method*), 296
 ci_lint (*gitlab.Gitlab attribute*), 182
 ci_lint (*gitlab.v4.objects.Project attribute*), 276
 CiLint (*class in gitlab.v4.objects*), 203
 CiLintManager (*class in gitlab.v4.objects*), 203
 closed_by() (*gitlab.v4.objects.ProjectIssue method*), 321
 closes_issues() (*gitlab.v4.objects.ProjectMergeRequest method*), 355
 cls_to_gitlab_resource() (*in module gitlab.cli*), 449

clusters (*gitlab.v4.objects.Group attribute*), 217
clusters (*gitlab.v4.objects.Project attribute*), 276
comments (*gitlab.v4.objects.ProjectCommit attribute*), 297
commit_message (*gitlab.v4.objects.ProjectFile attribute*), 311
COMMITS (*gitlab.const.SearchScope attribute*), 451
commits (*gitlab.v4.objects.Project attribute*), 276
commits() (*gitlab.v4.objects.ProjectMergeRequest method*), 355
compound_metrics() (*gitlab.v4.objects.SidekiqManager method*), 423
ConfigError, 450
content() (*gitlab.v4.objects.ProjectSnippet method*), 402
content() (*gitlab.v4.objects.Snippet method*), 424
copy_dict() (*in module gitlab.utils*), 479
create() (*gitlab.mixins.CreateMixin method*), 470
create() (*gitlab.v4.objects.GroupClusterManager method*), 227
create() (*gitlab.v4.objects.GroupEpicIssueManager method*), 234
create() (*gitlab.v4.objects.ProjectClusterManager method*), 295
create() (*gitlab.v4.objects.ProjectCommitStatusManager method*), 303
create() (*gitlab.v4.objects.ProjectFileManager method*), 313
create() (*gitlab.v4.objects.ProjectForkManager method*), 316
create() (*gitlab.v4.objects.ProjectIssueLinkManager method*), 326
create() (*gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager method*), 360
create() (*gitlab.v4.objects.ProjectPipelineManager method*), 382
create_fork_relation() (*gitlab.v4.objects.Project method*), 276
CreateMixin (*class in gitlab.mixins*), 470
CRUDMixin (*class in gitlab.mixins*), 470
current_failures() (*gitlab.v4.objects.GeoNodeManager method*), 214
current_page (*gitlab.base.RESTObjectList property*), 448
current_page (*gitlab.GitlabList property*), 191
CurrentUser (*class in gitlab.v4.objects*), 203
CurrentUserEmail (*class in gitlab.v4.objects*), 204
CurrentUserEmailManager (*class in gitlab.v4.objects*), 204
CurrentUserGPGKey (*class in gitlab.v4.objects*), 205
CurrentUserGPGKeyManager (*class in gitlab.v4.objects*), 205
CurrentUserKey (*class in gitlab.v4.objects*), 205
CurrentUserKeyManager (*class in gitlab.v4.objects*), 206
CurrentUserManager (*class in gitlab.v4.objects*), 206
CurrentUserStatus (*class in gitlab.v4.objects*), 207
CurrentUserStatusManager (*class in gitlab.v4.objects*), 207
CUSTOM (*gitlab.const.NotificationLevel attribute*), 451
custom_attributes (*gitlab.v4.objects.Group attribute*), 217
custom_attributes (*gitlab.v4.objects.Project attribute*), 276
custom_attributes (*gitlab.v4.objects.User attribute*), 431

D

deactivate() (*gitlab.v4.objects.User method*), 431
decode() (*gitlab.v4.objects.ProjectFile method*), 311
delete() (*gitlab.mixins.DeleteMixin method*), 471
delete() (*gitlab.mixins.ObjectDeleteMixin method*), 473
delete() (*gitlab.v4.objects.GroupLDAPGroupLink method*), 245
delete() (*gitlab.v4.objects.ProjectArtifactManager method*), 287
delete() (*gitlab.v4.objects.ProjectFile method*), 311
delete() (*gitlab.v4.objects.ProjectFileManager method*), 313
delete_artifacts() (*gitlab.v4.objects.ProjectJob method*), 337
delete_fork_relation() (*gitlab.v4.objects.Project method*), 276
delete_in_bulk() (*gitlab.v4.objects.ProjectRegistryTagManager method*), 393
delete_ldap_group_link() (*gitlab.v4.objects.Group method*), 217
delete_merged_branches() (*gitlab.v4.objects.RepositoryMixin method*), 415
DeleteMixin (*class in gitlab.mixins*), 471
DeployKey (*class in gitlab.v4.objects*), 208
DeployKeyManager (*class in gitlab.v4.objects*), 208
deploykeys (*gitlab.Gitlab attribute*), 182
deployments (*gitlab.v4.objects.Project attribute*), 276
DeployToken (*class in gitlab.v4.objects*), 208
DeployTokenManager (*class in gitlab.v4.objects*), 208
deploytokens (*gitlab.Gitlab attribute*), 182
deploytokens (*gitlab.v4.objects.Group attribute*), 217
deploytokens (*gitlab.v4.objects.Project attribute*), 276
descendant_groups (*gitlab.v4.objects.Group attribute*), 217
DEVELOPER (*gitlab.const.AccessLevel attribute*), 451
die() (*in module gitlab.cli*), 449

d
diff() (*gitlab.v4.objects.ProjectCommit method*), 297
diffs (*gitlab.v4.objects.ProjectMergeRequest attribute*), 355
DISABLED (*gitlab.const.NotificationLevel attribute*), 451
discussions (*gitlab.v4.objects.ProjectCommit attribute*), 297
discussions (*gitlab.v4.objects.ProjectIssue attribute*), 321
discussions (*gitlab.v4.objects.ProjectMergeRequest attribute*), 356
discussions (*gitlab.v4.objects.ProjectSnippet attribute*), 402
Dockerfile (*class in gitlab.v4.objects*), 209
DockerfileManager (*class in gitlab.v4.objects*), 209
dockerfiles (*gitlab.Gitlab attribute*), 183
docs() (*in module gitlab.cli*), 449
download() (*gitlab.mixins.DownloadMixin method*), 471
download() (*gitlab.v4.objects.GenericPackageManager method*), 211
download() (*gitlab.v4.objects.ProjectArtifactManager method*), 287
download() (*gitlab.v4.objects.ProjectSecureFile method*), 400
DownloadMixin (*class in gitlab.mixins*), 471

E
emails (*gitlab.v4.objects.CurrentUser attribute*), 204
emails (*gitlab.v4.objects.User attribute*), 431
enable() (*gitlab.v4.objects.ProjectKeyManager method*), 340
enable_debug() (*gitlab.Gitlab static method*), 183
encoded_id (*gitlab.base.RESTObject property*), 447
EncodedId (*class in gitlab.utils*), 478
entities (*gitlab.v4.objects.BulkImport attribute*), 200
environments (*gitlab.v4.objects.Project attribute*), 276
epics (*gitlab.v4.objects.Group attribute*), 217
erase() (*gitlab.v4.objects.ProjectJob method*), 337
Event (*class in gitlab.v4.objects*), 209
EventManager (*class in gitlab.v4.objects*), 210
events (*gitlab.Gitlab attribute*), 183
events (*gitlab.v4.objects.Project attribute*), 276
events (*gitlab.v4.objects.User attribute*), 431
exists() (*gitlab.v4.objects.NamespaceManager method*), 271
exports (*gitlab.v4.objects.Group attribute*), 217
exports (*gitlab.v4.objects.Project attribute*), 276

F
Feature (*class in gitlab.v4.objects*), 210
FeatureManager (*class in gitlab.v4.objects*), 210
features (*gitlab.Gitlab attribute*), 183
file_path (*gitlab.v4.objects.ProjectFile attribute*), 311
files (*gitlab.v4.objects.Project attribute*), 276

f
follow() (*gitlab.v4.objects.User method*), 431
followers_users (*gitlab.v4.objects.User attribute*), 431
following_users (*gitlab.v4.objects.User attribute*), 431
forks (*gitlab.v4.objects.Project attribute*), 277
format_help() (*gitlab.cli.VerticalHelpFormatter method*), 449
from_config() (*gitlab.Gitlab class method*), 183

G
generic_packages (*gitlab.v4.objects.Project attribute*), 277
GenericPackage (*class in gitlab.v4.objects*), 211
GenericPackageManager (*class in gitlab.v4.objects*), 211
GeoNode (*class in gitlab.v4.objects*), 213
GeoNodeManager (*class in gitlab.v4.objects*), 213
geonodes (*gitlab.Gitlab attribute*), 183
get() (*gitlab.mixins.GetMixin method*), 472
get() (*gitlab.mixins.GetWithoutIdMixin method*), 472
get() (*gitlab.v4.objects.ApplicationAppearanceManager method*), 193
get() (*gitlab.v4.objects.ApplicationSettingsManager method*), 196
get() (*gitlab.v4.objects.ApplicationStatisticsManager method*), 198
get() (*gitlab.v4.objects.AuditEventManager method*), 198
get() (*gitlab.v4.objects.BroadcastMessageManager method*), 200
get() (*gitlab.v4.objects.BulkImportEntityManager method*), 201
get() (*gitlab.v4.objects.BulkImportManager method*), 202
get() (*gitlab.v4.objects.CurrentUserEmailManager method*), 204
get() (*gitlab.v4.objects.CurrentUserGPGKeyManager method*), 205
get() (*gitlab.v4.objects.CurrentUserKeyManager method*), 206
get() (*gitlab.v4.objects.CurrentUserManager method*), 207
get() (*gitlab.v4.objects.CurrentUserStatusManager method*), 207
get() (*gitlab.v4.objects.DockerfileManager method*), 209
get() (*gitlab.v4.objects.GeoNodeManager method*), 214
get() (*gitlab.v4.objects.GitignoreManager method*), 215
get() (*gitlab.v4.objects.GitlabciymlManager method*), 216
get() (*gitlab.v4.objects.GroupAuditEventManager method*), 222

get() (*gitlab.v4.objects.GroupBadgeManager* method), 223
get() (*gitlab.v4.objects.GroupBoardListManager* method), 225
get() (*gitlab.v4.objects.GroupBoardManager* method), 226
get() (*gitlab.v4.objects.GroupClusterManager* method), 227
get() (*gitlab.v4.objects.GroupCustomAttributeManager* method), 228
get() (*gitlab.v4.objects.GroupDeployTokenManager* method), 229
get() (*gitlab.v4.objects.GroupEpicAwardEmojiManager* method), 231
get() (*gitlab.v4.objects.GroupEpicDiscussionNoteManager* method), 232
get() (*gitlab.v4.objects.GroupEpicManager* method), 235
get() (*gitlab.v4.objects.GroupEpicNoteAwardEmojiManager* method), 236
get() (*gitlab.v4.objects.GroupEpicNoteManager* method), 237
get() (*gitlab.v4.objects.GroupEpicResourceLabelEventManager* method), 238
get() (*gitlab.v4.objects.GroupExportManager* method), 239
get() (*gitlab.v4.objects.GroupHookManager* method), 240
get() (*gitlab.v4.objects.GroupImportManager* method), 241
get() (*gitlab.v4.objects.GroupInvitationManager* method), 242
get() (*gitlab.v4.objects.GroupIssuesStatisticsManager* method), 244
get() (*gitlab.v4.objects.GroupLabelManager* method), 247
get() (*gitlab.v4.objects.GroupManager* method), 249
get() (*gitlab.v4.objects.GroupMemberAllManager* method), 251
get() (*gitlab.v4.objects.GroupMemberManager* method), 252
get() (*gitlab.v4.objects.GroupMilestoneManager* method), 255
get() (*gitlab.v4.objects.GroupNotificationSettingsManager* method), 256
get() (*gitlab.v4.objects.GroupPushRulesManager* method), 259
get() (*gitlab.v4.objects.GroupSAMLGroupLinkManager* method), 261
get() (*gitlab.v4.objects.GroupVariableManager* method), 262
get() (*gitlab.v4.objects.GroupWikiManager* method), 264
get() (*gitlab.v4.objects.HookManager* method), 264
get() (*gitlab.v4.objects.IssueManager* method), 266
get() (*gitlab.v4.objects.IssuesStatisticsManager* method), 267
get() (*gitlab.v4.objects.KeyManager* method), 267
get() (*gitlab.v4.objects.LicenseManager* method), 269
get() (*gitlab.v4.objects.NamespaceManager* method), 272
get() (*gitlab.v4.objects.NotificationSettingsManager* method), 273
get() (*gitlab.v4.objects.PersonalAccessTokenManager* method), 274
get() (*gitlab.v4.objects.ProjectAdditionalStatisticsManager* method), 284
get() (*gitlab.v4.objects.ProjectApprovalManager* method), 285
get() (*gitlab.v4.objects.ProjectAuditEventManager* method), 289
get() (*gitlab.v4.objects.ProjectBadgeManager* method), 290
get() (*gitlab.v4.objects.ProjectBoardListManager* method), 291
get() (*gitlab.v4.objects.ProjectBoardManager* method), 292
get() (*gitlab.v4.objects.ProjectBranchManager* method), 293
get() (*gitlab.v4.objects.ProjectCiLintManager* method), 294
get() (*gitlab.v4.objects.ProjectClusterManager* method), 296
get() (*gitlab.v4.objects.ProjectCommitDiscussionManager* method), 299
get() (*gitlab.v4.objects.ProjectCommitDiscussionNoteManager* method), 301
get() (*gitlab.v4.objects.ProjectCommitManager* method), 302
get() (*gitlab.v4.objects.ProjectCustomAttributeManager* method), 304
get() (*gitlab.v4.objects.ProjectDeploymentManager* method), 306
get() (*gitlab.v4.objects.ProjectDeployTokenManager* method), 305
get() (*gitlab.v4.objects.ProjectEnvironmentManager* method), 309
get() (*gitlab.v4.objects.ProjectExportManager* method), 310
get() (*gitlab.v4.objects.ProjectFileManager* method), 314
get() (*gitlab.v4.objects.ProjectHookManager* method), 317
get() (*gitlab.v4.objects.ProjectImportManager* method), 318
get() (*gitlab.v4.objects.ProjectIntegrationManager* method), 319
get() (*gitlab.v4.objects.ProjectInvitationManager*

```

        method), 320
get() (gitlab.v4.objects.ProjectIssueAwardEmojiManager
        method), 323
get() (gitlab.v4.objects.ProjectIssueDiscussionManager
        method), 324
get() (gitlab.v4.objects.ProjectIssueDiscussionNoteManager
        method), 325
get() (gitlab.v4.objects.ProjectIssueManager method),
        328
get() (gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager
        method), 329
get() (gitlab.v4.objects.ProjectIssueNoteManager
        method), 330
get() (gitlab.v4.objects.ProjectIssueResourceIterationEventManager
        method), 330
get() (gitlab.v4.objects.ProjectIssueResourceLabelEventManager
        method), 331
get() (gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager
        method), 332
get() (gitlab.v4.objects.ProjectIssueResourceStateEventManager
        method), 333
get() (gitlab.v4.objects.ProjectIssueResourceWeightEventManager
        method), 334
get() (gitlab.v4.objects.ProjectIssuesStatisticsManager
        method), 335
get() (gitlab.v4.objects.ProjectJobManager method),
        339
get() (gitlab.v4.objects.ProjectKeyManager method),
        340
get() (gitlab.v4.objects.ProjectLabelManager method),
        341
get() (gitlab.v4.objects.ProjectManager method), 347
get() (gitlab.v4.objects.ProjectMemberAllManager
        method), 352
get() (gitlab.v4.objects.ProjectMemberManager
        method), 353
get() (gitlab.v4.objects.ProjectMergeRequestApprovalManager
        method), 358
get() (gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager
        method), 360
get() (gitlab.v4.objects.ProjectMergeRequestApprovalStateManager
        method), 361
get() (gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager
        method), 362
get() (gitlab.v4.objects.ProjectMergeRequestDiffManager
        method), 363
get() (gitlab.v4.objects.ProjectMergeRequestDiscussionManager
        method), 364
get() (gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager
        method), 365
get() (gitlab.v4.objects.ProjectMergeRequestManager
        method), 367
get() (gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager
        method), 368
get() (gitlab.v4.objects.ProjectMergeRequestNoteManager
        method), 369
get() (gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager
        method), 370
get() (gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager
        method), 371
get() (gitlab.v4.objects.ProjectMergeRequestResourceStateEventManager
        method), 372
get() (gitlab.v4.objects.ProjectMilestoneManager
        method), 375
get() (gitlab.v4.objects.ProjectNoteManager method),
        375
get() (gitlab.v4.objects.ProjectNotificationSettingsManager
        method), 377
get() (gitlab.v4.objects.ProjectPackageManager
        method), 378
get() (gitlab.v4.objects.ProjectPagesDomainManager
        method), 379
get() (gitlab.v4.objects.ProjectPipelineManager
        method), 380
get() (gitlab.v4.objects.ProjectPipelineScheduleManager
        method), 382
get() (gitlab.v4.objects.ProjectPipelineTestReportManager
        method), 384
get() (gitlab.v4.objects.ProjectPipelineTestReportSummaryManager
        method), 386
get() (gitlab.v4.objects.ProjectProtectedBranchManager
        method), 389
get() (gitlab.v4.objects.ProjectProtectedEnvironmentManager
        method), 390
get() (gitlab.v4.objects.ProjectProtectedTagManager
        method), 390
get() (gitlab.v4.objects.ProjectPushRulesManager
        method), 392
get() (gitlab.v4.objects.ProjectRegistryTagManager
        method), 394
get() (gitlab.v4.objects.ProjectReleaseLinkManager
        method), 395
get() (gitlab.v4.objects.ProjectReleaseManager
        method), 396
get() (gitlab.v4.objects.ProjectResourceGroupManager
        method), 398
get() (gitlab.v4.objects.ProjectSecureFileManager
        method), 400
get() (gitlab.v4.objects.ProjectServiceManager
        method), 401
get() (gitlab.v4.objects.ProjectSnippetAwardEmojiManager
        method), 403
get() (gitlab.v4.objects.ProjectSnippetDiscussionManager
        method), 404
get() (gitlab.v4.objects.ProjectSnippetDiscussionNoteManager
        method), 405
get() (gitlab.v4.objects.ProjectSnippetManager
        method), 406

```

```
get() (gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager attribute), 193
get() (gitlab.v4.objects.ProjectSnippetNoteManager attribute), 194
get() (gitlab.v4.objects.ProjectStorageManager attribute), 197
get() (gitlab.v4.objects.ProjectTagManager attribute), 198
get() (gitlab.v4.objects.ProjectTriggerManager attribute), 199
get() (gitlab.v4.objects.ProjectVariableManager attribute), 200
get() (gitlab.v4.objects.ProjectWikiManager attribute), 201
get() (gitlab.v4.objects.RegistryRepositoryManager attribute), 202
get() (gitlab.v4.objects.RunnerManager attribute), 202
get() (gitlab.v4.objects.SnippetManager attribute), 203
get() (gitlab.v4.objects.TopicManager attribute), 203
get() (gitlab.v4.objects.UserCustomAttributeManager attribute), 205
get() (gitlab.v4.objects.UserEmailManager attribute), 205
get() (gitlab.v4.objects.UserGPGKeyManager attribute), 206
get() (gitlab.v4.objects.UserImpersonationTokenManager attribute), 207
get() (gitlab.v4.objects.UserKeyManager attribute), 208
get() (gitlab.v4.objects.UserManager attribute), 208
get() (gitlab.v4.objects.UserMembershipManager attribute), 208
get() (gitlab.v4.objects.UserStatusManager attribute), 209
get() (gitlab.v4.objects.VariableManager attribute), 209
get_content_type() (in module gitlab.utils), 210
get_id() (gitlab.base.RESTObject attribute), 211
get_license() (gitlab.Gitlab method), 212
GetMixin (class in gitlab.mixins), 212
GetWithoutIdMixin (class in gitlab.mixins), 212
Gitignore (class in gitlab.v4.objects), 215
GitignoreManager (class in gitlab.v4.objects), 215
gitignores (gitlab.Gitlab attribute), 215
Gitlab (class in gitlab), 215
gitlab (gitlab.base.RESTManager attribute), 215
gitlab (gitlab.mixins.CreateMixin attribute), 216
gitlab (gitlab.mixins.CRUDMixin attribute), 216
gitlab (gitlab.mixins.DeleteMixin attribute), 216
gitlab (gitlab.mixins.GetMapping attribute), 216
gitlab (gitlab.mixins.GetWithoutIdMixin attribute), 216
gitlab (gitlab.mixins.ListMixin attribute), 216
gitlab (gitlab.mixins.NoUpdateMixin attribute), 216
gitlab (gitlab.mixins.RetrieveMixin attribute), 216
gitlab (gitlab.mixins.SetMixin attribute), 216
gitlab (gitlab.mixins.UpdateMixin attribute), 216
gitlab (gitlab.v4.objects.ApplicationAppearanceManager attribute), 217
gitlab (gitlab.v4.objects.ApplicationManager attribute), 217
gitlab (gitlab.v4.objects.ApplicationSettingsManager attribute), 217
gitlab (gitlab.v4.objects.ApplicationStatisticsManager attribute), 217
gitlab (gitlab.v4.objects.AuditEventManager attribute), 217
gitlab (gitlab.v4.objects.BroadcastMessageManager attribute), 217
gitlab (gitlab.v4.objects.BulkImportAllEntityManager attribute), 217
gitlab (gitlab.v4.objects.BulkImportEntityManager attribute), 217
gitlab (gitlab.v4.objects.BulkImportManager attribute), 217
gitlab (gitlab.v4.objects.CiLintManager attribute), 217
gitlab (gitlab.v4.objects.CurrentUserEmailManager attribute), 217
gitlab (gitlab.v4.objects.CurrentUserGPGKeyManager attribute), 217
gitlab (gitlab.v4.objects.CurrentUserKeyManager attribute), 217
gitlab (gitlab.v4.objects.CurrentUserManager attribute), 217
gitlab (gitlab.v4.objects.CurrentUserStatusManager attribute), 217
gitlab (gitlab.v4.objects.DeployKeyManager attribute), 217
gitlab (gitlab.v4.objects.DeployTokenManager attribute), 217
gitlab (gitlab.v4.objects.DockerfileManager attribute), 217
gitlab (gitlab.v4.objects.EventManager attribute), 217
gitlab (gitlab.v4.objects.FeatureManager attribute), 217
gitlab (gitlab.v4.objects.GenericPackageManager attribute), 217
gitlab (gitlab.v4.objects.GeoNodeManager attribute), 217
gitlab (gitlab.v4.objects.GitignoreManager attribute), 217
gitlab (gitlab.v4.objects.GitlabciymlManager attribute), 217
gitlab (gitlab.v4.objects.GroupAccessRequestManager attribute), 217
gitlab (gitlab.v4.objects.GroupAccessTokenManager attribute), 217
gitlab (gitlab.v4.objects.GroupAuditEventManager attribute), 217
gitlab (gitlab.v4.objects.GroupBadgeManager attribute), 217
```

gitlab (*gitlab.v4.objects.GroupBillableMemberManager attribute*), 224
gitlab (*gitlab.v4.objects.GroupBillableMemberMembershipManager attribute*), 224
gitlab (*gitlab.v4.objects.GroupBoardListManager attribute*), 226
gitlab (*gitlab.v4.objects.GroupBoardManager attribute*), 226
gitlab (*gitlab.v4.objects.GroupClusterManager attribute*), 228
gitlab (*gitlab.v4.objects.GroupCustomAttributeManager attribute*), 229
gitlab (*gitlab.v4.objects.GroupDeployTokenManager attribute*), 230
gitlab (*gitlab.v4.objects.GroupEpicAwardEmojiManager attribute*), 232
gitlab (*gitlab.v4.objects.GroupEpicDiscussionNoteManager attribute*), 233
gitlab (*gitlab.v4.objects.GroupEpicIssueManager attribute*), 234
gitlab (*gitlab.v4.objects.GroupEpicManager attribute*), 235
gitlab (*gitlab.v4.objects.GroupEpicNoteAwardEmojiManager attribute*), 236
gitlab (*gitlab.v4.objects.GroupEpicNoteManager attribute*), 237
gitlab (*gitlab.v4.objects.GroupEpicResourceLabelEventManager attribute*), 238
gitlab (*gitlab.v4.objects.GroupExportManager attribute*), 239
gitlab (*gitlab.v4.objects.GroupHookManager attribute*), 241
gitlab (*gitlab.v4.objects.GroupImportManager attribute*), 241
gitlab (*gitlab.v4.objects.GroupInvitationManager attribute*), 243
gitlab (*gitlab.v4.objects.GroupIssueManager attribute*), 243
gitlab (*gitlab.v4.objects.GroupIssuesStatisticsManager attribute*), 244
gitlab (*gitlab.v4.objects.GroupIterationManager attribute*), 245
gitlab (*gitlab.v4.objects.GroupLabelManager attribute*), 247
gitlab (*gitlab.v4.objects.GroupManager attribute*), 250
gitlab (*gitlab.v4.objects.GroupMemberAllManager attribute*), 251
gitlab (*gitlab.v4.objects.GroupMemberManager attribute*), 252
gitlab (*gitlab.v4.objects.GroupMergeRequestManager attribute*), 253
gitlab (*gitlab.v4.objects.GroupMilestoneManager attribute*), 255
gitlab (*gitlab.v4.objects.GroupNotificationSettingsManager attribute*), 256
gitlab (*gitlab.v4.objects.GroupPackageManager attribute*), 257
gitlab (*gitlab.v4.objects.GroupProjectManager attribute*), 258
gitlab (*gitlab.v4.objects.GroupPushRulesManager attribute*), 259
gitlab (*gitlab.v4.objects.GroupRegistryRepositoryManager attribute*), 259
gitlab (*gitlab.v4.objects.GroupRunnerManager attribute*), 260
gitlab (*gitlab.v4.objects.GroupVariableManager attribute*), 263
gitlab (*gitlab.v4.objects.GroupWikiManager attribute*), 264
gitlab (*gitlab.v4.objects.HookManager attribute*), 265
gitlab (*gitlab.v4.objects.IssueManager attribute*), 266
gitlab (*gitlab.v4.objects.IssuesStatisticsManager attribute*), 267
gitlab (*gitlab.v4.objects.KeyManager attribute*), 268
gitlab (*gitlab.v4.objects.LDAPGroupManager attribute*), 268
gitlab (*gitlab.v4.objects.LicenseManager attribute*), 270
gitlab (*gitlab.v4.objects.MergeRequestManager attribute*), 271
gitlab (*gitlab.v4.objects.NamespaceManager attribute*), 272
gitlab (*gitlab.v4.objects.NotificationSettingsManager attribute*), 273
gitlab (*gitlab.v4.objects.PagesDomainManager attribute*), 274
gitlab (*gitlab.v4.objects.PersonalAccessTokenManager attribute*), 275
gitlab (*gitlab.v4.objects.ProjectAccessRequestManager attribute*), 283
gitlab (*gitlab.v4.objects.ProjectAccessTokenManager attribute*), 284
gitlab (*gitlab.v4.objects.ProjectAdditionalStatisticsManager attribute*), 285
gitlab (*gitlab.v4.objects.ProjectApprovalManager attribute*), 285
gitlab (*gitlab.v4.objects.ProjectApprovalRuleManager attribute*), 286
gitlab (*gitlab.v4.objects.ProjectArtifactManager attribute*), 287
gitlab (*gitlab.v4.objects.ProjectAuditEventManager attribute*), 289
gitlab (*gitlab.v4.objects.ProjectAuditManager attribute*), 290
gitlab (*gitlab.v4.objects.ProjectBadgeManager attribute*), 291
gitlab (*gitlab.v4.objects.ProjectBoardListManager attribute*), 292

gitlab (*gitlab.v4.objects.ProjectBoardManager* attribute), 292
gitlab (*gitlab.v4.objects.ProjectBranchManager* attribute), 293
gitlab (*gitlab.v4.objects.ProjectCiLintManager* attribute), 294
gitlab (*gitlab.v4.objects.ProjectClusterManager* attribute), 296
gitlab (*gitlab.v4.objects.ProjectCommitCommentManager* attribute), 299
gitlab (*gitlab.v4.objects.ProjectCommitDiscussionManager* attribute), 300
gitlab (*gitlab.v4.objects.ProjectCommitDiscussionNoteManager* attribute), 301
gitlab (*gitlab.v4.objects.ProjectCommitManager* attribute), 302
gitlab (*gitlab.v4.objects.ProjectCommitStatusManager* attribute), 303
gitlab (*gitlab.v4.objects.ProjectCustomAttributeManager* attribute), 304
gitlab (*gitlab.v4.objects.ProjectDeploymentManager* attribute), 307
gitlab (*gitlab.v4.objects.ProjectDeploymentMergeRequestManager* attribute), 308
gitlab (*gitlab.v4.objects.ProjectDeployTokenManager* attribute), 305
gitlab (*gitlab.v4.objects.ProjectEnvironmentManager* attribute), 309
gitlab (*gitlab.v4.objects.ProjectEventManager* attribute), 310
gitlab (*gitlab.v4.objects.ProjectExportManager* attribute), 311
gitlab (*gitlab.v4.objects.ProjectFileManager* attribute), 314
gitlab (*gitlab.v4.objects.ProjectForkManager* attribute), 316
gitlab (*gitlab.v4.objects.ProjectHookManager* attribute), 318
gitlab (*gitlab.v4.objects.ProjectImportManager* attribute), 318
gitlab (*gitlab.v4.objects.ProjectIntegrationManager* attribute), 319
gitlab (*gitlab.v4.objects.ProjectInvitationManager* attribute), 321
gitlab (*gitlab.v4.objects.ProjectIssueAwardEmojiManager* attribute), 323
gitlab (*gitlab.v4.objects.ProjectIssueDiscussionManager* attribute), 324
gitlab (*gitlab.v4.objects.ProjectIssueDiscussionNoteManager* attribute), 325
gitlab (*gitlab.v4.objects.ProjectIssueLinkManager* attribute), 326
gitlab (*gitlab.v4.objects.ProjectIssueManager* attribute), 328
at- gitlab (*gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager* attribute), 329
at- gitlab (*gitlab.v4.objects.ProjectIssueNoteManager* attribute), 330
at- gitlab (*gitlab.v4.objects.ProjectIssueResourceIterationEventManager* attribute), 331
at- gitlab (*gitlab.v4.objects.ProjectIssueResourceLabelEventManager* attribute), 332
gitlab (*gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager* attribute), 332
gitlab (*gitlab.v4.objects.ProjectIssueResourceStateEventManager* attribute), 333
gitlab (*gitlab.v4.objects.ProjectIssueWeightEventManager* attribute), 334
gitlab (*gitlab.v4.objects.ProjectIssuesStatisticsManager* attribute), 335
gitlab (*gitlab.v4.objects.ProjectIterationManager* attribute), 335
gitlab (*gitlab.v4.objects.ProjectJobManager* attribute), 339
gitlab (*gitlab.v4.objects.ProjectKeyManager* attribute), 340
gitlab (*gitlab.v4.objects.ProjectLabelManager* attribute), 342
gitlab (*gitlab.v4.objects.ProjectManager* attribute), 348
gitlab (*gitlab.v4.objects.ProjectMemberAllManager* attribute), 353
gitlab (*gitlab.v4.objects.ProjectMemberManager* attribute), 353
gitlab (*gitlab.v4.objects.ProjectMergeRequestApprovalManager* attribute), 358
gitlab (*gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager* attribute), 360
gitlab (*gitlab.v4.objects.ProjectMergeRequestApprovalStateManager* attribute), 361
gitlab (*gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager* attribute), 362
gitlab (*gitlab.v4.objects.ProjectMergeRequestDiffManager* attribute), 363
gitlab (*gitlab.v4.objects.ProjectMergeRequestDiscussionManager* attribute), 364
gitlab (*gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager* attribute), 365
gitlab (*gitlab.v4.objects.ProjectMergeRequestManager* attribute), 367
gitlab (*gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager* attribute), 368
gitlab (*gitlab.v4.objects.ProjectMergeRequestNoteManager* attribute), 369
gitlab (*gitlab.v4.objects.ProjectMergeRequestPipelineManager* attribute), 370
gitlab (*gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager* attribute), 371
gitlab (*gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager* attribute), 372

attribute), 371

`gitlab`(`gitlab.v4.objects.ProjectMergeRequestResourceStage` *attribute*), 372

`gitlab`(`gitlab.v4.objects.ProjectMergeTrainManager` *attribute*), 373

`gitlab`(`gitlab.v4.objects.ProjectMilestoneManager` *attribute*), 375

`gitlab` (`gitlab.v4.objects.ProjectNoteManager` *attribute*), 376

`gitlab`(`gitlab.v4.objects.ProjectNotificationSettingsManager` *attribute*), 377

`gitlab` (`gitlab.v4.objects.ProjectPackageFileManager` *attribute*), 378

`gitlab` (`gitlab.v4.objects.ProjectPackageManager` *attribute*), 378

`gitlab`(`gitlab.v4.objects.ProjectPagesDomainManager` *attribute*), 380

`gitlab`(`gitlab.v4.objects.ProjectPipelineBridgeManager` *attribute*), 381

`gitlab`(`gitlab.v4.objects.ProjectPipelineJobManager` *attribute*), 381

`gitlab`(`gitlab.v4.objects.ProjectPipelineManager` *attribute*), 383

`gitlab`(`gitlab.v4.objects.ProjectPipelineScheduleManager` *attribute*), 384

`gitlab`(`gitlab.v4.objects.ProjectPipelineSchedulePipelineManager` *attribute*), 385

`gitlab`(`gitlab.v4.objects.ProjectPipelineScheduleVariableManager` *attribute*), 386

`gitlab`(`gitlab.v4.objects.ProjectPipelineTestReportManager` *attribute*), 386

`gitlab`(`gitlab.v4.objects.ProjectPipelineTestReportSummaryManager` *attribute*), 387

`gitlab`(`gitlab.v4.objects.ProjectPipelineVariableManager` *attribute*), 388

`gitlab`(`gitlab.v4.objects.ProjectProtectedBranchManager` *attribute*), 389

`gitlab`(`gitlab.v4.objects.ProjectProtectedEnvironmentManager` *attribute*), 390

`gitlab`(`gitlab.v4.objects.ProjectProtectedTagManager` *attribute*), 391

`gitlab`(`gitlab.v4.objects.ProjectPushRulesManager` *attribute*), 392

`gitlab`(`gitlab.v4.objects.ProjectRegistryRepositoryManager` *attribute*), 393

`gitlab`(`gitlab.v4.objects.ProjectRegistryTagManager` *attribute*), 394

`gitlab`(`gitlab.v4.objects.ProjectReleaseLinkManager` *attribute*), 395

`gitlab`(`gitlab.v4.objects.ProjectReleaseManager` *attribute*), 396

`gitlab`(`gitlab.v4.objects.ProjectRemoteMirrorManager` *attribute*), 397

`gitlab`(`gitlab.v4.objects.ProjectResourceGroupManager` *attribute*), 398

`gitlab`(`gitlab.v4.objects.ProjectResourceGroupUpcomingJobManager` *attribute*), 399

`gitlab`(`gitlab.v4.objects.ProjectRunnerManager` *attribute*), 399

`gitlab`(`gitlab.v4.objects.ProjectSecureFileManager` *attribute*), 401

`gitlab` (`gitlab.v4.objects.ProjectServiceManager` *attribute*), 402

`gitlab`(`gitlab.v4.objects.ProjectSnippetAwardEmojiManager` *attribute*), 403

`gitlab`(`gitlab.v4.objects.ProjectSnippetDiscussionManager` *attribute*), 404

`gitlab`(`gitlab.v4.objects.ProjectSnippetDiscussionNoteManager` *attribute*), 405

`gitlab` (`gitlab.v4.objects.ProjectSnippetManager` *attribute*), 406

`gitlab`(`gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager` *attribute*), 407

`gitlab`(`gitlab.v4.objects.ProjectSnippetNoteManager` *attribute*), 408

`gitlab` (`gitlab.v4.objects.ProjectStorageManager` *attribute*), 409

`gitlab`(`gitlab.v4.objects.ProjectTagManager` *attribute*), 410

`gitlab`(`gitlab.v4.objects.ProjectTriggerManager` *attribute*), 411

`gitlab`(`gitlab.v4.objects.ProjectUserManager` *attribute*), 411

`gitlab`(`gitlab.v4.objects.ProjectVariableManager` *attribute*), 413

`gitlab`(`gitlab.v4.objects.ProjectWikiManager` *attribute*), 414

`gitlab`(`gitlab.v4.objects.RegistryRepositoryManager` *attribute*), 414

`gitlab`(`gitlab.v4.objects.RunnerAllManager` *attribute*), 419

`gitlab`(`gitlab.v4.objects.RunnerJobManager` *attribute*), 420

`gitlab`(`gitlab.v4.objects.RunnerManager` *attribute*), 421

`gitlab`(`gitlab.v4.objects.SharedProjectManager` *attribute*), 422

`gitlab`(`gitlab.v4.objects.SidekiqManager` *attribute*), 423

`gitlab`(`gitlab.v4.objects.SnippetManager` *attribute*), 425

`gitlab`(`gitlab.v4.objects.StartedProjectManager` *attribute*), 427

`gitlab`(`gitlab.v4.objects.TodoManager` *attribute*), 428

`gitlab`(`gitlab.v4.objects.TopicManager` *attribute*), 429

`gitlab`(`gitlab.v4.objects.UserActivitiesManager` *attribute*), 433

`gitlab`(`gitlab.v4.objects.UserCustomAttributesManager` *attribute*), 434

`gitlab`(`gitlab.v4.objects.UserEmailManager` *attribute*), 435

```
gitlab (gitlab.v4.objects.UserEventManager attribute), 435
gitlab (gitlab.v4.objects.UserGPGKeyManager attribute), 436
gitlab (gitlab.v4.objects.UserIdentityProviderManager attribute), 437
gitlab (gitlab.v4.objects.UserImpersonationTokenManager attribute), 438
gitlab (gitlab.v4.objects.UserKeyManager attribute), 439
gitlab (gitlab.v4.objects.UserManager attribute), 441
gitlab (gitlab.v4.objects.UserMembershipManager attribute), 442
gitlab (gitlab.v4.objects.UserPersonalAccessTokenManager attribute), 442
gitlab (gitlab.v4.objects.UserProjectManager attribute), 444
gitlab (gitlab.v4.objects.UserStatusManager attribute), 445
gitlab (gitlab.v4.objects.VariableManager attribute), 446
gitlab command line option
  --api-version, 485
  --config-file, 484
  --debug, 484
  --fancy, 484
  --fields, 485
  --gitlab, 484
  --help, 484
  --job-token, 485
  --oauth-token, 485
  --order-by, 485
  --output, 484
  --pagination, 485
  --per-page, 485
  --private-token, 485
  --server-url, 485
  --ssl-verify, 485
  --timeout, 485
  --user-agent, 485
  --verbose, 484
  --version, 484
  -c, 484
  -d, 484
  -f, 485
  -g, 484
  -h, 484
  -o, 484
  -v, 484
gitlab.base
  module, 447
gitlab.cli
  module, 449
gitlab.config
  module, 450
gitlab.const
  module, 451
gitlab.exceptions
  module, 452
gitlab.mixins
  module, 470
gitlab.utils
  module, 478
gitlab.v4
  module, 447
gitlab.v4.objects
  module, 192
gitlab_resource_to_cls() (in module gitlab.cli), 449
gitlab-application command line option
  --help, 485
  -h, 485
gitlab-application-appearance command line option
  --help, 486
  -h, 486
gitlab-application-appearance-get command line option
  --help, 487
  --sudo, 487
  -h, 487
gitlab-application-appearance-update command line option
  --description, 487
  --email-header-and-footer-enabled, 487
  --favicon, 487
  --footer-message, 487
  --header-logo, 487
  --header-message, 487
  --help, 487
  --logo, 487
  --message-background-color, 487
  --message-font-color, 487
  --new-project-guidelines, 487
  --sudo, 487
  --title, 487
  -h, 487
gitlab-application-create command line option
  --confidential, 486
  --help, 485
  --name, 486
  --redirect-uri, 486
  --scopes, 486
  --sudo, 485
  -h, 485
gitlab-application-delete command line option
```

```

--help, 486
--id, 486
--sudo, 486
-h, 486
gitlab-application-list command line option
--all, 486
--get-all, 486
--help, 486
--page, 486
--per-page, 486
--sudo, 486
-h, 486
gitlab-application-settings command line
    option
--help, 488
-h, 488
gitlab-application-settings-get command
    line option
--help, 488
--sudo, 488
-h, 488
gitlab-application-settings-update command
    line option
--after-sign-out-path, 491
--allow-local-requests-from-hooks-and-services, -plantuml-url, 491
--allow-local-requests-from-system-hooks,
    491
--allow-local-requests-from-web-hooks-and-services, -key-restriction, 491
--asset-proxy-allowlist, 491
--asset-proxy-enabled, 491
--asset-proxy-url, 491
--asset-proxy-whitelist, 491
--container-registry-token-expire-delay,
    491
--created-at, 490
--default-branch-protection, 490
--default-group-visibility, 490
--default-project-visibility, 490
--default-projects-limit, 490
--default-snippet-visibility, 490
--disabled-oauth-sign-in-sources, 490
--domain-allowlist, 490
--domain-blacklist, 490
--domain-blacklist-enabled, 490
--domain-denylist, 490
--domain-denylist-enabled, 490
--domain-whitelist, 490
--dsa-key-restriction, 491
--ecdsa-key-restriction, 491
--ed25519-key-restriction, 491
--enforce-terms, 491
--external-authorization-service-default-label,
    490
--external-authorization-service-enabled,
    490
--external-authorization-service-timeout,
    490
--external-authorization-service-url, 490
--file-template-project-id, 491
--first-day-of-week, 491
--geo-node-allowed-ips, 491
--gravatar-enabled, 490
--help, 489
--home-page-url, 490
--id, 490
--import-sources, 490
--instance-statistics-visibility-private,
    491
--local-markdown-version, 491
--max-attachment-size, 490
--outbound-local-requests-whitelist, 490
--password-authentication-enabled-for-web,
    490
--performance-bar-allowed-group-id, 491
--plantuml-enabled, 491
--polling-interval-multiplier, 491
--repository-storages, 491
--restricted-visibility-levels, 490
--session-expire-delay, 490
--sign-in-text, 490
--signup-enabled, 490
--sudo, 490
--terminal-max-session-time, 491
--terms, 491
--updated-at, 490
--user-oauth-applications, 491
--user-show-add-ssh-key-message, 491
-h, 489
gitlab-application-statistics command line
    option
--help, 492
-h, 492
gitlab-application-statistics-get command
    line option
--help, 492
--sudo, 492
-h, 492
gitlab-audit-event command line option
--help, 492
-h, 492
gitlab-audit-event-get command line option
--help, 492
--id, 492

```

```
--sudo, 492
-h, 492
gitlab-audit-event-list command line option
--all, 493
--created-after, 492
--created-before, 492
--entity-id, 493
--entity-type, 493
--get-all, 493
--help, 492
--page, 493
--per-page, 493
--sudo, 492
-h, 492
gitlab-broadcast-message command line
    option
--help, 493
-h, 493
gitlab-broadcast-message-create command
    line option
--color, 493
--ends-at, 493
--font, 493
--help, 493
--message, 493
--starts-at, 493
--sudo, 493
--target-access-levels, 493
-h, 493
gitlab-broadcast-message-delete command
    line option
--help, 494
--id, 494
--sudo, 494
-h, 494
gitlab-broadcast-message-get command line
    option
--help, 494
--id, 494
--sudo, 494
-h, 494
gitlab-broadcast-message-list command line
    option
--all, 494
--get-all, 494
--help, 494
--page, 494
--per-page, 494
--sudo, 494
-h, 494
gitlab-broadcast-message-update command
    line option
--color, 495
--ends-at, 495
--font, 495
--help, 494
--id, 495
--message, 495
--starts-at, 495
--sudo, 495
--target-access-levels, 495
-h, 494
gitlab-bulk-import command line option
--help, 495
-h, 495
gitlab-bulk-import-all-entity command line
    option
--help, 496
-h, 496
gitlab-bulk-import-all-entity-list command
    line option
--all, 496
--get-all, 496
--help, 496
--page, 496
--per-page, 496
--sort, 496
--status, 496
--sudo, 496
-h, 496
gitlab-bulk-import-create command line
    option
--configuration, 495
--entities, 495
--help, 495
--sudo, 495
-h, 495
gitlab-bulk-import-entity command line
    option
--help, 497
-h, 497
gitlab-bulk-import-entity-get command line
    option
--bulk-import-id, 497
--help, 497
--id, 497
--sudo, 497
-h, 497
gitlab-bulk-import-entity-list command line
    option
--all, 497
--bulk-import-id, 497
--get-all, 497
--help, 497
--page, 497
--per-page, 497
--sort, 497
--status, 497
```

```
--sudo, 497
-h, 497
gitlab-bulk-import-get command line option
--help, 495
--id, 495
--sudo, 495
-h, 495
gitlab-bulk-import-list command line option
--all, 496
--get-all, 496
--help, 496
--page, 496
--per-page, 496
--sort, 496
--status, 496
--sudo, 496
-h, 496
gitlab-ci-lint command line option
--help, 498
-h, 498
gitlab-ci-lint-create command line option
--content, 498
--help, 498
--include-jobs, 498
--include-merged-yaml, 498
--sudo, 498
-h, 498
gitlab-ci-lint-validate command line option
--content, 498
--help, 498
--include-jobs, 498
--include-merged-yaml, 498
-h, 498
gitlab-current-user command line option
--help, 498
-h, 498
gitlab-current-user-email command line
    option
--help, 499
-h, 499
gitlab-current-user-email-create command
    line option
--email, 499
--help, 499
--sudo, 499
-h, 499
gitlab-current-user-email-delete command
    line option
--help, 499
--id, 499
--sudo, 499
-h, 499
gitlab-current-user-email-get command line
    option
--help, 499
--id, 499
--sudo, 499
-h, 499
gitlab-current-user-email-list command line
    option
--all, 500
--get-all, 500
--help, 500
--page, 500
--per-page, 500
--sudo, 500
-h, 500
gitlab-current-user-get command line option
--help, 499
--sudo, 499
-h, 499
gitlab-current-user-gpg-key command line
    option
--help, 500
-h, 500
gitlab-current-user-gpg-key-create command
    line option
--help, 500
--key, 500
--sudo, 500
-h, 500
gitlab-current-user-gpg-key-delete command
    line option
--help, 500
--id, 500
--sudo, 500
-h, 500
gitlab-current-user-gpg-key-get command
    line option
--help, 501
--id, 501
--sudo, 501
-h, 501
gitlab-current-user-gpg-key-list command
    line option
--all, 501
--get-all, 501
--help, 501
--page, 501
--per-page, 501
--sudo, 501
-h, 501
gitlab-current-user-key command line option
--help, 501
-h, 501
gitlab-current-user-key-create command line
    option
--help, 501
```

```
--key, 501
--sudo, 501
--title, 501
-h, 501
gitlab-current-user-key-delete command line
    option
--help, 502
--id, 502
--sudo, 502
-h, 502
gitlab-current-user-key-get command line
    option
--help, 502
--id, 502
--sudo, 502
-h, 502
gitlab-current-user-key-list command line
    option
--all, 502
--get-all, 502
--help, 502
--page, 502
--per-page, 502
--sudo, 502
-h, 502
gitlab-current-user-status command line
    option
--help, 502
-h, 502
gitlab-current-user-status-get command line
    option
--help, 503
--sudo, 503
-h, 503
gitlab-current-user-status-update command
    line option
--emoji, 503
--help, 503
--message, 503
--sudo, 503
-h, 503
gitlab-deploy-key command line option
--help, 503
-h, 503
gitlab-deploy-key-list command line option
--all, 503
--get-all, 503
--help, 503
--page, 503
--per-page, 503
--sudo, 503
-h, 503
gitlab-deploy-token command line option
--help, 504
gitlab-deploy-token-list command line
    option
--all, 504
--get-all, 504
--help, 504
--page, 504
--per-page, 504
--sudo, 504
-h, 504
gitlab-dockerfile command line option
--help, 504
-h, 504
gitlab-dockerfile-get command line option
--help, 504
--name, 504
--sudo, 504
-h, 504
gitlab-dockerfile-list command line option
--all, 505
--get-all, 505
--help, 505
--page, 505
--per-page, 505
--sudo, 505
-h, 505
gitlab-event command line option
--help, 505
-h, 505
gitlab-event-list command line option
--action, 505
--after, 505
--all, 506
--before, 505
--get-all, 505
--help, 505
--page, 505
--per-page, 505
--sort, 505
--sudo, 505
--target-type, 505
-h, 505
gitlab-feature command line option
--help, 506
-h, 506
gitlab-feature-delete command line option
--help, 506
--name, 506
--sudo, 506
-h, 506
gitlab-feature-list command line option
--all, 506
--get-all, 506
--help, 506
```

```

--page, 506
--per-page, 506
--sudo, 506
-h, 506
gitlab-generic-package command line option
--help, 507
-h, 507
gitlab-generic-package-download command
    line option
--file-name, 507
--help, 507
--package-name, 507
--package-version, 507
--project-id, 507
--sudo, 507
-h, 507
gitlab-generic-package-upload command line
    option
--file-name, 507
--help, 507
--package-name, 507
--package-version, 507
--path, 507
--project-id, 507
--sudo, 507
-h, 507
gitlab-geo-node command line option
--help, 508
-h, 508
gitlab-geo-node-current-failures command
    line option
--help, 508
--id, 508
-h, 508
gitlab-geo-node-delete command line option
--help, 508
--id, 508
--sudo, 508
-h, 508
gitlab-geo-node-get command line option
--help, 508
--id, 508
--sudo, 508
-h, 508
gitlab-geo-node-list command line option
--all, 509
--get-all, 509
--help, 509
--page, 509
--per-page, 509
--sudo, 509
-h, 509
gitlab-geo-node-repair command line option
--help, 509
--id, 509
-h, 509
gitlab-geo-node-status command line option
--help, 509
--id, 509
-h, 509
gitlab-geo-node-update command line option
--enabled, 509
--files-max-capacity, 510
--help, 509
--id, 509
--repos-max-capacity, 510
--sudo, 509
--url, 510
-h, 509
gitlab-gitignore command line option
--help, 510
-h, 510
gitlab-gitignore-get command line option
--help, 510
--name, 510
--sudo, 510
-h, 510
gitlab-gitignore-list command line option
--all, 510
--get-all, 510
--help, 510
--page, 510
--per-page, 510
--sudo, 510
-h, 510
gitlab-gitlabciyml command line option
--help, 511
-h, 511
gitlab-gitlabciyml-get command line option
--help, 511
--name, 511
--sudo, 511
-h, 511
gitlab-gitlabciyml-list command line option
--all, 511
--get-all, 511
--help, 511
--page, 511
--per-page, 511
--sudo, 511
-h, 511
gitlab-group command line option
--help, 512
-h, 512
gitlab-group-access-request command line
    option
--help, 518
-h, 518

```

```
gitlab-group-access-request-approve command
    line option
    --access-level, 518
    --group-id, 518
    --help, 518
    --id, 518
    --sudo, 518
    -h, 518
gitlab-group-access-request-create command
    line option
    --group-id, 519
    --help, 519
    --sudo, 519
    -h, 519
gitlab-group-access-request-delete command
    line option
    --group-id, 519
    --help, 519
    --id, 519
    --sudo, 519
    -h, 519
gitlab-group-access-request-list command
    line option
    --all, 519
    --get-all, 519
    --group-id, 519
    --help, 519
    --page, 519
    --per-page, 519
    --sudo, 519
    -h, 519
gitlab-group-access-token command line
    option
    --help, 520
    -h, 520
gitlab-group-access-token-create command
    line option
    --access-level, 520
    --expires-at, 520
    --group-id, 520
    --help, 520
    --name, 520
    --scopes, 520
    --sudo, 520
    -h, 520
gitlab-group-access-token-delete command
    line option
    --group-id, 520
    --help, 520
    --id, 520
    --sudo, 520
    -h, 520
gitlab-group-access-token-list command line
    option
    --all, 521
    --get-all, 521
    --group-id, 521
    --help, 520
    --page, 521
    --per-page, 521
    --sudo, 520
    -h, 520
gitlab-group-add-ldap-group-link command
    line option
    --cn, 512
    --group-access, 512
    --help, 512
    --id, 512
    --provider, 512
    -h, 512
gitlab-group-audit-event command line
    option
    --help, 521
    -h, 521
gitlab-group-audit-event-get command line
    option
    --group-id, 521
    --help, 521
    --id, 521
    --sudo, 521
    -h, 521
gitlab-group-audit-event-list command line
    option
    --all, 522
    --created-after, 521
    --created-before, 521
    --get-all, 522
    --group-id, 521
    --help, 521
    --page, 522
    --per-page, 522
    --sudo, 521
    -h, 521
gitlab-group-badge command line option
    --help, 522
    -h, 522
gitlab-group-badge-create command line
    option
    --group-id, 522
    --help, 522
    --image-url, 522
    --link-url, 522
    --sudo, 522
    -h, 522
gitlab-group-badge-delete command line
    option
    --group-id, 522
    --help, 522
```

```

--id, 522
--sudo, 522
-h, 522
gitlab-group-badge-get command line option
--group-id, 523
--help, 523
--id, 523
--sudo, 523
-h, 523
gitlab-group-badge-list command line option
--all, 523
--get-all, 523
--group-id, 523
--help, 523
--page, 523
--per-page, 523
--sudo, 523
-h, 523
gitlab-group-badge-render command line
    option
--group-id, 523
--help, 523
--id, 523
--image-url, 523
--link-url, 523
--sudo, 523
-h, 523
gitlab-group-badge-update command line
    option
--group-id, 524
--help, 524
--id, 524
--image-url, 524
--link-url, 524
--sudo, 524
-h, 524
gitlab-group-billable-member command line
    option
--help, 524
-h, 524
gitlab-group-billable-member-delete command
    line option
--group-id, 524
--help, 524
--id, 524
--sudo, 524
-h, 524
gitlab-group-billable-member-list command
    line option
--all, 525
--get-all, 525
--group-id, 525
--help, 524
--page, 525
--per-page, 525
--search, 525
--sort, 525
--sudo, 524
-h, 524
gitlab-group-billable-member-membership
    command line option
--help, 525
-h, 525
gitlab-group-billable-member-membership-list
    command line option
--all, 525
--get-all, 525
--group-id, 525
--help, 525
--page, 525
--per-page, 525
--sudo, 525
--user-id, 525
-h, 525
gitlab-group-board command line option
--help, 526
-h, 526
gitlab-group-board-create command line
    option
--group-id, 526
--help, 526
--name, 526
--sudo, 526
-h, 526
gitlab-group-board-delete command line
    option
--group-id, 526
--help, 526
--id, 526
--sudo, 526
-h, 526
gitlab-group-board-get command line option
--group-id, 526
--help, 526
--id, 526
--sudo, 526
-h, 526
gitlab-group-board-list command line option
--all, 527
--get-all, 527
--group-id, 527
--help, 527
--page, 527
--per-page, 527
--sudo, 527
-h, 527
gitlab-group-board-list-create command line
    option

```

```
--board-id, 528
--group-id, 528
--help, 528
--sudo, 528
-h, 528
gitlab-group-board-list-delete command line
    option
    --board-id, 528
    --group-id, 528
    --help, 528
    --id, 528
    --sudo, 528
    -h, 528
gitlab-group-board-list-get command line
    option
    --board-id, 528
    --group-id, 528
    --help, 528
    --id, 528
    --sudo, 528
    -h, 528
gitlab-group-board-list-list command line
    option
    --all, 529
    --board-id, 529
    --get-all, 529
    --group-id, 529
    --help, 529
    --page, 529
    --per-page, 529
    --sudo, 529
    -h, 529
gitlab-group-board-list-update command line
    option
    --board-id, 529
    --group-id, 529
    --help, 529
    --id, 529
    --position, 529
    --sudo, 529
    -h, 529
gitlab-group-board-update command line
    option
    --group-id, 527
    --help, 527
    --id, 527
    --sudo, 527
    -h, 527
gitlab-group-cluster command line option
    --help, 529
    -h, 529
gitlab-group-cluster-create command line
    option
    --domain, 530
    --enabled, 530
    --environment-scope, 530
    --group-id, 530
    --help, 530
    --managed, 530
    --name, 530
    --platform-kubernetes-attributes, 530
    --sudo, 530
    -h, 530
gitlab-group-cluster-delete command line
    option
    --group-id, 530
    --help, 530
    --id, 530
    --sudo, 530
    -h, 530
gitlab-group-cluster-get command line
    option
    --group-id, 530
    --help, 530
    --id, 530
    --sudo, 530
    -h, 530
gitlab-group-cluster-list command line
    option
    --all, 531
    --get-all, 531
    --group-id, 531
    --help, 531
    --page, 531
    --per-page, 531
    --sudo, 531
    -h, 531
gitlab-group-cluster-update command line
    option
    --domain, 531
    --environment-scope, 531
    --group-id, 531
    --help, 531
    --id, 531
    --management-project-id, 531
    --name, 531
    --platform-kubernetes-attributes, 531
    --sudo, 531
    -h, 531
gitlab-group-create command line option
    --auto-devops-enabled, 513
    --avatar, 513
    --default-branch-protection, 513
    --description, 513
    --emails-disabled, 513
    --extra-shared-runners-minutes-limit, 513
    --help, 512
    --lfs-enabled, 513
```

```
--membership-lock, 513
--mentions-disabled, 513
--name, 513
--parent-id, 513
--path, 513
--project-creation-level, 513
--request-access-enabled, 513
--require-two-factor-authentication, 513
--share-with-group-lock, 513
--shared-runners-minutes-limit, 513
--subgroup-creation-level, 513
--sudo, 512
--two-factor-grace-period, 513
--visibility, 513
-h, 512
gitlab-group-custom-attribute command line
    option
    --help, 532
    -h, 532
gitlab-group-custom-attribute-delete
    command line option
    --group-id, 532
    --help, 532
    --key, 532
    --sudo, 532
    -h, 532
gitlab-group-custom-attribute-get command
    line option
    --group-id, 532
    --help, 532
    --key, 532
    --sudo, 532
    -h, 532
gitlab-group-custom-attribute-list command
    line option
    --all, 533
    --get-all, 532
    --group-id, 532
    --help, 532
    --page, 532
    --per-page, 532
    --sudo, 532
    -h, 532
gitlab-group-delete command line option
    --help, 513
    --id, 513
    --sudo, 513
    -h, 513
gitlab-group-delete-ldap-group-link command
    line option
    --cn, 514
    --help, 514
    --id, 514
    --provider, 514
                                         -h, 514
                                         gitlab-group-deploy-token command line
                                         option
                                         --help, 533
                                         -h, 533
                                         gitlab-group-deploy-token-create command
                                         line option
                                         --expires-at, 533
                                         --group-id, 533
                                         --help, 533
                                         --name, 533
                                         --scopes, 533
                                         --sudo, 533
                                         --username, 533
                                         -h, 533
                                         gitlab-group-deploy-token-delete command
                                         line option
                                         --group-id, 533
                                         --help, 533
                                         --id, 533
                                         --sudo, 533
                                         -h, 533
                                         gitlab-group-deploy-token-get command line
                                         option
                                         --group-id, 534
                                         --help, 534
                                         --id, 534
                                         --sudo, 534
                                         -h, 534
                                         gitlab-group-deploy-token-list command line
                                         option
                                         --all, 534
                                         --get-all, 534
                                         --group-id, 534
                                         --help, 534
                                         --page, 534
                                         --per-page, 534
                                         --scopes, 534
                                         --sudo, 534
                                         -h, 534
                                         gitlab-group-descendant-group command line
                                         option
                                         --help, 534
                                         -h, 534
                                         gitlab-group-descendant-group-list command
                                         line option
                                         --all, 535
                                         --all-available, 535
                                         --get-all, 535
                                         --group-id, 535
                                         --help, 535
                                         --min-access-level, 535
                                         --order-by, 535
                                         --owned, 535
```

```
--page, 535
--per-page, 535
--search, 535
--skip-groups, 535
--sort, 535
--statistics, 535
--sudo, 535
--with-custom-attributes, 535
-h, 535
gitlab-group-epic command line option
--help, 536
-h, 536
gitlab-group-epic-award-emoji command line
    option
--help, 538
-h, 538
gitlab-group-epic-award-emoji-create
    command line option
--epic-iid, 538
--group-id, 538
--help, 538
--name, 538
--sudo, 538
-h, 538
gitlab-group-epic-award-emoji-delete
    command line option
--epic-iid, 539
--group-id, 539
--help, 539
--id, 539
--sudo, 539
-h, 539
gitlab-group-epic-award-emoji-get command
    line option
--epic-iid, 539
--group-id, 539
--help, 539
--id, 539
--sudo, 539
-h, 539
gitlab-group-epic-award-emoji-list command
    line option
--all, 540
--epic-iid, 539
--get-all, 539
--group-id, 539
--help, 539
--page, 539
--per-page, 539
--sudo, 539
-h, 539
gitlab-group-epic-create command line
    option
--description, 536
--end-date, 536
--group-id, 536
--help, 536
--labels, 536
--start-date, 536
--sudo, 536
--title, 536
-h, 536
gitlab-group-epic-delete command line
    option
--group-id, 536
--help, 536
--iid, 536
--sudo, 536
-h, 536
gitlab-group-epic-discussion-note command
    line option
--help, 540
-h, 540
gitlab-group-epic-discussion-note-create
    command line option
--body, 540
--created-at, 540
--discussion-id, 540
--epic-id, 540
--group-id, 540
--help, 540
--sudo, 540
-h, 540
gitlab-group-epic-discussion-note-delete
    command line option
--discussion-id, 540
--epic-id, 540
--group-id, 540
--help, 540
--id, 541
--sudo, 540
-h, 540
gitlab-group-epic-discussion-note-get
    command line option
--discussion-id, 541
--epic-id, 541
--group-id, 541
--help, 541
--id, 541
--sudo, 541
-h, 541
gitlab-group-epic-discussion-note-update
    command line option
--body, 541
--discussion-id, 541
--epic-id, 541
--group-id, 541
--help, 541
```

```

--id, 541
--sudo, 541
-h, 541
gitlab-group-epic-get command line option
--group-id, 537
--help, 537
--iid, 537
--sudo, 537
-h, 537
gitlab-group-epic-issue command line option
--help, 542
-h, 542
gitlab-group-epic-issue-create command line
    option
--epic-iid, 542
--group-id, 542
--help, 542
--issue-id, 542
--sudo, 542
-h, 542
gitlab-group-epic-issue-delete command line
    option
--epic-iid, 542
--epic-issue-id, 542
--group-id, 542
--help, 542
--sudo, 542
-h, 542
gitlab-group-epic-issue-list command line
    option
--all, 543
--epic-iid, 542
--get-all, 543
--group-id, 542
--help, 542
--page, 543
--per-page, 543
--sudo, 542
-h, 542
gitlab-group-epic-issue-update command line
    option
--epic-iid, 543
--epic-issue-id, 543
--group-id, 543
--help, 543
--move-after-id, 543
--move-before-id, 543
--sudo, 543
-h, 543
gitlab-group-epic-list command line option
--all, 537
--author-id, 537
--get-all, 537
--group-id, 537
--help, 537
--labels, 537
--order-by, 537
--page, 537
--per-page, 537
--search, 537
--sort, 537
--sudo, 537
-h, 537
gitlab-group-epic-note command line option
--help, 543
-h, 543
gitlab-group-epic-note-award-emoji command
    line option
--help, 545
-h, 545
gitlab-group-epic-note-award-emoji-create
    command line option
--epic-iid, 545
--group-id, 545
--help, 545
--name, 545
--note-id, 545
--sudo, 545
-h, 545
gitlab-group-epic-note-award-emoji-delete
    command line option
--epic-iid, 546
--group-id, 546
--help, 546
--id, 546
--note-id, 546
--sudo, 546
-h, 546
gitlab-group-epic-note-award-emoji-get
    command line option
--epic-iid, 546
--group-id, 546
--help, 546
--id, 546
--note-id, 546
--sudo, 546
-h, 546
gitlab-group-epic-note-award-emoji-list
    command line option
--all, 547
--epic-iid, 546
--get-all, 547
--group-id, 546
--help, 546
--note-id, 546
--page, 547
--per-page, 547
--sudo, 546

```

```
-h, 546
gitlab-group-epic-note-create command line
    option
    --body, 544
    --created-at, 544
    --epic-id, 544
    --group-id, 543
    --help, 543
    --sudo, 543
    -h, 543
gitlab-group-epic-note-delete command line
    option
    --epic-id, 544
    --group-id, 544
    --help, 544
    --id, 544
    --sudo, 544
    -h, 544
gitlab-group-epic-note-get command line
    option
    --epic-id, 544
    --group-id, 544
    --help, 544
    --id, 544
    --sudo, 544
    -h, 544
gitlab-group-epic-note-list command line
    option
    --all, 545
    --epic-id, 544
    --get-all, 545
    --group-id, 544
    --help, 544
    --page, 545
    --per-page, 545
    --sudo, 544
    -h, 544
gitlab-group-epic-note-update command line
    option
    --body, 545
    --epic-id, 545
    --group-id, 545
    --help, 545
    --id, 545
    --sudo, 545
    -h, 545
gitlab-group-epic-resource-label-event
    command line option
    --help, 547
    -h, 547
gitlab-group-epic-resource-label-event-get
    command line option
    --epic-id, 547
    --group-id, 547
    --help, 547
    --id, 547
    --sudo, 547
    -h, 547
gitlab-group-epic-resource-label-event-list
    command line option
    --all, 548
    --epic-id, 547
    --get-all, 548
    --group-id, 547
    --help, 547
    --page, 548
    --per-page, 548
    --sudo, 547
    -h, 547
gitlab-group-epic-update command line
    option
    --description, 538
    --end-date, 538
    --group-id, 538
    --help, 538
    --iid, 538
    --labels, 538
    --start-date, 538
    --sudo, 538
    --title, 538
    -h, 538
gitlab-group-export command line option
    --help, 548
    -h, 548
gitlab-group-export-create command line
    option
    --group-id, 548
    --help, 548
    --sudo, 548
    -h, 548
gitlab-group-export-download command line
    option
    --group-id, 548
    --help, 548
    --sudo, 548
    -h, 548
gitlab-group-export-get command line option
    --group-id, 548
    --help, 548
    --sudo, 548
    -h, 548
gitlab-group-get command line option
    --help, 514
    --id, 514
    --sudo, 514
    -h, 514
gitlab-group-hook command line option
    --help, 549
```

```

-h, 549
gitlab-group-hook-create command line
    option
    --confidential-issues-events, 549
    --confidential-note-events, 549
    --deployment-events, 549
    --enable-ssl-verification, 550
    --group-id, 549
    --help, 549
    --issues-events, 549
    --job-events, 549
    --merge-requests-events, 549
    --note-events, 549
    --pipeline-events, 549
    --push-events, 549
    --releases-events, 550
    --subgroup-events, 550
    --sudo, 549
    --tag-push-events, 549
    --token, 550
    --url, 549
    --wiki-page-events, 549
    -h, 549
gitlab-group-hook-delete command line
    option
    --group-id, 550
    --help, 550
    --id, 550
    --sudo, 550
    -h, 550
gitlab-group-hook-get command line option
    --group-id, 550
    --help, 550
    --id, 550
    --sudo, 550
    -h, 550
gitlab-group-hook-list command line option
    --all, 551
    --get-all, 550
    --group-id, 550
    --help, 550
    --page, 550
    --per-page, 550
    --sudo, 550
    -h, 550
gitlab-group-hook-update command line
    option
    --confidential-issues-events, 551
    --confidential-note-events, 551
    --deployment-events, 551
    --enable-ssl-verification, 552
    --group-id, 551
    --help, 551
    --id, 551
    --issues-events, 551
    --job-events, 551
    --merge-requests-events, 551
    --note-events, 551
    --pipeline-events, 551
    --push-events, 551
    --releases-events, 552
    --subgroup-events, 552
    --sudo, 551
    --tag-push-events, 551
    --token, 552
    --url, 551
    --wiki-page-events, 551
    -h, 551
gitlab-group-import command line option
    --help, 552
    -h, 552
gitlab-group-import-get command line option
    --group-id, 552
    --help, 552
    --sudo, 552
    -h, 552
gitlab-group-invitation command line option
    --help, 552
    -h, 552
gitlab-group-invitation-create command line
    option
    --access-level, 552
    --expires-at, 553
    --group-id, 552
    --help, 552
    --invite-source, 553
    --sudo, 552
    --tasks-project-id, 553
    --tasks-to-be-done, 553
    -h, 552
gitlab-group-invitation-delete command line
    option
    --email, 553
    --group-id, 553
    --help, 553
    --sudo, 553
    -h, 553
gitlab-group-invitation-get command line
    option
    --email, 553
    --group-id, 553
    --help, 553
    --sudo, 553
    -h, 553
gitlab-group-invitation-list command line
    option
    --all, 554
    --get-all, 554

```

```
--group-id, 553
--help, 553
--page, 553
--per-page, 554
--query, 553
--sudo, 553
-h, 553
gitlab-group-invitation-update command line
    option
    --access-level, 554
    --email, 554
    --expires-at, 554
    --group-id, 554
    --help, 554
    --sudo, 554
-h, 554
gitlab-group-issue command line option
    --help, 554
    -h, 554
gitlab-group-issue-list command line option
    --all, 555
    --assignee-id, 555
    --author-id, 555
    --created-after, 555
    --created-before, 555
    --get-all, 555
    --group-id, 555
    --help, 554
    --iids, 555
    --labels, 555
    --milestone, 555
    --my-reaction-emoji, 555
    --order-by, 555
    --page, 555
    --per-page, 555
    --search, 555
    --sort, 555
    --state, 555
    --sudo, 555
    --updated-after, 555
    --updated-before, 555
    -h, 554
gitlab-group-issues-statistics command line
    option
    --help, 555
    -h, 555
gitlab-group-issues-statistics-get command
    line option
    --group-id, 556
    --help, 556
    --sudo, 556
    -h, 556
gitlab-group-iteration command line option
    --help, 556
-h, 556
gitlab-group-iteration-list command line
    option
    --all, 556
    --get-all, 556
    --group-id, 556
    --help, 556
    --include-ancestors, 556
    --page, 556
    --per-page, 556
    --search, 556
    --state, 556
    --sudo, 556
    -h, 556
gitlab-group-label command line option
    --help, 557
    -h, 557
gitlab-group-label-create command line
    option
    --color, 557
    --description, 557
    --group-id, 557
    --help, 557
    --name, 557
    --priority, 557
    --sudo, 557
    -h, 557
gitlab-group-label-delete command line
    option
    --group-id, 557
    --help, 557
    --name, 557
    --sudo, 557
    -h, 557
gitlab-group-label-get command line option
    --group-id, 558
    --help, 558
    --name, 558
    --sudo, 558
    -h, 558
gitlab-group-label-list command line option
    --all, 558
    --get-all, 558
    --group-id, 558
    --help, 558
    --page, 558
    --per-page, 558
    --sudo, 558
    -h, 558
gitlab-group-label-subscribe command line
    option
    --group-id, 558
    --help, 558
    --name, 558
```

```

--sudo, 558
-h, 558
gitlab-group-label-unsubscribe command line
    option
    --group-id, 559
    --help, 559
    --name, 559
    --sudo, 559
    -h, 559
gitlab-group-label-update command line
    option
    --color, 559
    --description, 559
    --group-id, 559
    --help, 559
    --name, 559
    --new-name, 559
    --priority, 559
    --sudo, 559
    -h, 559
gitlab-group-ldap-group-link command line
    option
    --help, 559
    -h, 559
gitlab-group-ldap-group-link-create command
    line option
    --group-access, 560
    --group-id, 560
    --help, 560
    --provider, 560
    --sudo, 560
    -h, 560
gitlab-group-ldap-group-link-delete command
    line option
    --group-id, 560
    --help, 560
    --id, 560
    --sudo, 560
    -h, 560
gitlab-group-ldap-group-link-list command
    line option
    --all, 560
    --get-all, 560
    --group-id, 560
    --help, 560
    --page, 560
    --per-page, 560
    --sudo, 560
    -h, 560
gitlab-group-ldap-sync command line option
    --help, 514
    --id, 514
    -h, 514
gitlab-group-list command line option
    --all, 515
    --all-available, 514
    --get-all, 515
    --help, 514
    --min-access-level, 515
    --order-by, 515
    --owned, 515
    --page, 515
    --per-page, 515
    --search, 515
    --skip-groups, 514
    --sort, 515
    --statistics, 515
    --sudo, 514
    --top-level-only, 515
    --with-custom-attributes, 515
    -h, 514
gitlab-group-member command line option
    --help, 561
    -h, 561
gitlab-group-member-all command line option
    --help, 563
    -h, 563
gitlab-group-member-all-get command line
    option
    --group-id, 563
    --help, 563
    --id, 563
    --sudo, 563
    -h, 563
gitlab-group-member-all-list command line
    option
    --all, 563
    --get-all, 563
    --group-id, 563
    --help, 563
    --page, 563
    --per-page, 563
    --sudo, 563
    -h, 563
gitlab-group-member-create command line
    option
    --access-level, 561
    --expires-at, 561
    --group-id, 561
    --help, 561
    --sudo, 561
    --tasks-to-be-done, 561
    --user-id, 561
    -h, 561
gitlab-group-member-delete command line
    option
    --group-id, 561
    --help, 561

```

```
--id, 561
--sudo, 561
-h, 561
gitlab-group-member-get command line option
--group-id, 561
--help, 561
--id, 562
--sudo, 561
-h, 561
gitlab-group-member-list command line
    option
--all, 562
--get-all, 562
--group-id, 562
--help, 562
--page, 562
--per-page, 562
--sudo, 562
-h, 562
gitlab-group-member-update command line
    option
--access-level, 562
--expires-at, 562
--group-id, 562
--help, 562
--id, 562
--sudo, 562
-h, 562
gitlab-group-merge-request command line
    option
--help, 564
-h, 564
gitlab-group-merge-request-list command
    line option
--all, 565
--approved-by-ids, 565
--approver-ids, 565
--assignee-id, 565
--author-id, 565
--created-after, 564
--created-before, 564
--get-all, 565
--group-id, 564
--help, 564
--labels, 564
--milestone, 564
--my-reaction-emoji, 565
--order-by, 564
--page, 565
--per-page, 565
--scope, 564
--search, 565
--sort, 564
--source-branch, 565
--state, 564
--sudo, 564
--target-branch, 565
--updated-after, 564
--updated-before, 564
--view, 564
--wip, 565
-h, 564
gitlab-group-milestone command line option
--help, 565
-h, 565
gitlab-group-milestone-create command line
    option
--description, 566
--due-date, 566
--group-id, 566
--help, 565
--start-date, 566
--sudo, 565
--title, 566
-h, 565
gitlab-group-milestone-delete command line
    option
--group-id, 566
--help, 566
--id, 566
--sudo, 566
-h, 566
gitlab-group-milestone-get command line
    option
--group-id, 566
--help, 566
--id, 566
--sudo, 566
-h, 566
gitlab-group-milestone-issues command line
    option
--group-id, 566
--help, 566
--id, 566
--sudo, 566
-h, 566
gitlab-group-milestone-list command line
    option
--all, 567
--get-all, 567
--group-id, 567
--help, 567
--iids, 567
--page, 567
--per-page, 567
--search, 567
--state, 567
--sudo, 567
```

```

-h, 567
gitlab-group-milestone-merge-requests
    command line option
    --group-id, 567
    --help, 567
    --id, 567
    --sudo, 567
    -h, 567
gitlab-group-milestone-update command line
    option
    --description, 568
    --due-date, 568
    --group-id, 568
    --help, 567
    --id, 568
    --start-date, 568
    --state-event, 568
    --sudo, 568
    --title, 568
    -h, 567
gitlab-group-notification-settings command
    line option
    --help, 568
    -h, 568
gitlab-group-notification-settings-get
    command line option
    --group-id, 568
    --help, 568
    --sudo, 568
    -h, 568
gitlab-group-notification-settings-update
    command line option
    --close-issue, 569
    --close-merge-request, 569
    --group-id, 569
    --help, 569
    --level, 569
    --merge-merge-request, 569
    --new-issue, 569
    --new-merge-request, 569
    --new-note, 569
    --notification-email, 569
    --reassign-issue, 569
    --reassign-merge-request, 569
    --reopen-issue, 569
    --reopen-merge-request, 569
    --sudo, 569
    -h, 569
gitlab-group-package command line option
    --help, 569
    -h, 569
gitlab-group-package-list command line
    option
    --all, 570
    --exclude-subgroups, 570
    --get-all, 570
    --group-id, 570
    --help, 569
    --order-by, 570
    --package-name, 570
    --package-type, 570
    --page, 570
    --per-page, 570
    --sort, 570
    --sudo, 570
    -h, 569
gitlab-group-project command line option
    --help, 570
    -h, 570
gitlab-group-project-list command line
    option
    --all, 571
    --archived, 571
    --get-all, 571
    --group-id, 571
    --help, 570
    --include-subgroups, 571
    --min-access-level, 571
    --order-by, 571
    --owned, 571
    --page, 571
    --per-page, 571
    --search, 571
    --simple, 571
    --sort, 571
    --starred, 571
    --sudo, 571
    --visibility, 571
    --with-custom-attributes, 571
    --with-issues-enabled, 571
    --with-merge-requests-enabled, 571
    --with-security-reports, 571
    --with-shared, 571
    -h, 570
gitlab-group-push-rules command line option
    --help, 571
    -h, 571
gitlab-group-push-rules-create command line
    option
    --author-email-regex, 572
    --branch-name-regex, 572
    --commit-committer-check, 572
    --commit-message-negative-regex, 572
    --commit-message-regex, 572
    --deny-delete-tag, 572
    --file-name-regex, 572
    --group-id, 572
    --help, 572

```

```
--max-file-size, 572
--member-check, 572
--prevent-secrets, 572
--reject-unsigned-commits, 572
--sudo, 572
-h, 572
gitlab-group-push-rules-delete command line
    option
--group-id, 572
--help, 572
--sudo, 572
-h, 572
gitlab-group-push-rules-get command line
    option
--group-id, 573
--help, 573
--sudo, 573
-h, 573
gitlab-group-push-rules-update command line
    option
--author-email-regex, 573
--branch-name-regex, 573
--commit-committer-check, 573
--commit-message-negative-regex, 573
--commit-message-regex, 573
--deny-delete-tag, 573
--file-name-regex, 573
--group-id, 573
--help, 573
--max-file-size, 573
--member-check, 573
--prevent-secrets, 573
--reject-unsigned-commits, 573
--sudo, 573
-h, 573
gitlab-group-restore command line option
--help, 515
--id, 515
-h, 515
gitlab-group-runner command line option
--help, 574
-h, 574
gitlab-group-runner-list command line
    option
--all, 574
--get-all, 574
--group-id, 574
--help, 574
--page, 574
--per-page, 574
--scope, 574
--sudo, 574
--tag-list, 574
-h, 574
gitlab-group-saml-group-link command line
    option
--help, 574
-h, 574
gitlab-group-saml-group-link-create command
    line option
--access-level, 575
--group-id, 575
--help, 574
--saml-group-name, 575
--sudo, 574
-h, 574
gitlab-group-saml-group-link-delete command
    line option
--group-id, 575
--help, 575
--name, 575
--sudo, 575
-h, 575
gitlab-group-saml-group-link-get command
    line option
--group-id, 575
--help, 575
--name, 575
--sudo, 575
-h, 575
gitlab-group-saml-group-link-list command
    line option
--all, 576
--get-all, 575
--group-id, 575
--help, 575
--page, 575
--per-page, 575
--sudo, 575
-h, 575
gitlab-group-search command line option
--help, 515
--id, 515
--scope, 515
--search, 515
-h, 515
gitlab-group-share command line option
--expires-at, 516
--group-access, 516
--group-id, 516
--help, 516
--id, 516
-h, 516
gitlab-group-subgroup command line option
--help, 576
-h, 576
gitlab-group-subgroup-list command line
    option
```

```

--all, 577
--all-available, 576
--get-all, 576
--group-id, 576
--help, 576
--min-access-level, 576
--order-by, 576
--owned, 576
--page, 576
--per-page, 576
--search, 576
--skip-groups, 576
--sort, 576
--statistics, 576
--sudo, 576
--with-custom-attributes, 576
-h, 576
gitlab-group-transfer command line option
--group-id, 516
--help, 516
--id, 516
-h, 516
gitlab-group-transfer-project command line
    option
--help, 516
--id, 516
--project-id, 516
-h, 516
gitlab-group-unshare command line option
--group-id, 516
--help, 516
--id, 516
-h, 516
gitlab-group-update command line option
--auto-devops-enabled, 517
--avatar, 518
--default-branch-protection, 518
--description, 517
--emails-disabled, 517
--extra-shared-runners-minutes-limit, 518
--file-template-project-id, 518
--help, 517
--id, 517
--lfs-enabled, 518
--membership-lock, 517
--mentions-disabled, 518
--name, 517
--path, 517
--prevent-forking-outside-group, 518
--project-creation-level, 517
--request-access-enabled, 518
--require-two-factor-authentication, 517
--share-with-group-lock, 517
--shared-runners-minutes-limit, 518
--shared-runners-setting, 518
--subgroup-creation-level, 517
--sudo, 517
--two-factor-grace-period, 517
--visibility, 517
-h, 517
gitlab-group-variable command line option
--help, 577
-h, 577
gitlab-group-variable-create command line
    option
--group-id, 577
--help, 577
--key, 577
--masked, 577
--protected, 577
--sudo, 577
--value, 577
--variable-type, 577
-h, 577
gitlab-group-variable-delete command line
    option
--group-id, 577
--help, 577
--key, 577
--sudo, 577
-h, 577
gitlab-group-variable-get command line
    option
--group-id, 578
--help, 578
--key, 578
--sudo, 578
-h, 578
gitlab-group-variable-list command line
    option
--all, 578
--get-all, 578
--group-id, 578
--help, 578
--page, 578
--per-page, 578
--sudo, 578
-h, 578
gitlab-group-variable-update command line
    option
--group-id, 578
--help, 578
--key, 578
--masked, 579
--protected, 579
--sudo, 578
--value, 578
--variable-type, 579

```

```
-h, 578
gitlab-group-wiki command line option
--help, 579
-h, 579
gitlab-group-wiki-create command line
    option
--content, 579
--format, 579
--group-id, 579
--help, 579
--sudo, 579
--title, 579
-h, 579
gitlab-group-wiki-delete command line
    option
--group-id, 579
--help, 579
--slug, 579
--sudo, 579
-h, 579
gitlab-group-wiki-get command line option
--group-id, 580
--help, 580
--slug, 580
--sudo, 580
-h, 580
gitlab-group-wiki-list command line option
--all, 580
--get-all, 580
--group-id, 580
--help, 580
--page, 580
--per-page, 580
--sudo, 580
--with-content, 580
-h, 580
gitlab-group-wiki-update command line
    option
--content, 581
--format, 581
--group-id, 580
--help, 580
--slug, 580
--sudo, 580
--title, 580
-h, 580
gitlab-hook command line option
--help, 581
-h, 581
gitlab-hook-create command line option
--help, 581
--sudo, 581
--url, 581
-h, 581
gitlab-hook-delete command line option
--help, 581
--id, 581
--sudo, 581
-h, 581
gitlab-hook-get command line option
--help, 581
--id, 581
--sudo, 581
-h, 581
gitlab-hook-list command line option
--all, 582
--get-all, 582
--help, 582
--page, 582
--per-page, 582
--sudo, 582
-h, 582
gitlab-issue command line option
--help, 582
-h, 582
gitlab-issue-get command line option
--help, 582
--id, 582
--sudo, 582
-h, 582
gitlab-issue-list command line option
--all, 583
--assignee-id, 583
--author-id, 583
--created-after, 583
--created-before, 583
--get-all, 583
--help, 582
--iids, 583
--labels, 583
--milestone, 583
--my-reaction-emoji, 583
--order-by, 583
--page, 583
--per-page, 583
--scope, 583
--search, 583
--sort, 583
--state, 583
--sudo, 583
--updated-after, 583
--updated-before, 583
-h, 582
gitlab-issues-statistics command line
    option
--help, 583
-h, 583
```

```

gitlab-issues-statistics-get command line
    option
    --help, 584
    --sudo, 584
    -h, 584
gitlab-key command line option
    --help, 584
    -h, 584
gitlab-key-get command line option
    --help, 584
    --id, 584
    --sudo, 584
    -h, 584
gitlab-ldap-group command line option
    --help, 584
    -h, 584
gitlab-ldap-group-list command line option
    --all, 585
    --get-all, 585
    --help, 584
    --page, 584
    --per-page, 584
    --provider, 584
    --search, 584
    --sudo, 584
    -h, 584
gitlab-license command line option
    --help, 585
    -h, 585
gitlab-license-get command line option
    --fullname, 585
    --help, 585
    --key, 585
    --project, 585
    --sudo, 585
    -h, 585
gitlab-license-list command line option
    --all, 585
    --get-all, 585
    --help, 585
    --page, 585
    --per-page, 585
    --popular, 585
    --sudo, 585
    -h, 585
gitlab-merge-request command line option
    --help, 586
    -h, 586
gitlab-merge-request-list command line
    option
    --all, 587
    --approved-by-ids, 587
    --approver-ids, 587
    --assignee-id, 587
    --author-id, 587
    --author-username, 587
    --created-after, 587
    --created-before, 587
    --deployed-after, 587
    --deployed-before, 587
    --environment, 587
    --get-all, 587
    --help, 586
    --in, 587
    --labels, 586
    --milestone, 586
    --my-reaction-emoji, 587
    --not, 587
    --order-by, 586
    --page, 587
    --per-page, 587
    --reviewer-id, 587
    --reviewer-username, 587
    --scope, 587
    --search, 587
    --sort, 586
    --source-branch, 587
    --state, 586
    --sudo, 586
    --target-branch, 587
    --updated-after, 587
    --updated-before, 587
    --view, 586
    --wip, 587
    --with-labels-details, 586
    --with-merge-status-recheck, 586
    -h, 586
gitlab-namespace command line option
    --help, 588
    -h, 588
gitlab-namespace-exists command line option
    --help, 588
    --id, 588
    --namespace, 588
    --parent-id, 588
    -h, 588
gitlab-namespace-get command line option
    --help, 588
    --id, 588
    --sudo, 588
    -h, 588
gitlab-namespace-list command line option
    --all, 588
    --get-all, 588
    --help, 588
    --page, 588
    --per-page, 588
    --search, 588

```

```
--sudo, 588
-h, 588
gitlab-notification-settings command line
    option
    --help, 589
    -h, 589
gitlab-notification-settings-get command
    line option
    --help, 589
    --sudo, 589
    -h, 589
gitlab-notification-settings-update command
    line option
    --close-issue, 589
    --close-merge-request, 590
    --help, 589
    --level, 589
    --merge-merge-request, 590
    --new-issue, 589
    --new-merge-request, 589
    --new-note, 589
    --notification-email, 589
    --reassign-issue, 589
    --reassign-merge-request, 590
    --reopen-issue, 589
    --reopen-merge-request, 589
    --sudo, 589
    -h, 589
gitlab-pages-domain command line option
    --help, 590
    -h, 590
gitlab-pages-domain-list command line
    option
    --all, 590
    --get-all, 590
    --help, 590
    --page, 590
    --per-page, 590
    --sudo, 590
    -h, 590
gitlab-personal-access-token command line
    option
    --help, 590
    -h, 590
gitlab-personal-access-token-delete command
    line option
    --help, 590
    --id, 590
    --sudo, 590
    -h, 590
gitlab-personal-access-token-get command
    line option
    --help, 591
    --id, 591
    --sudo, 591
    -h, 591
gitlab-personal-access-token-list command
    line option
    --all, 591
    --get-all, 591
    --help, 591
    --page, 591
    --per-page, 591
    --sudo, 591
    --user-id, 591
    -h, 591
gitlab-project command line option
    --help, 592
    -h, 592
gitlab-project-access-request command line
    option
    --help, 610
    -h, 610
gitlab-project-access-request-approve
    command line option
    --access-level, 610
    --help, 610
    --id, 610
    --project-id, 610
    --sudo, 610
    -h, 610
gitlab-project-access-request-create
    command line option
    --help, 611
    --project-id, 611
    --sudo, 611
    -h, 611
gitlab-project-access-request-delete
    command line option
    --help, 611
    --id, 611
    --project-id, 611
    --sudo, 611
    -h, 611
gitlab-project-access-request-list command
    line option
    --all, 611
    --get-all, 611
    --help, 611
    --page, 611
    --per-page, 611
    --project-id, 611
    --sudo, 611
    -h, 611
gitlab-project-access-token command line
    option
    --help, 612
    -h, 612
```

```

gitlab-project-access-token-create command
    line option
    --access-level, 612
    --expires-at, 612
    --help, 612
    --name, 612
    --project-id, 612
    --scopes, 612
    --sudo, 612
    -h, 612
gitlab-project-access-token-delete command
    line option
    --help, 612
    --id, 612
    --project-id, 612
    --sudo, 612
    -h, 612
gitlab-project-access-token-list command
    line option
    --all, 613
    --get-all, 613
    --help, 612
    --page, 613
    --per-page, 613
    --project-id, 613
    --sudo, 612
    -h, 612
gitlab-project-additional-statistics
    command line option
    --help, 613
    -h, 613
gitlab-project-additional-statistics-get
    command line option
    --help, 613
    --project-id, 613
    --sudo, 613
    -h, 613
gitlab-project-approval command line option
    --help, 613
    -h, 613
gitlab-project-approval-get command line
    option
    --help, 613
    --project-id, 613
    --sudo, 613
    -h, 613
gitlab-project-approval-rule command line
    option
    --help, 614
    -h, 614
gitlab-project-approval-rule-create command
    line option
    --approvals-required, 615
    --group-ids, 615
    --help, 614
    --name, 614
    --project-id, 614
    --protected-branch-ids, 615
    --sudo, 614
    --user-ids, 615
    -h, 614
gitlab-project-approval-rule-delete command
    line option
    --help, 615
    --id, 615
    --project-id, 615
    --sudo, 615
    -h, 615
gitlab-project-approval-rule-list command
    line option
    --all, 615
    --get-all, 615
    --help, 615
    --page, 615
    --per-page, 615
    --project-id, 615
    --sudo, 615
    -h, 615
gitlab-project-approval-rule-update command
    line option
    --help, 616
    --id, 616
    --project-id, 616
    --sudo, 616
    -h, 616
gitlab-project-approval-update command line
    option
    --approvals-before-merge, 614
    --disable-overriding-approvers-per-merge-request,
        614
    --help, 614
    --merge-requests-author-approval, 614
    --merge-requests-disable-committers-approval,
        614
    --project-id, 614
    --reset-approvals-on-push, 614
    --sudo, 614
    -h, 614
gitlab-project-archive command line option
    --help, 592
    --id, 592
    -h, 592
gitlab-project-artifact command line option
    --artifact-path, 592
    --help, 592, 616
    --id, 592
    --job, 592
    --ref-name, 592

```

```
-h, 592, 616
gitlab-project-artifact-delete command line
    option
    --help, 616
    --project-id, 616
    --ref-name, 616
    --sudo, 616
    -h, 616
gitlab-project-artifact-download command
    line option
    --help, 616
    --job, 616
    --job-token, 616
    --project-id, 616
    --ref-name, 616
    --sudo, 616
    -h, 616
gitlab-project-artifact-raw command line
    option
    --artifact-path, 617
    --help, 617
    --job, 617
    --project-id, 617
    --ref-name, 617
    --sudo, 617
    -h, 617
gitlab-project-artifacts command line
    option
    --help, 593
    --id, 593
    --job, 593
    --job-token, 593
    --ref-name, 593
    -h, 593
gitlab-project-audit-event command line
    option
    --help, 617
    -h, 617
gitlab-project-audit-event-get command line
    option
    --help, 617
    --id, 617
    --project-id, 617
    --sudo, 617
    -h, 617
gitlab-project-audit-event-list command
    line option
    --all, 618
    --created-after, 618
    --created-before, 618
    --get-all, 618
    --help, 617
    --page, 618
    --per-page, 618
    --project-id, 618
    --ref-name, 618
    --sudo, 618
    -h, 618
gitlab-project-badge command line option
    --help, 618
    -h, 618
gitlab-project-badge-create command line
    option
    --help, 618
    --image-url, 618
    --link-url, 618
    --project-id, 618
    --sudo, 618
    -h, 618
gitlab-project-badge-delete command line
    option
    --help, 618
    --id, 618
    --project-id, 618
    --sudo, 618
    -h, 618
gitlab-project-badge-get command line
    option
    --help, 619
    --id, 619
    --project-id, 619
    --sudo, 619
    -h, 619
gitlab-project-badge-list command line
    option
    --all, 619
    --get-all, 619
    --help, 619
    --page, 619
    --per-page, 619
    --project-id, 619
    --sudo, 619
    -h, 619
gitlab-project-badge-render command line
    option
    --help, 619
    --id, 619
    --image-url, 619
    --link-url, 619
    --project-id, 619
    --sudo, 619
    -h, 619
gitlab-project-badge-update command line
    option
    --help, 620
    --id, 620
    --image-url, 620
    --link-url, 620
    --project-id, 620
```

```
--sudo, 620
-h, 620
gitlab-project-board command line option
--help, 620
-h, 620
gitlab-project-board-create command line
    option
--help, 620
--name, 620
--project-id, 620
--sudo, 620
-h, 620
gitlab-project-board-delete command line
    option
--help, 620
--id, 620
--project-id, 620
--sudo, 620
-h, 620
gitlab-project-board-get command line
    option
--help, 621
--id, 621
--project-id, 621
--sudo, 621
-h, 621
gitlab-project-board-list command line
    option
--all, 621
--get-all, 621
--help, 621, 622
--page, 621
--per-page, 621
--project-id, 621
--sudo, 621
-h, 621, 622
gitlab-project-board-list-create command
    line option
--board-id, 622
--help, 622
--project-id, 622
--sudo, 622
-h, 622
gitlab-project-board-list-delete command
    line option
--board-id, 622
--help, 622
--id, 622
--project-id, 622
--sudo, 622
-h, 622
gitlab-project-board-list-get command line
    option
--board-id, 622
--help, 622
--id, 622
--project-id, 622
--sudo, 622
-h, 622
gitlab-project-board-list-list command line
    option
--all, 623
--board-id, 623
--get-all, 623
--help, 623
--page, 623
--per-page, 623
--project-id, 623
--sudo, 623
-h, 623
gitlab-project-board-list-update command
    line option
--board-id, 623
--help, 623
--id, 623
--position, 623
--project-id, 623
--sudo, 623
-h, 623
gitlab-project-board-update command line
    option
--help, 621
--id, 621
--project-id, 621
--sudo, 621
-h, 621
gitlab-project-branch command line option
--help, 623
-h, 623
gitlab-project-branch-create command line
    option
--branch, 624
--help, 624
--project-id, 624
--ref, 624
--sudo, 624
-h, 624
gitlab-project-branch-delete command line
    option
--help, 624
--name, 624
--project-id, 624
--sudo, 624
-h, 624
gitlab-project-branch-get command line
    option
--help, 624
--name, 624
```

```
--project-id, 624
--sudo, 624
-h, 624
gitlab-project-branch-list command line
    option
    --all, 625
    --get-all, 625
    --help, 625
    --page, 625
    --per-page, 625
    --project-id, 625
    --sudo, 625
    -h, 625
gitlab-project-ci-lint command line option
    --help, 625
    -h, 625
gitlab-project-ci-lint-create command line
    option
    --content, 625
    --dry-run, 625
    --help, 625
    --include-jobs, 625
    --project-id, 625
    --ref, 625
    --sudo, 625
    -h, 625
gitlab-project-ci-lint-get command line
    option
    --help, 626
    --project-id, 626
    --sudo, 626
    -h, 626
gitlab-project-ci-lint-validate command
    line option
    --content, 626
    --dry-run, 626
    --help, 626
    --include-jobs, 626
    --project-id, 626
    --ref, 626
    --sudo, 626
    -h, 626
gitlab-project-cluster command line option
    --help, 626
    -h, 626
gitlab-project-cluster-create command line
    option
    --domain, 627
    --enabled, 627
    --environment-scope, 627
    --help, 626
    --managed, 627
    --name, 627
    --platform-kubernetes-attributes, 627
    --project-id, 627
    --sudo, 627
    -h, 627
gitlab-project-cluster-delete command line
    option
    --help, 627
    --id, 627
    --project-id, 627
    --sudo, 627
    -h, 627
gitlab-project-cluster-get command line
    option
    --help, 627
    --id, 627
    --project-id, 627
    --sudo, 627
    -h, 627
gitlab-project-cluster-list command line
    option
    --all, 628
    --get-all, 628
    --help, 628
    --page, 628
    --per-page, 628
    --project-id, 628
    --sudo, 628
    -h, 628
gitlab-project-cluster-update command line
    option
    --domain, 628
    --environment-scope, 628
    --help, 628
    --id, 628
    --management-project-id, 628
    --name, 628
    --platform-kubernetes-attributes, 628
    --project-id, 628
    --sudo, 628
    -h, 628
gitlab-project-commit command line option
    --help, 629
    -h, 629
gitlab-project-commit-cherry-pick command
    line option
    --branch, 629
    --help, 629
    --id, 629
    --project-id, 629
    --sudo, 629
    -h, 629
gitlab-project-commit-comment command line
    option
    --help, 632
    -h, 632
```

```

gitlab-project-commit-comment-create
    command line option
    --commit-id, 632
    --help, 632
    --line, 633
    --line-type, 633
    --note, 633
    --path, 633
    --project-id, 632
    --sudo, 632
    -h, 632
gitlab-project-commit-comment-list command
    line option
    --all, 633
    --commit-id, 633
    --get-all, 633
    --help, 633
    --page, 633
    --per-page, 633
    --project-id, 633
    --sudo, 633
    -h, 633
gitlab-project-commit-create command line
    option
    --actions, 629
    --author-email, 629
    --author-name, 630
    --branch, 629
    --commit-message, 629
    --help, 629
    --project-id, 629
    --sudo, 629
    -h, 629
gitlab-project-commit-diff command line
    option
    --help, 630
    --id, 630
    --project-id, 630
    --sudo, 630
    -h, 630
gitlab-project-commit-discussion command
    line option
    --help, 633
    -h, 633
gitlab-project-commit-discussion-create
    command line option
    --body, 634
    --commit-id, 634
    --created-at, 634
    --help, 633
    --project-id, 634
    --sudo, 633
    -h, 633
gitlab-project-commit-discussion-get
    command line option
    --commit-id, 634
    --help, 634
    --id, 634
    --project-id, 634
    --sudo, 634
    -h, 634
gitlab-project-commit-discussion-list
    command line option
    --all, 634
    --commit-id, 634
    --get-all, 634
    --help, 634
    --page, 634
    --per-page, 634
    --project-id, 634
    --sudo, 634
    -h, 634
gitlab-project-commit-discussion-note
    command line option
    --help, 635
    -h, 635
gitlab-project-commit-discussion-note-create
    command line option
    --body, 635
    --commit-id, 635
    --created-at, 635
    --discussion-id, 635
    --help, 635
    --position, 635
    --project-id, 635
    --sudo, 635
    -h, 635
gitlab-project-commit-discussion-note-delete
    command line option
    --commit-id, 635
    --discussion-id, 636
    --help, 635
    --id, 636
    --project-id, 635
    --sudo, 635
    -h, 635
gitlab-project-commit-discussion-note-get
    command line option
    --commit-id, 636
    --discussion-id, 636
    --help, 636
    --id, 636
    --project-id, 636
    --sudo, 636
    -h, 636
gitlab-project-commit-discussion-note-update
    command line option

```

```
--body, 636
--commit-id, 636
--discussion-id, 636
--help, 636
--id, 636
--project-id, 636
--sudo, 636
-h, 636
gitlab-project-commit-get command line
    option
    --help, 630
    --id, 630
    --project-id, 630
    --sudo, 630
    -h, 630
gitlab-project-commit-list command line
    option
    --all, 631
    --first-parent, 631
    --get-all, 631
    --help, 630
    --order, 631
    --page, 631
    --path, 631
    --per-page, 631
    --project-id, 630
    --ref-name, 630
    --since, 630
    --sudo, 630
    --trailers, 631
    --until, 631
    --with-stats, 631
    -h, 630
gitlab-project-commit-merge-requests
    command line option
    --help, 631
    --id, 631
    --project-id, 631
    --sudo, 631
    -h, 631
gitlab-project-commit-refs command line
    option
    --help, 631
    --id, 631
    --project-id, 631
    --sudo, 631
    --type, 631
    -h, 631
gitlab-project-commit-revert command line
    option
    --branch, 632
    --help, 632
    --id, 632
    --project-id, 632
    --sudo, 632
    -h, 632
    --line-option, 632
    --help, 632
    --id, 632
    --project-id, 632
    --sudo, 632
    -h, 632
gitlab-project-commit-signature command
    line option
    --help, 632
    --id, 632
    --project-id, 632
    --sudo, 632
    -h, 632
gitlab-project-commit-status command line
    option
    --help, 637
    -h, 637
gitlab-project-commit-status-create command
    line option
    --commit-id, 637
    --context, 637
    --coverage, 637
    --description, 637
    --help, 637
    --name, 637
    --project-id, 637
    --ref, 637
    --state, 637
    --sudo, 637
    --target-url, 637
    -h, 637
gitlab-project-commit-status-list command
    line option
    --all, 638
    --commit-id, 638
    --get-all, 638
    --help, 637
    --page, 638
    --per-page, 638
    --project-id, 637
    --sudo, 637
    -h, 637
gitlab-project-create command line option
    --allow-merge-on-skipped-pipeline, 595
    --analytics-access-level, 595
    --approvals-before-merge, 595
    --auto-cancel-pending-pipelines, 595
    --auto-devops-deploy-strategy, 595
    --auto-devops-enabled, 595
    --autoclose-referenced-issues, 595
    --avatar, 595
    --build-coverage-regex, 595
    --build-git-strategy, 595
    --build-timeout, 595
    --builds-access-level, 595
    --ci-config-path, 595
    --container-expiration-policy-attributes,
        595
```

```
--container-registry-access-level, 595
--container-registry-enabled, 595
--default-branch, 595
--description, 595
--emails-disabled, 595
--environments-access-level, 596
--external-authorization-classification-label, 595
--feature-flags-access-level, 596
--forking-access-level, 595
--group-with-project-templates-id, 595
--help, 594
--import-url, 595
--infrastructure-access-level, 596
--initialize-with-readme, 595
--issues-access-level, 595
--issues-enabled, 595
--jobs-enabled, 595
--lfs-enabled, 595
--merge-method, 595
--merge-pipelines-enabled, 595
--merge-requests-access-level, 596
--merge-requests-enabled, 596
--mirror, 596
--mirror-trigger-builds, 596
--monitor-access-level, 596
--name, 594
--namespace-id, 596
--only-allow-merge-if-all-discussions-are-solved, 596
--only-allow-merge-if-all-status-checks-passed, 595
--only-allow-merge-if-pipeline-succeeds, 596
--operations-access-level, 596
--packages-enabled, 596
--pages-access-level, 596
--path, 594
--printing-merge-request-link-enabled, 596
--public-builds, 596
--releases-access-level, 596
--remove-source-branch-after-merge, 596
--repository-access-level, 596
--repository-storage, 596
--request-access-enabled, 596
--requirements-access-level, 596
--resolve-outdated-diff-discussions, 596
--security-and-compliance-access-level, 596
--shared-runners-enabled, 596
--show-default-award-emojis, 596
--snippets-access-level, 596
--snippets-enabled, 596
--squash-option, 596
--sudo, 594
--tag-list, 596
--template-name, 597
--template-project-id, 597
--topics, 596
--visibility, 597
--wiki-access-level, 597
--wiki-enabled, 597
-h, 594
gitlab-project-create-fork-relation command
    line option
    --forked-from-id, 597
    --help, 597
    --id, 597
    -h, 597
gitlab-project-custom-attribute command
    line option
    --help, 638
    -h, 638
gitlab-project-custom-attribute-delete
    command line option
    --help, 638
    --key, 638
    --project-id, 638
    --sudo, 638
    -h, 638
gitlab-project-custom-attribute-get command
    line option
    --help, 638
    --key, 638
    --project-id, 638
    --sudo, 638
    -h, 638
gitlab-project-custom-attribute-list
    command line option
    --all, 639
    --get-all, 639
    --help, 639
    --page, 639
    --per-page, 639
    --project-id, 639
    --sudo, 639
    -h, 639
gitlab-project-delete command line option
    --help, 597
    --id, 597
    --sudo, 597
    -h, 597
gitlab-project-delete-fork-relation command
    line option
    --help, 597
    --id, 597
```

```
-h, 597
gitlab-project-delete-merged-branches
    command line option
    --help, 598
    --id, 598
    -h, 598
gitlab-project-deploy-token command line
    option
    --help, 639
    -h, 639
gitlab-project-deploy-token-create command
    line option
    --expires-at, 639
    --help, 639
    --name, 639
    --project-id, 639
    --scopes, 639
    --sudo, 639
    --username, 639
    -h, 639
gitlab-project-deploy-token-delete command
    line option
    --help, 640
    --id, 640
    --project-id, 640
    --sudo, 640
    -h, 640
gitlab-project-deploy-token-get command
    line option
    --help, 640
    --id, 640
    --project-id, 640
    --sudo, 640
    -h, 640
gitlab-project-deploy-token-list command
    line option
    --all, 640
    --get-all, 640
    --help, 640
    --page, 640
    --per-page, 640
    --project-id, 640
    --scopes, 640
    --sudo, 640
    -h, 640
gitlab-project-deployment command line
    option
    --help, 641
    -h, 641
gitlab-project-deployment-approval command
    line option
    --comment, 641
    --help, 641
    --id, 641
    --project-id, 641
    --ref, 641
    --represented-as, 641
    --status, 641
    --sudo, 641
    -h, 641
gitlab-project-deployment-create command
    line option
    --environment, 641
    --help, 641
    --project-id, 641
    --ref, 641
    --sha, 641
    --status, 641
    --sudo, 641
    --tag, 641
    -h, 641
gitlab-project-deployment-get command line
    option
    --help, 642
    --id, 642
    --project-id, 642
    --sudo, 642
    -h, 642
gitlab-project-deployment-list command line
    option
    --all, 642
    --environment, 642
    --get-all, 642
    --help, 642
    --order-by, 642
    --page, 642
    --per-page, 642
    --project-id, 642
    --sort, 642
    --status, 642
    --sudo, 642
    --updated-after, 642
    --updated-before, 642
    -h, 642
gitlab-project-deployment-merge-request
    command line option
    --help, 643
    -h, 643
gitlab-project-deployment-merge-request-list
    command line option
    --all, 645
    --approved-by-ids, 644
    --approver-ids, 644
    --assignee-id, 644
    --author-id, 644
    --author-username, 644
    --created-after, 644
    --created-before, 644
    --deployed-after, 645
```

```

--deployed-before, 645
--deployment-id, 644
--environment, 645
--get-all, 645
--help, 644
--in, 645
--labels, 644
--milestone, 644
--my-reaction-emoji, 645
--not, 645
--order-by, 644
--page, 645
--per-page, 645
--project-id, 644
--reviewer-id, 644
--reviewer-username, 644
--scope, 644
--search, 645
--sort, 644
--source-branch, 645
--state, 644
--sudo, 644
--target-branch, 645
--updated-after, 644
--updated-before, 644
--view, 644
--wip, 645
--with-labels-details, 644
--with-merge-status-recheck, 644
-h, 644
gitlab-project-deployment-update command
    line option
    --help, 643
    --id, 643
    --project-id, 643
    --sudo, 643
    -h, 643
gitlab-project-environment command line
    option
    --help, 645
    -h, 645
gitlab-project-environment-create command
    line option
    --external-url, 646
    --help, 645
    --name, 646
    --project-id, 646
    --sudo, 645
    -h, 645
gitlab-project-environment-delete command
    line option
    --help, 646
    --id, 646
    --project-id, 646
    --sudo, 646
    -h, 646
gitlab-project-environment-get command line
    option
    --help, 646
    -h, 646
gitlab-project-environment-list command
    line option
    --all, 647
    --get-all, 647
    --help, 646
    --name, 646
    --page, 647
    --per-page, 647
    --project-id, 646
    --search, 646
    --states, 647
    --sudo, 646
    -h, 646
gitlab-project-environment-stop command
    line option
    --help, 647
    --id, 647
    --project-id, 647
    --sudo, 647
    -h, 647
gitlab-project-environment-update command
    line option
    --external-url, 647
    --help, 647
    --id, 647
    --name, 647
    --project-id, 647
    --sudo, 647
    -h, 647
gitlab-project-event command line option
    --help, 648
    -h, 648
gitlab-project-event-list command line
    option
    --action, 648
    --after, 648
    --all, 648
    --before, 648
    --get-all, 648
    --help, 648
    --page, 648
    --per-page, 648
    --project-id, 648
    --sort, 648
    --sudo, 648

```

```
--target-type, 648
-h, 648
gitlab-project-export command line option
--help, 648
-h, 648
gitlab-project-export-create command line
    option
--description, 649
--help, 649
--project-id, 649
--sudo, 649
-h, 649
gitlab-project-export-download command line
    option
--help, 649
--project-id, 649
--sudo, 649
-h, 649
gitlab-project-export-get command line
    option
--help, 649
--project-id, 649
--sudo, 649
-h, 649
gitlab-project-file command line option
--help, 649
-h, 649
gitlab-project-file-blame command line
    option
--file-path, 650
--help, 650
--project-id, 650
--ref, 650
--sudo, 650
-h, 650
gitlab-project-file-create command line
    option
--author-email, 650
--author-name, 650
--branch, 650
--commit-message, 650
--content, 650
--encoding, 650
--file-path, 650
--help, 650
--project-id, 650
--sudo, 650
-h, 650
gitlab-project-file-delete command line
    option
--branch, 651
--commit-message, 651
--file-path, 651
--help, 651
--project-id, 651
--ref, 651
--sudo, 651
-h, 651
gitlab-project-file-get command line option
--file-path, 651
--help, 651
--project-id, 651
--ref, 651
--sudo, 651
-h, 651
gitlab-project-file-raw command line option
--file-path, 651
--help, 651
--project-id, 651
--ref, 651
--sudo, 651
-h, 651
gitlab-project-file-update command line
    option
--author-email, 652
--author-name, 652
--branch, 652
--commit-message, 652
--content, 652
--encoding, 652
--file-path, 652
--help, 652
--project-id, 652
--sudo, 652
-h, 652
gitlab-project-fork command line option
--help, 652
-h, 652
gitlab-project-fork-create command line
    option
--help, 652
--namespace, 652
--project-id, 652
--sudo, 652
-h, 652
gitlab-project-fork-list command line
    option
--all, 653
--archived, 653
--get-all, 653
--help, 653
--membership, 653
--order-by, 653
--owned, 653
--page, 653
--per-page, 653
--project-id, 653
--search, 653
--simple, 653
```

```
--sort, 653
--starred, 653
--statistics, 653
--sudo, 653
--visibility, 653
--with-custom-attributes, 653
--with-issues-enabled, 653
--with-merge-requests-enabled, 653
-h, 653
gitlab-project-get command line option
--help, 598
--id, 598
--sudo, 598
-h, 598
gitlab-project-hook command line option
--help, 654
-h, 654
gitlab-project-hook-create command line
    option
--confidential-issues-events, 654
--enable-ssl-verification, 654
--help, 654
--issues-events, 654
--job-events, 654
--merge-requests-events, 654
--note-events, 654
--pipeline-events, 654
--project-id, 654
--push-events, 654
--sudo, 654
--tag-push-events, 654
--token, 654
--url, 654
--wiki-page-events, 654
-h, 654
gitlab-project-hook-delete command line
    option
--help, 655
--id, 655
--project-id, 655
--sudo, 655
-h, 655
gitlab-project-hook-get command line option
--help, 655
--id, 655
--project-id, 655
--sudo, 655
-h, 655
gitlab-project-hook-list command line
    option
--all, 655
--get-all, 655
--help, 655
--page, 655
--per-page, 655
--project-id, 655
--sudo, 655
-h, 655
gitlab-project-hook-update command line
    option
--confidential-issues-events, 656
--enable-ssl-verification, 656
--help, 656
--id, 656
--issues-events, 656
--job-events, 656
--merge-requests-events, 656
--note-events, 656
--pipeline-events, 656
--project-id, 656
--push-events, 656
--sudo, 656
--tag-push-events, 656
--token, 656
--url, 656
--wiki-events, 656
-h, 656
gitlab-project-housekeeping command line
    option
--help, 598
--id, 598
-h, 598
gitlab-project-import command line option
--help, 657
-h, 657
gitlab-project-import-get command line
    option
--help, 657
--project-id, 657
--sudo, 657
-h, 657
gitlab-project-integration command line
    option
--help, 657
-h, 657
gitlab-project-integration-available
    command line option
--help, 657
--project-id, 657
--slug, 657
--sudo, 657
-h, 657
gitlab-project-integration-delete command
    line option
--help, 657
--project-id, 657
--slug, 657
--sudo, 657
```

```
-h, 657
gitlab-project-integration-get command line
    option
--help, 658
--project-id, 658
--slug, 658
--sudo, 658
-h, 658
gitlab-project-integration-list command
    line option
--all, 658
--get-all, 658
--help, 658
--page, 658
--per-page, 658
--project-id, 658
--sudo, 658
-h, 658
gitlab-project-integration-update command
    line option
--help, 658
--project-id, 658
--slug, 658
--sudo, 658
-h, 658
gitlab-project-invitation command line
    option
--help, 659
-h, 659
gitlab-project-invitation-create command
    line option
--access-level, 659
--expires-at, 659
--help, 659
--invite-source, 659
--project-id, 659
--sudo, 659
--tasks-project-id, 659
--tasks-to-be-done, 659
-h, 659
gitlab-project-invitation-delete command
    line option
--email, 659
--help, 659
--project-id, 659
--sudo, 659
-h, 659
gitlab-project-invitation-get command line
    option
--email, 660
--help, 660
--project-id, 660
--sudo, 660
-h, 660
gitlab-project-invitation-list command line option
--all, 660
--get-all, 660
--help, 660
--page, 660
--per-page, 660
--project-id, 660
--query, 660
--sudo, 660
-h, 660
gitlab-project-invitation-update command
    line option
--access-level, 661
--email, 660
--expires-at, 661
--help, 660
--project-id, 660
--sudo, 660
-h, 660
gitlab-project-issue command line option
--help, 661
-h, 661
gitlab-project-issue-add-spent-time command
    line option
--duration, 661
--help, 661
--iid, 661
--project-id, 661
--sudo, 661
-h, 661
gitlab-project-issue-award-emoji command
    line option
--help, 669
-h, 669
gitlab-project-issue-award-emoji-create command line option
--help, 669
--issue-iid, 669
--name, 669
--project-id, 669
--sudo, 669
-h, 669
gitlab-project-issue-award-emoji-delete command line option
--help, 669
--id, 669
--issue-iid, 669
--project-id, 669
--sudo, 669
-h, 669
gitlab-project-issue-award-emoji-get command line option
--help, 670
```

```

--id, 670
--issue-iid, 670
--project-id, 670
--sudo, 670
-h, 670
gitlab-project-issue-award-emoji-list
    command line option
--all, 670
--get-all, 670
--help, 670
--issue-iid, 670
--page, 670
--per-page, 670
--project-id, 670
--sudo, 670
-h, 670
gitlab-project-issue-closed-by command line
    option
--help, 662
--iid, 662
--project-id, 662
--sudo, 662
-h, 662
gitlab-project-issue-create command line
    option
--assignee-id, 662
--assignee-ids, 662
--confidential, 662
--created-at, 662
--description, 662
--discussion-to-resolve, 662
--due-date, 662
--help, 662
--labels, 662
--merge-request-to-resolve-discussions-of,
    662
--milestone-id, 662
--project-id, 662
--sudo, 662
--title, 662
-h, 662
gitlab-project-issue-delete command line
    option
--help, 663
--iid, 663
--project-id, 663
--sudo, 663
-h, 663
gitlab-project-issue-discussion command
    line option
--help, 670
-h, 670
gitlab-project-issue-discussion-create
    command line option
--body, 671
--created-at, 671
--help, 671
--issue-iid, 671
--project-id, 671
--sudo, 671
-h, 671
gitlab-project-issue-discussion-get command
    line option
--help, 671
--id, 671
--issue-iid, 671
--project-id, 671
--sudo, 671
-h, 671
gitlab-project-issue-discussion-list
    command line option
--all, 672
--get-all, 672
--help, 671
--issue-iid, 671
--page, 671
--per-page, 672
--project-id, 671
--sudo, 671
-h, 671
gitlab-project-issue-discussion-note
    command line option
--help, 672
-h, 672
gitlab-project-issue-discussion-note-create
    command line option
--body, 672
--created-at, 672
--discussion-id, 672
--help, 672
--issue-iid, 672
--project-id, 672
--sudo, 672
-h, 672
gitlab-project-issue-discussion-note-delete
    command line option
--discussion-id, 673
--help, 673
--id, 673
--issue-iid, 673
--project-id, 673
--sudo, 673
-h, 673
gitlab-project-issue-discussion-note-get
    command line option
--discussion-id, 673
--help, 673
--id, 673

```

```
--issue-iid, 673
--project-id, 673
--sudo, 673
-h, 673
gitlab-project-issue-discussion-note-update
    command line option
--body, 674
--discussion-id, 674
--help, 673
--id, 674
--issue-iid, 674
--project-id, 674
--sudo, 673
-h, 673
gitlab-project-issue-get command line
    option
--help, 663
--iid, 663
--project-id, 663
--sudo, 663
-h, 663
gitlab-project-issue-link command line
    option
--help, 674
-h, 674
gitlab-project-issue-link-create command
    line option
--help, 674
--issue-iid, 674
--project-id, 674
--sudo, 674
--target-issue-iid, 674
--target-project-id, 674
-h, 674
gitlab-project-issue-link-delete command
    line option
--help, 674
--issue-iid, 674
--issue-link-id, 674
--project-id, 674
--sudo, 674
-h, 674
gitlab-project-issue-link-list command line
    option
--all, 675
--get-all, 675
--help, 675
--issue-iid, 675
--page, 675
--per-page, 675
--project-id, 675
--sudo, 675
-h, 675
gitlab-project-issue-list command line
    option
--all, 664
--assignee-id, 664
--author-id, 664
--created-after, 664
--created-before, 664
--get-all, 664
--help, 663
--iids, 663
--labels, 664
--milestone, 664
--my-reaction-emoji, 664
--order-by, 664
--page, 664
--per-page, 664
--project-id, 663
--scope, 664
--search, 664
--sort, 664
--state, 663
--sudo, 663
--updated-after, 664
--updated-before, 664
-h, 663
gitlab-project-issue-move command line
    option
--help, 664
--iid, 664
--project-id, 664
--sudo, 664
--to-project-id, 664
-h, 664
gitlab-project-issue-note command line
    option
--help, 675
-h, 675
gitlab-project-issue-note-award-emoji
    command line option
--help, 677
-h, 677
gitlab-project-issue-note-award-emoji-create
    command line option
--help, 677
--issue-iid, 677
--name, 677
--note-id, 677
--project-id, 677
--sudo, 677
-h, 677
gitlab-project-issue-note-award-emoji-delete
    command line option
--help, 678
--id, 678
```

```
--issue-iid, 678
--note-id, 678
--project-id, 678
--sudo, 678
-h, 678
gitlab-project-issue-note-award-emoji-get
    command line option
--help, 678
--id, 678
--issue-iid, 678
--note-id, 678
--project-id, 678
--sudo, 678
-h, 678
gitlab-project-issue-note-award-emoji-list
    command line option
--all, 679
--get-all, 679
--help, 678
--issue-iid, 679
--note-id, 679
--page, 679
--per-page, 679
--project-id, 679
--sudo, 678
-h, 678
gitlab-project-issue-note-create command
    line option
--body, 675
--created-at, 675
--help, 675
--issue-iid, 675
--project-id, 675
--sudo, 675
-h, 675
gitlab-project-issue-note-delete command
    line option
--help, 676
--id, 676
--issue-iid, 676
--project-id, 676
--sudo, 676
-h, 676
gitlab-project-issue-note-get command line
    option
--help, 676
--id, 676
--issue-iid, 676
--project-id, 676
--sudo, 676
-h, 676
gitlab-project-issue-note-list command line
    option
--all, 677
--get-all, 676
--help, 676
--id, 676
--issue-iid, 676
--page, 676
--per-page, 676
--project-id, 676
--sudo, 676
-h, 676
gitlab-project-issue-note-update command
    line option
--body, 677
--help, 677
--id, 677
--issue-iid, 677
--project-id, 677
--sudo, 677
-h, 677
gitlab-project-issue-participants command
    line option
--help, 665
--iid, 665
--project-id, 665
--sudo, 665
-h, 665
gitlab-project-issue-related-merge-requests
    command line option
--help, 665
--iid, 665
--project-id, 665
--sudo, 665
-h, 665
gitlab-project-issue-reorder command line
    option
--help, 665
--iid, 665
--move-after-id, 665
--move-before-id, 665
--project-id, 665
--sudo, 665
-h, 665
gitlab-project-issue-reset-spent-time
    command line option
--help, 666
--iid, 666
--project-id, 666
--sudo, 666
-h, 666
gitlab-project-issue-reset-time-estimate
    command line option
--help, 666
--iid, 666
--project-id, 666
--sudo, 666
-h, 666
```

```
gitlab-project-issue-resource-iteration-event      --issue-iid, 681
    command line option
    --help, 679
    -h, 679
gitlab-project-issue-resource-iteration-event      --project-id, 681
    command line option
    --help, 679
    --id, 679
    --issue-iid, 679
    --project-id, 679
    --sudo, 679
    -h, 679
gitlab-project-issue-resource-iteration-event-list --sudo, 681
    command line option
    --all, 682
    --get-all, 682
    --help, 682
    --issue-iid, 682
    --page, 682
    --per-page, 682
gitlab-project-issue-resource-iteration-event-list-project-id, 682
    command line option
    --all, 680
    --get-all, 680
    --help, 679
    --issue-iid, 680
    --page, 680
    --per-page, 680
    --project-id, 680
    --sudo, 680
    -h, 679
gitlab-project-issue-resource-label-event          --sudo, 682
    command line option
    --help, 680
    -h, 680
gitlab-project-issue-resource-label-event          --h, 682
gitlab-project-issue-resource-label-event-get      gitlab-project-issue-resource-state-event
    command line option
    --help, 682
    --id, 682
    --issue-iid, 682
    --project-id, 682
    --sudo, 682
    -h, 682
gitlab-project-issue-resource-label-event-get      gitlab-project-issue-resource-state-event-list
    command line option
    --help, 680
    --id, 680
    --issue-iid, 680
    --project-id, 680
    --sudo, 680
    -h, 680
gitlab-project-issue-resource-label-event-get      gitlab-project-issue-resource-state-event-list
    command line option
    --all, 683
    --get-all, 683
    --help, 683
    --issue-iid, 683
    --page, 683
    --per-page, 683
gitlab-project-issue-resource-label-event-list     --project-id, 683
    command line option
    --all, 681
    --get-all, 681
    --help, 680
    --issue-iid, 681
    --page, 681
    --per-page, 681
    --project-id, 681
    --sudo, 681
    -h, 680
gitlab-project-issue-resource-milestone-event     --sudo, 683
    command line option
    --help, 681
    -h, 681
gitlab-project-issue-resource-milestone-event     gitlab-project-issue-resource-weight-event
    command line option
    --help, 681
    --id, 681
    --issue-iid, 681
    --project-id, 683
    --sudo, 683
    -h, 683
gitlab-project-issue-resource-milestone-event     gitlab-project-issue-resource-weight-event-list
    command line option
    --all, 684
    --get-all, 684
```

```

--help, 684
--issue-iid, 684
--page, 684
--per-page, 684
--project-id, 684
--sudo, 684
-h, 684
gitlab-project-issue-subscribe command line
    option
--help, 666
--iid, 666
--project-id, 666
--sudo, 666
-h, 666
gitlab-project-issue-time-estimate command
    line option
--duration, 667
--help, 666
--iid, 667
--project-id, 666
--sudo, 666
-h, 666
gitlab-project-issue-time-stats command
    line option
--help, 667
--iid, 667
--project-id, 667
--sudo, 667
-h, 667
gitlab-project-issue-todo command line
    option
--help, 667
--iid, 667
--project-id, 667
--sudo, 667
-h, 667
gitlab-project-issue-unsubscribe command
    line option
--help, 667
--iid, 667
--project-id, 667
--sudo, 667
-h, 667
gitlab-project-issue-update command line
    option
--assignee-id, 668
--assignee-ids, 668
--confidential, 668
--description, 668
--discussion-locked, 668
--due-date, 668
--help, 668
--iid, 668
--labels, 668
--milestone-id, 668
--project-id, 668
--state-event, 668
--sudo, 668
--title, 668
--updated-at, 668
-h, 668
gitlab-project-issue-user-agent-detail
    command line option
--help, 668
--iid, 669
--project-id, 668
--sudo, 668
-h, 668
gitlab-project-issues-statistics command
    line option
--help, 684
-h, 684
gitlab-project-issues-statistics-get
    command line option
--help, 684
--project-id, 684
--sudo, 684
-h, 684
gitlab-project-job command line option
--help, 685
-h, 685
gitlab-project-job-artifact command line
    option
--help, 685
--id, 685
--project-id, 685
--sudo, 685
-h, 685
gitlab-project-job-artifacts command line
    option
--help, 685
--id, 685
--project-id, 685
--sudo, 685
-h, 685
gitlab-project-job-cancel command line
    option
--help, 686
--id, 686
--project-id, 686
--sudo, 686
-h, 686
gitlab-project-job-delete-artifacts command
    line option
--help, 686
--id, 686
--project-id, 686
--sudo, 686

```

```
-h, 686
gitlab-project-job-erase command line
    option
    --help, 686
    --id, 686
    --project-id, 686
    --sudo, 686
    -h, 686
gitlab-project-job-get command line option
    --help, 686
    --id, 687
    --project-id, 686
    --sudo, 686
    -h, 686
gitlab-project-job-keep-artifacts command
    line option
    --help, 687
    --id, 687
    --project-id, 687
    --sudo, 687
    -h, 687
gitlab-project-job-list command line option
    --all, 687
    --get-all, 687
    --help, 687
    --page, 687
    --per-page, 687
    --project-id, 687
    --scope, 687
    --sudo, 687
    -h, 687
gitlab-project-job-play command line option
    --help, 687
    --id, 688
    --project-id, 687
    --sudo, 687
    -h, 687
gitlab-project-job-retry command line
    option
    --help, 688
    --id, 688
    --project-id, 688
    --sudo, 688
    -h, 688
gitlab-project-job-trace command line
    option
    --help, 688
    --id, 688
    --project-id, 688
    --sudo, 688
    -h, 688
gitlab-project-key command line option
    --help, 688
    -h, 688
gitlab-project-key-create command line
    option
    --can-push, 689
    --help, 688
    --key, 689
    --project-id, 688
    --sudo, 688
    --title, 688
    -h, 688
gitlab-project-key-delete command line
    option
    --help, 689
    --id, 689
    --project-id, 689
    --sudo, 689
    -h, 689
gitlab-project-key-enable command line
    option
    --help, 689
    --id, 689
    --key-id, 689
    --project-id, 689
    --sudo, 689
    -h, 689
gitlab-project-key-get command line option
    --help, 689
    --id, 689
    --project-id, 689
    --sudo, 689
    -h, 689
gitlab-project-key-list command line option
    --all, 690
    --get-all, 690
    --help, 690
    --page, 690
    --per-page, 690
    --project-id, 690
    --sudo, 690
    -h, 690
gitlab-project-key-update command line
    option
    --can-push, 690
    --help, 690
    --id, 690
    --project-id, 690
    --sudo, 690
    --title, 690
    -h, 690
gitlab-project-label command line option
    --help, 690
    -h, 690
gitlab-project-label-create command line
    option
    --color, 691
```

```

--description, 691
--help, 691
--name, 691
--priority, 691
--project-id, 691
--sudo, 691
-h, 691
gitlab-project-label-delete command line
    option
--help, 691
--name, 691
--project-id, 691
--sudo, 691
-h, 691
gitlab-project-label-get command line
    option
--help, 691
--name, 691
--project-id, 691
--sudo, 691
-h, 691
gitlab-project-label-list command line
    option
--all, 692
--get-all, 692
--help, 692
--page, 692
--per-page, 692
--project-id, 692
--sudo, 692
-h, 692
gitlab-project-label-subscribe command line
    option
--help, 692
--name, 692
--project-id, 692
--sudo, 692
-h, 692
gitlab-project-label-unsubscribe command
    line option
--help, 692
--name, 692
--project-id, 692
--sudo, 692
-h, 692
gitlab-project-label-update command line
    option
--color, 693
--description, 693
--help, 693
--name, 693
--new-name, 693
--priority, 693
--project-id, 693
--sudo, 693
-h, 693
gitlab-project-languages command line
    option
--help, 598
--id, 598
-h, 598
gitlab-project-list command line option
--all, 600
--archived, 599
--get-all, 600
--help, 599
--id-after, 599
--id-before, 599
--last-activity-after, 599
--last-activity-before, 599
--membership, 599
--min-access-level, 599
--order-by, 599
--owned, 599
--page, 600
--per-page, 600
--repository-checksum-failed, 599
--repository-storage, 599
--search, 599
--search-namespaces, 599
--simple, 599
--sort, 599
--starred, 599
--statistics, 599
--sudo, 599
--topic, 599
--visibility, 599
--wiki-checksum-failed, 599
--with-custom-attributes, 599
--with-issues-enabled, 599
--with-merge-requests-enabled, 600
--with-programming-language, 600
-h, 599
gitlab-project-member command line option
--help, 693
-h, 693
gitlab-project-member-all command line
    option
--help, 695
-h, 695
gitlab-project-member-all-get command line
    option
--help, 695
--id, 695
--project-id, 695
--sudo, 695
-h, 695

```

```
gitlab-project-member-all-list command line
    option
    --all, 696
    --get-all, 696
    --help, 695
    --page, 696
    --per-page, 696
    --project-id, 695
    --sudo, 695
    -h, 695
gitlab-project-member-create command line
    option
    --access-level, 693
    --expires-at, 693
    --help, 693
    --project-id, 693
    --sudo, 693
    --tasks-to-be-done, 693
    --user-id, 693
    -h, 693
gitlab-project-member-delete command line
    option
    --help, 694
    --id, 694
    --project-id, 694
    --sudo, 694
    -h, 694
gitlab-project-member-get command line
    option
    --help, 694
    --id, 694
    --project-id, 694
    --sudo, 694
    -h, 694
gitlab-project-member-list command line
    option
    --all, 694
    --get-all, 694
    --help, 694
    --page, 694
    --per-page, 694
    --project-id, 694
    --sudo, 694
    -h, 694
gitlab-project-member-update command line
    option
    --access-level, 695
    --expires-at, 695
    --help, 695
    --id, 695
    --project-id, 695
    --sudo, 695
    -h, 695
gitlab-project-merge-request command line
    option
    --help, 696
    -h, 696
gitlab-project-merge-request-add-spent-time
    command line option
    --duration, 697
    --help, 697
    --iid, 697
    --project-id, 697
    --sudo, 697
    -h, 697
gitlab-project-merge-request-approval
    command line option
    --help, 707
    -h, 707
gitlab-project-merge-request-approval-get
    command line option
    --help, 707
    --mr-iid, 707
    --project-id, 707
    --sudo, 707
    -h, 707
gitlab-project-merge-request-approval-rule
    command line option
    --help, 707
    -h, 707
gitlab-project-merge-request-approval-rule-create
    command line option
    --approval-project-rule-id, 708
    --approvals-required, 708
    --group-ids, 708
    --help, 708
    --id, 708
    --merge-request-iid, 708
    --mr-iid, 708
    --name, 708
    --project-id, 708
    --sudo, 708
    --user-ids, 708
    -h, 708
gitlab-project-merge-request-approval-rule-delete
    command line option
    --help, 708
    --id, 709
    --mr-iid, 709
    --project-id, 708
    --sudo, 708
    -h, 708
gitlab-project-merge-request-approval-rule-get
    command line option
    --help, 709
    --id, 709
    --mr-iid, 709
```

```

--project-id, 709
--sudo, 709
-h, 709
gitlab-project-merge-request-approval-rule-list      command line option
    --all, 709
    --get-all, 709
    --help, 709
    --mr-iid, 709
    --page, 709
    --per-page, 709
    --project-id, 709
    --sudo, 709
    -h, 709
gitlab-project-merge-request-approval-rule-update    command line option
    --approval-rule-id, 710
    --approvals-required, 710
    --group-ids, 710
    --help, 710
    --id, 710
    --merge-request-iid, 710
    --mr-iid, 710
    --name, 710
    --project-id, 710
    --sudo, 710
    --user-ids, 710
    -h, 710
gitlab-project-merge-request-approval-state          command line option
    --help, 710
    -h, 710
gitlab-project-merge-request-approval-state-get     command line option
    --help, 711
    --id, 711
    --mr-iid, 711
    --project-id, 711
    --sudo, 711
    -h, 711
gitlab-project-merge-request-approval-update         command line option
    --approvals-required, 707
    --help, 707
    --mr-iid, 707
    --project-id, 707
    --sudo, 707
    -h, 707
gitlab-project-merge-request-approve               command line option
    --help, 697
    --iid, 697
    --project-id, 697
    --sha, 697
                                         --sudo, 697
                                         -h, 697
gitlab-project-merge-request-award-emoji           command line option
    --help, 711
    -h, 711
gitlab-project-merge-request-award-emoji-create    command line option
    --help, 711
    --mr-iid, 711
    --name, 711
    --project-id, 711
    --sudo, 711
    -h, 711
gitlab-project-merge-request-award-emoji-delete   command line option
    --help, 712
    --id, 712
    --mr-iid, 712
    --project-id, 712
    --sudo, 712
    -h, 712
gitlab-project-merge-request-award-emoji-get      command line option
    --help, 712
    --id, 712
    --mr-iid, 712
    --project-id, 712
    --sudo, 712
    -h, 712
gitlab-project-merge-request-award-emoji-list     command line option
    --all, 713
    --get-all, 713
    --help, 712
    --mr-iid, 712
    --page, 712
    --per-page, 712
    --project-id, 712
    --sudo, 712
    -h, 712
gitlab-project-merge-request-cancel-merge-when-pipeline-su
    command line option
    --help, 697
    --iid, 697
    --project-id, 697
    --sudo, 697
    -h, 697
gitlab-project-merge-request-changes              command line option
    --access-raw-diffs, 698
    --help, 698
    --iid, 698
    --project-id, 698

```

```
--sudo, 698
-h, 698
gitlab-project-merge-request-closes-issues
    command line option
--help, 698
--iid, 698
--project-id, 698
--sudo, 698
-h, 698
gitlab-project-merge-request-commits
    command line option
--help, 698
--iid, 698
--project-id, 698
--sudo, 698
-h, 698
gitlab-project-merge-request-create command
    line option
--allow-collaboration, 699
--allow-maintainer-to-push, 699
--approvals-before-merge, 699
--assignee-id, 699
--assignee-ids, 699
--description, 699
--help, 699
--labels, 699
--milestone-id, 699
--project-id, 699
--remove-source-branch, 699
--reviewer-ids, 699
--source-branch, 699
--squash, 699
--sudo, 699
--target-branch, 699
--target-project-id, 699
--title, 699
-h, 699
gitlab-project-merge-request-delete command
    line option
--help, 700
--iid, 700
--project-id, 700
--sudo, 700
-h, 700
gitlab-project-merge-request-diff command
    line option
--help, 713
-h, 713
gitlab-project-merge-request-diff-get
    command line option
--help, 713
--id, 713
--mr-iid, 713
--project-id, 713
--sudo, 713
-h, 713
gitlab-project-merge-request-diff-list
    command line option
--all, 714
--get-all, 713
--help, 713
--mr-iid, 713
--page, 713
--per-page, 713
--project-id, 713
--sudo, 713
-h, 713
gitlab-project-merge-request-discussion
    command line option
--help, 714
-h, 714
gitlab-project-merge-request-discussion-create
    command line option
--body, 714
--created-at, 714
--help, 714
--mr-iid, 714
--position, 714
--project-id, 714
--sudo, 714
-h, 714
gitlab-project-merge-request-discussion-get
    command line option
--help, 714
--id, 715
--mr-iid, 715
--project-id, 714
--sudo, 714
-h, 714
gitlab-project-merge-request-discussion-list
    command line option
--all, 715
--get-all, 715
--help, 715
--mr-iid, 715
--page, 715
--per-page, 715
--project-id, 715
--sudo, 715
-h, 715
gitlab-project-merge-request-discussion-note
    command line option
--help, 716
-h, 716
gitlab-project-merge-request-discussion-note-create
    command line option
--body, 716
--created-at, 716
```

```

--discussion-id, 716
--help, 716
--mr-iid, 716
--project-id, 716
--sudo, 716
-h, 716
gitlab-project-merge-request-discussion-note-delete-author-id, 701
    command line option
--discussion-id, 717
--help, 716
--id, 717
--mr-iid, 717
--project-id, 716
--sudo, 716
-h, 716
gitlab-project-merge-request-discussion-note-get
    command line option
--discussion-id, 717
--help, 717
--id, 717
--mr-iid, 717
--project-id, 717
--sudo, 717
-h, 717
gitlab-project-merge-request-discussion-note-update-sudo, 701
    command line option
--body, 717
--discussion-id, 717
--help, 717
--id, 717
--mr-iid, 717
--project-id, 717
--sudo, 717
-h, 717
gitlab-project-merge-request-discussion-update
    command line option
--help, 715
--id, 715
--mr-iid, 715
--project-id, 715
--resolved, 715
--sudo, 715
-h, 715
gitlab-project-merge-request-get command
    line option
--help, 700
--iid, 700
--include-diverged-commits-count, 700
--include-rebase-in-progress, 700
--project-id, 700
--render-html, 700
--sudo, 700
-h, 700
gitlab-project-merge-request-list command
    line option
--all, 702
--approved-by-ids, 701
--approver-ids, 701
--assignee-id, 701
--created-after, 701
--created-before, 701
--get-all, 702
--help, 701
--iids, 701
--labels, 701
--milestone, 701
--my-reaction-emoji, 701
--order-by, 701
--page, 701
--per-page, 702
--project-id, 701
--scope, 701
--search, 701
--sort, 701
--source-branch, 701
--state, 701
--target-branch, 701
--updated-after, 701
--updated-before, 701
--view, 701
--wip, 701
-h, 701
gitlab-project-merge-request-merge command
    line option
--help, 702
--iid, 702
--merge-commit-message, 702
--merge-when-pipeline-succeeds, 702
--project-id, 702
--should-remove-source-branch, 702
--sudo, 702
-h, 702
gitlab-project-merge-request-merge-ref
    command line option
--help, 702
--iid, 702
--project-id, 702
--sudo, 702
-h, 702
gitlab-project-merge-request-note command
    line option
--help, 718
-h, 718
gitlab-project-merge-request-note-award-emoji
    command line option

```

```
--help, 720  
-h, 720  
gitlab-project-merge-request-note-award-emoji-create  
    command line option  
    --help, 720  
    --mr-iid, 720  
    --name, 720  
    --note-id, 720  
    --project-id, 720  
    --sudo, 720  
    -h, 720  
gitlab-project-merge-request-note-award-emoji-create  
    command line option  
    --help, 720  
    --id, 721  
    --mr-iid, 721  
    --note-id, 721  
    --project-id, 720  
    --sudo, 720  
    -h, 720  
gitlab-project-merge-request-note-award-emoji-get  
    command line option  
    --help, 721  
    --id, 721  
    --mr-iid, 721  
    --note-id, 721  
    --project-id, 721  
    --sudo, 721  
    -h, 721  
gitlab-project-merge-request-note-award-emoji-list-sudo, 719  
    command line option  
    --all, 722  
    --get-all, 721  
    --help, 721  
    --mr-iid, 721  
    --note-id, 721  
    --page, 721  
    --per-page, 721  
    --project-id, 721  
    --sudo, 721  
    -h, 721  
gitlab-project-merge-request-note-create  
    command line option  
    --body, 718  
    --help, 718  
    --mr-iid, 718  
    --project-id, 718  
    --sudo, 718  
    -h, 718  
gitlab-project-merge-request-note-delete  
    command line option  
    --help, 718  
    --id, 718  
    --mr-iid, 718  
    --project-id, 718  
    --sudo, 718  
    -h, 718  
gitlab-project-merge-request-note-get  
    command line option  
    --help, 719  
    --id, 719  
    --mr-iid, 719  
    --project-id, 719  
    --sudo, 719  
    -h, 719  
gitlab-project-merge-request-note-list  
    command line option  
    --all, 719  
    --get-all, 719  
    --help, 719  
    --mr-iid, 719  
    --page, 719  
    --per-page, 719  
    --project-id, 719  
    --sudo, 719  
    -h, 719  
gitlab-project-merge-request-note-update  
    command line option  
    --body, 720  
    --help, 719  
    --id, 720  
    --mr-iid, 720  
    --project-id, 720  
    --sudo, 720  
    -h, 719  
gitlab-project-merge-request-participants  
    command line option  
    --help, 703  
    --iid, 703  
    --project-id, 703  
    --sudo, 703  
    -h, 703  
gitlab-project-merge-request-pipeline  
    command line option  
    --help, 722  
    -h, 722  
gitlab-project-merge-request-pipeline-create  
    command line option  
    --help, 722  
    --mr-iid, 722  
    --project-id, 722  
    --sudo, 722  
    -h, 722  
gitlab-project-merge-request-pipeline-list  
    command line option  
    --all, 722  
    --get-all, 722  
    --help, 722
```

```

--mr-iid, 722
--page, 722
--per-page, 722
--project-id, 722
--sudo, 722
-h, 722
gitlab-project-merge-request-rebase command
    line option
--help, 703
--iid, 703
--project-id, 703
--sudo, 703
-h, 703
gitlab-project-merge-request-reset-approvals
    command line option
--help, 703
--iid, 703
--project-id, 703
--sudo, 703
-h, 703
gitlab-project-merge-request-reset-spent-time
    command line option
--help, 703
--iid, 704
--project-id, 703
--sudo, 704
-h, 703
gitlab-project-merge-request-reset-time-estimate
    command line option
--help, 704
--iid, 704
--project-id, 704
--sudo, 704
-h, 704
gitlab-project-merge-request-resource-label-event
    command line option
--help, 723
-h, 723
gitlab-project-merge-request-resource-label-event
    command line option
--help, 723
--id, 723
--mr-iid, 723
--project-id, 723
--sudo, 723
-h, 723
gitlab-project-merge-request-resource-label-event-list
    command line option
--all, 723
--get-all, 723
--help, 723
--mr-iid, 723
--page, 723
--per-page, 723
gitlab-project-merge-request-resource-label-event-list
    command line option
--all, 723
--get-all, 723
--help, 723
--mr-iid, 723
--page, 723
--per-page, 723
gitlab-project-merge-request-resource-milestone-event
    command line option
--help, 724
--id, 724
--mr-iid, 724
--project-id, 724
--sudo, 724
-h, 724
gitlab-project-merge-request-resource-milestone-event-get
    command line option
--help, 724
--id, 724
--mr-iid, 724
--project-id, 724
--sudo, 724
-h, 724
gitlab-project-merge-request-resource-milestone-event-list
    command line option
--all, 724
--get-all, 724
--help, 724
--mr-iid, 724
--page, 724
--per-page, 724
--project-id, 724
--sudo, 724
-h, 724
gitlab-project-merge-request-resource-state-event
    command line option
--help, 725
-h, 725
gitlab-project-merge-request-resource-state-event-get
    command line option
--help, 725
--id, 725
gitlab-project-merge-request-resource-state-event-list
    command line option
--all, 725
--get-all, 725
--help, 725
--mr-iid, 725
--page, 725
--per-page, 725
gitlab-project-merge-request-resource-state-event-list
    command line option
--all, 725
--get-all, 725
--help, 725
--mr-iid, 725
--page, 725
--per-page, 725
gitlab-project-merge-request-subscribe
    command line option
--help, 704
--iid, 704
--project-id, 704

```

```
--sudo, 704
-h, 704
gitlab-project-merge-request-time-estimate
    command line option
--duration, 704
--help, 704
--iid, 704
--project-id, 704
--sudo, 704
-h, 704
gitlab-project-merge-request-time-stats
    command line option
--help, 705
--iid, 705
--project-id, 705
--sudo, 705
-h, 705
gitlab-project-merge-request-todo command
    line option
--help, 705
--iid, 705
--project-id, 705
--sudo, 705
-h, 705
gitlab-project-merge-request-unapprove
    command line option
--help, 705
--iid, 705
--project-id, 705
--sudo, 705
-h, 705
gitlab-project-merge-request-unsubscribe
    command line option
--help, 705
--iid, 706
--project-id, 705
--sudo, 705
-h, 705
gitlab-project-merge-request-update command
    line option
--allow-maintainer-to-push, 706
--assignee-id, 706
--description, 706
--discussion-locked, 706
--help, 706
--iid, 706
--labels, 706
--milestone-id, 706
--project-id, 706
--remove-source-branch, 706
--reviewer-ids, 706
--squash, 706
--state-event, 706
--sudo, 706
--target-branch, 706
--title, 706
-h, 706
gitlab-project-merge-train command line
    option
--help, 726
-h, 726
gitlab-project-merge-train-list command
    line option
--all, 726
--get-all, 726
--help, 726
--page, 726
--per-page, 726
--project-id, 726
--scope, 726
--sudo, 726
-h, 726
gitlab-project-milestone command line
    option
--help, 726
-h, 726
gitlab-project-milestone-create command
    line option
--description, 727
--due-date, 727
--help, 727
--project-id, 727
--start-date, 727
--state-event, 727
--sudo, 727
--title, 727
-h, 727
gitlab-project-milestone-delete command
    line option
--help, 727
--id, 727
--project-id, 727
--sudo, 727
-h, 727
gitlab-project-milestone-get command line
    option
--help, 727
--id, 727
--project-id, 727
--sudo, 727
-h, 727
gitlab-project-milestone-issues command
    line option
--help, 728
--id, 728
--project-id, 728
--sudo, 728
-h, 728
```

```

gitlab-project-milestone-list command line
    option
    --all, 728
    --get-all, 728
    --help, 728
    --iids, 728
    --page, 728
    --per-page, 728
    --project-id, 728
    --search, 728
    --state, 728
    --sudo, 728
    -h, 728
gitlab-project-milestone-merge-requests
    command line option
    --help, 728
    --id, 729
    --project-id, 728
    --sudo, 728
    -h, 728
gitlab-project-milestone-update command
    line option
    --description, 729
    --due-date, 729
    --help, 729
    --id, 729
    --project-id, 729
    --start-date, 729
    --state-event, 729
    --sudo, 729
    --title, 729
    -h, 729
gitlab-project-mirror-pull command line
    option
    --help, 600
    --id, 600
    -h, 600
gitlab-project-mirror-pull-details command
    line option
    --help, 600
    --id, 600
    -h, 600
gitlab-project-note command line option
    --help, 729
    -h, 729
gitlab-project-note-get command line option
    --help, 729
    --id, 729
    --project-id, 729
    --sudo, 729
    -h, 729
gitlab-project-note-list command line
    option
    --all, 730
    --get-all, 730
    --help, 730
    --page, 730
    --per-page, 730
    --project-id, 730
    --sudo, 730
    -h, 730
gitlab-project-notification-settings
    command line option
    --help, 730
    -h, 730
gitlab-project-notification-settings-get
    command line option
    --help, 730
    --project-id, 730
    --sudo, 730
    -h, 730
gitlab-project-notification-settings-update
    command line option
    --close-issue, 731
    --close-merge-request, 731
    --help, 731
    --level, 731
    --merge-merge-request, 731
    --new-issue, 731
    --new-merge-request, 731
    --new-note, 731
    --notification-email, 731
    --project-id, 731
    --reassign-issue, 731
    --reassign-merge-request, 731
    --reopen-issue, 731
    --reopen-merge-request, 731
    --sudo, 731
    -h, 731
gitlab-project-package command line option
    --help, 731
    -h, 731
gitlab-project-package-delete command line
    option
    --help, 732
    --id, 732
    --project-id, 732
    --sudo, 732
    -h, 732
gitlab-project-package-file command line
    option
    --help, 733
    -h, 733
gitlab-project-package-file-delete command
    line option
    --help, 733
    --id, 733
    --package-id, 733

```

```
--project-id, 733
--sudo, 733
-h, 733
gitlab-project-package-file-list command
    line option
    --all, 733
    --get-all, 733
    --help, 733
    --package-id, 733
    --page, 733
    --per-page, 733
    --project-id, 733
    --sudo, 733
    -h, 733
gitlab-project-package-get command line
    option
    --help, 732
    --id, 732
    --project-id, 732
    --sudo, 732
    -h, 732
gitlab-project-package-list command line
    option
    --all, 733
    --get-all, 732
    --help, 732
    --order-by, 732
    --package-name, 732
    --package-type, 732
    --page, 732
    --per-page, 732
    --project-id, 732
    --sort, 732
    --sudo, 732
    -h, 732
gitlab-project-pages-domain command line
    option
    --help, 734
    -h, 734
gitlab-project-pages-domain-create command
    line option
    --certificate, 734
    --domain, 734
    --help, 734
    --key, 734
    --project-id, 734
    --sudo, 734
    -h, 734
gitlab-project-pages-domain-delete command
    line option
    --domain, 734
    --help, 734
    --project-id, 734
    --sudo, 734
-h, 734
gitlab-project-pages-domain-get command
    line option
    --domain, 735
    --help, 735
    --project-id, 735
    --sudo, 735
    -h, 735
gitlab-project-pages-domain-list command
    line option
    --all, 735
    --get-all, 735
    --help, 735
    --page, 735
    --per-page, 735
    --project-id, 735
    --sudo, 735
    -h, 735
gitlab-project-pages-domain-update command
    line option
    --certificate, 735
    --domain, 735
    --help, 735
    --key, 736
    --project-id, 735
    --sudo, 735
    -h, 735
gitlab-project-pipeline command line option
    --help, 736
    -h, 736
gitlab-project-pipeline-bridge command line
    option
    --help, 738
    -h, 738
gitlab-project-pipeline-bridge-list command
    line option
    --all, 738
    --get-all, 738
    --help, 738
    --page, 738
    --per-page, 738
    --pipeline-id, 738
    --project-id, 738
    --scope, 738
    --sudo, 738
    -h, 738
gitlab-project-pipeline-cancel command line
    option
    --help, 736
    --id, 736
    --project-id, 736
    --sudo, 736
    -h, 736
```

```

gitlab-project-pipeline-create command line
    option
    --help, 736
    --project-id, 736
    --ref, 736
    --sudo, 736
    -h, 736
gitlab-project-pipeline-delete command line
    option
    --help, 736
    --id, 736
    --project-id, 736
    --sudo, 736
    -h, 736
gitlab-project-pipeline-get command line
    option
    --help, 737
    --id, 737
    --project-id, 737
    --sudo, 737
    -h, 737
gitlab-project-pipeline-job command line
    option
    --help, 739
    -h, 739
gitlab-project-pipeline-job-list command
    line option
    --all, 739
    --get-all, 739
    --help, 739
    --include-retried, 739
    --page, 739
    --per-page, 739
    --pipeline-id, 739
    --project-id, 739
    --scope, 739
    --sudo, 739
    -h, 739
gitlab-project-pipeline-list command line
    option
    --all, 738
    --get-all, 737
    --help, 737
    --name, 737
    --order-by, 737
    --page, 737
    --per-page, 737
    --project-id, 737
    --ref, 737
    --scope, 737
    --sha, 737
    --sort, 737
    --source, 737
    --status, 737
    --sudo, 737
    --username, 737
    --yaml-errors, 737
    -h, 737
gitlab-project-pipeline-retry command line
    option
    --help, 738
    --id, 738
    --project-id, 738
    --sudo, 738
    -h, 738
gitlab-project-pipeline-schedule command
    line option
    --help, 739
    -h, 739
gitlab-project-pipeline-schedule-create
    command line option
    --active, 740
    --cron, 740
    --cron-timezone, 740
    --description, 740
    --help, 740
    --project-id, 740
    --ref, 740
    --sudo, 740
    -h, 740
gitlab-project-pipeline-schedule-delete
    command line option
    --help, 740
    --id, 740
    --project-id, 740
    --sudo, 740
    -h, 740
gitlab-project-pipeline-schedule-get
    command line option
    --help, 740
    --id, 741
    --project-id, 740
    --sudo, 740
    -h, 740
gitlab-project-pipeline-schedule-list
    command line option
    --all, 741
    --get-all, 741
    --help, 741
    --page, 741
    --per-page, 741
    --project-id, 741
    --sudo, 741
    -h, 741
gitlab-project-pipeline-schedule-pipeline
    command line option
    --help, 742
    -h, 742

```

```
gitlab-project-pipeline-schedule-pipeline-list      --pipeline-schedule-id, 744
                                                    command line option
                                                    --all, 743
                                                    --get-all, 743
                                                    --help, 742
                                                    --page, 743
                                                    --per-page, 743
                                                    --pipeline-schedule-id, 743
                                                    --project-id, 743
                                                    --sudo, 742
                                                    -h, 742
gitlab-project-pipeline-schedule-play             --pipeline-schedule-variable-update
                                                    command line option
                                                    --help, 744
                                                    --key, 744
                                                    --pipeline-schedule-id, 744
                                                    --project-id, 744
                                                    --sudo, 744
                                                    --value, 744
                                                    -h, 744
gitlab-project-pipeline-test-report command       gitlab-project-pipeline-test-report command
                                                    line option
                                                    --help, 744
                                                    -h, 744
gitlab-project-pipeline-test-report-get           gitlab-project-pipeline-test-report-get
                                                    command line option
                                                    --help, 745
                                                    --pipeline-id, 745
                                                    --project-id, 745
                                                    --sudo, 745
                                                    -h, 745
gitlab-project-pipeline-test-report-summary       gitlab-project-pipeline-test-report-summary
                                                    command line option
                                                    --help, 745
                                                    -h, 745
gitlab-project-pipeline-test-report-summary-get   gitlab-project-pipeline-test-report-summary-get
                                                    command line option
                                                    --help, 745
                                                    --pipeline-id, 745
                                                    --project-id, 745
                                                    --sudo, 745
                                                    -h, 745
gitlab-project-pipeline-variable command          gitlab-project-pipeline-variable command
                                                    line option
                                                    --help, 745
                                                    -h, 745
gitlab-project-pipeline-variable-list            gitlab-project-pipeline-variable-list
                                                    command line option
                                                    --all, 746
                                                    --get-all, 746
                                                    --help, 746
                                                    --page, 746
                                                    --per-page, 746
                                                    --pipeline-id, 746
                                                    --project-id, 746
                                                    --sudo, 746
                                                    -h, 746
gitlab-project-pipeline-variable-delegetlab-project-protected-branch command
                                                    command line option
                                                    --help, 746
                                                    --key, 746
```

```

gitlab-project-protected-branch-create
    command line option
    --allow-force-push, 747
    --allowed-to-merge, 747
    --allowed-to-push, 747
    --allowed-to-unprotect, 747
    --code-owner-approval-required, 747
    --help, 746
    --merge-access-level, 747
    --name, 747
    --project-id, 747
    --push-access-level, 747
    --sudo, 746
    --unprotect-access-level, 747
    -h, 746
gitlab-project-protected-branch-delete
    command line option
    --help, 747
    --name, 747
    --project-id, 747
    --sudo, 747
    -h, 747
gitlab-project-protected-branch-get command
    line option
    --help, 747
    --name, 747
    --project-id, 747
    --sudo, 747
    -h, 747
gitlab-project-protected-branch-list
    command line option
    --all, 748
    --get-all, 748
    --help, 748
    --page, 748
    --per-page, 748
    --project-id, 748
    --sudo, 748
    -h, 748
gitlab-project-protected-environment
    command line option
    --help, 748
    -h, 748
gitlab-project-protected-environment-create
    command line option
    --approval-rules, 749
    --deploy-access-levels, 748
    --help, 748
    --name, 748
    --project-id, 748
    --required-approval-count, 748
    --sudo, 748
    -h, 748
gitlab-project-protected-environment-delete
    command line option
    --help, 749
    --name, 749
    --project-id, 749
    --sudo, 749
    -h, 749
gitlab-project-protected-environment-get
    command line option
    --help, 749
    --name, 749
    --project-id, 749
    --sudo, 749
    -h, 749
gitlab-project-protected-environment-list
    command line option
    --all, 750
    --get-all, 749
    --help, 749
    --page, 749
    --per-page, 749
    --project-id, 749
    --sudo, 749
    -h, 749
gitlab-project-protected-tag command line
    option
    --help, 750
    -h, 750
gitlab-project-protected-tag-create command
    line option
    --create-access-level, 750
    --help, 750
    --name, 750
    --project-id, 750
    --sudo, 750
    -h, 750
gitlab-project-protected-tag-delete command
    line option
    --help, 750
    --name, 750
    --project-id, 750
    --sudo, 750
    -h, 750
gitlab-project-protected-tag-get command
    line option
    --help, 751
    --name, 751
    --project-id, 751
    --sudo, 751
    -h, 751
gitlab-project-protected-tag-list command
    line option
    --all, 751
    --get-all, 751

```

```
--help, 751
--page, 751
--per-page, 751
--project-id, 751
--sudo, 751
-h, 751
gitlab-project-push-rules command line
    option
    --help, 751
    -h, 751
gitlab-project-push-rules-create command
    line option
    --author-email-regex, 752
    --branch-name-regex, 752
    --commit-committer-check, 752
    --commit-message-negative-regex, 752
    --commit-message-regex, 752
    --deny-delete-tag, 752
    --file-name-regex, 752
    --help, 752
    --max-file-size, 752
    --member-check, 752
    --prevent-secrets, 752
    --project-id, 752
    --reject-unsigned-commits, 752
    --sudo, 752
    -h, 752
gitlab-project-push-rules-delete command
    line option
    --help, 752
    --project-id, 753
    --sudo, 752
    -h, 752
gitlab-project-push-rules-get command line
    option
    --help, 753
    --project-id, 753
    --sudo, 753
    -h, 753
gitlab-project-push-rules-update command
    line option
    --author-email-regex, 753
    --branch-name-regex, 753
    --commit-committer-check, 753
    --commit-message-negative-regex, 753
    --commit-message-regex, 753
    --deny-delete-tag, 753
    --file-name-regex, 753
    --help, 753
    --max-file-size, 753
    --member-check, 754
    --prevent-secrets, 754
    --project-id, 753
    --reject-unsigned-commits, 754
    --sudo, 753
    -h, 753
gitlab-project-registry-repository command
    line option
    --help, 754
    -h, 754
gitlab-project-registry-repository-delete
    command line option
    --help, 754
    --id, 754
    --project-id, 754
    --sudo, 754
    -h, 754
gitlab-project-registry-repository-list
    command line option
    --all, 754
    --get-all, 754
    --help, 754
    --page, 754
    --per-page, 754
    --project-id, 754
    --sudo, 754
    -h, 754
gitlab-project-registry-tag command line
    option
    --help, 755
    -h, 755
gitlab-project-registry-tag-delete command
    line option
    --help, 755
    --name, 755
    --project-id, 755
    --repository-id, 755
    --sudo, 755
    -h, 755
gitlab-project-registry-tag-delete-in-bulk
    command line option
    --help, 755
    --keep-n, 755
    --name, 755
    --name-regex-delete, 755
    --name-regex-keep, 755
    --older-than, 755
    --project-id, 755
    --repository-id, 755
    --sudo, 755
    -h, 755
gitlab-project-registry-tag-get command
    line option
    --help, 756
    --name, 756
    --project-id, 756
    --repository-id, 756
    --sudo, 756
    -h, 756
```

```

-h, 756
gitlab-project-registry-tag-list command
    line option
--all, 756
--get-all, 756
--help, 756
--page, 756
--per-page, 756
--project-id, 756
--repository-id, 756
--sudo, 756
-h, 756
gitlab-project-release command line option
--help, 756
-h, 756
gitlab-project-release-create command line
    option
--assets, 757
--description, 757
--help, 757
--name, 757
--project-id, 757
--ref, 757
--sudo, 757
--tag-name, 757
-h, 757
gitlab-project-release-delete command line
    option
--help, 757
--project-id, 757
--sudo, 757
--tag-name, 757
-h, 757
gitlab-project-release-get command line
    option
--help, 757
--project-id, 757
--sudo, 757
--tag-name, 757
-h, 757
gitlab-project-release-link command line
    option
--help, 759
-h, 759
gitlab-project-release-link-create command
    line option
--filepath, 759
--help, 759
--link-type, 759
--name, 759
--project-id, 759
--sudo, 759
--tag-name, 759
--url, 759
-h, 759
gitlab-project-release-link-delete command
    line option
--help, 759
--id, 759
--project-id, 759
--sudo, 759
--tag-name, 759
-h, 759
gitlab-project-release-link-get command
    line option
--help, 760
--id, 760
--project-id, 760
--sudo, 760
--tag-name, 760
-h, 760
gitlab-project-release-link-list command
    line option
--all, 760
--get-all, 760
--help, 760
--page, 760
--per-page, 760
--project-id, 760
--sudo, 760
--tag-name, 760
-h, 760
gitlab-project-release-link-update command
    line option
--filepath, 761
--help, 760
--id, 761
--link-type, 761
--name, 761
--project-id, 761
--sudo, 760
--tag-name, 761
--url, 761
-h, 760
gitlab-project-release-list command line
    option
--all, 758
--get-all, 758
--help, 758
--include-html-description, 758
--order-by, 758
--page, 758
--per-page, 758
--project-id, 758
--sort, 758
--sudo, 758
-h, 758

```

```
gitlab-project-release-update command line
    option
    --description, 758
    --help, 758
    --milestones, 758
    --name, 758
    --project-id, 758
    --released-at, 758
    --sudo, 758
    --tag-name, 758
    -h, 758
gitlab-project-remote-mirror command line
    option
    --help, 761
    -h, 761
gitlab-project-remote-mirror-create command
    line option
    --enabled, 761
    --help, 761
    --only-protected-branches, 761
    --project-id, 761
    --sudo, 761
    --url, 761
    -h, 761
gitlab-project-remote-mirror-list command
    line option
    --all, 762
    --get-all, 762
    --help, 761
    --page, 762
    --per-page, 762
    --project-id, 762
    --sudo, 761
    -h, 761
gitlab-project-remote-mirror-update command
    line option
    --enabled, 762
    --help, 762
    --id, 762
    --only-protected-branches, 762
    --project-id, 762
    --sudo, 762
    -h, 762
gitlab-project-repository-archive command
    line option
    --format, 600
    --help, 600
    --id, 600
    --sha, 600
    -h, 600
gitlab-project-repository-blob command line
    option
    --help, 601
    --id, 601
    --sha, 601
    -h, 601
gitlab-project-repository-command line option
    --from-, 601
    --help, 601
    --id, 601
    --to, 601
    -h, 601
gitlab-project-repository-contributors
    command line option
    --help, 601
    --id, 601
    -h, 601
gitlab-project-repository-merge-base
    command line option
    --help, 601
    --id, 601
    --refs, 601
    -h, 601
gitlab-project-repository-raw-blob command
    line option
    --help, 602
    --id, 602
    --sha, 602
    -h, 602
gitlab-project-repository-tree command line
    option
    --help, 602
    --id, 602
    --path, 602
    --recursive, 602
    --ref, 602
    -h, 602
gitlab-project-resource-group command line
    option
    --help, 762
    -h, 762
gitlab-project-resource-group-get command
    line option
    --help, 762
    --key, 762
    --project-id, 762
    --sudo, 762
    -h, 762
gitlab-project-resource-group-list command
    line option
    --all, 763
    --get-all, 763
    --help, 763
    --include-html-description, 763
    --order-by, 763
    --page, 763
    --per-page, 763
```

```

--project-id, 763
--sort, 763
--sudo, 763
-h, 763
gitlab-project-resource-group-upcoming-job
    command line option
--help, 764
-h, 764
gitlab-project-resource-group-upcoming-job-list
    command line option
--all, 764
--get-all, 764
--help, 764
--page, 764
--per-page, 764
--project-id, 764
--resource-group-key, 764
--sudo, 764
-h, 764
gitlab-project-resource-group-update
    command line option
--help, 763
--key, 763
--process-mode, 763
--project-id, 763
--sudo, 763
-h, 763
gitlab-project-restore command line option
--help, 602
--id, 602
-h, 602
gitlab-project-runner command line option
--help, 764
-h, 764
gitlab-project-runner-create command line
    option
--help, 764
--project-id, 765
--runner-id, 765
--sudo, 764
-h, 764
gitlab-project-runner-delete command line
    option
--help, 765
--id, 765
--project-id, 765
--sudo, 765
-h, 765
gitlab-project-runner-list command line
    option
--all, 765
--get-all, 765
--help, 765
--page, 765
--per-page, 765
--project-id, 765
--scope, 765
--sudo, 765
--tag-list, 765
-h, 765
gitlab-project-search command line option
--help, 602
--id, 602
--scope, 602
--search, 602
-h, 602
gitlab-project-secure-file command line
    option
--help, 766
-h, 766
gitlab-project-secure-file-create command
    line option
--file, 766
--help, 766
--name, 766
--project-id, 766
--sudo, 766
-h, 766
gitlab-project-secure-file-delete command
    line option
--help, 766
--id, 766
--project-id, 766
--sudo, 766
-h, 766
gitlab-project-secure-file-download command
    line option
--help, 766
--id, 766
--project-id, 766
--sudo, 766
-h, 766
gitlab-project-secure-file-get command line
    option
--help, 767
--id, 767
--project-id, 767
--sudo, 767
-h, 767
gitlab-project-secure-file-list command
    line option
--all, 767
--get-all, 767
--help, 767
--page, 767
--per-page, 767
--project-id, 767
--sudo, 767

```

```
-h, 767
gitlab-project-service command line option
--help, 767
-h, 767
gitlab-project-service-available command
    line option
--help, 768
--project-id, 768
--slug, 768
--sudo, 768
-h, 768
gitlab-project-service-delete command line
    option
--help, 768
--project-id, 768
--slug, 768
--sudo, 768
-h, 768
gitlab-project-service-get command line
    option
--help, 768
--project-id, 768
--slug, 768
--sudo, 768
-h, 768
gitlab-project-service-list command line
    option
--all, 769
--get-all, 769
--help, 768
--page, 769
--per-page, 769
--project-id, 768
--sudo, 768
-h, 768
gitlab-project-service-update command line
    option
--help, 769
--project-id, 769
--slug, 769
--sudo, 769
-h, 769
gitlab-project-share command line option
--expires-at, 603
--group-access, 603
--group-id, 603
--help, 603
--id, 603
-h, 603
gitlab-project-snapshot command line option
--help, 603
--id, 603
--wiki, 603
-h, 603
gitlab-project-snippet command line option
--help, 769
-h, 769
gitlab-project-snippet-award-emoji command
    line option
--help, 772
-h, 772
gitlab-project-snippet-award-emoji-create
    command line option
--help, 772
--name, 772
--project-id, 772
--snippet-id, 772
--sudo, 772
-h, 772
gitlab-project-snippet-award-emoji-delete
    command line option
--help, 772
--id, 773
--project-id, 772
--snippet-id, 773
--sudo, 772
-h, 772
gitlab-project-snippet-award-emoji-get
    command line option
--help, 773
--id, 773
--project-id, 773
--snippet-id, 773
--sudo, 773
-h, 773
gitlab-project-snippet-award-emoji-list
    command line option
--all, 773
--get-all, 773
--help, 773
--page, 773
--per-page, 773
--project-id, 773
--snippet-id, 773
--sudo, 773
-h, 773
gitlab-project-snippet-content command line
    option
--help, 769
--id, 769
--project-id, 769
--sudo, 769
-h, 769
gitlab-project-snippet-create command line
    option
--content, 770
--description, 770
--file-name, 770
```

```

--help, 770
--project-id, 770
--sudo, 770
--title, 770
--visibility, 770
-h, 770
gitlab-project-snippet-delete command line
    option
    --help, 770
    --id, 770
    --project-id, 770
    --sudo, 770
    -h, 770
gitlab-project-snippet-discussion command
    line option
    --help, 774
    -h, 774
gitlab-project-snippet-discussion-create
    command line option
    --body, 774
    --created-at, 774
    --help, 774
    --project-id, 774
    --snippet-id, 774
    --sudo, 774
    -h, 774
gitlab-project-snippet-discussion-get
    command line option
    --help, 774
    --id, 774
    --project-id, 774
    --snippet-id, 774
    --sudo, 774
    -h, 774
gitlab-project-snippet-discussion-list
    command line option
    --all, 775
    --get-all, 775
    --help, 775
    --page, 775
    --per-page, 775
    --project-id, 775
    --snippet-id, 775
    --sudo, 775
    -h, 775
gitlab-project-snippet-discussion-note
    command line option
    --help, 775
    -h, 775
gitlab-project-snippet-discussion-note-create
    command line option
    --body, 776
    --created-at, 776
    --discussion-id, 776
    --help, 775
    --project-id, 775
    --snippet-id, 775
    --sudo, 775
    -h, 775
gitlab-project-snippet-discussion-note-delete
    command line option
    --discussion-id, 776
    --help, 776
    --id, 776
    --project-id, 776
    --snippet-id, 776
    --sudo, 776
    -h, 776
gitlab-project-snippet-discussion-note-get
    command line option
    --discussion-id, 776
    --help, 776
    --id, 776
    --project-id, 776
    --snippet-id, 776
    --sudo, 776
    -h, 776
gitlab-project-snippet-discussion-note-update
    command line option
    --body, 777
    --discussion-id, 777
    --help, 777
    --id, 777
    --project-id, 777
    --snippet-id, 777
    --sudo, 777
    -h, 777
gitlab-project-snippet-get command line
    option
    --help, 770
    --id, 770
    --project-id, 770
    --sudo, 770
    -h, 770
gitlab-project-snippet-list command line
    option
    --all, 771
    --get-all, 771
    --help, 771
    --page, 771
    --per-page, 771
    --project-id, 771
    --sudo, 771
    -h, 771
gitlab-project-snippet-note command line
    option
    --help, 777
    -h, 777

```

```
gitlab-project-snippet-note-award-emoji
    command line option
    --help, 779
    -h, 779
gitlab-project-snippet-note-award-emoji-create
    command line option
    --help, 779
    --name, 780
    --note-id, 779
    --project-id, 779
    --snippet-id, 779
    --sudo, 779
    -h, 779
gitlab-project-snippet-note-award-emoji-delete
    command line option
    --help, 780
    --id, 780
    --note-id, 780
    --project-id, 780
    --snippet-id, 780
    --sudo, 780
    -h, 780
gitlab-project-snippet-note-award-emoji-get
    command line option
    --help, 780
    --id, 780
    --note-id, 780
    --project-id, 780
    --snippet-id, 780
    --sudo, 780
    -h, 780
gitlab-project-snippet-note-award-emoji-list
    command line option
    --all, 781
    --get-all, 781
    --help, 781
    --note-id, 781
    --page, 781
    --per-page, 781
    --project-id, 781
    --snippet-id, 781
    --sudo, 781
    -h, 781
gitlab-project-snippet-note-create command
    line option
    --body, 777
    --help, 777
    --project-id, 777
    --snippet-id, 777
    --sudo, 777
    -h, 777
gitlab-project-snippet-note-delete command
    line option
    --help, 778
    --id, 778
    --project-id, 778
    --snippet-id, 778
    --sudo, 778
    -h, 778
gitlab-project-snippet-note-get command
    line option
    --help, 778
    --id, 778
    --project-id, 778
    --snippet-id, 778
    --sudo, 778
    -h, 778
gitlab-project-snippet-note-list command
    line option
    --all, 779
    --get-all, 778
    --help, 778
    --page, 778
    --per-page, 778
    --project-id, 778
    --snippet-id, 778
    --sudo, 778
    -h, 778
gitlab-project-snippet-note-update command
    line option
    --body, 779
    --help, 779
    --id, 779
    --project-id, 779
    --snippet-id, 779
    --sudo, 779
    -h, 779
gitlab-project-snippet-update command line
    option
    --content, 771
    --description, 771
    --file-name, 771
    --help, 771
    --id, 771
    --project-id, 771
    --sudo, 771
    --title, 771
    --visibility, 771
    -h, 771
gitlab-project-snippet-user-agent-detail
    command line option
    --help, 772
    --id, 772
    --project-id, 772
    --sudo, 772
    -h, 772
gitlab-project-star command line option
    --help, 603
```

```

--id, 603
-h, 603
gitlab-project-storage command line option
--help, 781
-h, 781
gitlab-project-storage-get command line
    option
--help, 781
--id, 781
--project-id, 781
--sudo, 781
-h, 781
gitlab-project-tag command line option
--help, 782
-h, 782
gitlab-project-tag-create command line
    option
--help, 782
--message, 782
--project-id, 782
--ref, 782
--sudo, 782
--tag-name, 782
-h, 782
gitlab-project-tag-delete command line
    option
--help, 782
--name, 782
--project-id, 782
--sudo, 782
-h, 782
gitlab-project-tag-get command line option
--help, 782
--name, 782
--project-id, 782
--sudo, 782
-h, 782
gitlab-project-tag-list command line option
--all, 783
--get-all, 783
--help, 783
--page, 783
--per-page, 783
--project-id, 783
--sudo, 783
-h, 783
gitlab-project-transfer command line option
--help, 603
--id, 603
--to-namespace, 603
-h, 603
gitlab-project-transfer-project command
    line option
--help, 604
--id, 604
--to-namespace, 604
-h, 604
gitlab-project-trigger command line option
--help, 783
-h, 783
gitlab-project-trigger-create command line
    option
--description, 783
--help, 783
--project-id, 783
--sudo, 783
-h, 783
gitlab-project-trigger-delete command line
    option
--help, 784
--id, 784
--project-id, 784
--sudo, 784
-h, 784
gitlab-project-trigger-get command line
    option
--help, 784
--id, 784
--project-id, 784
--sudo, 784
-h, 784
gitlab-project-trigger-list command line
    option
--all, 784
--get-all, 784
--help, 784
--page, 784
--per-page, 784
--project-id, 784
--sudo, 784
-h, 784
gitlab-project-trigger-pipeline command
    line option
--help, 604
--id, 604
--ref, 604
--token, 604
-h, 604
gitlab-project-trigger-update command line
    option
--description, 785
--help, 785
--id, 785
--project-id, 785
--sudo, 785
-h, 785
gitlab-project-unarchive command line
    option

```

```
--help, 604
--id, 604
-h, 604
gitlab-project-unshare command line option
--group-id, 604
--help, 604
--id, 604
-h, 604
gitlab-project-unstar command line option
--help, 605
--id, 605
-h, 605
gitlab-project-update command line option
--allow-merge-on-skipped-pipeline, 607
--analytics-access-level, 607
--approvals-before-merge, 607
--auto-cancel-pending-pipelines, 607
--auto-devops-deploy-strategy, 607
--auto-devops-enabled, 607
--autoclose-referenced-issues, 607
--avatar, 607
--build-coverage-regex, 607
--build-git-strategy, 607
--build-timeout, 607
--builds-access-level, 607
--ci-allow-fork-pipelines-to-run-in-parent-project, 607
--ci-allow-fork-pipelines-to-run-in-parent-project-access-level, 608
--ci-config-path, 607
--ci-default-git-depth, 607
--ci-forward-deployment-enabled, 607
--ci-separated-caches, 607
--container-expiration-policy-attributes, 607
--container-registry-access-level, 607
--container-registry-enabled, 607
--default-branch, 607
--description, 607
--emails-disabled, 607
--enforce-auth-checks-on-uploads, 608
--environments-access-level, 609
--external-authorization-classification-label, 608
--feature-flags-access-level, 609
--forking-access-level, 608
--help, 607
--id, 607
--import-url, 608
--infrastructure-access-level, 609
--issue-branch-template, 609
--issues-access-level, 608
--issues-enabled, 608
--issues-template, 608
--jobs-enabled, 608
--keep-latest-artifact, 608
--lfs-enabled, 608
--merge-commit-template, 608
--merge-method, 608
--merge-pipelines-enabled, 608
--merge-requests-access-level, 608
--merge-requests-enabled, 608
--merge-requests-template, 608
--merge-trains-enabled, 608
--mirror, 608
--mirror-overwrites-diverged-branches, 608
--mirror-trigger-builds, 608
--mirror-user-id, 608
--monitor-access-level, 609
--mr-default-target-self, 608
--name, 608
--only-allow-merge-if-all-discussions-are-resolved, 608
--only-allow-merge-if-all-status-checks-passed, 607
--only-allow-merge-if-pipeline-succeeds, 608
--only-mirror-protected-branches, 608
--operations-access-level, 608
--packages-enabled, 608
--pages-access-level, 608
--path, 609
--public-builds, 609
--releases-access-level, 609
--remove-source-branch-after-merge, 609
--repository-access-level, 609
--repository-storage, 609
--request-access-enabled, 609
--requirements-access-level, 608
--resolve-outdated-diff-discussions, 609
--restrict-user-defined-variables, 608
--security-and-compliance-access-level, 609
--service-desk-enabled, 609
--shared-runners-enabled, 609
--show-default-award-emojis, 609
--snippets-access-level, 609
--snippets-enabled, 609
--squash-commit-template, 609
--squash-option, 609
--sudo, 607
--suggestion-commit-message, 609
--tag-list, 609
--topics, 609
--visibility, 609
--wiki-access-level, 609
--wiki-enabled, 609
-h, 607
```

```

gitlab-project-update-submodule command
    line option
    --branch, 610
    --commit-sha, 610
    --help, 610
    --id, 610
    --submodule, 610
    -h, 610
gitlab-project-upload command line option
    --filename, 610
    --filepath, 610
    --help, 610
    --id, 610
    -h, 610
gitlab-project-user command line option
    --help, 785
    -h, 785
gitlab-project-user-list command line
    option
    --all, 785
    --get-all, 785
    --help, 785
    --page, 785
    --per-page, 785
    --project-id, 785
    --search, 785
    --skip-users, 785
    --sudo, 785
    -h, 785
gitlab-project-variable command line option
    --help, 786
    -h, 786
gitlab-project-variable-create command line
    option
    --environment-scope, 786
    --help, 786
    --key, 786
    --masked, 786
    --project-id, 786
    --protected, 786
    --sudo, 786
    --value, 786
    --variable-type, 786
    -h, 786
gitlab-project-variable-delete command line
    option
    --help, 786
    --key, 786
    --project-id, 786
    --sudo, 786
    -h, 786
gitlab-project-variable-get command line
    option
    --help, 787
    --key, 787
    --project-id, 787
    --sudo, 787
    -h, 787
gitlab-project-variable-list command line
    option
    --all, 787
    --get-all, 787
    --help, 787
    --page, 787
    --per-page, 787
    --project-id, 787
    --sudo, 787
    -h, 787
gitlab-project-variable-update command line
    option
    --environment-scope, 788
    --help, 787
    --key, 787
    --masked, 788
    --project-id, 787
    --protected, 788
    --sudo, 787
    --value, 788
    --variable-type, 788
    -h, 787
gitlab-project-wiki command line option
    --help, 788
    -h, 788
gitlab-project-wiki-create command line
    option
    --content, 788
    --format, 788
    --help, 788
    --project-id, 788
    --sudo, 788
    --title, 788
    -h, 788
gitlab-project-wiki-delete command line
    option
    --help, 788
    --project-id, 788
    --slug, 788
    --sudo, 788
    -h, 788
gitlab-project-wiki-get command line option
    --help, 789
    --project-id, 789
    --slug, 789
    --sudo, 789
    -h, 789
gitlab-project-wiki-list command line
    option
    --all, 789

```

```
--get-all, 789
--help, 789
--page, 789
--per-page, 789
--project-id, 789
--sudo, 789
--with-content, 789
-h, 789
gitlab-project-wiki-update command line
    option
--content, 790
--format, 790
--help, 789
--project-id, 789
--slug, 789
--sudo, 789
--title, 789
-h, 789
gitlab-registry-repository command line
    option
--help, 790
-h, 790
gitlab-registry-repository-get command line
    option
--help, 790
--id, 790
--sudo, 790
-h, 790
gitlab-runner command line option
--help, 790
-h, 790
gitlab-runner-all command line option
--help, 790, 793
--id, 790
--scope, 790
-h, 790, 793
gitlab-runner-all-list command line option
--all, 793
--get-all, 793
--help, 793
--page, 793
--paused, 793
--per-page, 793
--scope, 793
--status, 793
--sudo, 793
--tag-list, 793
--type, 793
-h, 793
gitlab-runner-create command line option
--access-level, 791
--active, 791
--description, 791
--help, 791
--info, 791
--locked, 791
--maximum-timeout, 791
--run-untagged, 791
--sudo, 791
--tag-list, 791
--token, 791
-h, 791
gitlab-runner-delete command line option
--help, 791
--id, 791
--sudo, 791
-h, 791
gitlab-runner-get command line option
--help, 791
--id, 791
--sudo, 791
-h, 791
gitlab-runner-job command line option
--help, 794
-h, 794
gitlab-runner-job-list command line option
--all, 794
--get-all, 794
--help, 794
--page, 794
--per-page, 794
--runner-id, 794
--status, 794
--sudo, 794
-h, 794
gitlab-runner-list command line option
--all, 792
--get-all, 792
--help, 792
--page, 792
--paused, 792
--per-page, 792
--scope, 792
--status, 792
--sudo, 792
--tag-list, 792
--type, 792
-h, 792
gitlab-runner-update command line option
--access-level, 793
--active, 792
--description, 792
--help, 792
--id, 792
--locked, 792
--maximum-timeout, 793
--run-untagged, 792
--sudo, 792
```

```

--tag-list, 792
-h, 792
gitlab-runner-verify command line option
--help, 793
--id, 793
--token, 793
-h, 793
gitlab-shared-project command line option
--help, 794
-h, 794
gitlab-shared-project-list command line
    option
--all, 795
--archived, 795
--get-all, 795
--group-id, 795
--help, 795
--min-access-level, 795
--order-by, 795
--page, 795
--per-page, 795
--search, 795
--simple, 795
--sort, 795
--starred, 795
--sudo, 795
--visibility, 795
--with-custom-attributes, 795
--with-issues-enabled, 795
--with-merge-requests-enabled, 795
-h, 795
gitlab-snippet command line option
--help, 795
-h, 795
gitlab-snippet-content command line option
--help, 796
--id, 796
-h, 796
gitlab-snippet-create command line option
--content, 796
--file-name, 796
--help, 796
--lifetime, 796
--sudo, 796
--title, 796
--visibility, 796
-h, 796
gitlab-snippet-delete command line option
--help, 796
--id, 796
--sudo, 796
-h, 796
gitlab-snippet-get command line option
--help, 797
--id, 797
--sudo, 797
-h, 797
gitlab-snippet-list command line option
--all, 797
--get-all, 797
--help, 797
--page, 797
--per-page, 797
--sudo, 797
-h, 797
gitlab-snippet-public command line option
--help, 797
--id, 797
-h, 797
gitlab-snippet-update command line option
--content, 798
--file-name, 798
--help, 798
--id, 798
--sudo, 798
--title, 798
--visibility, 798
-h, 798
gitlab-snippet-user-agent-detail command
    line option
--help, 798
--id, 798
-h, 798
gitlab-starred-project command line option
--help, 798
-h, 798
gitlab-starred-project-list command line
    option
--all, 799
--archived, 799
--get-all, 799
--help, 799
--membership, 799
--min-access-level, 799
--order-by, 799
--owned, 799
--page, 799
--per-page, 799
--search, 799
--simple, 799
--sort, 799
--starred, 799
--statistics, 799
--sudo, 798
--user-id, 798
--visibility, 799
--with-custom-attributes, 799
--with-issues-enabled, 799

```

```
--with-merge-requests-enabled, 799
-h, 798
gitlab-todo command line option
--help, 799
-h, 799
gitlab-todo-delete command line option
--help, 799
--id, 799
--sudo, 799
-h, 799
gitlab-todo-list command line option
--action, 800
--all, 800
--author-id, 800
--get-all, 800
--help, 800
--page, 800
--per-page, 800
--project-id, 800
--state, 800
--sudo, 800
--type, 800
-h, 800
gitlab-todo-mark-all-as-done command line
    option
--help, 800
--id, 800
-h, 800
gitlab-todo-mark-as-done command line
    option
--help, 800
--id, 800
-h, 800
gitlab-topic command line option
--help, 801
-h, 801
gitlab-topic-create command line option
--avatar, 801
--description, 801
--help, 801
--name, 801
--sudo, 801
--title, 801
-h, 801
gitlab-topic-delete command line option
--help, 801
--id, 801
--sudo, 801
-h, 801
gitlab-topic-get command line option
--help, 801
--id, 801
--sudo, 801
-h, 801
gitlab-topic-list command line option
--all, 802
--get-all, 802
--help, 802
--page, 802
--per-page, 802
--sudo, 802
-h, 802
gitlab-topic-merge command line option
--help, 802
--id, 802
--source-topic-id, 802
--target-topic-id, 802
-h, 802
gitlab-topic-update command line option
--avatar, 802
--description, 802
--help, 802
--id, 802
--name, 802
--sudo, 802
-h, 802
gitlab-user command line option
--help, 803
-h, 803
gitlab-user-activate command line option
--help, 803
--id, 803
-h, 803
gitlab-user-activities command line option
--help, 809
-h, 809
gitlab-user-activities-list command line
    option
--all, 809
--get-all, 809
--help, 809
--page, 809
--per-page, 809
--sudo, 809
-h, 809
gitlab-user-approve command line option
--help, 803
--id, 803
-h, 803
gitlab-user-ban command line option
--help, 803
--id, 803
-h, 803
gitlab-user-block command line option
--help, 804
--id, 804
-h, 804
gitlab-user-create command line option
```

```

--admin, 805
--avatar, 805
--bio, 804
--can-create-group, 805
--color-scheme-id, 805
--email, 804
--extern-uid, 804
--external, 805
--help, 804
--linkedin, 804
--location, 805
--name, 804
--organization, 805
--password, 804
--private-profile, 805
--projects-limit, 804
--provider, 804
--public-email, 805
--reset-password, 804
--skip-confirmation, 805
--skype, 804
--sudo, 804
--theme-id, 805
--twitter, 804
--username, 804
--website-url, 805
-h, 804

gitlab-user-custom-attribute command line
    option
    --help, 809
    -h, 809
gitlab-user-custom-attribute-delete command
    line option
    --help, 810
    --key, 810
    --sudo, 810
    --user-id, 810
    -h, 810
gitlab-user-custom-attribute-get command
    line option
    --help, 810
    --key, 810
    --sudo, 810
    --user-id, 810
    -h, 810
gitlab-user-custom-attribute-list command
    line option
    --all, 810
    --get-all, 810
    --help, 810
    --page, 810
    --per-page, 810
    --sudo, 810
    --user-id, 810
-h, 810

gitlab-user-deactivate command line option
    --help, 805
    --id, 805
    -h, 805
gitlab-user-delete command line option
    --help, 805
    --id, 805
    --sudo, 805
    -h, 805
gitlab-user-email command line option
    --help, 811
    -h, 811
gitlab-user-email-create command line
    option
    --email, 811
    --help, 811
    --sudo, 811
    --user-id, 811
    -h, 811
gitlab-user-email-delete command line
    option
    --help, 811
    --id, 811
    --sudo, 811
    --user-id, 811
    -h, 811
gitlab-user-email-get command line option
    --help, 811
    --id, 811
    --sudo, 811
    --user-id, 811
    -h, 811
gitlab-user-email-list command line option
    --all, 812
    --get-all, 812
    --help, 812
    --page, 812
    --per-page, 812
    --sudo, 812
    --user-id, 812
    -h, 812
gitlab-user-event command line option
    --help, 812
    -h, 812
gitlab-user-event-list command line option
    --action, 812
    --after, 812
    --all, 813
    --before, 812
    --get-all, 813
    --help, 812
    --page, 812
    --per-page, 813

```

```
--sort, 812
--sudo, 812
--target-type, 812
--user-id, 812
-h, 812
gitlab-user-follow command line option
--help, 806
--id, 806
-h, 806
gitlab-user-get command line option
--help, 806
--id, 806
--sudo, 806
-h, 806
gitlab-user-gpg-key command line option
--help, 813
-h, 813
gitlab-user-gpg-key-create command line
    option
--help, 813
--key, 813
--sudo, 813
--user-id, 813
-h, 813
gitlab-user-gpg-key-delete command line
    option
--help, 813
--id, 813
--sudo, 813
--user-id, 813
-h, 813
gitlab-user-gpg-key-get command line option
--help, 814
--id, 814
--sudo, 814
--user-id, 814
-h, 814
gitlab-user-gpg-key-list command line
    option
--all, 814
--get-all, 814
--help, 814
--page, 814
--per-page, 814
--sudo, 814
--user-id, 814
-h, 814
gitlab-user-impersonation-token command
    line option
--help, 814
-h, 814
gitlab-user-impersonation-token-create
    command line option
--expires-at, 815
--help, 814
--name, 815
--scopes, 815
--sudo, 814
--user-id, 815
-h, 814
gitlab-user-impersonation-token-delete
    command line option
--help, 815
--id, 815
--sudo, 815
--user-id, 815
-h, 815
gitlab-user-impersonation-token-get command
    line option
--help, 815
--id, 815
--sudo, 815
--user-id, 815
-h, 815
gitlab-user-impersonation-token-list
    command line option
--all, 816
--get-all, 816
--help, 815
--page, 816
--per-page, 816
--state, 815
--sudo, 815
--user-id, 815
-h, 815
gitlab-user-key command line option
--help, 816
-h, 816
gitlab-user-key-create command line option
--help, 816
--key, 816
--sudo, 816
--title, 816
--user-id, 816
-h, 816
gitlab-user-key-delete command line option
--help, 816
--id, 816
--sudo, 816
--user-id, 816
-h, 816
gitlab-user-key-get command line option
--help, 817
--id, 817
--sudo, 817
--user-id, 817
-h, 817
gitlab-user-key-list command line option
```

```

--all, 817
--get-all, 817
--help, 817
--page, 817
--per-page, 817
--sudo, 817
--user-id, 817
-h, 817
gitlab-user-list command line option
--active, 806
--all, 807
--blocked, 806
--custom-attributes, 806
--extern-uid, 806
--external, 806
--get-all, 807
--help, 806
--page, 807
--per-page, 807
--provider, 806
--search, 806
--status, 806
--sudo, 806
--two-factor, 806
--username, 806
-h, 806
gitlab-user-membership command line option
--help, 817
-h, 817
gitlab-user-membership-get command line
    option
--help, 817
--source-id, 818
--sudo, 817
--user-id, 817
-h, 817
gitlab-user-membership-list command line
    option
--all, 818
--get-all, 818
--help, 818
--page, 818
--per-page, 818
--sudo, 818
--type, 818
--user-id, 818
-h, 818
gitlab-user-personal-access-token command
    line option
--help, 818
-h, 818
gitlab-user-personal-access-token-create
    command line option
--expires-at, 818
--help, 818
--name, 818
--scopes, 818
--sudo, 818
--user-id, 818
-h, 818
gitlab-user-project command line option
--help, 819
-h, 819
gitlab-user-project-create command line
    option
--builds-enabled, 819
--default-branch, 819
--description, 819
--help, 819
--import-url, 820
--issues-enabled, 819
--merge-requests-enabled, 819
--name, 819
--only-allow-merge-if-build-succeeds, 820
--public, 819
--public-builds, 819
--snippets-enabled, 819
--squash-option, 819
--sudo, 819
--user-id, 819
--visibility, 819
--wall-enabled, 819
--wiki-enabled, 819
-h, 819
gitlab-user-project-list command line
    option
--all, 821
--archived, 820
--get-all, 821
--help, 820
--id-after, 821
--id-before, 821
--membership, 820
--min-access-level, 821
--order-by, 820
--owned, 820
--page, 821
--per-page, 821
--repository-checksum-failed, 821
--search, 820
--simple, 820
--sort, 820
--starred, 820
--statistics, 820
--sudo, 820
--user-id, 820
--visibility, 820
--wiki-checksum-failed, 821

```

```
--with-custom-attributes, 821
--with-issues-enabled, 820
--with-merge-requests-enabled, 820
--with-programming-language, 821
-h, 820
gitlab-user-reject command line option
--help, 807
--id, 807
-h, 807
gitlab-user-status command line option
--help, 821
-h, 821
gitlab-user-status-get command line option
--help, 821
--sudo, 821
--user-id, 821
-h, 821
gitlab-user-unban command line option
--help, 807
--id, 807
-h, 807
gitlab-user-unblock command line option
--help, 807
--id, 807
-h, 807
gitlab-user-unfollow command line option
--help, 807
--id, 807
-h, 807
gitlab-user-update command line option
--admin, 808
--avatar, 809
--bio, 808
--can-create-group, 808
--color-scheme-id, 809
--email, 808
--extern-uid, 808
--external, 808
--help, 808
--id, 808
--linkedin, 808
--location, 809
--name, 808
--organization, 808
--password, 808
--private-profile, 809
--projects-limit, 808
--provider, 808
--public-email, 809
--skip-reconfirmation, 808
--skype, 808
--sudo, 808
--theme-id, 809
--twitter, 808
--username, 808
--website-url, 808
-h, 808
gitlab-variable command line option
--help, 821
-h, 821
gitlab-variable-create command line option
--help, 822
--key, 822
--masked, 822
--protected, 822
--sudo, 822
--value, 822
--variable-type, 822
-h, 822
gitlab-variable-delete command line option
--help, 822
--key, 822
--sudo, 822
-h, 822
gitlab-variable-get command line option
--help, 822
--key, 822
--sudo, 822
-h, 822
gitlab-variable-list command line option
--all, 823
--get-all, 823
--help, 823
--page, 823
--per-page, 823
--sudo, 823
-h, 823
gitlab-variable-update command line option
--help, 823
--key, 823
--masked, 823
--protected, 823
--sudo, 823
--value, 823
--variable-type, 823
-h, 823
GitlabActivateError, 452
GitlabAttachFileError, 452
GitlabAuthenticationError, 452
GitlabBanError, 453
GitlabBlockError, 453
GitlabBuildCancelError, 453
GitlabBuildEraseError, 453
GitlabBuildPlayError, 454
GitlabBuildRetryError, 454
GitlabCancelError, 454
GitlabCherryPickError, 454
GitlabCiLintError, 455
```

`GitlabCiYml` (*class in gitlab.v4.objects*), 215
`GitlabCiYmlManager` (*class in gitlab.v4.objects*), 216
`gitlab_ci_ymls` (*gitlab.Gitlab attribute*), 184
`GitlabConfigHelperError`, 450
`GitlabConfigMissingError`, 450
`GitlabConfigParser` (*class in gitlab.config*), 450
`GitlabConnectionError`, 455
`GitlabCreateError`, 455
`GitlabDataError`, 450
`GitlabDeactivateError`, 455
`GitlabDeleteError`, 456
`GitlabDeploymentApprovalError`, 456
`GitlabError`, 456
`GitlabFollowError`, 456
`GitlabGetError`, 457
`GitlabGroupTransferError`, 457
`GitlabHeadError`, 457
`GitlabHousekeepingError`, 457
`GitlabHttpError`, 458
`GitlabIDEError`, 450
`GitlabImportError`, 458
`GitlabInvitationError`, 458
`GitlabJobCancelError`, 458
`GitlabJobEraseError`, 459
`GitlabJobPlayError`, 459
`GitlabJobRetryError`, 459
`GitlabLicenseError`, 459
`GitlabList` (*class in gitlab*), 191
`GitlabListError`, 460
`GitlabMarkdownError`, 461
`GitlabMRAApprovalError`, 460
`GitlabMRClosedError`, 460
`GitlabMRForbiddenError`, 460
`GitlabMROnBuildSuccessError`, 461
`GitlabMRRebaseError`, 461
`GitlabMRResetApprovalError`, 461
`GitlabOperationError`, 462
`GitlabOwnershipError`, 462
`GitlabParsingError`, 462
`GitlabPipelineCancelError`, 462
`GitlabPipelinePlayError`, 463
`GitlabPipelineRetryError`, 463
`GitlabProjectDeployKeyError`, 463
`GitlabPromoteError`, 463
`GitlabProtectError`, 464
`GitlabRenderError`, 464
`GitlabRepairError`, 464
`GitlabRestoreError`, 464
`GitlabRetryError`, 465
`GitlabRevertError`, 465
`GitlabSearchError`, 465
`GitlabSetError`, 465
`GitlabStopError`, 466
`GitlabSubscribeError`, 466
`GitlabTimeTrackingError`, 466
`GitlabTodoError`, 466
`GitlabTopicMergeError`, 467
`GitlabTransferProjectError`, 467
`GitlabUnbanError`, 467
`GitlabUnblockError`, 467
`GitlabUnfollowError`, 468
`GitlabUnsubscribeError`, 468
`GitlabUpdateError`, 468
`GitlabUploadError`, 468
`GitlabUserApproveError`, 469
`GitlabUserRejectError`, 469
`GitlabVerifyError`, 469
`GLOBAL` (*gitlab.const.NotificationLevel attribute*), 451
`GLOBAL_SNIPPET_TITLES` (*gitlab.const.SearchScope attribute*), 451
`gpgkeys` (*gitlab.v4.objects.CurrentUser attribute*), 204
`gpgkeys` (*gitlab.v4.objects.User attribute*), 431
`Group` (*class in gitlab.v4.objects*), 216
`GroupAccessRequest` (*class in gitlab.v4.objects*), 220
`GroupAccessRequestManager` (*class in gitlab.v4.objects*), 220
`GroupAccessToken` (*class in gitlab.v4.objects*), 221
`GroupAccessTokenManager` (*class in gitlab.v4.objects*), 221
`GroupAuditEvent` (*class in gitlab.v4.objects*), 221
`GroupAuditEventManager` (*class in gitlab.v4.objects*), 222
`GroupBadge` (*class in gitlab.v4.objects*), 222
`GroupBadgeManager` (*class in gitlab.v4.objects*), 222
`GroupBillableMember` (*class in gitlab.v4.objects*), 223
`GroupBillableMemberManager` (*class in gitlab.v4.objects*), 224
`GroupBillableMemberMembership` (*class in gitlab.v4.objects*), 224
`GroupBillableMemberMembershipManager` (*class in gitlab.v4.objects*), 224
`GroupBoard` (*class in gitlab.v4.objects*), 224
`GroupBoardList` (*class in gitlab.v4.objects*), 225
`GroupBoardListManager` (*class in gitlab.v4.objects*), 225
`GroupBoardManager` (*class in gitlab.v4.objects*), 226
`GroupCluster` (*class in gitlab.v4.objects*), 226
`GroupClusterManager` (*class in gitlab.v4.objects*), 226
`GroupCustomAttribute` (*class in gitlab.v4.objects*), 228
`GroupCustomAttributeManager` (*class in gitlab.v4.objects*), 228
`GroupDeployToken` (*class in gitlab.v4.objects*), 229
`GroupDeployTokenManager` (*class in gitlab.v4.objects*), 229
`GroupDescendantGroup` (*class in gitlab.v4.objects*), 230

GroupDescendantGroupManager (class in gitlab.v4.objects), 230
GroupEpic (class in gitlab.v4.objects), 231
GroupEpicAwardEmoji (class in gitlab.v4.objects), 231
GroupEpicAwardEmojiManager (class in gitlab.v4.objects), 231
GroupEpicDiscussionNote (class in gitlab.v4.objects), 232
GroupEpicDiscussionNoteManager (class in gitlab.v4.objects), 232
GroupEpicIssue (class in gitlab.v4.objects), 233
GroupEpicIssueManager (class in gitlab.v4.objects), 233
GroupEpicManager (class in gitlab.v4.objects), 234
GroupEpicNote (class in gitlab.v4.objects), 235
GroupEpicNoteAwardEmoji (class in gitlab.v4.objects), 235
GroupEpicNoteAwardEmojiManager (class in gitlab.v4.objects), 236
GroupEpicNoteManager (class in gitlab.v4.objects), 236
GroupEpicResourceLabelEvent (class in gitlab.v4.objects), 237
GroupEpicResourceLabelEventManager (class in gitlab.v4.objects), 237
GroupExport (class in gitlab.v4.objects), 238
GroupExportManager (class in gitlab.v4.objects), 238
GroupHook (class in gitlab.v4.objects), 239
GroupHookManager (class in gitlab.v4.objects), 239
GroupImport (class in gitlab.v4.objects), 241
GroupImportManager (class in gitlab.v4.objects), 241
GroupInvitation (class in gitlab.v4.objects), 241
GroupInvitationManager (class in gitlab.v4.objects), 242
GroupIssue (class in gitlab.v4.objects), 243
GroupIssueManager (class in gitlab.v4.objects), 243
GroupIssuesStatistics (class in gitlab.v4.objects), 244
GroupIssuesStatisticsManager (class in gitlab.v4.objects), 244
GroupIteration (class in gitlab.v4.objects), 244
GroupIterationManager (class in gitlab.v4.objects), 245
GroupLabel (class in gitlab.v4.objects), 246
GroupLabelManager (class in gitlab.v4.objects), 246
GroupLDAPGroupLink (class in gitlab.v4.objects), 245
GroupLDAPGroupLinkManager (class in gitlab.v4.objects), 245
GroupManager (class in gitlab.v4.objects), 247
GroupMember (class in gitlab.v4.objects), 250
GroupMemberAll (class in gitlab.v4.objects), 250
GroupMemberAllManager (class in gitlab.v4.objects), 251
GroupMemberManager (class in gitlab.v4.objects), 251
GroupMergeRequest (class in gitlab.v4.objects), 252
GroupMergeRequestManager (class in gitlab.v4.objects), 252
GroupMilestone (class in gitlab.v4.objects), 253
GroupMilestoneManager (class in gitlab.v4.objects), 254
GroupNotificationSettings (class in gitlab.v4.objects), 255
GroupNotificationSettingsManager (class in gitlab.v4.objects), 255
GroupPackage (class in gitlab.v4.objects), 256
GroupPackageManager (class in gitlab.v4.objects), 256
GroupProject (class in gitlab.v4.objects), 257
GroupProjectManager (class in gitlab.v4.objects), 257
GroupPushRules (class in gitlab.v4.objects), 258
GroupPushRulesManager (class in gitlab.v4.objects), 258
GroupRegistryRepositoryManager (class in gitlab.v4.objects), 259
GroupRunner (class in gitlab.v4.objects), 259
GroupRunnerManager (class in gitlab.v4.objects), 260
groups (gitlab.Gitlab attribute), 184
groups (gitlab.v4.objects.Project attribute), 277
GroupSAMLGroupLink (class in gitlab.v4.objects), 260
GroupSAMLGroupLinkManager (class in gitlab.v4.objects), 260
GroupSubgroup (class in gitlab.v4.objects), 261
GroupSubgroupManager (class in gitlab.v4.objects), 261
GroupVariable (class in gitlab.v4.objects), 262
GroupVariableManager (class in gitlab.v4.objects), 262
GroupWiki (class in gitlab.v4.objects), 263
GroupWikiManager (class in gitlab.v4.objects), 263
GUEST (gitlab.const.AccessLevel attribute), 451

H

headers (gitlab.Gitlab attribute), 184
Hook (class in gitlab.v4.objects), 264
HookManager (class in gitlab.v4.objects), 264
hooks (gitlab.Gitlab attribute), 184
hooks (gitlab.v4.objects.Group attribute), 217
hooks (gitlab.v4.objects.Project attribute), 277
housekeeping() (gitlab.v4.objects.Project method), 277
http_delete() (gitlab.Gitlab method), 184
http_get() (gitlab.Gitlab method), 184
http_head() (gitlab.Gitlab method), 185
http_list() (gitlab.Gitlab method), 185
http_patch() (gitlab.Gitlab method), 186
http_post() (gitlab.Gitlab method), 186
http_put() (gitlab.Gitlab method), 186
http_request() (gitlab.Gitlab method), 187

I

- `id` (*gitlab.v4.objects.ProjectMergeRequestApprovalRule attribute*), 359
- `identityproviders` (*gitlab.v4.objects.User attribute*), 431
- `impersonationtokens` (*gitlab.v4.objects.User attribute*), 431
- `import_bitbucket_server()` (*gitlab.v4.objects.ProjectManager method*), 348
- `import_github()` (*gitlab.v4.objects.ProjectManager method*), 349
- `import_group()` (*gitlab.v4.objects.GroupManager method*), 250
- `import_project()` (*gitlab.v4.objects.ProjectManager method*), 350
- `imports` (*gitlab.v4.objects.Group attribute*), 217
- `imports` (*gitlab.v4.objects.Project attribute*), 277
- `integrations` (*gitlab.v4.objects.Project attribute*), 277
- `INTERNAL` (*gitlab.const.Visibility attribute*), 452
- `invitations` (*gitlab.v4.objects.Group attribute*), 217
- `invitations` (*gitlab.v4.objects.Project attribute*), 277
- `Issue` (*class in gitlab.v4.objects*), 265
- `IssueManager` (*class in gitlab.v4.objects*), 265
- `ISSUES` (*gitlab.const.SearchScope attribute*), 451
- `issues` (*gitlab.Gitlab attribute*), 188
- `issues` (*gitlab.v4.objects.Group attribute*), 218
- `issues` (*gitlab.v4.objects.GroupEpic attribute*), 231
- `issues` (*gitlab.v4.objects.Project attribute*), 277
- `issues()` (*gitlab.v4.objects.GroupMilestone method*), 253
- `issues()` (*gitlab.v4.objects.ProjectMilestone method*), 373
- `issues_statistics` (*gitlab.Gitlab attribute*), 188
- `issues_statistics` (*gitlab.v4.objects.Group attribute*), 218
- `issues_statistics` (*gitlab.v4.objects.Project attribute*), 277
- `IssuesStatistics` (*class in gitlab.v4.objects*), 266
- `IssuesStatisticsManager` (*class in gitlab.v4.objects*), 266
- `iterations` (*gitlab.v4.objects.Group attribute*), 218
- `iterations` (*gitlab.v4.objects.Project attribute*), 277

J

- `job_stats()` (*gitlab.v4.objects.SidekiqManager method*), 423
- `jobs` (*gitlab.v4.objects.Project attribute*), 277
- `jobs` (*gitlab.v4.objects.ProjectPipeline attribute*), 380
- `jobs` (*gitlab.v4.objects.Runner attribute*), 418

K

- `keep_artifacts()` (*gitlab.v4.objects.ProjectJob method*), 337

Key (*class in gitlab.v4.objects*), 267

KeyManager (*class in gitlab.v4.objects*), 267

`keys` (*gitlab.Gitlab attribute*), 188

`keys` (*gitlab.v4.objects.CurrentUser attribute*), 204

`keys` (*gitlab.v4.objects.Project attribute*), 277

`keys` (*gitlab.v4.objects.User attribute*), 431

L

- `labels` (*gitlab.v4.objects.Group attribute*), 218
- `labels` (*gitlab.v4.objects.Project attribute*), 277
- `languages()` (*gitlab.v4.objects.Project method*), 277
- `ldap_group_links` (*gitlab.v4.objects.Group attribute*), 218
- `ldap_sync()` (*gitlab.v4.objects.Group method*), 218
- `LDAPGroup` (*class in gitlab.v4.objects*), 268
- `LDAPGroupManager` (*class in gitlab.v4.objects*), 268
- `ldapgroups` (*gitlab.Gitlab attribute*), 188
- `License` (*class in gitlab.v4.objects*), 269
- `LicenseManager` (*class in gitlab.v4.objects*), 269
- `licenses` (*gitlab.Gitlab attribute*), 188
- `links` (*gitlab.v4.objects.ProjectIssue attribute*), 321
- `links` (*gitlab.v4.objects.ProjectRelease attribute*), 394
- `lint()` (*gitlab.Gitlab method*), 188
- `list()` (*gitlab.mixins.ListMixin method*), 473
- `list()` (*gitlab.v4.objects.LDAPGroupManager method*), 268
- `list()` (*gitlab.v4.objects.UserProjectManager method*), 444
- `ListMixin` (*class in gitlab.mixins*), 473
- `lists` (*gitlab.v4.objects.GroupBoard attribute*), 225
- `lists` (*gitlab.v4.objects.ProjectBoard attribute*), 291

M

- `main()` (*in module gitlab.cli*), 449
- `MAINTAINER` (*gitlab.const.AccessLevel attribute*), 451
- `manager` (*gitlab.base.RESTObject attribute*), 448
- `manager` (*gitlab.mixins.AccessRequestMixin attribute*), 470
- `manager` (*gitlab.mixins.DownloadMixin attribute*), 472
- `manager` (*gitlab.mixins.ObjectDeleteMixin attribute*), 473
- `manager` (*gitlab.mixins.ParticipantsMixin attribute*), 474
- `manager` (*gitlab.mixins.RefreshMixin attribute*), 474
- `manager` (*gitlab.mixins.SaveMixin attribute*), 475
- `manager` (*gitlab.mixins.SubscribableMixin attribute*), 475
- `manager` (*gitlab.mixins.TimeTrackingMixin attribute*), 476
- `manager` (*gitlab.mixins.TodoMixin attribute*), 477
- `manager` (*gitlab.mixins.UserAgentDetailMixin attribute*), 478
- `manager` (*gitlab.v4.objects.Application attribute*), 192
- `manager` (*gitlab.v4.objects.ApplicationAppearance attribute*), 193

manager (`gitlab.v4.objects.ApplicationSettings` attribute), 194
manager (`gitlab.v4.objects.ApplicationStatistics` attribute), 197
manager (`gitlab.v4.objects.AuditEvent` attribute), 198
manager (`gitlab.v4.objects.BroadcastMessage` attribute), 199
manager (`gitlab.v4.objects.BulkImportAllEntity` attribute), 200
manager (`gitlab.v4.objects.BulkImportEntity` attribute), 201
manager (`gitlab.v4.objects.CiLint` attribute), 203
manager (`gitlab.v4.objects.CurrentUserEmail` attribute), 204
manager (`gitlab.v4.objects.CurrentUserGPGKey` attribute), 205
manager (`gitlab.v4.objects.CurrentUserKey` attribute), 206
manager (`gitlab.v4.objects.CurrentUserStatus` attribute), 207
manager (`gitlab.v4.objects.DeployKey` attribute), 208
manager (`gitlab.v4.objects.DeployToken` attribute), 208
manager (`gitlab.v4.objects.Dockerfile` attribute), 209
manager (`gitlab.v4.objects.Event` attribute), 210
manager (`gitlab.v4.objects.Feature` attribute), 210
manager (`gitlab.v4.objects.GenericPackage` attribute), 211
manager (`gitlab.v4.objects.GeoNode` attribute), 213
manager (`gitlab.v4.objects.Gitignore` attribute), 215
manager (`gitlab.v4.objects.Gitlabciyml` attribute), 216
manager (`gitlab.v4.objects.GroupAccessRequest` attribute), 220
manager (`gitlab.v4.objects.GroupAccessToken` attribute), 221
manager (`gitlab.v4.objects.GroupAuditEvent` attribute), 222
manager (`gitlab.v4.objects.GroupBadge` attribute), 222
manager (`gitlab.v4.objects.GroupBillableMemberMemberships` attribute), 224
manager (`gitlab.v4.objects.GroupBoardList` attribute), 225
manager (`gitlab.v4.objects.GroupCluster` attribute), 226
manager (`gitlab.v4.objects.GroupCustomAttribute` attribute), 228
manager (`gitlab.v4.objects.GroupDeployToken` attribute), 229
manager (`gitlab.v4.objects.GroupDescendantGroup` attribute), 230
manager (`gitlab.v4.objects.GroupEpicAwardEmoji` attribute), 231
manager (`gitlab.v4.objects.GroupEpicDiscussionNote` attribute), 232
manager (`gitlab.v4.objects.GroupEpicIssue` attribute), 233
manager (`gitlab.v4.objects.GroupEpicNoteAwardEmoji` attribute), 236
manager (`gitlab.v4.objects.GroupEpicResourceLabelEvent` attribute), 237
manager (`gitlab.v4.objects.GroupExport` attribute), 238
manager (`gitlab.v4.objects.GroupHook` attribute), 239
manager (`gitlab.v4.objects.GroupImport` attribute), 241
manager (`gitlab.v4.objects.GroupInvitation` attribute), 242
manager (`gitlab.v4.objects.GroupIssue` attribute), 243
manager (`gitlab.v4.objects.GroupIssuesStatistics` attribute), 244
manager (`gitlab.v4.objects.GroupIteration` attribute), 245
manager (`gitlab.v4.objects.GroupLabel` attribute), 246
manager (`gitlab.v4.objects.GroupLDAPGroupLink` attribute), 245
manager (`gitlab.v4.objects.GroupMember` attribute), 250
manager (`gitlab.v4.objects.GroupMemberAll` attribute), 251
manager (`gitlab.v4.objects.GroupMergeRequest` attribute), 252
manager (`gitlab.v4.objects.GroupMilestone` attribute), 254
manager (`gitlab.v4.objects.GroupNotificationSettings` attribute), 255
manager (`gitlab.v4.objects.GroupPackage` attribute), 256
manager (`gitlab.v4.objects.GroupProject` attribute), 257
manager (`gitlab.v4.objects.GroupPushRules` attribute), 258
manager (`gitlab.v4.objects.GroupRunner` attribute), 260
manager (`gitlab.v4.objects.GroupSAMLGroupLink` attribute), 260
manager (`gitlab.v4.objects.GroupSubgroup` attribute), 261
manager (`gitlab.v4.objects.GroupVariable` attribute), 262
manager (`gitlab.v4.objects.GroupWiki` attribute), 263
manager (`gitlab.v4.objects.Hook` attribute), 264
manager (`gitlab.v4.objects.Issue` attribute), 265
manager (`gitlab.v4.objects.IssuesStatistics` attribute), 266
manager (`gitlab.v4.objects.Key` attribute), 267
manager (`gitlab.v4.objects.LDAPGroup` attribute), 268
manager (`gitlab.v4.objects.License` attribute), 269
manager (`gitlab.v4.objects.MergeRequest` attribute), 270
manager (`gitlab.v4.objects.Namespace` attribute), 271
manager (`gitlab.v4.objects.NotificationSettings` attribute), 272
manager (`gitlab.v4.objects.PagesDomain` attribute), 274
manager (`gitlab.v4.objects.PersonalAccessToken` attribute), 274
manager (`gitlab.v4.objects.ProjectAccessRequest` attribute), 283
manager (`gitlab.v4.objects.ProjectAccessToken` attribute), 283
manager (`gitlab.v4.objects.ProjectAdditionalStatistics`

attribute), 284

manager (*gitlab.v4.objects.ProjectApproval attribute*), 285

manager (*gitlab.v4.objects.ProjectApprovalRule attribute*), 286

manager (*gitlab.v4.objects.ProjectArtifact attribute*), 286

manager (*gitlab.v4.objects.ProjectAudit attribute*), 288

manager (*gitlab.v4.objects.ProjectAuditEvent attribute*), 289

manager (*gitlab.v4.objects.ProjectBadge attribute*), 290

manager (*gitlab.v4.objects.ProjectBoardList attribute*), 291

manager (*gitlab.v4.objects.ProjectBranch attribute*), 293

manager (*gitlab.v4.objects.ProjectCiLint attribute*), 294

manager (*gitlab.v4.objects.ProjectCluster attribute*), 295

manager (*gitlab.v4.objects.ProjectCommitComment attribute*), 298

manager (*gitlab.v4.objects.ProjectCommitDiscussionNote attribute*), 300

manager (*gitlab.v4.objects.ProjectCommitStatus attribute*), 302

manager (*gitlab.v4.objects.ProjectCustomAttribute attribute*), 303

manager (*gitlab.v4.objects.ProjectDeploymentMergeRequest attribute*), 307

manager (*gitlab.v4.objects.ProjectDeployToken attribute*), 304

manager (*gitlab.v4.objects.ProjectEnvironment attribute*), 308

manager (*gitlab.v4.objects.ProjectEvent attribute*), 309

manager (*gitlab.v4.objects.ProjectExport attribute*), 310

manager (*gitlab.v4.objects.ProjectFile attribute*), 311

manager (*gitlab.v4.objects.ProjectFork attribute*), 315

manager (*gitlab.v4.objects.ProjectHook attribute*), 316

manager (*gitlab.v4.objects.ProjectImport attribute*), 318

manager (*gitlab.v4.objects.ProjectIntegration attribute*), 319

manager (*gitlab.v4.objects.ProjectInvitation attribute*), 320

manager (*gitlab.v4.objects.ProjectIssueAwardEmoji attribute*), 323

manager (*gitlab.v4.objects.ProjectIssueDiscussionNote attribute*), 325

manager (*gitlab.v4.objects.ProjectIssueLink attribute*), 326

manager (*gitlab.v4.objects.ProjectIssueNoteAwardEmoji attribute*), 328

manager (*gitlab.v4.objects.ProjectIssueResourceIterationEvent attribute*), 330

manager (*gitlab.v4.objects.ProjectIssueResourceLabelEvent attribute*), 331

manager (*gitlab.v4.objects.ProjectIssueResourceMilestoneEvent attribute*), 332

manager (*gitlab.v4.objects.ProjectIssueResourceStateEvent attribute*), 334

attribute), 333

manager (*gitlab.v4.objects.ProjectIssueResourceWeightEvent attribute*), 334

manager (*gitlab.v4.objects.ProjectIssuesStatistics attribute*), 334

manager (*gitlab.v4.objects.ProjectJob attribute*), 337

manager (*gitlab.v4.objects.ProjectKey attribute*), 339

manager (*gitlab.v4.objects.ProjectLabel attribute*), 341

manager (*gitlab.v4.objects.ProjectMember attribute*), 352

manager (*gitlab.v4.objects.ProjectMemberAll attribute*), 352

manager (*gitlab.v4.objects.ProjectMergeRequestApproval attribute*), 357

manager (*gitlab.v4.objects.ProjectMergeRequestApprovalState attribute*), 361

manager (*gitlab.v4.objects.ProjectMergeRequestAwardEmoji attribute*), 361

manager (*gitlab.v4.objects.ProjectMergeRequestDiff attribute*), 362

manager (*gitlab.v4.objects.ProjectMergeRequestDiscussionNote attribute*), 364

manager (*gitlab.v4.objects.ProjectMergeRequestNoteAwardEmoji attribute*), 368

manager (*gitlab.v4.objects.ProjectMergeRequestPipeline attribute*), 369

manager (*gitlab.v4.objects.ProjectMergeRequestResourceLabelEvent attribute*), 370

manager (*gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEvent attribute*), 371

manager (*gitlab.v4.objects.ProjectMergeRequestResourceStateEvent attribute*), 372

manager (*gitlab.v4.objects.ProjectMergeTrain attribute*), 373

manager (*gitlab.v4.objects.ProjectMilestone attribute*), 373

manager (*gitlab.v4.objects.ProjectNote attribute*), 375

manager (*gitlab.v4.objects.ProjectNotificationSettings attribute*), 376

manager (*gitlab.v4.objects.ProjectPackageFile attribute*), 377

manager (*gitlab.v4.objects.ProjectPagesDomain attribute*), 379

manager (*gitlab.v4.objects.ProjectPipelineBridge attribute*), 381

manager (*gitlab.v4.objects.ProjectPipelineJob attribute*), 381

manager (*gitlab.v4.objects.ProjectPipelineSchedulePipeline attribute*), 385

manager (*gitlab.v4.objects.ProjectPipelineScheduleVariable attribute*), 385

manager (*gitlab.v4.objects.ProjectPipelineTestReport attribute*), 386

manager (*gitlab.v4.objects.ProjectPipelineTestReportSummary attribute*), 386

attribute), 387
manager (*gitlab.v4.objects.ProjectPipelineVariable attribute*), 388
manager (*gitlab.v4.objects.ProjectProtectedBranch attribute*), 388
manager (*gitlab.v4.objects.ProjectProtectedEnvironment attribute*), 389
manager (*gitlab.v4.objects.ProjectProtectedTag attribute*), 390
manager (*gitlab.v4.objects.ProjectPushRules attribute*), 391
manager (*gitlab.v4.objects.ProjectRegistryTag attribute*), 393
manager (*gitlab.v4.objects.ProjectReleaseLink attribute*), 394
manager (*gitlab.v4.objects.ProjectRemoteMirror attribute*), 397
manager (*gitlab.v4.objects.ProjectResourceGroupUpcoming attribute*), 398
manager (*gitlab.v4.objects.ProjectRunner attribute*), 399
manager (*gitlab.v4.objects.ProjectSecureFile attribute*), 400
manager (*gitlab.v4.objects.ProjectService attribute*), 401
manager (*gitlab.v4.objects.ProjectSnippetAwardEmoji attribute*), 403
manager (*gitlab.v4.objects.ProjectSnippetDiscussionNote attribute*), 404
manager (*gitlab.v4.objects.ProjectSnippetNoteAwardEmoji attribute*), 407
manager (*gitlab.v4.objects.ProjectStorage attribute*), 408
manager (*gitlab.v4.objects.ProjectTag attribute*), 409
manager (*gitlab.v4.objects.ProjectTrigger attribute*), 410
manager (*gitlab.v4.objects.ProjectUser attribute*), 411
manager (*gitlab.v4.objects.ProjectVariable attribute*), 411
manager (*gitlab.v4.objects.ProjectWiki attribute*), 413
manager (*gitlab.v4.objects.RegistryRepository attribute*), 414
manager (*gitlab.v4.objects.RunnerAll attribute*), 419
manager (*gitlab.v4.objects.RunnerJob attribute*), 419
manager (*gitlab.v4.objects.SharedProject attribute*), 422
manager (*gitlab.v4.objects.Snippet attribute*), 425
manager (*gitlab.v4.objects.StarredProject attribute*), 426
manager (*gitlab.v4.objects.Todo attribute*), 427
manager (*gitlab.v4.objects.Topic attribute*), 428
manager (*gitlab.v4.objects.UserActivities attribute*), 433
manager (*gitlab.v4.objects.UserCustomAttribute attribute*), 433
manager (*gitlab.v4.objects.UserEmail attribute*), 434
manager (*gitlab.v4.objects.UserEvent attribute*), 435
manager (*gitlab.v4.objects.UserGPGKey attribute*), 436
manager (*gitlab.v4.objects.UserImpersonationToken attribute*), 437
manager (*gitlab.v4.objects.UserKey attribute*), 438
manager (*gitlab.v4.objects.UserMembership attribute*), 441
manager (*gitlab.v4.objects.UserPersonalAccessToken attribute*), 442
manager (*gitlab.v4.objects.UserProject attribute*), 443
manager (*gitlab.v4.objects.UserStatus attribute*), 445
manager (*gitlab.v4.objects.Variable attribute*), 445
mark_all_as_done() (*gitlab.v4.objects.TodoManager method*), 428
mark_as_done() (*gitlab.v4.objects.Todo method*), 427
markdown() (*gitlab.Gitlab method*), 188
members (*gitlab.v4.objects.Group attribute*), 218
members (*gitlab.v4.objects.Project attribute*), 277
members_all (*gitlab.v4.objects.Group attribute*), 218
members_all (*gitlab.v4.objects.Project attribute*), 277
memberships (*gitlab.v4.objects.GroupBillableMember attribute*), 223
memberships (*gitlab.v4.objects.User attribute*), 431
MENTION (*gitlab.const.NotificationLevel attribute*), 451
merge() (*gitlab.v4.objects.ProjectMergeRequest method*), 356
merge() (*gitlab.v4.objects.TopicManager method*), 429
merge_config() (*gitlab.Gitlab class method*), 189
merge_ref() (*gitlab.v4.objects.ProjectMergeRequest method*), 356
merge_request_iid (*gitlab.v4.objects.ProjectMergeRequestApprovalRule attribute*), 359
MERGE_REQUESTS (*gitlab.const.SearchScope attribute*), 451
merge_requests() (*gitlab.v4.objects.GroupMilestone method*), 254
merge_requests() (*gitlab.v4.objects.ProjectCommit method*), 297
merge_requests() (*gitlab.v4.objects.ProjectMilestone method*), 374
merge_trains (*gitlab.v4.objects.Project attribute*), 277
MergeRequest (*class in gitlab.v4.objects*), 270
MergeRequestManager (*class in gitlab.v4.objects*), 270
mergerequests (*gitlab.Gitlab attribute*), 189
mergerequests (*gitlab.v4.objects.Group attribute*), 218
mergerequests (*gitlab.v4.objects.Project attribute*), 277
mergerequests (*gitlab.v4.objects.ProjectDeployment attribute*), 306
MILESTONES (*gitlab.const.SearchScope attribute*), 451
milestones (*gitlab.v4.objects.Group attribute*), 218
milestones (*gitlab.v4.objects.Project attribute*), 278
MINIMAL_ACCESS (*gitlab.const.AccessLevel attribute*), 451
mirror_pull() (*gitlab.v4.objects.Project method*), 278
mirror_pull_details() (*gitlab.v4.objects.Project method*), 278
module
 gitlab.base, 447

`gitlab.cli`, 449
`gitlab.config`, 450
`gitlab.const`, 451
`gitlab.exceptions`, 452
`gitlab.mixins`, 470
`gitlab.utils`, 478
`gitlab.v4`, 447
`gitlab.v4.objects`, 192
`move()` (*gitlab.v4.objects.ProjectIssue method*), 321

N

`Namespace` (*class in gitlab.v4.objects*), 271
`NamespaceManager` (*class in gitlab.v4.objects*), 271
`namespaces` (*gitlab.Gitlab attribute*), 189
`next()` (*gitlab.base.RESTObjectList method*), 448
`next()` (*gitlab.GitlabList method*), 192
`next_page` (*gitlab.base.RESTObjectList property*), 448
`next_page` (*gitlab.GitlabList property*), 192
`NO_ACCESS` (*gitlab.const.AccessLevel attribute*), 451
`notes` (*gitlab.v4.objects.GroupEpic attribute*), 231
`notes` (*gitlab.v4.objects.Project attribute*), 278
`notes` (*gitlab.v4.objects.ProjectCommitDiscussion attribute*), 299
`notes` (*gitlab.v4.objects.ProjectIssue attribute*), 322
`notes` (*gitlab.v4.objects.ProjectIssueDiscussion attribute*), 324
`notes` (*gitlab.v4.objects.ProjectMergeRequest attribute*), 356
`notes` (*gitlab.v4.objects.ProjectMergeRequestDiscussion attribute*), 363
`notes` (*gitlab.v4.objects.ProjectSnippet attribute*), 402
`notes` (*gitlab.v4.objects.ProjectSnippetDiscussion attribute*), 403
`NotificationLevel` (*class in gitlab.const*), 451
`NotificationSettings` (*class in gitlab.v4.objects*), 272
`notificationsettings` (*gitlab.Gitlab attribute*), 189
`notificationsettings` (*gitlab.v4.objects.Group attribute*), 218
`notificationsettings` (*gitlab.v4.objects.Project attribute*), 278
`NotificationSettingsManager` (*class in gitlab.v4.objects*), 272
`NoUpdateMixin` (*class in gitlab.mixins*), 473

O

`ObjectDeleteMixin` (*class in gitlab.mixins*), 473
`OWNER` (*gitlab.const.AccessLevel attribute*), 451

P

`package_files` (*gitlab.v4.objects.ProjectPackage attribute*), 377
`packages` (*gitlab.v4.objects.Group attribute*), 218

`packages` (*gitlab.v4.objects.Project attribute*), 278
`PagesDomain` (*class in gitlab.v4.objects*), 273
`PagesDomainManager` (*class in gitlab.v4.objects*), 274
`pagesdomains` (*gitlab.Gitlab attribute*), 189
`pagesdomains` (*gitlab.v4.objects.Project attribute*), 278
`parent_attrs` (*gitlab.base.RESTManager property*), 447
`participants()` (*gitlab.mixins.ParticipantsMixin method*), 474
`ParticipantsMixin` (*class in gitlab.mixins*), 473
`PARTICIPATING` (*gitlab.const.NotificationLevel attribute*), 451
`path` (*gitlab.base.RESTManager property*), 447
`per_page` (*gitlab.base.RESTObjectList property*), 448
`per_page` (*gitlab.GitlabList property*), 192
`personal_access_tokens` (*gitlab.Gitlab attribute*), 189
`personal_access_tokens` (*gitlab.v4.objects.User attribute*), 431
`PersonalAccessToken` (*class in gitlab.v4.objects*), 274
`PersonalAccessTokenManager` (*class in gitlab.v4.objects*), 274
`pformat()` (*gitlab.base.RESTObject method*), 448
`pipelines` (*gitlab.v4.objects.Project attribute*), 278
`pipelines` (*gitlab.v4.objects.ProjectMergeRequest attribute*), 356
`pipelines` (*gitlab.v4.objects.ProjectPipelineSchedule attribute*), 383
`pipelineschedules` (*gitlab.v4.objects.Project attribute*), 278
`play()` (*gitlab.v4.objects.ProjectJob method*), 337
`play()` (*gitlab.v4.objects.ProjectPipelineSchedule method*), 383
`pprint()` (*gitlab.base.RESTObject method*), 448
`prev_page` (*gitlab.base.RESTObjectList property*), 448
`prev_page` (*gitlab.GitlabList property*), 192
`PRIVATE` (*gitlab.const.Visibility attribute*), 452
`process_metrics()` (*gitlab.v4.objects.SidekiqManager method*), 423
`Project` (*class in gitlab.v4.objects*), 275
`PROJECT_NOTES` (*gitlab.const.SearchScope attribute*), 451
`ProjectAccessRequest` (*class in gitlab.v4.objects*), 283
`ProjectAccessRequestManager` (*class in gitlab.v4.objects*), 283
`ProjectAccessToken` (*class in gitlab.v4.objects*), 283
`ProjectAccessTokenManager` (*class in gitlab.v4.objects*), 283
`ProjectAdditionalStatistics` (*class in gitlab.v4.objects*), 284
`ProjectAdditionalStatisticsManager` (*class in gitlab.v4.objects*), 284
`ProjectApproval` (*class in gitlab.v4.objects*), 285

ProjectApprovalManager (*class in gitlab.v4.objects*), 285
ProjectApprovalRule (*class in gitlab.v4.objects*), 285
ProjectApprovalRuleManager (*class in gitlab.v4.objects*), 286
ProjectArtifact (*class in gitlab.v4.objects*), 286
ProjectArtifactManager (*class in gitlab.v4.objects*), 286
ProjectAudit (*class in gitlab.v4.objects*), 288
ProjectAuditEvent (*class in gitlab.v4.objects*), 288
ProjectAuditEventManager (*class in gitlab.v4.objects*), 289
ProjectAuditManager (*class in gitlab.v4.objects*), 289
ProjectBadge (*class in gitlab.v4.objects*), 290
ProjectBadgeManager (*class in gitlab.v4.objects*), 290
ProjectBoard (*class in gitlab.v4.objects*), 291
ProjectBoardList (*class in gitlab.v4.objects*), 291
ProjectBoardListManager (*class in gitlab.v4.objects*), 291
ProjectBoardManager (*class in gitlab.v4.objects*), 292
ProjectBranch (*class in gitlab.v4.objects*), 293
ProjectBranchManager (*class in gitlab.v4.objects*), 293
ProjectCiLint (*class in gitlab.v4.objects*), 293
ProjectCiLintManager (*class in gitlab.v4.objects*), 294
ProjectCluster (*class in gitlab.v4.objects*), 295
ProjectClusterManager (*class in gitlab.v4.objects*), 295
ProjectCommit (*class in gitlab.v4.objects*), 296
ProjectCommitComment (*class in gitlab.v4.objects*), 298
ProjectCommitCommentManager (*class in gitlab.v4.objects*), 299
ProjectCommitDiscussion (*class in gitlab.v4.objects*), 299
ProjectCommitDiscussionManager (*class in gitlab.v4.objects*), 299
ProjectCommitDiscussionNote (*class in gitlab.v4.objects*), 300
ProjectCommitDiscussionNoteManager (*class in gitlab.v4.objects*), 300
ProjectCommitManager (*class in gitlab.v4.objects*), 301
ProjectCommitStatus (*class in gitlab.v4.objects*), 302
ProjectCommitStatusManager (*class in gitlab.v4.objects*), 302
ProjectCustomAttribute (*class in gitlab.v4.objects*), 303
ProjectCustomAttributeManager (*class in gitlab.v4.objects*), 303
ProjectDeployment (*class in gitlab.v4.objects*), 305
ProjectDeploymentManager (*class in gitlab.v4.objects*), 306
ProjectDeploymentMergeRequest (*class in gitlab.v4.objects*), 307
ProjectDeploymentMergeRequestManager (*class in gitlab.v4.objects*), 307
ProjectDeployToken (*class in gitlab.v4.objects*), 304
ProjectDeployTokenManager (*class in gitlab.v4.objects*), 304
ProjectEnvironment (*class in gitlab.v4.objects*), 308
ProjectEnvironmentManager (*class in gitlab.v4.objects*), 308
ProjectEvent (*class in gitlab.v4.objects*), 309
ProjectEventManager (*class in gitlab.v4.objects*), 310
ProjectExport (*class in gitlab.v4.objects*), 310
ProjectExportManager (*class in gitlab.v4.objects*), 310
ProjectFile (*class in gitlab.v4.objects*), 311
ProjectFileManager (*class in gitlab.v4.objects*), 312
ProjectFork (*class in gitlab.v4.objects*), 315
ProjectForkManager (*class in gitlab.v4.objects*), 315
ProjectHook (*class in gitlab.v4.objects*), 316
ProjectHookManager (*class in gitlab.v4.objects*), 316
ProjectImport (*class in gitlab.v4.objects*), 318
ProjectImportManager (*class in gitlab.v4.objects*), 318
ProjectIntegration (*class in gitlab.v4.objects*), 318
ProjectIntegrationManager (*class in gitlab.v4.objects*), 319
ProjectInvitation (*class in gitlab.v4.objects*), 319
ProjectInvitationManager (*class in gitlab.v4.objects*), 320
ProjectIssue (*class in gitlab.v4.objects*), 321
ProjectIssueAwardEmoji (*class in gitlab.v4.objects*), 322
ProjectIssueAwardEmojiManager (*class in gitlab.v4.objects*), 323
ProjectIssueDiscussion (*class in gitlab.v4.objects*), 323
ProjectIssueDiscussionManager (*class in gitlab.v4.objects*), 324
ProjectIssueDiscussionNote (*class in gitlab.v4.objects*), 324
ProjectIssueDiscussionNoteManager (*class in gitlab.v4.objects*), 325
ProjectIssueLink (*class in gitlab.v4.objects*), 325
ProjectIssueLinkManager (*class in gitlab.v4.objects*), 326
ProjectIssueManager (*class in gitlab.v4.objects*), 326
ProjectIssueNote (*class in gitlab.v4.objects*), 328
ProjectIssueNoteAwardEmoji (*class in gitlab.v4.objects*), 328
ProjectIssueNoteAwardEmojiManager (*class in gitlab.v4.objects*), 328
ProjectIssueNoteManager (*class in gitlab.v4.objects*), 329

`ProjectIssueResourceIterationEvent` (*class in gitlab.v4.objects*), 330
`ProjectIssueResourceIterationEventManager` (*class in gitlab.v4.objects*), 330
`ProjectIssueResourceLabelEvent` (*class in gitlab.v4.objects*), 331
`ProjectIssueResourceLabelEventManager` (*class in gitlab.v4.objects*), 331
`ProjectIssueResourceMilestoneEvent` (*class in gitlab.v4.objects*), 332
`ProjectIssueResourceMilestoneEventManager` (*class in gitlab.v4.objects*), 332
`ProjectIssueResourceStateEvent` (*class in gitlab.v4.objects*), 333
`ProjectIssueResourceStateEventManager` (*class in gitlab.v4.objects*), 333
`ProjectIssueResourceWeightEvent` (*class in gitlab.v4.objects*), 333
`ProjectIssueResourceWeightEventManager` (*class in gitlab.v4.objects*), 334
`ProjectIssuesStatistics` (*class in gitlab.v4.objects*), 334
`ProjectIssuesStatisticsManager` (*class in gitlab.v4.objects*), 334
`ProjectIterationManager` (*class in gitlab.v4.objects*), 335
`ProjectJob` (*class in gitlab.v4.objects*), 335
`ProjectJobManager` (*class in gitlab.v4.objects*), 338
`ProjectKey` (*class in gitlab.v4.objects*), 339
`ProjectKeyManager` (*class in gitlab.v4.objects*), 339
`ProjectLabel` (*class in gitlab.v4.objects*), 340
`ProjectLabelManager` (*class in gitlab.v4.objects*), 341
`ProjectManager` (*class in gitlab.v4.objects*), 342
`ProjectMember` (*class in gitlab.v4.objects*), 352
`ProjectMemberAll` (*class in gitlab.v4.objects*), 352
`ProjectMemberAllManager` (*class in gitlab.v4.objects*), 352
`ProjectMemberManager` (*class in gitlab.v4.objects*), 353
`ProjectMergeRequest` (*class in gitlab.v4.objects*), 354
`ProjectMergeRequestApproval` (*class in gitlab.v4.objects*), 357
`ProjectMergeRequestApprovalManager` (*class in gitlab.v4.objects*), 357
`ProjectMergeRequestApprovalRule` (*class in gitlab.v4.objects*), 358
`ProjectMergeRequestApprovalRuleManager` (*class in gitlab.v4.objects*), 359
`ProjectMergeRequestApprovalState` (*class in gitlab.v4.objects*), 360
`ProjectMergeRequestApprovalStateManager` (*class in gitlab.v4.objects*), 361
`ProjectMergeRequestAwardEmoji` (*class in gitlab.v4.objects*), 361
`ProjectMergeRequestAwardEmojiManager` (*class in gitlab.v4.objects*), 361
`ProjectMergeRequestDiff` (*class in gitlab.v4.objects*), 362
`ProjectMergeRequestDiffManager` (*class in gitlab.v4.objects*), 362
`ProjectMergeRequestDiscussion` (*class in gitlab.v4.objects*), 363
`ProjectMergeRequestDiscussionManager` (*class in gitlab.v4.objects*), 363
`ProjectMergeRequestDiscussionNote` (*class in gitlab.v4.objects*), 364
`ProjectMergeRequestDiscussionNoteManager` (*class in gitlab.v4.objects*), 364
`ProjectMergeRequestManager` (*class in gitlab.v4.objects*), 365
`ProjectMergeRequestNote` (*class in gitlab.v4.objects*), 367
`ProjectMergeRequestNoteAwardEmoji` (*class in gitlab.v4.objects*), 367
`ProjectMergeRequestNoteAwardEmojiManager` (*class in gitlab.v4.objects*), 368
`ProjectMergeRequestNoteManager` (*class in gitlab.v4.objects*), 368
`ProjectMergeRequestPipeline` (*class in gitlab.v4.objects*), 369
`ProjectMergeRequestPipelineManager` (*class in gitlab.v4.objects*), 369
`ProjectMergeRequestResourceLabelEvent` (*class in gitlab.v4.objects*), 370
`ProjectMergeRequestResourceLabelEventManager` (*class in gitlab.v4.objects*), 370
`ProjectMergeRequestResourceMilestoneEvent` (*class in gitlab.v4.objects*), 371
`ProjectMergeRequestResourceMilestoneEventManager` (*class in gitlab.v4.objects*), 371
`ProjectMergeRequestResourceStateEvent` (*class in gitlab.v4.objects*), 372
`ProjectMergeRequestResourceStateEventManager` (*class in gitlab.v4.objects*), 372
`ProjectMergeTrain` (*class in gitlab.v4.objects*), 372
`ProjectMergeTrainManager` (*class in gitlab.v4.objects*), 373
`ProjectMilestone` (*class in gitlab.v4.objects*), 373
`ProjectMilestoneManager` (*class in gitlab.v4.objects*), 374
`ProjectNote` (*class in gitlab.v4.objects*), 375
`ProjectNoteManager` (*class in gitlab.v4.objects*), 375
`ProjectNotificationSettings` (*class in gitlab.v4.objects*), 376
`ProjectNotificationSettingsManager` (*class in gitlab.v4.objects*), 376
`ProjectPackage` (*class in gitlab.v4.objects*), 377
`ProjectPackageFile` (*class in gitlab.v4.objects*), 377

ProjectPackageManager (class in `gitlab.v4.objects`), 378
ProjectPagesDomain (class in `gitlab.v4.objects`), 378
ProjectPagesDomainManager (class in `gitlab.v4.objects`), 379
ProjectPipeline (class in `gitlab.v4.objects`), 380
ProjectPipelineBridge (class in `gitlab.v4.objects`), 380
ProjectPipelineBridgeManager (class in `gitlab.v4.objects`), 381
ProjectPipelineJob (class in `gitlab.v4.objects`), 381
ProjectPipelineJobManager (class in `gitlab.v4.objects`), 381
ProjectPipelineManager (class in `gitlab.v4.objects`), 381
ProjectPipelineSchedule (class in `gitlab.v4.objects`), 383
ProjectPipelineScheduleManager (class in `gitlab.v4.objects`), 384
ProjectPipelineSchedulePipeline (class in `gitlab.v4.objects`), 385
ProjectPipelineSchedulePipelineManager (class in `gitlab.v4.objects`), 385
ProjectPipelineScheduleVariable (class in `gitlab.v4.objects`), 385
ProjectPipelineScheduleVariableManager (class in `gitlab.v4.objects`), 385
ProjectPipelineTestReport (class in `gitlab.v4.objects`), 386
ProjectPipelineTestReportManager (class in `gitlab.v4.objects`), 386
ProjectPipelineTestReportSummary (class in `gitlab.v4.objects`), 387
ProjectPipelineTestReportSummaryManager (class in `gitlab.v4.objects`), 387
ProjectPipelineVariable (class in `gitlab.v4.objects`), 387
ProjectPipelineVariableManager (class in `gitlab.v4.objects`), 388
ProjectProtectedBranch (class in `gitlab.v4.objects`), 388
ProjectProtectedBranchManager (class in `gitlab.v4.objects`), 388
ProjectProtectedEnvironment (class in `gitlab.v4.objects`), 389
ProjectProtectedEnvironmentManager (class in `gitlab.v4.objects`), 389
ProjectProtectedTag (class in `gitlab.v4.objects`), 390
ProjectProtectedTagManager (class in `gitlab.v4.objects`), 390
ProjectPushRules (class in `gitlab.v4.objects`), 391
ProjectPushRulesManager (class in `gitlab.v4.objects`), 391
ProjectRegistryRepository (class in `gitlab.v4.objects`), 392
ProjectRegistryRepositoryManager (class in `gitlab.v4.objects`), 393
ProjectRegistryTag (class in `gitlab.v4.objects`), 393
ProjectRegistryTagManager (class in `gitlab.v4.objects`), 393
ProjectRelease (class in `gitlab.v4.objects`), 394
ProjectReleaseLink (class in `gitlab.v4.objects`), 394
ProjectReleaseLinkManager (class in `gitlab.v4.objects`), 394
ProjectReleaseManager (class in `gitlab.v4.objects`), 395
ProjectRemoteMirror (class in `gitlab.v4.objects`), 396
ProjectRemoteMirrorManager (class in `gitlab.v4.objects`), 397
ProjectResourceGroup (class in `gitlab.v4.objects`), 397
ProjectResourceGroupManager (class in `gitlab.v4.objects`), 397
ProjectResourceGroupUpcomingJob (class in `gitlab.v4.objects`), 398
ProjectResourceGroupUpcomingJobManager (class in `gitlab.v4.objects`), 399
ProjectRunner (class in `gitlab.v4.objects`), 399
ProjectRunnerManager (class in `gitlab.v4.objects`), 399
PROJECTS (`gitlab.const.SearchScope` attribute), 451
projects (`gitlab.Gitlab` attribute), 189
projects (`gitlab.v4.objects.Group` attribute), 218
projects (`gitlab.v4.objects.User` attribute), 431
ProjectSecureFile (class in `gitlab.v4.objects`), 399
ProjectSecureFileManager (class in `gitlab.v4.objects`), 400
ProjectService (class in `gitlab.v4.objects`), 401
ProjectServiceManager (class in `gitlab.v4.objects`), 401
ProjectSnippet (class in `gitlab.v4.objects`), 402
ProjectSnippetAwardEmoji (class in `gitlab.v4.objects`), 402
ProjectSnippetAwardEmojiManager (class in `gitlab.v4.objects`), 403
ProjectSnippetDiscussion (class in `gitlab.v4.objects`), 403
ProjectSnippetDiscussionManager (class in `gitlab.v4.objects`), 403
ProjectSnippetDiscussionNote (class in `gitlab.v4.objects`), 404
ProjectSnippetDiscussionNoteManager (class in `gitlab.v4.objects`), 404
ProjectSnippetManager (class in `gitlab.v4.objects`), 405
ProjectSnippetNote (class in `gitlab.v4.objects`), 406

P

- ProjectSnippetNoteAwardEmoji (class in `gitlab.v4.objects`), 406
- ProjectSnippetNoteAwardEmojiManager (class in `gitlab.v4.objects`), 407
- ProjectSnippetNoteManager (class in `gitlab.v4.objects`), 407
- ProjectStorage (class in `gitlab.v4.objects`), 408
- ProjectStorageManager (class in `gitlab.v4.objects`), 408
- ProjectTag (class in `gitlab.v4.objects`), 409
- ProjectTagManager (class in `gitlab.v4.objects`), 409
- ProjectTrigger (class in `gitlab.v4.objects`), 410
- ProjectTriggerManager (class in `gitlab.v4.objects`), 410
- ProjectUser (class in `gitlab.v4.objects`), 411
- ProjectUserManager (class in `gitlab.v4.objects`), 411
- ProjectVariable (class in `gitlab.v4.objects`), 411
- ProjectVariableManager (class in `gitlab.v4.objects`), 412
- ProjectWiki (class in `gitlab.v4.objects`), 413
- ProjectWikiManager (class in `gitlab.v4.objects`), 413
- protected_environments (`gitlab.v4.objects.Project` attribute), 278
- protectedbranches (`gitlab.v4.objects.Project` attribute), 278
- protectedtags (`gitlab.v4.objects.Project` attribute), 278
- PUBLIC (`gitlab.const.Visibility` attribute), 452
- public() (`gitlab.v4.objects.SnippetManager` method), 426
- pushrules (`gitlab.v4.objects.Group` attribute), 218
- pushrules (`gitlab.v4.objects.Project` attribute), 278

Q

- queue_metrics() (`gitlab.v4.objects.SidekiqManager` method), 424

R

- raw() (`gitlab.v4.objects.ProjectArtifactManager` method), 288
- raw() (`gitlab.v4.objects.ProjectFileManager` method), 314
- rebase() (`gitlab.v4.objects.ProjectMergeRequest` method), 356
- RedirectError, 469
- refresh() (`gitlab.mixins.RefreshMixin` method), 474
- RefreshMixin (class in `gitlab.mixins`), 474
- refs() (`gitlab.v4.objects.ProjectCommit` method), 297
- register_custom_action() (in module `gitlab.cli`), 450
- registry_repositories (`gitlab.Gitlab` attribute), 190
- registry_repositories (`gitlab.v4.objects.Group` attribute), 218
- RegistryRepository (class in `gitlab.v4.objects`), 414
- RegistryRepositoryManager (class in `gitlab.v4.objects`), 414
- reject() (`gitlab.v4.objects.User` method), 432
- related_merge_requests() (gitlab.v4.objects.ProjectIssue method), 322
- releases (`gitlab.v4.objects.Project` attribute), 278
- remote_import() (`gitlab.v4.objects.ProjectManager` method), 350
- remote_import_s3() (gitlab.v4.objects.ProjectManager method), 351
- remote_mirrors (gitlab.v4.objects.Project attribute), 278
- remove_none_from_dict() (in module `gitlab.utils`), 479
- render() (`gitlab.mixins.BadgeRenderMixin` method), 470
- reorder() (`gitlab.v4.objects.ProjectIssue` method), 322
- repair() (`gitlab.v4.objects.GeoNode` method), 213
- REPORTER (`gitlab.const.AccessLevel` attribute), 451
- repositories (`gitlab.v4.objects.Project` attribute), 278
- repository_archive() (gitlab.v4.objects.RepositoryMixin method), 415
- repository_blob() (gitlab.v4.objects.RepositoryMixin method), 415
- repository_compare() (gitlab.v4.objects.RepositoryMixin method), 416
- repository_contributors() (gitlab.v4.objects.RepositoryMixin method), 416
- repository_merge_base() (gitlab.v4.objects.RepositoryMixin method), 416
- repository_raw_blob() (gitlab.v4.objects.RepositoryMixin method), 417
- repository_tree() (gitlab.v4.objects.RepositoryMixin method), 417
- RepositoryMixin (class in `gitlab.v4.objects`), 415
- reset_approvals() (gitlab.v4.objects.ProjectMergeRequest method), 356
- reset_spent_time() (gitlab.mixins.TimeTrackingMixin method), 476
- reset_time_estimate() (gitlab.mixins.TimeTrackingMixin method), 476
- resource_groups (`gitlab.v4.objects.Project` attribute), 279
- resource_iteration_events (gitlab.v4.objects.ProjectIssue attribute), 322

```

resource_weight_events           (git-
    lab.v4.objects.ProjectIssue attribute), 322
resource_label_events          (gitlab.v4.objects.GroupEpic
    attribute), 231
resource_label_events          (gitlab.v4.objects.ProjectIssue
    attribute), 322
resource_label_events          (git-
    lab.v4.objects.ProjectMergeRequest attribute),
    357
resource_milestone_events      (git-
    lab.v4.objects.ProjectIssue attribute), 322
resource_milestone_events      (git-
    lab.v4.objects.ProjectMergeRequest attribute),
    357
resource_state_events          (gitlab.v4.objects.ProjectIssue
    attribute), 322
resource_state_events          (git-
    lab.v4.objects.ProjectMergeRequest attribute),
    357
response_content() (in module gitlab.utils), 479
RESTManager (class in gitlab.base), 447
RESTObject (class in gitlab.base), 447
RESTObjectList (class in gitlab.base), 448
restore() (gitlab.v4.objects.Group method), 218
restore() (gitlab.v4.objects.Project method), 279
RetrieveMixin (class in gitlab.mixins), 474
retry() (gitlab.v4.objects.ProjectJob method), 338
retry() (gitlab.v4.objects.ProjectPipeline method), 380
revert() (gitlab.v4.objects.ProjectCommit method),
    298
Runner (class in gitlab.v4.objects), 418
RunnerAll (class in gitlab.v4.objects), 418
RunnerAllManager (class in gitlab.v4.objects), 419
RunnerJob (class in gitlab.v4.objects), 419
RunnerJobManager (class in gitlab.v4.objects), 419
RunnerManager (class in gitlab.v4.objects), 420
runners (gitlab.Gitlab attribute), 190
runners (gitlab.v4.objects.Group attribute), 218
runners (gitlab.v4.objects.Project attribute), 279
runners_all (gitlab.Gitlab attribute), 190

S
saml_group_links (gitlab.v4.objects.Group attribute),
    218
save() (gitlab.mixins.SaveMixin method), 475
save() (gitlab.v4.objects.GroupEpicIssue method), 233
save() (gitlab.v4.objects.GroupLabel method), 246
save() (gitlab.v4.objects.ProjectFile method), 311
save() (gitlab.v4.objects.ProjectLabel method), 341
save() (gitlab.v4.objects.ProjectMergeRequestApprovalRule
    method), 359
SaveMixin (class in gitlab.mixins), 474
search() (gitlab.Gitlab method), 190
search() (gitlab.v4.objects.Group method), 218
search() (gitlab.v4.objects.Project method), 279
SearchScope (class in gitlab.const), 451
secure_files (gitlab.v4.objects.Project attribute), 279
services (gitlab.v4.objects.Project attribute), 279
set() (gitlab.mixins.SetMixin method), 475
set() (gitlab.v4.objects.FeatureManager method), 211
set_approvers()          (git-
    lab.v4.objects.ProjectMergeRequestApprovalManager
    method), 358
set_license() (gitlab.Gitlab method), 190
SetMixin (class in gitlab.mixins), 475
settings (gitlab.Gitlab attribute), 190
share() (gitlab.v4.objects.Group method), 219
share() (gitlab.v4.objects.Project method), 279
shared_projects (gitlab.v4.objects.Group attribute),
    219
SharedProject (class in gitlab.v4.objects), 422
SharedProjectManager (class in gitlab.v4.objects),
    422
sidekiq (gitlab.Gitlab attribute), 190
SidekiqManager (class in gitlab.v4.objects), 422
signature() (gitlab.v4.objects.ProjectCommit method),
    298
snapshot() (gitlab.v4.objects.Project method), 280
Snippet (class in gitlab.v4.objects), 424
SnippetManager (class in gitlab.v4.objects), 425
snippets (gitlab.Gitlab attribute), 190
snippets (gitlab.v4.objects.Project attribute), 280
ssl_verify (gitlab.Gitlab attribute), 190
star() (gitlab.v4.objects.Project method), 280
starred_projects (gitlab.v4.objects.User attribute),
    432
StarredProject (class in gitlab.v4.objects), 426
StarredProjectManager (class in gitlab.v4.objects),
    426
statistics (gitlab.Gitlab attribute), 191
status (gitlab.v4.objects.CurrentUser attribute), 204
status (gitlab.v4.objects.User attribute), 432
status() (gitlab.v4.objects.GeoNode method), 213
status() (gitlab.v4.objects.GeoNodeManager method),
    214
statuses (gitlab.v4.objects.ProjectCommit attribute),
    298
stop() (gitlab.v4.objects.ProjectEnvironment method),
    308
storage (gitlab.v4.objects.Project attribute), 280
subgroups (gitlab.v4.objects.Group attribute), 219
SubscribableMixin (class in gitlab.mixins), 475
subscribe()          (gitlab.mixins.SubscribableMixin
    method), 475
T
tags (gitlab.v4.objects.Project attribute), 280

```

t

- tags (*gitlab.v4.objects.ProjectRegistryRepository attribute*), 393
- take_ownership() (*gitlab.v4.objects.ProjectPipelineSchedule method*), 383
- test_report (*gitlab.v4.objects.ProjectPipeline attribute*), 380
- test_report_summary (*gitlab.v4.objects.ProjectPipeline attribute*), 380
- time_estimate() (*gitlab.mixins.TimeTrackingMixin method*), 477
- time_stats() (*gitlab.mixins.TimeTrackingMixin method*), 477
- timeout (*gitlab.Gitlab attribute*), 191
- TimeTrackingMixin (*class in gitlab.mixins*), 476
- to_json() (*gitlab.base.RESTObject method*), 448
- Todo (*class in gitlab.v4.objects*), 427
- todo() (*gitlab.mixins.TodoMixin method*), 477
- TodoManager (*class in gitlab.v4.objects*), 427
- TodoMixin (*class in gitlab.mixins*), 477
- todos (*gitlab.Gitlab attribute*), 191
- Topic (*class in gitlab.v4.objects*), 428
- TopicManager (*class in gitlab.v4.objects*), 428
- topics (*gitlab.Gitlab attribute*), 191
- total (*gitlab.base.RESTObjectList property*), 449
- total (*gitlab.GitlabList property*), 192
- total_pages (*gitlab.base.RESTObjectList property*), 449
- total_pages (*gitlab.GitlabList property*), 192
- trace() (*gitlab.v4.objects.ProjectJob method*), 338
- transfer() (*gitlab.v4.objects.Group method*), 219
- transfer() (*gitlab.v4.objects.Project method*), 280
- transfer_project() (*gitlab.v4.objects.Group method*), 220
- transfer_project() (*gitlab.v4.objects.Project method*), 281
- trigger_pipeline() (*gitlab.v4.objects.Project method*), 281
- triggers (*gitlab.v4.objects.Project attribute*), 281

U

- unapprove() (*gitlab.v4.objects.ProjectMergeRequest method*), 357
- unarchive() (*gitlab.v4.objects.Project method*), 281
- unban() (*gitlab.v4.objects.User method*), 432
- unblock() (*gitlab.v4.objects.User method*), 432
- unfollow() (*gitlab.v4.objects.User method*), 432
- unshare() (*gitlab.v4.objects.Group method*), 220
- unshare() (*gitlab.v4.objects.Project method*), 281
- unstar() (*gitlab.v4.objects.Project method*), 282
- unsubscribe() (*gitlab.mixins.SubscribableMixin method*), 476
- upcoming_jobs (*gitlab.v4.objects.ProjectResourceGroup attribute*), 397
- update() (*gitlab.mixins.UpdateMixin method*), 478
- update() (*gitlab.v4.objects.ApplicationAppearanceManager method*), 193
- update() (*gitlab.v4.objects.ApplicationSettingsManager method*), 197
- update() (*gitlab.v4.objects.GroupLabelManager method*), 247
- update() (*gitlab.v4.objects.ProjectFileManager method*), 314
- update() (*gitlab.v4.objects.ProjectLabelManager method*), 342
- update_submodule() (*gitlab.v4.objects.RepositoryMixin method*), 418
- UpdateMixin (*class in gitlab.mixins*), 477
- upload() (*gitlab.v4.objects.GenericPackageManager method*), 212
- upload() (*gitlab.v4.objects.Project method*), 282
- url (*gitlab.Gitlab property*), 191
- User (*class in gitlab.v4.objects*), 429
- user (*gitlab.Gitlab attribute*), 191
- user_activities (*gitlab.Gitlab attribute*), 191
- user_agent_detail() (*gitlab.mixins.UserAgentDetailMixin method*), 478
- UserActivities (*class in gitlab.v4.objects*), 433
- UserActivitiesManager (*class in gitlab.v4.objects*), 433
- UserAgentDetailMixin (*class in gitlab.mixins*), 478
- UserCustomAttribute (*class in gitlab.v4.objects*), 433
- UserCustomAttributeManager (*class in gitlab.v4.objects*), 433
- UserEmail (*class in gitlab.v4.objects*), 434
- UserEmailManager (*class in gitlab.v4.objects*), 434
- UserEvent (*class in gitlab.v4.objects*), 435
- UserEventManager (*class in gitlab.v4.objects*), 435
- UserGPGKey (*class in gitlab.v4.objects*), 436
- UserGPGKeyManager (*class in gitlab.v4.objects*), 436
- UserIdentityProviderManager (*class in gitlab.v4.objects*), 436
- UserImpersonationToken (*class in gitlab.v4.objects*), 437
- UserImpersonationTokenManager (*class in gitlab.v4.objects*), 437
- UserKey (*class in gitlab.v4.objects*), 438
- UserKeyManager (*class in gitlab.v4.objects*), 438
- UserManager (*class in gitlab.v4.objects*), 439
- UserMembership (*class in gitlab.v4.objects*), 441
- UserMembershipManager (*class in gitlab.v4.objects*), 441
- UserPersonalAccessToken (*class in gitlab.v4.objects*), 442

UserPersonalAccessTokenManager (*class in gitlab.v4.objects*), 442
UserProject (*class in gitlab.v4.objects*), 443
UserProjectManager (*class in gitlab.v4.objects*), 443
USERS (*gitlab.const.SearchScope attribute*), 451
users (*gitlab.Gitlab attribute*), 191
users (*gitlab.v4.objects.Project attribute*), 283
UserStatus (*class in gitlab.v4.objects*), 444
UserStatusManager (*class in gitlab.v4.objects*), 445

V

validate() (*gitlab.v4.objects.CiLintManager method*), 203
validate() (*gitlab.v4.objects.ProjectCiLintManager method*), 294
Variable (*class in gitlab.v4.objects*), 445
VariableManager (*class in gitlab.v4.objects*), 445
variables (*gitlab.Gitlab attribute*), 191
variables (*gitlab.v4.objects.Group attribute*), 220
variables (*gitlab.v4.objects.Project attribute*), 283
variables (*gitlab.v4.objects.ProjectPipeline attribute*), 380
variables (*gitlab.v4.objects.ProjectPipelineSchedule attribute*), 383
verify() (*gitlab.v4.objects.RunnerManager method*), 421
version() (*gitlab.Gitlab method*), 191
VerticalHelpFormatter (*class in gitlab.cli*), 449
Visibility (*class in gitlab.const*), 452

W

warn() (*in module gitlab.utils*), 479
WATCH (*gitlab.const.NotificationLevel attribute*), 451
WIKI_BLOBS (*gitlab.const.SearchScope attribute*), 452
wikis (*gitlab.v4.objects.Group attribute*), 220
wikis (*gitlab.v4.objects.Project attribute*), 283