
python-gitlab Documentation

Release 3.5.0

Gauvain Pocentek, Mika Mäenpää

May 28, 2022

TABLE OF CONTENTS

1	Installation	3
2	Using the docker image	5
2.1	Building the image	5
3	Bug reports	7
4	Gitter Community Chat	9
5	Documentation	11
5.1	Build the docs	11
6	Contributing	13
6.1	Getting started with the CLI	13
6.2	Getting started with the API	18
6.3	CLI examples	26
6.4	API examples	28
6.5	API reference (gitlab package)	134
6.6	CLI reference (gitlab command)	375
6.7	Changelog	666
6.8	Release notes	700
6.9	FAQ	704
7	Indices and tables	705
	Python Module Index	707
	Index	709

`python-gitlab` is a Python package providing access to the GitLab server API. It supports the v4 API of GitLab, and provides a CLI tool (`gitlab`).

INSTALLATION

As of 3.0.0, `python-gitlab` is compatible with Python 3.7+.

Use `pip` to install the latest stable version of `python-gitlab`:

```
$ pip install --upgrade python-gitlab
```

The current development version is available on both [GitHub.com](https://github.com/python-gitlab/python-gitlab) and [GitLab.com](https://gitlab.com/python-gitlab/python-gitlab), and can be installed directly from the git repository:

```
$ pip install git+https://github.com/python-gitlab/python-gitlab.git
```

From GitLab:

```
$ pip install git+https://gitlab.com/python-gitlab/python-gitlab.git
```


USING THE DOCKER IMAGE

You can run the Docker image directly from the GitLab registry:

```
$ docker run -it --rm registry.gitlab.com/python-gitlab/python-gitlab:latest <command> ..  
↪ .
```

For example, to get a project on GitLab.com (without authentication):

```
$ docker run -it --rm registry.gitlab.com/python-gitlab/python-gitlab:latest project get_..  
↪ --id gitlab-org/gitlab
```

You can also mount your own config file:

```
$ docker run -it --rm -v /path/to/python-gitlab.cfg:/etc/python-gitlab.cfg registry..  
↪ gitlab.com/python-gitlab/python-gitlab:latest <command> ...
```

2.1 Building the image

To build your own image from this repository, run:

```
$ docker build -t python-gitlab:latest .
```

Run your own image:

```
$ docker run -it --rm -v python-gitlab:latest <command> ...
```


BUG REPORTS

Please report bugs and feature requests at <https://github.com/python-gitlab/python-gitlab/issues>.

GITTER COMMUNITY CHAT

We have a [gitter](https://gitter.im/python-gitlab/Lobby) community chat available at <https://gitter.im/python-gitlab/Lobby>, which you can also directly access via the Open Chat button below.

If you have a simple question, the community might be able to help already, without you opening an issue. If you regularly use python-gitlab, we also encourage you to join and participate. You might discover new ideas and use cases yourself!

DOCUMENTATION

The full documentation for CLI and API is available on [readthedocs](#).

5.1 Build the docs

We use `tox` to manage our environment and build the documentation:

```
pip install tox
tox -e docs
```


CONTRIBUTING

For guidelines for contributing to `python-gitlab`, refer to [CONTRIBUTING.rst](#).

6.1 Getting started with the CLI

`python-gitlab` provides a **gitlab** command-line tool to interact with GitLab servers.

This is especially convenient for running quick ad-hoc commands locally, easily interacting with the API inside GitLab CI, or with more advanced shell scripting when integrating with other tooling.

6.1.1 Configuration

`gitlab` allows setting configuration options via command-line arguments, environment variables, and configuration files.

For a complete list of global CLI options and their environment variable equivalents, see *CLI reference (gitlab command)*.

With no configuration provided, `gitlab` will default to unauthenticated requests against [GitLab.com](#).

With no configuration but running inside a GitLab CI job, it will default to authenticated requests using the current job token against the current instance (via `CI_SERVER_URL` and `CI_JOB_TOKEN` environment variables).

Warning: Please note the job token has very limited permissions and can only be used with certain endpoints. You may need to provide a personal access token instead.

When you provide configuration, values are evaluated with the following precedence:

1. Explicitly provided CLI arguments,
2. Environment variables,
3. Configuration files:
 - a. explicitly defined config files:
 - i. via the `--config-file` CLI argument,
 - ii. via the `PYTHON_GITLAB_CFG` environment variable,
 - b. user-specific config file,
 - c. system-level config file,
4. Environment variables always present in CI (`CI_SERVER_URL`, `CI_JOB_TOKEN`).

Additionally, authentication will take the following precedence when multiple options or environment variables are present:

1. Private token,
2. OAuth token,
3. CI job token.

Configuration files

gitlab looks up 3 configuration files by default:

The PYTHON_GITLAB_CFG environment variable An environment variable that contains the path to a configuration file.

/etc/python-gitlab.cfg System-wide configuration file

~/.python-gitlab.cfg User configuration file

You can use a different configuration file with the `--config-file` option.

Warning: If the PYTHON_GITLAB_CFG environment variable is defined and the target file exists, it will be the only configuration file parsed by gitlab.

If the environment variable is defined and the target file cannot be accessed, gitlab will fail explicitly.

Configuration file format

The configuration file uses the INI format. It contains at least a `[global]` section, and a specific section for each GitLab server. For example:

```
[global]
default = somewhere
ssl_verify = true
timeout = 5

[somewhere]
url = https://some.whe.re
private_token = vTbFeqJYCY3sibBP7BZM
api_version = 4

[elsewhere]
url = http://else.whe.re:8080
private_token = helper: path/to/helper.sh
timeout = 1
```

The `default` option of the `[global]` section defines the GitLab server to use if no server is explicitly specified with the `--gitlab` CLI option.

The `[global]` section also defines the values for the default connection parameters. You can override the values in each GitLab server section.

Table 1: Global options

Option	Possible values	Description
<code>ssl_verify</code>	<code>True</code> , <code>False</code> , or a <code>str</code>	Verify the SSL certificate. Set to <code>False</code> to disable verification, though this will create warnings. Any other value is interpreted as path to a <code>CA_BUNDLE</code> file or directory with certificates of trusted CAs.
<code>timeout</code>	Integer	Number of seconds to wait for an answer before failing.
<code>api_version</code>	Integer	The API version to use to make queries. Only 4 is available since 1.5.0.
<code>per_page</code>	Integer between 1 and 100	The number of items to return in listing queries. GitLab limits the value at 100.
<code>user_agent</code>	<code>str</code>	A string defining a custom user agent to use when <code>gitlab</code> makes requests.

You must define the `url` in each GitLab server section.

Warning: Note that a url that results in 301/302 redirects will raise an error, so it is highly recommended to use the final destination in the `url` field. For example, if the GitLab server you are using redirects requests from `http` to `https`, make sure to use the `https://` protocol in the URL definition.

A URL that redirects using 301/302 (rather than 307/308) will most likely [cause malformed POST and PUT requests](#). `python-gitlab` will therefore raise a `RedirectionError` when it encounters a redirect which it believes will cause such an error, to avoid confusion between successful GET and failing POST/PUT requests on the same instance.

Only one of `private_token`, `oauth_token` or `job_token` should be defined. If neither are defined an anonymous request will be sent to the Gitlab server, with very limited permissions.

We recommend that you use [Credential helpers](#) to securely store your tokens.

Table 2: GitLab server options

Option	Description
<code>url</code>	URL for the GitLab server. Do NOT use a URL which redirects.
<code>private_token</code>	Your user token. Login/password is not supported. Refer to the official documentation to learn how to obtain a token.
<code>oauth_token</code>	An OAuth token for authentication. The Gitlab server must be configured to support this authentication method.
<code>job_token</code>	Your job token. See the official documentation to learn how to obtain a token.
<code>api_version</code>	GitLab API version to use. Only 4 is available since 1.5.0.
<code>http_username</code>	Username for optional HTTP authentication
<code>http_password</code>	Password for optional HTTP authentication

Credential helpers

For all configuration options that contain secrets (`http_password`, `personal_token`, `oauth_token`, `job_token`), you can specify a helper program to retrieve the secret indicated by a `helper:` prefix. This allows you to fetch values from a local keyring store or cloud-hosted vaults such as Bitwarden. Environment variables are expanded if they exist and `~` expands to your home directory.

It is expected that the helper program prints the secret to standard output. To use shell features such as piping to retrieve the value, you will need to use a wrapper script; see below.

Example for a [keyring](#) helper:

```
[global]
default = somewhere
ssl_verify = true
timeout = 5

[somewhere]
url = http://somewe.re
private_token = helper: keyring get Service Username
timeout = 1
```

Example for a `pass` helper with a wrapper script:

```
[global]
default = somewhere
ssl_verify = true
timeout = 5

[somewhere]
url = http://somewe.re
private_token = helper: /path/to/helper.sh
timeout = 1
```

In `/path/to/helper.sh`:

```
#!/bin/bash
pass show path/to/password | head -n 1
```

6.1.2 CLI

Objects and actions

The `gitlab` command expects two mandatory arguments. The first one is the type of object that you want to manipulate. The second is the action that you want to perform. For example:

```
$ gitlab project list
```

Use the `--help` option to list the available object types and actions:

```
$ gitlab --help
$ gitlab project --help
```

Some actions require additional parameters. Use the `--help` option to list mandatory and optional arguments for an action:

```
$ gitlab project create --help
```

Optional arguments

Use the following optional arguments to change the behavior of `gitlab`. These options must be defined before the mandatory arguments.

--verbose, -v Outputs detail about retrieved objects. Available for legacy (default) output only.

--config-file, -c Path to a configuration file.

--gitlab, -g ID of a GitLab server defined in the configuration file.

--output, -o Output format. Defaults to a custom format. Can also be `yaml` or `json`.

Important: The `PyYAML` package is required to use the `yaml` output option. You need to install it explicitly using `pip install python-gitlab[yaml]`

--fields, -f Comma-separated list of fields to display (`yaml` and `json` output formats only). If not used, all the object fields are displayed.

Example:

```
$ gitlab -o yaml -f id,permissions -g elsewhere -c /tmp/gl.cfg project list
```

Reading values from files

You can make `gitlab` read values from files instead of providing them on the command line. This is handy for values containing new lines for instance:

```
$ cat > /tmp/description << EOF
This is the description of my project.

It is obviously the best project around
EOF
$ gitlab project create --name SuperProject --description @/tmp/description
```

6.1.3 Enabling shell autocompletion

To get autocompletion, you'll need to install the package with the extra "autocompletion":

```
pip install python-gitlab[autocompletion]
```

Add the appropriate command below to your shell's config file so that it is run on startup. You will likely have to restart or re-login for the autocompletion to start working.

Bash

```
eval "$(register-python-argcomplete gitlab)"
```

tcsh

```
eval `register-python-argcomplete --shell tcsh gitlab`
```

fish

```
register-python-argcomplete --shell fish gitlab | .
```

Zsh

Warning: Zsh autocompletion support is broken right now in the argcomplete python package. Perhaps it will be fixed in a future release of argcomplete at which point the following instructions will enable autocompletion in zsh.

To activate completions for zsh you need to have bashcompinit enabled in zsh:

```
autoload -U bashcompinit
bashcompinit
```

Afterwards you can enable completion for gitlab:

```
eval "$(register-python-argcomplete gitlab)"
```

6.2 Getting started with the API

python-gitlab only supports GitLab API v4.

6.2.1 gitlab.Gitlab class

To connect to GitLab.com or another GitLab instance, create a `gitlab.Gitlab` object:

```
import gitlab

# anonymous read-only access for public resources (GitLab.com)
gl = gitlab.Gitlab()

# anonymous read-only access for public resources (self-hosted GitLab instance)
gl = gitlab.Gitlab('https://gitlab.example.com')

# private token or personal token authentication (GitLab.com)
gl = gitlab.Gitlab(private_token='JVNSEs8EwWRx5yDxM5q')
```

(continues on next page)

(continued from previous page)

```

# private token or personal token authentication (self-hosted GitLab instance)
gl = gitlab.Gitlab(url='https://gitlab.example.com', private_token='JVNSEs8EwWRx5yDxM5q
↪')

# oauth token authentication
gl = gitlab.Gitlab('https://gitlab.example.com', oauth_token='my_long_token_here')

# job token authentication (to be used in CI)
# bear in mind the limitations of the API endpoints it supports:
# https://docs.gitlab.com/ee/ci/jobs/ci_job_token.html
import os
gl = gitlab.Gitlab('https://gitlab.example.com', job_token=os.environ['CI_JOB_TOKEN'])

# Define your own custom user agent for requests
gl = gitlab.Gitlab('https://gitlab.example.com', user_agent='my-package/1.0.0')

# make an API request to create the gl.user object. This is mandatory if you
# use the username/password authentication - not required for token authentication,
# and will not work with job tokens.
gl.auth()

```

You can also use configuration files to create `gitlab.Gitlab` objects:

```
gl = gitlab.Gitlab.from_config('somewhere', ['/tmp/gl.cfg'])
```

See the [Configuration](#) section for more information about configuration files.

Warning: Note that a url that results in 301/302 redirects will raise an error, so it is highly recommended to use the final destination in the `url` field. For example, if the GitLab server you are using redirects requests from http to https, make sure to use the `https://` protocol in the URL definition.

A URL that redirects using 301/302 (rather than 307/308) will most likely cause malformed POST and PUT requests. python-gitlab will therefore raise a `RedirectionError` when it encounters a redirect which it believes will cause such an error, to avoid confusion between successful GET and failing POST/PUT requests on the same instance.

Note on password authentication

The `/session` API endpoint used for username/password authentication has been removed from GitLab in version 10.2, and is not available on gitlab.com anymore. Personal token authentication is the preferred authentication method.

If you need username/password authentication, you can use cookie-based authentication. You can use the web UI form to authenticate, retrieve cookies, and then use a custom `requests.Session` object to connect to the GitLab API. The following code snippet demonstrates how to automate this: <https://gist.github.com/gpocentek/bd4c3fbf8a6ce226ebddc4aad6b46c0a>.

See [issue 380](#) for a detailed discussion.

6.2.2 Managers

The `gitlab.Gitlab` class provides managers to access the GitLab resources. Each manager provides a set of methods to act on the resources. The available methods depend on the resource type.

Examples:

```
# list all the projects
projects = gl.projects.list()
for project in projects:
    print(project)

# get the group with id == 2
group = gl.groups.get(2)
for project in group.projects.list():
    print(project)

# create a new user
user_data = {'email': 'jen@foo.com', 'username': 'jen', 'name': 'Jen'}
user = gl.users.create(user_data)
print(user)
```

You can list the mandatory and optional attributes for object creation and update with the manager's `get_create_attrs()` and `get_update_attrs()` methods. They return 2 tuples, the first one is the list of mandatory attributes, the second one is the list of optional attribute:

```
# v4 only
print(gl.projects.get_create_attrs())
(('name',), ('path', 'namespace_id', ...))
```

The attributes of objects are defined upon object creation, and depend on the GitLab API itself. To list the available information associated with an object use the `attributes` attribute:

```
project = gl.projects.get(1)
print(project.attributes)
```

Some objects also provide managers to access related GitLab resources:

```
# list the issues for a project
project = gl.projects.get(1)
issues = project.issues.list()
```

python-gitlab allows to send any data to the GitLab server when making queries. In case of invalid or missing arguments python-gitlab will raise an exception with the GitLab server error message:

```
>>> gl.projects.list(sort='invalid value')
...
GitlabListError: 400: sort does not have a valid value
```

You can use the `query_parameters` argument to send arguments that would conflict with python or python-gitlab when using them as kwargs:

```
gl.user_activities.list(from_='2019-01-01') ## invalid

gl.user_activities.list(query_parameters={'from': '2019-01-01'}) # OK
```

6.2.3 Gitlab Objects

You can update or delete a remote object when it exists locally:

```
# update the attributes of a resource
project = gl.projects.get(1)
project.wall_enabled = False
# don't forget to apply your changes on the server:
project.save()

# delete the resource
project.delete()
```

Some classes provide additional methods, allowing more actions on the GitLab resources. For example:

```
# star a git repository
project = gl.projects.get(1)
project.star()
```

You can print a Gitlab Object. For example:

```
project = gl.projects.get(1)
print(project)

# Or in a prettier format.
project.pprint()

# Or explicitly via `pformat()`. This is equivalent to the above.
print(project.pformat())
```

You can also extend the object if the parameter isn't explicitly listed. For example, if you want to update a field that has been newly introduced to the Gitlab API, setting the value on the object is accepted:

```
issues = project.issues.list(state='opened')
for issue in issues:
    issue.my_super_awesome_feature_flag = "random_value"
    issue.save()
```

6.2.4 Base types

The gitlab package provides some base types.

- `gitlab.Gitlab` is the primary class, handling the HTTP requests. It holds the GitLab URL and authentication information.
- `gitlab.base.RESTObject` is the base class for all the GitLab v4 objects. These objects provide an abstraction for GitLab resources (projects, groups, and so on).
- `gitlab.base.RESTManager` is the base class for v4 objects managers, providing the API to manipulate the resources and their attributes.

6.2.5 Lazy objects

To avoid useless API calls to the server you can create lazy objects. These objects are created locally using a known ID, and give access to other managers and methods.

The following example will only make one API call to the GitLab server to star a project (the previous example used 2 API calls):

```
# star a git repository
project = gl.projects.get(1, lazy=True) # no API call
project.star() # API call
```

6.2.6 Pagination

You can use pagination to iterate over long lists. All the Gitlab objects listing methods support the `page` and `per_page` parameters:

```
ten_first_groups = gl.groups.list(page=1, per_page=10)
```

Warning: The first page is page 1, not page 0.

By default GitLab does not return the complete list of items. Use the `all` parameter to get all the items when using listing methods:

```
all_groups = gl.groups.list(all=True)
all_owned_projects = gl.projects.list(owned=True, all=True)
```

You can define the `per_page` value globally to avoid passing it to every `list()` method call:

```
gl = gitlab.Gitlab(url, token, per_page=50)
```

Gitlab allows to also use keyset pagination. You can supply it to your project listing, but you can also do so globally. Be aware that GitLab then also requires you to only use supported order options. At the time of writing, only `order_by="id"` works.

```
gl = gitlab.Gitlab(url, token, pagination="keyset", order_by="id", per_page=100)
gl.projects.list()
```

Reference: <https://docs.gitlab.com/ce/api/README.html#keyset-based-pagination>

`list()` methods can also return a generator object which will handle the next calls to the API when required. This is the recommended way to iterate through a large number of items:

```
items = gl.groups.list(as_list=False)
for item in items:
    print(item.attributes)
```

The generator exposes extra listing information as received from the server:

- `current_page`: current page number (first page is 1)
- `prev_page`: if `None` the current page is the first one
- `next_page`: if `None` the current page is the last one

- `per_page`: number of items per page
- `total_pages`: total number of pages available. This may be a `None` value.
- `total`: total number of items in the list. This may be a `None` value.

Note: For performance reasons, if a query returns more than 10,000 records, GitLab does not return the `total_pages` or `total` headers. In this case, `total_pages` and `total` will have a value of `None`.

For more information see: https://docs.gitlab.com/ee/user/gitlab_com/index.html#pagination-response-headers

6.2.7 Sudo

If you have the administrator status, you can use `sudo` to act as another user. For example:

```
p = gl.projects.create({'name': 'awesome_project'}, sudo='user1')
```

6.2.8 Advanced HTTP configuration

python-gitlab relies on `requests` `Session` objects to perform all the HTTP requests to the Gitlab servers.

You can provide your own `Session` object with custom configuration when you create a `Gitlab` object.

Context manager

You can use `Gitlab` objects as context managers. This makes sure that the `requests.Session` object associated with a `Gitlab` instance is always properly closed when you exit a `with` block:

```
with gitlab.Gitlab(host, token) as gl:
    gl.projects.list()
```

Warning: The context manager will also close the custom `Session` object you might have used to build the `Gitlab` instance.

Proxy configuration

The following sample illustrates how to define a proxy configuration when using python-gitlab:

```
import gitlab
import requests

session = requests.Session()
session.proxies = {
    'https': os.environ.get('https_proxy'),
    'http': os.environ.get('http_proxy'),
}
gl = gitlab.gitlab(url, token, api_version=4, session=session)
```

Reference: <https://2.python-requests.org/en/master/user/advanced/#proxies>

SSL certificate verification

python-gitlab relies on the CA certificate bundle in the *certifi* package that comes with the requests library.

If you need python-gitlab to use your system CA store instead, you can provide the path to the CA bundle in the *REQUESTS_CA_BUNDLE* environment variable.

Reference: <https://2.python-requests.org/en/master/user/advanced/#ssl-cert-verification>

Client side certificate

The following sample illustrates how to use a client-side certificate:

```
import gitlab
import requests

session = requests.Session()
session.cert = ('/path/to/client.cert', '/path/to/client.key')
gl = gitlab.gitlab(url, token, api_version=4, session=session)
```

Reference: <https://2.python-requests.org/en/master/user/advanced/#client-side-certificates>

Rate limits

python-gitlab obeys the rate limit of the GitLab server by default. On receiving a 429 response (Too Many Requests), python-gitlab sleeps for the amount of time in the Retry-After header that GitLab sends back. If GitLab does not return a response with the Retry-After header, python-gitlab will perform an exponential backoff.

If you don't want to wait, you can disable the rate-limiting feature, by supplying the *obey_rate_limit* argument.

```
import gitlab
import requests

gl = gitlab.gitlab(url, token, api_version=4)
gl.projects.list(all=True, obey_rate_limit=False)
```

If you do not disable the rate-limiting feature, you can supply a custom value for *max_retries*; by default, this is set to 10. To retry without bound when throttled, you can set this parameter to -1. This parameter is ignored if *obey_rate_limit* is set to False.

```
import gitlab
import requests

gl = gitlab.gitlab(url, token, api_version=4)
gl.projects.list(all=True, max_retries=12)
```

Warning: You will get an Exception, if you then go over the rate limit of your GitLab instance.

Transient errors

GitLab server can sometimes return a transient HTTP error. python-gitlab can automatically retry in such case, when `retry_transient_errors` argument is set to `True`. When enabled, HTTP error codes 500 (Internal Server Error), 502 (502 Bad Gateway), 503 (Service Unavailable), and 504 (Gateway Timeout) are retried. It will retry until reaching the `max_retries` value. By default, `retry_transient_errors` is set to `False` and an exception is raised for these errors.

```
import gitlab
import requests

gl = gitlab.gitlab(url, token, api_version=4)
gl.projects.list(all=True, retry_transient_errors=True)
```

The default `retry_transient_errors` can also be set on the Gitlab object and overridden by individual API calls.

```
import gitlab
import requests
gl = gitlab.gitlab(url, token, api_version=4, retry_transient_errors=True)
gl.projects.list(all=True) # retries due to default value
gl.projects.list(all=True, retry_transient_errors=False) # does not retry
```

Timeout

python-gitlab will by default use the `timeout` option from it's configuration for all requests. This is passed downwards to the `requests` module at the time of making the HTTP request. However if you would like to override the global timeout parameter for a particular call, you can provide the `timeout` parameter to that API invocation:

```
import gitlab

gl = gitlab.gitlab(url, token, api_version=4)
gl.projects.import_github(ACCESS_TOKEN, 123456, "root", timeout=120.0)
```

6.2.9 Attributes in updated objects

When methods manipulate an existing object, such as with `refresh()` and `save()`, the object will only have attributes that were returned by the server. In some cases, such as when the initial request fetches attributes that are needed later for additional processing, this may not be desired:

```
project = gl.projects.get(1, statistics=True)
project.statistics

project.refresh()
project.statistics # AttributeError
```

To avoid this, either copy the object/attributes before calling `refresh()/save()` or subsequently perform another `get()` call as needed, to fetch the attributes you want.

6.3 CLI examples

See also:

For a complete list of objects and actions available, see *CLI reference (gitlab command)*.

6.3.1 Projects

List the projects (paginated):

```
$ gitlab project list
```

List all the projects:

```
$ gitlab project list --all
```

List all projects of a group:

```
$ gitlab group-project list --all --group-id 1
```

List all projects of a group and its subgroups:

```
$ gitlab group-project list --all --include-subgroups true --group-id 1
```

Limit to 5 items per request, display the 1st page only

```
$ gitlab project list --page 1 --per-page 5
```

Get a specific project (id 2):

```
$ gitlab project get --id 2
```

6.3.2 Users

Get a specific user by id:

```
$ gitlab user get --id 3
```

6.3.3 Deploy tokens

Create a deploy token for a project:

```
$ gitlab -v project-deploy-token create --project-id 2 \  
    --name bar --username root --expires-at "2021-09-09" --scopes "read_repository"
```

List deploy tokens for a group:

```
$ gitlab -v group-deploy-token list --group-id 3
```

6.3.4 Packages

List packages for a project:

```
$ gitlab -v project-package list --project-id 3
```

List packages for a group:

```
$ gitlab -v group-package list --group-id 3
```

Get a specific project package by id:

```
$ gitlab -v project-package get --id 1 --project-id 3
```

Delete a specific project package by id:

```
$ gitlab -v project-package delete --id 1 --project-id 3
```

Upload a generic package to a project:

```
$ gitlab generic-package upload --project-id 1 --package-name hello-world \
  --package-version v1.0.0 --file-name hello.tar.gz --path /path/to/hello.tar.gz
```

Download a project's generic package:

```
$ gitlab generic-package download --project-id 1 --package-name hello-world \
  --package-version v1.0.0 --file-name hello.tar.gz > /path/to/hello.tar.gz
```

6.3.5 Issues

Get a list of issues for this project:

```
$ gitlab project-issue list --project-id 2
```

6.3.6 Snippets

Delete a snippet (id 3):

```
$ gitlab project-snippet delete --id 3 --project-id 2
```

Update a snippet:

```
$ gitlab project-snippet update --id 4 --project-id 2 \
  --code "My New Code"
```

Create a snippet:

```
$ gitlab project-snippet create --project-id 2
Impossible to create object (Missing attribute(s): title, file-name, code)
$ # oops, let's add the attributes:
$ gitlab project-snippet create --project-id 2 --title "the title" \
  --file-name "the name" --code "the code"
```

6.3.7 Commits

Get a specific project commit by its SHA id:

```
$ gitlab project-commit get --project-id 2 --id a43290c
```

Get the signature (e.g. GPG or x509) of a signed commit:

```
$ gitlab project-commit signature --project-id 2 --id a43290c
```

Define the status of a commit (as would be done from a CI tool for example):

```
$ gitlab project-commit-status create --project-id 2 \  
  --commit-id a43290c --state success --name ci/jenkins \  
  --target-url http://server/build/123 \  
  --description "Jenkins build succeeded"
```

6.3.8 Artifacts

Download the artifacts zip archive of a job:

```
$ gitlab project-job artifacts --id 10 --project-id 1 > artifacts.zip
```

6.3.9 Other

Use sudo to act as another user (admin only):

```
$ gitlab project create --name user_project1 --sudo username
```

List values are comma-separated:

```
$ gitlab issue list --labels foo,bar
```

6.4 API examples

6.4.1 Access requests

Users can request access to groups and projects.

When access is granted the user should be given a numerical access level. The following constants are provided to represent the access levels:

- `gitlab.const.GUEST_ACCESS: 10`
- `gitlab.const.REPORTER_ACCESS: 20`
- `gitlab.const.DEVELOPER_ACCESS: 30`
- `gitlab.const.MAINTAINER_ACCESS: 40`
- `gitlab.const.OWNER_ACCESS: 50`

References

- v4 API:
 - `gitlab.v4.objects.ProjectAccessRequest`
 - `gitlab.v4.objects.ProjectAccessRequestManager`
 - `gitlab.v4.objects.Project.accessrequests`
 - `gitlab.v4.objects.GroupAccessRequest`
 - `gitlab.v4.objects.GroupAccessRequestManager`
 - `gitlab.v4.objects.Group.accessrequests`
- GitLab API: https://docs.gitlab.com/ce/api/access_requests.html

Examples

List access requests from projects and groups:

```
p_ars = project.accessrequests.list()
g_ars = group.accessrequests.list()
```

Create an access request:

```
p_ar = project.accessrequests.create()
g_ar = group.accessrequests.create()
```

Approve an access request:

```
ar.approve() # defaults to DEVELOPER level
ar.approve(access_level=gitlab.const.MAINTAINER_ACCESS) # explicitly set access level
```

Deny (delete) an access request:

```
project.accessrequests.delete(user_id)
group.accessrequests.delete(user_id)
# or
ar.delete()
```

6.4.2 Appearance

Reference

- v4 API:
 - `gitlab.v4.objects.ApplicationAppearance`
 - `gitlab.v4.objects.ApplicationAppearanceManager`
 - `gitlab.Gitlab.appearance`
- GitLab API: <https://docs.gitlab.com/ce/api/appearance.html>

Examples

Get the appearance:

```
appearance = gl.appearance.get()
```

Update the appearance:

```
appearance.title = "Test"  
appearance.save()
```

6.4.3 Applications

Reference

- v4 API:
 - `gitlab.v4.objects.Applications`
 - `gitlab.v4.objects.ApplicationManager`
 - `gitlab.Gitlab.applications`
- GitLab API: <https://docs.gitlab.com/ce/api/applications.html>

Examples

List all OAuth applications:

```
applications = gl.applications.list()
```

Create an application:

```
gl.applications.create({'name': 'your_app', 'redirect_uri': 'http://application.url',  
→ 'scopes': 'read_user openid profile email'})
```

Delete an applications:

```
gl.applications.delete(app_id)  
# or  
application.delete()
```

6.4.4 Award Emojis

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssueAwardEmoji`
 - `gitlab.v4.objects.ProjectIssueNoteAwardEmoji`
 - `gitlab.v4.objects.ProjectMergeRequestAwardEmoji`
 - `gitlab.v4.objects.ProjectMergeRequestNoteAwardEmoji`

- `gitlab.v4.objects.ProjectSnippetAwardEmoji`
 - `gitlab.v4.objects.ProjectSnippetNoteAwardEmoji`
 - `gitlab.v4.objects.ProjectIssueAwardEmojiManager`
 - `gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager`
 - `gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager`
 - `gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager`
 - `gitlab.v4.objects.ProjectSnippetAwardEmojiManager`
 - `gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager`
- GitLab API: https://docs.gitlab.com/ce/api/award_emoji.html

Examples

List emojis for a resource:

```
emojis = obj.awardemojis.list()
```

Get a single emoji:

```
emoji = obj.awardemojis.get(emoji_id)
```

Add (create) an emoji:

```
emoji = obj.awardemojis.create({'name': 'tractor'})
```

Delete an emoji:

```
emoji.delete
# or
obj.awardemojis.delete(emoji_id)
```

6.4.5 Badges

Badges can be associated with groups and projects.

Reference

- v4 API:
 - `gitlab.v4.objects.GroupBadge`
 - `gitlab.v4.objects.GroupBadgeManager`
 - `gitlab.v4.objects.Group.badges`
 - `gitlab.v4.objects.ProjectBadge`
 - `gitlab.v4.objects.ProjectBadgeManager`
 - `gitlab.v4.objects.Project.badges`
- GitLab API:

- https://docs.gitlab.com/ce/api/group_badges.html
- https://docs.gitlab.com/ce/api/project_badges.html

Examples

List badges:

```
badges = group_or_project.badges.list()
```

Get a badge:

```
badge = group_or_project.badges.get(badge_id)
```

Create a badge:

```
badge = group_or_project.badges.create({'link_url': link, 'image_url': image_link})
```

Update a badge:

```
badge.image_link = new_link  
badge.save()
```

Delete a badge:

```
badge.delete()
```

Render a badge (preview the generate URLs):

```
output = group_or_project.badges.render(link, image_link)  
print(output['rendered_link_url'])  
print(output['rendered_image_url'])
```

6.4.6 Branches

References

- v4 API:
 - *gitlab.v4.objects.ProjectBranch*
 - *gitlab.v4.objects.ProjectBranchManager*
 - *gitlab.v4.objects.Project.branches*
- GitLab API: <https://docs.gitlab.com/ce/api/branches.html>

Examples

Get the list of branches for a repository:

```
branches = project.branches.list()
```

Get a single repository branch:

```
branch = project.branches.get('main')
```

Create a repository branch:

```
branch = project.branches.create({'branch': 'feature1',  
                                  'ref': 'main'})
```

Delete a repository branch:

```
project.branches.delete('feature1')  
# or  
branch.delete()
```

Delete the merged branches for a project:

```
project.delete_merged_branches()
```

To manage protected branches, see *Protected branches*.

6.4.7 Clusters

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCluster`
 - `gitlab.v4.objects.ProjectClusterManager`
 - `gitlab.v4.objects.Project.clusters`
 - `gitlab.v4.objects.GroupCluster`
 - `gitlab.v4.objects.GroupClusterManager`
 - `gitlab.v4.objects.Group.clusters`
- GitLab API: https://docs.gitlab.com/ee/api/project_clusters.html
- GitLab API: https://docs.gitlab.com/ee/api/group_clusters.html

Examples

List clusters for a project:

```
clusters = project.clusters.list()
```

Create an cluster for a project:

```
cluster = project.clusters.create(
{
    "name": "cluster1",
    "platform_kubernetes_attributes": {
        "api_url": "http://url",
        "token": "tokenval",
    },
})
```

Retrieve a specific cluster for a project:

```
cluster = project.clusters.get(cluster_id)
```

Update an cluster for a project:

```
cluster.platform_kubernetes_attributes = {"api_url": "http://newurl"}
cluster.save()
```

Delete an cluster for a project:

```
cluster = project.clusters.delete(cluster_id)
# or
cluster.delete()
```

List clusters for a group:

```
clusters = group.clusters.list()
```

Create an cluster for a group:

```
cluster = group.clusters.create(
{
    "name": "cluster1",
    "platform_kubernetes_attributes": {
        "api_url": "http://url",
        "token": "tokenval",
    },
})
```

Retrieve a specific cluster for a group:

```
cluster = group.clusters.get(cluster_id)
```

Update an cluster for a group:

```
cluster.platform_kubernetes_attributes = {"api_url": "http://newurl"}
cluster.save()
```

Delete an cluster for a group:

```
cluster = group.clusters.delete(cluster_id)
# or
cluster.delete()
```

6.4.8 Broadcast messages

You can use broadcast messages to display information on all pages of the gitlab web UI. You must have administration permissions to manipulate broadcast messages.

References

- v4 API:
 - *gitlab.v4.objects.BroadcastMessage*
 - *gitlab.v4.objects.BroadcastMessageManager*
 - *gitlab.Gitlab.broadcastmessages*
- GitLab API: https://docs.gitlab.com/ce/api/broadcast_messages.html

Examples

List the messages:

```
msgs = gl.broadcastmessages.list()
```

Get a single message:

```
msg = gl.broadcastmessages.get(msg_id)
```

Create a message:

```
msg = gl.broadcastmessages.create({'message': 'Important information'})
```

The date format for the `starts_at` and `ends_at` parameters is `YYYY-MM-ddThh:mm:ssZ`.

Update a message:

```
msg.font = '#444444'
msg.color = '#999999'
msg.save()
```

Delete a message:

```
gl.broadcastmessages.delete(msg_id)
# or
msg.delete()
```

6.4.9 Commits

Commits

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCommit`
 - `gitlab.v4.objects.ProjectCommitManager`
 - `gitlab.v4.objects.Project.commits`

Examples

List the commits for a project:

```
commits = project.commits.list()
```

You can use the `ref_name`, `since` and `until` filters to limit the results:

```
commits = project.commits.list(ref_name='my_branch')
commits = project.commits.list(since='2016-01-01T00:00:00Z')
```

Note: The available `all` listing argument conflicts with the `python-gitlab` argument. Use `query_parameters` to avoid the conflict:

```
commits = project.commits.list(all=True,
                               query_parameters={'ref_name': 'my_branch'})
```

Create a commit:

```
# See https://docs.gitlab.com/ce/api/commits.html#create-a-commit-with-multiple-files-
↪and-actions
# for actions detail
data = {
    'branch': 'main',
    'commit_message': 'blah blah blah',
    'actions': [
        {
            'action': 'create',
            'file_path': 'README.rst',
            'content': open('path/to/file.rst').read(),
        },
        {
            # Binary files need to be base64 encoded
            'action': 'create',
            'file_path': 'logo.png',
            'content': base64.b64encode(open('logo.png').read()),
            'encoding': 'base64',
        }
    ]
}
```

(continues on next page)

(continued from previous page)

```
    ]
}

commit = project.commits.create(data)
```

Get a commit detail:

```
commit = project.commits.get('e3d5a71b')
```

Get the diff for a commit:

```
diff = commit.diff()
```

Cherry-pick a commit into another branch:

```
commit.cherry_pick(branch='target_branch')
```

Revert a commit on a given branch:

```
commit.revert(branch='target_branch')
```

Get the references the commit has been pushed to (branches and tags):

```
commit.refs() # all references
commit.refs('tag') # only tags
commit.refs('branch') # only branches
```

Get the signature of the commit (if the commit was signed, e.g. with GPG or x509):

```
commit.signature()
```

List the merge requests related to a commit:

```
commit.merge_requests()
```

Commit comments

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectCommitComment*
 - *gitlab.v4.objects.ProjectCommitCommentManager*
 - *gitlab.v4.objects.ProjectCommit.comments*
- GitLab API: <https://docs.gitlab.com/ce/api/commits.html>

Examples

Get the comments for a commit:

```
comments = commit.comments.list()
```

Add a comment on a commit:

```
# Global comment
commit = commit.comments.create({'note': 'This is a nice comment'})
# Comment on a line in a file (on the new version of the file)
commit = commit.comments.create({'note': 'This is another comment',
                                'line': 12,
                                'line_type': 'new',
                                'path': 'README.rst'})
```

Commit status

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectCommitStatus*
 - *gitlab.v4.objects.ProjectCommitStatusManager*
 - *gitlab.v4.objects.ProjectCommit.statuses*
- GitLab API: <https://docs.gitlab.com/ce/api/commits.html>

Examples

List the statuses for a commit:

```
statuses = commit.statuses.list()
```

Change the status of a commit:

```
commit.statuses.create({'state': 'success'})
```

6.4.10 Deploy keys

Deploy keys

Reference

- v4 API:
 - *gitlab.v4.objects.DeployKey*
 - *gitlab.v4.objects.DeployKeyManager*
 - *gitlab.Gitlab.deploykeys*

- GitLab API: https://docs.gitlab.com/ce/api/deploy_keys.html

Examples

List the deploy keys:

```
keys = gl.deploykeys.list()
```

Deploy keys for projects

Deploy keys can be managed on a per-project basis.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectKey`
 - `gitlab.v4.objects.ProjectKeyManager`
 - `gitlab.v4.objects.Project.keys`
- GitLab API: https://docs.gitlab.com/ce/api/deploy_keys.html

Examples

List keys for a project:

```
keys = project.keys.list()
```

Get a single deploy key:

```
key = project.keys.get(key_id)
```

Create a deploy key for a project:

```
key = project.keys.create({'title': 'jenkins key',
                           'key': open('/home/me/.ssh/id_rsa.pub').read()})
```

Delete a deploy key for a project:

```
key = project.keys.list(key_id)
# or
key.delete()
```

Enable a deploy key for a project:

```
project.keys.enable(key_id)
```

Disable a deploy key for a project:

```
project.keys.delete(key_id)
```

6.4.11 Deploy tokens

Deploy tokens allow read-only access to your repository and registry images without having a user and a password.

Deploy tokens

This endpoint requires admin access.

Reference

- v4 API:
 - *gitlab.v4.objects.DeployToken*
 - *gitlab.v4.objects.DeployTokenManager*
 - *gitlab.Gitlab.deploytokens*
- GitLab API: https://docs.gitlab.com/ce/api/deploy_tokens.html

Examples

Use the `list()` method to list all deploy tokens across the GitLab instance.

```
# List deploy tokens
deploy_tokens = gl.deploytokens.list()
```

Project deploy tokens

This endpoint requires project maintainer access or higher.

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectDeployToken*
 - *gitlab.v4.objects.ProjectDeployTokenManager*
 - *gitlab.v4.objects.Project.deploytokens*
- GitLab API: https://docs.gitlab.com/ce/api/deploy_tokens.html#project-deploy-tokens

Examples

List the deploy tokens for a project:

```
deploy_tokens = project.deploytokens.list()
```

Get a deploy token for a project by id:

```
deploy_token = project.deploytokens.get(deploy_token_id)
```

Create a new deploy token to access registry images of a project:

In addition to required parameters `name` and `scopes`, this method accepts the following parameters:

- `expires_at` Expiration date of the deploy token. Does not expire if no value is provided.
- `username` Username for deploy token. Default is `gitlab+deploy-token-{n}`

```
deploy_token = project.deploytokens.create({'name': 'token1', 'scopes': ['read_registry'], 'username': '', 'expires_at': ''})
# show its id
print(deploy_token.id)
# show the token value. Make sure you save it, you won't be able to access it again.
print(deploy_token.token)
```

Warning: With GitLab 12.9, even though `username` and `expires_at` are not required, they always have to be passed to the API. You can set them to empty strings, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211878>. Also, the `username`'s value is ignored by the API and will be overridden with `gitlab+deploy-token-{n}`, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211963> These issues were fixed in GitLab 12.10.

Remove a deploy token from the project:

```
deploy_token.delete()
# or
project.deploytokens.delete(deploy_token.id)
```

Group deploy tokens

Reference

- v4 API:
 - `gitlab.v4.objects.GroupDeployToken`
 - `gitlab.v4.objects.GroupDeployTokenManager`
 - `gitlab.v4.objects.Group.deploytokens`
- GitLab API: https://docs.gitlab.com/ce/api/deploy_tokens.html#group-deploy-tokens

Examples

List the deploy tokens for a group:

```
deploy_tokens = group.deploytokens.list()
```

Get a deploy token for a group by id:

```
deploy_token = group.deploytokens.get(deploy_token_id)
```

Create a new deploy token to access all repositories of all projects in a group:

In addition to required parameters `name` and `scopes`, this method accepts the following parameters:

- `expires_at` Expiration date of the deploy token. Does not expire if no value is provided.
- `username` Username for deploy token. Default is `gitlab+deploy-token-{n}`

```
deploy_token = group.deploytokens.create({'name': 'token1', 'scopes': ['read_repository', '↪'], 'username': '', 'expires_at': ''})  
# show its id  
print(deploy_token.id)
```

Warning: With GitLab 12.9, even though `username` and `expires_at` are not required, they always have to be passed to the API. You can set them to empty strings, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211878>. Also, the `username`'s value is ignored by the API and will be overridden with `gitlab+deploy-token-{n}`, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211963> These issues were fixed in GitLab 12.10.

Remove a deploy token from the group:

```
deploy_token.delete()  
# or  
group.deploytokens.delete(deploy_token.id)
```

6.4.12 Deployments

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectDeployment`
 - `gitlab.v4.objects.ProjectDeploymentManager`
 - `gitlab.v4.objects.Project.deployments`
- GitLab API: <https://docs.gitlab.com/ce/api/deployments.html>

Examples

List deployments for a project:

```
deployments = project.deployments.list()
```

Get a single deployment:

```
deployment = project.deployments.get(deployment_id)
```

Create a new deployment:

```
deployment = project.deployments.create({
    "environment": "Test",
    "sha": "1agf4gs",
    "ref": "main",
    "tag": False,
    "status": "created",
})
```

Update a deployment:

```
deployment = project.deployments.get(42)
deployment.status = "failed"
deployment.save()
```

Merge requests associated with a deployment

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectDeploymentMergeRequest*
 - *gitlab.v4.objects.ProjectDeploymentMergeRequestManager*
 - *gitlab.v4.objects.ProjectDeployment.mergerequests*
- GitLab API: <https://docs.gitlab.com/ee/api/deployments.html#list-of-merge-requests-associated-with-a-deployment>

Examples

List the merge requests associated with a deployment:

```
deployment = project.deployments.get(42, lazy=True)
mrs = deployment.mergerequests.list()
```

6.4.13 Discussions

Discussions organize the notes in threads. See the *Notes* chapter for more information about notes.

Discussions are available for project issues, merge requests, snippets and commits.

Reference

- v4 API:

Issues:

- *gitlab.v4.objects.ProjectIssueDiscussion*
- *gitlab.v4.objects.ProjectIssueDiscussionManager*
- *gitlab.v4.objects.ProjectIssueDiscussionNote*
- *gitlab.v4.objects.ProjectIssueDiscussionNoteManager*
- *gitlab.v4.objects.ProjectIssue.notes*

MergeRequests:

- *gitlab.v4.objects.ProjectMergeRequestDiscussion*
- *gitlab.v4.objects.ProjectMergeRequestDiscussionManager*
- *gitlab.v4.objects.ProjectMergeRequestDiscussionNote*
- *gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager*
- *gitlab.v4.objects.ProjectMergeRequest.notes*

Snippets:

- *gitlab.v4.objects.ProjectSnippetDiscussion*
- *gitlab.v4.objects.ProjectSnippetDiscussionManager*
- *gitlab.v4.objects.ProjectSnippetDiscussionNote*
- *gitlab.v4.objects.ProjectSnippetDiscussionNoteManager*
- *gitlab.v4.objects.ProjectSnippet.notes*

- GitLab API: <https://docs.gitlab.com/ce/api/discussions.html>

Examples

List the discussions for a resource (issue, merge request, snippet or commit):

```
discussions = resource.discussions.list()
```

Get a single discussion:

```
discussion = resource.discussions.get(discussion_id)
```

You can access the individual notes in the discussion through the `notes` attribute. It holds a list of notes in chronological order:

```
# ``resource.notes`` is a DiscussionNoteManager, so we need to get the
# object notes using ``attributes``
for note in discussion.attributes['notes']:
    print(note['body'])
```

Note: The notes are dicts, not objects.

You can add notes to existing discussions:

```
new_note = discussion.notes.create({'body': 'Episode IV: A new note'})
```

You can get and update a single note using the **DiscussionNote* resources:

```
discussion = resource.discussions.get(discussion_id)
# Get the latest note's id
note_id = discussion.attributes['notes'][-1]['id']
last_note = discussion.notes.get(note_id)
last_note.body = 'Updated comment'
last_note.save()
```

Create a new discussion:

```
discussion = resource.discussions.create({'body': 'First comment of discussion'})
```

You can comment on merge requests and commit diffs. Provide the `position` dict to define where the comment should appear in the diff:

```
mr_diff = mr.diff.get(diff_id)
mr.discussions.create({'body': 'Note content',
                      'position': {
                          'base_sha': mr_diff.base_commit_sha,
                          'start_sha': mr_diff.start_commit_sha,
                          'head_sha': mr_diff.head_commit_sha,
                          'position_type': 'text',
                          'new_line': 1,
                          'old_path': 'README.rst',
                          'new_path': 'README.rst'
                      }})
```

Resolve / unresolve a merge request discussion:

```
mr_d = mr.discussions.get(d_id)
mr_d.resolved = True # True to resolve, False to unresolve
mr_d.save()
```

Delete a comment:

```
discussions.notes.delete(note_id)
# or
note.delete()
```

6.4.14 Environments

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectEnvironment`
 - `gitlab.v4.objects.ProjectEnvironmentManager`
 - `gitlab.v4.objects.Project.environments`
- GitLab API: <https://docs.gitlab.com/ce/api/environments.html>

Examples

List environments for a project:

```
environments = project.environments.list()
```

Create an environment for a project:

```
environment = project.environments.create({'name': 'production'})
```

Retrieve a specific environment for a project:

```
environment = project.environments.get(112)
```

Update an environment for a project:

```
environment.external_url = 'http://foo.bar.com'  
environment.save()
```

Delete an environment for a project:

```
environment = project.environments.delete(environment_id)  
# or  
environment.delete()
```

Stop an environments:

```
environment.stop()
```

6.4.15 Events

Events

Reference

- v4 API:
 - `gitlab.v4.objects.Event`
 - `gitlab.v4.objects.EventManager`
 - `gitlab.Gitlab.events`

- `gitlab.v4.objects.ProjectEvent`
 - `gitlab.v4.objects.ProjectEventManager`
 - `gitlab.v4.objects.Project.events`
 - `gitlab.v4.objects.UserEvent`
 - `gitlab.v4.objects.UserEventManager`
 - `gitlab.v4.objects.User.events`
- GitLab API: <https://docs.gitlab.com/ce/api/events.html>

Examples

You can list events for an entire Gitlab instance (admin), users and projects. You can filter you events you want to retrieve using the `action` and `target_type` attributes. The possible values for these attributes are available on [the gitlab documentation](#).

List all the events (paginated):

```
events = gl.events.list()
```

List the issue events on a project:

```
events = project.events.list(target_type='issue')
```

List the user events:

```
events = project.events.list()
```

Resource state events

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssueResourceStateEvent`
 - `gitlab.v4.objects.ProjectIssueResourceStateEventManager`
 - `gitlab.v4.objects.ProjectIssue.resourcestateevents`
 - `gitlab.v4.objects.ProjectMergeRequestResourceStateEvent`
 - `gitlab.v4.objects.ProjectMergeRequestResourceStateEventManager`
 - `gitlab.v4.objects.ProjectMergeRequest.resourcestateevents`
- GitLab API: https://docs.gitlab.com/ee/api/resource_state_events.html

Examples

You can list and get specific resource state events (via their id) for project issues and project merge requests.

List the state events of a project issue (paginated):

```
state_events = issue.resourcestateevents.list()
```

Get a specific state event of a project issue by its id:

```
state_event = issue.resourcestateevents.get(1)
```

List the state events of a project merge request (paginated):

```
state_events = mr.resourcestateevents.list()
```

Get a specific state event of a project merge request by its id:

```
state_event = mr.resourcestateevents.get(1)
```

6.4.16 Epics

Epics

Reference

- v4 API:
 - `gitlab.v4.objects.GroupEpic`
 - `gitlab.v4.objects.GroupEpicManager`
 - `gitlab.Gitlab.Group.epics`
- GitLab API: <https://docs.gitlab.com/ee/api/epics.html> (EE feature)

Examples

List the epics for a group:

```
epics = groups.epics.list()
```

Get a single epic for a group:

```
epic = group.epics.get(epic_iid)
```

Create an epic for a group:

```
epic = group.epics.create({'title': 'My Epic'})
```

Edit an epic:

```
epic.title = 'New title'  
epic.labels = ['label1', 'label2']  
epic.save()
```

Delete an epic:

```
epic.delete()
```

Epics issues

Reference

- v4 API:
 - *gitlab.v4.objects.GroupEpicIssue*
 - *gitlab.v4.objects.GroupEpicIssueManager*
 - *gitlab.Gitlab.GroupEpic.issues*
- GitLab API: https://docs.gitlab.com/ee/api/epic_issues.html (EE feature)

Examples

List the issues associated with an issue:

```
ei = epic.issues.list()
```

Associate an issue with an epic:

```
# use the issue id, not its iid
ei = epic.issues.create({'issue_id': 4})
```

Move an issue in the list:

```
ei.move_before_id = epic_issue_id_1
# or
ei.move_after_id = epic_issue_id_2
ei.save()
```

Delete an issue association:

```
ei.delete()
```

6.4.17 Features flags

Reference

- v4 API:
 - *gitlab.v4.objects.Feature*
 - *gitlab.v4.objects.FeatureManager*
 - *gitlab.Gitlab.features*
- GitLab API: <https://docs.gitlab.com/ce/api/features.html>

Examples

List features:

```
features = gl.features.list()
```

Create or set a feature:

```
feature = gl.features.set(feature_name, True)
feature = gl.features.set(feature_name, 30)
feature = gl.features.set(feature_name, True, user=filipowm)
feature = gl.features.set(feature_name, 40, group=mygroup)
```

Delete a feature:

```
feature.delete()
```

6.4.18 Geo nodes

Reference

- v4 API:
 - *gitlab.v4.objects.GeoNode*
 - *gitlab.v4.objects.GeoNodeManager*
 - *gitlab.Gitlab.geonodes*
- GitLab API: https://docs.gitlab.com/ee/api/geo_nodes.html (EE feature)

Examples

List the geo nodes:

```
nodes = gl.geonodes.list()
```

Get the status of all the nodes:

```
status = gl.geonodes.status()
```

Get a specific node and its status:

```
node = gl.geonodes.get(node_id)
node.status()
```

Edit a node configuration:

```
node.url = 'https://secondary.mygitlab.domain'
node.save()
```

Delete a node:

```
node.delete()
```

List the sync failure on the current node:

```
failures = gl.geonodes.current_failures()
```

6.4.19 Groups

Groups

Reference

- v4 API:
 - `gitlab.v4.objects.Group`
 - `gitlab.v4.objects.GroupManager`
 - `gitlab.Gitlab.groups`
- GitLab API: <https://docs.gitlab.com/ce/api/groups.html>

Examples

List the groups:

```
groups = gl.groups.list()
```

Get a group's detail:

```
group = gl.groups.get(group_id)
```

List a group's projects:

```
projects = group.projects.list()
```

Note: `GroupProject` objects returned by this API call are very limited, and do not provide all the features of `Project` objects. If you need to manipulate projects, create a new `Project` object:

```
first_group_project = group.projects.list()[0]  
manageable_project = gl.projects.get(first_group_project.id, lazy=True)
```

You can filter and sort the result using the following parameters:

- `archived`: limit by archived status
- `visibility`: limit by visibility. Allowed values are `public`, `internal` and `private`
- `search`: limit to groups matching the given value
- `order_by`: sort by criteria. Allowed values are `id`, `name`, `path`, `created_at`, `updated_at` and `last_activity_at`
- `sort`: sort order: `asc` or `desc`
- `ci_enabled_first`: return CI enabled groups first
- `include_subgroups`: include projects in subgroups

Create a group:

```
group = gl.groups.create({'name': 'group1', 'path': 'group1'})
```

Create a subgroup under an existing group:

```
subgroup = gl.groups.create({'name': 'subgroup1', 'path': 'subgroup1', 'parent_id':  
↪parent_group_id})
```

Update a group:

```
group.description = 'My awesome group'  
group.save()
```

Set the avatar image for a group:

```
# the avatar image can be passed as data (content of the file) or as a file  
# object opened in binary mode  
group.avatar = open('path/to/file.png', 'rb')  
group.save()
```

Remove a group:

```
gl.groups.delete(group_id)  
# or  
group.delete()
```

Share/unshare the group with a group:

```
group.share(group2.id, gitlab.const.DEVELOPER_ACCESS)  
group.unshare(group2.id)
```

Import / Export

You can export groups from gitlab, and re-import them to create new groups.

Reference

- v4 API:
 - `gitlab.v4.objects.GroupExport`
 - `gitlab.v4.objects.GroupExportManager`
 - `gitlab.v4.objects.Group.exports`
 - `gitlab.v4.objects.GroupImport`
 - `gitlab.v4.objects.GroupImportManager`
 - `gitlab.v4.objects.Group.imports`
 - `gitlab.v4.objects.GroupManager.import_group`
- GitLab API: https://docs.gitlab.com/ce/api/group_import_export.html

Examples

A group export is an asynchronous operation. To retrieve the archive generated by GitLab you need to:

1. Create an export using the API
2. Wait for the export to be done
3. Download the result

Warning: Unlike the Project Export API, GitLab does not provide an `export_status` for Group Exports. It is up to the user to ensure the export is finished.

However, Group Exports only contain metadata, so they are much faster than Project Exports.

```
# Create the export
group = gl.groups.get(my_group)
export = group.exports.create()

# Wait for the export to finish
time.sleep(3)

# Download the result
with open('/tmp/export.tgz', 'wb') as f:
    export.download(streamed=True, action=f.write)
```

Import the group:

```
with open('/tmp/export.tgz', 'rb') as f:
    gl.groups.import_group(f, path='imported-group', name="Imported Group")
```

Subgroups

Reference

- v4 API:
 - `gitlab.v4.objects.GroupSubgroup`
 - `gitlab.v4.objects.GroupSubgroupManager`
 - `gitlab.v4.objects.Group.subgroups`

Examples

List the subgroups for a group:

```
subgroups = group.subgroups.list()
```

Note: The `GroupSubgroup` objects don't expose the same API as the `Group` objects. If you need to manipulate a subgroup as a group, create a new `Group` object:

```
real_group = gl.groups.get(subgroup_id, lazy=True)
real_group.issues.list()
```

Descendant Groups

Reference

- v4 API:
 - *gitlab.v4.objects.GroupDescendantGroup*
 - *gitlab.v4.objects.GroupDescendantGroupManager*
 - *gitlab.v4.objects.Group.descendant_groups*

Examples

List the descendant groups of a group:

```
descendant_groups = group.descendant_groups.list()
```

Note: Like the GroupSubgroup objects described above, GroupDescendantGroup objects do not expose the same API as the Group objects. Create a new Group object instead if needed, as shown in the subgroup example.

Group custom attributes

Reference

- v4 API:
 - *gitlab.v4.objects.GroupCustomAttribute*
 - *gitlab.v4.objects.GroupCustomAttributeManager*
 - *gitlab.v4.objects.Group.customattributes*
- GitLab API: https://docs.gitlab.com/ce/api/custom_attributes.html

Examples

List custom attributes for a group:

```
attrs = group.customattributes.list()
```

Get a custom attribute for a group:

```
attr = group.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a group:

```
attr = group.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a group:

```
attr.delete()
# or
group.customattributes.delete(attr_key)
```

Search groups by custom attribute:

```
group.customattributes.set('role': 'admin')
gl.groups.list(custom_attributes={'role': 'admin'})
```

Group members

The following constants define the supported access levels:

- `gitlab.const.GUEST_ACCESS = 10`
- `gitlab.const.REPORTER_ACCESS = 20`
- `gitlab.const.DEVELOPER_ACCESS = 30`
- `gitlab.const.MAINTAINER_ACCESS = 40`
- `gitlab.const.OWNER_ACCESS = 50`

Reference

- v4 API:
 - `gitlab.v4.objects.GroupMember`
 - `gitlab.v4.objects.GroupMemberManager`
 - `gitlab.v4.objects.GroupMemberAllManager`
 - `gitlab.v4.objects.GroupBillableMember`
 - `gitlab.v4.objects.GroupBillableMemberManager`
 - `gitlab.v4.objects.Group.members`
 - `gitlab.v4.objects.Group.members_all`
 - `gitlab.v4.objects.Group.billable_members`
- GitLab API: <https://docs.gitlab.com/ce/api/members.html>

Billable group members are only available in GitLab EE.

Examples

List only direct group members:

```
members = group.members.list()
```

List the group members recursively (including inherited members through ancestor groups):

```
members = group.members_all.list(all=True)
```

Get only direct group member:

```
members = group.members.get(member_id)
```

Get a member of a group, including members inherited through ancestor groups:

```
members = group.members_all.get(member_id)
```

Add a member to the group:

```
member = group.members.create({'user_id': user_id,  
                               'access_level': gitlab.const.GUEST_ACCESS})
```

Update a member (change the access level):

```
member.access_level = gitlab.const.DEVELOPER_ACCESS  
member.save()
```

Remove a member from the group:

```
group.members.delete(member_id)  
# or  
member.delete()
```

List billable members of a group (top-level groups only):

```
billable_members = group.billable_members.list()
```

Remove a billable member from the group:

```
group.billable_members.delete(member_id)  
# or  
billable_member.delete()
```

List memberships of a billable member:

```
billable_member.memberships.list()
```

LDAP group links

Add an LDAP group link to an existing GitLab group:

```
group.add_ldap_group_link(ldap_group_cn, gitlab.const.DEVELOPER_ACCESS, 'ldapmain')
```

Remove a link:

```
group.delete_ldap_group_link(ldap_group_cn, 'ldapmain')
```

Sync the LDAP groups:

```
group.ldap_sync()
```

You can use the `ldapgroups` manager to list available LDAP groups:

```
# listing (supports pagination)
ldap_groups = gl.ldapgroups.list()

# filter using a group name
ldap_groups = gl.ldapgroups.list(search='foo')

# list the groups for a specific LDAP provider
ldap_groups = gl.ldapgroups.list(search='foo', provider='ldapmain')
```

Groups hooks

Reference

- v4 API:
 - `gitlab.v4.objects.GroupHook`
 - `gitlab.v4.objects.GroupHookManager`
 - `gitlab.v4.objects.Group.hooks`
- GitLab API: <https://docs.gitlab.com/ce/api/groups.html#hooks>

Examples

List the group hooks:

```
hooks = group.hooks.list()
```

Get a group hook:

```
hook = group.hooks.get(hook_id)
```

Create a group hook:

```
hook = group.hooks.create({'url': 'http://my/action/url', 'push_events': 1})
```

Update a group hook:

```
hook.push_events = 0
hook.save()
```

Delete a group hook:

```
group.hooks.delete(hook_id)
# or
hook.delete()
```

6.4.20 Group Access Tokens

Get a list of group access tokens

References

- v4 API:
 - *gitlab.v4.objects.GroupAccessToken*
 - *gitlab.v4.objects.GroupAccessTokenManager*
 - `gitlab.Gitlab.group_access_tokens`
- GitLab API: https://docs.gitlab.com/ee/api/group_access_tokens.html

Examples

List group access tokens:

```
access_tokens = gl.groups.get(1, lazy=True).access_tokens.list()
print(access_tokens[0].name)
```

Create group access token:

```
access_token = gl.groups.get(1).access_tokens.create({"name": "test", "scopes": ["api"]})
```

Revoke a group access tokens:

```
gl.groups.get(1).access_tokens.delete(42)
# or
access_token.delete()
```

6.4.21 Issues

Reported issues

Reference

- v4 API:
 - *gitlab.v4.objects.Issue*
 - *gitlab.v4.objects.IssueManager*

– `gitlab.Gitlab.issues`

- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

Examples

List the issues:

```
issues = gl.issues.list()
```

Use the `state` and `label` parameters to filter the results. Use the `order_by` and `sort` attributes to sort the results:

```
open_issues = gl.issues.list(state='opened')
closed_issues = gl.issues.list(state='closed')
tagged_issues = gl.issues.list(labels=['foo', 'bar'])
```

Note: It is not possible to edit or delete Issue objects. You need to create a `ProjectIssue` object to perform changes:

```
issue = gl.issues.list()[0]
project = gl.projects.get(issue.project_id, lazy=True)
editable_issue = project.issues.get(issue.iid, lazy=True)
editable_issue.title = updated_title
editable_issue.save()
```

Group issues

Reference

- v4 API:
 - `gitlab.v4.objects.GroupIssue`
 - `gitlab.v4.objects.GroupIssueManager`
 - `gitlab.v4.objects.Group.issues`
- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

Examples

List the group issues:

```
issues = group.issues.list()
# Filter using the state, labels and milestone parameters
issues = group.issues.list(milestone='1.0', state='opened')
# Order using the order_by and sort parameters
issues = group.issues.list(order_by='created_at', sort='desc')
```

Note: It is not possible to edit or delete `GroupIssue` objects. You need to create a `ProjectIssue` object to perform changes:

```
issue = group.issues.list()[0]
project = gl.projects.get(issue.project_id, lazy=True)
editable_issue = project.issues.get(issue.iid, lazy=True)
editable_issue.title = updated_title
editable_issue.save()
```

Project issues

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssue`
 - `gitlab.v4.objects.ProjectIssueManager`
 - `gitlab.v4.objects.Project.issues`
- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

Examples

List the project issues:

```
issues = project.issues.list()
# Filter using the state, labels and milestone parameters
issues = project.issues.list(milestone='1.0', state='opened')
# Order using the order_by and sort parameters
issues = project.issues.list(order_by='created_at', sort='desc')
```

Get a project issue:

```
issue = project.issues.get(issue_iid)
```

Create a new issue:

```
issue = project.issues.create({'title': 'I have a bug',
                              'description': 'Something useful here.'})
```

Update an issue:

```
issue.labels = ['foo', 'bar']
issue.save()
```

Close / reopen an issue:

```
# close an issue
issue.state_event = 'close'
issue.save()
# reopen it
issue.state_event = 'reopen'
issue.save()
```

Delete an issue (admin or project owner only):

```
project.issues.delete(issue_id)
# pr
issue.delete()
```

Assign the issues:

```
issue = gl.issues.list()[0]
issue.assignee_ids = [25, 10, 31, 12]
issue.save()
```

Note: The Gitlab API explicitly references that the *assignee_id* field is deprecated, so using a list of user IDs for *assignee_ids* is how to assign an issue to a user(s).

Subscribe / unsubscribe from an issue:

```
issue.subscribe()
issue.unsubscribe()
```

Move an issue to another project:

```
issue.move(other_project_id)
```

Make an issue as todo:

```
issue.todo()
```

Get time tracking stats:

```
issue.time_stats()
```

On recent versions of Gitlab the time stats are also returned as an issue object attribute:

```
issue = project.issue.get(iid)
print(issue.attributes['time_stats'])
```

Set a time estimate for an issue:

```
issue.time_estimate('3h30m')
```

Reset a time estimate for an issue:

```
issue.reset_time_estimate()
```

Add spent time for an issue:

```
issue.add_spent_time('3h30m')
```

Reset spent time for an issue:

```
issue.reset_spent_time()
```

Get user agent detail for the issue (admin only):

```
detail = issue.user_agent_detail()
```

Get the list of merge requests that will close an issue when merged:

```
mrs = issue.closed_by()
```

Get the merge requests related to an issue:

```
mrs = issue.related_merge_requests()
```

Get the list of participants:

```
users = issue.participants()
```

Issue links

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectIssueLink*
 - *gitlab.v4.objects.ProjectIssueLinkManager*
 - *gitlab.v4.objects.ProjectIssue.links*
- GitLab API: https://docs.gitlab.com/ee/api/issue_links.html (EE feature)

Examples

List the issues linked to `i1`:

```
links = i1.links.list()
```

Link issue `i1` to issue `i2`:

```
data = {
    'target_project_id': i2.project_id,
    'target_issue_iid': i2.iid
}
src_issue, dest_issue = i1.links.create(data)
```

Note: The `create()` method returns the source and destination `ProjectIssue` objects, not a `ProjectIssueLink` object.

Delete a link:

```
i1.links.delete(issue_link_id)
```

Issues statistics

Reference

- v4 API:
 - `gitlab.v4.objects.IssuesStatistics`
 - `gitlab.v4.objects.IssuesStatisticsManager`
 - `gitlab.issues_statistics`
 - `gitlab.v4.objects.GroupIssuesStatistics`
 - `gitlab.v4.objects.GroupIssuesStatisticsManager`
 - `gitlab.v4.objects.Group.issues_statistics`
 - `gitlab.v4.objects.ProjectIssuesStatistics`
 - `gitlab.v4.objects.ProjectIssuesStatisticsManager`
 - `gitlab.v4.objects.Project.issues_statistics`
- GitLab API: https://docs.gitlab.com/ce/api/issues_statistics.htm

Examples

Get statistics of all issues created by the current user:

```
statistics = gl.issues_statistics.get()
```

Get statistics of all issues the user has access to:

```
statistics = gl.issues_statistics.get(scope='all')
```

Get statistics of issues for the user with foobar in the title or the description:

```
statistics = gl.issues_statistics.get(search='foobar')
```

Get statistics of all issues in a group:

```
statistics = group.issues_statistics.get()
```

Get statistics of issues in a group with foobar in the title or the description:

```
statistics = group.issues_statistics.get(search='foobar')
```

Get statistics of all issues in a project:

```
statistics = project.issues_statistics.get()
```

Get statistics of issues in a project with foobar in the title or the description:

```
statistics = project.issues_statistics.get(search='foobar')
```

6.4.22 Keys

Keys

Reference

- v4 API
 - *gitlab.v4.objects.Key*
 - *gitlab.v4.objects.KeyManager*
 - *gitlab.Gitlab.keys*
- GitLab API: <https://docs.gitlab.com/ce/api/keys.html>

Examples

Get an ssh key by its id (requires admin access):

```
key = gl.keys.get(key_id)
```

Get an ssh key (requires admin access) or a deploy key by its fingerprint:

```
key = gl.keys.get(fingerprint="SHA256:ERJJ/OweAM6jA80jJ/gXs4N5fqUaREEJnz/EyfywFXY")
```

6.4.23 Issue boards

Boards

Boards are a visual representation of existing issues for a project or a group. Issues can be moved from one list to the other to track progress and help with priorities.

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectBoard*
 - *gitlab.v4.objects.ProjectBoardManager*
 - *gitlab.v4.objects.Project.boards*
 - *gitlab.v4.objects.GroupBoard*
 - *gitlab.v4.objects.GroupBoardManager*
 - *gitlab.v4.objects.Group.boards*
- GitLab API:
 - <https://docs.gitlab.com/ce/api/boards.html>
 - https://docs.gitlab.com/ce/api/group_boards.html

Examples

Get the list of existing boards for a project or a group:

```
# item is a Project or a Group
boards = project_or_group.boards.list()
```

Get a single board for a project or a group:

```
board = project_or_group.boards.get(board_id)
```

Create a board:

```
board = project_or_group.boards.create({'name': 'new-board'})
```

Note: Board creation is not supported in the GitLab CE edition.

Delete a board:

```
board.delete()
# or
project_or_group.boards.delete(board_id)
```

Note: Board deletion is not supported in the GitLab CE edition.

Board lists

Boards are made of lists of issues. Each list is associated to a label, and issues tagged with this label automatically belong to the list.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectBoardList`
 - `gitlab.v4.objects.ProjectBoardListManager`
 - `gitlab.v4.objects.ProjectBoard.lists`
 - `gitlab.v4.objects.GroupBoardList`
 - `gitlab.v4.objects.GroupBoardListManager`
 - `gitlab.v4.objects.GroupBoard.lists`
- GitLab API:
 - <https://docs.gitlab.com/ce/api/boards.html>
 - https://docs.gitlab.com/ce/api/group_boards.html

Examples

List the issue lists for a board:

```
b_lists = board.lists.list()
```

Get a single list:

```
b_list = board.lists.get(list_id)
```

Create a new list:

```
# First get a ProjectLabel
label = get_or_create_label()
# Then use its ID to create the new board list
b_list = board.lists.create({'label_id': label.id})
```

Change a list position. The first list is at position 0. Moving a list will set it at the given position and move the following lists up a position:

```
b_list.position = 2
b_list.save()
```

Delete a list:

```
b_list.delete()
```

6.4.24 Labels

Project labels

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectLabel`
 - `gitlab.v4.objects.ProjectLabelManager`
 - `gitlab.v4.objects.Project.labels`
- GitLab API: <https://docs.gitlab.com/ce/api/labels.html>

Examples

List labels for a project:

```
labels = project.labels.list()
```

Create a label for a project:

```
label = project.labels.create({'name': 'foo', 'color': '#8899aa'})
```

Update a label for a project:

```
# change the name of the label:
label.new_name = 'bar'
label.save()
# change its color:
label.color = '#112233'
label.save()
```

Promote a project label to a group label:

```
label.promote()
```

Delete a label for a project:

```
project.labels.delete(label_id)
# or
label.delete()
```

Manage labels in issues and merge requests:

```
# Labels are defined as lists in issues and merge requests. The labels must
# exist.
issue = p.issues.create({'title': 'issue title',
                        'description': 'issue description',
                        'labels': ['foo']})
issue.labels.append('bar')
issue.save()
```

Label events

Resource label events keep track about who, when, and which label was added or removed to an issuable.

Group epic label events are only available in the EE edition.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssueResourceLabelEvent`
 - `gitlab.v4.objects.ProjectIssueResourceLabelEventManager`
 - `gitlab.v4.objects.ProjectIssue.resourcelabelevents`
 - `gitlab.v4.objects.ProjectMergeRequestResourceLabelEvent`
 - `gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager`
 - `gitlab.v4.objects.ProjectMergeRequest.resourcelabelevents`
 - `gitlab.v4.objects.GroupEpicResourceLabelEvent`
 - `gitlab.v4.objects.GroupEpicResourceLabelEventManager`
 - `gitlab.v4.objects.GroupEpic.resourcelabelevents`
- GitLab API: https://docs.gitlab.com/ee/api/resource_label_events.html

Examples

Get the events for a resource (issue, merge request or epic):

```
events = resource.resourcelabelevents.list()
```

Get a specific event for a resource:

```
event = resource.resourcelabelevents.get(event_id)
```

6.4.25 Notification settings

You can define notification settings globally, for groups and for projects. Valid levels are defined as constants:

- `gitlab.const.NOTIFICATION_LEVEL_DISABLED`
- `gitlab.const.NOTIFICATION_LEVEL_PARTICIPATING`
- `gitlab.const.NOTIFICATION_LEVEL_WATCH`
- `gitlab.const.NOTIFICATION_LEVEL_GLOBAL`
- `gitlab.const.NOTIFICATION_LEVEL_MENTION`
- `gitlab.const.NOTIFICATION_LEVEL_CUSTOM`

You get access to fine-grained settings if you use the `NOTIFICATION_LEVEL_CUSTOM` level.

Reference

- v4 API:
 - `gitlab.v4.objects.NotificationSettings`
 - `gitlab.v4.objects.NotificationSettingsManager`
 - `gitlab.Gitlab.notificationsettings`
 - `gitlab.v4.objects.GroupNotificationSettings`
 - `gitlab.v4.objects.GroupNotificationSettingsManager`
 - `gitlab.v4.objects.Group.notificationsettings`
 - `gitlab.v4.objects.ProjectNotificationSettings`
 - `gitlab.v4.objects.ProjectNotificationSettingsManager`
 - `gitlab.v4.objects.Project.notificationsettings`
- GitLab API: https://docs.gitlab.com/ce/api/notification_settings.html

Examples

Get the notifications settings:

```
# global settings
settings = gl.notificationsettings.get()
# for a group
settings = gl.groups.get(group_id).notificationsettings.get()
# for a project
settings = gl.projects.get(project_id).notificationsettings.get()
```

Update the notifications settings:

```
# use a predefined level
settings.level = gitlab.const.NOTIFICATION_LEVEL_WATCH

# create a custom setup
settings.level = gitlab.const.NOTIFICATION_LEVEL_CUSTOM
settings.save() # will create additional attributes, but not mandatory

settings.new_merge_request = True
settings.new_issue = True
settings.new_note = True
settings.save()
```

6.4.26 Merge Trains

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectMergeTrain`
 - `gitlab.v4.objects.ProjectMergeTrainManager`
 - `gitlab.v4.objects.Project.merge_trains`
- GitLab API: https://docs.gitlab.com/ee/api/merge_trains.html

Examples

List merge trains for a project:

```
merge_trains = project.merge_trains.list()
```

List active merge trains for a project:

```
merge_trains = project.merge_trains.list(scope="active")
```

List completed (have been merged) merge trains for a project:

```
merge_trains = project.merge_trains.list(scope="complete")
```

6.4.27 Merge requests

You can use merge requests to notify a project that a branch is ready for merging. The owner of the target project can accept the merge request.

Merge requests are linked to projects, but they can be listed globally or for groups.

Group and global listing

Reference

- v4 API:
 - `gitlab.v4.objects.GroupMergeRequest`
 - `gitlab.v4.objects.GroupMergeRequestManager`
 - `gitlab.v4.objects.Group.mergerequests`
 - `gitlab.v4.objects.MergeRequest`
 - `gitlab.v4.objects.MergeRequestManager`
 - `gitlab.Gitlab.mergerequests`
- GitLab API: https://docs.gitlab.com/ce/api/merge_requests.html

Examples

List the merge requests created by the user of the token on the GitLab server:

```
mrs = gl.mergerequests.list()
```

List the merge requests available on the GitLab server:

```
mrs = gl.mergerequests.list(scope="all")
```

List the merge requests for a group:

```
group = gl.groups.get('mygroup')
mrs = group.mergerequests.list()
```

Note: It is not possible to edit or delete `MergeRequest` and `GroupMergeRequest` objects. You need to create a `ProjectMergeRequest` object to apply changes:

```
mr = group.mergerequests.list()[0]
project = gl.projects.get(mr.project_id, lazy=True)
editable_mr = project.mergerequests.get(mr.iid, lazy=True)
editable_mr.title = updated_title
editable_mr.save()
```

Project merge requests

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectMergeRequest`
 - `gitlab.v4.objects.ProjectMergeRequestManager`
 - `gitlab.v4.objects.Project.mergerequests`
- GitLab API: https://docs.gitlab.com/ce/api/merge_requests.html

Examples

List MRs for a project:

```
mrs = project.mergerequests.list()
```

You can filter and sort the returned list with the following parameters:

- **state:** state of the MR. It can be one of **all**, **merged**, **opened**, **closed** or **locked**
- **order_by:** sort by `created_at` or `updated_at`
- **sort:** sort order (asc or desc)

You can find a full updated list of parameters here: https://docs.gitlab.com/ee/api/merge_requests.html#list-merge-requests

For example:

```
mrs = project.mergerequests.list(state='merged', order_by='updated_at')
```

Get a single MR:

```
mr = project.mergerequests.get(mr_id)
```

Create a MR:

```
mr = project.mergerequests.create({'source_branch': 'cool_feature',
                                   'target_branch': 'main',
                                   'title': 'merge cool feature',
                                   'labels': ['label1', 'label2']})
```

Update a MR:

```
mr.description = 'New description'
mr.labels = ['foo', 'bar']
mr.save()
```

Change the state of a MR (close or reopen):

```
mr.state_event = 'close' # or 'reopen'
mr.save()
```

Delete a MR:

```
project.mergerequests.delete(mr_id)
# or
mr.delete()
```

Accept a MR:

```
mr.merge()
```

Cancel a MR when the build succeeds:

```
mr.cancel_merge_when_pipeline_succeeds()
```

List commits of a MR:

```
commits = mr.commits()
```

List the changes of a MR:

```
changes = mr.changes()
```

List issues that will close on merge:

```
mr.closes_issues()
```

Subscribe to / unsubscribe from a MR:

```
mr.subscribe()
mr.unsubscribe()
```

Mark a MR as todo:

```
mr.todo()
```

List the diffs for a merge request:

```
diffs = mr.diffs.list()
```

Get a diff for a merge request:

```
diff = mr.diffs.get(diff_id)
```

Get time tracking stats:

```
time_stats = mr.time_stats()
```

On recent versions of Gitlab the time stats are also returned as a merge request object attribute:

```
mr = project.mergerequests.get(id)
print(mr.attributes['time_stats'])
```

Set a time estimate for a merge request:

```
mr.time_estimate('3h30m')
```

Reset a time estimate for a merge request:

```
mr.reset_time_estimate()
```

Add spent time for a merge request:

```
mr.add_spent_time('3h30m')
```

Reset spent time for a merge request:

```
mr.reset_spent_time()
```

Get user agent detail for the issue (admin only):

```
detail = issue.user_agent_detail()
```

Attempt to rebase an MR:

```
mr.rebase()
```

Get status of a rebase for an MR:

```
mr = project.mergerequests.get(mr_id, include_rebase_in_progress=True)
print(mr.rebase_in_progress, mr.merge_error)
```

For more info see: https://docs.gitlab.com/ee/api/merge_requests.html#rebase-a-merge-request

Attempt to merge changes between source and target branch:

```
response = mr.merge_ref()
print(response['commit_id'])
```

Merge Request Pipelines

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectMergeRequestPipeline*
 - *gitlab.v4.objects.ProjectMergeRequestPipelineManager*
 - *gitlab.v4.objects.ProjectMergeRequest.pipelines*
- GitLab API: https://docs.gitlab.com/ee/api/merge_requests.html#list-mr-pipelines

Examples

List pipelines for a merge request:

```
pipelines = mr.pipelines.list()
```

Create a pipeline for a merge request:

```
pipeline = mr.pipelines.create()
```

6.4.28 Merge request approvals settings

Merge request approvals can be defined at the project level or at the merge request level.

References

- v4 API:
 - `gitlab.v4.objects.ProjectApproval`
 - `gitlab.v4.objects.ProjectApprovalManager`
 - `gitlab.v4.objects.ProjectApprovalRule`
 - `gitlab.v4.objects.ProjectApprovalRuleManager`
 - `gitlab.v4.objects.Project.approvals`
 - `gitlab.v4.objects.ProjectMergeRequestApproval`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalManager`
 - `gitlab.v4.objects.ProjectMergeRequest.approvals`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalRule`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager`
 - `gitlab.v4.objects.ProjectMergeRequest.approval_rules`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalState`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalStateManager`
 - `gitlab.v4.objects.ProjectMergeRequest.approval_state`
- GitLab API: https://docs.gitlab.com/ee/api/merge_request_approvals.html

Examples

List project-level MR approval rules:

```
p_mras = project.approvalrules.list()
```

Change project-level MR approval rule:

```
p_approvalrule.user_ids = [234]
p_approvalrule.save()
```

Delete project-level MR approval rule:

```
p_approvalrule.delete()
```

Get project-level or MR-level MR approvals settings:

```
p_mras = project.approvals.get()
mr_mras = mr.approvals.get()
```

Get MR-level approval state:

```
mr_approval_state = mr.approval_state.get()
```

Change project-level or MR-level MR approvals settings:

```
p_mras.approvals_before_merge = 2
p_mras.save()

mr_mras.set_approvers(approvals_required = 1)
```

Change project-level MR allowed approvers:

```
project.approvals.set_approvers(approver_ids=[105],
                                approver_group_ids=[653, 654])
```

Create a new MR-level approval rule or change an existing MR-level approval rule:

```
mr.approvals.set_approvers(approvals_required = 1, approver_ids=[105],
                           approver_group_ids=[653, 654],
                           approval_rule_name="my MR custom approval rule")
```

List MR-level MR approval rules:

```
mr.approval_rules.list()
```

Delete MR-level MR approval rule:

```
rules = mr.approval_rules.list()
rules[0].delete()

# or
mr.approval_rules.delete(approval_id)
```

Change MR-level MR approval rule:

```
mr_approvalrule.user_ids = [105]
mr_approvalrule.approvals_required = 2
mr_approvalrule.group_ids = [653, 654]
mr_approvalrule.save()
```

Create a MR-level MR approval rule:

```
mr.approval_rules.create({
    "name": "my MR custom approval rule",
    "approvals_required": 2,
    "rule_type": "regular",
    "user_ids": [105],
    "group_ids": [653, 654],
})
```

6.4.29 Milestones

Project milestones

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectMilestone`
 - `gitlab.v4.objects.ProjectMilestoneManager`
 - `gitlab.v4.objects.Project.milestones`
 - `gitlab.v4.objects.GroupMilestone`
 - `gitlab.v4.objects.GroupMilestoneManager`
 - `gitlab.v4.objects.Group.milestones`
- GitLab API:
 - <https://docs.gitlab.com/ce/api/milestones.html>
 - https://docs.gitlab.com/ce/api/group_milestones.html

Examples

List the milestones for a project or a group:

```
p_milestones = project.milestones.list()
g_milestones = group.milestones.list()
```

You can filter the list using the following parameters:

- `iids`: unique IDs of milestones for the project
- `state`: either `active` or `closed`
- `search`: to search using a string

```
p_milestones = project.milestones.list(state='closed')
g_milestones = group.milestones.list(state='active')
```

Get a single milestone:

```
p_milestone = project.milestones.get(milestone_id)
g_milestone = group.milestones.get(milestone_id)
```

Create a milestone:

```
milestone = project.milestones.create({'title': '1.0'})
```

Edit a milestone:

```
milestone.description = 'v 1.0 release'
milestone.save()
```

Change the state of a milestone (activate / close):

```
# close a milestone
milestone.state_event = 'close'
milestone.save()

# activate a milestone
milestone.state_event = 'activate'
milestone.save()
```

Promote a project milestone:

```
milestone.promote()
```

List the issues related to a milestone:

```
issues = milestone.issues()
```

List the merge requests related to a milestone:

```
merge_requests = milestone.merge_requests()
```

Milestone events

Resource milestone events keep track of what happens to GitLab issues and merge requests.

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectIssueResourceMilestoneEvent*
 - *gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager*
 - *gitlab.v4.objects.ProjectIssue.resourcemilestoneevents*
 - *gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEvent*
 - *gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager*
 - *gitlab.v4.objects.ProjectMergeRequest.resourcemilestoneevents*
- GitLab API: https://docs.gitlab.com/ee/api/resource_milestone_events.html

Examples

Get milestones for a resource (issue, merge request):

```
milestones = resource.resourcemilestoneevents.list()
```

Get a specific milestone for a resource:

```
milestone = resource.resourcemilestoneevents.get(milestone_id)
```

6.4.30 Namespaces

Reference

- v4 API:
 - `gitlab.v4.objects.Namespace`
 - `gitlab.v4.objects.NamespaceManager`
 - `gitlab.Gitlab.namespaces`
- GitLab API: <https://docs.gitlab.com/ce/api/namespaces.html>

Examples

List namespaces:

```
namespaces = gl.namespaces.list()
```

Search namespaces:

```
namespaces = gl.namespaces.list(search='foo')
```

6.4.31 Notes

You can manipulate notes (comments) on group epics, project issues, merge requests and snippets.

Reference

- v4 API:
 - Epics:
 - `gitlab.v4.objects.GroupEpicNote`
 - `gitlab.v4.objects.GroupEpicNoteManager`
 - `gitlab.v4.objects.GroupEpic.notes`
 - Issues:
 - `gitlab.v4.objects.ProjectIssueNote`
 - `gitlab.v4.objects.ProjectIssueNoteManager`
 - `gitlab.v4.objects.ProjectIssue.notes`
 - MergeRequests:
 - `gitlab.v4.objects.ProjectMergeRequestNote`
 - `gitlab.v4.objects.ProjectMergeRequestNoteManager`
 - `gitlab.v4.objects.ProjectMergeRequest.notes`
 - Snippets:
 - `gitlab.v4.objects.ProjectSnippetNote`
 - `gitlab.v4.objects.ProjectSnippetNoteManager`

- `gitlab.v4.objects.ProjectSnippet.notes`

- GitLab API: <https://docs.gitlab.com/ce/api/notes.html>

Examples

List the notes for a resource:

```
e_notes = epic.notes.list()
i_notes = issue.notes.list()
mr_notes = mr.notes.list()
s_notes = snippet.notes.list()
```

Get a note for a resource:

```
e_note = epic.notes.get(note_id)
i_note = issue.notes.get(note_id)
mr_note = mr.notes.get(note_id)
s_note = snippet.notes.get(note_id)
```

Create a note for a resource:

```
e_note = epic.notes.create({'body': 'note content'})
i_note = issue.notes.create({'body': 'note content'})
mr_note = mr.notes.create({'body': 'note content'})
s_note = snippet.notes.create({'body': 'note content'})
```

Update a note for a resource:

```
note.body = 'updated note content'
note.save()
```

Delete a note for a resource:

```
note.delete()
```

6.4.32 Packages

Packages allow you to utilize GitLab as a private repository for a variety of common package managers, as well as GitLab's generic package registry.

Project Packages

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectPackage`
 - `gitlab.v4.objects.ProjectPackageManager`
 - `gitlab.v4.objects.Project.packages`
- GitLab API: <https://docs.gitlab.com/ee/api/packages.html#within-a-project>

Examples

List the packages in a project:

```
packages = project.packages.list()
```

Filter the results by `package_type` or `package_name`

```
packages = project.packages.list(package_type='pypi')
```

Get a specific package of a project by id:

```
package = project.packages.get(1)
```

Delete a package from a project:

```
package.delete()  
# or  
project.packages.delete(package.id)
```

Group Packages

Reference

- v4 API:
 - `gitlab.v4.objects.GroupPackage`
 - `gitlab.v4.objects.GroupPackageManager`
 - `gitlab.v4.objects.Group.packages`
- GitLab API: <https://docs.gitlab.com/ee/api/packages.html#within-a-group>

Examples

List the packages in a group:

```
packages = group.packages.list()
```

Filter the results by `package_type` or `package_name`

```
packages = group.packages.list(package_type='pypi')
```

Project Package Files

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectPackageFile`
 - `gitlab.v4.objects.ProjectPackageFileManager`
 - `gitlab.v4.objects.ProjectPackage.package_files`
- GitLab API: <https://docs.gitlab.com/ee/api/packages.html#list-package-files>

Examples

List package files for package in project:

```
package = project.packages.get(1)
package_files = package.package_files.list()
```

Delete a package file in a project:

```
package = project.packages.get(1)
file = package.package_files.list()[0]
file.delete()
```

Generic Packages

You can use python-gitlab to upload and download generic packages.

Reference

- v4 API:
 - `gitlab.v4.objects.GenericPackage`
 - `gitlab.v4.objects.GenericPackageManager`
 - `gitlab.v4.objects.Project.generic_packages`
- GitLab API: https://docs.gitlab.com/ee/user/packages/generic_packages

Examples

Upload a generic package to a project:

```
project = gl.projects.get(1, lazy=True)
package = project.generic_packages.upload(
    package_name="hello-world",
    package_version="v1.0.0",
    file_name="hello.tar.gz",
    path="/path/to/local/hello.tar.gz"
)
```

Download a project's generic package:

```
project = gl.projects.get(1, lazy=True)
package = project.generic_packages.download(
    package_name="hello-world",
    package_version="v1.0.0",
    file_name="hello.tar.gz",
)
```

Hint: You can use the Packages API described above to find packages and retrieve the metadata you need download them.

6.4.33 Pages domains

Admin

References

- v4 API:
 - *gitlab.v4.objects.PagesDomain*
 - *gitlab.v4.objects.PagesDomainManager*
 - *gitlab.Gitlab.pagesdomains*
- GitLab API: https://docs.gitlab.com/ce/api/pages_domains.html#list-all-pages-domains

Examples

List all the existing domains (admin only):

```
domains = gl.pagesdomains.list()
```

Project pages domain

References

- v4 API:
 - *gitlab.v4.objects.ProjectPagesDomain*
 - *gitlab.v4.objects.ProjectPagesDomainManager*
 - *gitlab.v4.objects.Project.pagesdomains*
- GitLab API: https://docs.gitlab.com/ce/api/pages_domains.html#list-pages-domains

Examples

List domains for a project:

```
domains = project.pagesdomains.list()
```

Get a single domain:

```
domain = project.pagesdomains.get('d1.example.com')
```

Create a new domain:

```
domain = project.pagesdomains.create({'domain': 'd2.example.com'})
```

Update an existing domain:

```
domain.certificate = open('d2.crt').read()
domain.key = open('d2.key').read()
domain.save()
```

Delete an existing domain:

```
domain.delete
# or
project.pagesdomains.delete('d2.example.com')
```

6.4.34 Personal Access Tokens

References

- v4 API:
 - `gitlab.v4.objects.PersonalAccessToken`
 - `gitlab.v4.objects.PersonalAccessTokenManager`
 - `gitlab.Gitlab.personal_access_tokens`
 - `gitlab.v4.objects.UserPersonalAccessToken`
 - `gitlab.v4.objects.UserPersonalAccessTokenManager`
 - `gitlab.Gitlab.User.personal_access_tokens`
- GitLab API:
 - https://docs.gitlab.com/ee/api/personal_access_tokens.html
 - <https://docs.gitlab.com/ee/api/users.html#create-a-personal-access-token>

Examples

List personal access tokens:

```
access_tokens = gl.personal_access_tokens.list()
print(access_tokens[0].name)
```

List personal access tokens from other user_id (admin only):

```
access_tokens = gl.personal_access_tokens.list(user_id=25)
```

Revoke a personal access token fetched via list:

```
access_token = access_tokens[0]
access_token.delete()
```

Revoke a personal access token by id:

```
gl.personal_access_tokens.delete(123)
```

Create a personal access token for a user (admin only):

```
user = gl.users.get(25, lazy=True)
access_token = user.personal_access_tokens.create({"name": "test", "scopes": "api"})
```

Note: As you can see above, you can only create personal access tokens via the Users API, but you cannot revoke these objects directly. This is because the create API uses a different endpoint than the list and revoke APIs. You need to fetch the token via the list API first to revoke it.

As of 14.2, GitLab does not provide a GET API for single personal access tokens. You must use the list method to retrieve single tokens.

6.4.35 Pipelines and Jobs

Project pipelines

A pipeline is a group of jobs executed by GitLab CI.

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectPipeline*
 - *gitlab.v4.objects.ProjectPipelineManager*
 - *gitlab.v4.objects.Project.pipelines*
- GitLab API: <https://docs.gitlab.com/ce/api/pipelines.html>

Examples

List pipelines for a project:

```
pipelines = project.pipelines.list()
```

Get a pipeline for a project:

```
pipeline = project.pipelines.get(pipeline_id)
```

Get variables of a pipeline:

```
variables = pipeline.variables.list()
```

Create a pipeline for a particular reference with custom variables:

```
pipeline = project.pipelines.create({'ref': 'main', 'variables': [{  
    ↪ 'key': 'MY_VARIABLE',  
    ↪ 'value': 'hello'}]})
```

Retry the failed builds for a pipeline:

```
pipeline.retry()
```

Cancel builds in a pipeline:

```
pipeline.cancel()
```

Delete a pipeline:

```
pipeline.delete()
```

Triggers

Triggers provide a way to interact with the GitLab CI. Using a trigger a user or an application can run a new build/job for a specific commit.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectTrigger`
 - `gitlab.v4.objects.ProjectTriggerManager`
 - `gitlab.v4.objects.Project.triggers`
- GitLab API: https://docs.gitlab.com/ce/api/pipeline_triggers.html

Examples

List triggers:

```
triggers = project.triggers.list()
```

Get a trigger:

```
trigger = project.triggers.get(trigger_token)
```

Create a trigger:

```
trigger = project.triggers.create({'description': 'mytrigger'})
```

Remove a trigger:

```
project.triggers.delete(trigger_token)
# or
trigger.delete()
```

Full example with wait for finish:

```
def get_or_create_trigger(project):
    trigger_description = 'my_trigger_id'
    for t in project.triggers.list():
        if t.description == trigger_description:
            return t
    return project.triggers.create({'description': trigger_description})

trigger = get_or_create_trigger(project)
pipeline = project.trigger_pipeline('main', trigger.token, variables={"DEPLOY_ZONE": "us-
↪west1"})
while pipeline.finished_at is None:
    pipeline.refresh()
    time.sleep(1)
```

You can trigger a pipeline using token authentication instead of user authentication. To do so create an anonymous Gitlab instance and use lazy objects to get the associated project:

```
gl = gitlab.Gitlab(URL) # no authentication
project = gl.projects.get(project_id, lazy=True) # no API call
project.trigger_pipeline('main', trigger_token)
```

Reference: <https://docs.gitlab.com/ee/ci/triggers/#trigger-token>

Pipeline schedule

You can schedule pipeline runs using a cron-like syntax. Variables can be associated with the scheduled pipelines.

Reference

- v4 API
 - `gitlab.v4.objects.ProjectPipelineSchedule`
 - `gitlab.v4.objects.ProjectPipelineScheduleManager`
 - `gitlab.v4.objects.Project.pipelineschedules`
 - `gitlab.v4.objects.ProjectPipelineScheduleVariable`
 - `gitlab.v4.objects.ProjectPipelineScheduleVariableManager`
 - `gitlab.v4.objects.Project.pipelineschedules`
- GitLab API: https://docs.gitlab.com/ce/api/pipeline_schedules.html

Examples

List pipeline schedules:

```
scheds = project.pipelineschedules.list()
```

Get a single schedule:

```
sched = projects.pipelineschedules.get(schedule_id)
```

Create a new schedule:

```
sched = project.pipelineschedules.create({
    'ref': 'main',
    'description': 'Daily test',
    'cron': '@ 1 * * *'})
```

Update a schedule:

```
sched.cron = '1 2 * * *'
sched.save()
```

Take ownership of a schedule:

```
sched.take_ownership()
```

Trigger a pipeline schedule immediately:

```
sched = projects.pipelineschedules.get(schedule_id)
sched.play()
```

Delete a schedule:

```
sched.delete()
```

List schedule variables:

```
# note: you need to use get() to retrieve the schedule variables. The
# attribute is not present in the response of a list() call
sched = projects.pipelineschedules.get(schedule_id)
vars = sched.attributes['variables']
```

Create a schedule variable:

```
var = sched.variables.create({'key': 'foo', 'value': 'bar'})
```

Edit a schedule variable:

```
var.value = 'new_value'
var.save()
```

Delete a schedule variable:

```
var.delete()
```

Jobs

Jobs are associated to projects, pipelines and commits. They provide information on the jobs that have been run, and methods to manipulate them.

Reference

- v4 API
 - `gitlab.v4.objects.ProjectJob`
 - `gitlab.v4.objects.ProjectJobManager`
 - `gitlab.v4.objects.Project.jobs`
- GitLab API: <https://docs.gitlab.com/ce/api/jobs.html>

Examples

Jobs are usually automatically triggered, but you can explicitly trigger a new job:

```
project.trigger_build('main', trigger_token,
                      {'extra_var1': 'foo', 'extra_var2': 'bar'})
```

List jobs for the project:

```
jobs = project.jobs.list()
```

Get a single job:

```
project.jobs.get(job_id)
```

List the jobs of a pipeline:

```
project = gl.projects.get(project_id)
pipeline = project.pipelines.get(pipeline_id)
jobs = pipeline.jobs.list()
```

Note: Job methods (play, cancel, and so on) are not available on ProjectPipelineJob objects. To use these methods create a ProjectJob object:

```
pipeline_job = pipeline.jobs.list()[0]
job = project.jobs.get(pipeline_job.id, lazy=True)
job.retry()
```

Get the artifacts of a job:

```
build_or_job.artifacts()
```

Get the artifacts of a job by its name from the latest successful pipeline of a branch or tag:

```
project.artifacts.download(ref_name='main', job='build')
```

Attention: An older method `project.artifacts()` is deprecated and will be removed in a future version.

Warning: Artifacts are entirely stored in memory in this example.

You can download artifacts as a stream. Provide a callable to handle the stream:

```
with open("archive.zip", "wb") as f:
    build_or_job.artifacts(streamed=True, action=f.write)
```

You can also directly stream the output into a file, and unzip it afterwards:

```
zipfn = "___artifacts.zip"
with open(zipfn, "wb") as f:
    build_or_job.artifacts(streamed=True, action=f.write)
subprocess.run(["unzip", "-bo", zipfn])
os.unlink(zipfn)
```

Delete all artifacts of a project that can be deleted:

```
project.artifacts.delete()
```

Get a single artifact file:

```
build_or_job.artifact('path/to/file')
```

Get a single artifact file by branch and job:

```
project.artifacts.raw('branch', 'path/to/file', 'job')
```

Attention: An older method `project.artifact()` is deprecated and will be removed in a future version.

Mark a job artifact as kept when expiration is set:

```
build_or_job.keep_artifacts()
```

Delete the artifacts of a job:

```
build_or_job.delete_artifacts()
```

Get a job trace:

```
build_or_job.trace()
```

Warning: Traces are entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Cancel/retry a job:

```
build_or_job.cancel()  
build_or_job.retry()
```

Play (trigger) a job:

```
build_or_job.play()
```

Erase a job (artifacts and trace):

```
build_or_job.erase()
```

Pipeline bridges

Get a list of bridge jobs (including child pipelines) for a pipeline.

Reference

- v4 API
 - `gitlab.v4.objects.ProjectPipelineBridge`
 - `gitlab.v4.objects.ProjectPipelineBridgeManager`
 - `gitlab.v4.objects.ProjectPipeline.bridges`
- GitLab API: <https://docs.gitlab.com/ee/api/jobs.html#list-pipeline-bridges>

Examples

List bridges for the pipeline:

```
bridges = pipeline.bridges.list()
```

Pipeline test report

Get a pipeline's complete test report.

Reference

- v4 API
 - *gitlab.v4.objects.ProjectPipelineTestReport*
 - *gitlab.v4.objects.ProjectPipelineTestReportManager*
 - *gitlab.v4.objects.ProjectPipeline.test_report*
- GitLab API: <https://docs.gitlab.com/ee/api/pipelines.html#get-a-pipelines-test-report>

Examples

Get the test report for a pipeline:

```
test_report = pipeline.test_report.get()
```

Pipeline test report summary

Get a pipeline's test report summary.

Reference

- v4 API
 - *gitlab.v4.objects.ProjectPipelineTestReportSummary*
 - *gitlab.v4.objects.ProjectPipelineTestReportSummaryManager*
 - *gitlab.v4.objects.ProjectPipeline.test_report_summary*
- GitLab API: <https://docs.gitlab.com/ee/api/pipelines.html#get-a-pipelines-test-report-summary>

Examples

Get the test report summary for a pipeline:

```
test_report_summary = pipeline.test_report_summary.get()
```

6.4.36 Projects

Projects

Reference

- v4 API:
 - `gitlab.v4.objects.Project`
 - `gitlab.v4.objects.ProjectManager`
 - `gitlab.Gitlab.projects`
- GitLab API: <https://docs.gitlab.com/ce/api/projects.html>

Examples

List projects:

```
projects = gl.projects.list()
```

The API provides several filtering parameters for the listing methods:

- `archived`: if `True` only archived projects will be returned
- `visibility`: returns only projects with the specified visibility (can be `public`, `internal` or `private`)
- `search`: returns project matching the given pattern

Results can also be sorted using the following parameters:

- `order_by`: sort using the given argument. Valid values are `id`, `name`, `path`, `created_at`, `updated_at` and `last_activity_at`. The default is to sort by `created_at`
- `sort`: sort order (`asc` or `desc`)

```
# List all projects (default 20)
projects = gl.projects.list(all=True)
# Archived projects
projects = gl.projects.list(archived=1)
# Limit to projects with a defined visibility
projects = gl.projects.list(visibility='public')

# List owned projects
projects = gl.projects.list(owned=True)

# List starred projects
projects = gl.projects.list(starred=True)
```

(continues on next page)

(continued from previous page)

```
# Search projects
projects = gl.projects.list(search='keyword')
```

Note: To list the starred projects of another user, see the *Users API docs*.

Note: Fetching a list of projects, doesn't include all attributes of all projects. To retrieve all attributes, you'll need to fetch a single project

Get a single project:

```
# Get a project by ID
project_id = 851
project = gl.projects.get(project_id)

# Get a project by name with namespace
project_name_with_namespace = "namespace/project_name"
project = gl.projects.get(project_name_with_namespace)
```

Create a project:

```
project = gl.projects.create({'name': 'project1'})
```

Create a project for a user (admin only):

```
alice = gl.users.list(username='alice')[0]
user_project = alice.projects.create({'name': 'project'})
user_projects = alice.projects.list()
```

Create a project in a group:

```
# You need to get the id of the group, then use the namespace_id attribute
# to create the group
group_id = gl.groups.list(search='my-group')[0].id
project = gl.projects.create({'name': 'myrepo', 'namespace_id': group_id})
```

List a project's groups:

```
# Get a list of ancestor/parent groups for a project.
groups = project.groups.list()
```

Update a project:

```
project.snippets_enabled = 1
project.save()
```

Set the avatar image for a project:

```
# the avatar image can be passed as data (content of the file) or as a file
# object opened in binary mode
```

(continues on next page)

(continued from previous page)

```
project.avatar = open('path/to/file.png', 'rb')
project.save()
```

Delete a project:

```
gl.projects.delete(project_id)
# or
project.delete()
```

Fork a project:

```
fork = project.forks.create({})

# fork to a specific namespace
fork = project.forks.create({'namespace': 'myteam'})
```

Get a list of forks for the project:

```
forks = project.forks.list()
```

Create/delete a fork relation between projects (requires admin permissions):

```
project.create_fork_relation(source_project.id)
project.delete_fork_relation()
```

Get languages used in the project with percentage value:

```
languages = project.languages()
```

Star/unstar a project:

```
project.star()
project.unstar()
```

Archive/unarchive a project:

```
project.archive()
project.unarchive()
```

Start the housekeeping job:

```
project.housekeeping()
```

List the repository tree:

```
# list the content of the root directory for the default branch
items = project.repository_tree()

# list the content of a subdirectory on a specific branch
items = project.repository_tree(path='docs', ref='branch1')
```

Get the content and metadata of a file for a commit, using a blob sha:

```
items = project.repository_tree(path='docs', ref='branch1')
file_info = p.repository_blob(items[0]['id'])
content = base64.b64decode(file_info['content'])
size = file_info['size']
```

Update a project submodule:

```
items = project.update_submodule(
    submodule="foo/bar",
    branch="main",
    commit_sha="4c3674f66071e30b3311dac9b9ccc90502a72664",
    commit_message="Message", # optional
)
```

Get the repository archive:

```
tgz = project.repository_archive()

# get the archive for a branch/tag/commit
tgz = project.repository_archive(sha='4567abc')

# get the archive in a different format
zip = project.repository_archive(format='zip')
```

Note: For the formats available, refer to <https://docs.gitlab.com/ce/api/repositories.html#get-file-archive>

Warning: Archives are entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Get the content of a file using the blob id:

```
# find the id for the blob (simple search)
id = [d['id'] for d in p.repository_tree() if d['name'] == 'README.rst'][0]

# get the content
file_content = p.repository_raw_blob(id)
```

Warning: Blobs are entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Get a snapshot of the repository:

```
tar_file = project.snapshot()
```

Warning: Snapshots are entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Compare two branches, tags or commits:

```
result = project.repository_compare('main', 'branch1')

# get the commits
for commit in result['commits']:
    print(commit)

# get the diffs
for file_diff in result['diffs']:
    print(file_diff)
```

Get a list of contributors for the repository:

```
contributors = project.repository_contributors()
```

Get a list of users for the repository:

```
users = p.users.list()

# search for users
users = p.users.list(search='pattern')
```

Start the pull mirroring process (EE edition):

```
project.mirror_pull()
```

Import / Export

You can export projects from gitlab, and re-import them to create new projects or overwrite existing ones.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectExport`
 - `gitlab.v4.objects.ProjectExportManager`
 - `gitlab.v4.objects.Project.exports`
 - `gitlab.v4.objects.ProjectImport`
 - `gitlab.v4.objects.ProjectImportManager`
 - `gitlab.v4.objects.Project.imports`
 - `gitlab.v4.objects.ProjectManager.import_project`
- GitLab API: https://docs.gitlab.com/ce/api/project_import_export.html

Examples

A project export is an asynchronous operation. To retrieve the archive generated by GitLab you need to:

1. Create an export using the API
2. Wait for the export to be done
3. Download the result

```
# Create the export
p = gl.projects.get(my_project)
export = p.exports.create()

# Wait for the 'finished' status
export.refresh()
while export.export_status != 'finished':
    time.sleep(1)
    export.refresh()

# Download the result
with open('/tmp/export.tgz', 'wb') as f:
    export.download(streamed=True, action=f.write)
```

Import the project:

```
output = gl.projects.import_project(open('/tmp/export.tgz', 'rb'), 'my_new_project')
# Get a ProjectImport object to track the import status
project_import = gl.projects.get(output['id'], lazy=True).imports.get()
while project_import.import_status != 'finished':
    time.sleep(1)
    project_import.refresh()
```

Project custom attributes

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCustomAttribute`
 - `gitlab.v4.objects.ProjectCustomAttributeManager`
 - `gitlab.v4.objects.Project.customattributes`
- GitLab API: https://docs.gitlab.com/ce/api/custom_attributes.html

Examples

List custom attributes for a project:

```
attrs = project.customattributes.list()
```

Get a custom attribute for a project:

```
attr = project.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a project:

```
attr = project.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a project:

```
attr.delete()  
# or  
project.customattributes.delete(attr_key)
```

Search projects by custom attribute:

```
project.customattributes.set('type', 'internal')  
gl.projects.list(custom_attributes={'type': 'internal'})
```

Project files

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectFile`
 - `gitlab.v4.objects.ProjectFileManager`
 - `gitlab.v4.objects.Project.files`
- GitLab API: https://docs.gitlab.com/ce/api/repository_files.html

Examples

Get a file:

```
f = project.files.get(file_path='README.rst', ref='main')  
  
# get the base64 encoded content  
print(f.content)  
  
# get the decoded content  
print(f.decode())
```

Get a raw file:

```
raw_content = project.files.raw(file_path='README.rst', ref='main')
print(raw_content)
with open('/tmp/raw-download.txt', 'wb') as f:
    project.files.raw(file_path='README.rst', ref='main', streamed=True, action=f.write)
```

Create a new file:

```
f = project.files.create({'file_path': 'testfile.txt',
                          'branch': 'main',
                          'content': file_content,
                          'author_email': 'test@example.com',
                          'author_name': 'yourname',
                          'commit_message': 'Create testfile'})
```

Update a file. The entire content must be uploaded, as plain text or as base64 encoded text:

```
f.content = 'new content'
f.save(branch='main', commit_message='Update testfile')

# or for binary data
# Note: decode() is required with python 3 for data serialization. You can omit
# it with python 2
f.content = base64.b64encode(open('image.png').read()).decode()
f.save(branch='main', commit_message='Update testfile', encoding='base64')
```

Delete a file:

```
f.delete(commit_message='Delete testfile', branch='main')
# or
project.files.delete(file_path='testfile.txt', commit_message='Delete testfile', branch=
↳ 'main')
```

Get file blame:

```
b = project.files.blame(file_path='README.rst', ref='main')
```

Project tags

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectTag`
 - `gitlab.v4.objects.ProjectTagManager`
 - `gitlab.v4.objects.Project.tags`
- GitLab API: <https://docs.gitlab.com/ce/api/tags.html>

Examples

List the project tags:

```
tags = project.tags.list()
```

Get a tag:

```
tag = project.tags.get('1.0')
```

Create a tag:

```
tag = project.tags.create({'tag_name': '1.0', 'ref': 'main'})
```

Delete a tag:

```
project.tags.delete('1.0')  
# or  
tag.delete()
```

Project snippets

The snippet visibility can be defined using the following constants:

- `gitlab.const.VISIBILITY_PRIVATE`
- `gitlab.const.VISIBILITY_INTERNAL`
- `gitlab.const.VISIBILITY_PUBLIC`

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectSnippet`
 - `gitlab.v4.objects.ProjectSnippetManager`
 - `gitlab.v4.objects.Project.files`
- GitLab API: https://docs.gitlab.com/ce/api/project_snippets.html

Examples

List the project snippets:

```
snippets = project.snippets.list()
```

Get a snippet:

```
snippet = project.snippets.get(snippet_id)
```

Get the content of a snippet:

```
print(snippet.content())
```

Warning: The snippet content is entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Create a snippet:

```
snippet = project.snippets.create({'title': 'sample 1',
                                   'file_name': 'foo.py',
                                   'code': 'import gitlab',
                                   'visibility_level':
                                       gitlab.const.VISIBILITY_PRIVATE})
```

Update a snippet:

```
snippet.code = 'import gitlab\nimport whatever'
snippet.save
```

Delete a snippet:

```
project.snippets.delete(snippet_id)
# or
snippet.delete()
```

Get user agent detail (admin only):

```
detail = snippet.user_agent_detail()
```

Notes

See *Notes*.

Project members

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectMember*
 - *gitlab.v4.objects.ProjectMemberManager*
 - *gitlab.v4.objects.ProjectMemberAllManager*
 - *gitlab.v4.objects.Project.members*
 - *gitlab.v4.objects.Project.members_all*
- GitLab API: <https://docs.gitlab.com/ce/api/members.html>

Examples

List only direct project members:

```
members = project.members.list()
```

List the project members recursively (including inherited members through ancestor groups):

```
members = project.members_all.list(all=True)
```

Search project members matching a query string:

```
members = project.members.list(query='bar')
```

Get only direct project member:

```
member = project.members.get(user_id)
```

Get a member of a project, including members inherited through ancestor groups:

```
members = project.members_all.get(member_id)
```

Add a project member:

```
member = project.members.create({'user_id': user.id, 'access_level':  
                                gitlab.const.DEVELOPER_ACCESS})
```

Modify a project member (change the access level):

```
member.access_level = gitlab.const.MAINTAINER_ACCESS  
member.save()
```

Remove a member from the project team:

```
project.members.delete(user.id)  
# or  
member.delete()
```

Share/unshare the project with a group:

```
project.share(group.id, gitlab.const.DEVELOPER_ACCESS)  
project.unshare(group.id)
```

Project hooks

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectHook*
 - *gitlab.v4.objects.ProjectHookManager*
 - *gitlab.v4.objects.Project.hooks*
- GitLab API: <https://docs.gitlab.com/ce/api/projects.html#hooks>

Examples

List the project hooks:

```
hooks = project.hooks.list()
```

Get a project hook:

```
hook = project.hooks.get(hook_id)
```

Create a project hook:

```
hook = project.hooks.create({'url': 'http://my/action/url', 'push_events': 1})
```

Update a project hook:

```
hook.push_events = 0
hook.save()
```

Delete a project hook:

```
project.hooks.delete(hook_id)
# or
hook.delete()
```

Project Services

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectService`
 - `gitlab.v4.objects.ProjectServiceManager`
 - `gitlab.v4.objects.Project.services`
- GitLab API: <https://docs.gitlab.com/ce/api/services.html>

Examples

Get a service:

```
service = project.services.get('asana')
# display its status (enabled/disabled)
print(service.active)
```

List active project services:

```
service = project.services.list()
```

List the code names of available services (doesn't return objects):

```
services = project.services.available()
```

Configure and enable a service:

```
service.api_key = 'randomkey'  
service.save()
```

Disable a service:

```
service.delete()
```

File uploads

Reference

- v4 API:
 - *gitlab.v4.objects.Project.upload*
- Gitlab API: <https://docs.gitlab.com/ce/api/projects.html#upload-a-file>

Examples

Upload a file into a project using a filesystem path:

```
project.upload("filename.txt", filepath="/some/path/filename.txt")
```

Upload a file into a project without a filesystem path:

```
project.upload("filename.txt", filedata="Raw data")
```

Upload a file and comment on an issue using the uploaded file's markdown:

```
uploaded_file = project.upload("filename.txt", filedata="data")  
issue = project.issues.get(issue_id)  
issue.notes.create({  
    "body": "See the attached file: {}".format(uploaded_file["markdown"])  
})
```

Upload a file and comment on an issue while using custom markdown to reference the uploaded file:

```
uploaded_file = project.upload("filename.txt", filedata="data")  
issue = project.issues.get(issue_id)  
issue.notes.create({  
    "body": "See the [attached file]({})".format(uploaded_file["url"])  
})
```

Project push rules

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectPushRules`
 - `gitlab.v4.objects.ProjectPushRulesManager`
 - `gitlab.v4.objects.Project.pushrules`
- GitLab API: <https://docs.gitlab.com/ee/api/projects.html#push-rules>

Examples

Create project push rules (at least one rule is necessary):

```
project.pushrules.create({'deny_delete_tag': True})
```

Get project push rules (returns None if there are no push rules):

```
pr = project.pushrules.get()
```

Edit project push rules:

```
pr.branch_name_regex = '^ (main|develop|support-\d+|release-\d+\.|hotfix-.\+|feature-.\+)$'
pr.save()
```

Delete project push rules:

```
pr.delete()
```

Project protected tags

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectProtectedTag`
 - `gitlab.v4.objects.ProjectProtectedTagManager`
 - `gitlab.v4.objects.Project.protectedtags`
- GitLab API: https://docs.gitlab.com/ce/api/protected_tags.html

Examples

Get a list of protected tags from a project:

```
protected_tags = project.protectedtags.list()
```

Get a single protected tag or wildcard protected tag:

```
protected_tag = project.protectedtags.get('v*')
```

Protect a single repository tag or several project repository tags using a wildcard protected tag:

```
project.protectedtags.create({'name': 'v*', 'create_access_level': '40'})
```

Unprotect the given protected tag or wildcard protected tag.:

```
protected_tag.delete()
```

Additional project statistics

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectAdditionalStatistics*
 - *gitlab.v4.objects.ProjectAdditionalStatisticsManager*
 - *gitlab.v4.objects.Project.additionalstatistics*
- GitLab API: https://docs.gitlab.com/ce/api/project_statistics.html

Examples

Get all additional statistics of a project:

```
statistics = project.additionalstatistics.get()
```

Get total fetches in last 30 days of a project:

```
total_fetches = project.additionalstatistics.get().fetches['total']
```

Project storage

This endpoint requires admin access.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectStorage`
 - `gitlab.v4.objects.ProjectStorageManager`
 - `gitlab.v4.objects.Project.storage`
- GitLab API: <https://docs.gitlab.com/ee/api/projects.html#get-the-path-to-repository-storage>

Examples

Get the repository storage details for a project:

```
storage = project.storage.get()
```

Get the repository storage disk path:

```
disk_path = project.storage.get().disk_path
```

6.4.37 Project Access Tokens

Get a list of project access tokens

References

- v4 API:
 - `gitlab.v4.objects.ProjectAccessToken`
 - `gitlab.v4.objects.ProjectAccessTokenManager`
 - `gitlab.Gitlab.project_access_tokens`
- GitLab API: https://docs.gitlab.com/ee/api/project_access_tokens.html

Examples

List project access tokens:

```
access_tokens = gl.projects.get(1, lazy=True).access_tokens.list()
print(access_tokens[0].name)
```

Create project access token:

```
access_token = gl.projects.get(1).access_tokens.create({"name": "test", "scopes": ["api", "read_repository"]})
```

Revoke a project access tokens:

```
gl.projects.get(1).access_tokens.delete(42)
# or
access_token.delete()
```

6.4.38 Protected branches

You can define a list of protected branch names on a repository. Names can use wildcards (*).

References

- v4 API:
 - `gitlab.v4.objects.ProjectProtectedBranch`
 - `gitlab.v4.objects.ProjectProtectedBranchManager`
 - `gitlab.v4.objects.Project.protectedbranches`
- GitLab API: https://docs.gitlab.com/ce/api/protected_branches.html#protected-branches-api

Examples

Get the list of protected branches for a project:

```
p_branches = project.protectedbranches.list()
```

Get a single protected branch:

```
p_branch = project.protectedbranches.get('main')
```

Create a protected branch:

```
p_branch = project.protectedbranches.create({
    'name': '*-stable',
    'merge_access_level': gitlab.const.DEVELOPER_ACCESS,
    'push_access_level': gitlab.const.MAINTAINER_ACCESS
})
```

Create a protected branch with more granular access control:

```
p_branch = project.protectedbranches.create({
    'name': '*-stable',
    'allowed_to_push': [{"user_id": 99}, {"user_id": 98}],
    'allowed_to_merge': [{"group_id": 653}],
    'allowed_to_unprotect': [{"access_level": gitlab.const.MAINTAINER_ACCESS}]
})
```

Delete a protected branch:

```
project.protectedbranches.delete('*-stable')
# or
p_branch.delete()
```

6.4.39 Releases

Project releases

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectRelease`
 - `gitlab.v4.objects.ProjectReleaseManager`
 - `gitlab.v4.objects.Project.releases`
- Gitlab API: <https://docs.gitlab.com/ee/api/releases/index.html>

Examples

Get a list of releases from a project:

```
project = gl.projects.get(project_id, lazy=True)
release = project.releases.list()
```

Get a single release:

```
release = project.releases.get('v1.2.3')
```

Edit a release:

```
release.name = "Demo Release"
release.description = "release notes go here"
release.save()
```

Create a release for a project tag:

```
release = project.releases.create({'name': 'Demo Release', 'tag_name': 'v1.2.3',
↪ 'description': 'release notes go here'})
```

Delete a release:

```
# via its tag name from project attributes
release = project.releases.delete('v1.2.3')

# delete object directly
release.delete()
```

Note: The Releases API is one of the few working with `CI_JOB_TOKEN`, but the project can't be fetched with the token. Thus use *lazy* for the project as in the above example.

Also be aware that most of the capabilities of the endpoint were not accessible with `CI_JOB_TOKEN` until Gitlab version 14.5.

Project release links

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectReleaseLink`
 - `gitlab.v4.objects.ProjectReleaseLinkManager`
 - `gitlab.v4.objects.ProjectRelease.links`
- Gitlab API: <https://docs.gitlab.com/ee/api/releases/links.html>

Examples

Get a list of releases from a project:

```
links = release.links.list()
```

Get a single release link:

```
link = release.links.get(1)
```

Create a release link for a release:

```
link = release.links.create({"url": "https://example.com/asset", "name": "asset"})
```

Delete a release link:

```
# via its ID from release attributes
release.links.delete(1)

# delete object directly
link.delete()
```

6.4.40 Runners

Runners are external processes used to run CI jobs. They are deployed by the administrator and registered to the GitLab instance.

Shared runners are available for all projects. Specific runners are enabled for a list of projects.

Global runners (admin)

Reference

- v4 API:
 - `gitlab.v4.objects.Runner`
 - `gitlab.v4.objects.RunnerManager`
 - `gitlab.Gitlab.runners`
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

Examples

Use the `list()` and `all()` methods to list runners.

Both methods accept a `scope` parameter to filter the list. Allowed values for this parameter are:

- `active`
- `paused`
- `online`
- `specific` (`all()` only)
- `shared` (`all()` only)

Note: The returned objects hold minimal information about the runners. Use the `get()` method to retrieve detail about a runner.

```
# List owned runners
runners = gl.runners.list()
# With a filter
runners = gl.runners.list(scope='active')
# List all runners, using a filter
runners = gl.runners.all(scope='paused')
```

Get a runner's detail:

```
runner = gl.runners.get(runner_id)
```

Register a new runner:

```
runner = gl.runners.create({'token': secret_token})
```

Update a runner:

```
runner = gl.runners.get(runner_id)
runner.tag_list.append('new_tag')
runner.save()
```

Remove a runner:

```
gl.runners.delete(runner_id)
# or
runner.delete()
```

Remove a runner by its authentication token:

```
gl.runners.delete(token="runner-auth-token")
```

Verify a registered runner token:

```
try:
    gl.runners.verify(runner_token)
    print("Valid token")
```

(continues on next page)

(continued from previous page)

```
except GitlabVerifyError:
    print("Invalid token")
```

Project/Group runners

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectRunner*
 - *gitlab.v4.objects.ProjectRunnerManager*
 - *gitlab.v4.objects.Project.runners*
 - *gitlab.v4.objects.GroupRunner*
 - *gitlab.v4.objects.GroupRunnerManager*
 - *gitlab.v4.objects.Group.runners*
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

Examples

List the runners for a project:

```
runners = project.runners.list()
```

Enable a specific runner for a project:

```
p_runner = project.runners.create({'runner_id': runner.id})
```

Disable a specific runner for a project:

```
project.runners.delete(runner.id)
```

Runner jobs

Reference

- v4 API:
 - *gitlab.v4.objects.RunnerJob*
 - *gitlab.v4.objects.RunnerJobManager*
 - *gitlab.v4.objects.Runner.jobs*
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

Examples

List for jobs for a runner:

```
jobs = runner.jobs.list()
```

Filter the list using the jobs status:

```
# status can be 'running', 'success', 'failed' or 'canceled'
active_jobs = runner.jobs.list(status='running')
```

6.4.41 Project Remote Mirrors

Remote Mirrors allow you to set up push mirroring for a project.

References

- v4 API:
 - `gitlab.v4.objects.ProjectRemoteMirror`
 - `gitlab.v4.objects.ProjectRemoteMirrorManager`
 - `gitlab.v4.objects.Project.remote_mirrors`
- GitLab API: https://docs.gitlab.com/ce/api/remote_mirrors.html

Examples

Get the list of a project's remote mirrors:

```
mirrors = project.remote_mirrors.list()
```

Create (and enable) a remote mirror for a project:

```
mirror = project.remote_mirrors.create({'url': 'https://gitlab.com/example.git',
                                         'enabled': True})
```

Update an existing remote mirror's attributes:

```
mirror.enabled = False
mirror.only_protected_branches = True
mirror.save()
```

6.4.42 Registry Repositories

References

- v4 API:
 - `gitlab.v4.objects.ProjectRegistryRepository`
 - `gitlab.v4.objects.ProjectRegistryRepositoryManager`
 - `gitlab.v4.objects.Project.repositories`
- Gitlab API: https://docs.gitlab.com/ce/api/container_registry.html

Examples

Get the list of container registry repositories associated with the project:

```
repositories = project.repositories.list()
```

Delete repository:

```
project.repositories.delete(id=x)
# or
repository = repositories.pop()
repository.delete()
```

6.4.43 Registry Repository Tags

References

- v4 API:
 - `gitlab.v4.objects.ProjectRegistryTag`
 - `gitlab.v4.objects.ProjectRegistryTagManager`
 - `gitlab.v4.objects.Repository.tags`
- Gitlab API: https://docs.gitlab.com/ce/api/container_registry.html

Examples

Get the list of repository tags in given registry:

```
repositories = project.repositories.list()
repository = repositories.pop()
tags = repository.tags.list()
```

Get specific tag:

```
repository.tags.get(id=tag_name)
```

Delete tag:

```
repository.tags.delete(id=tag_name)
# or
tag = repository.tags.get(id=tag_name)
tag.delete()
```

Delete tag in bulk:

```
repository.tags.delete_in_bulk(keep_n=1)
# or
repository.tags.delete_in_bulk(older_than="1m")
# or
repository.tags.delete_in_bulk(name_regex="v.+ ", keep_n=2)
```

Note: Delete in bulk is asynchronous operation and may take a while. Refer to: https://docs.gitlab.com/ce/api/container_registry.html#delete-repository-tags-in-bulk

6.4.44 Search API

You can search for resources at the top level, in a project or in a group. Searches are based on a scope (issues, merge requests, and so on) and a search string. The following constants are provided to represent the possible scopes:

- Shared scopes (global, group and project):
 - `gitlab.const.SEARCH_SCOPE_PROJECTS`: projects
 - `gitlab.const.SEARCH_SCOPE_ISSUES`: issues
 - `gitlab.const.SEARCH_SCOPE_MERGE_REQUESTS`: merge_requests
 - `gitlab.const.SEARCH_SCOPE_MILESTONES`: milestones
 - `gitlab.const.SEARCH_SCOPE_WIKI_BLOBS`: wiki_blobs
 - `gitlab.const.SEARCH_SCOPE_COMMITS`: commits
 - `gitlab.const.SEARCH_SCOPE_BLOBS`: blobs
 - `gitlab.const.SEARCH_SCOPE_USERS`: users
- specific global scope:
 - `gitlab.const.SEARCH_SCOPE_GLOBAL_SNIPPET_TITLES`: snippet_titles
- specific project scope:
 - `gitlab.const.SEARCH_SCOPE_PROJECT_NOTES`: notes

Reference

- v4 API:
 - `gitlab.Gitlab.search`
 - `gitlab.v4.objects.Group.search`
 - `gitlab.v4.objects.Project.search`
- GitLab API: <https://docs.gitlab.com/ce/api/search.html>

Examples

Search for issues matching a specific string:

```
# global search
gl.search(gitlab.const.SEARCH_SCOPE_ISSUES, 'regression')

# group search
group = gl.groups.get('mygroup')
group.search(gitlab.const.SEARCH_SCOPE_ISSUES, 'regression')

# project search
project = gl.projects.get('myproject')
project.search(gitlab.const.SEARCH_SCOPE_ISSUES, 'regression')
```

The `search()` methods implement the pagination support:

```
# get lists of 10 items, and start at page 2
gl.search(gitlab.const.SEARCH_SCOPE_ISSUES, search_str, page=2, per_page=10)

# get a generator that will automatically make required API calls for
# pagination
for item in gl.search(gitlab.const.SEARCH_SCOPE_ISSUES, search_str, as_list=False):
    do_something(item)
```

The search API doesn't return objects, but dicts. If you need to act on objects, you need to create them explicitly:

```
for item in gl.search(gitlab.const.SEARCH_SCOPE_ISSUES, search_str, as_list=False):
    issue_project = gl.projects.get(item['project_id'], lazy=True)
    issue = issue_project.issues.get(item['iid'])
    issue.state = 'closed'
    issue.save()
```

6.4.45 Settings

Reference

- v4 API:
 - `gitlab.v4.objects.ApplicationSettings`
 - `gitlab.v4.objects.ApplicationSettingsManager`
 - `gitlab.Gitlab.settings`

- GitLab API: <https://docs.gitlab.com/ce/api/settings.html>

Examples

Get the settings:

```
settings = gl.settings.get()
```

Update the settings:

```
settings.signin_enabled = False
settings.save()
```

6.4.46 Snippets

Reference

- v4 API:
 - `gitlab.v4.objects.Snippet`
 - `gitlab.v4.objects.SnippetManager`
 - `gitlab.Gitlab.snippets`
- GitLab API: <https://docs.gitlab.com/ce/api/snippets.html>

Examples

List snippets owned by the current user:

```
snippets = gl.snippets.list()
```

List the public snippets:

```
public_snippets = gl.snippets.public()
```

Get a snippet:

```
snippet = gl.snippets.get(snippet_id)
# get the content
content = snippet.content()
```

Warning: Blobs are entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Create a snippet:

```
snippet = gl.snippets.create({'title': 'snippet1',
                              'file_name': 'snippet1.py',
                              'content': open('snippet1.py').read()})
```

Update the snippet attributes:

```
snippet.visibility_level = gitlab.const.VISIBILITY_PUBLIC
snippet.save()
```

To update a snippet code you need to create a `ProjectSnippet` object:

```
snippet = gl.snippets.get(snippet_id)
project = gl.projects.get(snippet.project_id, lazy=True)
editable_snippet = project.snippets.get(snippet.id)
editable_snippet.code = new_snippet_content
editable_snippet.save()
```

Delete a snippet:

```
gl.snippets.delete(snippet_id)
# or
snippet.delete()
```

Get user agent detail (admin only):

```
detail = snippet.user_agent_detail()
```

6.4.47 System hooks

Reference

- v4 API:
 - `gitlab.v4.objects.Hook`
 - `gitlab.v4.objects.HookManager`
 - `gitlab.Gitlab.hooks`
- GitLab API: https://docs.gitlab.com/ce/api/system_hooks.html

Examples

List the system hooks:

```
hooks = gl.hooks.list()
```

Create a system hook:

```
gl.hooks.get(hook_id)
```

Test a system hook. The returned object is not usable (it misses the hook ID):

```
hook = gl.hooks.create({'url': 'http://your.target.url'})
```

Delete a system hook:

```
gl.hooks.delete(hook_id)
# or
hook.delete()
```

6.4.48 Templates

You can request templates for different type of files:

- License files
- .gitignore files
- GitLab CI configuration files
- Dockerfiles

License templates

Reference

- v4 API:
 - `gitlab.v4.objects.License`
 - `gitlab.v4.objects.LicenseManager`
 - `gitlab.Gitlab.licenses`
- GitLab API: <https://docs.gitlab.com/ce/api/templates/licenses.html>

Examples

List known license templates:

```
licenses = gl.licenses.list()
```

Generate a license content for a project:

```
license = gl.licenses.get('apache-2.0', project='foobar', fullname='John Doe')
print(license.content)
```

.gitignore templates

Reference

- v4 API:
 - `gitlab.v4.objects.Gitignore`
 - `gitlab.v4.objects.GitignoreManager`
 - `gitlab.Gitlab.gitignores`
- GitLab API: <https://docs.gitlab.com/ce/api/templates/gitignores.html>

Examples

List known gitignore templates:

```
gitignores = gl.gitignores.list()
```

Get a gitignore template:

```
gitignore = gl.gitignores.get('Python')
print(gitignore.content)
```

GitLab CI templates

Reference

- v4 API:
 - *gitlab.v4.objects.Gitlabciyaml*
 - *gitlab.v4.objects.GitlabciyamlManager*
 - *gitlab.Gitlab.gitlabciyaml*s
- GitLab API: https://docs.gitlab.com/ce/api/templates/gitlab_ci_ymls.html

Examples

List known GitLab CI templates:

```
gitlabciyaml = gl.gitlabciyaml.list()
```

Get a GitLab CI template:

```
gitlabciyaml = gl.gitlabciyaml.get('Pelican')
print(gitlabciyaml.content)
```

Dockerfile templates

Reference

- v4 API:
 - *gitlab.v4.objects.Dockerfile*
 - *gitlab.v4.objects.DockerfileManager*
 - *gitlab.Gitlab.gitlabciyaml*s
- GitLab API: Not documented.

Examples

List known Dockerfile templates:

```
dockerfiles = gl.dockerfiles.list()
```

Get a Dockerfile template:

```
dockerfile = gl.dockerfiles.get('Python')
print(dockerfile.content)
```

6.4.49 Todos

Reference

- v4 API:
 - Todo
 - TodoManager
 - *gitlab.Gitlab.todos*
- GitLab API: <https://docs.gitlab.com/ce/api/todos.html>

Examples

List active todos:

```
todos = gl.todos.list()
```

You can filter the list using the following parameters:

- **action**: can be assigned, mentioned, build_failed, marked, or approval_required
- **author_id**
- **project_id**
- **state**: can be pending or done
- **type**: can be Issue or MergeRequest

For example:

```
todos = gl.todos.list(project_id=1)
todos = gl.todos.list(state='done', type='Issue')
```

Mark a todo as done:

```
todos = gl.todos.list(project_id=1)
todos[0].mark_as_done()
```

Mark all the todos as done:

```
gl.todos.mark_all_as_done()
```

6.4.50 Topics

Topics can be used to categorize projects and find similar new projects.

Reference

- v4 API:
 - `gitlab.v4.objects.Topic`
 - `gitlab.v4.objects.TopicManager`
 - `gitlab.Gitlab.topics`
- GitLab API: <https://docs.gitlab.com/ce/api/topics.html>

This endpoint requires admin access for creating, updating and deleting objects.

Examples

List project topics on the GitLab instance:

```
topics = gl.topics.list()
```

Get a specific topic by its ID:

```
topic = gl.topics.get(topic_id)
```

Create a new topic:

```
topic = gl.topics.create({"name": "my-topic"})
```

Update a topic:

```
topic.description = "My new topic"
topic.save()

# or
gl.topics.update(topic_id, {"description": "My new topic"})
```

Delete a topic:

```
topic.delete()

# or
gl.topics.delete(topic_id)
```

6.4.51 Users and current user

The Gitlab API exposes user-related method that can be manipulated by admins only.

The currently logged-in user is also exposed.

Users

References

- v4 API:
 - `gitlab.v4.objects.User`
 - `gitlab.v4.objects.UserManager`
 - `gitlab.Gitlab.users`
- GitLab API:
 - <https://docs.gitlab.com/ce/api/users.html>
 - <https://docs.gitlab.com/ee/api/projects.html#list-projects-starred-by-a-user>

Examples

Get the list of users:

```
users = gl.users.list()
```

Search users whose username match a given string:

```
users = gl.users.list(search='foo')
```

Get a single user:

```
# by ID
user = gl.users.get(user_id)
# by username
user = gl.users.list(username='root')[0]
```

Create a user:

```
user = gl.users.create({'email': 'john@doe.com',
                        'password': 's3cur3s3cr3T',
                        'username': 'jdoe',
                        'name': 'John Doe'})
```

Update a user:

```
user.name = 'Real Name'
user.save()
```

Delete a user:

```
gl.users.delete(user_id)
# or
user.delete()
```

Block/Unblock a user:

```
user.block()
user.unblock()
```

Activate/Deactivate a user:

```
user.activate()
user.deactivate()
```

Follow/Unfollow a user:

```
user.follow()
user.unfollow()
```

Set the avatar image for a user:

```
# the avatar image can be passed as data (content of the file) or as a file
# object opened in binary mode
user.avatar = open('path/to/file.png', 'rb')
user.save()
```

Set an external identity for a user:

```
user.provider = 'oauth2_generic'
user.extern_uid = '3'
user.save()
```

Delete an external identity by provider name:

```
user.identityproviders.delete('oauth2_generic')
```

Get the followers of a user

```
user.followers_users.list()
```

Get the followings of a user

```
user.following_users.list()
```

List a user's starred projects

```
user.starred_projects.list()
```

User custom attributes

References

- v4 API:
 - `gitlab.v4.objects.UserCustomAttribute`
 - `gitlab.v4.objects.UserCustomAttributeManager`
 - `gitlab.v4.objects.User.customattributes`
- GitLab API: https://docs.gitlab.com/ce/api/custom_attributes.html

Examples

List custom attributes for a user:

```
attrs = user.customattributes.list()
```

Get a custom attribute for a user:

```
attr = user.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a user:

```
attr = user.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a user:

```
attr.delete()
# or
user.customattributes.delete(attr_key)
```

Search users by custom attribute:

```
user.customattributes.set('role', 'QA')
gl.users.list(custom_attributes={'role': 'QA'})
```

User impersonation tokens

References

- v4 API:
 - `gitlab.v4.objects.UserImpersonationToken`
 - `gitlab.v4.objects.UserImpersonationTokenManager`
 - `gitlab.v4.objects.User.impersonationtokens`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#get-all-impersonation-tokens-of-a-user>

List impersonation tokens for a user:

```
i_t = user.impersonationtokens.list(state='active')
i_t = user.impersonationtokens.list(state='inactive')
```

Get an impersonation token for a user:

```
i_t = user.impersonationtokens.get(i_t_id)
```

Create and use an impersonation token for a user:

```
i_t = user.impersonationtokens.create({'name': 'token1', 'scopes': ['api']})
# use the token to create a new gitlab connection
user_gl = gitlab.Gitlab(gitlab_url, private_token=i_t.token)
```

Revoke (delete) an impersonation token for a user:

```
i_t.delete()
```

User memberships

References

- v4 API:
 - *gitlab.v4.objects.UserMembership*
 - *gitlab.v4.objects.UserMembershipManager*
 - *gitlab.v4.objects.User.memberships*
- GitLab API: <https://docs.gitlab.com/ee/api/users.html#user-memberships-admin-only>

List direct memberships for a user:

```
memberships = user.memberships.list()
```

List only direct project memberships:

```
memberships = user.memberships.list(type='Project')
```

List only direct group memberships:

```
memberships = user.memberships.list(type='Namespace')
```

Current User

References

- v4 API:
 - *gitlab.v4.objects.CurrentUser*
 - *gitlab.v4.objects.CurrentUserManager*
 - *gitlab.Gitlab.user*
- GitLab API: <https://docs.gitlab.com/ce/api/users.html>

Examples

Get the current user:

```
gl.auth()
current_user = gl.user
```

GPG keys

References

You can manipulate GPG keys for the current user and for the other users if you are admin.

- v4 API:
 - *gitlab.v4.objects.CurrentUserGPGKey*
 - *gitlab.v4.objects.CurrentUserGPGKeyManager*
 - *gitlab.v4.objects.CurrentUser.gpgkeys*
 - *gitlab.v4.objects.UserGPGKey*
 - *gitlab.v4.objects.UserGPGKeyManager*
 - *gitlab.v4.objects.User.gpgkeys*
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-all-gpg-keys>

Examples

List GPG keys for a user:

```
gpgkeys = user.gpgkeys.list()
```

Get a GPG gpgkey for a user:

```
gpgkey = user.gpgkeys.get(key_id)
```

Create a GPG gpgkey for a user:

```
# get the key with `gpg --export -a GPG_KEY_ID`
k = user.gpgkeys.create({'key': public_key_content})
```

Delete a GPG gpgkey for a user:

```
user.gpgkeys.delete(key_id)
# or
gpgkey.delete()
```

SSH keys

References

You can manipulate SSH keys for the current user and for the other users if you are admin.

- v4 API:
 - `gitlab.v4.objects.CurrentUserKey`
 - `gitlab.v4.objects.CurrentUserKeyManager`
 - `gitlab.v4.objects.CurrentUser.keys`
 - `gitlab.v4.objects.UserKey`
 - `gitlab.v4.objects.UserKeyManager`
 - `gitlab.v4.objects.User.keys`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-ssh-keys>

Examples

List SSH keys for a user:

```
keys = user.keys.list()
```

Create an SSH key for a user:

```
key = user.keys.create({'title': 'my_key',  
                        'key': open('/home/me/.ssh/id_rsa.pub').read()})
```

Get an SSH key for a user by id:

```
key = user.keys.get(key_id)
```

Delete an SSH key for a user:

```
user.keys.delete(key_id)  
# or  
key.delete()
```

Status

References

You can manipulate the status for the current user and you can read the status of other users.

- v4 API:
 - `gitlab.v4.objects.CurrentUserStatus`
 - `gitlab.v4.objects.CurrentUserStatusManager`
 - `gitlab.v4.objects.CurrentUser.status`
 - `gitlab.v4.objects.UserStatus`

- *gitlab.v4.objects.UserStatusManager*
- *gitlab.v4.objects.User.status*
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#user-status>

Examples

Get current user status:

```
status = user.status.get()
```

Update the status for the current user:

```
status = user.status.get()
status.message = "message"
status.emoji = "thumbsup"
status.save()
```

Get the status of other users:

```
gl.users.get(1).status.get()
```

Emails

References

You can manipulate emails for the current user and for the other users if you are admin.

- v4 API:
 - *gitlab.v4.objects.CurrentUserEmail*
 - *gitlab.v4.objects.CurrentUserEmailManager*
 - *gitlab.v4.objects.CurrentUser.emails*
 - *gitlab.v4.objects.UserEmail*
 - *gitlab.v4.objects.UserEmailManager*
 - *gitlab.v4.objects.User.emails*
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-emails>

Examples

List emails for a user:

```
emails = user.emails.list()
```

Get an email for a user:

```
email = user.emails.get(email_id)
```

Create an email for a user:

```
k = user.emails.create({'email': 'foo@bar.com'})
```

Delete an email for a user:

```
user.emails.delete(email_id)
# or
email.delete()
```

Users activities

References

- admin only
- v4 API:
 - *gitlab.v4.objects.UserActivities*
 - *gitlab.v4.objects.UserActivitiesManager*
 - *gitlab.Gitlab.user_activities*
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#get-user-activities-admin-only>

Examples

Get the users activities:

```
activities = gl.user_activities.list(
    query_parameters={'from': '2018-07-01'},
    all=True, as_list=False)
```

6.4.52 CI/CD Variables

You can configure variables at the instance-level (admin only), or associate variables to projects and groups, to modify pipeline/job scripts behavior.

Instance-level variables

This endpoint requires admin access.

Reference

- v4 API
 - *gitlab.v4.objects.Variable*
 - *gitlab.v4.objects.VariableManager*
 - *gitlab.Gitlab.variables*
- GitLab API

- https://docs.gitlab.com/ce/api/instance_level_ci_variables.html

Examples

List all instance variables:

```
variables = gl.variables.list()
```

Get an instance variable by key:

```
variable = gl.variables.get('key_name')
```

Create an instance variable:

```
variable = gl.variables.create({'key': 'key1', 'value': 'value1'})
```

Update a variable value:

```
variable.value = 'new_value'
variable.save()
```

Remove a variable:

```
gl.variables.delete('key_name')
# or
variable.delete()
```

Projects and groups variables

Reference

- v4 API
 - *gitlab.v4.objects.ProjectVariable*
 - *gitlab.v4.objects.ProjectVariableManager*
 - *gitlab.v4.objects.Project.variables*
 - *gitlab.v4.objects.GroupVariable*
 - *gitlab.v4.objects.GroupVariableManager*
 - *gitlab.v4.objects.Group.variables*
- GitLab API
 - https://docs.gitlab.com/ce/api/instance_level_ci_variables.html
 - https://docs.gitlab.com/ce/api/project_level_variables.html
 - https://docs.gitlab.com/ce/api/group_level_variables.html

Examples

List variables:

```
p_variables = project.variables.list()
g_variables = group.variables.list()
```

Get a variable:

```
p_var = project.variables.get('key_name')
g_var = group.variables.get('key_name')
```

Create a variable:

```
var = project.variables.create({'key': 'key1', 'value': 'value1'})
var = group.variables.create({'key': 'key1', 'value': 'value1'})
```

Update a variable value:

```
var.value = 'new_value'
var.save()
# or
project.variables.update("key1", {"value": "new_value"})
```

Remove a variable:

```
project.variables.delete('key_name')
group.variables.delete('key_name')
# or
var.delete()
```

6.4.53 Sidekiq metrics

Reference

- v4 API:
 - `gitlab.v4.objects.SidekiqManager`
 - `gitlab.Gitlab.sidekiq`
- GitLab API: https://docs.gitlab.com/ce/api/sidekiq_metrics.html

Examples

```
gl.sidekiq.queue_metrics()
gl.sidekiq.process_metrics()
gl.sidekiq.job_stats()
gl.sidekiq.compound_metrics()
```

6.4.54 Wiki pages

References

- v4 API:
 - `gitlab.v4.objects.ProjectWiki`
 - `gitlab.v4.objects.ProjectWikiManager`
 - `gitlab.v4.objects.Project.wikis`
 - `gitlab.v4.objects.GroupWiki`
 - `gitlab.v4.objects.GroupWikiManager`
 - `gitlab.v4.objects.Group.wikis`
- GitLab API for Projects: <https://docs.gitlab.com/ce/api/wikis.html>
- GitLab API for Groups: https://docs.gitlab.com/ee/api/group_wikis.html

Examples

Get the list of wiki pages for a project. These do not contain the contents of the wiki page. You will need to call `get(slug)` to retrieve the content by accessing the content attribute:

```
pages = project.wikis.list()
```

Get the list of wiki pages for a group. These do not contain the contents of the wiki page. You will need to call `get(slug)` to retrieve the content by accessing the content attribute:

```
pages = group.wikis.list()
```

Get a single wiki page for a project:

```
page = project.wikis.get(page_slug)
```

Get a single wiki page for a group:

```
page = group.wikis.get(page_slug)
```

Get the contents of a wiki page:

```
print(page.content)
```

Create a wiki page on a project level:

```
page = project.wikis.create({'title': 'Wiki Page 1',
                             'content': open(a_file).read()})
```

Update a wiki page:

```
page.content = 'My new content'
page.save()
```

Delete a wiki page:

page.delete()

6.5 API reference (gitlab package)

6.5.1 Module contents

Wrapper for the GitLab API.

```
class gitlab.Gitlab(url: Optional[str] = None, private_token: Optional[str] = None, oauth_token:
    Optional[str] = None, job_token: Optional[str] = None, ssl_verify: Union[bool, str] =
    True, http_username: Optional[str] = None, http_password: Optional[str] = None,
    timeout: Optional[float] = None, api_version: str = '4', session:
    Optional[requests.sessions.Session] = None, per_page: Optional[int] = None, pagination:
    Optional[str] = None, order_by: Optional[str] = None, user_agent: str =
    'python-gitlab/3.5.0', retry_transient_errors: bool = False)
```

Bases: object

Represents a GitLab server connection.

Parameters

- **url** (*Optional[str]*) – The URL of the GitLab server (defaults to <https://gitlab.com>).
- **private_token** (*Optional[str]*) – The user private token
- **oauth_token** (*Optional[str]*) – An oauth token
- **job_token** (*Optional[str]*) – A CI job token
- **ssl_verify** (*Union[bool, str]*) – Whether SSL certificates should be validated. If the value is a string, it is the path to a CA file used for certificate validation.
- **timeout** (*Optional[float]*) – Timeout to use for requests to the GitLab server.
- **http_username** (*Optional[str]*) – Username for HTTP authentication
- **http_password** (*Optional[str]*) – Password for HTTP authentication
- **api_version** (*str*) – Gitlab API version to use (support for 4 only)
- **pagination** (*Optional[str]*) – Can be set to 'keyset' to use keyset pagination
- **order_by** (*Optional[str]*) – Set order_by globally
- **user_agent** (*str*) – A custom user agent to use for making HTTP requests.
- **retry_transient_errors** (*bool*) – Whether to retry after 500, 502, 503, 504 or 52x responses. Defaults to False.
- **session** (*Optional[requests.sessions.Session]*) –
- **per_page** (*Optional[int]*) –

Return type None

property api_url: str

The computed API base URL.

property api_version: str

The API version used (4 only).

appearance

See [ApplicationAppearanceManager](#)

applications

See [ApplicationManager](#)

audit_events

See [AuditEventManager](#)

auth() → None

Performs an authentication using private token.

The *user* attribute will hold a *gitlab.objects.CurrentUser* object on success.

Return type None

broadcastmessages

See [BroadcastMessageManager](#)

deploykeys

See [DeployKeyManager](#)

deploytokens

See [DeployTokenManager](#)

dockerfiles

See [DockerfileManager](#)

enable_debug() → None

Return type None

events

See [EventManager](#)

features

See [FeatureManager](#)

classmethod from_config(*gitlab_id*: *Optional[str]* = None, *config_files*: *Optional[List[str]]* = None) → *gitlab.client.Gitlab*

Create a Gitlab connection from configuration files.

Parameters

- **gitlab_id** (*Optional[str]*) – ID of the configuration section.
- **list[str]** (*config_files*) – List of paths to configuration files.
- **config_files** (*Optional[List[str]]*) –

Returns A Gitlab connection.

Raises [gitlab.config.GitlabDataError](#) – If the configuration is not correct.

Return type *gitlab.client.Gitlab*

geonodes

See [GeoNodeManager](#)

get_license(**kwargs: Any) → Dict[str, Any]

Retrieve information about the current license.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the server cannot perform the request

Returns The current license information

Return type Dict[str, Any]

gitignores

See [`GitignoreManager`](#)

gitlabciymls

See [`GitlabciyamlManager`](#)

groups

See [`GroupManager`](#)

headers

Headers that will be used in request to GitLab

hooks

See [`HookManager`](#)

http_delete(path: str, **kwargs: Any) → requests.models.Response

Make a DELETE request to the Gitlab server.

Parameters

- **path** (str) – Path or full URL to query (‘/projects’ or ‘http://whatever/v4/api/projects’)
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The requests object.

Raises [`GitlabHttpError`](#) – When the return code is not 2xx

Return type requests.models.Response

http_get(path: str, query_data: Optional[Dict[str, Any]] = None, streamed: bool = False, raw: bool = False, **kwargs: Any) → Union[Dict[str, Any], requests.models.Response]

Make a GET request to the Gitlab server.

Parameters

- **path** (str) – Path or full URL to query (‘/projects’ or ‘http://whatever/v4/api/projects’)
- **query_data** (Optional[Dict[str, Any]]) – Data to send as query parameters
- **streamed** (bool) – Whether the data should be streamed
- **raw** (bool) – If True do not try to parse the output as json
- ****kwargs** – Extra options to send to the server (e.g. sudo)

- **kwargs** (*Any*) –

Returns A requests result object is streamed is True or the content type is not json. The parsed json data otherwise.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type `Union[Dict[str, Any], requests.models.Response]`

http_list(*path: str, query_data: Optional[Dict[str, Any]] = None, as_list: Optional[bool] = None, **kwargs: Any*) → `Union[gitlab.client.GitlabList, List[Dict[str, Any]]]`

Make a GET request to the Gitlab server for list-oriented queries.

Parameters

- **path** (*str*) – Path or full URL to query (‘/projects’ or ‘http://whatever/v4/api/projects’)
- **query_data** (*Optional[Dict[str, Any]]*) – Data to send as query parameters
- ****kwargs** – Extra options to send to the server (e.g. sudo, page, per_page)
- **as_list** (*Optional[bool]*) –
- **kwargs** (*Any*) –

Returns A list of the objects returned by the server. If *as_list* is False and no pagination-related arguments (*page*, *per_page*, *all*) are defined then a `GitlabList` object (generator) is returned instead. This object will make API calls when needed to fetch the next items from the server.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type `Union[gitlab.client.GitlabList, List[Dict[str, Any]]]`

http_post(*path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Dict[str, Any]] = None, raw: bool = False, files: Optional[Dict[str, Any]] = None, **kwargs: Any*) → `Union[Dict[str, Any], requests.models.Response]`

Make a POST request to the Gitlab server.

Parameters

- **path** (*str*) – Path or full URL to query (‘/projects’ or ‘http://whatever/v4/api/projects’)
- **query_data** (*Optional[Dict[str, Any]]*) – Data to send as query parameters
- **post_data** (*Optional[Dict[str, Any]]*) – Data to send in the body (will be converted to json by default)
- **raw** (*bool*) – If True, do not convert post_data to json
- **files** (*Optional[Dict[str, Any]]*) – The files to send to the server
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The parsed json returned by the server if json is return, else the raw content

Raises

- **GitlabHttpError** – When the return code is not 2xx

- **GitlabParsingError** – If the json data could not be parsed

Return type `Union[Dict[str, Any], requests.models.Response]`

http_put (*path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Union[Dict[str, Any], bytes]] = None, raw: bool = False, files: Optional[Dict[str, Any]] = None, **kwargs: Any*) → `Union[Dict[str, Any], requests.models.Response]`

Make a PUT request to the Gitlab server.

Parameters

- **path** (*str*) – Path or full URL to query (‘/projects’ or ‘<http://whatever/v4/api/projects>’)
- **query_data** (*Optional[Dict[str, Any]]*) – Data to send as query parameters
- **post_data** (*Optional[Union[Dict[str, Any], bytes]]*) – Data to send in the body (will be converted to json by default)
- **raw** (*bool*) – If True, do not convert post_data to json
- **files** (*Optional[Dict[str, Any]]*) – The files to send to the server
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The parsed json returned by the server.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type `Union[Dict[str, Any], requests.models.Response]`

http_request (*verb: str, path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Union[Dict[str, Any], bytes]] = None, raw: bool = False, streamed: bool = False, files: Optional[Dict[str, Any]] = None, timeout: Optional[float] = None, obey_rate_limit: bool = True, retry_transient_errors: Optional[bool] = None, max_retries: int = 10, **kwargs: Any*) → `requests.models.Response`

Make an HTTP request to the Gitlab server.

Parameters

- **verb** (*str*) – The HTTP method to call (‘get’, ‘post’, ‘put’, ‘delete’)
- **path** (*str*) – Path or full URL to query (‘/projects’ or ‘<http://whatever/v4/api/projects>’)
- **query_data** (*Optional[Dict[str, Any]]*) – Data to send as query parameters
- **post_data** (*Optional[Union[Dict[str, Any], bytes]]*) – Data to send in the body (will be converted to json by default)
- **raw** (*bool*) – If True, do not convert post_data to json
- **streamed** (*bool*) – Whether the data should be streamed
- **files** (*Optional[Dict[str, Any]]*) – The files to send to the server
- **timeout** (*Optional[float]*) – The timeout, in seconds, for the request
- **obey_rate_limit** (*bool*) – Whether to obey 429 Too Many Request responses. Defaults to True.
- **retry_transient_errors** (*Optional[bool]*) – Whether to retry after 500, 502, 503, 504 or 52x responses. Defaults to False.

- **max_retries** (*int*) – Max retries after 429 or transient errors, set to -1 to retry forever. Defaults to 10.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns A requests result object.

Raises [*GitlabHttpError*](#) – When the return code is not 2xx

Return type requests.models.Response

issues

See [*IssueManager*](#)

issues_statistics

See [*IssuesStatisticsManager*](#)

keys

See [*KeyManager*](#)

ldapgroups

See [*LDAPGroupManager*](#)

licenses

See [*LicenseManager*](#)

lint(*content: str, **kwargs: Any*) → Tuple[bool, List[str]]

Validate a gitlab CI configuration.

Parameters

- **content** (*str*) – The .gitlab-ci.yml content
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabVerifyError*](#) – If the validation could not be done

Returns (True, []) if the file is valid, (False, errors(list)) otherwise

Return type Tuple[bool, List[str]]

markdown(*text: str, gfm: bool = False, project: Optional[str] = None, **kwargs: Any*) → str

Render an arbitrary Markdown document.

Parameters

- **text** (*str*) – The markdown text to render
- **gfm** (*bool*) – Render text using GitLab Flavored Markdown. Default is False
- **project** (*Optional[str]*) – Full path of a project used a context when *gfm* is True
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct

- [`GitlabMarkdownError`](#) – If the server cannot perform the request

Returns The HTML rendering of the markdown text.

Return type `str`

classmethod `merge_config`(*options: dict, gitlab_id: Optional[str] = None, config_files: Optional[List[str]] = None*) → [`gitlab.client.Gitlab`](#)

Create a Gitlab connection by merging configuration with the following precedence:

1. Explicitly provided CLI arguments,
2. Environment variables,
3. **Configuration files:**
 - a. **explicitly defined config files:**
 - i. via the `--config-file` CLI argument,
 - ii. via the `PYTHON_GITLAB_CFG` environment variable,
 - b. user-specific config file,
 - c. system-level config file,
4. Environment variables always present in CI (`CI_SERVER_URL`, `CI_JOB_TOKEN`).

Parameters

- **options** (*dict*) – A dictionary of explicitly provided key-value options.
- **gitlab_id** (*Optional[str]*) – ID of the configuration section.
- **config_files** (*Optional[List[str]]*) – List of paths to configuration files.

Returns A Gitlab connection.

Return type ([`gitlab.Gitlab`](#))

Raises [`gitlab.config.GitlabDataError`](#) – If the configuration is not correct.

mergerequests

See [`MergeRequestManager`](#)

namespaces

See [`NamespaceManager`](#)

notificationsettings

See [`NotificationSettingsManager`](#)

pagesdomains

See [`PagesDomainManager`](#)

personal_access_tokens

See [`PersonalAccessTokenManager`](#)

projects

See [`ProjectManager`](#)

runners

See [`RunnerManager`](#)

search(*scope: str, search: str, **kwargs: Any*) → Union[[*gitlab.client.GitlabList*](#), List[Dict[str, Any]]]

Search GitLab resources matching the provided string.

Parameters

- **scope** (*str*) – Scope of the search
- **search** (*str*) – Search string
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabSearchError*](#) – If the server failed to perform the request

Returns A list of dicts describing the resources found.

Return type Union[[*gitlab.client.GitlabList*](#), List[Dict[str, Any]]]

session

Create a session object for requests

set_license(*license: str, **kwargs: Any*) → Dict[str, Any]

Add a new license.

Parameters

- **license** (*str*) – The license string
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabPostError*](#) – If the server cannot perform the request

Returns The new license information

Return type Dict[str, Any]

settings

See [*ApplicationSettingsManager*](#)

sidekiq

See [*SidekiqManager*](#)

snippets

See [*SnippetManager*](#)

ssl_verify

Whether SSL certificates should be validated

timeout

Timeout to use for requests to gitlab server

todos

See [*TodoManager*](#)

topics

See [*TopicManager*](#)

property url: str

The user-provided server URL.

user_activities

See [*UserActivitiesManager*](#)

users

See [*UserManager*](#)

variables

See [*VariableManager*](#)

version() → Tuple[str, str]

Returns the version and revision of the gitlab server.

Note that self.version and self.revision will be set on the gitlab object.

Returns

The server version and server revision. ('unknown', 'unknown') if the server doesn't perform as expected.

Return type *Tuple*[str, str]

class gitlab.**GitlabList**(gl: [*gitlab.client.Gitlab*](#), url: str, query_data: Dict[str, Any], get_next: bool = True, **kwargs: Any)

Bases: object

Generator representing a list of remote objects.

The object handles the links returned by a query to the API, and will call the API again when needed.

Parameters

- **gl** ([*gitlab.client.Gitlab*](#)) –
- **url** (str) –
- **query_data** (Dict[str, Any]) –
- **get_next** (bool) –
- **kwargs** (Any) –

Return type None

property current_page: int

The current page number.

next() → Dict[str, Any]

Return type *Dict*[str, Any]

property next_page: Optional[int]

The next page number.

If None, the current page is the last.

property per_page: Optional[int]

The number of items per page.

property prev_page: `Optional[int]`

The previous page number.

If None, the current page is the first.

property total: `Optional[int]`

The total number of items.

property total_pages: `Optional[int]`

The total number of pages.

6.5.2 Subpackages

gitlab.v4 package

Submodules

gitlab.v4.objects module

class `gitlab.v4.objects.Application`(*manager*: `gitlab.base.RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`)

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.ApplicationAppearance`(*manager*: `gitlab.base.RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.ApplicationAppearanceManager`(*gl*: `gitlab.client.Gitlab`, *parent*: `Optional[gitlab.base.RESTObject] = None`)

Bases: `gitlab.mixins.GetWithoutIdMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id*: `Optional[Union[int, str]] = None`, ***kwargs*: `Any`) → `Optional[gitlab.v4.objects.appearance.ApplicationAppearance]`

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (`Optional[Union[int, str]]`) –
- **kwargs** (`Any`) –

Returns The generated RESTObject**Raises**

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `Optional[gitlab.v4.objects.appearance.ApplicationAppearance]`

gitlab: `gitlab.client.Gitlab`

update(*id*: `Optional[Union[int, str]] = None`, *new_data*: `Dict[str, Any] = None`, ***kwargs*: `Any`) → `Dict[str, Any]`

Update an object on the server.

Parameters

- **id** (`Optional[Union[int, str]]`) – ID of the object to update (can be None if not required)
- **new_data** (`Dict[str, Any]`) – the update data for the object
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The new object data (*not* a RESTObject)**Raises**

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server cannot perform the request

Return type `Dict[str, Any]`

class `gitlab.v4.objects.ApplicationManager`(*gl*: `gitlab.client.Gitlab`, *parent*: `Optional[gitlab.base.RESTObject] = None`)

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object Creation**Object update****Parameters**

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ApplicationSettings(manager: gitlab.base.RESTManager, attrs: Dict[str, Any],
                                           *, created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ApplicationSettingsManager(gl: gitlab.client.Gitlab, parent:
                                                  Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.GetWithoutIdMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) →
Optional[gitlab.v4.objects.settings.ApplicationSettings]
```

Retrieve a single object.

Parameters

- **`**kwargs`** – Extra options to send to the server (e.g. `sudo`)
- `id` (`Optional[Union[int, str]]`) –
- `kwargs` (`Any`) –

Returns The generated `RESTObject`

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type `Optional[gitlab.v4.objects.settings.ApplicationSettings]`

gitlab: `gitlab.client.Gitlab`

update(*id*: *Optional*[*Union*[*int*, *str*]] = *None*, *new_data*: *Dict*[*str*, *Any*] = *None*, ***kwargs*: *Any*) → *Dict*[*str*, *Any*]

Update an object on the server.

Parameters

- **id** (*Optional*[*Union*[*int*, *str*]]) – ID of the object to update (can be *None* if not required)
- **new_data** (*Dict*[*str*, *Any*]) – the update data for the object
- ****kwargs** – Extra options to send to the server (e.g. *sudo*)
- **kwargs** (*Any*) –

Returns The new object data (*not* a *RESTObject*)

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabUpdateError* – If the server cannot perform the request

Return type *Dict*[*str*, *Any*]

class `gitlab.v4.objects.AuditEvent`(*manager*: `gitlab.base.RESTManager`, *attrs*: *Dict*[*str*, *Any*], *, *created_from_list*: *bool* = *False*)

Bases: `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –

Return type *None*

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.AuditEventManager`(*gl*: `gitlab.client.Gitlab`, *parent*: *Optional*[`gitlab.base.RESTObject`] = *None*)

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.base.RESTManager`

Object listing filters

- *created_after*
- *created_before*
- *entity_type*
- *entity_id*

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional*[`gitlab.base.RESTObject`]) –

Return type *None*

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → *gitlab.v4.objects.audit_events.AuditEvent*

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.audit_events.AuditEvent*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.BroadcastMessage(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                         created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (gitlab.base.RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –

Return type None

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.BroadcastMessageManager(gl: gitlab.client.Gitlab, parent:
                                                Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (gitlab.client.Gitlab) –
- **parent** (Optional[gitlab.base.RESTObject]) –

Return type None

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) →
gitlab.v4.objects.broadcast_messages.BroadcastMessage

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.broadcast_messages.BroadcastMessage*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.CurrentUser(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type None

emails: *gitlab.v4.objects.users.CurrentUserEmailManager*

gpgkeys: *gitlab.v4.objects.users.CurrentUserGPGKeyManager*

keys: *gitlab.v4.objects.users.CurrentUserKeyManager*

status: *gitlab.v4.objects.users.CurrentUserStatusManager*

```
class gitlab.v4.objects.CurrentUserEmail(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                          created_from_list: bool = False)
```

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type None

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.CurrentUserEmailManager(gl: gitlab.client.Gitlab, parent:
                                                Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`**get**(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → `gitlab.v4.objects.users.CurrentUserEmail`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated `RESTObject`.**Raises**

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type `gitlab.v4.objects.users.CurrentUserEmail`**gitlab:** `gitlab.client.Gitlab`

```
class gitlab.v4.objects.CurrentUserGPGKey(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                          created_from_list: bool = False)
```

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`**Parameters**

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`**manager:** `gitlab.base.RESTManager`

```
class gitlab.v4.objects.CurrentUserGPGKeyManager(gl: gitlab.client.Gitlab, parent:
                                                  Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`**Object Creation****Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → *gitlab.v4.objects.users.CurrentUserGPGKey*

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.users.CurrentUserGPGKey*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.CurrentUserKey(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                       created_from_list: bool = False)
```

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (gitlab.base.RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –

Return type None

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.CurrentUserKeyManager(gl: gitlab.client.Gitlab, parent:
                                              Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (gitlab.client.Gitlab) –
- **parent** (Optional[gitlab.base.RESTObject]) –

Return type None

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → *gitlab.v4.objects.users.CurrentUserKey*

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.users.CurrentUserKey*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.CurrentUserManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.GetWithoutIdMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) → Optional[gitlab.v4.objects.users.CurrentUser]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.users.CurrentUser]*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.CurrentUserStatus(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –

- **created_from_list** (*bool*) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.CurrentUserStatusManager` (*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: `gitlab.mixins.GetWithoutIdMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get (*id: Optional[Union[int, str]] = None, **kwargs: Any*) → `Optional[gitlab.v4.objects.users.CurrentUserStatus]`

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (`Optional[Union[int, str]]`) –
- **kwargs** (`Any`) –

Returns The generated `RESTObject`

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `Optional[gitlab.v4.objects.users.CurrentUserStatus]`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.DeployKey` (*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (*bool*) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.DeployKeyManager(gl: gitlab.client.Gitlab, parent:
    Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

`gitlab:` `gitlab.client.Gitlab`

```
class gitlab.v4.objects.DeployToken(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
    created_from_list: bool = False)
```

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –

Return type `None`

`manager:` `gitlab.base.RESTManager`

```
class gitlab.v4.objects.DeployTokenManager(gl: gitlab.client.Gitlab, parent:
    Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

`gitlab:` `gitlab.client.Gitlab`

```
class gitlab.v4.objects.Dockerfile(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
    created_from_list: bool = False)
```

Bases: `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –

Return type `None`

manager: [`gitlab.base.RESTManager`](#)

class `gitlab.v4.objects.DockerfileManager`(*gl*: [`gitlab.client.Gitlab`](#), *parent*: [`Optional\[gitlab.base.RESTObject\]`](#) = *None*)

Bases: [`gitlab.mixins.RetrieveMixin`](#), [`gitlab.base.RESTManager`](#)

Object Creation

Object update

Parameters

- **gl** ([`gitlab.client.Gitlab`](#)) –
- **parent** ([`Optional\[gitlab.base.RESTObject\]`](#)) –

Return type *None*

get(*id*: [`Union\[str, int\]`](#), *lazy*: *bool* = *False*, ***kwargs*: *Any*) → [`gitlab.v4.objects.templates.Dockerfile`](#)

Retrieve a single object.

Parameters

- **id** ([`Union\[str, int\]`](#)) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Returns The generated [`RESTObject`](#).

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the server cannot perform the request

Return type [`gitlab.v4.objects.templates.Dockerfile`](#)

gitlab: [`gitlab.client.Gitlab`](#)

class `gitlab.v4.objects.Event`(*manager*: [`gitlab.base.RESTManager`](#), *attrs*: [`Dict\[str, Any\]`](#), *, *created_from_list*: *bool* = *False*)

Bases: [`gitlab.base.RESTObject`](#)

Parameters

- **manager** ([`gitlab.base.RESTManager`](#)) –
- **attrs** ([`Dict\[str, Any\]`](#)) –
- **created_from_list** (*bool*) –

Return type *None*

manager: [`gitlab.base.RESTManager`](#)

class `gitlab.v4.objects.EventManager`(*gl*: [`gitlab.client.Gitlab`](#), *parent*: [`Optional\[gitlab.base.RESTObject\]`](#) = *None*)

Bases: [`gitlab.mixins.ListMixin`](#), [`gitlab.base.RESTManager`](#)

Object listing filters

- **action**

- `target_type`
- `before`
- `after`
- `sort`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.Feature(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                created_from_list: bool = False)
```

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.FeatureManager(gl: gitlab.client.Gitlab, parent:
                                       Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
set(name: str, value: Union[bool, int], feature_group: Optional[str] = None, user: Optional[str] = None,
    group: Optional[str] = None, project: Optional[str] = None, **kwargs: Any) →
gitlab.v4.objects.features.Feature
```

Create or update the object.

Parameters

- `name` (`str`) – The value to set for the object
- `value` (`Union[bool, int]`) – The value to set for the object

- **feature_group** (*Optional[str]*) – A feature group name
- **user** (*Optional[str]*) – A GitLab username
- **group** (*Optional[str]*) – A GitLab group
- **project** (*Optional[str]*) – A GitLab project in form group/project
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSetError** – If an error occurred

Returns The created/updated attribute

Return type *gitlab.v4.objects.features.Feature*

```
class gitlab.v4.objects.GenericPackage(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                       created_from_list: bool = False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.GenericPackageManager(gl: gitlab.client.Gitlab, parent:
                                              Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.base.RESTManager*

Object Creation**Object update****Parameters**

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
download(package_name: str, package_version: str, file_name: str, streamed: bool = False, action:
          Optional[Callable] = None, chunk_size: int = 1024, **kwargs: Any) → Optional[bytes]
```

Download a generic package.

Parameters

- **package_name** (*str*) – The package name.
- **package_version** (*str*) – The package version.
- **file_name** (*str*) – The name of the file in the registry
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment

- **action** (*Optional[Callable]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns The package content if streamed is False, None otherwise

Return type *Optional[bytes]*

gitlab: *gitlab.client.Gitlab*

upload(*package_name: str, package_version: str, file_name: str, path: Union[str, pathlib.Path], **kwargs: Any*) → *gitlab.v4.objects.packages.GenericPackage*

Upload a file as a generic package.

Parameters

- **package_name** (*str*) – The package name. Must follow generic package name regex rules
- **package_version** (*str*) – The package version. Must follow semantic version regex rules
- **file_name** (*str*) – The name of the file as uploaded in the registry
- **path** (*Union[str, pathlib.Path]*) – The path to a local file to upload
- **kwargs** (*Any*) –

Raises

- **GitlabConnectionError** – If the server cannot be reached
- **GitlabUploadError** – If the file upload fails
- **GitlabUploadError** – If filepath cannot be read

Returns An object storing the metadata of the uploaded package.

Return type *gitlab.v4.objects.packages.GenericPackage*

https://docs.gitlab.com/ee/user/packages/generic_packages/

class *gitlab.v4.objects.GeoNode*(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

repair(**kwargs: Any) → None

Repair the OAuth authentication of the geo node.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabRepairError`](#) – If the server failed to perform the request

Return type None

status(**kwargs: Any) → Dict[str, Any]

Get the status of the geo node.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the server failed to perform the request

Returns The status of the geo node

Return type Dict[str, Any]

class gitlab.v4.objects.**GeoNodeManager**(gl: [`gitlab.client.Gitlab`](#), parent: *Optional*[[`gitlab.base.RESTObject`](#)] = None)

Bases: [`gitlab.mixins.RetrieveMixin`](#), [`gitlab.mixins.UpdateMixin`](#), [`gitlab.mixins.DeleteMixin`](#), [`gitlab.base.RESTManager`](#)

Object Creation

Object update

Parameters

- **gl** ([`gitlab.client.Gitlab`](#)) –
- **parent** (*Optional*[[`gitlab.base.RESTObject`](#)]) –

Return type None

current_failures(**kwargs: Any) → List[Dict[str, Any]]

Get the list of failures on the current geo node.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the server failed to perform the request

Returns The list of failures

Return type *List[Dict[str, Any]]*

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *gitlab.v4.objects.geo_nodes.GeoNode*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.geo_nodes.GeoNode*

gitlab: *gitlab.client.Gitlab*

status(***kwargs: Any*) → *List[Dict[str, Any]]*

Get the status of all the geo nodes.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns The status of all the geo nodes

Return type *List[Dict[str, Any]]*

class *gitlab.v4.objects.Gitignore*(*manager: gitlab.base.RESTManager*, *attrs: Dict[str, Any]*, ***, *created_from_list: bool = False*)

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.GitignoreManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional*[[gitlab.base.RESTObject](#)]) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.templates.Gitignore
```

Retrieve a single object.

Parameters

- **id** (*Union*[`str`, `int`]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Returns The generated `RESTObject`.

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [gitlab.v4.objects.templates.Gitignore](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.Gitlabciyaml(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict*[`str`, `Any`]) –
- **created_from_list** (*bool*) –

Return type `None`

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.GitlabciyamlManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

get (*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) → *gitlab.v4.objects.templates.Gitlabciyaml*

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.templates.Gitlabciyaml*

gitlab: *gitlab.client.Gitlab*

class `gitlab.v4.objects.Group` (*manager*: *gitlab.base.RESTManager*, *attrs*: *Dict*[*str*, *Any*], *, *created_from_list*: *bool* = *False*)

Bases: *gitlab.mixins.SaveMixin*, *gitlab.mixins.ObjectDeleteMixin*, *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –

Return type `None`

access_tokens: *gitlab.v4.objects.group_access_tokens.GroupAccessTokenManager*

accessrequests: *gitlab.v4.objects.access_requests.GroupAccessRequestManager*

add_ldap_group_link (*cn*: *str*, *group_access*: *int*, *provider*: *str*, ***kwargs*: *Any*) → `None`

Add an LDAP group link.

Parameters

- **cn** (*str*) – CN of the LDAP group
- **group_access** (*int*) – Minimum access level for members of the LDAP group
- **provider** (*str*) – LDAP provider for the LDAP group
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct

- *GitlabCreateError* – If the server cannot perform the request

Return type `None`

`audit_events:` *gitlab.v4.objects.audit_events.GroupAuditEventManager*

`badges:` *gitlab.v4.objects.badges.GroupBadgeManager*

`billable_members:` *gitlab.v4.objects.members.GroupBillableMemberManager*

`boards:` *gitlab.v4.objects.boards.GroupBoardManager*

`clusters:` *gitlab.v4.objects.clusters.GroupClusterManager*

`customattributes:` *gitlab.v4.objects.custom_attributes.GroupCustomAttributeManager*

`delete_ldap_group_link`(*cn: str, provider: Optional[str] = None, **kwargs: Any*) → `None`

Delete an LDAP group link.

Parameters

- `cn` (*str*) – CN of the LDAP group
- `provider` (*Optional[str]*) – LDAP provider for the LDAP group
- `**kwargs` – Extra options to send to the server (e.g. `sudo`)
- `kwargs` (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabDeleteError* – If the server cannot perform the request

Return type `None`

`deploytokens:` *gitlab.v4.objects.deploy_tokens.GroupDeployTokenManager*

`descendant_groups:` *GroupDescendantGroupManager*

`epics:` *gitlab.v4.objects.epics.GroupEpicManager*

`exports:` *gitlab.v4.objects.export_import.GroupExportManager*

`hooks:` *gitlab.v4.objects.hooks.GroupHookManager*

`imports:` *gitlab.v4.objects.export_import.GroupImportManager*

`issues:` *gitlab.v4.objects.issues.GroupIssueManager*

`issues_statistics:` *gitlab.v4.objects.statistics.GroupIssuesStatisticsManager*

`labels:` *gitlab.v4.objects.labels.GroupLabelManager*

`ldap_sync`(***kwargs: Any*) → `None`

Sync LDAP groups.

Parameters

- `**kwargs` – Extra options to send to the server (e.g. `sudo`)
- `kwargs` (*Any*) –

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabCreateError`** – If the server cannot perform the request

Return type None

members: `gitlab.v4.objects.members.GroupMemberManager`

members_all: `gitlab.v4.objects.members.GroupMemberAllManager`

mergerequests: `gitlab.v4.objects.merge_requests.GroupMergeRequestManager`

milestones: `gitlab.v4.objects.milestones.GroupMilestoneManager`

notificationsettings:

`gitlab.v4.objects.notification_settings.GroupNotificationSettingsManager`

packages: `gitlab.v4.objects.packages.GroupPackageManager`

projects: `gitlab.v4.objects.projects.GroupProjectManager`

runners: `gitlab.v4.objects.runners.GroupRunnerManager`

search(*scope: str, search: str, **kwargs: Any*) → Union[`gitlab.client.GitlabList`, List[Dict[str, Any]]]

Search the group resources matching the provided string.

Parameters

- **scope** (*str*) – Scope of the search
- **search** (*str*) – Search string
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabSearchError`** – If the server failed to perform the request

Returns A list of dicts describing the resources found.

Return type Union[`gitlab.client.GitlabList`, List[Dict[str, Any]]]

share(*group_id: int, group_access: int, expires_at: Optional[str] = None, **kwargs: Any*) → None

Share the group with a group.

Parameters

- **group_id** (*int*) – ID of the group.
- **group_access** (*int*) – Access level for the group.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **expires_at** (*Optional[str]*) –
- **kwargs** (*Any*) –

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabCreateError`** – If the server failed to perform the request

Returns Group

Return type None

subgroups: [*GroupSubgroupManager*](#)

transfer(*group_id: Optional[int] = None, **kwargs: Any*) → None

Transfer the group to a new parent group or make it a top-level group.

Requires GitLab 14.6.

Parameters

- **group_id** (*Optional[int]*) – ID of the new parent group. When not specified, the group to transfer is instead turned into a top-level group.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabGroupTransferError*](#) – If the group could not be transferred

Return type None

transfer_project(*project_id: int, **kwargs: Any*) → None

Transfer a project to this group.

Parameters

- **to_project_id** – ID of the project to transfer
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **project_id** (*int*) –
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabTransferProjectError*](#) – If the project could not be transferred

Return type None

unshare(*group_id: int, **kwargs: Any*) → None

Delete a shared group link within a group.

Parameters

- **group_id** (*int*) – ID of the group.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabDeleteError*](#) – If the server failed to perform the request

Return type None

variables: `gitlab.v4.objects.variables.GroupVariableManager`

wikis: `gitlab.v4.objects.wikis.GroupWikiManager`

class `gitlab.v4.objects.GroupAccessRequest`(*manager*: `gitlab.base.RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`)

Bases: `gitlab.mixins.AccessRequestMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.GroupAccessRequestManager`(*gl*: `gitlab.client.Gitlab`, *parent*: `Optional[gitlab.base.RESTObject] = None`)

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.GroupAccessToken`(*manager*: `gitlab.base.RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`)

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.GroupAccessTokenManager`(*gl*: `gitlab.client.Gitlab`, *parent*: `Optional[gitlab.base.RESTObject] = None`)

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional*[`gitlab.base.RESTObject`]) –

Return type None**gitlab:** `gitlab.client.Gitlab`

```
class gitlab.v4.objects.GroupAuditEvent(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                         created_from_list: bool = False)
```

Bases: `gitlab.base.RESTObject`**Parameters**

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (*Dict*[`str`, `Any`]) –
- **created_from_list** (*bool*) –

Return type None**manager:** `gitlab.base.RESTManager`

```
class gitlab.v4.objects.GroupAuditEventManager(gl: gitlab.client.Gitlab, parent:
                                              Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.base.RESTManager`**Object listing filters**

- **created_after**
- **created_before**

Object Creation**Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional*[`gitlab.base.RESTObject`]) –

Return type None

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) →
    gitlab.v4.objects.audit_events.GroupAuditEvent
```

Retrieve a single object.

Parameters

- **id** (*Union*[`str`, `int`]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.**Raises**

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.audit_events.GroupAuditEvent*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.GroupBadge(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                   created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.GroupBadgeManager(gl: gitlab.client.Gitlab, parent:
                                          Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.BadgeRenderMixin, gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get (*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.badges.GroupBadge*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.badges.GroupBadge*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.GroupBillableMember(manager: gitlab.base.RESTManager, attrs: Dict[str, Any],
*, created_from_list: bool = False)
```

Bases: [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type `None`

memberships: [GroupBillableMemberMembershipManager](#)

```
class gitlab.v4.objects.GroupBillableMemberManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.ListMixin](#), [gitlab.mixins.DeleteMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- `search`
- `sort`

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type `None`

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.GroupBillableMemberMembership(manager: gitlab.base.RESTManager, attrs:
Dict[str, Any], *, created_from_list: bool =
False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type `None`

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.GroupBillableMemberMembershipManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] =
None)
```

Bases: [gitlab.mixins.ListMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type None**gitlab:** `gitlab.client.Gitlab`

```
class gitlab.v4.objects.GroupBoard(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                   created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`**Parameters**

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (*bool*) –

Return type None**lists:** `gitlab.v4.objects.boards.GroupBoardListManager`

```
class gitlab.v4.objects.GroupBoardList(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                       created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`**Parameters**

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (*bool*) –

Return type None**manager:** `gitlab.base.RESTManager`

```
class gitlab.v4.objects.GroupBoardListManager(gl: gitlab.client.Gitlab, parent:
                                              Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`**Object Creation****Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type None**get** (*id*: `Union[str, int]`, *lazy*: *bool* = *False*, ***kwargs*: *Any*) → `gitlab.v4.objects.boards.GroupBoardList`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.boards.GroupBoardList*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.GroupBoardManager(gl: gitlab.client.Gitlab, parent:
                                         Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.boards.GroupBoard
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.boards.GroupBoard*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.GroupCluster(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –

- **created_from_list** (*bool*) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.GroupClusterManager`(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: `gitlab.mixins.CRUDMixin, gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

create(*data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → `gitlab.v4.objects.clusters.GroupCluster`

Create a new object.

Parameters

- **data** (`Optional[Dict[str, Any]]`) – Parameters to send to the server to create the resource
- ****kwargs** – Extra options to send to the server (e.g. `sudo` or `'ref_name'`, `'stage'`, `'name'`, `'all'`)
- **kwargs** (*Any*) –

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

Returns

A new instance of the manage object class build with the data sent by the server

Return type `gitlab.v4.objects.clusters.GroupCluster`

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → `gitlab.v4.objects.clusters.GroupCluster`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type *gitlab.v4.objects.clusters.GroupCluster*

gitlab: *gitlab.client.Gitlab*

class gitlab.v4.objects.GroupCustomAttribute(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

class gitlab.v4.objects.GroupCustomAttributeManager(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.RetrieveMixin, gitlab.mixins.SetMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.custom_attributes.GroupCustomAttribute*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.custom_attributes.GroupCustomAttribute*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.GroupDeployToken(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                          created_from_list: bool = False)
```

Bases: [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.GroupDeployTokenManager(gl: gitlab.client.Gitlab, parent:
                                                Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.mixins.CreateMixin](#), [gitlab.mixins.DeleteMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type [None](#)

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) →
    gitlab.v4.objects.deploy_tokens.GroupDeployToken
```

Retrieve a single object.

Parameters

- **id** ([Union\[str, int\]](#)) – ID of the object to retrieve
- **lazy** ([bool](#)) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** ([Any](#)) –

Returns The generated [RESTObject](#).

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [gitlab.v4.objects.deploy_tokens.GroupDeployToken](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.GroupDescendantGroup(manager: gitlab.base.RESTManager, attrs: Dict[str,
                                                                                          Any], *, created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.GroupDescendantGroupManager`(*gl*: `gitlab.client.Gitlab`, *parent*: `Optional[gitlab.base.RESTObject] = None`)

Bases: `gitlab.v4.objects.groups.GroupSubgroupManager`

This manager inherits from `GroupSubgroupManager` as descendant groups share all attributes with subgroups, except the path and object class.

Object listing filters

- `skip_groups`
- `all_available`
- `search`
- `order_by`
- `sort`
- `statistics`
- `owned`
- `with_custom_attributes`
- `min_access_level`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

class `gitlab.v4.objects.GroupEpic`(*manager*: `gitlab.base.RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`)

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.mixins.SaveMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

issues: `GroupEpicIssueManager`

resourcelabelevents: `gitlab.v4.objects.events.GroupEpicResourceLabelEventManager`

```
class gitlab.v4.objects.GroupEpicAwardEmoji(manager: gitlab.base.RESTManager, attrs: Dict[str, Any],
*, created_from_list: bool = False)
```

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.GroupEpicAwardEmojiManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.NoUpdateMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) →
gitlab.v4.objects.award_emojis.GroupEpicAwardEmoji
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.award_emojis.GroupEpicAwardEmoji`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.GroupEpicDiscussionNote(manager: gitlab.base.RESTManager, attrs: Dict[str,
Any], *, created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –

- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

class *gitlab.v4.objects.GroupEpicDiscussionNoteManager*(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.GetMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.notes.GroupEpicDiscussionNote*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.notes.GroupEpicDiscussionNote*

gitlab: *gitlab.client.Gitlab*

class *gitlab.v4.objects.GroupEpicIssue*(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.mixins.SaveMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.v4.objects.epics.GroupEpicIssueManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *GroupEpicIssueManager*

save(**kwargs: Any) → None

Save the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabUpdateError* – If the server cannot perform the request

Return type None

```
class gitlab.v4.objects.GroupEpicIssueManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.ListMixin*, *gitlab.mixins.CreateMixin*, *gitlab.mixins.UpdateMixin*, *gitlab.mixins.DeleteMixin*, *gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

create(data: *Optional[Dict[str, Any]]* = None, **kwargs: Any) → *gitlab.v4.objects.epics.GroupEpicIssue*

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – Parameters to send to the server to create the resource
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabCreateError* – If the server cannot perform the request

Returns

A new instance of the manage object class build with the data sent by the server

Return type *gitlab.v4.objects.epics.GroupEpicIssue*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.GroupEpicManager(gl: gitlab.client.Gitlab, parent:
    Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin*, *gitlab.base.RESTManager*

Object listing filters

- `author_id`
- `labels`
- `order_by`
- `sort`
- `search`

Object Creation

Object update

Parameters

- `gl` (*gitlab.client.Gitlab*) –
- `parent` (*Optional[gitlab.base.RESTObject]*) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.epics.GroupEpic
```

Retrieve a single object.

Parameters

- `id` (*Union[str, int]*) – ID of the object to retrieve
- `lazy` (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` – Extra options to send to the server (e.g. sudo)
- `kwargs` (*Any*) –

Returns The generated RESTObject.

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.epics.GroupEpic*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.GroupEpicNote(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
    created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin*, *gitlab.mixins.ObjectDeleteMixin*, *gitlab.base.RESTObject*

Parameters

- `manager` (*gitlab.base.RESTManager*) –
- `attrs` (*Dict[str, Any]*) –
- `created_from_list` (*bool*) –

Return type `None`

awardemojis: [`gitlab.v4.objects.award\_emojis.GroupEpicNoteAwardEmojiManager`](#)

class `gitlab.v4.objects.GroupEpicNoteAwardEmoji`(*manager*: [`gitlab.base.RESTManager`](#), *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`)

Bases: [`gitlab.mixins.ObjectDeleteMixin`](#), [`gitlab.base.RESTObject`](#)

Parameters

- **manager** ([`gitlab.base.RESTManager`](#)) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: [`gitlab.base.RESTManager`](#)

class `gitlab.v4.objects.GroupEpicNoteAwardEmojiManager`(*gl*: [`gitlab.client.Gitlab`](#), *parent*: [`Optional\[gitlab.base.RESTObject\]`](#) = `None`)

Bases: [`gitlab.mixins.NoUpdateMixin`](#), [`gitlab.base.RESTManager`](#)

Object Creation

Object update

Parameters

- **gl** ([`gitlab.client.Gitlab`](#)) –
- **parent** ([`Optional\[gitlab.base.RESTObject\]`](#)) –

Return type `None`

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → [`gitlab.v4.objects.award\_emojis.GroupEpicNoteAwardEmoji`](#)

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the server cannot perform the request

Return type [`gitlab.v4.objects.award\_emojis.GroupEpicNoteAwardEmoji`](#)

gitlab: [`gitlab.client.Gitlab`](#)

```
class gitlab.v4.objects.GroupEpicNoteManager(gl: gitlab.client.Gitlab, parent:
                                             Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.CRUDMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional*[[gitlab.base.RESTObject](#)]) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.notes.GroupEpicNote
```

Retrieve a single object.

Parameters

- **id** (*Union*[`str`, `int`]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated `RESTObject`.

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [gitlab.v4.objects.notes.GroupEpicNote](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.GroupEpicResourceLabelEvent(manager: gitlab.base.RESTManager, attrs:
                                                    Dict[str, Any], *, created_from_list: bool =
                                                    False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict*[`str`, `Any`]) –
- **created_from_list** (*bool*) –

Return type `None`

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.GroupEpicResourceLabelEventManager(gl: gitlab.client.Gitlab, parent:
                                                           Optional[gitlab.base.RESTObject] =
                                                           None)
```

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.events.GroupEpicResourceLabelEvent*

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated `RESTObject`.**Raises**

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type *gitlab.v4.objects.events.GroupEpicResourceLabelEvent***gitlab:** *gitlab.client.Gitlab*

```
class gitlab.v4.objects.GroupExport(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                   created_from_list: bool = False)
```

Bases: *gitlab.mixins.DownloadMixin, gitlab.base.RESTObject***Parameters**

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`**manager:** *gitlab.base.RESTManager*

```
class gitlab.v4.objects.GroupExportManager(gl: gitlab.client.Gitlab, parent:
                                           Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.GetWithoutIdMixin, gitlab.mixins.CreateMixin, gitlab.base.RESTManager***Object Creation****Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id: Optional[Union[int, str]] = None, **kwargs: Any*) → *Optional[gitlab.v4.objects.export_import.GroupExport]*

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.export_import.GroupExport]*

gitlab: *gitlab.client.Gitlab*

class *gitlab.v4.objects.GroupHook*(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

class *gitlab.v4.objects.GroupHookManager*(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.hooks.GroupHook*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)

- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.hooks.GroupHook*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.GroupImport(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                   created_from_list: bool = False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.GroupImportManager(gl: gitlab.client.Gitlab, parent:
                                           Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.GetWithoutIdMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) →
Optional[gitlab.v4.objects.export_import.GroupImport]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.export_import.GroupImport]*

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.GroupIssue(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                   created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict](#)[[str](#), [Any](#)]) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.GroupIssueManager(gl: gitlab.client.Gitlab, parent:
                                          Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.ListMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- state
- labels
- milestone
- order_by
- sort
- iids
- author_id
- assignee_id
- my_reaction_emoji
- search
- created_after
- created_before
- updated_after
- updated_before

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional](#)[[gitlab.base.RESTObject](#)]) –

Return type [None](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.GroupIssuesStatistics(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [gitlab.mixins.RefreshMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.GroupIssuesStatisticsManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.GetWithoutIdMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type [None](#)

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) → Optional[gitlab.v4.objects.statistics.GroupIssuesStatistics]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** ([Optional\[Union\[int, str\]\]](#)) –
- **kwargs** ([Any](#)) –

Returns The generated [RESTObject](#)

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [Optional\[gitlab.v4.objects.statistics.GroupIssuesStatistics\]](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.GroupLabel(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [gitlab.mixins.SubscribableMixin](#), [gitlab.mixins.SaveMixin](#), [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.v4.objects.labels.GroupLabelManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –

- **created_from_list** (*bool*) –

Return type `None`

manager: `GroupLabelManager`

save(***kwargs: Any*) → `None`

Saves the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Raises

- `GitlabAuthenticationError` – If authentication is not correct.
- `GitlabUpdateError` – If the server cannot perform the request.

Return type `None`

```
class gitlab.v4.objects.GroupLabelManager(gl: gitlab.client.Gitlab, parent:
                                         Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → `gitlab.v4.objects.labels.GroupLabel`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Returns The generated `RESTObject`.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type `gitlab.v4.objects.labels.GroupLabel`

gitlab: `gitlab.client.Gitlab`

update(*name: Optional[str], new_data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → Dict[str, Any]

Update a Label on the server.

Parameters

- **name** (*Optional[str]*) – The name of the label
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **new_data** (*Optional[Dict[str, Any]]*) –
- **kwargs** (*Any*) –

Return type *Dict[str, Any]*

class gitlab.v4.objects.**GroupManager**(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object listing filters

- skip_groups
- all_available
- search
- order_by
- sort
- statistics
- owned
- with_custom_attributes
- min_access_level
- top_level_only

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.groups.Group*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type `gitlab.v4.objects.groups.Group`

gitlab: `gitlab.client.Gitlab`

```
import_group(file: BinaryIO, path: str, name: str, parent_id: Optional[str] = None, **kwargs: Any) → Union[Dict[str, Any], requests.models.Response]
```

Import a group from an archive file.

Parameters

- **file** (`BinaryIO`) – Data or file object containing the group
- **path** (`str`) – The path for the new group to be imported.
- **name** (`str`) – The name for the new group.
- **parent_id** (`Optional[str]`) – ID of a parent group that the group will be imported into.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabImportError`** – If the server failed to perform the request

Returns A representation of the import status.

Return type `Union[Dict[str, Any], requests.models.Response]`

```
class gitlab.v4.objects.GroupMember(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.GroupMemberAll(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type None

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.GroupMemberAllManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type None

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → `gitlab.v4.objects.members.GroupMemberAll`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type `gitlab.v4.objects.members.GroupMemberAll`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.GroupMemberManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type None

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → `gitlab.v4.objects.members.GroupMember`

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.members.GroupMember*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.GroupMergeRequest(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                           created_from_list: bool = False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.GroupMergeRequestManager(gl: gitlab.client.Gitlab, parent:
                                                  Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.ListMixin, gitlab.base.RESTManager*

Object listing filters

- state
- order_by
- sort
- milestone
- view
- labels
- created_after
- created_before
- updated_after
- updated_before
- scope
- author_id
- assignee_id

- `approver_ids`
- `approved_by_ids`
- `my_reaction_emoji`
- `source_branch`
- `target_branch`
- `search`
- `wip`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.GroupMilestone(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                       created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (*Dict* [`str`, `Any`]) –
- `created_from_list` (*bool*) –

Return type `None`

issues (***kwargs*: `Any`) → `gitlab.base.RESTObjectList`

List issues related to this milestone.

Parameters

- `all` – If True, return all the items, without pagination
- `per_page` – Number of items to retrieve per request
- `page` – ID of the page to return (starts with page 1)
- `as_list` – If set to False and no pagination option is defined, return a generator instead of a list
- ***kwargs* – Extra options to send to the server (e.g. `sudo`)
- `kwargs` (*Any*) –

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the list could not be retrieved

Returns The list of issues

Return type `gitlab.base.RESTObjectList`

manager: *gitlab.base.RESTManager*

merge_requests(**kwargs: Any) → *gitlab.base.RESTObjectList*

List the merge requests related to this milestone.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabListError* – If the list could not be retrieved

Returns The list of merge requests

Return type *gitlab.base.RESTObjectList*

class `gitlab.v4.objects.GroupMilestoneManager`(gl: *gitlab.client.Gitlab*, parent: *Optional[gitlab.base.RESTObject]* = None)

Bases: *gitlab.mixins.CRUDMixin*, *gitlab.base.RESTManager*

Object listing filters

- **iids**
- **state**
- **search**

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

get(id: *Union[str, int]*, lazy: *bool* = False, **kwargs: Any) → *gitlab.v4.objects.milestones.GroupMilestone*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.milestones.GroupMilestone*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.GroupNotificationSettings(manager: gitlab.base.RESTManager, attrs:
                                                Dict[str, Any], *, created_from_list: bool = False)
```

Bases: *gitlab.v4.objects.notification_settings.NotificationSettings*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.GroupNotificationSettingsManager(gl: gitlab.client.Gitlab, parent:
                                                         Optional[gitlab.base.RESTObject] =
                                                         None)
```

Bases: *gitlab.v4.objects.notification_settings.NotificationSettingsManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) →
Optional[gitlab.v4.objects.notification_settings.GroupNotificationSettings]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.notification_settings.GroupNotificationSettings]*

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.GroupPackage(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type `None`

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.GroupPackageManager(gl: gitlab.client.Gitlab, parent:
                                             Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.ListMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- `exclude_subgroups`
- `order_by`
- `sort`
- `package_type`
- `package_name`

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type `None`

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.GroupProject(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type `None`

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.GroupProjectManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.ListMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- archived
- visibility
- order_by
- sort
- search
- simple
- owned
- starred
- with_custom_attributes
- include_subgroups
- with_issues_enabled
- with_merge_requests_enabled
- with_shared
- min_access_level
- with_security_reports

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional*[[gitlab.base.RESTObject](#)]) –

Return type None

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.GroupRunner(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –

Return type None

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.GroupRunnerManager(gl: gitlab.client.Gitlab, parent:
                                         Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`

Object listing filters

- `scope`
- `tag_list`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.GroupSubgroup(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                       created_from_list: bool = False)
```

Bases: `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.GroupSubgroupManager(gl: gitlab.client.Gitlab, parent:
                                              Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`

Object listing filters

- `skip_groups`
- `all_available`
- `search`
- `order_by`
- `sort`
- `statistics`
- `owned`
- `with_custom_attributes`
- `min_access_level`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional*[`gitlab.base.RESTObject`]) –

Return type `None`

```
class gitlab.v4.objects.GroupVariable(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (*Dict*[`str`, `Any`]) –
- **created_from_list** (*bool*) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.GroupVariableManager(gl: gitlab.client.Gitlab, parent:
                                             Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object Creation**Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional*[`gitlab.base.RESTObject`]) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.variables.GroupVariable
```

Retrieve a single object.

Parameters

- **id** (*Union*[`str`, `int`]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated `RESTObject`.

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type `gitlab.v4.objects.variables.GroupVariable`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.GroupWiki(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                   created_from_list: bool = False)
```

Bases: [gitlab.mixins.SaveMixin](#), [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.GroupWikiManager(gl: gitlab.client.Gitlab, parent:
                                          Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.CRUDMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- **with_content**

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type [None](#)

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.wikis.GroupWiki
```

Retrieve a single object.

Parameters

- **id** ([Union\[str, int\]](#)) – ID of the object to retrieve
- **lazy** ([bool](#)) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** ([Any](#)) –

Returns The generated RESTObject.

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [gitlab.v4.objects.wikis.GroupWiki](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.Hook(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                              created_from_list: bool = False)
```

Bases: [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.HookManager`(*gl*: `gitlab.client.Gitlab`, *parent*: `Optional[gitlab.base.RESTObject]` = `None`)

Bases: `gitlab.mixins.NoUpdateMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id*: `Union[str, int]`, *lazy*: `bool` = `False`, ***kwargs*: `Any`) → `gitlab.v4.objects.hooks.Hook`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (`Any`) –

Returns The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.hooks.Hook`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.Issue`(*manager*: `gitlab.base.RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool` = `False`)

Bases: `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.IssueManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- `state`
- `labels`
- `milestone`
- `scope`
- `author_id`
- `assignee_id`
- `my_reaction_emoji`
- `iids`
- `order_by`
- `sort`
- `search`
- `created_after`
- `created_before`
- `updated_after`
- `updated_before`

Object Creation

Object update

Parameters

- `gl` ([gitlab.client.Gitlab](#)) –
- `parent` ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.issues.Issue
```

Retrieve a single object.

Parameters

- `id` ([Union\[str, int\]](#)) – ID of the object to retrieve
- `lazy` ([bool](#)) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` – Extra options to send to the server (e.g. `sudo`)
- `kwargs` ([Any](#)) –

Returns The generated [RESTObject](#).

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type *gitlab.v4.objects.issues.Issue*

gitlab: *gitlab.client.Gitlab*

class *gitlab.v4.objects.IssuesStatistics*(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.RefreshMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

class *gitlab.v4.objects.IssuesStatisticsManager*(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.GetWithoutIdMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get(*id: Optional[Union[int, str]] = None, **kwargs: Any*) → *Optional[gitlab.v4.objects.statistics.IssuesStatistics]*

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.statistics.IssuesStatistics]*

gitlab: *gitlab.client.Gitlab*

class *gitlab.v4.objects.Key*(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.KeyManager`(*gl*: `gitlab.client.Gitlab`, *parent*: `Optional[gitlab.base.RESTObject]` = `None`)

Bases: `gitlab.mixins.GetMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id*: `Optional[Union[int, str]]` = `None`, *lazy*: `bool` = `False`, ***kwargs*: `Any`) → `gitlab.v4.objects.keys.Key`

Retrieve a single object.

Parameters

- **id** (`Optional[Union[int, str]]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (`Any`) –

Returns The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.keys.Key`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.LDAPGroup`(*manager*: `gitlab.base.RESTManager`, *attrs*: `Dict[str, Any]`, ***, *created_from_list*: `bool` = `False`)

Bases: `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.LDAPGroupManager(gl: gitlab.client.Gitlab, parent:
                                     Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.base.RESTManager](#)

Object listing filters

- search
- provider

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional*[[gitlab.base.RESTObject](#)]) –

Return type `None`

gitlab: [gitlab.client.Gitlab](#)

list(**kwargs: Any) → Union[List[[gitlab.v4.objects ldap.LDAPGroup](#)], [gitlab.base.RESTObjectList](#)]

Retrieve a list of objects.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The list of objects, or a generator if *as_list* is False

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabListError](#) – If the server cannot perform the request

Return type *Union*[List[[gitlab.v4.objects ldap.LDAPGroup](#)], [gitlab.base.RESTObjectList](#)]

```
class gitlab.v4.objects.License(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict*[*str*, Any]) –
- **created_from_list** (*bool*) –

Return type `None`

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.LicenseManager(gl: gitlab.client.Gitlab, parent:
    Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- popular

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional*[[gitlab.base.RESTObject](#)]) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.templates.License
```

Retrieve a single object.

Parameters

- **id** (*Union*[`str`, `int`]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [gitlab.v4.objects.templates.License](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.MergeRequest(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
    created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict*[`str`, *Any*]) –
- **created_from_list** (*bool*) –

Return type `None`

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.MergeRequestManager(gl: gitlab.client.Gitlab, parent:
    Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.ListMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- state
- order_by
- sort
- milestone
- view
- labels
- with_labels_details
- with_merge_status_recheck
- created_after
- created_before
- updated_after
- updated_before
- scope
- author_id
- author_username
- assignee_id
- approver_ids
- approved_by_ids
- reviewer_id
- reviewer_username
- my_reaction_emoji
- source_branch
- target_branch
- search
- in
- wip
- not
- environment
- deployed_before
- deployed_after

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type None

gitlab: [gitlab.client.Gitlab](#)

class gitlab.v4.objects.Namespace(*manager*: [gitlab.base.RESTManager](#), *attrs*: *Dict[str, Any]*, *, *created_from_list*: *bool = False*)

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: [gitlab.base.RESTManager](#)

class gitlab.v4.objects.NamespaceManager(*gl*: [gitlab.client.Gitlab](#), *parent*: *Optional[gitlab.base.RESTObject] = None*)

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- **search**

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get(*id*: *Union[str, int]*, *lazy*: *bool = False*, ***kwargs*: *Any*) → *gitlab.v4.objects.namespaces.Namespace*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type *gitlab.v4.objects.namespaces.Namespace*

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.NotificationSettings(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [gitlab.mixins.SaveMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.NotificationSettingsManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.GetWithoutIdMixin](#), [gitlab.mixins.UpdateMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type [None](#)

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) → Optional[gitlab.v4.objects.notification_settings.NotificationSettings]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** ([Optional\[Union\[int, str\]\]](#)) –
- **kwargs** ([Any](#)) –

Returns The generated [RESTObject](#)

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [Optional\[gitlab.v4.objects.notification_settings.NotificationSettings\]](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.PagesDomain(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –

- `created_from_list` (*bool*) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.PagesDomainManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.PersonalAccessToken(manager: gitlab.base.RESTManager, attrs: Dict[str, Any],
*, created_from_list: bool = False)
```

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (*Dict* [`str`, `Any`]) –
- `created_from_list` (*bool*) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.PersonalAccessTokenManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.DeleteMixin`, `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`

Object listing filters

- `user_id`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.Project(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                created_from_list: bool = False)
```

Bases: [gitlab.mixins.RefreshMixin](#), [gitlab.mixins.SaveMixin](#), [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.v4.objects.repositories.RepositoryMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

access_tokens: [gitlab.v4.objects.project_access_tokens.ProjectAccessTokenManager](#)

accessrequests: [gitlab.v4.objects.access_requests.ProjectAccessRequestManager](#)

additionalstatistics:

[gitlab.v4.objects.statistics.ProjectAdditionalStatisticsManager](#)

approvalrules: [gitlab.v4.objects.merge_request_approvals.ProjectApprovalRuleManager](#)

approvals: [gitlab.v4.objects.merge_request_approvals.ProjectApprovalManager](#)

archive(**kwargs: Any) → [None](#)

Archive a project.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** ([Any](#)) –

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabCreateError](#) – If the server failed to perform the request

Return type [None](#)

artifact(*args: Any, **kwargs: Any) → [Optional\[bytes\]](#)

Parameters

- **args** ([Any](#)) –
- **kwargs** ([Any](#)) –

Return type [Optional\[bytes\]](#)

artifacts: [gitlab.v4.objects.artifacts.ProjectArtifactManager](#)

audit_events: [gitlab.v4.objects.audit_events.ProjectAuditEventManager](#)

badges: [gitlab.v4.objects.badges.ProjectBadgeManager](#)

boards: [gitlab.v4.objects.boards.ProjectBoardManager](#)

branches: [gitlab.v4.objects.branches.ProjectBranchManager](#)

clusters: *gitlab.v4.objects.clusters.ProjectClusterManager*

commits: *gitlab.v4.objects.commits.ProjectCommitManager*

create_fork_relation(*forked_from_id: int, **kwargs: Any*) → None

Create a forked from/to relation between existing projects.

Parameters

- **forked_from_id** (*int*) – The ID of the project that was forked from
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabCreateError* – If the relation could not be created

Return type None

customattributes: *gitlab.v4.objects.custom_attributes.ProjectCustomAttributeManager*

delete_fork_relation(***kwargs: Any*) → None

Delete a forked relation between existing projects.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabDeleteError* – If the server failed to perform the request

Return type None

deployments: *gitlab.v4.objects.deployments.ProjectDeploymentManager*

deploytokens: *gitlab.v4.objects.deploy_tokens.ProjectDeployTokenManager*

environments: *gitlab.v4.objects.environments.ProjectEnvironmentManager*

events: *gitlab.v4.objects.events.ProjectEventManager*

exports: *gitlab.v4.objects.export_import.ProjectExportManager*

files: *gitlab.v4.objects.files.ProjectFileManager*

forks: *ProjectForkManager*

generic_packages: *gitlab.v4.objects.packages.GenericPackageManager*

groups: *gitlab.v4.objects.projects.ProjectGroupManager*

hooks: *gitlab.v4.objects.hooks.ProjectHookManager*

housekeeping(**kwargs: Any) → None

Start the housekeeping task.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabHousekeepingError** – If the server failed to perform the request

Return type None

imports: `gitlab.v4.objects.export_import.ProjectImportManager`

issues: `gitlab.v4.objects.issues.ProjectIssueManager`

issues_statistics: `gitlab.v4.objects.statistics.ProjectIssuesStatisticsManager`

jobs: `gitlab.v4.objects.jobs.ProjectJobManager`

keys: `gitlab.v4.objects.deploy_keys.ProjectKeyManager`

labels: `gitlab.v4.objects.labels.ProjectLabelManager`

languages(**kwargs: Any) → Union[Dict[str, Any], requests.models.Response]

Get languages used in the project with percentage value.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Return type Union[Dict[str, Any], requests.models.Response]

members: `gitlab.v4.objects.members.ProjectMemberManager`

members_all: `gitlab.v4.objects.members.ProjectMemberAllManager`

merge_trains: `gitlab.v4.objects.merge_trains.ProjectMergeTrainManager`

mergerequests: `gitlab.v4.objects.merge_requests.ProjectMergeRequestManager`

milestones: `gitlab.v4.objects.milestones.ProjectMilestoneManager`

mirror_pull(**kwargs: Any) → None

Start the pull mirroring process for the project.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabCreateError`** – If the server failed to perform the request

Return type `None`

notes: `gitlab.v4.objects.notes.ProjectNoteManager`

notificationsettings:

`gitlab.v4.objects.notification_settings.ProjectNotificationSettingsManager`

packages: `gitlab.v4.objects.packages.ProjectPackageManager`

pagesdomains: `gitlab.v4.objects.pages.ProjectPagesDomainManager`

pipelines: `gitlab.v4.objects.pipelines.ProjectPipelineManager`

pipelineschedules: `gitlab.v4.objects.pipelines.ProjectPipelineScheduleManager`

protectedbranches: `gitlab.v4.objects.branches.ProjectProtectedBranchManager`

protectedtags: `gitlab.v4.objects.tags.ProjectProtectedTagManager`

pushrules: `gitlab.v4.objects.push_rules.ProjectPushRulesManager`

releases: `gitlab.v4.objects.releases.ProjectReleaseManager`

remote_mirrors: `ProjectRemoteMirrorManager`

repositories: `gitlab.v4.objects.container_registry.ProjectRegistryRepositoryManager`

runners: `gitlab.v4.objects.runners.ProjectRunnerManager`

search(*scope: str, search: str, **kwargs: Any*) → Union[`gitlab.client.GitlabList`, List[Dict[str, Any]]]

Search the project resources matching the provided string.

Parameters

- **scope** (*str*) – Scope of the search
- **search** (*str*) – Search string
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabSearchError`** – If the server failed to perform the request

Returns A list of dicts describing the resources found.

Return type Union[`gitlab.client.GitlabList`, List[Dict[str, Any]]]

services: `gitlab.v4.objects.services.ProjectServiceManager`

share(*group_id: int, group_access: int, expires_at: Optional[str] = None, **kwargs: Any*) → None

Share the project with a group.

Parameters

- **group_id** (*int*) – ID of the group.
- **group_access** (*int*) – Access level for the group.

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **expires_at** (*Optional[str]*) –
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server failed to perform the request

Return type None

snapshot (*wiki: bool = False, streamed: bool = False, action: Optional[Callable] = None, chunk_size: int = 1024, **kwargs: Any*) → *Optional[bytes]*

Return a snapshot of the repository.

Parameters

- **wiki** (*bool*) – If True return the wiki repository
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment.
- **action** (*Optional[Callable]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the content could not be retrieved

Returns The uncompressed tar archive of the repository

Return type *Optional[bytes]*

snippets: *gitlab.v4.objects.snippets.ProjectSnippetManager*

star (***kwargs: Any*) → None

Star a project.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server failed to perform the request

Return type None

storage: *ProjectStorageManager*

tags: *gitlab.v4.objects.tags.ProjectTagManager*

transfer(*to_namespace: Union[int, str], **kwargs: Any*) → None

Transfer a project to the given namespace ID

Parameters

- **to_namespace** (*Union[int, str]*) – ID or path of the namespace to transfer the
- **to** (*project*) –
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTransferProjectError** – If the project could not be transferred

Return type None

transfer_project(**args: Any, **kwargs: Any*) → None

Parameters

- **args** (*Any*) –
- **kwargs** (*Any*) –

Return type None

trigger_pipeline(*ref: str, token: str, variables: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *gitlab.v4.objects.pipelines.ProjectPipeline*

Trigger a CI build.

See <https://gitlab.com/help/ci/triggers/README.md#trigger-a-build>

Parameters

- **ref** (*str*) – Commit to build; can be a branch name or a tag
- **token** (*str*) – The trigger token
- **variables** (*Optional[Dict[str, Any]]*) – Variables passed to the build script
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server failed to perform the request

Return type *gitlab.v4.objects.pipelines.ProjectPipeline*

triggers: *gitlab.v4.objects.triggers.ProjectTriggerManager*

unarchive(***kwargs: Any*) → None

Unarchive a project.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabDeleteError](#) – If the server failed to perform the request

Return type None

unshare(*group_id: int, **kwargs: Any*) → None

Delete a shared project link within a group.

Parameters

- **group_id** (*int*) – ID of the group.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabDeleteError](#) – If the server failed to perform the request

Return type None

unstar(***kwargs: Any*) → None

Unstar a project.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabDeleteError](#) – If the server failed to perform the request

Return type None

upload(*filename: str, filedata: Optional[bytes] = None, filepath: Optional[str] = None, **kwargs: Any*) → Dict[str, Any]

Upload the specified file into the project.

Note: Either filedata or filepath *MUST* be specified.

Parameters

- **filename** (*str*) – The name of the file being uploaded
- **filedata** (*Optional[bytes]*) – The raw data of the file being uploaded
- **filepath** (*Optional[str]*) – The path to a local file to upload (optional)
- **kwargs** (*Any*) –

Raises

- [GitlabConnectionError](#) – If the server cannot be reached
- [GitlabUploadError](#) – If the file upload fails
- [GitlabUploadError](#) – If filedata and filepath are not specified

- `GitlabUploadError` – If both `filedata` and `filepath` are specified

Returns

- `alt` - The alternate text for the upload
- `url` - The direct url to the uploaded file
- `markdown` - Markdown for the uploaded file

Return type A dict with the keys

users: `gitlab.v4.objects.users.ProjectUserManager`

variables: `gitlab.v4.objects.variables.ProjectVariableManager`

wikis: `gitlab.v4.objects.wikis.ProjectWikiManager`

class `gitlab.v4.objects.ProjectAccessRequest`(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: `gitlab.mixins.AccessRequestMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.ProjectAccessRequestManager`(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object Creation**Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.ProjectAccessToken`(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type None

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectAccessTokenManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type None

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectAdditionalStatistics(manager: gitlab.base.RESTManager, attrs:
Dict[str, Any], *, created_from_list: bool =
False)
```

Bases: `gitlab.mixins.RefreshMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type None

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectAdditionalStatisticsManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] =
None)
```

Bases: `gitlab.mixins.GetWithoutIdMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type None

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) →
Optional[gitlab.v4.objects.statistics.ProjectAdditionalStatistics]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)

- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.statistics.ProjectAdditionalStatistics]*

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.ProjectApproval(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                         created_from_list: bool = False)
```

Bases: [gitlab.mixins.SaveMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.ProjectApprovalManager(gl: gitlab.client.Gitlab, parent:
                                                Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.GetWithoutIdMixin](#), [gitlab.mixins.UpdateMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) →
Optional[gitlab.v4.objects.merge_request_approvals.ProjectApproval]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabGetError** – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.merge_request_approvals.ProjectApproval]*

gitlab: *gitlab.client.Gitlab*

set_approvers(*approver_ids: Optional[List[int]] = None, approver_group_ids: Optional[List[int]] = None, **kwargs: Any*) → Dict[str, Any]

Change project-level allowed approvers and approver groups.

Parameters

- **approver_ids** (*Optional[List[int]]*) – User IDs that can approve MRs
- **approver_group_ids** (*Optional[List[int]]*) – Group IDs whose members can approve MRs
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server failed to perform the request

Returns A dict value of the result

Return type *Dict[str, Any]*

class gitlab.v4.objects.**ProjectApprovalRule**(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

class gitlab.v4.objects.**ProjectApprovalRuleManager**(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.ListMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectArtifact(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                         created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Dummy object to manage custom actions on artifacts

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.ProjectArtifactManager(gl: gitlab.client.Gitlab, parent:
                                              Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

delete(***kwargs: Any*) → *None*

Delete the project's artifacts on the server.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabDeleteError](#) – If the server cannot perform the request

Return type *None*

```
download(ref_name: str, job: str, streamed: bool = False, action: Optional[Callable] = None, chunk_size:
         int = 1024, **kwargs: Any) → Optional[bytes]
```

Get the job artifacts archive from a specific tag or branch.

Parameters

- **ref_name** (*str*) – Branch or tag name in repository. HEAD or SHA references
- **supported.** (*are not*) –
- **job** (*str*) – The name of the job.
- **job_token** – Job token for multi-project pipeline triggers.
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment

- **action** (*Optional[Callable]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns The artifacts if *streamed* is False, None otherwise.

Return type *Optional[bytes]*

gitlab: [gitlab.client.Gitlab](#)

raw(*ref_name: str, artifact_path: str, job: str, streamed: bool = False, action: Optional[Callable] = None, chunk_size: int = 1024, **kwargs: Any*) → *Optional[bytes]*

Download a single artifact file from a specific tag or branch from within the job's artifacts archive.

Parameters

- **ref_name** (*str*) – Branch or tag name in repository. HEAD or SHA references are not supported.
- **artifact_path** (*str*) – Path to a file inside the artifacts archive.
- **job** (*str*) – The name of the job.
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **action** (*Optional[Callable]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns The artifact if *streamed* is False, None otherwise.

Return type *Optional[bytes]*

class `gitlab.v4.objects.ProjectAudit`(*manager: [gitlab.base.RESTManager](#), attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: [gitlab.v4.objects.audit_events.ProjectAuditEvent](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type None

manager: [`gitlab.base.RESTManager`](#)

class `gitlab.v4.objects.ProjectAuditEvent`(*manager: [`gitlab.base.RESTManager`](#), *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*)*

Bases: [`gitlab.base.RESTObject`](#)

Parameters

- **manager** ([`gitlab.base.RESTManager`](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type `None`

manager: [`gitlab.base.RESTManager`](#)

class `gitlab.v4.objects.ProjectAuditEventManager`(*gl: [`gitlab.client.Gitlab`](#), *parent: Optional[[`gitlab.base.RESTObject`](#)] = None*)*

Bases: [`gitlab.mixins.RetrieveMixin`](#), [`gitlab.base.RESTManager`](#)

Object listing filters

- **created_after**
- **created_before**

Object Creation

Object update

Parameters

- **gl** ([`gitlab.client.Gitlab`](#)) –
- **parent** (*Optional[[`gitlab.base.RESTObject`](#)]*) –

Return type `None`

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [`gitlab.v4.objects.audit\_events.ProjectAuditEvent`](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the server cannot perform the request

Return type [`gitlab.v4.objects.audit\_events.ProjectAuditEvent`](#)

gitlab: [`gitlab.client.Gitlab`](#)

```
class gitlab.v4.objects.ProjectAuditManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.v4.objects.audit_events.ProjectAuditEventManager`

Object listing filters

- `created_after`
- `created_before`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectBadge(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectBadgeManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.BadgeRenderMixin`, `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.badges.ProjectBadge`

Retrieve a single object.

Parameters

- `id` (`Union[str, int]`) – ID of the object to retrieve
- `lazy` (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` – Extra options to send to the server (e.g. sudo)

- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.badges.ProjectBadge*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectBoard(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

lists: *gitlab.v4.objects.boards.ProjectBoardListManager*

```
class gitlab.v4.objects.ProjectBoardList(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                          created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectBoardListManager(gl: gitlab.client.Gitlab, parent:
                                                Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get (*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.boards.ProjectBoardList*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.boards.ProjectBoardList*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectBoardManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.boards.ProjectBoard
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.boards.ProjectBoard*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectBranch(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
created_from_list: bool = False)
```

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.ProjectBranchManager`(*gl*: `gitlab.client.Gitlab`, *parent*: `Optional[gitlab.base.RESTObject] = None`)

Bases: `gitlab.mixins.NoUpdateMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → `gitlab.v4.objects.branches.ProjectBranch`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (`Any`) –

Returns The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.branches.ProjectBranch`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.ProjectCluster`(*manager*: `gitlab.base.RESTManager`, *attrs*: `Dict[str, Any]`, ***, *created_from_list*: `bool = False`)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectClusterManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin*, *gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → gitlab.v4.objects.clusters.ProjectCluster
```

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – Parameters to send to the server to create the resource
- ****kwargs** – Extra options to send to the server (e.g. `sudo` or `'ref_name'`, `'stage'`, `'name'`, `'all'`)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabCreateError* – If the server cannot perform the request

Returns

A new instance of the manage object class build with the data sent by the server

Return type *gitlab.v4.objects.clusters.ProjectCluster*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.clusters.ProjectCluster
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.clusters.ProjectCluster*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectCommit(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

```
cherry_pick(branch: str, **kwargs: Any) → None
```

Cherry-pick a commit into a branch.

Parameters

- **branch** (*str*) – Name of target branch
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabCherryPickError](#) – If the cherry-pick could not be performed

Return type *None*

comments: [ProjectCommitCommentManager](#)

```
diff(**kwargs: Any) → Union[gitlab.client.GitlabList, List[Dict[str, Any]]]
```

Generate the commit diff.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the diff could not be retrieved

Returns The changes done in this commit

Return type *Union[gitlab.client.GitlabList, List[Dict[str, Any]]]*

discussions: [gitlab.v4.objects.discussions.ProjectCommitDiscussionManager](#)

```
merge_requests(**kwargs: Any) → Union[gitlab.client.GitlabList, List[Dict[str, Any]]]
```

List the merge requests related to the commit.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct

- **GitlabGetError** – If the references could not be retrieved

Returns The merge requests related to the commit.

Return type `Union[gitlab.client.GitlabList, List[Dict[str, Any]]]`

refs(*type*: *str* = 'all', ***kwargs*: *Any*) → `Union[gitlab.client.GitlabList, List[Dict[str, Any]]]`

List the references the commit is pushed to.

Parameters

- **type** (*str*) – The scope of references ('branch', 'tag' or 'all')
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the references could not be retrieved

Returns The references the commit is pushed to.

Return type `Union[gitlab.client.GitlabList, List[Dict[str, Any]]]`

revert(*branch*: *str*, ***kwargs*: *Any*) → `Union[Dict[str, Any], requests.models.Response]`

Revert a commit on a given branch.

Parameters

- **branch** (*str*) – Name of target branch
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabRevertError** – If the revert could not be performed

Returns The new commit data (*not* a RESTObject)

Return type `Union[Dict[str, Any], requests.models.Response]`

signature(***kwargs*: *Any*) → `Union[Dict[str, Any], requests.models.Response]`

Get the signature of the commit.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the signature could not be retrieved

Returns The commit's signature data

Return type `Union[Dict[str, Any], requests.models.Response]`

statuses: [*ProjectCommitStatusManager*](#)

```
class gitlab.v4.objects.ProjectCommitComment(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.ProjectCommitCommentManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.ListMixin](#), [gitlab.mixins.CreateMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type [None](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.ProjectCommitDiscussion(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

notes: [gitlab.v4.objects.notes.ProjectCommitDiscussionNoteManager](#)

```
class gitlab.v4.objects.ProjectCommitDiscussionManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.mixins.CreateMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type [None](#)

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) →
gitlab.v4.objects.discussions.ProjectCommitDiscussion

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.discussions.ProjectCommitDiscussion*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectCommitDiscussionNote(manager: gitlab.base.RESTManager, attrs:
    Dict[str, Any], *, created_from_list: bool =
    False)
```

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (gitlab.base.RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –

Return type None

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectCommitDiscussionNoteManager(gl: gitlab.client.Gitlab, parent:
    Optional[gitlab.base.RESTObject] =
    None)
```

Bases: *gitlab.mixins.GetMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (gitlab.client.Gitlab) –
- **parent** (Optional[gitlab.base.RESTObject]) –

Return type None

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → *gitlab.v4.objects.notes.ProjectCommitDiscussionNote*

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.notes.ProjectCommitDiscussionNote*

gitlab: *gitlab.client.Gitlab*

class gitlab.v4.objects.**ProjectCommitManager**(*gl*: gitlab.client.Gitlab, *parent*: Optional[gitlab.base.RESTObject] = None)

Bases: *gitlab.mixins.RetrieveMixin*, *gitlab.mixins.CreateMixin*, *gitlab.base.RESTManager*

Object listing filters

- *ref_name*
- *since*
- *until*
- *path*
- *with_stats*
- *first_parent*
- *order*
- *trailers*

Object Creation

Object update

Parameters

- **gl** (gitlab.client.Gitlab) –
- **parent** (Optional[gitlab.base.RESTObject]) –

Return type None

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → *gitlab.v4.objects.commits.ProjectCommit*

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.commits.ProjectCommit*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectCommitStatus(manager: gitlab.base.RESTManager, attrs: Dict[str, Any],
*, created_from_list: bool = False)
```

Bases: *gitlab.mixins.RefreshMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectCommitStatusManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.ListMixin, gitlab.mixins.CreateMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) →
gitlab.v4.objects.commits.ProjectCommitStatus
```

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – Parameters to send to the server to create the resource
- ****kwargs** – Extra options to send to the server (e.g. sudo or 'ref_name', 'stage', 'name', 'all')
- **kwargs** (*Any*) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabCreateError`](#) – If the server cannot perform the request

Returns

A new instance of the manage object class build with the data sent by the server

Return type `gitlab.v4.objects.commits.ProjectCommitStatus`

gitlab: [`gitlab.client.Gitlab`](#)

```
class gitlab.v4.objects.ProjectCustomAttribute(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [`gitlab.mixins.ObjectDeleteMixin`](#), [`gitlab.base.RESTObject`](#)

Parameters

- **manager** ([`gitlab.base.RESTManager`](#)) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: [`gitlab.base.RESTManager`](#)

```
class gitlab.v4.objects.ProjectCustomAttributeManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: [`gitlab.mixins.RetrieveMixin`](#), [`gitlab.mixins.SetMixin`](#), [`gitlab.mixins.DeleteMixin`](#), [`gitlab.base.RESTManager`](#)

Object Creation**Object update****Parameters**

- **gl** ([`gitlab.client.Gitlab`](#)) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.custom_attributes.ProjectCustomAttribute
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the server cannot perform the request

Return type *gitlab.v4.objects.custom_attributes.ProjectCustomAttribute*

gitlab: *gitlab.client.Gitlab*

class gitlab.v4.objects.**ProjectDeployToken**(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

class gitlab.v4.objects.**ProjectDeployTokenManager**(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.deploy_tokens.ProjectDeployToken*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.deploy_tokens.ProjectDeployToken*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectDeployment(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                          created_from_list: bool = False)
```

Bases: [gitlab.mixins.SaveMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

mergerequests:

[gitlab.v4.objects.merge_requests.ProjectDeploymentMergeRequestManager](#)

```
class gitlab.v4.objects.ProjectDeploymentManager(gl: gitlab.client.Gitlab, parent:
                                                Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.mixins.CreateMixin](#), [gitlab.mixins.UpdateMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- **order_by**
- **sort**
- **updated_after**
- **updated_before**
- **environment**
- **status**

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type [None](#)

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) →
    gitlab.v4.objects.deployments.ProjectDeployment
```

Retrieve a single object.

Parameters

- **id** ([Union\[str, int\]](#)) – ID of the object to retrieve
- **lazy** ([bool](#)) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** ([Any](#)) –

Returns The generated [RESTObject](#).

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type `gitlab.v4.objects.deployments.ProjectDeployment`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.ProjectDeploymentMergeRequest` (*manager:* `gitlab.base.RESTManager`, *attrs:* `Dict[str, Any], *, created_from_list: bool = False`)

Bases: `gitlab.v4.objects.merge_requests.MergeRequest`

Parameters

- **`manager`** (`gitlab.base.RESTManager`) –
- **`attrs`** (`Dict[str, Any]`) –
- **`created_from_list`** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.ProjectDeploymentMergeRequestManager` (*gl:* `gitlab.client.Gitlab`, *parent:* `Optional[gitlab.base.RESTObject] = None`)

Bases: `gitlab.v4.objects.merge_requests.MergeRequestManager`

Object listing filters

- `state`
- `order_by`
- `sort`
- `milestone`
- `view`
- `labels`
- `with_labels_details`
- `with_merge_status_recheck`
- `created_after`
- `created_before`
- `updated_after`
- `updated_before`
- `scope`
- `author_id`
- `author_username`
- `assignee_id`
- `approver_ids`
- `approved_by_ids`

- reviewer_id
- reviewer_username
- my_reaction_emoji
- source_branch
- target_branch
- search
- in
- wip
- not
- environment
- deployed_before
- deployed_after

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectEnvironment(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                           created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (*bool*) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
stop(**kwargs: Any) → Union[Dict[str, Any], requests.models.Response]
```

Stop the environment.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabStopError` – If the operation failed

Returns A dict of the result.

Return type `Union[Dict[str, Any], requests.models.Response]`

```
class gitlab.v4.objects.ProjectEnvironmentManager(gl: gitlab.client.Gitlab, parent:
                                                Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object listing filters

- name
- search
- states

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) →
gitlab.v4.objects.environments.ProjectEnvironment
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.environments.ProjectEnvironment`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectEvent(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: `gitlab.v4.objects.events.Event`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type None

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectEventManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.v4.objects.events.EventManager`

Object listing filters

- `action`
- `target_type`
- `before`
- `after`
- `sort`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type None

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectExport(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
created_from_list: bool = False)
```

Bases: `gitlab.mixins.DownloadMixin`, `gitlab.mixins.RefreshMixin`, `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –

Return type None

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectExportManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.GetWithoutIdMixin`, `gitlab.mixins.CreateMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type None

get(*id: Optional[Union[int, str]] = None, **kwargs: Any*) → *Optional[gitlab.v4.objects.export_import.ProjectExport]*

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.export_import.ProjectExport]*

gitlab: *gitlab.client.Gitlab*

class *gitlab.v4.objects.ProjectFile*(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.v4.objects.files.ProjectFileManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

decode() → *bytes*

Returns the decoded content of the file.

Returns The decoded content.

Return type *bytes*

delete(*branch: str, commit_message: str, **kwargs: Any*) → *None*

Delete the file from the server.

Parameters

- **branch** (*str*) – Branch from which the file will be removed
- **commit_message** (*str*) – Commit message for the deletion
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type *None*

file_path: *str*

manager: [*ProjectFileManager*](#)

save(*branch: str, commit_message: str, **kwargs: Any*) → None

Save the changes made to the file to the server.

The object is updated to match what the server returns.

Parameters

- **branch** (*str*) – Branch in which the file will be updated
- **commit_message** (*str*) – Message to send with the commit
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabUpdateError*](#) – If the server cannot perform the request

Return type None

class gitlab.v4.objects.**ProjectFileManager**(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: [*gitlab.mixins.GetMixin*](#), [*gitlab.mixins.CreateMixin*](#), [*gitlab.mixins.UpdateMixin*](#), [*gitlab.mixins.DeleteMixin*](#), [*gitlab.base.RESTManager*](#)

Object Creation

Object update

Parameters

- **gl** ([*gitlab.client.Gitlab*](#)) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

blame(*file_path: str, ref: str, **kwargs: Any*) → List[Dict[str, Any]]

Return the content of a file for a commit.

Parameters

- **file_path** (*str*) – Path of the file to retrieve
- **ref** (*str*) – Name of the branch, tag or commit
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabListError*](#) – If the server failed to perform the request

Returns A list of commits/lines matching the file

Return type *List[Dict[str, Any]]*

create(*data*: *Optional[Dict[str, Any]] = None*, ***kwargs*: *Any*) → *gitlab.v4.objects.files.ProjectFile*

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – parameters to send to the server to create the resource
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns

a new instance of the managed object class built with the data sent by the server

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabCreateError* – If the server cannot perform the request

Return type *gitlab.v4.objects.files.ProjectFile*

delete(*file_path*: *str*, *branch*: *str*, *commit_message*: *str*, ***kwargs*: *Any*) → *None*

Delete a file on the server.

Parameters

- **file_path** (*str*) – Path of the file to remove
- **branch** (*str*) – Branch from which the file will be removed
- **commit_message** (*str*) – Commit message for the deletion
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabDeleteError* – If the server cannot perform the request

Return type *None*

get(*file_path*: *str*, *ref*: *str*, ***kwargs*: *Any*) → *gitlab.v4.objects.files.ProjectFile*

Retrieve a single file.

Parameters

- **file_path** (*str*) – Path of the file to retrieve
- **ref** (*str*) – Name of the branch, tag or commit
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the file could not be retrieved

Returns The generated RESTObject

Return type *gitlab.v4.objects.files.ProjectFile*

gitlab: [`gitlab.client.Gitlab`](#)

raw(*file_path: str, ref: str, streamed: bool = False, action: Optional[Callable[[...], Any]] = None, chunk_size: int = 1024, **kwargs: Any*) → *Optional[bytes]*

Return the content of a file for a commit.

Parameters

- **ref** (*str*) – ID of the commit
- **filepath** – Path of the file to return
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **action** (*Optional[Callable[[...], Any]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **file_path** (*str*) –
- **kwargs** (*Any*) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the file could not be retrieved

Returns The file content

Return type *Optional[bytes]*

update(*file_path: str, new_data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *Dict[str, Any]*

Update an object on the server.

Parameters

- **id** – ID of the object to update (can be None if not required)
- **new_data** (*Optional[Dict[str, Any]]*) – the update data for the object
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **file_path** (*str*) –
- **kwargs** (*Any*) –

Returns The new object data (*not* a `RESTObject`)

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabUpdateError`](#) – If the server cannot perform the request

Return type *Dict[str, Any]*

class `gitlab.v4.objects.ProjectFork`(*manager: [`gitlab.base.RESTManager`](#), *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*)*

Bases: [`gitlab.base.RESTObject`](#)

Parameters

- **manager** ([`gitlab.base.RESTManager`](#)) –

- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type None

manager: *gitlab.base.RESTManager*

class *gitlab.v4.objects.ProjectForkManager* (*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.CreateMixin, gitlab.mixins.ListMixin, gitlab.base.RESTManager*

Object listing filters

- archived
- visibility
- order_by
- sort
- search
- simple
- owned
- membership
- starred
- statistics
- with_custom_attributes
- with_issues_enabled
- with_merge_requests_enabled

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

create (*data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *gitlab.v4.objects.projects.ProjectFork*

Creates a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – Parameters to send to the server to create the resource
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabCreateError* – If the server cannot perform the request

Returns

A new instance of the managed object class build with the data sent by the server

Return type `gitlab.v4.objects.projects.ProjectFork`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectHook(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectHookManager(gl: gitlab.client.Gitlab, parent:
                                           Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object Creation**Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.hooks.ProjectHook
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type `gitlab.v4.objects.hooks.ProjectHook`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectImport(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: [gitlab.mixins.RefreshMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.ProjectImportManager(gl: gitlab.client.Gitlab, parent:
                                             Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.GetWithoutIdMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type [None](#)

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) →
Optional[gitlab.v4.objects.export_import.ProjectImport]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** ([Optional\[Union\[int, str\]\]](#)) –
- **kwargs** ([Any](#)) –

Returns The generated [RESTObject](#)

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [Optional\[gitlab.v4.objects.export_import.ProjectImport\]](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.ProjectIssue(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: [gitlab.mixins.UserAgentDetailMixin](#), [gitlab.mixins.SubscribableMixin](#), [gitlab.mixins.TODOMixin](#), [gitlab.mixins.TimeTrackingMixin](#), [gitlab.mixins.ParticipantsMixin](#), [gitlab.mixins.SaveMixin](#), [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –

- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

awardemojis: [*gitlab.v4.objects.award_emojis.ProjectIssueAwardEmojiManager*](#)

closed_by(***kwargs: Any*) → *Dict[str, Any]*

List merge requests that will close the issue when merged.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabGetError*](#) – If the merge requests could not be retrieved

Returns The list of merge requests.

Return type *Dict[str, Any]*

discussions: [*gitlab.v4.objects.discussions.ProjectIssueDiscussionManager*](#)

links: [*ProjectIssueLinkManager*](#)

move(*to_project_id: int, **kwargs: Any*) → *None*

Move the issue to another project.

Parameters

- **to_project_id** (*int*) – ID of the target project
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabUpdateError*](#) – If the issue could not be moved

Return type *None*

notes: [*gitlab.v4.objects.notes.ProjectIssueNoteManager*](#)

related_merge_requests(***kwargs: Any*) → *Dict[str, Any]*

List merge requests related to the issue.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabGetError*](#) – If the merge requests could not be retrieved

Returns The list of merge requests.

Return type *Dict[str, Any]*

resourcelabelevents: *gitlab.v4.objects.events.ProjectIssueResourceLabelEventManager*

resourceilestoneevents:

gitlab.v4.objects.events.ProjectIssueResourceMilestoneEventManager

resourcestateevents: *gitlab.v4.objects.events.ProjectIssueResourceStateEventManager*

class *gitlab.v4.objects.ProjectIssueAwardEmoji*(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

class *gitlab.v4.objects.ProjectIssueAwardEmojiManager*(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.award_emojis.ProjectIssueAwardEmoji*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.award_emojis.ProjectIssueAwardEmoji*

gitlab: [gitlab.client.Gitlab](#)

class gitlab.v4.objects.**ProjectIssueDiscussion**(manager: [gitlab.base.RESTManager](#), attrs: *Dict[str, Any]*, *, created_from_list: bool = False)

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (bool) –

Return type None

notes: [gitlab.v4.objects.notes.ProjectIssueDiscussionNoteManager](#)

class gitlab.v4.objects.**ProjectIssueDiscussionManager**(gl: [gitlab.client.Gitlab](#), parent: *Optional[gitlab.base.RESTObject]* = None)

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.mixins.CreateMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

get(id: *Union[str, int]*, lazy: bool = False, **kwargs: Any) → [gitlab.v4.objects.discussions.ProjectIssueDiscussion](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The generated RESTObject.

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [gitlab.v4.objects.discussions.ProjectIssueDiscussion](#)

gitlab: [gitlab.client.Gitlab](#)

class gitlab.v4.objects.**ProjectIssueDiscussionNote**(manager: [gitlab.base.RESTManager](#), attrs: *Dict[str, Any]*, *, created_from_list: bool = False)

Bases: [gitlab.mixins.SaveMixin](#), [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.ProjectIssueDiscussionNoteManager` (*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: `gitlab.mixins.GetMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get (*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → `gitlab.v4.objects.notes.ProjectIssueDiscussionNote`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.notes.ProjectIssueDiscussionNote`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.ProjectIssueLink` (*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type None

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.ProjectIssueLinkManager`(*gl*: `gitlab.client.Gitlab`, *parent*:
Optional[`gitlab.base.RESTObject`] = None)

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`,
`gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional*[`gitlab.base.RESTObject`]) –

Return type None

create(*data*: *Dict*[*str*, *Any*], ***kwargs*: *Any*) → *Tuple*[`gitlab.base.RESTObject`, `gitlab.base.RESTObject`]

Create a new object.

Parameters

- **data** (*Dict*[*str*, *Any*]) – parameters to send to the server to create the resource
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The source and target issues

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Return type *Tuple*[`gitlab.base.RESTObject`, `gitlab.base.RESTObject`]

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.ProjectIssueManager`(*gl*: `gitlab.client.Gitlab`, *parent*:
Optional[`gitlab.base.RESTObject`] = None)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object listing filters

- `iids`
- `state`
- `labels`
- `milestone`
- `scope`
- `author_id`
- `assignee_id`
- `my_reaction_emoji`
- `order_by`

- `sort`
- `search`
- `created_after`
- `created_before`
- `updated_after`
- `updated_before`

Object Creation

Object update

Parameters

- **`gl`** (`gitlab.client.Gitlab`) –
- **`parent`** (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

`get`(*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) → *gitlab.v4.objects.issues.ProjectIssue*

Retrieve a single object.

Parameters

- **`id`** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **`lazy`** (*bool*) – If *True*, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- **`**kwargs`** – Extra options to send to the server (e.g. *sudo*)
- **`kwargs`** (*Any*) –

Returns The generated *RESTObject*.

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabGetError*** – If the server cannot perform the request

Return type *gitlab.v4.objects.issues.ProjectIssue*

`gitlab:` *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectIssueNote(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                          created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin*, *gitlab.mixins.ObjectDeleteMixin*, *gitlab.base.RESTObject*

Parameters

- **`manager`** (`gitlab.base.RESTManager`) –
- **`attrs`** (*Dict*[*str*, *Any*]) –
- **`created_from_list`** (*bool*) –

Return type `None`

`awardemojis:` *gitlab.v4.objects.award_emojis.ProjectIssueNoteAwardEmojiManager*

```
class gitlab.v4.objects.ProjectIssueNoteAwardEmoji(manager: gitlab.base.RESTManager, attrs:
                                                    Dict[str, Any], *, created_from_list: bool = False)
```

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager(gl: gitlab.client.Gitlab, parent:
                                                         Optional[gitlab.base.RESTObject] =
                                                         None)
```

Bases: *gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) →
    gitlab.v4.objects.award_emojis.ProjectIssueNoteAwardEmoji
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated *RESTObject*.

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabGetError*** – If the server cannot perform the request

Return type *gitlab.v4.objects.award_emojis.ProjectIssueNoteAwardEmoji*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectIssueNoteManager(gl: gitlab.client.Gitlab, parent:
                                                Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update**Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`**get**(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.notes.ProjectIssueNote*

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.**Raises**

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.notes.ProjectIssueNote***gitlab:** *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectIssueResourceLabelEvent(manager: gitlab.base.RESTManager, attrs:
Dict[str, Any], *, created_from_list: bool =
False)
```

Bases: *gitlab.base.RESTObject***Parameters**

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`**manager:** *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectIssueResourceLabelEventManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject]
= None)
```

Bases: *gitlab.mixins.RetrieveMixin, gitlab.base.RESTManager***Object Creation****Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type None

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) →
gitlab.v4.objects.events.ProjectIssueResourceLabelEvent

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The generated RESTObject.

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.events.ProjectIssueResourceLabelEvent*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectIssueResourceMilestoneEvent(manager: gitlab.base.RESTManager,  
                                                         attrs: Dict[str, Any], *,  
                                                         created_from_list: bool = False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (gitlab.base.RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –

Return type None

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager(gl: gitlab.client.Gitlab, parent:  
                                                                Op-  
                                                                tional[gitlab.base.RESTObject]  
                                                                = None)
```

Bases: *gitlab.mixins.RetrieveMixin*, *gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (gitlab.client.Gitlab) –
- **parent** (Optional[gitlab.base.RESTObject]) –

Return type None

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) →
[gitlab.v4.objects.events.ProjectIssueResourceMilestoneEvent](#)

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The generated RESTObject.

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [gitlab.v4.objects.events.ProjectIssueResourceMilestoneEvent](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.ProjectIssueResourceStateEvent(manager: gitlab.base.RESTManager, attrs:
    Dict[str, Any], *, created_from_list: bool =
    False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –

Return type None

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.ProjectIssueResourceStateEventManager(gl: gitlab.client.Gitlab, parent:
    Optional[gitlab.base.RESTObject]
    = None)
```

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (Optional[[gitlab.base.RESTObject](#)]) –

Return type None

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) →
[gitlab.v4.objects.events.ProjectIssueResourceStateEvent](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.events.ProjectIssueResourceStateEvent*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectIssuesStatistics(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: *gitlab.mixins.RefreshMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectIssuesStatisticsManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.GetWithoutIdMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) → Optional[gitlab.v4.objects.statistics.ProjectIssuesStatistics]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- **[GitlabAuthenticationError](#)** – If authentication is not correct
- **[GitlabGetError](#)** – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.statistics.ProjectIssuesStatistics]*

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.ProjectJob(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                   created_from_list: bool = False)
```

Bases: [gitlab.mixins.RefreshMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

```
artifact(path: str, streamed: bool = False, action: Optional[Callable[[...], Any]] = None, chunk_size: int
          = 1024, **kwargs: Any) → Optional[bytes]
```

Get a single artifact file from within the job's artifacts archive.

Parameters

- **path** (*str*) – Path of the artifact
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **action** (*Optional[Callable[[...], Any]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **[GitlabAuthenticationError](#)** – If authentication is not correct
- **[GitlabGetError](#)** – If the artifacts could not be retrieved

Returns The artifacts if *streamed* is False, None otherwise.

Return type *Optional[bytes]*

```
artifacts(streamed: bool = False, action: Optional[Callable[[...], Any]] = None, chunk_size: int = 1024,
           **kwargs: Any) → Optional[bytes]
```

Get the job artifacts.

Parameters

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **action** (*Optional[Callable[[...], Any]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **[GitlabAuthenticationError](#)** – If authentication is not correct
- **[GitlabGetError](#)** – If the artifacts could not be retrieved

Returns The artifacts if *streamed* is False, None otherwise.

Return type *Optional*[bytes]

cancel(**kwargs: *Any*) → Dict[str, *Any*]

Cancel the job.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **[GitlabAuthenticationError](#)** – If authentication is not correct
- **[GitlabJobCancelError](#)** – If the job could not be canceled

Return type Dict[str, *Any*]

delete_artifacts(**kwargs: *Any*) → None

Delete artifacts of a job.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **[GitlabAuthenticationError](#)** – If authentication is not correct
- **[GitlabDeleteError](#)** – If the request could not be performed

Return type None

erase(**kwargs: *Any*) → None

Erase the job (remove job artifacts and trace).

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **[GitlabAuthenticationError](#)** – If authentication is not correct
- **[GitlabJobEraseError](#)** – If the job could not be erased

Return type None

keep_artifacts(***kwargs: Any*) → None

Prevent artifacts from being deleted when expiration is set.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabCreateError*](#) – If the request could not be performed

Return type None

manager: [*gitlab.base.RESTManager*](#)

play(***kwargs: Any*) → None

Trigger a job explicitly.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabJobPlayError*](#) – If the job could not be triggered

Return type None

retry(***kwargs: Any*) → Dict[str, Any]

Retry the job.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabJobRetryError*](#) – If the job could not be retried

Return type Dict[str, Any]

trace(*streamed: bool = False, action: Optional[Callable[[...], Any]] = None, chunk_size: int = 1024, **kwargs: Any*) → Dict[str, Any]

Get the job trace.

Parameters

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **action** (*Optional[Callable[[...], Any]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** – Extra options to send to the server (e.g. sudo)

- **kwargs** (*Any*) –

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabGetError*** – If the artifacts could not be retrieved

Returns The trace

Return type *Dict[str, Any]*

```
class gitlab.v4.objects.ProjectJobManager(gl: gitlab.client.Gitlab, parent:
                                         Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.RetrieveMixin*, *gitlab.base.RESTManager*

Object Creation**Object update****Parameters**

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.jobs.ProjectJob
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabGetError*** – If the server cannot perform the request

Return type *gitlab.v4.objects.jobs.ProjectJob*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectKey(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                   created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin*, *gitlab.mixins.ObjectDeleteMixin*, *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.ProjectKeyManager`(*gl*: `gitlab.client.Gitlab`, *parent*: `Optional[gitlab.base.RESTObject]` = `None`)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

enable(*key_id*: `int`, ***kwargs*: `Any`) → `Union[Dict[str, Any], requests.models.Response]`

Enable a deploy key for a project.

Parameters

- **key_id** (`int`) – The ID of the key to enable
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (`Any`) –

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabProjectDeployKeyError` – If the key could not be enabled

Returns A dict of the result.

Return type `Union[Dict[str, Any], requests.models.Response]`

get(*id*: `Union[str, int]`, *lazy*: `bool` = `False`, ***kwargs*: `Any`) → `gitlab.v4.objects.deploy_keys.ProjectKey`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type `gitlab.v4.objects.deploy_keys.ProjectKey`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectLabel(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: `gitlab.mixins.PromoteMixin`, `gitlab.mixins.SubscribableMixin`, `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.v4.objects.labels.ProjectLabelManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `ProjectLabelManager`

save(**kwargs: Any) → `None`

Saves the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Raises

- `GitlabAuthenticationError` – If authentication is not correct.
- `GitlabUpdateError` – If the server cannot perform the request.

Return type `None`

```
class gitlab.v4.objects.ProjectLabelManager(gl: gitlab.client.Gitlab, parent:
                                           Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → `gitlab.v4.objects.labels.ProjectLabel`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.labels.ProjectLabel*

gitlab: *gitlab.client.Gitlab*

update(*name: Optional[str], new_data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → Dict[str, Any]
Update a Label on the server.

Parameters

- **name** (*Optional[str]*) – The name of the label
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **new_data** (*Optional[Dict[str, Any]]*) –
- **kwargs** (*Any*) –

Return type *Dict[str, Any]*

class *gitlab.v4.objects.ProjectManager*(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object listing filters

- archived
- id_after
- id_before
- last_activity_after
- last_activity_before
- membership
- min_access_level
- order_by
- owned
- repository_checksum_failed
- repository_storage
- search_namespaces
- search
- simple
- sort
- starred
- statistics
- topic
- visibility

- `wiki_checksum_failed`
- `with_custom_attributes`
- `with_issues_enabled`
- `with_merge_requests_enabled`
- `with_programming_language`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

get (*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) → *gitlab.v4.objects.projects.Project*

Retrieve a single object.

Parameters

- `id` (*Union*[*str*, *int*]) – ID of the object to retrieve
- `lazy` (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` – Extra options to send to the server (e.g. `sudo`)
- `kwargs` (*Any*) –

Returns The generated `RESTObject`.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type *gitlab.v4.objects.projects.Project*

gitlab: `gitlab.client.Gitlab`

```
import_bitbucket_server(bitbucket_server_url: str, bitbucket_server_username: str,  
                        personal_access_token: str, bitbucket_server_project: str,  
                        bitbucket_server_repo: str, new_name: Optional[str] = None,  
                        target_namespace: Optional[str] = None, **kwargs: Any) → Union[Dict[str,  
                        Any], requests.models.Response]
```

Import a project from BitBucket Server to Gitlab (schedule the import)

This method will return when an import operation has been safely queued, or an error has occurred. After triggering an import, check the `import_status` of the newly created project to detect when the import operation has completed.

Note: This request may take longer than most other API requests. So this method will specify a 60 second default timeout if none is specified. A timeout can be specified via `kwargs` to override this functionality.

Parameters

- **bitbucket_server_url** (*str*) – Bitbucket Server URL
- **bitbucket_server_username** (*str*) – Bitbucket Server Username
- **personal_access_token** (*str*) – Bitbucket Server personal access token/password
- **bitbucket_server_project** (*str*) – Bitbucket Project Key
- **bitbucket_server_repo** (*str*) – Bitbucket Repository Name
- **new_name** (*Optional[str]*) – New repository name (Optional)
- **target_namespace** (*Optional[str]*) – Namespace to import repository into. Supports subgroups like /namespace/subgroup (Optional)
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns A representation of the import status.

Return type *Union[Dict[str, Any], requests.models.Response]*

Example:

```
gl = gitlab.Gitlab_from_config()
print("Triggering import")
result = gl.projects.import_bitbucket_server(
    bitbucket_server_url="https://some.server.url",
    bitbucket_server_username="some_bitbucket_user",
    personal_access_token="my_password_or_access_token",
    bitbucket_server_project="my_project",
    bitbucket_server_repo="my_repo",
    new_name="gl_project_name",
    target_namespace="gl_project_path"
)
project = gl.projects.get(ret['id'])
print("Waiting for import to complete")
while project.import_status == u'started':
    time.sleep(1.0)
    project = gl.projects.get(project.id)
print("BitBucket import complete")
```

import_github(*personal_access_token: str, repo_id: int, target_namespace: str, new_name: Optional[str]*
*= None, **kwargs: Any*) → *Union[Dict[str, Any], requests.models.Response]*

Import a project from Github to Gitlab (schedule the import)

This method will return when an import operation has been safely queued, or an error has occurred. After triggering an import, check the `import_status` of the newly created project to detect when the import operation has completed.

Note: This request may take longer than most other API requests. So this method will specify a 60 second default timeout if none is specified. A timeout can be specified via `kwargs` to override this functionality.

Parameters

- **personal_access_token** (*str*) – GitHub personal access token
- **repo_id** (*int*) – Github repository ID
- **target_namespace** (*str*) – Namespace to import repo into
- **new_name** (*Optional[str]*) – New repo name (Optional)
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns A representation of the import status.

Return type *Union[Dict[str, Any], requests.models.Response]*

Example:

```
gl = gitlab.Gitlab_from_config()
print("Triggering import")
result = gl.projects.import_github(ACCESS_TOKEN,
                                   123456,
                                   "my-group/my-subgroup")

project = gl.projects.get(ret['id'])
print("Waiting for import to complete")
while project.import_status == u'started':
    time.sleep(1.0)
    project = gl.projects.get(project.id)
print("Github import complete")
```

import_project (*file: str, path: str, name: Optional[str] = None, namespace: Optional[str] = None, overwrite: bool = False, override_params: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *Union[Dict[str, Any], requests.models.Response]*

Import a project from an archive file.

Parameters

- **file** (*str*) – Data or file object containing the project
- **path** (*str*) – Name and path for the new project
- **namespace** (*Optional[str]*) – The ID or path of the namespace that the project will be imported to
- **overwrite** (*bool*) – If True overwrite an existing project with the same path
- **override_params** (*Optional[Dict[str, Any]]*) – Set the specific settings for the project
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **name** (*Optional[str]*) –
- **kwargs** (*Any*) –

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabListError`** – If the server failed to perform the request

Returns A representation of the import status.

Return type `Union[Dict[str, Any], requests.models.Response]`

```
class gitlab.v4.objects.ProjectMember(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **`manager`** (`gitlab.base.RESTManager`) –
- **`attrs`** (`Dict[str, Any]`) –
- **`created_from_list`** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectMemberAll(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                         created_from_list: bool = False)
```

Bases: `gitlab.base.RESTObject`

Parameters

- **`manager`** (`gitlab.base.RESTManager`) –
- **`attrs`** (`Dict[str, Any]`) –
- **`created_from_list`** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectMemberAllManager(gl: gitlab.client.Gitlab, parent:
                                                Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **`gl`** (`gitlab.client.Gitlab`) –
- **`parent`** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.members.ProjectMemberAll
```

Retrieve a single object.

Parameters

- **`id`** (`Union[str, int]`) – ID of the object to retrieve
- **`lazy`** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- **`**kwargs`** – Extra options to send to the server (e.g. sudo)

- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.members.ProjectMemberAll*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectMemberManager(gl: gitlab.client.Gitlab, parent:
                                           Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.members.ProjectMember
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.members.ProjectMember*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequest(manager: gitlab.base.RESTManager, attrs: Dict[str, Any],
                                           *, created_from_list: bool = False)
```

Bases: *gitlab.mixins.SubscribableMixin, gitlab.mixins.TODOMixin, gitlab.mixins.TimeTrackingMixin, gitlab.mixins.ParticipantsMixin, gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –

- **created_from_list** (*bool*) –

Return type *None*

approval_rules:

gitlab.v4.objects.merge_request_approvals.ProjectMergeRequestApprovalRuleManager

approval_state:

gitlab.v4.objects.merge_request_approvals.ProjectMergeRequestApprovalStateManager

approvals:

gitlab.v4.objects.merge_request_approvals.ProjectMergeRequestApprovalManager

approve(*sha: Optional[str] = None, **kwargs: Any*) → *Dict[str, Any]*

Approve the merge request.

Parameters

- **sha** (*Optional[str]*) – Head SHA of MR
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabMRApprovalError* – If the approval failed

Returns A dict containing the result.

Return type *Dict[str, Any]*

https://docs.gitlab.com/ee/api/merge_request_approvals.html#approve-merge-request

awardemojis: *gitlab.v4.objects.award_emojis.ProjectMergeRequestAwardEmojiManager*

cancel_merge_when_pipeline_succeeds(***kwargs: Any*) →

gitlab.v4.objects.merge_requests.ProjectMergeRequest

Cancel merge when the pipeline succeeds.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabMROnBuildSuccessError* – If the server could not handle the request

Returns *ProjectMergeRequest*

Return type *gitlab.v4.objects.merge_requests.ProjectMergeRequest*

changes(***kwargs: Any*) → *Union[Dict[str, Any], requests.models.Response]*

List the merge request changes.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabListError*** – If the list could not be retrieved

Returns List of changes

Return type *Union[Dict[str, Any], requests.models.Response]*

closes_issues(***kwargs: Any*) → *gitlab.base.RESTObjectList*

List issues that will close on merge.”

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabListError*** – If the list could not be retrieved

Returns List of issues

Return type *gitlab.base.RESTObjectList*

commits(***kwargs: Any*) → *gitlab.base.RESTObjectList*

List the merge request commits.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabListError*** – If the list could not be retrieved

Returns The list of commits

Return type *gitlab.base.RESTObjectList*

diffs: *ProjectMergeRequestDiffManager*

discussions: [`gitlab.v4.objects.discussions.ProjectMergeRequestDiscussionManager`](#)

merge(*merge_commit_message*: *Optional*[*str*] = *None*, *should_remove_source_branch*: *Optional*[*bool*] = *None*, *merge_when_pipeline_succeeds*: *Optional*[*bool*] = *None*, ***kwargs*: *Any*) → *Dict*[*str*, *Any*]

Accept the merge request.

Parameters

- **merge_commit_message** (*Optional*[*str*]) – Commit message
- **should_remove_source_branch** (*Optional*[*bool*]) – If True, removes the source branch
- **merge_when_pipeline_succeeds** (*Optional*[*bool*]) – Wait for the build to succeed, then merge
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabMRClosedError`](#) – If the merge failed

Return type *Dict*[*str*, *Any*]

merge_ref(***kwargs*: *Any*) → *Union*[*Dict*[*str*, *Any*], *requests.models.Response*]

Attempt to merge changes between source and target branches into *refs/merge-requests/:iid/merge*.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises [`GitlabGetError`](#) – If cannot be merged

Return type *Union*[*Dict*[*str*, *Any*], *requests.models.Response*]

notes: [`gitlab.v4.objects.notes.ProjectMergeRequestNoteManager`](#)

pipelines: [`gitlab.v4.objects.pipelines.ProjectMergeRequestPipelineManager`](#)

rebase(***kwargs*: *Any*) → *Union*[*Dict*[*str*, *Any*], *requests.models.Response*]

Attempt to rebase the source branch onto the target branch

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabMRRebaseError`](#) – If rebasing failed

Return type *Union*[*Dict*[*str*, *Any*], *requests.models.Response*]

resourcelabelevents:

[`gitlab.v4.objects.events.ProjectMergeRequestResourceLabelEventManager`](#)

resourceilestoneevents:

gitlab.v4.objects.events.ProjectMergeRequestResourceMilestoneEventManager

resourcestateevents:

gitlab.v4.objects.events.ProjectMergeRequestResourceStateEventManager

unapprove(***kwargs: Any*) → None

Unapprove the merge request.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabMRApprovalError* – If the unapproval failed

Return type None

https://docs.gitlab.com/ee/api/merge_request_approvals.html#unapprove-merge-request

```
class gitlab.v4.objects.ProjectMergeRequestApproval(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin*, *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type None

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectMergeRequestApprovalManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.GetWithoutIdMixin*, *gitlab.mixins.UpdateMixin*, *gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

get(*id: Optional[Union[int, str]] = None, **kwargs: Any*) → *Optional[gitlab.v4.objects.merge_request_approvals.ProjectMergeRequestApproval]*

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.merge_request_approvals.ProjectMergeRequestApproval]*

gitlab: *gitlab.client.Gitlab*

set_approvers(*approvals_required: int, approver_ids: Optional[List[int]] = None, approver_group_ids: Optional[List[int]] = None, approval_rule_name: str = 'name', **kwargs: Any*) → *gitlab.base.RESTObject*

Change MR-level allowed approvers and approver groups.

Parameters

- **approvals_required** (*int*) – The number of required approvals for this rule
- **approver_ids** (*Optional[List[int]]*) – User IDs that can approve MRs
- **approver_group_ids** (*Optional[List[int]]*) – Group IDs whose members can approve MRs
- **approval_rule_name** (*str*) –
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server failed to perform the request

Return type *gitlab.base.RESTObject*

class *gitlab.v4.objects.ProjectMergeRequestApprovalRule*(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

id: *int*

save(***kwargs: Any*) → *None*

Save the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabUpdateError*** – If the server cannot perform the request

Return type *None*

```
class gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager(gl: gitlab.client.Gitlab, parent:
                                                                Optional[gitlab.base.RESTObject] =
                                                                None)
```

Bases: *gitlab.mixins.ListMixin*, *gitlab.mixins.UpdateMixin*, *gitlab.mixins.CreateMixin*, *gitlab.mixins.DeleteMixin*, *gitlab.base.RESTManager*

Object listing filters

- **name**
- **rule_type**

Object Creation**Object update****Parameters**

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → gitlab.base.RESTObject
```

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – Parameters to send to the server to create the resource
- ****kwargs** – Extra options to send to the server (e.g. sudo or 'ref_name', 'stage', 'name', 'all')
- **kwargs** (*Any*) –

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabCreateError*** – If the server cannot perform the request

Returns

A new instance of the manage object class build with the data sent by the server

Return type *gitlab.base.RESTObject*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestApprovalState(manager: gitlab.base.RESTManager,
                                                         attrs: Dict[str, Any], *, created_from_list:
                                                         bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict](#)[[str](#), [Any](#)]) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.ProjectMergeRequestApprovalStateManager(gl: gitlab.client.Gitlab, parent:
                                                                Optional[gitlab.base.RESTObject]
                                                                = None)
```

Bases: [gitlab.mixins.GetWithoutIdMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional](#)[[gitlab.base.RESTObject](#)]) –

Return type [None](#)

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) →
Optional[gitlab.v4.objects.merge_request_approvals.ProjectMergeRequestApprovalState]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** ([Optional](#)[[Union](#)[[int](#), [str](#)]]) –
- **kwargs** ([Any](#)) –

Returns The generated [RESTObject](#)

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [Optional](#)[[gitlab.v4.objects.merge_request_approvals.ProjectMergeRequestApprovalState](#)]

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.ProjectMergeRequestAwardEmoji(manager: gitlab.base.RESTManager, attrs:
                                                         Dict[str, Any], *, created_from_list: bool =
                                                         False)
```

Bases: [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] =
None)
```

Bases: `gitlab.mixins.NoUpdateMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get (`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) →
`gitlab.v4.objects.award_emojis.ProjectMergeRequestAwardEmoji`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (`Any`) –

Returns The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.award_emojis.ProjectMergeRequestAwardEmoji`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectMergeRequestDiff(manager: gitlab.base.RESTManager, attrs: Dict[str,
Any], *, created_from_list: bool = False)
```

Bases: `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectMergeRequestDiffManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) →
gitlab.v4.objects.merge_requests.ProjectMergeRequestDiff
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.merge_requests.ProjectMergeRequestDiff`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectMergeRequestDiscussion(manager: gitlab.base.RESTManager, attrs:
Dict[str, Any], *, created_from_list: bool =
False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

notes: `gitlab.v4.objects.notes.ProjectMergeRequestDiscussionNoteManager`

```
class gitlab.v4.objects.ProjectMergeRequestDiscussionManager(gl: gitlab.client.Gitlab, parent:
                                                                Optional[gitlab.base.RESTObject] =
                                                                None)
```

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.mixins.CreateMixin](#), [gitlab.mixins.UpdateMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional*[[gitlab.base.RESTObject](#)]) –

Return type `None`

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [gitlab.v4.objects.discussions.ProjectMergeRequestDiscussion](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated [RESTObject](#).

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [gitlab.v4.objects.discussions.ProjectMergeRequestDiscussion](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.ProjectMergeRequestDiscussionNote(manager: gitlab.base.RESTManager,
                                                            attrs: Dict[str, Any], *,
                                                            created_from_list: bool = False)
```

Bases: [gitlab.mixins.SaveMixin](#), [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type `None`

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager(gl: gitlab.client.Gitlab, parent:
                                                                    Optional[gitlab.base.RESTObject]
                                                                    = None)
```

Bases: `gitlab.mixins.GetMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get (*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → `gitlab.v4.objects.notes.ProjectMergeRequestDiscussionNote`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.notes.ProjectMergeRequestDiscussionNote`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectMergeRequestManager(gl: gitlab.client.Gitlab, parent:
                                                    Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object listing filters

- state
- order_by
- sort
- milestone
- view
- labels
- created_after
- created_before

- `updated_after`
- `updated_before`
- `scope`
- `iids`
- `author_id`
- `assignee_id`
- `approver_ids`
- `approved_by_ids`
- `my_reaction_emoji`
- `source_branch`
- `target_branch`
- `search`
- `wip`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

get(*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) →
gitlab.v4.objects.merge_requests.ProjectMergeRequest

Retrieve a single object.

Parameters

- `id` (*Union*[*str*, *int*]) – ID of the object to retrieve
- `lazy` (*bool*) – If *True*, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` – Extra options to send to the server (e.g. *sudo*)
- `kwargs` (*Any*) –

Returns The generated *RESTObject*.

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.merge_requests.ProjectMergeRequest*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestNote(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [gitlab.mixins.SaveMixin](#), [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict](#)[[str](#), [Any](#)]) –
- **created_from_list** ([bool](#)) –

Return type `None`

awardemojis:

[gitlab.v4.objects.award_emojis.ProjectMergeRequestNoteAwardEmojiManager](#)

```
class gitlab.v4.objects.ProjectMergeRequestNoteAwardEmoji(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict](#)[[str](#), [Any](#)]) –
- **created_from_list** ([bool](#)) –

Return type `None`

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.NoUpdateMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional](#)[[gitlab.base.RESTObject](#)]) –

Return type `None`

get(*id*: [Union](#)[[str](#), [int](#)], *lazy*: [bool](#) = [False](#), ***kwargs*: [Any](#)) → [gitlab.v4.objects.award_emojis.ProjectMergeRequestNoteAwardEmoji](#)

Retrieve a single object.

Parameters

- **id** ([Union](#)[[str](#), [int](#)]) – ID of the object to retrieve
- **lazy** ([bool](#)) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)

- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.award_emojis.ProjectMergeRequestNoteAwardEmoji*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestNoteManager(gl: gitlab.client.Gitlab, parent:
                                                    Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) →
    gitlab.v4.objects.notes.ProjectMergeRequestNote
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.notes.ProjectMergeRequestNote*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestPipeline(manager: gitlab.base.RESTManager, attrs:
                                                    Dict[str, Any], *, created_from_list: bool =
                                                    False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –

- `created_from_list` (*bool*) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectMergeRequestPipelineManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] =
None)
```

Bases: `gitlab.mixins.CreateMixin`, `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (*Optional*[`gitlab.base.RESTObject`]) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectMergeRequestResourceLabelEvent(manager:
gitlab.base.RESTManager, attrs:
Dict[str, Any], *, created_from_list:
bool = False)
```

Bases: `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (*Dict*[*str*, *Any*]) –
- `created_from_list` (*bool*) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager(gl: gitlab.client.Gitlab,
parent: Op-
tional[gitlab.base.RESTObject]
= None)
```

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (*Optional*[`gitlab.base.RESTObject`]) –

Return type `None`

`get`(*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) →
`gitlab.v4.objects.events.ProjectMergeRequestResourceLabelEvent`

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.events.ProjectMergeRequestResourceLabelEvent*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEvent(manager:  
                                                                    gitlab.base.RESTManager,  
                                                                    attrs: Dict[str, Any], *,  
                                                                    created_from_list: bool =  
                                                                    False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type None

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager(gl:  
                                                                           gitlab.client.Gitlab,  
                                                                           parent: Op-  
                                                                           tional[gitlab.base.RESTObject]  
                                                                           = None)
```

Bases: *gitlab.mixins.RetrieveMixin, gitlab.base.RESTManager*

Object Creation**Object update****Parameters**

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) →
gitlab.v4.objects.events.ProjectMergeRequestResourceMilestoneEvent

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.events.ProjectMergeRequestResourceMilestoneEvent*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestResourceStateEvent(manager:
    gitlab.base.RESTManager, attrs:
    Dict[str, Any], *, created_from_list:
    bool = False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type None

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectMergeRequestResourceStateEventManager(gl: gitlab.client.Gitlab,
    parent: Optional[gitlab.base.RESTObject]
    = None)
```

Bases: *gitlab.mixins.RetrieveMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) →
gitlab.v4.objects.events.ProjectMergeRequestResourceStateEvent

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.events.ProjectMergeRequestResourceStateEvent*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectMergeTrain(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                          created_from_list: bool = False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectMergeTrainManager(gl: gitlab.client.Gitlab, parent:
                                                  Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.ListMixin, gitlab.base.RESTManager*

Object listing filters

- **scope**

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectMilestone(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                          created_from_list: bool = False)
```

Bases: *gitlab.mixins.PromoteMixin, gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –

- **created_from_list** (*bool*) –

Return type `None`

issues(**kwargs: *Any*) → *gitlab.base.RESTObjectList*

List issues related to this milestone.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabListError* – If the list could not be retrieved

Returns The list of issues

Return type *gitlab.base.RESTObjectList*

manager: *gitlab.base.RESTManager*

merge_requests(**kwargs: *Any*) → *gitlab.base.RESTObjectList*

List the merge requests related to this milestone.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabListError* – If the list could not be retrieved

Returns The list of merge requests

Return type *gitlab.base.RESTObjectList*

class `gitlab.v4.objects.ProjectMilestoneManager`(*gl*: *gitlab.client.Gitlab*, *parent*: *Optional[gitlab.base.RESTObject]* = *None*)

Bases: *gitlab.mixins.CRUDMixin*, *gitlab.base.RESTManager*

Object listing filters

- `iids`
- `state`
- `search`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `gitlab.v4.objects.milestones.ProjectMilestone`

Retrieve a single object.

Parameters

- `id` (`Union[str, int]`) – ID of the object to retrieve
- `lazy` (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` – Extra options to send to the server (e.g. `sudo`)
- `kwargs` (`Any`) –

Returns The generated `RESTObject`.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type `gitlab.v4.objects.milestones.ProjectMilestone`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectNote(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectNoteManager(gl: gitlab.client.Gitlab, parent:
                                           Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`**get** (*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) → *gitlab.v4.objects.notes.ProjectNote*

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If *True*, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. *sudo*)
- **kwargs** (*Any*) –

Returns The generated `RESTObject`.**Raises**

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabGetError*** – If the server cannot perform the request

Return type *gitlab.v4.objects.notes.ProjectNote***gitlab:** `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectNotificationSettings(manager: gitlab.base.RESTManager, attrs:
Dict[str, Any], *, created_from_list: bool =
False)
```

Bases: *gitlab.v4.objects.notification_settings.NotificationSettings***Parameters**

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –

Return type `None`**manager:** `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectNotificationSettingsManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] =
None)
```

Bases: *gitlab.v4.objects.notification_settings.NotificationSettingsManager***Object Creation****Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

get(*id*: *Optional[Union[int, str]] = None*, ***kwargs*: *Any*) →
Optional[gitlab.v4.objects.notification_settings.ProjectNotificationSettings]
Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.notification_settings.ProjectNotificationSettings]*

gitlab: *gitlab.client.Gitlab*

class *gitlab.v4.objects.ProjectPackage*(*manager*: *gitlab.base.RESTManager*, *attrs*: *Dict[str, Any]*, *,
created_from_list: *bool = False*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

package_files: *ProjectPackageFileManager*

class *gitlab.v4.objects.ProjectPackageFile*(*manager*: *gitlab.base.RESTManager*, *attrs*: *Dict[str, Any]*, *,
created_from_list: *bool = False*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

class *gitlab.v4.objects.ProjectPackageFileManager*(*gl*: *gitlab.client.Gitlab*, *parent*:
Optional[gitlab.base.RESTObject] = None)

Bases: *gitlab.mixins.DeleteMixin, gitlab.mixins.ListMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectPackageManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.GetMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object listing filters

- `order_by`
- `sort`
- `package_type`
- `package_name`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

get (*id*: *Union* [`str`, `int`], *lazy*: *bool* = *False*, ***kwargs*: *Any*) → `gitlab.v4.objects.packages.ProjectPackage`

Retrieve a single object.

Parameters

- **id** (*Union* [`str`, `int`]) – ID of the object to retrieve
- **lazy** (*bool*) – If *True*, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Returns The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.packages.ProjectPackage`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectPagesDomain(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –

- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

class *gitlab.v4.objects.ProjectPagesDomainManager* (*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get (*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.pages.ProjectPagesDomain*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.pages.ProjectPagesDomain*

gitlab: *gitlab.client.Gitlab*

class *gitlab.v4.objects.ProjectPipeline* (*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.RefreshMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

bridges: *ProjectPipelineBridgeManager*

cancel(**kwargs: Any) → Union[Dict[str, Any], requests.models.Response]

Cancel the job.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabPipelineCancelError`](#) – If the request failed

Return type Union[Dict[str, Any], requests.models.Response]

jobs: [`ProjectPipelineJobManager`](#)

retry(**kwargs: Any) → Union[Dict[str, Any], requests.models.Response]

Retry the job.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabPipelineRetryError`](#) – If the request failed

Return type Union[Dict[str, Any], requests.models.Response]

test_report: [`ProjectPipelineTestReportManager`](#)

test_report_summary: [`ProjectPipelineTestReportSummaryManager`](#)

variables: [`ProjectPipelineVariableManager`](#)

class gitlab.v4.objects.[`ProjectPipelineBridge`](#)(manager: [`gitlab.base.RESTManager`](#), attrs: Dict[str, Any], *, created_from_list: bool = False)

Bases: [`gitlab.base.RESTObject`](#)

Parameters

- **manager** ([`gitlab.base.RESTManager`](#)) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –

Return type None

manager: [`gitlab.base.RESTManager`](#)

class gitlab.v4.objects.[`ProjectPipelineBridgeManager`](#)(gl: [`gitlab.client.Gitlab`](#), parent: Optional[[`gitlab.base.RESTObject`](#)] = None)

Bases: [`gitlab.mixins.ListMixin`](#), [`gitlab.base.RESTManager`](#)

Object listing filters

- scope

Object Creation**Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional*[`gitlab.base.RESTObject`]) –

Return type None**gitlab:** `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectPipelineJob(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                           created_from_list: bool = False)
```

Bases: `gitlab.base.RESTObject`**Parameters**

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (*bool*) –

Return type None**manager:** `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectPipelineJobManager(gl: gitlab.client.Gitlab, parent:
                                                  Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`**Object listing filters**

- **scope**
- **include_retried**

Object Creation**Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional*[`gitlab.base.RESTObject`]) –

Return type None**gitlab:** `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectPipelineManager(gl: gitlab.client.Gitlab, parent:
                                              Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`**Object listing filters**

- **scope**
- **status**
- **ref**

- sha
- yaml_errors
- name
- username
- order_by
- sort

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type None

create(*data: Optional*[*Dict*[*str*, *Any*]] = None, ***kwargs: Any*) → *gitlab.v4.objects.pipelines.ProjectPipeline*

Creates a new object.

Parameters

- **data** (*Optional* [*Dict*[*str*, *Any*]]) – Parameters to send to the server to create the resource
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabCreateError*** – If the server cannot perform the request

Returns

A new instance of the managed object class build with the data sent by the server

Return type *gitlab.v4.objects.pipelines.ProjectPipeline*

get(*id: Union*[*str*, *int*], *lazy: bool* = False, ***kwargs: Any*) → *gitlab.v4.objects.pipelines.ProjectPipeline*

Retrieve a single object.

Parameters

- **id** (*Union* [*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct

- [`GitlabGetError`](#) – If the server cannot perform the request

Return type `gitlab.v4.objects.pipelines.ProjectPipeline`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.ProjectPipelineSchedule`(*manager*: `gitlab.base.RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

play(***kwargs*: `Any`) → `Dict[str, Any]`

Trigger a new scheduled pipeline, which runs immediately. The next scheduled run of this pipeline is not affected.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabPipelinePlayError`](#) – If the request failed

Return type `Dict[str, Any]`

take_ownership(***kwargs*: `Any`) → `None`

Update the owner of a pipeline schedule.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabOwnershipError`](#) – If the request failed

Return type `None`

variables: `gitlab.v4.objects.pipelines.ProjectPipelineScheduleVariableManager`

class `gitlab.v4.objects.ProjectPipelineScheduleManager`(*gl*: `gitlab.client.Gitlab`, *parent*: `Optional[gitlab.base.RESTObject] = None`)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`

get(*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) → *gitlab.v4.objects.pipelines.ProjectPipelineSchedule*

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.pipelines.ProjectPipelineSchedule*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectPipelineScheduleVariable(manager: gitlab.base.RESTManager, attrs:
Dict[str, Any], *, created_from_list: bool =
False)
```

Bases: *gitlab.mixins.SaveMixin*, *gitlab.mixins.ObjectDeleteMixin*, *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –

Return type `None`

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectPipelineScheduleVariableManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] =
None)
```

Bases: *gitlab.mixins.CreateMixin*, *gitlab.mixins.UpdateMixin*, *gitlab.mixins.DeleteMixin*, *gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type None

gitlab: [`gitlab.client.Gitlab`](#)

```
class gitlab.v4.objects.ProjectPipelineTestReport(manager: gitlab.base.RESTManager, attrs:
                                                    Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [`gitlab.base.RESTObject`](#)

Parameters

- **manager** ([`gitlab.base.RESTManager`](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type None

manager: [`gitlab.base.RESTManager`](#)

```
class gitlab.v4.objects.ProjectPipelineTestReportManager(gl: gitlab.client.Gitlab, parent:
                                                         Optional[gitlab.base.RESTObject] =
                                                         None)
```

Bases: [`gitlab.mixins.GetWithoutIdMixin`](#), [`gitlab.base.RESTManager`](#)

Object Creation

Object update

Parameters

- **gl** ([`gitlab.client.Gitlab`](#)) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) →
Optional[gitlab.v4.objects.pipelines.ProjectPipelineTestReport]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.pipelines.ProjectPipelineTestReport]*

gitlab: [`gitlab.client.Gitlab`](#)

```
class gitlab.v4.objects.ProjectPipelineTestReportSummary(manager: gitlab.base.RESTManager,
                                                         attrs: Dict[str, Any], *, created_from_list:
                                                         bool = False)
```

Bases: [`gitlab.base.RESTObject`](#)

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`**manager:** `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectPipelineTestReportSummaryManager(gl: gitlab.client.Gitlab, parent:
    Optional[gitlab.base.RESTObject]
    = None)
```

Bases: `gitlab.mixins.GetWithoutIdMixin`, `gitlab.base.RESTManager`**Object Creation****Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

```
get(id: Optional[Union[int, str]] = None, **kwargs: Any) →
    Optional[gitlab.v4.objects.pipelines.ProjectPipelineTestReportSummary]
```

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (`Optional[Union[int, str]]`) –
- **kwargs** (`Any`) –

Returns The generated `RESTObject`**Raises**

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `Optional[gitlab.v4.objects.pipelines.ProjectPipelineTestReportSummary]`**gitlab:** `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectPipelineVariable(manager: gitlab.base.RESTManager, attrs: Dict[str,
    Any], *, created_from_list: bool = False)
```

Bases: `gitlab.base.RESTObject`**Parameters**

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: [*gitlab.base.RESTManager*](#)

```
class gitlab.v4.objects.ProjectPipelineVariableManager(gl: gitlab.client.Gitlab, parent:
                                                    Optional[gitlab.base.RESTObject] = None)
```

Bases: [*gitlab.mixins.ListMixin*](#), [*gitlab.base.RESTManager*](#)

Object Creation

Object update

Parameters

- **gl** ([*gitlab.client.Gitlab*](#)) –
- **parent** ([*Optional\[gitlab.base.RESTObject\]*](#)) –

Return type *None*

gitlab: [*gitlab.client.Gitlab*](#)

```
class gitlab.v4.objects.ProjectProtectedBranch(manager: gitlab.base.RESTManager, attrs: Dict[str,
                                                                                          Any], *, created_from_list: bool = False)
```

Bases: [*gitlab.mixins.ObjectDeleteMixin*](#), [*gitlab.base.RESTObject*](#)

Parameters

- **manager** ([*gitlab.base.RESTManager*](#)) –
- **attrs** ([*Dict\[str, Any\]*](#)) –
- **created_from_list** (*bool*) –

Return type *None*

manager: [*gitlab.base.RESTManager*](#)

```
class gitlab.v4.objects.ProjectProtectedBranchManager(gl: gitlab.client.Gitlab, parent:
                                                    Optional[gitlab.base.RESTObject] = None)
```

Bases: [*gitlab.mixins.NoUpdateMixin*](#), [*gitlab.base.RESTManager*](#)

Object Creation

Object update

Parameters

- **gl** ([*gitlab.client.Gitlab*](#)) –
- **parent** ([*Optional\[gitlab.base.RESTObject\]*](#)) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) →
    gitlab.v4.objects.branches.ProjectProtectedBranch
```

Retrieve a single object.

Parameters

- **id** ([*Union\[str, int\]*](#)) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type `gitlab.v4.objects.branches.ProjectProtectedBranch`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectProtectedTag(manager: gitlab.base.RESTManager, attrs: Dict[str, Any],
*, created_from_list: bool = False)
```

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **`manager`** (`gitlab.base.RESTManager`) –
- **`attrs`** (`Dict[str, Any]`) –
- **`created_from_list`** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectProtectedTagManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.NoUpdateMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **`gl`** (`gitlab.client.Gitlab`) –
- **`parent`** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.tags.ProjectProtectedTag
```

Retrieve a single object.

Parameters

- **`id`** (`Union[str, int]`) – ID of the object to retrieve
- **`lazy`** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- **`**kwargs`** – Extra options to send to the server (e.g. sudo)
- **`kwargs`** (`Any`) –

Returns The generated RESTObject.

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type `gitlab.v4.objects.tags.ProjectProtectedTag`

gitlab: [`gitlab.client.Gitlab`](#)

class `gitlab.v4.objects.ProjectPushRules`(*manager*: [`gitlab.base.RESTManager`](#), *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`)

Bases: [`gitlab.mixins.SaveMixin`](#), [`gitlab.mixins.ObjectDeleteMixin`](#), [`gitlab.base.RESTObject`](#)

Parameters

- **manager** ([`gitlab.base.RESTManager`](#)) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: [`gitlab.base.RESTManager`](#)

class `gitlab.v4.objects.ProjectPushRulesManager`(*gl*: [`gitlab.client.Gitlab`](#), *parent*: `Optional[gitlab.base.RESTObject] = None`)

Bases: [`gitlab.mixins.GetWithoutIdMixin`](#), [`gitlab.mixins.CreateMixin`](#), [`gitlab.mixins.UpdateMixin`](#), [`gitlab.mixins.DeleteMixin`](#), [`gitlab.base.RESTManager`](#)

Object Creation

Object update

Parameters

- **gl** ([`gitlab.client.Gitlab`](#)) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id*: `Optional[Union[int, str]] = None`, ***kwargs*: `Any`) → `Optional[gitlab.v4.objects.push_rules.ProjectPushRules]`

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **id** (`Optional[Union[int, str]]`) –
- **kwargs** (`Any`) –

Returns The generated `RESTObject`

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the server cannot perform the request

Return type `Optional[gitlab.v4.objects.push_rules.ProjectPushRules]`

gitlab: [`gitlab.client.Gitlab`](#)

class `gitlab.v4.objects.ProjectRegistryRepository`(*manager*: [`gitlab.base.RESTManager`](#), *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`)

Bases: [`gitlab.mixins.ObjectDeleteMixin`](#), [`gitlab.base.RESTObject`](#)

Parameters

- **manager** ([`gitlab.base.RESTManager`](#)) –

- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –

Return type `None`

tags: `ProjectRegistryTagManager`

```
class gitlab.v4.objects.ProjectRegistryRepositoryManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] =
None)
```

Bases: `gitlab.mixins.DeleteMixin`, `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectRegistryTag(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
created_from_list: bool = False)
```

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectRegistryTagManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.DeleteMixin`, `gitlab.mixins.RetrieveMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

delete_in_bulk(`name_regex_delete: str`, `**kwargs: Any`) → `None`

Delete Tag in bulk

Parameters

- **name_regex_delete** (`str`) – The regex of the name to delete. To delete all tags specify `.*`.

- **keep_n** – The amount of latest tags of given name to keep.
- **name_regex_keep** – The regex of the name to keep. This value overrides any matches from `name_regex`.
- **older_than** – Tags to delete that are older than the given time, written in human readable form 1h, 1d, 1month.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Raises

- **[GitlabAuthenticationError](#)** – If authentication is not correct
- **[GitlabDeleteError](#)** – If the server cannot perform the request

Return type `None`

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: *Any*) → `gitlab.v4.objects.container_registry.ProjectRegistryTag`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Returns The generated `RESTObject`.**Raises**

- **[GitlabAuthenticationError](#)** – If authentication is not correct
- **[GitlabGetError](#)** – If the server cannot perform the request

Return type `gitlab.v4.objects.container_registry.ProjectRegistryTag`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.ProjectRelease`(*manager*: `gitlab.base.RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

links: `ProjectReleaseLinkManager`

class gitlab.v4.objects.**ProjectReleaseLink**(*manager*: gitlab.base.RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False)

Bases: *gitlab.mixins.ObjectDeleteMixin*, *gitlab.mixins.SaveMixin*, *gitlab.base.RESTObject*

Parameters

- **manager** (gitlab.base.RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –

Return type None

manager: *gitlab.base.RESTManager*

class gitlab.v4.objects.**ProjectReleaseLinkManager**(*gl*: gitlab.client.Gitlab, *parent*: Optional[gitlab.base.RESTObject] = None)

Bases: *gitlab.mixins.CRUDMixin*, *gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (gitlab.client.Gitlab) –
- **parent** (Optional[gitlab.base.RESTObject]) –

Return type None

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → *gitlab.v4.objects.releases.ProjectReleaseLink*

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.releases.ProjectReleaseLink*

gitlab: *gitlab.client.Gitlab*

class gitlab.v4.objects.**ProjectReleaseManager**(*gl*: gitlab.client.Gitlab, *parent*: Optional[gitlab.base.RESTObject] = None)

Bases: *gitlab.mixins.CRUDMixin*, *gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → `gitlab.v4.objects.releases.ProjectRelease`

Retrieve a single object.

Parameters

- `id` (`Union[str, int]`) – ID of the object to retrieve
- `lazy` (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` – Extra options to send to the server (e.g. `sudo`)
- `kwargs` (`Any`) –

Returns The generated `RESTObject`.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type `gitlab.v4.objects.releases.ProjectRelease`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.ProjectRemoteMirror`(*manager*: `gitlab.base.RESTManager`, *attrs*: `Dict[str, Any]`, **, created_from_list*: `bool = False`)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.base.RESTObject`

Parameters

- `manager` (`gitlab.base.RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.ProjectRemoteMirrorManager`(*gl*: `gitlab.client.Gitlab`, *parent*: `Optional[gitlab.base.RESTObject] = None`)

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- `gl` (`gitlab.client.Gitlab`) –
- `parent` (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectRunner(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type `None`

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.ProjectRunnerManager(gl: gitlab.client.Gitlab, parent:
                                           Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.CreateMixin](#), [gitlab.mixins.DeleteMixin](#), [gitlab.mixins.ListMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- `scope`
- `tag_list`

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type `None`

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.ProjectService(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                       created_from_list: bool = False)
```

Bases: [gitlab.mixins.SaveMixin](#), [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type `None`

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.ProjectServiceManager(gl: gitlab.client.Gitlab, parent:
                                              Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.GetMixin](#), [gitlab.mixins.UpdateMixin](#), [gitlab.mixins.DeleteMixin](#), [gitlab.mixins.ListMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`**available**(***kwargs: Any*) → `List[str]`

List the services known by python-gitlab.

Returns The list of service code names.**Parameters** **kwargs** (*Any*) –**Return type** `List[str]`**get**(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → `gitlab.v4.objects.services.ProjectService`

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated `RESTObject`.**Raises**

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type `gitlab.v4.objects.services.ProjectService`**gitlab:** `gitlab.client.Gitlab`**class** `gitlab.v4.objects.ProjectSnippet`(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)Bases: `gitlab.mixins.UserAgentDetailMixin`, `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`**Parameters**

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type `None`**awardemojis:** `gitlab.v4.objects.award_emojis.ProjectSnippetAwardEmojiManager`**content**(*streamed: bool = False, action: Optional[Callable[[...], Any]] = None, chunk_size: int = 1024, **kwargs: Any*) → `Optional[bytes]`

Return the content of a snippet.

Parameters

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment.
- **action** (*Optional*[*Callable*[[...], *Any*]]) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabGetError*** – If the content could not be retrieved

Returns The snippet content**Return type** *Optional*[bytes]**discussions:** *gitlab.v4.objects.discussions.ProjectSnippetDiscussionManager***notes:** *gitlab.v4.objects.notes.ProjectSnippetNoteManager*

```
class gitlab.v4.objects.ProjectSnippetAwardEmoji(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: *gitlab.mixins.ObjectDeleteMixin*, *gitlab.base.RESTObject***Parameters**

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –

Return type *None***manager:** *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectSnippetAwardEmojiManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.NoUpdateMixin*, *gitlab.base.RESTManager***Object Creation****Object update****Parameters**

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional*[*gitlab.base.RESTObject*]) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.award_emojis.ProjectSnippetAwardEmoji
```

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.award_emojis.ProjectSnippetAwardEmoji*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectSnippetDiscussion(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

notes: *gitlab.v4.objects.notes.ProjectSnippetDiscussionNoteManager*

```
class gitlab.v4.objects.ProjectSnippetDiscussionManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.discussions.ProjectSnippetDiscussion
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.discussions.ProjectSnippetDiscussion*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectSnippetDiscussionNote(manager: gitlab.base.RESTManager, attrs:
    Dict[str, Any], *, created_from_list: bool =
    False)
```

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectSnippetDiscussionNoteManager(gl: gitlab.client.Gitlab, parent:
    Optional[gitlab.base.RESTObject] =
    None)
```

Bases: *gitlab.mixins.GetMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) →
    gitlab.v4.objects.notes.ProjectSnippetDiscussionNote
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type `gitlab.v4.objects.notes.ProjectSnippetDiscussionNote`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectSnippetManager(gl: gitlab.client.Gitlab, parent:
Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **`gl`** (`gitlab.client.Gitlab`) –
- **`parent`** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

`get` (`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `gitlab.v4.objects.snippets.ProjectSnippet`

Retrieve a single object.

Parameters

- **`id`** (`Union[str, int]`) – ID of the object to retrieve
- **`lazy`** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- **`**kwargs`** – Extra options to send to the server (e.g. sudo)
- **`kwargs`** (`Any`) –

Returns The generated RESTObject.

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type `gitlab.v4.objects.snippets.ProjectSnippet`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectSnippetNote(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **`manager`** (`gitlab.base.RESTManager`) –
- **`attrs`** (`Dict[str, Any]`) –
- **`created_from_list`** (`bool`) –

Return type `None`

awardemojis: `gitlab.v4.objects.award_emojis.ProjectSnippetNoteAwardEmojiManager`

```
class gitlab.v4.objects.ProjectSnippetNoteAwardEmoji(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.award_emojis.ProjectSnippetNoteAwardEmoji
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.award_emojis.ProjectSnippetNoteAwardEmoji*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectSnippetNoteManager(gl: gitlab.client.Gitlab, parent:
                                                    Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.notes.ProjectSnippetNote
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.notes.ProjectSnippetNote*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectStorage(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                       created_from_list: bool = False)
```

Bases: *gitlab.mixins.RefreshMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectStorageManager(gl: gitlab.client.Gitlab, parent:
                                              Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.GetWithoutIdMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get (*id: Optional[Union[int, str]] = None, **kwargs: Any*) → `Optional[gitlab.v4.objects.projects.ProjectStorage]`

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (`Optional[Union[int, str]]`) –
- **kwargs** (`Any`) –

Returns The generated `RESTObject`

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type `Optional[gitlab.v4.objects.projects.ProjectStorage]`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectTag(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                   created_from_list: bool = False)
```

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectTagManager(gl: gitlab.client.Gitlab, parent:
                                           Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.NoUpdateMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get (*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → `gitlab.v4.objects.tags.ProjectTag`

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.tags.ProjectTag*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectTrigger(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                       created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectTriggerManager(gl: gitlab.client.Gitlab, parent:
                                              Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.triggers.ProjectTrigger
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabGetError*** – If the server cannot perform the request

Return type *gitlab.v4.objects.triggers.ProjectTrigger*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectUser(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectUserManager(gl: gitlab.client.Gitlab, parent:
                                           Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.ListMixin, gitlab.base.RESTManager*

Object listing filters

- **search**
- **skip_users**

Object Creation**Object update****Parameters**

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.ProjectVariable(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                         created_from_list: bool = False)
```

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectVariableManager(gl: gitlab.client.Gitlab, parent:
                                             Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.variables.ProjectVariable
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.variables.ProjectVariable`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.ProjectWiki(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.ProjectWikiManager(gl: gitlab.client.Gitlab, parent:
                                             Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object listing filters

- **with_content**

Object Creation**Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`**get** (*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) → *gitlab.v4.objects.wikis.ProjectWiki*

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If *True*, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. *sudo*)
- **kwargs** (*Any*) –

Returns The generated *RESTObject*.**Raises**

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.wikis.ProjectWiki***gitlab:** *gitlab.client.Gitlab***class** *gitlab.v4.objects.RepositoryMixin*Bases: *object***delete_merged_branches** (***kwargs*: *Any*) → *None*

Delete merged branches.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. *sudo*)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabDeleteError* – If the server failed to perform the request

Return type `None`**repository_archive** (*sha*: *str* = *None*, *streamed*: *bool* = *False*, *action*: *Optional*[*Callable*[[*...*], *Any*]] = *None*, *chunk_size*: *int* = 1024, *format*: *Optional*[*str*] = *None*, ***kwargs*: *Any*) → *Optional*[*bytes*]

Return an archive of the repository.

Parameters

- **sha** (*str*) – ID of the commit (default branch by default)

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **action** (*Optional[Callable[[...], Any]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- **format** (*Optional[str]*) – file format (tar.gz by default)
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns The binary data of the archive

Return type *Optional[bytes]*

repository_blob(*sha: str, **kwargs: Any*) → Union[Dict[str, Any], requests.models.Response]

Return a file by blob SHA.

Parameters

- **sha** (*str*) – ID of the blob
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns The blob content and metadata

Return type *Union[Dict[str, Any], requests.models.Response]*

repository_compare(*from_: str, to: str, **kwargs: Any*) → Union[Dict[str, Any], requests.models.Response]

Return a diff between two branches/commits.

Parameters

- **from** – Source branch/SHA
- **to** (*str*) – Destination branch/SHA
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **from_** (*str*) –
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns The diff

Return type *Union[Dict[str, Any], requests.models.Response]*

repository_contributors (**kwargs: Any) → Union[*gitlab.client.GitlabList*, List[Dict[str, Any]]]

Return a list of contributors for the project.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server failed to perform the request

Returns The contributors

Return type *Union[gitlab.client.GitlabList, List[Dict[str, Any]]]*

repository_raw_blob(sha: str, streamed: bool = False, action: Optional[Callable[[...], Any]] = None, chunk_size: int = 1024, **kwargs: Any) → Optional[bytes]

Return the raw file contents for a blob.

Parameters

- **sha** (str) – ID of the blob
- **streamed** (bool) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **action** (Optional[Callable[[...], Any]]) – Callable responsible of dealing with chunk of data
- **chunk_size** (int) – Size of each chunk
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server failed to perform the request

Returns The blob content if streamed is False, None otherwise

Return type *Optional[bytes]*

repository_tree(path: str = "", ref: str = "", recursive: bool = False, **kwargs: Any) → Union[*gitlab.client.GitlabList*, List[Dict[str, Any]]]

Return a list of files in the repository.

Parameters

- **path** (str) – Path of the top folder (/ by default)

- **ref** (*str*) – Reference to a commit or branch
- **recursive** (*bool*) – Whether to get the tree recursively
- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns The representation of the tree

Return type `Union[gitlab.client.GitlabList, List[Dict[str, Any]]]`

update_submodule (*submodule: str, branch: str, commit_sha: str, **kwargs: Any*) → `Union[Dict[str, Any], requests.models.Response]`

Update a project submodule

Parameters

- **submodule** (*str*) – Full path to the submodule
- **branch** (*str*) – Name of the branch to commit into
- **commit_sha** (*str*) – Full commit SHA to update the submodule to
- **commit_message** – Commit message. If no message is provided, a default one will be set (optional)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPutError** – If the submodule could not be updated

Return type `Union[Dict[str, Any], requests.models.Response]`

class `gitlab.v4.objects.Runner` (*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: `gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (*bool*) –

Return type `None`

jobs: `gitlab.v4.objects.runners.RunnerJobManager`

```
class gitlab.v4.objects.RunnerJob(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                  created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.RunnerJobManager(gl: gitlab.client.Gitlab, parent:
                                         Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.ListMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- **status**

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.RunnerManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject]
                                       = None)
```

Bases: [gitlab.mixins.CRUDMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- **scope**
- **tag_list**

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

```
all(scope: Optional[str] = None, **kwargs: Any) → List[gitlab.v4.objects.runners.Runner]
```

List all the runners.

Parameters

- **scope** (*Optional[str]*) – The scope of runners to show, one of: specific, shared, active, paused, online

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns A list of runners matching the scope.

Return type *List[gitlab.v4.objects.runners.Runner]*

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → *gitlab.v4.objects.runners.Runner*

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.runners.Runner*

gitlab: *gitlab.client.Gitlab*

verify(*token*: str, ***kwargs*: Any) → None

Validates authentication credentials for a registered Runner.

Parameters

- **token** (str) – The runner's authentication token
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabVerifyError** – If the server failed to verify the token

Return type None

class `gitlab.v4.objects.SidekiqManager`(*gl*: `gitlab.client.Gitlab`, *parent*: *Optional*[`gitlab.base.RESTObject`] = *None*)

Bases: `gitlab.base.RESTManager`

Manager for the Sidekiq methods.

This manager doesn't actually manage objects but provides helper function for the sidekiq metrics API.

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional*[`gitlab.base.RESTObject`]) –

Return type `None`

compound_metrics(***kwargs*: *Any*) → `Union`[`Dict`[`str`, *Any*], `requests.models.Response`]

Return all available metrics and statistics.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the information couldn't be retrieved

Returns All available Sidekiq metrics and statistics

Return type `Union`[`Dict`[`str`, *Any*], `requests.models.Response`]

gitlab: `gitlab.client.Gitlab`

job_stats(***kwargs*: *Any*) → `Union`[`Dict`[`str`, *Any*], `requests.models.Response`]

Return statistics about the jobs performed.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the information couldn't be retrieved

Returns Statistics about the Sidekiq jobs performed

Return type `Union`[`Dict`[`str`, *Any*], `requests.models.Response`]

process_metrics(***kwargs*: *Any*) → `Union`[`Dict`[`str`, *Any*], `requests.models.Response`]

Return the registered sidekiq workers.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. `sudo`)
- **kwargs** (*Any*) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the information couldn't be retrieved

Returns Information about the register Sidekiq worker

Return type `Union[Dict[str, Any], requests.models.Response]`

queue_metrics(***kwargs: Any*) → `Union[Dict[str, Any], requests.models.Response]`

Return the registered queues information.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the information couldn't be retrieved

Returns Information about the Sidekiq queues

Return type `Union[Dict[str, Any], requests.models.Response]`

class `gitlab.v4.objects.Snippet`(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: [`gitlab.mixins.UserAgentDetailMixin`](#), [`gitlab.mixins.SaveMixin`](#), [`gitlab.mixins.ObjectDeleteMixin`](#), [`gitlab.base.RESTObject`](#)

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (*bool*) –

Return type `None`

content(*streamed: bool = False, action: Optional[Callable[[...], Any]] = None, chunk_size: int = 1024, **kwargs: Any*) → `Optional[bytes]`

Return the content of a snippet.

Parameters

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment.
- **action** (`Optional[Callable[[...], Any]]`) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the content could not be retrieved

Returns The snippet content

Return type *Optional*[bytes]

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.SnippetManager(gl: gitlab.client.Gitlab, parent:
                                     Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CRUDMixin*, *gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional*[*gitlab.base.RESTObject*]) –

Return type *None*

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.snippets.Snippet
```

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated *RESTObject*.

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.snippets.Snippet*

gitlab: *gitlab.client.Gitlab*

```
public(**kwargs: Any) → Union[gitlab.base.RESTObjectList, List[gitlab.base.RESTObject]]
```

List all the public snippets.

Parameters

- **all** – If True the returned object will be a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises *GitlabListError* – If the list could not be retrieved

Returns A generator for the snippets list

Return type *Union*[*gitlab.base.RESTObjectList*, *List*[*gitlab.base.RESTObject*]]

```
class gitlab.v4.objects.StarredProject(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                       created_from_list: bool = False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.StarredProjectManager(gl: gitlab.client.Gitlab, parent:
                                              Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.ListMixin, gitlab.base.RESTManager*

Object listing filters

- archived
- membership
- min_access_level
- order_by
- owned
- search
- simple
- sort
- starred
- statistics
- visibility
- with_custom_attributes
- with_issues_enabled
- with_merge_requests_enabled

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.Todo(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                             created_from_list: bool = False)
```

Bases: [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

manager: [gitlab.base.RESTManager](#)

mark_as_done(**kwargs: Any) → [Dict\[str, Any\]](#)

Mark the todo as done.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** ([Any](#)) –

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabTodoError](#) – If the server failed to perform the request

Returns A dict with the result

Return type [Dict\[str, Any\]](#)

```
class gitlab.v4.objects.TodoManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] =
                                   None)
```

Bases: [gitlab.mixins.ListMixin](#), [gitlab.mixins.DeleteMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- action
- author_id
- project_id
- state
- type

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type [None](#)

gitlab: [gitlab.client.Gitlab](#)

mark_all_as_done(***kwargs: Any*) → None

Mark all the todos as done.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTodoError** – If the server failed to perform the request

Returns The number of todos marked done

Return type None

class gitlab.v4.objects.**Topic**(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type None

manager: *gitlab.base.RESTManager*

class gitlab.v4.objects.**TopicManager**(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.topics.Topic*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabGetError`** – If the server cannot perform the request

Return type `gitlab.v4.objects.topics.Topic`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.User(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                             created_from_list: bool = False)
```

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

Parameters

- **`manager`** (`gitlab.base.RESTManager`) –
- **`attrs`** (`Dict[str, Any]`) –
- **`created_from_list`** (`bool`) –

Return type `None`

```
activate(**kwargs: Any) → Union[Dict[str, Any], requests.models.Response]
```

Activate the user.

Parameters

- **`**kwargs`** – Extra options to send to the server (e.g. sudo)
- **`kwargs`** (`Any`) –

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabActivateError`** – If the user could not be activated

Returns Whether the user status has been changed

Return type `Union[Dict[str, Any], requests.models.Response]`

```
block(**kwargs: Any) → Union[Dict[str, Any], requests.models.Response]
```

Block the user.

Parameters

- **`**kwargs`** – Extra options to send to the server (e.g. sudo)
- **`kwargs`** (`Any`) –

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabBlockError`** – If the user could not be blocked

Returns Whether the user status has been changed

Return type `Union[Dict[str, Any], requests.models.Response]`

customattributes: `gitlab.v4.objects.custom_attributes.UserCustomAttributeManager`

```
deactivate(**kwargs: Any) → Union[Dict[str, Any], requests.models.Response]
```

Deactivate the user.

Parameters

- **`**kwargs`** – Extra options to send to the server (e.g. sudo)

- **kwargs** (*Any*) –

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabDeactivateError*** – If the user could not be deactivated

Returns Whether the user status has been changed

Return type *Union[Dict[str, Any], requests.models.Response]*

emails: *UserEmailManager*

events: *gitlab.v4.objects.events.UserEventManager*

follow(***kwargs: Any*) → *Union[Dict[str, Any], requests.models.Response]*

Follow the user.

Parameters

- *****kwargs*** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabFollowError*** – If the user could not be followed

Returns The new object data (*not* a RESTObject)

Return type *Union[Dict[str, Any], requests.models.Response]*

followers_users: *UserFollowersManager*

following_users: *UserFollowingManager*

gpgkeys: *UserGPGKeyManager*

identityproviders: *UserIdentityProviderManager*

impersonationtokens: *UserImpersonationTokenManager*

keys: *UserKeyManager*

memberships: *UserMembershipManager*

personal_access_tokens:
gitlab.v4.objects.personal_access_tokens.UserPersonalAccessTokenManager

projects: *UserProjectManager*

starred_projects: *StarredProjectManager*

status: *UserStatusManager*

unblock(***kwargs: Any*) → *Union[Dict[str, Any], requests.models.Response]*

Unblock the user.

Parameters

- *****kwargs*** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabUnblockError`** – If the user could not be unblocked

Returns Whether the user status has been changed

Return type `Union[Dict[str, Any], requests.models.Response]`

unfollow(***kwargs: Any*) → `Union[Dict[str, Any], requests.models.Response]`

Unfollow the user.

Parameters

- **`**kwargs`** – Extra options to send to the server (e.g. `sudo`)
- **`kwargs`** (*Any*) –

Raises

- **`GitlabAuthenticationError`** – If authentication is not correct
- **`GitlabUnfollowError`** – If the user could not be followed

Returns The new object data (*not* a `RESTObject`)

Return type `Union[Dict[str, Any], requests.models.Response]`

```
class gitlab.v4.objects.UserActivities(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                       created_from_list: bool = False)
```

Bases: `gitlab.base.RESTObject`

Parameters

- **`manager`** (`gitlab.base.RESTManager`) –
- **`attrs`** (`Dict[str, Any]`) –
- **`created_from_list`** (*bool*) –

Return type `None`

manager: `gitlab.base.RESTManager`

```
class gitlab.v4.objects.UserActivitiesManager(gl: gitlab.client.Gitlab, parent:
                                             Optional[gitlab.base.RESTObject] = None)
```

Bases: `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`

Object Creation**Object update****Parameters**

- **`gl`** (`gitlab.client.Gitlab`) –
- **`parent`** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

```
class gitlab.v4.objects.UserCustomAttribute(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –

Return type [None](#)

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.UserCustomAttributeManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.RetrieveMixin](#), [gitlab.mixins.SetMixin](#), [gitlab.mixins.DeleteMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** ([Optional\[gitlab.base.RESTObject\]](#)) –

Return type [None](#)

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.custom_attributes.UserCustomAttribute
```

Retrieve a single object.

Parameters

- **id** ([Union\[str, int\]](#)) – ID of the object to retrieve
- **lazy** ([bool](#)) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** ([Any](#)) –

Returns The generated [RESTObject](#).

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Return type [gitlab.v4.objects.custom_attributes.UserCustomAttribute](#)

gitlab: [gitlab.client.Gitlab](#)

```
class gitlab.v4.objects.UserEmail(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: [gitlab.mixins.ObjectDeleteMixin](#), [gitlab.base.RESTObject](#)

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.UserEmailManager`(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → `gitlab.v4.objects.users.UserEmail`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.users.UserEmail`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.UserEvent`(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: `gitlab.v4.objects.events.Event`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.UserEventManager`(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: `gitlab.v4.objects.events.EventManager`

Object listing filters

- `action`
- `target_type`
- `before`
- `after`
- `sort`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: `gitlab.client.Gitlab`

class `gitlab.v4.objects.UserGPGKey`(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: `gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject`

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: `gitlab.base.RESTManager`

class `gitlab.v4.objects.UserGPGKeyManager`(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: `gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager`

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → *gitlab.v4.objects.users.UserGPGKey*

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.users.UserGPGKey*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.UserIdentityProviderManager(gl: gitlab.client.Gitlab, parent:
                                                    Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

Manager for user identities.

This manager does not actually manage objects but enables functionality for deletion of user identities by provider.

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.UserImpersonationToken(manager: gitlab.base.RESTManager, attrs: Dict[str,
                                                                                               Any], *, created_from_list: bool = False)
```

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (bool) –

Return type None

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.UserImpersonationTokenManager(gl: gitlab.client.Gitlab, parent:
                                                    Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.NoUpdateMixin*, *gitlab.base.RESTManager*

Object listing filters

- `state`

Object Creation

Object update

Parameters

- `gl` (*gitlab.client.Gitlab*) –
- `parent` (*Optional[gitlab.base.RESTObject]*) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) →
    gitlab.v4.objects.users.UserImpersonationToken
```

Retrieve a single object.

Parameters

- `id` (*Union[str, int]*) – ID of the object to retrieve
- `lazy` (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` – Extra options to send to the server (e.g. `sudo`)
- `kwargs` (*Any*) –

Returns The generated *RESTObject*.

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

Return type *gitlab.v4.objects.users.UserImpersonationToken*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.UserKey(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                created_from_list: bool = False)
```

Bases: *gitlab.mixins.ObjectDeleteMixin*, *gitlab.base.RESTObject*

Parameters

- `manager` (*gitlab.base.RESTManager*) –
- `attrs` (*Dict[str, Any]*) –
- `created_from_list` (*bool*) –

Return type `None`

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.UserKeyManager(gl: gitlab.client.Gitlab, parent:
    Optional[gitlab.base.RESTObject] = None)

Bases:      gitlab.mixins.RetrieveMixin,      gitlab.mixins.CreateMixin,      gitlab.mixins.
DeleteMixin, gitlab.base.RESTManager
```

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → gitlab.v4.objects.users.UserKey
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type `gitlab.v4.objects.users.UserKey`

```
gitlab: gitlab.client.Gitlab
```

```
class gitlab.v4.objects.UserManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] =
    None)
```

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

Object listing filters

- active
- blocked
- username
- extern_uid
- provider
- external
- search
- custom_attributes
- status
- two_factor

Object Creation**Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (*Optional* [`gitlab.base.RESTObject`]) –

Return type `None`**get** (*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) → *gitlab.v4.objects.users.User*

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If *True*, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. *sudo*)
- **kwargs** (*Any*) –

Returns The generated *RESTObject*.**Raises**

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabGetError*** – If the server cannot perform the request

Return type *gitlab.v4.objects.users.User***gitlab:** *gitlab.client.Gitlab*

```
class gitlab.v4.objects.UserMembership(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                       created_from_list: bool = False)
```

Bases: *gitlab.base.RESTObject***Parameters**

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –

Return type `None`**manager:** *gitlab.base.RESTManager*

```
class gitlab.v4.objects.UserMembershipManager(gl: gitlab.client.Gitlab, parent:
                                             Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.RetrieveMixin*, *gitlab.base.RESTManager***Object listing filters**

- **type**

Object Creation**Object update****Parameters**

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.v4.objects.users.UserMembership*

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (`Any`) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.users.UserMembership*

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.UserPersonalAccessToken(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False)
```

Bases: *gitlab.base.RESTObject*

Parameters

- **manager** (`gitlab.base.RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –

Return type `None`

manager: *gitlab.base.RESTManager*

```
class gitlab.v4.objects.UserPersonalAccessTokenManager(gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None)
```

Bases: *gitlab.mixins.CreateMixin, gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (`gitlab.client.Gitlab`) –
- **parent** (`Optional[gitlab.base.RESTObject]`) –

Return type `None`

gitlab: *gitlab.client.Gitlab*

```
class gitlab.v4.objects.UserProject(manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *,
                                     created_from_list: bool = False)
```

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: [gitlab.base.RESTManager](#)

```
class gitlab.v4.objects.UserProjectManager(gl: gitlab.client.Gitlab, parent:
                                           Optional[gitlab.base.RESTObject] = None)
```

Bases: [gitlab.mixins.ListMixin](#), [gitlab.mixins.CreateMixin](#), [gitlab.base.RESTManager](#)

Object listing filters

- archived
- visibility
- order_by
- sort
- search
- simple
- owned
- membership
- starred
- statistics
- with_issues_enabled
- with_merge_requests_enabled
- with_custom_attributes
- with_programming_language
- wiki_checksum_failed
- repository_checksum_failed
- min_access_level
- id_after
- id_before

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type None

gitlab: [gitlab.client.Gitlab](#)

list(**kwargs: Any) → Union[[gitlab.base.RESTObjectList](#), List[[gitlab.base.RESTObject](#)]]

Retrieve a list of objects.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The list of objects, or a generator if *as_list* is False

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabListError](#) – If the server cannot perform the request

Return type Union[[gitlab.base.RESTObjectList](#), List[[gitlab.base.RESTObject](#)]]

class gitlab.v4.objects.**UserStatus**(manager: [gitlab.base.RESTManager](#), attrs: Dict[str, Any], *, created_from_list: bool = False)

Bases: [gitlab.base.RESTObject](#)

Parameters

- **manager** ([gitlab.base.RESTManager](#)) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –

Return type None

manager: [gitlab.base.RESTManager](#)

class gitlab.v4.objects.**UserStatusManager**(gl: [gitlab.client.Gitlab](#), parent: Optional[[gitlab.base.RESTObject](#)] = None)

Bases: [gitlab.mixins.GetWithoutIdMixin](#), [gitlab.base.RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([gitlab.client.Gitlab](#)) –
- **parent** (Optional[[gitlab.base.RESTObject](#)]) –

Return type None

get(*id*: *Optional[Union[int, str]] = None*, ***kwargs*: *Any*) → *Optional[gitlab.v4.objects.users.UserStatus]*

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *Optional[gitlab.v4.objects.users.UserStatus]*

gitlab: *gitlab.client.Gitlab*

class *gitlab.v4.objects.Variable*(*manager*: *gitlab.base.RESTManager*, *attrs*: *Dict[str, Any]*, *,
created_from_list: *bool = False*)

Bases: *gitlab.mixins.SaveMixin*, *gitlab.mixins.ObjectDeleteMixin*, *gitlab.base.RESTObject*

Parameters

- **manager** (*gitlab.base.RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

manager: *gitlab.base.RESTManager*

class *gitlab.v4.objects.VariableManager*(*gl*: *gitlab.client.Gitlab*, *parent*:
Optional[gitlab.base.RESTObject] = None)

Bases: *gitlab.mixins.CRUDMixin*, *gitlab.base.RESTManager*

Object Creation

Object update

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type *None*

get(*id*: *Union[str, int]*, *lazy*: *bool = False*, ***kwargs*: *Any*) → *gitlab.v4.objects.variables.Variable*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)

- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type *gitlab.v4.objects.variables.Variable*

gitlab: *gitlab.client.Gitlab*

Module contents

6.5.3 Submodules

6.5.4 gitlab.base module

class `gitlab.base.RESTManager`(*gl: gitlab.client.Gitlab, parent: Optional[gitlab.base.RESTObject] = None*)

Bases: `object`

Base class for CRUD operations on objects.

Derived class must define `_path` and `_obj_cls`.

`_path`: Base URL path on which requests will be sent (e.g. `‘/projects’`) `_obj_cls`: The class of objects that will be created

Parameters

- **gl** (*gitlab.client.Gitlab*) –
- **parent** (*Optional[gitlab.base.RESTObject]*) –

Return type `None`

gitlab: *gitlab.client.Gitlab*

property `parent_attrs`: `Optional[Dict[str, Any]]`

property `path`: `Optional[str]`

class `gitlab.base.RESTObject`(*manager: gitlab.base.RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False*)

Bases: `object`

Represents an object built from server data.

It holds the attributes know from the server, and the updated attributes in another. This allows smart updates, if the object allows it.

You can redefine `_id_attr` in child classes to specify which attribute must be used as the unique ID. `None` means that the object can be updated without ID in the url.

Likewise, you can define a `_repr_attr` in subclasses to specify which attribute should be added as a human-readable identifier when called in the object’s `__repr__()` method.

Parameters

- **manager** (*gitlab.base.RESTManager*) –

- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

Return type *None*

property attributes: *Dict[str, Any]*

property encoded_id: *Optional[Union[int, str]]*

Ensure that the ID is url-encoded so that it can be safely used in a URL path

get_id() → *Optional[Union[int, str]]*

Returns the id of the resource.

Return type *Optional[Union[int, str]]*

manager: *gitlab.base.RESTManager*

pformat() → *str*

Return type *str*

pprint() → *None*

Return type *None*

class *gitlab.base.RESTObjectList*(*manager: gitlab.base.RESTManager, obj_cls: Type[gitlab.base.RESTObject], _list: gitlab.client.GitlabList*)

Bases: *object*

Generator object representing a list of *RESTObject*'s.

This generator uses the Gitlab pagination system to fetch new data when required.

Note: you should not instantiate such objects, they are returned by calls to *RESTManager.list()*

Parameters

- **manager** (*RESTManager*) – Manager to attach to the created objects
- **obj_cls** (*Type[gitlab.base.RESTObject]*) – Type of objects to create from the json data
- **_list** (*gitlab.client.GitlabList*) – A *GitlabList* object

Return type *None*

property current_page: *int*

The current page number.

next() → *gitlab.base.RESTObject*

Return type *gitlab.base.RESTObject*

property next_page: *Optional[int]*

The next page number.

If *None*, the current page is the last.

property per_page: *Optional[int]*

The number of items per page.

property prev_page: `Optional[int]`

The previous page number.

If None, the current page is the first.

property total: `Optional[int]`

The total number of items.

property total_pages: `Optional[int]`

The total number of pages.

class `gitlab.base.RequiredOptional`(*required: Tuple[str, ...] = (), optional: Tuple[str, ...] = ()*)

Bases: `object`

Parameters

- **required** (*Tuple[str, ...]*) –
- **optional** (*Tuple[str, ...]*) –

Return type `None`

optional: `Tuple[str, ...] = ()`

required: `Tuple[str, ...] = ()`

6.5.5 gitlab.cli module

`gitlab.cli.cls_to_what`(*cls: gitlab.base.RESTObject*) → `str`

Parameters **cls** (*gitlab.base.RESTObject*) –

Return type `str`

`gitlab.cli.die`(*msg: str, e: Optional[Exception] = None*) → `None`

Parameters

- **msg** (*str*) –
- **e** (*Optional[Exception]*) –

Return type `None`

`gitlab.cli.docs`() → `argparse.ArgumentParser`

Provide a statically generated parser for sphinx only, so we don't need to provide dummy gitlab config for readthedocs.

Return type `argparse.ArgumentParser`

`gitlab.cli.main`() → `None`

Return type `None`

`gitlab.cli.register_custom_action`(*cls_names: Union[str, Tuple[str, ...]], mandatory: Tuple[str, ...] = (), optional: Tuple[str, ...] = (), custom_action: Optional[str] = None*) → `Callable[[gitlab.cli.__F], gitlab.cli.__F]`

Parameters

- **cls_names** (*Union[str, Tuple[str, ...]]*) –
- **mandatory** (*Tuple[str, ...]*) –

- **optional** (*Tuple*[*str*, ...]) –
- **custom_action** (*Optional*[*str*]) –

Return type *Callable*[[*gitlab.cli.__F*], *gitlab.cli.__F*]

gitlab.cli.what_to_cls(what: str, namespace: module) → Type[gitlab.base.RESTObject]

Parameters

- **what** (*str*) –
- **namespace** (*module*) –

Return type *Type*[*gitlab.base.RESTObject*]

6.5.6 gitlab.config module

exception *gitlab.config.ConfigError*

Bases: *Exception*

exception *gitlab.config.GitlabConfigHelperError*

Bases: *gitlab.config.ConfigError*

exception *gitlab.config.GitlabConfigMissingError*

Bases: *gitlab.config.ConfigError*

class *gitlab.config.GitlabConfigParser*(*gitlab_id: Optional[str] = None, config_files: Optional[List[str]] = None*)

Bases: *object*

Parameters

- **gitlab_id** (*Optional[str]*) –
- **config_files** (*Optional[List[str]]*) –

Return type *None*

exception *gitlab.config.GitlabDataError*

Bases: *gitlab.config.ConfigError*

exception *gitlab.config.GitlabIDError*

Bases: *gitlab.config.ConfigError*

6.5.7 gitlab.const module

6.5.8 gitlab.exceptions module

exception *gitlab.exceptions.GitlabActivateError*(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: *gitlab.exceptions.GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –

- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabAttachFileError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabAuthenticationError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabBlockError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabBuildCancelError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabCancelError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabBuildEraseError`(*error_message*: *Union[str, bytes]* = "",
response_code: *Optional[int]* = None,
response_body: *Optional[bytes]* = None)

Bases: [`gitlab.exceptions.GitlabRetryError`](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabBuildPlayError`(*error_message*: *Union[str, bytes]* = "",
response_code: *Optional[int]* = None,
response_body: *Optional[bytes]* = None)

Bases: [`gitlab.exceptions.GitlabRetryError`](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabBuildRetryError`(*error_message*: *Union[str, bytes]* = "",
response_code: *Optional[int]* = None,
response_body: *Optional[bytes]* = None)

Bases: [`gitlab.exceptions.GitlabRetryError`](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabCancelError`(*error_message*: *Union[str, bytes]* = "", *response_code*:
Optional[int] = None, *response_body*: *Optional[bytes]*
= None)

Bases: [`gitlab.exceptions.GitlabOperationError`](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabCherryPickError`(*error_message*: *Union[str, bytes]* = "",
response_code: *Optional[int]* = None,
response_body: *Optional[bytes]* = None)

Bases: [`gitlab.exceptions.GitlabOperationError`](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabConnectionError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabError](#)**Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabCreateError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabOperationError](#)**Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabDeactivateError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabOperationError](#)**Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabDeleteError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabOperationError](#)**Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –

- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabError`(*error_message: Union[str, bytes] = "*, *response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `Exception`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabFollowError`(*error_message: Union[str, bytes] = "*, *response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabGetError`(*error_message: Union[str, bytes] = "*, *response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabGroupTransferError`(*error_message: Union[str, bytes] = "*, *response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabHousekeepingError`(*error_message*: `Union[str, bytes]` = "",
response_code: `Optional[int]` = None,
response_body: `Optional[bytes]` = None)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type None

exception `gitlab.exceptions.GitlabHttpError`(*error_message*: `Union[str, bytes]` = "", *response_code*:
`Optional[int]` = None, *response_body*: `Optional[bytes]` =
None)

Bases: `gitlab.exceptions.GitlabError`

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type None

exception `gitlab.exceptions.GitlabImportError`(*error_message*: `Union[str, bytes]` = "", *response_code*:
`Optional[int]` = None, *response_body*: `Optional[bytes]`
= None)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type None

exception `gitlab.exceptions.GitlabJobCancelError`(*error_message*: `Union[str, bytes]` = "",
response_code: `Optional[int]` = None,
response_body: `Optional[bytes]` = None)

Bases: `gitlab.exceptions.GitlabCancelError`

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type None

exception `gitlab.exceptions.GitlabJobEraseError`(*error_message*: `Union[str, bytes]` = "", *response_code*:
`Optional[int]` = None, *response_body*:
`Optional[bytes]` = None)

Bases: `gitlab.exceptions.GitlabRetryError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabJobPlayError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabRetryError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabJobRetryError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabRetryError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabLicenseError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabListError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –

- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabMRApprovalError`(*error_message: Union[str, bytes] = "*
response_code: Optional[int] = None,
response_body: Optional[bytes] = None)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabMRClosedError`(*error_message: Union[str, bytes] = "*
response_code: Optional[int] = None, response_body:
Optional[bytes] = None)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabMRForbiddenError`(*error_message: Union[str, bytes] = "*
response_code: Optional[int] = None,
response_body: Optional[bytes] = None)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabMROnBuildSuccessError`(*error_message: Union[str, bytes] = "*
response_code: Optional[int] = None,
response_body: Optional[bytes] = None)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabMRRebaseError`(*error_message*: *Union[str, bytes]* = "", *response_code*: *Optional[int]* = None, *response_body*: *Optional[bytes]* = None)

Bases: [`gitlab.exceptions.GitlabOperationError`](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabMarkdownError`(*error_message*: *Union[str, bytes]* = "", *response_code*: *Optional[int]* = None, *response_body*: *Optional[bytes]* = None)

Bases: [`gitlab.exceptions.GitlabOperationError`](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabOperationError`(*error_message*: *Union[str, bytes]* = "", *response_code*: *Optional[int]* = None, *response_body*: *Optional[bytes]* = None)

Bases: [`gitlab.exceptions.GitlabError`](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabOwnershipError`(*error_message*: *Union[str, bytes]* = "", *response_code*: *Optional[int]* = None, *response_body*: *Optional[bytes]* = None)

Bases: [`gitlab.exceptions.GitlabOperationError`](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabParsingError`(*error_message*: *Union[str, bytes]* = "", *response_code*: *Optional[int]* = None, *response_body*: *Optional[bytes]* = None)

Bases: [`gitlab.exceptions.GitlabError`](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabPipelineCancelError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabCancelError](#)**Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabPipelinePlayError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabRetryError](#)**Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabPipelineRetryError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabRetryError](#)**Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabProjectDeployKeyError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabOperationError](#)**Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –

- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabPromoteError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabProtectError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabRenderError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabRepairError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabRetryError`(*error_message*: *Union[str, bytes]* = "", *response_code*: *Optional[int]* = None, *response_body*: *Optional[bytes]* = None)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabRevertError`(*error_message*: *Union[str, bytes]* = "", *response_code*: *Optional[int]* = None, *response_body*: *Optional[bytes]* = None)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabSearchError`(*error_message*: *Union[str, bytes]* = "", *response_code*: *Optional[int]* = None, *response_body*: *Optional[bytes]* = None)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabSetError`(*error_message*: *Union[str, bytes]* = "", *response_code*: *Optional[int]* = None, *response_body*: *Optional[bytes]* = None)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabStopError`(*error_message*: *Union[str, bytes]* = "", *response_code*: *Optional[int]* = None, *response_body*: *Optional[bytes]* = None)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabSubscribeError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabTimeTrackingError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabTodoError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception gitlab.exceptions.GitlabTransferProjectError(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: [gitlab.exceptions.GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –

- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabUnblockError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabUnfollowError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabUnsubscribeError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabUpdateError`(*error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None*)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type None

exception `gitlab.exceptions.GitlabUploadError`(*error_message*: `Union[str, bytes]` = "", *response_code*: `Optional[int]` = `None`, *response_body*: `Optional[bytes]` = `None`)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type `None`

exception `gitlab.exceptions.GitlabVerifyError`(*error_message*: `Union[str, bytes]` = "", *response_code*: `Optional[int]` = `None`, *response_body*: `Optional[bytes]` = `None`)

Bases: `gitlab.exceptions.GitlabOperationError`

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type `None`

exception `gitlab.exceptions.RedirectError`(*error_message*: `Union[str, bytes]` = "", *response_code*: `Optional[int]` = `None`, *response_body*: `Optional[bytes]` = `None`)

Bases: `gitlab.exceptions.GitlabError`

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type `None`

`gitlab.exceptions.on_http_error`(*error*: `Type[Exception]`) → `Callable[[gitlab.exceptions.__F], gitlab.exceptions.__F]`

Manage `GitlabHttpError` exceptions.

This decorator function can be used to catch `GitlabHttpError` exceptions raise specialized exceptions instead.

Parameters

- **GitlabError** (The exception type to raise -- must inherit from) –
- **error** (`Type[Exception]`) –

Return type `Callable[[gitlab.exceptions.__F], gitlab.exceptions.__F]`

6.5.9 gitlab.mixins module

class gitlab.mixins.AccessRequestMixin

Bases: object

approve(*access_level: int = 30, **kwargs: Any*) → None

Approve an access request.

Parameters

- **access_level** (*int*) – The access level for the user
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server fails to perform the request

Return type None

manager: *gitlab.base.RESTManager*

class gitlab.mixins.BadgeRenderMixin

Bases: object

render(*link_url: str, image_url: str, **kwargs: Any*) → Dict[str, Any]

Preview link_url and image_url after interpolation.

Parameters

- **link_url** (*str*) – URL of the badge link
- **image_url** (*str*) – URL of the badge image
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabRenderError** – If the rendering failed

Returns The rendering properties

Return type Dict[str, Any]

class gitlab.mixins.CRUDMixin

Bases: *gitlab.mixins.GetMixin, gitlab.mixins.ListMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin*

gitlab: *gitlab.client.Gitlab*

class gitlab.mixins.CreateMixin

Bases: object

create(*data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *gitlab.base.RESTObject*

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – parameters to send to the server to create the resource
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns

A new instance of the managed object class built with the data sent by the server

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabCreateError* – If the server cannot perform the request

Return type *gitlab.base.RESTObject*

gitlab: *gitlab.client.Gitlab*

class *gitlab.mixins.DeleteMixin*

Bases: object

delete(*id: Optional[Union[int, str]] = None, **kwargs: Any*) → None

Delete an object on the server.

Parameters

- **id** (*Optional[Union[int, str]]*) – ID of the object to delete
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabDeleteError* – If the server cannot perform the request

Return type None

gitlab: *gitlab.client.Gitlab*

class *gitlab.mixins.DownloadMixin*

Bases: object

download(*streamed: bool = False, action: Optional[Callable] = None, chunk_size: int = 1024, **kwargs: Any*) → *Optional[bytes]*

Download the archive of a resource export.

Parameters

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **action** (*Optional[Callable]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** – Extra options to send to the server (e.g. sudo)

- **kwargs** (*Any*) –

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabGetError*** – If the server failed to perform the request

Returns The blob content if streamed is False, None otherwise

Return type *Optional*[bytes]

manager: *gitlab.base.RESTManager*

class gitlab.mixins.GetMixin

Bases: object

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *gitlab.base.RESTObject*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The generated RESTObject.

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabGetError*** – If the server cannot perform the request

Return type *gitlab.base.RESTObject*

gitlab: *gitlab.client.Gitlab*

class gitlab.mixins.GetWithoutIdMixin

Bases: object

get(*id: Optional[Union[int, str]] = None, **kwargs: Any*) → *Optional[gitlab.base.RESTObject]*

Retrieve a single object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **id** (*Optional[Union[int, str]]*) –
- **kwargs** (*Any*) –

Returns The generated RESTObject

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabGetError*** – If the server cannot perform the request

Return type *Optional[gitlab.base.RESTObject]*

gitlab: *gitlab.client.Gitlab*

class gitlab.mixins.ListMixin

Bases: object

gitlab: *gitlab.client.Gitlab*

list(**kwargs: Any) → Union[*gitlab.base.RESTObjectList*, List[*gitlab.base.RESTObject*]]

Retrieve a list of objects.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The list of objects, or a generator if *as_list* is False

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabListError* – If the server cannot perform the request

Return type Union[*gitlab.base.RESTObjectList*, List[*gitlab.base.RESTObject*]]

class gitlab.mixins.NoUpdateMixin

Bases: *gitlab.mixins.GetMixin*, *gitlab.mixins.ListMixin*, *gitlab.mixins.CreateMixin*, *gitlab.mixins.DeleteMixin*

gitlab: *gitlab.client.Gitlab*

class gitlab.mixins.ObjectDeleteMixin

Bases: object

Mixin for RESTObject's that can be deleted.

delete(**kwargs: Any) → None

Delete the object from the server.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabDeleteError* – If the server cannot perform the request

Return type None

manager: *gitlab.base.RESTManager*

```
class gitlab.mixins.ParticipantsMixin
```

Bases: object

manager: [gitlab.base.RESTManager](#)

participants(**kwargs: Any) → Dict[str, Any]

List the participants.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **as_list** – If set to False and no pagination option is defined, return a generator instead of a list
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabListError](#) – If the list could not be retrieved

Returns The list of participants

Return type Dict[str, Any]

```
class gitlab.mixins.RefreshMixin
```

Bases: object

manager: [gitlab.base.RESTManager](#)

refresh(**kwargs: Any) → None

Refresh a single object from server.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Return type None

Returns None (updates the object)

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabGetError](#) – If the server cannot perform the request

Parameters **kwargs** (Any) –

Return type None

```
class gitlab.mixins.RetrieveMixin
```

Bases: [gitlab.mixins.ListMixin](#), [gitlab.mixins.GetMixin](#)

gitlab: [gitlab.client.Gitlab](#)

class gitlab.mixins.SaveMixin

Bases: object

Mixin for RESTObject's that can be updated.

manager: [gitlab.base.RESTManager](#)

save(**kwargs: Any) → Optional[Dict[str, Any]]

Save the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Returns The new object data (*not* a RESTObject)

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabUpdateError](#) – If the server cannot perform the request

Return type Optional[Dict[str, Any]]

class gitlab.mixins.SetMixin

Bases: object

gitlab: [gitlab.client.Gitlab](#)

set(key: str, value: str, **kwargs: Any) → [gitlab.base.RESTObject](#)

Create or update the object.

Parameters

- **key** (str) – The key of the object to create/update
- **value** (str) – The value to set for the object
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (Any) –

Raises

- [GitlabAuthenticationError](#) – If authentication is not correct
- [GitlabSetError](#) – If an error occurred

Returns The created/updated attribute

Return type [gitlab.base.RESTObject](#)

class gitlab.mixins.SubscribableMixin

Bases: object

manager: [gitlab.base.RESTManager](#)

subscribe(**kwargs: Any) → None

Subscribe to the object notifications.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)

- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabSubscribeError*](#) – If the subscription cannot be done

Return type *None***unsubscribe**(**kwargs: *Any*) → *None*

Unsubscribe from the object notifications.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabUnsubscribeError*](#) – If the unsubscription cannot be done

Return type *None***class** gitlab.mixins.TimeTrackingMixinBases: *object***add_spent_time**(duration: *str*, **kwargs: *Any*) → *Dict[str, Any]*

Add time spent working on the object.

Parameters

- **duration** (*str*) – Duration in human format (e.g. 3h30)
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabTimeTrackingError*](#) – If the time tracking update cannot be done

Return type *Dict[str, Any]***manager:** [*gitlab.base.RESTManager*](#)**reset_spent_time**(**kwargs: *Any*) → *Dict[str, Any]*

Resets the time spent working on the object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabTimeTrackingError*](#) – If the time tracking update cannot be done

Return type *Dict[str, Any]*

reset_time_estimate(***kwargs: Any*) → Dict[str, Any]

Resets estimated time for the object to 0 seconds.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabTimeTrackingError*](#) – If the time tracking update cannot be done

Return type *Dict[str, Any]*

time_estimate(*duration: str, **kwargs: Any*) → Dict[str, Any]

Set an estimated time of work for the object.

Parameters

- **duration** (*str*) – Duration in human format (e.g. 3h30)
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabTimeTrackingError*](#) – If the time tracking update cannot be done

Return type *Dict[str, Any]*

time_stats(***kwargs: Any*) → Dict[str, Any]

Get time stats for the object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [*GitlabAuthenticationError*](#) – If authentication is not correct
- [*GitlabTimeTrackingError*](#) – If the time tracking update cannot be done

Return type *Dict[str, Any]*

class gitlab.mixins.**TodoMixin**

Bases: object

manager: [*gitlab.base.RESTManager*](#)

todo(***kwargs: Any*) → None

Create a todo associated to the object.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabTodoError`](#) – If the todo cannot be set

Return type None

class gitlab.mixins.UpdateMixin

Bases: object

gitlab: [`gitlab.client.Gitlab`](#)

update(*id: Optional[Union[int, str]] = None, new_data: Optional[Dict[str, Any]] = None, **kwargs: Any*)
→ Dict[str, Any]

Update an object on the server.

Parameters

- **id** (*Optional[Union[int, str]]*) – ID of the object to update (can be None if not required)
- **new_data** (*Optional[Dict[str, Any]]*) – the update data for the object
- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Returns The new object data (*not* a RESTObject)

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabUpdateError`](#) – If the server cannot perform the request

Return type Dict[str, Any]

class gitlab.mixins.UserAgentDetailMixin

Bases: object

manager: [`gitlab.base.RESTManager`](#)

user_agent_detail(***kwargs: Any*) → Dict[str, Any]

Get the user agent detail.

Parameters

- ****kwargs** – Extra options to send to the server (e.g. sudo)
- **kwargs** (*Any*) –

Raises

- [`GitlabAuthenticationError`](#) – If authentication is not correct
- [`GitlabGetError`](#) – If the server cannot perform the request

Return type Dict[str, Any]

6.5.10 gitlab.utils module

class `gitlab.utils.EncodedId`(*value: Union[str, int, gitlab.utils.EncodedId]*)

Bases: `str`

A custom *str* class that will return the URL-encoded value of the string.

- Using it recursively will only url-encode the value once.
- Can accept either *str* or *int* as input value.
- Can be used in an f-string and output the URL-encoded string.

Reference to documentation on why this is necessary.

See:

<https://docs.gitlab.com/ee/api/index.html#namespaced-path-encoding>
<https://docs.gitlab.com/ee/api/index.html#path-parameters>

Parameters *value* (*Union[str, int, EncodedId]*) –

Return type *Union[int, EncodedId]*

`gitlab.utils.copy_dict`(**, src: Dict[str, Any], dest: Dict[str, Any]*) → `None`

Parameters

- **src** (*Dict[str, Any]*) –
- **dest** (*Dict[str, Any]*) –

Return type `None`

`gitlab.utils.remove_none_from_dict`(*data: Dict[str, Any]*) → `Dict[str, Any]`

Parameters *data* (*Dict[str, Any]*) –

Return type *Dict[str, Any]*

`gitlab.utils.response_content`(*response: requests.models.Response, streamed: bool, action: Optional[Callable], chunk_size: int*) → `Optional[bytes]`

Parameters

- **response** (*requests.models.Response*) –
- **streamed** (*bool*) –
- **action** (*Optional[Callable]*) –
- **chunk_size** (*int*) –

Return type *Optional[bytes]*

`gitlab.utils.warn`(*message: str, *, category: Optional[Type] = None, source: Optional[Any] = None*) → `None`

This `warnings.warn` wrapper function attempts to show the location causing the warning in the user code that called the library.

It does this by walking up the stack trace to find the first frame located outside the `gitlab/` directory. This is helpful to users as it shows them their code that is causing the warning.

Parameters

- **message** (*str*) –

- **category** (*Optional[Type]*) –
- **source** (*Optional[Any]*) –

Return type None

6.6 CLI reference (gitlab command)

Warning: The following is a complete, auto-generated list of subcommands available via the **gitlab** command-line tool. Some of the actions may currently not work as expected or lack functionality available via the API.

Please see the existing [list of CLI related issues](#), or open a new one if it is not already listed there.

6.6.1 gitlab

GitLab API Command Line Interface

```
usage: gitlab [-h] [--version] [-v] [-d] [-c CONFIG_FILE] [-g GITLAB]
             [-o {json,legacy,yaml}] [-f FIELDS] [--server-url SERVER_URL]
             [--ssl-verify SSL_VERIFY] [--timeout TIMEOUT]
             [--api-version API_VERSION] [--per-page PER_PAGE]
             [--pagination PAGINATION] [--order-by ORDER_BY]
             [--user-agent USER_AGENT]
             [--private-token PRIVATE_TOKEN | --oauth-token OAUTH_TOKEN | --job-token_
             ↪ JOB_TOKEN]
             {application,application-appearance,application-settings,audit-event,
             ↪ broadcast-message,current-user,current-user-email,current-user-gpg-key,current-user-
             ↪ key,current-user-status,deploy-key,deploy-token,dockerfile,event,feature,generic-
             ↪ package,geo-node,gitignore,gitlabciyaml,group,group-access-request,group-access-token,
             ↪ group-audit-event,group-badge,group-billable-member,group-billable-member-membership,
             ↪ group-board,group-board-list,group-cluster,group-custom-attribute,group-deploy-token,
             ↪ group-descendant-group,group-epic,group-epic-award-emoji,group-epic-discussion-note,
             ↪ group-epic-issue,group-epic-note,group-epic-note-award-emoji,group-epic-resource-label-
             ↪ event,group-export,group-hook,group-import,group-issue,group-issues-statistics,group-
             ↪ label,group-member,group-member-all,group-merge-request,group-milestone,group-
             ↪ notification-settings,group-package,group-project,group-runner,group-subgroup,group-
             ↪ variable,group-wiki,hook,issue,issues-statistics,key,ldap-group,license,merge-request,
             ↪ namespace,notification-settings,pages-domain,personal-access-token,project,project-
             ↪ access-request,project-access-token,project-additional-statistics,project-approval,
             ↪ project-approval-rule,project-artifact,project-audit-event,project-badge,project-board,
             ↪ project-board-list,project-branch,project-cluster,project-commit,project-commit-
             ↪ comment,project-commit-discussion,project-commit-discussion-note,project-commit-status,
             ↪ project-custom-attribute,project-deploy-token,project-deployment,project-deployment-
             ↪ merge-request,project-environment,project-event,project-export,project-file,project-
             ↪ fork,project-hook,project-import,project-issue,project-issue-award-emoji,project-issue-
             ↪ discussion,project-issue-discussion-note,project-issue-link,project-issue-note,project-
             ↪ issue-note-award-emoji,project-issue-resource-label-event,project-issue-resource-
             ↪ milestone-event,project-issue-resource-state-event,project-issues-statistics,project-
             ↪ job,project-key,project-label,project-member,project-member-all,project-merge-request,
             ↪ project-merge-request-approval,project-merge-request-approval-rule,project-merge-
             ↪ request-approval-state,project-merge-request-award-emoji,project-merge-request-diff,
             ↪ project-merge-request-discussion,project-merge-request-discussion-note,project-merge-
             ↪ request-note,project-merge-request-note-award-emoji,project-merge-request-pipeline,
             ↪ project-merge-request-resource-label-event,project-merge-request-resource-milestone-
             ↪ resource-state-event,project-merge-train,project-milestone-approval,project-milestone-
             ↪ project-note,project-notification-settings,project-package,project-package-file,
             ↪ project-pages-domain,project-pipeline,project-pipeline-bridge,project-pipeline-job,
             ↪ project-pipeline-schedule,project-pipeline-schedule-variable,project-pipeline-test-
             ↪ report,project-pipeline-test-report-summary,project-pipeline-variable,project-
```

(continues on next page)

6.6 CLI reference (gitlab command)

375

...

-h, --help
show this help message and exit

--version
Display the version.

-v, --verbose, --fancy
Verbose mode (legacy format only) [env var: GITLAB_VERBOSE]

-d, --debug
Debug mode (display HTTP requests) [env var: GITLAB_DEBUG]

-c <config_file>, --config-file <config_file>
Configuration file to use. Can be used multiple times. [env var: PYTHON_GITLAB_CFG]

-g <gitlab>, --gitlab <gitlab>
Which configuration section should be used. If not defined, the default selection will be used.

-o {json,legacy,yaml}, --output {json,legacy,yaml}
Output format (v4 only): json|legacy|yaml

-f <fields>, --fields <fields>
Fields to display in the output (comma separated). Not used with legacy output

--server-url <server_url>
GitLab server URL [env var: GITLAB_URL]

--ssl-verify <ssl_verify>
Whether SSL certificates should be validated. [env var: GITLAB_SSL_VERIFY]

--timeout <timeout>
Timeout to use for requests to the GitLab server. [env var: GITLAB_TIMEOUT]

--api-version <api_version>
GitLab API version [env var: GITLAB_API_VERSION]

--per-page <per_page>
Number of entries to return per page in the response. [env var: GITLAB_PER_PAGE]

--pagination <pagination>
Whether to use keyset or offset pagination [env var: GITLAB_PAGINATION]

--order-by <order_by>
Set order_by globally [env var: GITLAB_ORDER_BY]

--user-agent <user_agent>
The user agent to send to GitLab with the HTTP request. [env var: GITLAB_USER_AGENT]

--private-token <private_token>
GitLab private access token [env var: GITLAB_PRIVATE_TOKEN]

--oauth-token <oauth_token>
GitLab OAuth token [env var: GITLAB_OAUTH_TOKEN]

--job-token <job_token>
GitLab CI job token [env var: CI_JOB_TOKEN]

gitlab application

```
usage: gitlab application [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab application create

```
usage: gitlab application create [-h] [--sudo SUDO] --name NAME --redirect-uri
                                REDIRECT_URI --scopes SCOPES
                                [--confidential CONFIDENTIAL]
```

-h, --help

show this help message and exit

--sudo <sudo>

--name <name>

--redirect-uri <redirect_uri>

--scopes <scopes>

--confidential <confidential>

gitlab application delete

```
usage: gitlab application delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab application list

```
usage: gitlab application list [-h] [--sudo SUDO] [--page PAGE]
                                [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab application-appearance

```
usage: gitlab application-appearance [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab application-appearance get

```
usage: gitlab application-appearance get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab application-appearance update

```
usage: gitlab application-appearance update [-h] [--sudo SUDO] [--title TITLE]
                                           [--description DESCRIPTION]
                                           [--logo LOGO]
                                           [--header-logo HEADER_LOGO]
                                           [--favicon FAVICON]
                                           [--new-project-guidelines NEW_PROJECT_
↪GUIDELINES]
                                           [--header-message HEADER_MESSAGE]
                                           [--footer-message FOOTER_MESSAGE]
                                           [--message-background-color MESSAGE_
↪BACKGROUND_COLOR]
                                           [--message-font-color MESSAGE_FONT_COLOR]
                                           [--email-header-and-footer-enabled EMAIL_
↪HEADER_AND_FOOTER_ENABLED]
```

-h, --help

show this help message and exit

--sudo <sudo>

--title <title>

--description <description>

--logo <logo>

--header-logo <header_logo>

--favicon <favicon>

--new-project-guidelines <new_project_guidelines>

--header-message <header_message>

--footer-message <footer_message>

```
--message-background-color <message_background_color>
--message-font-color <message_font_color>
--email-header-and-footer-enabled <email_header_and_footer_enabled>
```

gitlab application-settings

```
usage: gitlab application-settings [-h] {get,update} ...
```

-h, --help
show this help message and exit

gitlab application-settings get

```
usage: gitlab application-settings get [-h] [--sudo SUDO]
```

-h, --help
show this help message and exit

--sudo <sudo>

gitlab application-settings update

```
usage: gitlab application-settings update [-h] [--sudo SUDO] [--id ID]
                                           [--default-projects-limit DEFAULT_PROJECTS_
↳LIMIT]
                                           [--signup-enabled SIGNUP_ENABLED]
                                           [--password-authentication-enabled-for-web-
↳PASSWORD_AUTHENTICATION_ENABLED_FOR_WEB]
                                           [--gravatar-enabled GRAVATAR_ENABLED]
                                           [--sign-in-text SIGN_IN_TEXT]
                                           [--created-at CREATED_AT]
                                           [--updated-at UPDATED_AT]
                                           [--home-page-url HOME_PAGE_URL]
                                           [--default-branch-protection DEFAULT_BRANCH_
↳PROTECTION]
                                           [--restricted-visibility-levels RESTRICTED_
↳VISIBILITY_LEVELS]
                                           [--max-attachment-size MAX_ATTACHMENT_SIZE]
                                           [--session-expire-delay SESSION_EXPIRE_DELAY]
                                           [--default-project-visibility DEFAULT_PROJECT_
↳VISIBILITY]
                                           [--default-snippet-visibility DEFAULT_SNIPPET_
↳VISIBILITY]
                                           [--default-group-visibility DEFAULT_GROUP_
↳VISIBILITY]
                                           [--outbound-local-requests-whitelist OUTBOUND_
↳LOCAL_REQUESTS_WHITELIST]
                                           [--disabled-oauth-sign-in-sources DISABLED_
↳OAUTH_SIGN_IN_SOURCES]
```

(continues on next page)

(continued from previous page)

```

--domain-whitelist DOMAIN_WHITELIST]
--domain-blacklist-enabled DOMAIN_BLACKLIST_
↳ENABLED]

--domain-blacklist DOMAIN_BLACKLIST]
--domain-allowlist DOMAIN_ALLOWLIST]
--domain-denylist-enabled DOMAIN_DENYLIST_
↳ENABLED]

--domain-denylist DOMAIN_DENYLIST]
--external-authorization-service-enabled↳
↳EXTERNAL_AUTHORIZATION_SERVICE_ENABLED]

--external-authorization-service-url EXTERNAL_
↳AUTHORIZATION_SERVICE_URL]

--external-authorization-service-default-
↳label EXTERNAL_AUTHORIZATION_SERVICE_DEFAULT_LABEL]

--external-authorization-service-timeout↳
↳EXTERNAL_AUTHORIZATION_SERVICE_TIMEOUT]

--import-sources IMPORT_SOURCES]
--user-oauth-applications USER_OAUTH_
↳APPLICATIONS]

--after-sign-out-path AFTER_SIGN_OUT_PATH]
--container-registry-token-expire-delay↳
↳CONTAINER_REGISTRY_TOKEN_EXPIRE_DELAY]

--repository-storages REPOSITORY_STORAGES]
--plantuml-enabled PLANTUML_ENABLED]
--plantuml-url PLANTUML_URL]
--terminal-max-session-time TERMINAL_MAX_
↳SESSION_TIME]

--polling-interval-multiplier POLLING_
↳INTERVAL_MULTIPLIER]

--rsa-key-restriction RSA_KEY_RESTRICTION]
--dsa-key-restriction DSA_KEY_RESTRICTION]
--ecdsa-key-restriction ECDSA_KEY_RESTRICTION]
--ed25519-key-restriction ED25519_KEY_
↳RESTRICTION]

--first-day-of-week FIRST_DAY_OF_WEEK]
--enforce-terms ENFORCE_TERMS]
--terms TERMS]
--performance-bar-allowed-group-id↳
↳PERFORMANCE_BAR_ALLOWED_GROUP_ID]

--instance-statistics-visibility-private↳
↳INSTANCE_STATISTICS_VISIBILITY_PRIVATE]

--user-show-add-ssh-key-message USER_SHOW_ADD_
↳SSH_KEY_MESSAGE]

--file-template-project-id FILE_TEMPLATE_
↳PROJECT_ID]

--local-markdown-version LOCAL_MARKDOWN_
↳VERSION]

--asset-proxy-enabled ASSET_PROXY_ENABLED]
--asset-proxy-url ASSET_PROXY_URL]
--asset-proxy-whitelist ASSET_PROXY_WHITELIST]
--asset-proxy-allowlist ASSET_PROXY_ALLOWLIST]
--geo-node-allowed-ips GEO_NODE_ALLOWED_IPS]

```

(continues on next page)

(continued from previous page)

```

                                [--allow-local-requests-from-hooks-and-
↪services ALLOW_LOCAL_REQUESTS_FROM_HOOKS_AND_SERVICES]
                                [--allow-local-requests-from-web-hooks-and-
↪services ALLOW_LOCAL_REQUESTS_FROM_WEB_HOOKS_AND_SERVICES]
                                [--allow-local-requests-from-system-hooks,
↪ALLOW_LOCAL_REQUESTS_FROM_SYSTEM_HOOKS]

```

-h, --help

show this help message and exit

--sudo <sudo>**--id <id>****--default-projects-limit <default_projects_limit>****--signup-enabled <signup_enabled>****--password-authentication-enabled-for-web <password_authentication_enabled_for_web>****--gravatar-enabled <gravatar_enabled>****--sign-in-text <sign_in_text>****--created-at <created_at>****--updated-at <updated_at>****--home-page-url <home_page_url>****--default-branch-protection <default_branch_protection>****--restricted-visibility-levels <restricted_visibility_levels>****--max-attachment-size <max_attachment_size>****--session-expire-delay <session_expire_delay>****--default-project-visibility <default_project_visibility>****--default-snippet-visibility <default_snippet_visibility>****--default-group-visibility <default_group_visibility>****--outbound-local-requests-whitelist <outbound_local_requests_whitelist>****--disabled-oauth-sign-in-sources <disabled_oauth_sign_in_sources>****--domain-whitelist <domain_whitelist>****--domain-blacklist-enabled <domain_blacklist_enabled>****--domain-blacklist <domain_blacklist>****--domain-allowlist <domain_allowlist>****--domain-denylist-enabled <domain_denylist_enabled>**

```
--domain-denylist <domain_denylist>
--external-authorization-service-enabled <external_authorization_service_enabled>
--external-authorization-service-url <external_authorization_service_url>
--external-authorization-service-default-label <external_authorization_service_default_label>
--external-authorization-service-timeout <external_authorization_service_timeout>
--import-sources <import_sources>
--user-oauth-applications <user_oauth_applications>
--after-sign-out-path <after_sign_out_path>
--container-registry-token-expire-delay <container_registry_token_expire_delay>
--repository-storages <repository_storages>
--plantuml-enabled <plantuml_enabled>
--plantuml-url <plantuml_url>
--terminal-max-session-time <terminal_max_session_time>
--polling-interval-multiplier <polling_interval_multiplier>
--rsa-key-restriction <rsa_key_restriction>
--dsa-key-restriction <dsa_key_restriction>
--ecdsa-key-restriction <ecdsa_key_restriction>
--ed25519-key-restriction <ed25519_key_restriction>
--first-day-of-week <first_day_of_week>
--enforce-terms <enforce_terms>
--terms <terms>
--performance-bar-allowed-group-id <performance_bar_allowed_group_id>
--instance-statistics-visibility-private <instance_statistics_visibility_private>
--user-show-add-ssh-key-message <user_show_add_ssh_key_message>
--file-template-project-id <file_template_project_id>
--local-markdown-version <local_markdown_version>
--asset-proxy-enabled <asset_proxy_enabled>
--asset-proxy-url <asset_proxy_url>
--asset-proxy-whitelist <asset_proxy_whitelist>
--asset-proxy-allowlist <asset_proxy_allowlist>
--geo-node-allowed-ips <geo_node_allowed_ips>
```

```
--allow-local-requests-from-hooks-and-services <allow_local_requests_from_hooks_and_services>
--allow-local-requests-from-web-hooks-and-services <allow_local_requests_from_web_hooks_and_services>
--allow-local-requests-from-system-hooks <allow_local_requests_from_system_hooks>
```

gitlab audit-event

```
usage: gitlab audit-event [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab audit-event get

```
usage: gitlab audit-event get [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab audit-event list

```
usage: gitlab audit-event list [-h] [--sudo SUDO]
                                [--created-after CREATED_AFTER]
                                [--created-before CREATED_BEFORE]
                                [--entity-type ENTITY_TYPE]
                                [--entity-id ENTITY_ID] [--page PAGE]
                                [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--created-after <created_after>

--created-before <created_before>

--entity-type <entity_type>

--entity-id <entity_id>

--page <page>

--per-page <per_page>

--all

gitlab broadcast-message

```
usage: gitlab broadcast-message [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab broadcast-message create

```
usage: gitlab broadcast-message create [-h] [--sudo SUDO] --message MESSAGE
                                         [--starts-at STARTS_AT]
                                         [--ends-at ENDS_AT] [--color COLOR]
                                         [--font FONT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--message <message>

--starts-at <starts_at>

--ends-at <ends_at>

--color <color>

--font

gitlab broadcast-message delete

```
usage: gitlab broadcast-message delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab broadcast-message get

```
usage: gitlab broadcast-message get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab broadcast-message list

```
usage: gitlab broadcast-message list [-h] [--sudo SUDO] [--page PAGE]
                                     [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab broadcast-message update

```
usage: gitlab broadcast-message update [-h] [--sudo SUDO] --id ID
                                     [--message MESSAGE]
                                     [--starts-at STARTS_AT]
                                     [--ends-at ENDS_AT] [--color COLOR]
                                     [--font FONT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

--message <message>

--starts-at <starts_at>

--ends-at <ends_at>

--color <color>

--font

gitlab current-user

```
usage: gitlab current-user [-h] {get} ...
```

-h, --help
show this help message and exit

gitlab current-user get

```
usage: gitlab current-user get [-h] [--sudo SUDO]
```

-h, --help
show this help message and exit

--sudo <sudo>

gitlab current-user-email

```
usage: gitlab current-user-email [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab current-user-email create

```
usage: gitlab current-user-email create [-h] [--sudo SUDO] --email EMAIL
```

-h, --help
show this help message and exit

--sudo <sudo>

--email <email>

gitlab current-user-email delete

```
usage: gitlab current-user-email delete [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-email get

```
usage: gitlab current-user-email get [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-email list

```
usage: gitlab current-user-email list [-h] [--sudo SUDO] [--page PAGE]
                                     [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab current-user-gpg-key

```
usage: gitlab current-user-gpg-key [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab current-user-gpg-key create

```
usage: gitlab current-user-gpg-key create [-h] [--sudo SUDO] --key KEY
```

-h, --help
show this help message and exit

--sudo <sudo>

--key <key>

gitlab current-user-gpg-key delete

```
usage: gitlab current-user-gpg-key delete [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-gpg-key get

```
usage: gitlab current-user-gpg-key get [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-gpg-key list

```
usage: gitlab current-user-gpg-key list [-h] [--sudo SUDO] [--page PAGE]
                                         [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab current-user-key

```
usage: gitlab current-user-key [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab current-user-key create

```
usage: gitlab current-user-key create [-h] [--sudo SUDO] --title TITLE --key
                                         KEY
```

-h, --help
show this help message and exit

--sudo <sudo>

--title <title>

--key <key>

gitlab current-user-key delete

```
usage: gitlab current-user-key delete [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-key get

```
usage: gitlab current-user-key get [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-key list

```
usage: gitlab current-user-key list [-h] [--sudo SUDO] [--page PAGE]
                                     [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab current-user-status

```
usage: gitlab current-user-status [-h] {get,update} ...
```

-h, --help
show this help message and exit

gitlab current-user-status get

```
usage: gitlab current-user-status get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab current-user-status update

```
usage: gitlab current-user-status update [-h] [--sudo SUDO] [--emoji EMOJI]
                                           [--message MESSAGE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--emoji <emoji>

--message <message>

gitlab deploy-key

```
usage: gitlab deploy-key [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab deploy-key list

```
usage: gitlab deploy-key list [-h] [--sudo SUDO] [--page PAGE]
                               [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab deploy-token

```
usage: gitlab deploy-token [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab deploy-token list

```
usage: gitlab deploy-token list [-h] [--sudo SUDO] [--page PAGE]
                                [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab dockerfile

```
usage: gitlab dockerfile [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab dockerfile get

```
usage: gitlab dockerfile get [-h] [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--name <name>

gitlab dockerfile list

```
usage: gitlab dockerfile list [-h] [--sudo SUDO] [--page PAGE]
                                [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>
--per-page <per_page>
--all

gitlab event

```
usage: gitlab event [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab event list

```
usage: gitlab event list [-h] [--sudo SUDO] [--action ACTION]
                        [--target-type TARGET_TYPE] [--before BEFORE]
                        [--after AFTER] [--sort SORT] [--page PAGE]
                        [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>
--action <action>
--target-type <target_type>
--before <before>
--after <after>
--sort <sort>
--page <page>
--per-page <per_page>
--all

gitlab feature

```
usage: gitlab feature [-h] {list,delete} ...
```

-h, --help
show this help message and exit

gitlab feature delete

```
usage: gitlab feature delete [-h] [--sudo SUDO] --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--name <name>

gitlab feature list

```
usage: gitlab feature list [-h] [--sudo SUDO] [--page PAGE]
                        [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab generic-package

```
usage: gitlab generic-package [-h] {upload,download} ...
```

-h, --help
show this help message and exit

gitlab generic-package download

```
usage: gitlab generic-package download [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --package-name
                                         PACKAGE_NAME --package-version
                                         PACKAGE_VERSION --file-name FILE_NAME
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--package-name <package_name>

--package-version <package_version>

--file-name <file_name>

gitlab generic-package upload

```
usage: gitlab generic-package upload [-h] --project-id PROJECT_ID
                                     [--sudo SUDO] --package-name PACKAGE_NAME
                                     --package-version PACKAGE_VERSION
                                     --file-name FILE_NAME --path PATH
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--package-name <package_name>

--package-version <package_version>

--file-name <file_name>

--path <path>

gitlab geo-node

```
usage: gitlab geo-node [-h]
                       {list,get,update,delete,repair,status,current-failures}
                       ...
```

-h, --help

show this help message and exit

gitlab geo-node current-failures

```
usage: gitlab geo-node current-failures [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab geo-node delete

```
usage: gitlab geo-node delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab geo-node get

```
usage: gitlab geo-node get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab geo-node list

```
usage: gitlab geo-node list [-h] [--sudo SUDO] [--page PAGE]
                             [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab geo-node repair

```
usage: gitlab geo-node repair [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab geo-node status

```
usage: gitlab geo-node status [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab geo-node update

```
usage: gitlab geo-node update [-h] [--sudo SUDO] --id ID [--enabled ENABLED]
                               [--url URL]
                               [--files-max-capacity FILES_MAX_CAPACITY]
                               [--repos-max-capacity REPOS_MAX_CAPACITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

--enabled <enabled>

--url <url>

--files-max-capacity <files_max_capacity>

--repos-max-capacity <repos_max_capacity>

gitlab gitignore

```
usage: gitlab gitignore [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab gitignore get

```
usage: gitlab gitignore get [-h] [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--name <name>

gitlab gitignore list

```
usage: gitlab gitignore list [-h] [--sudo SUDO] [--page PAGE]
                               [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab gitlabciyaml

```
usage: gitlab gitlabciyaml [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab gitlabciyaml get

```
usage: gitlab gitlabciyaml get [-h] [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--name <name>

gitlab gitlabciyaml list

```
usage: gitlab gitlabciyaml list [-h] [--sudo SUDO] [--page PAGE]
                                [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab group

```
usage: gitlab group [-h]
                    {list,get,create,update,delete,transfer-project,transfer,search,add-
↳ ldap-group-link,delete-ldap-group-link,ldap-sync,share,unshare}
                    ...
```

-h, --help

show this help message and exit

gitlab group add-ldap-group-link

```
usage: gitlab group add-ldap-group-link [-h] --id ID --cn CN --group-access
                                         GROUP_ACCESS --provider PROVIDER
```

-h, --help
show this help message and exit

--id <id>

--cn <cn>

--group-access <group_access>

--provider <provider>

gitlab group create

```
usage: gitlab group create [-h] [--sudo SUDO] --name NAME --path PATH
                           [--description DESCRIPTION]
                           [--membership-lock MEMBERSHIP_LOCK]
                           [--visibility VISIBILITY]
                           [--share-with-group-lock SHARE_WITH_GROUP_LOCK]
                           [--require-two-factor-authentication REQUIRE_TWO_FACTOR_
↪AUTHENTICATION]
                           [--two-factor-grace-period TWO_FACTOR_GRACE_PERIOD]
                           [--project-creation-level PROJECT_CREATION_LEVEL]
                           [--auto-devops-enabled AUTO_DEVOPS_ENABLED]
                           [--subgroup-creation-level SUBGROUP_CREATION_LEVEL]
                           [--emails-disabled EMAILS_DISABLED]
                           [--avatar AVATAR]
                           [--mentions-disabled MENTIONS_DISABLED]
                           [--lfs-enabled LFS_ENABLED]
                           [--request-access-enabled REQUEST_ACCESS_ENABLED]
                           [--parent-id PARENT_ID]
                           [--default-branch-protection DEFAULT_BRANCH_PROTECTION]
                           [--shared-runners-minutes-limit SHARED_RUNNERS_MINUTES_LIMIT]
                           [--extra-shared-runners-minutes-limit EXTRA_SHARED_RUNNERS_
↪MINUTES_LIMIT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--name <name>

--path <path>

--description <description>

--membership-lock <membership_lock>

--visibility <visibility>

```

--share-with-group-lock <share_with_group_lock>
--require-two-factor-authentication <require_two_factor_authentication>
--two-factor-grace-period <two_factor_grace_period>
--project-creation-level <project_creation_level>
--auto-devops-enabled <auto_devops_enabled>
--subgroup-creation-level <subgroup_creation_level>
--emails-disabled <emails_disabled>
--avatar <avatar>
--mentions-disabled <mentions_disabled>
--lfs-enabled <lfs_enabled>
--request-access-enabled <request_access_enabled>
--parent-id <parent_id>
--default-branch-protection <default_branch_protection>
--shared-runners-minutes-limit <shared_runners_minutes_limit>
--extra-shared-runners-minutes-limit <extra_shared_runners_minutes_limit>

```

gitlab group delete

```
usage: gitlab group delete [-h] [--sudo SUDO] --id ID
```

```

-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>

```

gitlab group delete-ldap-group-link

```
usage: gitlab group delete-ldap-group-link [-h] --id ID --cn CN
                                           [--provider PROVIDER]
```

```

-h, --help
    show this help message and exit
--id <id>
--cn <cn>
--provider <provider>

```

gitlab group get

```
usage: gitlab group get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab group ldap-sync

```
usage: gitlab group ldap-sync [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab group list

```
usage: gitlab group list [-h] [--sudo SUDO] [--skip-groups SKIP_GROUPS]
                        [--all-available ALL_AVAILABLE] [--search SEARCH]
                        [--order-by ORDER_BY] [--sort SORT]
                        [--statistics STATISTICS] [--owned OWNED]
                        [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                        [--min-access-level MIN_ACCESS_LEVEL]
                        [--top-level-only TOP_LEVEL_ONLY] [--page PAGE]
                        [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--skip-groups <skip_groups>

--all-available <all_available>

--search <search>

--order-by <order_by>

--sort <sort>

--statistics <statistics>

--owned <owned>

--with-custom-attributes <with_custom_attributes>

--min-access-level <min_access_level>

--top-level-only <top_level_only>
--page <page>
--per-page <per_page>
--all

gitlab group search

```
usage: gitlab group search [-h] --id ID --scope SCOPE --search SEARCH
```

-h, --help
show this help message and exit
--id <id>
--scope <scope>
--search <search>

gitlab group share

```
usage: gitlab group share [-h] --id ID --group-id GROUP_ID --group-access  
GROUP_ACCESS [--expires-at EXPIRES_AT]
```

-h, --help
show this help message and exit
--id <id>
--group-id <group_id>
--group-access <group_access>
--expires-at <expires_at>

gitlab group transfer

```
usage: gitlab group transfer [-h] --id ID [--group-id GROUP_ID]
```

-h, --help
show this help message and exit
--id <id>
--group-id <group_id>

gitlab group transfer-project

```
usage: gitlab group transfer-project [-h] --id ID --project-id PROJECT_ID
```

-h, --help
show this help message and exit

--id <id>

--project-id <project_id>

gitlab group unshare

```
usage: gitlab group unshare [-h] --id ID --group-id GROUP_ID
```

-h, --help
show this help message and exit

--id <id>

--group-id <group_id>

gitlab group update

```
usage: gitlab group update [-h] [--sudo SUDO] --id ID [--name NAME]
                             [--path PATH] [--description DESCRIPTION]
                             [--membership-lock MEMBERSHIP_LOCK]
                             [--share-with-group-lock SHARE_WITH_GROUP_LOCK]
                             [--visibility VISIBILITY]
                             [--require-two-factor-authentication REQUIRE_TWO_FACTOR_
↪AUTHENTICATION]
                             [--two-factor-grace-period TWO_FACTOR_GRACE_PERIOD]
                             [--project-creation-level PROJECT_CREATION_LEVEL]
                             [--auto-devops-enabled AUTO_DEVOPS_ENABLED]
                             [--subgroup-creation-level SUBGROUP_CREATION_LEVEL]
                             [--emails-disabled EMAILS_DISABLED]
                             [--avatar AVATAR]
                             [--mentions-disabled MENTIONS_DISABLED]
                             [--lfs-enabled LFS_ENABLED]
                             [--request-access-enabled REQUEST_ACCESS_ENABLED]
                             [--default-branch-protection DEFAULT_BRANCH_PROTECTION]
                             [--file-template-project-id FILE_TEMPLATE_PROJECT_ID]
                             [--shared-runners-minutes-limit SHARED_RUNNERS_MINUTES_LIMIT]
                             [--extra-shared-runners-minutes-limit EXTRA_SHARED_RUNNERS_
↪MINUTES_LIMIT]
                             [--prevent-forking-outside-group PREVENT_FORKING_OUTSIDE_
↪GROUP]
                             [--shared-runners-setting SHARED_RUNNERS_SETTING]
```

-h, --help
show this help message and exit

```

--sudo <sudo>
--id <id>
--name <name>
--path <path>
--description <description>
--membership-lock <membership_lock>
--share-with-group-lock <share_with_group_lock>
--visibility <visibility>
--require-two-factor-authentication <require_two_factor_authentication>
--two-factor-grace-period <two_factor_grace_period>
--project-creation-level <project_creation_level>
--auto-devops-enabled <auto_devops_enabled>
--subgroup-creation-level <subgroup_creation_level>
--emails-disabled <emails_disabled>
--avatar <avatar>
--mentions-disabled <mentions_disabled>
--lfs-enabled <lfs_enabled>
--request-access-enabled <request_access_enabled>
--default-branch-protection <default_branch_protection>
--file-template-project-id <file_template_project_id>
--shared-runners-minutes-limit <shared_runners_minutes_limit>
--extra-shared-runners-minutes-limit <extra_shared_runners_minutes_limit>
--prevent-forking-outside-group <prevent_forking_outside_group>
--shared-runners-setting <shared_runners_setting>

```

gitlab group-access-request

```
usage: gitlab group-access-request [-h] {list,create,delete,approve} ...
```

```

-h, --help
    show this help message and exit

```

gitlab group-access-request approve

```
usage: gitlab group-access-request approve [-h] --group-id GROUP_ID
                                           [--sudo SUDO] --id ID
                                           [--access-level ACCESS_LEVEL]
```

-h, --help
show this help message and exit

--group-id <group_id>

--sudo <sudo>

--id <id>

--access-level <access_level>

gitlab group-access-request create

```
usage: gitlab group-access-request create [-h] [--sudo SUDO] --group-id
                                           GROUP_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-access-request delete

```
usage: gitlab group-access-request delete [-h] [--sudo SUDO] --group-id
                                           GROUP_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-access-request list

```
usage: gitlab group-access-request list [-h] [--sudo SUDO] --group-id GROUP_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--all]
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--page <page>
--per-page <per_page>
--all
```

gitlab group-access-token

```
usage: gitlab group-access-token [-h] {list,create,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-access-token create

```
usage: gitlab group-access-token create [-h] [--sudo SUDO] --group-id GROUP_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

gitlab group-access-token delete

```
usage: gitlab group-access-token delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-access-token list

```
usage: gitlab group-access-token list [-h] [--sudo SUDO] --group-id GROUP_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--all]
```

```
-h, --help
    show this help message and exit
```

```
--sudo <sudo>
--group-id <group_id>
--page <page>
--per-page <per_page>
--all
```

gitlab group-audit-event

```
usage: gitlab group-audit-event [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab group-audit-event get

```
usage: gitlab group-audit-event get [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --id ID
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-audit-event list

```
usage: gitlab group-audit-event list [-h] [--sudo SUDO] --group-id GROUP_ID
                                     [--created-after CREATED_AFTER]
                                     [--created-before CREATED_BEFORE]
                                     [--page PAGE] [--per-page PER_PAGE]
                                     [--all]
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--created-after <created_after>
--created-before <created_before>
--page <page>
--per-page <per_page>
--all
```

gitlab group-badge

```
usage: gitlab group-badge [-h] {list,get,create,update,delete,render} ...
```

-h, --help

show this help message and exit

gitlab group-badge create

```
usage: gitlab group-badge create [-h] [--sudo SUDO] --group-id GROUP_ID
                                --link-url LINK_URL --image-url IMAGE_URL
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--link-url <link_url>

--image-url <image_url>

gitlab group-badge delete

```
usage: gitlab group-badge delete [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-badge get

```
usage: gitlab group-badge get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-badge list

```
usage: gitlab group-badge list [-h] [--sudo SUDO] --group-id GROUP_ID
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--all

gitlab group-badge render

```
usage: gitlab group-badge render [-h] --group-id GROUP_ID [--sudo SUDO] --id
                                ID --link-url LINK_URL --image-url IMAGE_URL
```

-h, --help
show this help message and exit

--group-id <group_id>

--sudo <sudo>

--id <id>

--link-url <link_url>

--image-url <image_url>

gitlab group-badge update

```
usage: gitlab group-badge update [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                ID [--link-url LINK_URL]
                                [--image-url IMAGE_URL]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

--link-url <link_url>

--image-url <image_url>

gitlab group-billable-member

```
usage: gitlab group-billable-member [-h] {list,delete} ...
```

-h, --help

show this help message and exit

gitlab group-billable-member delete

```
usage: gitlab group-billable-member delete [-h] [--sudo SUDO] --group-id
                                           GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-billable-member list

```
usage: gitlab group-billable-member list [-h] [--sudo SUDO] --group-id
                                           GROUP_ID [--search SEARCH]
                                           [--sort SORT] [--page PAGE]
                                           [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--search <search>

--sort <sort>

--page <page>

--per-page <per_page>

--all

gitlab group-billable-member-membership

```
usage: gitlab group-billable-member-membership [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-billable-member-membership list

```
usage: gitlab group-billable-member-membership list [-h] [--sudo SUDO]
                                                    --group-id GROUP_ID
                                                    --user-id USER_ID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--user-id <user_id>

--page <page>

--per-page <per_page>

--all

gitlab group-board

```
usage: gitlab group-board [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-board create

```
usage: gitlab group-board create [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                   NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

gitlab group-board delete

```
usage: gitlab group-board delete [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-board get

```
usage: gitlab group-board get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-board list

```
usage: gitlab group-board list [-h] [--sudo SUDO] --group-id GROUP_ID  
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--all

gitlab group-board update

```
usage: gitlab group-board update [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-board-list

```
usage: gitlab group-board-list [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab group-board-list create

```
usage: gitlab group-board-list create [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --board-id BOARD_ID --label-id LABEL_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--label-id <label_id>

gitlab group-board-list delete

```
usage: gitlab group-board-list delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --board-id BOARD_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--id <id>

gitlab group-board-list get

```
usage: gitlab group-board-list get [-h] [--sudo SUDO] --group-id GROUP_ID
                                   --board-id BOARD_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--id <id>

gitlab group-board-list list

```
usage: gitlab group-board-list list [-h] [--sudo SUDO] --group-id GROUP_ID
                                   --board-id BOARD_ID [--page PAGE]
                                   [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--page <page>

--per-page <per_page>

--all

gitlab group-board-list update

```
usage: gitlab group-board-list update [-h] [--sudo SUDO] --group-id GROUP_ID
                                       --board-id BOARD_ID --id ID --position
                                       POSITION
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--id <id>

--position <position>

gitlab group-cluster

```
usage: gitlab group-cluster [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-cluster create

```
usage: gitlab group-cluster create [-h] [--sudo SUDO] --group-id GROUP_ID
                                   --name NAME
                                   --platform-kubernetes-attributes
                                   PLATFORM_KUBERNETES_ATTRIBUTES
                                   [--domain DOMAIN] [--enabled ENABLED]
                                   [--managed MANAGED]
                                   [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

--platform-kubernetes-attributes <platform_kubernetes_attributes>

--domain <domain>

--enabled <enabled>

--managed <managed>

--environment-scope <environment_scope>

gitlab group-cluster delete

```
usage: gitlab group-cluster delete [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-cluster get

```
usage: gitlab group-cluster get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-cluster list

```
usage: gitlab group-cluster list [-h] [--sudo SUDO] --group-id GROUP_ID
                                   [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--all

gitlab group-cluster update

```
usage: gitlab group-cluster update [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID [--name NAME] [--domain DOMAIN]
                                   [--management-project-id MANAGEMENT_PROJECT_ID]
                                   [--platform-kubernetes-attributes PLATFORM_KUBERNETES_
↪ATTRIBUTES]
                                   [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

--name <name>

--domain <domain>

--management-project-id <management_project_id>

--platform-kubernetes-attributes <platform_kubernetes_attributes>

--environment-scope <environment_scope>

gitlab group-custom-attribute

```
usage: gitlab group-custom-attribute [-h] {list,get,delete} ...
```

-h, --help

show this help message and exit

gitlab group-custom-attribute delete

```
usage: gitlab group-custom-attribute delete [-h] [--sudo SUDO] --group-id
                                             GROUP_ID --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

gitlab group-custom-attribute get

```
usage: gitlab group-custom-attribute get [-h] [--sudo SUDO] --group-id
                                           GROUP_ID --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

gitlab group-custom-attribute list

```
usage: gitlab group-custom-attribute list [-h] [--sudo SUDO] --group-id
                                           GROUP_ID [--page PAGE]
                                           [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--group-id <group_id>
--page <page>
--per-page <per_page>
--all
```

gitlab group-deploy-token

```
usage: gitlab group-deploy-token [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab group-deploy-token create

```
usage: gitlab group-deploy-token create [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --name NAME --scopes SCOPES
                                         [--expires-at EXPIRES_AT]
                                         [--username USERNAME]
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--name <name>
--scopes <scopes>
--expires-at <expires_at>
--username <username>
```

gitlab group-deploy-token delete

```
usage: gitlab group-deploy-token delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --id ID
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-deploy-token get

```
usage: gitlab group-deploy-token get [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-deploy-token list

```
usage: gitlab group-deploy-token list [-h] [--sudo SUDO] --group-id GROUP_ID
                                     [--page PAGE] [--per-page PER_PAGE]
                                     [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--all

gitlab group-descendant-group

```
usage: gitlab group-descendant-group [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab group-descendant-group list

```
usage: gitlab group-descendant-group list [-h] [--sudo SUDO] --group-id
GROUP_ID [--skip-groups SKIP_GROUPS]
        [--all-available ALL_AVAILABLE]
        [--search SEARCH]
        [--order-by ORDER_BY] [--sort SORT]
        [--statistics STATISTICS]
        [--owned OWNED]
        [--with-custom-attributes WITH_CUSTOM_
↪ATTRIBUTES]
```

(continues on next page)

(continued from previous page)

```
[--min-access-level MIN_ACCESS_LEVEL]
[--page PAGE] [--per-page PER_PAGE]
[--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--skip-groups <skip_groups>

--all-available <all_available>

--search <search>

--order-by <order_by>

--sort <sort>

--statistics <statistics>

--owned <owned>

--with-custom-attributes <with_custom_attributes>

--min-access-level <min_access_level>

--page <page>

--per-page <per_page>

--all

gitlab group-epic

```
usage: gitlab group-epic [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab group-epic create

```
usage: gitlab group-epic create [-h] [--sudo SUDO] --group-id GROUP_ID --title
                                TITLE [--labels LABELS]
                                [--description DESCRIPTION]
                                [--start-date START_DATE]
                                [--end-date END_DATE]
```

-h, --help
show this help message and exit

--sudo <sudo>
--group-id <group_id>
--title <title>
--labels <labels>
--description <description>
--start-date <start_date>
--end-date <end_date>

gitlab group-epic delete

```
usage: gitlab group-epic delete [-h] [--sudo SUDO] --group-id GROUP_ID --iid IID
```

-h, --help
show this help message and exit
--sudo <sudo>
--group-id <group_id>
--iid <iid>

gitlab group-epic get

```
usage: gitlab group-epic get [-h] [--sudo SUDO] --group-id GROUP_ID --iid IID
```

-h, --help
show this help message and exit
--sudo <sudo>
--group-id <group_id>
--iid <iid>

gitlab group-epic list

```
usage: gitlab group-epic list [-h] [--sudo SUDO] --group-id GROUP_ID  
                             [--author-id AUTHOR_ID] [--labels LABELS]  
                             [--order-by ORDER_BY] [--sort SORT]  
                             [--search SEARCH] [--page PAGE]  
                             [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit
--sudo <sudo>

```

--group-id <group_id>
--author-id <author_id>
--labels <labels>
--order-by <order_by>
--sort <sort>
--search <search>
--page <page>
--per-page <per_page>
--all

```

gitlab group-epic update

```

usage: gitlab group-epic update [-h] [--sudo SUDO] --group-id GROUP_ID --iid
                                IID [--title TITLE] [--labels LABELS]
                                [--description DESCRIPTION]
                                [--start-date START_DATE]
                                [--end-date END_DATE]

```

```

-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--iid <iid>
--title <title>
--labels <labels>
--description <description>
--start-date <start_date>
--end-date <end_date>

```

gitlab group-epic-award-emoji

```

usage: gitlab group-epic-award-emoji [-h] {list,get,create,delete} ...

```

```

-h, --help
    show this help message and exit

```

gitlab group-epic-award-emoji create

```
usage: gitlab group-epic-award-emoji create [-h] [--sudo SUDO] --group-id
                                           GROUP_ID --epic-iid EPIC_IID
                                           --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--name <name>

gitlab group-epic-award-emoji delete

```
usage: gitlab group-epic-award-emoji delete [-h] [--sudo SUDO] --group-id
                                           GROUP_ID --epic-iid EPIC_IID --id
                                           ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--id <id>

gitlab group-epic-award-emoji get

```
usage: gitlab group-epic-award-emoji get [-h] [--sudo SUDO] --group-id
                                           GROUP_ID --epic-iid EPIC_IID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--id <id>

gitlab group-epic-award-emoji list

```
usage: gitlab group-epic-award-emoji list [-h] [--sudo SUDO] --group-id
                                         GROUP_ID --epic-iid EPIC_IID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id** <group_id>**--epic-iid** <epic_iid>**--page** <page>**--per-page** <per_page>**--all**

gitlab group-epic-discussion-note

```
usage: gitlab group-epic-discussion-note [-h] {get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-epic-discussion-note create

```
usage: gitlab group-epic-discussion-note create [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --discussion-id DISCUSSION_ID
                                                --body BODY
                                                [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id** <group_id>**--epic-iid** <epic_iid>**--discussion-id** <discussion_id>**--body** <body>**--created-at** <created_at>

gitlab group-epic-discussion-note delete

```
usage: gitlab group-epic-discussion-note delete [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --discussion-id DISCUSSION_ID
                                                --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--discussion-id <discussion_id>

--id <id>

gitlab group-epic-discussion-note get

```
usage: gitlab group-epic-discussion-note get [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --discussion-id DISCUSSION_ID
                                                --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--discussion-id <discussion_id>

--id <id>

gitlab group-epic-discussion-note update

```
usage: gitlab group-epic-discussion-note update [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --discussion-id DISCUSSION_ID
                                                --id ID --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

```
--epic-iid <epic_iid>
--discussion-id <discussion_id>
--id <id>
--body <body>
```

gitlab group-epic-issue

```
usage: gitlab group-epic-issue [-h] {list,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab group-epic-issue create

```
usage: gitlab group-epic-issue create [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --epic-iid EPIC_IID --issue-id ISSUE_ID
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--epic-iid <epic_iid>
--issue-id <issue_id>
```

gitlab group-epic-issue delete

```
usage: gitlab group-epic-issue delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --epic-iid EPIC_IID --epic-issue-id
                                         EPIC_ISSUE_ID
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--epic-iid <epic_iid>
--epic-issue-id <epic_issue_id>
```

gitlab group-epic-issue list

```
usage: gitlab group-epic-issue list [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --epic-iid EPIC_IID [--page PAGE]
                                     [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--page <page>

--per-page <per_page>

--all

gitlab group-epic-issue update

```
usage: gitlab group-epic-issue update [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --epic-iid EPIC_IID --epic-issue-id
                                     EPIC_ISSUE_ID
                                     [--move-before-id MOVE_BEFORE_ID]
                                     [--move-after-id MOVE_AFTER_ID]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--epic-issue-id <epic_issue_id>

--move-before-id <move_before_id>

--move-after-id <move_after_id>

gitlab group-epic-note

```
usage: gitlab group-epic-note [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab group-epic-note create

```
usage: gitlab group-epic-note create [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --epic-iid EPIC_IID --body BODY
                                     [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--body <body>

--created-at <created_at>

gitlab group-epic-note delete

```
usage: gitlab group-epic-note delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --epic-iid EPIC_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--id <id>

gitlab group-epic-note get

```
usage: gitlab group-epic-note get [-h] [--sudo SUDO] --group-id GROUP_ID
                                   --epic-iid EPIC_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--id <id>

gitlab group-epic-note list

```
usage: gitlab group-epic-note list [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --epic-iid EPIC_IID [--page PAGE]
                                     [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--page <page>

--per-page <per_page>

--all

gitlab group-epic-note update

```
usage: gitlab group-epic-note update [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --epic-iid EPIC_IID --id ID --body BODY
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--id <id>

--body <body>

gitlab group-epic-note-award-emoji

```
usage: gitlab group-epic-note-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab group-epic-note-award-emoji create

```
usage: gitlab group-epic-note-award-emoji create [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --note-id NOTE_ID --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--note-id <note_id>

--name <name>

gitlab group-epic-note-award-emoji delete

```
usage: gitlab group-epic-note-award-emoji delete [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --note-id NOTE_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--note-id <note_id>

--id <id>

gitlab group-epic-note-award-emoji get

```
usage: gitlab group-epic-note-award-emoji get [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --note-id NOTE_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--note-id <note_id>

--id <id>

gitlab group-epic-note-award-emoji list

```
usage: gitlab group-epic-note-award-emoji list [-h] [--sudo SUDO] --group-id
        GROUP_ID --epic-iid EPIC_IID
        --note-id NOTE_ID [--page PAGE]
        [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--note-id <note_id>

--page <page>

--per-page <per_page>

--all

gitlab group-epic-resource-label-event

```
usage: gitlab group-epic-resource-label-event [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab group-epic-resource-label-event get

```
usage: gitlab group-epic-resource-label-event get [-h] [--sudo SUDO]
        --group-id GROUP_ID
        --epic-id EPIC_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-id <epic_id>

--id <id>

gitlab group-epic-resource-label-event list

```
usage: gitlab group-epic-resource-label-event list [-h] [--sudo SUDO]
                                                    --group-id GROUP_ID
                                                    --epic-id EPIC_ID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-id <epic_id>

--page <page>

--per-page <per_page>

--all

gitlab group-export

```
usage: gitlab group-export [-h] {get,create,download} ...
```

-h, --help
show this help message and exit

gitlab group-export create

```
usage: gitlab group-export create [-h] [--sudo SUDO] --group-id GROUP_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-export download

```
usage: gitlab group-export download [-h] --group-id GROUP_ID [--sudo SUDO]
```

-h, --help
show this help message and exit

--group-id <group_id>

--sudo <sudo>

gitlab group-export get

```
usage: gitlab group-export get [-h] [--sudo SUDO] --group-id GROUP_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-hook

```
usage: gitlab group-hook [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab group-hook create

```
usage: gitlab group-hook create [-h] [--sudo SUDO] --group-id GROUP_ID --url
                                URL [--push-events PUSH_EVENTS]
                                [--issues-events ISSUES_EVENTS]
                                [--confidential-issues-events CONFIDENTIAL_ISSUES_EVENTS]
                                [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                [--tag-push-events TAG_PUSH_EVENTS]
                                [--note-events NOTE_EVENTS]
                                [--confidential-note-events CONFIDENTIAL_NOTE_EVENTS]
                                [--job-events JOB_EVENTS]
                                [--pipeline-events PIPELINE_EVENTS]
                                [--wiki-page-events WIKI_PAGE_EVENTS]
                                [--deployment-events DEPLOYMENT_EVENTS]
                                [--releases-events RELEASES_EVENTS]
                                [--subgroup-events SUBGROUP_EVENTS]
                                [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                [--token TOKEN]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--url <url>

--push-events <push_events>

--issues-events <issues_events>

--confidential-issues-events <confidential_issues_events>

--merge-requests-events <merge_requests_events>

```
--tag-push-events <tag_push_events>
--note-events <note_events>
--confidential-note-events <confidential_note_events>
--job-events <job_events>
--pipeline-events <pipeline_events>
--wiki-page-events <wiki_page_events>
--deployment-events <deployment_events>
--releases-events <releases_events>
--subgroup-events <subgroup_events>
--enable-ssl-verification <enable_ssl_verification>
--token <token>
```

gitlab group-hook delete

```
usage: gitlab group-hook delete [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-hook get

```
usage: gitlab group-hook get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-hook list

```
usage: gitlab group-hook list [-h] [--sudo SUDO] --group-id GROUP_ID
                               [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--all

gitlab group-hook update

```
usage: gitlab group-hook update [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
                                --url URL [--push-events PUSH_EVENTS]
                                [--issues-events ISSUES_EVENTS]
                                [--confidential-issues-events CONFIDENTIAL_ISSUES_EVENTS]
                                [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                [--tag-push-events TAG_PUSH_EVENTS]
                                [--note-events NOTE_EVENTS]
                                [--confidential-note-events CONFIDENTIAL_NOTE_EVENTS]
                                [--job-events JOB_EVENTS]
                                [--pipeline-events PIPELINE_EVENTS]
                                [--wiki-page-events WIKI_PAGE_EVENTS]
                                [--deployment-events DEPLOYMENT_EVENTS]
                                [--releases-events RELEASES_EVENTS]
                                [--subgroup-events SUBGROUP_EVENTS]
                                [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                [--token TOKEN]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

--url <url>

--push-events <push_events>

--issues-events <issues_events>

--confidential-issues-events <confidential_issues_events>

--merge-requests-events <merge_requests_events>

```

--tag-push-events <tag_push_events>
--note-events <note_events>
--confidential-note-events <confidential_note_events>
--job-events <job_events>
--pipeline-events <pipeline_events>
--wiki-page-events <wiki_page_events>
--deployment-events <deployment_events>
--releases-events <releases_events>
--subgroup-events <subgroup_events>
--enable-ssl-verification <enable_ssl_verification>
--token <token>

```

gitlab group-import

```
usage: gitlab group-import [-h] {get} ...
```

```

-h, --help
    show this help message and exit

```

gitlab group-import get

```
usage: gitlab group-import get [-h] [--sudo SUDO] --group-id GROUP_ID
```

```

-h, --help
    show this help message and exit

--sudo <sudo>
--group-id <group_id>

```

gitlab group-issue

```
usage: gitlab group-issue [-h] {list} ...
```

```

-h, --help
    show this help message and exit

```

gitlab group-issue list

```
usage: gitlab group-issue list [-h] [--sudo SUDO] --group-id GROUP_ID
                                [--state STATE] [--labels LABELS]
                                [--milestone MILESTONE] [--order-by ORDER_BY]
                                [--sort SORT] [--iids IIDS]
                                [--author-id AUTHOR_ID]
                                [--assignee-id ASSIGNEE_ID]
                                [--my-reaction-emoji MY_REACTION_EMOJI]
                                [--search SEARCH]
                                [--created-after CREATED_AFTER]
                                [--created-before CREATED_BEFORE]
                                [--updated-after UPDATED_AFTER]
                                [--updated-before UPDATED_BEFORE] [--page PAGE]
                                [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--state <state>

--labels <labels>

--milestone <milestone>

--order-by <order_by>

--sort <sort>

--iids <iids>

--author-id <author_id>

--assignee-id <assignee_id>

--my-reaction-emoji <my_reaction_emoji>

--search <search>

--created-after <created_after>

--created-before <created_before>

--updated-after <updated_after>

--updated-before <updated_before>

--page <page>

--per-page <per_page>

--all

gitlab group-issues-statistics

```
usage: gitlab group-issues-statistics [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab group-issues-statistics get

```
usage: gitlab group-issues-statistics get [-h] [--sudo SUDO] --group-id
                                           GROUP_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-label

```
usage: gitlab group-label [-h]
                           {list,get,create,update,delete,subscribe,unsubscribe}
                           ...
```

-h, --help

show this help message and exit

gitlab group-label create

```
usage: gitlab group-label create [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                  NAME --color COLOR
                                  [--description DESCRIPTION]
                                  [--priority PRIORITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

--color <color>

--description <description>

--priority <priority>

gitlab group-label delete

```
usage: gitlab group-label delete [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

gitlab group-label get

```
usage: gitlab group-label get [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

gitlab group-label list

```
usage: gitlab group-label list [-h] [--sudo SUDO] --group-id GROUP_ID
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--all

gitlab group-label subscribe

```
usage: gitlab group-label subscribe [-h] --group-id GROUP_ID [--sudo SUDO]
                                   --name NAME
```

-h, --help
show this help message and exit

--group-id <group_id>

--sudo <sudo>

--name <name>

gitlab group-label unsubscribe

```
usage: gitlab group-label unsubscribe [-h] --group-id GROUP_ID [--sudo SUDO]
                                   --name NAME
```

-h, --help
show this help message and exit

--group-id <group_id>

--sudo <sudo>

--name <name>

gitlab group-label update

```
usage: gitlab group-label update [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                NAME [--new-name NEW_NAME] [--color COLOR]
                                [--description DESCRIPTION]
                                [--priority PRIORITY]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

--new-name <new_name>

--color <color>

--description <description>

--priority <priority>

gitlab group-member

```
usage: gitlab group-member [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-member create

```
usage: gitlab group-member create [-h] [--sudo SUDO] --group-id GROUP_ID
                                   --access-level ACCESS_LEVEL --user-id
                                   USER_ID [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--access-level <access_level>

--user-id <user_id>

--expires-at <expires_at>

gitlab group-member delete

```
usage: gitlab group-member delete [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-member get

```
usage: gitlab group-member get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-member list

```
usage: gitlab group-member list [-h] [--sudo SUDO] --group-id GROUP_ID
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--all

gitlab group-member update

```
usage: gitlab group-member update [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID --access-level ACCESS_LEVEL
                                   [--expires-at EXPIRES_AT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

--access-level <access_level>

--expires-at <expires_at>

gitlab group-member-all

```
usage: gitlab group-member-all [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab group-member-all get

```
usage: gitlab group-member-all get [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID
```

-h, --help
show this help message and exit

--sudo <sudo>
--group-id <group_id>
--id <id>

gitlab group-member-all list

```
usage: gitlab group-member-all list [-h] [--sudo SUDO] --group-id GROUP_ID
                                     [--page PAGE] [--per-page PER_PAGE]
                                     [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>
--group-id <group_id>
--page <page>
--per-page <per_page>
--all

gitlab group-merge-request

```
usage: gitlab group-merge-request [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab group-merge-request list

```
usage: gitlab group-merge-request list [-h] [--sudo SUDO] --group-id GROUP_ID
                                     [--state STATE] [--order-by ORDER_BY]
                                     [--sort SORT] [--milestone MILESTONE]
                                     [--view VIEW] [--labels LABELS]
                                     [--created-after CREATED_AFTER]
                                     [--created-before CREATED_BEFORE]
                                     [--updated-after UPDATED_AFTER]
                                     [--updated-before UPDATED_BEFORE]
                                     [--scope SCOPE] [--author-id AUTHOR_ID]
                                     [--assignee-id ASSIGNEE_ID]
                                     [--approver-ids APPROVER_IDS]
                                     [--approved-by-ids APPROVED_BY_IDS]
                                     [--my-reaction-emoji MY_REACTION_EMOJI]
                                     [--source-branch SOURCE_BRANCH]
                                     [--target-branch TARGET_BRANCH]
                                     [--search SEARCH] [--wip WIP]
                                     [--page PAGE] [--per-page PER_PAGE]
                                     [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--state <state>

--order-by <order_by>

--sort <sort>

--milestone <milestone>

--view <view>

--labels <labels>

--created-after <created_after>

--created-before <created_before>

--updated-after <updated_after>

--updated-before <updated_before>

--scope <scope>

--author-id <author_id>

--assignee-id <assignee_id>

--approver-ids <approver_ids>

--approved-by-ids <approved_by_ids>

--my-reaction-emoji <my_reaction_emoji>

--source-branch <source_branch>

--target-branch <target_branch>

--search <search>

--wip <wip>

--page <page>

--per-page <per_page>

--all

gitlab group-milestone

```
usage: gitlab group-milestone [-h]
                               {list,get,create,update,delete,issues,merge-requests}
                               ...
```

-h, --help

show this help message and exit

gitlab group-milestone create

```
usage: gitlab group-milestone create [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --title TITLE [--description DESCRIPTION]
                                     [--due-date DUE_DATE]
                                     [--start-date START_DATE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--title <title>

--description <description>

--due-date <due_date>

--start-date <start_date>

gitlab group-milestone delete

```
usage: gitlab group-milestone delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-milestone get

```
usage: gitlab group-milestone get [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-milestone issues

```
usage: gitlab group-milestone issues [-h] --group-id GROUP_ID [--sudo SUDO]
                                       --id ID
```

-h, --help
show this help message and exit

--group-id <group_id>

--sudo <sudo>

--id <id>

gitlab group-milestone list

```
usage: gitlab group-milestone list [-h] [--sudo SUDO] --group-id GROUP_ID
                                   [--iids IIDS] [--state STATE]
                                   [--search SEARCH] [--page PAGE]
                                   [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--iids <iids>

--state <state>

--search <search>

--page <page>

--per-page <per_page>

--all

gitlab group-milestone merge-requests

```
usage: gitlab group-milestone merge-requests [-h] --group-id GROUP_ID
                                             [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--group-id <group_id>

--sudo <sudo>

--id <id>

gitlab group-milestone update

```
usage: gitlab group-milestone update [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --id ID [--title TITLE]
                                     [--description DESCRIPTION]
                                     [--due-date DUE_DATE]
                                     [--start-date START_DATE]
                                     [--state-event STATE_EVENT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

--title <title>

--description <description>

--due-date <due_date>

--start-date <start_date>

--state-event <state_event>

gitlab group-notification-settings

```
usage: gitlab group-notification-settings [-h] {get,update} ...
```

-h, --help
show this help message and exit

gitlab group-notification-settings get

```
usage: gitlab group-notification-settings get [-h] [--sudo SUDO] --group-id
GROUP_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-notification-settings update

```
usage: gitlab group-notification-settings update [-h] [--sudo SUDO] --group-id
GROUP_ID [--level LEVEL]
[--notification-email NOTIFICATION_
↪EMAIL]
[--new-note NEW_NOTE]
[--new-issue NEW_ISSUE]
[--reopen-issue REOPEN_ISSUE]
[--close-issue CLOSE_ISSUE]
[--reassign-issue REASSIGN_ISSUE]
[--new-merge-request NEW_MERGE_REQUEST]
[--reopen-merge-request REOPEN_MERGE_
↪REQUEST]
[--close-merge-request CLOSE_MERGE_
↪REQUEST]
[--reassign-merge-request REASSIGN_
↪MERGE_REQUEST]
[--merge-merge-request MERGE_MERGE_
↪REQUEST]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--level <level>

--notification-email <notification_email>

--new-note <new_note>

--new-issue <new_issue>

--reopen-issue <reopen_issue>

--close-issue <close_issue>

--reassign-issue <reassign_issue>

--new-merge-request <new_merge_request>

```
--reopen-merge-request <reopen_merge_request>
--close-merge-request <close_merge_request>
--reassign-merge-request <reassign_merge_request>
--merge-merge-request <merge_merge_request>
```

gitlab group-package

```
usage: gitlab group-package [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab group-package list

```
usage: gitlab group-package list [-h] [--sudo SUDO] --group-id GROUP_ID
                                [--exclude-subgroups EXCLUDE_SUBGROUPS]
                                [--order-by ORDER_BY] [--sort SORT]
                                [--package-type PACKAGE_TYPE]
                                [--package-name PACKAGE_NAME] [--page PAGE]
                                [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--exclude-subgroups <exclude_subgroups>
--order-by <order_by>
--sort <sort>
--package-type <package_type>
--package-name <package_name>
--page <page>
--per-page <per_page>
--all
```

gitlab group-project

```
usage: gitlab group-project [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-project list

```
usage: gitlab group-project list [-h] [--sudo SUDO] --group-id GROUP_ID
                                [--archived ARCHIVED]
                                [--visibility VISIBILITY]
                                [--order-by ORDER_BY] [--sort SORT]
                                [--search SEARCH] [--simple SIMPLE]
                                [--owned OWNED] [--starred STARRED]
                                [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                [--include-subgroups INCLUDE_SUBGROUPS]
                                [--with-issues-enabled WITH_ISSUES_ENABLED]
                                --with-merge-requests-enabled WITH_MERGE_REQUESTS_
                                ↪ENABLED]
                                [--with-shared WITH_SHARED]
                                [--min-access-level MIN_ACCESS_LEVEL]
                                [--with-security-reports WITH_SECURITY_REPORTS]
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--archived <archived>

--visibility <visibility>

--order-by <order_by>

--sort <sort>

--search <search>

--simple <simple>

--owned <owned>

--starred <starred>

--with-custom-attributes <with_custom_attributes>

--include-subgroups <include_subgroups>

--with-issues-enabled <with_issues_enabled>

--with-merge-requests-enabled <with_merge_requests_enabled>

--with-shared <with_shared>
--min-access-level <min_access_level>
--with-security-reports <with_security_reports>
--page <page>
--per-page <per_page>
--all

gitlab group-runner

```
usage: gitlab group-runner [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab group-runner list

```
usage: gitlab group-runner list [-h] [--sudo SUDO] --group-id GROUP_ID
                                [--scope SCOPE] [--tag-list TAG_LIST]
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>
--group-id <group_id>
--scope <scope>
--tag-list <tag_list>
--page <page>
--per-page <per_page>
--all

gitlab group-subgroup

```
usage: gitlab group-subgroup [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab group-subgroup list

```
usage: gitlab group-subgroup list [-h] [--sudo SUDO] --group-id GROUP_ID
                                   [--skip-groups SKIP_GROUPS]
                                   [--all-available ALL_AVAILABLE]
                                   [--search SEARCH] [--order-by ORDER_BY]
                                   [--sort SORT] [--statistics STATISTICS]
                                   [--owned OWNED]
                                   [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                   [--min-access-level MIN_ACCESS_LEVEL]
                                   [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--skip-groups <skip_groups>

--all-available <all_available>

--search <search>

--order-by <order_by>

--sort <sort>

--statistics <statistics>

--owned <owned>

--with-custom-attributes <with_custom_attributes>

--min-access-level <min_access_level>

--page <page>

--per-page <per_page>

--all

gitlab group-variable

```
usage: gitlab group-variable [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-variable create

```
usage: gitlab group-variable create [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --key KEY --value VALUE
                                     [--protected PROTECTED]
                                     [--variable-type VARIABLE_TYPE]
                                     [--masked MASKED]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

--value <value>

--protected <protected>

--variable-type <variable_type>

--masked <masked>

gitlab group-variable delete

```
usage: gitlab group-variable delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --key KEY
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

gitlab group-variable get

```
usage: gitlab group-variable get [-h] [--sudo SUDO] --group-id GROUP_ID --key
                                   KEY
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

gitlab group-variable list

```
usage: gitlab group-variable list [-h] [--sudo SUDO] --group-id GROUP_ID
                                   [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--all

gitlab group-variable update

```
usage: gitlab group-variable update [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --key KEY --value VALUE
                                     [--protected PROTECTED]
                                     [--variable-type VARIABLE_TYPE]
                                     [--masked MASKED]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

--value <value>

--protected <protected>

--variable-type <variable_type>

--masked <masked>

gitlab group-wiki

```
usage: gitlab group-wiki [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab group-wiki create

```
usage: gitlab group-wiki create [-h] [--sudo SUDO] --group-id GROUP_ID --title
                                TITLE --content CONTENT [--format FORMAT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--title <title>

--content <content>

--format <format>

gitlab group-wiki delete

```
usage: gitlab group-wiki delete [-h] [--sudo SUDO] --group-id GROUP_ID --slug
                                SLUG
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--slug <slug>

gitlab group-wiki get

```
usage: gitlab group-wiki get [-h] [--sudo SUDO] --group-id GROUP_ID --slug
                               SLUG
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--slug <slug>

gitlab group-wiki list

```
usage: gitlab group-wiki list [-h] [--sudo SUDO] --group-id GROUP_ID
                               [--with-content WITH_CONTENT] [--page PAGE]
                               [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--with-content <with_content>

--page <page>

--per-page <per_page>

--all

gitlab group-wiki update

```
usage: gitlab group-wiki update [-h] [--sudo SUDO] --group-id GROUP_ID --slug
                                SLUG [--title TITLE] [--content CONTENT]
                                [--format FORMAT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--slug <slug>

--title <title>

--content <content>

--format <format>

gitlab hook

```
usage: gitlab hook [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab hook create

```
usage: gitlab hook create [-h] [--sudo SUDO] --url URL
```

-h, --help
show this help message and exit

--sudo <sudo>

--url <url>

gitlab hook delete

```
usage: gitlab hook delete [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab hook get

```
usage: gitlab hook get [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab hook list

```
usage: gitlab hook list [-h] [--sudo SUDO] [--page PAGE] [--per-page PER_PAGE]
                        [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab issue

```
usage: gitlab issue [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab issue get

```
usage: gitlab issue get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab issue list

```
usage: gitlab issue list [-h] [--sudo SUDO] [--state STATE] [--labels LABELS]
                        [--milestone MILESTONE] [--scope SCOPE]
                        [--author-id AUTHOR_ID] [--assignee-id ASSIGNEE_ID]
                        [--my-reaction-emoji MY_REACTION_EMOJI] [--iids IIDS]
                        [--order-by ORDER_BY] [--sort SORT] [--search SEARCH]
                        [--created-after CREATED_AFTER]
                        [--created-before CREATED_BEFORE]
                        [--updated-after UPDATED_AFTER]
                        [--updated-before UPDATED_BEFORE] [--page PAGE]
                        [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--state <state>

--labels <labels>

--milestone <milestone>

--scope <scope>

--author-id <author_id>

--assignee-id <assignee_id>

--my-reaction-emoji <my_reaction_emoji>

--iids <iids>

--order-by <order_by>

```
--sort <sort>
--search <search>
--created-after <created_after>
--created-before <created_before>
--updated-after <updated_after>
--updated-before <updated_before>
--page <page>
--per-page <per_page>
--all
```

gitlab issues-statistics

```
usage: gitlab issues-statistics [-h] {get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab issues-statistics get

```
usage: gitlab issues-statistics get [-h] [--sudo SUDO]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
```

gitlab key

```
usage: gitlab key [-h] {get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab key get

```
usage: gitlab key get [-h] [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>
```

gitlab ldap-group

```
usage: gitlab ldap-group [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab ldap-group list

```
usage: gitlab ldap-group list [-h] [--sudo SUDO] [--search SEARCH]
                             [--provider PROVIDER] [--page PAGE]
                             [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--search <search>

--provider <provider>

--page <page>

--per-page <per_page>

--all

gitlab license

```
usage: gitlab license [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab license get

```
usage: gitlab license get [-h] [--sudo SUDO] --key KEY [--project PROJECT]
                          [--fullname FULLNAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

--project <project>

--fullname <fullname>

gitlab license list

```
usage: gitlab license list [-h] [--sudo SUDO] [--popular POPULAR]
                          [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--popular <popular>

--page <page>

--per-page <per_page>

--all

gitlab merge-request

```
usage: gitlab merge-request [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab merge-request list

```
usage: gitlab merge-request list [-h] [--sudo SUDO] [--state STATE]
                                [--order-by ORDER_BY] [--sort SORT]
                                [--milestone MILESTONE] [--view VIEW]
                                [--labels LABELS]
                                [--with-labels-details WITH_LABELS_DETAILS]
                                [--with-merge-status-recheck WITH_MERGE_STATUS_RECHECK]
                                [--created-after CREATED_AFTER]
                                [--created-before CREATED_BEFORE]
                                [--updated-after UPDATED_AFTER]
                                [--updated-before UPDATED_BEFORE]
                                [--scope SCOPE] [--author-id AUTHOR_ID]
                                [--author-username AUTHOR_USERNAME]
                                [--assignee-id ASSIGNEE_ID]
                                [--approver-ids APPROVER_IDS]
                                [--approved-by-ids APPROVED_BY_IDS]
                                [--reviewer-id REVIEWER_ID]
                                [--reviewer-username REVIEWER_USERNAME]
                                [--my-reaction-emoji MY_REACTION_EMOJI]
                                [--source-branch SOURCE_BRANCH]
                                [--target-branch TARGET_BRANCH]
                                [--search SEARCH] [--in IN] [--wip WIP]
                                [--not NOT] [--environment ENVIRONMENT]
                                [--deployed-before DEPLOYED_BEFORE]
                                [--deployed-after DEPLOYED_AFTER]
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--state <state>

--order-by <order_by>

--sort <sort>

--milestone <milestone>

--view <view>

--labels <labels>

--with-labels-details <with_labels_details>

--with-merge-status-recheck <with_merge_status_recheck>

--created-after <created_after>

--created-before <created_before>

--updated-after <updated_after>

--updated-before <updated_before>

--scope <scope>

--author-id <author_id>

--author-username <author_username>

--assignee-id <assignee_id>

--approver-ids <approver_ids>

--approved-by-ids <approved_by_ids>

--reviewer-id <reviewer_id>

--reviewer-username <reviewer_username>

--my-reaction-emoji <my_reaction_emoji>

--source-branch <source_branch>

--target-branch <target_branch>

--search <search>

--in <in>

--wip <wip>

--not <not>

--environment <environment>

--deployed-before <deployed_before>
--deployed-after <deployed_after>
--page <page>
--per-page <per_page>
--all

gitlab namespace

```
usage: gitlab namespace [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab namespace get

```
usage: gitlab namespace get [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit
--sudo <sudo>
--id <id>

gitlab namespace list

```
usage: gitlab namespace list [-h] [--sudo SUDO] [--search SEARCH]
                             [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit
--sudo <sudo>
--search <search>
--page <page>
--per-page <per_page>
--all

gitlab notification-settings

```
usage: gitlab notification-settings [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab notification-settings get

```
usage: gitlab notification-settings get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab notification-settings update

```
usage: gitlab notification-settings update [-h] [--sudo SUDO] [--level LEVEL]
                                           [--notification-email NOTIFICATION_EMAIL]
                                           [--new-note NEW_NOTE]
                                           [--new-issue NEW_ISSUE]
                                           [--reopen-issue REOPEN_ISSUE]
                                           [--close-issue CLOSE_ISSUE]
                                           [--reassign-issue REASSIGN_ISSUE]
                                           [--new-merge-request NEW_MERGE_REQUEST]
                                           [--reopen-merge-request REOPEN_MERGE_REQUEST]
                                           [--close-merge-request CLOSE_MERGE_REQUEST]
                                           [--reassign-merge-request REASSIGN_MERGE_
↪REQUEST]
                                           [--merge-merge-request MERGE_MERGE_REQUEST]
```

-h, --help

show this help message and exit

--sudo <sudo>

--level <level>

--notification-email <notification_email>

--new-note <new_note>

--new-issue <new_issue>

--reopen-issue <reopen_issue>

--close-issue <close_issue>

--reassign-issue <reassign_issue>

--new-merge-request <new_merge_request>

```
--reopen-merge-request <reopen_merge_request>
--close-merge-request <close_merge_request>
--reassign-merge-request <reassign_merge_request>
--merge-merge-request <merge_merge_request>
```

gitlab pages-domain

```
usage: gitlab pages-domain [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab pages-domain list

```
usage: gitlab pages-domain list [-h] [--sudo SUDO] [--page PAGE]
                                [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab personal-access-token

```
usage: gitlab personal-access-token [-h] {list,delete} ...
```

-h, --help
show this help message and exit

gitlab personal-access-token delete

```
usage: gitlab personal-access-token delete [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab personal-access-token list

```
usage: gitlab personal-access-token list [-h] [--sudo SUDO]
                                         [--user-id USER_ID] [--page PAGE]
                                         [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--all

gitlab project

```
usage: gitlab project [-h]
                    {list,get,create,update,delete,artifacts,update-submodule,
↳ repository-tree,repository-blob,repository-raw-blob,repository-compare,repository-
↳ contributors,repository-archive,delete-merged-branches,create-fork-relation,delete-
↳ fork-relation,languages,star,unstar,archive,unarchive,share,unshare,trigger-pipeline,
↳ housekeeping,upload,snapshot,search,mirror-pull,transfer,transfer-project,artifact}
                    ...
```

-h, --help
show this help message and exit

gitlab project archive

```
usage: gitlab project archive [-h] --id ID
```

-h, --help
show this help message and exit

--id <id>

gitlab project artifact

```
usage: gitlab project artifact [-h] --id ID --ref-name REF_NAME
                               --artifact-path ARTIFACT_PATH --job JOB
```

-h, --help
show this help message and exit

--id <id>

```
--ref-name <ref_name>
--artifact-path <artifact_path>
--job <job>
```

gitlab project artifacts

```
usage: gitlab project artifacts [-h] --id ID --ref-name REF_NAME --job JOB
                                [--job-token JOB_TOKEN]
```

```
-h, --help
    show this help message and exit
--id <id>
--ref-name <ref_name>
--job <job>
--job-token <job_token>
```

gitlab project create

```
usage: gitlab project create [-h] [--sudo SUDO] [--name NAME] [--path PATH]
                             [--allow-merge-on-skipped-pipeline ALLOW_MERGE_ON_SKIPPED_
↳PIPELINE]
                             [--analytics-access-level ANALYTICS_ACCESS_LEVEL]
                             [--approvals-before-merge APPROVALS_BEFORE_MERGE]
                             [--auto-cancel-pending-pipelines AUTO_CANCEL_PENDING_
↳PIPELINES]
                             [--auto-devops-deploy-strategy AUTO_DEVOPS_DEPLOY_STRATEGY]
                             [--auto-devops-enabled AUTO_DEVOPS_ENABLED]
                             [--autoclose-referenced-issues AUTOCLOSE_REFERENCED_ISSUES]
                             [--avatar AVATAR]
                             [--build-coverage-regex BUILD_COVERAGE_REGEX]
                             [--build-git-strategy BUILD_GIT_STRATEGY]
                             [--build-timeout BUILD_TIMEOUT]
                             [--builds-access-level BUILDS_ACCESS_LEVEL]
                             [--ci-config-path CI_CONFIG_PATH]
                             [--container-expiration-policy-attributes CONTAINER_
↳EXPIRATION_POLICY_ATTRIBUTES]
                             [--container-registry-enabled CONTAINER_REGISTRY_ENABLED]
                             [--default-branch DEFAULT_BRANCH]
                             [--description DESCRIPTION]
                             [--emails-disabled EMAILS_DISABLED]
                             [--external-authorization-classification-label EXTERNAL_
↳AUTHORIZATION_CLASSIFICATION_LABEL]
                             [--forking-access-level FORKING_ACCESS_LEVEL]
                             [--group-with-project-templates-id GROUP_WITH_PROJECT_
↳TEMPLATES_ID]
                             [--import-url IMPORT_URL]
```

(continues on next page)

(continued from previous page)

```

[--initialize-with-readme INITIALIZE_WITH_README]
[--issues-access-level ISSUES_ACCESS_LEVEL]
[--issues-enabled ISSUES_ENABLED]
[--jobs-enabled JOBS_ENABLED]
[--lfs-enabled LFS_ENABLED]
[--merge-method MERGE_METHOD]
[--merge-requests-access-level MERGE_REQUESTS_ACCESS_LEVEL]
[--merge-requests-enabled MERGE_REQUESTS_ENABLED]
[--mirror-trigger-builds MIRROR_TRIGGER_BUILDS]
[--mirror MIRROR] [--namespace-id NAMESPACE_ID]
[--operations-access-level OPERATIONS_ACCESS_LEVEL]
[--only-allow-merge-if-all-discussions-are-resolved ONLY_
↪ ALLOW_MERGE_IF_ALL_DISCUSSIONS_ARE_RESOLVED]
[--only-allow-merge-if-pipeline-succeeds ONLY_ALLOW_MERGE_
↪ IF_PIPELINE_SUCCEEDS]
[--packages-enabled PACKAGES_ENABLED]
[--pages-access-level PAGES_ACCESS_LEVEL]
[--requirements-access-level REQUIREMENTS_ACCESS_LEVEL]
[--printing-merge-request-link-enabled PRINTING_MERGE_
↪ REQUEST_LINK_ENABLED]
[--public-builds PUBLIC_BUILDS]
[--remove-source-branch-after-merge REMOVE_SOURCE_BRANCH_
↪ AFTER_MERGE]
[--repository-access-level REPOSITORY_ACCESS_LEVEL]
[--repository-storage REPOSITORY_STORAGE]
[--request-access-enabled REQUEST_ACCESS_ENABLED]
[--resolve-outdated-diff-discussions RESOLVE_OUTDATED_DIFF_
↪ DISCUSSIONS]
[--shared-runners-enabled SHARED_RUNNERS_ENABLED]
[--show-default-award-emojis SHOW_DEFAULT_AWARD_EMOJIS]
[--snippets-access-level SNIPPETS_ACCESS_LEVEL]
[--snippets-enabled SNIPPETS_ENABLED]
[--squash-option SQUASH_OPTION]
[--tag-list TAG_LIST]
[--template-name TEMPLATE_NAME]
[--template-project-id TEMPLATE_PROJECT_ID]
[--use-custom-template USE_CUSTOM_TEMPLATE]
[--visibility VISIBILITY]
[--wiki-access-level WIKI_ACCESS_LEVEL]
[--wiki-enabled WIKI_ENABLED]

```

-h, --help

show this help message and exit

--sudo <sudo>**--name** <name>**--path** <path>**--allow-merge-on-skipped-pipeline** <allow_merge_on_skipped_pipeline>**--analytics-access-level** <analytics_access_level>

```
--approvals-before-merge <approvals_before_merge>
--auto-cancel-pending-pipelines <auto_cancel_pending_pipelines>
--auto-devops-deploy-strategy <auto_devops_deploy_strategy>
--auto-devops-enabled <auto_devops_enabled>
--autoclose-referenced-issues <autoclose_referenced_issues>
--avatar <avatar>
--build-coverage-regex <build_coverage_regex>
--build-git-strategy <build_git_strategy>
--build-timeout <build_timeout>
--builds-access-level <builds_access_level>
--ci-config-path <ci_config_path>
--container-expiration-policy-attributes <container_expiration_policy_attributes>
--container-registry-enabled <container_registry_enabled>
--default-branch <default_branch>
--description <description>
--emails-disabled <emails_disabled>
--external-authorization-classification-label <external_authorization_classification_label>
--forking-access-level <forking_access_level>
--group-with-project-templates-id <group_with_project_templates_id>
--import-url <import_url>
--initialize-with-readme <initialize_with_readme>
--issues-access-level <issues_access_level>
--issues-enabled <issues_enabled>
--jobs-enabled <jobs_enabled>
--lfs-enabled <lfs_enabled>
--merge-method <merge_method>
--merge-requests-access-level <merge_requests_access_level>
--merge-requests-enabled <merge_requests_enabled>
--mirror-trigger-builds <mirror_trigger_builds>
--mirror <mirror>
--namespace-id <namespace_id>
```

```

--operations-access-level <operations_access_level>
--only-allow-merge-if-all-discussions-are-resolved <only_allow_merge_if_all_discussions_are_resolved>
--only-allow-merge-if-pipeline-succeeds <only_allow_merge_if_pipeline_succeeds>
--packages-enabled <packages_enabled>
--pages-access-level <pages_access_level>
--requirements-access-level <requirements_access_level>
--printing-merge-request-link-enabled <printing_merge_request_link_enabled>
--public-builds <public_builds>
--remove-source-branch-after-merge <remove_source_branch_after_merge>
--repository-access-level <repository_access_level>
--repository-storage <repository_storage>
--request-access-enabled <request_access_enabled>
--resolve-outdated-diff-discussions <resolve_outdated_diff_discussions>
--shared-runners-enabled <shared_runners_enabled>
--show-default-award-emojis <show_default_award_emojis>
--snippets-access-level <snippets_access_level>
--snippets-enabled <snippets_enabled>
--squash-option <squash_option>
--tag-list <tag_list>
--template-name <template_name>
--template-project-id <template_project_id>
--use-custom-template <use_custom_template>
--visibility <visibility>
--wiki-access-level <wiki_access_level>
--wiki-enabled <wiki_enabled>

```

gitlab project create-fork-relation

```
usage: gitlab project create-fork-relation [-h] --id ID --forked-from-id
                                         FORKED_FROM_ID
```

```

-h, --help
    show this help message and exit
--id <id>
--forked-from-id <forked_from_id>

```

gitlab project delete

```
usage: gitlab project delete [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab project delete-fork-relation

```
usage: gitlab project delete-fork-relation [-h] --id ID
```

-h, --help
show this help message and exit

--id <id>

gitlab project delete-merged-branches

```
usage: gitlab project delete-merged-branches [-h] --id ID
```

-h, --help
show this help message and exit

--id <id>

gitlab project get

```
usage: gitlab project get [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab project housekeeping

```
usage: gitlab project housekeeping [-h] --id ID
```

-h, --help
show this help message and exit

--id <id>

gitlab project languages

```
usage: gitlab project languages [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project list

```
usage: gitlab project list [-h] [--sudo SUDO] [--archived ARCHIVED]
                           [--id-after ID_AFTER] [--id-before ID_BEFORE]
                           [--last-activity-after LAST_ACTIVITY_AFTER]
                           [--last-activity-before LAST_ACTIVITY_BEFORE]
                           [--membership MEMBERSHIP]
                           [--min-access-level MIN_ACCESS_LEVEL]
                           [--order-by ORDER_BY] [--owned OWNED]
                           [--repository-checksum-failed REPOSITORY_CHECKSUM_FAILED]
                           [--repository-storage REPOSITORY_STORAGE]
                           [--search-namespaces SEARCH_NAMESPACES]
                           [--search SEARCH] [--simple SIMPLE] [--sort SORT]
                           [--starred STARRED] [--statistics STATISTICS]
                           [--topic TOPIC] [--visibility VISIBILITY]
                           [--wiki-checksum-failed WIKI_CHECKSUM_FAILED]
                           [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                           [--with-issues-enabled WITH_ISSUES_ENABLED]
                           [--with-merge-requests-enabled WITH_MERGE_REQUESTS_ENABLED]
                           [--with-programming-language WITH_PROGRAMMING_LANGUAGE]
                           [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--archived <archived>

--id-after <id_after>

--id-before <id_before>

--last-activity-after <last_activity_after>

--last-activity-before <last_activity_before>

--membership <membership>

--min-access-level <min_access_level>

--order-by <order_by>

--owned <owned>

--repository-checksum-failed <repository_checksum_failed>

```
--repository-storage <repository_storage>
--search-namespaces <search_namespaces>
--search <search>
--simple <simple>
--sort <sort>
--starred <starred>
--statistics <statistics>
--topic <topic>
--visibility <visibility>
--wiki-checksum-failed <wiki_checksum_failed>
--with-custom-attributes <with_custom_attributes>
--with-issues-enabled <with_issues_enabled>
--with-merge-requests-enabled <with_merge_requests_enabled>
--with-programming-language <with_programming_language>
--page <page>
--per-page <per_page>
--all
```

gitlab project mirror-pull

```
usage: gitlab project mirror-pull [-h] --id ID
```

```
-h, --help
    show this help message and exit
--id <id>
```

gitlab project repository-archive

```
usage: gitlab project repository-archive [-h] --id ID [--sha SHA]
                                         [--format FORMAT]
```

```
-h, --help
    show this help message and exit
--id <id>
--sha <sha>
--format <format>
```

gitlab project repository-blob

```
usage: gitlab project repository-blob [-h] --id ID --sha SHA
```

-h, --help

show this help message and exit

--id <id>

--sha <sha>

gitlab project repository-compare

```
usage: gitlab project repository-compare [-h] --id ID --from- FROM_ --to TO
```

-h, --help

show this help message and exit

--id <id>

--from- <from_>

--to <to>

gitlab project repository-contributors

```
usage: gitlab project repository-contributors [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project repository-raw-blob

```
usage: gitlab project repository-raw-blob [-h] --id ID --sha SHA
```

-h, --help

show this help message and exit

--id <id>

--sha <sha>

gitlab project repository-tree

```
usage: gitlab project repository-tree [-h] --id ID [--path PATH] [--ref REF]
                                     [--recursive RECURSIVE]
```

-h, --help
show this help message and exit

--id <id>

--path <path>

--ref <ref>

--recursive <recursive>

gitlab project search

```
usage: gitlab project search [-h] --id ID --scope SCOPE --search SEARCH
```

-h, --help
show this help message and exit

--id <id>

--scope <scope>

--search <search>

gitlab project share

```
usage: gitlab project share [-h] --id ID --group-id GROUP_ID --group-access
                             GROUP_ACCESS [--expires-at EXPIRES_AT]
```

-h, --help
show this help message and exit

--id <id>

--group-id <group_id>

--group-access <group_access>

--expires-at <expires_at>

gitlab project snapshot

```
usage: gitlab project snapshot [-h] --id ID [--wiki WIKI]
```

-h, --help

show this help message and exit

--id <id>

--wiki <wiki>

gitlab project star

```
usage: gitlab project star [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project transfer

```
usage: gitlab project transfer [-h] --id ID --to-namespace TO_NAMESPACE
```

-h, --help

show this help message and exit

--id <id>

--to-namespace <to_namespace>

gitlab project transfer-project

```
usage: gitlab project transfer-project [-h] --id ID --to-namespace
                                         TO_NAMESPACE
```

-h, --help

show this help message and exit

--id <id>

--to-namespace <to_namespace>

gitlab project trigger-pipeline

```
usage: gitlab project trigger-pipeline [-h] --id ID --ref REF --token TOKEN
```

-h, --help
show this help message and exit

--id <id>

--ref <ref>

--token <token>

gitlab project unarchive

```
usage: gitlab project unarchive [-h] --id ID
```

-h, --help
show this help message and exit

--id <id>

gitlab project unshare

```
usage: gitlab project unshare [-h] --id ID --group-id GROUP_ID
```

-h, --help
show this help message and exit

--id <id>

--group-id <group_id>

gitlab project unstar

```
usage: gitlab project unstar [-h] --id ID
```

-h, --help
show this help message and exit

--id <id>

gitlab project update

```
usage: gitlab project update [-h] [--sudo SUDO] --id ID
                             [--allow-merge-on-skipped-pipeline ALLOW_MERGE_ON_SKIPPED_
↳ PIPELINE]
                             [--analytics-access-level ANALYTICS_ACCESS_LEVEL]
                             [--approvals-before-merge APPROVALS_BEFORE_MERGE]
                             [--auto-cancel-pending-pipelines AUTO_CANCEL_PENDING_
↳ PIPELINES]
                             [--auto-devops-deploy-strategy AUTO_DEVOPS_DEPLOY_STRATEGY]
                             [--auto-devops-enabled AUTO_DEVOPS_ENABLED]
                             [--autoclose-referenced-issues AUTOCLOSE_REFERENCED_ISSUES]
                             [--avatar AVATAR]
                             [--build-coverage-regex BUILD_COVERAGE_REGEX]
                             [--build-git-strategy BUILD_GIT_STRATEGY]
                             [--build-timeout BUILD_TIMEOUT]
                             [--builds-access-level BUILDS_ACCESS_LEVEL]
                             [--ci-config-path CI_CONFIG_PATH]
                             [--ci-default-git-depth CI_DEFAULT_GIT_DEPTH]
                             [--ci-forward-deployment-enabled CI_FORWARD_DEPLOYMENT_
↳ ENABLED]
                             [--container-expiration-policy-attributes CONTAINER_
↳ EXPIRATION_POLICY_ATTRIBUTES]
                             [--container-registry-enabled CONTAINER_REGISTRY_ENABLED]
                             [--default-branch DEFAULT_BRANCH]
                             [--description DESCRIPTION]
                             [--emails-disabled EMAILS_DISABLED]
                             [--external-authorization-classification-label EXTERNAL_
↳ AUTHORIZATION_CLASSIFICATION_LABEL]
                             [--forking-access-level FORKING_ACCESS_LEVEL]
                             [--import-url IMPORT_URL]
                             [--issues-access-level ISSUES_ACCESS_LEVEL]
                             [--issues-enabled ISSUES_ENABLED]
                             [--jobs-enabled JOBS_ENABLED]
                             [--lfs-enabled LFS_ENABLED]
                             [--merge-method MERGE_METHOD]
                             [--merge-requests-access-level MERGE_REQUESTS_ACCESS_LEVEL]
                             [--merge-requests-enabled MERGE_REQUESTS_ENABLED]
                             [--mirror-overwrites-diverged-branches MIRROR_OVERWRITES_
↳ DIVERGED_BRANCHES]
                             [--mirror-trigger-builds MIRROR_TRIGGER_BUILDS]
                             [--mirror-user-id MIRROR_USER_ID]
                             [--mirror MIRROR] [--name NAME]
                             [--operations-access-level OPERATIONS_ACCESS_LEVEL]
                             [--only-allow-merge-if-all-discussions-are-resolved ONLY_
↳ ALLOW_MERGE_IF_ALL_DISCUSSIONS_ARE_RESOLVED]
                             [--only-allow-merge-if-pipeline-succeeds ONLY_ALLOW_MERGE_
↳ IF_PIPELINE_SUCCEEDS]
                             [--only-mirror-protected-branches ONLY_MIRROR_PROTECTED_
↳ BRANCHES]
                             [--packages-enabled PACKAGES_ENABLED]
                             [--pages-access-level PAGES_ACCESS_LEVEL]
                             [--requirements-access-level REQUIREMENTS_ACCESS_LEVEL]
```

(continues on next page)

(continued from previous page)

```

--restrict-user-defined-variables RESTRICT_USER_DEFINED_
↪VARIABLES]
--path PATH] [--public-builds PUBLIC_BUILDS]
--remove-source-branch-after-merge REMOVE_SOURCE_BRANCH_
↪AFTER_MERGE]
--repository-access-level REPOSITORY_ACCESS_LEVEL]
--repository-storage REPOSITORY_STORAGE]
--request-access-enabled REQUEST_ACCESS_ENABLED]
--resolve-outdated-diff-discussions RESOLVE_OUTDATED_DIFF_
↪DISCUSSIONS]
--service-desk-enabled SERVICE_DESK_ENABLED]
--shared-runners-enabled SHARED_RUNNERS_ENABLED]
--show-default-award-emojis SHOW_DEFAULT_AWARD_EMOJIS]
--snippets-access-level SNIPPETS_ACCESS_LEVEL]
--snippets-enabled SNIPPETS_ENABLED]
--squash-option SQUASH_OPTION]
--suggestion-commit-message SUGGESTION_COMMIT_MESSAGE]
--tag-list TAG_LIST] [--visibility VISIBILITY]
--wiki-access-level WIKI_ACCESS_LEVEL]
--wiki-enabled WIKI_ENABLED]
--issues-template ISSUES_TEMPLATE]
--merge-requests-template MERGE_REQUESTS_TEMPLATE]

```

-h, --help

show this help message and exit

--sudo <sudo>**--id** <id>**--allow-merge-on-skipped-pipeline** <allow_merge_on_skipped_pipeline>**--analytics-access-level** <analytics_access_level>**--approvals-before-merge** <approvals_before_merge>**--auto-cancel-pending-pipelines** <auto_cancel_pending_pipelines>**--auto-devops-deploy-strategy** <auto_devops_deploy_strategy>**--auto-devops-enabled** <auto_devops_enabled>**--autoclose-referenced-issues** <autoclose_referenced_issues>**--avatar** <avatar>**--build-coverage-regex** <build_coverage_regex>**--build-git-strategy** <build_git_strategy>**--build-timeout** <build_timeout>**--builds-access-level** <builds_access_level>**--ci-config-path** <ci_config_path>

```
--ci-default-git-depth <ci_default_git_depth>
--ci-forward-deployment-enabled <ci_forward_deployment_enabled>
--container-expiration-policy-attributes <container_expiration_policy_attributes>
--container-registry-enabled <container_registry_enabled>
--default-branch <default_branch>
--description <description>
--emails-disabled <emails_disabled>
--external-authorization-classification-label <external_authorization_classification_label>
--forking-access-level <forking_access_level>
--import-url <import_url>
--issues-access-level <issues_access_level>
--issues-enabled <issues_enabled>
--jobs-enabled <jobs_enabled>
--lfs-enabled <lfs_enabled>
--merge-method <merge_method>
--merge-requests-access-level <merge_requests_access_level>
--merge-requests-enabled <merge_requests_enabled>
--mirror-overwrites-diverged-branches <mirror_overwrites_diverged_branches>
--mirror-trigger-builds <mirror_trigger_builds>
--mirror-user-id <mirror_user_id>
--mirror <mirror>
--name <name>
--operations-access-level <operations_access_level>
--only-allow-merge-if-all-discussions-are-resolved <only_allow_merge_if_all_discussions_are_resolved>
--only-allow-merge-if-pipeline-succeeds <only_allow_merge_if_pipeline_succeeds>
--only-mirror-protected-branches <only_mirror_protected_branches>
--packages-enabled <packages_enabled>
--pages-access-level <pages_access_level>
--requirements-access-level <requirements_access_level>
--restrict-user-defined-variables <restrict_user_defined_variables>
--path <path>
```

```
--public-builds <public_builds>
--remove-source-branch-after-merge <remove_source_branch_after_merge>
--repository-access-level <repository_access_level>
--repository-storage <repository_storage>
--request-access-enabled <request_access_enabled>
--resolve-outdated-diff-discussions <resolve_outdated_diff_discussions>
--service-desk-enabled <service_desk_enabled>
--shared-runners-enabled <shared_runners_enabled>
--show-default-award-emojis <show_default_award_emojis>
--snippets-access-level <snippets_access_level>
--snippets-enabled <snippets_enabled>
--squash-option <squash_option>
--suggestion-commit-message <suggestion_commit_message>
--tag-list <tag_list>
--visibility <visibility>
--wiki-access-level <wiki_access_level>
--wiki-enabled <wiki_enabled>
--issues-template <issues_template>
--merge-requests-template <merge_requests_template>
```

gitlab project update-submodule

```
usage: gitlab project update-submodule [-h] --id ID --submodule SUBMODULE
                                         --branch BRANCH --commit-sha COMMIT_SHA
```

```
-h, --help
    show this help message and exit
--id <id>
--submodule <submodule>
--branch <branch>
--commit-sha <commit_sha>
```

gitlab project upload

```
usage: gitlab project upload [-h] --id ID --filename FILENAME --filepath
                             FILEPATH
```

-h, --help
show this help message and exit

--id <id>

--filename <filename>

--filepath <filepath>

gitlab project-access-request

```
usage: gitlab project-access-request [-h] {list,create,delete,approve} ...
```

-h, --help
show this help message and exit

gitlab project-access-request approve

```
usage: gitlab project-access-request approve [-h] --project-id PROJECT_ID
                                              [--sudo SUDO] --id ID
                                              [--access-level ACCESS_LEVEL]
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--access-level <access_level>

gitlab project-access-request create

```
usage: gitlab project-access-request create [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-access-request delete

```
usage: gitlab project-access-request delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-access-request list

```
usage: gitlab project-access-request list [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID [--page PAGE]
                                           [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-access-token

```
usage: gitlab project-access-token [-h] {list,create,delete} ...
```

-h, --help
show this help message and exit

gitlab project-access-token create

```
usage: gitlab project-access-token create [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-access-token delete

```
usage: gitlab project-access-token delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-access-token list

```
usage: gitlab project-access-token list [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID [--page PAGE]
                                           [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-additional-statistics

```
usage: gitlab project-additional-statistics [-h] {get} ...
```

-h, --help
show this help message and exit

gitlab project-additional-statistics get

```
usage: gitlab project-additional-statistics get [-h] [--sudo SUDO]
                                                  --project-id PROJECT_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-approval

```
usage: gitlab project-approval [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab project-approval get

```
usage: gitlab project-approval get [-h] [--sudo SUDO] --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-approval update

```
usage: gitlab project-approval update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID
                                         [--approvals-before-merge APPROVALS_BEFORE_MERGE]
                                         [--reset-approvals-on-push RESET_APPROVALS_ON_PUSH]
                                         [--disable-overriding-approvers-per-merge-request_
↳DISABLE_OVERRIDING_APPROVERS_PER_MERGE_REQUEST]
                                         [--merge-requests-author-approval MERGE_REQUESTS_
↳AUTHOR_APPROVAL]
                                         [--merge-requests-disable-committers-approval_
↳MERGE_REQUESTS_DISABLE_COMMITTERS_APPROVAL]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--approvals-before-merge <approvals_before_merge>

--reset-approvals-on-push <reset_approvals_on_push>

--disable-overriding-approvers-per-merge-request <disable_overriding_approvers_per_merge_request>

--merge-requests-author-approval <merge_requests_author_approval>

--merge-requests-disable-committers-approval <merge_requests_disable_committers_approval>

gitlab project-approval-rule

```
usage: gitlab project-approval-rule [-h] {list,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-approval-rule create

```
usage: gitlab project-approval-rule create [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --name NAME
                                           --approvals-required
                                           APPROVALS_REQUIRED
                                           [--user-ids USER_IDS]
                                           [--group-ids GROUP_IDS]
                                           [--protected-branch-ids PROTECTED_BRANCH_IDS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--approvals-required <approvals_required>

--user-ids <user_ids>

--group-ids <group_ids>

--protected-branch-ids <protected_branch_ids>

gitlab project-approval-rule delete

```
usage: gitlab project-approval-rule delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-approval-rule list

```
usage: gitlab project-approval-rule list [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID [--page PAGE]
                                           [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-approval-rule update

```
usage: gitlab project-approval-rule update [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-artifact

```
usage: gitlab project-artifact [-h] {delete,download,raw} ...
```

-h, --help
show this help message and exit

gitlab project-artifact delete

```
usage: gitlab project-artifact delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --ref-name REF_NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--ref-name <ref_name>

gitlab project-artifact download

```
usage: gitlab project-artifact download [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --ref-name REF_NAME
                                         --job JOB [--job-token JOB_TOKEN]
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--ref-name <ref_name>

--job <job>

--job-token <job_token>

gitlab project-artifact raw

```
usage: gitlab project-artifact raw [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --ref-name REF_NAME --artifact-path
                                   ARTIFACT_PATH --job JOB
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--ref-name <ref_name>

--artifact-path <artifact_path>

--job <job>

gitlab project-audit-event

```
usage: gitlab project-audit-event [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab project-audit-event get

```
usage: gitlab project-audit-event get [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-audit-event list

```
usage: gitlab project-audit-event list [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID
                                     [--created-after CREATED_AFTER]
                                     [--created-before CREATED_BEFORE]
                                     [--page PAGE] [--per-page PER_PAGE]
                                     [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--created-after <created_after>

--created-before <created_before>

--page <page>

--per-page <per_page>

--all

gitlab project-badge

```
usage: gitlab project-badge [-h] {list,get,create,update,delete,render} ...
```

-h, --help
show this help message and exit

gitlab project-badge create

```
usage: gitlab project-badge create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --link-url LINK_URL --image-url IMAGE_URL
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--link-url <link_url>

--image-url <image_url>

gitlab project-badge delete

```
usage: gitlab project-badge delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-badge get

```
usage: gitlab project-badge get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-badge list

```
usage: gitlab project-badge list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-badge render

```
usage: gitlab project-badge render [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID --link-url LINK_URL --image-url
                                   IMAGE_URL
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--link-url <link_url>

--image-url <image_url>

gitlab project-badge update

```
usage: gitlab project-badge update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID [--link-url LINK_URL]
                                   [--image-url IMAGE_URL]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--link-url <link_url>

--image-url <image_url>

gitlab project-board

```
usage: gitlab project-board [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-board create

```
usage: gitlab project-board create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-board delete

```
usage: gitlab project-board delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-board get

```
usage: gitlab project-board get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-board list

```
usage: gitlab project-board list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-board update

```
usage: gitlab project-board update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-board-list

```
usage: gitlab project-board-list [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-board-list create

```
usage: gitlab project-board-list create [-h] [--sudo SUDO] --project-id
                                PROJECT_ID --board-id BOARD_ID
                                --label-id LABEL_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

--label-id <label_id>

gitlab project-board-list delete

```
usage: gitlab project-board-list delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --board-id BOARD_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

--id <id>

gitlab project-board-list get

```
usage: gitlab project-board-list get [-h] [--sudo SUDO] --project-id
                                       PROJECT_ID --board-id BOARD_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

--id <id>

gitlab project-board-list list

```
usage: gitlab project-board-list list [-h] [--sudo SUDO] --project-id
                                       PROJECT_ID --board-id BOARD_ID
                                       [--page PAGE] [--per-page PER_PAGE]
                                       [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

--page <page>

--per-page <per_page>
--all

gitlab project-board-list update

```
usage: gitlab project-board-list update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --board-id BOARD_ID --id ID
                                         --position POSITION
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

--id <id>

--position <position>

gitlab project-branch

```
usage: gitlab project-branch [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab project-branch create

```
usage: gitlab project-branch create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                     --branch BRANCH --ref REF
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--branch <branch>

--ref <ref>

gitlab project-branch delete

```
usage: gitlab project-branch delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                     --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-branch get

```
usage: gitlab project-branch get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-branch list

```
usage: gitlab project-branch list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-cluster

```
usage: gitlab project-cluster [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-cluster create

```
usage: gitlab project-cluster create [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --name NAME
                                     --platform-kubernetes-attributes
                                     PLATFORM_KUBERNETES_ATTRIBUTES
                                     [--domain DOMAIN] [--enabled ENABLED]
                                     [--managed MANAGED]
                                     [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--platform-kubernetes-attributes <platform_kubernetes_attributes>

--domain <domain>

--enabled <enabled>

--managed <managed>

--environment-scope <environment_scope>

gitlab project-cluster delete

```
usage: gitlab project-cluster delete [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-cluster get

```
usage: gitlab project-cluster get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-cluster list

```
usage: gitlab project-cluster list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-cluster update

```
usage: gitlab project-cluster update [-h] [--sudo SUDO] --project-id
                                PROJECT_ID --id ID [--name NAME]
                                [--domain DOMAIN]
                                [--management-project-id MANAGEMENT_PROJECT_ID]
                                [--platform-kubernetes-attributes PLATFORM_
↪ KUBERNETES_ATTRIBUTES]
                                [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--name <name>

--domain <domain>

--management-project-id <management_project_id>
--platform-kubernetes-attributes <platform_kubernetes_attributes>
--environment-scope <environment_scope>

gitlab project-commit

```
usage: gitlab project-commit [-h]
                             {list,get,create,diff,cherry-pick,refs,merge-requests,
                             ↪revert,signature}
                             ...
```

-h, --help
show this help message and exit

gitlab project-commit cherry-pick

```
usage: gitlab project-commit cherry-pick [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --id ID --branch BRANCH
```

-h, --help
show this help message and exit

--project-id <project_id>
--sudo <sudo>
--id <id>
--branch <branch>

gitlab project-commit create

```
usage: gitlab project-commit create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                     --branch BRANCH --commit-message
                                     COMMIT_MESSAGE --actions ACTIONS
                                     [--author-email AUTHOR_EMAIL]
                                     [--author-name AUTHOR_NAME]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--branch <branch>

--commit-message <commit_message>

--actions <actions>

--author-email <author_email>

--author-name <author_name>

gitlab project-commit diff

```
usage: gitlab project-commit diff [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-commit get

```
usage: gitlab project-commit get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-commit list

```
usage: gitlab project-commit list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   [--ref-name REF_NAME] [--since SINCE]
                                   [--until UNTIL] [--path PATH]
                                   [--with-stats WITH_STATS]
                                   [--first-parent FIRST_PARENT]
                                   [--order ORDER] [--trailers TRAILERS]
                                   [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--ref-name <ref_name>

--since <since>

--until <until>
--path <path>
--with-stats <with_stats>
--first-parent <first_parent>
--order <order>
--trailers <trailers>
--page <page>
--per-page <per_page>
--all

gitlab project-commit merge-requests

```
usage: gitlab project-commit merge-requests [-h] --project-id PROJECT_ID
                                           [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>

gitlab project-commit refs

```
usage: gitlab project-commit refs [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID [--type TYPE]
```

-h, --help
show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>
--type <type>

gitlab project-commit revert

```
usage: gitlab project-commit revert [-h] --project-id PROJECT_ID [--sudo SUDO]
                                     --id ID --branch BRANCH
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--branch <branch>

gitlab project-commit signature

```
usage: gitlab project-commit signature [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-commit-comment

```
usage: gitlab project-commit-comment [-h] {list,create} ...
```

-h, --help
show this help message and exit

gitlab project-commit-comment create

```
usage: gitlab project-commit-comment create [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --commit-id COMMIT_ID
                                           --note NOTE [--path PATH]
                                           [--line LINE]
                                           [--line-type LINE_TYPE]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--commit-id <commit_id>
--note <note>
--path <path>
--line <line>
--line-type <line_type>
```

gitlab project-commit-comment list

```
usage: gitlab project-commit-comment list [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --commit-id COMMIT_ID
                                           [--page PAGE] [--per-page PER_PAGE]
                                           [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--commit-id <commit_id>
--page <page>
--per-page <per_page>
--all
```

gitlab project-commit-discussion

```
usage: gitlab project-commit-discussion [-h] {list,get,create} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-commit-discussion create

```
usage: gitlab project-commit-discussion create [-h] [--sudo SUDO] --project-id
                                                PROJECT_ID --commit-id
                                                COMMIT_ID --body BODY
                                                [--created-at CREATED_AT]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
```

--commit-id <commit_id>
--body <body>
--created-at <created_at>

gitlab project-commit-discussion get

```
usage: gitlab project-commit-discussion get [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --commit-id COMMIT_ID
                                           --id ID
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--commit-id <commit_id>
--id <id>

gitlab project-commit-discussion list

```
usage: gitlab project-commit-discussion list [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --commit-id COMMIT_ID
                                           [--page PAGE]
                                           [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--commit-id <commit_id>
--page <page>
--per-page <per_page>
--all

gitlab project-commit-discussion-note

```
usage: gitlab project-commit-discussion-note [-h]
                                             {get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-commit-discussion-note create

```
usage: gitlab project-commit-discussion-note create [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --commit-id COMMIT_ID
                                                    --discussion-id
DISCUSSION_ID --body BODY
                                                    [--created-at CREATED_AT]
                                                    [--position POSITION]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--discussion-id <discussion_id>

--body <body>

--created-at <created_at>

--position <position>

gitlab project-commit-discussion-note delete

```
usage: gitlab project-commit-discussion-note delete [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --commit-id COMMIT_ID
                                                    --discussion-id
DISCUSSION_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--discussion-id <discussion_id>

--id <id>

gitlab project-commit-discussion-note get

```
usage: gitlab project-commit-discussion-note get [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --commit-id COMMIT_ID
                                                --discussion-id DISCUSSION_ID
                                                --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--discussion-id <discussion_id>

--id <id>

gitlab project-commit-discussion-note update

```
usage: gitlab project-commit-discussion-note update [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --commit-id COMMIT_ID
                                                --discussion-id
DISCUSSION_ID --id ID
                                                --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--discussion-id <discussion_id>

--id <id>

--body <body>

gitlab project-commit-status

```
usage: gitlab project-commit-status [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab project-commit-status create

```
usage: gitlab project-commit-status create [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --commit-id COMMIT_ID
                                           --state STATE
                                           [--description DESCRIPTION]
                                           [--name NAME] [--context CONTEXT]
                                           [--ref REF]
                                           [--target-url TARGET_URL]
                                           [--coverage COVERAGE]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--state <state>

--description <description>

--name <name>

--context <context>

--ref <ref>

--target-url <target_url>

--coverage <coverage>

gitlab project-commit-status list

```
usage: gitlab project-commit-status list [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --commit-id COMMIT_ID
                                           [--page PAGE] [--per-page PER_PAGE]
                                           [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--page <page>

--per-page <per_page>

--all

gitlab project-custom-attribute

```
usage: gitlab project-custom-attribute [-h] {list,get,delete} ...
```

-h, --help
show this help message and exit

gitlab project-custom-attribute delete

```
usage: gitlab project-custom-attribute delete [-h] [--sudo SUDO] --project-id
      PROJECT_ID --key KEY
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--key <key>

gitlab project-custom-attribute get

```
usage: gitlab project-custom-attribute get [-h] [--sudo SUDO] --project-id
      PROJECT_ID --key KEY
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--key <key>

gitlab project-custom-attribute list

```
usage: gitlab project-custom-attribute list [-h] [--sudo SUDO] --project-id
      PROJECT_ID [--page PAGE]
      [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-deploy-token

```
usage: gitlab project-deploy-token [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-deploy-token create

```
usage: gitlab project-deploy-token create [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --name NAME --scopes
                                           SCOPES [--expires-at EXPIRES_AT]
                                           [--username USERNAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--scopes <scopes>

--expires-at <expires_at>

--username <username>

gitlab project-deploy-token delete

```
usage: gitlab project-deploy-token delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-deploy-token get

```
usage: gitlab project-deploy-token get [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-deploy-token list

```
usage: gitlab project-deploy-token list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--page PAGE]
                                         [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-deployment

```
usage: gitlab project-deployment [-h] {list,get,create,update} ...
```

-h, --help

show this help message and exit

gitlab project-deployment create

```
usage: gitlab project-deployment create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --sha SHA --ref REF --tag
                                         TAG --status STATUS --environment
                                         ENVIRONMENT
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--sha <sha>

--ref <ref>

--tag <tag>

--status <status>

--environment <environment>

gitlab project-deployment get

```
usage: gitlab project-deployment get [-h] [--sudo SUDO] --project-id
PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-deployment list

```
usage: gitlab project-deployment list [-h] [--sudo SUDO] --project-id
PROJECT_ID [--order-by ORDER_BY]
[--sort SORT]
[--updated-after UPDATED_AFTER]
[--updated-before UPDATED_BEFORE]
[--environment ENVIRONMENT]
[--status STATUS] [--page PAGE]
[--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--order-by <order_by>

--sort <sort>

--updated-after <updated_after>

--updated-before <updated_before>

--environment <environment>

--status <status>

--page <page>

--per-page <per_page>

--all

gitlab project-deployment update

```
usage: gitlab project-deployment update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-deployment-merge-request

```
usage: gitlab project-deployment-merge-request [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab project-deployment-merge-request list

```
usage: gitlab project-deployment-merge-request list [-h] [--sudo SUDO]
                                                    --deployment-id
                                                    DEPLOYMENT_ID --project-id
                                                    PROJECT_ID [--state STATE]
                                                    [--order-by ORDER_BY]
                                                    [--sort SORT]
                                                    [--milestone MILESTONE]
                                                    [--view VIEW]
                                                    [--labels LABELS]
                                                    [--with-labels-details WITH_LABELS_
↪DETAILS]
                                                    [--with-merge-status-recheck WITH_
↪MERGE_STATUS_RECHECK]
                                                    [--created-after CREATED_AFTER]
                                                    [--created-before CREATED_BEFORE]
                                                    [--updated-after UPDATED_AFTER]
                                                    [--updated-before UPDATED_BEFORE]
                                                    [--scope SCOPE]
                                                    [--author-id AUTHOR_ID]
                                                    [--author-username AUTHOR_USERNAME]
                                                    [--assignee-id ASSIGNEE_ID]
                                                    [--approver-ids APPROVER_IDS]
                                                    [--approved-by-ids APPROVED_BY_IDS]
                                                    [--reviewer-id REVIEWER_ID]
                                                    [--reviewer-username REVIEWER_
↪USERNAME]
                                                    [--my-reaction-emoji MY_REACTION_
↪EMOJI]
```

(continues on next page)

(continued from previous page)

```
[--source-branch SOURCE_BRANCH]
[--target-branch TARGET_BRANCH]
[--search SEARCH]
[--in IN] [--wip WIP]
[--not NOT]
[--environment ENVIRONMENT]
[--deployed-before DEPLOYED_BEFORE]
[--deployed-after DEPLOYED_AFTER]
[--page PAGE]
[--per-page PER_PAGE]
[--all]
```

```
-h, --help
    show this help message and exit

--sudo <sudo>

--deployment-id <deployment_id>

--project-id <project_id>

--state <state>

--order-by <order_by>

--sort <sort>

--milestone <milestone>

--view <view>

--labels <labels>

--with-labels-details <with_labels_details>

--with-merge-status-recheck <with_merge_status_recheck>

--created-after <created_after>

--created-before <created_before>

--updated-after <updated_after>

--updated-before <updated_before>

--scope <scope>

--author-id <author_id>

--author-username <author_username>

--assignee-id <assignee_id>

--approver-ids <approver_ids>

--approved-by-ids <approved_by_ids>

--reviewer-id <reviewer_id>
```

```

--reviewer-username <reviewer_username>
--my-reaction-emoji <my_reaction_emoji>
--source-branch <source_branch>
--target-branch <target_branch>
--search <search>
--in <in>
--wip <wip>
--not <not>
--environment <environment>
--deployed-before <deployed_before>
--deployed-after <deployed_after>
--page <page>
--per-page <per_page>
--all

```

gitlab project-environment

```

usage: gitlab project-environment [-h]
                                   {list,get,create,update,delete,stop} ...

```

-h, --help
show this help message and exit

gitlab project-environment create

```

usage: gitlab project-environment create [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --name NAME
                                           [--external-url EXTERNAL_URL]

```

-h, --help
show this help message and exit

```

--sudo <sudo>
--project-id <project_id>
--name <name>
--external-url <external_url>

```

gitlab project-environment delete

```
usage: gitlab project-environment delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-environment get

```
usage: gitlab project-environment get [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-environment list

```
usage: gitlab project-environment list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--name NAME]
                                         [--search SEARCH] [--states STATES]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--search <search>

--states <states>

--page <page>

--per-page <per_page>

--all

gitlab project-environment stop

```
usage: gitlab project-environment stop [-h] --project-id PROJECT_ID
                                     [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-environment update

```
usage: gitlab project-environment update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID [--name NAME]
                                         [--external-url EXTERNAL_URL]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--name <name>

--external-url <external_url>

gitlab project-event

```
usage: gitlab project-event [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab project-event list

```
usage: gitlab project-event list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 [--action ACTION] [--target-type TARGET_TYPE]
                                 [--before BEFORE] [--after AFTER]
                                 [--sort SORT] [--page PAGE]
                                 [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>
--project-id <project_id>
--action <action>
--target-type <target_type>
--before <before>
--after <after>
--sort <sort>
--page <page>
--per-page <per_page>
--all

gitlab project-export

```
usage: gitlab project-export [-h] {get,create,download} ...
```

-h, --help
show this help message and exit

gitlab project-export create

```
usage: gitlab project-export create [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                     [--description DESCRIPTION]
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--description <description>

gitlab project-export download

```
usage: gitlab project-export download [-h] --project-id PROJECT_ID  
                                       [--sudo SUDO]
```

-h, --help
show this help message and exit
--project-id <project_id>
--sudo <sudo>

gitlab project-export get

```
usage: gitlab project-export get [-h] [--sudo SUDO] --project-id PROJECT_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-file

```
usage: gitlab project-file [-h] {get,create,update,delete,raw,blame} ...
```

-h, --help
show this help message and exit

gitlab project-file blame

```
usage: gitlab project-file blame [-h] --project-id PROJECT_ID [--sudo SUDO]
                                --file-path FILE_PATH --ref REF
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--ref <ref>

gitlab project-file create

```
usage: gitlab project-file create [-h] --project-id PROJECT_ID [--sudo SUDO]
                                --file-path FILE_PATH --branch BRANCH
                                --content CONTENT --commit-message
                                COMMIT_MESSAGE [--encoding ENCODING]
                                [--author-email AUTHOR_EMAIL]
                                [--author-name AUTHOR_NAME]
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--branch <branch>
--content <content>
--commit-message <commit_message>
--encoding <encoding>
--author-email <author_email>
--author-name <author_name>

gitlab project-file delete

```
usage: gitlab project-file delete [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --file-path FILE_PATH --branch BRANCH
                                   --commit-message COMMIT_MESSAGE
```

-h, --help
show this help message and exit
--project-id <project_id>
--sudo <sudo>
--file-path <file_path>
--branch <branch>
--commit-message <commit_message>

gitlab project-file get

```
usage: gitlab project-file get [-h] --project-id PROJECT_ID [--sudo SUDO]
                                --file-path FILE_PATH --ref REF
```

-h, --help
show this help message and exit
--project-id <project_id>
--sudo <sudo>
--file-path <file_path>
--ref <ref>

gitlab project-file raw

```
usage: gitlab project-file raw [-h] --project-id PROJECT_ID [--sudo SUDO]
                               --file-path FILE_PATH --ref REF
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--ref <ref>

gitlab project-file update

```
usage: gitlab project-file update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --file-path FILE_PATH --branch BRANCH
                                   --content CONTENT --commit-message
                                   COMMIT_MESSAGE [--encoding ENCODING]
                                   [--author-email AUTHOR_EMAIL]
                                   [--author-name AUTHOR_NAME]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--file-path <file_path>

--branch <branch>

--content <content>

--commit-message <commit_message>

--encoding <encoding>

--author-email <author_email>

--author-name <author_name>

gitlab project-fork

```
usage: gitlab project-fork [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab project-fork create

```
usage: gitlab project-fork create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   [--namespace NAMESPACE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--namespace <namespace>

gitlab project-fork list

```
usage: gitlab project-fork list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--archived ARCHIVED]
                                [--visibility VISIBILITY]
                                [--order-by ORDER_BY] [--sort SORT]
                                [--search SEARCH] [--simple SIMPLE]
                                [--owned OWNED] [--membership MEMBERSHIP]
                                [--starred STARRED] [--statistics STATISTICS]
                                [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                [--with-issues-enabled WITH_ISSUES_ENABLED]
                                [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
↳ENABLED]
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--archived <archived>

--visibility <visibility>

--order-by <order_by>

--sort <sort>

--search <search>

```

--simple <simple>
--owned <owned>
--membership <membership>
--starred <starred>
--statistics <statistics>
--with-custom-attributes <with_custom_attributes>
--with-issues-enabled <with_issues_enabled>
--with-merge-requests-enabled <with_merge_requests_enabled>
--page <page>
--per-page <per_page>
--all

```

gitlab project-hook

```
usage: gitlab project-hook [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-hook create

```

usage: gitlab project-hook create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --url URL [--push-events PUSH_EVENTS]
                                [--issues-events ISSUES_EVENTS]
                                [--confidential-issues-events CONFIDENTIAL_ISSUES_
↵EVENTS]
                                [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                [--tag-push-events TAG_PUSH_EVENTS]
                                [--note-events NOTE_EVENTS]
                                [--job-events JOB_EVENTS]
                                [--pipeline-events PIPELINE_EVENTS]
                                [--wiki-page-events WIKI_PAGE_EVENTS]
                                [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                [--token TOKEN]

```

-h, --help
show this help message and exit

```

--sudo <sudo>
--project-id <project_id>
--url <url>

```

```
--push-events <push_events>
--issues-events <issues_events>
--confidential-issues-events <confidential_issues_events>
--merge-requests-events <merge_requests_events>
--tag-push-events <tag_push_events>
--note-events <note_events>
--job-events <job_events>
--pipeline-events <pipeline_events>
--wiki-page-events <wiki_page_events>
--enable-ssl-verification <enable_ssl_verification>
--token <token>
```

gitlab project-hook delete

```
usage: gitlab project-hook delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-hook get

```
usage: gitlab project-hook get [-h] [--sudo SUDO] --project-id PROJECT_ID --id
                                ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-hook list

```
usage: gitlab project-hook list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-hook update

```
usage: gitlab project-hook update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --id ID --url URL
                                [--push-events PUSH_EVENTS]
                                [--issues-events ISSUES_EVENTS]
                                [--confidential-issues-events CONFIDENTIAL_ISSUES_
↩EVENTS]
                                [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                [--tag-push-events TAG_PUSH_EVENTS]
                                [--note-events NOTE_EVENTS]
                                [--job-events JOB_EVENTS]
                                [--pipeline-events PIPELINE_EVENTS]
                                [--wiki-events WIKI_EVENTS]
                                [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                [--token TOKEN]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--url <url>

--push-events <push_events>

--issues-events <issues_events>

--confidential-issues-events <confidential_issues_events>

--merge-requests-events <merge_requests_events>

--tag-push-events <tag_push_events>

```
--note-events <note_events>
--job-events <job_events>
--pipeline-events <pipeline_events>
--wiki-events <wiki_events>
--enable-ssl-verification <enable_ssl_verification>
--token <token>
```

gitlab project-import

```
usage: gitlab project-import [-h] {get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-import get

```
usage: gitlab project-import get [-h] [--sudo SUDO] --project-id PROJECT_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
```

gitlab project-issue

```
usage: gitlab project-issue [-h]
                        {list,get,create,update,delete,user-agent-detail,subscribe,
↳ unsubscribe,todo,time-stats,time-estimate,reset-time-estimate,add-spent-time,reset-
↳ spent-time,participants,move,related-merge-requests,closed-by}
                        ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-issue add-spent-time

```
usage: gitlab project-issue add-spent-time [-h] --project-id PROJECT_ID
                                           [--sudo SUDO] --iid IID --duration
                                           DURATION
```

```
-h, --help
    show this help message and exit
```

--project-id <project_id>
--sudo <sudo>
--iid <iid>
--duration <duration>

gitlab project-issue closed-by

```
usage: gitlab project-issue closed-by [-h] --project-id PROJECT_ID
                                     [--sudo SUDO] --iid IID
```

-h, --help
 show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>

gitlab project-issue create

```
usage: gitlab project-issue create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --title TITLE [--description DESCRIPTION]
                                   [--confidential CONFIDENTIAL]
                                   [--assignee-ids ASSIGNEE_IDS]
                                   [--assignee-id ASSIGNEE_ID]
                                   [--milestone-id MILESTONE_ID]
                                   [--labels LABELS] [--created-at CREATED_AT]
                                   [--due-date DUE_DATE]
                                   [--merge-request-to-resolve-discussions-of MERGE_
↪REQUEST_TO_RESOLVE_DISCUSSIONS_OF]
                                   [--discussion-to-resolve DISCUSSION_TO_RESOLVE]
```

-h, --help
 show this help message and exit
--sudo <sudo>
--project-id <project_id>
--title <title>
--description <description>
--confidential <confidential>
--assignee-ids <assignee_ids>
--assignee-id <assignee_id>
--milestone-id <milestone_id>

--labels <labels>
--created-at <created_at>
--due-date <due_date>
--merge-request-to-resolve-discussions-of <merge_request_to_resolve_discussions_of>
--discussion-to-resolve <discussion_to_resolve>

gitlab project-issue delete

```
usage: gitlab project-issue delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --iid IID
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--iid <iid>

gitlab project-issue get

```
usage: gitlab project-issue get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --iid IID
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--iid <iid>

gitlab project-issue list

```
usage: gitlab project-issue list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--iids IIDS] [--state STATE]
                                [--labels LABELS] [--milestone MILESTONE]
                                [--scope SCOPE] [--author-id AUTHOR_ID]
                                [--assignee-id ASSIGNEE_ID]
                                [--my-reaction-emoji MY_REACTION_EMOJI]
                                [--order-by ORDER_BY] [--sort SORT]
                                [--search SEARCH]
                                [--created-after CREATED_AFTER]
                                [--created-before CREATED_BEFORE]
                                [--updated-after UPDATED_AFTER]
                                [--updated-before UPDATED_BEFORE]
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

```

-h, --help
    show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iids <iids>

--state <state>

--labels <labels>

--milestone <milestone>

--scope <scope>

--author-id <author_id>

--assignee-id <assignee_id>

--my-reaction-emoji <my_reaction_emoji>

--order-by <order_by>

--sort <sort>

--search <search>

--created-after <created_after>

--created-before <created_before>

--updated-after <updated_after>

--updated-before <updated_before>

--page <page>

--per-page <per_page>

--all

```

gitlab project-issue move

```

usage: gitlab project-issue move [-h] --project-id PROJECT_ID [--sudo SUDO]
                                --iid IID --to-project-id TO_PROJECT_ID

```

```

-h, --help
    show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--to-project-id <to_project_id>

```

gitlab project-issue participants

```
usage: gitlab project-issue participants [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue related-merge-requests

```
usage: gitlab project-issue related-merge-requests [-h] --project-id
                                                    PROJECT_ID [--sudo SUDO]
                                                    --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue reset-spent-time

```
usage: gitlab project-issue reset-spent-time [-h] --project-id PROJECT_ID
                                              [--sudo SUDO] --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue reset-time-estimate

```
usage: gitlab project-issue reset-time-estimate [-h] --project-id PROJECT_ID
                                                [--sudo SUDO] --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue subscribe

```
usage: gitlab project-issue subscribe [-h] --project-id PROJECT_ID
                                     [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue time-estimate

```
usage: gitlab project-issue time-estimate [-h] --project-id PROJECT_ID
                                           [--sudo SUDO] --iid IID --duration
                                           DURATION
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--duration <duration>

gitlab project-issue time-stats

```
usage: gitlab project-issue time-stats [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue todo

```
usage: gitlab project-issue todo [-h] --project-id PROJECT_ID [--sudo SUDO]
                                --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue unsubscribe

```
usage: gitlab project-issue unsubscribe [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue update

```
usage: gitlab project-issue update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --iid IID [--title TITLE]
                                   [--description DESCRIPTION]
                                   [--confidential CONFIDENTIAL]
                                   [--assignee-ids ASSIGNEE_IDS]
                                   [--assignee-id ASSIGNEE_ID]
                                   [--milestone-id MILESTONE_ID]
                                   [--labels LABELS]
                                   [--state-event STATE_EVENT]
                                   [--updated-at UPDATED_AT]
                                   [--due-date DUE_DATE]
                                   [--discussion-locked DISCUSSION_LOCKED]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iid <iid>

--title <title>

```

--description <description>
--confidential <confidential>
--assignee-ids <assignee_ids>
--assignee-id <assignee_id>
--milestone-id <milestone_id>
--labels <labels>
--state-event <state_event>
--updated-at <updated_at>
--due-date <due_date>
--discussion-locked <discussion_locked>

```

gitlab project-issue user-agent-detail

```
usage: gitlab project-issue user-agent-detail [-h] --project-id PROJECT_ID
                                             [--sudo SUDO] --iid IID

```

```

-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>

```

gitlab project-issue-award-emoji

```
usage: gitlab project-issue-award-emoji [-h] {list,get,create,delete} ...

```

```

-h, --help
    show this help message and exit

```

gitlab project-issue-award-emoji create

```
usage: gitlab project-issue-award-emoji create [-h] [--sudo SUDO] --project-id
                                                PROJECT_ID --issue-iid
                                                ISSUE_IID --name NAME

```

```

-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>

```

--issue-iid <issue_iid>

--name <name>

gitlab project-issue-award-emoji delete

```
usage: gitlab project-issue-award-emoji delete [-h] [--sudo SUDO] --project-id
                                                PROJECT_ID --issue-iid
                                                ISSUE_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-award-emoji get

```
usage: gitlab project-issue-award-emoji get [-h] [--sudo SUDO] --project-id
                                                PROJECT_ID --issue-iid ISSUE_IID
                                                --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-award-emoji list

```
usage: gitlab project-issue-award-emoji list [-h] [--sudo SUDO] --project-id
                                                PROJECT_ID --issue-iid ISSUE_IID
                                                [--page PAGE]
                                                [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--issue-iid <issue_iid>
--page <page>
--per-page <per_page>
--all
```

gitlab project-issue-discussion

```
usage: gitlab project-issue-discussion [-h] {list,get,create} ...
```

-h, --help
show this help message and exit

gitlab project-issue-discussion create

```
usage: gitlab project-issue-discussion create [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --issue-iid ISSUE_IID
                                             --body BODY
                                             [--created-at CREATED_AT]
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--body <body>
--created-at <created_at>
```

gitlab project-issue-discussion get

```
usage: gitlab project-issue-discussion get [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --issue-iid ISSUE_IID
                                           --id ID
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--id <id>
```

gitlab project-issue-discussion list

```
usage: gitlab project-issue-discussion list [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --issue-iid ISSUE_IID
                                           [--page PAGE]
                                           [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--all

gitlab project-issue-discussion-note

```
usage: gitlab project-issue-discussion-note [-h]
                                           {get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-issue-discussion-note create

```
usage: gitlab project-issue-discussion-note create [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --discussion-id
                                                    DISCUSSION_ID --body BODY
                                                    [--created-at CREATED_AT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--discussion-id <discussion_id>

--body <body>

--created-at <created_at>

gitlab project-issue-discussion-note delete

```
usage: gitlab project-issue-discussion-note delete [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --discussion-id
DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--discussion-id <discussion_id>

--id <id>

gitlab project-issue-discussion-note get

```
usage: gitlab project-issue-discussion-note get [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --discussion-id DISCUSSION_ID
--id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--discussion-id <discussion_id>

--id <id>

gitlab project-issue-discussion-note update

```
usage: gitlab project-issue-discussion-note update [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --discussion-id
DISCUSSION_ID --id ID
                                                    --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--discussion-id <discussion_id>
--id <id>
--body <body>

gitlab project-issue-link

```
usage: gitlab project-issue-link [-h] {list,create,delete} ...
```

-h, --help
show this help message and exit

gitlab project-issue-link create

```
usage: gitlab project-issue-link create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --issue-iid ISSUE_IID  
--target-project-id TARGET_PROJECT_ID  
--target-issue-iid TARGET_ISSUE_IID
```

-h, --help
show this help message and exit

--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--target-project-id <target_project_id>
--target-issue-iid <target_issue_iid>

gitlab project-issue-link delete

```
usage: gitlab project-issue-link delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --issue-iid ISSUE_IID  
--issue-link-id ISSUE_LINK_ID
```

-h, --help
show this help message and exit

--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--issue-link-id <issue_link_id>

gitlab project-issue-link list

```
usage: gitlab project-issue-link list [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --issue-iid ISSUE_IID
                                     [--page PAGE] [--per-page PER_PAGE]
                                     [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--all

gitlab project-issue-note

```
usage: gitlab project-issue-note [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-issue-note create

```
usage: gitlab project-issue-note create [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --issue-iid ISSUE_IID
                                     --body BODY [--created-at CREATED_AT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--body <body>

--created-at <created_at>

gitlab project-issue-note delete

```
usage: gitlab project-issue-note delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --issue-iid ISSUE_IID --id
                                         ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-note get

```
usage: gitlab project-issue-note get [-h] [--sudo SUDO] --project-id
                                       PROJECT_ID --issue-iid ISSUE_IID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-note list

```
usage: gitlab project-issue-note list [-h] [--sudo SUDO] --project-id
                                       PROJECT_ID --issue-iid ISSUE_IID
                                       [--page PAGE] [--per-page PER_PAGE]
                                       [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--all

gitlab project-issue-note update

```
usage: gitlab project-issue-note update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --issue-iid ISSUE_IID --id
                                         ID --body BODY
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

--body <body>

gitlab project-issue-note-award-emoji

```
usage: gitlab project-issue-note-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab project-issue-note-award-emoji create

```
usage: gitlab project-issue-note-award-emoji create [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --note-id NOTE_ID --name
                                                    NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--note-id <note_id>

--name <name>

gitlab project-issue-note-award-emoji delete

```
usage: gitlab project-issue-note-award-emoji delete [-h] [--sudo SUDO]
                                         --project-id PROJECT_ID
                                         --issue-iid ISSUE_IID
                                         --note-id NOTE_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--note-id <note_id>

--id <id>

gitlab project-issue-note-award-emoji get

```
usage: gitlab project-issue-note-award-emoji get [-h] [--sudo SUDO]
                                         --project-id PROJECT_ID
                                         --issue-iid ISSUE_IID
                                         --note-id NOTE_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--note-id <note_id>

--id <id>

gitlab project-issue-note-award-emoji list

```
usage: gitlab project-issue-note-award-emoji list [-h] [--sudo SUDO]
                                         --project-id PROJECT_ID
                                         --issue-iid ISSUE_IID
                                         --note-id NOTE_ID
                                         [--page PAGE]
                                         [--per-page PER_PAGE]
                                         [--all]
```

-h, --help
show this help message and exit

```

--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--note-id <note_id>
--page <page>
--per-page <per_page>
--all

```

gitlab project-issue-resource-label-event

```
usage: gitlab project-issue-resource-label-event [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab project-issue-resource-label-event get

```
usage: gitlab project-issue-resource-label-event get [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --id ID
```

-h, --help
show this help message and exit

```

--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--id <id>

```

gitlab project-issue-resource-label-event list

```
usage: gitlab project-issue-resource-label-event list [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--all]
```

-h, --help
show this help message and exit

```
--sudo <sudo>
```

--project-id <project_id>
--issue-iid <issue_iid>
--page <page>
--per-page <per_page>
--all

gitlab project-issue-resource-milestone-event

```
usage: gitlab project-issue-resource-milestone-event [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab project-issue-resource-milestone-event get

```
usage: gitlab project-issue-resource-milestone-event get [-h] [--sudo SUDO]
                                                    --project-id
                                                    PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--id <id>

gitlab project-issue-resource-milestone-event list

```
usage: gitlab project-issue-resource-milestone-event list [-h] [--sudo SUDO]
                                                    --project-id
                                                    PROJECT_ID
                                                    --issue-iid
                                                    ISSUE_IID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--all]
```

-h, --help
show this help message and exit
--sudo <sudo>

```

--project-id <project_id>
--issue-iid <issue_iid>
--page <page>
--per-page <per_page>
--all

```

gitlab project-issue-resource-state-event

```
usage: gitlab project-issue-resource-state-event [-h] {list,get} ...
```

```

-h, --help
    show this help message and exit

```

gitlab project-issue-resource-state-event get

```
usage: gitlab project-issue-resource-state-event get [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --id ID

```

```

-h, --help
    show this help message and exit

```

```

--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--id <id>

```

gitlab project-issue-resource-state-event list

```
usage: gitlab project-issue-resource-state-event list [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--all]

```

```

-h, --help
    show this help message and exit

```

```

--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>

```

--page <page>
--per-page <per_page>
--all

gitlab project-issues-statistics

```
usage: gitlab project-issues-statistics [-h] {get} ...
```

-h, --help
show this help message and exit

gitlab project-issues-statistics get

```
usage: gitlab project-issues-statistics get [-h] [--sudo SUDO] --project-id  
PROJECT_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-job

```
usage: gitlab project-job [-h]  
                           {list,get,cancel,retry,play,erase,keep-artifacts,delete-  
↪artifacts,artifacts,artifact,trace}  
                           ...
```

-h, --help
show this help message and exit

gitlab project-job artifact

```
usage: gitlab project-job artifact [-h] --project-id PROJECT_ID [--sudo SUDO]  
--id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job artifacts

```
usage: gitlab project-job artifacts [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job cancel

```
usage: gitlab project-job cancel [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job delete-artifacts

```
usage: gitlab project-job delete-artifacts [-h] --project-id PROJECT_ID
                                           [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job erase

```
usage: gitlab project-job erase [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job get

```
usage: gitlab project-job get [-h] [--sudo SUDO] --project-id PROJECT_ID --id
                                ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-job keep-artifacts

```
usage: gitlab project-job keep-artifacts [-h] --project-id PROJECT_ID
                                           [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job list

```
usage: gitlab project-job list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-job play

```
usage: gitlab project-job play [-h] --project-id PROJECT_ID [--sudo SUDO] --id
                                ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job retry

```
usage: gitlab project-job retry [-h] --project-id PROJECT_ID [--sudo SUDO]
                                --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job trace

```
usage: gitlab project-job trace [-h] --project-id PROJECT_ID [--sudo SUDO]
                                --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-key

```
usage: gitlab project-key [-h] {list,get,create,update,delete,enable} ...
```

-h, --help
show this help message and exit

gitlab project-key create

```
usage: gitlab project-key create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --title TITLE --key KEY [--can-push CAN_PUSH]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--title <title>

--key <key>

--can-push <can_push>

gitlab project-key delete

```
usage: gitlab project-key delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-key enable

```
usage: gitlab project-key enable [-h] --project-id PROJECT_ID [--sudo SUDO]
                                --id ID --key-id KEY_ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--key-id <key_id>

gitlab project-key get

```
usage: gitlab project-key get [-h] [--sudo SUDO] --project-id PROJECT_ID --id
                               ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-key list

```
usage: gitlab project-key list [-h] [--sudo SUDO] --project-id PROJECT_ID
                               [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-key update

```
usage: gitlab project-key update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --id ID [--title TITLE] [--can-push CAN_PUSH]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--title <title>

--can-push <can_push>

gitlab project-label

```
usage: gitlab project-label [-h]
                             {list,get,create,update,delete,subscribe,unsubscribe}
                             ...
```

-h, --help

show this help message and exit

gitlab project-label create

```
usage: gitlab project-label create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --name NAME --color COLOR
                                   [--description DESCRIPTION]
                                   [--priority PRIORITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--color <color>

--description <description>

--priority <priority>

gitlab project-label delete

```
usage: gitlab project-label delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-label get

```
usage: gitlab project-label get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-label list

```
usage: gitlab project-label list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-label subscribe

```
usage: gitlab project-label subscribe [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --name NAME
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--name <name>

gitlab project-label unsubscribe

```
usage: gitlab project-label unsubscribe [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --name NAME
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--name <name>

gitlab project-label update

```
usage: gitlab project-label update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                     --name NAME [--new-name NEW_NAME]
                                     [--color COLOR] [--description DESCRIPTION]
                                     [--priority PRIORITY]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--new-name <new_name>

--color <color>

--description <description>

--priority <priority>

gitlab project-member

```
usage: gitlab project-member [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-member create

```
usage: gitlab project-member create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                     --access-level ACCESS_LEVEL --user-id
                                     USER_ID [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--access-level <access_level>

--user-id <user_id>

--expires-at <expires_at>

gitlab project-member delete

```
usage: gitlab project-member delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                     --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-member get

```
usage: gitlab project-member get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-member list

```
usage: gitlab project-member list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-member update

```
usage: gitlab project-member update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                     --id ID --access-level ACCESS_LEVEL
                                     [--expires-at EXPIRES_AT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--access-level <access_level>

--expires-at <expires_at>

gitlab project-member-all

```
usage: gitlab project-member-all [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab project-member-all get

```
usage: gitlab project-member-all get [-h] [--sudo SUDO] --project-id
                                       PROJECT_ID --id ID
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-member-all list

```
usage: gitlab project-member-all list [-h] [--sudo SUDO] --project-id
PROJECT_ID [--page PAGE]
[--per-page PER_PAGE] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--page <page>
--per-page <per_page>
--all
```

gitlab project-merge-request

```
usage: gitlab project-merge-request [-h]
                                     {list,get,create,update,delete,subscribe,unsubscribe,
→ todo,time-stats,time-estimate,reset-time-estimate,add-spent-time,reset-spent-time,
→ participants,cancel-merge-when-pipeline-succeeds,closes-issues,commits,changes,approve,
→ unapprove,rebase,merge-ref,merge}
                                     ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-merge-request add-spent-time

```
usage: gitlab project-merge-request add-spent-time [-h] --project-id
PROJECT_ID [--sudo SUDO]
--iid IID --duration
DURATION
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
--duration <duration>
```

gitlab project-merge-request approve

```
usage: gitlab project-merge-request approve [-h] --project-id PROJECT_ID
                                           [--sudo SUDO] --iid IID
                                           [--sha SHA]
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--sha <sha>

gitlab project-merge-request cancel-merge-when-pipeline-succeeds

```
usage: gitlab project-merge-request cancel-merge-when-pipeline-succeeds
       [-h] --project-id PROJECT_ID [--sudo SUDO] --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request changes

```
usage: gitlab project-merge-request changes [-h] --project-id PROJECT_ID
                                           [--sudo SUDO] --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request closes-issues

```
usage: gitlab project-merge-request closes-issues [-h] --project-id PROJECT_ID
                                                [--sudo SUDO] --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request commits

```
usage: gitlab project-merge-request commits [-h] --project-id PROJECT_ID
                                           [--sudo SUDO] --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request create

```
usage: gitlab project-merge-request create [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --source-branch
                                           SOURCE_BRANCH --target-branch
                                           TARGET_BRANCH --title TITLE
                                           [--assignee-id ASSIGNEE_ID]
                                           [--description DESCRIPTION]
                                           [--target-project-id TARGET_PROJECT_ID]
                                           [--labels LABELS]
                                           [--milestone-id MILESTONE_ID]
                                           [--remove-source-branch REMOVE_SOURCE_BRANCH]
                                           [--allow-maintainer-to-push ALLOW_MAINTAINER_
↪ TO_PUSH]
                                           [--squash SQUASH]
                                           [--reviewer-ids REVIEWER_IDS]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--source-branch <source_branch>

```
--target-branch <target_branch>
--title <title>
--assignee-id <assignee_id>
--description <description>
--target-project-id <target_project_id>
--labels <labels>
--milestone-id <milestone_id>
--remove-source-branch <remove_source_branch>
--allow-maintainer-to-push <allow_maintainer_to_push>
--squash <squash>
--reviewer-ids <reviewer_ids>
```

gitlab project-merge-request delete

```
usage: gitlab project-merge-request delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --iid IID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--iid <iid>
```

gitlab project-merge-request get

```
usage: gitlab project-merge-request get [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --iid IID
                                           [--render-html RENDER_HTML]
                                           [--include-diverged-commits-count INCLUDE_
↪DIVERGED_COMMITS_COUNT]
                                           [--include-rebase-in-progress INCLUDE_REBASE_IN_
↪PROGRESS]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--iid <iid>
```

--render-html <render_html>

--include-diverged-commits-count <include_diverged_commits_count>

--include-rebase-in-progress <include_rebase_in_progress>

gitlab project-merge-request list

```
usage: gitlab project-merge-request list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--state STATE]
                                         [--order-by ORDER_BY] [--sort SORT]
                                         [--milestone MILESTONE] [--view VIEW]
                                         [--labels LABELS]
                                         [--created-after CREATED_AFTER]
                                         [--created-before CREATED_BEFORE]
                                         [--updated-after UPDATED_AFTER]
                                         [--updated-before UPDATED_BEFORE]
                                         [--scope SCOPE] [--iids IIDS]
                                         [--author-id AUTHOR_ID]
                                         [--assignee-id ASSIGNEE_ID]
                                         [--approver-ids APPROVER_IDS]
                                         [--approved-by-ids APPROVED_BY_IDS]
                                         [--my-reaction-emoji MY_REACTION_EMOJI]
                                         [--source-branch SOURCE_BRANCH]
                                         [--target-branch TARGET_BRANCH]
                                         [--search SEARCH] [--wip WIP]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--state <state>

--order-by <order_by>

--sort <sort>

--milestone <milestone>

--view <view>

--labels <labels>

--created-after <created_after>

--created-before <created_before>

--updated-after <updated_after>

--updated-before <updated_before>

```
--scope <scope>
--iids <iids>
--author-id <author_id>
--assignee-id <assignee_id>
--approver-ids <approver_ids>
--approved-by-ids <approved_by_ids>
--my-reaction-emoji <my_reaction_emoji>
--source-branch <source_branch>
--target-branch <target_branch>
--search <search>
--wip <wip>
--page <page>
--per-page <per_page>
--all
```

gitlab project-merge-request merge

```
usage: gitlab project-merge-request merge [-h] --project-id PROJECT_ID
                                           [--sudo SUDO] --iid IID
                                           [--merge-commit-message MERGE_COMMIT_MESSAGE]
                                           [--should-remove-source-branch SHOULD_REMOVE_
↪SOURCE_BRANCH]
                                           [--merge-when-pipeline-succeeds MERGE_WHEN_
↪PIPELINE_SUCCEEDS]
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
--merge-commit-message <merge_commit_message>
--should-remove-source-branch <should_remove_source_branch>
--merge-when-pipeline-succeeds <merge_when_pipeline_succeeds>
```

gitlab project-merge-request merge-ref

```
usage: gitlab project-merge-request merge-ref [-h] --project-id PROJECT_ID
                                             [--sudo SUDO] --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request participants

```
usage: gitlab project-merge-request participants [-h] --project-id PROJECT_ID
                                                [--sudo SUDO] --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request rebase

```
usage: gitlab project-merge-request rebase [-h] --project-id PROJECT_ID
                                           [--sudo SUDO] --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request reset-spent-time

```
usage: gitlab project-merge-request reset-spent-time [-h] --project-id
                                                    PROJECT_ID [--sudo SUDO]
                                                    --iid IID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request reset-time-estimate

```
usage: gitlab project-merge-request reset-time-estimate [-h] --project-id
                                                    PROJECT_ID
                                                    [--sudo SUDO] --iid
                                                    IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request subscribe

```
usage: gitlab project-merge-request subscribe [-h] --project-id PROJECT_ID
                                                    [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request time-estimate

```
usage: gitlab project-merge-request time-estimate [-h] --project-id PROJECT_ID
                                                    [--sudo SUDO] --iid IID
                                                    --duration DURATION
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--duration <duration>

gitlab project-merge-request time-stats

```
usage: gitlab project-merge-request time-stats [-h] --project-id PROJECT_ID
                                              [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request todo

```
usage: gitlab project-merge-request todo [-h] --project-id PROJECT_ID
                                          [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request unapprove

```
usage: gitlab project-merge-request unapprove [-h] --project-id PROJECT_ID
                                              [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request unsubscribe

```
usage: gitlab project-merge-request unsubscribe [-h] --project-id PROJECT_ID
                                              [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request update

```
usage: gitlab project-merge-request update [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --iid IID
                                           [--target-branch TARGET_BRANCH]
                                           [--assignee-id ASSIGNEE_ID]
                                           [--title TITLE]
                                           [--description DESCRIPTION]
                                           [--state-event STATE_EVENT]
                                           [--labels LABELS]
                                           [--milestone-id MILESTONE_ID]
                                           [--remove-source-branch REMOVE_SOURCE_BRANCH]
                                           [--discussion-locked DISCUSSION_LOCKED]
                                           [--allow-maintainer-to-push ALLOW_MAINTAINER_
↪TO_PUSH]
                                           [--squash SQUASH]
                                           [--reviewer-ids REVIEWER_IDS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iid <iid>

--target-branch <target_branch>

--assignee-id <assignee_id>

--title <title>

--description <description>

--state-event <state_event>

--labels <labels>

--milestone-id <milestone_id>

--remove-source-branch <remove_source_branch>

--discussion-locked <discussion_locked>

--allow-maintainer-to-push <allow_maintainer_to_push>

--squash <squash>

--reviewer-ids <reviewer_ids>

gitlab project-merge-request-approval

```
usage: gitlab project-merge-request-approval [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-approval get

```
usage: gitlab project-merge-request-approval get [-h] [--sudo SUDO]
                                         --project-id PROJECT_ID
                                         --mr-iid MR_IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

gitlab project-merge-request-approval update

```
usage: gitlab project-merge-request-approval update [-h] [--sudo SUDO]
                                         --project-id PROJECT_ID
                                         --mr-iid MR_IID
                                         --approvals-required
                                         APPROVALS_REQUIRED
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--approvals-required <approvals_required>

gitlab project-merge-request-approval-rule

```
usage: gitlab project-merge-request-approval-rule [-h]
                                         {list,create,update,delete}
                                         ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-approval-rule create

```
usage: gitlab project-merge-request-approval-rule create [-h] [--sudo SUDO]
                                                         --project-id
                                                         PROJECT_ID --mr-iid
                                                         MR_IID --id ID
                                                         --merge-request-iid
                                                         MERGE_REQUEST_IID
                                                         --name NAME
                                                         --approvals-required
                                                         APPROVALS_REQUIRED
                                                         [--approval-project-rule-id_
→APPROVAL_PROJECT_RULE_ID]
                                                         [--user-ids USER_IDS]
                                                         [--group-ids GROUP_IDS]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

--merge-request-iid <merge_request_iid>

--name <name>

--approvals-required <approvals_required>

--approval-project-rule-id <approval_project_rule_id>

--user-ids <user_ids>

--group-ids <group_ids>

gitlab project-merge-request-approval-rule delete

```
usage: gitlab project-merge-request-approval-rule delete [-h] [--sudo SUDO]
                                                         --project-id
                                                         PROJECT_ID --mr-iid
                                                         MR_IID
                                                         --approval-rule-id
                                                         APPROVAL_RULE_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--mr-iid <mr_iid>
--approval-rule-id <approval_rule_id>
```

gitlab project-merge-request-approval-rule list

```
usage: gitlab project-merge-request-approval-rule list [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID
                                                    [--name NAME]
                                                    [--rule-type RULE_TYPE]
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--name <name>
--rule-type <rule_type>
--page <page>
--per-page <per_page>
--all
```

gitlab project-merge-request-approval-rule update

```
usage: gitlab project-merge-request-approval-rule update [-h] [--sudo SUDO]
                                                    --project-id
PROJECT_ID --mr-iid
MR_IID
--approval-rule-id
APPROVAL_RULE_ID --id
ID
--merge-request-iid
MERGE_REQUEST_IID
--name NAME
--approvals-required
APPROVALS_REQUIRED
[--user-ids USER_IDS]
[--group-ids GROUP_IDS]
```

```
-h, --help
    show this help message and exit
```

```
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--approval-rule-id <approval_rule_id>
--id <id>
--merge-request-iid <merge_request_iid>
--name <name>
--approvals-required <approvals_required>
--user-ids <user_ids>
--group-ids <group_ids>
```

gitlab project-merge-request-approval-state

```
usage: gitlab project-merge-request-approval-state [-h] {get} ...
```

-h, --help
show this help message and exit

gitlab project-merge-request-approval-state get

```
usage: gitlab project-merge-request-approval-state get [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID --id ID
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--id <id>
```

gitlab project-merge-request-award-emoji

```
usage: gitlab project-merge-request-award-emoji [-h]
                                                    {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab project-merge-request-award-emoji create

```
usage: gitlab project-merge-request-award-emoji create [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID --name
                                                    NAME
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id** <project_id>**--mr-iid** <mr_iid>**--name** <name>

gitlab project-merge-request-award-emoji delete

```
usage: gitlab project-merge-request-award-emoji delete [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id** <project_id>**--mr-iid** <mr_iid>**--id** <id>

gitlab project-merge-request-award-emoji get

```
usage: gitlab project-merge-request-award-emoji get [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id** <project_id>**--mr-iid** <mr_iid>**--id** <id>

gitlab project-merge-request-award-emoji list

```
usage: gitlab project-merge-request-award-emoji list [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--all

gitlab project-merge-request-diff

```
usage: gitlab project-merge-request-diff [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab project-merge-request-diff get

```
usage: gitlab project-merge-request-diff get [-h] [--sudo SUDO] --project-id
PROJECT_ID --mr-iid MR_IID --id
ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-diff list

```
usage: gitlab project-merge-request-diff list [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --mr-iid MR_IID
                                           [--page PAGE]
                                           [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--all

gitlab project-merge-request-discussion

```
usage: gitlab project-merge-request-discussion [-h]
                                                {list,get,create,update} ...
```

-h, --help
show this help message and exit

gitlab project-merge-request-discussion create

```
usage: gitlab project-merge-request-discussion create [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --body
                                                       BODY
                                                       [--created-at CREATED_AT]
                                                       [--position POSITION]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--body <body>

--created-at <created_at>

--position <position>

gitlab project-merge-request-discussion get

```
usage: gitlab project-merge-request-discussion get [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --mr-iid MR_IID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-discussion list

```
usage: gitlab project-merge-request-discussion list [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --mr-iid MR_IID
                                                [--page PAGE]
                                                [--per-page PER_PAGE]
                                                [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--all

gitlab project-merge-request-discussion update

```
usage: gitlab project-merge-request-discussion update [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --mr-iid MR_IID --id ID
                                                --resolved RESOLVED
```

-h, --help
show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--mr-iid <mr_iid>
--id <id>
--resolved <resolved>
```

gitlab project-merge-request-discussion-note

```
usage: gitlab project-merge-request-discussion-note [-h]
                                                    {get,create,update,delete}
                                                    ...
```

-h, --help
show this help message and exit

gitlab project-merge-request-discussion-note create

```
usage: gitlab project-merge-request-discussion-note create [-h] [--sudo SUDO]
                                                           --project-id
                                                           PROJECT_ID --mr-iid
                                                           MR_IID
                                                           --discussion-id
                                                           DISCUSSION_ID
                                                           --body BODY
                                                           [--created-at CREATED_AT]
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--discussion-id <discussion_id>
--body <body>
--created-at <created_at>
```

gitlab project-merge-request-discussion-note delete

```
usage: gitlab project-merge-request-discussion-note delete [-h] [--sudo SUDO]
                                                           --project-id
                                                           PROJECT_ID --mr-iid
                                                           MR_IID
                                                           --discussion-id
                                                           DISCUSSION_ID --id
                                                           ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--discussion-id <discussion_id>

--id <id>

gitlab project-merge-request-discussion-note get

```
usage: gitlab project-merge-request-discussion-note get [-h] [--sudo SUDO]
                                                    --project-id
                                                    PROJECT_ID --mr-iid
                                                    MR_IID --discussion-id
                                                    DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--discussion-id <discussion_id>

--id <id>

gitlab project-merge-request-discussion-note update

```
usage: gitlab project-merge-request-discussion-note update [-h] [--sudo SUDO]
                                                    --project-id
                                                    PROJECT_ID --mr-iid
                                                    MR_IID
                                                    --discussion-id
                                                    DISCUSSION_ID --id
                                                    ID --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--discussion-id <discussion_id>

--id <id>
--body <body>

gitlab project-merge-request-note

```
usage: gitlab project-merge-request-note [-h]
                                         {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-merge-request-note create

```
usage: gitlab project-merge-request-note create [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --mr-iid MR_IID --body BODY
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--body <body>

gitlab project-merge-request-note delete

```
usage: gitlab project-merge-request-note delete [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --mr-iid MR_IID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-note get

```
usage: gitlab project-merge-request-note get [-h] [--sudo SUDO] --project-id
PROJECT_ID --mr-iid MR_IID --id
ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-note list

```
usage: gitlab project-merge-request-note list [-h] [--sudo SUDO] --project-id
PROJECT_ID --mr-iid MR_IID
[--page PAGE]
[--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--all

gitlab project-merge-request-note update

```
usage: gitlab project-merge-request-note update [-h] [--sudo SUDO]
--project-id PROJECT_ID
--mr-iid MR_IID --id ID --body
BODY
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>
--body <body>

gitlab project-merge-request-note-award-emoji

```
usage: gitlab project-merge-request-note-award-emoji [-h]
                                                    {list,get,create,delete}
                                                    ...
```

-h, --help
show this help message and exit

gitlab project-merge-request-note-award-emoji create

```
usage: gitlab project-merge-request-note-award-emoji create
       [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --note-id
       NOTE_ID --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--note-id <note_id>

--name <name>

gitlab project-merge-request-note-award-emoji delete

```
usage: gitlab project-merge-request-note-award-emoji delete
       [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --note-id
       NOTE_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--note-id <note_id>

--id <id>

gitlab project-merge-request-note-award-emoji get

```
usage: gitlab project-merge-request-note-award-emoji get [-h] [--sudo SUDO]
                                                         --project-id
                                                         PROJECT_ID --mr-iid
                                                         MR_IID --note-id
                                                         NOTE_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--note-id <note_id>

--id <id>

gitlab project-merge-request-note-award-emoji list

```
usage: gitlab project-merge-request-note-award-emoji list [-h] [--sudo SUDO]
                                                         --project-id
                                                         PROJECT_ID --mr-iid
                                                         MR_IID --note-id
                                                         NOTE_ID
                                                         [--page PAGE]
                                                         [--per-page PER_PAGE]
                                                         [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--note-id <note_id>

--page <page>

--per-page <per_page>

--all

gitlab project-merge-request-pipeline

```
usage: gitlab project-merge-request-pipeline [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-pipeline create

```
usage: gitlab project-merge-request-pipeline create [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

gitlab project-merge-request-pipeline list

```
usage: gitlab project-merge-request-pipeline list [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--all

gitlab project-merge-request-resource-label-event

```
usage: gitlab project-merge-request-resource-label-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-resource-label-event get

```
usage: gitlab project-merge-request-resource-label-event get
       [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-resource-label-event list

```
usage: gitlab project-merge-request-resource-label-event list
       [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID
       [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--all

gitlab project-merge-request-resource-milestone-event

```
usage: gitlab project-merge-request-resource-milestone-event
       [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-resource-milestone-event get

```
usage: gitlab project-merge-request-resource-milestone-event get
       [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-resource-milestone-event list

```
usage: gitlab project-merge-request-resource-milestone-event list
       [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID
       [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--all

gitlab project-merge-request-resource-state-event

```
usage: gitlab project-merge-request-resource-state-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-resource-state-event get

```
usage: gitlab project-merge-request-resource-state-event get
       [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-resource-state-event list

```
usage: gitlab project-merge-request-resource-state-event list
       [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID
       [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--all

gitlab project-merge-train

```
usage: gitlab project-merge-train [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-merge-train list

```
usage: gitlab project-merge-train list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--scope SCOPE]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--scope <scope>

--page <page>

--per-page <per_page>

--all

gitlab project-milestone

```
usage: gitlab project-milestone [-h]
                                {list,get,create,update,delete,issues,merge-requests}
                                ...
```

-h, --help

show this help message and exit

gitlab project-milestone create

```
usage: gitlab project-milestone create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --title TITLE
                                         [--description DESCRIPTION]
                                         [--due-date DUE_DATE]
                                         [--start-date START_DATE]
                                         [--state-event STATE_EVENT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>
--title <title>
--description <description>
--due-date <due_date>
--start-date <start_date>
--state-event <state_event>

gitlab project-milestone delete

```
usage: gitlab project-milestone delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>

gitlab project-milestone get

```
usage: gitlab project-milestone get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                     --id ID
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>

gitlab project-milestone issues

```
usage: gitlab project-milestone issues [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>

gitlab project-milestone list

```
usage: gitlab project-milestone list [-h] [--sudo SUDO] --project-id
PROJECT_ID [--iids IIDS] [--state STATE]
[--search SEARCH] [--page PAGE]
[--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id** <project_id>**--iids** <iids>**--state** <state>**--search** <search>**--page** <page>**--per-page** <per_page>**--all**

gitlab project-milestone merge-requests

```
usage: gitlab project-milestone merge-requests [-h] --project-id PROJECT_ID
[--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>**--sudo** <sudo>**--id** <id>

gitlab project-milestone update

```
usage: gitlab project-milestone update [-h] [--sudo SUDO] --project-id
PROJECT_ID --id ID [--title TITLE]
[--description DESCRIPTION]
[--due-date DUE_DATE]
[--start-date START_DATE]
[--state-event STATE_EVENT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>
--id <id>
--title <title>
--description <description>
--due-date <due_date>
--start-date <start_date>
--state-event <state_event>

gitlab project-note

```
usage: gitlab project-note [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab project-note get

```
usage: gitlab project-note get [-h] [--sudo SUDO] --project-id PROJECT_ID --id  
ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-note list

```
usage: gitlab project-note list [-h] [--sudo SUDO] --project-id PROJECT_ID  
[--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-notification-settings

```
usage: gitlab project-notification-settings [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab project-notification-settings get

```
usage: gitlab project-notification-settings get [-h] [--sudo SUDO]
                                              --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-notification-settings update

```
usage: gitlab project-notification-settings update [-h] [--sudo SUDO]
                                              --project-id PROJECT_ID
                                              [--level LEVEL]
                                              [--notification-email NOTIFICATION_
↳EMAIL]
                                              [--new-note NEW_NOTE]
                                              [--new-issue NEW_ISSUE]
                                              [--reopen-issue REOPEN_ISSUE]
                                              [--close-issue CLOSE_ISSUE]
                                              [--reassign-issue REASSIGN_ISSUE]
                                              [--new-merge-request NEW_MERGE_
↳REQUEST]
                                              [--reopen-merge-request REOPEN_MERGE_
↳REQUEST]
                                              [--close-merge-request CLOSE_MERGE_
↳REQUEST]
                                              [--reassign-merge-request REASSIGN_
↳MERGE_REQUEST]
                                              [--merge-merge-request MERGE_MERGE_
↳REQUEST]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--level <level>

--notification-email <notification_email>

```
--new-note <new_note>
--new-issue <new_issue>
--reopen-issue <reopen_issue>
--close-issue <close_issue>
--reassign-issue <reassign_issue>
--new-merge-request <new_merge_request>
--reopen-merge-request <reopen_merge_request>
--close-merge-request <close_merge_request>
--reassign-merge-request <reassign_merge_request>
--merge-merge-request <merge_merge_request>
```

gitlab project-package

```
usage: gitlab project-package [-h] {list,get,delete} ...
```

-h, --help
show this help message and exit

gitlab project-package delete

```
usage: gitlab project-package delete [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-package get

```
usage: gitlab project-package get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-package list

```
usage: gitlab project-package list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   [--order-by ORDER_BY] [--sort SORT]
                                   [--package-type PACKAGE_TYPE]
                                   [--package-name PACKAGE_NAME] [--page PAGE]
                                   [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--order-by <order_by>

--sort <sort>

--package-type <package_type>

--package-name <package_name>

--page <page>

--per-page <per_page>

--all

gitlab project-package-file

```
usage: gitlab project-package-file [-h] {list,delete} ...
```

-h, --help

show this help message and exit

gitlab project-package-file delete

```
usage: gitlab project-package-file delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --package-id PACKAGE_ID
                                           --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--package-id <package_id>

--id <id>

gitlab project-package-file list

```
usage: gitlab project-package-file list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --package-id PACKAGE_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--package-id <package_id>

--page <page>

--per-page <per_page>

--all

gitlab project-pages-domain

```
usage: gitlab project-pages-domain [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-pages-domain create

```
usage: gitlab project-pages-domain create [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --domain DOMAIN
                                           [--certificate CERTIFICATE]
                                           [--key KEY]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--domain <domain>

--certificate <certificate>

--key <key>

gitlab project-pages-domain delete

```
usage: gitlab project-pages-domain delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --domain DOMAIN
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--domain <domain>

gitlab project-pages-domain get

```
usage: gitlab project-pages-domain get [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --domain DOMAIN
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--domain <domain>

gitlab project-pages-domain list

```
usage: gitlab project-pages-domain list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--page PAGE]
                                         [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-pages-domain update

```
usage: gitlab project-pages-domain update [-h] [--sudo SUDO] --project-id
PROJECT_ID --domain DOMAIN
[--certificate CERTIFICATE]
[--key KEY]
```

```
-h, --help
    show this help message and exit

--sudo <sudo>

--project-id <project_id>

--domain <domain>

--certificate <certificate>

--key <key>
```

gitlab project-pipeline

```
usage: gitlab project-pipeline [-h] {list,get,create,delete,cancel,retry} ...
```

-h, --help
show this help message and exit

gitlab project-pipeline cancel

```
usage: gitlab project-pipeline cancel [-h] --project-id PROJECT_ID
                                     [--sudo SUDO] --id ID
```

```
-h, --help          show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>
```

gitlab project-pipeline create

```
usage: gitlab project-pipeline create [-h] [--sudo SUDO] --project-id
PROJECT_ID --ref REF
```

```
-h, --help
    show this help message and exit

--sudo <sudo>

--project-id <project_id>

--ref <ref>
```

gitlab project-pipeline delete

```
usage: gitlab project-pipeline delete [-h] [--sudo SUDO] --project-id
PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-pipeline get

```
usage: gitlab project-pipeline get [-h] [--sudo SUDO] --project-id PROJECT_ID
--id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-pipeline list

```
usage: gitlab project-pipeline list [-h] [--sudo SUDO] --project-id PROJECT_ID
[--scope SCOPE] [--status STATUS]
[--ref REF] [--sha SHA]
[--yaml-errors YAML_ERRORS] [--name NAME]
[--username USERNAME]
[--order-by ORDER_BY] [--sort SORT]
[--page PAGE] [--per-page PER_PAGE]
[--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--scope <scope>

--status <status>

--ref <ref>

--sha <sha>

--yaml-errors <yaml_errors>
--name <name>
--username <username>
--order-by <order_by>
--sort <sort>
--page <page>
--per-page <per_page>
--all

gitlab project-pipeline retry

```
usage: gitlab project-pipeline retry [-h] --project-id PROJECT_ID
                                     [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>

gitlab project-pipeline-bridge

```
usage: gitlab project-pipeline-bridge [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab project-pipeline-bridge list

```
usage: gitlab project-pipeline-bridge list [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --pipeline-id
                                           PIPELINE_ID [--scope SCOPE]
                                           [--page PAGE] [--per-page PER_PAGE]
                                           [--all]
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--pipeline-id <pipeline_id>

```
--scope <scope>
--page <page>
--per-page <per_page>
--all
```

gitlab project-pipeline-job

```
usage: gitlab project-pipeline-job [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab project-pipeline-job list

```
usage: gitlab project-pipeline-job list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --pipeline-id PIPELINE_ID
                                         [--scope SCOPE]
                                         [--include-retried INCLUDE_RETRIED]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--all]
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--pipeline-id <pipeline_id>
--scope <scope>
--include-retried <include_retried>
--page <page>
--per-page <per_page>
--all
```

gitlab project-pipeline-schedule

```
usage: gitlab project-pipeline-schedule [-h]
                                         {list,get,create,update,delete,take-ownership,
->play}
                                         ...
```

-h, --help
show this help message and exit

gitlab project-pipeline-schedule create

```
usage: gitlab project-pipeline-schedule create [-h] [--sudo SUDO] --project-id
PROJECT_ID --description
DESCRIPTION --ref REF --cron
CRON
[--cron-timezone CRON_TIMEZONE]
[--active ACTIVE]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--description <description>

--ref <ref>

--cron <cron>

--cron-timezone <cron_timezone>

--active <active>

gitlab project-pipeline-schedule delete

```
usage: gitlab project-pipeline-schedule delete [-h] [--sudo SUDO] --project-id
PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-pipeline-schedule get

```
usage: gitlab project-pipeline-schedule get [-h] [--sudo SUDO] --project-id
PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-pipeline-schedule list

```
usage: gitlab project-pipeline-schedule list [-h] [--sudo SUDO] --project-id
      PROJECT_ID [--page PAGE]
      [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-pipeline-schedule play

```
usage: gitlab project-pipeline-schedule play [-h] --project-id PROJECT_ID
      [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-pipeline-schedule take-ownership

```
usage: gitlab project-pipeline-schedule take-ownership [-h] --project-id
      PROJECT_ID
      [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-pipeline-schedule update

```
usage: gitlab project-pipeline-schedule update [-h] [--sudo SUDO] --project-id
PROJECT_ID --id ID
        [--description DESCRIPTION]
        [--ref REF] [--cron CRON]
        [--cron-timezone CRON_TIMEZONE]
        [--active ACTIVE]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--description <description>

--ref <ref>

--cron <cron>

--cron-timezone <cron_timezone>

--active <active>

gitlab project-pipeline-schedule-variable

```
usage: gitlab project-pipeline-schedule-variable [-h]
        {create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-pipeline-schedule-variable create

```
usage: gitlab project-pipeline-schedule-variable create [-h] [--sudo SUDO]
        --project-id
        PROJECT_ID
        --pipeline-schedule-id
        PIPELINE_SCHEDULE_ID
        --key KEY --value
        VALUE
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--pipeline-schedule-id <pipeline_schedule_id>
--key <key>
--value <value>
```

gitlab project-pipeline-schedule-variable delete

```
usage: gitlab project-pipeline-schedule-variable delete [-h] [--sudo SUDO]
                                                    --project-id
                                                    PROJECT_ID
                                                    --pipeline-schedule-id
                                                    PIPELINE_SCHEDULE_ID
                                                    --key KEY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--pipeline-schedule-id <pipeline_schedule_id>
--key <key>
```

gitlab project-pipeline-schedule-variable update

```
usage: gitlab project-pipeline-schedule-variable update [-h] [--sudo SUDO]
                                                    --project-id
                                                    PROJECT_ID
                                                    --pipeline-schedule-id
                                                    PIPELINE_SCHEDULE_ID
                                                    --key KEY --value
                                                    VALUE
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--pipeline-schedule-id <pipeline_schedule_id>
--key <key>
--value <value>
```

gitlab project-pipeline-test-report

```
usage: gitlab project-pipeline-test-report [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-test-report get

```
usage: gitlab project-pipeline-test-report get [-h] [--sudo SUDO] --project-id
                                                PROJECT_ID --pipeline-id
                                                PIPELINE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-id <pipeline_id>

gitlab project-pipeline-test-report-summary

```
usage: gitlab project-pipeline-test-report-summary [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-test-report-summary get

```
usage: gitlab project-pipeline-test-report-summary get [-h] [--sudo SUDO]
                                                         --project-id PROJECT_ID
                                                         --pipeline-id
                                                         PIPELINE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-id <pipeline_id>

gitlab project-pipeline-variable

```
usage: gitlab project-pipeline-variable [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-variable list

```
usage: gitlab project-pipeline-variable list [-h] [--sudo SUDO] --project-id
      PROJECT_ID --pipeline-id
      PIPELINE_ID [--page PAGE]
      [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-id <pipeline_id>

--page <page>

--per-page <per_page>

--all

gitlab project-protected-branch

```
usage: gitlab project-protected-branch [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-protected-branch create

```
usage: gitlab project-protected-branch create [-h] [--sudo SUDO] --project-id
      PROJECT_ID --name NAME
      [--push-access-level PUSH_ACCESS_LEVEL]
      [--merge-access-level MERGE_ACCESS_LEVEL]
      [--unprotect-access-level UNPROTECT_ACCESS_
↪LEVEL]
      [--allowed-to-push ALLOWED_TO_PUSH]
      [--allowed-to-merge ALLOWED_TO_MERGE]
      [--allowed-to-unprotect ALLOWED_TO_
↪UNPROTECT]
      [--code-owner-approval-required CODE_OWNER_
↪APPROVAL_REQUIRED]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--push-access-level <push_access_level>

--merge-access-level <merge_access_level>

--unprotect-access-level <unprotect_access_level>

--allowed-to-push <allowed_to_push>

--allowed-to-merge <allowed_to_merge>

--allowed-to-unprotect <allowed_to_unprotect>

--code-owner-approval-required <code_owner_approval_required>

gitlab project-protected-branch delete

```
usage: gitlab project-protected-branch delete [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-protected-branch get

```
usage: gitlab project-protected-branch get [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-protected-branch list

```
usage: gitlab project-protected-branch list [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID [--page PAGE]
                                           [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-protected-tag

```
usage: gitlab project-protected-tag [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab project-protected-tag create

```
usage: gitlab project-protected-tag create [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --name NAME
                                           [--create-access-level CREATE_ACCESS_LEVEL]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--create-access-level <create_access_level>

gitlab project-protected-tag delete

```
usage: gitlab project-protected-tag delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-protected-tag get

```
usage: gitlab project-protected-tag get [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-protected-tag list

```
usage: gitlab project-protected-tag list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--page PAGE]
                                         [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-push-rules

```
usage: gitlab project-push-rules [-h] {get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-push-rules create

```
usage: gitlab project-push-rules create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID
                                         [--deny-delete-tag DENY_DELETE_TAG]
                                         [--member-check MEMBER_CHECK]
                                         [--prevent-secrets PREVENT_SECRETS]
                                         [--commit-message-regex COMMIT_MESSAGE_REGEX]
                                         [--branch-name-regex BRANCH_NAME_REGEX]
                                         [--author-email-regex AUTHOR_EMAIL_REGEX]
                                         [--file-name-regex FILE_NAME_REGEX]
                                         [--max-file-size MAX_FILE_SIZE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--deny-delete-tag <deny_delete_tag>

--member-check <member_check>

--prevent-secrets <prevent_secrets>

--commit-message-regex <commit_message_regex>

--branch-name-regex <branch_name_regex>

--author-email-regex <author_email_regex>

--file-name-regex <file_name_regex>

--max-file-size <max_file_size>

gitlab project-push-rules delete

```
usage: gitlab project-push-rules delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-push-rules get

```
usage: gitlab project-push-rules get [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-push-rules update

```
usage: gitlab project-push-rules update [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID
                                     [--deny-delete-tag DENY_DELETE_TAG]
                                     [--member-check MEMBER_CHECK]
                                     [--prevent-secrets PREVENT_SECRETS]
                                     [--commit-message-regex COMMIT_MESSAGE_REGEX]
                                     [--branch-name-regex BRANCH_NAME_REGEX]
                                     [--author-email-regex AUTHOR_EMAIL_REGEX]
                                     [--file-name-regex FILE_NAME_REGEX]
                                     [--max-file-size MAX_FILE_SIZE]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--deny-delete-tag <deny_delete_tag>

--member-check <member_check>

--prevent-secrets <prevent_secrets>

--commit-message-regex <commit_message_regex>

--branch-name-regex <branch_name_regex>

--author-email-regex <author_email_regex>

--file-name-regex <file_name_regex>

--max-file-size <max_file_size>

gitlab project-registry-repository

```
usage: gitlab project-registry-repository [-h] {list,delete} ...
```

-h, --help

show this help message and exit

gitlab project-registry-repository delete

```
usage: gitlab project-registry-repository delete [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID --id
                                                ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-registry-repository list

```
usage: gitlab project-registry-repository list [-h] [--sudo SUDO] --project-id
                                                PROJECT_ID [--page PAGE]
                                                [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-registry-tag

```
usage: gitlab project-registry-tag [-h] {list,get,delete,delete-in-bulk} ...
```

-h, --help

show this help message and exit

gitlab project-registry-tag delete

```
usage: gitlab project-registry-tag delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --repository-id
                                           REPOSITORY_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--repository-id <repository_id>

--name <name>

gitlab project-registry-tag delete-in-bulk

```
usage: gitlab project-registry-tag delete-in-bulk [-h] --project-id PROJECT_ID
                                                    --repository-id
                                                    REPOSITORY_ID [--sudo SUDO]
                                                    --name NAME
                                                    --name-regex-delete
                                                    NAME_REGEX_DELETE
                                                    [--keep-n KEEP_N]
                                                    [--name-regex-keep NAME_REGEX_KEEP]
                                                    [--older-than OLDER_THAN]
```

-h, --help

show this help message and exit

--project-id <project_id>

--repository-id <repository_id>

--sudo <sudo>

--name <name>

--name-regex-delete <name_regex_delete>

--keep-n <keep_n>

--name-regex-keep <name_regex_keep>

--older-than <older_than>

gitlab project-registry-tag get

```
usage: gitlab project-registry-tag get [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --repository-id
                                         REPOSITORY_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--repository-id <repository_id>

--name <name>

gitlab project-registry-tag list

```
usage: gitlab project-registry-tag list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --repository-id
                                         REPOSITORY_ID [--page PAGE]
                                         [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--repository-id <repository_id>

--page <page>

--per-page <per_page>

--all

gitlab project-release

```
usage: gitlab project-release [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-release create

```
usage: gitlab project-release create [-h] [--sudo SUDO] --project-id
PROJECT_ID --tag-name TAG_NAME
--description DESCRIPTION [--name NAME]
[--ref REF] [--assets ASSETS]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--description <description>

--name <name>

--ref <ref>

--assets <assets>

gitlab project-release delete

```
usage: gitlab project-release delete [-h] [--sudo SUDO] --project-id
PROJECT_ID --tag-name TAG_NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

gitlab project-release get

```
usage: gitlab project-release get [-h] [--sudo SUDO] --project-id PROJECT_ID
--tag-name TAG_NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

gitlab project-release list

```
usage: gitlab project-release list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-release update

```
usage: gitlab project-release update [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --tag-name TAG_NAME
                                     [--name NAME] [--description DESCRIPTION]
                                     [--milestones MILESTONES]
                                     [--released-at RELEASED_AT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--name <name>

--description <description>

--milestones <milestones>

--released-at <released_at>

gitlab project-release-link

```
usage: gitlab project-release-link [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-release-link create

```
usage: gitlab project-release-link create [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --tag-name TAG_NAME
                                           --name NAME --url URL
                                           [--filepath FILEPATH]
                                           [--link-type LINK_TYPE]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--name <name>

--url <url>

--filepath <filepath>

--link-type <link_type>

gitlab project-release-link delete

```
usage: gitlab project-release-link delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --tag-name TAG_NAME --id
                                           ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--id <id>

gitlab project-release-link get

```
usage: gitlab project-release-link get [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --tag-name TAG_NAME --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--id <id>

gitlab project-release-link list

```
usage: gitlab project-release-link list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --tag-name TAG_NAME
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--page <page>

--per-page <per_page>

--all

gitlab project-release-link update

```
usage: gitlab project-release-link update [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --tag-name TAG_NAME --id
                                           ID [--name NAME] [--url URL]
                                           [--filepath FILEPATH]
                                           [--link-type LINK_TYPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--id <id>

--name <name>

--url <url>

--filepath <filepath>

--link-type <link_type>

gitlab project-remote-mirror

```
usage: gitlab project-remote-mirror [-h] {list,create,update} ...
```

-h, --help

show this help message and exit

gitlab project-remote-mirror create

```
usage: gitlab project-remote-mirror create [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --url URL
                                           [--enabled ENABLED]
                                           [--only-protected-branches ONLY_PROTECTED_
↪BRANCHES]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--url <url>

--enabled <enabled>

--only-protected-branches <only_protected_branches>

gitlab project-remote-mirror list

```
usage: gitlab project-remote-mirror list [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID [--page PAGE]
                                           [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-remote-mirror update

```
usage: gitlab project-remote-mirror update [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --id ID
                                           [--enabled ENABLED]
                                           [--only-protected-branches ONLY_PROTECTED_
↪BRANCHES]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id** <project_id>**--id** <id>**--enabled** <enabled>**--only-protected-branches** <only_protected_branches>

gitlab project-runner

```
usage: gitlab project-runner [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-runner create

```
usage: gitlab project-runner create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                     --runner-id RUNNER_ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id** <project_id>**--runner-id** <runner_id>

gitlab project-runner delete

```
usage: gitlab project-runner delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                     --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-runner list

```
usage: gitlab project-runner list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   [--scope SCOPE] [--tag-list TAG_LIST]
                                   [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--scope <scope>

--tag-list <tag_list>

--page <page>

--per-page <per_page>

--all

gitlab project-service

```
usage: gitlab project-service [-h] {list,get,update,delete,available} ...
```

-h, --help

show this help message and exit

gitlab project-service available

```
usage: gitlab project-service available [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --slug SLUG
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--slug <slug>

gitlab project-service delete

```
usage: gitlab project-service delete [-h] [--sudo SUDO] --project-id
PROJECT_ID --slug SLUG
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-service get

```
usage: gitlab project-service get [-h] [--sudo SUDO] --project-id PROJECT_ID
--slug SLUG
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-service list

```
usage: gitlab project-service list [-h] [--sudo SUDO] --project-id PROJECT_ID
[--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-service update

```
usage: gitlab project-service update [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --slug SLUG
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-snippet

```
usage: gitlab project-snippet [-h]
                               {list,get,create,update,delete,user-agent-detail,content}
                               ...
```

-h, --help
show this help message and exit

gitlab project-snippet content

```
usage: gitlab project-snippet content [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-snippet create

```
usage: gitlab project-snippet create [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --title TITLE --file-name
                                     FILE_NAME --content CONTENT --visibility
                                     VISIBILITY [--description DESCRIPTION]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

```

--title <title>
--file-name <file_name>
--content <content>
--visibility <visibility>
--description <description>

```

gitlab project-snippet delete

```
usage: gitlab project-snippet delete [-h] [--sudo SUDO] --project-id
PROJECT_ID --id ID
```

```

-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>

```

gitlab project-snippet get

```
usage: gitlab project-snippet get [-h] [--sudo SUDO] --project-id PROJECT_ID
--id ID
```

```

-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>

```

gitlab project-snippet list

```
usage: gitlab project-snippet list [-h] [--sudo SUDO] --project-id PROJECT_ID
[--page PAGE] [--per-page PER_PAGE] [--all]
```

```

-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--page <page>
--per-page <per_page>
--all

```

gitlab project-snippet update

```
usage: gitlab project-snippet update [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --id ID [--title TITLE]
                                     [--file-name FILE_NAME]
                                     [--content CONTENT]
                                     [--visibility VISIBILITY]
                                     [--description DESCRIPTION]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--title <title>

--file-name <file_name>

--content <content>

--visibility <visibility>

--description <description>

gitlab project-snippet user-agent-detail

```
usage: gitlab project-snippet user-agent-detail [-h] --project-id PROJECT_ID
                                                [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-snippet-award-emoji

```
usage: gitlab project-snippet-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab project-snippet-award-emoji create

```
usage: gitlab project-snippet-award-emoji create [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --snippet-id SNIPPET_ID
                                                --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--name <name>

gitlab project-snippet-award-emoji delete

```
usage: gitlab project-snippet-award-emoji delete [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --snippet-id SNIPPET_ID --id
                                                ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--id <id>

gitlab project-snippet-award-emoji get

```
usage: gitlab project-snippet-award-emoji get [-h] [--sudo SUDO] --project-id
                                                PROJECT_ID --snippet-id
                                                SNIPPET_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--id <id>

gitlab project-snippet-award-emoji list

```
usage: gitlab project-snippet-award-emoji list [-h] [--sudo SUDO] --project-id
        PROJECT_ID --snippet-id
        SNIPPET_ID [--page PAGE]
        [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--page <page>

--per-page <per_page>

--all

gitlab project-snippet-discussion

```
usage: gitlab project-snippet-discussion [-h] {list,get,create} ...
```

-h, --help
show this help message and exit

gitlab project-snippet-discussion create

```
usage: gitlab project-snippet-discussion create [-h] [--sudo SUDO]
        --project-id PROJECT_ID
        --snippet-id SNIPPET_ID --body
        BODY [--created-at CREATED_AT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--body <body>

--created-at <created_at>

gitlab project-snippet-discussion get

```
usage: gitlab project-snippet-discussion get [-h] [--sudo SUDO] --project-id
      PROJECT_ID --snippet-id
      SNIPPET_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--id <id>

gitlab project-snippet-discussion list

```
usage: gitlab project-snippet-discussion list [-h] [--sudo SUDO] --project-id
      PROJECT_ID --snippet-id
      SNIPPET_ID [--page PAGE]
      [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--page <page>

--per-page <per_page>

--all

gitlab project-snippet-discussion-note

```
usage: gitlab project-snippet-discussion-note [-h]
      {get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-snippet-discussion-note create

```
usage: gitlab project-snippet-discussion-note create [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --discussion-id
DISCUSSION_ID --body BODY
                                                    [--created-at CREATED_AT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--discussion-id <discussion_id>

--body <body>

--created-at <created_at>

gitlab project-snippet-discussion-note delete

```
usage: gitlab project-snippet-discussion-note delete [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --discussion-id
DISCUSSION_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--discussion-id <discussion_id>

--id <id>

gitlab project-snippet-discussion-note get

```
usage: gitlab project-snippet-discussion-note get [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --discussion-id
DISCUSSION_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--discussion-id <discussion_id>

--id <id>

gitlab project-snippet-discussion-note update

```
usage: gitlab project-snippet-discussion-note update [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --discussion-id
DISCUSSION_ID --id ID
                                                    --body BODY
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--discussion-id <discussion_id>

--id <id>

--body <body>

gitlab project-snippet-note

```
usage: gitlab project-snippet-note [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-snippet-note create

```
usage: gitlab project-snippet-note create [-h] [--sudo SUDO] --project-id
PROJECT_ID --snippet-id SNIPPET_ID
--body BODY
```

-h, --help
show this help message and exit

--sudo <sudo>
--project-id <project_id>
--snippet-id <snippet_id>
--body <body>

gitlab project-snippet-note delete

```
usage: gitlab project-snippet-note delete [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --snippet-id SNIPPET_ID
                                           --id ID
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--snippet-id <snippet_id>
--id <id>

gitlab project-snippet-note get

```
usage: gitlab project-snippet-note get [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --snippet-id SNIPPET_ID --id
                                         ID
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--snippet-id <snippet_id>
--id <id>

gitlab project-snippet-note list

```
usage: gitlab project-snippet-note list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --snippet-id SNIPPET_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--all]
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--snippet-id <snippet_id>
--page <page>
--per-page <per_page>
--all
```

gitlab project-snippet-note update

```
usage: gitlab project-snippet-note update [-h] [--sudo SUDO] --project-id
                                           PROJECT_ID --snippet-id SNIPPET_ID
                                           --id ID --body BODY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--snippet-id <snippet_id>
--id <id>
--body <body>
```

gitlab project-snippet-note-award-emoji

```
usage: gitlab project-snippet-note-award-emoji [-h]
                                                {list,get,create,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-snippet-note-award-emoji create

```
usage: gitlab project-snippet-note-award-emoji create [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --snippet-id SNIPPET_ID
                                                       --note-id NOTE_ID --name
                                                       NAME
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
```

--project-id <project_id>
--snippet-id <snippet_id>
--note-id <note_id>
--name <name>

gitlab project-snippet-note-award-emoji delete

```
usage: gitlab project-snippet-note-award-emoji delete [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --note-id NOTE_ID --id
                                                    ID
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--snippet-id <snippet_id>
--note-id <note_id>
--id <id>

gitlab project-snippet-note-award-emoji get

```
usage: gitlab project-snippet-note-award-emoji get [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --note-id NOTE_ID --id ID
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--snippet-id <snippet_id>
--note-id <note_id>
--id <id>

gitlab project-snippet-note-award-emoji list

```
usage: gitlab project-snippet-note-award-emoji list [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --note-id NOTE_ID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--note-id <note_id>

--page <page>

--per-page <per_page>

--all

gitlab project-storage

```
usage: gitlab project-storage [-h] {get} ...
```

-h, --help
show this help message and exit

gitlab project-storage get

```
usage: gitlab project-storage get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-tag

```
usage: gitlab project-tag [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab project-tag create

```
usage: gitlab project-tag create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --tag-name TAG_NAME --ref REF
                                [--message MESSAGE]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--ref <ref>

--message <message>

gitlab project-tag delete

```
usage: gitlab project-tag delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-tag get

```
usage: gitlab project-tag get [-h] [--sudo SUDO] --project-id PROJECT_ID
                              --name NAME
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-tag list

```
usage: gitlab project-tag list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-trigger

```
usage: gitlab project-trigger [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab project-trigger create

```
usage: gitlab project-trigger create [-h] [--sudo SUDO] --project-id
PROJECT_ID --description DESCRIPTION
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--description <description>

gitlab project-trigger delete

```
usage: gitlab project-trigger delete [-h] [--sudo SUDO] --project-id
PROJECT_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-trigger get

```
usage: gitlab project-trigger get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-trigger list

```
usage: gitlab project-trigger list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--all

gitlab project-trigger update

```
usage: gitlab project-trigger update [-h] [--sudo SUDO] --project-id
                                   PROJECT_ID --id ID --description
                                   DESCRIPTION
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--description <description>

gitlab project-user

```
usage: gitlab project-user [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-user list

```
usage: gitlab project-user list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--search SEARCH] [--skip-users SKIP_USERS]
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--search <search>

--skip-users <skip_users>

--page <page>

--per-page <per_page>

--all

gitlab project-variable

```
usage: gitlab project-variable [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-variable create

```
usage: gitlab project-variable create [-h] [--sudo SUDO] --project-id
                                PROJECT_ID --key KEY --value VALUE
                                [--protected PROTECTED]
                                [--variable-type VARIABLE_TYPE]
                                [--masked MASKED]
                                [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>
--key <key>
--value <value>
--protected <protected>
--variable-type <variable_type>
--masked <masked>
--environment-scope <environment_scope>

gitlab project-variable delete

```
usage: gitlab project-variable delete [-h] [--sudo SUDO] --project-id
PROJECT_ID --key KEY
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--key <key>

gitlab project-variable get

```
usage: gitlab project-variable get [-h] [--sudo SUDO] --project-id PROJECT_ID
--key KEY
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--key <key>

gitlab project-variable list

```
usage: gitlab project-variable list [-h] [--sudo SUDO] --project-id PROJECT_ID
[--page PAGE] [--per-page PER_PAGE]
[--all]
```

-h, --help
show this help message and exit
--sudo <sudo>

--project-id <project_id>
--page <page>
--per-page <per_page>
--all

gitlab project-variable update

```
usage: gitlab project-variable update [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --key KEY --value VALUE
                                     [--protected PROTECTED]
                                     [--variable-type VARIABLE_TYPE]
                                     [--masked MASKED]
                                     [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help
 show this help message and exit

--sudo <sudo>

--project-id <project_id>

--key <key>

--value <value>

--protected <protected>

--variable-type <variable_type>

--masked <masked>

--environment-scope <environment_scope>

gitlab project-wiki

```
usage: gitlab project-wiki [-h] {list,get,create,update,delete} ...
```

-h, --help
 show this help message and exit

gitlab project-wiki create

```
usage: gitlab project-wiki create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --title TITLE --content CONTENT
                                   [--format FORMAT]
```

-h, --help
 show this help message and exit

--sudo <sudo>
--project-id <project_id>
--title <title>
--content <content>
--format <format>

gitlab project-wiki delete

```
usage: gitlab project-wiki delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --slug SLUG
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--slug <slug>

gitlab project-wiki get

```
usage: gitlab project-wiki get [-h] [--sudo SUDO] --project-id PROJECT_ID
                               --slug SLUG
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--slug <slug>

gitlab project-wiki list

```
usage: gitlab project-wiki list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--with-content WITH_CONTENT] [--page PAGE]
                                [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--with-content <with_content>

--page <page>
--per-page <per_page>
--all

gitlab project-wiki update

```
usage: gitlab project-wiki update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --slug SLUG [--title TITLE]
                                   [--content CONTENT] [--format FORMAT]
```

-h, --help
show this help message and exit
--sudo <sudo>
--project-id <project_id>
--slug <slug>
--title <title>
--content <content>
--format <format>

gitlab runner

```
usage: gitlab runner [-h] {list,get,create,update,delete,all,verify} ...
```

-h, --help
show this help message and exit

gitlab runner all

```
usage: gitlab runner all [-h] --id ID [--scope SCOPE]
```

-h, --help
show this help message and exit
--id <id>
--scope <scope>

gitlab runner create

```
usage: gitlab runner create [-h] [--sudo SUDO] --token TOKEN
                             [--description DESCRIPTION] [--info INFO]
                             [--active ACTIVE] [--locked LOCKED]
                             [--run-untagged RUN_UNTAGGED]
                             [--tag-list TAG_LIST]
                             [--access-level ACCESS_LEVEL]
                             [--maximum-timeout MAXIMUM_TIMEOUT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--token <token>

--description <description>

--info <info>

--active <active>

--locked <locked>

--run-untagged <run_untagged>

--tag-list <tag_list>

--access-level <access_level>

--maximum-timeout <maximum_timeout>

gitlab runner delete

```
usage: gitlab runner delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab runner get

```
usage: gitlab runner get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab runner list

```
usage: gitlab runner list [-h] [--sudo SUDO] [--scope SCOPE]
                        [--tag-list TAG_LIST] [--page PAGE]
                        [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--scope <scope>

--tag-list <tag_list>

--page <page>

--per-page <per_page>

--all

gitlab runner update

```
usage: gitlab runner update [-h] [--sudo SUDO] --id ID
                        [--description DESCRIPTION] [--active ACTIVE]
                        [--tag-list TAG_LIST]
                        [--run-untagged RUN_UNTAGGED] [--locked LOCKED]
                        [--access-level ACCESS_LEVEL]
                        [--maximum-timeout MAXIMUM_TIMEOUT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

--description <description>

--active <active>

--tag-list <tag_list>

--run-untagged <run_untagged>

--locked <locked>

--access-level <access_level>

--maximum-timeout <maximum_timeout>

gitlab runner verify

```
usage: gitlab runner verify [-h] --id ID --token TOKEN
```

-h, --help

show this help message and exit

--id <id>

--token <token>

gitlab runner-job

```
usage: gitlab runner-job [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab runner-job list

```
usage: gitlab runner-job list [-h] [--sudo SUDO] --runner-id RUNNER_ID
                                [--status STATUS] [--page PAGE]
                                [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--runner-id <runner_id>

--status <status>

--page <page>

--per-page <per_page>

--all

gitlab snippet

```
usage: gitlab snippet [-h]
                        {list,get,create,update,delete,user-agent-detail,content,public}
                        ...
```

-h, --help

show this help message and exit

gitlab snippet content

```
usage: gitlab snippet content [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab snippet create

```
usage: gitlab snippet create [-h] [--sudo SUDO] --title TITLE --file-name
                             FILE_NAME --content CONTENT [--lifetime LIFETIME]
                             [--visibility VISIBILITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--title <title>

--file-name <file_name>

--content <content>

--lifetime <lifetime>

--visibility <visibility>

gitlab snippet delete

```
usage: gitlab snippet delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab snippet get

```
usage: gitlab snippet get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab snippet list

```
usage: gitlab snippet list [-h] [--sudo SUDO] [--page PAGE]
                          [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab snippet public

```
usage: gitlab snippet public [-h] --id ID
```

-h, --help
show this help message and exit

--id <id>

gitlab snippet update

```
usage: gitlab snippet update [-h] [--sudo SUDO] --id ID [--title TITLE]
                             [--file-name FILE_NAME] [--content CONTENT]
                             [--visibility VISIBILITY]
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

--title <title>

--file-name <file_name>

--content <content>

--visibility <visibility>

gitlab snippet user-agent-detail

```
usage: gitlab snippet user-agent-detail [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab starred-project

```
usage: gitlab starred-project [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab starred-project list

```
usage: gitlab starred-project list [-h] [--sudo SUDO] --user-id USER_ID
                                     [--archived ARCHIVED]
                                     [--membership MEMBERSHIP]
                                     [--min-access-level MIN_ACCESS_LEVEL]
                                     [--order-by ORDER_BY] [--owned OWNED]
                                     [--search SEARCH] [--simple SIMPLE]
                                     [--sort SORT] [--starred STARRED]
                                     [--statistics STATISTICS]
                                     [--visibility VISIBILITY]
                                     [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                     [--with-issues-enabled WITH_ISSUES_ENABLED]
                                     [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
↳ENABLED]
                                     [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--archived <archived>

--membership <membership>

--min-access-level <min_access_level>

--order-by <order_by>

--owned <owned>

--search <search>

--simple <simple>

--sort <sort>
--starred <starred>
--statistics <statistics>
--visibility <visibility>
--with-custom-attributes <with_custom_attributes>
--with-issues-enabled <with_issues_enabled>
--with-merge-requests-enabled <with_merge_requests_enabled>
--page <page>
--per-page <per_page>
--all

gitlab todo

```
usage: gitlab todo [-h] {list,delete,mark-as-done,mark-all-as-done} ...
```

-h, --help
show this help message and exit

gitlab todo delete

```
usage: gitlab todo delete [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>
--id <id>

gitlab todo list

```
usage: gitlab todo list [-h] [--sudo SUDO] [--action ACTION]
                        [--author-id AUTHOR_ID] [--project-id PROJECT_ID]
                        [--state STATE] [--type TYPE] [--page PAGE]
                        [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>
--action <action>
--author-id <author_id>

```

--project-id <project_id>
--state <state>
--type <type>
--page <page>
--per-page <per_page>
--all

```

gitlab todo mark-all-as-done

```
usage: gitlab todo mark-all-as-done [-h] --id ID
```

```

-h, --help
    show this help message and exit
--id <id>

```

gitlab todo mark-as-done

```
usage: gitlab todo mark-as-done [-h] --id ID
```

```

-h, --help
    show this help message and exit
--id <id>

```

gitlab topic

```
usage: gitlab topic [-h] {list,get,create,update,delete} ...
```

```

-h, --help
    show this help message and exit

```

gitlab topic create

```
usage: gitlab topic create [-h] [--sudo SUDO] --name NAME [--avatar AVATAR]
                             [--description DESCRIPTION]
```

```

-h, --help
    show this help message and exit
--sudo <sudo>
--name <name>
--avatar <avatar>
--description <description>

```

gitlab topic delete

```
usage: gitlab topic delete [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab topic get

```
usage: gitlab topic get [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

gitlab topic list

```
usage: gitlab topic list [-h] [--sudo SUDO] [--page PAGE]
                        [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab topic update

```
usage: gitlab topic update [-h] [--sudo SUDO] --id ID [--avatar AVATAR]
                        [--description DESCRIPTION] [--name NAME]
```

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

--avatar <avatar>

--description <description>

--name <name>

gitlab user

```
usage: gitlab user [-h]
                  {list,get,create,update,delete,block,unfollow,unblock,
↪ deactivate,activate}
                  ...
```

-h, --help

show this help message and exit

gitlab user activate

```
usage: gitlab user activate [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user block

```
usage: gitlab user block [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user create

```
usage: gitlab user create [-h] [--sudo SUDO] [--email EMAIL]
                          [--username USERNAME] [--name NAME]
                          [--password PASSWORD]
                          [--reset-password RESET_PASSWORD] [--skype SKYPE]
                          [--linkedin LINKEDIN] [--twitter TWITTER]
                          [--projects-limit PROJECTS_LIMIT]
                          [--extern-uid EXTERN_UID] [--provider PROVIDER]
                          [--bio BIO] [--admin ADMIN]
                          [--can-create-group CAN_CREATE_GROUP]
                          [--website-url WEBSITE_URL]
                          [--skip-confirmation SKIP_CONFIRMATION]
                          [--external EXTERNAL] [--organization ORGANIZATION]
                          [--location LOCATION] [--avatar AVATAR]
                          [--public-email PUBLIC_EMAIL]
                          [--private-profile PRIVATE_PROFILE]
```

(continues on next page)

(continued from previous page)

<pre>[--color-scheme-id COLOR_SCHEME_ID] [--theme-id THEME_ID]</pre>
--

```
-h, --help
    show this help message and exit

--sudo <sudo>

--email <email>

--username <username>

--name <name>

--password <password>

--reset-password <reset_password>

--skype <skype>

--linkedin <linkedin>

--twitter <twitter>

--projects-limit <projects_limit>

--extern-uid <extern_uid>

--provider <provider>

--bio <bio>

--admin <admin>

--can-create-group <can_create_group>

--website-url <website_url>

--skip-confirmation <skip_confirmation>

--external <external>

--organization <organization>

--location <location>

--avatar <avatar>

--public-email <public_email>

--private-profile <private_profile>

--color-scheme-id <color_scheme_id>

--theme-id <theme_id>
```

gitlab user deactivate

```
usage: gitlab user deactivate [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user delete

```
usage: gitlab user delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab user follow

```
usage: gitlab user follow [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user get

```
usage: gitlab user get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab user list

```
usage: gitlab user list [-h] [--sudo SUDO] [--active ACTIVE]
                        [--blocked BLOCKED] [--username USERNAME]
                        [--extern-uid EXTERN_UID] [--provider PROVIDER]
                        [--external EXTERNAL] [--search SEARCH]
                        [--custom-attributes CUSTOM_ATTRIBUTES]
                        [--status STATUS] [--two-factor TWO_FACTOR]
                        [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--active <active>

--blocked <blocked>

--username <username>

--extern-uid <extern_uid>

--provider <provider>

--external <external>

--search <search>

--custom-attributes <custom_attributes>

--status <status>

--two-factor <two_factor>

--page <page>

--per-page <per_page>

--all

gitlab user unblock

```
usage: gitlab user unblock [-h] --id ID
```

-h, --help
show this help message and exit

--id <id>

gitlab user unfollow

```
usage: gitlab user unfollow [-h] --id ID
```

-h, --help
show this help message and exit

--id <id>

gitlab user update

```
usage: gitlab user update [-h] [--sudo SUDO] --id ID --email EMAIL --username
                        USERNAME --name NAME [--password PASSWORD]
                        [--skype SKYPE] [--linkedin LINKEDIN]
                        [--twitter TWITTER]
                        [--projects-limit PROJECTS_LIMIT]
                        [--extern-uid EXTERN_UID] [--provider PROVIDER]
                        [--bio BIO] [--admin ADMIN]
                        [--can-create-group CAN_CREATE_GROUP]
                        [--website-url WEBSITE_URL]
                        [--skip-reconfirmation SKIP_RECONFIRMATION]
                        [--external EXTERNAL] [--organization ORGANIZATION]
                        [--location LOCATION] [--avatar AVATAR]
                        [--public-email PUBLIC_EMAIL]
                        [--private-profile PRIVATE_PROFILE]
                        [--color-scheme-id COLOR_SCHEME_ID]
                        [--theme-id THEME_ID]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

--email <email>

--username <username>

--name <name>

--password <password>

--skype <skype>

--linkedin <linkedin>

--twitter <twitter>

--projects-limit <projects_limit>

--extern-uid <extern_uid>

--provider <provider>

--bio <bio>

--admin <admin>

--can-create-group <can_create_group>

--website-url <website_url>

--skip-reconfirmation <skip_reconfirmation>

--external <external>

```
--organization <organization>
--location <location>
--avatar <avatar>
--public-email <public_email>
--private-profile <private_profile>
--color-scheme-id <color_scheme_id>
--theme-id <theme_id>
```

gitlab user-activities

```
usage: gitlab user-activities [-h] {list} ...
```

```
-h, --help
    show this help message and exit
```

gitlab user-activities list

```
usage: gitlab user-activities list [-h] [--sudo SUDO] [--page PAGE]
                                     [--per-page PER_PAGE] [--all]
```

```
-h, --help
    show this help message and exit

--sudo <sudo>
--page <page>
--per-page <per_page>
--all
```

gitlab user-custom-attribute

```
usage: gitlab user-custom-attribute [-h] {list,get,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab user-custom-attribute delete

```
usage: gitlab user-custom-attribute delete [-h] [--sudo SUDO] --user-id
USER_ID --key KEY
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--key <key>

gitlab user-custom-attribute get

```
usage: gitlab user-custom-attribute get [-h] [--sudo SUDO] --user-id USER_ID
--key KEY
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--key <key>

gitlab user-custom-attribute list

```
usage: gitlab user-custom-attribute list [-h] [--sudo SUDO] --user-id USER_ID
[--page PAGE] [--per-page PER_PAGE]
[--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--all

gitlab user-email

```
usage: gitlab user-email [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab user-email create

```
usage: gitlab user-email create [-h] [--sudo SUDO] --user-id USER_ID --email  
                                EMAIL
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--email <email>

gitlab user-email delete

```
usage: gitlab user-email delete [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-email get

```
usage: gitlab user-email get [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-email list

```
usage: gitlab user-email list [-h] [--sudo SUDO] --user-id USER_ID
                               [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--all

gitlab user-event

```
usage: gitlab user-event [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab user-event list

```
usage: gitlab user-event list [-h] [--sudo SUDO] --user-id USER_ID
                               [--action ACTION] [--target-type TARGET_TYPE]
                               [--before BEFORE] [--after AFTER] [--sort SORT]
                               [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--action <action>

--target-type <target_type>

--before <before>

--after <after>

--sort <sort>

--page <page>

--per-page <per_page>

--all

gitlab user-gpg-key

```
usage: gitlab user-gpg-key [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab user-gpg-key create

```
usage: gitlab user-gpg-key create [-h] [--sudo SUDO] --user-id USER_ID --key  
KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--key <key>

gitlab user-gpg-key delete

```
usage: gitlab user-gpg-key delete [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-gpg-key get

```
usage: gitlab user-gpg-key get [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-gpg-key list

```
usage: gitlab user-gpg-key list [-h] [--sudo SUDO] --user-id USER_ID
                                [--page PAGE] [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--all

gitlab user-impersonation-token

```
usage: gitlab user-impersonation-token [-h] {list,get,create,delete} ...
```

-h, --help
show this help message and exit

gitlab user-impersonation-token create

```
usage: gitlab user-impersonation-token create [-h] [--sudo SUDO] --user-id
                                              USER_ID --name NAME --scopes
                                              SCOPES [--expires-at EXPIRES_AT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--name <name>

--scopes <scopes>

--expires-at <expires_at>

gitlab user-impersonation-token delete

```
usage: gitlab user-impersonation-token delete [-h] [--sudo SUDO] --user-id
USER_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-impersonation-token get

```
usage: gitlab user-impersonation-token get [-h] [--sudo SUDO] --user-id
USER_ID --id ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-impersonation-token list

```
usage: gitlab user-impersonation-token list [-h] [--sudo SUDO] --user-id
USER_ID [--state STATE]
[--page PAGE]
[--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--state <state>

--page <page>

--per-page <per_page>

--all

gitlab user-key

```
usage: gitlab user-key [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab user-key create

```
usage: gitlab user-key create [-h] [--sudo SUDO] --user-id USER_ID --title  
                               TITLE --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--title <title>

--key <key>

gitlab user-key delete

```
usage: gitlab user-key delete [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-key get

```
usage: gitlab user-key get [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-key list

```
usage: gitlab user-key list [-h] [--sudo SUDO] --user-id USER_ID [--page PAGE]
                             [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--all

gitlab user-membership

```
usage: gitlab user-membership [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab user-membership get

```
usage: gitlab user-membership get [-h] [--sudo SUDO] --user-id USER_ID
                                   --source-id SOURCE_ID
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--source-id <source_id>

gitlab user-membership list

```
usage: gitlab user-membership list [-h] [--sudo SUDO] --user-id USER_ID
                                   [--type TYPE] [--page PAGE]
                                   [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

```
--type <type>
--page <page>
--per-page <per_page>
--all
```

gitlab user-personal-access-token

```
usage: gitlab user-personal-access-token [-h] {create} ...
```

```
-h, --help
    show this help message and exit
```

gitlab user-personal-access-token create

```
usage: gitlab user-personal-access-token create [-h] [--sudo SUDO] --user-id
                                                USER_ID --name NAME --scopes
                                                SCOPES
                                                [--expires-at EXPIRES_AT]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--user-id <user_id>
--name <name>
--scopes <scopes>
--expires-at <expires_at>
```

gitlab user-project

```
usage: gitlab user-project [-h] {list,create} ...
```

```
-h, --help
    show this help message and exit
```

gitlab user-project create

```
usage: gitlab user-project create [-h] [--sudo SUDO] --user-id USER_ID --name
                                   NAME [--default-branch DEFAULT_BRANCH]
                                   [--issues-enabled ISSUES_ENABLED]
                                   [--wall-enabled WALL_ENABLED]
                                   [--merge-requests-enabled MERGE_REQUESTS_ENABLED]
                                   [--wiki-enabled WIKI_ENABLED]
```

(continues on next page)

(continued from previous page)

```

[--snippets-enabled SNIPPETS_ENABLED]
[--squash-option SQUASH_OPTION]
[--public PUBLIC] [--visibility VISIBILITY]
[--description DESCRIPTION]
[--builds-enabled BUILDS_ENABLED]
[--public-builds PUBLIC_BUILDS]
[--import-url IMPORT_URL]
[--only-allow-merge-if-build-succeeds ONLY_ALLOW_MERGE_
↪IF_BUILD_SUCCEEDS]

```

-h, --help

show this help message and exit

--sudo <sudo>**--user-id** <user_id>**--name** <name>**--default-branch** <default_branch>**--issues-enabled** <issues_enabled>**--wall-enabled** <wall_enabled>**--merge-requests-enabled** <merge_requests_enabled>**--wiki-enabled** <wiki_enabled>**--snippets-enabled** <snippets_enabled>**--squash-option** <squash_option>**--public** <public>**--visibility** <visibility>**--description** <description>**--builds-enabled** <builds_enabled>**--public-builds** <public_builds>**--import-url** <import_url>**--only-allow-merge-if-build-succeeds** <only_allow_merge_if_build_succeeds>

gitlab user-project list

```

usage: gitlab user-project list [-h] [--sudo SUDO] --user-id USER_ID
                                [--archived ARCHIVED]
                                [--visibility VISIBILITY]
                                [--order-by ORDER_BY] [--sort SORT]
                                [--search SEARCH] [--simple SIMPLE]
                                [--owned OWNED] [--membership MEMBERSHIP]

```

(continues on next page)

(continued from previous page)

```

--starred STARRED] [--statistics STATISTICS]
--with-issues-enabled WITH_ISSUES_ENABLED]
--with-merge-requests-enabled WITH_MERGE_REQUESTS_
↳ENABLED]
--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
--with-programming-language WITH_PROGRAMMING_LANGUAGE]
--wiki-checksum-failed WIKI_CHECKSUM_FAILED]
--repository-checksum-failed REPOSITORY_CHECKSUM_FAILED]
--min-access-level MIN_ACCESS_LEVEL]
--id-after ID_AFTER] [--id-before ID_BEFORE]
--page PAGE] [--per-page PER_PAGE] [--all]

```

-h, --help

show this help message and exit

--sudo <sudo>**--user-id** <user_id>**--archived** <archived>**--visibility** <visibility>**--order-by** <order_by>**--sort** <sort>**--search** <search>**--simple** <simple>**--owned** <owned>**--membership** <membership>**--starred** <starred>**--statistics** <statistics>**--with-issues-enabled** <with_issues_enabled>**--with-merge-requests-enabled** <with_merge_requests_enabled>**--with-custom-attributes** <with_custom_attributes>**--with-programming-language** <with_programming_language>**--wiki-checksum-failed** <wiki_checksum_failed>**--repository-checksum-failed** <repository_checksum_failed>**--min-access-level** <min_access_level>**--id-after** <id_after>**--id-before** <id_before>**--page** <page>

--per-page <per_page>

--all

gitlab user-status

```
usage: gitlab user-status [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab user-status get

```
usage: gitlab user-status get [-h] [--sudo SUDO] --user-id USER_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

gitlab variable

```
usage: gitlab variable [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab variable create

```
usage: gitlab variable create [-h] [--sudo SUDO] --key KEY --value VALUE
                                [--protected PROTECTED]
                                [--variable-type VARIABLE_TYPE]
                                [--masked MASKED]
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

--value <value>

--protected <protected>

--variable-type <variable_type>

--masked <masked>

gitlab variable delete

```
usage: gitlab variable delete [-h] [--sudo SUDO] --key KEY
```

-h, --help
show this help message and exit

--sudo <sudo>

--key <key>

gitlab variable get

```
usage: gitlab variable get [-h] [--sudo SUDO] --key KEY
```

-h, --help
show this help message and exit

--sudo <sudo>

--key <key>

gitlab variable list

```
usage: gitlab variable list [-h] [--sudo SUDO] [--page PAGE]
                             [--per-page PER_PAGE] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--all

gitlab variable update

```
usage: gitlab variable update [-h] [--sudo SUDO] --key KEY --value VALUE
                             [--protected PROTECTED]
                             [--variable-type VARIABLE_TYPE]
                             [--masked MASKED]
```

-h, --help
show this help message and exit

--sudo <sudo>

--key <key>

`--value <value>`
`--protected <protected>`
`--variable-type <variable_type>`
`--masked <masked>`

6.7 Changelog

6.7.1 v3.5.0 (2022-05-28)

Feature

- **objects:** Support get project storage endpoint ([8867ee5](#))
- Display human-readable attribute in `repr()` if present ([6b47c26](#))
- **ux:** Display `project.name_with_namespace` on project repr ([e598762](#))

Fix

- **cli:** Changed default `allow_abbrev` value to fix arguments collision problem ([#2013](#)) ([d68cacf](#))
- Duplicate subparsers being added to `argparse` ([f553fd3](#))

Documentation

- Update issue example and extend API usage docs ([aad71d2](#))
- **CONTRIBUTING.rst:** Fix link to conventional-changelog commit format documentation ([2373a4f](#))
- Add missing Admin access const value ([3e0d4d9](#))
- **merge_requests:** Add new possible merge request state and link to the upstream docs ([e660fa8](#))

6.7.2 v3.4.0 (2022-04-28)

Feature

- Emit a warning when using a `list()` method returns max ([1339d64](#))
- **objects:** Support getting project/group deploy tokens by id ([fcd37fe](#))
- **user:** Support getting user SSH key by id ([6f93c05](#))
- **api:** Re-add topic delete endpoint ([d1d96bd](#))

Fix

- Add ChunkedEncodingError to list of retryable exceptions ([7beb20f](#))
- Avoid passing redundant arguments to API ([3431887](#))
- **cli:** Add missing filters for project commit list ([149d244](#))
- Add 52x range to retry transient failures and tests ([c3ef1b5](#))
- Also retry HTTP-based transient errors ([3b49e4d](#))

Documentation

- **api-docs:** Docs fix for application scopes ([e1ad93d](#))

6.7.3 v3.3.0 (2022-03-28)

Feature

- **object:** Add pipeline test report summary support ([a97e0cf](#))

Fix

- Support RateLimit-Reset header ([4060146](#))

Documentation

- Fix typo and incorrect style ([2828b10](#))
- Add pipeline test report summary support ([d78afb3](#))
- **chore:** Include docs .js files in sdist ([3010b40](#))

6.7.4 v3.2.0 (2022-02-28)

Feature

- **merge_request_approvals:** Add support for deleting MR approval rules ([85a734f](#))
- **artifacts:** Add support for project artifacts delete API ([c01c034](#))
- **mixins:** Allow deleting resources without IDs ([0717517](#))
- **objects:** Add a complete artifacts manager ([c8c2fa7](#))

Fix

- **services:** Use slug for id_attr instead of custom methods (e30f39d)
- Remove custom delete method for labels (0841a2a)

Documentation

- Enable gitter chat directly in docs (bd1ecdd)
- Add delete methods for runners and project artifacts (5e711fd)
- Add retry_transient infos (bb1f054)
- Add transient errors retry info (b7a1266)
- **artifacts:** Deprecate artifacts() and artifact() methods (64d01ef)
- Revert “chore: add temporary banner for v3” (#1864) (7a13b9b)

6.7.5 v3.1.1 (2022-01-28)

Fix

- **cli:** Make ‘per_page’ and ‘page’ type explicit (d493a5e)
- **cli:** Make ‘timeout’ type explicit (bbb7df5)
- **cli:** Allow custom methods in managers (8dfed0c)
- **objects:** Make resource access tokens and repos available in CLI (e0a3a41)

Documentation

- Enhance release docs for CI_JOB_TOKEN usage (5d973de)
- **changelog:** Add missing changelog items (01755fb)

6.7.6 v3.1.0 (2022-01-14)

Feature

- add support for Group Access Token API (c01b7c4)
- Add support for Groups API method transfer() (0007006)
- **api:** Add project.transfer() and deprecate transfer_project() (259668a)
- **api:** Return result from SaveMixin.save() (e6258a4)

Fix

- **cli:** Add missing list filters for environments ([6f64d40](#))
- Use url-encoded ID in all paths ([12435d7](#))
- **members:** Use new *All objects for *AllManager managers ([755e0a3](#))
- **api:** Services: add missing lazy parameter ([888f332](#))
- broken URL for FAQ about attribute-error-list ([1863f30](#))
- remove default arguments for mergerequests.merge() ([8e589c4](#))
- remove custom URL encoding ([3d49e5e](#))

Documentation

- **cli:** make examples more easily navigable by generating TOC ([f33c523](#))
- update project access token API reference link ([73ae955](#))

6.7.7 v3.0.0 (2022-01-05)

Feature

- **docker:** Remove custom entrypoint from image ([80754a1](#))
- **cli:** Allow options from args and environment variables ([ca58008](#))
- **api:** Support file format for repository archive ([83dcabf](#))
- Add support for `squash_option` in Projects ([a246ce8](#))
- **cli:** Do not require config file to run CLI ([92a893b](#))
- **api:** Add support for Topics API ([e7559bf](#))
- Add delete on `package_file` object ([124667b](#))
- Add support for `projects.groups.list()` ([68ff595](#))
- **api:** Add support for epic notes ([7f4edb5](#))
- Remove support for Python 3.6, require 3.7 or higher ([414009d](#))
- **api:** Add project milestone promotion ([f068520](#))
- **api:** Add merge trains ([fd73a73](#))
- **api:** Add merge request approval state ([f41b093](#))
- **api:** Add project label promotion ([6d7c88a](#))
- **objects:** Support delete package files API ([4518046](#))
- **objects:** List starred projects of a user ([47a5606](#))
- **build:** Officially support and test python 3.10 ([c042ddc](#))
- **objects:** Support Create and Revoke personal access token API ([e19314d](#))
- Default to gitlab.com if no URL given ([8236281](#))
- Allow global `retry_transient_errors` setup ([3b1d3a4](#))

Fix

- Handle situation where GitLab does not return values ([cb824a4](#))
- Stop encoding ‘.’ to ‘%2E’ ([702e41d](#))
- **build:** Do not include docs in wheel package ([68a97ce](#))
- **api:** Delete invalid ‘project-runner get’ command ([#1628](#)) ([905781b](#))
- **api:** Replace deprecated attribute in `delete_in_bulk()` ([#1536](#)) ([c59fbdb](#))
- **objects:** Rename confusing `to_project_id` argument ([ce4bc0d](#))
- Raise error if there is a 301/302 redirection ([d56a434](#))
- **build:** Do not package tests in wheel ([969dccc](#))

Breaking

- The gitlab CLI will now accept CLI arguments and environment variables for its global options in addition to configuration file options. This may change behavior for some workflows such as running inside GitLab CI and with certain environment variables configured. ([ca58008](#))
- stop encoding ‘.’ to ‘%2E’. This could potentially be a breaking change for users who have incorrectly configured GitLab servers which don’t handle period ‘.’ characters correctly. ([702e41d](#))
- A config file is no longer needed to run the CLI. python-gitlab will default to `https://gitlab.com` with no authentication if there is no config file provided. python-gitlab will now also only look for configuration in the provided `PYTHON_GITLAB_CFG` path, instead of merging it with user- and system-wide config files. If the environment variable is defined and the file cannot be opened, python-gitlab will now explicitly fail. ([92a893b](#))
- As of python-gitlab 3.0.0, Python 3.6 is no longer supported. Python 3.7 or higher is required. ([414009d](#))
- As of python-gitlab 3.0.0, the default branch for development has changed from `master` to `main`. ([545f8ed](#))
- remove deprecated branch protect methods in favor of the more complete protected branches API. ([9656a16](#))
- The deprecated `name_regex` attribute has been removed in favor of `name_regex_delete`. (see <https://gitlab.com/gitlab-org/gitlab/-/commit/ce99813cf54>) ([c59fbdb](#))
- rename confusing `to_project_id` argument in `transfer_project` to `project_id` (`--project-id` in CLI). This is used for the source project, not for the target namespace. ([ce4bc0d](#))
- remove deprecated constants defined in `gitlab.v4.objects`, and use only `gitlab.const` module ([3f320af](#))
- remove deprecated tag release API. This was removed in GitLab 14.0 ([2b8a94a](#))
- remove deprecated `project.issuesstatistics` in favor of `project.issues_statistics` ([ca7777e](#))
- remove deprecated `members.all()` method in favor of `members_all.list()` ([4d7b848](#))
- remove deprecated `pipelines()` methods in favor of `pipelines.list()` ([c4f5ec6](#))
- python-gitlab will now default to `gitlab.com` if no URL is given ([8236281](#))
- raise error if there is a 301/302 redirection ([d56a434](#))

Documentation

- Switch to Furo and refresh introduction pages ([ee6b024](#))
- Correct documentation for updating discussion note ([ee66f4a](#))
- Rename documentation files to match names of code files ([ee3f865](#))
- **project:** Remove redundant encoding parameter ([fed613f](#))
- Use annotations for return types ([79e785e](#))
- Update docs to use gitlab.const for constants ([b3b0b5f](#))
- Only use type annotations for documentation ([b7dde0d](#))
- Add links to the GitLab API docs ([e3b5d27](#))
- Fix API delete key example ([b31bb05](#))
- **pipelines:** Document take_ownership method ([69461f6](#))
- **api:** Document the update method for project variables ([7992911](#))
- **api:** Clarify job token usage with auth() ([3f423ef](#))
- Fix a few typos ([7ea4ddc](#))
- Consolidate changelogs and remove v3 API docs ([90da8ba](#))
- Correct documented return type ([acabf63](#))

6.7.8 v2.10.1 (2021-08-28)

Fix

- **mixins:** Improve deprecation warning ([57e0187](#))
- **deps:** Upgrade requests to 2.25.0 (see CVE-2021-33503) ([ce995b2](#))

Documentation

- **mergequests:** Gl.mergequests.list documentation was misleading ([5b5a7bc](#))

6.7.9 v2.10.0 (2021-07-28)

Feature

- **api:** Add merge_ref for merge requests ([1e24ab2](#))
- **api:** Add name_regex_keep attribute in delete_in_bulk() ([e49ff3f](#))

Fix

- **api:** Do not require Release name for creation ([98cd03b](#))

Documentation

- **readme:** Move contributing docs to CONTRIBUTING.rst ([edf49a3](#))
- Add example for mr.merge_ref ([b30b8ac](#))
- **project:** Add example on getting a single project using name with namespace ([ef16a97](#))

6.7.10 v2.9.0 (2021-06-28)

Feature

- **release:** Allow to update release ([b4c4787](#))
- **api:** Add group hooks ([4a7e9b8](#))
- **api:** Remove responsibility for API inconsistencies for MR reviewers ([3d985ee](#))
- **api:** Add MR pipeline manager and deprecate pipelines() method ([954357c](#))
- **api:** Add support for creating/editing reviewers in project merge requests ([676d1f6](#))

Documentation

- **tags:** Remove deprecated functions ([1b1a827](#))
- **release:** Add update example ([6254a5f](#))
- Make Gitlab class usable for intersphinx ([8753add](#))

6.7.11 v2.8.0 (2021-06-10)

Feature

- Add keys endpoint ([a81525a](#))
- **objects:** Add support for Group wikis ([#1484](#)) ([74f5e62](#))
- **objects:** Add support for generic packages API ([79d88bd](#))
- **api:** Add deployment mergerequests interface ([fbbc0d4](#))
- **objects:** Support all issues statistics endpoints ([f731707](#))
- **objects:** Add support for descendant groups API ([1b70580](#))
- **objects:** Add pipeline test report support ([ee9f96e](#))
- **objects:** Add support for billable members ([fb0b083](#))
- Add feature to get inherited member for project/group ([e444b39](#))
- Add code owner approval as attribute ([fdc46ba](#))
- Indicate that we are a typed package ([e4421ca](#))

- Add support for lists of integers to ListAttribute ([115938b](#))

Fix

- Catch invalid type used to initialize RESTObject ([c7bcc25](#))
- Functional project service test ([#1500](#)) ([093db9d](#))
- Ensure kwargs are passed appropriately for ObjectDeleteMixin ([4e690c2](#))
- **cli:** Add missing list filter for jobs ([b3d1c26](#))
- Change mr.merge() to use 'post_data' ([cb6a3c6](#))
- **cli:** Fix parsing CLI objects to classnames ([4252070](#))
- **objects:** Return server data in cancel/retry methods ([9fed061](#))
- **objects:** Add missing group attributes ([d20ff4f](#))
- **objects:** Allow lists for filters for in all objects ([603a351](#))
- Iids not working as a list in projects.issues.list() ([45f806c](#))
- Add a check to ensure the MRO is correct ([565d548](#))

Documentation

- Fix typo in http_delete docstring ([5226f09](#))
- **api:** Add behavior in local attributes when updating objects ([38f65e8](#))
- Fail on warnings during sphinx build ([cbd4d52](#))

6.7.12 v2.7.1 (2021-04-26)

- fix(files): do not url-encode file paths twice

6.7.13 v2.7.0 (2021-04-25)

Bug Fixes

- update user's bool data and avatar ([3ba27ffb](#))
- argument type was not a tuple as expected ([062f8f6a](#))
- correct some type-hints in gitlab/mixins.py ([8bd31240](#))
- only append kwargs as query parameters ([b9ecc9a8](#))
- only add query_parameters to GitlabList once ([1386](#))
- checking if RESTManager._from_parent_attrs is set ([8224b406](#))
- handling config value in _get_values_from_helper ([9dfb4cd9](#))
- let the homedir be expanded in path of helper ([fc7387a0](#))
- make secret helper more user friendly ([fc2798fc](#))
- linting issues and test ([b04dd2c0](#))

- handle tags like debian/2%2.6-21 as identifiers (b4dac5ce)
- remove duplicate class definitions in v4/objects/users.py (7c4e6259)
- wrong variable name (15ec41ca)
- tox pep8 target, so that it can run (f518e87b)
- undefined name errors (48ec9e0f)
- extend wait timeout for test_delete_user() (19fde8ed)
- test_update_group() dependency on ordering (e78a8d63)
- honor parameter value passed (c2f8f0e7)
- **objects:** add single get endpoint for instance audit events (c3f0a6f1)
- **types:** prevent **dir** from producing duplicates (5bf7525d)

Features

- add ProjectPackageFile (#1372)
- add option to add a helper to lookup token (8ecf5592)
- add project audit endpoint (6660dbef)
- add personal access token API (2bb16fac)
- add import from bitbucket server (ff3013a2)
- **api,cli:** make user agent configurable (4bb201b9)
- **issues:** add missing get verb to IssueManager (f78ebe06)
- **objects:**
 - add support for resource state events API (d4799c40)
 - add support for group audit events API (2a0fbdf9)
 - add Release Links API support (28d75181)
- **projects:** add project access token api (1becef02)
- **users:** add follow/unfollow API (e456869d)

Documentation

- correct ProjectFile.decode() documentation (b180bafd)
- update doc for token helper (3ac6fa12)
- better real life token lookup example (9ef83118)

6.7.14 v2.6.0 (2021-01-29)

Features

- support multipart uploads (2fa3004d)
- add MINIMAL_ACCESS constant (49eb3ca7)
- unit tests added (f37ebf5f)
- added support for pipeline bridges (05cbdc22)
- adds support for project merge request approval rules (#1199) (c6fbf399)
- **api:**
 - added wip filter param for merge requests (d6078f80)
 - added wip filter param for merge requests (aa6e80d5)
 - add support for user identity provider deletion (e78e1215)
- **tests:** test label getter (a41af902)

Bug Fixes

- docs changed using the consts (650b65c3)
- typo (9baa9053)
- **api:**
 - use RetrieveMixin for ProjectLabelManager (1a143952)
 - add missing runner access_level param (92669f2e)
- **base:** really refresh object (e1e0d8cb), closes (#1155)
- **cli:**
 - write binary data to stdout buffer (0733ec6c)
 - add missing args for project lists (c73e2374)

6.7.15 v2.5.0 (2020-09-01)

Features

- add support to resource milestone events (88f8cc78), closes #1154
- add share/unshare group with group (7c6e541d)
- add support for instance variables (4492fc42)
- add support for Packages API (71495d12)
- add endpoint for latest ref artifacts (b7a07fca)

Bug Fixes

- wrong reconfirmation parameter when updating user's email (b5c267e1)
- tests fail when using REUSE_CONTAINER option (0078f899, closes #1146)
- implement Gitlab's behavior change for owned=True (99777991)

6.7.16 v2.4.0 (2020-07-09)

Bug Fixes

- do not check if kwargs is none (a349b90e)
- make query kwargs consistent between call in init and next (72ffa016)
- pass kwargs to subsequent queries in gitlab list (1d011ac7)
- **merge:** parse arguments as query_data (878098b7)

Features

- add NO_ACCESS const (dab4d0a1)
- add masked parameter for variables command (b6339bf8)

6.7.17 v2.3.1 (2020-06-09)

- revert keyset pagination by default

6.7.18 v2.3.0 (2020-06-08)

Features

- add group runners api (49439916)
- add play command to project pipeline schedules (07b99881)
- allow an environment variable to specify config location (401e702a)
- **api:** added support in the GroupManager to upload Group avatars (28eb7eab)
- **services:** add project service list API (fc522218)
- **types:** add **dir** to RESTObject to expose attributes (cad134c0)

Bug Fixes

- use keyset pagination by default for /projects > 50000 (f86ef3bb)
- **config:** fix duplicate code (ee2df6f1), closes (#1094)
- **project:** add missing project parameters (ad8c67d6)

6.7.19 v2.2.0 (2020-04-07)

Bug Fixes

- add missing import_project param (9b16614b)
- **types:** do not split single value string in ListAttribute (a26e5858)

Features

- add commit GPG signature API (da7a8097)
- add create from template args to ProjectManager (f493b73e)
- add remote mirrors API (#1056) (4cfaa2fd)
- add Gitlab Deploy Token API (01de524c)
- add Group Import/Export API (#1037) (6cb9d923)

6.7.20 v2.1.2 (2020-03-09)

Bug Fixes

- Fix regression, when using keyset pagination with merge requests. Related to [https://github.com/python-gitlab/issues/1044](https://github.com/python-gitlab/python-gitlab/issues/1044)

6.7.21 v2.1.1 (2020-03-09)

Bug Fixes

users: update user attributes

This change was made to mitigate an issue in Gitlab (again). Fix available in: https://gitlab.com/gitlab-org/gitlab/-/merge_requests/26792

6.7.22 v2.1.0 (2020-03-08)

Bug Fixes

- do not require empty data dict for create() (99d959f7)
- remove trailing slashes from base URL (#913) (2e396e4a)
- return response with commit data (b77b945c)
- remove null values from features POST data, because it fails with HTTP 500 (1ec1816d)
- **docs:**
 - fix typo in user memberships example (33889becb)
 - update to new set approvers call for # of approvers (8e0c5262)
 - update docs and tests for set_approvers (2cf12c79)
- **objects:**
 - add default name data and use http post (70c0cfb6)
 - update set_approvers function call (65ecadcf)
 - update to new gitlab api for path, and args (e512cddd)

Features

- add support for user memberships API (#1009) (c313c2b0)
- add support for commit revert API (#991) (5298964e)
- add capability to control GitLab features per project or group (7f192b4f)
- use keyset pagination by default for all=True (99b4484d)
- add support for GitLab OAuth Applications API (4e12356d)

6.7.23 v2.0.1 (2020-02-05)

Changes

- **users:** update user attributes

This change was made to mitigate an issue in Gitlab. See: <https://gitlab.com/gitlab-org/gitlab/issues/202070>

6.7.24 v2.0.0 (2020-01-26)

This releases drops support for python < 3.6

Bug Fixes

- **projects:** adjust snippets to match the API (e104e213)

Features

- add global order_by option to ease pagination (d1879253)
- support keyset pagination globally (0b71ba4d)
- add appearance API (4c4ac5ca)
- add autocompletion support (973cb8b9)

6.7.25 v1.15.0 (2019-12-16)

Bug Fixes

- ignore all parameter, when as_list=True 137d72b3, closes #962

Features

- allow cfg timeout to be overridden via kwargs e9a8289a
- add support for /import/github aa4d41b7
- nicer stacktrace 697cda24
- retry transient HTTP errors 59fe2714, closes #970
- access project's issues statistics 482e57ba, closes #966
- adding project stats db0b00a9, closes #967
- add variable_type/protected to projects ci variables 4724c50e
- add variable_type to groups ci variables 0986c931

6.7.26 v1.14.0 (2019-12-07)

Bug Fixes

- added missing attributes for project approvals 460ed63c
- **labels:** ensure label.save() works 727f5361
- **project-fork:**
 - copy create fix from ProjectPipelineManager 516307f1
 - correct path computation for project-fork list 44a7c278

Features

- add audit endpoint 2534020b
- add project and group clusters ebd053e7
- add support for include_subgroups filter adbcd83f

6.7.27 v1.13.0 (2019-11-02)

Features

- add users activate, deactivate functionality (32ad6692)
- send python-gitlab version as user-agent (c22d49d0)
- add deployment creation (ca256a07), closes [#917]
- **auth:** remove deprecated session auth (b751cdf4)
- **doc:** remove refs to api v3 in docs (6beea99)
- **test:** unused unittest2, type -> isinstance (33b18012)

Bug Fixes

- **projects:** support approval_rules endpoint for projects (2cef2bb4)

6.7.28 v1.12.1 (2019-10-07)

Bug Fixes

fix: fix not working without auth provided

6.7.29 v1.12.0 (2019-10-06)

Features

- add support for job token
- **project:**
 - implement update_submodule
 - add file blame api
- **user:** add status api

Bug Fixes

- **cli:** fix cli command user-project list
- **labels:** don't mangle label name on update
- **todo:** mark_all_as_done doesn't return anything

6.7.30 v1.11.0 (2019-08-31)

Features

- add methods to retrieve an individual project environment
- group labels with subscriptable mixin

Bug Fixes

- projects: avatar uploading for projects
- remove empty list default arguments
- remove empty dict default arguments
- add project and group label update without id to fix cli

6.7.31 v1.10.0 (2019-07-22)

Features

- add mr rebase method bc4280c2
- get artifact by ref and job cda11745
- add support for board update 908d79fa, closes #801
- add support for issue.related_merge_requests 90a36315, closes #794

Bug Fixes

- improve pickle support b4b5decb
- **cli:**
 - allow `--recursive` parameter in repository tree 7969a78c, closes #718, #731
 - don't fail when the short print attr value is None 8d1552a0, closes #717, #727
 - fix update value for key not working b7662039

6.7.32 v1.9.0 (2019-06-19)

Features

- implement artifacts deletion
- add endpoint to get the variables of a pipeline
- delete ProjectPipeline
- implement **eq** and **hash** methods
- Allow runpy invocation of CLI tool (python -m gitlab)
- add project releases api
- merged new release & registry apis

Bug Fixes

- convert # to %23 in URLs
- pep8 errors
- use python2 compatible syntax for super
- Make MemberManager.all() return a list of objects
-
- Re-enable command specific help messages
- dont ask for id attr if this is *Manager originating custom action
- fix -/_ replacament for *Manager custom actions
- fix repository_id marshaling in cli
- register cli action for delete_in_bulk

6.7.33 v1.8.0 (2019-02-22)

- docs(setup): use proper readme on PyPI
- docs(readme): provide commit message guidelines
- fix(api): make reset_time_estimate() work again
- fix: handle empty 'Retry-After' header from GitLab
- fix: remove decode() on error_message string
- chore: release tags to PyPI automatically
- fix(api): avoid parameter conflicts with python and gitlab
- fix(api): Don't try to parse raw downloads
- feat: Added approve & unapprove method for Mergerequests
- fix all kwarg behaviour

6.7.34 v1.7.0 (2018-12-09)

- **docs:** Fix the owned/starred usage documentation
- **docs:** Add a warning about http to https redirects
- Fix the https redirection test
- **docs:** Add a note about GroupProject limited API
- Add missing comma in ProjectIssueManager _create_attrs
- More flexible docker image
- Add project protected tags management
- **cli:** Print help and usage without config file
- Rename MASTER_ACCESS to MAINTAINER_ACCESS
- **docs:** Add docs build information
- Use docker image with current sources
- **docs:** Add PyYAML requirement notice
- Add Gitter badge to README
- **docs:** Add an example of pipeline schedule vars listing
- **cli:** Exit on config parse error, instead of crashing
- Add support for resource label events
- **docs:** Fix the milestone filetring doc (iid -> iids)
- **docs:** Fix typo in custom attributes example
- Improve error message handling in exceptions
- Add support for members all() method
- Add access control options to protected branch creation

6.7.35 v1.6.0 (2018-08-25)

- **docs:** Don't use hardcoded values for ids
- **docs:** Improve the snippets examples
- **cli:** Output: handle bytes in API responses
- **cli:** Fix the case where we have nothing to print
- Project import: fix the override_params parameter
- Support group and global MR listing
- Implement MR.pipelines()
- MR: add the squash attribute for create/update
- Added support for listing forks of a project
- **docs:** Add/update notes about read-only objects
- Raise an exception on https redirects for PUT/POST

- **docs:** Add a FAQ
- **cli:** Fix the project-export download

6.7.36 v1.5.1 (2018-06-23)

- Fix the ProjectPipelineJob base class (regression)

6.7.37 v1.5.0 (2018-06-22)

- Drop API v3 support
- Drop GetFromListMixin
- Update the sphinx extension for v4 objects
- Add support for user avatar upload
- Add support for project import/export
- Add support for the search API
- Add a global per_page config option
- Add support for the discussions API
- Add support for merged branches deletion
- Add support for Project badges
- Implement user_agent_detail for snippets
- Implement commit.refs()
- Add commit.merge_requests() support
- Deployment: add list filters
- Deploy key: add missing attributes
- Add support for environment stop()
- Add feature flags deletion support
- Update some group attributes
- Issues: add missing attributes and methods
- Fix the participants() decorator
- Add support for group boards
- Implement the markdown rendering API
- Update MR attributes
- Add pipeline listing filters
- Add missing project attributes
- Implement runner jobs listing
- Runners can be created (registered)
- Implement runner token validation
- Update the settings attributes

- Add support for the gitlab CI lint API
- Add support for group badges
- Fix the IssueManager path to avoid redirections
- time_stats(): use an existing attribute if available
- Make ProjectCommitStatus.create work with CLI
- Tests: default to python 3
- ProjectPipelineJob was defined twice
- Silence logs/warnings in unittests
- Add support for MR approval configuration (EE)
- Change post_data default value to None
- Add geo nodes API support (EE)
- Add support for issue links (EE)
- Add support for LDAP groups (EE)
- Add support for board creation/deletion (EE)
- Add support for Project.pull_mirror (EE)
- Add project push rules configuration (EE)
- Add support for the EE license API
- Add support for the LDAP groups API (EE)
- Add support for epics API (EE)
- Fix the non-verbose output of ProjectCommitComment

6.7.38 v1.4.0 (2018-05-19)

- Require requests>=2.4.2
- ProjectKeys can be updated
- Add support for unsharing projects (v3/v4)
- **cli:** fix listing for json and yaml output
- Fix typos in documentation
- Introduce RefreshMixin
- **docs:** Fix the time tracking examples
- **docs:** Commits: add an example of binary file creation
- **cli:** Allow to read args from files
- Add support for recursive tree listing
- **cli:** Restore the --help option behavior
- Add basic unit tests for v4 CLI
- **cli:** Fix listing of strings
- Support downloading a single artifact file

- Update docs copyright years
- Implement attribute types to handle special cases
- **docs:** fix GitLab reference for notes
- Expose additional properties for Gitlab objects
- Fix the impersonation token deletion example
- feat: obey the rate limit
- Fix URL encoding on branch methods
- **docs:** add a code example for listing commits of a MR
- **docs:** update service.available() example for API v4
- **tests:** fix functional tests for python3
- api-usage: bit more detail for listing with all
- More efficient .get() for group members
- Add docs for the files arg in http_*
- Deprecate GetFromListMixin

6.7.39 v1.3.0 (2018-02-18)

- Add support for pipeline schedules and schedule variables
- Clarify information about supported python version
- Add manager for jobs within a pipeline
- Fix wrong tag example
- Update the groups documentation
- Add support for MR participants API
- Add support for getting list of user projects
- Add Gitlab and User events support
- Make trigger_pipeline return the pipeline
- Config: support api_version in the global section
- Gitlab can be used as context manager
- Default to API v4
- Add a simplified example for streamed artifacts
- Add documentation about labels update

6.7.40 v1.2.0 (2018-01-01)

- Add mattermost service support
- Add users custom attributes support
- **doc:** Fix project.triggers.create example with v4 API
- OAuth token support
- Remove deprecated objects/methods
- Rework authentication args handling
- Add support for oauth and anonymous auth in config/CLI
- Add support for impersonation tokens API
- Add support for user activities
- Update user docs with gitlab URLs
- **docs:** Bad arguments in projects file documentation
- Add support for user_agent_detail (issues)
- Add a SetMixin
- Add support for project housekeeping
- Expected HTTP response for subscribe is 201
- Update pagination docs for ProjectCommit
- Add doc to get issue from iid
- Make todo() raise GitlabTodoError on error
- Add support for award emojis
- Update project services docs for v4
- Avoid sending empty update data to issue.save
- **docstrings:** Explicitly document pagination arguments
- **docs:** Add a note about password auth being removed from GitLab
- Submanagers: allow having undefined parameters
- ProjectFile.create(): don't modify the input data
- Update testing tools for /session removal
- Update groups tests
- Allow per_page to be used with generators
- Add groups listing attributes
- Add support for subgroups listing
- Add supported python versions in setup.py
- Add support for pagesdomains
- Add support for features flags
- Add support for project and group custom variables
- Add support for user/group/project filter by custom attribute

- Respect content of REQUESTS_CA_BUNDLE and *_proxy envvars

6.7.41 v1.1.0 (2017-11-03)

- Fix trigger variables in v4 API
- Make the delete() method handle / in ids
- **docs:** update the file upload samples
- Tags release description: support / in tag names
- **docs:** improve the labels usage documentation
- Add support for listing project users
- ProjectFileManager.create: handle / in file paths
- Change ProjectUser and GroupProject base class
- **docs:** document get_create_attrs in the API tutorial
- Document the Gitlab session parameter
- ProjectFileManager: custom update() method
- Project: add support for printing_merge_request_link_enabled attr
- Update the ssl_verify docstring
- Add support for group milestones
- Add support for GPG keys
- Add support for wiki pages
- Update the repository_blob documentation
- Fix the CLI for objects without ID (API v4)
- Add a contributed Dockerfile
- Pagination generators: expose more information
- Module's base objects serialization
- **doc:** Add sample code for client-side certificates

6.7.42 v1.0.2 (2017-09-29)

- **docs:** remove example usage of submanagers
- Properly handle the labels attribute in ProjectMergeRequest
- ProjectFile: handle / in path for delete() and save()

6.7.43 v1.0.1 (2017-09-21)

- Tags can be retrieved by ID
- Add the server response in GitlabError exceptions
- Add support for project file upload
- Minor typo fix in “Switching to v4” documentation
- Fix password authentication for v4
- Fix the labels attrs on MR and issues
- Exceptions: use a proper error message
- Fix http_get method in get artifacts and job trace
- CommitStatus: sha is parent attribute
- Fix a couple listing calls to allow proper pagination
- Add missing doc file

6.7.44 v1.0.0 (2017-09-08)

- Support for API v4. See <http://python-gitlab.readthedocs.io/en/master/switching-to-v4.html>
- Support SSL verification via internal CA bundle
- Docs: Add link to gitlab docs on obtaining a token
- Added dependency injection support for Session
- Fixed repository_compare examples
- Fix changelog and release notes inclusion in sdist
- Missing expires_at in GroupMembers update
- Add lower-level methods for Gitlab()

6.7.45 v0.21.2 (2017-06-11)

- Install doc: use sudo for system commands
- **v4:** Make MR work properly
- Remove extra_attrs argument from _raw_list
- **v4:** Make project issues work properly
- Fix urlencode() usage (python 2/3) (#268)
- Fixed spelling mistake (#269)
- Add new event types to ProjectHook

6.7.46 v0.21.1 (2017-05-25)

- Fix the manager name for jobs in the Project class
- Fix the docs

6.7.47 v0.21 (2017-05-24)

- Add time_stats to ProjectMergeRequest
- Update User options for creation and update (#246)
- Add milestone.merge_requests() API
- Fix docs typo (s/correspnding/corresponding/)
- Support milestone start date (#251)
- Add support for priority attribute in labels (#256)
- Add support for nested groups (#257)
- Make GroupProjectManager a subclass of ProjectManager (#255)
- Available services: return a list instead of JSON (#258)
- MR: add support for time tracking features (#248)
- Fixed repository_tree and repository_blob path encoding (#265)
- Add 'search' attribute to projects.list()
- Initial gitlab API v4 support
- Reorganise the code to handle v3 and v4 objects
- Allow 202 as delete return code
- Deprecate parameter related methods in gitlab.Gitlab

6.7.48 v0.20 (2017-03-25)

- Add time tracking support (#222)
- Improve changelog (#229, #230)
- Make sure that manager objects are never overwritten (#209)
- Include chanlog and release notes in docs
- Add DeployKey{,Manager} classes (#212)
- Add support for merge request notes deletion (#227)
- Properly handle extra args when listing with all=True (#233)
- Implement pipeline creation API (#237)
- Fix spent_time methods
- Add 'delete source branch' option when creating MR (#241)
- Provide API wrapper for cherry picking commits (#236)
- Stop listing if recursion limit is hit (#234)

6.7.49 v0.19 (2017-02-21)

- Update project.archive() docs
- Support the scope attribute in runners.list()
- Add support for project runners
- Add support for commit creation
- Fix install doc
- Add builds-email and pipelines-email services
- Deploy keys: rework enable/disable
- Document the dynamic aspect of objects
- Add pipeline_events to ProjectHook attrs
- Add due_date attribute to ProjectIssue
- Handle settings.domain_whitelist, partly
- {Project,Group}Member: support expires_at attribute

6.7.50 v0.18 (2016-12-27)

- Fix JIRA service editing for GitLab 8.14+
- Add jira_issue_transition_id to the JIRA service optional fields
- Added support for Snippets (new API in Gitlab 8.15)
- **docs:** update pagination section
- **docs:** artifacts example: open file in wb mode
- **CLI:** ignore empty arguments
- **CLI:** Fix wrong use of arguments
- **docs:** Add doc for snippets
- Fix duplicated data in API docs
- Update known attributes for projects
- sudo: always use strings

6.7.51 v0.17 (2016-12-02)

- README: add badges for pypi and RTD
- Fix ProjectBuild.play (raised error on success)
- Pass kwargs to the object factory
- Add .tox to ignore to respect default tox settings
- Convert response list to single data source for iid requests
- Add support for boards API
- Add support for Gitlab.version()

- Add support for broadcast messages API
- Add support for the notification settings API
- Don't overwrite attributes returned by the server
- Fix bug when retrieving changes for merge request
- Feature: enable / disable the deploy key in a project
- Docs: add a note for python 3.5 for file content update
- ProjectHook: support the token attribute
- Rework the API documentation
- Fix docstring for `http_{username,password}`
- Build managers on demand on `GitlabObject`'s
- API docs: add managers doc in `GitlabObject`'s
- Sphinx ext: factorize the build methods
- Implement `__repr__` for gitlab objects
- Add a 'report a bug' link on doc
- Remove deprecated methods
- Implement merge requests diff support
- Make the manager objects creation more dynamic
- Add support for templates API
- Add attr 'created_at' to `ProjectIssueNote`
- Add attr 'updated_at' to `ProjectIssue`
- CLI: add support for project all -all
- Add support for triggering a new build
- Rework requests arguments (support latest requests release)
- Fix `should_remove_source_branch`

6.7.52 v0.16 (2016-10-16)

- Add the ability to fork to a specific namespace
- JIRA service - add `api_url` to optional attributes
- Fix bug: Missing coma concatenates array values
- docs: branch protection notes
- Create a project in a group
- Add `only_allow_merge_if_build_succeeds` option to project objects
- Add support for -all in CLI
- Fix examples for file modification
- Use the plural `merge_requests` URL everywhere
- Rework travis and tox setup

- Workaround gitlab setup failure in tests
- Add ProjectBuild.erase()
- Implement ProjectBuild.play()

6.7.53 v0.15.1 (2016-10-16)

- docs: improve the pagination section
- Fix and test pagination
- ‘path’ is an existing gitlab attr, don’t use it as method argument

6.7.54 v0.15 (2016-08-28)

- Add a basic HTTP debug method
- Run more tests in travis
- Fix fork creation documentation
- Add more API examples in docs
- Update the ApplicationSettings attributes
- Implement the todo API
- Add sidekiq metrics support
- Move the constants at the gitlab root level
- Remove methods marked as deprecated 7 months ago
- Refactor the Gitlab class
- Remove `_get_list_or_object()` and its tests
- Fix `canGet` attribute (typo)
- Remove unused `ProjectTagReleaseManager` class
- Add support for project services API
- Add support for project pipelines
- Add support for access requests
- Add support for project deployments

6.7.55 v0.14 (2016-08-07)

- Remove ‘next_url’ from kwargs before passing it to the cls constructor.
- List projects under group
- Add support for subscribe and unsubscribe in issues
- Project issue: doc and CLI for (un)subscribe
- Added support for HTTP basic authentication
- Add support for build artifacts and trace

- `-title` is a required argument for `ProjectMilestone`
- Commit status: add optional context url
- Commit status: optional get attrs
- Add support for commit comments
- Issues: add optional listing parameters
- Issues: add missing optional listing parameters
- Project issue: proper update attributes
- Add support for project-issue move
- Update `ProjectLabel` attributes
- Milestone: optional listing attrs
- Add support for namespaces
- Add support for label (un)subscribe
- MR: add (un)subscribe support
- Add `note_events` to project hooks attributes
- Add code examples for a bunch of resources
- Implement user emails support
- Project: add `VISIBILITY_*` constants
- Fix the `Project.archive` call
- Implement archive/unarchive for a projet
- Update `ProjectSnippet` attributes
- Fix `ProjectMember` update
- Implement sharing project with a group
- Implement CLI for project archive/unarchive/share
- Implement runners global API
- Gitlab: add managers for build-related resources
- Implement `ProjectBuild.keep_artifacts`
- Allow to stream the downloads when appropriate
- Groups can be updated
- Replace `Snippet.Content()` with a new `content()` method
- CLI: refactor `_die()`
- Improve commit statuses and comments
- Add support from listing group issues
- Added a new project attribute to enable the container registry.
- Add a contributing section in README
- Add support for global deploy key listing
- Add support for project environments

- MR: get list of changes and commits
- Fix the listing of some resources
- MR: fix updates
- Handle empty messages from server in exceptions
- MR (un)subscribe: don't fail if state doesn't change
- MR merge(): update the object

6.7.56 v0.13 (2016-05-16)

- Add support for MergeRequest validation
- MR: add support for cancel_merge_when_build_succeeds
- MR: add support for closes_issues
- Add “external” parameter for users
- Add deletion support for issues and MR
- Add missing group creation parameters
- Add a Session instance for all HTTP requests
- Enable updates on ProjectIssueNotes
- Add support for Project raw_blob
- Implement project compare
- Implement project contributors
- Drop the next_url attribute when listing
- Remove unnecessary canUpdate property from ProjectIssuesNote
- Add new optional attributes for projects
- Enable deprecation warnings for gitlab only
- Rework merge requests update
- Rework the Gitlab.delete method
- ProjectFile: file_path is required for deletion
- Rename some methods to better match the API URLs
- Deprecate the file_* methods in favor of the files manager
- Implement star/unstar for projects
- Implement list/get licenses
- Manage optional parameters for list() and get()

6.7.57 v0.12.2 (2016-03-19)

- Add new ProjectHook attributes
- Add support for user block/unblock
- Fix GitlabObject creation in `_custom_list`
- Add support for more CLI subcommands
- Add some unit tests for CLI
- Add a coverage tox env
- Define `GitlabObject.as_dict()` to dump object as a dict
- Define `GitlabObject.__eq__()` and `__ne__()` equivalence methods
- Define `UserManager.search()` to search for users
- Define `UserManager.get_by_username()` to get a user by username
- Implement “user search” CLI
- Improve the doc for `UserManager`
- CLI: implement user get-by-username
- Re-implement `_custom_list` in the `Gitlab` class
- Fix the ‘invalid syntax’ error on Python 3.2
- `Gitlab.update()`: use the proper attributes if defined

6.7.58 v0.12.1 (2016-02-03)

- Fix a broken upload to pypi

6.7.59 v0.12 (2016-02-03)

- Improve documentation
- Improve unit tests
- Improve test scripts
- Skip `BaseManager` attributes when encoding to JSON
- Fix the `json()` method for python 3
- Add Travis CI support
- Add a decode method for `ProjectFile`
- Make connection exceptions more explicit
- Fix `ProjectLabel` get and delete
- Implement `ProjectMilestone.issues()`
- `ProjectTag` supports deletion
- Implement setting release info on a tag
- Implement project triggers support

- Implement project variables support
- Add support for application settings
- Fix the ‘password’ requirement for User creation
- Add sudo support
- Fix project update
- Fix Project.tree()
- Add support for project builds

6.7.60 v0.11.1 (2016-01-17)

- Fix discovery of parents object attrs for managers
- Support setting commit status
- Support deletion without getting the object first
- Improve the documentation

6.7.61 v0.11 (2016-01-09)

- functional_tests.sh: support python 2 and 3
- Add a get method for GitlabObject
- CLI: Add the -g short option for –gitlab
- Provide a create method for GitlabObject’s
- Rename the _created attribute _from_api
- More unit tests
- CLI: fix error when arguments are missing (python 3)
- Remove deprecated methods
- Implement managers to get access to resources
- Documentation improvements
- Add fork project support
- Deprecate the “old” Gitlab methods
- Add support for groups search

6.7.62 v0.10 (2015-12-29)

- Implement pagination for list() (#63)
- Fix url when fetching a single MergeRequest
- Add support to update MergeRequestNotes
- API: Provide a Gitlab.from_config method
- setup.py: require requests>=1 (#69)

- Fix deletion of object not using 'id' as ID (#68)
- Fix GET/POST for project files
- Make 'confirm' an optional attribute for user creation
- Python 3 compatibility fixes
- Add support for group members update (#73)

6.7.63 v0.9.2 (2015-07-11)

- CLI: fix the update and delete subcommands (#62)

6.7.64 v0.9.1 (2015-05-15)

- Fix the setup.py script

6.7.65 v0.9 (2015-05-15)

- Implement argparse library for parsing argument on CLI
- Provide unit tests and (a few) functional tests
- Provide PEP8 tests
- Use tox to run the tests
- CLI: provide a `--config-file` option
- Turn the gitlab module into a proper package
- Allow projects to be updated
- Use more pythonic names for some methods
- Deprecate some Gitlab object methods:
 - `raw*` methods should never have been exposed; replace them with `_raw_*` methods
 - `setCredentials` and `setToken` are replaced with `set_credentials` and `set_token`
- Sphinx: don't hardcode the version in `conf.py`

6.7.66 v0.8 (2014-10-26)

- Better python 2.6 and python 3 support
- Timeout support in HTTP requests
- `Gitlab.get()` raised `GitlabListError` instead of `GitlabGetError`
- Support api-objects which don't have id in api response
- Add `ProjectLabel` and `ProjectFile` classes
- Moved url attributes to separate list
- Added list for delete attributes

6.7.67 v0.7 (2014-08-21)

- Fix license classifier in `setup.py`
- Fix encoding error when printing to redirected output
- Fix encoding error when updating with redirected output
- Add support for UserKey listing and deletion
- Add support for branches creation and deletion
- Support `state_event` in ProjectMilestone (#30)
- Support namespace/name for project id (#28)
- Fix handling of boolean values (#22)

6.7.68 v0.6 (2014-01-16)

- IDs can be unicode (#15)
- ProjectMember: constructor should not create a User object
- Add support for extra parameters when listing all projects (#12)
- Projects listing: explicitly define arguments for pagination

6.7.69 v0.5 (2013-12-26)

- Add SSH key for user
- Fix comments
- Add support for project events
- Support creation of projects for users
- Project: add methods for create/update/delete files
- Support projects listing: search, all, owned
- System hooks can't be updated
- Project.archive(): download tarball of the project
- Define new optional attributes for user creation
- Provide constants for access permissions in groups

6.7.70 v0.4 (2013-09-26)

- Fix strings encoding (Closes #6)
- Allow to get a project commit (GitLab 6.1)
- ProjectMergeRequest: fix Note() method
- Gitlab 6.1 methods: diff, blob (commit), tree, blob (project)
- Add support for Gitlab 6.1 group members

6.7.71 v0.3 (2013-08-27)

- Use PRIVATE-TOKEN header for passing the auth token
- provide an AUTHORS file
- cli: support ssl_verify config option
- Add ssl_verify option to Gitlab object. Defaults to True
- Correct url for merge requests API.

6.7.72 v0.2 (2013-08-08)

- provide a pip requirements.txt
- drop some debug statements

6.7.73 v0.1 (2013-07-08)

- Initial release

6.8 Release notes

Prior to version 2.0.0 and GitHub Releases, a summary of changes was maintained in release notes. They are available below for historical purposes. For the list of current releases, including breaking changes, please see the changelog.

6.8.1 Changes from 1.8 to 1.9

- `ProjectMemberManager.all()` and `GroupMemberManager.all()` now return a list of `ProjectMember` and `GroupMember` objects respectively, instead of a list of dicts.

6.8.2 Changes from 1.7 to 1.8

- You can now use the `query_parameters` argument in method calls to define arguments to send to the GitLab server. This allows to avoid conflicts between python-gitlab and GitLab server variables, and allows to use the python reserved keywords as GitLab arguments.

The following examples make the same GitLab request with the 2 syntaxes:

```
projects = gl.projects.list(owned=True, starred=True)
projects = gl.projects.list(query_parameters={'owned': True, 'starred': True})
```

The following example only works with the new parameter:

```
activities = gl.user_activities.list(
    query_parameters={'from': '2019-01-01'},
    all=True)
```

- Additionally the `all` parameter is not sent to the GitLab anymore.

6.8.3 Changes from 1.5 to 1.6

- When python-gitlab detects HTTP redirections from http to https it will raise a `RedirectionError` instead of a cryptic error.

Make sure to use an `https://` protocol in your GitLab URL parameter if the server requires it.

6.8.4 Changes from 1.4 to 1.5

- APIv3 support has been removed. Use the 1.4 release/branch if you need v3 support.
- GitLab EE features are now supported: Geo nodes, issue links, LDAP groups, project/group boards, project mirror pulling, project push rules, EE license configuration, epics.
- The `GetFromListMixin` class has been removed. The `get()` method is not available anymore for the following managers:
 - `UserKeyManager`
 - `DeployKeyManager`
 - `GroupAccessRequestManager`
 - `GroupIssueManager`
 - `GroupProjectManager`
 - `GroupSubgroupManager`
 - `IssueManager`
 - `ProjectCommitStatusManager`
 - `ProjectEnvironmentManager`
 - `ProjectLabelManager`
 - `ProjectPipelineJobManager`
 - `ProjectAccessRequestManager`
 - `TodoManager`
- `ProjectPipelineJob` do not heritate from `ProjectJob` anymore and thus can only be listed.

6.8.5 Changes from 1.3 to 1.4

- 1.4 is the last release supporting the v3 API, and the related code will be removed in the 1.5 version.

If you are using a Gitlab server version that does not support the v4 API you can:

- upgrade the server (recommended)
- make sure to use version 1.4 of python-gitlab (`pip install python-gitlab==1.4`)

See also the [Switching to GitLab API v4 documentation](#).

- python-gitlab now handles the server rate limiting feature. It will pause for the required time when reaching the limit ([documentation](#))
- The `GetFromListMixin.get()` method is deprecated and will be removed in the next python-gitlab version. The goal of this mixin/method is to provide a way to get an object by looping through a list for GitLab objects that don't support the GET method. The method is [broken](#) and conflicts with the GET method now supported by some GitLab objects.

You can implement your own method with something like:

```
def get_from_list(self, id):
    for obj in self.list(as_list=False):
        if obj.get_id() == id:
            return obj
```

- The GroupMemberManager, NamespaceManager and ProjectBoardManager managers now use the GET API from GitLab instead of the GetFromListMixin.get() method.

6.8.6 Changes from 1.2 to 1.3

- gitlab.Gitlab objects can be used as context managers in a with block.

6.8.7 Changes from 1.1 to 1.2

- python-gitlab now respects the *_proxy, REQUESTS_CA_BUNDLE and CURL_CA_BUNDLE environment variables (#352)
- The following deprecated methods and objects have been removed:
 - gitlab.v3.object Key and KeyManager objects: use DeployKey and DeployKeyManager instead
 - gitlab.v3.objects.Project archive_ and unarchive_ methods
 - gitlab.Gitlab credentials_auth, token_auth, set_url, set_token and set_credentials methods. Once a Gitlab object has been created its URL and authentication information cannot be updated: create a new Gitlab object if you need to use new information
- The todo() method raises a GitlabTodoError exception on error

6.8.8 Changes from 1.0.2 to 1.1

- The ProjectUser class doesn't inherit from User anymore, and the GroupProject class doesn't inherit from Project anymore. The Gitlab API doesn't provide the same set of features for these objects, so python-gitlab objects shouldn't try to workaround that.

You can create User or Project objects from ProjectUser and GroupProject objects using the id attribute:

```
for gr_project in group.projects.list():
    # lazy object creation avoids a Gitlab API request
    project = gl.projects.get(gr_project.id, lazy=True)
    project.default_branch = 'develop'
    project.save()
```

6.8.9 Changes from 0.21 to 1.0.0

1.0.0 brings a stable python-gitlab API for the v4 Gitlab API. v3 is still used by default.

v4 is mostly compatible with the v3, but some important changes have been introduced. Make sure to read [Switching to GitLab API v4](#).

The development focus will be v4 from now on. v3 has been deprecated by GitLab and will disappear from python-gitlab at some point.

6.8.10 Changes from 0.20 to 0.21

- Initial support for the v4 API (experimental)

The support for v4 is stable enough to be tested, but some features might be broken. Please report issues to <https://github.com/python-gitlab/python-gitlab/issues/>

Be aware that the python-gitlab API for v4 objects might change in the next releases.

Warning: Consider defining explicitly which API version you want to use in the configuration files or in your `gitlab.Gitlab` instances. The default will change from v3 to v4 soon.

- Several methods have been deprecated in the `gitlab.Gitlab` class:
 - `credentials_auth()` is deprecated and will be removed. Call `auth()`.
 - `token_auth()` is deprecated and will be removed. Call `auth()`.
 - `set_url()` is deprecated, create a new `Gitlab` instance if you need an updated URL.
 - `set_token()` is deprecated, use the `private_token` argument of the `Gitlab` constructor.
 - `set_credentials()` is deprecated, use the `email` and `password` arguments of the `Gitlab` constructor.
- The service listing method (`ProjectServiceManager.list()`) now returns a python list instead of a JSON string.

6.8.11 Changes from 0.19 to 0.20

- The `projects` attribute of `Group` objects is not a list of `Project` objects anymore. It is a `Manager` object giving access to `GroupProject` objects. To get the list of projects use:

```
group.projects.list()
```

Documentation: http://python-gitlab.readthedocs.io/en/stable/gl_objects/groups.html#examples

Related issue: <https://github.com/python-gitlab/python-gitlab/issues/209>

- The `Key` objects are deprecated in favor of the new `DeployKey` objects. They are exactly the same but the name makes more sense.

Documentation: http://python-gitlab.readthedocs.io/en/stable/gl_objects/deploy_keys.html

Related issue: <https://github.com/python-gitlab/python-gitlab/issues/212>

6.9 FAQ

I cannot edit the merge request / issue I've just retrieved It is likely that you used a `MergeRequest`, `GroupMergeRequest`, `Issue` or `GroupIssue` object. These objects cannot be edited. But you can create a new `ProjectMergeRequest` or `ProjectIssue` object to apply changes. For example:

```
issue = gl.issues.list()[0]
project = gl.projects.get(issue.project_id, lazy=True)
editable_issue = project.issues.get(issue.iid, lazy=True)
# you can now edit the object
```

See the *merge requests example* and the *issues examples*.

I get an `AttributeError` when accessing attributes of an object retrieved via a `list()` call. Fetching a list of objects, doesn't always include all attributes in the objects. To retrieve an object with all attributes use a `get()` call.

Example with projects:

```
for projects in gl.projects.list():
    # Retrieve project object with all attributes
    project = gl.projects.get(project.id)
```

How can I clone the repository of a project? python-gitlab doesn't provide an API to clone a project. You have to use a git library or call the git command.

The git URI is exposed in the `ssh_url_to_repo` attribute of `Project` objects.

Example:

```
import subprocess

project = gl.projects.create(data) # or gl.projects.get(project_id)
print(project.attributes) # displays all the attributes
git_url = project.ssh_url_to_repo
subprocess.call(['git', 'clone', git_url])
```

I get an `AttributeError` when accessing attributes after `save()` or `refresh()`. You are most likely trying to access an attribute that was not returned by the server on the second request. Please look at the documentation in *Attributes in updated objects* to see how to avoid this.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

g

- `gitlab`, 134
- `gitlab.base`, 347
- `gitlab.cli`, 349
- `gitlab.config`, 350
- `gitlab.const`, 350
- `gitlab.exceptions`, 350
- `gitlab.mixins`, 365
- `gitlab.utils`, 374
- `gitlab.v4`, 347
- `gitlab.v4.objects`, 143

Symbols

- access-level
 - gitlab-group-access-request-approve command line option, [404](#)
 - gitlab-group-member-create command line option, [440](#)
 - gitlab-group-member-update command line option, [441](#)
 - gitlab-project-access-request-approve command line option, [481](#)
 - gitlab-project-member-create command line option, [553](#)
 - gitlab-project-member-update command line option, [554](#)
 - gitlab-runner-create command line option, [638](#)
 - gitlab-runner-update command line option, [639](#)
- action
 - gitlab-event-list command line option, [392](#)
 - gitlab-project-event-list command line option, [516](#)
 - gitlab-todo-list command line option, [644](#)
 - gitlab-user-event-list command line option, [655](#)
- actions
 - gitlab-project-commit-create command line option, [498](#)
- active
 - gitlab-project-pipeline-schedule-create command line option, [596](#)
 - gitlab-project-pipeline-schedule-update command line option, [598](#)
 - gitlab-runner-create command line option, [638](#)
 - gitlab-runner-update command line option, [639](#)
 - gitlab-user-list command line option, [650](#)
- admin
 - gitlab-user-create command line option, [648](#)
 - gitlab-user-update command line option, [651](#)
- after
 - gitlab-event-list command line option, [392](#)
 - gitlab-project-event-list command line option, [516](#)
 - gitlab-user-event-list command line option, [655](#)
- after-sign-out-path
 - gitlab-application-settings-update command line option, [382](#)
- all
 - gitlab-application-list command line option, [377](#)
 - gitlab-audit-event-list command line option, [383](#)
 - gitlab-broadcast-message-list command line option, [385](#)
 - gitlab-current-user-email-list command line option, [387](#)
 - gitlab-current-user-gpg-key-list command line option, [388](#)
 - gitlab-current-user-key-list command line option, [389](#)
 - gitlab-deploy-key-list command line option, [390](#)
 - gitlab-deploy-token-list command line option, [391](#)
 - gitlab-dockerfile-list command line option, [392](#)
 - gitlab-event-list command line option, [392](#)
 - gitlab-feature-list command line option, [393](#)
 - gitlab-geo-node-list command line option, [395](#)
 - gitlab-gitignore-list command line option, [397](#)
 - gitlab-gitlabciyaml-list command line option, [397](#)
 - gitlab-group-access-request-list

- command line option, [405](#)
- gitlab-group-access-token-list command line option, [406](#)
- gitlab-group-audit-event-list command line option, [406](#)
- gitlab-group-badge-list command line option, [408](#)
- gitlab-group-billable-member-list command line option, [409](#)
- gitlab-group-billable-member-membership-list command line option, [410](#)
- gitlab-group-board-list command line option, [411](#)
- gitlab-group-board-list-list command line option, [413](#)
- gitlab-group-cluster-list command line option, [415](#)
- gitlab-group-custom-attribute-list command line option, [417](#)
- gitlab-group-deploy-token-list command line option, [418](#)
- gitlab-group-descendant-group-list command line option, [419](#)
- gitlab-group-epic-award-emoji-list command line option, [423](#)
- gitlab-group-epic-issue-list command line option, [426](#)
- gitlab-group-epic-list command line option, [421](#)
- gitlab-group-epic-note-award-emoji-list command line option, [430](#)
- gitlab-group-epic-note-list command line option, [428](#)
- gitlab-group-epic-resource-label-event-list command line option, [431](#)
- gitlab-group-hook-list command line option, [434](#)
- gitlab-group-issue-list command line option, [436](#)
- gitlab-group-label-list command line option, [438](#)
- gitlab-group-list command line option, [401](#)
- gitlab-group-member-all-list command line option, [442](#)
- gitlab-group-member-list command line option, [441](#)
- gitlab-group-merge-request-list command line option, [443](#)
- gitlab-group-milestone-list command line option, [445](#)
- gitlab-group-package-list command line option, [448](#)
- gitlab-group-project-list command line option, [450](#)
- gitlab-group-runner-list command line option, [450](#)
- gitlab-group-subgroup-list command line option, [451](#)
- gitlab-group-variable-list command line option, [453](#)
- gitlab-group-wiki-list command line option, [455](#)
- gitlab-hook-list command line option, [456](#)
- gitlab-issue-list command line option, [458](#)
- gitlab-ldap-group-list command line option, [459](#)
- gitlab-license-list command line option, [460](#)
- gitlab-merge-request-list command line option, [462](#)
- gitlab-namespace-list command line option, [462](#)
- gitlab-pages-domain-list command line option, [464](#)
- gitlab-personal-access-token-list command line option, [465](#)
- gitlab-project-access-request-list command line option, [482](#)
- gitlab-project-access-token-list command line option, [483](#)
- gitlab-project-approval-rule-list command line option, [486](#)
- gitlab-project-audit-event-list command line option, [488](#)
- gitlab-project-badge-list command line option, [490](#)
- gitlab-project-board-list command line option, [492](#)
- gitlab-project-board-list-list command line option, [494](#)
- gitlab-project-branch-list command line option, [495](#)
- gitlab-project-cluster-list command line option, [497](#)
- gitlab-project-commit-comment-list command line option, [502](#)
- gitlab-project-commit-discussion-list command line option, [503](#)
- gitlab-project-commit-list command line option, [500](#)
- gitlab-project-commit-status-list command line option, [506](#)
- gitlab-project-custom-attribute-list command line option, [507](#)
- gitlab-project-deploy-token-list command line option, [509](#)

- gitlab-project-deployment-list command line option, [510](#)
- gitlab-project-deployment-merge-request-list command line option, [513](#)
- gitlab-project-environment-list command line option, [514](#)
- gitlab-project-event-list command line option, [516](#)
- gitlab-project-fork-list command line option, [521](#)
- gitlab-project-hook-list command line option, [523](#)
- gitlab-project-issue-award-emoji-list command line option, [533](#)
- gitlab-project-issue-discussion-list command line option, [534](#)
- gitlab-project-issue-link-list command line option, [537](#)
- gitlab-project-issue-list command line option, [527](#)
- gitlab-project-issue-note-award-emoji-list command line option, [541](#)
- gitlab-project-issue-note-list command line option, [538](#)
- gitlab-project-issue-resource-label-event-list command line option, [542](#)
- gitlab-project-issue-resource-milestone-event-list command line option, [543](#)
- gitlab-project-issue-resource-state-event-list command line option, [544](#)
- gitlab-project-job-list command line option, [546](#)
- gitlab-project-key-list command line option, [549](#)
- gitlab-project-label-list command line option, [551](#)
- gitlab-project-list command line option, [472](#)
- gitlab-project-member-all-list command line option, [555](#)
- gitlab-project-member-list command line option, [554](#)
- gitlab-project-merge-request-approval-rule-list command line option, [567](#)
- gitlab-project-merge-request-award-emoji-list command line option, [570](#)
- gitlab-project-merge-request-diff-list command line option, [571](#)
- gitlab-project-merge-request-discussion-list command line option, [572](#)
- gitlab-project-merge-request-list command line option, [560](#)
- gitlab-project-merge-request-note-award-emoji-list command line option, [578](#)
- gitlab-project-merge-request-note-list command line option, [576](#)
- gitlab-project-merge-request-pipeline-list command line option, [579](#)
- gitlab-project-merge-request-resource-label-event-list command line option, [580](#)
- gitlab-project-merge-request-resource-milestone-event-list command line option, [581](#)
- gitlab-project-merge-request-resource-state-event-list command line option, [582](#)
- gitlab-project-merge-train-list command line option, [583](#)
- gitlab-project-milestone-list command line option, [585](#)
- gitlab-project-note-list command line option, [586](#)
- gitlab-project-package-file-list command line option, [590](#)
- gitlab-project-package-list command line option, [589](#)
- gitlab-project-pages-domain-list command line option, [591](#)
- gitlab-project-pipeline-bridge-list command line option, [595](#)
- gitlab-project-pipeline-job-list command line option, [595](#)
- gitlab-project-pipeline-list command line option, [594](#)
- gitlab-project-pipeline-schedule-list command line option, [597](#)
- gitlab-project-pipeline-variable-list command line option, [601](#)
- gitlab-project-protected-branch-list command line option, [603](#)
- gitlab-project-protected-tag-list command line option, [604](#)
- gitlab-project-registry-repository-list command line option, [607](#)
- gitlab-project-registry-tag-list command line option, [609](#)
- gitlab-project-release-link-list command line option, [613](#)
- gitlab-project-release-list command line option, [611](#)
- gitlab-project-remote-mirror-list command line option, [614](#)
- gitlab-project-runner-list command line option, [616](#)
- gitlab-project-service-list command line option, [617](#)
- gitlab-project-snippet-award-emoji-list command line option, [622](#)
- gitlab-project-snippet-discussion-list command line option, [623](#)

gitlab-project-snippet-list command line option, [619](#)
gitlab-project-snippet-note-award-emoji-list command line option, [629](#)
gitlab-project-snippet-note-list command line option, [627](#)
gitlab-project-tag-list command line option, [631](#)
gitlab-project-trigger-list command line option, [632](#)
gitlab-project-user-list command line option, [633](#)
gitlab-project-variable-list command line option, [635](#)
gitlab-project-wiki-list command line option, [637](#)
gitlab-runner-job-list command line option, [640](#)
gitlab-runner-list command line option, [639](#)
gitlab-snippet-list command line option, [642](#)
gitlab-starred-project-list command line option, [644](#)
gitlab-todo-list command line option, [645](#)
gitlab-topic-list command line option, [646](#)
gitlab-user-activities-list command line option, [652](#)
gitlab-user-custom-attribute-list command line option, [653](#)
gitlab-user-email-list command line option, [655](#)
gitlab-user-event-list command line option, [655](#)
gitlab-user-gpg-key-list command line option, [657](#)
gitlab-user-impersonation-token-list command line option, [658](#)
gitlab-user-key-list command line option, [660](#)
gitlab-user-list command line option, [650](#)
gitlab-user-membership-list command line option, [661](#)
gitlab-user-project-list command line option, [664](#)
gitlab-variable-list command line option, [665](#)
--all-available
gitlab-group-descendant-group-list command line option, [419](#)
gitlab-group-list command line option, [400](#)
gitlab-group-subgroup-list command line option, [451](#)
--allow-local-requests-from-hooks-and-services gitlab-application-settings-update command line option, [382](#)
--allow-local-requests-from-system-hooks gitlab-application-settings-update command line option, [383](#)
--allow-local-requests-from-web-hooks-and-services gitlab-application-settings-update command line option, [383](#)
--allow-maintainer-to-push gitlab-project-merge-request-create command line option, [558](#)
gitlab-project-merge-request-update command line option, [564](#)
--allow-merge-on-skipped-pipeline gitlab-project-create command line option, [467](#)
gitlab-project-update command line option, [478](#)
--allowed-to-merge gitlab-project-protected-branch-create command line option, [602](#)
--allowed-to-push gitlab-project-protected-branch-create command line option, [602](#)
--allowed-to-unprotect gitlab-project-protected-branch-create command line option, [602](#)
--analytics-access-level gitlab-project-create command line option, [467](#)
gitlab-project-update command line option, [478](#)
--api-version gitlab command line option, [376](#)
--approval-project-rule-id gitlab-project-merge-request-approval-rule-create command line option, [566](#)
--approval-rule-id gitlab-project-merge-request-approval-rule-delete command line option, [567](#)
gitlab-project-merge-request-approval-rule-update command line option, [568](#)
--approvals-before-merge gitlab-project-approval-update command line option, [484](#)
gitlab-project-create command line option, [467](#)
gitlab-project-update command line option, [478](#)
--approvals-required gitlab-project-approval-rule-create command line option, [485](#)

gitlab-project-merge-request-approval-rule-create line option, 610
 command line option, 566
 gitlab-project-merge-request-approval-rule-update line option, 568
 command line option, 568
 gitlab-project-merge-request-approval-update gitlab-group-merge-request-list command
 command line option, 565 line option, 443
 gitlab-issue-list command line option, 457
 gitlab-merge-request-list command line
 option, 461
 gitlab-project-deployment-merge-request-list
 command line option, 512
 gitlab-project-issue-create command
 line option, 525
 gitlab-project-issue-list command line
 option, 527
 gitlab-project-issue-update command
 line option, 531
 gitlab-project-merge-request-create
 command line option, 558
 gitlab-project-merge-request-list
 command line option, 560
 gitlab-project-merge-request-update
 command line option, 564
 --approved-by-ids
 gitlab-group-merge-request-list command
 line option, 443
 gitlab-merge-request-list command line
 option, 461
 gitlab-project-deployment-merge-request-list
 command line option, 512
 gitlab-project-merge-request-list
 command line option, 560
 --approver-ids
 gitlab-group-merge-request-list command
 line option, 443
 gitlab-merge-request-list command line
 option, 461
 gitlab-project-deployment-merge-request-list
 command line option, 512
 gitlab-project-merge-request-list
 command line option, 560
 --archived
 gitlab-group-project-list command line
 option, 449
 gitlab-project-fork-list command line
 option, 520
 gitlab-project-list command line option, 471
 gitlab-starred-project-list command
 line option, 643
 gitlab-user-project-list command line
 option, 663
 --artifact-path
 gitlab-project-artifact command line
 option, 466
 gitlab-project-artifact-raw command
 line option, 487
 --asset-proxy-allowlist
 gitlab-application-settings-update
 command line option, 382
 --asset-proxy-enabled
 gitlab-application-settings-update
 command line option, 382
 --asset-proxy-url
 gitlab-application-settings-update
 command line option, 382
 --asset-proxy-whitelist
 gitlab-application-settings-update
 command line option, 382
 --assets
 gitlab-project-release-create command

gitlab-project-issue-list command line option, [527](#)
gitlab-project-merge-request-list command line option, [560](#)
gitlab-todo-list command line option, [644](#)
--author-name
gitlab-project-commit-create command line option, [499](#)
gitlab-project-file-create command line option, [518](#)
gitlab-project-file-update command line option, [519](#)
--author-username
gitlab-merge-request-list command line option, [461](#)
gitlab-project-deployment-merge-request-list command line option, [512](#)
--auto-cancel-pending-pipelines
gitlab-project-create command line option, [468](#)
gitlab-project-update command line option, [478](#)
--auto-devops-deploy-strategy
gitlab-project-create command line option, [468](#)
gitlab-project-update command line option, [478](#)
--auto-devops-enabled
gitlab-group-create command line option, [399](#)
gitlab-group-update command line option, [403](#)
gitlab-project-create command line option, [468](#)
gitlab-project-update command line option, [478](#)
--autoclose-referenced-issues
gitlab-project-create command line option, [468](#)
gitlab-project-update command line option, [478](#)
--avatar
gitlab-group-create command line option, [399](#)
gitlab-group-update command line option, [403](#)
gitlab-project-create command line option, [468](#)
gitlab-project-update command line option, [478](#)
gitlab-topic-create command line option, [645](#)
gitlab-topic-update command line option, [646](#)
gitlab-user-create command line option, [648](#)
gitlab-user-update command line option, [652](#)
--before
gitlab-event-list command line option, [392](#)
gitlab-project-event-list command line option, [516](#)
gitlab-user-event-list command line option, [655](#)
--bio
gitlab-user-create command line option, [648](#)
gitlab-user-update command line option, [651](#)
--blocked
gitlab-user-list command line option, [650](#)
--board-id
gitlab-group-board-list-create command line option, [412](#)
gitlab-group-board-list-delete command line option, [412](#)
gitlab-group-board-list-get command line option, [413](#)
gitlab-group-board-list-list command line option, [413](#)
gitlab-group-board-list-update command line option, [413](#)
gitlab-project-board-list-create command line option, [492](#)
gitlab-project-board-list-delete command line option, [493](#)
gitlab-project-board-list-get command line option, [493](#)
gitlab-project-board-list-list command line option, [493](#)
gitlab-project-board-list-update command line option, [494](#)
--body
gitlab-group-epic-discussion-note-create command line option, [423](#)
gitlab-group-epic-discussion-note-update command line option, [425](#)
gitlab-group-epic-note-create command line option, [427](#)
gitlab-group-epic-note-update command line option, [428](#)
gitlab-project-commit-discussion-create command line option, [503](#)
gitlab-project-commit-discussion-note-create command line option, [504](#)
gitlab-project-commit-discussion-note-update command line option, [505](#)

gitlab-project-issue-discussion-create	option, 468
command line option, 533	gitlab-project-update command line
gitlab-project-issue-discussion-note-create	option, 478
command line option, 534	--build-git-strategy
gitlab-project-issue-discussion-note-update	gitlab-project-create command line
command line option, 536	option, 468
gitlab-project-issue-note-create	gitlab-project-update command line
command line option, 537	option, 478
gitlab-project-issue-note-update	--build-timeout
command line option, 539	gitlab-project-create command line
gitlab-project-merge-request-discussion-create	option, 468
command line option, 571	gitlab-project-update command line
gitlab-project-merge-request-discussion-note-create	option, 478
command line option, 573	--builds-access-level
gitlab-project-merge-request-discussion-note-update	gitlab-project-create command line
command line option, 575	option, 468
gitlab-project-merge-request-note-create	gitlab-project-update command line
command line option, 575	option, 478
gitlab-project-merge-request-note-update	--builds-enabled
command line option, 577	gitlab-user-project-create command line
gitlab-project-snippet-discussion-create	option, 662
command line option, 622	--can-create-group
gitlab-project-snippet-discussion-note-create	gitlab-user-create command line option,
command line option, 624	648
gitlab-project-snippet-discussion-note-update	gitlab-user-update command line option,
command line option, 625	651
gitlab-project-snippet-note-create	--can-push
command line option, 626	gitlab-project-key-create command line
gitlab-project-snippet-note-update	option, 548
command line option, 627	gitlab-project-key-update command line
--branch	option, 549
gitlab-project-branch-create command	--certificate
line option, 494	gitlab-project-pages-domain-create
gitlab-project-commit-cherry-pick	command line option, 590
command line option, 498	gitlab-project-pages-domain-update
gitlab-project-commit-create command	command line option, 592
line option, 498	--ci-config-path
gitlab-project-commit-revert command	gitlab-project-create command line
line option, 501	option, 468
gitlab-project-file-create command line	gitlab-project-update command line
option, 517	option, 478
gitlab-project-file-delete command line	--ci-default-git-depth
option, 518	gitlab-project-update command line
gitlab-project-file-update command line	option, 478
option, 519	--ci-forward-deployment-enabled
gitlab-project-update-submodule command	gitlab-project-update command line
line option, 480	option, 479
--branch-name-regex	--close-issue
gitlab-project-push-rules-create	gitlab-group-notification-settings-update
command line option, 605	command line option, 447
gitlab-project-push-rules-update	gitlab-notification-settings-update
command line option, 606	command line option, 463
--build-coverage-regex	gitlab-project-notification-settings-update
gitlab-project-create command line	command line option, 588

```
--close-merge-request
  gitlab-group-notification-settings-update
    command line option, 448
  gitlab-notification-settings-update
    command line option, 464
  gitlab-project-notification-settings-update
    command line option, 588
--cn
  gitlab-group-add-ldap-group-link
    command line option, 398
  gitlab-group-delete-ldap-group-link
    command line option, 399
--code-owner-approval-required
  gitlab-project-protected-branch-create
    command line option, 602
--color
  gitlab-broadcast-message-create command
    line option, 384
  gitlab-broadcast-message-update command
    line option, 385
  gitlab-group-label-create command line
    option, 437
  gitlab-group-label-update command line
    option, 439
  gitlab-project-label-create command
    line option, 550
  gitlab-project-label-update command
    line option, 552
--color-scheme-id
  gitlab-user-create command line option,
    648
  gitlab-user-update command line option,
    652
--commit-id
  gitlab-project-commit-comment-create
    command line option, 501
  gitlab-project-commit-comment-list
    command line option, 502
  gitlab-project-commit-discussion-create
    command line option, 502
  gitlab-project-commit-discussion-get
    command line option, 503
  gitlab-project-commit-discussion-list
    command line option, 503
  gitlab-project-commit-discussion-note-create
    command line option, 504
  gitlab-project-commit-discussion-note-delete
    command line option, 504
  gitlab-project-commit-discussion-note-get
    command line option, 505
  gitlab-project-commit-discussion-note-update
    command line option, 505
  gitlab-project-commit-status-create
    command line option, 506
  gitlab-project-commit-status-list
    command line option, 506
--commit-message
  gitlab-project-commit-create command
    line option, 498
  gitlab-project-file-create command line
    option, 518
  gitlab-project-file-delete command line
    option, 518
  gitlab-project-file-update command line
    option, 519
--commit-message-regex
  gitlab-project-push-rules-create
    command line option, 605
  gitlab-project-push-rules-update
    command line option, 606
--commit-sha
  gitlab-project-update-submodule command
    line option, 480
--confidential
  gitlab-application-create command line
    option, 377
  gitlab-project-issue-create command
    line option, 525
  gitlab-project-issue-update command
    line option, 531
--confidential-issues-events
  gitlab-group-hook-create command line
    option, 432
  gitlab-group-hook-update command line
    option, 434
  gitlab-project-hook-create command line
    option, 522
  gitlab-project-hook-update command line
    option, 523
--confidential-note-events
  gitlab-group-hook-create command line
    option, 433
  gitlab-group-hook-update command line
    option, 435
--config-file
  gitlab command line option, 376
--container-expiration-policy-attributes
  gitlab-project-create command line
    option, 468
  gitlab-project-update command line
    option, 479
--container-registry-enabled
  gitlab-project-create command line
    option, 468
  gitlab-project-update command line
    option, 479
--container-registry-token-expire-delay
  gitlab-application-settings-update
```

- command line option, [382](#)
- content
 - gitlab-group-wiki-create command line option, [454](#)
 - gitlab-group-wiki-update command line option, [455](#)
 - gitlab-project-file-create command line option, [518](#)
 - gitlab-project-file-update command line option, [519](#)
 - gitlab-project-snippet-create command line option, [619](#)
 - gitlab-project-snippet-update command line option, [620](#)
 - gitlab-project-wiki-create command line option, [636](#)
 - gitlab-project-wiki-update command line option, [637](#)
 - gitlab-snippet-create command line option, [641](#)
 - gitlab-snippet-update command line option, [642](#)
- context
 - gitlab-project-commit-status-create command line option, [506](#)
- coverage
 - gitlab-project-commit-status-create command line option, [506](#)
- create-access-level
 - gitlab-project-protected-tag-create command line option, [603](#)
- created-after
 - gitlab-audit-event-list command line option, [383](#)
 - gitlab-group-audit-event-list command line option, [406](#)
 - gitlab-group-issue-list command line option, [436](#)
 - gitlab-group-merge-request-list command line option, [443](#)
 - gitlab-issue-list command line option, [458](#)
 - gitlab-merge-request-list command line option, [461](#)
 - gitlab-project-audit-event-list command line option, [488](#)
 - gitlab-project-deployment-merge-request-list command line option, [512](#)
 - gitlab-project-issue-list command line option, [527](#)
 - gitlab-project-merge-request-list command line option, [559](#)
- created-at
 - gitlab-application-settings-update command line option, [381](#)
- gitlab-group-epic-discussion-note-create command line option, [423](#)
- gitlab-group-epic-note-create command line option, [427](#)
- gitlab-project-commit-discussion-create command line option, [503](#)
- gitlab-project-commit-discussion-note-create command line option, [504](#)
- gitlab-project-issue-create command line option, [526](#)
- gitlab-project-issue-discussion-create command line option, [533](#)
- gitlab-project-issue-discussion-note-create command line option, [534](#)
- gitlab-project-issue-note-create command line option, [537](#)
- gitlab-project-merge-request-discussion-create command line option, [571](#)
- gitlab-project-merge-request-discussion-note-create command line option, [573](#)
- gitlab-project-snippet-discussion-create command line option, [622](#)
- gitlab-project-snippet-discussion-note-create command line option, [624](#)
- created-before
 - gitlab-audit-event-list command line option, [383](#)
 - gitlab-group-audit-event-list command line option, [406](#)
 - gitlab-group-issue-list command line option, [436](#)
 - gitlab-group-merge-request-list command line option, [443](#)
 - gitlab-issue-list command line option, [458](#)
 - gitlab-merge-request-list command line option, [461](#)
 - gitlab-project-audit-event-list command line option, [488](#)
 - gitlab-project-deployment-merge-request-list command line option, [512](#)
 - gitlab-project-issue-list command line option, [527](#)
 - gitlab-project-merge-request-list command line option, [559](#)
 - gitlab-project-pipeline-schedule-create command line option, [596](#)
 - gitlab-project-pipeline-schedule-update command line option, [598](#)
- cron-timezone
 - gitlab-project-pipeline-schedule-create command line option, [596](#)

- gitlab-project-pipeline-schedule-update
 - command line option, [598](#)
- custom-attributes
 - gitlab-user-list command line option, [650](#)
- debug
 - gitlab command line option, [376](#)
- default-branch
 - gitlab-project-create command line option, [468](#)
 - gitlab-project-update command line option, [479](#)
 - gitlab-user-project-create command line option, [662](#)
- default-branch-protection
 - gitlab-application-settings-update command line option, [381](#)
 - gitlab-group-create command line option, [399](#)
 - gitlab-group-update command line option, [403](#)
- default-group-visibility
 - gitlab-application-settings-update command line option, [381](#)
- default-project-visibility
 - gitlab-application-settings-update command line option, [381](#)
- default-projects-limit
 - gitlab-application-settings-update command line option, [381](#)
- default-snippet-visibility
 - gitlab-application-settings-update command line option, [381](#)
- deny-delete-tag
 - gitlab-project-push-rules-create command line option, [605](#)
 - gitlab-project-push-rules-update command line option, [606](#)
- deployed-after
 - gitlab-merge-request-list command line option, [462](#)
 - gitlab-project-deployment-merge-request-list command line option, [513](#)
- deployed-before
 - gitlab-merge-request-list command line option, [461](#)
 - gitlab-project-deployment-merge-request-list command line option, [513](#)
- deployment-events
 - gitlab-group-hook-create command line option, [433](#)
 - gitlab-group-hook-update command line option, [435](#)
- deployment-id
 - gitlab-project-deployment-merge-request-list command line option, [512](#)
- description
 - gitlab-application-appearance-update command line option, [378](#)
 - gitlab-group-create command line option, [398](#)
 - gitlab-group-epic-create command line option, [420](#)
 - gitlab-group-epic-update command line option, [421](#)
 - gitlab-group-label-create command line option, [437](#)
 - gitlab-group-label-update command line option, [439](#)
 - gitlab-group-milestone-create command line option, [444](#)
 - gitlab-group-milestone-update command line option, [446](#)
 - gitlab-group-update command line option, [403](#)
 - gitlab-project-commit-status-create command line option, [506](#)
 - gitlab-project-create command line option, [468](#)
 - gitlab-project-export-create command line option, [516](#)
 - gitlab-project-issue-create command line option, [525](#)
 - gitlab-project-issue-update command line option, [530](#)
 - gitlab-project-label-create command line option, [550](#)
 - gitlab-project-label-update command line option, [552](#)
 - gitlab-project-merge-request-create command line option, [558](#)
 - gitlab-project-merge-request-update command line option, [564](#)
 - gitlab-project-milestone-create command line option, [584](#)
 - gitlab-project-milestone-update command line option, [586](#)
 - gitlab-project-pipeline-schedule-create command line option, [596](#)
 - gitlab-project-pipeline-schedule-update command line option, [598](#)
 - gitlab-project-release-create command line option, [610](#)
 - gitlab-project-release-update command line option, [611](#)
 - gitlab-project-snippet-create command line option, [619](#)
 - gitlab-project-snippet-update command line option, [620](#)

gitlab-project-trigger-create command line option, [631](#)
 gitlab-project-trigger-update command line option, [632](#)
 gitlab-project-update command line option, [479](#)
 gitlab-runner-create command line option, [638](#)
 gitlab-runner-update command line option, [639](#)
 gitlab-topic-create command line option, [645](#)
 gitlab-topic-update command line option, [646](#)
 gitlab-user-project-create command line option, [662](#)
 --disable-overriding-approvers-per-merge-request
 gitlab-project-approval-update command line option, [484](#)
 --disabled-oauth-sign-in-sources
 gitlab-application-settings-update command line option, [381](#)
 --discussion-id
 gitlab-group-epic-discussion-note-create command line option, [423](#)
 gitlab-group-epic-discussion-note-delete command line option, [424](#)
 gitlab-group-epic-discussion-note-get command line option, [424](#)
 gitlab-group-epic-discussion-note-update command line option, [425](#)
 gitlab-project-commit-discussion-note-create command line option, [504](#)
 gitlab-project-commit-discussion-note-delete command line option, [504](#)
 gitlab-project-commit-discussion-note-get command line option, [505](#)
 gitlab-project-commit-discussion-note-update command line option, [505](#)
 gitlab-project-issue-discussion-note-create command line option, [534](#)
 gitlab-project-issue-discussion-note-delete command line option, [535](#)
 gitlab-project-issue-discussion-note-get command line option, [535](#)
 gitlab-project-issue-discussion-note-update command line option, [536](#)
 gitlab-project-merge-request-discussion-note-create command line option, [573](#)
 gitlab-project-merge-request-discussion-note-delete command line option, [574](#)
 gitlab-project-merge-request-discussion-note-get command line option, [574](#)
 gitlab-project-merge-request-discussion-note-update command line option, [574](#)
 gitlab-project-snippet-discussion-note-create command line option, [624](#)
 gitlab-project-snippet-discussion-note-delete command line option, [624](#)
 gitlab-project-snippet-discussion-note-get command line option, [625](#)
 gitlab-project-snippet-discussion-note-update command line option, [625](#)
 --discussion-locked
 gitlab-project-issue-update command line option, [531](#)
 gitlab-project-merge-request-update command line option, [564](#)
 --discussion-to-resolve
 gitlab-project-issue-create command line option, [526](#)
 --domain
 gitlab-group-cluster-create command line option, [414](#)
 gitlab-group-cluster-update command line option, [415](#)
 gitlab-project-cluster-create command line option, [496](#)
 gitlab-project-cluster-update command line option, [497](#)
 gitlab-project-pages-domain-create command line option, [590](#)
 gitlab-project-pages-domain-delete command line option, [591](#)
 gitlab-project-pages-domain-get command line option, [591](#)
 gitlab-project-pages-domain-update command line option, [592](#)
 --domain-allowlist
 gitlab-application-settings-update command line option, [381](#)
 --domain-blacklist
 gitlab-application-settings-update command line option, [381](#)
 --domain-blacklist-enabled
 gitlab-application-settings-update command line option, [381](#)
 --domain-denylist
 gitlab-application-settings-update command line option, [381](#)
 --domain-denylist-enabled
 gitlab-application-settings-update command line option, [381](#)
 --domain-whitelist
 gitlab-application-settings-update command line option, [381](#)
 --dsa-key-restriction
 gitlab-application-settings-update

- command line option, [382](#)
- due-date
 - gitlab-group-milestone-create command line option, [444](#)
 - gitlab-group-milestone-update command line option, [446](#)
 - gitlab-project-issue-create command line option, [526](#)
 - gitlab-project-issue-update command line option, [531](#)
 - gitlab-project-milestone-create command line option, [584](#)
 - gitlab-project-milestone-update command line option, [586](#)
- duration
 - gitlab-project-issue-add-spent-time command line option, [525](#)
 - gitlab-project-issue-time-estimate command line option, [529](#)
 - gitlab-project-merge-request-add-spent-time-encoding command line option, [555](#)
 - gitlab-project-merge-request-time-estimate command line option, [562](#)
- ecdsa-key-restriction
 - gitlab-application-settings-update command line option, [382](#)
- ed25519-key-restriction
 - gitlab-application-settings-update command line option, [382](#)
- email
 - gitlab-current-user-email-create command line option, [386](#)
 - gitlab-user-create command line option, [648](#)
 - gitlab-user-email-create command line option, [654](#)
 - gitlab-user-update command line option, [651](#)
- email-header-and-footer-enabled
 - gitlab-application-appearance-update command line option, [379](#)
- emails-disabled
 - gitlab-group-create command line option, [399](#)
 - gitlab-group-update command line option, [403](#)
 - gitlab-project-create command line option, [468](#)
 - gitlab-project-update command line option, [479](#)
- emoji
 - gitlab-current-user-status-update command line option, [390](#)
- enable-ssl-verification
 - gitlab-group-hook-create command line option, [433](#)
 - gitlab-group-hook-update command line option, [435](#)
 - gitlab-project-hook-create command line option, [522](#)
 - gitlab-project-hook-update command line option, [524](#)
- enabled
 - gitlab-geo-node-update command line option, [396](#)
 - gitlab-group-cluster-create command line option, [414](#)
 - gitlab-project-cluster-create command line option, [496](#)
 - gitlab-project-remote-mirror-create command line option, [614](#)
 - gitlab-project-remote-mirror-update command line option, [615](#)
 - gitlab-project-file-create command line option, [518](#)
 - gitlab-project-file-update command line option, [519](#)
- end-date
 - gitlab-group-epic-create command line option, [420](#)
 - gitlab-group-epic-update command line option, [421](#)
- ends-at
 - gitlab-broadcast-message-create command line option, [384](#)
 - gitlab-broadcast-message-update command line option, [385](#)
- enforce-terms
 - gitlab-application-settings-update command line option, [382](#)
- entity-id
 - gitlab-audit-event-list command line option, [383](#)
- entity-type
 - gitlab-audit-event-list command line option, [383](#)
- environment
 - gitlab-merge-request-list command line option, [461](#)
 - gitlab-project-deployment-create command line option, [509](#)
 - gitlab-project-deployment-list command line option, [510](#)
 - gitlab-project-deployment-merge-request-list command line option, [513](#)
- environment-scope
 - gitlab-group-cluster-create command

```

    line option, 414
gitlab-group-cluster-update command
    line option, 416
gitlab-project-cluster-create command
    line option, 496
gitlab-project-cluster-update command
    line option, 498
gitlab-project-variable-create command
    line option, 634
gitlab-project-variable-update command
    line option, 635
--epic-id
    gitlab-group-epic-resource-label-event-get
        command line option, 430
    gitlab-group-epic-resource-label-event-list
        command line option, 431
--epic-iid
    gitlab-group-epic-award-emoji-create
        command line option, 422
    gitlab-group-epic-award-emoji-delete
        command line option, 422
    gitlab-group-epic-award-emoji-get
        command line option, 422
    gitlab-group-epic-award-emoji-list
        command line option, 423
    gitlab-group-epic-discussion-note-create
        command line option, 423
    gitlab-group-epic-discussion-note-delete
        command line option, 424
    gitlab-group-epic-discussion-note-get
        command line option, 424
    gitlab-group-epic-discussion-note-update
        command line option, 424
    gitlab-group-epic-issue-create command
        line option, 425
    gitlab-group-epic-issue-delete command
        line option, 425
    gitlab-group-epic-issue-list command
        line option, 426
    gitlab-group-epic-issue-update command
        line option, 426
    gitlab-group-epic-note-award-emoji-create
        command line option, 429
    gitlab-group-epic-note-award-emoji-delete
        command line option, 429
    gitlab-group-epic-note-award-emoji-get
        command line option, 429
    gitlab-group-epic-note-award-emoji-list
        command line option, 430
    gitlab-group-epic-note-create command
        line option, 427
    gitlab-group-epic-note-delete command
        line option, 427
    gitlab-group-epic-note-get command line
        option, 427
    gitlab-group-epic-note-list command
        line option, 428
    gitlab-group-epic-note-update command
        line option, 428
--epic-issue-id
    gitlab-group-epic-issue-delete command
        line option, 425
    gitlab-group-epic-issue-update command
        line option, 426
--exclude-subgroups
    gitlab-group-package-list command line
        option, 448
--expires-at
    gitlab-group-deploy-token-create
        command line option, 417
    gitlab-group-member-create command line
        option, 440
    gitlab-group-member-update command line
        option, 441
    gitlab-group-share command line option,
        401
    gitlab-project-deploy-token-create
        command line option, 508
    gitlab-project-member-create command
        line option, 553
    gitlab-project-member-update command
        line option, 554
    gitlab-project-share command line
        option, 474
    gitlab-user-impersonation-token-create
        command line option, 657
    gitlab-user-personal-access-token-create
        command line option, 661
--extern-uid
    gitlab-user-create command line option,
        648
    gitlab-user-list command line option, 650
    gitlab-user-update command line option,
        651
--external
    gitlab-user-create command line option,
        648
    gitlab-user-list command line option, 650
    gitlab-user-update command line option,
        651
--external-authorization-classification-label
    gitlab-project-create command line
        option, 468
    gitlab-project-update command line
        option, 479
--external-authorization-service-default-label
    gitlab-application-settings-update
        command line option, 382

```

--external-authorization-service-enabled
gitlab-application-settings-update
command line option, [382](#)

--external-authorization-service-timeout
gitlab-application-settings-update
command line option, [382](#)

--external-authorization-service-url
gitlab-application-settings-update
command line option, [382](#)

--external-url
gitlab-project-environment-create
command line option, [513](#)
gitlab-project-environment-update
command line option, [515](#)

--extra-shared-runners-minutes-limit
gitlab-group-create command line option,
[399](#)
gitlab-group-update command line option,
[403](#)

--fancy
gitlab command line option, [376](#)

--favicon
gitlab-application-appearance-update
command line option, [378](#)

--fields
gitlab command line option, [376](#)

--file-name
gitlab-generic-package-download command
line option, [393](#)
gitlab-generic-package-upload command
line option, [394](#)
gitlab-project-snippet-create command
line option, [619](#)
gitlab-project-snippet-update command
line option, [620](#)
gitlab-snippet-create command line
option, [641](#)
gitlab-snippet-update command line
option, [642](#)

--file-name-regex
gitlab-project-push-rules-create
command line option, [605](#)
gitlab-project-push-rules-update
command line option, [606](#)

--file-path
gitlab-project-file-blame command line
option, [517](#)
gitlab-project-file-create command line
option, [517](#)
gitlab-project-file-delete command line
option, [518](#)
gitlab-project-file-get command line
option, [518](#)
gitlab-project-file-raw command line
option, [519](#)
gitlab-project-file-update command line
option, [519](#)

--file-template-project-id
gitlab-application-settings-update
command line option, [382](#)
gitlab-group-update command line option,
[403](#)

--filename
gitlab-project-upload command line
option, [481](#)

--filepath
gitlab-project-release-link-create
command line option, [612](#)
gitlab-project-release-link-update
command line option, [613](#)
gitlab-project-upload command line
option, [481](#)

--files-max-capacity
gitlab-geo-node-update command line
option, [396](#)

--first-day-of-week
gitlab-application-settings-update
command line option, [382](#)

--first-parent
gitlab-project-commit-list command line
option, [500](#)

--font
gitlab-broadcast-message-create command
line option, [384](#)
gitlab-broadcast-message-update command
line option, [385](#)

--footer-message
gitlab-application-appearance-update
command line option, [378](#)

--forked-from-id
gitlab-project-create-fork-relation
command line option, [469](#)

--forking-access-level
gitlab-project-create command line
option, [468](#)
gitlab-project-update command line
option, [479](#)

--format
gitlab-group-wiki-create command line
option, [454](#)
gitlab-group-wiki-update command line
option, [455](#)
gitlab-project-repository-archive
command line option, [472](#)
gitlab-project-wiki-create command line
option, [636](#)
gitlab-project-wiki-update command line
option, [637](#)

```

--from-
  gitlab-project-repository-compare
    command line option, 473
--fullname
  gitlab-license-get command line option,
    459
--geo-node-allowed-ips
  gitlab-application-settings-update
    command line option, 382
--gitlab
  gitlab command line option, 376
--gravatar-enabled
  gitlab-application-settings-update
    command line option, 381
--group-access
  gitlab-group-add-ldap-group-link
    command line option, 398
  gitlab-group-share command line option,
    401
  gitlab-project-share command line
    option, 474
--group-id
  gitlab-group-access-request-approve
    command line option, 404
  gitlab-group-access-request-create
    command line option, 404
  gitlab-group-access-request-delete
    command line option, 404
  gitlab-group-access-request-list
    command line option, 405
  gitlab-group-access-token-create
    command line option, 405
  gitlab-group-access-token-delete
    command line option, 405
  gitlab-group-access-token-list command
    line option, 406
  gitlab-group-audit-event-get command
    line option, 406
  gitlab-group-audit-event-list command
    line option, 406
  gitlab-group-badge-create command line
    option, 407
  gitlab-group-badge-delete command line
    option, 407
  gitlab-group-badge-get command line
    option, 407
  gitlab-group-badge-list command line
    option, 408
  gitlab-group-badge-render command line
    option, 408
  gitlab-group-badge-update command line
    option, 408
  gitlab-group-billable-member-delete
    command line option, 409
  gitlab-group-billable-member-list
    command line option, 409
  gitlab-group-billable-member-membership-list
    command line option, 410
  gitlab-group-board-create command line
    option, 410
  gitlab-group-board-delete command line
    option, 411
  gitlab-group-board-get command line
    option, 411
  gitlab-group-board-list command line
    option, 411
  gitlab-group-board-list-create command
    line option, 412
  gitlab-group-board-list-delete command
    line option, 412
  gitlab-group-board-list-get command
    line option, 413
  gitlab-group-board-list-list command
    line option, 413
  gitlab-group-board-list-update command
    line option, 413
  gitlab-group-board-update command line
    option, 412
  gitlab-group-cluster-create command
    line option, 414
  gitlab-group-cluster-delete command
    line option, 414
  gitlab-group-cluster-get command line
    option, 415
  gitlab-group-cluster-list command line
    option, 415
  gitlab-group-cluster-update command
    line option, 415
  gitlab-group-custom-attribute-delete
    command line option, 416
  gitlab-group-custom-attribute-get
    command line option, 416
  gitlab-group-custom-attribute-list
    command line option, 416
  gitlab-group-deploy-token-create
    command line option, 417
  gitlab-group-deploy-token-delete
    command line option, 417
  gitlab-group-deploy-token-get command
    line option, 418
  gitlab-group-deploy-token-list command
    line option, 418
  gitlab-group-descendant-group-list
    command line option, 419
  gitlab-group-epic-award-emoji-create
    command line option, 422
  gitlab-group-epic-award-emoji-delete
    command line option, 422

```

gitlab-group-epic-award-emoji-get
command line option, [422](#)

gitlab-group-epic-award-emoji-list
command line option, [423](#)

gitlab-group-epic-create command line
option, [420](#)

gitlab-group-epic-delete command line
option, [420](#)

gitlab-group-epic-discussion-note-create
command line option, [423](#)

gitlab-group-epic-discussion-note-delete
command line option, [424](#)

gitlab-group-epic-discussion-note-get
command line option, [424](#)

gitlab-group-epic-discussion-note-update
command line option, [424](#)

gitlab-group-epic-get command line
option, [420](#)

gitlab-group-epic-issue-create command
line option, [425](#)

gitlab-group-epic-issue-delete command
line option, [425](#)

gitlab-group-epic-issue-list command
line option, [426](#)

gitlab-group-epic-issue-update command
line option, [426](#)

gitlab-group-epic-list command line
option, [420](#)

gitlab-group-epic-note-award-emoji-create
command line option, [429](#)

gitlab-group-epic-note-award-emoji-delete
command line option, [429](#)

gitlab-group-epic-note-award-emoji-get
command line option, [429](#)

gitlab-group-epic-note-award-emoji-list
command line option, [430](#)

gitlab-group-epic-note-create command
line option, [427](#)

gitlab-group-epic-note-delete command
line option, [427](#)

gitlab-group-epic-note-get command line
option, [427](#)

gitlab-group-epic-note-list command
line option, [428](#)

gitlab-group-epic-note-update command
line option, [428](#)

gitlab-group-epic-resource-label-event-get
command line option, [430](#)

gitlab-group-epic-resource-label-event-list
command line option, [431](#)

gitlab-group-epic-update command line
option, [421](#)

gitlab-group-export-create command line
option, [431](#)

gitlab-group-export-download command
line option, [431](#)

gitlab-group-export-get command line
option, [432](#)

gitlab-group-hook-create command line
option, [432](#)

gitlab-group-hook-delete command line
option, [433](#)

gitlab-group-hook-get command line
option, [433](#)

gitlab-group-hook-list command line
option, [434](#)

gitlab-group-hook-update command line
option, [434](#)

gitlab-group-import-get command line
option, [435](#)

gitlab-group-issue-list command line
option, [436](#)

gitlab-group-issues-statistics-get
command line option, [437](#)

gitlab-group-label-create command line
option, [437](#)

gitlab-group-label-delete command line
option, [438](#)

gitlab-group-label-get command line
option, [438](#)

gitlab-group-label-list command line
option, [438](#)

gitlab-group-label-subscribe command
line option, [439](#)

gitlab-group-label-unsubscribe command
line option, [439](#)

gitlab-group-label-update command line
option, [439](#)

gitlab-group-member-all-get command
line option, [442](#)

gitlab-group-member-all-list command
line option, [442](#)

gitlab-group-member-create command line
option, [440](#)

gitlab-group-member-delete command line
option, [440](#)

gitlab-group-member-get command line
option, [440](#)

gitlab-group-member-list command line
option, [441](#)

gitlab-group-member-update command line
option, [441](#)

gitlab-group-merge-request-list command
line option, [443](#)

gitlab-group-milestone-create command
line option, [444](#)

gitlab-group-milestone-delete command
line option, [444](#)

```

gitlab-group-milestone-get command line
    option, 445
gitlab-group-milestone-issues command
    line option, 445
gitlab-group-milestone-list command
    line option, 445
gitlab-group-milestone-merge-requests
    command line option, 446
gitlab-group-milestone-update command
    line option, 446
gitlab-group-notification-settings-get
    command line option, 447
gitlab-group-notification-settings-update
    command line option, 447
gitlab-group-package-list command line
    option, 448
gitlab-group-project-list command line
    option, 449
gitlab-group-runner-list command line
    option, 450
gitlab-group-share command line option,
    401
gitlab-group-subgroup-list command line
    option, 451
gitlab-group-transfer command line
    option, 401
gitlab-group-unshare command line
    option, 402
gitlab-group-variable-create command
    line option, 452
gitlab-group-variable-delete command
    line option, 452
gitlab-group-variable-get command line
    option, 452
gitlab-group-variable-list command line
    option, 453
gitlab-group-variable-update command
    line option, 453
gitlab-group-wiki-create command line
    option, 454
gitlab-group-wiki-delete command line
    option, 454
gitlab-group-wiki-get command line
    option, 454
gitlab-group-wiki-list command line
    option, 455
gitlab-group-wiki-update command line
    option, 455
gitlab-project-share command line
    option, 474
gitlab-project-unshare command line
    option, 476
--group-ids
    gitlab-project-approval-rule-create
        command line option, 485
    gitlab-project-merge-request-approval-rule-create
        command line option, 566
    gitlab-project-merge-request-approval-rule-update
        command line option, 568
--group-with-project-templates-id
    gitlab-project-create command line
        option, 468
--header-logo
    gitlab-application-appearance-update
        command line option, 378
--header-message
    gitlab-application-appearance-update
        command line option, 378
--help
    gitlab command line option, 376
    gitlab-application command line option,
        377
    gitlab-application-appearance command
        line option, 378
    gitlab-application-appearance-get
        command line option, 378
    gitlab-application-appearance-update
        command line option, 378
    gitlab-application-create command line
        option, 377
    gitlab-application-delete command line
        option, 377
    gitlab-application-list command line
        option, 377
    gitlab-application-settings command
        line option, 379
    gitlab-application-settings-get command
        line option, 379
    gitlab-application-settings-update
        command line option, 381
    gitlab-audit-event command line option,
        383
    gitlab-audit-event-get command line
        option, 383
    gitlab-audit-event-list command line
        option, 383
    gitlab-broadcast-message command line
        option, 384
    gitlab-broadcast-message-create command
        line option, 384
    gitlab-broadcast-message-delete command
        line option, 384
    gitlab-broadcast-message-get command
        line option, 384
    gitlab-broadcast-message-list command
        line option, 385
    gitlab-broadcast-message-update command
        line option, 385

```

gitlab-current-user command line option, [385](#)
gitlab-current-user-email command line option, [386](#)
gitlab-current-user-email-create command line option, [386](#)
gitlab-current-user-email-delete command line option, [386](#)
gitlab-current-user-email-get command line option, [386](#)
gitlab-current-user-email-list command line option, [387](#)
gitlab-current-user-get command line option, [386](#)
gitlab-current-user-gpg-key command line option, [387](#)
gitlab-current-user-gpg-key-create command line option, [387](#)
gitlab-current-user-gpg-key-delete command line option, [387](#)
gitlab-current-user-gpg-key-get command line option, [388](#)
gitlab-current-user-gpg-key-list command line option, [388](#)
gitlab-current-user-key command line option, [388](#)
gitlab-current-user-key-create command line option, [388](#)
gitlab-current-user-key-delete command line option, [389](#)
gitlab-current-user-key-get command line option, [389](#)
gitlab-current-user-key-list command line option, [389](#)
gitlab-current-user-status command line option, [389](#)
gitlab-current-user-status-get command line option, [390](#)
gitlab-current-user-status-update command line option, [390](#)
gitlab-deploy-key command line option, [390](#)
gitlab-deploy-key-list command line option, [390](#)
gitlab-deploy-token command line option, [391](#)
gitlab-deploy-token-list command line option, [391](#)
gitlab-dockerfile command line option, [391](#)
gitlab-dockerfile-get command line option, [391](#)
gitlab-dockerfile-list command line option, [391](#)
gitlab-event command line option, [392](#)
gitlab-event-list command line option, [392](#)
gitlab-feature command line option, [392](#)
gitlab-feature-delete command line option, [393](#)
gitlab-feature-list command line option, [393](#)
gitlab-generic-package command line option, [393](#)
gitlab-generic-package-download command line option, [393](#)
gitlab-generic-package-upload command line option, [394](#)
gitlab-geo-node command line option, [394](#)
gitlab-geo-node-current-failures command line option, [394](#)
gitlab-geo-node-delete command line option, [394](#)
gitlab-geo-node-get command line option, [395](#)
gitlab-geo-node-list command line option, [395](#)
gitlab-geo-node-repair command line option, [395](#)
gitlab-geo-node-status command line option, [395](#)
gitlab-geo-node-update command line option, [396](#)
gitlab-gitignore command line option, [396](#)
gitlab-gitignore-get command line option, [396](#)
gitlab-gitignore-list command line option, [396](#)
gitlab-gitlabciyaml command line option, [397](#)
gitlab-gitlabciyaml-get command line option, [397](#)
gitlab-gitlabciyaml-list command line option, [397](#)
gitlab-group command line option, [397](#)
gitlab-group-access-request command line option, [403](#)
gitlab-group-access-request-approve command line option, [404](#)
gitlab-group-access-request-create command line option, [404](#)
gitlab-group-access-request-delete command line option, [404](#)
gitlab-group-access-request-list command line option, [404](#)
gitlab-group-access-token command line option, [405](#)
gitlab-group-access-token-create

- command line option, 405
- gitlab-group-access-token-delete
 - command line option, 405
- gitlab-group-access-token-list command
 - line option, 405
- gitlab-group-add-ldap-group-link
 - command line option, 398
- gitlab-group-audit-event command line
 - option, 406
- gitlab-group-audit-event-get command
 - line option, 406
- gitlab-group-audit-event-list command
 - line option, 406
- gitlab-group-badge command line option, 407
- gitlab-group-badge-create command line
 - option, 407
- gitlab-group-badge-delete command line
 - option, 407
- gitlab-group-badge-get command line
 - option, 407
- gitlab-group-badge-list command line
 - option, 408
- gitlab-group-badge-render command line
 - option, 408
- gitlab-group-badge-update command line
 - option, 408
- gitlab-group-billable-member command
 - line option, 409
- gitlab-group-billable-member-delete
 - command line option, 409
- gitlab-group-billable-member-list
 - command line option, 409
- gitlab-group-billable-member-membership
 - command line option, 410
- gitlab-group-billable-member-membership-list
 - command line option, 410
- gitlab-group-board command line option, 410
- gitlab-group-board-create command line
 - option, 410
- gitlab-group-board-delete command line
 - option, 411
- gitlab-group-board-get command line
 - option, 411
- gitlab-group-board-list command line
 - option, 411, 412
- gitlab-group-board-list-create command
 - line option, 412
- gitlab-group-board-list-delete command
 - line option, 412
- gitlab-group-board-list-get command
 - line option, 413
- gitlab-group-board-list-list command
 - line option, 413
- gitlab-group-board-list-update command
 - line option, 413
- gitlab-group-board-update command line
 - option, 412
- gitlab-group-cluster command line
 - option, 414
- gitlab-group-cluster-create command
 - line option, 414
- gitlab-group-cluster-delete command
 - line option, 414
- gitlab-group-cluster-get command line
 - option, 415
- gitlab-group-cluster-list command line
 - option, 415
- gitlab-group-cluster-update command
 - line option, 415
- gitlab-group-create command line option, 398
- gitlab-group-custom-attribute command
 - line option, 416
- gitlab-group-custom-attribute-delete
 - command line option, 416
- gitlab-group-custom-attribute-get
 - command line option, 416
- gitlab-group-custom-attribute-list
 - command line option, 416
- gitlab-group-delete command line option, 399
- gitlab-group-delete-ldap-group-link
 - command line option, 399
- gitlab-group-deploy-token command line
 - option, 417
- gitlab-group-deploy-token-create
 - command line option, 417
- gitlab-group-deploy-token-delete
 - command line option, 417
- gitlab-group-deploy-token-get command
 - line option, 418
- gitlab-group-deploy-token-list command
 - line option, 418
- gitlab-group-descendant-group command
 - line option, 418
- gitlab-group-descendant-group-list
 - command line option, 419
- gitlab-group-epic command line option, 419
- gitlab-group-epic-award-emoji command
 - line option, 421
- gitlab-group-epic-award-emoji-create
 - command line option, 422
- gitlab-group-epic-award-emoji-delete
 - command line option, 422
- gitlab-group-epic-award-emoji-get

- command line option, [422](#)
- gitlab-group-epic-award-emoji-list
 - command line option, [423](#)
- gitlab-group-epic-create command line option, [419](#)
- gitlab-group-epic-delete command line option, [420](#)
- gitlab-group-epic-discussion-note
 - command line option, [423](#)
- gitlab-group-epic-discussion-note-create
 - command line option, [423](#)
- gitlab-group-epic-discussion-note-delete
 - command line option, [424](#)
- gitlab-group-epic-discussion-note-get
 - command line option, [424](#)
- gitlab-group-epic-discussion-note-update
 - command line option, [424](#)
- gitlab-group-epic-get command line option, [420](#)
- gitlab-group-epic-issue command line option, [425](#)
- gitlab-group-epic-issue-create command line option, [425](#)
- gitlab-group-epic-issue-delete command line option, [425](#)
- gitlab-group-epic-issue-list command line option, [426](#)
- gitlab-group-epic-issue-update command line option, [426](#)
- gitlab-group-epic-list command line option, [420](#)
- gitlab-group-epic-note command line option, [426](#)
- gitlab-group-epic-note-award-emoji
 - command line option, [428](#)
- gitlab-group-epic-note-award-emoji-create
 - command line option, [429](#)
- gitlab-group-epic-note-award-emoji-delete
 - command line option, [429](#)
- gitlab-group-epic-note-award-emoji-get
 - command line option, [429](#)
- gitlab-group-epic-note-award-emoji-list
 - command line option, [430](#)
- gitlab-group-epic-note-create command line option, [427](#)
- gitlab-group-epic-note-delete command line option, [427](#)
- gitlab-group-epic-note-get command line option, [427](#)
- gitlab-group-epic-note-list command line option, [428](#)
- gitlab-group-epic-note-update command line option, [428](#)
- gitlab-group-epic-resource-label-event
 - command line option, [430](#)
- gitlab-group-epic-resource-label-event-get
 - command line option, [430](#)
- gitlab-group-epic-resource-label-event-list
 - command line option, [431](#)
- gitlab-group-epic-update command line option, [421](#)
- gitlab-group-export command line option, [431](#)
- gitlab-group-export-create command line option, [431](#)
- gitlab-group-export-download command line option, [431](#)
- gitlab-group-export-get command line option, [432](#)
- gitlab-group-get command line option, [400](#)
- gitlab-group-hook command line option, [432](#)
- gitlab-group-hook-create command line option, [432](#)
- gitlab-group-hook-delete command line option, [433](#)
- gitlab-group-hook-get command line option, [433](#)
- gitlab-group-hook-list command line option, [434](#)
- gitlab-group-hook-update command line option, [434](#)
- gitlab-group-import command line option, [435](#)
- gitlab-group-import-get command line option, [435](#)
- gitlab-group-issue command line option, [435](#)
- gitlab-group-issue-list command line option, [436](#)
- gitlab-group-issues-statistics command line option, [437](#)
- gitlab-group-issues-statistics-get
 - command line option, [437](#)
- gitlab-group-label command line option, [437](#)
- gitlab-group-label-create command line option, [437](#)
- gitlab-group-label-delete command line option, [438](#)
- gitlab-group-label-get command line option, [438](#)
- gitlab-group-label-list command line option, [438](#)
- gitlab-group-label-subscribe command line option, [439](#)
- gitlab-group-label-unsubscribe command line option, [439](#)

gitlab-group-label-update command line option, [439](#)
gitlab-group-ldap-sync command line option, [400](#)
gitlab-group-list command line option, [400](#)
gitlab-group-member command line option, [440](#)
gitlab-group-member-all command line option, [441](#)
gitlab-group-member-all-get command line option, [441](#)
gitlab-group-member-all-list command line option, [442](#)
gitlab-group-member-create command line option, [440](#)
gitlab-group-member-delete command line option, [440](#)
gitlab-group-member-get command line option, [440](#)
gitlab-group-member-list command line option, [441](#)
gitlab-group-member-update command line option, [441](#)
gitlab-group-merge-request command line option, [442](#)
gitlab-group-merge-request-list command line option, [442](#)
gitlab-group-milestone command line option, [444](#)
gitlab-group-milestone-create command line option, [444](#)
gitlab-group-milestone-delete command line option, [444](#)
gitlab-group-milestone-get command line option, [445](#)
gitlab-group-milestone-issues command line option, [445](#)
gitlab-group-milestone-list command line option, [445](#)
gitlab-group-milestone-merge-requests command line option, [446](#)
gitlab-group-milestone-update command line option, [446](#)
gitlab-group-notification-settings command line option, [446](#)
gitlab-group-notification-settings-get command line option, [447](#)
gitlab-group-notification-settings-update command line option, [447](#)
gitlab-group-package command line option, [448](#)
gitlab-group-package-list command line option, [448](#)
gitlab-group-project command line option, [449](#)
gitlab-group-project-list command line option, [449](#)
gitlab-group-runner command line option, [450](#)
gitlab-group-runner-list command line option, [450](#)
gitlab-group-search command line option, [401](#)
gitlab-group-share command line option, [401](#)
gitlab-group-subgroup command line option, [450](#)
gitlab-group-subgroup-list command line option, [451](#)
gitlab-group-transfer command line option, [401](#)
gitlab-group-transfer-project command line option, [402](#)
gitlab-group-unshare command line option, [402](#)
gitlab-group-update command line option, [402](#)
gitlab-group-variable command line option, [451](#)
gitlab-group-variable-create command line option, [452](#)
gitlab-group-variable-delete command line option, [452](#)
gitlab-group-variable-get command line option, [452](#)
gitlab-group-variable-list command line option, [453](#)
gitlab-group-variable-update command line option, [453](#)
gitlab-group-wiki command line option, [453](#)
gitlab-group-wiki-create command line option, [454](#)
gitlab-group-wiki-delete command line option, [454](#)
gitlab-group-wiki-get command line option, [454](#)
gitlab-group-wiki-list command line option, [455](#)
gitlab-group-wiki-update command line option, [455](#)
gitlab-hook command line option, [455](#)
gitlab-hook-create command line option, [456](#)
gitlab-hook-delete command line option, [456](#)
gitlab-hook-get command line option, [456](#)

gitlab-hook-list command line option, [456](#)
gitlab-issue command line option, [457](#)
gitlab-issue-get command line option, [457](#)
gitlab-issue-list command line option, [457](#)
gitlab-issues-statistics command line option, [458](#)
gitlab-issues-statistics-get command line option, [458](#)
gitlab-key command line option, [458](#)
gitlab-key-get command line option, [458](#)
gitlab-ldap-group command line option, [459](#)
gitlab-ldap-group-list command line option, [459](#)
gitlab-license command line option, [459](#)
gitlab-license-get command line option, [459](#)
gitlab-license-list command line option, [460](#)
gitlab-merge-request command line option, [460](#)
gitlab-merge-request-list command line option, [460](#)
gitlab-namespace command line option, [462](#)
gitlab-namespace-get command line option, [462](#)
gitlab-namespace-list command line option, [462](#)
gitlab-notification-settings command line option, [463](#)
gitlab-notification-settings-get command line option, [463](#)
gitlab-notification-settings-update command line option, [463](#)
gitlab-pages-domain command line option, [464](#)
gitlab-pages-domain-list command line option, [464](#)
gitlab-personal-access-token command line option, [464](#)
gitlab-personal-access-token-delete command line option, [464](#)
gitlab-personal-access-token-list command line option, [465](#)
gitlab-project command line option, [465](#)
gitlab-project-access-request command line option, [481](#)
gitlab-project-access-request-approve command line option, [481](#)
gitlab-project-access-request-create command line option, [481](#)
gitlab-project-access-request-delete command line option, [482](#)
gitlab-project-access-request-list command line option, [482](#)
gitlab-project-access-token command line option, [482](#)
gitlab-project-access-token-create command line option, [482](#)
gitlab-project-access-token-delete command line option, [483](#)
gitlab-project-access-token-list command line option, [483](#)
gitlab-project-additional-statistics command line option, [483](#)
gitlab-project-additional-statistics-get command line option, [483](#)
gitlab-project-approval command line option, [484](#)
gitlab-project-approval-get command line option, [484](#)
gitlab-project-approval-rule command line option, [485](#)
gitlab-project-approval-rule-create command line option, [485](#)
gitlab-project-approval-rule-delete command line option, [485](#)
gitlab-project-approval-rule-list command line option, [486](#)
gitlab-project-approval-rule-update command line option, [486](#)
gitlab-project-approval-update command line option, [484](#)
gitlab-project-archive command line option, [465](#)
gitlab-project-artifact command line option, [465](#), [486](#)
gitlab-project-artifact-delete command line option, [486](#)
gitlab-project-artifact-download command line option, [487](#)
gitlab-project-artifact-raw command line option, [487](#)
gitlab-project-artifacts command line option, [466](#)
gitlab-project-audit-event command line option, [487](#)
gitlab-project-audit-event-get command line option, [488](#)
gitlab-project-audit-event-list command line option, [488](#)
gitlab-project-badge command line option, [488](#)
gitlab-project-badge-create command line option, [489](#)
gitlab-project-badge-delete command line option, [489](#)

gitlab-project-badge-get command line option, 489

gitlab-project-badge-list command line option, 490

gitlab-project-badge-render command line option, 490

gitlab-project-badge-update command line option, 490

gitlab-project-board command line option, 491

gitlab-project-board-create command line option, 491

gitlab-project-board-delete command line option, 491

gitlab-project-board-get command line option, 491

gitlab-project-board-list command line option, 492

gitlab-project-board-list-create command line option, 492

gitlab-project-board-list-delete command line option, 493

gitlab-project-board-list-get command line option, 493

gitlab-project-board-list-list command line option, 493

gitlab-project-board-list-update command line option, 494

gitlab-project-board-update command line option, 492

gitlab-project-branch command line option, 494

gitlab-project-branch-create command line option, 494

gitlab-project-branch-delete command line option, 495

gitlab-project-branch-get command line option, 495

gitlab-project-branch-list command line option, 495

gitlab-project-cluster command line option, 496

gitlab-project-cluster-create command line option, 496

gitlab-project-cluster-delete command line option, 496

gitlab-project-cluster-get command line option, 497

gitlab-project-cluster-list command line option, 497

gitlab-project-cluster-update command line option, 497

gitlab-project-commit command line option, 498

gitlab-project-commit-cherry-pick command line option, 498

gitlab-project-commit-comment command line option, 501

gitlab-project-commit-comment-create command line option, 501

gitlab-project-commit-comment-list command line option, 502

gitlab-project-commit-create command line option, 498

gitlab-project-commit-diff command line option, 499

gitlab-project-commit-discussion command line option, 502

gitlab-project-commit-discussion-create command line option, 502

gitlab-project-commit-discussion-get command line option, 503

gitlab-project-commit-discussion-list command line option, 503

gitlab-project-commit-discussion-note command line option, 504

gitlab-project-commit-discussion-note-create command line option, 504

gitlab-project-commit-discussion-note-delete command line option, 504

gitlab-project-commit-discussion-note-get command line option, 505

gitlab-project-commit-discussion-note-update command line option, 505

gitlab-project-commit-get command line option, 499

gitlab-project-commit-list command line option, 499

gitlab-project-commit-merge-requests command line option, 500

gitlab-project-commit-refs command line option, 500

gitlab-project-commit-revert command line option, 501

gitlab-project-commit-signature command line option, 501

gitlab-project-commit-status command line option, 505

gitlab-project-commit-status-create command line option, 506

gitlab-project-commit-status-list command line option, 506

gitlab-project-create command line option, 467

gitlab-project-create-fork-relation command line option, 469

gitlab-project-custom-attribute command line option, 507

gitlab-project-custom-attribute-delete
command line option, [507](#)

gitlab-project-custom-attribute-get
command line option, [507](#)

gitlab-project-custom-attribute-list
command line option, [507](#)

gitlab-project-delete command line
option, [470](#)

gitlab-project-delete-fork-relation
command line option, [470](#)

gitlab-project-delete-merged-branches
command line option, [470](#)

gitlab-project-deploy-token command
line option, [508](#)

gitlab-project-deploy-token-create
command line option, [508](#)

gitlab-project-deploy-token-delete
command line option, [508](#)

gitlab-project-deploy-token-get command
line option, [508](#)

gitlab-project-deploy-token-list
command line option, [509](#)

gitlab-project-deployment command line
option, [509](#)

gitlab-project-deployment-create
command line option, [509](#)

gitlab-project-deployment-get command
line option, [510](#)

gitlab-project-deployment-list command
line option, [510](#)

gitlab-project-deployment-merge-request
command line option, [511](#)

gitlab-project-deployment-merge-request-list
command line option, [512](#)

gitlab-project-deployment-update
command line option, [511](#)

gitlab-project-environment command line
option, [513](#)

gitlab-project-environment-create
command line option, [513](#)

gitlab-project-environment-delete
command line option, [514](#)

gitlab-project-environment-get command
line option, [514](#)

gitlab-project-environment-list command
line option, [514](#)

gitlab-project-environment-stop command
line option, [515](#)

gitlab-project-environment-update
command line option, [515](#)

gitlab-project-event command line
option, [515](#)

gitlab-project-event-list command line
option, [515](#)

gitlab-project-export command line
option, [516](#)

gitlab-project-export-create command
line option, [516](#)

gitlab-project-export-download command
line option, [516](#)

gitlab-project-export-get command line
option, [517](#)

gitlab-project-file command line option,
[517](#)

gitlab-project-file-blame command line
option, [517](#)

gitlab-project-file-create command line
option, [517](#)

gitlab-project-file-delete command line
option, [518](#)

gitlab-project-file-get command line
option, [518](#)

gitlab-project-file-raw command line
option, [519](#)

gitlab-project-file-update command line
option, [519](#)

gitlab-project-fork command line option,
[520](#)

gitlab-project-fork-create command line
option, [520](#)

gitlab-project-fork-list command line
option, [520](#)

gitlab-project-get command line option,
[470](#)

gitlab-project-hook command line option,
[521](#)

gitlab-project-hook-create command line
option, [521](#)

gitlab-project-hook-delete command line
option, [522](#)

gitlab-project-hook-get command line
option, [522](#)

gitlab-project-hook-list command line
option, [523](#)

gitlab-project-hook-update command line
option, [523](#)

gitlab-project-housekeeping command
line option, [470](#)

gitlab-project-import command line
option, [524](#)

gitlab-project-import-get command line
option, [524](#)

gitlab-project-issue command line
option, [524](#)

gitlab-project-issue-add-spent-time
command line option, [524](#)

gitlab-project-issue-award-emoji
command line option, [531](#)

- gitlab-project-issue-award-emoji-create
command line option, [531](#)
- gitlab-project-issue-award-emoji-delete
command line option, [532](#)
- gitlab-project-issue-award-emoji-get
command line option, [532](#)
- gitlab-project-issue-award-emoji-list
command line option, [532](#)
- gitlab-project-issue-closed-by command
line option, [525](#)
- gitlab-project-issue-create command
line option, [525](#)
- gitlab-project-issue-delete command
line option, [526](#)
- gitlab-project-issue-discussion command
line option, [533](#)
- gitlab-project-issue-discussion-create
command line option, [533](#)
- gitlab-project-issue-discussion-get
command line option, [533](#)
- gitlab-project-issue-discussion-list
command line option, [534](#)
- gitlab-project-issue-discussion-note
command line option, [534](#)
- gitlab-project-issue-discussion-note-create
command line option, [534](#)
- gitlab-project-issue-discussion-note-delete
command line option, [535](#)
- gitlab-project-issue-discussion-note-get
command line option, [535](#)
- gitlab-project-issue-discussion-note-update
command line option, [535](#)
- gitlab-project-issue-get command line
option, [526](#)
- gitlab-project-issue-link command line
option, [536](#)
- gitlab-project-issue-link-create
command line option, [536](#)
- gitlab-project-issue-link-delete
command line option, [536](#)
- gitlab-project-issue-link-list command
line option, [537](#)
- gitlab-project-issue-list command line
option, [526](#)
- gitlab-project-issue-move command line
option, [527](#)
- gitlab-project-issue-note command line
option, [537](#)
- gitlab-project-issue-note-award-emoji
command line option, [539](#)
- gitlab-project-issue-note-award-emoji-create
command line option, [539](#)
- gitlab-project-issue-note-award-emoji-delete
command line option, [540](#)
- gitlab-project-issue-note-award-emoji-get
command line option, [540](#)
- gitlab-project-issue-note-award-emoji-list
command line option, [540](#)
- gitlab-project-issue-note-create
command line option, [537](#)
- gitlab-project-issue-note-delete
command line option, [538](#)
- gitlab-project-issue-note-get command
line option, [538](#)
- gitlab-project-issue-note-list command
line option, [538](#)
- gitlab-project-issue-note-update
command line option, [539](#)
- gitlab-project-issue-participants
command line option, [528](#)
- gitlab-project-issue-related-merge-requests
command line option, [528](#)
- gitlab-project-issue-reset-spent-time
command line option, [528](#)
- gitlab-project-issue-reset-time-estimate
command line option, [528](#)
- gitlab-project-issue-resource-label-event
command line option, [541](#)
- gitlab-project-issue-resource-label-event-get
command line option, [541](#)
- gitlab-project-issue-resource-label-event-list
command line option, [541](#)
- gitlab-project-issue-resource-milestone-event
command line option, [542](#)
- gitlab-project-issue-resource-milestone-event-get
command line option, [542](#)
- gitlab-project-issue-resource-milestone-event-list
command line option, [542](#)
- gitlab-project-issue-resource-state-event
command line option, [543](#)
- gitlab-project-issue-resource-state-event-get
command line option, [543](#)
- gitlab-project-issue-resource-state-event-list
command line option, [543](#)
- gitlab-project-issue-subscribe command
line option, [529](#)
- gitlab-project-issue-time-estimate
command line option, [529](#)
- gitlab-project-issue-time-stats command
line option, [529](#)
- gitlab-project-issue-todo command line
option, [530](#)
- gitlab-project-issue-unsubscribe
command line option, [530](#)
- gitlab-project-issue-update command
line option, [530](#)
- gitlab-project-issue-user-agent-detail
command line option, [531](#)

`gitlab-project-issues-statistics`
command line option, [544](#)

`gitlab-project-issues-statistics-get`
command line option, [544](#)

`gitlab-project-job` command line option, [544](#)

`gitlab-project-job-artifact` command line option, [544](#)

`gitlab-project-job-artifacts` command line option, [545](#)

`gitlab-project-job-cancel` command line option, [545](#)

`gitlab-project-job-delete-artifacts`
command line option, [545](#)

`gitlab-project-job-erase` command line option, [545](#)

`gitlab-project-job-get` command line option, [546](#)

`gitlab-project-job-keep-artifacts`
command line option, [546](#)

`gitlab-project-job-list` command line option, [546](#)

`gitlab-project-job-play` command line option, [547](#)

`gitlab-project-job-retry` command line option, [547](#)

`gitlab-project-job-trace` command line option, [547](#)

`gitlab-project-key` command line option, [547](#)

`gitlab-project-key-create` command line option, [548](#)

`gitlab-project-key-delete` command line option, [548](#)

`gitlab-project-key-enable` command line option, [548](#)

`gitlab-project-key-get` command line option, [549](#)

`gitlab-project-key-list` command line option, [549](#)

`gitlab-project-key-update` command line option, [549](#)

`gitlab-project-label` command line option, [550](#)

`gitlab-project-label-create` command line option, [550](#)

`gitlab-project-label-delete` command line option, [550](#)

`gitlab-project-label-get` command line option, [551](#)

`gitlab-project-label-list` command line option, [551](#)

`gitlab-project-label-subscribe` command line option, [551](#)

`gitlab-project-label-unsubscribe`
command line option, [552](#)

`gitlab-project-label-update` command line option, [552](#)

`gitlab-project-languages` command line option, [471](#)

`gitlab-project-list` command line option, [471](#)

`gitlab-project-member` command line option, [552](#)

`gitlab-project-member-all` command line option, [554](#)

`gitlab-project-member-all-get` command line option, [554](#)

`gitlab-project-member-all-list` command line option, [555](#)

`gitlab-project-member-create` command line option, [553](#)

`gitlab-project-member-delete` command line option, [553](#)

`gitlab-project-member-get` command line option, [553](#)

`gitlab-project-member-list` command line option, [554](#)

`gitlab-project-member-update` command line option, [554](#)

`gitlab-project-merge-request` command line option, [555](#)

`gitlab-project-merge-request-add-spent-time`
command line option, [555](#)

`gitlab-project-merge-request-approval`
command line option, [565](#)

`gitlab-project-merge-request-approval-get`
command line option, [565](#)

`gitlab-project-merge-request-approval-rule`
command line option, [565](#)

`gitlab-project-merge-request-approval-rule-create`
command line option, [566](#)

`gitlab-project-merge-request-approval-rule-delete`
command line option, [566](#)

`gitlab-project-merge-request-approval-rule-list`
command line option, [567](#)

`gitlab-project-merge-request-approval-rule-update`
command line option, [567](#)

`gitlab-project-merge-request-approval-state`
command line option, [568](#)

`gitlab-project-merge-request-approval-state-get`
command line option, [568](#)

`gitlab-project-merge-request-approval-update`
command line option, [565](#)

`gitlab-project-merge-request-approve`
command line option, [556](#)

`gitlab-project-merge-request-award-emoji`
command line option, [568](#)

gitlab-project-merge-request-award-emoji-create	gitlab-project-merge-request-note
command line option, 569	command line option, 575
gitlab-project-merge-request-award-emoji-delete	gitlab-project-merge-request-note-award-emoji
command line option, 569	command line option, 577
gitlab-project-merge-request-award-emoji-get	gitlab-project-merge-request-note-award-emoji-create
command line option, 569	command line option, 577
gitlab-project-merge-request-award-emoji-list	gitlab-project-merge-request-note-award-emoji-delete
command line option, 570	command line option, 577
gitlab-project-merge-request-cancel-merge-when-pipeline-fails	gitlab-project-merge-request-note-award-emoji-get
command line option, 556	command line option, 578
gitlab-project-merge-request-changes	gitlab-project-merge-request-note-award-emoji-list
command line option, 556	command line option, 578
gitlab-project-merge-request-closes-issues	gitlab-project-merge-request-note-create
command line option, 557	command line option, 575
gitlab-project-merge-request-commits	gitlab-project-merge-request-note-delete
command line option, 557	command line option, 575
gitlab-project-merge-request-create	gitlab-project-merge-request-note-get
command line option, 557	command line option, 576
gitlab-project-merge-request-delete	gitlab-project-merge-request-note-list
command line option, 558	command line option, 576
gitlab-project-merge-request-diff	gitlab-project-merge-request-note-update
command line option, 570	command line option, 576
gitlab-project-merge-request-diff-get	gitlab-project-merge-request-participants
command line option, 570	command line option, 561
gitlab-project-merge-request-diff-list	gitlab-project-merge-request-pipeline
command line option, 571	command line option, 579
gitlab-project-merge-request-discussion	gitlab-project-merge-request-pipeline-create
command line option, 571	command line option, 579
gitlab-project-merge-request-discussion-create	gitlab-project-merge-request-pipeline-list
command line option, 571	command line option, 579
gitlab-project-merge-request-discussion-get	gitlab-project-merge-request-rebase
command line option, 572	command line option, 561
gitlab-project-merge-request-discussion-list	gitlab-project-merge-request-reset-spent-time
command line option, 572	command line option, 561
gitlab-project-merge-request-discussion-note	gitlab-project-merge-request-reset-time-estimate
command line option, 573	command line option, 562
gitlab-project-merge-request-discussion-note-create	gitlab-project-merge-request-resource-label-event
command line option, 573	command line option, 580
gitlab-project-merge-request-discussion-note-delete	gitlab-project-merge-request-resource-label-event-get
command line option, 573	command line option, 580
gitlab-project-merge-request-discussion-note-get	gitlab-project-merge-request-resource-label-event-list
command line option, 574	command line option, 580
gitlab-project-merge-request-discussion-note-update	gitlab-project-merge-request-resource-milestone-event
command line option, 574	command line option, 581
gitlab-project-merge-request-discussion-update	gitlab-project-merge-request-resource-milestone-event-
command line option, 572	command line option, 581
gitlab-project-merge-request-get	gitlab-project-merge-request-resource-milestone-event-
command line option, 558	command line option, 581
gitlab-project-merge-request-list	gitlab-project-merge-request-resource-state-event
command line option, 559	command line option, 582
gitlab-project-merge-request-merge	gitlab-project-merge-request-resource-state-event-get
command line option, 560	command line option, 582
gitlab-project-merge-request-merge-ref	gitlab-project-merge-request-resource-state-event-list
command line option, 561	command line option, 582

`gitlab-project-merge-request-subscribe`
command line option, [562](#)

`gitlab-project-merge-request-time-estimate`
command line option, [562](#)

`gitlab-project-merge-request-time-stats`
command line option, [563](#)

`gitlab-project-merge-request-todo`
command line option, [563](#)

`gitlab-project-merge-request-unapprove`
command line option, [563](#)

`gitlab-project-merge-request-unsubscribe`
command line option, [563](#)

`gitlab-project-merge-request-update`
command line option, [564](#)

`gitlab-project-merge-train` command line
option, [583](#)

`gitlab-project-merge-train-list` command
line option, [583](#)

`gitlab-project-milestone` command line
option, [583](#)

`gitlab-project-milestone-create` command
line option, [583](#)

`gitlab-project-milestone-delete` command
line option, [584](#)

`gitlab-project-milestone-get` command
line option, [584](#)

`gitlab-project-milestone-issues` command
line option, [584](#)

`gitlab-project-milestone-list` command
line option, [585](#)

`gitlab-project-milestone-merge-requests`
command line option, [585](#)

`gitlab-project-milestone-update` command
line option, [585](#)

`gitlab-project-mirror-pull` command line
option, [472](#)

`gitlab-project-note` command line option,
[586](#)

`gitlab-project-note-get` command line
option, [586](#)

`gitlab-project-note-list` command line
option, [586](#)

`gitlab-project-notification-settings`
command line option, [587](#)

`gitlab-project-notification-settings-get`
command line option, [587](#)

`gitlab-project-notification-settings-update`
command line option, [587](#)

`gitlab-project-package` command line
option, [588](#)

`gitlab-project-package-delete` command
line option, [588](#)

`gitlab-project-package-file` command
line option, [589](#)

`gitlab-project-package-file-delete`
command line option, [589](#)

`gitlab-project-package-file-list`
command line option, [590](#)

`gitlab-project-package-get` command line
option, [588](#)

`gitlab-project-package-list` command
line option, [589](#)

`gitlab-project-pages-domain` command
line option, [590](#)

`gitlab-project-pages-domain-create`
command line option, [590](#)

`gitlab-project-pages-domain-delete`
command line option, [591](#)

`gitlab-project-pages-domain-get` command
line option, [591](#)

`gitlab-project-pages-domain-list`
command line option, [591](#)

`gitlab-project-pages-domain-update`
command line option, [592](#)

`gitlab-project-pipeline` command line
option, [592](#)

`gitlab-project-pipeline-bridge` command
line option, [594](#)

`gitlab-project-pipeline-bridge-list`
command line option, [594](#)

`gitlab-project-pipeline-cancel` command
line option, [592](#)

`gitlab-project-pipeline-create` command
line option, [592](#)

`gitlab-project-pipeline-delete` command
line option, [593](#)

`gitlab-project-pipeline-get` command
line option, [593](#)

`gitlab-project-pipeline-job` command
line option, [595](#)

`gitlab-project-pipeline-job-list`
command line option, [595](#)

`gitlab-project-pipeline-list` command
line option, [593](#)

`gitlab-project-pipeline-retry` command
line option, [594](#)

`gitlab-project-pipeline-schedule`
command line option, [595](#)

`gitlab-project-pipeline-schedule-create`
command line option, [596](#)

`gitlab-project-pipeline-schedule-delete`
command line option, [596](#)

`gitlab-project-pipeline-schedule-get`
command line option, [596](#)

`gitlab-project-pipeline-schedule-list`
command line option, [597](#)

`gitlab-project-pipeline-schedule-play`
command line option, [597](#)

gitlab-project-pipeline-schedule-take-ownership command line option, 597	gitlab-project-registry-repository command line option, 607
gitlab-project-pipeline-schedule-update command line option, 598	gitlab-project-registry-repository-delete command line option, 607
gitlab-project-pipeline-schedule-variable command line option, 598	gitlab-project-registry-repository-list command line option, 607
gitlab-project-pipeline-schedule-variable-create command line option, 598	gitlab-project-registry-tag command line option, 607
gitlab-project-pipeline-schedule-variable-delete command line option, 599	gitlab-project-registry-tag-delete command line option, 608
gitlab-project-pipeline-schedule-variable-update command line option, 599	gitlab-project-registry-tag-delete-in-bulk command line option, 608
gitlab-project-pipeline-test-report command line option, 600	gitlab-project-registry-tag-get command line option, 609
gitlab-project-pipeline-test-report-get command line option, 600	gitlab-project-registry-tag-list command line option, 609
gitlab-project-pipeline-test-report-summary command line option, 600	gitlab-project-release command line option, 609
gitlab-project-pipeline-test-report-summary-get command line option, 600	gitlab-project-release-create command line option, 610
gitlab-project-pipeline-variable command line option, 601	gitlab-project-release-delete command line option, 610
gitlab-project-pipeline-variable-list command line option, 601	gitlab-project-release-get command line option, 610
gitlab-project-protected-branch command line option, 601	gitlab-project-release-link command line option, 611
gitlab-project-protected-branch-create command line option, 601	gitlab-project-release-link-create command line option, 612
gitlab-project-protected-branch-delete command line option, 602	gitlab-project-release-link-delete command line option, 612
gitlab-project-protected-branch-get command line option, 602	gitlab-project-release-link-get command line option, 612
gitlab-project-protected-branch-list command line option, 603	gitlab-project-release-link-list command line option, 613
gitlab-project-protected-tag command line option, 603	gitlab-project-release-link-update command line option, 613
gitlab-project-protected-tag-create command line option, 603	gitlab-project-release-list command line option, 611
gitlab-project-protected-tag-delete command line option, 603	gitlab-project-release-update command line option, 611
gitlab-project-protected-tag-get command line option, 604	gitlab-project-remote-mirror command line option, 614
gitlab-project-protected-tag-list command line option, 604	gitlab-project-remote-mirror-create command line option, 614
gitlab-project-push-rules command line option, 604	gitlab-project-remote-mirror-list command line option, 614
gitlab-project-push-rules-create command line option, 605	gitlab-project-remote-mirror-update command line option, 615
gitlab-project-push-rules-delete command line option, 605	gitlab-project-repository-archive command line option, 472
gitlab-project-push-rules-get command line option, 606	gitlab-project-repository-blob command line option, 473
gitlab-project-push-rules-update command line option, 606	gitlab-project-repository-compare command line option, 473

`gitlab-project-repository-contributors`
command line option, [473](#)

`gitlab-project-repository-raw-blob`
command line option, [473](#)

`gitlab-project-repository-tree` command
line option, [474](#)

`gitlab-project-runner` command line
option, [615](#)

`gitlab-project-runner-create` command
line option, [615](#)

`gitlab-project-runner-delete` command
line option, [615](#)

`gitlab-project-runner-list` command line
option, [616](#)

`gitlab-project-search` command line
option, [474](#)

`gitlab-project-service` command line
option, [616](#)

`gitlab-project-service-available`
command line option, [616](#)

`gitlab-project-service-delete` command
line option, [617](#)

`gitlab-project-service-get` command line
option, [617](#)

`gitlab-project-service-list` command
line option, [617](#)

`gitlab-project-service-update` command
line option, [618](#)

`gitlab-project-share` command line
option, [474](#)

`gitlab-project-snapshot` command line
option, [475](#)

`gitlab-project-snippet` command line
option, [618](#)

`gitlab-project-snippet-award-emoji`
command line option, [620](#)

`gitlab-project-snippet-award-emoji-create`
command line option, [621](#)

`gitlab-project-snippet-award-emoji-delete`
command line option, [621](#)

`gitlab-project-snippet-award-emoji-get`
command line option, [621](#)

`gitlab-project-snippet-award-emoji-list`
command line option, [622](#)

`gitlab-project-snippet-content` command
line option, [618](#)

`gitlab-project-snippet-create` command
line option, [618](#)

`gitlab-project-snippet-delete` command
line option, [619](#)

`gitlab-project-snippet-discussion`
command line option, [622](#)

`gitlab-project-snippet-discussion-create`
command line option, [622](#)

`gitlab-project-snippet-discussion-get`
command line option, [623](#)

`gitlab-project-snippet-discussion-list`
command line option, [623](#)

`gitlab-project-snippet-discussion-note`
command line option, [623](#)

`gitlab-project-snippet-discussion-note-create`
command line option, [624](#)

`gitlab-project-snippet-discussion-note-delete`
command line option, [624](#)

`gitlab-project-snippet-discussion-note-get`
command line option, [624](#)

`gitlab-project-snippet-discussion-note-update`
command line option, [625](#)

`gitlab-project-snippet-get` command line
option, [619](#)

`gitlab-project-snippet-list` command
line option, [619](#)

`gitlab-project-snippet-note` command
line option, [625](#)

`gitlab-project-snippet-note-award-emoji`
command line option, [627](#)

`gitlab-project-snippet-note-award-emoji-create`
command line option, [627](#)

`gitlab-project-snippet-note-award-emoji-delete`
command line option, [628](#)

`gitlab-project-snippet-note-award-emoji-get`
command line option, [628](#)

`gitlab-project-snippet-note-award-emoji-list`
command line option, [629](#)

`gitlab-project-snippet-note-create`
command line option, [625](#)

`gitlab-project-snippet-note-delete`
command line option, [626](#)

`gitlab-project-snippet-note-get` command
line option, [626](#)

`gitlab-project-snippet-note-list`
command line option, [626](#)

`gitlab-project-snippet-note-update`
command line option, [627](#)

`gitlab-project-snippet-update` command
line option, [620](#)

`gitlab-project-snippet-user-agent-detail`
command line option, [620](#)

`gitlab-project-star` command line option,
[475](#)

`gitlab-project-storage` command line
option, [629](#)

`gitlab-project-storage-get` command line
option, [629](#)

`gitlab-project-tag` command line option,
[630](#)

`gitlab-project-tag-create` command line
option, [630](#)

gitlab-project-tag-delete command line option, [630](#)
gitlab-project-tag-get command line option, [630](#)
gitlab-project-tag-list command line option, [631](#)
gitlab-project-transfer command line option, [475](#)
gitlab-project-transfer-project command line option, [475](#)
gitlab-project-trigger command line option, [631](#)
gitlab-project-trigger-create command line option, [631](#)
gitlab-project-trigger-delete command line option, [631](#)
gitlab-project-trigger-get command line option, [632](#)
gitlab-project-trigger-list command line option, [632](#)
gitlab-project-trigger-pipeline command line option, [476](#)
gitlab-project-trigger-update command line option, [632](#)
gitlab-project-unarchive command line option, [476](#)
gitlab-project-unshare command line option, [476](#)
gitlab-project-unstar command line option, [476](#)
gitlab-project-update command line option, [478](#)
gitlab-project-update-submodule command line option, [480](#)
gitlab-project-upload command line option, [481](#)
gitlab-project-user command line option, [633](#)
gitlab-project-user-list command line option, [633](#)
gitlab-project-variable command line option, [633](#)
gitlab-project-variable-create command line option, [633](#)
gitlab-project-variable-delete command line option, [634](#)
gitlab-project-variable-get command line option, [634](#)
gitlab-project-variable-list command line option, [634](#)
gitlab-project-variable-update command line option, [635](#)
gitlab-project-wiki command line option, [635](#)
gitlab-project-wiki-create command line option, [635](#)
gitlab-project-wiki-delete command line option, [636](#)
gitlab-project-wiki-get command line option, [636](#)
gitlab-project-wiki-list command line option, [636](#)
gitlab-project-wiki-update command line option, [637](#)
gitlab-runner command line option, [637](#)
gitlab-runner-all command line option, [637](#)
gitlab-runner-create command line option, [638](#)
gitlab-runner-delete command line option, [638](#)
gitlab-runner-get command line option, [638](#)
gitlab-runner-job command line option, [640](#)
gitlab-runner-job-list command line option, [640](#)
gitlab-runner-list command line option, [639](#)
gitlab-runner-update command line option, [639](#)
gitlab-runner-verify command line option, [640](#)
gitlab-snippet command line option, [640](#)
gitlab-snippet-content command line option, [641](#)
gitlab-snippet-create command line option, [641](#)
gitlab-snippet-delete command line option, [641](#)
gitlab-snippet-get command line option, [641](#)
gitlab-snippet-list command line option, [642](#)
gitlab-snippet-public command line option, [642](#)
gitlab-snippet-update command line option, [642](#)
gitlab-snippet-user-agent-detail command line option, [643](#)
gitlab-starred-project command line option, [643](#)
gitlab-starred-project-list command line option, [643](#)
gitlab-todo command line option, [644](#)
gitlab-todo-delete command line option, [644](#)
gitlab-todo-list command line option, [644](#)

gitlab-todo-mark-all-as-done command line option, [645](#)
gitlab-todo-mark-as-done command line option, [645](#)
gitlab-topic command line option, [645](#)
gitlab-topic-create command line option, [645](#)
gitlab-topic-delete command line option, [646](#)
gitlab-topic-get command line option, [646](#)
gitlab-topic-list command line option, [646](#)
gitlab-topic-update command line option, [646](#)
gitlab-user command line option, [647](#)
gitlab-user-activate command line option, [647](#)
gitlab-user-activities command line option, [652](#)
gitlab-user-activities-list command line option, [652](#)
gitlab-user-block command line option, [647](#)
gitlab-user-create command line option, [648](#)
gitlab-user-custom-attribute command line option, [652](#)
gitlab-user-custom-attribute-delete command line option, [653](#)
gitlab-user-custom-attribute-get command line option, [653](#)
gitlab-user-custom-attribute-list command line option, [653](#)
gitlab-user-deactivate command line option, [649](#)
gitlab-user-delete command line option, [649](#)
gitlab-user-email command line option, [654](#)
gitlab-user-email-create command line option, [654](#)
gitlab-user-email-delete command line option, [654](#)
gitlab-user-email-get command line option, [654](#)
gitlab-user-email-list command line option, [655](#)
gitlab-user-event command line option, [655](#)
gitlab-user-event-list command line option, [655](#)
gitlab-user-follow command line option, [649](#)
gitlab-user-get command line option, [649](#)
gitlab-user-gpg-key command line option, [656](#)
gitlab-user-gpg-key-create command line option, [656](#)
gitlab-user-gpg-key-delete command line option, [656](#)
gitlab-user-gpg-key-get command line option, [656](#)
gitlab-user-gpg-key-list command line option, [657](#)
gitlab-user-impersonation-token command line option, [657](#)
gitlab-user-impersonation-token-create command line option, [657](#)
gitlab-user-impersonation-token-delete command line option, [658](#)
gitlab-user-impersonation-token-get command line option, [658](#)
gitlab-user-impersonation-token-list command line option, [658](#)
gitlab-user-key command line option, [659](#)
gitlab-user-key-create command line option, [659](#)
gitlab-user-key-delete command line option, [659](#)
gitlab-user-key-get command line option, [659](#)
gitlab-user-key-list command line option, [660](#)
gitlab-user-list command line option, [649](#)
gitlab-user-membership command line option, [660](#)
gitlab-user-membership-get command line option, [660](#)
gitlab-user-membership-list command line option, [660](#)
gitlab-user-personal-access-token command line option, [661](#)
gitlab-user-personal-access-token-create command line option, [661](#)
gitlab-user-project command line option, [661](#)
gitlab-user-project-create command line option, [662](#)
gitlab-user-project-list command line option, [663](#)
gitlab-user-status command line option, [664](#)
gitlab-user-status-get command line option, [664](#)
gitlab-user-unblock command line option, [650](#)
gitlab-user-unfollow command line option, [650](#)

- gitlab-user-update command line option, 651
- gitlab-variable command line option, 664
- gitlab-variable-create command line option, 664
- gitlab-variable-delete command line option, 665
- gitlab-variable-get command line option, 665
- gitlab-variable-list command line option, 665
- gitlab-variable-update command line option, 665
- home-page-url
 - gitlab-application-settings-update command line option, 381
- id
 - gitlab-application-delete command line option, 377
 - gitlab-application-settings-update command line option, 381
 - gitlab-audit-event-get command line option, 383
 - gitlab-broadcast-message-delete command line option, 384
 - gitlab-broadcast-message-get command line option, 384
 - gitlab-broadcast-message-update command line option, 385
 - gitlab-current-user-email-delete command line option, 386
 - gitlab-current-user-email-get command line option, 386
 - gitlab-current-user-gpg-key-delete command line option, 387
 - gitlab-current-user-gpg-key-get command line option, 388
 - gitlab-current-user-key-delete command line option, 389
 - gitlab-current-user-key-get command line option, 389
 - gitlab-geo-node-current-failures command line option, 394
 - gitlab-geo-node-delete command line option, 394
 - gitlab-geo-node-get command line option, 395
 - gitlab-geo-node-repair command line option, 395
 - gitlab-geo-node-status command line option, 395
 - gitlab-geo-node-update command line option, 396
 - gitlab-group-access-request-approve command line option, 404
 - gitlab-group-access-request-delete command line option, 404
 - gitlab-group-access-token-delete command line option, 405
 - gitlab-group-add-ldap-group-link command line option, 398
 - gitlab-group-audit-event-get command line option, 406
 - gitlab-group-badge-delete command line option, 407
 - gitlab-group-badge-get command line option, 407
 - gitlab-group-badge-render command line option, 408
 - gitlab-group-badge-update command line option, 408
 - gitlab-group-billable-member-delete command line option, 409
 - gitlab-group-board-delete command line option, 411
 - gitlab-group-board-get command line option, 411
 - gitlab-group-board-list-delete command line option, 412
 - gitlab-group-board-list-get command line option, 413
 - gitlab-group-board-list-update command line option, 413
 - gitlab-group-board-update command line option, 412
 - gitlab-group-cluster-delete command line option, 414
 - gitlab-group-cluster-get command line option, 415
 - gitlab-group-cluster-update command line option, 415
 - gitlab-group-delete command line option, 399
 - gitlab-group-delete-ldap-group-link command line option, 399
 - gitlab-group-deploy-token-delete command line option, 417
 - gitlab-group-deploy-token-get command line option, 418
 - gitlab-group-epic-award-emoji-delete command line option, 422
 - gitlab-group-epic-award-emoji-get command line option, 422
 - gitlab-group-epic-discussion-note-delete command line option, 424
 - gitlab-group-epic-discussion-note-get command line option, 424
 - gitlab-group-epic-discussion-note-update

command line option, [425](#)
gitlab-group-epic-note-award-emoji-delete
command line option, [429](#)
gitlab-group-epic-note-award-emoji-get
command line option, [429](#)
gitlab-group-epic-note-delete command
line option, [427](#)
gitlab-group-epic-note-get command line
option, [427](#)
gitlab-group-epic-note-update command
line option, [428](#)
gitlab-group-epic-resource-label-event-get
command line option, [430](#)
gitlab-group-get command line option, [400](#)
gitlab-group-hook-delete command line
option, [433](#)
gitlab-group-hook-get command line
option, [433](#)
gitlab-group-hook-update command line
option, [434](#)
gitlab-group-ldap-sync command line
option, [400](#)
gitlab-group-member-all-get command
line option, [442](#)
gitlab-group-member-delete command line
option, [440](#)
gitlab-group-member-get command line
option, [440](#)
gitlab-group-member-update command line
option, [441](#)
gitlab-group-milestone-delete command
line option, [444](#)
gitlab-group-milestone-get command line
option, [445](#)
gitlab-group-milestone-issues command
line option, [445](#)
gitlab-group-milestone-merge-requests
command line option, [446](#)
gitlab-group-milestone-update command
line option, [446](#)
gitlab-group-search command line option,
[401](#)
gitlab-group-share command line option,
[401](#)
gitlab-group-transfer command line
option, [401](#)
gitlab-group-transfer-project command
line option, [402](#)
gitlab-group-unshare command line
option, [402](#)
gitlab-group-update command line option,
[403](#)
gitlab-hook-delete command line option,
[456](#)
gitlab-hook-get command line option, [456](#)
gitlab-issue-get command line option, [457](#)
gitlab-key-get command line option, [458](#)
gitlab-namespace-get command line
option, [462](#)
gitlab-personal-access-token-delete
command line option, [464](#)
gitlab-project-access-request-approve
command line option, [481](#)
gitlab-project-access-request-delete
command line option, [482](#)
gitlab-project-access-token-delete
command line option, [483](#)
gitlab-project-approval-rule-delete
command line option, [485](#)
gitlab-project-approval-rule-update
command line option, [486](#)
gitlab-project-archive command line
option, [465](#)
gitlab-project-artifact command line
option, [465](#)
gitlab-project-artifacts command line
option, [466](#)
gitlab-project-audit-event-get command
line option, [488](#)
gitlab-project-badge-delete command
line option, [489](#)
gitlab-project-badge-get command line
option, [489](#)
gitlab-project-badge-render command
line option, [490](#)
gitlab-project-badge-update command
line option, [490](#)
gitlab-project-board-delete command
line option, [491](#)
gitlab-project-board-get command line
option, [491](#)
gitlab-project-board-list-delete
command line option, [493](#)
gitlab-project-board-list-get command
line option, [493](#)
gitlab-project-board-list-update
command line option, [494](#)
gitlab-project-board-update command
line option, [492](#)
gitlab-project-cluster-delete command
line option, [496](#)
gitlab-project-cluster-get command line
option, [497](#)
gitlab-project-cluster-update command
line option, [497](#)
gitlab-project-commit-cherry-pick
command line option, [498](#)
gitlab-project-commit-diff command line

- option, [499](#)
- gitlab-project-commit-discussion-get
 - command line option, [503](#)
- gitlab-project-commit-discussion-note-delete
 - command line option, [504](#)
- gitlab-project-commit-discussion-note-get
 - command line option, [505](#)
- gitlab-project-commit-discussion-note-update
 - command line option, [505](#)
- gitlab-project-commit-get command line option, [499](#)
- gitlab-project-commit-merge-requests
 - command line option, [500](#)
- gitlab-project-commit-refs command line option, [500](#)
- gitlab-project-commit-revert command line option, [501](#)
- gitlab-project-commit-signature command line option, [501](#)
- gitlab-project-create-fork-relation
 - command line option, [469](#)
- gitlab-project-delete command line option, [470](#)
- gitlab-project-delete-fork-relation
 - command line option, [470](#)
- gitlab-project-delete-merged-branches
 - command line option, [470](#)
- gitlab-project-deploy-token-delete
 - command line option, [508](#)
- gitlab-project-deploy-token-get command line option, [509](#)
- gitlab-project-deployment-get command line option, [510](#)
- gitlab-project-deployment-update
 - command line option, [511](#)
- gitlab-project-environment-delete
 - command line option, [514](#)
- gitlab-project-environment-get command line option, [514](#)
- gitlab-project-environment-stop command line option, [515](#)
- gitlab-project-environment-update
 - command line option, [515](#)
- gitlab-project-get command line option, [470](#)
- gitlab-project-hook-delete command line option, [522](#)
- gitlab-project-hook-get command line option, [522](#)
- gitlab-project-hook-update command line option, [523](#)
- gitlab-project-housekeeping command line option, [470](#)
- gitlab-project-issue-award-emoji-delete
 - command line option, [532](#)
- gitlab-project-issue-award-emoji-get
 - command line option, [532](#)
- gitlab-project-issue-discussion-get
 - command line option, [533](#)
- gitlab-project-issue-discussion-note-delete
 - command line option, [535](#)
- gitlab-project-issue-discussion-note-get
 - command line option, [535](#)
- gitlab-project-issue-discussion-note-update
 - command line option, [536](#)
- gitlab-project-issue-note-award-emoji-delete
 - command line option, [540](#)
- gitlab-project-issue-note-award-emoji-get
 - command line option, [540](#)
- gitlab-project-issue-note-delete
 - command line option, [538](#)
- gitlab-project-issue-note-get command line option, [538](#)
- gitlab-project-issue-note-update
 - command line option, [539](#)
- gitlab-project-issue-resource-label-event-get
 - command line option, [541](#)
- gitlab-project-issue-resource-milestone-event-get
 - command line option, [542](#)
- gitlab-project-issue-resource-state-event-get
 - command line option, [543](#)
- gitlab-project-job-artifact command line option, [544](#)
- gitlab-project-job-artifacts command line option, [545](#)
- gitlab-project-job-cancel command line option, [545](#)
- gitlab-project-job-delete-artifacts
 - command line option, [545](#)
- gitlab-project-job-erase command line option, [546](#)
- gitlab-project-job-get command line option, [546](#)
- gitlab-project-job-keep-artifacts
 - command line option, [546](#)
- gitlab-project-job-play command line option, [547](#)
- gitlab-project-job-retry command line option, [547](#)
- gitlab-project-job-trace command line option, [547](#)
- gitlab-project-key-delete command line option, [548](#)
- gitlab-project-key-enable command line option, [548](#)
- gitlab-project-key-get command line option, [549](#)
- gitlab-project-key-update command line

option, [549](#)

gitlab-project-languages command line option, [471](#)

gitlab-project-member-all-get command line option, [555](#)

gitlab-project-member-delete command line option, [553](#)

gitlab-project-member-get command line option, [553](#)

gitlab-project-member-update command line option, [554](#)

gitlab-project-merge-request-approval-rule-create command line option, [566](#)

gitlab-project-merge-request-approval-rule-update command line option, [568](#)

gitlab-project-merge-request-approval-state-get command line option, [568](#)

gitlab-project-merge-request-award-emoji-delete command line option, [569](#)

gitlab-project-merge-request-award-emoji-get command line option, [569](#)

gitlab-project-merge-request-diff-get command line option, [570](#)

gitlab-project-merge-request-discussion-get command line option, [572](#)

gitlab-project-merge-request-discussion-note-delete command line option, [574](#)

gitlab-project-merge-request-discussion-note-get command line option, [574](#)

gitlab-project-merge-request-discussion-note-update command line option, [574](#)

gitlab-project-merge-request-discussion-update command line option, [573](#)

gitlab-project-merge-request-note-award-emoji-delete command line option, [577](#)

gitlab-project-merge-request-note-award-emoji-get command line option, [578](#)

gitlab-project-merge-request-note-delete command line option, [575](#)

gitlab-project-merge-request-note-get command line option, [576](#)

gitlab-project-merge-request-note-update command line option, [576](#)

gitlab-project-merge-request-resource-label-event-get command line option, [580](#)

gitlab-project-merge-request-resource-milestone-event-get command line option, [581](#)

gitlab-project-merge-request-resource-state-event-get command line option, [582](#)

gitlab-project-milestone-delete command line option, [584](#)

gitlab-project-milestone-get command line option, [584](#)

gitlab-project-milestone-issues command line option, [584](#)

gitlab-project-milestone-merge-requests command line option, [585](#)

gitlab-project-milestone-update command line option, [586](#)

gitlab-project-mirror-pull command line option, [472](#)

gitlab-project-note-get command line option, [586](#)

gitlab-project-package-delete command line option, [588](#)

gitlab-project-package-file-delete command line option, [589](#)

gitlab-project-package-get command line option, [588](#)

gitlab-project-pipeline-cancel command line option, [592](#)

gitlab-project-pipeline-delete command line option, [593](#)

gitlab-project-pipeline-get command line option, [593](#)

gitlab-project-pipeline-retry command line option, [594](#)

gitlab-project-pipeline-schedule-delete command line option, [596](#)

gitlab-project-pipeline-schedule-get command line option, [596](#)

gitlab-project-pipeline-schedule-play command line option, [597](#)

gitlab-project-pipeline-schedule-take-ownership command line option, [597](#)

gitlab-project-pipeline-schedule-update command line option, [598](#)

gitlab-project-registry-repository-delete command line option, [607](#)

gitlab-project-release-link-delete command line option, [612](#)

gitlab-project-release-link-get command line option, [613](#)

gitlab-project-release-link-update command line option, [613](#)

gitlab-project-remote-mirror-update command line option, [615](#)

gitlab-project-repository-archive command line option, [472](#)

gitlab-project-repository-blob command line option, [473](#)

gitlab-project-repository-compare command line option, [473](#)

gitlab-project-repository-contributors command line option, [473](#)

gitlab-project-repository-raw-blob command line option, [473](#)

gitlab-project-repository-tree command

- line option, [474](#)
- gitlab-project-runner-delete command
 - line option, [616](#)
- gitlab-project-search command line
 - option, [474](#)
- gitlab-project-share command line
 - option, [474](#)
- gitlab-project-snapshot command line
 - option, [475](#)
- gitlab-project-snippet-award-emoji-delete
 - command line option, [621](#)
- gitlab-project-snippet-award-emoji-get
 - command line option, [621](#)
- gitlab-project-snippet-content command
 - line option, [618](#)
- gitlab-project-snippet-delete command
 - line option, [619](#)
- gitlab-project-snippet-discussion-get
 - command line option, [623](#)
- gitlab-project-snippet-discussion-note-delete
 - command line option, [624](#)
- gitlab-project-snippet-discussion-note-get
 - command line option, [625](#)
- gitlab-project-snippet-discussion-note-update
 - command line option, [625](#)
- gitlab-project-snippet-get command line
 - option, [619](#)
- gitlab-project-snippet-note-award-emoji-delete
 - command line option, [628](#)
- gitlab-project-snippet-note-award-emoji-get
 - command line option, [628](#)
- gitlab-project-snippet-note-delete
 - command line option, [626](#)
- gitlab-project-snippet-note-get command
 - line option, [626](#)
- gitlab-project-snippet-note-update
 - command line option, [627](#)
- gitlab-project-snippet-update command
 - line option, [620](#)
- gitlab-project-snippet-user-agent-detail
 - command line option, [620](#)
- gitlab-project-star command line option, [475](#)
- gitlab-project-storage-get command line
 - option, [629](#)
- gitlab-project-transfer command line
 - option, [475](#)
- gitlab-project-transfer-project command
 - line option, [475](#)
- gitlab-project-trigger-delete command
 - line option, [631](#)
- gitlab-project-trigger-get command line
 - option, [632](#)
- gitlab-project-trigger-pipeline command
 - line option, [476](#)
- gitlab-project-trigger-update command
 - line option, [632](#)
- gitlab-project-unarchive command line
 - option, [476](#)
- gitlab-project-unshare command line
 - option, [476](#)
- gitlab-project-unstar command line
 - option, [476](#)
- gitlab-project-update command line
 - option, [478](#)
- gitlab-project-update-submodule command
 - line option, [480](#)
- gitlab-project-upload command line
 - option, [481](#)
- gitlab-runner-all command line option, [637](#)
- gitlab-runner-delete command line
 - option, [638](#)
- gitlab-runner-get command line option, [638](#)
- gitlab-runner-update command line
 - option, [639](#)
- gitlab-runner-verify command line
 - option, [640](#)
- gitlab-snippet-content command line
 - option, [641](#)
- gitlab-snippet-delete command line
 - option, [641](#)
- gitlab-snippet-get command line option, [641](#)
- gitlab-snippet-public command line
 - option, [642](#)
- gitlab-snippet-update command line
 - option, [642](#)
- gitlab-snippet-user-agent-detail
 - command line option, [643](#)
- gitlab-todo-delete command line option, [644](#)
- gitlab-todo-mark-all-as-done command
 - line option, [645](#)
- gitlab-todo-mark-as-done command line
 - option, [645](#)
- gitlab-topic-delete command line option, [646](#)
- gitlab-topic-get command line option, [646](#)
- gitlab-topic-update command line option, [646](#)
- gitlab-user-activate command line
 - option, [647](#)
- gitlab-user-block command line option, [647](#)
- gitlab-user-deactivate command line
 - option, [649](#)

- gitlab-user-delete command line option, [649](#)
- gitlab-user-email-delete command line option, [654](#)
- gitlab-user-email-get command line option, [654](#)
- gitlab-user-follow command line option, [649](#)
- gitlab-user-get command line option, [649](#)
- gitlab-user-gpg-key-delete command line option, [656](#)
- gitlab-user-gpg-key-get command line option, [656](#)
- gitlab-user-impersonation-token-delete command line option, [658](#)
- gitlab-user-impersonation-token-get command line option, [658](#)
- gitlab-user-key-delete command line option, [659](#)
- gitlab-user-key-get command line option, [659](#)
- gitlab-user-unblock command line option, [650](#)
- gitlab-user-unfollow command line option, [650](#)
- gitlab-user-update command line option, [651](#)
- id-after
 - gitlab-project-list command line option, [471](#)
 - gitlab-user-project-list command line option, [663](#)
- id-before
 - gitlab-project-list command line option, [471](#)
 - gitlab-user-project-list command line option, [663](#)
- iid
 - gitlab-group-epic-delete command line option, [420](#)
 - gitlab-group-epic-get command line option, [420](#)
 - gitlab-group-epic-update command line option, [421](#)
 - gitlab-project-issue-add-spent-time command line option, [525](#)
 - gitlab-project-issue-closed-by command line option, [525](#)
 - gitlab-project-issue-delete command line option, [526](#)
 - gitlab-project-issue-get command line option, [526](#)
 - gitlab-project-issue-move command line option, [527](#)
 - gitlab-project-issue-participants command line option, [528](#)
 - gitlab-project-issue-related-merge-requests command line option, [528](#)
 - gitlab-project-issue-reset-spent-time command line option, [528](#)
 - gitlab-project-issue-reset-time-estimate command line option, [529](#)
 - gitlab-project-issue-subscribe command line option, [529](#)
 - gitlab-project-issue-time-estimate command line option, [529](#)
 - gitlab-project-issue-time-stats command line option, [529](#)
 - gitlab-project-issue-todo command line option, [530](#)
 - gitlab-project-issue-unsubscribe command line option, [530](#)
 - gitlab-project-issue-update command line option, [530](#)
 - gitlab-project-issue-user-agent-detail command line option, [531](#)
 - gitlab-project-merge-request-add-spent-time command line option, [555](#)
 - gitlab-project-merge-request-approve command line option, [556](#)
 - gitlab-project-merge-request-cancel-merge-when-pipeline command line option, [556](#)
 - gitlab-project-merge-request-changes command line option, [556](#)
 - gitlab-project-merge-request-closes-issues command line option, [557](#)
 - gitlab-project-merge-request-commits command line option, [557](#)
 - gitlab-project-merge-request-delete command line option, [558](#)
 - gitlab-project-merge-request-get command line option, [558](#)
 - gitlab-project-merge-request-merge command line option, [560](#)
 - gitlab-project-merge-request-merge-ref command line option, [561](#)
 - gitlab-project-merge-request-participants command line option, [561](#)
 - gitlab-project-merge-request-rebase command line option, [561](#)
 - gitlab-project-merge-request-reset-spent-time command line option, [562](#)
 - gitlab-project-merge-request-reset-time-estimate command line option, [562](#)
 - gitlab-project-merge-request-subscribe command line option, [562](#)
 - gitlab-project-merge-request-time-estimate command line option, [562](#)

```

gitlab-project-merge-request-time-stats
    command line option, 563
gitlab-project-merge-request-todo
    command line option, 563
gitlab-project-merge-request-unapprove
    command line option, 563
gitlab-project-merge-request-unsubscribe
    command line option, 564
gitlab-project-merge-request-update
    command line option, 564
--iids
    gitlab-group-issue-list command line
        option, 436
    gitlab-group-milestone-list command
        line option, 445
    gitlab-issue-list command line option,
        457
    gitlab-project-issue-list command line
        option, 527
    gitlab-project-merge-request-list
        command line option, 560
    gitlab-project-milestone-list command
        line option, 585
--image-url
    gitlab-group-badge-create command line
        option, 407
    gitlab-group-badge-render command line
        option, 408
    gitlab-group-badge-update command line
        option, 408
    gitlab-project-badge-create command
        line option, 489
    gitlab-project-badge-render command
        line option, 490
    gitlab-project-badge-update command
        line option, 490
--import-sources
    gitlab-application-settings-update
        command line option, 382
--import-url
    gitlab-project-create command line
        option, 468
    gitlab-project-update command line
        option, 479
    gitlab-user-project-create command line
        option, 662
--in
    gitlab-merge-request-list command line
        option, 461
    gitlab-project-deployment-merge-request-list
        command line option, 513
--include-diverged-commits-count
    gitlab-project-merge-request-get
        command line option, 559
    --include-rebase-in-progress
        gitlab-project-merge-request-get
            command line option, 559
    --include-retried
        gitlab-project-pipeline-job-list
            command line option, 595
    --include-subgroups
        gitlab-group-project-list command line
            option, 449
    --info
        gitlab-runner-create command line
            option, 638
    --initialize-with-readme
        gitlab-project-create command line
            option, 468
    --instance-statistics-visibility-private
        gitlab-application-settings-update
            command line option, 382
    --issue-id
        gitlab-group-epic-issue-create command
            line option, 425
    --issue-iid
        gitlab-project-issue-award-emoji-create
            command line option, 531
        gitlab-project-issue-award-emoji-delete
            command line option, 532
        gitlab-project-issue-award-emoji-get
            command line option, 532
        gitlab-project-issue-award-emoji-list
            command line option, 532
        gitlab-project-issue-discussion-create
            command line option, 533
        gitlab-project-issue-discussion-get
            command line option, 533
        gitlab-project-issue-discussion-list
            command line option, 534
        gitlab-project-issue-discussion-note-create
            command line option, 534
        gitlab-project-issue-discussion-note-delete
            command line option, 535
        gitlab-project-issue-discussion-note-get
            command line option, 535
        gitlab-project-issue-discussion-note-update
            command line option, 536
        gitlab-project-issue-link-create
            command line option, 536
        gitlab-project-issue-link-delete
            command line option, 536
        gitlab-project-issue-link-list command
            line option, 537
        gitlab-project-issue-note-award-emoji-create
            command line option, 539
        gitlab-project-issue-note-award-emoji-delete
            command line option, 540

```

gitlab-project-issue-note-award-emoji-get
command line option, [540](#)

gitlab-project-issue-note-award-emoji-list
command line option, [541](#)

gitlab-project-issue-note-create
command line option, [537](#)

gitlab-project-issue-note-delete
command line option, [538](#)

gitlab-project-issue-note-get command
line option, [538](#)

gitlab-project-issue-note-list command
line option, [538](#)

gitlab-project-issue-note-update
command line option, [539](#)

gitlab-project-issue-resource-label-event-get
command line option, [541](#)

gitlab-project-issue-resource-label-event-list
command line option, [542](#)

gitlab-project-issue-resource-milestone-event-get
command line option, [542](#)

gitlab-project-issue-resource-milestone-event-list
command line option, [543](#)

gitlab-project-issue-resource-state-event-get
command line option, [543](#)

gitlab-project-issue-resource-state-event-list
command line option, [543](#)

--issue-link-id
gitlab-project-issue-link-delete
command line option, [536](#)

--issues-access-level
gitlab-project-create command line
option, [468](#)

gitlab-project-update command line
option, [479](#)

--issues-enabled
gitlab-project-create command line
option, [468](#)

gitlab-project-update command line
option, [479](#)

gitlab-user-project-create command line
option, [662](#)

--issues-events
gitlab-group-hook-create command line
option, [432](#)

gitlab-group-hook-update command line
option, [434](#)

gitlab-project-hook-create command line
option, [522](#)

gitlab-project-hook-update command line
option, [523](#)

--issues-template
gitlab-project-update command line
option, [480](#)

--job
gitlab-project-artifact command line
option, [466](#)

gitlab-project-artifact-download
command line option, [487](#)

gitlab-project-artifact-raw command
line option, [487](#)

gitlab-project-artifacts command line
option, [466](#)

--job-events
gitlab-group-hook-create command line
option, [433](#)

gitlab-group-hook-update command line
option, [435](#)

gitlab-project-hook-create command line
option, [522](#)

gitlab-project-hook-update command line
option, [524](#)

--job-token
gitlab command line option, [376](#)

gitlab-project-artifact-download
command line option, [487](#)

gitlab-project-artifacts command line
option, [466](#)

--jobs-enabled
gitlab-project-create command line
option, [468](#)

gitlab-project-update command line
option, [479](#)

--keep-n
gitlab-project-registry-tag-delete-in-bulk
command line option, [608](#)

--key
gitlab-current-user-gpg-key-create
command line option, [387](#)

gitlab-current-user-key-create command
line option, [388](#)

gitlab-group-custom-attribute-delete
command line option, [416](#)

gitlab-group-custom-attribute-get
command line option, [416](#)

gitlab-group-variable-create command
line option, [452](#)

gitlab-group-variable-delete command
line option, [452](#)

gitlab-group-variable-get command line
option, [452](#)

gitlab-group-variable-update command
line option, [453](#)

gitlab-license-get command line option,
[459](#)

gitlab-project-custom-attribute-delete
command line option, [507](#)

gitlab-project-custom-attribute-get
command line option, [507](#)

- gitlab-project-key-create command line option, [548](#)
- gitlab-project-pages-domain-create command line option, [590](#)
- gitlab-project-pages-domain-update command line option, [592](#)
- gitlab-project-pipeline-schedule-variable-create command line option, [599](#)
- gitlab-project-pipeline-schedule-variable-delete line option, [525](#)
command line option, [599](#)
- gitlab-project-pipeline-schedule-variable-update option, [527](#)
command line option, [599](#)
- gitlab-project-variable-create command line option, [634](#)
- gitlab-project-variable-delete command line option, [634](#)
- gitlab-project-variable-get command line option, [634](#)
- gitlab-project-variable-update command line option, [635](#)
- gitlab-user-custom-attribute-delete command line option, [653](#)
- gitlab-user-custom-attribute-get command line option, [653](#)
- gitlab-user-gpg-key-create command line option, [656](#)
- gitlab-user-key-create command line option, [659](#)
- gitlab-variable-create command line option, [664](#)
- gitlab-variable-delete command line option, [665](#)
- gitlab-variable-get command line option, [665](#)
- gitlab-variable-update command line option, [665](#)
- key-id
 - gitlab-project-key-enable command line option, [548](#)
- label-id
 - gitlab-group-board-list-create command line option, [412](#)
 - gitlab-project-board-list-create command line option, [493](#)
- labels
 - gitlab-group-epic-create command line option, [420](#)
 - gitlab-group-epic-list command line option, [421](#)
 - gitlab-group-epic-update command line option, [421](#)
 - gitlab-group-issue-list command line option, [436](#)
 - gitlab-group-merge-request-list command line option, [443](#)
 - gitlab-issue-list command line option, [457](#)
 - gitlab-merge-request-list command line option, [461](#)
 - gitlab-project-deployment-merge-request-list
 - gitlab-project-issue-create command
 - gitlab-project-issue-list command line
 - gitlab-project-issue-update command line option, [531](#)
 - gitlab-project-merge-request-create command line option, [558](#)
 - gitlab-project-merge-request-list command line option, [559](#)
 - gitlab-project-merge-request-update command line option, [564](#)
- last-activity-after
 - gitlab-project-list command line option, [471](#)
- last-activity-before
 - gitlab-project-list command line option, [471](#)
- level
 - gitlab-group-notification-settings-update command line option, [447](#)
 - gitlab-notification-settings-update command line option, [463](#)
 - gitlab-project-notification-settings-update command line option, [587](#)
- lfs-enabled
 - gitlab-group-create command line option, [399](#)
 - gitlab-group-update command line option, [403](#)
 - gitlab-project-create command line option, [468](#)
 - gitlab-project-update command line option, [479](#)
- lifetime
 - gitlab-snippet-create command line option, [641](#)
- line
 - gitlab-project-commit-comment-create command line option, [502](#)
- line-type
 - gitlab-project-commit-comment-create command line option, [502](#)
- link-type
 - gitlab-project-release-link-create command line option, [612](#)
 - gitlab-project-release-link-update

- command line option, [613](#)
- `--link-url`
 - `gitlab-group-badge-create` command line option, [407](#)
 - `gitlab-group-badge-render` command line option, [408](#)
 - `gitlab-group-badge-update` command line option, [408](#)
 - `gitlab-project-badge-create` command line option, [489](#)
 - `gitlab-project-badge-render` command line option, [490](#)
 - `gitlab-project-badge-update` command line option, [490](#)
- `--linkedin`
 - `gitlab-user-create` command line option, [648](#)
 - `gitlab-user-update` command line option, [651](#)
- `--local-markdown-version`
 - `gitlab-application-settings-update` command line option, [382](#)
- `--location`
 - `gitlab-user-create` command line option, [648](#)
 - `gitlab-user-update` command line option, [652](#)
- `--locked`
 - `gitlab-runner-create` command line option, [638](#)
 - `gitlab-runner-update` command line option, [639](#)
- `--logo`
 - `gitlab-application-appearance-update` command line option, [378](#)
- `--managed`
 - `gitlab-group-cluster-create` command line option, [414](#)
 - `gitlab-project-cluster-create` command line option, [496](#)
- `--management-project-id`
 - `gitlab-group-cluster-update` command line option, [415](#)
 - `gitlab-project-cluster-update` command line option, [497](#)
- `--masked`
 - `gitlab-group-variable-create` command line option, [452](#)
 - `gitlab-group-variable-update` command line option, [453](#)
 - `gitlab-project-variable-create` command line option, [634](#)
 - `gitlab-project-variable-update` command line option, [635](#)
 - `gitlab-variable-create` command line option, [664](#)
 - `gitlab-variable-update` command line option, [666](#)
- `--max-attachment-size`
 - `gitlab-application-settings-update` command line option, [381](#)
- `--max-file-size`
 - `gitlab-project-push-rules-create` command line option, [605](#)
 - `gitlab-project-push-rules-update` command line option, [606](#)
- `--maximum-timeout`
 - `gitlab-runner-create` command line option, [638](#)
 - `gitlab-runner-update` command line option, [639](#)
- `--member-check`
 - `gitlab-project-push-rules-create` command line option, [605](#)
 - `gitlab-project-push-rules-update` command line option, [606](#)
- `--membership`
 - `gitlab-project-fork-list` command line option, [521](#)
 - `gitlab-project-list` command line option, [471](#)
 - `gitlab-starred-project-list` command line option, [643](#)
 - `gitlab-user-project-list` command line option, [663](#)
- `--membership-lock`
 - `gitlab-group-create` command line option, [398](#)
 - `gitlab-group-update` command line option, [403](#)
- `--mentions-disabled`
 - `gitlab-group-create` command line option, [399](#)
 - `gitlab-group-update` command line option, [403](#)
- `--merge-access-level`
 - `gitlab-project-protected-branch-create` command line option, [602](#)
- `--merge-commit-message`
 - `gitlab-project-merge-request-merge` command line option, [560](#)
- `--merge-merge-request`
 - `gitlab-group-notification-settings-update` command line option, [448](#)
 - `gitlab-notification-settings-update` command line option, [464](#)
 - `gitlab-project-notification-settings-update` command line option, [588](#)

```

--merge-method
  gitlab-project-create command line
    option, 468
  gitlab-project-update command line
    option, 479
--merge-request-iid
  gitlab-project-merge-request-approval-rule-create command line option, 379
  command line option, 566
  gitlab-project-merge-request-approval-rule-update command line option, 568
--merge-request-to-resolve-discussions-of
  gitlab-project-issue-create command
  line option, 526
--merge-requests-access-level
  gitlab-project-create command line
    option, 468
  gitlab-project-update command line
    option, 479
--merge-requests-author-approval
  gitlab-project-approval-update command
  line option, 484
--merge-requests-disable-committers-approval
  gitlab-project-approval-update command
  line option, 484
--merge-requests-enabled
  gitlab-project-create command line
    option, 468
  gitlab-project-update command line
    option, 479
  gitlab-user-project-create command line
    option, 662
--merge-requests-events
  gitlab-group-hook-create command line
    option, 432
  gitlab-group-hook-update command line
    option, 434
  gitlab-project-hook-create command line
    option, 522
  gitlab-project-hook-update command line
    option, 523
--merge-requests-template
  gitlab-project-update command line
    option, 480
--merge-when-pipeline-succeeds
  gitlab-project-merge-request-merge
  command line option, 560
--message
  gitlab-broadcast-message-create command
  line option, 384
  gitlab-broadcast-message-update command
  line option, 385
  gitlab-current-user-status-update
  command line option, 390
  gitlab-project-tag-create command line
    option, 630
--message-background-color
  gitlab-application-appearance-update
  command line option, 378
--message-font-color
  gitlab-application-appearance-update
  command line option, 378
--milestone
  gitlab-group-issue-list command line
  option, 436
  gitlab-group-merge-request-list command
  line option, 443
  gitlab-issue-list command line option,
  457
  gitlab-merge-request-list command line
  option, 461
  gitlab-project-deployment-merge-request-list
  command line option, 512
  gitlab-project-issue-list command line
  option, 527
  gitlab-project-merge-request-list
  command line option, 559
--milestone-id
  gitlab-project-issue-create command
  line option, 525
  gitlab-project-issue-update command
  line option, 531
  gitlab-project-merge-request-create
  command line option, 558
  gitlab-project-merge-request-update
  command line option, 564
--milestones
  gitlab-project-release-update command
  line option, 611
--min-access-level
  gitlab-group-descendant-group-list
  command line option, 419
  gitlab-group-list command line option,
  400
  gitlab-group-project-list command line
  option, 450
  gitlab-group-subgroup-list command line
  option, 451
  gitlab-project-list command line option,
  471
  gitlab-starred-project-list command
  line option, 643
  gitlab-user-project-list command line
  option, 663
--mirror
  gitlab-project-create command line
  option, 468
  gitlab-project-update command line
  option, 479

```

```
--mirror-overwrites-diverged-branches
  gitlab-project-update command line
    option, 479
--mirror-trigger-builds
  gitlab-project-create command line
    option, 468
  gitlab-project-update command line
    option, 479
--mirror-user-id
  gitlab-project-update command line
    option, 479
--move-after-id
  gitlab-group-epic-issue-update command
    line option, 426
--move-before-id
  gitlab-group-epic-issue-update command
    line option, 426
--mr-iid
  gitlab-project-merge-request-approval-get
    command line option, 565
  gitlab-project-merge-request-approval-rule-create
    command line option, 566
  gitlab-project-merge-request-approval-rule-delete
    command line option, 566
  gitlab-project-merge-request-approval-rule-list
    command line option, 567
  gitlab-project-merge-request-approval-rule-update
    command line option, 568
  gitlab-project-merge-request-approval-state-get
    command line option, 568
  gitlab-project-merge-request-approval-update
    command line option, 565
  gitlab-project-merge-request-award-emoji-create
    command line option, 569
  gitlab-project-merge-request-award-emoji-delete
    command line option, 569
  gitlab-project-merge-request-award-emoji-get
    command line option, 569
  gitlab-project-merge-request-award-emoji-list
    command line option, 570
  gitlab-project-merge-request-diff-get
    command line option, 570
  gitlab-project-merge-request-diff-list
    command line option, 571
  gitlab-project-merge-request-discussion-create
    command line option, 571
  gitlab-project-merge-request-discussion-get
    command line option, 572
  gitlab-project-merge-request-discussion-list
    command line option, 572
  gitlab-project-merge-request-discussion-note-create
    command line option, 573
  gitlab-project-merge-request-discussion-note-delete
    command line option, 574
  gitlab-project-merge-request-discussion-note-get
    command line option, 574
  gitlab-project-merge-request-discussion-note-update
    command line option, 574
  gitlab-project-merge-request-discussion-update
    command line option, 573
  gitlab-project-merge-request-note-award-emoji-create
    command line option, 577
  gitlab-project-merge-request-note-award-emoji-delete
    command line option, 577
  gitlab-project-merge-request-note-award-emoji-get
    command line option, 578
  gitlab-project-merge-request-note-award-emoji-list
    command line option, 578
  gitlab-project-merge-request-note-create
    command line option, 575
  gitlab-project-merge-request-note-delete
    command line option, 575
  gitlab-project-merge-request-note-get
    command line option, 576
  gitlab-project-merge-request-note-list
    command line option, 576
  gitlab-project-merge-request-note-update
    command line option, 576
  gitlab-project-merge-request-pipeline-create
    command line option, 579
  gitlab-project-merge-request-pipeline-list
    command line option, 579
  gitlab-project-merge-request-resource-label-event-get
    command line option, 580
  gitlab-project-merge-request-resource-label-event-list
    command line option, 580
  gitlab-project-merge-request-resource-milestone-event-
    command line option, 581
  gitlab-project-merge-request-resource-milestone-event-
    command line option, 581
  gitlab-project-merge-request-resource-state-event-get
    command line option, 582
  gitlab-project-merge-request-resource-state-event-list
    command line option, 582
  --my-reaction-emoji
  gitlab-group-issue-list command line
    option, 436
  gitlab-group-merge-request-list command
    line option, 443
  gitlab-issue-list command line option,
    457
  gitlab-merge-request-list command line
    option, 461
  gitlab-project-deployment-merge-request-list
    command line option, 513
  gitlab-project-issue-list command line
    option, 527
  gitlab-project-merge-request-list
```

- command line option, [560](#)
- name
 - gitlab-application-create command line option, [377](#)
 - gitlab-dockerfile-get command line option, [391](#)
 - gitlab-feature-delete command line option, [393](#)
 - gitlab-gitignore-get command line option, [396](#)
 - gitlab-gitlabciyaml-get command line option, [397](#)
 - gitlab-group-board-create command line option, [410](#)
 - gitlab-group-cluster-create command line option, [414](#)
 - gitlab-group-cluster-update command line option, [415](#)
 - gitlab-group-create command line option, [398](#)
 - gitlab-group-deploy-token-create command line option, [417](#)
 - gitlab-group-epic-award-emoji-create command line option, [422](#)
 - gitlab-group-epic-note-award-emoji-create command line option, [429](#)
 - gitlab-group-label-create command line option, [437](#)
 - gitlab-group-label-delete command line option, [438](#)
 - gitlab-group-label-get command line option, [438](#)
 - gitlab-group-label-subscribe command line option, [439](#)
 - gitlab-group-label-unsubscribe command line option, [439](#)
 - gitlab-group-label-update command line option, [439](#)
 - gitlab-group-update command line option, [403](#)
 - gitlab-project-approval-rule-create command line option, [485](#)
 - gitlab-project-board-create command line option, [491](#)
 - gitlab-project-branch-delete command line option, [495](#)
 - gitlab-project-branch-get command line option, [495](#)
 - gitlab-project-cluster-create command line option, [496](#)
 - gitlab-project-cluster-update command line option, [497](#)
 - gitlab-project-commit-status-create command line option, [506](#)
 - gitlab-project-create command line option, [467](#)
 - gitlab-project-deploy-token-create command line option, [508](#)
 - gitlab-project-environment-create command line option, [513](#)
 - gitlab-project-environment-list command line option, [514](#)
 - gitlab-project-environment-update command line option, [515](#)
 - gitlab-project-issue-award-emoji-create command line option, [532](#)
 - gitlab-project-issue-note-award-emoji-create command line option, [539](#)
 - gitlab-project-label-create command line option, [550](#)
 - gitlab-project-label-delete command line option, [550](#)
 - gitlab-project-label-get command line option, [551](#)
 - gitlab-project-label-subscribe command line option, [551](#)
 - gitlab-project-label-unsubscribe command line option, [552](#)
 - gitlab-project-label-update command line option, [552](#)
 - gitlab-project-merge-request-approval-rule-create command line option, [566](#)
 - gitlab-project-merge-request-approval-rule-list command line option, [567](#)
 - gitlab-project-merge-request-approval-rule-update command line option, [568](#)
 - gitlab-project-merge-request-award-emoji-create command line option, [569](#)
 - gitlab-project-merge-request-note-award-emoji-create command line option, [577](#)
 - gitlab-project-pipeline-list command line option, [594](#)
 - gitlab-project-protected-branch-create command line option, [602](#)
 - gitlab-project-protected-branch-delete command line option, [602](#)
 - gitlab-project-protected-branch-get command line option, [602](#)
 - gitlab-project-protected-tag-create command line option, [603](#)
 - gitlab-project-protected-tag-delete command line option, [604](#)
 - gitlab-project-protected-tag-get command line option, [604](#)
 - gitlab-project-registry-tag-delete command line option, [608](#)
 - gitlab-project-registry-tag-delete-in-bulk command line option, [608](#)

gitlab-project-registry-tag-get command line option, [609](#)
gitlab-project-release-create command line option, [610](#)
gitlab-project-release-link-create command line option, [612](#)
gitlab-project-release-link-update command line option, [613](#)
gitlab-project-release-update command line option, [611](#)
gitlab-project-snippet-award-emoji-create command line option, [621](#)
gitlab-project-snippet-note-award-emoji-create command line option, [628](#)
gitlab-project-tag-delete command line option, [630](#)
gitlab-project-tag-get command line option, [630](#)
gitlab-project-update command line option, [479](#)
gitlab-topic-create command line option, [645](#)
gitlab-topic-update command line option, [647](#)
gitlab-user-create command line option, [648](#)
gitlab-user-impersonation-token-create command line option, [657](#)
gitlab-user-personal-access-token-create command line option, [661](#)
gitlab-user-project-create command line option, [662](#)
gitlab-user-update command line option, [651](#)
--name-regex-delete
gitlab-project-registry-tag-delete-in-bulk command line option, [608](#)
--name-regex-keep
gitlab-project-registry-tag-delete-in-bulk command line option, [608](#)
--namespace
gitlab-project-fork-create command line option, [520](#)
--namespace-id
gitlab-project-create command line option, [468](#)
--new-issue
gitlab-group-notification-settings-update command line option, [447](#)
gitlab-notification-settings-update command line option, [463](#)
gitlab-project-notification-settings-update command line option, [588](#)
--new-merge-request
gitlab-group-notification-settings-update command line option, [447](#)
gitlab-notification-settings-update command line option, [463](#)
gitlab-project-notification-settings-update command line option, [588](#)
--new-name
gitlab-group-label-update command line option, [439](#)
gitlab-project-label-update command line option, [552](#)
--new-note
gitlab-group-notification-settings-update command line option, [447](#)
gitlab-notification-settings-update command line option, [463](#)
gitlab-project-notification-settings-update command line option, [587](#)
--new-project-guidelines
gitlab-application-appearance-update command line option, [378](#)
--not
gitlab-merge-request-list command line option, [461](#)
gitlab-project-deployment-merge-request-list command line option, [513](#)
--note
gitlab-project-commit-comment-create command line option, [502](#)
--note-events
gitlab-group-hook-create command line option, [433](#)
gitlab-group-hook-update command line option, [435](#)
gitlab-project-hook-create command line option, [522](#)
gitlab-project-hook-update command line option, [523](#)
--note-id
gitlab-group-epic-note-award-emoji-create command line option, [429](#)
gitlab-group-epic-note-award-emoji-delete command line option, [429](#)
gitlab-group-epic-note-award-emoji-get command line option, [429](#)
gitlab-group-epic-note-award-emoji-list command line option, [430](#)
gitlab-project-issue-note-award-emoji-create command line option, [539](#)
gitlab-project-issue-note-award-emoji-delete command line option, [540](#)
gitlab-project-issue-note-award-emoji-get command line option, [540](#)
gitlab-project-issue-note-award-emoji-list

- command line option, [541](#)
- gitlab-project-merge-request-note-award-emoji-create
 - command line option, [577](#)
- gitlab-project-merge-request-note-award-emoji-delete
 - command line option, [577](#)
- gitlab-project-merge-request-note-award-emoji-get
 - command line option, [578](#)
- gitlab-project-merge-request-note-award-emoji-list
 - command line option, [578](#)
- gitlab-project-snippet-note-award-emoji-create
 - command line option, [628](#)
- gitlab-project-snippet-note-award-emoji-delete
 - command line option, [628](#)
- gitlab-project-snippet-note-award-emoji-get
 - command line option, [628](#)
- gitlab-project-snippet-note-award-emoji-list
 - command line option, [629](#)
- notification-email
 - gitlab-group-notification-settings-update
 - command line option, [447](#)
 - gitlab-notification-settings-update
 - command line option, [463](#)
 - gitlab-project-notification-settings-update
 - command line option, [587](#)
- oauth-token
 - gitlab command line option, [376](#)
- older-than
 - gitlab-project-registry-tag-delete-in-bulk
 - command line option, [608](#)
- only-allow-merge-if-all-discussions-are-resolved
 - gitlab-project-create command line option, [469](#)
 - gitlab-project-update command line option, [479](#)
- only-allow-merge-if-build-succeeds
 - gitlab-user-project-create command line option, [662](#)
- only-allow-merge-if-pipeline-succeeds
 - gitlab-project-create command line option, [469](#)
 - gitlab-project-update command line option, [479](#)
- only-mirror-protected-branches
 - gitlab-project-update command line option, [479](#)
- only-protected-branches
 - gitlab-project-remote-mirror-create
 - command line option, [614](#)
 - gitlab-project-remote-mirror-update
 - command line option, [615](#)
- operations-access-level
 - gitlab-project-create command line option, [468](#)
 - gitlab-project-update command line option, [479](#)
- organization
 - gitlab-user-create command line option, [648](#)
 - gitlab-user-update command line option, [651](#)
- outbound-local-requests-whitelist
 - gitlab-application-settings-update
 - command line option, [381](#)
- order-by
 - gitlab command line option, [376](#)
- gitlab-group-descendant-group-list
 - command line option, [419](#)
- gitlab-group-epic-list
 - command line option, [421](#)
- gitlab-group-issue-list
 - command line option, [436](#)
- gitlab-group-list
 - command line option, [400](#)
- gitlab-group-merge-request-list
 - command line option, [443](#)
- gitlab-group-package-list
 - command line option, [448](#)
- gitlab-group-project-list
 - command line option, [449](#)
- gitlab-group-subgroup-list
 - command line option, [451](#)
- gitlab-issue-list
 - command line option, [457](#)
- gitlab-merge-request-list
 - command line option, [461](#)
- gitlab-project-deployment-list
 - command line option, [510](#)
- gitlab-project-deployment-merge-request-list
 - command line option, [512](#)
- gitlab-project-fork-list
 - command line option, [520](#)
- gitlab-project-issue-list
 - command line option, [527](#)
- gitlab-project-list
 - command line option, [471](#)
- gitlab-project-merge-request-list
 - command line option, [559](#)
- gitlab-project-package-list
 - command line option, [589](#)
- gitlab-project-pipeline-list
 - command line option, [594](#)
- gitlab-starred-project-list
 - command line option, [643](#)
- gitlab-user-project-list
 - command line option, [663](#)

--output
 gitlab command line option, [376](#)

--owned
 gitlab-group-descendant-group-list
 command line option, [419](#)
 gitlab-group-list command line option,
 [400](#)
 gitlab-group-project-list command line
 option, [449](#)
 gitlab-group-subgroup-list command line
 option, [451](#)
 gitlab-project-fork-list command line
 option, [521](#)
 gitlab-project-list command line option,
 [471](#)
 gitlab-starred-project-list command
 line option, [643](#)
 gitlab-user-project-list command line
 option, [663](#)

--package-id
 gitlab-project-package-file-delete
 command line option, [589](#)
 gitlab-project-package-file-list
 command line option, [590](#)

--package-name
 gitlab-generic-package-download command
 line option, [393](#)
 gitlab-generic-package-upload command
 line option, [394](#)
 gitlab-group-package-list command line
 option, [448](#)
 gitlab-project-package-list command
 line option, [589](#)

--package-type
 gitlab-group-package-list command line
 option, [448](#)
 gitlab-project-package-list command
 line option, [589](#)

--package-version
 gitlab-generic-package-download command
 line option, [393](#)
 gitlab-generic-package-upload command
 line option, [394](#)

--packages-enabled
 gitlab-project-create command line
 option, [469](#)
 gitlab-project-update command line
 option, [479](#)

--page
 gitlab-application-list command line
 option, [377](#)
 gitlab-audit-event-list command line
 option, [383](#)
 gitlab-broadcast-message-list command
 line option, [385](#)
 gitlab-current-user-email-list command
 line option, [387](#)
 gitlab-current-user-gpg-key-list
 command line option, [388](#)
 gitlab-current-user-key-list command
 line option, [389](#)
 gitlab-deploy-key-list command line
 option, [390](#)
 gitlab-deploy-token-list command line
 option, [391](#)
 gitlab-dockerfile-list command line
 option, [391](#)
 gitlab-event-list command line option,
 [392](#)
 gitlab-feature-list command line option,
 [393](#)
 gitlab-geo-node-list command line
 option, [395](#)
 gitlab-gitignore-list command line
 option, [396](#)
 gitlab-gitlabciyaml-list command line
 option, [397](#)
 gitlab-group-access-request-list
 command line option, [405](#)
 gitlab-group-access-token-list command
 line option, [406](#)
 gitlab-group-audit-event-list command
 line option, [406](#)
 gitlab-group-badge-list command line
 option, [408](#)
 gitlab-group-billable-member-list
 command line option, [409](#)
 gitlab-group-billable-member-membership-list
 command line option, [410](#)
 gitlab-group-board-list command line
 option, [411](#)
 gitlab-group-board-list-list command
 line option, [413](#)
 gitlab-group-cluster-list command line
 option, [415](#)
 gitlab-group-custom-attribute-list
 command line option, [417](#)
 gitlab-group-deploy-token-list command
 line option, [418](#)
 gitlab-group-descendant-group-list
 command line option, [419](#)
 gitlab-group-epic-award-emoji-list
 command line option, [423](#)
 gitlab-group-epic-issue-list command
 line option, [426](#)
 gitlab-group-epic-list command line
 option, [421](#)
 gitlab-group-epic-note-award-emoji-list

- command line option, [430](#)
- gitlab-group-epic-note-list command line option, [428](#)
- gitlab-group-epic-resource-label-event-list command line option, [431](#)
- gitlab-group-hook-list command line option, [434](#)
- gitlab-group-issue-list command line option, [436](#)
- gitlab-group-label-list command line option, [438](#)
- gitlab-group-list command line option, [401](#)
- gitlab-group-member-all-list command line option, [442](#)
- gitlab-group-member-list command line option, [441](#)
- gitlab-group-merge-request-list command line option, [443](#)
- gitlab-group-milestone-list command line option, [445](#)
- gitlab-group-package-list command line option, [448](#)
- gitlab-group-project-list command line option, [450](#)
- gitlab-group-runner-list command line option, [450](#)
- gitlab-group-subgroup-list command line option, [451](#)
- gitlab-group-variable-list command line option, [453](#)
- gitlab-group-wiki-list command line option, [455](#)
- gitlab-hook-list command line option, [456](#)
- gitlab-issue-list command line option, [458](#)
- gitlab-ldap-group-list command line option, [459](#)
- gitlab-license-list command line option, [460](#)
- gitlab-merge-request-list command line option, [462](#)
- gitlab-namespace-list command line option, [462](#)
- gitlab-pages-domain-list command line option, [464](#)
- gitlab-personal-access-token-list command line option, [465](#)
- gitlab-project-access-request-list command line option, [482](#)
- gitlab-project-access-token-list command line option, [483](#)
- gitlab-project-approval-rule-list command line option, [486](#)
- gitlab-project-audit-event-list command line option, [488](#)
- gitlab-project-badge-list command line option, [490](#)
- gitlab-project-board-list command line option, [492](#)
- gitlab-project-board-list-list command line option, [493](#)
- gitlab-project-branch-list command line option, [495](#)
- gitlab-project-cluster-list command line option, [497](#)
- gitlab-project-commit-comment-list command line option, [502](#)
- gitlab-project-commit-discussion-list command line option, [503](#)
- gitlab-project-commit-list command line option, [500](#)
- gitlab-project-commit-status-list command line option, [506](#)
- gitlab-project-custom-attribute-list command line option, [507](#)
- gitlab-project-deploy-token-list command line option, [509](#)
- gitlab-project-deployment-list command line option, [510](#)
- gitlab-project-deployment-merge-request-list command line option, [513](#)
- gitlab-project-environment-list command line option, [514](#)
- gitlab-project-event-list command line option, [516](#)
- gitlab-project-fork-list command line option, [521](#)
- gitlab-project-hook-list command line option, [523](#)
- gitlab-project-issue-award-emoji-list command line option, [533](#)
- gitlab-project-issue-discussion-list command line option, [534](#)
- gitlab-project-issue-link-list command line option, [537](#)
- gitlab-project-issue-list command line option, [527](#)
- gitlab-project-issue-note-award-emoji-list command line option, [541](#)
- gitlab-project-issue-note-list command line option, [538](#)
- gitlab-project-issue-resource-label-event-list command line option, [542](#)
- gitlab-project-issue-resource-milestone-event-list command line option, [543](#)
- gitlab-project-issue-resource-state-event-list command line option, [543](#)

`gitlab-project-job-list` command line option, [546](#)

`gitlab-project-key-list` command line option, [549](#)

`gitlab-project-label-list` command line option, [551](#)

`gitlab-project-list` command line option, [472](#)

`gitlab-project-member-all-list` command line option, [555](#)

`gitlab-project-member-list` command line option, [554](#)

`gitlab-project-merge-request-approval-rule-list` command line option, [567](#)

`gitlab-project-merge-request-award-emoji-list` command line option, [570](#)

`gitlab-project-merge-request-diff-list` command line option, [571](#)

`gitlab-project-merge-request-discussion-list` command line option, [572](#)

`gitlab-project-merge-request-list` command line option, [560](#)

`gitlab-project-merge-request-note-award-emoji-list` command line option, [578](#)

`gitlab-project-merge-request-note-list` command line option, [576](#)

`gitlab-project-merge-request-pipeline-list` command line option, [579](#)

`gitlab-project-merge-request-resource-label-event-list` command line option, [580](#)

`gitlab-project-merge-request-resource-milestone-event-list` command line option, [581](#)

`gitlab-project-merge-request-resource-state-event-list` command line option, [582](#)

`gitlab-project-merge-train-list` command line option, [583](#)

`gitlab-project-milestone-list` command line option, [585](#)

`gitlab-project-note-list` command line option, [586](#)

`gitlab-project-package-file-list` command line option, [590](#)

`gitlab-project-package-list` command line option, [589](#)

`gitlab-project-pages-domain-list` command line option, [591](#)

`gitlab-project-pipeline-bridge-list` command line option, [595](#)

`gitlab-project-pipeline-job-list` command line option, [595](#)

`gitlab-project-pipeline-list` command line option, [594](#)

`gitlab-project-pipeline-schedule-list` command line option, [597](#)

`gitlab-project-pipeline-variable-list` command line option, [601](#)

`gitlab-project-protected-branch-list` command line option, [603](#)

`gitlab-project-protected-tag-list` command line option, [604](#)

`gitlab-project-registry-repository-list` command line option, [607](#)

`gitlab-project-registry-tag-list` command line option, [609](#)

`gitlab-project-release-link-list` command line option, [613](#)

`gitlab-project-release-list` command line option, [611](#)

`gitlab-project-remote-mirror-list` command line option, [614](#)

`gitlab-project-runner-list` command line option, [616](#)

`gitlab-project-service-list` command line option, [617](#)

`gitlab-project-snippet-award-emoji-list` command line option, [622](#)

`gitlab-project-snippet-discussion-list` command line option, [623](#)

`gitlab-project-snippet-list` command line option, [619](#)

`gitlab-project-snippet-note-award-emoji-list` command line option, [629](#)

`gitlab-project-snippet-note-list` command line option, [627](#)

`gitlab-project-tag-list` command line option, [631](#)

`gitlab-project-trigger-list` command line option, [632](#)

`gitlab-project-user-list` command line option, [633](#)

`gitlab-project-variable-list` command line option, [635](#)

`gitlab-project-wiki-list` command line option, [636](#)

`gitlab-runner-job-list` command line option, [640](#)

`gitlab-runner-list` command line option, [639](#)

`gitlab-snippet-list` command line option, [642](#)

`gitlab-starred-project-list` command line option, [644](#)

`gitlab-todo-list` command line option, [645](#)

`gitlab-topic-list` command line option, [646](#)

`gitlab-user-activities-list` command line option, [652](#)

`gitlab-user-custom-attribute-list`

- command line option, [653](#)
- gitlab-user-email-list command line option, [655](#)
- gitlab-user-event-list command line option, [655](#)
- gitlab-user-gpg-key-list command line option, [657](#)
- gitlab-user-impersonation-token-list command line option, [658](#)
- gitlab-user-key-list command line option, [660](#)
- gitlab-user-list command line option, [650](#)
- gitlab-user-membership-list command line option, [661](#)
- gitlab-user-project-list command line option, [663](#)
- gitlab-variable-list command line option, [665](#)
- pages-access-level
 - gitlab-project-create command line option, [469](#)
 - gitlab-project-update command line option, [479](#)
- pagination
 - gitlab command line option, [376](#)
- parent-id
 - gitlab-group-create command line option, [399](#)
- password
 - gitlab-user-create command line option, [648](#)
 - gitlab-user-update command line option, [651](#)
- password-authentication-enabled-for-web
 - gitlab-application-settings-update command line option, [381](#)
- path
 - gitlab-generic-package-upload command line option, [394](#)
 - gitlab-group-create command line option, [398](#)
 - gitlab-group-update command line option, [403](#)
 - gitlab-project-commit-comment-create command line option, [502](#)
 - gitlab-project-commit-list command line option, [500](#)
 - gitlab-project-create command line option, [467](#)
 - gitlab-project-repository-tree command line option, [474](#)
 - gitlab-project-update command line option, [479](#)
- per-page
 - gitlab command line option, [376](#)
 - gitlab-application-list command line option, [377](#)
 - gitlab-audit-event-list command line option, [383](#)
 - gitlab-broadcast-message-list command line option, [385](#)
 - gitlab-current-user-email-list command line option, [387](#)
 - gitlab-current-user-gpg-key-list command line option, [388](#)
 - gitlab-current-user-key-list command line option, [389](#)
 - gitlab-deploy-key-list command line option, [390](#)
 - gitlab-deploy-token-list command line option, [391](#)
 - gitlab-dockerfile-list command line option, [392](#)
 - gitlab-event-list command line option, [392](#)
 - gitlab-feature-list command line option, [393](#)
 - gitlab-geo-node-list command line option, [395](#)
 - gitlab-gitignore-list command line option, [396](#)
 - gitlab-gitlabciyaml-list command line option, [397](#)
 - gitlab-group-access-request-list command line option, [405](#)
 - gitlab-group-access-token-list command line option, [406](#)
 - gitlab-group-audit-event-list command line option, [406](#)
 - gitlab-group-badge-list command line option, [408](#)
 - gitlab-group-billable-member-list command line option, [409](#)
 - gitlab-group-billable-member-membership-list command line option, [410](#)
 - gitlab-group-board-list command line option, [411](#)
 - gitlab-group-board-list-list command line option, [413](#)
 - gitlab-group-cluster-list command line option, [415](#)
 - gitlab-group-custom-attribute-list command line option, [417](#)
 - gitlab-group-deploy-token-list command line option, [418](#)
 - gitlab-group-descendant-group-list command line option, [419](#)
 - gitlab-group-epic-award-emoji-list

command line option, [423](#)
gitlab-group-epic-issue-list command line option, [426](#)
gitlab-group-epic-list command line option, [421](#)
gitlab-group-epic-note-award-emoji-list command line option, [430](#)
gitlab-group-epic-note-list command line option, [428](#)
gitlab-group-epic-resource-label-event-list command line option, [431](#)
gitlab-group-hook-list command line option, [434](#)
gitlab-group-issue-list command line option, [436](#)
gitlab-group-label-list command line option, [438](#)
gitlab-group-list command line option, [401](#)
gitlab-group-member-all-list command line option, [442](#)
gitlab-group-member-list command line option, [441](#)
gitlab-group-merge-request-list command line option, [443](#)
gitlab-group-milestone-list command line option, [445](#)
gitlab-group-package-list command line option, [448](#)
gitlab-group-project-list command line option, [450](#)
gitlab-group-runner-list command line option, [450](#)
gitlab-group-subgroup-list command line option, [451](#)
gitlab-group-variable-list command line option, [453](#)
gitlab-group-wiki-list command line option, [455](#)
gitlab-hook-list command line option, [456](#)
gitlab-issue-list command line option, [458](#)
gitlab-ldap-group-list command line option, [459](#)
gitlab-license-list command line option, [460](#)
gitlab-merge-request-list command line option, [462](#)
gitlab-namespace-list command line option, [462](#)
gitlab-pages-domain-list command line option, [464](#)
gitlab-personal-access-token-list command line option, [465](#)
gitlab-project-access-request-list command line option, [482](#)
gitlab-project-access-token-list command line option, [483](#)
gitlab-project-approval-rule-list command line option, [486](#)
gitlab-project-audit-event-list command line option, [488](#)
gitlab-project-badge-list command line option, [490](#)
gitlab-project-board-list command line option, [492](#)
gitlab-project-board-list-list command line option, [493](#)
gitlab-project-branch-list command line option, [495](#)
gitlab-project-cluster-list command line option, [497](#)
gitlab-project-commit-comment-list command line option, [502](#)
gitlab-project-commit-discussion-list command line option, [503](#)
gitlab-project-commit-list command line option, [500](#)
gitlab-project-commit-status-list command line option, [506](#)
gitlab-project-custom-attribute-list command line option, [507](#)
gitlab-project-deploy-token-list command line option, [509](#)
gitlab-project-deployment-list command line option, [510](#)
gitlab-project-deployment-merge-request-list command line option, [513](#)
gitlab-project-environment-list command line option, [514](#)
gitlab-project-event-list command line option, [516](#)
gitlab-project-fork-list command line option, [521](#)
gitlab-project-hook-list command line option, [523](#)
gitlab-project-issue-award-emoji-list command line option, [533](#)
gitlab-project-issue-discussion-list command line option, [534](#)
gitlab-project-issue-link-list command line option, [537](#)
gitlab-project-issue-list command line option, [527](#)
gitlab-project-issue-note-award-emoji-list command line option, [541](#)
gitlab-project-issue-note-list command line option, [538](#)

- gitlab-project-issue-resource-label-event-list command line option, 542
- gitlab-project-issue-resource-milestone-event-list command line option, 543
- gitlab-project-issue-resource-state-event-list command line option, 544
- gitlab-project-job-list command line option, 546
- gitlab-project-key-list command line option, 549
- gitlab-project-label-list command line option, 551
- gitlab-project-list command line option, 472
- gitlab-project-member-all-list command line option, 555
- gitlab-project-member-list command line option, 554
- gitlab-project-merge-request-approval-rule-list command line option, 567
- gitlab-project-merge-request-award-emoji-list command line option, 570
- gitlab-project-merge-request-diff-list command line option, 571
- gitlab-project-merge-request-discussion-list command line option, 572
- gitlab-project-merge-request-list command line option, 560
- gitlab-project-merge-request-note-award-emoji-list command line option, 578
- gitlab-project-merge-request-note-list command line option, 576
- gitlab-project-merge-request-pipeline-list command line option, 579
- gitlab-project-merge-request-resource-label-event-list command line option, 580
- gitlab-project-merge-request-resource-milestone-event-list command line option, 581
- gitlab-project-merge-request-resource-state-event-list command line option, 582
- gitlab-project-merge-train-list command line option, 583
- gitlab-project-milestone-list command line option, 585
- gitlab-project-note-list command line option, 586
- gitlab-project-package-file-list command line option, 590
- gitlab-project-package-list command line option, 589
- gitlab-project-pages-domain-list command line option, 591
- gitlab-project-pipeline-bridge-list command line option, 595
- gitlab-project-pipeline-job-list command line option, 595
- gitlab-project-pipeline-list command line option, 594
- gitlab-project-pipeline-schedule-list command line option, 597
- gitlab-project-pipeline-variable-list command line option, 601
- gitlab-project-protected-branch-list command line option, 603
- gitlab-project-protected-tag-list command line option, 604
- gitlab-project-registry-repository-list command line option, 607
- gitlab-project-registry-tag-list command line option, 609
- gitlab-project-release-link-list command line option, 613
- gitlab-project-release-list command line option, 611
- gitlab-project-remote-mirror-list command line option, 614
- gitlab-project-runner-list command line option, 616
- gitlab-project-service-list command line option, 617
- gitlab-project-snippet-award-emoji-list command line option, 622
- gitlab-project-snippet-discussion-list command line option, 623
- gitlab-project-snippet-list command line option, 619
- gitlab-project-snippet-note-award-emoji-list command line option, 629
- gitlab-project-snippet-note-list command line option, 627
- gitlab-project-snippet-tag-list command line option, 631
- gitlab-project-trigger-list command line option, 632
- gitlab-project-user-list command line option, 633
- gitlab-project-variable-list command line option, 635
- gitlab-project-wiki-list command line option, 637
- gitlab-runner-job-list command line option, 640
- gitlab-runner-list command line option, 639
- gitlab-snippet-list command line option, 642
- gitlab-starred-project-list command line option, 644

- gitlab-todo-list command line option, [645](#)
- gitlab-topic-list command line option, [646](#)
- gitlab-user-activities-list command line option, [652](#)
- gitlab-user-custom-attribute-list command line option, [653](#)
- gitlab-user-email-list command line option, [655](#)
- gitlab-user-event-list command line option, [655](#)
- gitlab-user-gpg-key-list command line option, [657](#)
- gitlab-user-impersonation-token-list command line option, [658](#)
- gitlab-user-key-list command line option, [660](#)
- gitlab-user-list command line option, [650](#)
- gitlab-user-membership-list command line option, [661](#)
- gitlab-user-project-list command line option, [663](#)
- gitlab-variable-list command line option, [665](#)
- performance-bar-allowed-group-id
 - gitlab-application-settings-update command line option, [382](#)
- pipeline-events
 - gitlab-group-hook-create command line option, [433](#)
 - gitlab-group-hook-update command line option, [435](#)
 - gitlab-project-hook-create command line option, [522](#)
 - gitlab-project-hook-update command line option, [524](#)
- pipeline-id
 - gitlab-project-pipeline-bridge-list command line option, [594](#)
 - gitlab-project-pipeline-job-list command line option, [595](#)
 - gitlab-project-pipeline-test-report-get command line option, [600](#)
 - gitlab-project-pipeline-test-report-summary-get command line option, [600](#)
 - gitlab-project-pipeline-variable-list command line option, [601](#)
- pipeline-schedule-id
 - gitlab-project-pipeline-schedule-variable-create command line option, [598](#)
 - gitlab-project-pipeline-schedule-variable-delete command line option, [599](#)
 - gitlab-project-pipeline-schedule-variable-update command line option, [599](#)
- plantuml-enabled
 - gitlab-application-settings-update command line option, [382](#)
- plantuml-url
 - gitlab-application-settings-update command line option, [382](#)
- platform-kubernetes-attributes
 - gitlab-group-cluster-create command line option, [414](#)
 - gitlab-group-cluster-update command line option, [415](#)
 - gitlab-project-cluster-create command line option, [496](#)
 - gitlab-project-cluster-update command line option, [498](#)
- polling-interval-multiplier
 - gitlab-application-settings-update command line option, [382](#)
- popular
 - gitlab-license-list command line option, [460](#)
- position
 - gitlab-group-board-list-update command line option, [413](#)
 - gitlab-project-board-list-update command line option, [494](#)
 - gitlab-project-commit-discussion-note-create command line option, [504](#)
 - gitlab-project-merge-request-discussion-create command line option, [571](#)
- prevent-forking-outside-group
 - gitlab-group-update command line option, [403](#)
- prevent-secrets
 - gitlab-project-push-rules-create command line option, [605](#)
 - gitlab-project-push-rules-update command line option, [606](#)
- printing-merge-request-link-enabled
 - gitlab-project-create command line option, [469](#)
- priority
 - gitlab-group-label-create command line option, [437](#)
 - gitlab-group-label-update command line option, [439](#)
 - gitlab-project-label-create command line option, [550](#)
 - gitlab-project-label-update command line option, [552](#)
- private-profile
 - gitlab-user-create command line option, [648](#)
 - gitlab-user-update command line option, [648](#)

- 652
- private-token
 - gitlab command line option, 376
 - project
 - gitlab-license-get command line option, 459
 - project-creation-level
 - gitlab-group-create command line option, 399
 - gitlab-group-update command line option, 403
 - project-id
 - gitlab-generic-package-download command line option, 393
 - gitlab-generic-package-upload command line option, 394
 - gitlab-group-transfer-project command line option, 402
 - gitlab-project-access-request-approve command line option, 481
 - gitlab-project-access-request-create command line option, 481
 - gitlab-project-access-request-delete command line option, 482
 - gitlab-project-access-request-list command line option, 482
 - gitlab-project-access-token-create command line option, 482
 - gitlab-project-access-token-delete command line option, 483
 - gitlab-project-access-token-list command line option, 483
 - gitlab-project-additional-statistics-get command line option, 483
 - gitlab-project-approval-get command line option, 484
 - gitlab-project-approval-rule-create command line option, 485
 - gitlab-project-approval-rule-delete command line option, 485
 - gitlab-project-approval-rule-list command line option, 486
 - gitlab-project-approval-rule-update command line option, 486
 - gitlab-project-approval-update command line option, 484
 - gitlab-project-artifact-delete command line option, 486
 - gitlab-project-artifact-download command line option, 487
 - gitlab-project-artifact-raw command line option, 487
 - gitlab-project-audit-event-get command line option, 488
 - gitlab-project-audit-event-list command line option, 488
 - gitlab-project-badge-create command line option, 489
 - gitlab-project-badge-delete command line option, 489
 - gitlab-project-badge-get command line option, 489
 - gitlab-project-badge-list command line option, 490
 - gitlab-project-badge-render command line option, 490
 - gitlab-project-badge-update command line option, 490
 - gitlab-project-board-create command line option, 491
 - gitlab-project-board-delete command line option, 491
 - gitlab-project-board-get command line option, 491
 - gitlab-project-board-list command line option, 492
 - gitlab-project-board-list-create command line option, 492
 - gitlab-project-board-list-delete command line option, 493
 - gitlab-project-board-list-get command line option, 493
 - gitlab-project-board-list-list command line option, 493
 - gitlab-project-board-list-update command line option, 494
 - gitlab-project-board-update command line option, 492
 - gitlab-project-branch-create command line option, 494
 - gitlab-project-branch-delete command line option, 495
 - gitlab-project-branch-get command line option, 495
 - gitlab-project-branch-list command line option, 495
 - gitlab-project-cluster-create command line option, 496
 - gitlab-project-cluster-delete command line option, 496
 - gitlab-project-cluster-get command line option, 497
 - gitlab-project-cluster-list command line option, 497
 - gitlab-project-cluster-update command line option, 497
 - gitlab-project-commit-cherry-pick command line option, 498

`gitlab-project-commit-comment-create`
command line option, [501](#)

`gitlab-project-commit-comment-list`
command line option, [502](#)

`gitlab-project-commit-create` command
line option, [498](#)

`gitlab-project-commit-diff` command line
option, [499](#)

`gitlab-project-commit-discussion-create`
command line option, [502](#)

`gitlab-project-commit-discussion-get`
command line option, [503](#)

`gitlab-project-commit-discussion-list`
command line option, [503](#)

`gitlab-project-commit-discussion-note-create`
command line option, [504](#)

`gitlab-project-commit-discussion-note-delete`
command line option, [504](#)

`gitlab-project-commit-discussion-note-get`
command line option, [505](#)

`gitlab-project-commit-discussion-note-update`
command line option, [505](#)

`gitlab-project-commit-get` command line
option, [499](#)

`gitlab-project-commit-list` command line
option, [499](#)

`gitlab-project-commit-merge-requests`
command line option, [500](#)

`gitlab-project-commit-refs` command line
option, [500](#)

`gitlab-project-commit-revert` command
line option, [501](#)

`gitlab-project-commit-signature` command
line option, [501](#)

`gitlab-project-commit-status-create`
command line option, [506](#)

`gitlab-project-commit-status-list`
command line option, [506](#)

`gitlab-project-custom-attribute-delete`
command line option, [507](#)

`gitlab-project-custom-attribute-get`
command line option, [507](#)

`gitlab-project-custom-attribute-list`
command line option, [507](#)

`gitlab-project-deploy-token-create`
command line option, [508](#)

`gitlab-project-deploy-token-delete`
command line option, [508](#)

`gitlab-project-deploy-token-get` command
line option, [508](#)

`gitlab-project-deploy-token-list`
command line option, [509](#)

`gitlab-project-deployment-create`
command line option, [509](#)

`gitlab-project-deployment-get` command
line option, [510](#)

`gitlab-project-deployment-list` command
line option, [510](#)

`gitlab-project-deployment-merge-request-list`
command line option, [512](#)

`gitlab-project-deployment-update`
command line option, [511](#)

`gitlab-project-environment-create`
command line option, [513](#)

`gitlab-project-environment-delete`
command line option, [514](#)

`gitlab-project-environment-get` command
line option, [514](#)

`gitlab-project-environment-list` command
line option, [514](#)

`gitlab-project-environment-stop` command
line option, [515](#)

`gitlab-project-environment-update`
command line option, [515](#)

`gitlab-project-event-list` command line
option, [516](#)

`gitlab-project-export-create` command
line option, [516](#)

`gitlab-project-export-download` command
line option, [516](#)

`gitlab-project-export-get` command line
option, [517](#)

`gitlab-project-file-blame` command line
option, [517](#)

`gitlab-project-file-create` command line
option, [517](#)

`gitlab-project-file-delete` command line
option, [518](#)

`gitlab-project-file-get` command line
option, [518](#)

`gitlab-project-file-raw` command line
option, [519](#)

`gitlab-project-file-update` command line
option, [519](#)

`gitlab-project-fork-create` command line
option, [520](#)

`gitlab-project-fork-list` command line
option, [520](#)

`gitlab-project-hook-create` command line
option, [521](#)

`gitlab-project-hook-delete` command line
option, [522](#)

`gitlab-project-hook-get` command line
option, [522](#)

`gitlab-project-hook-list` command line
option, [523](#)

`gitlab-project-hook-update` command line
option, [523](#)

gitlab-project-import-get command line option, [524](#)

gitlab-project-issue-add-spent-time command line option, [524](#)

gitlab-project-issue-award-emoji-create command line option, [531](#)

gitlab-project-issue-award-emoji-delete command line option, [532](#)

gitlab-project-issue-award-emoji-get command line option, [532](#)

gitlab-project-issue-award-emoji-list command line option, [532](#)

gitlab-project-issue-closed-by command line option, [525](#)

gitlab-project-issue-create command line option, [525](#)

gitlab-project-issue-delete command line option, [526](#)

gitlab-project-issue-discussion-create command line option, [533](#)

gitlab-project-issue-discussion-get command line option, [533](#)

gitlab-project-issue-discussion-list command line option, [534](#)

gitlab-project-issue-discussion-note-create command line option, [534](#)

gitlab-project-issue-discussion-note-delete command line option, [535](#)

gitlab-project-issue-discussion-note-get command line option, [535](#)

gitlab-project-issue-discussion-note-update command line option, [536](#)

gitlab-project-issue-get command line option, [526](#)

gitlab-project-issue-link-create command line option, [536](#)

gitlab-project-issue-link-delete command line option, [536](#)

gitlab-project-issue-link-list command line option, [537](#)

gitlab-project-issue-list command line option, [527](#)

gitlab-project-issue-move command line option, [527](#)

gitlab-project-issue-note-award-emoji-create command line option, [539](#)

gitlab-project-issue-note-award-emoji-delete command line option, [540](#)

gitlab-project-issue-note-award-emoji-get command line option, [540](#)

gitlab-project-issue-note-award-emoji-list command line option, [541](#)

gitlab-project-issue-note-create command line option, [537](#)

gitlab-project-issue-note-delete command line option, [538](#)

gitlab-project-issue-note-get command line option, [538](#)

gitlab-project-issue-note-list command line option, [538](#)

gitlab-project-issue-note-update command line option, [539](#)

gitlab-project-issue-participants command line option, [528](#)

gitlab-project-issue-related-merge-requests command line option, [528](#)

gitlab-project-issue-reset-spent-time command line option, [528](#)

gitlab-project-issue-reset-time-estimate command line option, [528](#)

gitlab-project-issue-resource-label-event-get command line option, [541](#)

gitlab-project-issue-resource-label-event-list command line option, [541](#)

gitlab-project-issue-resource-milestone-event-get command line option, [542](#)

gitlab-project-issue-resource-milestone-event-list command line option, [542](#)

gitlab-project-issue-resource-state-event-get command line option, [543](#)

gitlab-project-issue-resource-state-event-list command line option, [543](#)

gitlab-project-issue-subscribe command line option, [529](#)

gitlab-project-issue-time-estimate command line option, [529](#)

gitlab-project-issue-time-stats command line option, [529](#)

gitlab-project-issue-todo command line option, [530](#)

gitlab-project-issue-unsubscribe command line option, [530](#)

gitlab-project-issue-update command line option, [530](#)

gitlab-project-issue-user-agent-detail command line option, [531](#)

gitlab-project-issues-statistics-get command line option, [544](#)

gitlab-project-job-artifact command line option, [544](#)

gitlab-project-job-artifacts command line option, [545](#)

gitlab-project-job-cancel command line option, [545](#)

gitlab-project-job-delete-artifacts command line option, [545](#)

gitlab-project-job-erase command line option, [545](#)

`gitlab-project-job-get` command line option, [546](#)
`gitlab-project-job-keep-artifacts` command line option, [546](#)
`gitlab-project-job-list` command line option, [546](#)
`gitlab-project-job-play` command line option, [547](#)
`gitlab-project-job-retry` command line option, [547](#)
`gitlab-project-job-trace` command line option, [547](#)
`gitlab-project-key-create` command line option, [548](#)
`gitlab-project-key-delete` command line option, [548](#)
`gitlab-project-key-enable` command line option, [548](#)
`gitlab-project-key-get` command line option, [549](#)
`gitlab-project-key-list` command line option, [549](#)
`gitlab-project-key-update` command line option, [549](#)
`gitlab-project-label-create` command line option, [550](#)
`gitlab-project-label-delete` command line option, [550](#)
`gitlab-project-label-get` command line option, [551](#)
`gitlab-project-label-list` command line option, [551](#)
`gitlab-project-label-subscribe` command line option, [551](#)
`gitlab-project-label-unsubscribe` command line option, [552](#)
`gitlab-project-label-update` command line option, [552](#)
`gitlab-project-member-all-get` command line option, [555](#)
`gitlab-project-member-all-list` command line option, [555](#)
`gitlab-project-member-create` command line option, [553](#)
`gitlab-project-member-delete` command line option, [553](#)
`gitlab-project-member-get` command line option, [553](#)
`gitlab-project-member-list` command line option, [554](#)
`gitlab-project-member-update` command line option, [554](#)
`gitlab-project-merge-request-add-spent-time` command line option, [555](#)
`gitlab-project-merge-request-approval-get` command line option, [565](#)
`gitlab-project-merge-request-approval-rule-create` command line option, [566](#)
`gitlab-project-merge-request-approval-rule-delete` command line option, [566](#)
`gitlab-project-merge-request-approval-rule-list` command line option, [567](#)
`gitlab-project-merge-request-approval-rule-update` command line option, [568](#)
`gitlab-project-merge-request-approval-state-get` command line option, [568](#)
`gitlab-project-merge-request-approval-update` command line option, [565](#)
`gitlab-project-merge-request-approve` command line option, [556](#)
`gitlab-project-merge-request-award-emoji-create` command line option, [569](#)
`gitlab-project-merge-request-award-emoji-delete` command line option, [569](#)
`gitlab-project-merge-request-award-emoji-get` command line option, [569](#)
`gitlab-project-merge-request-award-emoji-list` command line option, [570](#)
`gitlab-project-merge-request-cancel-merge-when-pipeline` command line option, [556](#)
`gitlab-project-merge-request-changes` command line option, [556](#)
`gitlab-project-merge-request-closes-issues` command line option, [557](#)
`gitlab-project-merge-request-commits` command line option, [557](#)
`gitlab-project-merge-request-create` command line option, [557](#)
`gitlab-project-merge-request-delete` command line option, [558](#)
`gitlab-project-merge-request-diff-get` command line option, [570](#)
`gitlab-project-merge-request-diff-list` command line option, [571](#)
`gitlab-project-merge-request-discussion-create` command line option, [571](#)
`gitlab-project-merge-request-discussion-get` command line option, [572](#)
`gitlab-project-merge-request-discussion-list` command line option, [572](#)
`gitlab-project-merge-request-discussion-note-create` command line option, [573](#)
`gitlab-project-merge-request-discussion-note-delete` command line option, [574](#)
`gitlab-project-merge-request-discussion-note-get` command line option, [574](#)
`gitlab-project-merge-request-discussion-note-update` command line option, [574](#)

- gitlab-project-merge-request-discussion-update command line option, 572
- gitlab-project-merge-request-get command line option, 558
- gitlab-project-merge-request-list command line option, 559
- gitlab-project-merge-request-merge command line option, 560
- gitlab-project-merge-request-merge-ref command line option, 561
- gitlab-project-merge-request-note-award-emoji-create command line option, 577
- gitlab-project-merge-request-note-award-emoji-delete command line option, 577
- gitlab-project-merge-request-note-award-emoji-get command line option, 578
- gitlab-project-merge-request-note-award-emoji-list command line option, 578
- gitlab-project-merge-request-note-create command line option, 575
- gitlab-project-merge-request-note-delete command line option, 575
- gitlab-project-merge-request-note-get command line option, 576
- gitlab-project-merge-request-note-list command line option, 576
- gitlab-project-merge-request-note-update command line option, 576
- gitlab-project-merge-request-participants command line option, 561
- gitlab-project-merge-request-pipeline-create command line option, 579
- gitlab-project-merge-request-pipeline-list command line option, 579
- gitlab-project-merge-request-rebase command line option, 561
- gitlab-project-merge-request-reset-spent-time command line option, 561
- gitlab-project-merge-request-reset-time-estimate command line option, 562
- gitlab-project-merge-request-resource-label-event-get command line option, 580
- gitlab-project-merge-request-resource-label-event-list command line option, 580
- gitlab-project-merge-request-resource-milestone-get command line option, 581
- gitlab-project-merge-request-resource-milestone-list command line option, 581
- gitlab-project-merge-request-resource-state-event-get command line option, 582
- gitlab-project-merge-request-resource-state-event-list command line option, 582
- gitlab-project-merge-request-subscribe command line option, 562
- gitlab-project-merge-request-time-estimate command line option, 562
- gitlab-project-merge-request-time-stats command line option, 563
- gitlab-project-merge-request-todo command line option, 563
- gitlab-project-merge-request-unapprove command line option, 563
- gitlab-project-merge-request-unsubscribe command line option, 563
- gitlab-project-merge-request-update command line option, 564
- gitlab-project-merge-train-list command line option, 583
- gitlab-project-milestone-create command line option, 583
- gitlab-project-milestone-delete command line option, 584
- gitlab-project-milestone-get command line option, 584
- gitlab-project-milestone-issues command line option, 584
- gitlab-project-milestone-list command line option, 585
- gitlab-project-milestone-merge-requests command line option, 585
- gitlab-project-milestone-update command line option, 585
- gitlab-project-note-get command line option, 586
- gitlab-project-note-list command line option, 586
- gitlab-project-notification-settings-get command line option, 587
- gitlab-project-notification-settings-update command line option, 587
- gitlab-project-package-delete command line option, 588
- gitlab-project-package-file-delete command line option, 589
- gitlab-project-package-file-list command line option, 590
- gitlab-project-package-get command line option, 588
- gitlab-project-package-list command line option, 589
- gitlab-project-pages-domain-create command line option, 590
- gitlab-project-pages-domain-delete command line option, 591
- gitlab-project-pages-domain-get command line option, 591
- gitlab-project-pages-domain-list command line option, 591

<code>gitlab-project-pages-domain-update</code> command line option, 592	<code>gitlab-project-protected-tag-delete</code> command line option, 603
<code>gitlab-project-pipeline-bridge-list</code> command line option, 594	<code>gitlab-project-protected-tag-get</code> command line option, 604
<code>gitlab-project-pipeline-cancel</code> command line option, 592	<code>gitlab-project-protected-tag-list</code> command line option, 604
<code>gitlab-project-pipeline-create</code> command line option, 592	<code>gitlab-project-push-rules-create</code> command line option, 605
<code>gitlab-project-pipeline-delete</code> command line option, 593	<code>gitlab-project-push-rules-delete</code> command line option, 605
<code>gitlab-project-pipeline-get</code> command line option, 593	<code>gitlab-project-push-rules-get</code> command line option, 606
<code>gitlab-project-pipeline-job-list</code> command line option, 595	<code>gitlab-project-push-rules-update</code> command line option, 606
<code>gitlab-project-pipeline-list</code> command line option, 593	<code>gitlab-project-registry-repository-delete</code> command line option, 607
<code>gitlab-project-pipeline-retry</code> command line option, 594	<code>gitlab-project-registry-repository-list</code> command line option, 607
<code>gitlab-project-pipeline-schedule-create</code> command line option, 596	<code>gitlab-project-registry-tag-delete</code> command line option, 608
<code>gitlab-project-pipeline-schedule-delete</code> command line option, 596	<code>gitlab-project-registry-tag-delete-in-bulk</code> command line option, 608
<code>gitlab-project-pipeline-schedule-get</code> command line option, 596	<code>gitlab-project-registry-tag-get</code> command line option, 609
<code>gitlab-project-pipeline-schedule-list</code> command line option, 597	<code>gitlab-project-registry-tag-list</code> command line option, 609
<code>gitlab-project-pipeline-schedule-play</code> command line option, 597	<code>gitlab-project-release-create</code> command line option, 610
<code>gitlab-project-pipeline-schedule-take-ownership</code> command line option, 597	<code>gitlab-project-release-delete</code> command line option, 610
<code>gitlab-project-pipeline-schedule-update</code> command line option, 598	<code>gitlab-project-release-get</code> command line option, 610
<code>gitlab-project-pipeline-schedule-variable-create</code> command line option, 598	<code>gitlab-project-release-link-create</code> command line option, 612
<code>gitlab-project-pipeline-schedule-variable-delete</code> command line option, 599	<code>gitlab-project-release-link-delete</code> command line option, 612
<code>gitlab-project-pipeline-schedule-variable-update</code> command line option, 599	<code>gitlab-project-release-link-get</code> command line option, 612
<code>gitlab-project-pipeline-test-report-get</code> command line option, 600	<code>gitlab-project-release-link-list</code> command line option, 613
<code>gitlab-project-pipeline-test-report-summary-get</code> command line option, 600	<code>gitlab-project-release-link-update</code> command line option, 613
<code>gitlab-project-pipeline-variable-list</code> command line option, 601	<code>gitlab-project-release-list</code> command line option, 611
<code>gitlab-project-protected-branch-create</code> command line option, 602	<code>gitlab-project-release-update</code> command line option, 611
<code>gitlab-project-protected-branch-delete</code> command line option, 602	<code>gitlab-project-remote-mirror-create</code> command line option, 614
<code>gitlab-project-protected-branch-get</code> command line option, 602	<code>gitlab-project-remote-mirror-list</code> command line option, 614
<code>gitlab-project-protected-branch-list</code> command line option, 603	<code>gitlab-project-remote-mirror-update</code> command line option, 615
<code>gitlab-project-protected-tag-create</code> command line option, 603	<code>gitlab-project-runner-create</code> command line option, 615

gitlab-project-runner-delete command line option, [615](#)
 gitlab-project-runner-list command line option, [616](#)
 gitlab-project-service-available command line option, [616](#)
 gitlab-project-service-delete command line option, [617](#)
 gitlab-project-service-get command line option, [617](#)
 gitlab-project-service-list command line option, [617](#)
 gitlab-project-service-update command line option, [618](#)
 gitlab-project-snippet-award-emoji-create command line option, [621](#)
 gitlab-project-snippet-award-emoji-delete command line option, [621](#)
 gitlab-project-snippet-award-emoji-get command line option, [621](#)
 gitlab-project-snippet-award-emoji-list command line option, [622](#)
 gitlab-project-snippet-content command line option, [618](#)
 gitlab-project-snippet-create command line option, [618](#)
 gitlab-project-snippet-delete command line option, [619](#)
 gitlab-project-snippet-discussion-create command line option, [622](#)
 gitlab-project-snippet-discussion-get command line option, [623](#)
 gitlab-project-snippet-discussion-list command line option, [623](#)
 gitlab-project-snippet-discussion-note-create command line option, [624](#)
 gitlab-project-snippet-discussion-note-delete command line option, [624](#)
 gitlab-project-snippet-discussion-note-get command line option, [625](#)
 gitlab-project-snippet-discussion-note-update command line option, [625](#)
 gitlab-project-snippet-get command line option, [619](#)
 gitlab-project-snippet-list command line option, [619](#)
 gitlab-project-snippet-note-award-emoji-create command line option, [627](#)
 gitlab-project-snippet-note-award-emoji-delete command line option, [628](#)
 gitlab-project-snippet-note-award-emoji-get command line option, [628](#)
 gitlab-project-snippet-note-award-emoji-list command line option, [629](#)
 gitlab-project-snippet-note-create command line option, [626](#)
 gitlab-project-snippet-note-delete command line option, [626](#)
 gitlab-project-snippet-note-get command line option, [626](#)
 gitlab-project-snippet-note-list command line option, [627](#)
 gitlab-project-snippet-note-update command line option, [627](#)
 gitlab-project-snippet-update command line option, [620](#)
 gitlab-project-snippet-user-agent-detail command line option, [620](#)
 gitlab-project-storage-get command line option, [629](#)
 gitlab-project-tag-create command line option, [630](#)
 gitlab-project-tag-delete command line option, [630](#)
 gitlab-project-tag-get command line option, [630](#)
 gitlab-project-tag-list command line option, [631](#)
 gitlab-project-trigger-create command line option, [631](#)
 gitlab-project-trigger-delete command line option, [631](#)
 gitlab-project-trigger-get command line option, [632](#)
 gitlab-project-trigger-list command line option, [632](#)
 gitlab-project-trigger-update command line option, [632](#)
 gitlab-project-user-list command line option, [633](#)
 gitlab-project-variable-create command line option, [633](#)
 gitlab-project-variable-delete command line option, [634](#)
 gitlab-project-variable-get command line option, [634](#)
 gitlab-project-variable-list command line option, [634](#)
 gitlab-project-variable-update command line option, [635](#)
 gitlab-project-wiki-create command line option, [636](#)
 gitlab-project-wiki-delete command line option, [636](#)
 gitlab-project-wiki-get command line option, [636](#)
 gitlab-project-wiki-list command line option, [636](#)

- gitlab-project-wiki-update command line option, [637](#)
- gitlab-todo-list command line option, [644](#)
- projects-limit
 - gitlab-user-create command line option, [648](#)
 - gitlab-user-update command line option, [651](#)
- protected
 - gitlab-group-variable-create command line option, [452](#)
 - gitlab-group-variable-update command line option, [453](#)
 - gitlab-project-variable-create command line option, [634](#)
 - gitlab-project-variable-update command line option, [635](#)
 - gitlab-variable-create command line option, [664](#)
 - gitlab-variable-update command line option, [666](#)
- protected-branch-ids
 - gitlab-project-approval-rule-create command line option, [485](#)
- provider
 - gitlab-group-add-ldap-group-link command line option, [398](#)
 - gitlab-group-delete-ldap-group-link command line option, [399](#)
 - gitlab-ldap-group-list command line option, [459](#)
 - gitlab-user-create command line option, [648](#)
 - gitlab-user-list command line option, [650](#)
 - gitlab-user-update command line option, [651](#)
- public
 - gitlab-user-project-create command line option, [662](#)
- public-builds
 - gitlab-project-create command line option, [469](#)
 - gitlab-project-update command line option, [479](#)
 - gitlab-user-project-create command line option, [662](#)
- public-email
 - gitlab-user-create command line option, [648](#)
 - gitlab-user-update command line option, [652](#)
- push-access-level
 - gitlab-project-protected-branch-create command line option, [602](#)
- push-events
 - gitlab-group-hook-create command line option, [432](#)
 - gitlab-group-hook-update command line option, [434](#)
 - gitlab-project-hook-create command line option, [521](#)
 - gitlab-project-hook-update command line option, [523](#)
- reassign-issue
 - gitlab-group-notification-settings-update command line option, [447](#)
 - gitlab-notification-settings-update command line option, [463](#)
 - gitlab-project-notification-settings-update command line option, [588](#)
- reassign-merge-request
 - gitlab-group-notification-settings-update command line option, [448](#)
 - gitlab-notification-settings-update command line option, [464](#)
 - gitlab-project-notification-settings-update command line option, [588](#)
- recursive
 - gitlab-project-repository-tree command line option, [474](#)
- redirect-uri
 - gitlab-application-create command line option, [377](#)
- ref
 - gitlab-project-branch-create command line option, [494](#)
 - gitlab-project-commit-status-create command line option, [506](#)
 - gitlab-project-deployment-create command line option, [509](#)
 - gitlab-project-file-blame command line option, [517](#)
 - gitlab-project-file-get command line option, [518](#)
 - gitlab-project-file-raw command line option, [519](#)
 - gitlab-project-pipeline-create command line option, [592](#)
 - gitlab-project-pipeline-list command line option, [593](#)
 - gitlab-project-pipeline-schedule-create command line option, [596](#)
 - gitlab-project-pipeline-schedule-update command line option, [598](#)
 - gitlab-project-release-create command line option, [610](#)
 - gitlab-project-repository-tree command line option, [474](#)

```

gitlab-project-tag-create command line
    option, 630
gitlab-project-trigger-pipeline command
    line option, 476
--ref-name
    gitlab-project-artifact command line
        option, 465
    gitlab-project-artifact-delete command
        line option, 486
    gitlab-project-artifact-download
        command line option, 487
    gitlab-project-artifact-raw command
        line option, 487
    gitlab-project-artifacts command line
        option, 466
    gitlab-project-commit-list command line
        option, 499
--released-at
    gitlab-project-release-update command
        line option, 611
--releases-events
    gitlab-group-hook-create command line
        option, 433
    gitlab-group-hook-update command line
        option, 435
--remove-source-branch
    gitlab-project-merge-request-create
        command line option, 558
    gitlab-project-merge-request-update
        command line option, 564
--remove-source-branch-after-merge
    gitlab-project-create command line
        option, 469
    gitlab-project-update command line
        option, 480
--render-html
    gitlab-project-merge-request-get
        command line option, 558
--reopen-issue
    gitlab-group-notification-settings-update
        command line option, 447
    gitlab-notification-settings-update
        command line option, 463
    gitlab-project-notification-settings-update
        command line option, 588
--reopen-merge-request
    gitlab-group-notification-settings-update
        command line option, 447
    gitlab-notification-settings-update
        command line option, 463
    gitlab-project-notification-settings-update
        command line option, 588
--repos-max-capacity
    gitlab-geo-node-update command line
        option, 396
--repository-access-level
    gitlab-project-create command line
        option, 469
    gitlab-project-update command line
        option, 480
--repository-checksum-failed
    gitlab-project-list command line option,
        471
    gitlab-user-project-list command line
        option, 663
--repository-id
    gitlab-project-registry-tag-delete
        command line option, 608
    gitlab-project-registry-tag-delete-in-bulk
        command line option, 608
    gitlab-project-registry-tag-get command
        line option, 609
    gitlab-project-registry-tag-list
        command line option, 609
--repository-storage
    gitlab-project-create command line
        option, 469
    gitlab-project-list command line option,
        471
    gitlab-project-update command line
        option, 480
--repository-storages
    gitlab-application-settings-update
        command line option, 382
--request-access-enabled
    gitlab-group-create command line option,
        399
    gitlab-group-update command line option,
        403
    gitlab-project-create command line
        option, 469
    gitlab-project-update command line
        option, 480
--require-two-factor-authentication
    gitlab-group-create command line option,
        399
    gitlab-group-update command line option,
        403
--requirements-access-level
    gitlab-project-create command line
        option, 469
    gitlab-project-update command line
        option, 479
--reset-approvals-on-push
    gitlab-project-approval-update command
        line option, 484
--reset-password
    gitlab-user-create command line option,

```

648
--resolve-outdated-diff-discussions
 gitlab-project-create command line
 option, 469
 gitlab-project-update command line
 option, 480
--resolved
 gitlab-project-merge-request-discussion-update command line option, 573
--restrict-user-defined-variables
 gitlab-project-update command line
 option, 479
--restricted-visibility-levels
 gitlab-application-settings-update
 command line option, 381
--reviewer-id
 gitlab-merge-request-list command line
 option, 461
 gitlab-project-deployment-merge-request-list
 command line option, 512
--reviewer-ids
 gitlab-project-merge-request-create
 command line option, 558
 gitlab-project-merge-request-update
 command line option, 564
--reviewer-username
 gitlab-merge-request-list command line
 option, 461
 gitlab-project-deployment-merge-request-list
 command line option, 512
--rsa-key-restriction
 gitlab-application-settings-update
 command line option, 382
--rule-type
 gitlab-project-merge-request-approval-rule-list
 command line option, 567
--run-untagged
 gitlab-runner-create command line
 option, 638
 gitlab-runner-update command line
 option, 639
--runner-id
 gitlab-project-runner-create command
 line option, 615
 gitlab-runner-job-list command line
 option, 640
--scope
 gitlab-group-merge-request-list command
 line option, 443
 gitlab-group-runner-list command line
 option, 450
 gitlab-group-search command line option,
 401
 gitlab-issue-list command line option,
 457
 gitlab-merge-request-list command line
 option, 461
 gitlab-project-deployment-merge-request-list
 command line option, 512
 gitlab-project-issue-list command line
 option, 527
 gitlab-project-merge-request-list
 command line option, 559
 gitlab-project-merge-train-list command
 line option, 583
 gitlab-project-pipeline-bridge-list
 command line option, 594
 gitlab-project-pipeline-job-list
 command line option, 595
 gitlab-project-pipeline-list command
 line option, 593
 gitlab-project-runner-list command line
 option, 616
 gitlab-project-search command line
 option, 474
 gitlab-runner-all command line option,
 637
 gitlab-runner-list command line option,
 639
--scopes
 gitlab-application-create command line
 option, 377
 gitlab-group-deploy-token-create
 command line option, 417
 gitlab-project-deploy-token-create
 command line option, 508
 gitlab-user-impersonation-token-create
 command line option, 657
 gitlab-user-personal-access-token-create
 command line option, 661
--search
 gitlab-group-billable-member-list
 command line option, 409
 gitlab-group-descendant-group-list
 command line option, 419
 gitlab-group-epic-list command line
 option, 421
 gitlab-group-issue-list command line
 option, 436
 gitlab-group-list command line option,
 400
 gitlab-group-merge-request-list command
 line option, 443
 gitlab-group-milestone-list command
 line option, 445
 gitlab-group-project-list command line
 option, 449
 gitlab-group-search command line option,

- 401
- gitlab-group-subgroup-list command line option, 451
- gitlab-issue-list command line option, 458
- gitlab-ldap-group-list command line option, 459
- gitlab-merge-request-list command line option, 461
- gitlab-namespace-list command line option, 462
- gitlab-project-deployment-merge-request-list command line option, 513
- gitlab-project-environment-list command line option, 514
- gitlab-project-fork-list command line option, 520
- gitlab-project-issue-list command line option, 527
- gitlab-project-list command line option, 472
- gitlab-project-merge-request-list command line option, 560
- gitlab-project-milestone-list command line option, 585
- gitlab-project-search command line option, 474
- gitlab-project-user-list command line option, 633
- gitlab-starred-project-list command line option, 643
- gitlab-user-list command line option, 650
- gitlab-user-project-list command line option, 663
- search-namespaces
 - gitlab-project-list command line option, 472
- server-url
 - gitlab command line option, 376
- service-desk-enabled
 - gitlab-project-update command line option, 480
- session-expire-delay
 - gitlab-application-settings-update command line option, 381
- sha
 - gitlab-project-deployment-create command line option, 509
 - gitlab-project-merge-request-approve command line option, 556
 - gitlab-project-pipeline-list command line option, 593
 - gitlab-project-repository-archive command line option, 472
 - gitlab-project-repository-blob command line option, 473
 - gitlab-project-repository-raw-blob command line option, 473
- share-with-group-lock
 - gitlab-group-create command line option, 398
 - gitlab-group-update command line option, 403
- shared-runners-enabled
 - gitlab-project-create command line option, 469
 - gitlab-project-update command line option, 480
- shared-runners-minutes-limit
 - gitlab-group-create command line option, 399
 - gitlab-group-update command line option, 403
- shared-runners-setting
 - gitlab-group-update command line option, 403
- should-remove-source-branch
 - gitlab-project-merge-request-merge command line option, 560
- show-default-award-emojis
 - gitlab-project-create command line option, 469
 - gitlab-project-update command line option, 480
- sign-in-text
 - gitlab-application-settings-update command line option, 381
- signup-enabled
 - gitlab-application-settings-update command line option, 381
- simple
 - gitlab-group-project-list command line option, 449
 - gitlab-project-fork-list command line option, 520
 - gitlab-project-list command line option, 472
 - gitlab-starred-project-list command line option, 643
 - gitlab-user-project-list command line option, 663
- since
 - gitlab-project-commit-list command line option, 499
- skip-confirmation
 - gitlab-user-create command line option, 648
- skip-groups

- gitlab-group-descendant-group-list
 - command line option, [419](#)
- gitlab-group-list command line option, [400](#)
- gitlab-group-subgroup-list command line option, [451](#)
- skip-reconfirmation
 - gitlab-user-update command line option, [651](#)
- skip-users
 - gitlab-project-user-list command line option, [633](#)
- skype
 - gitlab-user-create command line option, [648](#)
 - gitlab-user-update command line option, [651](#)
- slug
 - gitlab-group-wiki-delete command line option, [454](#)
 - gitlab-group-wiki-get command line option, [454](#)
 - gitlab-group-wiki-update command line option, [455](#)
 - gitlab-project-service-available command line option, [616](#)
 - gitlab-project-service-delete command line option, [617](#)
 - gitlab-project-service-get command line option, [617](#)
 - gitlab-project-service-update command line option, [618](#)
 - gitlab-project-wiki-delete command line option, [636](#)
 - gitlab-project-wiki-get command line option, [636](#)
 - gitlab-project-wiki-update command line option, [637](#)
- snippet-id
 - gitlab-project-snippet-award-emoji-create command line option, [621](#)
 - gitlab-project-snippet-award-emoji-delete command line option, [621](#)
 - gitlab-project-snippet-award-emoji-get command line option, [621](#)
 - gitlab-project-snippet-award-emoji-list command line option, [622](#)
 - gitlab-project-snippet-discussion-create command line option, [622](#)
 - gitlab-project-snippet-discussion-get command line option, [623](#)
 - gitlab-project-snippet-discussion-list command line option, [623](#)
 - gitlab-project-snippet-discussion-note-create command line option, [624](#)
- gitlab-project-snippet-discussion-note-delete command line option, [624](#)
- gitlab-project-snippet-discussion-note-get command line option, [625](#)
- gitlab-project-snippet-discussion-note-update command line option, [625](#)
- gitlab-project-snippet-note-award-emoji-create command line option, [628](#)
- gitlab-project-snippet-note-award-emoji-delete command line option, [628](#)
- gitlab-project-snippet-note-award-emoji-get command line option, [628](#)
- gitlab-project-snippet-note-award-emoji-list command line option, [629](#)
- gitlab-project-snippet-note-create command line option, [626](#)
- gitlab-project-snippet-note-delete command line option, [626](#)
- gitlab-project-snippet-note-get command line option, [626](#)
- gitlab-project-snippet-note-list command line option, [627](#)
- gitlab-project-snippet-note-update command line option, [627](#)
- snippets-access-level
 - gitlab-project-create command line option, [469](#)
 - gitlab-project-update command line option, [480](#)
- snippets-enabled
 - gitlab-project-create command line option, [469](#)
 - gitlab-project-update command line option, [480](#)
 - gitlab-user-project-create command line option, [662](#)
- sort
 - gitlab-event-list command line option, [392](#)
 - gitlab-group-billable-member-list command line option, [409](#)
 - gitlab-group-descendant-group-list command line option, [419](#)
 - gitlab-group-epic-list command line option, [421](#)
 - gitlab-group-issue-list command line option, [436](#)
 - gitlab-group-list command line option, [400](#)
 - gitlab-group-merge-request-list command line option, [443](#)
 - gitlab-group-package-list command line option, [448](#)

- gitlab-group-project-list command line option, [449](#)
- gitlab-group-subgroup-list command line option, [451](#)
- gitlab-issue-list command line option, [457](#)
- gitlab-merge-request-list command line option, [461](#)
- gitlab-project-deployment-list command line option, [510](#)
- gitlab-project-deployment-merge-request-list command line option, [512](#)
- gitlab-project-event-list command line option, [516](#)
- gitlab-project-fork-list command line option, [520](#)
- gitlab-project-issue-list command line option, [527](#)
- gitlab-project-list command line option, [472](#)
- gitlab-project-merge-request-list command line option, [559](#)
- gitlab-project-package-list command line option, [589](#)
- gitlab-project-pipeline-list command line option, [594](#)
- gitlab-starred-project-list command line option, [643](#)
- gitlab-user-event-list command line option, [655](#)
- gitlab-user-project-list command line option, [663](#)
- source-branch
 - gitlab-group-merge-request-list command line option, [443](#)
 - gitlab-merge-request-list command line option, [461](#)
 - gitlab-project-deployment-merge-request-list command line option, [513](#)
 - gitlab-project-merge-request-create command line option, [557](#)
 - gitlab-project-merge-request-list command line option, [560](#)
- source-id
 - gitlab-user-membership-get command line option, [660](#)
- squash
 - gitlab-project-merge-request-create command line option, [558](#)
 - gitlab-project-merge-request-update command line option, [564](#)
- squash-option
 - gitlab-project-create command line option, [469](#)
 - gitlab-project-update command line option, [480](#)
- gitlab-user-project-create command line option, [662](#)
- ssl-verify
 - gitlab command line option, [376](#)
- starred
 - gitlab-group-project-list command line option, [449](#)
 - gitlab-project-fork-list command line option, [521](#)
 - gitlab-project-list command line option, [472](#)
 - gitlab-starred-project-list command line option, [644](#)
 - gitlab-user-project-list command line option, [663](#)
- start-date
 - gitlab-group-epic-create command line option, [420](#)
 - gitlab-group-epic-update command line option, [421](#)
 - gitlab-group-milestone-create command line option, [444](#)
 - gitlab-group-milestone-update command line option, [446](#)
 - gitlab-project-milestone-create command line option, [584](#)
 - gitlab-project-milestone-update command line option, [586](#)
- starts-at
 - gitlab-broadcast-message-create command line option, [384](#)
 - gitlab-broadcast-message-update command line option, [385](#)
- state
 - gitlab-group-issue-list command line option, [436](#)
 - gitlab-group-merge-request-list command line option, [443](#)
 - gitlab-group-milestone-list command line option, [445](#)
 - gitlab-issue-list command line option, [457](#)
 - gitlab-merge-request-list command line option, [461](#)
 - gitlab-project-commit-status-create command line option, [506](#)
 - gitlab-project-deployment-merge-request-list command line option, [512](#)
 - gitlab-project-issue-list command line option, [527](#)
 - gitlab-project-merge-request-list command line option, [559](#)

- gitlab-project-milestone-list command line option, [585](#)
- gitlab-todo-list command line option, [645](#)
- gitlab-user-impersonation-token-list command line option, [658](#)
- state-event
 - gitlab-group-milestone-update command line option, [446](#)
 - gitlab-project-issue-update command line option, [531](#)
 - gitlab-project-merge-request-update command line option, [564](#)
 - gitlab-project-milestone-create command line option, [584](#)
 - gitlab-project-milestone-update command line option, [586](#)
- states
 - gitlab-project-environment-list command line option, [514](#)
- statistics
 - gitlab-group-descendant-group-list command line option, [419](#)
 - gitlab-group-list command line option, [400](#)
 - gitlab-group-subgroup-list command line option, [451](#)
 - gitlab-project-fork-list command line option, [521](#)
 - gitlab-project-list command line option, [472](#)
 - gitlab-starred-project-list command line option, [644](#)
 - gitlab-user-project-list command line option, [663](#)
- status
 - gitlab-project-deployment-create command line option, [509](#)
 - gitlab-project-deployment-list command line option, [510](#)
 - gitlab-project-pipeline-list command line option, [593](#)
 - gitlab-runner-job-list command line option, [640](#)
 - gitlab-user-list command line option, [650](#)
- subgroup-creation-level
 - gitlab-group-create command line option, [399](#)
 - gitlab-group-update command line option, [403](#)
- subgroup-events
 - gitlab-group-hook-create command line option, [433](#)
 - gitlab-group-hook-update command line option, [435](#)
- submodule
 - gitlab-project-update-submodule command line option, [480](#)
- sudo
 - gitlab-application-appearance-get command line option, [378](#)
 - gitlab-application-appearance-update command line option, [378](#)
 - gitlab-application-create command line option, [377](#)
 - gitlab-application-delete command line option, [377](#)
 - gitlab-application-list command line option, [377](#)
 - gitlab-application-settings-get command line option, [379](#)
 - gitlab-application-settings-update command line option, [381](#)
 - gitlab-audit-event-get command line option, [383](#)
 - gitlab-audit-event-list command line option, [383](#)
 - gitlab-broadcast-message-create command line option, [384](#)
 - gitlab-broadcast-message-delete command line option, [384](#)
 - gitlab-broadcast-message-get command line option, [384](#)
 - gitlab-broadcast-message-list command line option, [385](#)
 - gitlab-broadcast-message-update command line option, [385](#)
 - gitlab-current-user-email-create command line option, [386](#)
 - gitlab-current-user-email-delete command line option, [386](#)
 - gitlab-current-user-email-get command line option, [386](#)
 - gitlab-current-user-email-list command line option, [387](#)
 - gitlab-current-user-get command line option, [386](#)
 - gitlab-current-user-gpg-key-create command line option, [387](#)
 - gitlab-current-user-gpg-key-delete command line option, [387](#)
 - gitlab-current-user-gpg-key-get command line option, [388](#)
 - gitlab-current-user-gpg-key-list command line option, [388](#)
 - gitlab-current-user-key-create command line option, [388](#)
 - gitlab-current-user-key-delete command line option, [389](#)

gitlab-current-user-key-get command line option, [389](#)
gitlab-current-user-key-list command line option, [389](#)
gitlab-current-user-status-get command line option, [390](#)
gitlab-current-user-status-update command line option, [390](#)
gitlab-deploy-key-list command line option, [390](#)
gitlab-deploy-token-list command line option, [391](#)
gitlab-dockerfile-get command line option, [391](#)
gitlab-dockerfile-list command line option, [391](#)
gitlab-event-list command line option, [392](#)
gitlab-feature-delete command line option, [393](#)
gitlab-feature-list command line option, [393](#)
gitlab-generic-package-download command line option, [393](#)
gitlab-generic-package-upload command line option, [394](#)
gitlab-geo-node-delete command line option, [394](#)
gitlab-geo-node-get command line option, [395](#)
gitlab-geo-node-list command line option, [395](#)
gitlab-geo-node-update command line option, [396](#)
gitlab-gitignore-get command line option, [396](#)
gitlab-gitignore-list command line option, [396](#)
gitlab-gitlabciyaml-get command line option, [397](#)
gitlab-gitlabciyaml-list command line option, [397](#)
gitlab-group-access-request-approve command line option, [404](#)
gitlab-group-access-request-create command line option, [404](#)
gitlab-group-access-request-delete command line option, [404](#)
gitlab-group-access-request-list command line option, [404](#)
gitlab-group-access-token-create command line option, [405](#)
gitlab-group-access-token-delete command line option, [405](#)
gitlab-group-access-token-list command line option, [405](#)
gitlab-group-audit-event-get command line option, [406](#)
gitlab-group-audit-event-list command line option, [406](#)
gitlab-group-badge-create command line option, [407](#)
gitlab-group-badge-delete command line option, [407](#)
gitlab-group-badge-get command line option, [407](#)
gitlab-group-badge-list command line option, [408](#)
gitlab-group-badge-render command line option, [408](#)
gitlab-group-badge-update command line option, [408](#)
gitlab-group-billable-member-delete command line option, [409](#)
gitlab-group-billable-member-list command line option, [409](#)
gitlab-group-billable-member-membership-list command line option, [410](#)
gitlab-group-board-create command line option, [410](#)
gitlab-group-board-delete command line option, [411](#)
gitlab-group-board-get command line option, [411](#)
gitlab-group-board-list command line option, [411](#)
gitlab-group-board-list-create command line option, [412](#)
gitlab-group-board-list-delete command line option, [412](#)
gitlab-group-board-list-get command line option, [413](#)
gitlab-group-board-list-list command line option, [413](#)
gitlab-group-board-list-update command line option, [413](#)
gitlab-group-board-update command line option, [412](#)
gitlab-group-cluster-create command line option, [414](#)
gitlab-group-cluster-delete command line option, [414](#)
gitlab-group-cluster-get command line option, [415](#)
gitlab-group-cluster-list command line option, [415](#)
gitlab-group-cluster-update command line option, [415](#)

- gitlab-group-create command line option, [398](#)
- gitlab-group-custom-attribute-delete command line option, [416](#)
- gitlab-group-custom-attribute-get command line option, [416](#)
- gitlab-group-custom-attribute-list command line option, [416](#)
- gitlab-group-delete command line option, [399](#)
- gitlab-group-deploy-token-create command line option, [417](#)
- gitlab-group-deploy-token-delete command line option, [417](#)
- gitlab-group-deploy-token-get command line option, [418](#)
- gitlab-group-deploy-token-list command line option, [418](#)
- gitlab-group-descendant-group-list command line option, [419](#)
- gitlab-group-epic-award-emoji-create command line option, [422](#)
- gitlab-group-epic-award-emoji-delete command line option, [422](#)
- gitlab-group-epic-award-emoji-get command line option, [422](#)
- gitlab-group-epic-award-emoji-list command line option, [423](#)
- gitlab-group-epic-create command line option, [419](#)
- gitlab-group-epic-delete command line option, [420](#)
- gitlab-group-epic-discussion-note-create command line option, [423](#)
- gitlab-group-epic-discussion-note-delete command line option, [424](#)
- gitlab-group-epic-discussion-note-get command line option, [424](#)
- gitlab-group-epic-discussion-note-update command line option, [424](#)
- gitlab-group-epic-get command line option, [420](#)
- gitlab-group-epic-issue-create command line option, [425](#)
- gitlab-group-epic-issue-delete command line option, [425](#)
- gitlab-group-epic-issue-list command line option, [426](#)
- gitlab-group-epic-issue-update command line option, [426](#)
- gitlab-group-epic-list command line option, [420](#)
- gitlab-group-epic-note-award-emoji-create command line option, [429](#)
- gitlab-group-epic-note-award-emoji-delete command line option, [429](#)
- gitlab-group-epic-note-award-emoji-get command line option, [429](#)
- gitlab-group-epic-note-award-emoji-list command line option, [430](#)
- gitlab-group-epic-note-create command line option, [427](#)
- gitlab-group-epic-note-delete command line option, [427](#)
- gitlab-group-epic-note-get command line option, [427](#)
- gitlab-group-epic-note-list command line option, [428](#)
- gitlab-group-epic-note-update command line option, [428](#)
- gitlab-group-epic-resource-label-event-get command line option, [430](#)
- gitlab-group-epic-resource-label-event-list command line option, [431](#)
- gitlab-group-epic-update command line option, [421](#)
- gitlab-group-export-create command line option, [431](#)
- gitlab-group-export-download command line option, [431](#)
- gitlab-group-export-get command line option, [432](#)
- gitlab-group-get command line option, [400](#)
- gitlab-group-hook-create command line option, [432](#)
- gitlab-group-hook-delete command line option, [433](#)
- gitlab-group-hook-get command line option, [433](#)
- gitlab-group-hook-list command line option, [434](#)
- gitlab-group-hook-update command line option, [434](#)
- gitlab-group-import-get command line option, [435](#)
- gitlab-group-issue-list command line option, [436](#)
- gitlab-group-issues-statistics-get command line option, [437](#)
- gitlab-group-label-create command line option, [437](#)
- gitlab-group-label-delete command line option, [438](#)
- gitlab-group-label-get command line option, [438](#)
- gitlab-group-label-list command line option, [438](#)
- gitlab-group-label-subscribe command

- line option, [439](#)
- gitlab-group-label-unsubscribe command line option, [439](#)
- gitlab-group-label-update command line option, [439](#)
- gitlab-group-list command line option, [400](#)
- gitlab-group-member-all-get command line option, [441](#)
- gitlab-group-member-all-list command line option, [442](#)
- gitlab-group-member-create command line option, [440](#)
- gitlab-group-member-delete command line option, [440](#)
- gitlab-group-member-get command line option, [440](#)
- gitlab-group-member-list command line option, [441](#)
- gitlab-group-member-update command line option, [441](#)
- gitlab-group-merge-request-list command line option, [443](#)
- gitlab-group-milestone-create command line option, [444](#)
- gitlab-group-milestone-delete command line option, [444](#)
- gitlab-group-milestone-get command line option, [445](#)
- gitlab-group-milestone-issues command line option, [445](#)
- gitlab-group-milestone-list command line option, [445](#)
- gitlab-group-milestone-merge-requests command line option, [446](#)
- gitlab-group-milestone-update command line option, [446](#)
- gitlab-group-notification-settings-get command line option, [447](#)
- gitlab-group-notification-settings-update command line option, [447](#)
- gitlab-group-package-list command line option, [448](#)
- gitlab-group-project-list command line option, [449](#)
- gitlab-group-runner-list command line option, [450](#)
- gitlab-group-subgroup-list command line option, [451](#)
- gitlab-group-update command line option, [402](#)
- gitlab-group-variable-create command line option, [452](#)
- gitlab-group-variable-delete command line option, [452](#)
- gitlab-group-variable-get command line option, [452](#)
- gitlab-group-variable-list command line option, [453](#)
- gitlab-group-variable-update command line option, [453](#)
- gitlab-group-wiki-create command line option, [454](#)
- gitlab-group-wiki-delete command line option, [454](#)
- gitlab-group-wiki-get command line option, [454](#)
- gitlab-group-wiki-list command line option, [455](#)
- gitlab-group-wiki-update command line option, [455](#)
- gitlab-hook-create command line option, [456](#)
- gitlab-hook-delete command line option, [456](#)
- gitlab-hook-get command line option, [456](#)
- gitlab-hook-list command line option, [456](#)
- gitlab-issue-get command line option, [457](#)
- gitlab-issue-list command line option, [457](#)
- gitlab-issues-statistics-get command line option, [458](#)
- gitlab-key-get command line option, [458](#)
- gitlab-ldap-group-list command line option, [459](#)
- gitlab-license-get command line option, [459](#)
- gitlab-license-list command line option, [460](#)
- gitlab-merge-request-list command line option, [461](#)
- gitlab-namespace-get command line option, [462](#)
- gitlab-namespace-list command line option, [462](#)
- gitlab-notification-settings-get command line option, [463](#)
- gitlab-notification-settings-update command line option, [463](#)
- gitlab-pages-domain-list command line option, [464](#)
- gitlab-personal-access-token-delete command line option, [464](#)
- gitlab-personal-access-token-list command line option, [465](#)
- gitlab-project-access-request-approve command line option, [481](#)
- gitlab-project-access-request-create

- command line option, [481](#)
- gitlab-project-access-request-delete
 - command line option, [482](#)
- gitlab-project-access-request-list
 - command line option, [482](#)
- gitlab-project-access-token-create
 - command line option, [482](#)
- gitlab-project-access-token-delete
 - command line option, [483](#)
- gitlab-project-access-token-list
 - command line option, [483](#)
- gitlab-project-additional-statistics-get
 - command line option, [483](#)
- gitlab-project-approval-get command line option, [484](#)
- gitlab-project-approval-rule-create
 - command line option, [485](#)
- gitlab-project-approval-rule-delete
 - command line option, [485](#)
- gitlab-project-approval-rule-list
 - command line option, [486](#)
- gitlab-project-approval-rule-update
 - command line option, [486](#)
- gitlab-project-approval-update command line option, [484](#)
- gitlab-project-artifact-delete command line option, [486](#)
- gitlab-project-artifact-download
 - command line option, [487](#)
- gitlab-project-artifact-raw command line option, [487](#)
- gitlab-project-audit-event-get command line option, [488](#)
- gitlab-project-audit-event-list command line option, [488](#)
- gitlab-project-badge-create command line option, [489](#)
- gitlab-project-badge-delete command line option, [489](#)
- gitlab-project-badge-get command line option, [489](#)
- gitlab-project-badge-list command line option, [490](#)
- gitlab-project-badge-render command line option, [490](#)
- gitlab-project-badge-update command line option, [490](#)
- gitlab-project-board-create command line option, [491](#)
- gitlab-project-board-delete command line option, [491](#)
- gitlab-project-board-get command line option, [491](#)
- gitlab-project-board-list command line option, [492](#)
- gitlab-project-board-list-create
 - command line option, [492](#)
- gitlab-project-board-list-delete
 - command line option, [493](#)
- gitlab-project-board-list-get command line option, [493](#)
- gitlab-project-board-list-list command line option, [493](#)
- gitlab-project-board-list-update
 - command line option, [494](#)
- gitlab-project-board-update command line option, [492](#)
- gitlab-project-branch-create command line option, [494](#)
- gitlab-project-branch-delete command line option, [495](#)
- gitlab-project-branch-get command line option, [495](#)
- gitlab-project-branch-list command line option, [495](#)
- gitlab-project-cluster-create command line option, [496](#)
- gitlab-project-cluster-delete command line option, [496](#)
- gitlab-project-cluster-get command line option, [497](#)
- gitlab-project-cluster-list command line option, [497](#)
- gitlab-project-cluster-update command line option, [497](#)
- gitlab-project-commit-cherry-pick
 - command line option, [498](#)
- gitlab-project-commit-comment-create
 - command line option, [501](#)
- gitlab-project-commit-comment-list
 - command line option, [502](#)
- gitlab-project-commit-create command line option, [498](#)
- gitlab-project-commit-diff command line option, [499](#)
- gitlab-project-commit-discussion-create
 - command line option, [502](#)
- gitlab-project-commit-discussion-get
 - command line option, [503](#)
- gitlab-project-commit-discussion-list
 - command line option, [503](#)
- gitlab-project-commit-discussion-note-create
 - command line option, [504](#)
- gitlab-project-commit-discussion-note-delete
 - command line option, [504](#)
- gitlab-project-commit-discussion-note-get
 - command line option, [505](#)
- gitlab-project-commit-discussion-note-update

- command line option, [505](#)
- gitlab-project-commit-get command line option, [499](#)
- gitlab-project-commit-list command line option, [499](#)
- gitlab-project-commit-merge-requests command line option, [500](#)
- gitlab-project-commit-refs command line option, [500](#)
- gitlab-project-commit-revert command line option, [501](#)
- gitlab-project-commit-signature command line option, [501](#)
- gitlab-project-commit-status-create command line option, [506](#)
- gitlab-project-commit-status-list command line option, [506](#)
- gitlab-project-create command line option, [467](#)
- gitlab-project-custom-attribute-delete command line option, [507](#)
- gitlab-project-custom-attribute-get command line option, [507](#)
- gitlab-project-custom-attribute-list command line option, [507](#)
- gitlab-project-delete command line option, [470](#)
- gitlab-project-deploy-token-create command line option, [508](#)
- gitlab-project-deploy-token-delete command line option, [508](#)
- gitlab-project-deploy-token-get command line option, [508](#)
- gitlab-project-deploy-token-list command line option, [509](#)
- gitlab-project-deployment-create command line option, [509](#)
- gitlab-project-deployment-get command line option, [510](#)
- gitlab-project-deployment-list command line option, [510](#)
- gitlab-project-deployment-merge-request-list command line option, [512](#)
- gitlab-project-deployment-update command line option, [511](#)
- gitlab-project-environment-create command line option, [513](#)
- gitlab-project-environment-delete command line option, [514](#)
- gitlab-project-environment-get command line option, [514](#)
- gitlab-project-environment-list command line option, [514](#)
- gitlab-project-environment-stop command line option, [515](#)
- gitlab-project-environment-update command line option, [515](#)
- gitlab-project-event-list command line option, [515](#)
- gitlab-project-export-create command line option, [516](#)
- gitlab-project-export-download command line option, [516](#)
- gitlab-project-export-get command line option, [517](#)
- gitlab-project-file-blame command line option, [517](#)
- gitlab-project-file-create command line option, [517](#)
- gitlab-project-file-delete command line option, [518](#)
- gitlab-project-file-get command line option, [518](#)
- gitlab-project-file-raw command line option, [519](#)
- gitlab-project-file-update command line option, [519](#)
- gitlab-project-fork-create command line option, [520](#)
- gitlab-project-fork-list command line option, [520](#)
- gitlab-project-get command line option, [470](#)
- gitlab-project-hook-create command line option, [521](#)
- gitlab-project-hook-delete command line option, [522](#)
- gitlab-project-hook-get command line option, [522](#)
- gitlab-project-hook-list command line option, [523](#)
- gitlab-project-hook-update command line option, [523](#)
- gitlab-project-import-get command line option, [524](#)
- gitlab-project-issue-add-spent-time command line option, [525](#)
- gitlab-project-issue-award-emoji-create command line option, [531](#)
- gitlab-project-issue-award-emoji-delete command line option, [532](#)
- gitlab-project-issue-award-emoji-get command line option, [532](#)
- gitlab-project-issue-award-emoji-list command line option, [532](#)
- gitlab-project-issue-closed-by command line option, [525](#)
- gitlab-project-issue-create command

- line option, [525](#)
- gitlab-project-issue-delete command
 - line option, [526](#)
- gitlab-project-issue-discussion-create
 - command line option, [533](#)
- gitlab-project-issue-discussion-get
 - command line option, [533](#)
- gitlab-project-issue-discussion-list
 - command line option, [534](#)
- gitlab-project-issue-discussion-note-create
 - command line option, [534](#)
- gitlab-project-issue-discussion-note-delete
 - command line option, [535](#)
- gitlab-project-issue-discussion-note-get
 - command line option, [535](#)
- gitlab-project-issue-discussion-note-update
 - command line option, [535](#)
- gitlab-project-issue-get command line option, [526](#)
- gitlab-project-issue-link-create
 - command line option, [536](#)
- gitlab-project-issue-link-delete
 - command line option, [536](#)
- gitlab-project-issue-link-list command line option, [537](#)
- gitlab-project-issue-list command line option, [527](#)
- gitlab-project-issue-move command line option, [527](#)
- gitlab-project-issue-note-award-emoji-create
 - command line option, [539](#)
- gitlab-project-issue-note-award-emoji-delete
 - command line option, [540](#)
- gitlab-project-issue-note-award-emoji-get
 - command line option, [540](#)
- gitlab-project-issue-note-award-emoji-list
 - command line option, [540](#)
- gitlab-project-issue-note-create
 - command line option, [537](#)
- gitlab-project-issue-note-delete
 - command line option, [538](#)
- gitlab-project-issue-note-get command line option, [538](#)
- gitlab-project-issue-note-list command line option, [538](#)
- gitlab-project-issue-note-update
 - command line option, [539](#)
- gitlab-project-issue-participants
 - command line option, [528](#)
- gitlab-project-issue-related-merge-requests
 - command line option, [528](#)
- gitlab-project-issue-reset-spent-time
 - command line option, [528](#)
- gitlab-project-issue-reset-time-estimate
 - command line option, [528](#)
- gitlab-project-issue-resource-label-event-get
 - command line option, [541](#)
- gitlab-project-issue-resource-label-event-list
 - command line option, [541](#)
- gitlab-project-issue-resource-milestone-event-get
 - command line option, [542](#)
- gitlab-project-issue-resource-milestone-event-list
 - command line option, [542](#)
- gitlab-project-issue-resource-state-event-get
 - command line option, [543](#)
- gitlab-project-issue-resource-state-event-list
 - command line option, [543](#)
- gitlab-project-issue-subscribe command line option, [529](#)
- gitlab-project-issue-time-estimate
 - command line option, [529](#)
- gitlab-project-issue-time-stats command line option, [529](#)
- gitlab-project-issue-todo command line option, [530](#)
- gitlab-project-issue-unsubscribe
 - command line option, [530](#)
- gitlab-project-issue-update command line option, [530](#)
- gitlab-project-issue-user-agent-detail
 - command line option, [531](#)
- gitlab-project-issues-statistics-get
 - command line option, [544](#)
- gitlab-project-job-artifact command line option, [544](#)
- gitlab-project-job-artifacts command line option, [545](#)
- gitlab-project-job-cancel command line option, [545](#)
- gitlab-project-job-delete-artifacts
 - command line option, [545](#)
- gitlab-project-job-erase command line option, [545](#)
- gitlab-project-job-get command line option, [546](#)
- gitlab-project-job-keep-artifacts
 - command line option, [546](#)
- gitlab-project-job-list command line option, [546](#)
- gitlab-project-job-play command line option, [547](#)
- gitlab-project-job-retry command line option, [547](#)
- gitlab-project-job-trace command line option, [547](#)
- gitlab-project-key-create command line option, [548](#)
- gitlab-project-key-delete command line

- option, 548
- gitlab-project-key-enable command line option, 548
- gitlab-project-key-get command line option, 549
- gitlab-project-key-list command line option, 549
- gitlab-project-key-update command line option, 549
- gitlab-project-label-create command line option, 550
- gitlab-project-label-delete command line option, 550
- gitlab-project-label-get command line option, 551
- gitlab-project-label-list command line option, 551
- gitlab-project-label-subscribe command line option, 551
- gitlab-project-label-unsubscribe command line option, 552
- gitlab-project-label-update command line option, 552
- gitlab-project-list command line option, 471
- gitlab-project-member-all-get command line option, 554
- gitlab-project-member-all-list command line option, 555
- gitlab-project-member-create command line option, 553
- gitlab-project-member-delete command line option, 553
- gitlab-project-member-get command line option, 553
- gitlab-project-member-list command line option, 554
- gitlab-project-member-update command line option, 554
- gitlab-project-merge-request-add-spent-time command line option, 555
- gitlab-project-merge-request-approval-get command line option, 565
- gitlab-project-merge-request-approval-rule-create command line option, 566
- gitlab-project-merge-request-approval-rule-delete command line option, 566
- gitlab-project-merge-request-approval-rule-list command line option, 567
- gitlab-project-merge-request-approval-rule-update command line option, 567
- gitlab-project-merge-request-approval-state-get command line option, 568
- gitlab-project-merge-request-approval-update command line option, 565
- gitlab-project-merge-request-approve command line option, 556
- gitlab-project-merge-request-award-emoji-create command line option, 569
- gitlab-project-merge-request-award-emoji-delete command line option, 569
- gitlab-project-merge-request-award-emoji-get command line option, 569
- gitlab-project-merge-request-award-emoji-list command line option, 570
- gitlab-project-merge-request-cancel-merge-when-pipeline command line option, 556
- gitlab-project-merge-request-changes command line option, 556
- gitlab-project-merge-request-closes-issues command line option, 557
- gitlab-project-merge-request-commits command line option, 557
- gitlab-project-merge-request-create command line option, 557
- gitlab-project-merge-request-delete command line option, 558
- gitlab-project-merge-request-diff-get command line option, 570
- gitlab-project-merge-request-diff-list command line option, 571
- gitlab-project-merge-request-discussion-create command line option, 571
- gitlab-project-merge-request-discussion-get command line option, 572
- gitlab-project-merge-request-discussion-list command line option, 572
- gitlab-project-merge-request-discussion-note-create command line option, 573
- gitlab-project-merge-request-discussion-note-delete command line option, 574
- gitlab-project-merge-request-discussion-note-get command line option, 574
- gitlab-project-merge-request-discussion-note-update command line option, 574
- gitlab-project-merge-request-discussion-update command line option, 572
- gitlab-project-merge-request-get command line option, 558
- gitlab-project-merge-request-list command line option, 559
- gitlab-project-merge-request-merge command line option, 560
- gitlab-project-merge-request-merge-ref command line option, 561
- gitlab-project-merge-request-note-award-emoji-create command line option, 577
- gitlab-project-merge-request-note-award-emoji-delete

command line option, [577](#)
gitlab-project-merge-request-note-award-emoji-get command line option, [578](#)
gitlab-project-merge-request-note-award-emoji-list command line option, [578](#)
gitlab-project-merge-request-note-create command line option, [575](#)
gitlab-project-merge-request-note-delete command line option, [575](#)
gitlab-project-merge-request-note-get command line option, [576](#)
gitlab-project-merge-request-note-list command line option, [576](#)
gitlab-project-merge-request-note-update command line option, [576](#)
gitlab-project-merge-request-participants command line option, [561](#)
gitlab-project-merge-request-pipeline-create command line option, [579](#)
gitlab-project-merge-request-pipeline-list command line option, [579](#)
gitlab-project-merge-request-rebase command line option, [561](#)
gitlab-project-merge-request-reset-spent-time command line option, [561](#)
gitlab-project-merge-request-reset-time-estimate command line option, [562](#)
gitlab-project-merge-request-resource-label-events-get command line option, [580](#)
gitlab-project-merge-request-resource-label-events-list command line option, [580](#)
gitlab-project-merge-request-resource-milestone-get command line option, [581](#)
gitlab-project-merge-request-resource-milestone-get-emoji command line option, [581](#)
gitlab-project-merge-request-resource-state-events-get command line option, [582](#)
gitlab-project-merge-request-resource-state-events-list command line option, [582](#)
gitlab-project-merge-request-subscribe command line option, [562](#)
gitlab-project-merge-request-time-estimate command line option, [562](#)
gitlab-project-merge-request-time-stats command line option, [563](#)
gitlab-project-merge-request-todo command line option, [563](#)
gitlab-project-merge-request-unapprove command line option, [563](#)
gitlab-project-merge-request-unsubscribe command line option, [563](#)
gitlab-project-merge-request-update command line option, [564](#)
gitlab-project-merge-train-list command line option, [583](#)
gitlab-project-milestone-create command line option, [583](#)
gitlab-project-milestone-delete command line option, [584](#)
gitlab-project-milestone-get command line option, [584](#)
gitlab-project-milestone-issues command line option, [584](#)
gitlab-project-milestone-list command line option, [585](#)
gitlab-project-milestone-merge-requests command line option, [585](#)
gitlab-project-milestone-update command line option, [585](#)
gitlab-project-note-get command line option, [586](#)
gitlab-project-note-list command line option, [586](#)
gitlab-project-notification-settings-get command line option, [587](#)
gitlab-project-notification-settings-update command line option, [587](#)
gitlab-project-package-delete command line option, [588](#)
gitlab-project-package-file-delete command line option, [589](#)
gitlab-project-package-file-list command line option, [590](#)
gitlab-project-package-get command line option, [588](#)
gitlab-project-package-list command line option, [589](#)
gitlab-project-pages-domain-create command line option, [590](#)
gitlab-project-pages-domain-delete command line option, [591](#)
gitlab-project-pages-domain-get command line option, [591](#)
gitlab-project-pages-domain-list command line option, [591](#)
gitlab-project-pages-domain-update command line option, [592](#)
gitlab-project-pipeline-bridge-list command line option, [594](#)
gitlab-project-pipeline-cancel command line option, [592](#)
gitlab-project-pipeline-create command line option, [592](#)
gitlab-project-pipeline-delete command line option, [593](#)
gitlab-project-pipeline-get command line option, [593](#)
gitlab-project-pipeline-job-list

- command line option, [595](#)
- gitlab-project-pipeline-list command line option, [593](#)
- gitlab-project-pipeline-retry command line option, [594](#)
- gitlab-project-pipeline-schedule-create command line option, [596](#)
- gitlab-project-pipeline-schedule-delete command line option, [596](#)
- gitlab-project-pipeline-schedule-get command line option, [596](#)
- gitlab-project-pipeline-schedule-list command line option, [597](#)
- gitlab-project-pipeline-schedule-play command line option, [597](#)
- gitlab-project-pipeline-schedule-take-ownership command line option, [597](#)
- gitlab-project-pipeline-schedule-update command line option, [598](#)
- gitlab-project-pipeline-schedule-variable-create command line option, [598](#)
- gitlab-project-pipeline-schedule-variable-delete command line option, [599](#)
- gitlab-project-pipeline-schedule-variable-update command line option, [599](#)
- gitlab-project-pipeline-test-report-get command line option, [600](#)
- gitlab-project-pipeline-test-report-summary-get command line option, [600](#)
- gitlab-project-pipeline-variable-list command line option, [601](#)
- gitlab-project-protected-branch-create command line option, [602](#)
- gitlab-project-protected-branch-delete command line option, [602](#)
- gitlab-project-protected-branch-get command line option, [602](#)
- gitlab-project-protected-branch-list command line option, [603](#)
- gitlab-project-protected-tag-create command line option, [603](#)
- gitlab-project-protected-tag-delete command line option, [603](#)
- gitlab-project-protected-tag-get command line option, [604](#)
- gitlab-project-protected-tag-list command line option, [604](#)
- gitlab-project-push-rules-create command line option, [605](#)
- gitlab-project-push-rules-delete command line option, [605](#)
- gitlab-project-push-rules-get command line option, [606](#)
- gitlab-project-push-rules-update command line option, [606](#)
- gitlab-project-registry-repository-delete command line option, [607](#)
- gitlab-project-registry-repository-list command line option, [607](#)
- gitlab-project-registry-tag-delete command line option, [608](#)
- gitlab-project-registry-tag-delete-in-bulk command line option, [608](#)
- gitlab-project-registry-tag-get command line option, [609](#)
- gitlab-project-registry-tag-list command line option, [609](#)
- gitlab-project-release-create command line option, [610](#)
- gitlab-project-release-delete command line option, [610](#)
- gitlab-project-release-get command line option, [610](#)
- gitlab-project-release-link-create command line option, [612](#)
- gitlab-project-release-link-delete command line option, [612](#)
- gitlab-project-release-link-get command line option, [612](#)
- gitlab-project-release-link-list command line option, [613](#)
- gitlab-project-release-link-update command line option, [613](#)
- gitlab-project-release-list command line option, [611](#)
- gitlab-project-release-update command line option, [611](#)
- gitlab-project-remote-mirror-create command line option, [614](#)
- gitlab-project-remote-mirror-list command line option, [614](#)
- gitlab-project-remote-mirror-update command line option, [615](#)
- gitlab-project-runner-create command line option, [615](#)
- gitlab-project-runner-delete command line option, [615](#)
- gitlab-project-runner-list command line option, [616](#)
- gitlab-project-service-available command line option, [616](#)
- gitlab-project-service-delete command line option, [617](#)
- gitlab-project-service-get command line option, [617](#)
- gitlab-project-service-list command line option, [617](#)
- gitlab-project-service-update command

line option, [618](#)

gitlab-project-snippet-award-emoji-create
command line option, [621](#)

gitlab-project-snippet-award-emoji-delete
command line option, [621](#)

gitlab-project-snippet-award-emoji-get
command line option, [621](#)

gitlab-project-snippet-award-emoji-list
command line option, [622](#)

gitlab-project-snippet-content command
line option, [618](#)

gitlab-project-snippet-create command
line option, [618](#)

gitlab-project-snippet-delete command
line option, [619](#)

gitlab-project-snippet-discussion-create
command line option, [622](#)

gitlab-project-snippet-discussion-get
command line option, [623](#)

gitlab-project-snippet-discussion-list
command line option, [623](#)

gitlab-project-snippet-discussion-note-create
command line option, [624](#)

gitlab-project-snippet-discussion-note-delete
command line option, [624](#)

gitlab-project-snippet-discussion-note-get
command line option, [625](#)

gitlab-project-snippet-discussion-note-update
command line option, [625](#)

gitlab-project-snippet-get command line
option, [619](#)

gitlab-project-snippet-list command
line option, [619](#)

gitlab-project-snippet-note-award-emoji-create
command line option, [627](#)

gitlab-project-snippet-note-award-emoji-delete
command line option, [628](#)

gitlab-project-snippet-note-award-emoji-get
command line option, [628](#)

gitlab-project-snippet-note-award-emoji-list
command line option, [629](#)

gitlab-project-snippet-note-create
command line option, [625](#)

gitlab-project-snippet-note-delete
command line option, [626](#)

gitlab-project-snippet-note-get command
line option, [626](#)

gitlab-project-snippet-note-list
command line option, [626](#)

gitlab-project-snippet-note-update
command line option, [627](#)

gitlab-project-snippet-update command
line option, [620](#)

gitlab-project-snippet-user-agent-detail
command line option, [620](#)

gitlab-project-storage-get command line
option, [629](#)

gitlab-project-tag-create command line
option, [630](#)

gitlab-project-tag-delete command line
option, [630](#)

gitlab-project-tag-get command line
option, [630](#)

gitlab-project-tag-list command line
option, [631](#)

gitlab-project-trigger-create command
line option, [631](#)

gitlab-project-trigger-delete command
line option, [631](#)

gitlab-project-trigger-get command line
option, [632](#)

gitlab-project-trigger-list command
line option, [632](#)

gitlab-project-trigger-update command
line option, [632](#)

gitlab-project-update command line
option, [478](#)

gitlab-project-user-list command line
option, [633](#)

gitlab-project-variable-create command
line option, [633](#)

gitlab-project-variable-delete command
line option, [634](#)

gitlab-project-variable-get command
line option, [634](#)

gitlab-project-variable-list command
line option, [634](#)

gitlab-project-variable-update command
line option, [635](#)

gitlab-project-wiki-create command line
option, [635](#)

gitlab-project-wiki-delete command line
option, [636](#)

gitlab-project-wiki-get command line
option, [636](#)

gitlab-project-wiki-list command line
option, [636](#)

gitlab-project-wiki-update command line
option, [637](#)

gitlab-runner-create command line
option, [638](#)

gitlab-runner-delete command line
option, [638](#)

gitlab-runner-get command line option,
[638](#)

gitlab-runner-job-list command line
option, [640](#)

gitlab-runner-list command line option,

- 639
- gitlab-runner-update command line option, 639
- gitlab-snippet-create command line option, 641
- gitlab-snippet-delete command line option, 641
- gitlab-snippet-get command line option, 641
- gitlab-snippet-list command line option, 642
- gitlab-snippet-update command line option, 642
- gitlab-starred-project-list command line option, 643
- gitlab-todo-delete command line option, 644
- gitlab-todo-list command line option, 644
- gitlab-topic-create command line option, 645
- gitlab-topic-delete command line option, 646
- gitlab-topic-get command line option, 646
- gitlab-topic-list command line option, 646
- gitlab-topic-update command line option, 646
- gitlab-user-activities-list command line option, 652
- gitlab-user-create command line option, 648
- gitlab-user-custom-attribute-delete command line option, 653
- gitlab-user-custom-attribute-get command line option, 653
- gitlab-user-custom-attribute-list command line option, 653
- gitlab-user-delete command line option, 649
- gitlab-user-email-create command line option, 654
- gitlab-user-email-delete command line option, 654
- gitlab-user-email-get command line option, 654
- gitlab-user-email-list command line option, 655
- gitlab-user-event-list command line option, 655
- gitlab-user-get command line option, 649
- gitlab-user-gpg-key-create command line option, 656
- gitlab-user-gpg-key-delete command line option, 656
- gitlab-user-gpg-key-get command line option, 656
- gitlab-user-gpg-key-list command line option, 657
- gitlab-user-impersonation-token-create command line option, 657
- gitlab-user-impersonation-token-delete command line option, 658
- gitlab-user-impersonation-token-get command line option, 658
- gitlab-user-impersonation-token-list command line option, 658
- gitlab-user-key-create command line option, 659
- gitlab-user-key-delete command line option, 659
- gitlab-user-key-get command line option, 659
- gitlab-user-key-list command line option, 660
- gitlab-user-list command line option, 650
- gitlab-user-membership-get command line option, 660
- gitlab-user-membership-list command line option, 660
- gitlab-user-personal-access-token-create command line option, 661
- gitlab-user-project-create command line option, 662
- gitlab-user-project-list command line option, 663
- gitlab-user-status-get command line option, 664
- gitlab-user-update command line option, 651
- gitlab-variable-create command line option, 664
- gitlab-variable-delete command line option, 665
- gitlab-variable-get command line option, 665
- gitlab-variable-list command line option, 665
- gitlab-variable-update command line option, 665
- suggestion-commit-message
 - gitlab-project-update command line option, 480
- tag
 - gitlab-project-deployment-create command line option, 509
- tag-list
 - gitlab-group-runner-list command line option, 450

- gitlab-project-create command line option, [469](#)
- gitlab-project-runner-list command line option, [616](#)
- gitlab-project-update command line option, [480](#)
- gitlab-runner-create command line option, [638](#)
- gitlab-runner-list command line option, [639](#)
- gitlab-runner-update command line option, [639](#)
- tag-name
 - gitlab-project-release-create command line option, [610](#)
 - gitlab-project-release-delete command line option, [610](#)
 - gitlab-project-release-get command line option, [610](#)
 - gitlab-project-release-link-create command line option, [612](#)
 - gitlab-project-release-link-delete command line option, [612](#)
 - gitlab-project-release-link-get command line option, [612](#)
 - gitlab-project-release-link-list command line option, [613](#)
 - gitlab-project-release-link-update command line option, [613](#)
 - gitlab-project-release-update command line option, [611](#)
 - gitlab-project-tag-create command line option, [630](#)
- tag-push-events
 - gitlab-group-hook-create command line option, [432](#)
 - gitlab-group-hook-update command line option, [434](#)
 - gitlab-project-hook-create command line option, [522](#)
 - gitlab-project-hook-update command line option, [523](#)
- target-branch
 - gitlab-group-merge-request-list command line option, [443](#)
 - gitlab-merge-request-list command line option, [461](#)
 - gitlab-project-deployment-merge-request-list command line option, [513](#)
 - gitlab-project-merge-request-create command line option, [557](#)
 - gitlab-project-merge-request-list command line option, [560](#)
 - gitlab-project-merge-request-update command line option, [564](#)
- target-issue-iiid
 - gitlab-project-issue-link-create command line option, [536](#)
- target-project-id
 - gitlab-project-issue-link-create command line option, [536](#)
 - gitlab-project-merge-request-create command line option, [558](#)
- target-type
 - gitlab-event-list command line option, [392](#)
 - gitlab-project-event-list command line option, [516](#)
 - gitlab-user-event-list command line option, [655](#)
- target-url
 - gitlab-project-commit-status-create command line option, [506](#)
- template-name
 - gitlab-project-create command line option, [469](#)
- template-project-id
 - gitlab-project-create command line option, [469](#)
- terminal-max-session-time
 - gitlab-application-settings-update command line option, [382](#)
- terms
 - gitlab-application-settings-update command line option, [382](#)
- theme-id
 - gitlab-user-create command line option, [648](#)
 - gitlab-user-update command line option, [652](#)
- timeout
 - gitlab command line option, [376](#)
- title
 - gitlab-application-appearance-update command line option, [378](#)
 - gitlab-current-user-key-create command line option, [388](#)
 - gitlab-group-epic-create command line option, [420](#)
 - gitlab-group-epic-update command line option, [421](#)
 - gitlab-group-milestone-create command line option, [444](#)
 - gitlab-group-milestone-update command line option, [446](#)
 - gitlab-group-wiki-create command line option, [454](#)
 - gitlab-group-wiki-update command line

- option, [455](#)
- gitlab-project-issue-create command line option, [525](#)
- gitlab-project-issue-update command line option, [530](#)
- gitlab-project-key-create command line option, [548](#)
- gitlab-project-key-update command line option, [549](#)
- gitlab-project-merge-request-create command line option, [558](#)
- gitlab-project-merge-request-update command line option, [564](#)
- gitlab-project-milestone-create command line option, [584](#)
- gitlab-project-milestone-update command line option, [586](#)
- gitlab-project-snippet-create command line option, [618](#)
- gitlab-project-snippet-update command line option, [620](#)
- gitlab-project-wiki-create command line option, [636](#)
- gitlab-project-wiki-update command line option, [637](#)
- gitlab-snippet-create command line option, [641](#)
- gitlab-snippet-update command line option, [642](#)
- gitlab-user-key-create command line option, [659](#)
- to
 - gitlab-project-repository-compare command line option, [473](#)
- to-namespace
 - gitlab-project-transfer command line option, [475](#)
 - gitlab-project-transfer-project command line option, [475](#)
- to-project-id
 - gitlab-project-issue-move command line option, [527](#)
- token
 - gitlab-group-hook-create command line option, [433](#)
 - gitlab-group-hook-update command line option, [435](#)
 - gitlab-project-hook-create command line option, [522](#)
 - gitlab-project-hook-update command line option, [524](#)
 - gitlab-project-trigger-pipeline command line option, [476](#)
 - gitlab-runner-create command line option, [638](#)
 - gitlab-runner-verify command line option, [640](#)
- top-level-only
 - gitlab-group-list command line option, [400](#)
- topic
 - gitlab-project-list command line option, [472](#)
- trailers
 - gitlab-project-commit-list command line option, [500](#)
- twitter
 - gitlab-user-create command line option, [648](#)
 - gitlab-user-update command line option, [651](#)
- two-factor
 - gitlab-user-list command line option, [650](#)
- two-factor-grace-period
 - gitlab-group-create command line option, [399](#)
 - gitlab-group-update command line option, [403](#)
- type
 - gitlab-project-commit-refs command line option, [500](#)
 - gitlab-todo-list command line option, [645](#)
 - gitlab-user-membership-list command line option, [660](#)
- unprotect-access-level
 - gitlab-project-protected-branch-create command line option, [602](#)
- until
 - gitlab-project-commit-list command line option, [499](#)
- updated-after
 - gitlab-group-issue-list command line option, [436](#)
 - gitlab-group-merge-request-list command line option, [443](#)
 - gitlab-issue-list command line option, [458](#)
 - gitlab-merge-request-list command line option, [461](#)
 - gitlab-project-deployment-list command line option, [510](#)
 - gitlab-project-deployment-merge-request-list command line option, [512](#)
 - gitlab-project-issue-list command line option, [527](#)
 - gitlab-project-merge-request-list command line option, [559](#)
- updated-at

gitlab-application-settings-update
command line option, [381](#)

gitlab-project-issue-update command
line option, [531](#)

--updated-before

gitlab-group-issue-list command line
option, [436](#)

gitlab-group-merge-request-list command
line option, [443](#)

gitlab-issue-list command line option,
[458](#)

gitlab-merge-request-list command line
option, [461](#)

gitlab-project-deployment-list command
line option, [510](#)

gitlab-project-deployment-merge-request-list
command line option, [512](#)

gitlab-project-issue-list command line
option, [527](#)

gitlab-project-merge-request-list
command line option, [559](#)

--url

gitlab-geo-node-update command line
option, [396](#)

gitlab-group-hook-create command line
option, [432](#)

gitlab-group-hook-update command line
option, [434](#)

gitlab-hook-create command line option,
[456](#)

gitlab-project-hook-create command line
option, [521](#)

gitlab-project-hook-update command line
option, [523](#)

gitlab-project-release-link-create
command line option, [612](#)

gitlab-project-release-link-update
command line option, [613](#)

gitlab-project-remote-mirror-create
command line option, [614](#)

--use-custom-template

gitlab-project-create command line
option, [469](#)

--user-agent

gitlab command line option, [376](#)

--user-id

gitlab-group-billable-member-membership-list
command line option, [410](#)

gitlab-group-member-create command line
option, [440](#)

gitlab-personal-access-token-list
command line option, [465](#)

gitlab-project-member-create command
line option, [553](#)

gitlab-starred-project-list command
line option, [643](#)

gitlab-user-custom-attribute-delete
command line option, [653](#)

gitlab-user-custom-attribute-get
command line option, [653](#)

gitlab-user-custom-attribute-list
command line option, [653](#)

gitlab-user-email-create command line
option, [654](#)

gitlab-user-email-delete command line
option, [654](#)

gitlab-user-email-get command line
option, [654](#)

gitlab-user-email-list command line
option, [655](#)

gitlab-user-event-list command line
option, [655](#)

gitlab-user-gpg-key-create command line
option, [656](#)

gitlab-user-gpg-key-delete command line
option, [656](#)

gitlab-user-gpg-key-get command line
option, [656](#)

gitlab-user-gpg-key-list command line
option, [657](#)

gitlab-user-impersonation-token-create
command line option, [657](#)

gitlab-user-impersonation-token-delete
command line option, [658](#)

gitlab-user-impersonation-token-get
command line option, [658](#)

gitlab-user-impersonation-token-list
command line option, [658](#)

gitlab-user-key-create command line
option, [659](#)

gitlab-user-key-delete command line
option, [659](#)

gitlab-user-key-get command line option,
[659](#)

gitlab-user-key-list command line
option, [660](#)

gitlab-user-membership-get command line
option, [660](#)

gitlab-user-membership-list command
line option, [660](#)

gitlab-user-personal-access-token-create
command line option, [661](#)

gitlab-user-project-create command line
option, [662](#)

gitlab-user-project-list command line
option, [663](#)

gitlab-user-status-get command line
option, [664](#)

```

--user-ids
    gitlab-project-approval-rule-create
        command line option, 485
    gitlab-project-merge-request-approval-rule-creation
        command line option, 566
    gitlab-project-merge-request-approval-rule-update
        command line option, 568
--user-oauth-applications
    gitlab-application-settings-update
        command line option, 382
--user-show-add-ssh-key-message
    gitlab-application-settings-update
        command line option, 382
--username
    gitlab-group-deploy-token-create
        command line option, 417
    gitlab-project-deploy-token-create
        command line option, 508
    gitlab-project-pipeline-list command
        line option, 594
    gitlab-user-create command line option,
        648
    gitlab-user-list command line option, 650
    gitlab-user-update command line option,
        651
--value
    gitlab-group-variable-create command
        line option, 452
    gitlab-group-variable-update command
        line option, 453
    gitlab-project-pipeline-schedule-variable-create
        command line option, 599
    gitlab-project-pipeline-schedule-variable-update
        command line option, 599
    gitlab-project-variable-create command
        line option, 634
    gitlab-project-variable-update command
        line option, 635
    gitlab-variable-create command line
        option, 664
    gitlab-variable-update command line
        option, 665
--variable-type
    gitlab-group-variable-create command
        line option, 452
    gitlab-group-variable-update command
        line option, 453
    gitlab-project-variable-create command
        line option, 634
    gitlab-project-variable-update command
        line option, 635
    gitlab-variable-create command line
        option, 664
    gitlab-variable-update command line
        option, 666
--verbose
    gitlab command line option, 376
    gitlab command line option, 376
gitlab-group-merge-request-list command
    line option, 443
gitlab-merge-request-list command line
    option, 461
gitlab-project-deployment-merge-request-list
    command line option, 512
gitlab-project-merge-request-list
    command line option, 559
--visibility
    gitlab-group-create command line option,
        398
    gitlab-group-project-list command line
        option, 449
    gitlab-group-update command line option,
        403
    gitlab-project-create command line
        option, 469
    gitlab-project-fork-list command line
        option, 520
    gitlab-project-list command line option,
        472
    gitlab-project-snippet-create command
        line option, 619
    gitlab-project-snippet-update command
        line option, 620
    gitlab-project-update command line
        option, 480
    gitlab-snippet-create command line
        option, 641
    gitlab-snippet-update command line
        option, 642
    gitlab-starred-project-list command
        line option, 644
    gitlab-user-project-create command line
        option, 662
    gitlab-user-project-list command line
        option, 663
--wall-enabled
    gitlab-user-project-create command line
        option, 662
--website-url
    gitlab-user-create command line option,
        648
    gitlab-user-update command line option,
        651
--wiki
    gitlab-project-snapshot command line
        option, 475

```

```
--wiki-access-level
  gitlab-project-create command line
    option, 469
  gitlab-project-update command line
    option, 480
--wiki-checksum-failed
  gitlab-project-list command line option,
    472
  gitlab-user-project-list command line
    option, 663
--wiki-enabled
  gitlab-project-create command line
    option, 469
  gitlab-project-update command line
    option, 480
  gitlab-user-project-create command line
    option, 662
--wiki-events
  gitlab-project-hook-update command line
    option, 524
--wiki-page-events
  gitlab-group-hook-create command line
    option, 433
  gitlab-group-hook-update command line
    option, 435
  gitlab-project-hook-create command line
    option, 522
--wip
  gitlab-group-merge-request-list command
    line option, 443
  gitlab-merge-request-list command line
    option, 461
  gitlab-project-deployment-merge-request-list
    command line option, 513
  gitlab-project-merge-request-list
    command line option, 560
--with-content
  gitlab-group-wiki-list command line
    option, 455
  gitlab-project-wiki-list command line
    option, 636
--with-custom-attributes
  gitlab-group-descendant-group-list
    command line option, 419
  gitlab-group-list command line option,
    400
  gitlab-group-project-list command line
    option, 449
  gitlab-group-subgroup-list command line
    option, 451
  gitlab-project-fork-list command line
    option, 521
  gitlab-project-list command line option,
    472
  gitlab-starred-project-list command
    line option, 644
  gitlab-user-project-list command line
    option, 663
--with-issues-enabled
  gitlab-group-project-list command line
    option, 449
  gitlab-project-fork-list command line
    option, 521
  gitlab-project-list command line option,
    472
  gitlab-starred-project-list command
    line option, 644
  gitlab-user-project-list command line
    option, 663
--with-labels-details
  gitlab-merge-request-list command line
    option, 461
  gitlab-project-deployment-merge-request-list
    command line option, 512
--with-merge-requests-enabled
  gitlab-group-project-list command line
    option, 449
  gitlab-project-fork-list command line
    option, 521
  gitlab-project-list command line option,
    472
  gitlab-starred-project-list command
    line option, 644
  gitlab-user-project-list command line
    option, 663
--with-merge-status-recheck
  gitlab-merge-request-list command line
    option, 461
  gitlab-project-deployment-merge-request-list
    command line option, 512
--with-programming-language
  gitlab-project-list command line option,
    472
  gitlab-user-project-list command line
    option, 663
--with-security-reports
  gitlab-group-project-list command line
    option, 450
--with-shared
  gitlab-group-project-list command line
    option, 449
--with-stats
  gitlab-project-commit-list command line
    option, 500
--yaml-errors
  gitlab-project-pipeline-list command
    line option, 593
-c
```

- gitlab command line option, [376](#)
- d
 - gitlab command line option, [376](#)
- f
 - gitlab command line option, [376](#)
- g
 - gitlab command line option, [376](#)
- h
 - gitlab command line option, [376](#)
 - gitlab-application command line option, [377](#)
 - gitlab-application-appearance command line option, [378](#)
 - gitlab-application-appearance-get command line option, [378](#)
 - gitlab-application-appearance-update command line option, [378](#)
 - gitlab-application-create command line option, [377](#)
 - gitlab-application-delete command line option, [377](#)
 - gitlab-application-list command line option, [377](#)
 - gitlab-application-settings command line option, [379](#)
 - gitlab-application-settings-get command line option, [379](#)
 - gitlab-application-settings-update command line option, [381](#)
 - gitlab-audit-event command line option, [383](#)
 - gitlab-audit-event-get command line option, [383](#)
 - gitlab-audit-event-list command line option, [383](#)
 - gitlab-broadcast-message command line option, [384](#)
 - gitlab-broadcast-message-create command line option, [384](#)
 - gitlab-broadcast-message-delete command line option, [384](#)
 - gitlab-broadcast-message-get command line option, [384](#)
 - gitlab-broadcast-message-list command line option, [385](#)
 - gitlab-broadcast-message-update command line option, [385](#)
 - gitlab-current-user command line option, [385](#)
 - gitlab-current-user-email command line option, [386](#)
 - gitlab-current-user-email-create command line option, [386](#)
 - gitlab-current-user-email-delete
 - command line option, [386](#)
 - gitlab-current-user-email-get command line option, [386](#)
 - gitlab-current-user-email-list command line option, [387](#)
 - gitlab-current-user-get command line option, [386](#)
 - gitlab-current-user-gpg-key command line option, [387](#)
 - gitlab-current-user-gpg-key-create command line option, [387](#)
 - gitlab-current-user-gpg-key-delete command line option, [387](#)
 - gitlab-current-user-gpg-key-get command line option, [388](#)
 - gitlab-current-user-gpg-key-list command line option, [388](#)
 - gitlab-current-user-key command line option, [388](#)
 - gitlab-current-user-key-create command line option, [388](#)
 - gitlab-current-user-key-delete command line option, [389](#)
 - gitlab-current-user-key-get command line option, [389](#)
 - gitlab-current-user-key-list command line option, [389](#)
 - gitlab-current-user-status command line option, [389](#)
 - gitlab-current-user-status-get command line option, [390](#)
 - gitlab-current-user-status-update command line option, [390](#)
 - gitlab-deploy-key command line option, [390](#)
 - gitlab-deploy-key-list command line option, [390](#)
 - gitlab-deploy-token command line option, [391](#)
 - gitlab-deploy-token-list command line option, [391](#)
 - gitlab-dockerfile command line option, [391](#)
 - gitlab-dockerfile-get command line option, [391](#)
 - gitlab-dockerfile-list command line option, [391](#)
 - gitlab-event command line option, [392](#)
 - gitlab-event-list command line option, [392](#)
 - gitlab-feature command line option, [392](#)
 - gitlab-feature-delete command line option, [393](#)
 - gitlab-feature-list command line option,

- 393
- gitlab-generic-package command line option, 393
- gitlab-generic-package-download command line option, 393
- gitlab-generic-package-upload command line option, 394
- gitlab-geo-node command line option, 394
- gitlab-geo-node-current-failures command line option, 394
- gitlab-geo-node-delete command line option, 394
- gitlab-geo-node-get command line option, 395
- gitlab-geo-node-list command line option, 395
- gitlab-geo-node-repair command line option, 395
- gitlab-geo-node-status command line option, 395
- gitlab-geo-node-update command line option, 396
- gitlab-gitignore command line option, 396
- gitlab-gitignore-get command line option, 396
- gitlab-gitignore-list command line option, 396
- gitlab-gitlabciyaml command line option, 397
- gitlab-gitlabciyaml-get command line option, 397
- gitlab-gitlabciyaml-list command line option, 397
- gitlab-group command line option, 397
- gitlab-group-access-request command line option, 403
- gitlab-group-access-request-approve command line option, 404
- gitlab-group-access-request-create command line option, 404
- gitlab-group-access-request-delete command line option, 404
- gitlab-group-access-request-list command line option, 404
- gitlab-group-access-token command line option, 405
- gitlab-group-access-token-create command line option, 405
- gitlab-group-access-token-delete command line option, 405
- gitlab-group-access-token-list command line option, 405
- gitlab-group-add-ldap-group-link command line option, 398
- gitlab-group-audit-event command line option, 406
- gitlab-group-audit-event-get command line option, 406
- gitlab-group-audit-event-list command line option, 406
- gitlab-group-badge command line option, 407
- gitlab-group-badge-create command line option, 407
- gitlab-group-badge-delete command line option, 407
- gitlab-group-badge-get command line option, 407
- gitlab-group-badge-list command line option, 408
- gitlab-group-badge-render command line option, 408
- gitlab-group-badge-update command line option, 408
- gitlab-group-billable-member command line option, 409
- gitlab-group-billable-member-delete command line option, 409
- gitlab-group-billable-member-list command line option, 409
- gitlab-group-billable-member-membership command line option, 410
- gitlab-group-billable-member-membership-list command line option, 410
- gitlab-group-board command line option, 410
- gitlab-group-board-create command line option, 410
- gitlab-group-board-delete command line option, 411
- gitlab-group-board-get command line option, 411
- gitlab-group-board-list command line option, 411, 412
- gitlab-group-board-list-create command line option, 412
- gitlab-group-board-list-delete command line option, 412
- gitlab-group-board-list-get command line option, 413
- gitlab-group-board-list-list command line option, 413
- gitlab-group-board-list-update command line option, 413
- gitlab-group-board-update command line option, 412
- gitlab-group-cluster command line option, 414

gitlab-group-cluster-create command line option, [414](#)
 gitlab-group-cluster-delete command line option, [414](#)
 gitlab-group-cluster-get command line option, [415](#)
 gitlab-group-cluster-list command line option, [415](#)
 gitlab-group-cluster-update command line option, [415](#)
 gitlab-group-create command line option, [398](#)
 gitlab-group-custom-attribute command line option, [416](#)
 gitlab-group-custom-attribute-delete command line option, [416](#)
 gitlab-group-custom-attribute-get command line option, [416](#)
 gitlab-group-custom-attribute-list command line option, [416](#)
 gitlab-group-delete command line option, [399](#)
 gitlab-group-delete-ldap-group-link command line option, [399](#)
 gitlab-group-deploy-token command line option, [417](#)
 gitlab-group-deploy-token-create command line option, [417](#)
 gitlab-group-deploy-token-delete command line option, [417](#)
 gitlab-group-deploy-token-get command line option, [418](#)
 gitlab-group-deploy-token-list command line option, [418](#)
 gitlab-group-descendant-group command line option, [418](#)
 gitlab-group-descendant-group-list command line option, [419](#)
 gitlab-group-epic command line option, [419](#)
 gitlab-group-epic-award-emoji command line option, [421](#)
 gitlab-group-epic-award-emoji-create command line option, [422](#)
 gitlab-group-epic-award-emoji-delete command line option, [422](#)
 gitlab-group-epic-award-emoji-get command line option, [422](#)
 gitlab-group-epic-award-emoji-list command line option, [423](#)
 gitlab-group-epic-create command line option, [419](#)
 gitlab-group-epic-delete command line option, [420](#)
 gitlab-group-epic-discussion-note command line option, [423](#)
 gitlab-group-epic-discussion-note-create command line option, [423](#)
 gitlab-group-epic-discussion-note-delete command line option, [424](#)
 gitlab-group-epic-discussion-note-get command line option, [424](#)
 gitlab-group-epic-discussion-note-update command line option, [424](#)
 gitlab-group-epic-get command line option, [420](#)
 gitlab-group-epic-issue command line option, [425](#)
 gitlab-group-epic-issue-create command line option, [425](#)
 gitlab-group-epic-issue-delete command line option, [425](#)
 gitlab-group-epic-issue-list command line option, [426](#)
 gitlab-group-epic-issue-update command line option, [426](#)
 gitlab-group-epic-list command line option, [420](#)
 gitlab-group-epic-note command line option, [426](#)
 gitlab-group-epic-note-award-emoji command line option, [428](#)
 gitlab-group-epic-note-award-emoji-create command line option, [429](#)
 gitlab-group-epic-note-award-emoji-delete command line option, [429](#)
 gitlab-group-epic-note-award-emoji-get command line option, [429](#)
 gitlab-group-epic-note-award-emoji-list command line option, [430](#)
 gitlab-group-epic-note-create command line option, [427](#)
 gitlab-group-epic-note-delete command line option, [427](#)
 gitlab-group-epic-note-get command line option, [427](#)
 gitlab-group-epic-note-list command line option, [428](#)
 gitlab-group-epic-note-update command line option, [428](#)
 gitlab-group-epic-resource-label-event command line option, [430](#)
 gitlab-group-epic-resource-label-event-get command line option, [430](#)
 gitlab-group-epic-resource-label-event-list command line option, [431](#)
 gitlab-group-epic-update command line option, [421](#)

gitlab-group-export command line option, [431](#)
gitlab-group-export-create command line option, [431](#)
gitlab-group-export-download command line option, [431](#)
gitlab-group-export-get command line option, [432](#)
gitlab-group-get command line option, [400](#)
gitlab-group-hook command line option, [432](#)
gitlab-group-hook-create command line option, [432](#)
gitlab-group-hook-delete command line option, [433](#)
gitlab-group-hook-get command line option, [433](#)
gitlab-group-hook-list command line option, [434](#)
gitlab-group-hook-update command line option, [434](#)
gitlab-group-import command line option, [435](#)
gitlab-group-import-get command line option, [435](#)
gitlab-group-issue command line option, [435](#)
gitlab-group-issue-list command line option, [436](#)
gitlab-group-issues-statistics command line option, [437](#)
gitlab-group-issues-statistics-get command line option, [437](#)
gitlab-group-label command line option, [437](#)
gitlab-group-label-create command line option, [437](#)
gitlab-group-label-delete command line option, [438](#)
gitlab-group-label-get command line option, [438](#)
gitlab-group-label-list command line option, [438](#)
gitlab-group-label-subscribe command line option, [439](#)
gitlab-group-label-unsubscribe command line option, [439](#)
gitlab-group-label-update command line option, [439](#)
gitlab-group-ldap-sync command line option, [400](#)
gitlab-group-list command line option, [400](#)
gitlab-group-member command line option, [440](#)
gitlab-group-member-all command line option, [441](#)
gitlab-group-member-all-get command line option, [441](#)
gitlab-group-member-all-list command line option, [442](#)
gitlab-group-member-create command line option, [440](#)
gitlab-group-member-delete command line option, [440](#)
gitlab-group-member-get command line option, [440](#)
gitlab-group-member-list command line option, [441](#)
gitlab-group-member-update command line option, [441](#)
gitlab-group-merge-request command line option, [442](#)
gitlab-group-merge-request-list command line option, [442](#)
gitlab-group-milestone command line option, [444](#)
gitlab-group-milestone-create command line option, [444](#)
gitlab-group-milestone-delete command line option, [444](#)
gitlab-group-milestone-get command line option, [445](#)
gitlab-group-milestone-issues command line option, [445](#)
gitlab-group-milestone-list command line option, [445](#)
gitlab-group-milestone-merge-requests command line option, [446](#)
gitlab-group-milestone-update command line option, [446](#)
gitlab-group-notification-settings command line option, [446](#)
gitlab-group-notification-settings-get command line option, [447](#)
gitlab-group-notification-settings-update command line option, [447](#)
gitlab-group-package command line option, [448](#)
gitlab-group-package-list command line option, [448](#)
gitlab-group-project command line option, [449](#)
gitlab-group-project-list command line option, [449](#)
gitlab-group-runner command line option, [450](#)
gitlab-group-runner-list command line

- option, [450](#)
- gitlab-group-search command line option, [401](#)
- gitlab-group-share command line option, [401](#)
- gitlab-group-subgroup command line option, [450](#)
- gitlab-group-subgroup-list command line option, [451](#)
- gitlab-group-transfer command line option, [401](#)
- gitlab-group-transfer-project command line option, [402](#)
- gitlab-group-unshare command line option, [402](#)
- gitlab-group-update command line option, [402](#)
- gitlab-group-variable command line option, [451](#)
- gitlab-group-variable-create command line option, [452](#)
- gitlab-group-variable-delete command line option, [452](#)
- gitlab-group-variable-get command line option, [452](#)
- gitlab-group-variable-list command line option, [453](#)
- gitlab-group-variable-update command line option, [453](#)
- gitlab-group-wiki command line option, [453](#)
- gitlab-group-wiki-create command line option, [454](#)
- gitlab-group-wiki-delete command line option, [454](#)
- gitlab-group-wiki-get command line option, [454](#)
- gitlab-group-wiki-list command line option, [455](#)
- gitlab-group-wiki-update command line option, [455](#)
- gitlab-hook command line option, [455](#)
- gitlab-hook-create command line option, [456](#)
- gitlab-hook-delete command line option, [456](#)
- gitlab-hook-get command line option, [456](#)
- gitlab-hook-list command line option, [456](#)
- gitlab-issue command line option, [457](#)
- gitlab-issue-get command line option, [457](#)
- gitlab-issue-list command line option, [457](#)
- gitlab-issues-statistics command line option, [458](#)
- gitlab-issues-statistics-get command line option, [458](#)
- gitlab-key command line option, [458](#)
- gitlab-key-get command line option, [458](#)
- gitlab-ldap-group command line option, [459](#)
- gitlab-ldap-group-list command line option, [459](#)
- gitlab-license command line option, [459](#)
- gitlab-license-get command line option, [459](#)
- gitlab-license-list command line option, [460](#)
- gitlab-merge-request command line option, [460](#)
- gitlab-merge-request-list command line option, [460](#)
- gitlab-namespace command line option, [462](#)
- gitlab-namespace-get command line option, [462](#)
- gitlab-namespace-list command line option, [462](#)
- gitlab-notification-settings command line option, [463](#)
- gitlab-notification-settings-get command line option, [463](#)
- gitlab-notification-settings-update command line option, [463](#)
- gitlab-pages-domain command line option, [464](#)
- gitlab-pages-domain-list command line option, [464](#)
- gitlab-personal-access-token command line option, [464](#)
- gitlab-personal-access-token-delete command line option, [464](#)
- gitlab-personal-access-token-list command line option, [465](#)
- gitlab-project command line option, [465](#)
- gitlab-project-access-request command line option, [481](#)
- gitlab-project-access-request-approve command line option, [481](#)
- gitlab-project-access-request-create command line option, [481](#)
- gitlab-project-access-request-delete command line option, [482](#)
- gitlab-project-access-request-list command line option, [482](#)
- gitlab-project-access-token command line option, [482](#)
- gitlab-project-access-token-create command line option, [482](#)
- gitlab-project-access-token-delete

- command line option, [483](#)
- gitlab-project-access-token-list
 - command line option, [483](#)
- gitlab-project-additional-statistics
 - command line option, [483](#)
- gitlab-project-additional-statistics-get
 - command line option, [483](#)
- gitlab-project-approval command line option, [484](#)
- gitlab-project-approval-get command line option, [484](#)
- gitlab-project-approval-rule command line option, [485](#)
- gitlab-project-approval-rule-create
 - command line option, [485](#)
- gitlab-project-approval-rule-delete
 - command line option, [485](#)
- gitlab-project-approval-rule-list
 - command line option, [486](#)
- gitlab-project-approval-rule-update
 - command line option, [486](#)
- gitlab-project-approval-update command line option, [484](#)
- gitlab-project-archive command line option, [465](#)
- gitlab-project-artifact command line option, [465](#), [486](#)
- gitlab-project-artifact-delete command line option, [486](#)
- gitlab-project-artifact-download
 - command line option, [487](#)
- gitlab-project-artifact-raw command line option, [487](#)
- gitlab-project-artifacts command line option, [466](#)
- gitlab-project-audit-event command line option, [487](#)
- gitlab-project-audit-event-get command line option, [488](#)
- gitlab-project-audit-event-list command line option, [488](#)
- gitlab-project-badge command line option, [488](#)
- gitlab-project-badge-create command line option, [489](#)
- gitlab-project-badge-delete command line option, [489](#)
- gitlab-project-badge-get command line option, [489](#)
- gitlab-project-badge-list command line option, [490](#)
- gitlab-project-badge-render command line option, [490](#)
- gitlab-project-badge-update command line option, [490](#)
- gitlab-project-board command line option, [491](#)
- gitlab-project-board-create command line option, [491](#)
- gitlab-project-board-delete command line option, [491](#)
- gitlab-project-board-get command line option, [491](#)
- gitlab-project-board-list command line option, [492](#)
- gitlab-project-board-list-create
 - command line option, [492](#)
- gitlab-project-board-list-delete
 - command line option, [493](#)
- gitlab-project-board-list-get command line option, [493](#)
- gitlab-project-board-list-list command line option, [493](#)
- gitlab-project-board-list-update
 - command line option, [494](#)
- gitlab-project-board-update command line option, [492](#)
- gitlab-project-branch command line option, [494](#)
- gitlab-project-branch-create command line option, [494](#)
- gitlab-project-branch-delete command line option, [495](#)
- gitlab-project-branch-get command line option, [495](#)
- gitlab-project-branch-list command line option, [495](#)
- gitlab-project-cluster command line option, [496](#)
- gitlab-project-cluster-create command line option, [496](#)
- gitlab-project-cluster-delete command line option, [496](#)
- gitlab-project-cluster-get command line option, [497](#)
- gitlab-project-cluster-list command line option, [497](#)
- gitlab-project-cluster-update command line option, [497](#)
- gitlab-project-commit command line option, [498](#)
- gitlab-project-commit-cherry-pick
 - command line option, [498](#)
- gitlab-project-commit-comment command line option, [501](#)
- gitlab-project-commit-comment-create
 - command line option, [501](#)
- gitlab-project-commit-comment-list

- command line option, [502](#)
- gitlab-project-commit-create command line option, [498](#)
- gitlab-project-commit-diff command line option, [499](#)
- gitlab-project-commit-discussion command line option, [502](#)
- gitlab-project-commit-discussion-create command line option, [502](#)
- gitlab-project-commit-discussion-get command line option, [503](#)
- gitlab-project-commit-discussion-list command line option, [503](#)
- gitlab-project-commit-discussion-note command line option, [504](#)
- gitlab-project-commit-discussion-note-create command line option, [504](#)
- gitlab-project-commit-discussion-note-delete command line option, [504](#)
- gitlab-project-commit-discussion-note-get command line option, [505](#)
- gitlab-project-commit-discussion-note-update command line option, [505](#)
- gitlab-project-commit-get command line option, [499](#)
- gitlab-project-commit-list command line option, [499](#)
- gitlab-project-commit-merge-requests command line option, [500](#)
- gitlab-project-commit-refs command line option, [500](#)
- gitlab-project-commit-revert command line option, [501](#)
- gitlab-project-commit-signature command line option, [501](#)
- gitlab-project-commit-status command line option, [505](#)
- gitlab-project-commit-status-create command line option, [506](#)
- gitlab-project-commit-status-list command line option, [506](#)
- gitlab-project-create command line option, [467](#)
- gitlab-project-create-fork-relation command line option, [469](#)
- gitlab-project-custom-attribute command line option, [507](#)
- gitlab-project-custom-attribute-delete command line option, [507](#)
- gitlab-project-custom-attribute-get command line option, [507](#)
- gitlab-project-custom-attribute-list command line option, [507](#)
- gitlab-project-delete command line option, [470](#)
- gitlab-project-delete-fork-relation command line option, [470](#)
- gitlab-project-delete-merged-branches command line option, [470](#)
- gitlab-project-deploy-token command line option, [508](#)
- gitlab-project-deploy-token-create command line option, [508](#)
- gitlab-project-deploy-token-delete command line option, [508](#)
- gitlab-project-deploy-token-get command line option, [508](#)
- gitlab-project-deploy-token-list command line option, [509](#)
- gitlab-project-deployment command line option, [509](#)
- gitlab-project-deployment-create command line option, [509](#)
- gitlab-project-deployment-get command line option, [510](#)
- gitlab-project-deployment-list command line option, [510](#)
- gitlab-project-deployment-merge-request command line option, [511](#)
- gitlab-project-deployment-merge-request-list command line option, [512](#)
- gitlab-project-deployment-update command line option, [511](#)
- gitlab-project-environment command line option, [513](#)
- gitlab-project-environment-create command line option, [513](#)
- gitlab-project-environment-delete command line option, [514](#)
- gitlab-project-environment-get command line option, [514](#)
- gitlab-project-environment-list command line option, [514](#)
- gitlab-project-environment-stop command line option, [515](#)
- gitlab-project-environment-update command line option, [515](#)
- gitlab-project-event command line option, [515](#)
- gitlab-project-event-list command line option, [515](#)
- gitlab-project-export command line option, [516](#)
- gitlab-project-export-create command line option, [516](#)
- gitlab-project-export-download command line option, [516](#)
- gitlab-project-export-get command line

- option, [517](#)
- gitlab-project-file command line option, [517](#)
- gitlab-project-file-blame command line option, [517](#)
- gitlab-project-file-create command line option, [517](#)
- gitlab-project-file-delete command line option, [518](#)
- gitlab-project-file-get command line option, [518](#)
- gitlab-project-file-raw command line option, [519](#)
- gitlab-project-file-update command line option, [519](#)
- gitlab-project-fork command line option, [520](#)
- gitlab-project-fork-create command line option, [520](#)
- gitlab-project-fork-list command line option, [520](#)
- gitlab-project-get command line option, [470](#)
- gitlab-project-hook command line option, [521](#)
- gitlab-project-hook-create command line option, [521](#)
- gitlab-project-hook-delete command line option, [522](#)
- gitlab-project-hook-get command line option, [522](#)
- gitlab-project-hook-list command line option, [523](#)
- gitlab-project-hook-update command line option, [523](#)
- gitlab-project-housekeeping command line option, [470](#)
- gitlab-project-import command line option, [524](#)
- gitlab-project-import-get command line option, [524](#)
- gitlab-project-issue command line option, [524](#)
- gitlab-project-issue-add-spent-time command line option, [524](#)
- gitlab-project-issue-award-emoji command line option, [531](#)
- gitlab-project-issue-award-emoji-create command line option, [531](#)
- gitlab-project-issue-award-emoji-delete command line option, [532](#)
- gitlab-project-issue-award-emoji-get command line option, [532](#)
- gitlab-project-issue-award-emoji-list command line option, [532](#)
- gitlab-project-issue-closed-by command line option, [525](#)
- gitlab-project-issue-create command line option, [525](#)
- gitlab-project-issue-delete command line option, [526](#)
- gitlab-project-issue-discussion command line option, [533](#)
- gitlab-project-issue-discussion-create command line option, [533](#)
- gitlab-project-issue-discussion-get command line option, [533](#)
- gitlab-project-issue-discussion-list command line option, [534](#)
- gitlab-project-issue-discussion-note command line option, [534](#)
- gitlab-project-issue-discussion-note-create command line option, [534](#)
- gitlab-project-issue-discussion-note-delete command line option, [535](#)
- gitlab-project-issue-discussion-note-get command line option, [535](#)
- gitlab-project-issue-discussion-note-update command line option, [535](#)
- gitlab-project-issue-get command line option, [526](#)
- gitlab-project-issue-link command line option, [536](#)
- gitlab-project-issue-link-create command line option, [536](#)
- gitlab-project-issue-link-delete command line option, [536](#)
- gitlab-project-issue-link-list command line option, [537](#)
- gitlab-project-issue-list command line option, [526](#)
- gitlab-project-issue-move command line option, [527](#)
- gitlab-project-issue-note command line option, [537](#)
- gitlab-project-issue-note-award-emoji command line option, [539](#)
- gitlab-project-issue-note-award-emoji-create command line option, [539](#)
- gitlab-project-issue-note-award-emoji-delete command line option, [540](#)
- gitlab-project-issue-note-award-emoji-get command line option, [540](#)
- gitlab-project-issue-note-award-emoji-list command line option, [540](#)
- gitlab-project-issue-note-create command line option, [537](#)
- gitlab-project-issue-note-delete

- command line option, [538](#)
- gitlab-project-issue-note-get command line option, [538](#)
- gitlab-project-issue-note-list command line option, [538](#)
- gitlab-project-issue-note-update command line option, [539](#)
- gitlab-project-issue-participants command line option, [528](#)
- gitlab-project-issue-related-merge-requests command line option, [528](#)
- gitlab-project-issue-reset-spent-time command line option, [528](#)
- gitlab-project-issue-reset-time-estimate command line option, [528](#)
- gitlab-project-issue-resource-label-event command line option, [541](#)
- gitlab-project-issue-resource-label-event-get command line option, [541](#)
- gitlab-project-issue-resource-label-event-list command line option, [541](#)
- gitlab-project-issue-resource-milestone-event command line option, [542](#)
- gitlab-project-issue-resource-milestone-event-get command line option, [542](#)
- gitlab-project-issue-resource-milestone-event-list command line option, [542](#)
- gitlab-project-issue-resource-state-event command line option, [543](#)
- gitlab-project-issue-resource-state-event-get command line option, [543](#)
- gitlab-project-issue-resource-state-event-list command line option, [543](#)
- gitlab-project-issue-subscribe command line option, [529](#)
- gitlab-project-issue-time-estimate command line option, [529](#)
- gitlab-project-issue-time-stats command line option, [529](#)
- gitlab-project-issue-todo command line option, [530](#)
- gitlab-project-issue-unsubscribe command line option, [530](#)
- gitlab-project-issue-update command line option, [530](#)
- gitlab-project-issue-user-agent-detail command line option, [531](#)
- gitlab-project-issues-statistics command line option, [544](#)
- gitlab-project-issues-statistics-get command line option, [544](#)
- gitlab-project-job command line option, [544](#)
- gitlab-project-job-artifact command line option, [544](#)
- gitlab-project-job-artifacts command line option, [545](#)
- gitlab-project-job-cancel command line option, [545](#)
- gitlab-project-job-delete-artifacts command line option, [545](#)
- gitlab-project-job-erase command line option, [545](#)
- gitlab-project-job-get command line option, [546](#)
- gitlab-project-job-keep-artifacts command line option, [546](#)
- gitlab-project-job-list command line option, [546](#)
- gitlab-project-job-play command line option, [547](#)
- gitlab-project-job-retry command line option, [547](#)
- gitlab-project-job-trace command line option, [547](#)
- gitlab-project-key command line option, [547](#)
- gitlab-project-key-create command line option, [548](#)
- gitlab-project-key-delete command line option, [548](#)
- gitlab-project-key-enable command line option, [548](#)
- gitlab-project-key-get command line option, [549](#)
- gitlab-project-key-list command line option, [549](#)
- gitlab-project-key-update command line option, [549](#)
- gitlab-project-label command line option, [550](#)
- gitlab-project-label-create command line option, [550](#)
- gitlab-project-label-delete command line option, [550](#)
- gitlab-project-label-get command line option, [551](#)
- gitlab-project-label-list command line option, [551](#)
- gitlab-project-label-subscribe command line option, [551](#)
- gitlab-project-label-unsubscribe command line option, [552](#)
- gitlab-project-label-update command line option, [552](#)
- gitlab-project-languages command line option, [471](#)
- gitlab-project-list command line option,

- 471
- gitlab-project-member command line option, 552
- gitlab-project-member-all command line option, 554
- gitlab-project-member-all-get command line option, 554
- gitlab-project-member-all-list command line option, 555
- gitlab-project-member-create command line option, 553
- gitlab-project-member-delete command line option, 553
- gitlab-project-member-get command line option, 553
- gitlab-project-member-list command line option, 554
- gitlab-project-member-update command line option, 554
- gitlab-project-merge-request command line option, 555
- gitlab-project-merge-request-add-spent-time command line option, 555
- gitlab-project-merge-request-approval command line option, 565
- gitlab-project-merge-request-approval-get command line option, 565
- gitlab-project-merge-request-approval-rule command line option, 565
- gitlab-project-merge-request-approval-rule-create command line option, 566
- gitlab-project-merge-request-approval-rule-delete command line option, 566
- gitlab-project-merge-request-approval-rule-list command line option, 567
- gitlab-project-merge-request-approval-rule-update command line option, 567
- gitlab-project-merge-request-approval-state command line option, 568
- gitlab-project-merge-request-approval-state-get command line option, 568
- gitlab-project-merge-request-approval-update command line option, 565
- gitlab-project-merge-request-approve command line option, 556
- gitlab-project-merge-request-award-emoji command line option, 568
- gitlab-project-merge-request-award-emoji-create command line option, 569
- gitlab-project-merge-request-award-emoji-delete command line option, 569
- gitlab-project-merge-request-award-emoji-get command line option, 569
- gitlab-project-merge-request-award-emoji-list command line option, 570
- gitlab-project-merge-request-cancel-merge-when-pipeline command line option, 556
- gitlab-project-merge-request-changes command line option, 556
- gitlab-project-merge-request-closes-issues command line option, 557
- gitlab-project-merge-request-commits command line option, 557
- gitlab-project-merge-request-create command line option, 557
- gitlab-project-merge-request-delete command line option, 558
- gitlab-project-merge-request-diff command line option, 570
- gitlab-project-merge-request-diff-get command line option, 570
- gitlab-project-merge-request-diff-list command line option, 571
- gitlab-project-merge-request-discussion command line option, 571
- gitlab-project-merge-request-discussion-create command line option, 571
- gitlab-project-merge-request-discussion-get command line option, 572
- gitlab-project-merge-request-discussion-list command line option, 572
- gitlab-project-merge-request-discussion-note command line option, 573
- gitlab-project-merge-request-discussion-note-create command line option, 573
- gitlab-project-merge-request-discussion-note-delete command line option, 573
- gitlab-project-merge-request-discussion-note-get command line option, 574
- gitlab-project-merge-request-discussion-note-update command line option, 574
- gitlab-project-merge-request-discussion-update command line option, 572
- gitlab-project-merge-request-get command line option, 558
- gitlab-project-merge-request-list command line option, 559
- gitlab-project-merge-request-merge command line option, 560
- gitlab-project-merge-request-merge-ref command line option, 561
- gitlab-project-merge-request-note command line option, 575
- gitlab-project-merge-request-note-award-emoji command line option, 577
- gitlab-project-merge-request-note-award-emoji-create command line option, 577
- gitlab-project-merge-request-note-award-emoji-delete

- command line option, [577](#)
- gitlab-project-merge-request-note-award-emoji-get
 - command line option, [578](#)
- gitlab-project-merge-request-note-award-emoji-list
 - command line option, [578](#)
- gitlab-project-merge-request-note-create
 - command line option, [575](#)
- gitlab-project-merge-request-note-delete
 - command line option, [575](#)
- gitlab-project-merge-request-note-get
 - command line option, [576](#)
- gitlab-project-merge-request-note-list
 - command line option, [576](#)
- gitlab-project-merge-request-note-update
 - command line option, [576](#)
- gitlab-project-merge-request-participants
 - command line option, [561](#)
- gitlab-project-merge-request-pipeline
 - command line option, [579](#)
- gitlab-project-merge-request-pipeline-create
 - command line option, [579](#)
- gitlab-project-merge-request-pipeline-list
 - command line option, [579](#)
- gitlab-project-merge-request-rebase
 - command line option, [561](#)
- gitlab-project-merge-request-reset-spent-time
 - command line option, [561](#)
- gitlab-project-merge-request-reset-time-estimate
 - command line option, [562](#)
- gitlab-project-merge-request-resource-label-events
 - command line option, [580](#)
- gitlab-project-merge-request-resource-label-events-get
 - command line option, [580](#)
- gitlab-project-merge-request-resource-label-events-list
 - command line option, [580](#)
- gitlab-project-merge-request-resource-milestones
 - command line option, [581](#)
- gitlab-project-merge-request-resource-milestones-get
 - command line option, [581](#)
- gitlab-project-merge-request-resource-milestones-list
 - command line option, [581](#)
- gitlab-project-merge-request-resource-state-events
 - command line option, [582](#)
- gitlab-project-merge-request-resource-state-events-get
 - command line option, [582](#)
- gitlab-project-merge-request-resource-state-events-list
 - command line option, [582](#)
- gitlab-project-merge-request-subscribe
 - command line option, [562](#)
- gitlab-project-merge-request-time-estimate
 - command line option, [562](#)
- gitlab-project-merge-request-time-stats
 - command line option, [563](#)
- gitlab-project-merge-request-todo
 - command line option, [563](#)
- gitlab-project-merge-request-unapprove
 - command line option, [563](#)
- gitlab-project-merge-request-unsubscribe
 - command line option, [563](#)
- gitlab-project-merge-request-update
 - command line option, [564](#)
- gitlab-project-merge-train
 - command line option, [583](#)
- gitlab-project-merge-train-list
 - command line option, [583](#)
- gitlab-project-milestone
 - command line option, [583](#)
- gitlab-project-milestone-create
 - command line option, [583](#)
- gitlab-project-milestone-delete
 - command line option, [584](#)
- gitlab-project-milestone-get
 - command line option, [584](#)
- gitlab-project-milestone-issues
 - command line option, [584](#)
- gitlab-project-milestone-list
 - command line option, [585](#)
- gitlab-project-milestone-merge-requests
 - command line option, [585](#)
- gitlab-project-milestone-update
 - command line option, [585](#)
- gitlab-project-mirror-pull
 - command line option, [472](#)
- gitlab-project-note
 - command line option, [586](#)
- gitlab-project-note-get
 - command line option, [586](#)
- gitlab-project-note-list
 - command line option, [586](#)
- gitlab-project-notification-settings
 - command line option, [587](#)
- gitlab-project-notification-settings-get
 - command line option, [587](#)
- gitlab-project-notification-settings-update
 - command line option, [587](#)
- gitlab-project-package
 - command line option, [588](#)
- gitlab-project-package-delete
 - command line option, [588](#)
- gitlab-project-package-file
 - command line option, [589](#)
- gitlab-project-package-file-delete
 - command line option, [589](#)
- gitlab-project-package-file-list
 - command line option, [590](#)
- gitlab-project-package-get
 - command line option, [588](#)
- gitlab-project-package-list
 - command line option, [588](#)

- line option, [589](#)
- gitlab-project-pages-domain command
 - line option, [590](#)
- gitlab-project-pages-domain-create
 - command line option, [590](#)
- gitlab-project-pages-domain-delete
 - command line option, [591](#)
- gitlab-project-pages-domain-get command
 - line option, [591](#)
- gitlab-project-pages-domain-list
 - command line option, [591](#)
- gitlab-project-pages-domain-update
 - command line option, [592](#)
- gitlab-project-pipeline command line option, [592](#)
- gitlab-project-pipeline-bridge command
 - line option, [594](#)
- gitlab-project-pipeline-bridge-list
 - command line option, [594](#)
- gitlab-project-pipeline-cancel command
 - line option, [592](#)
- gitlab-project-pipeline-create command
 - line option, [592](#)
- gitlab-project-pipeline-delete command
 - line option, [593](#)
- gitlab-project-pipeline-get command
 - line option, [593](#)
- gitlab-project-pipeline-job command
 - line option, [595](#)
- gitlab-project-pipeline-job-list
 - command line option, [595](#)
- gitlab-project-pipeline-list command
 - line option, [593](#)
- gitlab-project-pipeline-retry command
 - line option, [594](#)
- gitlab-project-pipeline-schedule
 - command line option, [595](#)
- gitlab-project-pipeline-schedule-create
 - command line option, [596](#)
- gitlab-project-pipeline-schedule-delete
 - command line option, [596](#)
- gitlab-project-pipeline-schedule-get
 - command line option, [596](#)
- gitlab-project-pipeline-schedule-list
 - command line option, [597](#)
- gitlab-project-pipeline-schedule-play
 - command line option, [597](#)
- gitlab-project-pipeline-schedule-take-ownership
 - command line option, [597](#)
- gitlab-project-pipeline-schedule-update
 - command line option, [598](#)
- gitlab-project-pipeline-schedule-variable
 - command line option, [598](#)
- gitlab-project-pipeline-schedule-variable-create
 - command line option, [598](#)
- gitlab-project-pipeline-schedule-variable-delete
 - command line option, [599](#)
- gitlab-project-pipeline-schedule-variable-update
 - command line option, [599](#)
- gitlab-project-pipeline-test-report
 - command line option, [600](#)
- gitlab-project-pipeline-test-report-get
 - command line option, [600](#)
- gitlab-project-pipeline-test-report-summary
 - command line option, [600](#)
- gitlab-project-pipeline-test-report-summary-get
 - command line option, [600](#)
- gitlab-project-pipeline-variable
 - command line option, [601](#)
- gitlab-project-pipeline-variable-list
 - command line option, [601](#)
- gitlab-project-protected-branch command
 - line option, [601](#)
- gitlab-project-protected-branch-create
 - command line option, [601](#)
- gitlab-project-protected-branch-delete
 - command line option, [602](#)
- gitlab-project-protected-branch-get
 - command line option, [602](#)
- gitlab-project-protected-branch-list
 - command line option, [603](#)
- gitlab-project-protected-tag command
 - line option, [603](#)
- gitlab-project-protected-tag-create
 - command line option, [603](#)
- gitlab-project-protected-tag-delete
 - command line option, [603](#)
- gitlab-project-protected-tag-get
 - command line option, [604](#)
- gitlab-project-protected-tag-list
 - command line option, [604](#)
- gitlab-project-push-rules command line option, [604](#)
- gitlab-project-push-rules-create
 - command line option, [605](#)
- gitlab-project-push-rules-delete
 - command line option, [605](#)
- gitlab-project-push-rules-get command
 - line option, [606](#)
- gitlab-project-push-rules-update
 - command line option, [606](#)
- gitlab-project-registry-repository
 - command line option, [607](#)
- gitlab-project-registry-repository-delete
 - command line option, [607](#)
- gitlab-project-registry-repository-list
 - command line option, [607](#)
- gitlab-project-registry-tag command

- line option, [607](#)
- gitlab-project-registry-tag-delete
 - command line option, [608](#)
- gitlab-project-registry-tag-delete-in-bulk
 - command line option, [608](#)
- gitlab-project-registry-tag-get command
 - line option, [609](#)
- gitlab-project-registry-tag-list
 - command line option, [609](#)
- gitlab-project-release command line
 - option, [609](#)
- gitlab-project-release-create command
 - line option, [610](#)
- gitlab-project-release-delete command
 - line option, [610](#)
- gitlab-project-release-get command line
 - option, [610](#)
- gitlab-project-release-link command
 - line option, [611](#)
- gitlab-project-release-link-create
 - command line option, [612](#)
- gitlab-project-release-link-delete
 - command line option, [612](#)
- gitlab-project-release-link-get command
 - line option, [612](#)
- gitlab-project-release-link-list
 - command line option, [613](#)
- gitlab-project-release-link-update
 - command line option, [613](#)
- gitlab-project-release-list command
 - line option, [611](#)
- gitlab-project-release-update command
 - line option, [611](#)
- gitlab-project-remote-mirror command
 - line option, [614](#)
- gitlab-project-remote-mirror-create
 - command line option, [614](#)
- gitlab-project-remote-mirror-list
 - command line option, [614](#)
- gitlab-project-remote-mirror-update
 - command line option, [615](#)
- gitlab-project-repository-archive
 - command line option, [472](#)
- gitlab-project-repository-blob command
 - line option, [473](#)
- gitlab-project-repository-compare
 - command line option, [473](#)
- gitlab-project-repository-contributors
 - command line option, [473](#)
- gitlab-project-repository-raw-blob
 - command line option, [473](#)
- gitlab-project-repository-tree command
 - line option, [474](#)
- gitlab-project-runner command line
 - option, [615](#)
- gitlab-project-runner-create command
 - line option, [615](#)
- gitlab-project-runner-delete command
 - line option, [615](#)
- gitlab-project-runner-list command line
 - option, [616](#)
- gitlab-project-search command line
 - option, [474](#)
- gitlab-project-service command line
 - option, [616](#)
- gitlab-project-service-available
 - command line option, [616](#)
- gitlab-project-service-delete command
 - line option, [617](#)
- gitlab-project-service-get command line
 - option, [617](#)
- gitlab-project-service-list command
 - line option, [617](#)
- gitlab-project-service-update command
 - line option, [618](#)
- gitlab-project-share command line
 - option, [474](#)
- gitlab-project-snapshot command line
 - option, [475](#)
- gitlab-project-snippet command line
 - option, [618](#)
- gitlab-project-snippet-award-emoji
 - command line option, [620](#)
- gitlab-project-snippet-award-emoji-create
 - command line option, [621](#)
- gitlab-project-snippet-award-emoji-delete
 - command line option, [621](#)
- gitlab-project-snippet-award-emoji-get
 - command line option, [621](#)
- gitlab-project-snippet-award-emoji-list
 - command line option, [622](#)
- gitlab-project-snippet-content command
 - line option, [618](#)
- gitlab-project-snippet-create command
 - line option, [618](#)
- gitlab-project-snippet-delete command
 - line option, [619](#)
- gitlab-project-snippet-discussion
 - command line option, [622](#)
- gitlab-project-snippet-discussion-create
 - command line option, [622](#)
- gitlab-project-snippet-discussion-get
 - command line option, [623](#)
- gitlab-project-snippet-discussion-list
 - command line option, [623](#)
- gitlab-project-snippet-discussion-note
 - command line option, [623](#)
- gitlab-project-snippet-discussion-note-create

command line option, [624](#)
gitlab-project-snippet-discussion-note-delete command line option, [624](#)
gitlab-project-snippet-discussion-note-get command line option, [624](#)
gitlab-project-snippet-discussion-note-update command line option, [625](#)
gitlab-project-snippet-get command line option, [619](#)
gitlab-project-snippet-list command line option, [619](#)
gitlab-project-snippet-note command line option, [625](#)
gitlab-project-snippet-note-award-emoji command line option, [627](#)
gitlab-project-snippet-note-award-emoji-create command line option, [627](#)
gitlab-project-snippet-note-award-emoji-delete command line option, [628](#)
gitlab-project-snippet-note-award-emoji-get command line option, [628](#)
gitlab-project-snippet-note-award-emoji-list command line option, [629](#)
gitlab-project-snippet-note-create command line option, [625](#)
gitlab-project-snippet-note-delete command line option, [626](#)
gitlab-project-snippet-note-get command line option, [626](#)
gitlab-project-snippet-note-list command line option, [626](#)
gitlab-project-snippet-note-update command line option, [627](#)
gitlab-project-snippet-update command line option, [620](#)
gitlab-project-snippet-user-agent-detail command line option, [620](#)
gitlab-project-star command line option, [475](#)
gitlab-project-storage command line option, [629](#)
gitlab-project-storage-get command line option, [629](#)
gitlab-project-tag command line option, [630](#)
gitlab-project-tag-create command line option, [630](#)
gitlab-project-tag-delete command line option, [630](#)
gitlab-project-tag-get command line option, [630](#)
gitlab-project-tag-list command line option, [631](#)
gitlab-project-transfer command line option, [475](#)
gitlab-project-transfer-project command line option, [475](#)
gitlab-project-trigger command line option, [631](#)
gitlab-project-trigger-create command line option, [631](#)
gitlab-project-trigger-delete command line option, [631](#)
gitlab-project-trigger-get command line option, [632](#)
gitlab-project-trigger-list command line option, [632](#)
gitlab-project-trigger-pipeline command line option, [476](#)
gitlab-project-trigger-update command line option, [632](#)
gitlab-project-unarchive command line option, [476](#)
gitlab-project-unshare command line option, [476](#)
gitlab-project-unstar command line option, [476](#)
gitlab-project-update command line option, [478](#)
gitlab-project-update-submodule command line option, [480](#)
gitlab-project-upload command line option, [481](#)
gitlab-project-user command line option, [633](#)
gitlab-project-user-list command line option, [633](#)
gitlab-project-variable command line option, [633](#)
gitlab-project-variable-create command line option, [633](#)
gitlab-project-variable-delete command line option, [634](#)
gitlab-project-variable-get command line option, [634](#)
gitlab-project-variable-list command line option, [634](#)
gitlab-project-variable-update command line option, [635](#)
gitlab-project-wiki command line option, [635](#)
gitlab-project-wiki-create command line option, [635](#)
gitlab-project-wiki-delete command line option, [636](#)
gitlab-project-wiki-get command line option, [636](#)
gitlab-project-wiki-list command line

- option, [636](#)
- gitlab-project-wiki-update command line option, [637](#)
- gitlab-runner command line option, [637](#)
- gitlab-runner-all command line option, [637](#)
- gitlab-runner-create command line option, [638](#)
- gitlab-runner-delete command line option, [638](#)
- gitlab-runner-get command line option, [638](#)
- gitlab-runner-job command line option, [640](#)
- gitlab-runner-job-list command line option, [640](#)
- gitlab-runner-list command line option, [639](#)
- gitlab-runner-update command line option, [639](#)
- gitlab-runner-verify command line option, [640](#)
- gitlab-snippet command line option, [640](#)
- gitlab-snippet-content command line option, [641](#)
- gitlab-snippet-create command line option, [641](#)
- gitlab-snippet-delete command line option, [641](#)
- gitlab-snippet-get command line option, [641](#)
- gitlab-snippet-list command line option, [642](#)
- gitlab-snippet-public command line option, [642](#)
- gitlab-snippet-update command line option, [642](#)
- gitlab-snippet-user-agent-detail command line option, [643](#)
- gitlab-starred-project command line option, [643](#)
- gitlab-starred-project-list command line option, [643](#)
- gitlab-todo command line option, [644](#)
- gitlab-todo-delete command line option, [644](#)
- gitlab-todo-list command line option, [644](#)
- gitlab-todo-mark-all-as-done command line option, [645](#)
- gitlab-todo-mark-as-done command line option, [645](#)
- gitlab-topic command line option, [645](#)
- gitlab-topic-create command line option, [645](#)
- gitlab-topic-delete command line option, [646](#)
- gitlab-topic-get command line option, [646](#)
- gitlab-topic-list command line option, [646](#)
- gitlab-topic-update command line option, [646](#)
- gitlab-user command line option, [647](#)
- gitlab-user-activate command line option, [647](#)
- gitlab-user-activities command line option, [652](#)
- gitlab-user-activities-list command line option, [652](#)
- gitlab-user-block command line option, [647](#)
- gitlab-user-create command line option, [648](#)
- gitlab-user-custom-attribute command line option, [652](#)
- gitlab-user-custom-attribute-delete command line option, [653](#)
- gitlab-user-custom-attribute-get command line option, [653](#)
- gitlab-user-custom-attribute-list command line option, [653](#)
- gitlab-user-deactivate command line option, [649](#)
- gitlab-user-delete command line option, [649](#)
- gitlab-user-email command line option, [654](#)
- gitlab-user-email-create command line option, [654](#)
- gitlab-user-email-delete command line option, [654](#)
- gitlab-user-email-get command line option, [654](#)
- gitlab-user-email-list command line option, [655](#)
- gitlab-user-event command line option, [655](#)
- gitlab-user-event-list command line option, [655](#)
- gitlab-user-follow command line option, [649](#)
- gitlab-user-get command line option, [649](#)
- gitlab-user-gpg-key command line option, [656](#)
- gitlab-user-gpg-key-create command line option, [656](#)
- gitlab-user-gpg-key-delete command line option, [656](#)
- gitlab-user-gpg-key-get command line

- option, [656](#)
- gitlab-user-gpg-key-list command line option, [657](#)
- gitlab-user-impersonation-token command line option, [657](#)
- gitlab-user-impersonation-token-create command line option, [657](#)
- gitlab-user-impersonation-token-delete command line option, [658](#)
- gitlab-user-impersonation-token-get command line option, [658](#)
- gitlab-user-impersonation-token-list command line option, [658](#)
- gitlab-user-key command line option, [659](#)
- gitlab-user-key-create command line option, [659](#)
- gitlab-user-key-delete command line option, [659](#)
- gitlab-user-key-get command line option, [659](#)
- gitlab-user-key-list command line option, [660](#)
- gitlab-user-list command line option, [649](#)
- gitlab-user-membership command line option, [660](#)
- gitlab-user-membership-get command line option, [660](#)
- gitlab-user-membership-list command line option, [660](#)
- gitlab-user-personal-access-token command line option, [661](#)
- gitlab-user-personal-access-token-create command line option, [661](#)
- gitlab-user-project command line option, [661](#)
- gitlab-user-project-create command line option, [662](#)
- gitlab-user-project-list command line option, [663](#)
- gitlab-user-status command line option, [664](#)
- gitlab-user-status-get command line option, [664](#)
- gitlab-user-unblock command line option, [650](#)
- gitlab-user-unfollow command line option, [650](#)
- gitlab-user-update command line option, [651](#)
- gitlab-variable command line option, [664](#)
- gitlab-variable-create command line option, [664](#)
- gitlab-variable-delete command line option, [665](#)

- gitlab-variable-get command line option, [665](#)
- gitlab-variable-list command line option, [665](#)
- gitlab-variable-update command line option, [665](#)
- o
 - gitlab command line option, [376](#)
- v
 - gitlab command line option, [376](#)

A

- access_tokens (*gitlab.v4.objects.Group* attribute), [161](#)
- access_tokens (*gitlab.v4.objects.Project* attribute), [209](#)
- AccessRequestMixin (*class in gitlab.mixins*), [365](#)
- accessrequests (*gitlab.v4.objects.Group* attribute), [161](#)
- accessrequests (*gitlab.v4.objects.Project* attribute), [209](#)
- activate() (*gitlab.v4.objects.User* method), [333](#)
- add_ldap_group_link() (*gitlab.v4.objects.Group* method), [161](#)
- add_spent_time() (*gitlab.mixins.TimeTrackingMixin* method), [371](#)
- additionalstatistics (*gitlab.v4.objects.Project* attribute), [209](#)
- all() (*gitlab.v4.objects.RunnerManager* method), [325](#)
- api_url (*gitlab.Gitlab* property), [134](#)
- api_version (*gitlab.Gitlab* property), [134](#)
- appearance (*gitlab.Gitlab* attribute), [134](#)
- Application (*class in gitlab.v4.objects*), [143](#)
- ApplicationAppearance (*class in gitlab.v4.objects*), [143](#)
- ApplicationAppearanceManager (*class in gitlab.v4.objects*), [143](#)
- ApplicationManager (*class in gitlab.v4.objects*), [144](#)
- applications (*gitlab.Gitlab* attribute), [135](#)
- ApplicationSettings (*class in gitlab.v4.objects*), [145](#)
- ApplicationSettingsManager (*class in gitlab.v4.objects*), [145](#)
- approval_rules (*gitlab.v4.objects.ProjectMergeRequest* attribute), [271](#)
- approval_state (*gitlab.v4.objects.ProjectMergeRequest* attribute), [271](#)
- approvalrules (*gitlab.v4.objects.Project* attribute), [209](#)
- approvals (*gitlab.v4.objects.Project* attribute), [209](#)
- approvals (*gitlab.v4.objects.ProjectMergeRequest* attribute), [271](#)
- approve() (*gitlab.mixins.AccessRequestMixin* method), [365](#)
- approve() (*gitlab.v4.objects.ProjectMergeRequest* method), [271](#)
- archive() (*gitlab.v4.objects.Project* method), [209](#)
- artifact() (*gitlab.v4.objects.Project* method), [209](#)

- [artifact\(\)](#) (*gitlab.v4.objects.ProjectJob method*), 259
[artifacts](#) (*gitlab.v4.objects.Project attribute*), 209
[artifacts\(\)](#) (*gitlab.v4.objects.ProjectJob method*), 259
[attributes](#) (*gitlab.base.RESTObject property*), 348
[audit_events](#) (*gitlab.Gitlab attribute*), 135
[audit_events](#) (*gitlab.v4.objects.Group attribute*), 162
[audit_events](#) (*gitlab.v4.objects.Project attribute*), 209
[AuditEvent](#) (*class in gitlab.v4.objects*), 146
[AuditEventManager](#) (*class in gitlab.v4.objects*), 146
[auth\(\)](#) (*gitlab.Gitlab method*), 135
[available\(\)](#) (*gitlab.v4.objects.ProjectServiceManager method*), 310
[awardemojis](#) (*gitlab.v4.objects.GroupEpicNote attribute*), 178
[awardemojis](#) (*gitlab.v4.objects.ProjectIssue attribute*), 248
[awardemojis](#) (*gitlab.v4.objects.ProjectIssueNote attribute*), 253
[awardemojis](#) (*gitlab.v4.objects.ProjectMergeRequest attribute*), 271
[awardemojis](#) (*gitlab.v4.objects.ProjectMergeRequestNote attribute*), 283
[awardemojis](#) (*gitlab.v4.objects.ProjectSnippet attribute*), 310
[awardemojis](#) (*gitlab.v4.objects.ProjectSnippetNote attribute*), 314
- ## B
- [BadgeRenderMixin](#) (*class in gitlab.mixins*), 365
[badges](#) (*gitlab.v4.objects.Group attribute*), 162
[badges](#) (*gitlab.v4.objects.Project attribute*), 209
[billable_members](#) (*gitlab.v4.objects.Group attribute*), 162
[blame\(\)](#) (*gitlab.v4.objects.ProjectFileManager method*), 242
[block\(\)](#) (*gitlab.v4.objects.User method*), 333
[boards](#) (*gitlab.v4.objects.Group attribute*), 162
[boards](#) (*gitlab.v4.objects.Project attribute*), 209
[branches](#) (*gitlab.v4.objects.Project attribute*), 209
[bridges](#) (*gitlab.v4.objects.ProjectPipeline attribute*), 294
[BroadcastMessage](#) (*class in gitlab.v4.objects*), 147
[BroadcastMessageManager](#) (*class in gitlab.v4.objects*), 147
[broadcastmessages](#) (*gitlab.Gitlab attribute*), 135
- ## C
- [cancel\(\)](#) (*gitlab.v4.objects.ProjectJob method*), 260
[cancel\(\)](#) (*gitlab.v4.objects.ProjectPipeline method*), 294
[cancel_merge_when_pipeline_succeeds\(\)](#) (*gitlab.v4.objects.ProjectMergeRequest method*), 271
[changes\(\)](#) (*gitlab.v4.objects.ProjectMergeRequest method*), 271
[cherry_pick\(\)](#) (*gitlab.v4.objects.ProjectCommit method*), 228
[closed_by\(\)](#) (*gitlab.v4.objects.ProjectIssue method*), 248
[closes_issues\(\)](#) (*gitlab.v4.objects.ProjectMergeRequest method*), 272
[cls_to_what\(\)](#) (*in module gitlab.cli*), 349
[clusters](#) (*gitlab.v4.objects.Group attribute*), 162
[clusters](#) (*gitlab.v4.objects.Project attribute*), 209
[comments](#) (*gitlab.v4.objects.ProjectCommit attribute*), 228
[commits](#) (*gitlab.v4.objects.Project attribute*), 210
[commits\(\)](#) (*gitlab.v4.objects.ProjectMergeRequest method*), 272
[compound_metrics\(\)](#) (*gitlab.v4.objects.SidekiqManager method*), 327
[ConfigError](#), 350
[content\(\)](#) (*gitlab.v4.objects.ProjectSnippet method*), 310
[content\(\)](#) (*gitlab.v4.objects.Snippet method*), 328
[copy_dict\(\)](#) (*in module gitlab.utils*), 374
[create\(\)](#) (*gitlab.mixins.CreateMixin method*), 365
[create\(\)](#) (*gitlab.v4.objects.GroupClusterManager method*), 171
[create\(\)](#) (*gitlab.v4.objects.GroupEpicIssueManager method*), 177
[create\(\)](#) (*gitlab.v4.objects.ProjectClusterManager method*), 227
[create\(\)](#) (*gitlab.v4.objects.ProjectCommitStatusManager method*), 233
[create\(\)](#) (*gitlab.v4.objects.ProjectFileManager method*), 242
[create\(\)](#) (*gitlab.v4.objects.ProjectForkManager method*), 245
[create\(\)](#) (*gitlab.v4.objects.ProjectIssueLinkManager method*), 252
[create\(\)](#) (*gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager method*), 276
[create\(\)](#) (*gitlab.v4.objects.ProjectPipelineManager method*), 297
[create_fork_relation\(\)](#) (*gitlab.v4.objects.Project method*), 210
[CreateMixin](#) (*class in gitlab.mixins*), 365
[CRUDMixin](#) (*class in gitlab.mixins*), 365
[current_failures\(\)](#) (*gitlab.v4.objects.GeoNodeManager method*), 158
[current_page](#) (*gitlab.base.RESTObjectList property*), 348
[current_page](#) (*gitlab.GitlabList property*), 142

`CurrentUser` (class in `gitlab.v4.objects`), 148
`CurrentUserEmail` (class in `gitlab.v4.objects`), 148
`CurrentUserEmailManager` (class in `gitlab.v4.objects`), 148
`CurrentUserGPGKey` (class in `gitlab.v4.objects`), 149
`CurrentUserGPGKeyManager` (class in `gitlab.v4.objects`), 149
`CurrentUserKey` (class in `gitlab.v4.objects`), 150
`CurrentUserKeyManager` (class in `gitlab.v4.objects`), 150
`CurrentUserManager` (class in `gitlab.v4.objects`), 151
`CurrentUserStatus` (class in `gitlab.v4.objects`), 151
`CurrentUserStatusManager` (class in `gitlab.v4.objects`), 152
`customattributes` (`gitlab.v4.objects.Group` attribute), 162
`customattributes` (`gitlab.v4.objects.Project` attribute), 210
`customattributes` (`gitlab.v4.objects.User` attribute), 333

D

`deactivate()` (`gitlab.v4.objects.User` method), 333
`decode()` (`gitlab.v4.objects.ProjectFile` method), 241
`delete()` (`gitlab.mixins.DeleteMixin` method), 366
`delete()` (`gitlab.mixins.ObjectDeleteMixin` method), 368
`delete()` (`gitlab.v4.objects.ProjectArtifactManager` method), 220
`delete()` (`gitlab.v4.objects.ProjectFile` method), 241
`delete()` (`gitlab.v4.objects.ProjectFileManager` method), 243
`delete_artifacts()` (`gitlab.v4.objects.ProjectJob` method), 260
`delete_fork_relation()` (`gitlab.v4.objects.Project` method), 210
`delete_in_bulk()` (`gitlab.v4.objects.ProjectRegistryTagManager` method), 305
`delete_ldap_group_link()` (`gitlab.v4.objects.Group` method), 162
`delete_merged_branches()` (`gitlab.v4.objects.RepositoryMixin` method), 321
`DeleteMixin` (class in `gitlab.mixins`), 366
`DeployKey` (class in `gitlab.v4.objects`), 152
`DeployKeyManager` (class in `gitlab.v4.objects`), 152
`deploykeys` (`gitlab.Gitlab` attribute), 135
`deployments` (`gitlab.v4.objects.Project` attribute), 210
`DeployToken` (class in `gitlab.v4.objects`), 153
`DeployTokenManager` (class in `gitlab.v4.objects`), 153
`deploytokens` (`gitlab.Gitlab` attribute), 135
`deploytokens` (`gitlab.v4.objects.Group` attribute), 162
`deploytokens` (`gitlab.v4.objects.Project` attribute), 210

`descendant_groups` (`gitlab.v4.objects.Group` attribute), 162
`die()` (in module `gitlab.cli`), 349
`diff()` (`gitlab.v4.objects.ProjectCommit` method), 228
`diffs` (`gitlab.v4.objects.ProjectMergeRequest` attribute), 272
`discussions` (`gitlab.v4.objects.ProjectCommit` attribute), 228
`discussions` (`gitlab.v4.objects.ProjectIssue` attribute), 248
`discussions` (`gitlab.v4.objects.ProjectMergeRequest` attribute), 272
`discussions` (`gitlab.v4.objects.ProjectSnippet` attribute), 311
`Dockerfile` (class in `gitlab.v4.objects`), 153
`DockerfileManager` (class in `gitlab.v4.objects`), 154
`dockerfiles` (`gitlab.Gitlab` attribute), 135
`docs()` (in module `gitlab.cli`), 349
`download()` (`gitlab.mixins.DownloadMixin` method), 366
`download()` (`gitlab.v4.objects.GenericPackageManager` method), 156
`download()` (`gitlab.v4.objects.ProjectArtifactManager` method), 220
`DownloadMixin` (class in `gitlab.mixins`), 366

E

`emails` (`gitlab.v4.objects.CurrentUser` attribute), 148
`emails` (`gitlab.v4.objects.User` attribute), 334
`enable()` (`gitlab.v4.objects.ProjectKeyManager` method), 263
`enable_debug()` (`gitlab.Gitlab` method), 135
`encoded_id` (`gitlab.base.RESTObject` property), 348
`EncodedId` (class in `gitlab.utils`), 374
`environments` (`gitlab.v4.objects.Project` attribute), 210
`epics` (`gitlab.v4.objects.Group` attribute), 162
`erase()` (`gitlab.v4.objects.ProjectJob` method), 260
`Event` (class in `gitlab.v4.objects`), 154
`EventManager` (class in `gitlab.v4.objects`), 154
`events` (`gitlab.Gitlab` attribute), 135
`events` (`gitlab.v4.objects.Project` attribute), 210
`events` (`gitlab.v4.objects.User` attribute), 334
`exports` (`gitlab.v4.objects.Group` attribute), 162
`exports` (`gitlab.v4.objects.Project` attribute), 210

F

`Feature` (class in `gitlab.v4.objects`), 155
`FeatureManager` (class in `gitlab.v4.objects`), 155
`features` (`gitlab.Gitlab` attribute), 135
`file_path` (`gitlab.v4.objects.ProjectFile` attribute), 241
`files` (`gitlab.v4.objects.Project` attribute), 210
`follow()` (`gitlab.v4.objects.User` method), 334
`followers_users` (`gitlab.v4.objects.User` attribute), 334

`following_users` (*gitlab.v4.objects.User* attribute), 334
`forks` (*gitlab.v4.objects.Project* attribute), 210
`from_config()` (*gitlab.Gitlab* class method), 135

G

`generic_packages` (*gitlab.v4.objects.Project* attribute), 210
`GenericPackage` (class in *gitlab.v4.objects*), 156
`GenericPackageManager` (class in *gitlab.v4.objects*), 156
`GeoNode` (class in *gitlab.v4.objects*), 157
`GeoNodeManager` (class in *gitlab.v4.objects*), 158
`geonodes` (*gitlab.Gitlab* attribute), 135
`get()` (*gitlab.mixins.GetMixin* method), 367
`get()` (*gitlab.mixins.GetWithoutIdMixin* method), 367
`get()` (*gitlab.v4.objects.ApplicationAppearanceManager* method), 144
`get()` (*gitlab.v4.objects.ApplicationSettingsManager* method), 145
`get()` (*gitlab.v4.objects.AuditEventManager* method), 146
`get()` (*gitlab.v4.objects.BroadcastMessageManager* method), 147
`get()` (*gitlab.v4.objects.CurrentUserEmailManager* method), 149
`get()` (*gitlab.v4.objects.CurrentUserGPGKeyManager* method), 149
`get()` (*gitlab.v4.objects.CurrentUserKeyManager* method), 150
`get()` (*gitlab.v4.objects.CurrentUserManager* method), 151
`get()` (*gitlab.v4.objects.CurrentUserStatusManager* method), 152
`get()` (*gitlab.v4.objects.DockerfileManager* method), 154
`get()` (*gitlab.v4.objects.GeoNodeManager* method), 159
`get()` (*gitlab.v4.objects.GitignoreManager* method), 160
`get()` (*gitlab.v4.objects.GitlabciyamlManager* method), 161
`get()` (*gitlab.v4.objects.GroupAuditEventManager* method), 166
`get()` (*gitlab.v4.objects.GroupBadgeManager* method), 167
`get()` (*gitlab.v4.objects.GroupBoardListManager* method), 169
`get()` (*gitlab.v4.objects.GroupBoardManager* method), 170
`get()` (*gitlab.v4.objects.GroupClusterManager* method), 171
`get()` (*gitlab.v4.objects.GroupCustomAttributeManager* method), 172
`get()` (*gitlab.v4.objects.GroupDeployTokenManager* method), 173

`get()` (*gitlab.v4.objects.GroupEpicAwardEmojiManager* method), 175
`get()` (*gitlab.v4.objects.GroupEpicDiscussionNoteManager* method), 176
`get()` (*gitlab.v4.objects.GroupEpicManager* method), 178
`get()` (*gitlab.v4.objects.GroupEpicNoteAwardEmojiManager* method), 179
`get()` (*gitlab.v4.objects.GroupEpicNoteManager* method), 180
`get()` (*gitlab.v4.objects.GroupEpicResourceLabelEventManager* method), 181
`get()` (*gitlab.v4.objects.GroupExportManager* method), 181
`get()` (*gitlab.v4.objects.GroupHookManager* method), 182
`get()` (*gitlab.v4.objects.GroupImportManager* method), 183
`get()` (*gitlab.v4.objects.GroupIssuesStatisticsManager* method), 185
`get()` (*gitlab.v4.objects.GroupLabelManager* method), 186
`get()` (*gitlab.v4.objects.GroupManager* method), 187
`get()` (*gitlab.v4.objects.GroupMemberAllManager* method), 189
`get()` (*gitlab.v4.objects.GroupMemberManager* method), 189
`get()` (*gitlab.v4.objects.GroupMilestoneManager* method), 192
`get()` (*gitlab.v4.objects.GroupNotificationSettingsManager* method), 193
`get()` (*gitlab.v4.objects.GroupVariableManager* method), 197
`get()` (*gitlab.v4.objects.GroupWikiManager* method), 198
`get()` (*gitlab.v4.objects.HookManager* method), 199
`get()` (*gitlab.v4.objects.IssueManager* method), 200
`get()` (*gitlab.v4.objects.IssuesStatisticsManager* method), 201
`get()` (*gitlab.v4.objects.KeyManager* method), 202
`get()` (*gitlab.v4.objects.LicenseManager* method), 204
`get()` (*gitlab.v4.objects.NamespaceManager* method), 206
`get()` (*gitlab.v4.objects.NotificationSettingsManager* method), 207
`get()` (*gitlab.v4.objects.ProjectAdditionalStatisticsManager* method), 217
`get()` (*gitlab.v4.objects.ProjectApprovalManager* method), 218
`get()` (*gitlab.v4.objects.ProjectAuditEventManager* method), 222
`get()` (*gitlab.v4.objects.ProjectBadgeManager* method), 223
`get()` (*gitlab.v4.objects.ProjectBoardListManager*

method), 224

get() (gitlab.v4.objects.ProjectBoardManager method), 225

get() (gitlab.v4.objects.ProjectBranchManager method), 226

get() (gitlab.v4.objects.ProjectClusterManager method), 227

get() (gitlab.v4.objects.ProjectCommitDiscussionManager method), 230

get() (gitlab.v4.objects.ProjectCommitDiscussionNoteManager method), 231

get() (gitlab.v4.objects.ProjectCommitManager method), 232

get() (gitlab.v4.objects.ProjectCustomAttributeManager method), 234

get() (gitlab.v4.objects.ProjectDeploymentManager method), 236

get() (gitlab.v4.objects.ProjectDeployTokenManager method), 235

get() (gitlab.v4.objects.ProjectEnvironmentManager method), 239

get() (gitlab.v4.objects.ProjectExportManager method), 240

get() (gitlab.v4.objects.ProjectFileManager method), 243

get() (gitlab.v4.objects.ProjectHookManager method), 246

get() (gitlab.v4.objects.ProjectImportManager method), 247

get() (gitlab.v4.objects.ProjectIssueAwardEmojiManager method), 249

get() (gitlab.v4.objects.ProjectIssueDiscussionManager method), 250

get() (gitlab.v4.objects.ProjectIssueDiscussionNoteManager method), 251

get() (gitlab.v4.objects.ProjectIssueManager method), 253

get() (gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager method), 254

get() (gitlab.v4.objects.ProjectIssueNoteManager method), 255

get() (gitlab.v4.objects.ProjectIssueResourceLabelEventManager method), 256

get() (gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager method), 256

get() (gitlab.v4.objects.ProjectIssueResourceStateEventManager method), 257

get() (gitlab.v4.objects.ProjectIssuesStatisticsManager method), 258

get() (gitlab.v4.objects.ProjectJobManager method), 262

get() (gitlab.v4.objects.ProjectKeyManager method), 263

get() (gitlab.v4.objects.ProjectLabelManager method), 264

get() (gitlab.v4.objects.ProjectManager method), 266

get() (gitlab.v4.objects.ProjectMemberAllManager method), 269

get() (gitlab.v4.objects.ProjectMemberManager method), 270

get() (gitlab.v4.objects.ProjectMergeRequestApprovalManager method), 274

get() (gitlab.v4.objects.ProjectMergeRequestApprovalStateManager method), 277

get() (gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager method), 278

get() (gitlab.v4.objects.ProjectMergeRequestDiffManager method), 279

get() (gitlab.v4.objects.ProjectMergeRequestDiscussionManager method), 280

get() (gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager method), 281

get() (gitlab.v4.objects.ProjectMergeRequestManager method), 282

get() (gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager method), 283

get() (gitlab.v4.objects.ProjectMergeRequestNoteManager method), 284

get() (gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager method), 285

get() (gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager method), 286

get() (gitlab.v4.objects.ProjectMergeRequestResourceStateEventManager method), 287

get() (gitlab.v4.objects.ProjectMilestoneManager method), 290

get() (gitlab.v4.objects.ProjectNoteManager method), 291

get() (gitlab.v4.objects.ProjectNotificationSettingsManager method), 291

get() (gitlab.v4.objects.ProjectPackageManager method), 293

get() (gitlab.v4.objects.ProjectPagesDomainManager method), 294

get() (gitlab.v4.objects.ProjectPipelineManager method), 297

get() (gitlab.v4.objects.ProjectPipelineScheduleManager method), 299

get() (gitlab.v4.objects.ProjectPipelineTestReportManager method), 300

get() (gitlab.v4.objects.ProjectPipelineTestReportSummaryManager method), 301

get() (gitlab.v4.objects.ProjectProtectedBranchManager method), 302

get() (gitlab.v4.objects.ProjectProtectedTagManager method), 303

get() (gitlab.v4.objects.ProjectPushRulesManager method), 304

- `get()` (`gitlab.v4.objects.ProjectRegistryTagManager` method), 306
- `get()` (`gitlab.v4.objects.ProjectReleaseLinkManager` method), 307
- `get()` (`gitlab.v4.objects.ProjectReleaseManager` method), 308
- `get()` (`gitlab.v4.objects.ProjectServiceManager` method), 310
- `get()` (`gitlab.v4.objects.ProjectSnippetAwardEmojiManager` method), 311
- `get()` (`gitlab.v4.objects.ProjectSnippetDiscussionManager` method), 312
- `get()` (`gitlab.v4.objects.ProjectSnippetDiscussionNoteManager` method), 313
- `get()` (`gitlab.v4.objects.ProjectSnippetManager` method), 314
- `get()` (`gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager` method), 315
- `get()` (`gitlab.v4.objects.ProjectSnippetNoteManager` method), 316
- `get()` (`gitlab.v4.objects.ProjectStorageManager` method), 317
- `get()` (`gitlab.v4.objects.ProjectTagManager` method), 317
- `get()` (`gitlab.v4.objects.ProjectTriggerManager` method), 318
- `get()` (`gitlab.v4.objects.ProjectVariableManager` method), 320
- `get()` (`gitlab.v4.objects.ProjectWikiManager` method), 321
- `get()` (`gitlab.v4.objects.RunnerManager` method), 326
- `get()` (`gitlab.v4.objects.SnippetManager` method), 329
- `get()` (`gitlab.v4.objects.TopicManager` method), 332
- `get()` (`gitlab.v4.objects.UserCustomAttributeManager` method), 336
- `get()` (`gitlab.v4.objects.UserEmailManager` method), 337
- `get()` (`gitlab.v4.objects.UserGPGKeyManager` method), 338
- `get()` (`gitlab.v4.objects.UserImpersonationTokenManager` method), 340
- `get()` (`gitlab.v4.objects.UserKeyManager` method), 341
- `get()` (`gitlab.v4.objects.UserManager` method), 342
- `get()` (`gitlab.v4.objects.UserMembershipManager` method), 343
- `get()` (`gitlab.v4.objects.UserStatusManager` method), 345
- `get()` (`gitlab.v4.objects.VariableManager` method), 346
- `get_id()` (`gitlab.base.RESTObject` method), 348
- `get_license()` (`gitlab.Gitlab` method), 135
- `GetMixin` (class in `gitlab.mixins`), 367
- `GetWithoutIdMixin` (class in `gitlab.mixins`), 367
- `Gitignore` (class in `gitlab.v4.objects`), 159
- `GitignoreManager` (class in `gitlab.v4.objects`), 159
- `gitignores` (`gitlab.Gitlab` attribute), 136
- `gitlab` module, 134
- `Gitlab` (class in `gitlab`), 134
- `gitlab` (`gitlab.base.RESTManager` attribute), 347
- `gitlab` (`gitlab.mixins.CreateMixin` attribute), 366
- `gitlab` (`gitlab.mixins.CRUDMixin` attribute), 365
- `gitlab` (`gitlab.mixins.DeleteMixin` attribute), 366
- `gitlab` (`gitlab.mixins.GetMixin` attribute), 367
- `gitlab` (`gitlab.mixins.GetWithoutIdMixin` attribute), 367
- `gitlab` (`gitlab.mixins.ListMixin` attribute), 368
- `gitlab` (`gitlab.mixins.NoUpdateMixin` attribute), 368
- `gitlab` (`gitlab.mixins.RetrieveMixin` attribute), 369
- `gitlab` (`gitlab.mixins.SetMixin` attribute), 370
- `gitlab` (`gitlab.mixins.UpdateMixin` attribute), 373
- `gitlab` (`gitlab.v4.objects.ApplicationAppearanceManager` attribute), 144
- `gitlab` (`gitlab.v4.objects.ApplicationManager` attribute), 145
- `gitlab` (`gitlab.v4.objects.ApplicationSettingsManager` attribute), 145
- `gitlab` (`gitlab.v4.objects.AuditEventManager` attribute), 147
- `gitlab` (`gitlab.v4.objects.BroadcastMessageManager` attribute), 148
- `gitlab` (`gitlab.v4.objects.CurrentUserEmailManager` attribute), 149
- `gitlab` (`gitlab.v4.objects.CurrentUserGPGKeyManager` attribute), 150
- `gitlab` (`gitlab.v4.objects.CurrentUserKeyManager` attribute), 151
- `gitlab` (`gitlab.v4.objects.CurrentUserManager` attribute), 151
- `gitlab` (`gitlab.v4.objects.CurrentUserStatusManager` attribute), 152
- `gitlab` (`gitlab.v4.objects.DeployKeyManager` attribute), 153
- `gitlab` (`gitlab.v4.objects.DeployTokenManager` attribute), 153
- `gitlab` (`gitlab.v4.objects.DockerfileManager` attribute), 154
- `gitlab` (`gitlab.v4.objects.EventManager` attribute), 155
- `gitlab` (`gitlab.v4.objects.FeatureManager` attribute), 155
- `gitlab` (`gitlab.v4.objects.GenericPackageManager` attribute), 157
- `gitlab` (`gitlab.v4.objects.GeoNodeManager` attribute), 159
- `gitlab` (`gitlab.v4.objects.GitignoreManager` attribute), 160
- `gitlab` (`gitlab.v4.objects.GitlabciyamlManager` attribute), 161
- `gitlab` (`gitlab.v4.objects.GroupAccessRequestManager` attribute), 165

`gitlab (gitlab.v4.objects.GroupAccessTokenManager attribute)`, 166

`gitlab (gitlab.v4.objects.GroupAuditEventManager attribute)`, 167

`gitlab (gitlab.v4.objects.GroupBadgeManager attribute)`, 167

`gitlab (gitlab.v4.objects.GroupBillableMemberManager attribute)`, 168

`gitlab (gitlab.v4.objects.GroupBillableMemberMembershipManager attribute)`, 169

`gitlab (gitlab.v4.objects.GroupBoardListManager attribute)`, 170

`gitlab (gitlab.v4.objects.GroupBoardManager attribute)`, 170

`gitlab (gitlab.v4.objects.GroupClusterManager attribute)`, 172

`gitlab (gitlab.v4.objects.GroupCustomAttributeManager attribute)`, 172

`gitlab (gitlab.v4.objects.GroupDeployTokenManager attribute)`, 173

`gitlab (gitlab.v4.objects.GroupEpicAwardEmojiManager attribute)`, 175

`gitlab (gitlab.v4.objects.GroupEpicDiscussionNoteManager attribute)`, 176

`gitlab (gitlab.v4.objects.GroupEpicIssueManager attribute)`, 177

`gitlab (gitlab.v4.objects.GroupEpicManager attribute)`, 178

`gitlab (gitlab.v4.objects.GroupEpicNoteAwardEmojiManager attribute)`, 179

`gitlab (gitlab.v4.objects.GroupEpicNoteManager attribute)`, 180

`gitlab (gitlab.v4.objects.GroupEpicResourceLabelEventManager attribute)`, 181

`gitlab (gitlab.v4.objects.GroupExportManager attribute)`, 182

`gitlab (gitlab.v4.objects.GroupHookManager attribute)`, 183

`gitlab (gitlab.v4.objects.GroupImportManager attribute)`, 183

`gitlab (gitlab.v4.objects.GroupIssueManager attribute)`, 184

`gitlab (gitlab.v4.objects.GroupIssuesStatisticsManager attribute)`, 185

`gitlab (gitlab.v4.objects.GroupLabelManager attribute)`, 186

`gitlab (gitlab.v4.objects.GroupManager attribute)`, 188

`gitlab (gitlab.v4.objects.GroupMemberAllManager attribute)`, 189

`gitlab (gitlab.v4.objects.GroupMemberManager attribute)`, 190

`gitlab (gitlab.v4.objects.GroupMergeRequestManager attribute)`, 191

`gitlab (gitlab.v4.objects.GroupMilestoneManager attribute)`, 193

`gitlab (gitlab.v4.objects.GroupNotificationSettingsManager attribute)`, 193

`gitlab (gitlab.v4.objects.GroupPackageManager attribute)`, 194

`gitlab (gitlab.v4.objects.GroupProjectManager attribute)`, 195

`gitlab (gitlab.v4.objects.GroupRunnerManager attribute)`, 196

`gitlab (gitlab.v4.objects.GroupVariableManager attribute)`, 197

`gitlab (gitlab.v4.objects.GroupWikiManager attribute)`, 198

`gitlab (gitlab.v4.objects.HookManager attribute)`, 199

`gitlab (gitlab.v4.objects.IssueManager attribute)`, 201

`gitlab (gitlab.v4.objects.IssuesStatisticsManager attribute)`, 201

`gitlab (gitlab.v4.objects.KeyManager attribute)`, 202

`gitlab (gitlab.v4.objects.LDAPGroupManager attribute)`, 203

`gitlab (gitlab.v4.objects.LicenseManager attribute)`, 204

`gitlab (gitlab.v4.objects.MergeRequestManager attribute)`, 205

`gitlab (gitlab.v4.objects.NamespaceManager attribute)`, 206

`gitlab (gitlab.v4.objects.NotificationSettingsManager attribute)`, 207

`gitlab (gitlab.v4.objects.PagesDomainManager attribute)`, 208

`gitlab (gitlab.v4.objects.PersonalAccessTokenManager attribute)`, 208

`gitlab (gitlab.v4.objects.ProjectAccessRequestManager attribute)`, 216

`gitlab (gitlab.v4.objects.ProjectAccessTokenManager attribute)`, 217

`gitlab (gitlab.v4.objects.ProjectAdditionalStatisticsManager attribute)`, 218

`gitlab (gitlab.v4.objects.ProjectApprovalManager attribute)`, 219

`gitlab (gitlab.v4.objects.ProjectApprovalRuleManager attribute)`, 219

`gitlab (gitlab.v4.objects.ProjectArtifactManager attribute)`, 221

`gitlab (gitlab.v4.objects.ProjectAuditEventManager attribute)`, 222

`gitlab (gitlab.v4.objects.ProjectAuditManager attribute)`, 223

`gitlab (gitlab.v4.objects.ProjectBadgeManager attribute)`, 224

`gitlab (gitlab.v4.objects.ProjectBoardListManager attribute)`, 225

`gitlab (gitlab.v4.objects.ProjectBoardManager attribute)`, 225

gitlab (gitlab.v4.objects.ProjectBranchManager attribute), 226	gitlab (gitlab.v4.objects.ProjectIssueResourceStateEventManager attribute), 258
gitlab (gitlab.v4.objects.ProjectClusterManager attribute), 227	gitlab (gitlab.v4.objects.ProjectIssuesStatisticsManager attribute), 259
gitlab (gitlab.v4.objects.ProjectCommitCommentManager attribute), 230	gitlab (gitlab.v4.objects.ProjectJobManager attribute), 262
gitlab (gitlab.v4.objects.ProjectCommitDiscussionManager attribute), 231	gitlab (gitlab.v4.objects.ProjectKeyManager attribute), 263
gitlab (gitlab.v4.objects.ProjectCommitDiscussionNoteManager attribute), 232	gitlab (gitlab.v4.objects.ProjectLabelManager attribute), 265
gitlab (gitlab.v4.objects.ProjectCommitManager attribute), 233	gitlab (gitlab.v4.objects.ProjectManager attribute), 266
gitlab (gitlab.v4.objects.ProjectCommitStatusManager attribute), 234	gitlab (gitlab.v4.objects.ProjectMemberAllManager attribute), 270
gitlab (gitlab.v4.objects.ProjectCustomAttributeManager attribute), 235	gitlab (gitlab.v4.objects.ProjectMemberManager attribute), 270
gitlab (gitlab.v4.objects.ProjectDeploymentManager attribute), 237	gitlab (gitlab.v4.objects.ProjectMergeRequestApprovalManager attribute), 275
gitlab (gitlab.v4.objects.ProjectDeploymentMergeRequestManager attribute), 238	gitlab (gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager attribute), 276
gitlab (gitlab.v4.objects.ProjectDeployTokenManager attribute), 235	gitlab (gitlab.v4.objects.ProjectMergeRequestApprovalStateManager attribute), 277
gitlab (gitlab.v4.objects.ProjectEnvironmentManager attribute), 239	gitlab (gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager attribute), 278
gitlab (gitlab.v4.objects.ProjectEventManager attribute), 240	gitlab (gitlab.v4.objects.ProjectMergeRequestDiffManager attribute), 279
gitlab (gitlab.v4.objects.ProjectExportManager attribute), 241	gitlab (gitlab.v4.objects.ProjectMergeRequestDiscussionManager attribute), 280
gitlab (gitlab.v4.objects.ProjectFileManager attribute), 243	gitlab (gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager attribute), 281
gitlab (gitlab.v4.objects.ProjectForkManager attribute), 246	gitlab (gitlab.v4.objects.ProjectMergeRequestManager attribute), 282
gitlab (gitlab.v4.objects.ProjectHookManager attribute), 246	gitlab (gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager attribute), 284
gitlab (gitlab.v4.objects.ProjectImportManager attribute), 247	gitlab (gitlab.v4.objects.ProjectMergeRequestNoteManager attribute), 284
gitlab (gitlab.v4.objects.ProjectIssueAwardEmojiManager attribute), 249	gitlab (gitlab.v4.objects.ProjectMergeRequestPipelineManager attribute), 285
gitlab (gitlab.v4.objects.ProjectIssueDiscussionManager attribute), 250	gitlab (gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager attribute), 286
gitlab (gitlab.v4.objects.ProjectIssueDiscussionNoteManager attribute), 251	gitlab (gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager attribute), 287
gitlab (gitlab.v4.objects.ProjectIssueLinkManager attribute), 252	gitlab (gitlab.v4.objects.ProjectMergeRequestResourceStateEventManager attribute), 288
gitlab (gitlab.v4.objects.ProjectIssueManager attribute), 253	gitlab (gitlab.v4.objects.ProjectMergeTrainManager attribute), 288
gitlab (gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager attribute), 254	gitlab (gitlab.v4.objects.ProjectMilestoneManager attribute), 290
gitlab (gitlab.v4.objects.ProjectIssueNoteManager attribute), 255	gitlab (gitlab.v4.objects.ProjectNoteManager attribute), 291
gitlab (gitlab.v4.objects.ProjectIssueResourceLabelEventManager attribute), 256	gitlab (gitlab.v4.objects.ProjectNotificationSettingsManager attribute), 292
gitlab (gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager attribute), 257	gitlab (gitlab.v4.objects.ProjectPackageFileManager attribute), 293
	gitlab (gitlab.v4.objects.ProjectPackageManager attribute), 293

- [attribute](#), 293
- [gitlab \(gitlab.v4.objects.ProjectPagesDomainManager attribute\)](#), 294
- [gitlab \(gitlab.v4.objects.ProjectPipelineBridgeManager attribute\)](#), 296
- [gitlab \(gitlab.v4.objects.ProjectPipelineJobManager attribute\)](#), 296
- [gitlab \(gitlab.v4.objects.ProjectPipelineManager attribute\)](#), 298
- [gitlab \(gitlab.v4.objects.ProjectPipelineScheduleManager attribute\)](#), 299
- [gitlab \(gitlab.v4.objects.ProjectPipelineScheduleVariableManager attribute\)](#), 300
- [gitlab \(gitlab.v4.objects.ProjectPipelineTestReportManager attribute\)](#), 300
- [gitlab \(gitlab.v4.objects.ProjectPipelineTestReportSummaryManager attribute\)](#), 301
- [gitlab \(gitlab.v4.objects.ProjectPipelineVariableManager attribute\)](#), 302
- [gitlab \(gitlab.v4.objects.ProjectProtectedBranchManager attribute\)](#), 303
- [gitlab \(gitlab.v4.objects.ProjectProtectedTagManager attribute\)](#), 303
- [gitlab \(gitlab.v4.objects.ProjectPushRulesManager attribute\)](#), 304
- [gitlab \(gitlab.v4.objects.ProjectRegistryRepositoryManager attribute\)](#), 305
- [gitlab \(gitlab.v4.objects.ProjectRegistryTagManager attribute\)](#), 306
- [gitlab \(gitlab.v4.objects.ProjectReleaseLinkManager attribute\)](#), 307
- [gitlab \(gitlab.v4.objects.ProjectReleaseManager attribute\)](#), 308
- [gitlab \(gitlab.v4.objects.ProjectRemoteMirrorManager attribute\)](#), 308
- [gitlab \(gitlab.v4.objects.ProjectRunnerManager attribute\)](#), 309
- [gitlab \(gitlab.v4.objects.ProjectServiceManager attribute\)](#), 310
- [gitlab \(gitlab.v4.objects.ProjectSnippetAwardEmojiManager attribute\)](#), 312
- [gitlab \(gitlab.v4.objects.ProjectSnippetDiscussionManager attribute\)](#), 313
- [gitlab \(gitlab.v4.objects.ProjectSnippetDiscussionNoteManager attribute\)](#), 314
- [gitlab \(gitlab.v4.objects.ProjectSnippetManager attribute\)](#), 314
- [gitlab \(gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager attribute\)](#), 315
- [gitlab \(gitlab.v4.objects.ProjectSnippetNoteManager attribute\)](#), 316
- [gitlab \(gitlab.v4.objects.ProjectStorageManager attribute\)](#), 317
- [gitlab \(gitlab.v4.objects.ProjectTagManager attribute\)](#), 318
- [gitlab \(gitlab.v4.objects.ProjectTriggerManager attribute\)](#), 319
- [gitlab \(gitlab.v4.objects.ProjectUserManager attribute\)](#), 319
- [gitlab \(gitlab.v4.objects.ProjectVariableManager attribute\)](#), 320
- [gitlab \(gitlab.v4.objects.ProjectWikiManager attribute\)](#), 321
- [gitlab \(gitlab.v4.objects.RunnerJobManager attribute\)](#), 325
- [gitlab \(gitlab.v4.objects.RunnerManager attribute\)](#), 326
- [gitlab \(gitlab.v4.objects.SidekiqManager attribute\)](#), 327
- [gitlab \(gitlab.v4.objects.SnippetManager attribute\)](#), 329
- [gitlab \(gitlab.v4.objects.StarredProjectManager attribute\)](#), 330
- [gitlab \(gitlab.v4.objects.TODOManager attribute\)](#), 331
- [gitlab \(gitlab.v4.objects.TopicManager attribute\)](#), 333
- [gitlab \(gitlab.v4.objects.UserActivitiesManager attribute\)](#), 335
- [gitlab \(gitlab.v4.objects.UserCustomAttributeManager attribute\)](#), 336
- [gitlab \(gitlab.v4.objects.UserEmailManager attribute\)](#), 337
- [gitlab \(gitlab.v4.objects.UserEventManager attribute\)](#), 338
- [gitlab \(gitlab.v4.objects.UserGPGKeyManager attribute\)](#), 339
- [gitlab \(gitlab.v4.objects.UserIdentityProviderManager attribute\)](#), 339
- [gitlab \(gitlab.v4.objects.UserImpersonationTokenManager attribute\)](#), 340
- [gitlab \(gitlab.v4.objects.UserKeyManager attribute\)](#), 341
- [gitlab \(gitlab.v4.objects.UserManager attribute\)](#), 342
- [gitlab \(gitlab.v4.objects.UserMembershipManager attribute\)](#), 343
- [gitlab \(gitlab.v4.objects.UserPersonalAccessTokenManager attribute\)](#), 343
- [gitlab \(gitlab.v4.objects.UserProjectManager attribute\)](#), 345
- [gitlab \(gitlab.v4.objects.UserStatusManager attribute\)](#), 346
- [gitlab \(gitlab.v4.objects.VariableManager attribute\)](#), 347
- [gitlab command line option](#)
 - [--api-version](#), 376
 - [--config-file](#), 376
 - [--debug](#), 376
 - [--fancy](#), 376
 - [--fields](#), 376
 - [--gitlab](#), 376
 - [--help](#), 376
 - [--job-token](#), 376

```

--oauth-token, 376
--order-by, 376
--output, 376
--pagination, 376
--per-page, 376
--private-token, 376
--server-url, 376
--ssl-verify, 376
--timeout, 376
--user-agent, 376
--verbose, 376
--version, 376
-c, 376
-d, 376
-f, 376
-g, 376
-h, 376
-o, 376
-v, 376
gitlab.base
    module, 347
gitlab.cli
    module, 349
gitlab.config
    module, 350
gitlab.const
    module, 350
gitlab.exceptions
    module, 350
gitlab.mixins
    module, 365
gitlab.utils
    module, 374
gitlab.v4
    module, 347
gitlab.v4.objects
    module, 143
gitlab-application command line option
    --help, 377
    -h, 377
gitlab-application-appearance command line
    option
    --help, 378
    -h, 378
gitlab-application-appearance-get command
    line option
    --help, 378
    --sudo, 378
    -h, 378
gitlab-application-appearance-update
    command line option
    --description, 378
    --email-header-and-footer-enabled, 379
    --favicon, 378
    --footer-message, 378
    --header-logo, 378
    --header-message, 378
    --help, 378
    --logo, 378
    --message-background-color, 378
    --message-font-color, 379
    --new-project-guidelines, 378
    --sudo, 378
    --title, 378
    -h, 378
gitlab-application-create command line
    option
    --confidential, 377
    --help, 377
    --name, 377
    --redirect-uri, 377
    --scopes, 377
    --sudo, 377
    -h, 377
gitlab-application-delete command line
    option
    --help, 377
    --id, 377
    --sudo, 377
    -h, 377
gitlab-application-list command line option
    --all, 377
    --help, 377
    --page, 377
    --per-page, 377
    --sudo, 377
    -h, 377
gitlab-application-settings command line
    option
    --help, 379
    -h, 379
gitlab-application-settings-get command
    line option
    --help, 379
    --sudo, 379
    -h, 379
gitlab-application-settings-update command
    line option
    --after-sign-out-path, 382
    --allow-local-requests-from-hooks-and-services,
        382
    --allow-local-requests-from-system-hooks,
        383
    --allow-local-requests-from-web-hooks-and-services,
        383
    --asset-proxy-allowlist, 382
    --asset-proxy-enabled, 382
    --asset-proxy-url, 382

```

--asset-proxy-whitelist, 382
--container-registry-token-expire-delay, 382
--created-at, 381
--default-branch-protection, 381
--default-group-visibility, 381
--default-project-visibility, 381
--default-projects-limit, 381
--default-snippet-visibility, 381
--disabled-oauth-sign-in-sources, 381
--domain-allowlist, 381
--domain-blacklist, 381
--domain-blacklist-enabled, 381
--domain-denylist, 381
--domain-denylist-enabled, 381
--domain-whitelist, 381
--dsa-key-restriction, 382
--ecdsa-key-restriction, 382
--ed25519-key-restriction, 382
--enforce-terms, 382
--external-authorization-service-default-label, 382
--external-authorization-service-enabled, 382
--external-authorization-service-timeout, 382
--external-authorization-service-url, 382
--file-template-project-id, 382
--first-day-of-week, 382
--geo-node-allowed-ips, 382
--gravatar-enabled, 381
--help, 381
--home-page-url, 381
--id, 381
--import-sources, 382
--instance-statistics-visibility-private, 382
--local-markdown-version, 382
--max-attachment-size, 381
--outbound-local-requests-whitelist, 381
--password-authentication-enabled-for-web, 381
--performance-bar-allowed-group-id, 382
--plantuml-enabled, 382
--plantuml-url, 382
--polling-interval-multiplier, 382
--repository-storages, 382
--restricted-visibility-levels, 381
--rsa-key-restriction, 382
--session-expire-delay, 381
--sign-in-text, 381
--signup-enabled, 381
--sudo, 381
--terminal-max-session-time, 382
--terms, 382
--updated-at, 381
--user-oauth-applications, 382
--user-show-add-ssh-key-message, 382
-h, 381
gitlab-audit-event command line option
--help, 383
-h, 383
gitlab-audit-event-get command line option
--help, 383
--id, 383
--sudo, 383
-h, 383
gitlab-audit-event-list command line option
--all, 383
--created-after, 383
--created-before, 383
--entity-id, 383
--entity-type, 383
--help, 383
--page, 383
--per-page, 383
--sudo, 383
-h, 383
gitlab-broadcast-message command line option
--help, 384
-h, 384
gitlab-broadcast-message-create command line option
--color, 384
--ends-at, 384
--font, 384
--help, 384
--message, 384
--starts-at, 384
--sudo, 384
-h, 384
gitlab-broadcast-message-delete command line option
--help, 384
--id, 384
--sudo, 384
-h, 384
gitlab-broadcast-message-get command line option
--help, 384
--id, 384
--sudo, 384
-h, 384
gitlab-broadcast-message-list command line option
--all, 385
--help, 385

```

--page, 385
--per-page, 385
--sudo, 385
-h, 385
gitlab-broadcast-message-update command
    line option
--color, 385
--ends-at, 385
--font, 385
--help, 385
--id, 385
--message, 385
--starts-at, 385
--sudo, 385
-h, 385
gitlab-current-user command line option
--help, 385
-h, 385
gitlab-current-user-email command line
    option
--help, 386
-h, 386
gitlab-current-user-email-create command
    line option
--email, 386
--help, 386
--sudo, 386
-h, 386
gitlab-current-user-email-delete command
    line option
--help, 386
--id, 386
--sudo, 386
-h, 386
gitlab-current-user-email-get command line
    option
--help, 386
--id, 386
--sudo, 386
-h, 386
gitlab-current-user-email-list command line
    option
--all, 387
--help, 387
--page, 387
--per-page, 387
--sudo, 387
-h, 387
gitlab-current-user-get command line option
--help, 386
--sudo, 386
-h, 386
gitlab-current-user-gpg-key command line
    option
--help, 387
-h, 387
gitlab-current-user-gpg-key-create command
    line option
--help, 387
--key, 387
--sudo, 387
-h, 387
gitlab-current-user-gpg-key-delete command
    line option
--help, 387
--id, 387
--sudo, 387
-h, 387
gitlab-current-user-gpg-key-get command
    line option
--help, 388
--id, 388
--sudo, 388
-h, 388
gitlab-current-user-gpg-key-list command
    line option
--all, 388
--help, 388
--page, 388
--per-page, 388
--sudo, 388
-h, 388
gitlab-current-user-key command line option
--help, 388
-h, 388
gitlab-current-user-key-create command line
    option
--help, 388
--key, 388
--sudo, 388
--title, 388
-h, 388
gitlab-current-user-key-delete command line
    option
--help, 389
--id, 389
--sudo, 389
-h, 389
gitlab-current-user-key-get command line
    option
--help, 389
--id, 389
--sudo, 389
-h, 389
gitlab-current-user-key-list command line
    option
--all, 389
--help, 389

```

--page, 389
--per-page, 389
--sudo, 389
-h, 389
gitlab-current-user-status command line option
--help, 389
-h, 389
gitlab-current-user-status-get command line option
--help, 390
--sudo, 390
-h, 390
gitlab-current-user-status-update command line option
--emoji, 390
--help, 390
--message, 390
--sudo, 390
-h, 390
gitlab-deploy-key command line option
--help, 390
-h, 390
gitlab-deploy-key-list command line option
--all, 390
--help, 390
--page, 390
--per-page, 390
--sudo, 390
-h, 390
gitlab-deploy-token command line option
--help, 391
-h, 391
gitlab-deploy-token-list command line option
--all, 391
--help, 391
--page, 391
--per-page, 391
--sudo, 391
-h, 391
gitlab-dockerfile command line option
--help, 391
-h, 391
gitlab-dockerfile-get command line option
--help, 391
--name, 391
--sudo, 391
-h, 391
gitlab-dockerfile-list command line option
--all, 392
--help, 391
--page, 391
--per-page, 392
--sudo, 391
-h, 391
--sudo, 391
-h, 391
gitlab-event command line option
--help, 392
-h, 392
gitlab-event-list command line option
--action, 392
--after, 392
--all, 392
--before, 392
--help, 392
--page, 392
--per-page, 392
--sort, 392
--sudo, 392
--target-type, 392
-h, 392
gitlab-feature command line option
--help, 392
-h, 392
gitlab-feature-delete command line option
--help, 393
--name, 393
--sudo, 393
-h, 393
gitlab-feature-list command line option
--all, 393
--help, 393
--page, 393
--per-page, 393
--sudo, 393
-h, 393
gitlab-generic-package command line option
--help, 393
-h, 393
gitlab-generic-package-download command line option
--file-name, 393
--help, 393
--package-name, 393
--package-version, 393
--project-id, 393
--sudo, 393
-h, 393
gitlab-generic-package-upload command line option
--file-name, 394
--help, 394
--package-name, 394
--package-version, 394
--path, 394
--project-id, 394
--sudo, 394
-h, 394

```

gitlab-geo-node command line option
  --help, 394
  -h, 394
gitlab-geo-node-current-failures command
  line option
  --help, 394
  --id, 394
  -h, 394
gitlab-geo-node-delete command line option
  --help, 394
  --id, 394
  --sudo, 394
  -h, 394
gitlab-geo-node-get command line option
  --help, 395
  --id, 395
  --sudo, 395
  -h, 395
gitlab-geo-node-list command line option
  --all, 395
  --help, 395
  --page, 395
  --per-page, 395
  --sudo, 395
  -h, 395
gitlab-geo-node-repair command line option
  --help, 395
  --id, 395
  -h, 395
gitlab-geo-node-status command line option
  --help, 395
  --id, 395
  -h, 395
gitlab-geo-node-update command line option
  --enabled, 396
  --files-max-capacity, 396
  --help, 396
  --id, 396
  --repos-max-capacity, 396
  --sudo, 396
  --url, 396
  -h, 396
gitlab-gitignore command line option
  --help, 396
  -h, 396
gitlab-gitignore-get command line option
  --help, 396
  --name, 396
  --sudo, 396
  -h, 396
gitlab-gitignore-list command line option
  --all, 397
  --help, 396
  --page, 396
  --per-page, 396
  --sudo, 396
  -h, 396
gitlab-gitlabciyaml command line option
  --help, 397
  -h, 397
gitlab-gitlabciyaml-get command line option
  --help, 397
  --name, 397
  --sudo, 397
  -h, 397
gitlab-gitlabciyaml-list command line option
  --all, 397
  --help, 397
  --page, 397
  --per-page, 397
  --sudo, 397
  -h, 397
gitlab-group command line option
  --help, 397
  -h, 397
gitlab-group-access-request command line
  option
  --help, 403
  -h, 403
gitlab-group-access-request-approve command
  line option
  --access-level, 404
  --group-id, 404
  --help, 404
  --id, 404
  --sudo, 404
  -h, 404
gitlab-group-access-request-create command
  line option
  --group-id, 404
  --help, 404
  --sudo, 404
  -h, 404
gitlab-group-access-request-delete command
  line option
  --group-id, 404
  --help, 404
  --id, 404
  --sudo, 404
  -h, 404
gitlab-group-access-request-list command
  line option
  --all, 405
  --group-id, 405
  --help, 404
  --page, 405
  --per-page, 405
  --sudo, 404

```

-h, 404
gitlab-group-access-token command line
 option
 --help, 405
 -h, 405
gitlab-group-access-token-create command
 line option
 --group-id, 405
 --help, 405
 --sudo, 405
 -h, 405
gitlab-group-access-token-delete command
 line option
 --group-id, 405
 --help, 405
 --id, 405
 --sudo, 405
 -h, 405
gitlab-group-access-token-list command line
 option
 --all, 406
 --group-id, 406
 --help, 405
 --page, 406
 --per-page, 406
 --sudo, 405
 -h, 405
gitlab-group-add-ldap-group-link command
 line option
 --cn, 398
 --group-access, 398
 --help, 398
 --id, 398
 --provider, 398
 -h, 398
gitlab-group-audit-event command line
 option
 --help, 406
 -h, 406
gitlab-group-audit-event-get command line
 option
 --group-id, 406
 --help, 406
 --id, 406
 --sudo, 406
 -h, 406
gitlab-group-audit-event-list command line
 option
 --all, 406
 --created-after, 406
 --created-before, 406
 --group-id, 406
 --help, 406
 --page, 406
 --per-page, 406
 --sudo, 406
 -h, 406
gitlab-group-badge command line option
 --help, 407
 -h, 407
gitlab-group-badge-create command line
 option
 --group-id, 407
 --help, 407
 --image-url, 407
 --link-url, 407
 --sudo, 407
 -h, 407
gitlab-group-badge-delete command line
 option
 --group-id, 407
 --help, 407
 --id, 407
 --sudo, 407
 -h, 407
gitlab-group-badge-get command line option
 --group-id, 407
 --help, 407
 --id, 407
 --sudo, 407
 -h, 407
gitlab-group-badge-list command line option
 --all, 408
 --group-id, 408
 --help, 408
 --page, 408
 --per-page, 408
 --sudo, 408
 -h, 408
gitlab-group-badge-render command line
 option
 --group-id, 408
 --help, 408
 --id, 408
 --image-url, 408
 --link-url, 408
 --sudo, 408
 -h, 408
gitlab-group-badge-update command line
 option
 --group-id, 408
 --help, 408
 --id, 408
 --image-url, 408
 --link-url, 408
 --sudo, 408
 -h, 408

```

gitlab-group-billable-member command line
    option
    --help, 409
    -h, 409
gitlab-group-billable-member-delete command
    line option
    --group-id, 409
    --help, 409
    --id, 409
    --sudo, 409
    -h, 409
gitlab-group-billable-member-list command
    line option
    --all, 409
    --group-id, 409
    --help, 409
    --page, 409
    --per-page, 409
    --search, 409
    --sort, 409
    --sudo, 409
    -h, 409
gitlab-group-billable-member-membership
    command line option
    --help, 410
    -h, 410
gitlab-group-billable-member-membership-list
    command line option
    --all, 410
    --group-id, 410
    --help, 410
    --page, 410
    --per-page, 410
    --sudo, 410
    --user-id, 410
    -h, 410
gitlab-group-board command line option
    --help, 410
    -h, 410
gitlab-group-board-create command line
    option
    --group-id, 410
    --help, 410
    --name, 410
    --sudo, 410
    -h, 410
gitlab-group-board-delete command line
    option
    --group-id, 411
    --help, 411
    --id, 411
    --sudo, 411
    -h, 411
gitlab-group-board-get command line option
    --group-id, 411
    --help, 411
    --id, 411
    --sudo, 411
    -h, 411
gitlab-group-board-list command line option
    --all, 411
    --group-id, 411
    --help, 411, 412
    --page, 411
    --per-page, 411
    --sudo, 411
    -h, 411, 412
gitlab-group-board-list-create command line
    option
    --board-id, 412
    --group-id, 412
    --help, 412
    --label-id, 412
    --sudo, 412
    -h, 412
gitlab-group-board-list-delete command line
    option
    --board-id, 412
    --group-id, 412
    --help, 412
    --id, 412
    --sudo, 412
    -h, 412
gitlab-group-board-list-get command line
    option
    --board-id, 413
    --group-id, 413
    --help, 413
    --id, 413
    --sudo, 413
    -h, 413
gitlab-group-board-list-list command line
    option
    --all, 413
    --board-id, 413
    --group-id, 413
    --help, 413
    --page, 413
    --per-page, 413
    --sudo, 413
    -h, 413
gitlab-group-board-list-update command line
    option
    --board-id, 413
    --group-id, 413
    --help, 413
    --id, 413
    --position, 413

```

--sudo, 413
-h, 413
gitlab-group-board-update command line option
--group-id, 412
--help, 412
--id, 412
--sudo, 412
-h, 412
gitlab-group-cluster command line option
--help, 414
-h, 414
gitlab-group-cluster-create command line option
--domain, 414
--enabled, 414
--environment-scope, 414
--group-id, 414
--help, 414
--managed, 414
--name, 414
--platform-kubernetes-attributes, 414
--sudo, 414
-h, 414
gitlab-group-cluster-delete command line option
--group-id, 414
--help, 414
--id, 414
--sudo, 414
-h, 414
gitlab-group-cluster-get command line option
--group-id, 415
--help, 415
--id, 415
--sudo, 415
-h, 415
gitlab-group-cluster-list command line option
--all, 415
--group-id, 415
--help, 415
--page, 415
--per-page, 415
--sudo, 415
-h, 415
gitlab-group-cluster-update command line option
--domain, 415
--environment-scope, 416
--group-id, 415
--help, 415
--id, 415
--management-project-id, 415
--name, 415
--platform-kubernetes-attributes, 415
--sudo, 415
-h, 415
gitlab-group-create command line option
--auto-devops-enabled, 399
--avatar, 399
--default-branch-protection, 399
--description, 398
--emails-disabled, 399
--extra-shared-runners-minutes-limit, 399
--help, 398
--lfs-enabled, 399
--membership-lock, 398
--mentions-disabled, 399
--name, 398
--parent-id, 399
--path, 398
--project-creation-level, 399
--request-access-enabled, 399
--require-two-factor-authentication, 399
--share-with-group-lock, 398
--shared-runners-minutes-limit, 399
--subgroup-creation-level, 399
--sudo, 398
--two-factor-grace-period, 399
--visibility, 398
-h, 398
gitlab-group-custom-attribute command line option
--help, 416
-h, 416
gitlab-group-custom-attribute-delete command line option
--group-id, 416
--help, 416
--key, 416
--sudo, 416
-h, 416
gitlab-group-custom-attribute-get command line option
--group-id, 416
--help, 416
--key, 416
--sudo, 416
-h, 416
gitlab-group-custom-attribute-list command line option
--all, 417
--group-id, 416
--help, 416
--page, 417
--per-page, 417

```

--sudo, 416
-h, 416
gitlab-group-delete command line option
--help, 399
--id, 399
--sudo, 399
-h, 399
gitlab-group-delete-ldap-group-link command
    line option
--cn, 399
--help, 399
--id, 399
--provider, 399
-h, 399
gitlab-group-deploy-token command line
    option
--help, 417
-h, 417
gitlab-group-deploy-token-create command
    line option
--expires-at, 417
--group-id, 417
--help, 417
--name, 417
--scopes, 417
--sudo, 417
--username, 417
-h, 417
gitlab-group-deploy-token-delete command
    line option
--group-id, 417
--help, 417
--id, 417
--sudo, 417
-h, 417
gitlab-group-deploy-token-get command line
    option
--group-id, 418
--help, 418
--id, 418
--sudo, 418
-h, 418
gitlab-group-deploy-token-list command line
    option
--all, 418
--group-id, 418
--help, 418
--page, 418
--per-page, 418
--sudo, 418
-h, 418
gitlab-group-descendant-group command line
    option
--help, 418
-h, 418
gitlab-group-descendant-group-list command
    line option
--all, 419
--all-available, 419
--group-id, 419
--help, 419
--min-access-level, 419
--order-by, 419
--owned, 419
--page, 419
--per-page, 419
--search, 419
--skip-groups, 419
--sort, 419
--statistics, 419
--sudo, 419
--with-custom-attributes, 419
-h, 419
gitlab-group-epic command line option
--help, 419
-h, 419
gitlab-group-epic-award-emoji command line
    option
--help, 421
-h, 421
gitlab-group-epic-award-emoji-create
    command line option
--epic-id, 422
--group-id, 422
--help, 422
--name, 422
--sudo, 422
-h, 422
gitlab-group-epic-award-emoji-delete
    command line option
--epic-id, 422
--group-id, 422
--help, 422
--id, 422
--sudo, 422
-h, 422
gitlab-group-epic-award-emoji-get command
    line option
--epic-id, 422
--group-id, 422
--help, 422
--id, 422
--sudo, 422
-h, 422
gitlab-group-epic-award-emoji-list command
    line option
--all, 423
--epic-id, 423

```

```
--group-id, 423
--help, 423
--page, 423
--per-page, 423
--sudo, 423
-h, 423
gitlab-group-epic-create command line
    option
--description, 420
--end-date, 420
--group-id, 420
--help, 419
--labels, 420
--start-date, 420
--sudo, 419
--title, 420
-h, 419
gitlab-group-epic-delete command line
    option
--group-id, 420
--help, 420
--iid, 420
--sudo, 420
-h, 420
gitlab-group-epic-discussion-note command
line option
--help, 423
-h, 423
gitlab-group-epic-discussion-note-create
    command line option
--body, 423
--created-at, 423
--discussion-id, 423
--epic-iid, 423
--group-id, 423
--help, 423
--sudo, 423
-h, 423
gitlab-group-epic-discussion-note-delete
    command line option
--discussion-id, 424
--epic-iid, 424
--group-id, 424
--help, 424
--id, 424
--sudo, 424
-h, 424
gitlab-group-epic-discussion-note-get
    command line option
--discussion-id, 424
--epic-iid, 424
--group-id, 424
--help, 424
--id, 424
--sudo, 424
-h, 424
gitlab-group-epic-discussion-note-update
    command line option
--body, 425
--discussion-id, 425
--epic-iid, 424
--group-id, 424
--help, 424
--id, 425
--sudo, 424
-h, 424
gitlab-group-epic-get command line option
--group-id, 420
--help, 420
--iid, 420
--sudo, 420
-h, 420
gitlab-group-epic-issue command line option
--help, 425
-h, 425
gitlab-group-epic-issue-create command line
    option
--epic-iid, 425
--group-id, 425
--help, 425
--issue-id, 425
--sudo, 425
-h, 425
gitlab-group-epic-issue-delete command line
    option
--epic-iid, 425
--epic-issue-id, 425
--group-id, 425
--help, 425
--sudo, 425
-h, 425
gitlab-group-epic-issue-list command line
    option
--all, 426
--epic-iid, 426
--group-id, 426
--help, 426
--page, 426
--per-page, 426
--sudo, 426
-h, 426
gitlab-group-epic-issue-update command line
    option
--epic-iid, 426
--epic-issue-id, 426
--group-id, 426
--help, 426
--move-after-id, 426
```

```

--move-before-id, 426
--sudo, 426
-h, 426
gitlab-group-epic-list command line option
--all, 421
--author-id, 421
--group-id, 420
--help, 420
--labels, 421
--order-by, 421
--page, 421
--per-page, 421
--search, 421
--sort, 421
--sudo, 420
-h, 420
gitlab-group-epic-note command line option
--help, 426
-h, 426
gitlab-group-epic-note-award-emoji command
line option
--help, 428
-h, 428
gitlab-group-epic-note-award-emoji-create
command line option
--epic-iid, 429
--group-id, 429
--help, 429
--name, 429
--note-id, 429
--sudo, 429
-h, 429
gitlab-group-epic-note-award-emoji-delete
command line option
--epic-iid, 429
--group-id, 429
--help, 429
--id, 429
--note-id, 429
--sudo, 429
-h, 429
gitlab-group-epic-note-award-emoji-get
command line option
--epic-iid, 429
--group-id, 429
--help, 429
--id, 429
--note-id, 429
--sudo, 429
-h, 429
gitlab-group-epic-note-award-emoji-list
command line option
--all, 430
--epic-iid, 430
--group-id, 430
--help, 430
--note-id, 430
--page, 430
--per-page, 430
--sudo, 430
-h, 430
gitlab-group-epic-note-create command line
option
--body, 427
--created-at, 427
--epic-iid, 427
--group-id, 427
--help, 427
--sudo, 427
-h, 427
gitlab-group-epic-note-delete command line
option
--epic-iid, 427
--group-id, 427
--help, 427
--id, 427
--sudo, 427
-h, 427
gitlab-group-epic-note-get command line
option
--epic-iid, 427
--group-id, 427
--help, 427
--id, 427
--sudo, 427
-h, 427
gitlab-group-epic-note-list command line
option
--all, 428
--epic-iid, 428
--group-id, 428
--help, 428
--page, 428
--per-page, 428
--sudo, 428
-h, 428
gitlab-group-epic-note-update command line
option
--body, 428
--epic-iid, 428
--group-id, 428
--help, 428
--id, 428
--sudo, 428
-h, 428
gitlab-group-epic-resource-label-event
command line option
--help, 430

```

-h, 430

gitlab-group-epic-resource-label-event-get
command line option

- epic-id, 430
- group-id, 430
- help, 430
- id, 430
- sudo, 430

-h, 430

gitlab-group-epic-resource-label-event-list
command line option

- all, 431
- epic-id, 431
- group-id, 431
- help, 431
- page, 431
- per-page, 431
- sudo, 431

-h, 431

gitlab-group-epic-update command line
option

- description, 421
- end-date, 421
- group-id, 421
- help, 421
- iid, 421
- labels, 421
- start-date, 421
- sudo, 421
- title, 421

-h, 421

gitlab-group-export command line option

- help, 431

-h, 431

gitlab-group-export-create command line
option

- group-id, 431
- help, 431
- sudo, 431

-h, 431

gitlab-group-export-download command line
option

- group-id, 431
- help, 431
- sudo, 431

-h, 431

gitlab-group-export-get command line option

- group-id, 432
- help, 432
- sudo, 432

-h, 432

gitlab-group-get command line option

- help, 400
- id, 400
- sudo, 400
- h, 400

gitlab-group-hook command line option

- help, 432

-h, 432

gitlab-group-hook-create command line
option

- confidential-issues-events, 432
- confidential-note-events, 433
- deployment-events, 433
- enable-ssl-verification, 433
- group-id, 432
- help, 432
- issues-events, 432
- job-events, 433
- merge-requests-events, 432
- note-events, 433
- pipeline-events, 433
- push-events, 432
- releases-events, 433
- subgroup-events, 433
- sudo, 432
- tag-push-events, 432
- token, 433
- url, 432
- wiki-page-events, 433

-h, 432

gitlab-group-hook-delete command line
option

- group-id, 433
- help, 433
- id, 433
- sudo, 433

-h, 433

gitlab-group-hook-get command line option

- group-id, 433
- help, 433
- id, 433
- sudo, 433

-h, 433

gitlab-group-hook-list command line option

- all, 434
- group-id, 434
- help, 434
- page, 434
- per-page, 434
- sudo, 434

-h, 434

gitlab-group-hook-update command line
option

- confidential-issues-events, 434
- confidential-note-events, 435
- deployment-events, 435
- enable-ssl-verification, 435

```

--group-id, 434
--help, 434
--id, 434
--issues-events, 434
--job-events, 435
--merge-requests-events, 434
--note-events, 435
--pipeline-events, 435
--push-events, 434
--releases-events, 435
--subgroup-events, 435
--sudo, 434
--tag-push-events, 434
--token, 435
--url, 434
--wiki-page-events, 435
-h, 434
gitlab-group-import command line option
--help, 435
-h, 435
gitlab-group-import-get command line option
--group-id, 435
--help, 435
--sudo, 435
-h, 435
gitlab-group-issue command line option
--help, 435
-h, 435
gitlab-group-issue-list command line option
--all, 436
--assignee-id, 436
--author-id, 436
--created-after, 436
--created-before, 436
--group-id, 436
--help, 436
--iids, 436
--labels, 436
--milestone, 436
--my-reaction-emoji, 436
--order-by, 436
--page, 436
--per-page, 436
--search, 436
--sort, 436
--state, 436
--sudo, 436
--updated-after, 436
--updated-before, 436
-h, 436
gitlab-group-issues-statistics command line
option
--help, 437
-h, 437
gitlab-group-issues-statistics-get command
line option
--group-id, 437
--help, 437
--sudo, 437
-h, 437
gitlab-group-label command line option
--help, 437
-h, 437
gitlab-group-label-create command line
option
--color, 437
--description, 437
--group-id, 437
--help, 437
--name, 437
--priority, 437
--sudo, 437
-h, 437
gitlab-group-label-delete command line
option
--group-id, 438
--help, 438
--name, 438
--sudo, 438
-h, 438
gitlab-group-label-get command line option
--group-id, 438
--help, 438
--name, 438
--sudo, 438
-h, 438
gitlab-group-label-list command line option
--all, 438
--group-id, 438
--help, 438
--page, 438
--per-page, 438
--sudo, 438
-h, 438
gitlab-group-label-subscribe command line
option
--group-id, 439
--help, 439
--name, 439
--sudo, 439
-h, 439
gitlab-group-label-unsubscribe command line
option
--group-id, 439
--help, 439
--name, 439
--sudo, 439
-h, 439

```

gitlab-group-label-update command line
option

--color, 439
--description, 439
--group-id, 439
--help, 439
--name, 439
--new-name, 439
--priority, 439
--sudo, 439
-h, 439

gitlab-group-ldap-sync command line option

--help, 400
--id, 400
-h, 400

gitlab-group-list command line option

--all, 401
--all-available, 400
--help, 400
--min-access-level, 400
--order-by, 400
--owned, 400
--page, 401
--per-page, 401
--search, 400
--skip-groups, 400
--sort, 400
--statistics, 400
--sudo, 400
--top-level-only, 400
--with-custom-attributes, 400
-h, 400

gitlab-group-member command line option

--help, 440
-h, 440

gitlab-group-member-all command line option

--help, 441
-h, 441

gitlab-group-member-all-get command line
option

--group-id, 442
--help, 441
--id, 442
--sudo, 441
-h, 441

gitlab-group-member-all-list command line
option

--all, 442
--group-id, 442
--help, 442
--page, 442
--per-page, 442
--sudo, 442
-h, 442

gitlab-group-member-create command line
option

--access-level, 440
--expires-at, 440
--group-id, 440
--help, 440
--sudo, 440
--user-id, 440
-h, 440

gitlab-group-member-delete command line
option

--group-id, 440
--help, 440
--id, 440
--sudo, 440
-h, 440

gitlab-group-member-get command line option

--group-id, 440
--help, 440
--id, 440
--sudo, 440
-h, 440

gitlab-group-member-list command line

option
--all, 441
--group-id, 441
--help, 441
--page, 441
--per-page, 441
--sudo, 441
-h, 441

gitlab-group-member-update command line
option

--access-level, 441
--expires-at, 441
--group-id, 441
--help, 441
--id, 441
--sudo, 441
-h, 441

gitlab-group-merge-request command line
option

--help, 442
-h, 442

gitlab-group-merge-request-list command
line option

--all, 443
--approved-by-ids, 443
--approver-ids, 443
--assignee-id, 443
--author-id, 443
--created-after, 443
--created-before, 443
--group-id, 443

```

--help, 442
--labels, 443
--milestone, 443
--my-reaction-emoji, 443
--order-by, 443
--page, 443
--per-page, 443
--scope, 443
--search, 443
--sort, 443
--source-branch, 443
--state, 443
--sudo, 443
--target-branch, 443
--updated-after, 443
--updated-before, 443
--view, 443
--wip, 443
-h, 442
gitlab-group-milestone command line option
--help, 444
-h, 444
gitlab-group-milestone-create command line
    option
--description, 444
--due-date, 444
--group-id, 444
--help, 444
--start-date, 444
--sudo, 444
--title, 444
-h, 444
gitlab-group-milestone-delete command line
    option
--group-id, 444
--help, 444
--id, 444
--sudo, 444
-h, 444
gitlab-group-milestone-get command line
    option
--group-id, 445
--help, 445
--id, 445
--sudo, 445
-h, 445
gitlab-group-milestone-issues command line
    option
--group-id, 445
--help, 445
--id, 445
--sudo, 445
-h, 445
gitlab-group-milestone-list command line
    option
--all, 445
--group-id, 445
--help, 445
--iids, 445
--page, 445
--per-page, 445
--search, 445
--state, 445
--sudo, 445
-h, 445
gitlab-group-milestone-merge-requests
    command line option
--group-id, 446
--help, 446
--id, 446
--sudo, 446
-h, 446
gitlab-group-milestone-update command line
    option
--description, 446
--due-date, 446
--group-id, 446
--help, 446
--id, 446
--start-date, 446
--state-event, 446
--sudo, 446
--title, 446
-h, 446
gitlab-group-notification-settings command
    line option
--help, 446
-h, 446
gitlab-group-notification-settings-get
    command line option
--group-id, 447
--help, 447
--sudo, 447
-h, 447
gitlab-group-notification-settings-update
    command line option
--close-issue, 447
--close-merge-request, 448
--group-id, 447
--help, 447
--level, 447
--merge-merge-request, 448
--new-issue, 447
--new-merge-request, 447
--new-note, 447
--notification-email, 447
--reassign-issue, 447

```

```
--reassign-merge-request, 448
--reopen-issue, 447
--reopen-merge-request, 447
--sudo, 447
-h, 447
gitlab-group-package command line option
--help, 448
-h, 448
gitlab-group-package-list command line
  option
--all, 448
--exclude-subgroups, 448
--group-id, 448
--help, 448
--order-by, 448
--package-name, 448
--package-type, 448
--page, 448
--per-page, 448
--sort, 448
--sudo, 448
-h, 448
gitlab-group-project command line option
--help, 449
-h, 449
gitlab-group-project-list command line
  option
--all, 450
--archived, 449
--group-id, 449
--help, 449
--include-subgroups, 449
--min-access-level, 450
--order-by, 449
--owned, 449
--page, 450
--per-page, 450
--search, 449
--simple, 449
--sort, 449
--starred, 449
--sudo, 449
--visibility, 449
--with-custom-attributes, 449
--with-issues-enabled, 449
--with-merge-requests-enabled, 449
--with-security-reports, 450
--with-shared, 449
-h, 449
gitlab-group-runner command line option
--help, 450
-h, 450
gitlab-group-runner-list command line
  option
--all, 450
--group-id, 450
--help, 450
--page, 450
--per-page, 450
--scope, 450
--sudo, 450
--tag-list, 450
-h, 450
gitlab-group-search command line option
--help, 401
--id, 401
--scope, 401
--search, 401
-h, 401
gitlab-group-share command line option
--expires-at, 401
--group-access, 401
--group-id, 401
--help, 401
--id, 401
-h, 401
gitlab-group-subgroup command line option
--help, 450
-h, 450
gitlab-group-subgroup-list command line
  option
--all, 451
--all-available, 451
--group-id, 451
--help, 451
--min-access-level, 451
--order-by, 451
--owned, 451
--page, 451
--per-page, 451
--search, 451
--skip-groups, 451
--sort, 451
--statistics, 451
--sudo, 451
--with-custom-attributes, 451
-h, 451
gitlab-group-transfer command line option
--group-id, 401
--help, 401
--id, 401
-h, 401
gitlab-group-transfer-project command line
  option
--help, 402
--id, 402
--project-id, 402
-h, 402
```

- gitlab-group-unshare command line option
 - group-id, [402](#)
 - help, [402](#)
 - id, [402](#)
 - h, [402](#)
- gitlab-group-update command line option
 - auto-devops-enabled, [403](#)
 - avatar, [403](#)
 - default-branch-protection, [403](#)
 - description, [403](#)
 - emails-disabled, [403](#)
 - extra-shared-runners-minutes-limit, [403](#)
 - file-template-project-id, [403](#)
 - help, [402](#)
 - id, [403](#)
 - lfs-enabled, [403](#)
 - membership-lock, [403](#)
 - mentions-disabled, [403](#)
 - name, [403](#)
 - path, [403](#)
 - prevent-forking-outside-group, [403](#)
 - project-creation-level, [403](#)
 - request-access-enabled, [403](#)
 - require-two-factor-authentication, [403](#)
 - share-with-group-lock, [403](#)
 - shared-runners-minutes-limit, [403](#)
 - shared-runners-setting, [403](#)
 - subgroup-creation-level, [403](#)
 - sudo, [402](#)
 - two-factor-grace-period, [403](#)
 - visibility, [403](#)
 - h, [402](#)
- gitlab-group-variable command line option
 - help, [451](#)
 - h, [451](#)
- gitlab-group-variable-create command line option
 - group-id, [452](#)
 - help, [452](#)
 - key, [452](#)
 - masked, [452](#)
 - protected, [452](#)
 - sudo, [452](#)
 - value, [452](#)
 - variable-type, [452](#)
 - h, [452](#)
- gitlab-group-variable-delete command line option
 - group-id, [452](#)
 - help, [452](#)
 - key, [452](#)
 - sudo, [452](#)
 - h, [452](#)
- gitlab-group-variable-get command line option
 - group-id, [452](#)
 - help, [452](#)
 - key, [452](#)
 - sudo, [452](#)
 - h, [452](#)
- gitlab-group-variable-list command line option
 - all, [453](#)
 - group-id, [453](#)
 - help, [453](#)
 - page, [453](#)
 - per-page, [453](#)
 - sudo, [453](#)
 - h, [453](#)
- gitlab-group-variable-update command line option
 - group-id, [453](#)
 - help, [453](#)
 - key, [453](#)
 - masked, [453](#)
 - protected, [453](#)
 - sudo, [453](#)
 - value, [453](#)
 - variable-type, [453](#)
 - h, [453](#)
- gitlab-group-wiki command line option
 - help, [453](#)
 - h, [453](#)
- gitlab-group-wiki-create command line option
 - content, [454](#)
 - format, [454](#)
 - group-id, [454](#)
 - help, [454](#)
 - sudo, [454](#)
 - title, [454](#)
 - h, [454](#)
- gitlab-group-wiki-delete command line option
 - group-id, [454](#)
 - help, [454](#)
 - slug, [454](#)
 - sudo, [454](#)
 - h, [454](#)
- gitlab-group-wiki-get command line option
 - group-id, [454](#)
 - help, [454](#)
 - slug, [454](#)
 - sudo, [454](#)
 - h, [454](#)
- gitlab-group-wiki-list command line option
 - all, [455](#)

`--group-id`, 455
`--help`, 455
`--page`, 455
`--per-page`, 455
`--sudo`, 455
`--with-content`, 455
`-h`, 455

`gitlab-group-wiki-update` command line option
`--content`, 455
`--format`, 455
`--group-id`, 455
`--help`, 455
`--slug`, 455
`--sudo`, 455
`--title`, 455
`-h`, 455

`gitlab-hook` command line option
`--help`, 455
`-h`, 455

`gitlab-hook-create` command line option
`--help`, 456
`--sudo`, 456
`--url`, 456
`-h`, 456

`gitlab-hook-delete` command line option
`--help`, 456
`--id`, 456
`--sudo`, 456
`-h`, 456

`gitlab-hook-get` command line option
`--help`, 456
`--id`, 456
`--sudo`, 456
`-h`, 456

`gitlab-hook-list` command line option
`--all`, 456
`--help`, 456
`--page`, 456
`--per-page`, 456
`--sudo`, 456
`-h`, 456

`gitlab-issue` command line option
`--help`, 457
`-h`, 457

`gitlab-issue-get` command line option
`--help`, 457
`--id`, 457
`--sudo`, 457
`-h`, 457

`gitlab-issue-list` command line option
`--all`, 458
`--assignee-id`, 457
`--author-id`, 457
`--created-after`, 458
`--created-before`, 458
`--help`, 457
`--iids`, 457
`--labels`, 457
`--milestone`, 457
`--my-reaction-emoji`, 457
`--order-by`, 457
`--page`, 458
`--per-page`, 458
`--scope`, 457
`--search`, 458
`--sort`, 457
`--state`, 457
`--sudo`, 457
`--updated-after`, 458
`--updated-before`, 458
`-h`, 457

`gitlab-issues-statistics` command line option
`--help`, 458
`-h`, 458

`gitlab-issues-statistics-get` command line option
`--help`, 458
`--sudo`, 458
`-h`, 458

`gitlab-key` command line option
`--help`, 458
`-h`, 458

`gitlab-key-get` command line option
`--help`, 458
`--id`, 458
`--sudo`, 458
`-h`, 458

`gitlab-ldap-group` command line option
`--help`, 459
`-h`, 459

`gitlab-ldap-group-list` command line option
`--all`, 459
`--help`, 459
`--page`, 459
`--per-page`, 459
`--provider`, 459
`--search`, 459
`--sudo`, 459
`-h`, 459

`gitlab-license` command line option
`--help`, 459
`-h`, 459

`gitlab-license-get` command line option
`--fullname`, 459
`--help`, 459
`--key`, 459

```

--project, 459
--sudo, 459
-h, 459
gitlab-license-list command line option
--all, 460
--help, 460
--page, 460
--per-page, 460
--popular, 460
--sudo, 460
-h, 460
gitlab-merge-request command line option
--help, 460
-h, 460
gitlab-merge-request-list command line
    option
--all, 462
--approved-by-ids, 461
--approver-ids, 461
--assignee-id, 461
--author-id, 461
--author-username, 461
--created-after, 461
--created-before, 461
--deployed-after, 462
--deployed-before, 461
--environment, 461
--help, 460
--in, 461
--labels, 461
--milestone, 461
--my-reaction-emoji, 461
--not, 461
--order-by, 461
--page, 462
--per-page, 462
--reviewer-id, 461
--reviewer-username, 461
--scope, 461
--search, 461
--sort, 461
--source-branch, 461
--state, 461
--sudo, 461
--target-branch, 461
--updated-after, 461
--updated-before, 461
--view, 461
--wip, 461
--with-labels-details, 461
--with-merge-status-recheck, 461
-h, 460
gitlab-namespace command line option
--help, 462
-h, 462
gitlab-namespace-get command line option
--help, 462
--id, 462
--sudo, 462
-h, 462
gitlab-namespace-list command line option
--all, 462
--help, 462
--page, 462
--per-page, 462
--search, 462
--sudo, 462
-h, 462
gitlab-notification-settings command line
    option
--help, 463
-h, 463
gitlab-notification-settings-get command
    line option
--help, 463
--sudo, 463
-h, 463
gitlab-notification-settings-update command
    line option
--close-issue, 463
--close-merge-request, 464
--help, 463
--level, 463
--merge-merge-request, 464
--new-issue, 463
--new-merge-request, 463
--new-note, 463
--notification-email, 463
--reassign-issue, 463
--reassign-merge-request, 464
--reopen-issue, 463
--reopen-merge-request, 463
--sudo, 463
-h, 463
gitlab-pages-domain command line option
--help, 464
-h, 464
gitlab-pages-domain-list command line
    option
--all, 464
--help, 464
--page, 464
--per-page, 464
--sudo, 464
-h, 464
gitlab-personal-access-token command line
    option
--help, 464

```

```
-h, 464
gitlab-personal-access-token-delete command
    line option
    --help, 464
    --id, 464
    --sudo, 464
    -h, 464
gitlab-personal-access-token-list command
    line option
    --all, 465
    --help, 465
    --page, 465
    --per-page, 465
    --sudo, 465
    --user-id, 465
    -h, 465
gitlab-project command line option
    --help, 465
    -h, 465
gitlab-project-access-request command line
    option
    --help, 481
    -h, 481
gitlab-project-access-request-approve
    command line option
    --access-level, 481
    --help, 481
    --id, 481
    --project-id, 481
    --sudo, 481
    -h, 481
gitlab-project-access-request-create
    command line option
    --help, 481
    --project-id, 481
    --sudo, 481
    -h, 481
gitlab-project-access-request-delete
    command line option
    --help, 482
    --id, 482
    --project-id, 482
    --sudo, 482
    -h, 482
gitlab-project-access-request-list command
    line option
    --all, 482
    --help, 482
    --page, 482
    --per-page, 482
    --project-id, 482
    --sudo, 482
    -h, 482
gitlab-project-access-token command line
    option
    --help, 482
    -h, 482
gitlab-project-access-token-create command
    line option
    --help, 482
    --project-id, 482
    --sudo, 482
    -h, 482
gitlab-project-access-token-delete command
    line option
    --help, 483
    --id, 483
    --project-id, 483
    --sudo, 483
    -h, 483
gitlab-project-access-token-list command
    line option
    --all, 483
    --help, 483
    --page, 483
    --per-page, 483
    --project-id, 483
    --sudo, 483
    -h, 483
gitlab-project-additional-statistics
    command line option
    --help, 483
    -h, 483
gitlab-project-additional-statistics-get
    command line option
    --help, 483
    --project-id, 483
    --sudo, 483
    -h, 483
gitlab-project-approval command line option
    --help, 484
    -h, 484
gitlab-project-approval-get command line
    option
    --help, 484
    --project-id, 484
    --sudo, 484
    -h, 484
gitlab-project-approval-rule command line
    option
    --help, 485
    -h, 485
gitlab-project-approval-rule-create command
    line option
    --approvals-required, 485
    --group-ids, 485
    --help, 485
```

```

--name, 485
--project-id, 485
--protected-branch-ids, 485
--sudo, 485
--user-ids, 485
-h, 485
gitlab-project-approval-rule-delete command
  line option
  --help, 485
  --id, 485
  --project-id, 485
  --sudo, 485
  -h, 485
gitlab-project-approval-rule-list command
  line option
  --all, 486
  --help, 486
  --page, 486
  --per-page, 486
  --project-id, 486
  --sudo, 486
  -h, 486
gitlab-project-approval-rule-update command
  line option
  --help, 486
  --id, 486
  --project-id, 486
  --sudo, 486
  -h, 486
gitlab-project-approval-update command line
  option
  --approvals-before-merge, 484
  --disable-overriding-approvers-per-merge-request, 484
  --help, 484
  --merge-requests-author-approval, 484
  --merge-requests-disable-committers-approval, 484
  --project-id, 484
  --reset-approvals-on-push, 484
  --sudo, 484
  -h, 484
gitlab-project-archive command line option
  --help, 465
  --id, 465
  -h, 465
gitlab-project-artifact command line option
  --artifact-path, 466
  --help, 465, 486
  --id, 465
  --job, 466
  --ref-name, 465
  -h, 465, 486
gitlab-project-artifact-delete command line
  option
  --help, 486
  --project-id, 486
  --ref-name, 486
  --sudo, 486
  -h, 486
gitlab-project-artifact-download command
  line option
  --help, 487
  --job, 487
  --job-token, 487
  --project-id, 487
  --ref-name, 487
  --sudo, 487
  -h, 487
gitlab-project-artifact-raw command line
  option
  --artifact-path, 487
  --help, 487
  --job, 487
  --project-id, 487
  --ref-name, 487
  --sudo, 487
  -h, 487
gitlab-project-artifacts command line
  option
  --help, 466
  --id, 466
  --job, 466
  --job-token, 466
  --ref-name, 466
gitlab-project-audit-event command line
  option
  --help, 487
  -h, 487
gitlab-project-audit-event-get command line
  option
  --help, 488
  --id, 488
  --project-id, 488
  --sudo, 488
  -h, 488
gitlab-project-audit-event-list command
  line option
  --all, 488
  --created-after, 488
  --created-before, 488
  --help, 488
  --page, 488
  --per-page, 488
  --project-id, 488
  --sudo, 488

```

```
-h, 488
gitlab-project-badge command line option
--help, 488
-h, 488
gitlab-project-badge-create command line
  option
--help, 489
--image-url, 489
--link-url, 489
--project-id, 489
--sudo, 489
-h, 489
gitlab-project-badge-delete command line
  option
--help, 489
--id, 489
--project-id, 489
--sudo, 489
-h, 489
gitlab-project-badge-get command line
  option
--help, 489
--id, 489
--project-id, 489
--sudo, 489
-h, 489
gitlab-project-badge-list command line
  option
--all, 490
--help, 490
--page, 490
--per-page, 490
--project-id, 490
--sudo, 490
-h, 490
gitlab-project-badge-render command line
  option
--help, 490
--id, 490
--image-url, 490
--link-url, 490
--project-id, 490
--sudo, 490
-h, 490
gitlab-project-badge-update command line
  option
--help, 490
--id, 490
--image-url, 490
--link-url, 490
--project-id, 490
--sudo, 490
-h, 490
gitlab-project-board command line option
--help, 491
-h, 491
gitlab-project-board-create command line
  option
--help, 491
--name, 491
--project-id, 491
--sudo, 491
-h, 491
gitlab-project-board-delete command line
  option
--help, 491
--id, 491
--project-id, 491
--sudo, 491
-h, 491
gitlab-project-board-get command line
  option
--help, 491
--id, 491
--project-id, 491
--sudo, 491
-h, 491
gitlab-project-board-list command line
  option
--all, 492
--help, 492
--page, 492
--per-page, 492
--project-id, 492
--sudo, 492
-h, 492
gitlab-project-board-list-create command
  line option
--board-id, 492
--help, 492
--label-id, 493
--project-id, 492
--sudo, 492
-h, 492
gitlab-project-board-list-delete command
  line option
--board-id, 493
--help, 493
--id, 493
--project-id, 493
--sudo, 493
-h, 493
gitlab-project-board-list-get command line
  option
--board-id, 493
--help, 493
--id, 493
--project-id, 493
```

- `--sudo`, 493
- `-h`, 493
- gitlab-project-board-list-list command line
 - option
 - `--all`, 494
 - `--board-id`, 493
 - `--help`, 493
 - `--page`, 493
 - `--per-page`, 493
 - `--project-id`, 493
 - `--sudo`, 493
 - `-h`, 493
- gitlab-project-board-list-update command
 - line option
 - `--board-id`, 494
 - `--help`, 494
 - `--id`, 494
 - `--position`, 494
 - `--project-id`, 494
 - `--sudo`, 494
 - `-h`, 494
- gitlab-project-board-update command line
 - option
 - `--help`, 492
 - `--id`, 492
 - `--project-id`, 492
 - `--sudo`, 492
 - `-h`, 492
- gitlab-project-branch command line option
 - `--help`, 494
 - `-h`, 494
- gitlab-project-branch-create command line
 - option
 - `--branch`, 494
 - `--help`, 494
 - `--project-id`, 494
 - `--ref`, 494
 - `--sudo`, 494
 - `-h`, 494
- gitlab-project-branch-delete command line
 - option
 - `--help`, 495
 - `--name`, 495
 - `--project-id`, 495
 - `--sudo`, 495
 - `-h`, 495
- gitlab-project-branch-get command line
 - option
 - `--help`, 495
 - `--name`, 495
 - `--project-id`, 495
 - `--sudo`, 495
 - `-h`, 495
- gitlab-project-branch-list command line
 - option
 - `--all`, 495
 - `--help`, 495
 - `--page`, 495
 - `--per-page`, 495
 - `--project-id`, 495
 - `--sudo`, 495
 - `-h`, 495
- gitlab-project-cluster command line option
 - `--help`, 496
 - `-h`, 496
- gitlab-project-cluster-create command line
 - option
 - `--domain`, 496
 - `--enabled`, 496
 - `--environment-scope`, 496
 - `--help`, 496
 - `--managed`, 496
 - `--name`, 496
 - `--platform-kubernetes-attributes`, 496
 - `--project-id`, 496
 - `--sudo`, 496
 - `-h`, 496
- gitlab-project-cluster-delete command line
 - option
 - `--help`, 496
 - `--id`, 496
 - `--project-id`, 496
 - `--sudo`, 496
 - `-h`, 496
- gitlab-project-cluster-get command line
 - option
 - `--help`, 497
 - `--id`, 497
 - `--project-id`, 497
 - `--sudo`, 497
 - `-h`, 497
- gitlab-project-cluster-list command line
 - option
 - `--all`, 497
 - `--help`, 497
 - `--page`, 497
 - `--per-page`, 497
 - `--project-id`, 497
 - `--sudo`, 497
 - `-h`, 497
- gitlab-project-cluster-update command line
 - option
 - `--domain`, 497
 - `--environment-scope`, 498
 - `--help`, 497
 - `--id`, 497
 - `--management-project-id`, 497

```
--name, 497
--platform-kubernetes-attributes, 498
--project-id, 497
--sudo, 497
-h, 497
gitlab-project-commit command line option
--help, 498
-h, 498
gitlab-project-commit-cherry-pick command
  line option
--branch, 498
--help, 498
--id, 498
--project-id, 498
--sudo, 498
-h, 498
gitlab-project-commit-comment command line
  option
--help, 501
-h, 501
gitlab-project-commit-comment-create
  command line option
--commit-id, 501
--help, 501
--line, 502
--line-type, 502
--note, 502
--path, 502
--project-id, 501
--sudo, 501
-h, 501
gitlab-project-commit-comment-list command
  line option
--all, 502
--commit-id, 502
--help, 502
--page, 502
--per-page, 502
--project-id, 502
--sudo, 502
-h, 502
gitlab-project-commit-create command line
  option
--actions, 498
--author-email, 498
--author-name, 499
--branch, 498
--commit-message, 498
--help, 498
--project-id, 498
--sudo, 498
-h, 498
gitlab-project-commit-diff command line
  option
--help, 499
--id, 499
--project-id, 499
--sudo, 499
-h, 499
gitlab-project-commit-discussion command
  line option
--help, 502
-h, 502
gitlab-project-commit-discussion-create
  command line option
--body, 503
--commit-id, 502
--created-at, 503
--help, 502
--project-id, 502
--sudo, 502
-h, 502
gitlab-project-commit-discussion-get
  command line option
--commit-id, 503
--help, 503
--id, 503
--project-id, 503
--sudo, 503
-h, 503
gitlab-project-commit-discussion-list
  command line option
--all, 503
--commit-id, 503
--help, 503
--page, 503
--per-page, 503
--project-id, 503
--sudo, 503
-h, 503
gitlab-project-commit-discussion-note
  command line option
--help, 504
-h, 504
gitlab-project-commit-discussion-note-create
  command line option
--body, 504
--commit-id, 504
--created-at, 504
--discussion-id, 504
--help, 504
--position, 504
--project-id, 504
--sudo, 504
-h, 504
gitlab-project-commit-discussion-note-delete
  command line option
--commit-id, 504
```

```

--discussion-id, 504
--help, 504
--id, 504
--project-id, 504
--sudo, 504
-h, 504
gitlab-project-commit-discussion-note-get
    command line option
--commit-id, 505
--discussion-id, 505
--help, 505
--id, 505
--project-id, 505
--sudo, 505
-h, 505
gitlab-project-commit-discussion-note-update
    command line option
--body, 505
--commit-id, 505
--discussion-id, 505
--help, 505
--id, 505
--project-id, 505
--sudo, 505
-h, 505
gitlab-project-commit-get command line
    option
--help, 499
--id, 499
--project-id, 499
--sudo, 499
-h, 499
gitlab-project-commit-list command line
    option
--all, 500
--first-parent, 500
--help, 499
--order, 500
--page, 500
--path, 500
--per-page, 500
--project-id, 499
--ref-name, 499
--since, 499
--sudo, 499
--trailers, 500
--until, 499
--with-stats, 500
-h, 499
gitlab-project-commit-merge-requests
    command line option
--help, 500
--id, 500
--project-id, 500
--sudo, 500
-h, 500
gitlab-project-commit-refs command line
    option
--help, 500
--id, 500
--project-id, 500
--sudo, 500
--type, 500
-h, 500
gitlab-project-commit-revert command line
    option
--branch, 501
--help, 501
--id, 501
--project-id, 501
--sudo, 501
-h, 501
gitlab-project-commit-signature command
    line option
--help, 501
--id, 501
--project-id, 501
--sudo, 501
-h, 501
gitlab-project-commit-status command line
    option
--help, 505
-h, 505
gitlab-project-commit-status-create command
    line option
--commit-id, 506
--context, 506
--coverage, 506
--description, 506
--help, 506
--name, 506
--project-id, 506
--ref, 506
--state, 506
--sudo, 506
--target-url, 506
-h, 506
gitlab-project-commit-status-list command
    line option
--all, 506
--commit-id, 506
--help, 506
--page, 506
--per-page, 506
--project-id, 506
--sudo, 506
-h, 506
gitlab-project-create command line option

```

`--allow-merge-on-skipped-pipeline`, 467
`--analytics-access-level`, 467
`--approvals-before-merge`, 467
`--auto-cancel-pending-pipelines`, 468
`--auto-devops-deploy-strategy`, 468
`--auto-devops-enabled`, 468
`--autoclose-referenced-issues`, 468
`--avatar`, 468
`--build-coverage-regex`, 468
`--build-git-strategy`, 468
`--build-timeout`, 468
`--builds-access-level`, 468
`--ci-config-path`, 468
`--container-expiration-policy-attributes`, 468
`--container-registry-enabled`, 468
`--default-branch`, 468
`--description`, 468
`--emails-disabled`, 468
`--external-authorization-classification-label`, 468
`--forking-access-level`, 468
`--group-with-project-templates-id`, 468
`--help`, 467
`--import-url`, 468
`--initialize-with-readme`, 468
`--issues-access-level`, 468
`--issues-enabled`, 468
`--jobs-enabled`, 468
`--lfs-enabled`, 468
`--merge-method`, 468
`--merge-requests-access-level`, 468
`--merge-requests-enabled`, 468
`--mirror`, 468
`--mirror-trigger-builds`, 468
`--name`, 467
`--namespace-id`, 468
`--only-allow-merge-if-all-discussions-are-resolved`, 469
`--only-allow-merge-if-pipeline-succeeds`, 469
`--operations-access-level`, 468
`--packages-enabled`, 469
`--pages-access-level`, 469
`--path`, 467
`--printing-merge-request-link-enabled`, 469
`--public-builds`, 469
`--remove-source-branch-after-merge`, 469
`--repository-access-level`, 469
`--repository-storage`, 469
`--request-access-enabled`, 469
`--requirements-access-level`, 469
`--resolve-outdated-diff-discussions`, 469
`--shared-runners-enabled`, 469
`--show-default-award-emojis`, 469
`--snippets-access-level`, 469
`--snippets-enabled`, 469
`--squash-option`, 469
`--sudo`, 467
`--tag-list`, 469
`--template-name`, 469
`--template-project-id`, 469
`--use-custom-template`, 469
`--visibility`, 469
`--wiki-access-level`, 469
`--wiki-enabled`, 469
`-h`, 467
`gitlab-project-create-fork-relation` command line option
`--forked-from-id`, 469
`--help`, 469
`--id`, 469
`gitlab-project-custom-attribute` command line option
`--help`, 507
`-h`, 507
`gitlab-project-custom-attribute-delete` command line option
`--help`, 507
`--key`, 507
`--project-id`, 507
`--sudo`, 507
`-h`, 507
`gitlab-project-custom-attribute-get` command line option
`--help`, 507
`--key`, 507
`--project-id`, 507
`--sudo`, 507
`gitlab-project-custom-attribute-list` command line option
`--all`, 507
`--help`, 507
`--page`, 507
`--per-page`, 507
`--project-id`, 507
`--sudo`, 507
`-h`, 507
`gitlab-project-delete` command line option
`--help`, 470
`--id`, 470
`--sudo`, 470
`-h`, 470
`gitlab-project-delete-fork-relation` command line option

```

--help, 470
--id, 470
-h, 470
gitlab-project-delete-merged-branches
    command line option
--help, 470
--id, 470
-h, 470
gitlab-project-deploy-token command line
    option
--help, 508
-h, 508
gitlab-project-deploy-token-create command
    line option
--expires-at, 508
--help, 508
--name, 508
--project-id, 508
--scopes, 508
--sudo, 508
--username, 508
-h, 508
gitlab-project-deploy-token-delete command
    line option
--help, 508
--id, 508
--project-id, 508
--sudo, 508
-h, 508
gitlab-project-deploy-token-get command
    line option
--help, 508
--id, 509
--project-id, 508
--sudo, 508
-h, 508
gitlab-project-deploy-token-list command
    line option
--all, 509
--help, 509
--page, 509
--per-page, 509
--project-id, 509
--sudo, 509
-h, 509
gitlab-project-deployment command line
    option
--help, 509
-h, 509
gitlab-project-deployment-create command
    line option
--environment, 509
--help, 509
--project-id, 509
--ref, 509
--sha, 509
--status, 509
--sudo, 509
--tag, 509
-h, 509
gitlab-project-deployment-get command line
    option
--help, 510
--id, 510
--project-id, 510
--sudo, 510
-h, 510
gitlab-project-deployment-list command line
    option
--all, 510
--environment, 510
--help, 510
--order-by, 510
--page, 510
--per-page, 510
--project-id, 510
--sort, 510
--status, 510
--sudo, 510
--updated-after, 510
--updated-before, 510
-h, 510
gitlab-project-deployment-merge-request
    command line option
--help, 511
-h, 511
gitlab-project-deployment-merge-request-list
    command line option
--all, 513
--approved-by-ids, 512
--approver-ids, 512
--assignee-id, 512
--author-id, 512
--author-username, 512
--created-after, 512
--created-before, 512
--deployed-after, 513
--deployed-before, 513
--deployment-id, 512
--environment, 513
--help, 512
--in, 513
--labels, 512
--milestone, 512
--my-reaction-emoji, 513
--not, 513
--order-by, 512
--page, 513

```

```
--per-page, 513
--project-id, 512
--reviewer-id, 512
--reviewer-username, 512
--scope, 512
--search, 513
--sort, 512
--source-branch, 513
--state, 512
--sudo, 512
--target-branch, 513
--updated-after, 512
--updated-before, 512
--view, 512
--wip, 513
--with-labels-details, 512
--with-merge-status-recheck, 512
-h, 512
gitlab-project-deployment-update command
    line option
    --help, 511
    --id, 511
    --project-id, 511
    --sudo, 511
    -h, 511
gitlab-project-environment command line
    option
    --help, 513
    -h, 513
gitlab-project-environment-create command
    line option
    --external-url, 513
    --help, 513
    --name, 513
    --project-id, 513
    --sudo, 513
    -h, 513
gitlab-project-environment-delete command
    line option
    --help, 514
    --id, 514
    --project-id, 514
    --sudo, 514
    -h, 514
gitlab-project-environment-get command line
    option
    --help, 514
    --id, 514
    --project-id, 514
    --sudo, 514
    -h, 514
gitlab-project-environment-list command
    line option
    --all, 514
    --help, 514
    --name, 514
    --page, 514
    --per-page, 514
    --project-id, 514
    --search, 514
    --states, 514
    --sudo, 514
    -h, 514
gitlab-project-environment-stop command
    line option
    --help, 515
    --id, 515
    --project-id, 515
    --sudo, 515
    -h, 515
gitlab-project-environment-update command
    line option
    --external-url, 515
    --help, 515
    --id, 515
    --name, 515
    --project-id, 515
    --sudo, 515
    -h, 515
gitlab-project-event command line option
    --help, 515
    -h, 515
gitlab-project-event-list command line
    option
    --action, 516
    --after, 516
    --all, 516
    --before, 516
    --help, 515
    --page, 516
    --per-page, 516
    --project-id, 516
    --sort, 516
    --sudo, 515
    --target-type, 516
    -h, 515
gitlab-project-export command line option
    --help, 516
    -h, 516
gitlab-project-export-create command line
    option
    --description, 516
    --help, 516
    --project-id, 516
    --sudo, 516
    -h, 516
gitlab-project-export-download command line
    option
```

```

--help, 516
--project-id, 516
--sudo, 516
-h, 516
gitlab-project-export-get command line
    option
--help, 517
--project-id, 517
--sudo, 517
-h, 517
gitlab-project-file command line option
--help, 517
-h, 517
gitlab-project-file-blame command line
    option
--file-path, 517
--help, 517
--project-id, 517
--ref, 517
--sudo, 517
-h, 517
gitlab-project-file-create command line
    option
--author-email, 518
--author-name, 518
--branch, 517
--commit-message, 518
--content, 518
--encoding, 518
--file-path, 517
--help, 517
--project-id, 517
--sudo, 517
-h, 517
gitlab-project-file-delete command line
    option
--branch, 518
--commit-message, 518
--file-path, 518
--help, 518
--project-id, 518
--sudo, 518
-h, 518
gitlab-project-file-get command line option
--file-path, 518
--help, 518
--project-id, 518
--ref, 518
--sudo, 518
-h, 518
gitlab-project-file-raw command line option
--file-path, 519
--help, 519
--project-id, 519
--ref, 519
--sudo, 519
-h, 519
gitlab-project-file-update command line
    option
--author-email, 519
--author-name, 519
--branch, 519
--commit-message, 519
--content, 519
--encoding, 519
--file-path, 519
--help, 519
--project-id, 519
--sudo, 519
-h, 519
gitlab-project-fork command line option
--help, 520
-h, 520
gitlab-project-fork-create command line
    option
--help, 520
--namespace, 520
--project-id, 520
--sudo, 520
-h, 520
gitlab-project-fork-list command line
    option
--all, 521
--archived, 520
--help, 520
--membership, 521
--order-by, 520
--owned, 521
--page, 521
--per-page, 521
--project-id, 520
--search, 520
--simple, 520
--sort, 520
--starred, 521
--statistics, 521
--sudo, 520
--visibility, 520
--with-custom-attributes, 521
--with-issues-enabled, 521
--with-merge-requests-enabled, 521
-h, 520
gitlab-project-get command line option
--help, 470
--id, 470
--sudo, 470
-h, 470
gitlab-project-hook command line option

```

```
--help, 521
-h, 521
gitlab-project-hook-create command line
    option
--confidential-issues-events, 522
--enable-ssl-verification, 522
--help, 521
--issues-events, 522
--job-events, 522
--merge-requests-events, 522
--note-events, 522
--pipeline-events, 522
--project-id, 521
--push-events, 521
--sudo, 521
--tag-push-events, 522
--token, 522
--url, 521
--wiki-page-events, 522
-h, 521
gitlab-project-hook-delete command line
    option
--help, 522
--id, 522
--project-id, 522
--sudo, 522
-h, 522
gitlab-project-hook-get command line option
--help, 522
--id, 522
--project-id, 522
--sudo, 522
-h, 522
gitlab-project-hook-list command line
    option
--all, 523
--help, 523
--page, 523
--per-page, 523
--project-id, 523
--sudo, 523
-h, 523
gitlab-project-hook-update command line
    option
--confidential-issues-events, 523
--enable-ssl-verification, 524
--help, 523
--id, 523
--issues-events, 523
--job-events, 524
--merge-requests-events, 523
--note-events, 523
--pipeline-events, 524
--project-id, 523
--push-events, 523
--sudo, 523
--tag-push-events, 523
--token, 524
--url, 523
--wiki-events, 524
-h, 523
gitlab-project-housekeeping command line
    option
--help, 470
--id, 470
-h, 470
gitlab-project-import command line option
--help, 524
-h, 524
gitlab-project-import-get command line
    option
--help, 524
--project-id, 524
--sudo, 524
-h, 524
gitlab-project-issue command line option
--help, 524
-h, 524
gitlab-project-issue-add-spent-time command
    line option
--duration, 525
--help, 524
--iid, 525
--project-id, 524
--sudo, 525
-h, 524
gitlab-project-issue-award-emoji command
    line option
--help, 531
-h, 531
gitlab-project-issue-award-emoji-create
    command line option
--help, 531
--issue-iid, 531
--name, 532
--project-id, 531
--sudo, 531
-h, 531
gitlab-project-issue-award-emoji-delete
    command line option
--help, 532
--id, 532
--issue-iid, 532
--project-id, 532
--sudo, 532
-h, 532
gitlab-project-issue-award-emoji-get
    command line option
```

```

--help, 532
--id, 532
--issue-iid, 532
--project-id, 532
--sudo, 532
-h, 532
gitlab-project-issue-award-emoji-list
    command line option
--all, 533
--help, 532
--issue-iid, 532
--page, 533
--per-page, 533
--project-id, 532
--sudo, 532
-h, 532
gitlab-project-issue-closed-by command line
    option
--help, 525
--iid, 525
--project-id, 525
--sudo, 525
-h, 525
gitlab-project-issue-create command line
    option
--assignee-id, 525
--assignee-ids, 525
--confidential, 525
--created-at, 526
--description, 525
--discussion-to-resolve, 526
--due-date, 526
--help, 525
--labels, 525
--merge-request-to-resolve-discussions-of,
    526
--milestone-id, 525
--project-id, 525
--sudo, 525
--title, 525
-h, 525
gitlab-project-issue-delete command line
    option
--help, 526
--iid, 526
--project-id, 526
--sudo, 526
-h, 526
gitlab-project-issue-discussion command
    line option
--help, 533
-h, 533
gitlab-project-issue-discussion-create
    command line option
--body, 533
--created-at, 533
--help, 533
--issue-iid, 533
--project-id, 533
--sudo, 533
-h, 533
gitlab-project-issue-discussion-get command
    line option
--help, 533
--id, 533
--issue-iid, 533
--project-id, 533
--sudo, 533
-h, 533
gitlab-project-issue-discussion-list
    command line option
--all, 534
--help, 534
--issue-iid, 534
--page, 534
--per-page, 534
--project-id, 534
--sudo, 534
-h, 534
gitlab-project-issue-discussion-note
    command line option
--help, 534
-h, 534
gitlab-project-issue-discussion-note-create
    command line option
--body, 534
--created-at, 534
--discussion-id, 534
--help, 534
--issue-iid, 534
--project-id, 534
--sudo, 534
-h, 534
gitlab-project-issue-discussion-note-delete
    command line option
--discussion-id, 535
--help, 535
--id, 535
--issue-iid, 535
--project-id, 535
--sudo, 535
-h, 535
gitlab-project-issue-discussion-note-get
    command line option
--discussion-id, 535
--help, 535
--id, 535
--issue-iid, 535

```

```
--project-id, 535
--sudo, 535
-h, 535
gitlab-project-issue-discussion-note-update
    command line option
--body, 536
--discussion-id, 536
--help, 535
--id, 536
--issue-iid, 536
--project-id, 536
--sudo, 535
-h, 535
gitlab-project-issue-get command line
    option
--help, 526
--iid, 526
--project-id, 526
--sudo, 526
-h, 526
gitlab-project-issue-link command line
    option
--help, 536
-h, 536
gitlab-project-issue-link-create command
    line option
--help, 536
--issue-iid, 536
--project-id, 536
--sudo, 536
--target-issue-iid, 536
--target-project-id, 536
-h, 536
gitlab-project-issue-link-delete command
    line option
--help, 536
--issue-iid, 536
--issue-link-id, 536
--project-id, 536
--sudo, 536
-h, 536
gitlab-project-issue-link-list command line
    option
--all, 537
--help, 537
--issue-iid, 537
--page, 537
--per-page, 537
--project-id, 537
--sudo, 537
-h, 537
gitlab-project-issue-list command line
    option
--all, 527
--assignee-id, 527
--author-id, 527
--created-after, 527
--created-before, 527
--help, 526
--iids, 527
--labels, 527
--milestone, 527
--my-reaction-emoji, 527
--order-by, 527
--page, 527
--per-page, 527
--project-id, 527
--scope, 527
--search, 527
--sort, 527
--state, 527
--sudo, 527
--updated-after, 527
--updated-before, 527
-h, 526
gitlab-project-issue-move command line
    option
--help, 527
--iid, 527
--project-id, 527
--sudo, 527
--to-project-id, 527
-h, 527
gitlab-project-issue-note command line
    option
--help, 537
-h, 537
gitlab-project-issue-note-award-emoji
    command line option
--help, 539
-h, 539
gitlab-project-issue-note-award-emoji-create
    command line option
--help, 539
--issue-iid, 539
--name, 539
--note-id, 539
--project-id, 539
--sudo, 539
-h, 539
gitlab-project-issue-note-award-emoji-delete
    command line option
--help, 540
--id, 540
--issue-iid, 540
--note-id, 540
--project-id, 540
--sudo, 540
```

```

    -h, 540
gitlab-project-issue-note-award-emoji-get
    command line option
    --help, 540
    --id, 540
    --issue-iid, 540
    --note-id, 540
    --project-id, 540
    --sudo, 540
    -h, 540
gitlab-project-issue-note-award-emoji-list
    command line option
    --all, 541
    --help, 540
    --issue-iid, 541
    --note-id, 541
    --page, 541
    --per-page, 541
    --project-id, 541
    --sudo, 540
    -h, 540
gitlab-project-issue-note-create command
    line option
    --body, 537
    --created-at, 537
    --help, 537
    --issue-iid, 537
    --project-id, 537
    --sudo, 537
    -h, 537
gitlab-project-issue-note-delete command
    line option
    --help, 538
    --id, 538
    --issue-iid, 538
    --project-id, 538
    --sudo, 538
    -h, 538
gitlab-project-issue-note-get command line
    option
    --help, 538
    --id, 538
    --issue-iid, 538
    --project-id, 538
    --sudo, 538
    -h, 538
gitlab-project-issue-note-list command line
    option
    --all, 538
    --help, 538
    --issue-iid, 538
    --page, 538
    --per-page, 538
    --project-id, 538
    --sudo, 538
    -h, 538
gitlab-project-issue-note-update command
    line option
    --body, 539
    --help, 539
    --id, 539
    --issue-iid, 539
    --project-id, 539
    --sudo, 539
    -h, 539
gitlab-project-issue-participants command
    line option
    --help, 528
    --iid, 528
    --project-id, 528
    --sudo, 528
    -h, 528
gitlab-project-issue-related-merge-requests
    command line option
    --help, 528
    --iid, 528
    --project-id, 528
    --sudo, 528
    -h, 528
gitlab-project-issue-reset-spent-time
    command line option
    --help, 528
    --iid, 528
    --project-id, 528
    --sudo, 528
    -h, 528
gitlab-project-issue-reset-time-estimate
    command line option
    --help, 528
    --iid, 529
    --project-id, 528
    --sudo, 528
    -h, 528
gitlab-project-issue-resource-label-event
    command line option
    --help, 541
    -h, 541
gitlab-project-issue-resource-label-event-get
    command line option
    --help, 541
    --id, 541
    --issue-iid, 541
    --project-id, 541
    --sudo, 541
    -h, 541
gitlab-project-issue-resource-label-event-list
    command line option
    --all, 542

```

```
--help, 541
--issue-iid, 542
--page, 542
--per-page, 542
--project-id, 541
--sudo, 541
-h, 541
gitlab-project-issue-resource-milestone-event
    command line option
--help, 542
-h, 542
gitlab-project-issue-resource-milestone-event-get
    command line option
--help, 542
--id, 542
--issue-iid, 542
--project-id, 542
--sudo, 542
-h, 542
gitlab-project-issue-resource-milestone-event-list
    command line option
--all, 543
--help, 542
--issue-iid, 543
--page, 543
--per-page, 543
--project-id, 542
--sudo, 542
-h, 542
gitlab-project-issue-resource-state-event
    command line option
--help, 543
-h, 543
gitlab-project-issue-resource-state-event-get
    command line option
--help, 543
--id, 543
--issue-iid, 543
--project-id, 543
--sudo, 543
-h, 543
gitlab-project-issue-resource-state-event-list
    command line option
--all, 544
--help, 543
--issue-iid, 543
--page, 543
--per-page, 544
--project-id, 543
--sudo, 543
-h, 543
gitlab-project-issue-subscribe command line
    option
--help, 529
--iid, 529
--project-id, 529
--sudo, 529
-h, 529
gitlab-project-issue-time-estimate command
    line option
--duration, 529
--help, 529
--iid, 529
--project-id, 529
--sudo, 529
-h, 529
gitlab-project-issue-time-stats command
    line option
--help, 529
--iid, 529
--project-id, 529
--sudo, 529
-h, 529
gitlab-project-issue-todo command line
    option
--help, 530
--iid, 530
--project-id, 530
--sudo, 530
-h, 530
gitlab-project-issue-unsubscribe command
    line option
--help, 530
--iid, 530
--project-id, 530
--sudo, 530
-h, 530
gitlab-project-issue-update command line
    option
--assignee-id, 531
--assignee-ids, 531
--confidential, 531
--description, 530
--discussion-locked, 531
--due-date, 531
--help, 530
--iid, 530
--labels, 531
--milestone-id, 531
--project-id, 530
--state-event, 531
--sudo, 530
--title, 530
--updated-at, 531
-h, 530
gitlab-project-issue-user-agent-detail
    command line option
--help, 531
```

```

--iid, 531
--project-id, 531
--sudo, 531
-h, 531
gitlab-project-issues-statistics command
    line option
--help, 544
-h, 544
gitlab-project-issues-statistics-get
    command line option
--help, 544
--project-id, 544
--sudo, 544
-h, 544
gitlab-project-job command line option
--help, 544
-h, 544
gitlab-project-job-artifact command line
    option
--help, 544
--id, 544
--project-id, 544
--sudo, 544
-h, 544
gitlab-project-job-artifacts command line
    option
--help, 545
--id, 545
--project-id, 545
--sudo, 545
-h, 545
gitlab-project-job-cancel command line
    option
--help, 545
--id, 545
--project-id, 545
--sudo, 545
-h, 545
gitlab-project-job-delete-artifacts command
    line option
--help, 545
--id, 545
--project-id, 545
--sudo, 545
-h, 545
gitlab-project-job-erase command line
    option
--help, 545
--id, 546
--project-id, 545
--sudo, 545
-h, 545
gitlab-project-job-get command line option
--help, 546
--id, 546
--project-id, 546
--sudo, 546
-h, 546
gitlab-project-job-keep-artifacts command
    line option
--help, 546
--id, 546
--project-id, 546
--sudo, 546
-h, 546
gitlab-project-job-list command line option
--all, 546
--help, 546
--page, 546
--per-page, 546
--project-id, 546
--sudo, 546
-h, 546
gitlab-project-job-play command line option
--help, 547
--id, 547
--project-id, 547
--sudo, 547
-h, 547
gitlab-project-job-retry command line
    option
--help, 547
--id, 547
--project-id, 547
--sudo, 547
-h, 547
gitlab-project-job-trace command line
    option
--help, 547
--id, 547
--project-id, 547
--sudo, 547
-h, 547
gitlab-project-key command line option
--help, 547
-h, 547
gitlab-project-key-create command line
    option
--can-push, 548
--help, 548
--key, 548
--project-id, 548
--sudo, 548
--title, 548
-h, 548
gitlab-project-key-delete command line
    option
--help, 548

```

```
--id, 548
--project-id, 548
--sudo, 548
-h, 548
gitlab-project-key-enable command line
    option
--help, 548
--id, 548
--key-id, 548
--project-id, 548
--sudo, 548
-h, 548
gitlab-project-key-get command line option
--help, 549
--id, 549
--project-id, 549
--sudo, 549
-h, 549
gitlab-project-key-list command line option
--all, 549
--help, 549
--page, 549
--per-page, 549
--project-id, 549
--sudo, 549
-h, 549
gitlab-project-key-update command line
    option
--can-push, 549
--help, 549
--id, 549
--project-id, 549
--sudo, 549
--title, 549
-h, 549
gitlab-project-label command line option
--help, 550
-h, 550
gitlab-project-label-create command line
    option
--color, 550
--description, 550
--help, 550
--name, 550
--priority, 550
--project-id, 550
--sudo, 550
-h, 550
gitlab-project-label-delete command line
    option
--help, 550
--name, 550
--project-id, 550
--sudo, 550
-h, 550
gitlab-project-label-get command line
    option
--help, 551
--name, 551
--project-id, 551
--sudo, 551
-h, 551
gitlab-project-label-list command line
    option
--all, 551
--help, 551
--page, 551
--per-page, 551
--project-id, 551
--sudo, 551
-h, 551
gitlab-project-label-subscribe command line
    option
--help, 551
--name, 551
--project-id, 551
--sudo, 551
-h, 551
gitlab-project-label-unsubscribe command
    line option
--help, 552
--name, 552
--project-id, 552
--sudo, 552
-h, 552
gitlab-project-label-update command line
    option
--color, 552
--description, 552
--help, 552
--name, 552
--new-name, 552
--priority, 552
--project-id, 552
--sudo, 552
-h, 552
gitlab-project-languages command line
    option
--help, 471
--id, 471
-h, 471
gitlab-project-list command line option
--all, 472
--archived, 471
--help, 471
--id-after, 471
--id-before, 471
--last-activity-after, 471
```

```

--last-activity-before, 471
--membership, 471
--min-access-level, 471
--order-by, 471
--owned, 471
--page, 472
--per-page, 472
--repository-checksum-failed, 471
--repository-storage, 471
--search, 472
--search-namespaces, 472
--simple, 472
--sort, 472
--starred, 472
--statistics, 472
--sudo, 471
--topic, 472
--visibility, 472
--wiki-checksum-failed, 472
--with-custom-attributes, 472
--with-issues-enabled, 472
--with-merge-requests-enabled, 472
--with-programming-language, 472
-h, 471
gitlab-project-member command line option
--help, 552
-h, 552
gitlab-project-member-all command line
    option
--help, 554
-h, 554
gitlab-project-member-all-get command line
    option
--help, 554
--id, 555
--project-id, 555
--sudo, 554
-h, 554
gitlab-project-member-all-list command line
    option
--all, 555
--help, 555
--page, 555
--per-page, 555
--project-id, 555
--sudo, 555
-h, 555
gitlab-project-member-create command line
    option
--access-level, 553
--expires-at, 553
--help, 553
--project-id, 553
--sudo, 553
--user-id, 553
-h, 553
gitlab-project-member-delete command line
    option
--help, 553
--id, 553
--project-id, 553
--sudo, 553
-h, 553
gitlab-project-member-get command line
    option
--help, 553
--id, 553
--project-id, 553
--sudo, 553
-h, 553
gitlab-project-member-list command line
    option
--all, 554
--help, 554
--page, 554
--per-page, 554
--project-id, 554
--sudo, 554
-h, 554
gitlab-project-member-update command line
    option
--access-level, 554
--expires-at, 554
--help, 554
--id, 554
--project-id, 554
--sudo, 554
-h, 554
gitlab-project-merge-request command line
    option
--help, 555
-h, 555
gitlab-project-merge-request-add-spent-time
    command line option
--duration, 555
--help, 555
--iid, 555
--project-id, 555
--sudo, 555
-h, 555
gitlab-project-merge-request-approval
    command line option
--help, 565
-h, 565
gitlab-project-merge-request-approval-get
    command line option
--help, 565
--mr-iid, 565

```

```
--project-id, 565
--sudo, 565
-h, 565
gitlab-project-merge-request-approval-rule
    command line option
--help, 565
-h, 565
gitlab-project-merge-request-approval-rule-create
    command line option
--approval-project-rule-id, 566
--approvals-required, 566
--group-ids, 566
--help, 566
--id, 566
--merge-request-iid, 566
--mr-iid, 566
--name, 566
--project-id, 566
--sudo, 566
--user-ids, 566
-h, 566
gitlab-project-merge-request-approval-rule-delete
    command line option
--approval-rule-id, 567
--help, 566
--mr-iid, 566
--project-id, 566
--sudo, 566
-h, 566
gitlab-project-merge-request-approval-rule-list
    command line option
--all, 567
--help, 567
--mr-iid, 567
--name, 567
--page, 567
--per-page, 567
--project-id, 567
--rule-type, 567
--sudo, 567
-h, 567
gitlab-project-merge-request-approval-rule-update
    command line option
--approval-rule-id, 568
--approvals-required, 568
--group-ids, 568
--help, 567
--id, 568
--merge-request-iid, 568
--mr-iid, 568
--name, 568
--project-id, 568
--sudo, 567
--user-ids, 568
-h, 567
gitlab-project-merge-request-approval-state
    command line option
--help, 568
-h, 568
gitlab-project-merge-request-approval-state-get
    command line option
--help, 568
--id, 568
--mr-iid, 568
--project-id, 568
--sudo, 568
-h, 568
gitlab-project-merge-request-approval-update
    command line option
--approvals-required, 565
--help, 565
--mr-iid, 565
--project-id, 565
--sudo, 565
-h, 565
gitlab-project-merge-request-approve
    command line option
--help, 556
--iid, 556
--project-id, 556
--sha, 556
--sudo, 556
-h, 556
gitlab-project-merge-request-award-emoji
    command line option
--help, 568
-h, 568
gitlab-project-merge-request-award-emoji-create
    command line option
--help, 569
--mr-iid, 569
--name, 569
--project-id, 569
--sudo, 569
-h, 569
gitlab-project-merge-request-award-emoji-delete
    command line option
--help, 569
--id, 569
--mr-iid, 569
--project-id, 569
--sudo, 569
-h, 569
gitlab-project-merge-request-award-emoji-get
    command line option
--help, 569
--id, 569
--mr-iid, 569
```

```

--project-id, 569
--sudo, 569
-h, 569
gitlab-project-merge-request-award-emoji-list
    command line option
--all, 570
--help, 570
--mr-iid, 570
--page, 570
--per-page, 570
--project-id, 570
--sudo, 570
-h, 570
gitlab-project-merge-request-cancel-merge-when-pipeline-succeeds
    command line option
--help, 556
--iid, 556
--project-id, 556
--sudo, 556
-h, 556
gitlab-project-merge-request-changes
    command line option
--help, 556
--iid, 556
--project-id, 556
--sudo, 556
-h, 556
gitlab-project-merge-request-closes-issues
    command line option
--help, 557
--iid, 557
--project-id, 557
--sudo, 557
-h, 557
gitlab-project-merge-request-commits
    command line option
--help, 557
--iid, 557
--project-id, 557
--sudo, 557
-h, 557
gitlab-project-merge-request-create command
    line option
--allow-maintainer-to-push, 558
--assignee-id, 558
--description, 558
--help, 557
--labels, 558
--milestone-id, 558
--project-id, 557
--remove-source-branch, 558
--reviewer-ids, 558
--source-branch, 557
--squash, 558
--sudo, 557
--target-branch, 557
--target-project-id, 558
--title, 558
-h, 557
gitlab-project-merge-request-delete command
    line option
--help, 558
--iid, 558
--project-id, 558
--sudo, 558
-h, 558
gitlab-project-merge-request-diff command
    line option
--help, 570
-h, 570
gitlab-project-merge-request-diff-get
    command line option
--help, 570
--id, 570
--mr-iid, 570
--project-id, 570
--sudo, 570
-h, 570
gitlab-project-merge-request-diff-list
    command line option
--all, 571
--help, 571
--mr-iid, 571
--page, 571
--per-page, 571
--project-id, 571
--sudo, 571
-h, 571
gitlab-project-merge-request-discussion
    command line option
--help, 571
-h, 571
gitlab-project-merge-request-discussion-create
    command line option
--body, 571
--created-at, 571
--help, 571
--mr-iid, 571
--position, 571
--project-id, 571
--sudo, 571
-h, 571
gitlab-project-merge-request-discussion-get
    command line option
--help, 572
--id, 572
--mr-iid, 572
--project-id, 572

```

```
--sudo, 572
-h, 572
gitlab-project-merge-request-discussion-list
    command line option
    --all, 572
    --help, 572
    --mr-iid, 572
    --page, 572
    --per-page, 572
    --project-id, 572
    --sudo, 572
    -h, 572
gitlab-project-merge-request-discussion-note
    command line option
    --help, 573
    -h, 573
gitlab-project-merge-request-discussion-note-create-render-html, 558
    command line option
    --body, 573
    --created-at, 573
    --discussion-id, 573
    --help, 573
    --mr-iid, 573
    --project-id, 573
    --sudo, 573
    -h, 573
gitlab-project-merge-request-discussion-note-delete
    command line option
    --discussion-id, 574
    --help, 573
    --id, 574
    --mr-iid, 574
    --project-id, 574
    --sudo, 574
    -h, 573
gitlab-project-merge-request-discussion-note-get
    command line option
    --discussion-id, 574
    --help, 574
    --id, 574
    --mr-iid, 574
    --project-id, 574
    --sudo, 574
    -h, 574
gitlab-project-merge-request-discussion-note-update
    command line option
    --body, 575
    --discussion-id, 574
    --help, 574
    --id, 574
    --mr-iid, 574
    --project-id, 574
    --sudo, 574
    -h, 574
gitlab-project-merge-request-discussion-update
    command line option
    --help, 572
    --id, 573
    --mr-iid, 573
    --project-id, 572
    --resolved, 573
    --sudo, 572
    -h, 572
gitlab-project-merge-request-get command
    line option
    --help, 558
    --iid, 558
    --include-diverged-commits-count, 559
    --include-rebase-in-progress, 559
    --project-id, 558
    --sudo, 558
    -h, 558
gitlab-project-merge-request-list command
    line option
    --all, 560
    --approved-by-ids, 560
    --approver-ids, 560
    --assignee-id, 560
    --author-id, 560
    --created-after, 559
    --created-before, 559
    --help, 559
    --iids, 560
    --labels, 559
    --milestone, 559
    --my-reaction-emoji, 560
    --order-by, 559
    --page, 560
    --per-page, 560
    --project-id, 559
    --scope, 559
    --search, 560
    --sort, 559
    --source-branch, 560
    --state, 559
    --sudo, 559
    --target-branch, 560
    --updated-after, 559
    --updated-before, 559
    --view, 559
    --wip, 560
    -h, 559
gitlab-project-merge-request-merge command
    line option
    --help, 560
    --iid, 560
    --merge-commit-message, 560
```

```

--merge-when-pipeline-succeeds, 560
--project-id, 560
--should-remove-source-branch, 560
--sudo, 560
-h, 560
gitlab-project-merge-request-merge-ref
    command line option
--help, 561
--iid, 561
--project-id, 561
--sudo, 561
-h, 561
gitlab-project-merge-request-note command
    line option
--help, 575
-h, 575
gitlab-project-merge-request-note-award-emoji
    command line option
--help, 577
-h, 577
gitlab-project-merge-request-note-award-emoji-create
    command line option
--help, 577
--mr-iid, 577
--name, 577
--note-id, 577
--project-id, 577
--sudo, 577
-h, 577
gitlab-project-merge-request-note-award-emoji-delete
    command line option
--help, 577
--id, 577
--mr-iid, 577
--note-id, 577
--project-id, 577
--sudo, 577
-h, 577
gitlab-project-merge-request-note-award-emoji-get
    command line option
--help, 578
--id, 578
--mr-iid, 578
--note-id, 578
--project-id, 578
--sudo, 578
-h, 578
gitlab-project-merge-request-note-award-emoji-list
    command line option
--all, 578
--help, 578
--mr-iid, 578
--note-id, 578
--page, 578
--per-page, 578
--project-id, 578
--sudo, 578
-h, 578
gitlab-project-merge-request-note-award-emoji-update
    command line option
--body, 577
--help, 576
--id, 576
--mr-iid, 576
--project-id, 576
--sudo, 576
-h, 576
gitlab-project-merge-request-note-create
    command line option
--body, 575
--help, 575
--mr-iid, 575
--project-id, 575
--sudo, 575
-h, 575
gitlab-project-merge-request-note-delete
    command line option
--help, 575
--id, 575
--mr-iid, 575
--project-id, 575
--sudo, 575
-h, 575
gitlab-project-merge-request-note-get
    command line option
--help, 576
--id, 576
--mr-iid, 576
--project-id, 576
--sudo, 576
-h, 576
gitlab-project-merge-request-note-list
    command line option
--all, 576
--help, 576
--mr-iid, 576
--page, 576
--per-page, 576
--project-id, 576
--sudo, 576
-h, 576
gitlab-project-merge-request-note-participants
    command line option
--help, 561
--iid, 561
--project-id, 561
--sudo, 561
-h, 561

```

```
gitlab-project-merge-request-pipeline
    command line option
    --help, 579
    -h, 579
gitlab-project-merge-request-pipeline-create
    command line option
    --help, 579
    --mr-iid, 579
    --project-id, 579
    --sudo, 579
    -h, 579
gitlab-project-merge-request-pipeline-list
    command line option
    --all, 579
    --help, 579
    --mr-iid, 579
    --page, 579
    --per-page, 579
    --project-id, 579
    --sudo, 579
    -h, 579
gitlab-project-merge-request-rebase
    command line option
    --help, 561
    --iid, 561
    --project-id, 561
    --sudo, 561
    -h, 561
gitlab-project-merge-request-reset-spent-time
    command line option
    --help, 561
    --iid, 562
    --project-id, 561
    --sudo, 561
    -h, 561
gitlab-project-merge-request-reset-time-estimate
    command line option
    --help, 562
    --iid, 562
    --project-id, 562
    --sudo, 562
    -h, 562
gitlab-project-merge-request-resource-label-event
    command line option
    --help, 580
    -h, 580
gitlab-project-merge-request-resource-label-event-get
    command line option
    --help, 580
    --id, 580
    --mr-iid, 580
    --project-id, 580
    --sudo, 580
    -h, 580
gitlab-project-merge-request-resource-label-event-list
    command line option
    --all, 580
    --help, 580
    --mr-iid, 580
    --page, 580
    --per-page, 580
    --project-id, 580
    --sudo, 580
    -h, 580
gitlab-project-merge-request-resource-milestone-event
    command line option
    --help, 581
    -h, 581
gitlab-project-merge-request-resource-milestone-event-get
    command line option
    --help, 581
    --id, 581
    --mr-iid, 581
    --project-id, 581
    --sudo, 581
    -h, 581
gitlab-project-merge-request-resource-milestone-event-list
    command line option
    --all, 581
    --help, 581
    --mr-iid, 581
    --page, 581
    --per-page, 581
    --project-id, 581
    --sudo, 581
    -h, 581
gitlab-project-merge-request-resource-state-event
    command line option
    --help, 582
    -h, 582
gitlab-project-merge-request-resource-state-event-get
    command line option
    --help, 582
    --id, 582
    --mr-iid, 582
    --project-id, 582
    --sudo, 582
    -h, 582
gitlab-project-merge-request-resource-state-event-list
    command line option
    --all, 582
    --help, 582
    --mr-iid, 582
    --page, 582
    --per-page, 582
    --project-id, 582
    --sudo, 582
    -h, 582
```

```

gitlab-project-merge-request-subscribe
    command line option
    --help, 562
    --iid, 562
    --project-id, 562
    --sudo, 562
    -h, 562
gitlab-project-merge-request-time-estimate
    command line option
    --duration, 562
    --help, 562
    --iid, 562
    --project-id, 562
    --sudo, 562
    -h, 562
gitlab-project-merge-request-time-stats
    command line option
    --help, 563
    --iid, 563
    --project-id, 563
    --sudo, 563
    -h, 563
gitlab-project-merge-request-todo command
    line option
    --help, 563
    --iid, 563
    --project-id, 563
    --sudo, 563
    -h, 563
gitlab-project-merge-request-unapprove
    command line option
    --help, 563
    --iid, 563
    --project-id, 563
    --sudo, 563
    -h, 563
gitlab-project-merge-request-unsubscribe
    command line option
    --help, 563
    --iid, 564
    --project-id, 563
    --sudo, 563
    -h, 563
gitlab-project-merge-request-update command
    line option
    --allow-maintainer-to-push, 564
    --assignee-id, 564
    --description, 564
    --discussion-locked, 564
    --help, 564
    --iid, 564
    --labels, 564
    --milestone-id, 564
    --project-id, 564
    --remove-source-branch, 564
    --reviewer-ids, 564
    --squash, 564
    --state-event, 564
    --sudo, 564
    --target-branch, 564
    --title, 564
    -h, 564
gitlab-project-merge-train command line
    option
    --help, 583
    -h, 583
gitlab-project-merge-train-list command
    line option
    --all, 583
    --help, 583
    --page, 583
    --per-page, 583
    --project-id, 583
    --scope, 583
    --sudo, 583
    -h, 583
gitlab-project-milestone command line
    option
    --help, 583
    -h, 583
gitlab-project-milestone-create command
    line option
    --description, 584
    --due-date, 584
    --help, 583
    --project-id, 583
    --start-date, 584
    --state-event, 584
    --sudo, 583
    --title, 584
    -h, 583
gitlab-project-milestone-delete command
    line option
    --help, 584
    --id, 584
    --project-id, 584
    --sudo, 584
    -h, 584
gitlab-project-milestone-get command line
    option
    --help, 584
    --id, 584
    --project-id, 584
    --sudo, 584
    -h, 584
gitlab-project-milestone-issues command
    line option
    --help, 584

```

```
--id, 584
--project-id, 584
--sudo, 584
-h, 584
gitlab-project-milestone-list command line
    option
--all, 585
--help, 585
--iids, 585
--page, 585
--per-page, 585
--project-id, 585
--search, 585
--state, 585
--sudo, 585
-h, 585
gitlab-project-milestone-merge-requests
    command line option
--help, 585
--id, 585
--project-id, 585
--sudo, 585
-h, 585
gitlab-project-milestone-update command
    line option
--description, 586
--due-date, 586
--help, 585
--id, 586
--project-id, 585
--start-date, 586
--state-event, 586
--sudo, 585
--title, 586
-h, 585
gitlab-project-mirror-pull command line
    option
--help, 472
--id, 472
-h, 472
gitlab-project-note command line option
--help, 586
-h, 586
gitlab-project-note-get command line option
--help, 586
--id, 586
--project-id, 586
--sudo, 586
-h, 586
gitlab-project-note-list command line
    option
--all, 586
--help, 586
--page, 586
--per-page, 586
--project-id, 586
--sudo, 586
-h, 586
gitlab-project-notification-settings
    command line option
--help, 587
-h, 587
gitlab-project-notification-settings-get
    command line option
--help, 587
--project-id, 587
--sudo, 587
-h, 587
gitlab-project-notification-settings-update
    command line option
--close-issue, 588
--close-merge-request, 588
--help, 587
--level, 587
--merge-merge-request, 588
--new-issue, 588
--new-merge-request, 588
--new-note, 587
--notification-email, 587
--project-id, 587
--reassign-issue, 588
--reassign-merge-request, 588
--reopen-issue, 588
--reopen-merge-request, 588
--sudo, 587
-h, 587
gitlab-project-package command line option
--help, 588
-h, 588
gitlab-project-package-delete command line
    option
--help, 588
--id, 588
--project-id, 588
--sudo, 588
-h, 588
gitlab-project-package-file command line
    option
--help, 589
-h, 589
gitlab-project-package-file-delete command
    line option
--help, 589
--id, 589
--package-id, 589
--project-id, 589
--sudo, 589
-h, 589
```

```

gitlab-project-package-file-list command
    line option
    --all, 590
    --help, 590
    --package-id, 590
    --page, 590
    --per-page, 590
    --project-id, 590
    --sudo, 590
    -h, 590
gitlab-project-package-get command line
    option
    --help, 588
    --id, 588
    --project-id, 588
    --sudo, 588
    -h, 588
gitlab-project-package-list command line
    option
    --all, 589
    --help, 589
    --order-by, 589
    --package-name, 589
    --package-type, 589
    --page, 589
    --per-page, 589
    --project-id, 589
    --sort, 589
    --sudo, 589
    -h, 589
gitlab-project-pages-domain command line
    option
    --help, 590
    -h, 590
gitlab-project-pages-domain-create command
    line option
    --certificate, 590
    --domain, 590
    --help, 590
    --key, 590
    --project-id, 590
    --sudo, 590
    -h, 590
gitlab-project-pages-domain-delete command
    line option
    --domain, 591
    --help, 591
    --project-id, 591
    --sudo, 591
    -h, 591
gitlab-project-pages-domain-get command
    line option
    --domain, 591
    --help, 591
    --project-id, 591
    --sudo, 591
    -h, 591
gitlab-project-pages-domain-list command
    line option
    --all, 591
    --help, 591
    --page, 591
    --per-page, 591
    --project-id, 591
    --sudo, 591
    -h, 591
gitlab-project-pages-domain-update command
    line option
    --certificate, 592
    --domain, 592
    --help, 592
    --key, 592
    --project-id, 592
    --sudo, 592
    -h, 592
gitlab-project-pipeline command line option
    --help, 592
    -h, 592
gitlab-project-pipeline-bridge command line
    option
    --help, 594
    -h, 594
gitlab-project-pipeline-bridge-list command
    line option
    --all, 595
    --help, 594
    --page, 595
    --per-page, 595
    --pipeline-id, 594
    --project-id, 594
    --scope, 594
    --sudo, 594
    -h, 594
gitlab-project-pipeline-cancel command line
    option
    --help, 592
    --id, 592
    --project-id, 592
    --sudo, 592
    -h, 592
gitlab-project-pipeline-create command line
    option
    --help, 592
    --project-id, 592
    --ref, 592
    --sudo, 592
    -h, 592

```

gitlab-project-pipeline-delete command line option
--help, 593
--id, 593
--project-id, 593
--sudo, 593
-h, 593

gitlab-project-pipeline-get command line option
--help, 593
--id, 593
--project-id, 593
--sudo, 593
-h, 593

gitlab-project-pipeline-job command line option
--help, 595
-h, 595

gitlab-project-pipeline-job-list command line option
--all, 595
--help, 595
--include-retried, 595
--page, 595
--per-page, 595
--pipeline-id, 595
--project-id, 595
--scope, 595
--sudo, 595
-h, 595

gitlab-project-pipeline-list command line option
--all, 594
--help, 593
--name, 594
--order-by, 594
--page, 594
--per-page, 594
--project-id, 593
--ref, 593
--scope, 593
--sha, 593
--sort, 594
--status, 593
--sudo, 593
--username, 594
--yaml-errors, 593
-h, 593

gitlab-project-pipeline-retry command line option
--help, 594
--id, 594
--project-id, 594
--sudo, 594
-h, 594

gitlab-project-pipeline-schedule command line option
--help, 595
-h, 595

gitlab-project-pipeline-schedule-create command line option
--active, 596
--cron, 596
--cron-timezone, 596
--description, 596
--help, 596
--project-id, 596
--ref, 596
--sudo, 596
-h, 596

gitlab-project-pipeline-schedule-delete command line option
--help, 596
--id, 596
--project-id, 596
--sudo, 596
-h, 596

gitlab-project-pipeline-schedule-get command line option
--help, 596
--id, 596
--project-id, 596
--sudo, 596
-h, 596

gitlab-project-pipeline-schedule-list command line option
--all, 597
--help, 597
--page, 597
--per-page, 597
--project-id, 597
--sudo, 597
-h, 597

gitlab-project-pipeline-schedule-play command line option
--help, 597
--id, 597
--project-id, 597
--sudo, 597
-h, 597

gitlab-project-pipeline-schedule-take-ownership command line option
--help, 597
--id, 597
--project-id, 597
--sudo, 597
-h, 597

```

gitlab-project-pipeline-schedule-update
    command line option
    --active, 598
    --cron, 598
    --cron-timezone, 598
    --description, 598
    --help, 598
    --id, 598
    --project-id, 598
    --ref, 598
    --sudo, 598
    -h, 598
gitlab-project-pipeline-schedule-variable
    command line option
    --help, 598
    -h, 598
gitlab-project-pipeline-schedule-variable-create
    command line option
    --help, 598
    --key, 599
    --pipeline-schedule-id, 598
    --project-id, 598
    --sudo, 598
    --value, 599
    -h, 598
gitlab-project-pipeline-schedule-variable-delete
    command line option
    --help, 599
    --key, 599
    --pipeline-schedule-id, 599
    --project-id, 599
    --sudo, 599
    -h, 599
gitlab-project-pipeline-schedule-variable-update
    command line option
    --help, 599
    --key, 599
    --pipeline-schedule-id, 599
    --project-id, 599
    --sudo, 599
    --value, 599
    -h, 599
gitlab-project-pipeline-test-report command
    line option
    --help, 600
    -h, 600
gitlab-project-pipeline-test-report-get
    command line option
    --help, 600
    --pipeline-id, 600
    --project-id, 600
    --sudo, 600
    -h, 600
gitlab-project-pipeline-test-report-summary
    command line option
    --help, 600
    -h, 600
gitlab-project-pipeline-test-report-summary-get
    command line option
    --help, 600
    --pipeline-id, 600
    --project-id, 600
    --sudo, 600
    -h, 600
gitlab-project-pipeline-variable command
    line option
    --help, 601
    -h, 601
gitlab-project-pipeline-variable-list
    command line option
    --all, 601
    --help, 601
    --page, 601
    --per-page, 601
    --pipeline-id, 601
    --project-id, 601
    --sudo, 601
    -h, 601
gitlab-project-protected-branch command
    line option
    --help, 601
    -h, 601
gitlab-project-protected-branch-create
    command line option
    --allowed-to-merge, 602
    --allowed-to-push, 602
    --allowed-to-unprotect, 602
    --code-owner-approval-required, 602
    --help, 601
    --merge-access-level, 602
    --name, 602
    --project-id, 602
    --push-access-level, 602
    --sudo, 602
    --unprotect-access-level, 602
    -h, 601
gitlab-project-protected-branch-delete
    command line option
    --help, 602
    --name, 602
    --project-id, 602
    --sudo, 602
    -h, 602
gitlab-project-protected-branch-get command
    line option
    --help, 602
    --name, 602

```

```
--project-id, 602
--sudo, 602
-h, 602
gitlab-project-protected-branch-list
    command line option
--all, 603
--help, 603
--page, 603
--per-page, 603
--project-id, 603
--sudo, 603
-h, 603
gitlab-project-protected-tag command line
    option
--help, 603
-h, 603
gitlab-project-protected-tag-create command
    line option
--create-access-level, 603
--help, 603
--name, 603
--project-id, 603
--sudo, 603
-h, 603
gitlab-project-protected-tag-delete command
    line option
--help, 603
--name, 604
--project-id, 603
--sudo, 603
-h, 603
gitlab-project-protected-tag-get command
    line option
--help, 604
--name, 604
--project-id, 604
--sudo, 604
-h, 604
gitlab-project-protected-tag-list command
    line option
--all, 604
--help, 604
--page, 604
--per-page, 604
--project-id, 604
--sudo, 604
-h, 604
gitlab-project-push-rules command line
    option
--help, 604
-h, 604
gitlab-project-push-rules-create command
    line option
--author-email-regex, 605
--branch-name-regex, 605
--commit-message-regex, 605
--deny-delete-tag, 605
--file-name-regex, 605
--help, 605
--max-file-size, 605
--member-check, 605
--prevent-secrets, 605
--project-id, 605
--sudo, 605
-h, 605
gitlab-project-push-rules-delete command
    line option
--help, 605
--project-id, 605
--sudo, 605
-h, 605
gitlab-project-push-rules-get command line
    option
--help, 606
--project-id, 606
--sudo, 606
-h, 606
gitlab-project-push-rules-update command
    line option
--author-email-regex, 606
--branch-name-regex, 606
--commit-message-regex, 606
--deny-delete-tag, 606
--file-name-regex, 606
--help, 606
--max-file-size, 606
--member-check, 606
--prevent-secrets, 606
--project-id, 606
--sudo, 606
-h, 606
gitlab-project-registry-repository command
    line option
--help, 607
-h, 607
gitlab-project-registry-repository-delete
    command line option
--help, 607
--id, 607
--project-id, 607
--sudo, 607
-h, 607
gitlab-project-registry-repository-list
    command line option
--all, 607
--help, 607
--page, 607
--per-page, 607
```

```

--project-id, 607
--sudo, 607
-h, 607
gitlab-project-registry-tag command line
    option
--help, 607
-h, 607
gitlab-project-registry-tag-delete command
    line option
--help, 608
--name, 608
--project-id, 608
--repository-id, 608
--sudo, 608
-h, 608
gitlab-project-registry-tag-delete-in-bulk
    command line option
--help, 608
--keep-n, 608
--name, 608
--name-regex-delete, 608
--name-regex-keep, 608
--older-than, 608
--project-id, 608
--repository-id, 608
--sudo, 608
-h, 608
gitlab-project-registry-tag-get command
    line option
--help, 609
--name, 609
--project-id, 609
--repository-id, 609
--sudo, 609
-h, 609
gitlab-project-registry-tag-list command
    line option
--all, 609
--help, 609
--page, 609
--per-page, 609
--project-id, 609
--repository-id, 609
--sudo, 609
-h, 609
gitlab-project-release command line option
--help, 609
-h, 609
gitlab-project-release-create command line
    option
--assets, 610
--description, 610
--help, 610
--name, 610
--project-id, 610
--ref, 610
--sudo, 610
--tag-name, 610
-h, 610
gitlab-project-release-delete command line
    option
--help, 610
--project-id, 610
--sudo, 610
--tag-name, 610
-h, 610
gitlab-project-release-get command line
    option
--help, 610
--project-id, 610
--sudo, 610
--tag-name, 610
-h, 610
gitlab-project-release-link command line
    option
--help, 611
-h, 611
gitlab-project-release-link-create command
    line option
--filepath, 612
--help, 612
--link-type, 612
--name, 612
--project-id, 612
--sudo, 612
--tag-name, 612
--url, 612
-h, 612
gitlab-project-release-link-delete command
    line option
--help, 612
--id, 612
--project-id, 612
--sudo, 612
--tag-name, 612
-h, 612
gitlab-project-release-link-get command
    line option
--help, 612
--id, 613
--project-id, 612
--sudo, 612
--tag-name, 612
-h, 612
gitlab-project-release-link-list command
    line option
--all, 613
--help, 613

```

```
--page, 613
--per-page, 613
--project-id, 613
--sudo, 613
--tag-name, 613
-h, 613
gitlab-project-release-link-update command
    line option
--filepath, 613
--help, 613
--id, 613
--link-type, 613
--name, 613
--project-id, 613
--sudo, 613
--tag-name, 613
--url, 613
-h, 613
gitlab-project-release-list command line
    option
--all, 611
--help, 611
--page, 611
--per-page, 611
--project-id, 611
--sudo, 611
-h, 611
gitlab-project-release-update command line
    option
--description, 611
--help, 611
--milestones, 611
--name, 611
--project-id, 611
--released-at, 611
--sudo, 611
--tag-name, 611
-h, 611
gitlab-project-remote-mirror command line
    option
--help, 614
-h, 614
gitlab-project-remote-mirror-create command
    line option
--enabled, 614
--help, 614
--only-protected-branches, 614
--project-id, 614
--sudo, 614
--url, 614
-h, 614
gitlab-project-remote-mirror-list command
    line option
--all, 614
--help, 614
--page, 614
--per-page, 614
--project-id, 614
--sudo, 614
-h, 614
gitlab-project-remote-mirror-update command
    line option
--enabled, 615
--help, 615
--id, 615
--only-protected-branches, 615
--project-id, 615
--sudo, 615
-h, 615
gitlab-project-repository-archive command
    line option
--format, 472
--help, 472
--id, 472
--sha, 472
-h, 472
gitlab-project-repository-blob command line
    option
--help, 473
--id, 473
--sha, 473
-h, 473
gitlab-project-repository-compare command
    line option
--from-, 473
--help, 473
--id, 473
--to, 473
-h, 473
gitlab-project-repository-contributors
    command line option
--help, 473
--id, 473
-h, 473
gitlab-project-repository-raw-blob command
    line option
--help, 473
--id, 473
--sha, 473
-h, 473
gitlab-project-repository-tree command line
    option
--help, 474
--id, 474
--path, 474
--recursive, 474
--ref, 474
-h, 474
```

```

gitlab-project-runner command line option
  --help, 615
  -h, 615
gitlab-project-runner-create command line
  option
  --help, 615
  --project-id, 615
  --runner-id, 615
  --sudo, 615
  -h, 615
gitlab-project-runner-delete command line
  option
  --help, 615
  --id, 616
  --project-id, 615
  --sudo, 615
  -h, 615
gitlab-project-runner-list command line
  option
  --all, 616
  --help, 616
  --page, 616
  --per-page, 616
  --project-id, 616
  --scope, 616
  --sudo, 616
  --tag-list, 616
  -h, 616
gitlab-project-search command line option
  --help, 474
  --id, 474
  --scope, 474
  --search, 474
  -h, 474
gitlab-project-service command line option
  --help, 616
  -h, 616
gitlab-project-service-available command
  line option
  --help, 616
  --project-id, 616
  --slug, 616
  --sudo, 616
  -h, 616
gitlab-project-service-delete command line
  option
  --help, 617
  --project-id, 617
  --slug, 617
  --sudo, 617
  -h, 617
gitlab-project-service-get command line
  option
  --help, 617
  --project-id, 617
  --slug, 617
  --sudo, 617
  -h, 617
gitlab-project-service-list command line
  option
  --all, 617
  --help, 617
  --page, 617
  --per-page, 617
  --project-id, 617
  --sudo, 617
  -h, 617
gitlab-project-service-update command line
  option
  --help, 618
  --project-id, 618
  --slug, 618
  --sudo, 618
  -h, 618
gitlab-project-share command line option
  --expires-at, 474
  --group-access, 474
  --group-id, 474
  --help, 474
  --id, 474
  -h, 474
gitlab-project-snapshot command line option
  --help, 475
  --id, 475
  --wiki, 475
  -h, 475
gitlab-project-snippet command line option
  --help, 618
  -h, 618
gitlab-project-snippet-award-emoji command
  line option
  --help, 620
  -h, 620
gitlab-project-snippet-award-emoji-create
  command line option
  --help, 621
  --name, 621
  --project-id, 621
  --snippet-id, 621
  --sudo, 621
  -h, 621
gitlab-project-snippet-award-emoji-delete
  command line option
  --help, 621
  --id, 621
  --project-id, 621
  --snippet-id, 621
  --sudo, 621

```

```
-h, 621
gitlab-project-snippet-award-emoji-get
    command line option
    --help, 621
    --id, 621
    --project-id, 621
    --snippet-id, 621
    --sudo, 621
    -h, 621
gitlab-project-snippet-award-emoji-list
    command line option
    --all, 622
    --help, 622
    --page, 622
    --per-page, 622
    --project-id, 622
    --snippet-id, 622
    --sudo, 622
    -h, 622
gitlab-project-snippet-content command line
    option
    --help, 618
    --id, 618
    --project-id, 618
    --sudo, 618
    -h, 618
gitlab-project-snippet-create command line
    option
    --content, 619
    --description, 619
    --file-name, 619
    --help, 618
    --project-id, 618
    --sudo, 618
    --title, 618
    --visibility, 619
    -h, 618
gitlab-project-snippet-delete command line
    option
    --help, 619
    --id, 619
    --project-id, 619
    --sudo, 619
    -h, 619
gitlab-project-snippet-discussion command
    line option
    --help, 622
    -h, 622
gitlab-project-snippet-discussion-create
    command line option
    --body, 622
    --created-at, 622
    --help, 622
    --project-id, 622
    --snippet-id, 622
    --sudo, 622
    -h, 622
gitlab-project-snippet-discussion-get
    command line option
    --help, 623
    --id, 623
    --project-id, 623
    --snippet-id, 623
    --sudo, 623
    -h, 623
gitlab-project-snippet-discussion-list
    command line option
    --all, 623
    --help, 623
    --page, 623
    --per-page, 623
    --project-id, 623
    --snippet-id, 623
    --sudo, 623
    -h, 623
gitlab-project-snippet-discussion-note
    command line option
    --help, 623
    -h, 623
gitlab-project-snippet-discussion-note-create
    command line option
    --body, 624
    --created-at, 624
    --discussion-id, 624
    --help, 624
    --project-id, 624
    --snippet-id, 624
    --sudo, 624
    -h, 624
gitlab-project-snippet-discussion-note-delete
    command line option
    --discussion-id, 624
    --help, 624
    --id, 624
    --project-id, 624
    --snippet-id, 624
    --sudo, 624
    -h, 624
gitlab-project-snippet-discussion-note-get
    command line option
    --discussion-id, 625
    --help, 624
    --id, 625
    --project-id, 625
    --snippet-id, 625
    --sudo, 625
    -h, 624
```

```

gitlab-project-snippet-discussion-note-update
    command line option
    --body, 625
    --discussion-id, 625
    --help, 625
    --id, 625
    --project-id, 625
    --snippet-id, 625
    --sudo, 625
    -h, 625
gitlab-project-snippet-get command line
    option
    --help, 619
    --id, 619
    --project-id, 619
    --sudo, 619
    -h, 619
gitlab-project-snippet-list command line
    option
    --all, 619
    --help, 619
    --page, 619
    --per-page, 619
    --project-id, 619
    --sudo, 619
    -h, 619
gitlab-project-snippet-note command line
    option
    --help, 625
    -h, 625
gitlab-project-snippet-note-award-emoji
    command line option
    --help, 627
    -h, 627
gitlab-project-snippet-note-award-emoji-create
    command line option
    --help, 627
    --name, 628
    --note-id, 628
    --project-id, 627
    --snippet-id, 628
    --sudo, 627
    -h, 627
gitlab-project-snippet-note-award-emoji-delete
    command line option
    --help, 628
    --id, 628
    --note-id, 628
    --project-id, 628
    --snippet-id, 628
    --sudo, 628
    -h, 628
gitlab-project-snippet-note-award-emoji-get
    command line option
    --help, 628
    --id, 628
    --note-id, 628
    --project-id, 628
    --snippet-id, 628
    --sudo, 628
    -h, 628
gitlab-project-snippet-note-award-emoji-list
    command line option
    --all, 629
    --help, 629
    --note-id, 629
    --page, 629
    --per-page, 629
    --project-id, 629
    --snippet-id, 629
    --sudo, 629
    -h, 629
gitlab-project-snippet-note-create command
    line option
    --body, 626
    --help, 625
    --project-id, 626
    --snippet-id, 626
    --sudo, 625
    -h, 625
gitlab-project-snippet-note-delete command
    line option
    --help, 626
    --id, 626
    --project-id, 626
    --snippet-id, 626
    --sudo, 626
    -h, 626
gitlab-project-snippet-note-get command
    line option
    --help, 626
    --id, 626
    --project-id, 626
    --snippet-id, 626
    --sudo, 626
    -h, 626
gitlab-project-snippet-note-list command
    line option
    --all, 627
    --help, 626
    --page, 627
    --per-page, 627
    --project-id, 627
    --snippet-id, 627
    --sudo, 626
    -h, 626
gitlab-project-snippet-note-update command
    line option

```

```
--body, 627
--help, 627
--id, 627
--project-id, 627
--snippet-id, 627
--sudo, 627
-h, 627
gitlab-project-snippet-update command line
  option
--content, 620
--description, 620
--file-name, 620
--help, 620
--id, 620
--project-id, 620
--sudo, 620
--title, 620
--visibility, 620
-h, 620
gitlab-project-snippet-user-agent-detail
  command line option
--help, 620
--id, 620
--project-id, 620
--sudo, 620
-h, 620
gitlab-project-star command line option
--help, 475
--id, 475
-h, 475
gitlab-project-storage command line option
--help, 629
-h, 629
gitlab-project-storage-get command line
  option
--help, 629
--id, 629
--project-id, 629
--sudo, 629
-h, 629
gitlab-project-tag command line option
--help, 630
-h, 630
gitlab-project-tag-create command line
  option
--help, 630
--message, 630
--project-id, 630
--ref, 630
--sudo, 630
--tag-name, 630
-h, 630
gitlab-project-tag-delete command line
  option
--help, 630
--name, 630
--project-id, 630
--sudo, 630
-h, 630
gitlab-project-tag-get command line option
--help, 630
--name, 630
--project-id, 630
--sudo, 630
-h, 630
gitlab-project-tag-list command line option
--all, 631
--help, 631
--page, 631
--per-page, 631
--project-id, 631
--sudo, 631
-h, 631
gitlab-project-transfer command line option
--help, 475
--id, 475
--to-namespace, 475
-h, 475
gitlab-project-transfer-project command
  line option
--help, 475
--id, 475
--to-namespace, 475
-h, 475
gitlab-project-trigger command line option
--help, 631
-h, 631
gitlab-project-trigger-create command line
  option
--description, 631
--help, 631
--project-id, 631
--sudo, 631
-h, 631
gitlab-project-trigger-delete command line
  option
--help, 631
--id, 631
--project-id, 631
--sudo, 631
-h, 631
gitlab-project-trigger-get command line
  option
--help, 632
--id, 632
--project-id, 632
--sudo, 632
-h, 632
```

gitlab-project-trigger-list command line option

- all, 632
- help, 632
- page, 632
- per-page, 632
- project-id, 632
- sudo, 632
- h, 632

gitlab-project-trigger-pipeline command line option

- help, 476
- id, 476
- ref, 476
- token, 476
- h, 476

gitlab-project-trigger-update command line option

- description, 632
- help, 632
- id, 632
- project-id, 632
- sudo, 632
- h, 632

gitlab-project-unarchive command line option

- help, 476
- id, 476
- h, 476

gitlab-project-unshare command line option

- group-id, 476
- help, 476
- id, 476
- h, 476

gitlab-project-unstar command line option

- help, 476
- id, 476
- h, 476

gitlab-project-update command line option

- allow-merge-on-skipped-pipeline, 478
- analytics-access-level, 478
- approvals-before-merge, 478
- auto-cancel-pending-pipelines, 478
- auto-devops-deploy-strategy, 478
- auto-devops-enabled, 478
- autoclose-referenced-issues, 478
- avatar, 478
- build-coverage-regex, 478
- build-git-strategy, 478
- build-timeout, 478
- builds-access-level, 478
- ci-config-path, 478
- ci-default-git-depth, 478
- ci-forward-deployment-enabled, 479

- container-expiration-policy-attributes, 479
- container-registry-enabled, 479
- default-branch, 479
- description, 479
- emails-disabled, 479
- external-authorization-classification-label, 479
- forking-access-level, 479
- help, 478
- id, 478
- import-url, 479
- issues-access-level, 479
- issues-enabled, 479
- issues-template, 480
- jobs-enabled, 479
- lfs-enabled, 479
- merge-method, 479
- merge-requests-access-level, 479
- merge-requests-enabled, 479
- merge-requests-template, 480
- mirror, 479
- mirror-overwrites-diverged-branches, 479
- mirror-trigger-builds, 479
- mirror-user-id, 479
- name, 479
- only-allow-merge-if-all-discussions-are-resolved, 479
- only-allow-merge-if-pipeline-succeeds, 479
- only-mirror-protected-branches, 479
- operations-access-level, 479
- packages-enabled, 479
- pages-access-level, 479
- path, 479
- public-builds, 479
- remove-source-branch-after-merge, 480
- repository-access-level, 480
- repository-storage, 480
- request-access-enabled, 480
- requirements-access-level, 479
- resolve-outdated-diff-discussions, 480
- restrict-user-defined-variables, 479
- service-desk-enabled, 480
- shared-runners-enabled, 480
- show-default-award-emojis, 480
- snippets-access-level, 480
- snippets-enabled, 480
- squash-option, 480
- sudo, 478
- suggestion-commit-message, 480
- tag-list, 480
- visibility, 480

```
--wiki-access-level, 480
--wiki-enabled, 480
-h, 478
gitlab-project-update-submodule command
  line option
  --branch, 480
  --commit-sha, 480
  --help, 480
  --id, 480
  --submodule, 480
  -h, 480
gitlab-project-upload command line option
  --filename, 481
  --filepath, 481
  --help, 481
  --id, 481
  -h, 481
gitlab-project-user command line option
  --help, 633
  -h, 633
gitlab-project-user-list command line
  option
  --all, 633
  --help, 633
  --page, 633
  --per-page, 633
  --project-id, 633
  --search, 633
  --skip-users, 633
  --sudo, 633
  -h, 633
gitlab-project-variable command line option
  --help, 633
  -h, 633
gitlab-project-variable-create command line
  option
  --environment-scope, 634
  --help, 633
  --key, 634
  --masked, 634
  --project-id, 633
  --protected, 634
  --sudo, 633
  --value, 634
  --variable-type, 634
  -h, 633
gitlab-project-variable-delete command line
  option
  --help, 634
  --key, 634
  --project-id, 634
  --sudo, 634
  -h, 634
gitlab-project-variable-get command line
  option
  --help, 634
  --key, 634
  --project-id, 634
  --sudo, 634
  -h, 634
gitlab-project-variable-list command line
  option
  --all, 635
  --help, 634
  --page, 635
  --per-page, 635
  --project-id, 634
  --sudo, 634
  -h, 634
gitlab-project-variable-update command line
  option
  --environment-scope, 635
  --help, 635
  --key, 635
  --masked, 635
  --project-id, 635
  --protected, 635
  --sudo, 635
  --value, 635
  --variable-type, 635
  -h, 635
gitlab-project-wiki command line option
  --help, 635
  -h, 635
gitlab-project-wiki-create command line
  option
  --content, 636
  --format, 636
  --help, 635
  --project-id, 636
  --sudo, 635
  --title, 636
  -h, 635
gitlab-project-wiki-delete command line
  option
  --help, 636
  --project-id, 636
  --slug, 636
  --sudo, 636
  -h, 636
gitlab-project-wiki-get command line option
  --help, 636
  --project-id, 636
  --slug, 636
  --sudo, 636
  -h, 636
```

gitlab-project-wiki-list command line option

- all, 637
- help, 636
- page, 636
- per-page, 637
- project-id, 636
- sudo, 636
- with-content, 636
- h, 636

gitlab-project-wiki-update command line option

- content, 637
- format, 637
- help, 637
- project-id, 637
- slug, 637
- sudo, 637
- title, 637
- h, 637

gitlab-runner command line option

- help, 637
- h, 637

gitlab-runner-all command line option

- help, 637
- id, 637
- scope, 637
- h, 637

gitlab-runner-create command line option

- access-level, 638
- active, 638
- description, 638
- help, 638
- info, 638
- locked, 638
- maximum-timeout, 638
- run-untagged, 638
- sudo, 638
- tag-list, 638
- token, 638
- h, 638

gitlab-runner-delete command line option

- help, 638
- id, 638
- sudo, 638
- h, 638

gitlab-runner-get command line option

- help, 638
- id, 638
- sudo, 638
- h, 638

gitlab-runner-job command line option

- help, 640
- h, 640

gitlab-runner-job-list command line option

- all, 640
- help, 640
- page, 640
- per-page, 640
- runner-id, 640
- status, 640
- sudo, 640
- h, 640

gitlab-runner-list command line option

- all, 639
- help, 639
- page, 639
- per-page, 639
- scope, 639
- sudo, 639
- tag-list, 639
- h, 639

gitlab-runner-update command line option

- access-level, 639
- active, 639
- description, 639
- help, 639
- id, 639
- locked, 639
- maximum-timeout, 639
- run-untagged, 639
- sudo, 639
- tag-list, 639
- h, 639

gitlab-runner-verify command line option

- help, 640
- id, 640
- token, 640
- h, 640

gitlab-snippet command line option

- help, 640
- h, 640

gitlab-snippet-content command line option

- help, 641
- id, 641
- h, 641

gitlab-snippet-create command line option

- content, 641
- file-name, 641
- help, 641
- lifetime, 641
- sudo, 641
- title, 641
- visibility, 641
- h, 641

gitlab-snippet-delete command line option

- help, 641
- id, 641

```
--sudo, 641
-h, 641
gitlab-snippet-get command line option
--help, 641
--id, 641
--sudo, 641
-h, 641
gitlab-snippet-list command line option
--all, 642
--help, 642
--page, 642
--per-page, 642
--sudo, 642
-h, 642
gitlab-snippet-public command line option
--help, 642
--id, 642
-h, 642
gitlab-snippet-update command line option
--content, 642
--file-name, 642
--help, 642
--id, 642
--sudo, 642
--title, 642
--visibility, 642
-h, 642
gitlab-snippet-user-agent-detail command
line option
--help, 643
--id, 643
-h, 643
gitlab-starred-project command line option
--help, 643
-h, 643
gitlab-starred-project-list command line
option
--all, 644
--archived, 643
--help, 643
--membership, 643
--min-access-level, 643
--order-by, 643
--owned, 643
--page, 644
--per-page, 644
--search, 643
--simple, 643
--sort, 643
--starred, 644
--statistics, 644
--sudo, 643
--user-id, 643
--visibility, 644
--with-custom-attributes, 644
--with-issues-enabled, 644
--with-merge-requests-enabled, 644
-h, 643
gitlab-todo command line option
--help, 644
-h, 644
gitlab-todo-delete command line option
--help, 644
--id, 644
--sudo, 644
-h, 644
gitlab-todo-list command line option
--action, 644
--all, 645
--author-id, 644
--help, 644
--page, 645
--per-page, 645
--project-id, 644
--state, 645
--sudo, 644
--type, 645
-h, 644
gitlab-todo-mark-all-as-done command line
option
--help, 645
--id, 645
-h, 645
gitlab-todo-mark-as-done command line
option
--help, 645
--id, 645
-h, 645
gitlab-topic command line option
--help, 645
-h, 645
gitlab-topic-create command line option
--avatar, 645
--description, 645
--help, 645
--name, 645
--sudo, 645
-h, 645
gitlab-topic-delete command line option
--help, 646
--id, 646
--sudo, 646
-h, 646
gitlab-topic-get command line option
--help, 646
--id, 646
--sudo, 646
-h, 646
```

gitlab-topic-list command line option

- all, 646
- help, 646
- page, 646
- per-page, 646
- sudo, 646
- h, 646

gitlab-topic-update command line option

- avatar, 646
- description, 646
- help, 646
- id, 646
- name, 647
- sudo, 646
- h, 646

gitlab-user command line option

- help, 647
- h, 647

gitlab-user-activate command line option

- help, 647
- id, 647
- h, 647

gitlab-user-activities command line option

- help, 652
- h, 652

gitlab-user-activities-list command line option

- all, 652
- help, 652
- page, 652
- per-page, 652
- sudo, 652
- h, 652

gitlab-user-block command line option

- help, 647
- id, 647
- h, 647

gitlab-user-create command line option

- admin, 648
- avatar, 648
- bio, 648
- can-create-group, 648
- color-scheme-id, 648
- email, 648
- extern-uid, 648
- external, 648
- help, 648
- linkedin, 648
- location, 648
- name, 648
- organization, 648
- password, 648
- private-profile, 648
- projects-limit, 648

- provider, 648
- public-email, 648
- reset-password, 648
- skip-confirmation, 648
- skype, 648
- sudo, 648
- theme-id, 648
- twitter, 648
- username, 648
- website-url, 648
- h, 648

gitlab-user-custom-attribute command line option

- help, 652
- h, 652

gitlab-user-custom-attribute-delete command line option

- help, 653
- key, 653
- sudo, 653
- user-id, 653
- h, 653

gitlab-user-custom-attribute-get command line option

- help, 653
- key, 653
- sudo, 653
- user-id, 653
- h, 653

gitlab-user-custom-attribute-list command line option

- all, 653
- help, 653
- page, 653
- per-page, 653
- sudo, 653
- user-id, 653
- h, 653

gitlab-user-deactivate command line option

- help, 649
- id, 649
- h, 649

gitlab-user-delete command line option

- help, 649
- id, 649
- sudo, 649
- h, 649

gitlab-user-email command line option

- help, 654
- h, 654

gitlab-user-email-create command line option

- email, 654
- help, 654

```
--sudo, 654
--user-id, 654
-h, 654
gitlab-user-email-delete command line
    option
--help, 654
--id, 654
--sudo, 654
--user-id, 654
-h, 654
gitlab-user-email-get command line option
--help, 654
--id, 654
--sudo, 654
--user-id, 654
-h, 654
gitlab-user-email-list command line option
--all, 655
--help, 655
--page, 655
--per-page, 655
--sudo, 655
--user-id, 655
-h, 655
gitlab-user-event command line option
--help, 655
-h, 655
gitlab-user-event-list command line option
--action, 655
--after, 655
--all, 655
--before, 655
--help, 655
--page, 655
--per-page, 655
--sort, 655
--sudo, 655
--target-type, 655
--user-id, 655
-h, 655
gitlab-user-follow command line option
--help, 649
--id, 649
-h, 649
gitlab-user-get command line option
--help, 649
--id, 649
--sudo, 649
-h, 649
gitlab-user-gpg-key command line option
--help, 656
-h, 656
gitlab-user-gpg-key-create command line
    option
--help, 656
--key, 656
--sudo, 656
--user-id, 656
-h, 656
gitlab-user-gpg-key-delete command line
    option
--help, 656
--id, 656
--sudo, 656
--user-id, 656
-h, 656
gitlab-user-gpg-key-get command line option
--help, 656
--id, 656
--sudo, 656
--user-id, 656
-h, 656
gitlab-user-gpg-key-list command line
    option
--all, 657
--help, 657
--page, 657
--per-page, 657
--sudo, 657
--user-id, 657
-h, 657
gitlab-user-impersonation-token command
    line option
--help, 657
-h, 657
gitlab-user-impersonation-token-create
    command line option
--expires-at, 657
--help, 657
--name, 657
--scopes, 657
--sudo, 657
--user-id, 657
-h, 657
gitlab-user-impersonation-token-delete
    command line option
--help, 658
--id, 658
--sudo, 658
--user-id, 658
-h, 658
gitlab-user-impersonation-token-get command
    line option
--help, 658
--id, 658
--sudo, 658
--user-id, 658
-h, 658
```

```

gitlab-user-impersonation-token-list
    command line option
    --all, 658
    --help, 658
    --page, 658
    --per-page, 658
    --state, 658
    --sudo, 658
    --user-id, 658
    -h, 658
gitlab-user-key command line option
    --help, 659
    -h, 659
gitlab-user-key-create command line option
    --help, 659
    --key, 659
    --sudo, 659
    --title, 659
    --user-id, 659
    -h, 659
gitlab-user-key-delete command line option
    --help, 659
    --id, 659
    --sudo, 659
    --user-id, 659
    -h, 659
gitlab-user-key-get command line option
    --help, 659
    --id, 659
    --sudo, 659
    --user-id, 659
    -h, 659
gitlab-user-key-list command line option
    --all, 660
    --help, 660
    --page, 660
    --per-page, 660
    --sudo, 660
    --user-id, 660
    -h, 660
gitlab-user-list command line option
    --active, 650
    --all, 650
    --blocked, 650
    --custom-attributes, 650
    --extern-uid, 650
    --external, 650
    --help, 649
    --page, 650
    --per-page, 650
    --provider, 650
    --search, 650
    --status, 650
    --sudo, 650
    --two-factor, 650
    --username, 650
    -h, 649
gitlab-user-membership command line option
    --help, 660
    -h, 660
gitlab-user-membership-get command line
    option
    --help, 660
    --source-id, 660
    --sudo, 660
    --user-id, 660
    -h, 660
gitlab-user-membership-list command line
    option
    --all, 661
    --help, 660
    --page, 661
    --per-page, 661
    --sudo, 660
    --type, 660
    --user-id, 660
    -h, 660
gitlab-user-personal-access-token command
    line option
    --help, 661
    -h, 661
gitlab-user-personal-access-token-create
    command line option
    --expires-at, 661
    --help, 661
    --name, 661
    --scopes, 661
    --sudo, 661
    --user-id, 661
    -h, 661
gitlab-user-project command line option
    --help, 661
    -h, 661
gitlab-user-project-create command line
    option
    --builds-enabled, 662
    --default-branch, 662
    --description, 662
    --help, 662
    --import-url, 662
    --issues-enabled, 662
    --merge-requests-enabled, 662
    --name, 662
    --only-allow-merge-if-build-succeeds, 662
    --public, 662
    --public-builds, 662
    --snippets-enabled, 662
    --squash-option, 662

```

```
--sudo, 662
--user-id, 662
--visibility, 662
--wall-enabled, 662
--wiki-enabled, 662
-h, 662
gitlab-user-project-list command line
    option
--all, 664
--archived, 663
--help, 663
--id-after, 663
--id-before, 663
--membership, 663
--min-access-level, 663
--order-by, 663
--owned, 663
--page, 663
--per-page, 663
--repository-checksum-failed, 663
--search, 663
--simple, 663
--sort, 663
--starred, 663
--statistics, 663
--sudo, 663
--user-id, 663
--visibility, 663
--wiki-checksum-failed, 663
--with-custom-attributes, 663
--with-issues-enabled, 663
--with-merge-requests-enabled, 663
--with-programming-language, 663
-h, 663
gitlab-user-status command line option
--help, 664
-h, 664
gitlab-user-status-get command line option
--help, 664
--sudo, 664
--user-id, 664
-h, 664
gitlab-user-unblock command line option
--help, 650
--id, 650
-h, 650
gitlab-user-unfollow command line option
--help, 650
--id, 650
-h, 650
gitlab-user-update command line option
--admin, 651
--avatar, 652
--bio, 651
--can-create-group, 651
--color-scheme-id, 652
--email, 651
--extern-uid, 651
--external, 651
--help, 651
--id, 651
--linkedin, 651
--location, 652
--name, 651
--organization, 651
--password, 651
--private-profile, 652
--projects-limit, 651
--provider, 651
--public-email, 652
--skip-reconfirmation, 651
--skype, 651
--sudo, 651
--theme-id, 652
--twitter, 651
--username, 651
--website-url, 651
-h, 651
gitlab-variable command line option
--help, 664
-h, 664
gitlab-variable-create command line option
--help, 664
--key, 664
--masked, 664
--protected, 664
--sudo, 664
--value, 664
--variable-type, 664
-h, 664
gitlab-variable-delete command line option
--help, 665
--key, 665
--sudo, 665
-h, 665
gitlab-variable-get command line option
--help, 665
--key, 665
--sudo, 665
-h, 665
gitlab-variable-list command line option
--all, 665
--help, 665
--page, 665
--per-page, 665
--sudo, 665
-h, 665
gitlab-variable-update command line option
```

- `--help`, 665
- `--key`, 665
- `--masked`, 666
- `--protected`, 666
- `--sudo`, 665
- `--value`, 665
- `--variable-type`, 666
- `-h`, 665
- `GitlabActivateError`, 350
- `GitlabAttachFileError`, 351
- `GitlabAuthenticationError`, 351
- `GitlabBlockError`, 351
- `GitlabBuildCancelError`, 351
- `GitlabBuildEraseError`, 351
- `GitlabBuildPlayError`, 352
- `GitlabBuildRetryError`, 352
- `GitlabCancelError`, 352
- `GitlabCherryPickError`, 352
- `Gitlabciyaml` (*class in gitlab.v4.objects*), 160
- `GitlabciyamlManager` (*class in gitlab.v4.objects*), 160
- `gitlabciyaml` (*gitlab.Gitlab attribute*), 136
- `GitlabConfigHelperError`, 350
- `GitlabConfigMissingError`, 350
- `GitlabConfigParser` (*class in gitlab.config*), 350
- `GitlabConnectionError`, 353
- `GitlabCreateError`, 353
- `GitlabDataError`, 350
- `GitlabDeactivateError`, 353
- `GitlabDeleteError`, 353
- `GitlabError`, 354
- `GitlabFollowError`, 354
- `GitlabGetError`, 354
- `GitlabGroupTransferError`, 354
- `GitlabHousekeepingError`, 354
- `GitlabHttpError`, 355
- `GitlabIDError`, 350
- `GitlabImportError`, 355
- `GitlabJobCancelError`, 355
- `GitlabJobEraseError`, 355
- `GitlabJobPlayError`, 356
- `GitlabJobRetryError`, 356
- `GitlabLicenseError`, 356
- `GitlabList` (*class in gitlab*), 142
- `GitlabListError`, 356
- `GitlabMarkdownError`, 358
- `GitlabMRApprovalError`, 357
- `GitlabMRClosedError`, 357
- `GitlabMRForbiddenError`, 357
- `GitlabMROnBuildSuccessError`, 357
- `GitlabMRRebaseError`, 357
- `GitlabOperationError`, 358
- `GitlabOwnershipError`, 358
- `GitlabParsingError`, 358
- `GitlabPipelineCancelError`, 359
- `GitlabPipelinePlayError`, 359
- `GitlabPipelineRetryError`, 359
- `GitlabProjectDeployKeyError`, 359
- `GitlabPromoteError`, 360
- `GitlabProtectError`, 360
- `GitlabRenderError`, 360
- `GitlabRepairError`, 360
- `GitlabRetryError`, 360
- `GitlabRevertError`, 361
- `GitlabSearchError`, 361
- `GitlabSetError`, 361
- `GitlabStopError`, 361
- `GitlabSubscribeError`, 362
- `GitlabTimeTrackingError`, 362
- `GitlabTodoError`, 362
- `GitlabTransferProjectError`, 362
- `GitlabUnblockError`, 363
- `GitlabUnfollowError`, 363
- `GitlabUnsubscribeError`, 363
- `GitlabUpdateError`, 363
- `GitlabUploadError`, 363
- `GitlabVerifyError`, 364
- `gpgkeys` (*gitlab.v4.objects.CurrentUser attribute*), 148
- `gpgkeys` (*gitlab.v4.objects.User attribute*), 334
- `Group` (*class in gitlab.v4.objects*), 161
- `GroupAccessRequest` (*class in gitlab.v4.objects*), 165
- `GroupAccessRequestManager` (*class in gitlab.v4.objects*), 165
- `GroupAccessToken` (*class in gitlab.v4.objects*), 165
- `GroupAccessTokenManager` (*class in gitlab.v4.objects*), 165
- `GroupAuditEvent` (*class in gitlab.v4.objects*), 166
- `GroupAuditEventManager` (*class in gitlab.v4.objects*), 166
- `GroupBadge` (*class in gitlab.v4.objects*), 167
- `GroupBadgeManager` (*class in gitlab.v4.objects*), 167
- `GroupBillableMember` (*class in gitlab.v4.objects*), 167
- `GroupBillableMemberManager` (*class in gitlab.v4.objects*), 168
- `GroupBillableMemberMembership` (*class in gitlab.v4.objects*), 168
- `GroupBillableMemberMembershipManager` (*class in gitlab.v4.objects*), 168
- `GroupBoard` (*class in gitlab.v4.objects*), 169
- `GroupBoardList` (*class in gitlab.v4.objects*), 169
- `GroupBoardListManager` (*class in gitlab.v4.objects*), 169
- `GroupBoardManager` (*class in gitlab.v4.objects*), 170
- `GroupCluster` (*class in gitlab.v4.objects*), 170
- `GroupClusterManager` (*class in gitlab.v4.objects*), 171
- `GroupCustomAttribute` (*class in gitlab.v4.objects*), 172
- `GroupCustomAttributeManager` (*class in gitlab.v4.objects*), 172

- `GroupDeployToken` (class in `gitlab.v4.objects`), 172
`GroupDeployTokenManager` (class in `gitlab.v4.objects`), 173
`GroupDescendantGroup` (class in `gitlab.v4.objects`), 173
`GroupDescendantGroupManager` (class in `gitlab.v4.objects`), 174
`GroupEpic` (class in `gitlab.v4.objects`), 174
`GroupEpicAwardEmoji` (class in `gitlab.v4.objects`), 174
`GroupEpicAwardEmojiManager` (class in `gitlab.v4.objects`), 175
`GroupEpicDiscussionNote` (class in `gitlab.v4.objects`), 175
`GroupEpicDiscussionNoteManager` (class in `gitlab.v4.objects`), 176
`GroupEpicIssue` (class in `gitlab.v4.objects`), 176
`GroupEpicIssueManager` (class in `gitlab.v4.objects`), 177
`GroupEpicManager` (class in `gitlab.v4.objects`), 177
`GroupEpicNote` (class in `gitlab.v4.objects`), 178
`GroupEpicNoteAwardEmoji` (class in `gitlab.v4.objects`), 179
`GroupEpicNoteAwardEmojiManager` (class in `gitlab.v4.objects`), 179
`GroupEpicNoteManager` (class in `gitlab.v4.objects`), 179
`GroupEpicResourceLabelEvent` (class in `gitlab.v4.objects`), 180
`GroupEpicResourceLabelEventManager` (class in `gitlab.v4.objects`), 180
`GroupExport` (class in `gitlab.v4.objects`), 181
`GroupExportManager` (class in `gitlab.v4.objects`), 181
`GroupHook` (class in `gitlab.v4.objects`), 182
`GroupHookManager` (class in `gitlab.v4.objects`), 182
`GroupImport` (class in `gitlab.v4.objects`), 183
`GroupImportManager` (class in `gitlab.v4.objects`), 183
`GroupIssue` (class in `gitlab.v4.objects`), 184
`GroupIssueManager` (class in `gitlab.v4.objects`), 184
`GroupIssuesStatistics` (class in `gitlab.v4.objects`), 184
`GroupIssuesStatisticsManager` (class in `gitlab.v4.objects`), 185
`GroupLabel` (class in `gitlab.v4.objects`), 185
`GroupLabelManager` (class in `gitlab.v4.objects`), 186
`GroupManager` (class in `gitlab.v4.objects`), 187
`GroupMember` (class in `gitlab.v4.objects`), 188
`GroupMemberAll` (class in `gitlab.v4.objects`), 188
`GroupMemberAllManager` (class in `gitlab.v4.objects`), 189
`GroupMemberManager` (class in `gitlab.v4.objects`), 189
`GroupMergeRequest` (class in `gitlab.v4.objects`), 190
`GroupMergeRequestManager` (class in `gitlab.v4.objects`), 190
`GroupMilestone` (class in `gitlab.v4.objects`), 191
`GroupMilestoneManager` (class in `gitlab.v4.objects`), 192
`GroupNotificationSettings` (class in `gitlab.v4.objects`), 193
`GroupNotificationSettingsManager` (class in `gitlab.v4.objects`), 193
`GroupPackage` (class in `gitlab.v4.objects`), 194
`GroupPackageManager` (class in `gitlab.v4.objects`), 194
`GroupProject` (class in `gitlab.v4.objects`), 194
`GroupProjectManager` (class in `gitlab.v4.objects`), 194
`GroupRunner` (class in `gitlab.v4.objects`), 195
`GroupRunnerManager` (class in `gitlab.v4.objects`), 195
`groups` (`gitlab.Gitlab` attribute), 136
`groups` (`gitlab.v4.objects.Project` attribute), 210
`GroupSubgroup` (class in `gitlab.v4.objects`), 196
`GroupSubgroupManager` (class in `gitlab.v4.objects`), 196
`GroupVariable` (class in `gitlab.v4.objects`), 197
`GroupVariableManager` (class in `gitlab.v4.objects`), 197
`GroupWiki` (class in `gitlab.v4.objects`), 197
`GroupWikiManager` (class in `gitlab.v4.objects`), 198
- ## H
- `headers` (`gitlab.Gitlab` attribute), 136
`Hook` (class in `gitlab.v4.objects`), 198
`HookManager` (class in `gitlab.v4.objects`), 199
`hooks` (`gitlab.Gitlab` attribute), 136
`hooks` (`gitlab.v4.objects.Group` attribute), 162
`hooks` (`gitlab.v4.objects.Project` attribute), 210
`housekeeping()` (`gitlab.v4.objects.Project` method), 210
`http_delete()` (`gitlab.Gitlab` method), 136
`http_get()` (`gitlab.Gitlab` method), 136
`http_list()` (`gitlab.Gitlab` method), 137
`http_post()` (`gitlab.Gitlab` method), 137
`http_put()` (`gitlab.Gitlab` method), 138
`http_request()` (`gitlab.Gitlab` method), 138
- ## I
- `id` (`gitlab.v4.objects.ProjectMergeRequestApprovalRule` attribute), 275
`identityproviders` (`gitlab.v4.objects.User` attribute), 334
`impersonationtokens` (`gitlab.v4.objects.User` attribute), 334
`import_bitbucket_server()` (`gitlab.v4.objects.ProjectManager` method), 266
`import_github()` (`gitlab.v4.objects.ProjectManager` method), 267
`import_group()` (`gitlab.v4.objects.GroupManager` method), 188

`import_project()` (*gitlab.v4.objects.ProjectManager* method), 268

`imports` (*gitlab.v4.objects.Group* attribute), 162

`imports` (*gitlab.v4.objects.Project* attribute), 211

`Issue` (class in *gitlab.v4.objects*), 199

`IssueManager` (class in *gitlab.v4.objects*), 199

`issues` (*gitlab.Gitlab* attribute), 139

`issues` (*gitlab.v4.objects.Group* attribute), 162

`issues` (*gitlab.v4.objects.GroupEpic* attribute), 174

`issues` (*gitlab.v4.objects.Project* attribute), 211

`issues()` (*gitlab.v4.objects.GroupMilestone* method), 191

`issues()` (*gitlab.v4.objects.ProjectMilestone* method), 289

`issues_statistics` (*gitlab.Gitlab* attribute), 139

`issues_statistics` (*gitlab.v4.objects.Group* attribute), 162

`issues_statistics` (*gitlab.v4.objects.Project* attribute), 211

`IssuesStatistics` (class in *gitlab.v4.objects*), 201

`IssuesStatisticsManager` (class in *gitlab.v4.objects*), 201

J

`job_stats()` (*gitlab.v4.objects.SidekiqManager* method), 327

`jobs` (*gitlab.v4.objects.Project* attribute), 211

`jobs` (*gitlab.v4.objects.ProjectPipeline* attribute), 295

`jobs` (*gitlab.v4.objects.Runner* attribute), 324

K

`keep_artifacts()` (*gitlab.v4.objects.ProjectJob* method), 260

`Key` (class in *gitlab.v4.objects*), 201

`KeyManager` (class in *gitlab.v4.objects*), 202

`keys` (*gitlab.Gitlab* attribute), 139

`keys` (*gitlab.v4.objects.CurrentUser* attribute), 148

`keys` (*gitlab.v4.objects.Project* attribute), 211

`keys` (*gitlab.v4.objects.User* attribute), 334

L

`labels` (*gitlab.v4.objects.Group* attribute), 162

`labels` (*gitlab.v4.objects.Project* attribute), 211

`languages()` (*gitlab.v4.objects.Project* method), 211

`ldap_sync()` (*gitlab.v4.objects.Group* method), 162

`LDAPGroup` (class in *gitlab.v4.objects*), 202

`LDAPGroupManager` (class in *gitlab.v4.objects*), 202

`ldapgroups` (*gitlab.Gitlab* attribute), 139

`License` (class in *gitlab.v4.objects*), 203

`LicenseManager` (class in *gitlab.v4.objects*), 203

`licenses` (*gitlab.Gitlab* attribute), 139

`links` (*gitlab.v4.objects.ProjectIssue* attribute), 248

`links` (*gitlab.v4.objects.ProjectRelease* attribute), 306

`lint()` (*gitlab.Gitlab* method), 139

`list()` (*gitlab.mixins.ListMixin* method), 368

`list()` (*gitlab.v4.objects.LDAPGroupManager* method), 203

`list()` (*gitlab.v4.objects.UserProjectManager* method), 345

`ListMixin` (class in *gitlab.mixins*), 368

`lists` (*gitlab.v4.objects.GroupBoard* attribute), 169

`lists` (*gitlab.v4.objects.ProjectBoard* attribute), 224

M

`main()` (in module *gitlab.cli*), 349

`manager` (*gitlab.base.RESTObject* attribute), 348

`manager` (*gitlab.mixins.AccessRequestMixin* attribute), 365

`manager` (*gitlab.mixins.DownloadMixin* attribute), 367

`manager` (*gitlab.mixins.ObjectDeleteMixin* attribute), 368

`manager` (*gitlab.mixins.ParticipantsMixin* attribute), 369

`manager` (*gitlab.mixins.RefreshMixin* attribute), 369

`manager` (*gitlab.mixins.SaveMixin* attribute), 370

`manager` (*gitlab.mixins.SubscribableMixin* attribute), 370

`manager` (*gitlab.mixins.TimeTrackingMixin* attribute), 371

`manager` (*gitlab.mixins.TODOMixin* attribute), 372

`manager` (*gitlab.mixins.UserAgentDetailMixin* attribute), 373

`manager` (*gitlab.v4.objects.Application* attribute), 143

`manager` (*gitlab.v4.objects.ApplicationAppearance* attribute), 143

`manager` (*gitlab.v4.objects.ApplicationSettings* attribute), 145

`manager` (*gitlab.v4.objects.AuditEvent* attribute), 146

`manager` (*gitlab.v4.objects.BroadcastMessage* attribute), 147

`manager` (*gitlab.v4.objects.CurrentUserEmail* attribute), 148

`manager` (*gitlab.v4.objects.CurrentUserGPGKey* attribute), 149

`manager` (*gitlab.v4.objects.CurrentUserKey* attribute), 150

`manager` (*gitlab.v4.objects.CurrentUserStatus* attribute), 152

`manager` (*gitlab.v4.objects.DeployKey* attribute), 152

`manager` (*gitlab.v4.objects.DeployToken* attribute), 153

`manager` (*gitlab.v4.objects.Dockerfile* attribute), 153

`manager` (*gitlab.v4.objects.Event* attribute), 154

`manager` (*gitlab.v4.objects.Feature* attribute), 155

`manager` (*gitlab.v4.objects.GenericPackage* attribute), 156

`manager` (*gitlab.v4.objects.GeoNode* attribute), 157

`manager` (*gitlab.v4.objects.Gitignore* attribute), 159

`manager` (*gitlab.v4.objects.Gitlabciyaml* attribute), 160

- manager (*gitlab.v4.objects.GroupAccessRequest* attribute), 165
- manager (*gitlab.v4.objects.GroupAccessToken* attribute), 165
- manager (*gitlab.v4.objects.GroupAuditEvent* attribute), 166
- manager (*gitlab.v4.objects.GroupBadge* attribute), 167
- manager (*gitlab.v4.objects.GroupBillableMemberMemberships* attribute), 168
- manager (*gitlab.v4.objects.GroupBoardList* attribute), 169
- manager (*gitlab.v4.objects.GroupCluster* attribute), 171
- manager (*gitlab.v4.objects.GroupCustomAttribute* attribute), 172
- manager (*gitlab.v4.objects.GroupDeployToken* attribute), 173
- manager (*gitlab.v4.objects.GroupDescendantGroup* attribute), 174
- manager (*gitlab.v4.objects.GroupEpicAwardEmoji* attribute), 175
- manager (*gitlab.v4.objects.GroupEpicDiscussionNote* attribute), 176
- manager (*gitlab.v4.objects.GroupEpicIssue* attribute), 176
- manager (*gitlab.v4.objects.GroupEpicNoteAwardEmoji* attribute), 179
- manager (*gitlab.v4.objects.GroupEpicResourceLabelEvent* attribute), 180
- manager (*gitlab.v4.objects.GroupExport* attribute), 181
- manager (*gitlab.v4.objects.GroupHook* attribute), 182
- manager (*gitlab.v4.objects.GroupImport* attribute), 183
- manager (*gitlab.v4.objects.GroupIssue* attribute), 184
- manager (*gitlab.v4.objects.GroupIssuesStatistics* attribute), 185
- manager (*gitlab.v4.objects.GroupLabel* attribute), 186
- manager (*gitlab.v4.objects.GroupMember* attribute), 188
- manager (*gitlab.v4.objects.GroupMemberAll* attribute), 189
- manager (*gitlab.v4.objects.GroupMergeRequest* attribute), 190
- manager (*gitlab.v4.objects.GroupMilestone* attribute), 191
- manager (*gitlab.v4.objects.GroupNotificationSettings* attribute), 193
- manager (*gitlab.v4.objects.GroupPackage* attribute), 194
- manager (*gitlab.v4.objects.GroupProject* attribute), 194
- manager (*gitlab.v4.objects.GroupRunner* attribute), 195
- manager (*gitlab.v4.objects.GroupSubgroup* attribute), 196
- manager (*gitlab.v4.objects.GroupVariable* attribute), 197
- manager (*gitlab.v4.objects.GroupWiki* attribute), 198
- manager (*gitlab.v4.objects.Hook* attribute), 199
- manager (*gitlab.v4.objects.Issue* attribute), 199
- manager (*gitlab.v4.objects.IssuesStatistics* attribute), 201
- manager (*gitlab.v4.objects.Key* attribute), 202
- manager (*gitlab.v4.objects.LDAPGroup* attribute), 202
- manager (*gitlab.v4.objects.License* attribute), 203
- manager (*gitlab.v4.objects.MergeRequest* attribute), 204
- manager (*gitlab.v4.objects.Namespace* attribute), 206
- manager (*gitlab.v4.objects.NotificationSettings* attribute), 207
- manager (*gitlab.v4.objects.PagesDomain* attribute), 208
- manager (*gitlab.v4.objects.PersonalAccessToken* attribute), 208
- manager (*gitlab.v4.objects.ProjectAccessRequest* attribute), 216
- manager (*gitlab.v4.objects.ProjectAccessToken* attribute), 217
- manager (*gitlab.v4.objects.ProjectAdditionalStatistics* attribute), 217
- manager (*gitlab.v4.objects.ProjectApproval* attribute), 218
- manager (*gitlab.v4.objects.ProjectApprovalRule* attribute), 219
- manager (*gitlab.v4.objects.ProjectArtifact* attribute), 220
- manager (*gitlab.v4.objects.ProjectAudit* attribute), 221
- manager (*gitlab.v4.objects.ProjectAuditEvent* attribute), 222
- manager (*gitlab.v4.objects.ProjectBadge* attribute), 223
- manager (*gitlab.v4.objects.ProjectBoardList* attribute), 224
- manager (*gitlab.v4.objects.ProjectBranch* attribute), 226
- manager (*gitlab.v4.objects.ProjectCluster* attribute), 226
- manager (*gitlab.v4.objects.ProjectCommitComment* attribute), 230
- manager (*gitlab.v4.objects.ProjectCommitDiscussionNote* attribute), 231
- manager (*gitlab.v4.objects.ProjectCommitStatus* attribute), 233
- manager (*gitlab.v4.objects.ProjectCustomAttribute* attribute), 234
- manager (*gitlab.v4.objects.ProjectDeploymentMergeRequest* attribute), 237
- manager (*gitlab.v4.objects.ProjectDeployToken* attribute), 235
- manager (*gitlab.v4.objects.ProjectEnvironment* attribute), 238
- manager (*gitlab.v4.objects.ProjectEvent* attribute), 240
- manager (*gitlab.v4.objects.ProjectExport* attribute), 240
- manager (*gitlab.v4.objects.ProjectFile* attribute), 241
- manager (*gitlab.v4.objects.ProjectFork* attribute), 245
- manager (*gitlab.v4.objects.ProjectHook* attribute), 246
- manager (*gitlab.v4.objects.ProjectImport* attribute), 247
- manager (*gitlab.v4.objects.ProjectIssueAwardEmoji* attribute), 249
- manager (*gitlab.v4.objects.ProjectIssueDiscussionNote* attribute), 251
- manager (*gitlab.v4.objects.ProjectIssueLink* attribute),

- 252
- manager (gitlab.v4.objects.ProjectIssueNoteAwardEmoji attribute), 254
- manager (gitlab.v4.objects.ProjectIssueResourceLabelEventManager attribute), 255
- manager (gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager attribute), 256
- manager (gitlab.v4.objects.ProjectIssueResourceStateEventManager attribute), 257
- manager (gitlab.v4.objects.ProjectIssuesStatistics attribute), 258
- manager (gitlab.v4.objects.ProjectJob attribute), 261
- manager (gitlab.v4.objects.ProjectKey attribute), 262
- manager (gitlab.v4.objects.ProjectLabel attribute), 264
- manager (gitlab.v4.objects.ProjectMember attribute), 269
- manager (gitlab.v4.objects.ProjectMemberAll attribute), 269
- manager (gitlab.v4.objects.ProjectMergeRequestApproval attribute), 274
- manager (gitlab.v4.objects.ProjectMergeRequestApprovalSummary attribute), 277
- manager (gitlab.v4.objects.ProjectMergeRequestAwardEmoji attribute), 278
- manager (gitlab.v4.objects.ProjectMergeRequestDiff attribute), 278
- manager (gitlab.v4.objects.ProjectMergeRequestDiscussionNote attribute), 280
- manager (gitlab.v4.objects.ProjectMergeRequestNoteAwardEmoji attribute), 283
- manager (gitlab.v4.objects.ProjectMergeRequestPipeline attribute), 285
- manager (gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager attribute), 285
- manager (gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager attribute), 286
- manager (gitlab.v4.objects.ProjectMergeRequestResourceSummary attribute), 287
- manager (gitlab.v4.objects.ProjectMergeTrain attribute), 288
- manager (gitlab.v4.objects.ProjectMilestone attribute), 289
- manager (gitlab.v4.objects.ProjectNote attribute), 290
- manager (gitlab.v4.objects.ProjectNotificationSettings attribute), 291
- manager (gitlab.v4.objects.ProjectPackageFile attribute), 292
- manager (gitlab.v4.objects.ProjectPagesDomain attribute), 294
- manager (gitlab.v4.objects.ProjectPipelineBridge attribute), 295
- manager (gitlab.v4.objects.ProjectPipelineJob attribute), 296
- manager (gitlab.v4.objects.ProjectPipelineScheduleVariable attribute), 299
- manager (gitlab.v4.objects.ProjectPipelineTestReport attribute), 300
- manager (gitlab.v4.objects.ProjectPipelineTestReportSummary attribute), 301
- manager (gitlab.v4.objects.ProjectPipelineVariable attribute), 301
- manager (gitlab.v4.objects.ProjectProtectedBranch attribute), 302
- manager (gitlab.v4.objects.ProjectProtectedTag attribute), 303
- manager (gitlab.v4.objects.ProjectPushRules attribute), 304
- manager (gitlab.v4.objects.ProjectRegistryTag attribute), 305
- manager (gitlab.v4.objects.ProjectReleaseLink attribute), 307
- manager (gitlab.v4.objects.ProjectRemoteMirror attribute), 308
- manager (gitlab.v4.objects.ProjectRunner attribute), 309
- manager (gitlab.v4.objects.ProjectService attribute), 309
- manager (gitlab.v4.objects.ProjectSnippetAwardEmoji attribute), 311
- manager (gitlab.v4.objects.ProjectSnippetDiscussionNote attribute), 313
- manager (gitlab.v4.objects.ProjectSnippetNoteAwardEmoji attribute), 315
- manager (gitlab.v4.objects.ProjectStorage attribute), 316
- manager (gitlab.v4.objects.ProjectTag attribute), 317
- manager (gitlab.v4.objects.ProjectTrigger attribute), 318
- manager (gitlab.v4.objects.ProjectUser attribute), 319
- manager (gitlab.v4.objects.ProjectVariable attribute), 319
- manager (gitlab.v4.objects.ProjectWiki attribute), 320
- manager (gitlab.v4.objects.RunnerJob attribute), 325
- manager (gitlab.v4.objects.Snippet attribute), 329
- manager (gitlab.v4.objects.StarredProject attribute), 330
- manager (gitlab.v4.objects.TODO attribute), 331
- manager (gitlab.v4.objects.Topic attribute), 332
- manager (gitlab.v4.objects.UserActivities attribute), 335
- manager (gitlab.v4.objects.UserCustomAttribute attribute), 336
- manager (gitlab.v4.objects.UserEmail attribute), 337
- manager (gitlab.v4.objects.UserEvent attribute), 337
- manager (gitlab.v4.objects.UserGPGKey attribute), 338
- manager (gitlab.v4.objects.UserImpersonationToken attribute), 339
- manager (gitlab.v4.objects.UserKey attribute), 340
- manager (gitlab.v4.objects.UserMembership attribute), 342
- manager (gitlab.v4.objects.UserPersonalAccessToken attribute), 343
- manager (gitlab.v4.objects.UserProject attribute), 344
- manager (gitlab.v4.objects.UserStatus attribute), 345

`manager` (*gitlab.v4.objects.Variable* attribute), 346
`mark_all_as_done()` (*gitlab.v4.objects.TODOManager* method), 331
`mark_as_done()` (*gitlab.v4.objects.TODO* method), 331
`markdown()` (*gitlab.Gitlab* method), 139
`members` (*gitlab.v4.objects.Group* attribute), 163
`members` (*gitlab.v4.objects.Project* attribute), 211
`members_all` (*gitlab.v4.objects.Group* attribute), 163
`members_all` (*gitlab.v4.objects.Project* attribute), 211
`memberships` (*gitlab.v4.objects.GroupBillableMember* attribute), 168
`memberships` (*gitlab.v4.objects.User* attribute), 334
`merge()` (*gitlab.v4.objects.ProjectMergeRequest* method), 273
`merge_config()` (*gitlab.Gitlab* class method), 140
`merge_ref()` (*gitlab.v4.objects.ProjectMergeRequest* method), 273
`merge_requests()` (*gitlab.v4.objects.GroupMilestone* method), 192
`merge_requests()` (*gitlab.v4.objects.ProjectCommit* method), 228
`merge_requests()` (*gitlab.v4.objects.ProjectMilestone* method), 289
`merge_trains` (*gitlab.v4.objects.Project* attribute), 211
`MergeRequest` (class in *gitlab.v4.objects*), 204
`MergeRequestManager` (class in *gitlab.v4.objects*), 204
`mergerequests` (*gitlab.Gitlab* attribute), 140
`mergerequests` (*gitlab.v4.objects.Group* attribute), 163
`mergerequests` (*gitlab.v4.objects.Project* attribute), 211
`mergerequests` (*gitlab.v4.objects.ProjectDeployment* attribute), 236
`milestones` (*gitlab.v4.objects.Group* attribute), 163
`milestones` (*gitlab.v4.objects.Project* attribute), 211
`mirror_pull()` (*gitlab.v4.objects.Project* method), 211
`module`
 gitlab, 134
 gitlab.base, 347
 gitlab.cli, 349
 gitlab.config, 350
 gitlab.const, 350
 gitlab.exceptions, 350
 gitlab.mixins, 365
 gitlab.utils, 374
 gitlab.v4, 347
 gitlab.v4.objects, 143
`move()` (*gitlab.v4.objects.ProjectIssue* method), 248

N

`Namespace` (class in *gitlab.v4.objects*), 206
`NamespaceManager` (class in *gitlab.v4.objects*), 206
`namespaces` (*gitlab.Gitlab* attribute), 140
`next()` (*gitlab.base.RESTObjectList* method), 348
`next()` (*gitlab.GitlabList* method), 142
`next_page` (*gitlab.base.RESTObjectList* property), 348

`next_page` (*gitlab.GitlabList* property), 142
`notes` (*gitlab.v4.objects.Project* attribute), 212
`notes` (*gitlab.v4.objects.ProjectCommitDiscussion* attribute), 230
`notes` (*gitlab.v4.objects.ProjectIssue* attribute), 248
`notes` (*gitlab.v4.objects.ProjectIssueDiscussion* attribute), 250
`notes` (*gitlab.v4.objects.ProjectMergeRequest* attribute), 273
`notes` (*gitlab.v4.objects.ProjectMergeRequestDiscussion* attribute), 279
`notes` (*gitlab.v4.objects.ProjectSnippet* attribute), 311
`notes` (*gitlab.v4.objects.ProjectSnippetDiscussion* attribute), 312
`NotificationSettings` (class in *gitlab.v4.objects*), 206
`notificationsettings` (*gitlab.Gitlab* attribute), 140
`notificationsettings` (*gitlab.v4.objects.Group* attribute), 163
`notificationsettings` (*gitlab.v4.objects.Project* attribute), 212
`NotificationSettingsManager` (class in *gitlab.v4.objects*), 207
`NoUpdateMixin` (class in *gitlab.mixins*), 368

O

`ObjectDeleteMixin` (class in *gitlab.mixins*), 368
`on_http_error()` (in module *gitlab.exceptions*), 364
`optional` (*gitlab.base.RequiredOptional* attribute), 349

P

`package_files` (*gitlab.v4.objects.ProjectPackage* attribute), 292
`packages` (*gitlab.v4.objects.Group* attribute), 163
`packages` (*gitlab.v4.objects.Project* attribute), 212
`PagesDomain` (class in *gitlab.v4.objects*), 207
`PagesDomainManager` (class in *gitlab.v4.objects*), 208
`pagesdomains` (*gitlab.Gitlab* attribute), 140
`pagesdomains` (*gitlab.v4.objects.Project* attribute), 212
`parent_attrs` (*gitlab.base.RESTManager* property), 347
`participants()` (*gitlab.mixins.ParticipantsMixin* method), 369
`ParticipantsMixin` (class in *gitlab.mixins*), 368
`path` (*gitlab.base.RESTManager* property), 347
`per_page` (*gitlab.base.RESTObjectList* property), 348
`per_page` (*gitlab.GitlabList* property), 142
`personal_access_tokens` (*gitlab.Gitlab* attribute), 140
`personal_access_tokens` (*gitlab.v4.objects.User* attribute), 334
`PersonalAccessToken` (class in *gitlab.v4.objects*), 208
`PersonalAccessTokenManager` (class in *gitlab.v4.objects*), 208

- `pformat()` (*gitlab.base.RESTObject* method), 348
- `pipelines` (*gitlab.v4.objects.Project* attribute), 212
- `pipelines` (*gitlab.v4.objects.ProjectMergeRequest* attribute), 273
- `pipelineschedules` (*gitlab.v4.objects.Project* attribute), 212
- `play()` (*gitlab.v4.objects.ProjectJob* method), 261
- `play()` (*gitlab.v4.objects.ProjectPipelineSchedule* method), 298
- `pprint()` (*gitlab.base.RESTObject* method), 348
- `prev_page` (*gitlab.base.RESTObjectList* property), 348
- `prev_page` (*gitlab.GitlabList* property), 142
- `process_metrics()` (*gitlab.v4.objects.SidekiqManager* method), 327
- `Project` (class in *gitlab.v4.objects*), 208
- `ProjectAccessRequest` (class in *gitlab.v4.objects*), 216
- `ProjectAccessRequestManager` (class in *gitlab.v4.objects*), 216
- `ProjectAccessToken` (class in *gitlab.v4.objects*), 216
- `ProjectAccessTokenManager` (class in *gitlab.v4.objects*), 217
- `ProjectAdditionalStatistics` (class in *gitlab.v4.objects*), 217
- `ProjectAdditionalStatisticsManager` (class in *gitlab.v4.objects*), 217
- `ProjectApproval` (class in *gitlab.v4.objects*), 218
- `ProjectApprovalManager` (class in *gitlab.v4.objects*), 218
- `ProjectApprovalRule` (class in *gitlab.v4.objects*), 219
- `ProjectApprovalRuleManager` (class in *gitlab.v4.objects*), 219
- `ProjectArtifact` (class in *gitlab.v4.objects*), 219
- `ProjectArtifactManager` (class in *gitlab.v4.objects*), 220
- `ProjectAudit` (class in *gitlab.v4.objects*), 221
- `ProjectAuditEvent` (class in *gitlab.v4.objects*), 222
- `ProjectAuditEventManager` (class in *gitlab.v4.objects*), 222
- `ProjectAuditManager` (class in *gitlab.v4.objects*), 222
- `ProjectBadge` (class in *gitlab.v4.objects*), 223
- `ProjectBadgeManager` (class in *gitlab.v4.objects*), 223
- `ProjectBoard` (class in *gitlab.v4.objects*), 224
- `ProjectBoardList` (class in *gitlab.v4.objects*), 224
- `ProjectBoardListManager` (class in *gitlab.v4.objects*), 224
- `ProjectBoardManager` (class in *gitlab.v4.objects*), 225
- `ProjectBranch` (class in *gitlab.v4.objects*), 225
- `ProjectBranchManager` (class in *gitlab.v4.objects*), 226
- `ProjectCluster` (class in *gitlab.v4.objects*), 226
- `ProjectClusterManager` (class in *gitlab.v4.objects*), 226
- `ProjectCommit` (class in *gitlab.v4.objects*), 227
- `ProjectCommitComment` (class in *gitlab.v4.objects*), 229
- `ProjectCommitCommentManager` (class in *gitlab.v4.objects*), 230
- `ProjectCommitDiscussion` (class in *gitlab.v4.objects*), 230
- `ProjectCommitDiscussionManager` (class in *gitlab.v4.objects*), 230
- `ProjectCommitDiscussionNote` (class in *gitlab.v4.objects*), 231
- `ProjectCommitDiscussionNoteManager` (class in *gitlab.v4.objects*), 231
- `ProjectCommitManager` (class in *gitlab.v4.objects*), 232
- `ProjectCommitStatus` (class in *gitlab.v4.objects*), 233
- `ProjectCommitStatusManager` (class in *gitlab.v4.objects*), 233
- `ProjectCustomAttribute` (class in *gitlab.v4.objects*), 234
- `ProjectCustomAttributeManager` (class in *gitlab.v4.objects*), 234
- `ProjectDeployment` (class in *gitlab.v4.objects*), 235
- `ProjectDeploymentManager` (class in *gitlab.v4.objects*), 236
- `ProjectDeploymentMergeRequest` (class in *gitlab.v4.objects*), 237
- `ProjectDeploymentMergeRequestManager` (class in *gitlab.v4.objects*), 237
- `ProjectDeployToken` (class in *gitlab.v4.objects*), 235
- `ProjectDeployTokenManager` (class in *gitlab.v4.objects*), 235
- `ProjectEnvironment` (class in *gitlab.v4.objects*), 238
- `ProjectEnvironmentManager` (class in *gitlab.v4.objects*), 239
- `ProjectEvent` (class in *gitlab.v4.objects*), 239
- `ProjectEventManager` (class in *gitlab.v4.objects*), 240
- `ProjectExport` (class in *gitlab.v4.objects*), 240
- `ProjectExportManager` (class in *gitlab.v4.objects*), 240
- `ProjectFile` (class in *gitlab.v4.objects*), 241
- `ProjectFileManager` (class in *gitlab.v4.objects*), 242
- `ProjectFork` (class in *gitlab.v4.objects*), 244
- `ProjectForkManager` (class in *gitlab.v4.objects*), 245
- `ProjectHook` (class in *gitlab.v4.objects*), 246
- `ProjectHookManager` (class in *gitlab.v4.objects*), 246
- `ProjectImport` (class in *gitlab.v4.objects*), 246
- `ProjectImportManager` (class in *gitlab.v4.objects*), 247
- `ProjectIssue` (class in *gitlab.v4.objects*), 247
- `ProjectIssueAwardEmoji` (class in *gitlab.v4.objects*), 249
- `ProjectIssueAwardEmojiManager` (class in *gitlab.v4.objects*), 249
- `ProjectIssueDiscussion` (class in *gitlab.v4.objects*),

- 250
- `ProjectIssueDiscussionManager` (class in `gitlab.v4.objects`), 250
- `ProjectIssueDiscussionNote` (class in `gitlab.v4.objects`), 250
- `ProjectIssueDiscussionNoteManager` (class in `gitlab.v4.objects`), 251
- `ProjectIssueLink` (class in `gitlab.v4.objects`), 251
- `ProjectIssueLinkManager` (class in `gitlab.v4.objects`), 252
- `ProjectIssueManager` (class in `gitlab.v4.objects`), 252
- `ProjectIssueNote` (class in `gitlab.v4.objects`), 253
- `ProjectIssueNoteAwardEmoji` (class in `gitlab.v4.objects`), 253
- `ProjectIssueNoteAwardEmojiManager` (class in `gitlab.v4.objects`), 254
- `ProjectIssueNoteManager` (class in `gitlab.v4.objects`), 254
- `ProjectIssueResourceLabelEvent` (class in `gitlab.v4.objects`), 255
- `ProjectIssueResourceLabelEventManager` (class in `gitlab.v4.objects`), 255
- `ProjectIssueResourceMilestoneEvent` (class in `gitlab.v4.objects`), 256
- `ProjectIssueResourceMilestoneEventManager` (class in `gitlab.v4.objects`), 256
- `ProjectIssueResourceStateEvent` (class in `gitlab.v4.objects`), 257
- `ProjectIssueResourceStateEventManager` (class in `gitlab.v4.objects`), 257
- `ProjectIssuesStatistics` (class in `gitlab.v4.objects`), 258
- `ProjectIssuesStatisticsManager` (class in `gitlab.v4.objects`), 258
- `ProjectJob` (class in `gitlab.v4.objects`), 259
- `ProjectJobManager` (class in `gitlab.v4.objects`), 262
- `ProjectKey` (class in `gitlab.v4.objects`), 262
- `ProjectKeyManager` (class in `gitlab.v4.objects`), 263
- `ProjectLabel` (class in `gitlab.v4.objects`), 263
- `ProjectLabelManager` (class in `gitlab.v4.objects`), 264
- `ProjectManager` (class in `gitlab.v4.objects`), 265
- `ProjectMember` (class in `gitlab.v4.objects`), 269
- `ProjectMemberAll` (class in `gitlab.v4.objects`), 269
- `ProjectMemberAllManager` (class in `gitlab.v4.objects`), 269
- `ProjectMemberManager` (class in `gitlab.v4.objects`), 270
- `ProjectMergeRequest` (class in `gitlab.v4.objects`), 270
- `ProjectMergeRequestApproval` (class in `gitlab.v4.objects`), 274
- `ProjectMergeRequestApprovalManager` (class in `gitlab.v4.objects`), 274
- `ProjectMergeRequestApprovalRule` (class in `gitlab.v4.objects`), 275
- `ProjectMergeRequestApprovalRuleManager` (class in `gitlab.v4.objects`), 276
- `ProjectMergeRequestApprovalState` (class in `gitlab.v4.objects`), 276
- `ProjectMergeRequestApprovalStateManager` (class in `gitlab.v4.objects`), 277
- `ProjectMergeRequestAwardEmoji` (class in `gitlab.v4.objects`), 277
- `ProjectMergeRequestAwardEmojiManager` (class in `gitlab.v4.objects`), 278
- `ProjectMergeRequestDiff` (class in `gitlab.v4.objects`), 278
- `ProjectMergeRequestDiffManager` (class in `gitlab.v4.objects`), 279
- `ProjectMergeRequestDiscussion` (class in `gitlab.v4.objects`), 279
- `ProjectMergeRequestDiscussionManager` (class in `gitlab.v4.objects`), 279
- `ProjectMergeRequestDiscussionNote` (class in `gitlab.v4.objects`), 280
- `ProjectMergeRequestDiscussionNoteManager` (class in `gitlab.v4.objects`), 280
- `ProjectMergeRequestManager` (class in `gitlab.v4.objects`), 281
- `ProjectMergeRequestNote` (class in `gitlab.v4.objects`), 282
- `ProjectMergeRequestNoteAwardEmoji` (class in `gitlab.v4.objects`), 283
- `ProjectMergeRequestNoteAwardEmojiManager` (class in `gitlab.v4.objects`), 283
- `ProjectMergeRequestNoteManager` (class in `gitlab.v4.objects`), 284
- `ProjectMergeRequestPipeline` (class in `gitlab.v4.objects`), 284
- `ProjectMergeRequestPipelineManager` (class in `gitlab.v4.objects`), 285
- `ProjectMergeRequestResourceLabelEvent` (class in `gitlab.v4.objects`), 285
- `ProjectMergeRequestResourceLabelEventManager` (class in `gitlab.v4.objects`), 285
- `ProjectMergeRequestResourceMilestoneEvent` (class in `gitlab.v4.objects`), 286
- `ProjectMergeRequestResourceMilestoneEventManager` (class in `gitlab.v4.objects`), 286
- `ProjectMergeRequestResourceStateEvent` (class in `gitlab.v4.objects`), 287
- `ProjectMergeRequestResourceStateEventManager` (class in `gitlab.v4.objects`), 287
- `ProjectMergeTrain` (class in `gitlab.v4.objects`), 288
- `ProjectMergeTrainManager` (class in `gitlab.v4.objects`), 288
- `ProjectMilestone` (class in `gitlab.v4.objects`), 288
- `ProjectMilestoneManager` (class in `gitlab.v4.objects`), 289

- ProjectNote (class in *gitlab.v4.objects*), 290
- ProjectNoteManager (class in *gitlab.v4.objects*), 290
- ProjectNotificationSettings (class in *gitlab.v4.objects*), 291
- ProjectNotificationSettingsManager (class in *gitlab.v4.objects*), 291
- ProjectPackage (class in *gitlab.v4.objects*), 292
- ProjectPackageFile (class in *gitlab.v4.objects*), 292
- ProjectPackageFileManager (class in *gitlab.v4.objects*), 292
- ProjectPackageManager (class in *gitlab.v4.objects*), 293
- ProjectPagesDomain (class in *gitlab.v4.objects*), 293
- ProjectPagesDomainManager (class in *gitlab.v4.objects*), 294
- ProjectPipeline (class in *gitlab.v4.objects*), 294
- ProjectPipelineBridge (class in *gitlab.v4.objects*), 295
- ProjectPipelineBridgeManager (class in *gitlab.v4.objects*), 295
- ProjectPipelineJob (class in *gitlab.v4.objects*), 296
- ProjectPipelineJobManager (class in *gitlab.v4.objects*), 296
- ProjectPipelineManager (class in *gitlab.v4.objects*), 296
- ProjectPipelineSchedule (class in *gitlab.v4.objects*), 298
- ProjectPipelineScheduleManager (class in *gitlab.v4.objects*), 298
- ProjectPipelineScheduleVariable (class in *gitlab.v4.objects*), 299
- ProjectPipelineScheduleVariableManager (class in *gitlab.v4.objects*), 299
- ProjectPipelineTestReport (class in *gitlab.v4.objects*), 300
- ProjectPipelineTestReportManager (class in *gitlab.v4.objects*), 300
- ProjectPipelineTestReportSummary (class in *gitlab.v4.objects*), 300
- ProjectPipelineTestReportSummaryManager (class in *gitlab.v4.objects*), 301
- ProjectPipelineVariable (class in *gitlab.v4.objects*), 301
- ProjectPipelineVariableManager (class in *gitlab.v4.objects*), 302
- ProjectProtectedBranch (class in *gitlab.v4.objects*), 302
- ProjectProtectedBranchManager (class in *gitlab.v4.objects*), 302
- ProjectProtectedTag (class in *gitlab.v4.objects*), 303
- ProjectProtectedTagManager (class in *gitlab.v4.objects*), 303
- ProjectPushRules (class in *gitlab.v4.objects*), 304
- ProjectPushRulesManager (class in *gitlab.v4.objects*), 304
- ProjectRegistryRepository (class in *gitlab.v4.objects*), 304
- ProjectRegistryRepositoryManager (class in *gitlab.v4.objects*), 305
- ProjectRegistryTag (class in *gitlab.v4.objects*), 305
- ProjectRegistryTagManager (class in *gitlab.v4.objects*), 305
- ProjectRelease (class in *gitlab.v4.objects*), 306
- ProjectReleaseLink (class in *gitlab.v4.objects*), 306
- ProjectReleaseLinkManager (class in *gitlab.v4.objects*), 307
- ProjectReleaseManager (class in *gitlab.v4.objects*), 307
- ProjectRemoteMirror (class in *gitlab.v4.objects*), 308
- ProjectRemoteMirrorManager (class in *gitlab.v4.objects*), 308
- ProjectRunner (class in *gitlab.v4.objects*), 308
- ProjectRunnerManager (class in *gitlab.v4.objects*), 309
- projects (*gitlab.Gitlab* attribute), 140
- projects (*gitlab.v4.objects.Group* attribute), 163
- projects (*gitlab.v4.objects.User* attribute), 334
- ProjectService (class in *gitlab.v4.objects*), 309
- ProjectServiceManager (class in *gitlab.v4.objects*), 309
- ProjectSnippet (class in *gitlab.v4.objects*), 310
- ProjectSnippetAwardEmoji (class in *gitlab.v4.objects*), 311
- ProjectSnippetAwardEmojiManager (class in *gitlab.v4.objects*), 311
- ProjectSnippetDiscussion (class in *gitlab.v4.objects*), 312
- ProjectSnippetDiscussionManager (class in *gitlab.v4.objects*), 312
- ProjectSnippetDiscussionNote (class in *gitlab.v4.objects*), 313
- ProjectSnippetDiscussionNoteManager (class in *gitlab.v4.objects*), 313
- ProjectSnippetManager (class in *gitlab.v4.objects*), 314
- ProjectSnippetNote (class in *gitlab.v4.objects*), 314
- ProjectSnippetNoteAwardEmoji (class in *gitlab.v4.objects*), 314
- ProjectSnippetNoteAwardEmojiManager (class in *gitlab.v4.objects*), 315
- ProjectSnippetNoteManager (class in *gitlab.v4.objects*), 315
- ProjectStorage (class in *gitlab.v4.objects*), 316
- ProjectStorageManager (class in *gitlab.v4.objects*), 316
- ProjectTag (class in *gitlab.v4.objects*), 317
- ProjectTagManager (class in *gitlab.v4.objects*), 317
- ProjectTrigger (class in *gitlab.v4.objects*), 318

- ProjectTriggerManager (class in `gitlab.v4.objects`), 318
- ProjectUser (class in `gitlab.v4.objects`), 319
- ProjectUserManager (class in `gitlab.v4.objects`), 319
- ProjectVariable (class in `gitlab.v4.objects`), 319
- ProjectVariableManager (class in `gitlab.v4.objects`), 319
- ProjectWiki (class in `gitlab.v4.objects`), 320
- ProjectWikiManager (class in `gitlab.v4.objects`), 320
- protectedbranches (`gitlab.v4.objects.Project` attribute), 212
- protectedtags (`gitlab.v4.objects.Project` attribute), 212
- public() (`gitlab.v4.objects.SnippetManager` method), 329
- pushrules (`gitlab.v4.objects.Project` attribute), 212
- ## Q
- queue_metrics() (`gitlab.v4.objects.SidekiqManager` method), 328
- ## R
- raw() (`gitlab.v4.objects.ProjectArtifactManager` method), 221
- raw() (`gitlab.v4.objects.ProjectFileManager` method), 244
- rebase() (`gitlab.v4.objects.ProjectMergeRequest` method), 273
- RedirectError, 364
- refresh() (`gitlab.mixins.RefreshMixin` method), 369
- RefreshMixin (class in `gitlab.mixins`), 369
- refs() (`gitlab.v4.objects.ProjectCommit` method), 229
- register_custom_action() (in module `gitlab.cli`), 349
- related_merge_requests() (`gitlab.v4.objects.ProjectIssue` method), 248
- releases (`gitlab.v4.objects.Project` attribute), 212
- remote_mirrors (`gitlab.v4.objects.Project` attribute), 212
- remove_none_from_dict() (in module `gitlab.utils`), 374
- render() (`gitlab.mixins.BadgeRenderMixin` method), 365
- repair() (`gitlab.v4.objects.GeoNode` method), 157
- repositories (`gitlab.v4.objects.Project` attribute), 212
- repository_archive() (`gitlab.v4.objects.RepositoryMixin` method), 321
- repository_blob() (`gitlab.v4.objects.RepositoryMixin` method), 322
- repository_compare() (`gitlab.v4.objects.RepositoryMixin` method), 322
- repository_contributors() (`gitlab.v4.objects.RepositoryMixin` method), 323
- repository_raw_blob() (`gitlab.v4.objects.RepositoryMixin` method), 323
- repository_tree() (`gitlab.v4.objects.RepositoryMixin` method), 323
- RepositoryMixin (class in `gitlab.v4.objects`), 321
- required (`gitlab.base.RequiredOptional` attribute), 349
- RequiredOptional (class in `gitlab.base`), 349
- reset_spent_time() (`gitlab.mixins.TimeTrackingMixin` method), 371
- reset_time_estimate() (`gitlab.mixins.TimeTrackingMixin` method), 371
- resourcelabelevents (`gitlab.v4.objects.GroupEpic` attribute), 174
- resourcelabelevents (`gitlab.v4.objects.ProjectIssue` attribute), 249
- resourcelabelevents (`gitlab.v4.objects.ProjectMergeRequest` attribute), 273
- resourceilestoneevents (`gitlab.v4.objects.ProjectIssue` attribute), 249
- resourceilestoneevents (`gitlab.v4.objects.ProjectMergeRequest` attribute), 273
- resourcestateevents (`gitlab.v4.objects.ProjectIssue` attribute), 249
- resourcestateevents (`gitlab.v4.objects.ProjectMergeRequest` attribute), 274
- response_content() (in module `gitlab.utils`), 374
- RESTManager (class in `gitlab.base`), 347
- RESTObject (class in `gitlab.base`), 347
- RESTObjectList (class in `gitlab.base`), 348
- RetrieveMixin (class in `gitlab.mixins`), 369
- retry() (`gitlab.v4.objects.ProjectJob` method), 261
- retry() (`gitlab.v4.objects.ProjectPipeline` method), 295
- revert() (`gitlab.v4.objects.ProjectCommit` method), 229
- Runner (class in `gitlab.v4.objects`), 324
- RunnerJob (class in `gitlab.v4.objects`), 324
- RunnerJobManager (class in `gitlab.v4.objects`), 325
- RunnerManager (class in `gitlab.v4.objects`), 325
- runners (`gitlab.Gitlab` attribute), 140
- runners (`gitlab.v4.objects.Group` attribute), 163
- runners (`gitlab.v4.objects.Project` attribute), 212
- ## S
- save() (`gitlab.mixins.SaveMixin` method), 370
- save() (`gitlab.v4.objects.GroupEpicIssue` method), 177
- save() (`gitlab.v4.objects.GroupLabel` method), 186
- save() (`gitlab.v4.objects.ProjectFile` method), 242

[save\(\)](#) ([gitlab.v4.objects.ProjectLabel](#) method), 264
[save\(\)](#) ([gitlab.v4.objects.ProjectMergeRequestApprovalRule](#) method), 275
[SaveMixin](#) (class in [gitlab.mixins](#)), 369
[search\(\)](#) ([gitlab.Gitlab](#) method), 140
[search\(\)](#) ([gitlab.v4.objects.Group](#) method), 163
[search\(\)](#) ([gitlab.v4.objects.Project](#) method), 212
[services](#) ([gitlab.v4.objects.Project](#) attribute), 212
[session](#) ([gitlab.Gitlab](#) attribute), 141
[set\(\)](#) ([gitlab.mixins.SetMixin](#) method), 370
[set\(\)](#) ([gitlab.v4.objects.FeatureManager](#) method), 155
[set_approvers\(\)](#) ([gitlab.v4.objects.ProjectApprovalManager](#) method), 219
[set_approvers\(\)](#) ([gitlab.v4.objects.ProjectMergeRequestApprovalManager](#) method), 275
[set_license\(\)](#) ([gitlab.Gitlab](#) method), 141
[SetMixin](#) (class in [gitlab.mixins](#)), 370
[settings](#) ([gitlab.Gitlab](#) attribute), 141
[share\(\)](#) ([gitlab.v4.objects.Group](#) method), 163
[share\(\)](#) ([gitlab.v4.objects.Project](#) method), 212
[sidekiq](#) ([gitlab.Gitlab](#) attribute), 141
[SidekiqManager](#) (class in [gitlab.v4.objects](#)), 326
[signature\(\)](#) ([gitlab.v4.objects.ProjectCommit](#) method), 229
[snapshot\(\)](#) ([gitlab.v4.objects.Project](#) method), 213
[Snippet](#) (class in [gitlab.v4.objects](#)), 328
[SnippetManager](#) (class in [gitlab.v4.objects](#)), 329
[snippets](#) ([gitlab.Gitlab](#) attribute), 141
[snippets](#) ([gitlab.v4.objects.Project](#) attribute), 213
[ssl_verify](#) ([gitlab.Gitlab](#) attribute), 141
[star\(\)](#) ([gitlab.v4.objects.Project](#) method), 213
[starred_projects](#) ([gitlab.v4.objects.User](#) attribute), 334
[StarredProject](#) (class in [gitlab.v4.objects](#)), 329
[StarredProjectManager](#) (class in [gitlab.v4.objects](#)), 330
[status](#) ([gitlab.v4.objects.CurrentUser](#) attribute), 148
[status](#) ([gitlab.v4.objects.User](#) attribute), 334
[status\(\)](#) ([gitlab.v4.objects.GeoNode](#) method), 158
[status\(\)](#) ([gitlab.v4.objects.GeoNodeManager](#) method), 159
[statuses](#) ([gitlab.v4.objects.ProjectCommit](#) attribute), 229
[stop\(\)](#) ([gitlab.v4.objects.ProjectEnvironment](#) method), 238
[storage](#) ([gitlab.v4.objects.Project](#) attribute), 213
[subgroups](#) ([gitlab.v4.objects.Group](#) attribute), 164
[SubscribableMixin](#) (class in [gitlab.mixins](#)), 370
[subscribe\(\)](#) ([gitlab.mixins.SubscribableMixin](#) method), 370

T

[tags](#) ([gitlab.v4.objects.Project](#) attribute), 213
[tags](#) ([gitlab.v4.objects.ProjectRegistryRepository](#) attribute), 305
[take_ownership\(\)](#) ([gitlab.v4.objects.ProjectPipelineSchedule](#) method), 298
[test_report](#) ([gitlab.v4.objects.ProjectPipeline](#) attribute), 295
[test_report_summary](#) ([gitlab.v4.objects.ProjectPipeline](#) attribute), 295
[time_estimate\(\)](#) ([gitlab.mixins.TimeTrackingMixin](#) method), 372
[time_stats\(\)](#) ([gitlab.mixins.TimeTrackingMixin](#) method), 372
[timeout](#) ([gitlab.Gitlab](#) attribute), 141
[TimeTrackingMixin](#) (class in [gitlab.mixins](#)), 371
[Todo](#) (class in [gitlab.v4.objects](#)), 330
[todo\(\)](#) ([gitlab.mixins.TODOMixin](#) method), 372
[TodoManager](#) (class in [gitlab.v4.objects](#)), 331
[TodoMixin](#) (class in [gitlab.mixins](#)), 372
[todos](#) ([gitlab.Gitlab](#) attribute), 141
[Topic](#) (class in [gitlab.v4.objects](#)), 332
[TopicManager](#) (class in [gitlab.v4.objects](#)), 332
[topics](#) ([gitlab.Gitlab](#) attribute), 141
[total](#) ([gitlab.base.RESTObjectList](#) property), 349
[total](#) ([gitlab.GitlabList](#) property), 143
[total_pages](#) ([gitlab.base.RESTObjectList](#) property), 349
[total_pages](#) ([gitlab.GitlabList](#) property), 143
[trace\(\)](#) ([gitlab.v4.objects.ProjectJob](#) method), 261
[transfer\(\)](#) ([gitlab.v4.objects.Group](#) method), 164
[transfer\(\)](#) ([gitlab.v4.objects.Project](#) method), 213
[transfer_project\(\)](#) ([gitlab.v4.objects.Group](#) method), 164
[transfer_project\(\)](#) ([gitlab.v4.objects.Project](#) method), 214
[trigger_pipeline\(\)](#) ([gitlab.v4.objects.Project](#) method), 214
[triggers](#) ([gitlab.v4.objects.Project](#) attribute), 214

U

[unapprove\(\)](#) ([gitlab.v4.objects.ProjectMergeRequest](#) method), 274
[unarchive\(\)](#) ([gitlab.v4.objects.Project](#) method), 214
[unblock\(\)](#) ([gitlab.v4.objects.User](#) method), 334
[unfollow\(\)](#) ([gitlab.v4.objects.User](#) method), 335
[unshare\(\)](#) ([gitlab.v4.objects.Group](#) method), 164
[unshare\(\)](#) ([gitlab.v4.objects.Project](#) method), 215
[unstar\(\)](#) ([gitlab.v4.objects.Project](#) method), 215
[unsubscribe\(\)](#) ([gitlab.mixins.SubscribableMixin](#) method), 371
[update\(\)](#) ([gitlab.mixins.UpdateMixin](#) method), 373

`update()` (*gitlab.v4.objects.ApplicationAppearanceManager* method), 144

`update()` (*gitlab.v4.objects.ApplicationSettingsManager* method), 145

`update()` (*gitlab.v4.objects.GroupLabelManager* method), 186

`update()` (*gitlab.v4.objects.ProjectFileManager* method), 244

`update()` (*gitlab.v4.objects.ProjectLabelManager* method), 265

`update_submodule()` (*gitlab.v4.objects.RepositoryMixin* method), 324

`UpdateMixin` (class in *gitlab.mixins*), 373

`upload()` (*gitlab.v4.objects.GenericPackageManager* method), 157

`upload()` (*gitlab.v4.objects.Project* method), 215

`url` (*gitlab.Gitlab* property), 142

`User` (class in *gitlab.v4.objects*), 333

`user_activities` (*gitlab.Gitlab* attribute), 142

`user_agent_detail()` (*gitlab.mixins.UserAgentDetailMixin* method), 373

`UserActivities` (class in *gitlab.v4.objects*), 335

`UserActivitiesManager` (class in *gitlab.v4.objects*), 335

`UserAgentDetailMixin` (class in *gitlab.mixins*), 373

`UserCustomAttribute` (class in *gitlab.v4.objects*), 335

`UserCustomAttributeManager` (class in *gitlab.v4.objects*), 336

`UserEmail` (class in *gitlab.v4.objects*), 336

`UserEmailManager` (class in *gitlab.v4.objects*), 337

`UserEvent` (class in *gitlab.v4.objects*), 337

`UserEventManager` (class in *gitlab.v4.objects*), 338

`UserGPGKey` (class in *gitlab.v4.objects*), 338

`UserGPGKeyManager` (class in *gitlab.v4.objects*), 338

`UserIdentityProviderManager` (class in *gitlab.v4.objects*), 339

`UserImpersonationToken` (class in *gitlab.v4.objects*), 339

`UserImpersonationTokenManager` (class in *gitlab.v4.objects*), 339

`UserKey` (class in *gitlab.v4.objects*), 340

`UserKeyManager` (class in *gitlab.v4.objects*), 340

`UserManager` (class in *gitlab.v4.objects*), 341

`UserMembership` (class in *gitlab.v4.objects*), 342

`UserMembershipManager` (class in *gitlab.v4.objects*), 342

`UserPersonalAccessToken` (class in *gitlab.v4.objects*), 343

`UserPersonalAccessTokenManager` (class in *gitlab.v4.objects*), 343

`UserProject` (class in *gitlab.v4.objects*), 343

`UserProjectManager` (class in *gitlab.v4.objects*), 344

`users` (*gitlab.Gitlab* attribute), 142

`users` (*gitlab.v4.objects.Project* attribute), 216

`UserStatus` (class in *gitlab.v4.objects*), 345

`UserStatusManager` (class in *gitlab.v4.objects*), 345

V

`Variable` (class in *gitlab.v4.objects*), 346

`VariableManager` (class in *gitlab.v4.objects*), 346

`variables` (*gitlab.Gitlab* attribute), 142

`variables` (*gitlab.v4.objects.Group* attribute), 164

`variables` (*gitlab.v4.objects.Project* attribute), 216

`variables` (*gitlab.v4.objects.ProjectPipeline* attribute), 295

`variables` (*gitlab.v4.objects.ProjectPipelineSchedule* attribute), 298

`verify()` (*gitlab.v4.objects.RunnerManager* method), 326

`version()` (*gitlab.Gitlab* method), 142

W

`warn()` (in module *gitlab.utils*), 374

`what_to_cls()` (in module *gitlab.cli*), 350

`wikis` (*gitlab.v4.objects.Group* attribute), 165

`wikis` (*gitlab.v4.objects.Project* attribute), 216