
python-gitlab Documentation

Release 3.10.0

Gauvain Pocentek, Mika Mäenpää

Sep 28, 2022

TABLE OF CONTENTS

1 Installation	3
2 Using the docker images	5
2.1 Building the image	5
3 Bug reports	7
4 Gitter Community Chat	9
5 Documentation	11
5.1 Build the docs	11
6 Contributing	13
6.1 Getting started with the CLI	13
6.2 Getting started with the API	18
6.3 Advanced usage	25
6.4 CLI examples	27
6.5 API examples	32
6.6 API reference (gitlab package)	146
6.7 CLI reference (gitlab command)	455
6.8 Changelog	783
6.9 Release notes	821
6.10 FAQ	824
7 Indices and tables	827
Python Module Index	829
Index	831

`python-gitlab` is a Python package providing access to the GitLab server API.

It supports the v4 API of GitLab, and provides a CLI tool (`gitlab`).

**CHAPTER
ONE**

INSTALLATION

As of 3.0.0, `python-gitlab` is compatible with Python 3.7+.

Use pip to install the latest stable version of `python-gitlab`:

```
$ pip install --upgrade python-gitlab
```

The current development version is available on both [GitHub.com](#) and [GitLab.com](#), and can be installed directly from the git repository:

```
$ pip install git+https://github.com/python-gitlab/python-gitlab.git
```

From GitLab:

```
$ pip install git+https://gitlab.com/python-gitlab/python-gitlab.git
```


USING THE DOCKER IMAGES

python-gitlab provides Docker images in two flavors, based on the Alpine and Debian slim python base images. The default tag is alpine, but you can explicitly use the alias (see below).

The alpine image is smaller, but you may want to use the Debian-based slim tag (currently based on -slim-bullseye) if you are running into issues or need a more complete environment with a bash shell, such as in CI jobs.

The images are published on the GitLab registry, for example:

- `registry.gitlab.com/python-gitlab/python-gitlab:latest` (latest, alpine alias)
- `registry.gitlab.com/python-gitlab/python-gitlab:alpine` (latest alpine)
- `registry.gitlab.com/python-gitlab/python-gitlab:slim-bullseye` (latest slim-bullseye)
- `registry.gitlab.com/python-gitlab/python-gitlab:v3.2.0` (alpine alias)
- `registry.gitlab.com/python-gitlab/python-gitlab:v3.2.0-alpine`
- `registry.gitlab.com/python-gitlab/python-gitlab:v3.2.0-slim-bullseye`

You can run the Docker image directly from the GitLab registry:

```
$ docker run -it --rm registry.gitlab.com/python-gitlab/python-gitlab:latest <command> ..  
→ .
```

For example, to get a project on GitLab.com (without authentication):

```
$ docker run -it --rm registry.gitlab.com/python-gitlab/python-gitlab:latest project get  
→ --id gitlab-org/gitlab
```

You can also mount your own config file:

```
$ docker run -it --rm -v /path/to/python-gitlab.cfg:/etc/python-gitlab.cfg registry.  
→ gitlab.com/python-gitlab/python-gitlab:latest <command> ...
```

2.1 Building the image

To build your own image from this repository, run:

```
$ docker build -t python-gitlab:latest .
```

Run your own image:

```
$ docker run -it --rm python-gitlab:latest <command> ...
```

Build a Debian slim-based image:

```
$ docker build -t python-gitlab:latest --build-arg PYTHON_FLAVOR=slim-bullseye .
```

**CHAPTER
THREE**

BUG REPORTS

Please report bugs and feature requests at <https://github.com/python-gitlab/python-gitlab/issues>.

**CHAPTER
FOUR**

GITTER COMMUNITY CHAT

We have a [gitter](#) community chat available at <https://gitter.im/python-gitlab/Lobby>, which you can also directly access via the Open Chat button below.

If you have a simple question, the community might be able to help already, without you opening an issue. If you regularly use python-gitlab, we also encourage you to join and participate. You might discover new ideas and use cases yourself!

DOCUMENTATION

The full documentation for CLI and API is available on [readthedocs](#).

5.1 Build the docs

We use `tox` to manage our environment and build the documentation:

```
pip install tox  
tox -e docs
```


CONTRIBUTING

For guidelines for contributing to `python-gitlab`, refer to [CONTRIBUTING.rst](#).

6.1 Getting started with the CLI

`python-gitlab` provides a **gitlab** command-line tool to interact with GitLab servers.

This is especially convenient for running quick ad-hoc commands locally, easily interacting with the API inside GitLab CI, or with more advanced shell scripting when integrating with other tooling.

6.1.1 Configuration

`gitlab` allows setting configuration options via command-line arguments, environment variables, and configuration files.

For a complete list of global CLI options and their environment variable equivalents, see [*CLI reference \(gitlab command\)*](#).

With no configuration provided, `gitlab` will default to unauthenticated requests against [GitLab.com](#).

With no configuration but running inside a GitLab CI job, it will default to authenticated requests using the current job token against the current instance (via `CI_SERVER_URL` and `CI_JOB_TOKEN` environment variables).

Warning: Please note the job token has very limited permissions and can only be used with certain endpoints. You may need to provide a personal access token instead.

When you provide configuration, values are evaluated with the following precedence:

1. Explicitly provided CLI arguments,
2. Environment variables,
3. Configuration files:
 - a. explicitly defined config files:
 - i. via the `--config-file` CLI argument,
 - ii. via the `PYTHON_GITLAB_CFG` environment variable,
 - b. user-specific config file,
 - c. system-level config file,
4. Environment variables always present in CI (`CI_SERVER_URL`, `CI_JOB_TOKEN`).

Additionally, authentication will take the following precedence when multiple options or environment variables are present:

1. Private token,
2. OAuth token,
3. CI job token.

Configuration files

`gitlab` looks up 3 configuration files by default:

The `PYTHON_GITLAB_CFG` environment variable

An environment variable that contains the path to a configuration file.

`/etc/python-gitlab.cfg`

System-wide configuration file

`~/.python-gitlab.cfg`

User configuration file

You can use a different configuration file with the `--config-file` option.

Warning: If the `PYTHON_GITLAB_CFG` environment variable is defined and the target file exists, it will be the only configuration file parsed by `gitlab`.

If the environment variable is defined and the target file cannot be accessed, `gitlab` will fail explicitly.

Configuration file format

The configuration file uses the INI format. It contains at least a `[global]` section, and a specific section for each GitLab server. For example:

```
[global]
default = somewhere
ssl_verify = true
timeout = 5

[somewhere]
url = https://some.whe.re
private_token = vTbFeqJCY3sibBP7BZM
api_version = 4

[elsewhere]
url = http://else.whe.re:8080
private_token = helper: path/to/helper.sh
timeout = 1
```

The `default` option of the `[global]` section defines the GitLab server to use if no server is explicitly specified with the `--gitlab` CLI option.

The `[global]` section also defines the values for the default connection parameters. You can override the values in each GitLab server section.

Table 1: Global options

Option	Possible values	Description
ssl_verify	True, False, or a str	Verify the SSL certificate. Set to <code>False</code> to disable verification, though this will create warnings. Any other value is interpreted as path to a CA_BUNDLE file or directory with certificates of trusted CAs.
timeout	Integer	Number of seconds to wait for an answer before failing.
api_version	4	The API version to use to make queries. Only 4 is available since 1.5.0.
per_page	Integer between 1 and 100	The number of items to return in listing queries. GitLab limits the value at 100.
user_agent	str	A string defining a custom user agent to use when gitlab makes requests.

You must define the `url` in each GitLab server section.

Warning: Note that a url that results in 301/302 redirects will raise an error, so it is highly recommended to use the final destination in the `url` field. For example, if the GitLab server you are using redirects requests from http to https, make sure to use the `https://` protocol in the URL definition.

A URL that redirects using 301/302 (rather than 307/308) will most likely cause malformed POST and PUT requests. python-gitlab will therefore raise a `RedirectionError` when it encounters a redirect which it believes will cause such an error, to avoid confusion between successful GET and failing POST/PUT requests on the same instance.

Only one of `private_token`, `oauth_token` or `job_token` should be defined. If neither are defined an anonymous request will be sent to the Gitlab server, with very limited permissions.

We recommend that you use [Credential helpers](#) to securely store your tokens.

Table 2: GitLab server options

Option	Description
<code>url</code>	URL for the GitLab server. Do NOT use a URL which redirects.
<code>private_token</code>	Your user token. Login/password is not supported. Refer to the official documentation to learn how to obtain a token.
<code>oauth_token</code>	An Oauth token for authentication. The Gitlab server must be configured to support this authentication method.
<code>job_token</code>	Your job token. See the official documentation to learn how to obtain a token.
<code>api_version</code>	GitLab API version to use. Only 4 is available since 1.5.0.

Credential helpers

For all configuration options that contain secrets (for example, `personal_token`, `oauth_token`, `job_token`), you can specify a helper program to retrieve the secret indicated by a `helper:` prefix. This allows you to fetch values from a local keyring store or cloud-hosted vaults such as Bitwarden. Environment variables are expanded if they exist and `~` expands to your home directory.

It is expected that the helper program prints the secret to standard output. To use shell features such as piping to retrieve the value, you will need to use a wrapper script; see below.

Example for a `keyring` helper:

```
[global]
default = somewhere
ssl_verify = true
timeout = 5

[somewhere]
url = http://somewhe.re
private_token = helper: keyring get Service Username
timeout = 1
```

Example for a `pass` helper with a wrapper script:

```
[global]
default = somewhere
ssl_verify = true
timeout = 5

[somewhere]
url = http://somewhe.re
private_token = helper: /path/to/helper.sh
timeout = 1
```

In `/path/to/helper.sh`:

```
#!/bin/bash
pass show path/to/credentials | head -n 1
```

6.1.2 CLI

Objects and actions

The `gitlab` command expects two mandatory arguments. The first one is the type of object that you want to manipulate. The second is the action that you want to perform. For example:

```
$ gitlab project list
```

Use the `--help` option to list the available object types and actions:

```
$ gitlab --help
$ gitlab project --help
```

Some actions require additional parameters. Use the `--help` option to list mandatory and optional arguments for an action:

```
$ gitlab project create --help
```

Optional arguments

Use the following optional arguments to change the behavior of `gitlab`. These options must be defined before the mandatory arguments.

`--verbose, -v`

Outputs detail about retrieved objects. Available for legacy (default) output only.

`--config-file, -c`

Path to a configuration file.

`--gitlab, -g`

ID of a GitLab server defined in the configuration file.

`--output, -o`

Output format. Defaults to a custom format. Can also be `yaml` or `json`.

Important: The [PyYAML package](#) is required to use the `yaml` output option. You need to install it explicitly using `pip install python-gitlab[yaml]`

`--fields, -f`

Comma-separated list of fields to display (`yaml` and `json` output formats only). If not used, all the object fields are displayed.

Example:

```
$ gitlab -o yaml -f id,permissions -g elsewhere -c /tmp/gl.cfg project list
```

Reading values from files

You can make `gitlab` read values from files instead of providing them on the command line. This is handy for values containing new lines for instance:

```
$ cat > /tmp/description << EOF
This is the description of my project.

It is obviously the best project around
EOF
$ gitlab project create --name SuperProject --description @/tmp/description
```

6.1.3 Enabling shell completion

To get completion, you'll need to install the package with the extra “completion”:

```
pip install python_gitlab[completion]
```

Add the appropriate command below to your shell's config file so that it is run on startup. You will likely have to restart or re-login for the completion to start working.

Bash

```
eval "$(register-python-argcomplete gitlab)"
```

tcsh

```
eval `register-python-argcomplete --shell tcsh gitlab`
```

fish

```
register-python-argcomplete --shell fish gitlab | .
```

Zsh

Warning: Zsh completion support is broken right now in the argcomplete python package. Perhaps it will be fixed in a future release of argcomplete at which point the following instructions will enable completion in zsh.

To activate completions for zsh you need to have bashcompinit enabled in zsh:

```
autoload -U bashcompinit  
bashcompinit
```

Afterwards you can enable completion for gitlab:

```
eval "$(register-python-argcomplete gitlab)"
```

6.2 Getting started with the API

python-gitlab only supports GitLab API v4.

6.2.1 `gitlab.Gitlab` class

To connect to GitLab.com or another GitLab instance, create a `gitlab.Gitlab` object:

Hint: You can use different types of tokens for authenticated requests against the GitLab API. You will most likely want to use a resource (project/group) access token or a personal access token.

For the full list of available options and how to obtain these tokens, please see <https://docs.gitlab.com/ee/api/index.html#authentication>.

```
import gitlab  
  
# anonymous read-only access for public resources (GitLab.com)
```

(continues on next page)

(continued from previous page)

```

gl = gitlab.Gitlab()

# anonymous read-only access for public resources (self-hosted GitLab instance)
gl = gitlab.Gitlab('https://gitlab.example.com')

# private token or personal token authentication (GitLab.com)
gl = gitlab.Gitlab(private_token='JVNSESSs8EwWRx5yDxM5q')

# private token or personal token authentication (self-hosted GitLab instance)
gl = gitlab.Gitlab(url='https://gitlab.example.com', private_token='JVNSESSs8EwWRx5yDxM5q
    ↵')

# oauth token authentication
gl = gitlab.Gitlab('https://gitlab.example.com', oauth_token='my_long_token_here')

# job token authentication (to be used in CI)
# bear in mind the limitations of the API endpoints it supports:
# https://docs.gitlab.com/ee/ci/jobs/ci_job_token.html
import os
gl = gitlab.Gitlab('https://gitlab.example.com', job_token=os.environ['CI_JOB_TOKEN'])

# Define your own custom user agent for requests
gl = gitlab.Gitlab('https://gitlab.example.com', user_agent='my-package/1.0.0')

# make an API request to create the gl.user object. This is not required but may be
    ↵ useful
# to validate your token authentication. Note that this will not work with job tokens.
gl.auth()

```

You can also use configuration files to create `gitlab.Gitlab` objects:

```
gl = gitlab.Gitlab.from_config('somewhere', ['/tmp/gl.cfg'])
```

See the [Configuration](#) section for more information about configuration files.

Warning: Note that a url that results in 301/302 redirects will raise an error, so it is highly recommended to use the final destination in the `url` field. For example, if the GitLab server you are using redirects requests from http to https, make sure to use the `https://` protocol in the URL definition.

A URL that redirects using 301/302 (rather than 307/308) will most likely cause malformed POST and PUT requests.

`python-gitlab` will therefore raise a `RedirectionError` when it encounters a redirect which it believes will cause such an error, to avoid confusion between successful GET and failing POST/PUT requests on the same instance.

Note on password authentication

GitLab has long removed password-based basic authentication. You can currently still use the [resource owner password credentials](#) flow to obtain an OAuth token.

However, we do not recommend this as it will not work with 2FA enabled, and GitLab is removing ROPC-based flows without client IDs in a future release. We recommend you obtain tokens for automated workflows as linked above or obtain a session cookie from your browser.

For a python example of password authentication using the ROPC-based OAuth2 flow, see [this Ansible snippet](#).

6.2.2 Managers

The `gitlab.Gitlab` class provides managers to access the GitLab resources. Each manager provides a set of methods to act on the resources. The available methods depend on the resource type.

Examples:

```
# list all the projects
projects = gl.projects.list(iterator=True)
for project in projects:
    print(project)

# get the group with id == 2
group = gl.groups.get(2)
for project in group.projects.list(iterator=True):
    print(project)
```

Warning: Calling `list()` without any arguments will by default not return the complete list of items. Use either the `get_all=True` or `iterator=True` parameters to get all the items when using listing methods. See the [Pagination](#) section for more information.

```
# create a new user
user_data = {'email': 'jen@foo.com', 'username': 'jen', 'name': 'Jen'}
user = gl.users.create(user_data)
print(user)
```

Note: `python-gitlab` attempts to sync the required, optional, and mutually exclusive attributes for resource creation and update with the upstream API.

You are encouraged to follow upstream API documentation for each resource to find these - each resource documented here links to the corresponding upstream resource documentation at the top of the page.

The attributes of objects are defined upon object creation, and depend on the GitLab API itself. To list the available information associated with an object use the `attributes` attribute:

```
project = gl.projects.get(1)
print(project.attributes)
```

Some objects also provide managers to access related GitLab resources:

```
# list the issues for a project
project = gl.projects.get(1)
issues = project.issues.list(get_all=True)
```

python-gitlab allows to send any data to the GitLab server when making queries. In case of invalid or missing arguments python-gitlab will raise an exception with the GitLab server error message:

```
>>> gl.projects.list(sort='invalid value')
...
GitlabListError: 400: sort does not have a valid value
```

You can use the `query_parameters` argument to send arguments that would conflict with python or python-gitlab when using them as kwargs:

```
gl.user_activities.list(from='2019-01-01', iterator=True) ## invalid
gl.user_activities.list(query_parameters={'from': '2019-01-01'}, iterator=True) # OK
```

6.2.3 Gitlab Objects

You can update or delete a remote object when it exists locally:

```
# update the attributes of a resource
project = gl.projects.get(1)
project.wall_enabled = False
# don't forget to apply your changes on the server:
project.save()

# delete the resource
project.delete()
```

Some classes provide additional methods, allowing more actions on the GitLab resources. For example:

```
# star a git repository
project = gl.projects.get(1)
project.star()
```

You can print a Gitlab Object. For example:

```
project = gl.projects.get(1)
print(project)

# Or in a prettier format.
project pprint()

# Or explicitly via `pformat()`. This is equivalent to the above.
print(project.pformat())
```

You can also extend the object if the parameter isn't explicitly listed. For example, if you want to update a field that has been newly introduced to the Gitlab API, setting the value on the object is accepted:

```
issues = project.issues.list(state='opened')
for issue in issues:
    issue.my_super_awesome_feature_flag = "random_value"
    issue.save()
```

You can get a dictionary representation copy of the Gitlab Object. Modifications made to the dictionary will have no impact on the GitLab Object.

- *asdict()* method. Returns a dictionary representation of the Gitlab object.
- *attributes* property. Returns a dictionary representation of the Gitlab object. Also returns any relevant parent object attributes.

Note: *attributes* returns the parent object attributes that are defined in *object._from_parent_attrs*. What this can mean is that for example a *ProjectIssue* object will have a *project_id* key in the dictionary returned from *attributes* but *asdict()* will not.

```
project = gl.projects.get(1)
project_dict = project.asdict()

# Or a dictionary representation also containing some of the parent attributes
issue = project.issues.get(1)
attribute_dict = issue.attributes
```

You can get a JSON string representation of the Gitlab Object. For example:

```
project = gl.projects.get(1)
print(project.to_json())
# Use arguments supported by `json.dump()`
print(project.to_json(sort_keys=True, indent=4))
```

6.2.4 Base types

The gitlab package provides some base types.

- *gitlab.Gitlab* is the primary class, handling the HTTP requests. It holds the GitLab URL and authentication information.
- *gitlab.base.RESTObject* is the base class for all the GitLab v4 objects. These objects provide an abstraction for GitLab resources (projects, groups, and so on).
- *gitlab.base.RESTManager* is the base class for v4 objects managers, providing the API to manipulate the resources and their attributes.

6.2.5 Lazy objects

To avoid useless API calls to the server you can create lazy objects. These objects are created locally using a known ID, and give access to other managers and methods.

The following example will only make one API call to the GitLab server to star a project (the previous example used 2 API calls):

```
# star a git repository
project = gl.projects.get(1, lazy=True) # no API call
project.star() # API call
```

6.2.6 head() methods

All endpoints that support `get()` and `list()` also support a `head()` method. In this case, the server responds only with headers and not the response JSON or body. This allows more efficient API calls, such as checking repository file size without fetching its content.

Note: In some cases, GitLab may omit specific headers. See more in the [Pagination](#) section.

```
# See total number of personal access tokens for current user
gl.personal_access_tokens.head()
print(headers["X-Total"])

# See returned content-type for project GET endpoint
headers = gl.projects.head("gitlab-org/gitlab")
print(headers["Content-Type"])
```

6.2.7 Pagination

You can use pagination to iterate over long lists. All the GitLab objects listing methods support the `page` and `per_page` parameters:

```
ten_first_groups = gl.groups.list(page=1, per_page=10)
```

Warning: The first page is page 1, not page 0.

By default GitLab does not return the complete list of items. Use the `get_all` parameter to get all the items when using listing methods:

```
all_groups = gl.groups.list(get_all=True)

all_owned_projects = gl.projects.list(owned=True, get_all=True)
```

You can define the `per_page` value globally to avoid passing it to every `list()` method call:

```
gl = gitlab.Gitlab(url, token, per_page=50)
```

Gitlab allows to also use keyset pagination. You can supply it to your project listing, but you can also do so globally. Be aware that GitLab then also requires you to only use supported order options. At the time of writing, only `order_by="id"` works.

```
gl = gitlab.Gitlab(url, token, pagination="keyset", order_by="id", per_page=100)
gl.projects.list()
```

Reference: <https://docs.gitlab.com/ce/api/README.html#keyset-based-pagination>

`list()` methods can also return a generator object, by passing the argument `iterator=True`, which will handle the next calls to the API when required. This is the recommended way to iterate through a large number of items:

```
items = gl.groups.list(iterator=True)
for item in items:
    print(item.attributes)
```

The generator exposes extra listing information as received from the server:

- `current_page`: current page number (first page is 1)
- `prev_page`: if `None` the current page is the first one
- `next_page`: if `None` the current page is the last one
- `per_page`: number of items per page
- `total_pages`: total number of pages available. This may be a `None` value.
- `total`: total number of items in the list. This may be a `None` value.

Note: For performance reasons, if a query returns more than 10,000 records, GitLab does not return the `total_pages` or `total` headers. In this case, `total_pages` and `total` will have a value of `None`.

For more information see: https://docs.gitlab.com/ee/user/gitlab_com/index.html#pagination-response-headers

Note: Prior to python-gitlab 3.6.0 the argument `as_list` was used instead of `iterator`. `as_list=False` is the equivalent of `iterator=True`.

6.2.8 Sudo

If you have the administrator status, you can use `sudo` to act as another user. For example:

```
p = gl.projects.create({'name': 'awesome_project'}, sudo='user1')
```

6.2.9 Attributes in updated objects

When methods manipulate an existing object, such as with `refresh()` and `save()`, the object will only have attributes that were returned by the server. In some cases, such as when the initial request fetches attributes that are needed later for additional processing, this may not be desired:

```
project = gl.projects.get(1, statistics=True)
project.statistics

project.refresh()
project.statistics # AttributeError
```

To avoid this, either copy the object/attributes before calling `refresh()/save()` or subsequently perform another `get()` call as needed, to fetch the attributes you want.

6.3 Advanced usage

6.3.1 Using a custom session

`python-gitlab` relies on `requests.Session` objects to perform all the HTTP requests to the Gitlab servers.

You can provide your own `Session` object with custom configuration when you create a `Gitlab` object.

6.3.2 Context manager

You can use `Gitlab` objects as context managers. This makes sure that the `requests.Session` object associated with a `Gitlab` instance is always properly closed when you exit a `with` block:

```
with gitlab.Gitlab(host, token) as gl:
    gl.projects.list()
```

Warning: The context manager will also close the custom `Session` object you might have used to build the `Gitlab` instance.

6.3.3 Proxy configuration

The following sample illustrates how to define a proxy configuration when using `python-gitlab`:

```
import os
import gitlab
import requests

session = requests.Session()
session.proxies = {
    'https': os.environ.get('https_proxy'),
    'http': os.environ.get('http_proxy'),
}
gl = gitlab.gitlab(url, token, api_version=4, session=session)
```

Reference: <https://requests.readthedocs.io/en/latest/user/advanced/#proxies>

6.3.4 SSL certificate verification

python-gitlab relies on the CA certificate bundle in the *certifi* package that comes with the requests library.

If you need python-gitlab to use your system CA store instead, you can provide the path to the CA bundle in the *REQUESTS_CA_BUNDLE* environment variable.

Reference: <https://requests.readthedocs.io/en/latest/user/advanced/#ssl-cert-verification>

6.3.5 Client side certificate

The following sample illustrates how to use a client-side certificate:

```
import gitlab
import requests

session = requests.Session()
session.cert = ('/path/to/client.cert', '/path/to/client.key')
gl = gitlab.gitlab(url, token, api_version=4, session=session)
```

Reference: <https://requests.readthedocs.io/en/latest/user/advanced/#client-side-certificates>

6.3.6 Rate limits

python-gitlab obeys the rate limit of the GitLab server by default. On receiving a 429 response (Too Many Requests), python-gitlab sleeps for the amount of time in the Retry-After header that GitLab sends back. If GitLab does not return a response with the Retry-After header, python-gitlab will perform an exponential backoff.

If you don't want to wait, you can disable the rate-limiting feature, by supplying the *obey_rate_limit* argument.

```
import gitlab
import requests

gl = gitlab.gitlab(url, token, api_version=4)
gl.projects.list(get_all=True, obey_rate_limit=False)
```

If you do not disable the rate-limiting feature, you can supply a custom value for *max_retries*; by default, this is set to 10. To retry without bound when throttled, you can set this parameter to -1. This parameter is ignored if *obey_rate_limit* is set to False.

```
import gitlab
import requests

gl = gitlab.gitlab(url, token, api_version=4)
gl.projects.list(get_all=True, max_retries=12)
```

Warning: You will get an Exception, if you then go over the rate limit of your GitLab instance.

6.3.7 Transient errors

GitLab server can sometimes return a transient HTTP error. python-gitlab can automatically retry in such case, when `retry_transient_errors` argument is set to `True`. When enabled, HTTP error codes 500 (Internal Server Error), 502 (502 Bad Gateway), 503 (Service Unavailable), and 504 (Gateway Timeout) are retried. It will retry until reaching the `max_retries` value. By default, `retry_transient_errors` is set to `False` and an exception is raised for these errors.

```
import gitlab
import requests

gl = gitlab.gitlab(url, token, api_version=4)
gl.projects.list(get_all=True, retry_transient_errors=True)
```

The default `retry_transient_errors` can also be set on the `Gitlab` object and overridden by individual API calls.

```
import gitlab
import requests
gl = gitlab.gitlab(url, token, api_version=4, retry_transient_errors=True)
gl.projects.list(get_all=True) # retries due to default
                             # value
gl.projects.list(get_all=True, retry_transient_errors=False) # does not retry
```

6.3.8 Timeout

python-gitlab will by default use the `timeout` option from its configuration for all requests. This is passed downwards to the `requests` module at the time of making the HTTP request. However if you would like to override the global timeout parameter for a particular call, you can provide the `timeout` parameter to that API invocation:

```
import gitlab

gl = gitlab.gitlab(url, token, api_version=4)
gl.projects.import_github(ACCESS_TOKEN, 123456, "root", timeout=120.0)
```

6.4 CLI examples

See also:

For a complete list of objects and actions available, see [CLI reference \(gitlab command\)](#).

6.4.1 CI Lint

Lint a CI YAML configuration from a string:

Note: To see output, you will need to use the `-v`/`--verbose` flag.

To exit with non-zero on YAML lint failures instead, use the `validate` subcommand shown below.

```
$ gitlab --verbose ci-lint create --content \  
"---  
test:  
  script:  
    - echo hello  
"
```

Lint a CI YAML configuration from a file (see [Reading values from files](#)):

```
$ gitlab --verbose ci-lint create --content @.gitlab-ci.yml
```

Validate a CI YAML configuration from a file (lints and exits with non-zero on failure):

```
$ gitlab ci-lint validate --content @.gitlab-ci.yml
```

Lint a project's CI YAML configuration:

```
$ gitlab --verbose project-ci-lint create --project-id group/my-project --content @.  
~gitlab-ci.yml
```

Validate a project's CI YAML configuration (lints and exits with non-zero on failure):

```
$ gitlab project-ci-lint validate --project-id group/my-project --content @.gitlab-ci.yml
```

Lint a project's current CI YAML configuration:

```
$ gitlab --verbose project-ci-lint get --project-id group/my-project
```

Lint a project's current CI YAML configuration on a specific branch:

```
$ gitlab --verbose project-ci-lint get --project-id group/my-project --ref my-branch
```

6.4.2 Projects

List the projects (paginated):

```
$ gitlab project list
```

List all the projects:

```
$ gitlab project list --get-all
```

List all projects of a group:

```
$ gitlab group-project list --get-all --group-id 1
```

List all projects of a group and its subgroups:

```
$ gitlab group-project list --get-all --include-subgroups true --group-id 1
```

Limit to 5 items per request, display the 1st page only

```
$ gitlab project list --page 1 --per-page 5
```

Get a specific project (id 2):

```
$ gitlab project get --id 2
```

6.4.3 Users

Get a specific user by id:

```
$ gitlab user get --id 3
```

Create a user impersonation token (admin-only):

```
gitlab user-impersonation-token create --user-id 2 --name test-token --scopes api,read_user
```

6.4.4 Deploy tokens

Create a deploy token for a project:

```
$ gitlab -v project-deploy-token create --project-id 2 \
--name bar --username root --expires-at "2021-09-09" --scopes "api,read_repository"
```

List deploy tokens for a group:

```
$ gitlab -v group-deploy-token list --group-id 3
```

6.4.5 Personal access tokens

List the current user's personal access tokens (or all users' tokens, if admin):

```
$ gitlab -v personal-access-token list
```

Revoke a personal access token by id:

```
$ gitlab personal-access-token delete --id 1
```

Revoke the personal access token currently used:

```
$ gitlab personal-access-token delete --id self
```

Create a personal access token for a user (admin only):

```
$ gitlab -v user-personal-access-token create --user-id 2 \
--name personal-access-token --expires-at "2023-01-01" --scopes "api,read_repository"
" "
```

6.4.6 Resource access tokens

Create a project access token:

```
$ gitlab -v project-access-token create --project-id 2 \
--name project-token --expires-at "2023-01-01" --scopes "api,read_repository"
```

List project access tokens:

```
$ gitlab -v project-access-token list --project-id 3
```

Revoke a project access token:

```
$ gitlab project-access-token delete --project-id 3 --id 1
```

Create a group access token:

```
$ gitlab -v group-access-token create --group-id 2 \
--name group-token --expires-at "2022-01-01" --scopes "api,read_repository"
```

List group access tokens:

```
$ gitlab -v group-access-token list --group-id 3
```

Revoke a group access token:

```
$ gitlab group-access-token delete --group-id 3 --id 1
```

6.4.7 Packages

List packages for a project:

```
$ gitlab -v project-package list --project-id 3
```

List packages for a group:

```
$ gitlab -v group-package list --group-id 3
```

Get a specific project package by id:

```
$ gitlab -v project-package get --id 1 --project-id 3
```

Delete a specific project package by id:

```
$ gitlab -v project-package delete --id 1 --project-id 3
```

Upload a generic package to a project:

```
$ gitlab generic-package upload --project-id 1 --package-name hello-world \
--package-version v1.0.0 --file-name hello.tar.gz --path /path/to/hello.tar.gz
```

Download a project's generic package:

```
$ gitlab generic-package download --project-id 1 --package-name hello-world \
--package-version v1.0.0 --file-name hello.tar.gz > /path/to/hello.tar.gz
```

6.4.8 Issues

Get a list of issues for this project:

```
$ gitlab project-issue list --project-id 2
```

6.4.9 Snippets

Delete a snippet (id 3):

```
$ gitlab project-snippet delete --id 3 --project-id 2
```

Update a snippet:

```
$ gitlab project-snippet update --id 4 --project-id 2 \
--code "My New Code"
```

Create a snippet:

```
$ gitlab project-snippet create --project-id 2
Impossible to create object (Missing attribute(s): title, file-name, code)
$ # oops, let's add the attributes:
$ gitlab project-snippet create --project-id 2 --title "the title" \
--file-name "the name" --code "the code"
```

6.4.10 Commits

Get a specific project commit by its SHA id:

```
$ gitlab project-commit get --project-id 2 --id a43290c
```

Get the signature (e.g. GPG or x509) of a signed commit:

```
$ gitlab project-commit signature --project-id 2 --id a43290c
```

Define the status of a commit (as would be done from a CI tool for example):

```
$ gitlab project-commit-status create --project-id 2 \
--commit-id a43290c --state success --name ci/jenkins \
--target-url http://server/build/123 \
--description "Jenkins build succeeded"
```

Get the merge base for two or more branches, tags or commits:

```
gitlab project repository-merge-base --id 1 --refs bd1324e2f,main,v1.0.0
```

6.4.11 Artifacts

Download the artifacts zip archive of a job:

```
$ gitlab project-job artifacts --id 10 --project-id 1 > artifacts.zip
```

6.4.12 Runners

List owned runners:

```
$ gitlab runner list
```

List owned runners with a filter:

```
$ gitlab runner list --scope active
```

List all runners in the GitLab instance (specific and shared):

```
$ gitlab runner-all list
```

Get a runner's details:

```
$ gitlab -v runner get --id 123
```

6.4.13 Other

Use sudo to act as another user (admin only):

```
$ gitlab project create --name user_project1 --sudo username
```

List values are comma-separated:

```
$ gitlab issue list --labels foo,bar
```

6.5 API examples

6.5.1 Access requests

Users can request access to groups and projects.

When access is granted the user should be given a numerical access level. The following constants are provided to represent the access levels:

- `gitlab.const.AccessLevel.GUEST: 10`
- `gitlab.const.AccessLevel.REPORTER: 20`
- `gitlab.const.AccessLevel.DEVELOPER: 30`
- `gitlab.const.AccessLevel.MAINTAINER: 40`
- `gitlab.const.AccessLevel.OWNER: 50`

References

- v4 API:
 - `gitlab.v4.objects.ProjectAccessRequest`
 - `gitlab.v4.objects.ProjectAccessRequestManager`
 - `gitlab.v4.objects.Project.accessrequests`
 - `gitlab.v4.objects.GroupAccessRequest`
 - `gitlab.v4.objects.GroupAccessRequestManager`
 - `gitlab.v4.objects.Group.accessrequests`
- GitLab API: https://docs.gitlab.com/ce/api/access_requests.html

Examples

List access requests from projects and groups:

```
p_ars = project.accessrequests.list()
g_ars = group.accessrequests.list()
```

Create an access request:

```
p_ar = project.accessrequests.create()
g_ar = group.accessrequests.create()
```

Approve an access request:

```
ar.approve()  # defaults to DEVELOPER level
ar.approve(access_level=gitlab.const.AccessLevel.MAINTAINER)  # explicitly set access_level
```

Deny (delete) an access request:

```
project.accessrequests.delete(user_id)
group.accessrequests.delete(user_id)
# or
ar.delete()
```

6.5.2 Appearance

Reference

- v4 API:
 - `gitlab.v4.objects.ApplicationAppearance`
 - `gitlab.v4.objects.ApplicationAppearanceManager`
 - `gitlab.Gitlab.appearance`
- GitLab API: <https://docs.gitlab.com/ce/api/appearance.html>

Examples

Get the appearance:

```
appearance = gl.appearance.get()
```

Update the appearance:

```
appearance.title = "Test"  
appearance.save()
```

6.5.3 Applications

Reference

- v4 API:
 - `gitlab.v4.objects.Applications`
 - `gitlab.v4.objects.ApplicationManager`
 - `gitlab.Gitlab.applications`
- GitLab API: <https://docs.gitlab.com/ce/api/applications.html>

Examples

List all OAuth applications:

```
applications = gl.applications.list()
```

Create an application:

```
gl.applications.create({'name': 'your_app', 'redirect_uri': 'http://application.url',  
    ↪'scopes': 'read_user openid profile email'})
```

Delete an application:

```
gl.applications.delete(app_id)  
# or  
application.delete()
```

6.5.4 Award Emojis

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssueAwardEmoji`
 - `gitlab.v4.objects.ProjectIssueNoteAwardEmoji`
 - `gitlab.v4.objects.ProjectMergeRequestAwardEmoji`
 - `gitlab.v4.objects.ProjectMergeRequestNoteAwardEmoji`

- `gitlab.v4.objects.ProjectSnippetAwardEmoji`
 - `gitlab.v4.objects.ProjectSnippetNoteAwardEmoji`
 - `gitlab.v4.objects.ProjectIssueAwardEmojiManager`
 - `gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager`
 - `gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager`
 - `gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager`
 - `gitlab.v4.objects.ProjectSnippetAwardEmojiManager`
 - `gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager`
- GitLab API: https://docs.gitlab.com/ce/api/award_emoji.html

Examples

List emojis for a resource:

```
emojis = obj.awardemojis.list()
```

Get a single emoji:

```
emoji = obj.awardemojis.get(emoji_id)
```

Add (create) an emoji:

```
emoji = obj.awardemojis.create({'name': 'tractor'})
```

Delete an emoji:

```
emoji.delete
# or
obj.awardemojis.delete(emoji_id)
```

6.5.5 Badges

Badges can be associated with groups and projects.

Reference

- v4 API:
 - `gitlab.v4.objects.GroupBadge`
 - `gitlab.v4.objects.GroupBadgeManager`
 - `gitlab.v4.objects.Group.badges`
 - `gitlab.v4.objects.ProjectBadge`
 - `gitlab.v4.objects.ProjectBadgeManager`
 - `gitlab.v4.objects.Project.badges`
- GitLab API:
 -

- https://docs.gitlab.com/ce/api/group_badges.html
- https://docs.gitlab.com/ce/api/project_badges.html

Examples

List badges:

```
badges = group_or_project.badges.list()
```

Get a badge:

```
badge = group_or_project.badges.get(badge_id)
```

Create a badge:

```
badge = group_or_project.badges.create({'link_url': link, 'image_url': image_link})
```

Update a badge:

```
badge.image_link = new_link  
badge.save()
```

Delete a badge:

```
badge.delete()
```

Render a badge (preview the generate URLs):

```
output = group_or_project.badges.render(link, image_link)  
print(output['rendered_link_url'])  
print(output['rendered_image_url'])
```

6.5.6 Branches

References

- v4 API:
 - *gitlab.v4.objects.ProjectBranch*
 - *gitlab.v4.objects.ProjectBranchManager*
 - *gitlab.v4.objects.Project.branches*
- GitLab API: <https://docs.gitlab.com/ce/api/branches.html>

Examples

Get the list of branches for a repository:

```
branches = project.branches.list()
```

Get a single repository branch:

```
branch = project.branches.get('main')
```

Create a repository branch:

```
branch = project.branches.create({'branch': 'feature1',
                                  'ref': 'main'})
```

Delete a repository branch:

```
project.branches.delete('feature1')
# or
branch.delete()
```

Delete the merged branches for a project:

```
project.delete_merged_branches()
```

To manage protected branches, see [Protected branches](#).

6.5.7 Broadcast messages

You can use broadcast messages to display information on all pages of the gitlab web UI. You must have administration permissions to manipulate broadcast messages.

References

- v4 API:
 - `gitlab.v4.objects.BroadcastMessage`
 - `gitlab.v4.objects.BroadcastMessageManager`
 - `gitlab.Gitlab.broadcastmessages`
- GitLab API: https://docs.gitlab.com/ce/api/broadcast_messages.html

Examples

List the messages:

```
msgs = gl.broadcastmessages.list()
```

Get a single message:

```
msg = gl.broadcastmessages.get(msg_id)
```

Create a message:

```
msg = gl.broadcastmessages.create({'message': 'Important information'})
```

The date format for the `starts_at` and `ends_at` parameters is `YYYY-MM-ddThh:mm:ssZ`.

Update a message:

```
msg.font = '#444444'  
msg.color = '#999999'  
msg.save()
```

Delete a message:

```
gl.broadcastmessages.delete(msg_id)  
# or  
msg.delete()
```

6.5.8 CI Lint

Reference

- v4 API:
 - `gitlab.v4.objects.CiLint`
 - `gitlab.v4.objects.CiLintManager`
 - `gitlab.Gitlab.ci_lint`
 - `gitlab.v4.objects.ProjectCiLint`
 - `gitlab.v4.objects.ProjectCiLintManager`
 - `gitlab.v4.objects.Project.ci_lint`
- GitLab API: <https://docs.gitlab.com/ee/api/lint.html>

Examples

Lint a CI YAML configuration:

```
gitlab_ci_yml = """ .api_test:  
    rules:  
      - if: $CI_PIPELINE_SOURCE=="merge_request_event"  
        changes:  
          - src/api/*  
  deploy:  
    extends:  
      - .api_test  
    rules:  
      - when: manual  
        allow_failure: true  
    script:  
      - echo "hello world"  
"""  
  
lint_result = gl.ci_lint.create({"content": gitlab_ci_yml})
```

(continues on next page)

(continued from previous page)

```
print(lint_result.status) # Print the status of the CI YAML
print(lint_result.merged_yaml) # Print the merged YAML file
```

Lint a project's CI configuration:

```
lint_result = project.ci_lint.get()
assert lint_result.valid is True # Test that the .gitlab-ci.yml is valid
print(lint_result.merged_yaml) # Print the merged YAML file
```

Lint a CI YAML configuration with a namespace:

```
lint_result = project.ci_lint.create({"content": gitlab_ci_yml})
assert lint_result.valid is True # Test that the .gitlab-ci.yml is valid
print(lint_result.merged_yaml) # Print the merged YAML file
```

Validate a CI YAML configuration (raises `GitlabCiLintError` on failures):

```
# returns None
gl.ci_lint.validate({"content": gitlab_ci_yml})

# raises GitlabCiLintError
gl.ci_lint.validate({"content": "invalid"})
```

Validate a CI YAML configuration with a namespace:

```
# returns None
project.ci_lint.validate({"content": gitlab_ci_yml})

# raises GitlabCiLintError
project.ci_lint.validate({"content": "invalid"})
```

6.5.9 Commits

Commits

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCommit`
 - `gitlab.v4.objects.ProjectCommitManager`
 - `gitlab.v4.objects.Project.commits`

Examples

List the commits for a project:

```
commits = project.commits.list()
```

You can use the `ref_name`, `since` and `until` filters to limit the results:

```
commits = project.commits.list(ref_name='my_branch')
commits = project.commits.list(since='2016-01-01T00:00:00Z')
```

List all commits for a project (see [Pagination](#)) on all branches:

```
commits = project.commits.list(get_all=True, all=True)
```

Create a commit:

```
# See https://docs.gitlab.com/ce/api/commits.html#create-a-commit-with-multiple-files-and-actions
# for actions detail
data = {
    'branch': 'main',
    'commit_message': 'blah blah blah',
    'actions': [
        {
            'action': 'create',
            'file_path': 'README.rst',
            'content': open('path/to/file.rst').read(),
        },
        {
            # Binary files need to be base64 encoded
            'action': 'create',
            'file_path': 'logo.png',
            'content': base64.b64encode(open('logo.png').read()),
            'encoding': 'base64',
        }
    ]
}

commit = project.commits.create(data)
```

Get a commit detail:

```
commit = project.commits.get('e3d5a71b')
```

Get the diff for a commit:

```
diff = commit.diff()
```

Cherry-pick a commit into another branch:

```
commit.cherry_pick(branch='target_branch')
```

Revert a commit on a given branch:

```
commit.revert(branch='target_branch')
```

Get the references the commit has been pushed to (branches and tags):

```
commit.refs()  # all references
commit.refs('tag') # only tags
commit.refs('branch') # only branches
```

Get the signature of the commit (if the commit was signed, e.g. with GPG or x509):

```
commit.signature()
```

List the merge requests related to a commit:

```
commit.merge_requests()
```

Commit comments

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCommitComment`
 - `gitlab.v4.objects.ProjectCommitCommentManager`
 - `gitlab.v4.objects.ProjectCommit.comments`
- GitLab API: <https://docs.gitlab.com/ce/api/commits.html>

Examples

Get the comments for a commit:

```
comments = commit.comments.list()
```

Add a comment on a commit:

```
# Global comment
commit = commit.comments.create({'note': 'This is a nice comment'})
# Comment on a line in a file (on the new version of the file)
commit = commit.comments.create({'note': 'This is another comment',
                                'line': 12,
                                'line_type': 'new',
                                'path': 'README.rst'})
```

Commit status

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCommitStatus`
 - `gitlab.v4.objects.ProjectCommitStatusManager`
 - `gitlab.v4.objects.ProjectCommit.statuses`
- GitLab API: <https://docs.gitlab.com/ce/api/commits.html>

Examples

List the statuses for a commit:

```
statuses = commit.statuses.list()
```

Change the status of a commit:

```
commit.statuses.create({'state': 'success'})
```

6.5.10 Deploy keys

Deploy keys

Reference

- v4 API:
 - `gitlab.v4.objects.DeployKey`
 - `gitlab.v4.objects.DeployKeyManager`
 - `gitlab.Gitlab.deploykeys`
- GitLab API: https://docs.gitlab.com/ce/api/deploy_keys.html

Examples

List the deploy keys:

```
keys = gl.deploykeys.list()
```

Deploy keys for projects

Deploy keys can be managed on a per-project basis.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectKey`
 - `gitlab.v4.objects.ProjectKeyManager`
 - `gitlab.v4.objects.Project.keys`
- GitLab API: https://docs.gitlab.com/ce/api/deploy_keys.html

Examples

List keys for a project:

```
keys = project.keys.list()
```

Get a single deploy key:

```
key = project.keys.get(key_id)
```

Create a deploy key for a project:

```
key = project.keys.create({'title': 'jenkins key',
                           'key': open('/home/me/.ssh/id_rsa.pub').read()})
```

Delete a deploy key for a project:

```
key = project.keys.list(key_id)
# or
key.delete()
```

Enable a deploy key for a project:

```
project.keys.enable(key_id)
```

Disable a deploy key for a project:

```
project.keys.delete(key_id)
```

6.5.11 Deploy tokens

Deploy tokens allow read-only access to your repository and registry images without having a user and a password.

Deploy tokens

This endpoint requires admin access.

Reference

- v4 API:
 - `gitlab.v4.objects.DeployToken`
 - `gitlab.v4.objects.DeployTokenManager`
 - `gitlab.Gitlab.deploytokens`
- GitLab API: https://docs.gitlab.com/ce/api/deploy_tokens.html

Examples

Use the `list()` method to list all deploy tokens across the GitLab instance.

```
# List deploy tokens
deploy_tokens = gl.deploytokens.list()
```

Project deploy tokens

This endpoint requires project maintainer access or higher.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectDeployToken`
 - `gitlab.v4.objects.ProjectDeployTokenManager`
 - `gitlab.v4.objects.Project.deploytokens`
- GitLab API: https://docs.gitlab.com/ce/api/deploy_tokens.html#project-deploy-tokens

Examples

List the deploy tokens for a project:

```
deploy_tokens = project.deploytokens.list()
```

Get a deploy token for a project by id:

```
deploy_token = project.deploytokens.get(deploy_token_id)
```

Create a new deploy token to access registry images of a project:

In addition to required parameters `name` and `scopes`, this method accepts the following parameters:

- `expires_at` Expiration date of the deploy token. Does not expire if no value is provided.
- `username` Username for deploy token. Default is `gitlab+deploy-token-{n}`

```
deploy_token = project.deploytokens.create({'name': 'token1', 'scopes': ['read_registry'
    ↴'], 'username': '', 'expires_at': ''})
# show its id
print(deploy_token.id)
# show the token value. Make sure you save it, you won't be able to access it again.
print(deploy_token.token)
```

Warning: With GitLab 12.9, even though `username` and `expires_at` are not required, they always have to be passed to the API. You can set them to empty strings, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211878>. Also, the `username`'s value is ignored by the API and will be overridden with `gitlab+deploy-token-{n}`, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211963> These issues were fixed in GitLab 12.10.

Remove a deploy token from the project:

```
deploy_token.delete()
# or
project.deploytokens.delete(deploy_token.id)
```

Group deploy tokens

Reference

- v4 API:
 - `gitlab.v4.objects.GroupDeployToken`
 - `gitlab.v4.objects.GroupDeployTokenManager`
 - `gitlab.v4.objects.Group.deploytokens`
- GitLab API: https://docs.gitlab.com/ce/api/deploy_tokens.html#group-deploy-tokens

Examples

List the deploy tokens for a group:

```
deploy_tokens = group.deploytokens.list()
```

Get a deploy token for a group by id:

```
deploy_token = group.deploytokens.get(deploy_token_id)
```

Create a new deploy token to access all repositories of all projects in a group:

In addition to required parameters `name` and `scopes`, this method accepts the following parameters:

- `expires_at` Expiration date of the deploy token. Does not expire if no value is provided.
- `username` Username for deploy token. Default is `gitlab+deploy-token-{n}`

```
deploy_token = group.deploytokens.create({'name': 'token1', 'scopes': ['read_repository'
    ↴'], 'username': '', 'expires_at': ''})
# show its id
print(deploy_token.id)
```

Warning: With GitLab 12.9, even though `username` and `expires_at` are not required, they always have to be passed to the API. You can set them to empty strings, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211878>. Also, the `username`'s value is ignored by the API and will be overridden with `gitlab+deploy-token-{n}`, see: <https://gitlab.com/gitlab-org/gitlab/-/issues/211963> These issues were fixed in GitLab 12.10.

Remove a deploy token from the group:

```
deploy_token.delete()
# or
group.deploytokens.delete(deploy_token.id)
```

6.5.12 Deployments

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectDeployment`
 - `gitlab.v4.objects.ProjectDeploymentManager`
 - `gitlab.v4.objects.Project.deployments`
- GitLab API: <https://docs.gitlab.com/ce/api/deployments.html>

Examples

List deployments for a project:

```
deployments = project.deployments.list()
```

Get a single deployment:

```
deployment = project.deployments.get(deployment_id)
```

Create a new deployment:

```
deployment = project.deployments.create({
    "environment": "Test",
    "sha": "1agf4gs",
    "ref": "main",
    "tag": False,
    "status": "created",
})
```

Update a deployment:

```
deployment = project.deployments.get(42)
deployment.status = "failed"
deployment.save()
```

Approve a deployment:

```
deployment = project.deployments.get(42)
# `status` must be either "approved" or "rejected".
deployment.approval(status="approved")
```

Reject a deployment:

```
deployment = project.deployments.get(42)
# Using the optional `comment` and `represented_as` arguments
deployment.approval(status="rejected", comment="Fails CI", represented_as="security")
```

Merge requests associated with a deployment

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectDeploymentMergeRequest`
 - `gitlab.v4.objects.ProjectDeploymentMergeRequestManager`
 - `gitlab.v4.objects.ProjectDeployment.mergerequests`
- GitLab API: <https://docs.gitlab.com/ee/api/deployments.html#list-of-merge-requests-associated-with-a-deployment>

Examples

List the merge requests associated with a deployment:

```
deployment = project.deployments.get(42, lazy=True)
mrs = deployment.mergerequests.list()
```

6.5.13 Discussions

Discussions organize the notes in threads. See the [Notes](#) chapter for more information about notes.

Discussions are available for project issues, merge requests, snippets and commits.

Reference

- v4 API:

Issues:

- *gitlab.v4.objects.ProjectIssueDiscussion*
- *gitlab.v4.objects.ProjectIssueDiscussionManager*
- *gitlab.v4.objects.ProjectIssueDiscussionNote*
- *gitlab.v4.objects.ProjectIssueDiscussionNoteManager*
- *gitlab.v4.objects.ProjectIssue.notes*

MergeRequests:

- *gitlab.v4.objects.ProjectMergeRequestDiscussion*
- *gitlab.v4.objects.ProjectMergeRequestDiscussionManager*
- *gitlab.v4.objects.ProjectMergeRequestDiscussionNote*
- *gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager*
- *gitlab.v4.objects.ProjectMergeRequest.notes*

Snippets:

- *gitlab.v4.objects.ProjectSnippetDiscussion*
- *gitlab.v4.objects.ProjectSnippetDiscussionManager*
- *gitlab.v4.objects.ProjectSnippetDiscussionNote*
- *gitlab.v4.objects.ProjectSnippetDiscussionNoteManager*
- *gitlab.v4.objects.ProjectSnippet.notes*

- GitLab API: <https://docs.gitlab.com/ce/api/discussions.html>

Examples

List the discussions for a resource (issue, merge request, snippet or commit):

```
discussions = resource.discussions.list()
```

Get a single discussion:

```
discussion = resource.discussions.get(discussion_id)
```

You can access the individual notes in the discussion through the `notes` attribute. It holds a list of notes in chronological order:

```
# ``resource.notes`` is a DiscussionNoteManager, so we need to get the
# object notes using ``attributes``
for note in discussion.attributes['notes']:
    print(note['body'])
```

Note: The notes are dicts, not objects.

You can add notes to existing discussions:

```
new_note = discussion.notes.create({'body': 'Episode IV: A new note'})
```

You can get and update a single note using the *DiscussionNote resources:

```
discussion = resource.discussions.get(discussion_id)
# Get the latest note's id
note_id = discussion.attributes['notes'][ -1 ]['id']
last_note = discussion.notes.get(note_id)
last_note.body = 'Updated comment'
last_note.save()
```

Create a new discussion:

```
discussion = resource.discussions.create({'body': 'First comment of discussion'})
```

You can comment on merge requests and commit diffs. Provide the `position` dict to define where the comment should appear in the diff:

```
mr_diff = mr.diffs.get(diff_id)
mr.discussions.create({'body': 'Note content',
                      'position': {
                          'base_sha': mr_diff.base_commit_sha,
                          'start_sha': mr_diff.start_commit_sha,
                          'head_sha': mr_diff.head_commit_sha,
                          'position_type': 'text',
                          'new_line': 1,
                          'old_path': 'README.rst',
                          'new_path': 'README.rst'}}
```

Resolve / unresolve a merge request discussion:

```
mr_d = mr.discussions.get(d_id)
mr_d.resolved = True # True to resolve, False to unresolve
mr_d.save()
```

Delete a comment:

```
discussions.notes.delete(note_id)
# or
note.delete()
```

6.5.14 Environments

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectEnvironment`
 - `gitlab.v4.objects.ProjectEnvironmentManager`
 - `gitlab.v4.objects.Project.environments`
- GitLab API: <https://docs.gitlab.com/ce/api/environments.html>

Examples

List environments for a project:

```
environments = project.environments.list()
```

Create an environment for a project:

```
environment = project.environments.create({'name': 'production'})
```

Retrieve a specific environment for a project:

```
environment = project.environments.get(112)
```

Update an environment for a project:

```
environment.external_url = 'http://foo.bar.com'
environment.save()
```

Delete an environment for a project:

```
environment = project.environments.delete(environment_id)
# or
environment.delete()
```

Stop an environment:

```
environment.stop()
```

To manage protected environments, see [Protected environments](#).

6.5.15 Events

Events

Reference

- v4 API:
 - `gitlab.v4.objects.Event`
 - `gitlab.v4.objects.EventManager`
 - `gitlab.Gitlab.events`
 - `gitlab.v4.objects.ProjectEvent`
 - `gitlab.v4.objects.ProjectEventManager`
 - `gitlab.v4.objects.Project.events`
 - `gitlab.v4.objects.UserEvent`
 - `gitlab.v4.objects.UserEventManager`
 - `gitlab.v4.objects.User.events`
- GitLab API: <https://docs.gitlab.com/ce/api/events.html>

Examples

You can list events for an entire Gitlab instance (admin), users and projects. You can filter you events you want to retrieve using the `action` and `target_type` attributes. The possible values for these attributes are available on [the gitlab documentation](#).

List all the events (paginated):

```
events = gl.events.list()
```

List the issue events on a project:

```
events = project.events.list(target_type='issue')
```

List the user events:

```
events = project.events.list()
```

Resource state events

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssueResourceStateEvent`
 - `gitlab.v4.objects.ProjectIssueResourceEventManager`
 - `gitlab.v4.objects.ProjectIssue.resourcestateevents`
 - `gitlab.v4.objects.ProjectMergeRequestResourceStateEvent`

- *gitlab.v4.objects.ProjectMergeRequestResourceStateEventManager*
- *gitlab.v4.objects.ProjectMergeRequest.resourcestateevents*
- GitLab API: https://docs.gitlab.com/ee/api/resource_state_events.html

Examples

You can list and get specific resource state events (via their id) for project issues and project merge requests.

List the state events of a project issue (paginated):

```
state_events = issue.resourcestateevents.list()
```

Get a specific state event of a project issue by its id:

```
state_event = issue.resourcestateevents.get(1)
```

List the state events of a project merge request (paginated):

```
state_events = mr.resourcestateevents.list()
```

Get a specific state event of a project merge request by its id:

```
state_event = mr.resourcestateevents.get(1)
```

6.5.16 Epics

Epics

Reference

- v4 API:
 - *gitlab.v4.objects.GroupEpic*
 - *gitlab.v4.objects.GroupEpicManager*
 - *gitlab.Gitlab.Group.epics*
- GitLab API: <https://docs.gitlab.com/ee/api/epics.html> (EE feature)

Examples

List the epics for a group:

```
epics = groups.epics.list()
```

Get a single epic for a group:

```
epic = group.epics.get(epic_iid)
```

Create an epic for a group:

```
epic = group.epics.create({'title': 'My Epic'})
```

Edit an epic:

```
epic.title = 'New title'
epic.labels = ['label1', 'label2']
epic.save()
```

Delete an epic:

```
epic.delete()
```

Epics issues

Reference

- v4 API:
 - `gitlab.v4.objects.GroupEpicIssue`
 - `gitlab.v4.objects.GroupEpicIssueManager`
 - `gitlab.Gitlab.GroupEpic.issues`
- GitLab API: https://docs.gitlab.com/ee/api/epic_issues.html (EE feature)

Examples

List the issues associated with an issue:

```
ei = epic.issues.list()
```

Associate an issue with an epic:

```
# use the issue id, not its iid
ei = epic.issues.create({'issue_id': 4})
```

Move an issue in the list:

```
ei.move_before_id = epic_issue_id_1
# or
ei.move_after_id = epic_issue_id_2
ei.save()
```

Delete an issue association:

```
ei.delete()
```

6.5.17 Features flags

Reference

- v4 API:
 - `gitlab.v4.objects.Feature`
 - `gitlab.v4.objects.FeatureManager`
 - `gitlab.Gitlab.features`
- GitLab API: <https://docs.gitlab.com/ce/api/features.html>

Examples

List features:

```
features = gl.features.list()
```

Create or set a feature:

```
feature = gl.features.set(feature_name, True)
feature = gl.features.set(feature_name, 30)
feature = gl.features.set(feature_name, True, user=filipowm)
feature = gl.features.set(feature_name, 40, group=mygroup)
```

Delete a feature:

```
feature.delete()
```

6.5.18 Geo nodes

Reference

- v4 API:
 - `gitlab.v4.objects.GeoNode`
 - `gitlab.v4.objects.GeoNodeManager`
 - `gitlab.Gitlab.geonodes`
- GitLab API: https://docs.gitlab.com/ee/api/geo_nodes.html (EE feature)

Examples

List the geo nodes:

```
nodes = gl.geonodes.list()
```

Get the status of all the nodes:

```
status = gl.geonodes.status()
```

Get a specific node and its status:

```
node = gl.geonodes.get(node_id)
node.status()
```

Edit a node configuration:

```
node.url = 'https://secondary.mygitlab.domain'
node.save()
```

Delete a node:

```
node.delete()
```

List the sync failure on the current node:

```
failures = gl.geonodes.current_failures()
```

6.5.19 Groups

Groups

Reference

- v4 API:
 - `gitlab.v4.objects.Group`
 - `gitlab.v4.objects.GroupManager`
 - `gitlab.Gitlab.groups`
- GitLab API: <https://docs.gitlab.com/ce/api/groups.html>

Examples

List the groups:

```
groups = gl.groups.list()
```

Get a group's detail:

```
group = gl.groups.get(group_id)
```

List a group's projects:

```
projects = group.projects.list()
```

List a group's shared projects:

```
projects = group.shared_projects.list()
```

Note: `GroupProject` and `SharedProject` objects returned by these two API calls are very limited, and do not provide all the features of `Project` objects. If you need to manipulate projects, create a new `Project` object:

```
first_group_project = group.projects.list()[0]
manageable_project = gl.projects.get(first_group_project.id, lazy=True)
```

You can filter and sort the result using the following parameters:

- `archived`: limit by archived status
- `visibility`: limit by visibility. Allowed values are `public`, `internal` and `private`
- `search`: limit to groups matching the given value
- `order_by`: sort by criteria. Allowed values are `id`, `name`, `path`, `created_at`, `updated_at` and `last_activity_at`
- `sort`: sort order: `asc` or `desc`
- `ci_enabled_first`: return CI enabled groups first
- `include_subgroups`: include projects in subgroups

Create a group:

```
group = gl.groups.create({'name': 'group1', 'path': 'group1'})
```

Create a subgroup under an existing group:

```
subgroup = gl.groups.create({'name': 'subgroup1', 'path': 'subgroup1', 'parent_id': parent_group_id})
```

Update a group:

```
group.description = 'My awesome group'
group.save()
```

Set the avatar image for a group:

```
# the avatar image can be passed as data (content of the file) or as a file
# object opened in binary mode
group.avatar = open('path/to/file.png', 'rb')
group.save()
```

Remove a group:

```
gl.groups.delete(group_id)
# or
group.delete()
```

Share/unshare the group with a group:

```
group.share(group2.id, gitlab.const.AccessLevel.DEVELOPER)
group.unshare(group2.id)
```

Import / Export

You can export groups from gitlab, and re-import them to create new groups.

Reference

- v4 API:
 - `gitlab.v4.objects.GroupExport`
 - `gitlab.v4.objects.GroupExportManager`
 - `gitlab.v4.objects.Group.exports`
 - `gitlab.v4.objects.GroupImport`
 - `gitlab.v4.objects.GroupImportManager`
 - `gitlab.v4.objects.Group.imports`
 - `gitlab.v4.objects.GroupManager.import_group`
- GitLab API: https://docs.gitlab.com/ce/api/group_import_export.html

Examples

A group export is an asynchronous operation. To retrieve the archive generated by GitLab you need to:

1. Create an export using the API
2. Wait for the export to be done
3. Download the result

Warning: Unlike the Project Export API, GitLab does not provide an `export_status` for Group Exports. It is up to the user to ensure the export is finished.

However, Group Exports only contain metadata, so they are much faster than Project Exports.

```
# Create the export
group = gl.groups.get(my_group)
export = group.exports.create()

# Wait for the export to finish
time.sleep(3)

# Download the result
with open('/tmp/export.tgz', 'wb') as f:
    export.download(streamed=True, action=f.write)
```

Import the group:

```
with open('/tmp/export.tgz', 'rb') as f:
    gl.groups.import_group(f, path='imported-group', name="Imported Group")
```

Subgroups

Reference

- v4 API:
 - `gitlab.v4.objects.GroupSubgroup`
 - `gitlab.v4.objects.GroupSubgroupManager`
 - `gitlab.v4.objects.Group.subgroups`

Examples

List the subgroups for a group:

```
subgroups = group.subgroups.list()
```

Note: The GroupSubgroup objects don't expose the same API as the Group objects. If you need to manipulate a subgroup as a group, create a new Group object:

```
real_group = gl.groups.get(subgroup_id, lazy=True)
real_group.issues.list()
```

Descendant Groups

Reference

- v4 API:
 - `gitlab.v4.objects.GroupDescendantGroup`
 - `gitlab.v4.objects.GroupDescendantGroupManager`
 - `gitlab.v4.objects.Group.descendant_groups`

Examples

List the descendant groups of a group:

```
descendant_groups = group.descendant_groups.list()
```

Note: Like the GroupSubgroup objects described above, GroupDescendantGroup objects do not expose the same API as the Group objects. Create a new Group object instead if needed, as shown in the subgroup example.

Group custom attributes

Reference

- v4 API:
 - `gitlab.v4.objects.GroupCustomAttribute`
 - `gitlab.v4.objects.GroupCustomAttributeManager`
 - `gitlab.v4.objects.Group.customattributes`
- GitLab API: https://docs.gitlab.com/ce/api/custom_attributes.html

Examples

List custom attributes for a group:

```
attrs = group.customattributes.list()
```

Get a custom attribute for a group:

```
attr = group.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a group:

```
attr = group.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a group:

```
attr.delete()
# or
group.customattributes.delete(attr_key)
```

Search groups by custom attribute:

```
group.customattributes.set('role': 'admin')
gl.groups.list(custom_attributes={'role': 'admin'})
```

Group members

The following constants define the supported access levels:

- `gitlab.const.AccessLevel.GUEST = 10`
- `gitlab.const.AccessLevel.REPORTER = 20`
- `gitlab.const.AccessLevel.DEVELOPER = 30`
- `gitlab.const.AccessLevel.MAINTAINER = 40`
- `gitlab.const.AccessLevel.OWNER = 50`

Reference

- v4 API:
 - `gitlab.v4.objects.GroupMember`
 - `gitlab.v4.objects.GroupMemberManager`
 - `gitlab.v4.objects.GroupMemberAllManager`
 - `gitlab.v4.objects.GroupBillableMember`
 - `gitlab.v4.objects.GroupBillableMemberManager`
 - `gitlab.v4.objects.Group.members`
 - `gitlab.v4.objects.Group.members_all`
 - `gitlab.v4.objects.Group.billable_members`
- GitLab API: <https://docs.gitlab.com/ce/api/members.html>

Billable group members are only available in GitLab EE.

Examples

List only direct group members:

```
members = group.members.list()
```

List the group members recursively (including inherited members through ancestor groups):

```
members = group.members_all.list(get_all=True)
```

Get only direct group member:

```
members = group.members.get(member_id)
```

Get a member of a group, including members inherited through ancestor groups:

```
members = group.members_all.get(member_id)
```

Add a member to the group:

```
member = group.members.create({'user_id': user_id,
                               'access_level': gitlab.const.AccessLevel.GUEST})
```

Update a member (change the access level):

```
member.access_level = gitlab.const.AccessLevel.DEVELOPER
member.save()
```

Remove a member from the group:

```
group.members.delete(member_id)
# or
member.delete()
```

List billable members of a group (top-level groups only):

```
billable_members = group.billable_members.list()
```

Remove a billable member from the group:

```
group.billable_members.delete(member_id)
# or
billable_member.delete()
```

List memberships of a billable member:

```
billable_member.memberships.list()
```

LDAP group links

Add an LDAP group link to an existing GitLab group:

```
group.add_ldap_group_link(ldap_group_cn, gitlab.const.AccessLevel.DEVELOPER, 'ldapmain')
```

Remove a link:

```
group.delete_ldap_group_link(ldap_group_cn, 'ldapmain')
```

Sync the LDAP groups:

```
group.ldap_sync()
```

You can use the `ldapgroups` manager to list available LDAP groups:

```
# listing (supports pagination)
ldap_groups = gl.ldapgroups.list()

# filter using a group name
ldap_groups = gl.ldapgroups.list(search='foo')

# list the groups for a specific LDAP provider
ldap_groups = gl.ldapgroups.list(search='foo', provider='ldapmain')
```

Groups hooks

Reference

- v4 API:
 - `gitlab.v4.objects.GroupHook`
 - `gitlab.v4.objects.GroupHookManager`
 - `gitlab.v4.objects.Group.hooks`
- GitLab API: <https://docs.gitlab.com/ce/api/groups.html#hooks>

Examples

List the group hooks:

```
hooks = group.hooks.list()
```

Get a group hook:

```
hook = group.hooks.get(hook_id)
```

Create a group hook:

```
hook = group.hooks.create({'url': 'http://my/action/url', 'push_events': 1})
```

Update a group hook:

```
hook.push_events = 0  
hook.save()
```

Delete a group hook:

```
group.hooks.delete(hook_id)  
# or  
hook.delete()
```

Group push rules

Reference

- v4 API:
 - `gitlab.v4.objects.GroupPushRules`
 - `gitlab.v4.objects.GroupPushRulesManager`
 - `gitlab.v4.objects.Group.pushrules`
- GitLab API: <https://docs.gitlab.com/ee/api/groups.html#push-rules>

Examples

Create group push rules (at least one rule is necessary):

```
group.pushrules.create({'deny_delete_tag': True})
```

Get group push rules (returns None if there are no push rules):

```
pr = group.pushrules.get()
```

Edit group push rules:

```
pr.branch_name_regex = '^((master|develop|support-\d+|release-\d+\.\+\.|hotfix-\.\+|feature-\.\+|)\+\+)\$'  
pr.save()
```

Delete group push rules:

```
pr.delete()
```

6.5.20 Group Access Tokens

Get a list of group access tokens

References

- v4 API:
 - `gitlab.v4.objects.GroupAccessToken`
 - `gitlab.v4.objects.GroupAccessTokenManager`
 - `gitlab.Gitlab.group_access_tokens`
- GitLab API: https://docs.gitlab.com/ee/api/group_access_tokens.html

Examples

List group access tokens:

```
access_tokens = gl.groups.get(1, lazy=True).access_tokens.list()
print(access_tokens[0].name)
```

Create group access token:

```
access_token = gl.groups.get(1).access_tokens.create({"name": "test", "scopes": ["api"]})
```

Revoke a group access tokens:

```
gl.groups.get(1).access_tokens.delete(42)
# or
access_token.delete()
```

6.5.21 Invitations

Invitations let you invite or add users to a group or project.

Reference

- v4 API:
 - `gitlab.v4.objects.GroupInvitation`
 - `gitlab.v4.objects.GroupInvitationManager`
 - `gitlab.v4.objects.Group.invitations`
 - `gitlab.v4.objects.ProjectInvitation`
 - `gitlab.v4.objects.ProjectInvitationManager`

- *gitlab.v4.objects.Project.invitations*
- GitLab API: <https://docs.gitlab.com/ce/api/invitations.html>

Examples

Danger: Creating an invitation with `create()` returns a status response, rather than invitation details, because it allows sending multiple invitations at the same time.

Thus when using several emails, you do not create a real invitation object you can manipulate, because python-gitlab cannot know which email to track as the ID.

In that case, use a **lazy** `get()` method shown below using a specific email address to create an invitation object you can manipulate.

Create an invitation:

```
invitation = group_or_project.invitations.create(  
    {  
        "email": "email@example.com",  
        "access_level": gitlab.const.AccessLevel.DEVELOPER,  
    }  
)
```

List invitations for a group or project:

```
invitations = group_or_project.invitations.list()
```

Warning: As mentioned above, GitLab does not provide a real GET endpoint for a single invitation. We can create a lazy object to later manipulate it.

Update an invitation:

```
invitation = group_or_project.invitations.get("email@example.com", lazy=True)  
invitation.access_level = gitlab.const.AccessLevel.DEVELOPER  
invitation.save()  
  
# or  
group_or_project.invitations.update(  
    "email@example.com",  
    {"access_level": gitlab.const.AccessLevel.DEVELOPER}  
)
```

Delete an invitation:

```
invitation = group_or_project.invitations.get("email@example.com", lazy=True)  
invitation.delete()  
  
# or  
group_or_project.invitations.delete("email@example.com")
```

6.5.22 Issues

Reported issues

Reference

- v4 API:
 - `gitlab.v4.objects.Issue`
 - `gitlab.v4.objects.IssueManager`
 - `gitlab.Gitlab.issues`
- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

Examples

List the issues:

```
issues = gl.issues.list()
```

Use the `state` and `label` parameters to filter the results. Use the `order_by` and `sort` attributes to sort the results:

```
open_issues = gl.issues.list(state='opened')
closed_issues = gl.issues.list(state='closed')
tagged_issues = gl.issues.list(labels=['foo', 'bar'])
```

Note: It is not possible to edit or delete Issue objects. You need to create a `ProjectIssue` object to perform changes:

```
issue = gl.issues.list()[0]
project = gl.projects.get(issue.project_id, lazy=True)
editable_issue = project.issues.get(issue.iid, lazy=True)
editable_issue.title = updated_title
editable_issue.save()
```

Group issues

Reference

- v4 API:
 - `gitlab.v4.objects.GroupIssue`
 - `gitlab.v4.objects.GroupIssueManager`
 - `gitlab.v4.objects.Group.issues`
- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

Examples

List the group issues:

```
issues = group.issues.list()  
# Filter using the state, labels and milestone parameters  
issues = group.issues.list(milestone='1.0', state='opened')  
# Order using the order_by and sort parameters  
issues = group.issues.list(order_by='created_at', sort='desc')
```

Note: It is not possible to edit or delete GroupIssue objects. You need to create a ProjectIssue object to perform changes:

```
issue = group.issues.list()[0]  
project = gl.projects.get(issue.project_id, lazy=True)  
editable_issue = project.issues.get(issue.iid, lazy=True)  
editable_issue.title = updated_title  
editable_issue.save()
```

Project issues

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssue`
 - `gitlab.v4.objects.ProjectIssueManager`
 - `gitlab.v4.objects.Project.issues`
- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

Examples

List the project issues:

```
issues = project.issues.list()  
# Filter using the state, labels and milestone parameters  
issues = project.issues.list(milestone='1.0', state='opened')  
# Order using the order_by and sort parameters  
issues = project.issues.list(order_by='created_at', sort='desc')
```

Get a project issue:

```
issue = project.issues.get(issue_iid)
```

Create a new issue:

```
issue = project.issues.create({'title': 'I have a bug',  
                             'description': 'Something useful here.'})
```

Update an issue:

```
issue.labels = ['foo', 'bar']
issue.save()
```

Close / reopen an issue:

```
# close an issue
issue.state_event = 'close'
issue.save()
# reopen it
issue.state_event = 'reopen'
issue.save()
```

Delete an issue (admin or project owner only):

```
project.issues.delete(issue_id)
# pr
issue.delete()
```

Assign the issues:

```
issue = gl.issues.list()[0]
issue.assignee_ids = [25, 10, 31, 12]
issue.save()
```

Note: The Gitlab API explicitly references that the *assignee_id* field is deprecated, so using a list of user IDs for *assignee_ids* is how to assign an issue to a user(s).

Subscribe / unsubscribe from an issue:

```
issue.subscribe()
issue.unsubscribe()
```

Move an issue to another project:

```
issue.move(other_project_id)
```

Reorder an issue on a board:

```
issue.reorder(move_after_id=2, move_before_id=3)
```

Make an issue as todo:

```
issue.todo()
```

Get time tracking stats:

```
issue.time_stats()
```

On recent versions of Gitlab the time stats are also returned as an issue object attribute:

```
issue = project.issue.get(iid)
print(issue.attributes['time_stats'])
```

Set a time estimate for an issue:

```
issue.time_estimate('3h30m')
```

Reset a time estimate for an issue:

```
issue.reset_time_estimate()
```

Add spent time for an issue:

```
issue.add_spent_time('3h30m')
```

Reset spent time for an issue:

```
issue.reset_spent_time()
```

Get user agent detail for the issue (admin only):

```
detail = issue.user_agent_detail()
```

Get the list of merge requests that will close an issue when merged:

```
mrs = issue.closed_by()
```

Get the merge requests related to an issue:

```
mrs = issue.related_merge_requests()
```

Get the list of participants:

```
users = issue.participants()
```

Issue links

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectIssueLink*
 - *gitlab.v4.objects.ProjectIssueLinkManager*
 - *gitlab.v4.objects.ProjectIssue.links*
- GitLab API: https://docs.gitlab.com/ee/api/issue_links.html (EE feature)

Examples

List the issues linked to i1:

```
links = i1.links.list()
```

Link issue i1 to issue i2:

```
data = {
    'target_project_id': i2.project_id,
    'target_issue_iid': i2.iid
}
src_issue, dest_issue = i1.links.create(data)
```

Note: The `create()` method returns the source and destination `ProjectIssue` objects, not a `ProjectIssueLink` object.

Delete a link:

```
i1.links.delete(issue_link_id)
```

Issues statistics

Reference

- v4 API:
 - `gitlab.v4.objects.IssuesStatistics`
 - `gitlab.v4.objects.IssuesStatisticsManager`
 - `gitlab.issues_statistics`
 - `gitlab.v4.objects.GroupIssuesStatistics`
 - `gitlab.v4.objects.GroupIssuesStatisticsManager`
 - `gitlab.v4.objects.Group.issues_statistics`
 - `gitlab.v4.objects.ProjectIssuesStatistics`
 - `gitlab.v4.objects.ProjectIssuesStatisticsManager`
 - `gitlab.v4.objects.Project.issues_statistics`
- GitLab API: https://docs.gitlab.com/ce/api/issues_statistics.htm

Examples

Get statistics of all issues created by the current user:

```
statistics = gl.issues_statistics.get()
```

Get statistics of all issues the user has access to:

```
statistics = gl.issues_statistics.get(scope='all')
```

Get statistics of issues for the user with foobar in the title or the description:

```
statistics = gl.issues_statistics.get(search='foobar')
```

Get statistics of all issues in a group:

```
statistics = group.issues_statistics.get()
```

Get statistics of issues in a group with foobar in the title or the description:

```
statistics = group.issues_statistics.get(search='foobar')
```

Get statistics of all issues in a project:

```
statistics = project.issues_statistics.get()
```

Get statistics of issues in a project with foobar in the title or the description:

```
statistics = project.issues_statistics.get(search='foobar')
```

6.5.23 Iterations

Reference

- v4 API:
 - `gitlab.v4.objects.GroupIteration`
 - `gitlab.v4.objects.GroupIterationManager`
 - `gitlab.v4.objects.Group.iterations`
 - `gitlab.v4.objects.ProjectIterationManager`
 - `gitlab.v4.objects.Project.iterations`
- GitLab API: <https://docs.gitlab.com/ee/api/iterations.html>

Examples

Note: GitLab no longer has project iterations. Using a project endpoint returns the ancestor groups' iterations.

List iterations for a project's ancestor groups:

```
iterations = project.iterations.list()
```

List iterations for a group:

```
iterations = group.iterations.list()
```

6.5.24 Keys

Keys

Reference

- v4 API
 - *gitlab.v4.objects.Key*
 - *gitlab.v4.objects.KeyManager*
 - *gitlab.Gitlab.keys*
- GitLab API: <https://docs.gitlab.com/ce/api/keys.html>

Examples

Get an ssh key by its id (requires admin access):

```
key = gl.keys.get(key_id)
```

Get an ssh key (requires admin access) or a deploy key by its fingerprint:

```
key = gl.keys.get(fingerprint="SHA256:ERJJ/OweAM6jA80jj/gXs4N5fqUaREEJnz/EyfywfXY")
```

6.5.25 Issue boards

Boards

Boards are a visual representation of existing issues for a project or a group. Issues can be moved from one list to the other to track progress and help with priorities.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectBoard`
 - `gitlab.v4.objects.ProjectBoardManager`
 - `gitlab.v4.objects.Project.boards`
 - `gitlab.v4.objects.GroupBoard`
 - `gitlab.v4.objects.GroupBoardManager`
 - `gitlab.v4.objects.Group.boards`
- GitLab API:
 - <https://docs.gitlab.com/ce/api/boards.html>
 - https://docs.gitlab.com/ce/api/group_boards.html

Examples

Get the list of existing boards for a project or a group:

```
# item is a Project or a Group
boards = project_or_group.boards.list()
```

Get a single board for a project or a group:

```
board = project_or_group.boards.get(board_id)
```

Create a board:

```
board = project_or_group.boards.create({'name': 'new-board'})
```

Note: Board creation is not supported in the GitLab CE edition.

Delete a board:

```
board.delete()
# or
project_or_group.boards.delete(board_id)
```

Note: Board deletion is not supported in the GitLab CE edition.

Board lists

Boards are made of lists of issues. Each list is associated to a label, and issues tagged with this label automatically belong to the list.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectBoardList`
 - `gitlab.v4.objects.ProjectBoardListManager`
 - `gitlab.v4.objects.ProjectBoard.lists`
 - `gitlab.v4.objects.GroupBoardList`
 - `gitlab.v4.objects.GroupBoardListManager`
 - `gitlab.v4.objects.GroupBoard.lists`
- GitLab API:
 - <https://docs.gitlab.com/ce/api/boards.html>
 - https://docs.gitlab.com/ce/api/group_boards.html

Examples

List the issue lists for a board:

```
b_lists = board.lists.list()
```

Get a single list:

```
b_list = board.lists.get(list_id)
```

Create a new list:

```
# First get a ProjectLabel
label = get_or_create_label()
# Then use its ID to create the new board list
b_list = board.lists.create({'label_id': label.id})
```

Change a list position. The first list is at position 0. Moving a list will set it at the given position and move the following lists up a position:

```
b_list.position = 2
b_list.save()
```

Delete a list:

```
b_list.delete()
```

6.5.26 Labels

Project labels

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectLabel`
 - `gitlab.v4.objects.ProjectLabelManager`
 - `gitlab.v4.objects.Project.labels`
- GitLab API: <https://docs.gitlab.com/ce/api/labels.html>

Examples

List labels for a project:

```
labels = project.labels.list()
```

Create a label for a project:

```
label = project.labels.create({'name': 'foo', 'color': '#8899aa'})
```

Update a label for a project:

```
# change the name of the label:
label.new_name = 'bar'
label.save()
# change its color:
label.color = '#112233'
label.save()
```

Promote a project label to a group label:

```
label.promote()
```

Delete a label for a project:

```
project.labels.delete(label_id)
# or
label.delete()
```

Manage labels in issues and merge requests:

```
# Labels are defined as lists in issues and merge requests. The labels must
# exist.
issue = p.issues.create({'title': 'issue title',
                         'description': 'issue description',
                         'labels': ['foo']})
issue.labels.append('bar')
issue.save()
```

Label events

Resource label events keep track about who, when, and which label was added or removed to an issuable.

Group epic label events are only available in the EE edition.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssueResourceLabelEvent`
 - `gitlab.v4.objects.ProjectIssueResourceLabelEventManager`
 - `gitlab.v4.objects.ProjectIssue.resourcelabelevents`
 - `gitlab.v4.objects.ProjectMergeRequestResourceLabelEvent`
 - `gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager`
 - `gitlab.v4.objects.ProjectMergeRequest.resourcelabelevents`
 - `gitlab.v4.objects.GroupEpicResourceLabelEvent`
 - `gitlab.v4.objects.GroupEpicResourceLabelEventManager`
 - `gitlab.v4.objects.GroupEpic.resourcelabelevents`
- GitLab API: https://docs.gitlab.com/ee/api/resource_label_events.html

Examples

Get the events for a resource (issue, merge request or epic):

```
events = resource.resourcelabelevents.list()
```

Get a specific event for a resource:

```
event = resource.resourcelabelevents.get(event_id)
```

6.5.27 Notification settings

You can define notification settings globally, for groups and for projects. Valid levels are defined as constants:

- `gitlab.const.NotificationLevel.DISABLED`
- `gitlab.const.NotificationLevel.PARTICIPATING`
- `gitlab.const.NotificationLevel.WATCH`
- `gitlab.const.NotificationLevel.GLOBAL`
- `gitlab.const.NotificationLevel.MENTION`
- `gitlab.const.NotificationLevel.CUSTOM`

You get access to fine-grained settings if you use the `NOTIFICATION_LEVEL_CUSTOM` level.

Reference

- v4 API:
 - `gitlab.v4.objects.NotificationSettings`
 - `gitlab.v4.objects.NotificationSettingsManager`
 - `gitlab.Gitlab.notificationsettings`
 - `gitlab.v4.objects.GroupNotificationSettings`
 - `gitlab.v4.objects.GroupNotificationSettingsManager`
 - `gitlab.v4.objects.Group.notificationsettings`
 - `gitlab.v4.objects.ProjectNotificationSettings`
 - `gitlab.v4.objects.ProjectNotificationSettingsManager`
 - `gitlab.v4.objects.Project.notificationsettings`
- GitLab API: https://docs.gitlab.com/ce/api/notification_settings.html

Examples

Get the notifications settings:

```
# global settings
settings = gl.notificationsettings.get()
# for a group
settings = gl.groups.get(group_id).notificationsettings.get()
# for a project
settings = gl.projects.get(project_id).notificationsettings.get()
```

Update the notifications settings:

```
# use a predefined level
settings.level = gitlab.const.NotificationLevel.WATCH

# create a custom setup
settings.level = gitlab.const.NotificationLevel.CUSTOM
settings.save()  # will create additional attributes, but not mandatory

settings.new_merge_request = True
settings.new_issue = True
settings.new_note = True
settings.save()
```

6.5.28 Merge Trains

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectMergeTrain*
 - *gitlab.v4.objects.ProjectMergeTrainManager*
 - *gitlab.v4.objects.Project.merge_trains*
- GitLab API: https://docs.gitlab.com/ee/api/merge_trains.html

Examples

List merge trains for a project:

```
merge_trains = project.merge_trains.list()
```

List active merge trains for a project:

```
merge_trains = project.merge_trains.list(scope="active")
```

List completed (have been merged) merge trains for a project:

```
merge_trains = project.merge_trains.list(scope="complete")
```

6.5.29 Merge requests

You can use merge requests to notify a project that a branch is ready for merging. The owner of the target project can accept the merge request.

Merge requests are linked to projects, but they can be listed globally or for groups.

Group and global listing

Reference

- v4 API:
 - *gitlab.v4.objects.GroupMergeRequest*
 - *gitlab.v4.objects.GroupMergeRequestManager*
 - *gitlab.v4.objects.Group.mergerequests*
 - *gitlab.v4.objects.MergeRequest*
 - *gitlab.v4.objects.MergeRequestManager*
 - *gitlab.Gitlab.mergerequests*
- GitLab API: https://docs.gitlab.com/ce/api/merge_requests.html

Examples

List the merge requests created by the user of the token on the GitLab server:

```
mrs = gl.mergerequests.list()
```

List the merge requests available on the GitLab server:

```
mrs = gl.mergerequests.list(scope="all")
```

List the merge requests for a group:

```
group = gl.groups.get('mygroup')
mrs = group.mergerequests.list()
```

Note: It is not possible to edit or delete `MergeRequest` and `GroupMergeRequest` objects. You need to create a `ProjectMergeRequest` object to apply changes:

```
mr = group.mergerequests.list()[0]
project = gl.projects.get(mr.project_id, lazy=True)
editable_mr = project.mergerequests.get(mr.iid, lazy=True)
editable_mr.title = updated_title
editable_mr.save()
```

Project merge requests

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectMergeRequest`
 - `gitlab.v4.objects.ProjectMergeRequestManager`
 - `gitlab.v4.objects.Project.mergerequests`
- GitLab API: https://docs.gitlab.com/ce/api/merge_requests.html

Examples

List MRs for a project:

```
mrs = project.mergerequests.list()
```

You can filter and sort the returned list with the following parameters:

- **state:** state of the MR. It can be one of `all`, `merged`, `opened`, `closed` or `locked`
- **order_by:** sort by `created_at` or `updated_at`
- **sort:** sort order (`asc` or `desc`)

You can find a full updated list of parameters here: https://docs.gitlab.com/ee/api/merge_requests.html#list-merge-requests

For example:

```
mrs = project.mergerequests.list(state='merged', order_by='updated_at')
```

Get a single MR:

```
mr = project.mergerequests.get(mr_id)
```

Create a MR:

```
mr = project.mergerequests.create({'source_branch': 'cool_feature',
                                    'target_branch': 'main',
                                    'title': 'merge cool feature',
                                    'labels': ['label1', 'label2']})
```

Update a MR:

```
mr.description = 'New description'
mr.labels = ['foo', 'bar']
mr.save()
```

Change the state of a MR (close or reopen):

```
mr.state_event = 'close' # or 'reopen'
mr.save()
```

Delete a MR:

```
project.mergerequests.delete(mr_id)
# or
mr.delete()
```

Accept a MR:

```
mr.merge()
```

Cancel a MR when the build succeeds:

```
mr.cancel_merge_when_pipeline_succeeds()
```

List commits of a MR:

```
commits = mr.commits()
```

List the changes of a MR:

```
changes = mr.changes()
```

List issues that will close on merge:

```
mr.closes_issues()
```

Subscribe to / unsubscribe from a MR:

```
mr.subscribe()  
mr.unsubscribe()
```

Mark a MR as todo:

```
mr.todo()
```

List the diffs for a merge request:

```
diffs = mr.diffs.list()
```

Get a diff for a merge request:

```
diff = mr.diffs.get(diff_id)
```

Get time tracking stats:

```
time_stats = mr.time_stats()
```

On recent versions of Gitlab the time stats are also returned as a merge request object attribute:

```
mr = project.mergerequests.get(id)  
print(mr.attributes['time_stats'])
```

Set a time estimate for a merge request:

```
mr.time_estimate('3h30m')
```

Reset a time estimate for a merge request:

```
mr.reset_time_estimate()
```

Add spent time for a merge request:

```
mr.add_spent_time('3h30m')
```

Reset spent time for a merge request:

```
mr.reset_spent_time()
```

Get user agent detail for the issue (admin only):

```
detail = issue.user_agent_detail()
```

Attempt to rebase an MR:

```
mr.rebase()
```

Clear all approvals of a merge request (possible with project or group access tokens only):

```
mr.reset_approvals()
```

Get status of a rebase for an MR:

```
mr = project.mergerequests.get(mr_id, include_rebase_in_progress=True)  
print(mr.rebase_in_progress, mr.merge_error)
```

For more info see: https://docs.gitlab.com/ee/api/merge_requests.html#rebase-a-merge-request

Attempt to merge changes between source and target branch:

```
response = mr.merge_ref()
print(response['commit_id'])
```

Merge Request Pipelines

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectMergeRequestPipeline`
 - `gitlab.v4.objects.ProjectMergeRequestPipelineManager`
 - `gitlab.v4.objects.ProjectMergeRequest.pipelines`
- GitLab API: https://docs.gitlab.com/ee/api/merge_requests.html#list-mr-pipelines

Examples

List pipelines for a merge request:

```
pipelines = mr.pipelines.list()
```

Create a pipeline for a merge request:

```
pipeline = mr.pipelines.create()
```

6.5.30 Merge request approvals settings

Merge request approvals can be defined at the project level or at the merge request level.

References

- v4 API:
 - `gitlab.v4.objects.ProjectApproval`
 - `gitlab.v4.objects.ProjectApprovalManager`
 - `gitlab.v4.objects.ProjectApprovalRule`
 - `gitlab.v4.objects.ProjectApprovalRuleManager`
 - `gitlab.v4.objects.Project.approvals`
 - `gitlab.v4.objects.ProjectMergeRequestApproval`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalManager`
 - `gitlab.v4.objects.ProjectMergeRequest.approvals`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalRule`

- `gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager`
 - `gitlab.v4.objects.ProjectMergeRequest.approval_rules`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalState`
 - `gitlab.v4.objects.ProjectMergeRequestApprovalStateManager`
 - `gitlab.v4.objects.ProjectMergeRequest.approval_state`
- GitLab API: https://docs.gitlab.com/ee/api/merge_request_approvals.html

Examples

List project-level MR approval rules:

```
p_mrmas = project.approvalrules.list()
```

Change project-level MR approval rule:

```
p_approvalrule.user_ids = [234]  
p_approvalrule.save()
```

Delete project-level MR approval rule:

```
p_approvalrule.delete()
```

Get project-level or MR-level MR approvals settings:

```
p_mrmas = project.approvals.get()  
  
mr_mrmas = mr.approvals.get()
```

Get MR-level approval state:

```
mr_approval_state = mr.approval_state.get()
```

Change project-level or MR-level MR approvals settings:

```
p_mrmas.approvals_before_merge = 2  
p_mrmas.save()  
  
mr.approvals.set_approvers(approvals_required=1)  
# or  
mr_mrmas.approvals_required = 1  
mr_mrmas.save()
```

Change project-level MR allowed approvers:

```
project.approvals.set_approvers(approver_ids=[105],  
                                 approver_group_ids=[653, 654])
```

Create a new MR-level approval rule or change an existing MR-level approval rule:

```
mr.approvals.set_approvers(approvals_required = 1, approver_ids=[105],  
                           approver_group_ids=[653, 654],  
                           approval_rule_name="my MR custom approval rule")
```

List MR-level MR approval rules:

```
mr.approval_rules.list()
```

Get a single MR approval rule:

```
approval_rule_id = 123
mr_approvalrule = mr.approval_rules.get(approval_rule_id)
```

Delete MR-level MR approval rule:

```
rules = mr.approval_rules.list()
rules[0].delete()

# or
mr.approval_rules.delete(approval_id)
```

Change MR-level MR approval rule:

```
mr_approvalrule.user_ids = [105]
mr_approvalrule.approvals_required = 2
mr_approvalrule.group_ids = [653, 654]
mr_approvalrule.save()
```

Create a MR-level MR approval rule:

```
mr.approval_rules.create({
    "name": "my MR custom approval rule",
    "approvals_required": 2,
    "rule_type": "regular",
    "user_ids": [105],
    "group_ids": [653, 654],
})
```

6.5.31 Milestones

Project milestones

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectMilestone`
 - `gitlab.v4.objects.ProjectMilestoneManager`
 - `gitlab.v4.objects.Project.milestones`
 - `gitlab.v4.objects.GroupMilestone`
 - `gitlab.v4.objects.GroupMilestoneManager`
 - `gitlab.v4.objects.Group.milestones`
- GitLab API:
 - <https://docs.gitlab.com/ce/api/milestones.html>

– https://docs.gitlab.com/ce/api/group_milestones.html

Examples

List the milestones for a project or a group:

```
p_milestones = project.milestones.list()  
g_milestones = group.milestones.list()
```

You can filter the list using the following parameters:

- `iids`: unique IDs of milestones for the project
- `state`: either `active` or `closed`
- `search`: to search using a string

```
p_milestones = project.milestones.list(state='closed')  
g_milestones = group.milestones.list(state='active')
```

Get a single milestone:

```
p_milestone = project.milestones.get(milestone_id)  
g_milestone = group.milestones.get(milestone_id)
```

Create a milestone:

```
milestone = project.milestones.create({'title': '1.0'})
```

Edit a milestone:

```
milestone.description = 'v 1.0 release'  
milestone.save()
```

Change the state of a milestone (activate / close):

```
# close a milestone  
milestone.state_event = 'close'  
milestone.save()  
  
# activate a milestone  
milestone.state_event = 'activate'  
milestone.save()
```

Promote a project milestone:

```
milestone.promote()
```

List the issues related to a milestone:

```
issues = milestone.issues()
```

List the merge requests related to a milestone:

```
merge_requests = milestone.merge_requests()
```

Milestone events

Resource milestone events keep track of what happens to GitLab issues and merge requests.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIssueResourceMilestoneEvent`
 - `gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager`
 - `gitlab.v4.objects.ProjectIssue.resourcemilestoneevents`
 - `gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEvent`
 - `gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager`
 - `gitlab.v4.objects.ProjectMergeRequest.resourcemilestoneevents`
- GitLab API: https://docs.gitlab.com/ee/api/resource_milestone_events.html

Examples

Get milestones for a resource (issue, merge request):

```
milestones = resource.resourcemilestoneevents.list()
```

Get a specific milestone for a resource:

```
milestone = resource.resourcemilestoneevents.get(milestone_id)
```

6.5.32 Namespaces

Reference

- v4 API:
 - `gitlab.v4.objects.Namespace`
 - `gitlab.v4.objects.NamespaceManager`
 - `gitlab.Gitlab.namespaces`
- GitLab API: <https://docs.gitlab.com/ce/api/namespaces.html>

Examples

List namespaces:

```
namespaces = gl.namespaces.list()
```

Search namespaces:

```
namespaces = gl.namespaces.list(search='foo')
```

Get a namespace by ID or path:

```
namespace = gl.namespaces.get("my-namespace")
```

Get existence of a namespace by path:

```
namespace = gl.namespaces.exists("new-namespace")

if namespace.exists:
    # get suggestions of namespaces that don't already exist
    print(namespace.suggests)
```

6.5.33 Notes

You can manipulate notes (comments) on group epics, project issues, merge requests and snippets.

Reference

- v4 API:

Epics:

- `gitlab.v4.objects.GroupEpicNote`
- `gitlab.v4.objects.GroupEpicNoteManager`
- `gitlab.v4.objects.GroupEpic.notes`

Issues:

- `gitlab.v4.objects.ProjectIssueNote`
- `gitlab.v4.objects.ProjectIssueNoteManager`
- `gitlab.v4.objects.ProjectIssue.notes`

MergeRequests:

- `gitlab.v4.objects.ProjectMergeRequestNote`
- `gitlab.v4.objects.ProjectMergeRequestNoteManager`
- `gitlab.v4.objects.ProjectMergeRequest.notes`

Snippets:

- `gitlab.v4.objects.ProjectSnippetNote`
- `gitlab.v4.objects.ProjectSnippetNoteManager`
- `gitlab.v4.objects.ProjectSnippet.notes`

- GitLab API: <https://docs.gitlab.com/ce/api/notes.html>

Examples

List the notes for a resource:

```
e_notes = epic.notes.list()
i_notes = issue.notes.list()
mr_notes = mr.notes.list()
s_notes = snippet.notes.list()
```

Get a note for a resource:

```
e_note = epic.notes.get(note_id)
i_note = issue.notes.get(note_id)
mr_note = mr.notes.get(note_id)
s_note = snippet.notes.get(note_id)
```

Create a note for a resource:

```
e_note = epic.notes.create({'body': 'note content'})
i_note = issue.notes.create({'body': 'note content'})
mr_note = mr.notes.create({'body': 'note content'})
s_note = snippet.notes.create({'body': 'note content'})
```

Update a note for a resource:

```
note.body = 'updated note content'
note.save()
```

Delete a note for a resource:

```
note.delete()
```

6.5.34 Packages

Packages allow you to utilize GitLab as a private repository for a variety of common package managers, as well as GitLab's generic package registry.

Project Packages

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectPackage`
 - `gitlab.v4.objects.ProjectPackageManager`
 - `gitlab.v4.objects.Project.packages`
- GitLab API: <https://docs.gitlab.com/ee/api/packages.html#within-a-project>

Examples

List the packages in a project:

```
packages = project.packages.list()
```

Filter the results by package_type or package_name

```
packages = project.packages.list(package_type='pypi')
```

Get a specific package of a project by id:

```
package = project.packages.get(1)
```

Delete a package from a project:

```
package.delete()  
# or  
project.packages.delete(package.id)
```

Group Packages

Reference

- v4 API:
 - *gitlab.v4.objects.GroupPackage*
 - *gitlab.v4.objects.GroupPackageManager*
 - *gitlab.v4.objects.Group.packages*
- GitLab API: <https://docs.gitlab.com/ee/api/packages.html#within-a-group>

Examples

List the packages in a group:

```
packages = group.packages.list()
```

Filter the results by package_type or package_name

```
packages = group.packages.list(package_type='pypi')
```

Project Package Files

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectPackageFile`
 - `gitlab.v4.objects.ProjectPackageManager`
 - `gitlab.v4.objects.ProjectPackage.package_files`
- GitLab API: <https://docs.gitlab.com/ee/api/packages.html#list-package-files>

Examples

List package files for package in project:

```
package = project.packages.get(1)
package_files = package.package_files.list()
```

Delete a package file in a project:

```
package = project.packages.get(1)
file = package.package_files.list()[0]
file.delete()
```

Generic Packages

You can use python-gitlab to upload and download generic packages.

Reference

- v4 API:
 - `gitlab.v4.objects.GenericPackage`
 - `gitlab.v4.objects.GenericPackageManager`
 - `gitlab.v4.objects.Project.generic_packages`
- GitLab API: https://docs.gitlab.com/ee/user/packages/generic_packages

Examples

Upload a generic package to a project:

```
project = gl.projects.get(1, lazy=True)
package = project.generic_packages.upload(
    package_name="hello-world",
    package_version="v1.0.0",
    file_name="hello.tar.gz",
    path="/path/to/local/hello.tar.gz"
)
```

Download a project's generic package:

```
project = gl.projects.get(1, lazy=True)
package = project.generic_packages.download(
    package_name="hello-world",
    package_version="v1.0.0",
    file_name="hello.tar.gz",
)
```

Hint: You can use the Packages API described above to find packages and retrieve the metadata you need download them.

6.5.35 Pages domains

Admin

References

- v4 API:
 - *gitlab.v4.objects.PagesDomain*
 - *gitlab.v4.objects.PagesDomainManager*
 - *gitlab.Gitlab.pagesdomains*
- GitLab API: https://docs.gitlab.com/ce/api/pages_domains.html#list-all-pages-domains

Examples

List all the existing domains (admin only):

```
domains = gl.pagesdomains.list()
```

Project pages domain

References

- v4 API:
 - *gitlab.v4.objects.ProjectPagesDomain*
 - *gitlab.v4.objects.ProjectPagesDomainManager*
 - *gitlab.v4.objects.Project.pagesdomains*
- GitLab API: https://docs.gitlab.com/ce/api/pages_domains.html#list-pages-domains

Examples

List domains for a project:

```
domains = project.pagesdomains.list()
```

Get a single domain:

```
domain = project.pagesdomains.get('d1.example.com')
```

Create a new domain:

```
domain = project.pagesdomains.create({'domain': 'd2.example.com'})
```

Update an existing domain:

```
domain.certificate = open('d2.crt').read()
domain.key = open('d2.key').read()
domain.save()
```

Delete an existing domain:

```
domain.delete
# or
project.pagesdomains.delete('d2.example.com')
```

6.5.36 Personal Access Tokens

References

- v4 API:
 - *gitlab.v4.objects.PersonalAccessToken*
 - *gitlab.v4.objects.PersonalAccessTokenManager*
 - *gitlab.Gitlab.personal_access_tokens*
 - *gitlab.v4.objects.UserPersonalAccessToken*
 - *gitlab.v4.objects.UserPersonalAccessTokenManager*
 - *gitlab.Gitlab.User.personal_access_tokens*
- GitLab API:
 - https://docs.gitlab.com/ee/api/personal_access_tokens.html
 - <https://docs.gitlab.com/ee/api/users.html#create-a-personal-access-token>

Examples

List personal access tokens:

```
access_tokens = gl.personal_access_tokens.list()  
print(access_tokens[0].name)
```

List personal access tokens from other user_id (admin only):

```
access_tokens = gl.personal_access_tokens.list(user_id=25)
```

Revoke a personal access token fetched via list:

```
access_token = access_tokens[0]  
access_token.delete()
```

Revoke a personal access token by id:

```
gl.personal_access_tokens.delete(123)
```

Revoke the personal access token currently used:

```
gl.personal_access_tokens.delete("self")
```

Create a personal access token for a user (admin only):

```
user = gl.users.get(25, lazy=True)  
access_token = user.personal_access_tokens.create({"name": "test", "scopes": "api"})
```

Note: As you can see above, you can only create personal access tokens via the Users API, but you cannot revoke these objects directly. This is because the create API uses a different endpoint than the list and revoke APIs. You need to fetch the token via the list API first to revoke it.

As of 14.2, GitLab does not provide a GET API for single personal access tokens. You must use the list method to retrieve single tokens.

6.5.37 Pipelines and Jobs

Project pipelines

A pipeline is a group of jobs executed by GitLab CI.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectPipeline`
 - `gitlab.v4.objects.ProjectPipelineManager`
 - `gitlab.v4.objects.Project.pipelines`
- GitLab API: <https://docs.gitlab.com/ce/api/pipelines.html>

Examples

List pipelines for a project:

```
pipelines = project.pipelines.list()
```

Get a pipeline for a project:

```
pipeline = project.pipelines.get(pipeline_id)
```

Get variables of a pipeline:

```
variables = pipeline.variables.list()
```

Create a pipeline for a particular reference with custom variables:

```
pipeline = project.pipelines.create({'ref': 'main', 'variables': [{key: 'MY_VARIABLE',  
    ↪ value: 'hello'}]})
```

Retry the failed builds for a pipeline:

```
pipeline.retry()
```

Cancel builds in a pipeline:

```
pipeline.cancel()
```

Delete a pipeline:

```
pipeline.delete()
```

Triggers

Triggers provide a way to interact with the GitLab CI. Using a trigger a user or an application can run a new build/job for a specific commit.

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectTrigger*
 - *gitlab.v4.objects.ProjectTriggerManager*
 - *gitlab.v4.objects.Project.triggers*
- GitLab API: https://docs.gitlab.com/ce/api/pipeline_triggers.html

Examples

List triggers:

```
triggers = project.triggers.list()
```

Get a trigger:

```
trigger = project.triggers.get(trigger_token)
```

Create a trigger:

```
trigger = project.triggers.create({'description': 'mytrigger'})
```

Remove a trigger:

```
project.triggers.delete(trigger_token)
# or
trigger.delete()
```

Full example with wait for finish:

```
def get_or_create_trigger(project):
    trigger_decription = 'my_trigger_id'
    for t in project.triggers.list():
        if t.description == trigger_decription:
            return t
    return project.triggers.create({'description': trigger_decription})

trigger = get_or_create_trigger(project)
pipeline = project.trigger_pipeline('main', trigger.token, variables={"DEPLOY_ZONE": "us-west1"})
while pipeline.finished_at is None:
    pipeline.refresh()
    time.sleep(1)
```

You can trigger a pipeline using token authentication instead of user authentication. To do so create an anonymous Gitlab instance and use lazy objects to get the associated project:

```
gl = gitlab.Gitlab(URL)  # no authentication
project = gl.projects.get(project_id, lazy=True)  # no API call
project.trigger_pipeline('main', trigger_token)
```

Reference: <https://docs.gitlab.com/ee/ci/triggers/#trigger-token>

Pipeline schedule

You can schedule pipeline runs using a cron-like syntax. Variables can be associated with the scheduled pipelines.

Reference

- v4 API
 - `gitlab.v4.objects.ProjectPipelineSchedule`
 - `gitlab.v4.objects.ProjectPipelineScheduleManager`
 - `gitlab.v4.objects.Project.pipelineschedules`
 - `gitlab.v4.objects.ProjectPipelineScheduleVariable`
 - `gitlab.v4.objects.ProjectPipelineScheduleVariableManager`
 - `gitlab.v4.objects.Project.pipelineschedules`
- GitLab API: https://docs.gitlab.com/ce/api/pipeline_schedules.html

Examples

List pipeline schedules:

```
scheds = project.pipelineschedules.list()
```

Get a single schedule:

```
sched = projects.pipelineschedules.get(schedule_id)
```

Create a new schedule:

```
sched = project.pipelineschedules.create({
    'ref': 'main',
    'description': 'Daily test',
    'cron': '@ 1 * * *'})
```

Update a schedule:

```
sched.cron = '1 2 * * *'
sched.save()
```

Take ownership of a schedule:

```
sched.take_ownership()
```

Trigger a pipeline schedule immediately:

```
sched = projects.pipelineschedules.get(schedule_id)
sched.play()
```

Delete a schedule:

```
sched.delete()
```

List schedule variables:

```
# note: you need to use get() to retrieve the schedule variables. The
# attribute is not present in the response of a list() call
sched = projects.pipelineschedules.get(schedule_id)
vars = sched.attributes['variables']
```

Create a schedule variable:

```
var = sched.variables.create({'key': 'foo', 'value': 'bar'})
```

Edit a schedule variable:

```
var.value = 'new_value'
var.save()
```

Delete a schedule variable:

```
var.delete()
```

Jobs

Jobs are associated to projects, pipelines and commits. They provide information on the jobs that have been run, and methods to manipulate them.

Reference

- v4 API
 - `gitlab.v4.objects.ProjectJob`
 - `gitlab.v4.objects.ProjectJobManager`
 - `gitlab.v4.objects.Project.jobs`
- GitLab API: <https://docs.gitlab.com/ce/api/jobs.html>

Examples

Jobs are usually automatically triggered, but you can explicitly trigger a new job:

```
project.trigger_build('main', trigger_token,
                      {'extra_var1': 'foo', 'extra_var2': 'bar'})
```

List jobs for the project:

```
jobs = project.jobs.list()
```

Get a single job:

```
project.jobs.get(job_id)
```

List the jobs of a pipeline:

```
project = gl.projects.get(project_id)
pipeline = project.pipelines.get(pipeline_id)
jobs = pipeline.jobs.list()
```

Note: Job methods (play, cancel, and so on) are not available on ProjectPipelineJob objects. To use these methods create a ProjectJob object:

```
pipeline_job = pipeline.jobs.list()[0]
job = project.jobs.get(pipeline_job.id, lazy=True)
job.retry()
```

Get the artifacts of a job:

```
build_or_job.artifacts()
```

Get the artifacts of a job by its name from the latest successful pipeline of a branch or tag:

```
project.artifacts.download(ref_name='main', job='build')
```

Attention: An older method `project.artifacts()` is deprecated and will be removed in a future version.

Warning: Artifacts are entirely stored in memory in this example.

You can download artifacts as a stream. Provide a callable to handle the stream:

```
with open("archive.zip", "wb") as f:
    build_or_job.artifacts(streamed=True, action=f.write)
```

You can also directly stream the output into a file, and unzip it afterwards:

```
zipfn = "__artifacts.zip"
with open(zipfn, "wb") as f:
    build_or_job.artifacts(streamed=True, action=f.write)
subprocess.run(["unzip", "-bo", zipfn])
os.unlink(zipfn)
```

Or, you can also use the underlying response iterator directly:

```
artifact_bytes_iterator = build_or_job.artifacts(iterator=True)
```

This can be used with frameworks that expect an iterator (such as FastAPI/Starlette's `StreamingResponse`) to forward a download from GitLab without having to download the entire content server-side first:

```
@app.get("/download_artifact")
def download_artifact():
    artifact_bytes_iterator = build_or_job.artifacts(iterator=True)
    return StreamingResponse(artifact_bytes_iterator, media_type="application/zip")
```

Delete all artifacts of a project that can be deleted:

```
project.artifacts.delete()
```

Get a single artifact file:

```
build_or_job.artifact('path/to/file')
```

Get a single artifact file by branch and job:

```
project.artifacts.raw('branch', 'path/to/file', 'job')
```

Attention: An older method `project.artifact()` is deprecated and will be removed in a future version.

Mark a job artifact as kept when expiration is set:

```
build_or_job.keep_artifacts()
```

Delete the artifacts of a job:

```
build_or_job.delete_artifacts()
```

Get a job trace:

```
build_or_job.trace()
```

Warning: Traces are entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Cancel/retry a job:

```
build_or_job.cancel()  
build_or_job.retry()
```

Play (trigger) a job:

```
build_or_job.play()
```

Erase a job (artifacts and trace):

```
build_or_job.erase()
```

Pipeline bridges

Get a list of bridge jobs (including child pipelines) for a pipeline.

Reference

- v4 API
 - `gitlab.v4.objects.ProjectPipelineBridge`
 - `gitlab.v4.objects.ProjectPipelineBridgeManager`
 - `gitlab.v4.objects.ProjectPipeline.bridges`
- GitLab API: <https://docs.gitlab.com/ee/api/jobs.html#list-pipeline-bridges>

Examples

List bridges for the pipeline:

```
bridges = pipeline.bridges.list()
```

Pipeline test report

Get a pipeline's complete test report.

Reference

- v4 API
 - `gitlab.v4.objects.ProjectPipelineTestReport`
 - `gitlab.v4.objects.ProjectPipelineTestReportManager`
 - `gitlab.v4.objects.ProjectPipeline.test_report`
- GitLab API: <https://docs.gitlab.com/ee/api/pipelines.html#get-a-pipelines-test-report>

Examples

Get the test report for a pipeline:

```
test_report = pipeline.test_report.get()
```

Pipeline test report summary

Get a pipeline's test report summary.

Reference

- v4 API
 - *gitlab.v4.objects.ProjectPipelineTestReportSummary*
 - *gitlab.v4.objects.ProjectPipelineTestReportSummaryManager*
 - *gitlab.v4.objects.ProjectPipeline.test_report_summary*
- GitLab API: <https://docs.gitlab.com/ee/api/pipelines.html#get-a-pipelines-test-report-summary>

Examples

Get the test report summary for a pipeline:

```
test_report_summary = pipeline.test_report_summary.get()
```

6.5.38 Projects

Projects

Reference

- v4 API:
 - *gitlab.v4.objects.Project*
 - *gitlab.v4.objects.ProjectManager*
 - *gitlab.Gitlab.projects*
- GitLab API: <https://docs.gitlab.com/ce/api/projects.html>

Examples

List projects:

```
projects = gl.projects.list()
```

The API provides several filtering parameters for the listing methods:

- **archived**: if True only archived projects will be returned
- **visibility**: returns only projects with the specified visibility (can be `public`, `internal` or `private`)
- **search**: returns project matching the given pattern

Results can also be sorted using the following parameters:

- **order_by**: sort using the given argument. Valid values are `id`, `name`, `path`, `created_at`, `updated_at` and `last_activity_at`. The default is to sort by `created_at`
- **sort**: sort order (`asc` or `desc`)

```
# List all projects (default 20)
projects = gl.projects.list(get_all=True)

# Archived projects
projects = gl.projects.list(archived=1)

# Limit to projects with a defined visibility
projects = gl.projects.list.visibility='public')

# List owned projects
projects = gl.projects.list(owned=True)

# List starred projects
projects = gl.projects.list(starred=True)

# Search projects
projects = gl.projects.list(search='keyword')
```

Note: To list the starred projects of another user, see the [Users API docs](#).

Note: Fetching a list of projects, doesn't include all attributes of all projects. To retrieve all attributes, you'll need to fetch a single project

Get a single project:

```
# Get a project by ID
project_id = 851
project = gl.projects.get(project_id)

# Get a project by name with namespace
project_name_with_namespace = "namespace/project_name"
project = gl.projects.get(project_name_with_namespace)
```

Create a project:

```
project = gl.projects.create({'name': 'project1'})
```

Create a project for a user (admin only):

```
alice = gl.users.list(username='alice')[0]
user_project = alice.projects.create({'name': 'project'})
user_projects = alice.projects.list()
```

Create a project in a group:

```
# You need to get the id of the group, then use the namespace_id attribute
# to create the group
group_id = gl.groups.list(search='my-group')[0].id
project = gl.projects.create({'name': 'myrepo', 'namespace_id': group_id})
```

List a project's groups:

```
# Get a list of ancestor/parent groups for a project.  
groups = project.groups.list()
```

Update a project:

```
project.snippets_enabled = 1  
project.save()
```

Set the avatar image for a project:

```
# the avatar image can be passed as data (content of the file) or as a file  
# object opened in binary mode  
project.avatar = open('path/to/file.png', 'rb')  
project.save()
```

Delete a project:

```
gl.projects.delete(project_id)  
# or  
project.delete()
```

Restore a project marked for deletion (Premium only):

```
project.restore()
```

Fork a project:

```
fork = project.forks.create({})  
  
# fork to a specific namespace  
fork = project.forks.create({'namespace': 'myteam'})
```

Get a list of forks for the project:

```
forks = project.forks.list()
```

Create/delete a fork relation between projects (requires admin permissions):

```
project.create_fork_relation(source_project.id)  
project.delete_fork_relation()
```

Get languages used in the project with percentage value:

```
languages = project.languages()
```

Star/unstar a project:

```
project.star()  
project.unstar()
```

Archive/unarchive a project:

```
project.archive()  
project.unarchive()
```

Start the housekeeping job:

```
project.housekeeping()
```

List the repository tree:

```
# list the content of the root directory for the default branch
items = project.repository_tree()

# list the content of a subdirectory on a specific branch
items = project.repository_tree(path='docs', ref='branch1')
```

Get the content and metadata of a file for a commit, using a blob sha:

```
items = project.repository_tree(path='docs', ref='branch1')
file_info = p.repository_blob(items[0]['id'])
content = base64.b64decode(file_info['content'])
size = file_info['size']
```

Update a project submodule:

```
items = project.update_submodule(
    submodule="foo/bar",
    branch="main",
    commit_sha="4c3674f66071e30b3311dac9b9ccc90502a72664",
    commit_message="Message", # optional
)
```

Get the repository archive:

```
tgz = project.repository_archive()

# get the archive for a branch/tag/commit
tzg = project.repository_archive(sha='4567abc')

# get the archive in a different format
zip = project.repository_archive(format='zip')
```

Note: For the formats available, refer to <https://docs.gitlab.com/ce/api/repositories.html#get-file-archive>

Warning: Archives are entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Get the content of a file using the blob id:

```
# find the id for the blob (simple search)
id = [d['id'] for d in p.repository_tree() if d['name'] == 'README.rst'][0]

# get the content
file_content = p.repository_raw_blob(id)
```

Warning: Blobs are entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Get a snapshot of the repository:

```
tar_file = project.snapshot()
```

Warning: Snapshots are entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Compare two branches, tags or commits:

```
result = project.repository_compare('main', 'branch1')

# get the commits
for commit in result['commits']:
    print(commit)

# get the diffs
for file_diff in result['diffs']:
    print(file_diff)
```

Get the merge base for two or more branches, tags or commits:

```
commit = project.repository_merge_base(['main', 'v1.2.3', 'bd1324e2f'])
```

Get a list of contributors for the repository:

```
contributors = project.repository_contributors()
```

Get a list of users for the repository:

```
users = p.users.list()

# search for users
users = p.users.list(search='pattern')
```

Start the pull mirroring process (EE edition):

```
project.mirror_pull()
```

Import / Export

You can export projects from gitlab, and re-import them to create new projects or overwrite existing ones.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectExport`
 - `gitlab.v4.objects.ProjectExportManager`
 - `gitlab.v4.objects.Project.exports`
 - `gitlab.v4.objects.ProjectImport`
 - `gitlab.v4.objects.ProjectImportManager`

- `gitlab.v4.objects.Project.imports`
- `gitlab.v4.objects.ProjectManager.import_project`
- GitLab API: https://docs.gitlab.com/ce/api/project_import_export.html

Examples

A project export is an asynchronous operation. To retrieve the archive generated by GitLab you need to:

1. Create an export using the API
2. Wait for the export to be done
3. Download the result

```
# Create the export
p = gl.projects.get(my_project)
export = p.exports.create()

# Wait for the 'finished' status
export.refresh()
while export.export_status != 'finished':
    time.sleep(1)
    export.refresh()

# Download the result
with open('/tmp/export.tgz', 'wb') as f:
    export.download(streamed=True, action=f.write)
```

You can export and upload a project to an external URL (see upstream documentation for more details):

```
project.exports.create(
{
    "upload":
    {
        "url": "http://localhost:8080",
        "method": "POST"
    }
})
```

You can also get the status of an existing export, regardless of whether it was created via the API or the Web UI:

```
project = gl.projects.get(my_project)

# Gets the current export status
export = project.exports.get()
```

Import the project into the current user's namespace:

```
with open('/tmp/export.tgz', 'rb') as f:
    output = gl.projects.import_project(
        f, path='my_new_project', name='My New Project'
    )
```

(continues on next page)

(continued from previous page)

```
# Get a ProjectImport object to track the import status
project_import = gl.projects.get(output['id'], lazy=True).imports.get()
while project_import.import_status != 'finished':
    time.sleep(1)
    project_import.refresh()
```

Import the project into a namespace and override parameters:

```
with open('/tmp/export.tgz', 'rb') as f:
    output = gl.projects.import_project(
        f,
        path='my_new_project',
        name='My New Project',
        namespace='my-group',
        override_params={'visibility': 'private'},
    )
```

Project custom attributes

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectCustomAttribute`
 - `gitlab.v4.objects.ProjectCustomAttributeManager`
 - `gitlab.v4.objects.Project.customattributes`
- GitLab API: https://docs.gitlab.com/ce/api/custom_attributes.html

Examples

List custom attributes for a project:

```
attrs = project.customattributes.list()
```

Get a custom attribute for a project:

```
attr = project.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a project:

```
attr = project.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a project:

```
attr.delete()
# or
project.customattributes.delete(attr_key)
```

Search projects by custom attribute:

```
project.customattributes.set('type', 'internal')
gl.projects.list(custom_attributes={'type': 'internal'})
```

Project files

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectFile`
 - `gitlab.v4.objects.ProjectFileManager`
 - `gitlab.v4.objects.Project.files`
- GitLab API: https://docs.gitlab.com/ce/api/repository_files.html

Examples

Get a file:

```
f = project.files.get(file_path='README.rst', ref='main')

# get the base64 encoded content
print(f.content)

# get the decoded content
print(f.decode())
```

Get file details from headers, without fetching its entire content:

```
headers = project.files.head('README.rst', ref='main')

# Get the file size:
# For a full list of headers returned, see upstream documentation.
# https://docs.gitlab.com/ee/api/repository_files.html#get-file-from-repository
print(headers["X-Gitlab-Size"])
```

Get a raw file:

```
raw_content = project.files.raw(file_path='README.rst', ref='main')
print(raw_content)
with open('/tmp/raw-download.txt', 'wb') as f:
    project.files.raw(file_path='README.rst', ref='main', streamed=True, action=f.write)
```

Create a new file:

```
f = project.files.create({'file_path': 'testfile.txt',
                           'branch': 'main',
                           'content': file_content,
                           'author_email': 'test@example.com',
                           'author_name': 'yourname',
                           'commit_message': 'Create testfile'})
```

Update a file. The entire content must be uploaded, as plain text or as base64 encoded text:

```
f.content = 'new content'  
f.save(branch='main', commit_message='Update testfile')  
  
# or for binary data  
# Note: decode() is required with python 3 for data serialization. You can omit  
# it with python 2  
f.content = base64.b64encode(open('image.png').read()).decode()  
f.save(branch='main', commit_message='Update testfile', encoding='base64')
```

Delete a file:

```
f.delete(commit_message='Delete testfile', branch='main')  
# or  
project.files.delete(file_path='testfile.txt', commit_message='Delete testfile', branch=  
    ↪'main')
```

Get file blame:

```
b = project.files.blame(file_path='README.rst', ref='main')
```

Project tags

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectTag`
 - `gitlab.v4.objects.ProjectTagManager`
 - `gitlab.v4.objects.Project.tags`
- GitLab API: <https://docs.gitlab.com/ce/api/tags.html>

Examples

List the project tags:

```
tags = project.tags.list()
```

Get a tag:

```
tag = project.tags.get('1.0')
```

Create a tag:

```
tag = project.tags.create({'tag_name': '1.0', 'ref': 'main'})
```

Delete a tag:

```
project.tags.delete('1.0')  
# or  
tag.delete()
```

Project snippets

The snippet visibility can be defined using the following constants:

- `gitlab.const.Visibility.PRIVATE`
- `gitlab.const.Visibility.INTERNAL`
- `gitlab.const.Visibility.PUBLIC`

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectSnippet`
 - `gitlab.v4.objects.ProjectSnippetManager`
 - `gitlab.v4.objects.Project.files`
- GitLab API: https://docs.gitlab.com/ce/api/project_snippets.html

Examples

List the project snippets:

```
snippets = project.snippets.list()
```

Get a snippet:

```
snippet = project.snippets.get(snippet_id)
```

Get the content of a snippet:

```
print(snippet.content())
```

Warning: The snippet content is entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Create a snippet:

```
snippet = project.snippets.create({'title': 'sample 1',
                                    'file_name': 'foo.py',
                                    'code': 'import gitlab',
                                    'visibility_level':
                                    gitlab.const.Visibility.PRIVATE})
```

Update a snippet:

```
snippet.code = 'import gitlab\nimport whatever'
snippet.save
```

Delete a snippet:

```
project.snippets.delete(snippet_id)
# or
snippet.delete()
```

Get user agent detail (admin only):

```
detail = snippet.user_agent_detail()
```

Notes

See *Notes*.

Project members

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectMember*
 - *gitlab.v4.objects.ProjectMemberManager*
 - *gitlab.v4.objects.ProjectMemberAllManager*
 - *gitlab.v4.objects.Project.members*
 - *gitlab.v4.objects.Project.members_all*
- GitLab API: <https://docs.gitlab.com/ce/api/members.html>

Examples

List only direct project members:

```
members = project.members.list()
```

List the project members recursively (including inherited members through ancestor groups):

```
members = project.members_all.list(get_all=True)
```

Search project members matching a query string:

```
members = project.members.list(query='bar')
```

Get only direct project member:

```
member = project.members.get(user_id)
```

Get a member of a project, including members inherited through ancestor groups:

```
members = project.members_all.get(member_id)
```

Add a project member:

```
member = project.members.create({'user_id': user.id, 'access_level':
                                gitlab.const.AccessLevel.DEVELOPER})
```

Modify a project member (change the access level):

```
member.access_level = gitlab.const.AccessLevel.MAINTAINER
member.save()
```

Remove a member from the project team:

```
project.members.delete(user.id)
# or
member.delete()
```

Share/unshare the project with a group:

```
project.share(group.id, gitlab.const.AccessLevel.DEVELOPER)
project.unshare(group.id)
```

Project hooks

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectHook`
 - `gitlab.v4.objects.ProjectHookManager`
 - `gitlab.v4.objects.Project.hooks`
- GitLab API: <https://docs.gitlab.com/ce/api/projects.html#hooks>

Examples

List the project hooks:

```
hooks = project.hooks.list()
```

Get a project hook:

```
hook = project.hooks.get(hook_id)
```

Create a project hook:

```
hook = project.hooks.create({'url': 'http://my/action/url', 'push_events': 1})
```

Update a project hook:

```
hook.push_events = 0
hook.save()
```

Delete a project hook:

```
project.hooks.delete(hook_id)
# or
hook.delete()
```

Project Integrations

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectIntegration`
 - `gitlab.v4.objects.ProjectIntegrationManager`
 - `gitlab.v4.objects.Project.integrations`
- GitLab API: <https://docs.gitlab.com/ce/api/integrations.html>

Examples

Danger: Since GitLab 13.12, `get()` calls to project integrations return a `404 Not Found` response until they have been activated the first time.

To avoid this, we recommend using `lazy=True` to prevent making the initial call when activating new integrations unless they have previously already been activated.

Configure and enable an integration for the first time:

```
integration = project.integrations.get('asana', lazy=True)

integration.api_key = 'randomkey'
integration.save()
```

Get an existing integration:

```
integration = project.integrations.get('asana')
# display its status (enabled/disabled)
print(integration.active)
```

List active project integrations:

```
integration = project.integrations.list()
```

List the code names of available integrations (doesn't return objects):

```
integrations = project.integrations.available()
```

Disable an integration:

```
integration.delete()
```

File uploads

Reference

- v4 API:
 - `gitlab.v4.objects.Project.upload`
- Gitlab API: <https://docs.gitlab.com/ce/api/projects.html#upload-a-file>

Examples

Upload a file into a project using a filesystem path:

```
project.upload("filename.txt", filepath="/some/path/filename.txt")
```

Upload a file into a project without a filesystem path:

```
project.upload("filename.txt", filedatal="Raw data")
```

Upload a file and comment on an issue using the uploaded file's markdown:

```
uploaded_file = project.upload("filename.txt", filedatal="data")
issue = project.issues.get(issue_id)
issue.notes.create({
    "body": "See the attached file: {}".format(uploaded_file["markdown"])
})
```

Upload a file and comment on an issue while using custom markdown to reference the uploaded file:

```
uploaded_file = project.upload("filename.txt", filedatal="data")
issue = project.issues.get(issue_id)
issue.notes.create({
    "body": "See the [attached file]({})".format(uploaded_file["url"])
})
```

Project push rules

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectPushRules`
 - `gitlab.v4.objects.ProjectPushRulesManager`
 - `gitlab.v4.objects.Project.pushrules`
- GitLab API: <https://docs.gitlab.com/ee/api/projects.html#push-rules>

Examples

Create project push rules (at least one rule is necessary):

```
project.pushrules.create({'deny_delete_tag': True})
```

Get project push rules (returns `None` if there are no push rules):

```
pr = project.pushrules.get()
```

Edit project push rules:

```
pr.branch_name_regex = '^(\main|develop|support-\d+|release-\d+\.\.+|hotfix-\.\.+|feature-\.\.+)$'  
pr.save()
```

Delete project push rules:

```
pr.delete()
```

Project protected tags

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectProtectedTag`
 - `gitlab.v4.objects.ProjectProtectedTagManager`
 - `gitlab.v4.objects.Project.protectedtags`
- GitLab API: https://docs.gitlab.com/ce/api/protected_tags.html

Examples

Get a list of protected tags from a project:

```
protected_tags = project.protectedtags.list()
```

Get a single protected tag or wildcard protected tag:

```
protected_tag = project.protectedtags.get('v*')
```

Protect a single repository tag or several project repository tags using a wildcard protected tag:

```
project.protectedtags.create({'name': 'v*', 'create_access_level': '40'})
```

Unprotect the given protected tag or wildcard protected tag.:

```
protected_tag.delete()
```

Additional project statistics

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectAdditionalStatistics`
 - `gitlab.v4.objects.ProjectAdditionalStatisticsManager`
 - `gitlab.v4.objects.Project.additionalstatistics`
- GitLab API: https://docs.gitlab.com/ce/api/project_statistics.html

Examples

Get all additional statistics of a project:

```
statistics = project.additionalstatistics.get()
```

Get total fetches in last 30 days of a project:

```
total_fetches = project.additionalstatistics.get().fetches['total']
```

Project storage

This endpoint requires admin access.

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectStorage`
 - `gitlab.v4.objects.ProjectStorageManager`
 - `gitlab.v4.objects.Project.storage`
- GitLab API: <https://docs.gitlab.com/ee/api/projects.html#get-the-path-to-repository-storage>

Examples

Get the repository storage details for a project:

```
storage = project.storage.get()
```

Get the repository storage disk path:

```
disk_path = project.storage.get().disk_path
```

6.5.39 Project Access Tokens

Get a list of project access tokens

References

- v4 API:
 - `gitlab.v4.objects.ProjectAccessToken`
 - `gitlab.v4.objects.ProjectAccessTokenManager`
 - `gitlab.Gitlab.project_access_tokens`
- GitLab API: https://docs.gitlab.com/ee/api/project_access_tokens.html

Examples

List project access tokens:

```
access_tokens = gl.projects.get(1, lazy=True).access_tokens.list()
print(access_tokens[0].name)
```

Create project access token:

```
access_token = gl.projects.get(1).access_tokens.create({"name": "test", "scopes": ["api
˓→"]})
```

Revoke a project access tokens:

```
gl.projects.get(1).access_tokens.delete(42)
# or
access_token.delete()
```

6.5.40 Protected branches

You can define a list of protected branch names on a repository. Names can use wildcards (*).

References

- v4 API:
 - `gitlab.v4.objects.ProjectProtectedBranch`
 - `gitlab.v4.objects.ProjectProtectedBranchManager`
 - `gitlab.v4.objects.Project.protectedbranches`
- GitLab API: https://docs.gitlab.com/ce/api/protected_branches.html#protected-branches-api

Examples

Get the list of protected branches for a project:

```
p_branches = project.protectedbranches.list()
```

Get a single protected branch:

```
p_branch = project.protectedbranches.get('main')
```

Create a protected branch:

```
p_branch = project.protectedbranches.create({
    'name': '*-stable',
    'merge_access_level': gitlab.const.AccessLevel.DEVELOPER,
    'push_access_level': gitlab.const.AccessLevel.MAINTAINER
})
```

Create a protected branch with more granular access control:

```
p_branch = project.protectedbranches.create({
    'name': '*-stable',
    'allowed_to_push': [{"user_id": 99}, {"user_id": 98}],
    'allowed_to_merge': [{"group_id": 653}],
    'allowed_to_unprotect': [{"access_level": gitlab.const.AccessLevel.MAINTAINER}]
})
```

Delete a protected branch:

```
project.protectedbranches.delete('*-stable')
# or
p_branch.delete()
```

6.5.41 Protected environments

You can list and manage protected environments in a project.

References

- v4 API:
 - [gitlab.v4.objects.ProjectProtectedEnvironment](#)
 - [gitlab.v4.objects.ProjectProtectedEnvironmentManager](#)
 - [gitlab.v4.objects.Project.protected_environment](#)
- GitLab API: https://docs.gitlab.com/ee/api/protected_environments.html

Examples

Get the list of protected environments for a project:

```
p_environments = project.protected_environments.list()
```

Get a single protected environment:

```
p_environment = project.protected_environments.get('production')
```

Protect an existing environment:

```
p_environment = project.protected_environments.create(  
    {  
        'name': 'production',  
        'deploy_access_levels': [  
            {'access_level': 40}  
        ],  
    }  
)
```

Unprotect a protected environment:

```
p_environment = project.protected_environments.delete('production')  
# or  
p_environment.delete()
```

6.5.42 Releases

Project releases

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectRelease`
 - `gitlab.v4.objects.ProjectReleaseManager`
 - `gitlab.v4.objects.Project.releases`
- Gitlab API: <https://docs.gitlab.com/ee/api/releases/index.html>

Examples

Get a list of releases from a project:

```
project = gl.projects.get(project_id, lazy=True)  
release = project.releases.list()
```

Get a single release:

```
release = project.releases.get('v1.2.3')
```

Edit a release:

```
release.name = "Demo Release"
release.description = "release notes go here"
release.save()
```

Create a release for a project tag:

```
release = project.releases.create({'name':'Demo Release', 'tag_name':'v1.2.3',
                                   'description':'release notes go here'})
```

Delete a release:

```
# via its tag name from project attributes
release = project.releases.delete('v1.2.3')

# delete object directly
release.delete()
```

Note: The Releases API is one of the few working with CI_JOB_TOKEN, but the project can't be fetched with the token. Thus use *lazy* for the project as in the above example.

Also be aware that most of the capabilities of the endpoint were not accessible with CI_JOB_TOKEN until Gitlab version 14.5.

Project release links

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectReleaseLink`
 - `gitlab.v4.objects.ProjectReleaseLinkManager`
 - `gitlab.v4.objects.ProjectRelease.links`
- Gitlab API: <https://docs.gitlab.com/ee/api/releases/links.html>

Examples

Get a list of releases from a project:

```
links = release.links.list()
```

Get a single release link:

```
link = release.links.get(1)
```

Create a release link for a release:

```
link = release.links.create({"url": "https://example.com/asset", "name": "asset"})
```

Delete a release link:

```
# via its ID from release attributes
release.links.delete(1)

# delete object directly
link.delete()
```

6.5.43 Runners

Runners are external processes used to run CI jobs. They are deployed by the administrator and registered to the GitLab instance.

Shared runners are available for all projects. Specific runners are enabled for a list of projects.

Global runners (admin)

Reference

- v4 API:
 - `gitlab.v4.objects.Runner`
 - `gitlab.v4.objects.RunnerManager`
 - `gitlab.Gitlab.runners`
 - `gitlab.v4.objects.RunnerAll`
 - `gitlab.v4.objects.RunnerAllManager`
 - `gitlab.Gitlab.runners_all`
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

Examples

Use the `list()` and `all()` methods to list runners.

Both methods accept a `scope` parameter to filter the list. Allowed values for this parameter are:

- `active`
- `paused`
- `online`
- `specific` (`all()` only)
- `shared` (`all()` only)

Note: The returned objects hold minimal information about the runners. Use the `get()` method to retrieve detail about a runner.

Runners returned via `runners_all.list()` also cannot be manipulated directly. You will need to use the `get()` method to create an editable object.

```
# List owned runners
runners = gl.runners.list()

# List owned runners with a filter
runners = gl.runners.list(scope='active')

# List all runners in the GitLab instance (specific and shared), using a filter
runners = gl.runners_all.list(scope='paused')
```

Get a runner's detail:

```
runner = gl.runners.get(runner_id)
```

Register a new runner:

```
runner = gl.runners.create({'token': secret_token})
```

Update a runner:

```
runner = gl.runners.get(runner_id)
runner.tag_list.append('new_tag')
runner.save()
```

Remove a runner:

```
gl.runners.delete(runner_id)
# or
runner.delete()
```

Remove a runner by its authentication token:

```
gl.runners.delete(token="runner-auth-token")
```

Verify a registered runner token:

```
try:
    gl.runners.verify(runner_token)
    print("Valid token")
except GitlabVerifyError:
    print("Invalid token")
```

Project/Group runners

Reference

- v4 API:
 - `gitlab.v4.objects.ProjectRunner`
 - `gitlab.v4.objects.ProjectRunnerManager`
 - `gitlab.v4.objects.Project.runners`
 - `gitlab.v4.objects.GroupRunner`
 - `gitlab.v4.objects.GroupRunnerManager`

- *gitlab.v4.objects.Group.runners*
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

Examples

List the runners for a project:

```
runners = project.runners.list()
```

Enable a specific runner for a project:

```
p_runner = project.runners.create({'runner_id': runner.id})
```

Disable a specific runner for a project:

```
project.runners.delete(runner.id)
```

Runner jobs

Reference

- v4 API:
 - *gitlab.v4.objects.RunnerJob*
 - *gitlab.v4.objects.RunnerJobManager*
 - *gitlab.v4.objects.Runner.jobs*
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

Examples

List for jobs for a runner:

```
jobs = runner.jobs.list()
```

Filter the list using the jobs status:

```
# status can be 'running', 'success', 'failed' or 'canceled'  
active_jobs = runner.jobs.list(status='running')
```

6.5.44 Project Remote Mirrors

Remote Mirrors allow you to set up push mirroring for a project.

References

- v4 API:
 - `gitlab.v4.objects.ProjectRemoteMirror`
 - `gitlab.v4.objects.ProjectRemoteMirrorManager`
 - `gitlab.v4.objects.Project.remote_mirrors`
- GitLab API: https://docs.gitlab.com/ce/api/remote_mirrors.html

Examples

Get the list of a project's remote mirrors:

```
mirrors = project.remote_mirrors.list()
```

Create (and enable) a remote mirror for a project:

```
mirror = project.remote_mirrors.create({'url': 'https://gitlab.com/example.git',
                                         'enabled': True})
```

Update an existing remote mirror's attributes:

```
mirror.enabled = False
mirror.only_protected_branches = True
mirror.save()
```

6.5.45 Registry Repositories

References

- v4 API:
 - `gitlab.v4.objects.ProjectRegistryRepository`
 - `gitlab.v4.objects.ProjectRegistryRepositoryManager`
 - `gitlab.v4.objects.Project.repositories`
- GitLab API: https://docs.gitlab.com/ce/api/container_registry.html

Examples

Get the list of container registry repositories associated with the project:

```
repositories = project.repositories.list()
```

Get the list of all project container registry repositories in a group:

```
repositories = group.registry_repositories.list()
```

Delete repository:

```
project.repositories.delete(id=x)
# or
repository = repositories.pop()
repository.delete()
```

6.5.46 Registry Repository Tags

References

- v4 API:
 - `gitlab.v4.objects.ProjectRegistryTag`
 - `gitlab.v4.objects.ProjectRegistryTagManager`
 - `gitlab.v4.objects.Repository.tags`
- Gitlab API: https://docs.gitlab.com/ce/api/container_registry.html

Examples

Get the list of repository tags in given registry:

```
repositories = project.repositories.list()
repository = repositories.pop()
tags = repository.tags.list()
```

Get specific tag:

```
repository.tags.get(id=tag_name)
```

Delete tag:

```
repository.tags.delete(id=tag_name)
# or
tag = repository.tags.get(id=tag_name)
tag.delete()
```

Delete tag in bulk:

```
repository.tags.delete_in_bulk(keep_n=1)
# or
repository.tags.delete_in_bulk(older_than="1m")
# or
repository.tags.delete_in_bulk(name_regex="v.+", keep_n=2)
```

Note: Delete in bulk is asynchronous operation and may take a while. Refer to: https://docs.gitlab.com/ce/api/container_registry.html#delete-repository-tags-in-bulk

6.5.47 Search API

You can search for resources at the top level, in a project or in a group. Searches are based on a scope (issues, merge requests, and so on) and a search string. The following constants are provided to represent the possible scopes:

- Shared scopes (global, group and project):
 - `gitlab.const.SearchScope.PROJECTS`: projects
 - `gitlab.const.SearchScope.ISSUES`: issues
 - `gitlab.const.SearchScope.MERGE_REQUESTS`: merge_requests
 - `gitlab.const.SearchScope.MILESTONES`: milestones
 - `gitlab.const.SearchScope.WIKI_BLOBS`: wiki_blobs
 - `gitlab.const.SearchScope.COMMITS`: commits
 - `gitlab.const.SearchScope.BLOBS`: blobs
 - `gitlab.const.SearchScope.USERS`: users
- specific global scope:
 - `gitlab.const.SearchScope.GLOBAL_SNIPPET_TITLES`: snippet_titles
- specific project scope:
 - `gitlab.const.SearchScope.PROJECT_NOTES`: notes

Reference

- v4 API:
 - `gitlab.Gitlab.search`
 - `gitlab.v4.objects.Group.search`
 - `gitlab.v4.objects.Project.search`
- GitLab API: <https://docs.gitlab.com/ce/api/search.html>

Examples

Search for issues matching a specific string:

```
# global search
gl.search(gitlab.const.SearchScope.ISSUES, 'regression')

# group search
group = gl.groups.get('mygroup')
group.search(gitlab.const.SearchScope.ISSUES, 'regression')

# project search
project = gl.projects.get('myproject')
project.search(gitlab.const.SearchScope.ISSUES, 'regression')
```

The `search()` methods implement the pagination support:

```
# get lists of 10 items, and start at page 2
gl.search(gl.const.SearchScope.ISSUES, search_str, page=2, per_page=10)

# get a generator that will automatically make required API calls for
# pagination
for item in gl.search(gl.const.SearchScope.ISSUES, search_str, iterator=True):
    do_something(item)
```

The search API doesn't return objects, but dicts. If you need to act on objects, you need to create them explicitly:

```
for item in gl.search(gl.const.SearchScope.ISSUES, search_str, iterator=True):
    issue_project = gl.projects.get(item['project_id'], lazy=True)
    issue = issue_project.issues.get(item['iid'])
    issue.state = 'closed'
    issue.save()
```

6.5.48 Settings

Reference

- v4 API:
 - *gitlab.v4.objects.ApplicationSettings*
 - *gitlab.v4.objects.ApplicationSettingsManager*
 - *gitlab.Gitlab.settings*
- GitLab API: <https://docs.gitlab.com/ce/api/settings.html>

Examples

Get the settings:

```
settings = gl.settings.get()
```

Update the settings:

```
settings.signin_enabled = False
settings.save()
```

6.5.49 Snippets

Reference

- v4 API:
 - *gitlab.v4.objects.Snippet*
 - *gitlab.v4.objects.SnippetManager*
 - *gitlab.Gitlab.snippets*
- GitLab API: <https://docs.gitlab.com/ce/api/snippets.html>

Examples

List snippets owned by the current user:

```
snippets = gl.snippets.list()
```

List the public snippets:

```
public_snippets = gl.snippets.public()
```

Get a snippet:

```
snippet = gl.snippets.get(snippet_id)
# get the content
content = snippet.content()
```

Warning: Blobs are entirely stored in memory unless you use the streaming feature. See [the artifacts example](#).

Create a snippet:

```
snippet = gl.snippets.create({'title': 'snippet1',
                             'file_name': 'snippet1.py',
                             'content': open('snippet1.py').read()})
```

Update the snippet attributes:

```
snippet.visibility_level = gitlab.const.Visibility.PUBLIC
snippet.save()
```

To update a snippet code you need to create a ProjectSnippet object:

```
snippet = gl.snippets.get(snippet_id)
project = gl.projects.get(snippet.project_id, lazy=True)
editable_snippet = project.snippets.get(snippet.id)
editable_snippet.code = new_snippet_content
editable_snippet.save()
```

Delete a snippet:

```
gl.snippets.delete(snippet_id)
# or
snippet.delete()
```

Get user agent detail (admin only):

```
detail = snippet.user_agent_detail()
```

6.5.50 System hooks

Reference

- v4 API:
 - `gitlab.v4.objects.Hook`
 - `gitlab.v4.objects.HookManager`
 - `gitlab.Gitlab.hooks`
- GitLab API: https://docs.gitlab.com/ce/api/system_hooks.html

Examples

List the system hooks:

```
hooks = gl.hooks.list()
```

Create a system hook:

```
gl.hooks.get(hook_id)
```

Test a system hook. The returned object is not usable (it misses the hook ID):

```
hook = gl.hooks.create({'url': 'http://your.target.url'})
```

Delete a system hook:

```
gl.hooks.delete(hook_id)  
# or  
hook.delete()
```

6.5.51 Templates

You can request templates for different type of files:

- License files
- .gitignore files
- GitLab CI configuration files
- Dockerfiles

License templates

Reference

- v4 API:
 - `gitlab.v4.objects.License`
 - `gitlab.v4.objects.LicenseManager`
 - `gitlab.Gitlab.licenses`

- GitLab API: <https://docs.gitlab.com/ce/api/templates/licenses.html>

Examples

List known license templates:

```
licenses = gl.licenses.list()
```

Generate a license content for a project:

```
license = gl.licenses.get('apache-2.0', project='foobar', fullname='John Doe')
print(license.content)
```

.gitignore templates

Reference

- v4 API:
 - *gitlab.v4.objects.Gitignore*
 - *gitlab.v4.objects.GitignoreManager*
 - *gitlab.Gitlab.gitignores*
- GitLab API: <https://docs.gitlab.com/ce/api/templates/gitignores.html>

Examples

List known gitignore templates:

```
gitignores = gl.gitignores.list()
```

Get a gitignore template:

```
gitignore = gl.gitignores.get('Python')
print(gitignore.content)
```

GitLab CI templates

Reference

- v4 API:
 - *gitlab.v4.objects.Gitlabciyml*
 - *gitlab.v4.objects.GitlabciymlManager*
 - *gitlab.Gitlab.gitlabciymls*
- GitLab API: https://docs.gitlab.com/ce/api/templates/gitlab_ci_ymls.html

Examples

List known GitLab CI templates:

```
gitlabciymls = gl.gitlabciymls.list()
```

Get a GitLab CI template:

```
gitlabciyml = gl.gitlabciymls.get('Pelican')
print(gitlabciyml.content)
```

Dockerfile templates

Reference

- v4 API:
 - `gitlab.v4.objects.Dockerfile`
 - `gitlab.v4.objects.DockerfileManager`
 - `gitlab.Gitlab.gitlabciymls`
- GitLab API: Not documented.

Examples

List known Dockerfile templates:

```
dockerfiles = gl.dockerfiles.list()
```

Get a Dockerfile template:

```
dockerfile = gl.dockerfiles.get('Python')
print(dockerfile.content)
```

6.5.52 Todos

Reference

- v4 API:
 - Todo
 - TodoManager
 - `gitlab.Gitlab.todos`
- GitLab API: <https://docs.gitlab.com/ce/api/todos.html>

Examples

List active todos:

```
todos = gl.todos.list()
```

You can filter the list using the following parameters:

- `action`: can be `assigned`, `mentioned`, `build_failed`, `marked`, or `approval_required`
- `author_id`
- `project_id`
- `state`: can be `pending` or `done`
- `type`: can be `Issue` or `MergeRequest`

For example:

```
todos = gl.todos.list(project_id=1)
todos = gl.todos.list(state='done', type='Issue')
```

Mark a todo as done:

```
todos = gl.todos.list(project_id=1)
todos[0].mark_as_done()
```

Mark all the todos as done:

```
gl.todos.mark_all_as_done()
```

6.5.53 Topics

Topics can be used to categorize projects and find similar new projects.

Reference

- v4 API:
 - `gitlab.v4.objects.Topic`
 - `gitlab.v4.objects.TopicManager`
 - `gitlab.Gitlab.topics`
- GitLab API: <https://docs.gitlab.com/ce/api/topics.html>

This endpoint requires admin access for creating, updating and deleting objects.

Examples

List project topics on the GitLab instance:

```
topics = gl.topics.list()
```

Get a specific topic by its ID:

```
topic = gl.topics.get(topic_id)
```

Create a new topic:

```
topic = gl.topics.create({"name": "my-topic", "title": "my title"})
```

Update a topic:

```
topic.description = "My new topic"
topic.save()

# or
gl.topics.update(topic_id, {"description": "My new topic"})
```

Delete a topic:

```
topic.delete()

# or
gl.topics.delete(topic_id)
```

6.5.4 Users and current user

The Gitlab API exposes user-related method that can be manipulated by admins only.

The currently logged-in user is also exposed.

Users

References

- v4 API:
 - *gitlab.v4.objects.User*
 - *gitlab.v4.objects.UserManager*
 - *gitlab.Gitlab.users*
- GitLab API:
 - <https://docs.gitlab.com/ce/api/users.html>
 - <https://docs.gitlab.com/ee/api/projects.html#list-projects-starred-by-a-user>

Examples

Get the list of users:

```
users = gl.users.list()
```

Search users whose username match a given string:

```
users = gl.users.list(search='foo')
```

Get a single user:

```
# by ID
user = gl.users.get(user_id)
# by username
user = gl.users.list(username='root')[0]
```

Create a user:

```
user = gl.users.create({'email': 'john@doe.com',
                       'password': 's3cur3s3cr3T',
                       'username': 'jdoe',
                       'name': 'John Doe'})
```

Update a user:

```
user.name = 'Real Name'
user.save()
```

Delete a user:

```
gl.users.delete(user_id)
# or
user.delete()
```

Block/Unblock a user:

```
user.block()
user.unblock()
```

Activate/Deactivate a user:

```
user.activate()
user.deactivate()
```

Ban/Unban a user:

```
user.ban()
user.unban()
```

Follow/Unfollow a user:

```
user.follow()
user.unfollow()
```

Set the avatar image for a user:

```
# the avatar image can be passed as data (content of the file) or as a file
# object opened in binary mode
user.avatar = open('path/to/file.png', 'rb')
user.save()
```

Set an external identity for a user:

```
user.provider = 'oauth2_generic'
user.extern_uid = '3'
user.save()
```

Delete an external identity by provider name:

```
user.identityproviders.delete('oauth2_generic')
```

Get the followers of a user

```
user.followers_users.list()
```

Get the followings of a user

```
user.following_users.list()
```

List a user's starred projects

```
user.starred_projects.list()
```

If the GitLab instance has new user account approval enabled some users may have `user.state == 'blocked_pending_approval'`. Administrators can approve and reject such users:

```
user.approve()
user.reject()
```

User custom attributes

References

- v4 API:
 - `gitlab.v4.objects.UserCustomAttribute`
 - `gitlab.v4.objects.UserCustomAttributeManager`
 - `gitlab.v4.objects.User.customattributes`
- GitLab API: https://docs.gitlab.com/ce/api/custom_attributes.html

Examples

List custom attributes for a user:

```
attrs = user.customattributes.list()
```

Get a custom attribute for a user:

```
attr = user.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a user:

```
attr = user.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a user:

```
attr.delete()
# or
user.customattributes.delete(attr_key)
```

Search users by custom attribute:

```
user.customattributes.set('role', 'QA')
gl.users.list(custom_attributes={'role': 'QA'})
```

User impersonation tokens

References

- v4 API:
 - `gitlab.v4.objects.UserImpersonationToken`
 - `gitlab.v4.objects.UserImpersonationTokenManager`
 - `gitlab.v4.objects.User.impersonationtokens`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#get-all-impersonation-tokens-of-a-user>

List impersonation tokens for a user:

```
i_t = user.impersonationtokens.list(state='active')
i_t = user.impersonationtokens.list(state='inactive')
```

Get an impersonation token for a user:

```
i_t = user.impersonationtokens.get(i_t_id)
```

Create and use an impersonation token for a user:

```
i_t = user.impersonationtokens.create({'name': 'token1', 'scopes': ['api']})
# use the token to create a new gitlab connection
user_gl = gitlab.Gitlab(gitlab_url, private_token=i_t.token)
```

Revoke (delete) an impersonation token for a user:

```
i_t.delete()
```

User projects

References

- v4 API:
 - `gitlab.v4.objects.UserProject`
 - `gitlab.v4.objects.UserProjectManager`
 - `gitlab.v4.objects.User.projects`
- GitLab API: <https://docs.gitlab.com/ee/api/projects.html#list-user-projects>

List visible projects in the user's namespace:

```
projects = user.projects.list()
```

Note: Only the projects in the user's namespace are returned. Projects owned by the user in any group or subgroups are not returned. An empty list is returned if a profile is set to private.

User memberships

References

- v4 API:
 - `gitlab.v4.objects.UserMembership`
 - `gitlab.v4.objects.UserMembershipManager`
 - `gitlab.v4.objects.User.memberships`
- GitLab API: <https://docs.gitlab.com/ee/api/users.html#user-memberships>

List direct memberships for a user:

```
memberships = user.memberships.list()
```

List only direct project memberships:

```
memberships = user.memberships.list(type='Project')
```

List only direct group memberships:

```
memberships = user.memberships.list(type='Namespace')
```

Note: This endpoint requires admin access.

Current User

References

- v4 API:
 - `gitlab.v4.objects.CurrentUser`
 - `gitlab.v4.objects.CurrentUserManager`
 - `gitlab.Gitlab.user`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html>

Examples

Get the current user:

```
gl.auth()  
current_user = gl.user
```

GPG keys

References

You can manipulate GPG keys for the current user and for the other users if you are admin.

- v4 API:
 - `gitlab.v4.objects.CurrentUserGPGKey`
 - `gitlab.v4.objects.CurrentUserGPGKeyManager`
 - `gitlab.v4.objects.CurrentUser.gpgkeys`
 - `gitlab.v4.objects.UserGPGKey`
 - `gitlab.v4.objects.UserGPGKeyManager`
 - `gitlab.v4.objects.User.gpgkeys`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-all-gpg-keys>

Examples

List GPG keys for a user:

```
gpgkeys = user.gpgkeys.list()
```

Get a GPG gpgkey for a user:

```
gpgkey = user.gpgkeys.get(key_id)
```

Create a GPG gpgkey for a user:

```
# get the key with `gpg --export -a GPG_KEY_ID`  
k = user.gpgkeys.create({'key': public_key_content})
```

Delete a GPG gpgkey for a user:

```
user.gpgkeys.delete(key_id)
# or
gpgkey.delete()
```

SSH keys

References

You can manipulate SSH keys for the current user and for the other users if you are admin.

- v4 API:
 - `gitlab.v4.objects.CurrentUserKey`
 - `gitlab.v4.objects.CurrentUserKeyManager`
 - `gitlab.v4.objects.CurrentUser.keys`
 - `gitlab.v4.objects.UserKey`
 - `gitlab.v4.objects.UserKeyManager`
 - `gitlab.v4.objects.User.keys`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-ssh-keys>

Examples

List SSH keys for a user:

```
keys = user.keys.list()
```

Create an SSH key for a user:

```
key = user.keys.create({'title': 'my_key',
                       'key': open('/home/me/.ssh/id_rsa.pub').read()})
```

Get an SSH key for a user by id:

```
key = user.keys.get(key_id)
```

Delete an SSH key for a user:

```
user.keys.delete(key_id)
# or
key.delete()
```

Status

References

You can manipulate the status for the current user and you can read the status of other users.

- v4 API:
 - `gitlab.v4.objects.CurrentUserStatus`
 - `gitlab.v4.objects.CurrentUserStatusManager`
 - `gitlab.v4.objects.CurrentUser.status`
 - `gitlab.v4.objects.UserStatus`
 - `gitlab.v4.objects.UserStatusManager`
 - `gitlab.v4.objects.User.status`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#user-status>

Examples

Get current user status:

```
status = user.status.get()
```

Update the status for the current user:

```
status = user.status.get()
status.message = "message"
status.emoji = "thumbsup"
status.save()
```

Get the status of other users:

```
gl.users.get(1).status.get()
```

Emails

References

You can manipulate emails for the current user and for the other users if you are admin.

- v4 API:
 - `gitlab.v4.objects.CurrentUserEmail`
 - `gitlab.v4.objects.CurrentUserEmailManager`
 - `gitlab.v4.objects.CurrentUser.emails`
 - `gitlab.v4.objects.UserEmail`
 - `gitlab.v4.objects.UserEmailManager`
 - `gitlab.v4.objects.User.emails`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-emails>

Examples

List emails for a user:

```
emails = user.emails.list()
```

Get an email for a user:

```
email = user.emails.get(email_id)
```

Create an email for a user:

```
k = user.emails.create({'email': 'foo@bar.com'})
```

Delete an email for a user:

```
user.emails.delete(email_id)
# or
email.delete()
```

Users activities

References

- admin only
- v4 API:
 - *gitlab.v4.objects.UserActivities*
 - *gitlab.v4.objects.UserActivitiesManager*
 - *gitlab.Gitlab.user_activities*
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#get-user-activities-admin-only>

Examples

Get the users activities:

```
activities = gl.user_activities.list(
    query_parameters={'from': '2018-07-01'},
    get_all=True,
)
```

6.5.55 CI/CD Variables

You can configure variables at the instance-level (admin only), or associate variables to projects and groups, to modify pipeline/job scripts behavior.

Warning: Please always follow GitLab's rules for CI/CD variables, especially for values in masked variables. If you do not, your variables may silently fail to save.

Instance-level variables

This endpoint requires admin access.

Reference

- v4 API
 - `gitlab.v4.objects.Variable`
 - `gitlab.v4.objects.VariableManager`
 - `gitlab.Gitlab.variables`
- GitLab API
 - https://docs.gitlab.com/ce/api/instance_level_ci_variables.html

Examples

List all instance variables:

```
variables = gl.variables.list()
```

Get an instance variable by key:

```
variable = gl.variables.get('key_name')
```

Create an instance variable:

```
variable = gl.variables.create({'key': 'key1', 'value': 'value1'})
```

Update a variable value:

```
variable.value = 'new_value'  
variable.save()
```

Remove a variable:

```
gl.variables.delete('key_name')  
# or  
variable.delete()
```

Projects and groups variables

Reference

- v4 API
 - `gitlab.v4.objects.ProjectVariable`
 - `gitlab.v4.objects.ProjectVariableManager`
 - `gitlab.v4.objects.Project.variables`
 - `gitlab.v4.objects.GroupVariable`
 - `gitlab.v4.objects.GroupVariableManager`
 - `gitlab.v4.objects.Group.variables`
- GitLab API
 - https://docs.gitlab.com/ce/api/instance_level_ci_variables.html
 - https://docs.gitlab.com/ce/api/project_level_variables.html
 - https://docs.gitlab.com/ce/api/group_level_variables.html

Examples

List variables:

```
p_variables = project.variables.list()  
g_variables = group.variables.list()
```

Get a variable:

```
p_var = project.variables.get('key_name')  
g_var = group.variables.get('key_name')
```

Create a variable:

```
var = project.variables.create({'key': 'key1', 'value': 'value1'})  
var = group.variables.create({'key': 'key1', 'value': 'value1'})
```

Update a variable value:

```
var.value = 'new_value'  
var.save()  
# or  
project.variables.update("key1", {"value": "new_value"})
```

Remove a variable:

```
project.variables.delete('key_name')  
group.variables.delete('key_name')  
# or  
var.delete()
```

6.5.56 Sidekiq metrics

Reference

- v4 API:
 - `gitlab.v4.objects.SidekiqManager`
 - `gitlab.Gitlab.sidekiq`
- GitLab API: https://docs.gitlab.com/ce/api/sidekiq_metrics.html

Examples

```
gl.sidekiq.queue_metrics()
gl.sidekiq.process_metrics()
gl.sidekiq.job_stats()
gl.sidekiq.compound_metrics()
```

6.5.57 Wiki pages

References

- v4 API:
 - `gitlab.v4.objects.ProjectWiki`
 - `gitlab.v4.objects.ProjectWikiManager`
 - `gitlab.v4.objects.Project.wikis`
 - `gitlab.v4.objects.GroupWiki`
 - `gitlab.v4.objects.GroupWikiManager`
 - `gitlab.v4.objects.Group.wikis`
- GitLab API for Projects: <https://docs.gitlab.com/ce/api/wikis.html>
- GitLab API for Groups: https://docs.gitlab.com/ee/api/group_wikis.html

Examples

Get the list of wiki pages for a project. These do not contain the contents of the wiki page. You will need to call `get(slug)` to retrieve the content by accessing the `content` attribute:

```
pages = project.wikis.list()
```

Get the list of wiki pages for a group. These do not contain the contents of the wiki page. You will need to call `get(slug)` to retrieve the content by accessing the `content` attribute:

```
pages = group.wikis.list()
```

Get a single wiki page for a project:

```
page = project.wikis.get(page_slug)
```

Get a single wiki page for a group:

```
page = group.wikis.get(page_slug)
```

Get the contents of a wiki page:

```
print(page.content)
```

Create a wiki page on a project level:

```
page = project.wikis.create({'title': 'Wiki Page 1',
                             'content': open(a_file).read()})
```

Update a wiki page:

```
page.content = 'My new content'
page.save()
```

Delete a wiki page:

```
page.delete()
```

6.5.58 Clusters (DEPRECATED)

Warning: Cluster support was deprecated in GitLab 14.5 and disabled by default as of GitLab 15.0

Reference

- v4 API:
 - *gitlab.v4.objects.ProjectCluster*
 - *gitlab.v4.objects.ProjectClusterManager*
 - *gitlab.v4.objects.Project.clusters*
 - *gitlab.v4.objects.GroupCluster*
 - *gitlab.v4.objects.GroupClusterManager*
 - *gitlab.v4.objects.Group.clusters*
- GitLab API: https://docs.gitlab.com/ee/api/project_clusters.html
- GitLab API: https://docs.gitlab.com/ee/api/group_clusters.html

Examples

List clusters for a project:

```
clusters = project.clusters.list()
```

Create an cluster for a project:

```
cluster = project.clusters.create(
{
    "name": "cluster1",
    "platform_kubernetes_attributes": {
        "api_url": "http://url",
        "token": "tokenval",
    },
})
```

Retrieve a specific cluster for a project:

```
cluster = project.clusters.get(cluster_id)
```

Update an cluster for a project:

```
cluster.platform_kubernetes_attributes = {"api_url": "http://newurl"}
cluster.save()
```

Delete an cluster for a project:

```
cluster = project.clusters.delete(cluster_id)
# or
cluster.delete()
```

List clusters for a group:

```
clusters = group.clusters.list()
```

Create an cluster for a group:

```
cluster = group.clusters.create(
{
    "name": "cluster1",
    "platform_kubernetes_attributes": {
        "api_url": "http://url",
        "token": "tokenval",
    },
})
```

Retrieve a specific cluster for a group:

```
cluster = group.clusters.get(cluster_id)
```

Update an cluster for a group:

```
cluster.platform_kubernetes_attributes = {"api_url": "http://newurl"}
cluster.save()
```

Delete a cluster for a group:

```
cluster = group.clusters.delete(cluster_id)
# or
cluster.delete()
```

6.6 API reference (gitlab package)

6.6.1 Module contents

Wrapper for the GitLab API.

```
class gitlab.Gitlab(url: Optional[str] = None, private_token: Optional[str] = None, oauth_token:
    Optional[str] = None, job_token: Optional[str] = None, ssl_verify: Union[bool, str] =
    True, http_username: Optional[str] = None, http_password: Optional[str] = None,
    timeout: Optional[float] = None, api_version: str = '4', session: Optional[Session] =
    None, per_page: Optional[int] = None, pagination: Optional[str] = None, order_by:
    Optional[str] = None, user_agent: str = 'python-gitlab/3.10.0', retry_transient_errors:
    bool = False, keep_base_url: bool = False)
```

Bases: `object`

Represents a GitLab server connection.

Parameters

- **url** (`Optional[str]`) – The URL of the GitLab server (defaults to <https://gitlab.com>).
- **private_token** (`Optional[str]`) – The user private token
- **oauth_token** (`Optional[str]`) – An oauth token
- **job_token** (`Optional[str]`) – A CI job token
- **ssl_verify** (`Union[bool, str]`) – Whether SSL certificates should be validated. If the value is a string, it is the path to a CA file used for certificate validation.
- **timeout** (`Optional[float]`) – Timeout to use for requests to the GitLab server.
- **http_username** (`Optional[str]`) – Username for HTTP authentication
- **http_password** (`Optional[str]`) – Password for HTTP authentication
- **api_version** (`str`) – Gitlab API version to use (support for 4 only)
- **pagination** (`Optional[str]`) – Can be set to ‘keyset’ to use keyset pagination
- **order_by** (`Optional[str]`) – Set order_by globally
- **user_agent** (`str`) – A custom user agent to use for making HTTP requests.
- **retry_transient_errors** (`bool`) – Whether to retry after 500, 502, 503, 504 or 52x responses. Defaults to False.
- **keep_base_url** (`bool`) – keep user-provided base URL for pagination if it differs from response headers
- **session** (`Optional[Session]`) –
- **per_page** (`Optional[int]`) –

property api_url: str

The computed API base URL.

property api_version: str

The API version used (4 only).

appearance

See [ApplicationAppearanceManager](#)

applications

See [ApplicationManager](#)

audit_events

See [AuditEventManager](#)

auth() → None

Performs an authentication using private token. Warns the user if a potentially misconfigured URL is detected on the client or server side.

The `user` attribute will hold a `gitlab.objects.CurrentUser` object on success.

Return type

None

broadcastmessages

See [BroadcastMessageManager](#)

ci_lint

See [CiLintManager](#)

deploykeys

See [DeployKeyManager](#)

deploytokens

See [DeployTokenManager](#)

dockerfiles

See [DockerfileManager](#)

static enable_debug() → None**Return type**

None

events

See [EventManager](#)

features

See [FeatureManager](#)

classmethod from_config(gitlab_id: Optional[str] = None, config_files: Optional[List[str]] = None) → Gitlab

Create a Gitlab connection from configuration files.

Parameters

- `gitlab_id (Optional[str])` – ID of the configuration section.
- `list[str] (config_files)` – List of paths to configuration files.
- `config_files (Optional[List[str]])` –

Returns

A Gitlab connection.

Raises

`gitlab.config.GitlabDataError` – If the configuration is not correct.

Return type

`Gitlab`

geonodes

See [GeoNodeManager](#)

get_license(kwargs: Any) → Dict[str, Any]**

Retrieve information about the current license.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Returns

The current license information

Return type

`Dict[str, Any]`

gitignores

See [GitignoreManager](#)

gitlabciymls

See [GitlabciymlManager](#)

groups

See [GroupManager](#)

headers

Headers that will be used in request to GitLab

hooks

See [HookManager](#)

http_delete(path: str, **kwargs: Any) → Response

Make a DELETE request to the Gitlab server.

Parameters

- `path (str)` – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The requests object.

Raises

`GitlabHttpError` – When the return code is not 2xx

Return type

`Response`

http_get(*path: str, query_data: Optional[Dict[str, Any]] = None, streamed: bool = False, raw: bool = False, **kwargs: Any*) → Union[Dict[str, Any], Response]

Make a GET request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **streamed (bool)** – Whether the data should be streamed
- **raw (bool)** – If True do not try to parse the output as json
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

A requests result object is streamed is True or the content type is not json. The parsed json data otherwise.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

http_head(*path: str, query_data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → requests.structures.CaseInsensitiveDict[Any]

Make a HEAD request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo, page, per_page)

Returns

A requests.header object

Raises

GitlabHttpError – When the return code is not 2xx

Return type

requests.structures.CaseInsensitiveDict[Any]

http_list(*path: str, query_data: Optional[Dict[str, Any]] = None, *, as_list: Optional[bool] = None, iterator: Optional[bool] = None, **kwargs: Any*) → Union[[GitlabList](#), List[Dict[str, Any]]]

Make a GET request to the Gitlab server for list-oriented queries.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **iterator (Optional[bool])** – Indicate if should return a generator (True)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo, page, per_page)
- **as_list (Optional[bool])** –

Returns

A list of the objects returned by the server. If `iterator` is True and no pagination-related arguments (`page`, `per_page`, `get_all`) are defined then a `GitlabList` object (generator) is returned instead. This object will make API calls when needed to fetch the next items from the server.

Raises

- `GitlabHttpError` – When the return code is not 2xx
- `GitlabParsingError` – If the json data could not be parsed

Return type

`Union[GitlabList, List[Dict[str, Any]]]`

`http_post(path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Dict[str, Any]] = None, raw: bool = False, files: Optional[Dict[str, Any]] = None, **kwargs: Any) → Union[Dict[str, Any], Response]`

Make a POST request to the Gitlab server.

Parameters

- `path (str)` – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projecs')
- `query_data (Optional[Dict[str, Any]])` – Data to send as query parameters
- `post_data (Optional[Dict[str, Any]])` – Data to send in the body (will be converted to json by default)
- `raw (bool)` – If True, do not convert post_data to json
- `files (Optional[Dict[str, Any]])` – The files to send to the server
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The parsed json returned by the server if json is return, else the raw content

Raises

- `GitlabHttpError` – When the return code is not 2xx
- `GitlabParsingError` – If the json data could not be parsed

Return type

`Union[Dict[str, Any], Response]`

`http_put(path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Union[Dict[str, Any], bytes]] = None, raw: bool = False, files: Optional[Dict[str, Any]] = None, **kwargs: Any) → Union[Dict[str, Any], Response]`

Make a PUT request to the Gitlab server.

Parameters

- `path (str)` – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projecs')
- `query_data (Optional[Dict[str, Any]])` – Data to send as query parameters
- `post_data (Optional[Union[Dict[str, Any], bytes]])` – Data to send in the body (will be converted to json by default)
- `raw (bool)` – If True, do not convert post_data to json
- `files (Optional[Dict[str, Any]])` – The files to send to the server
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The parsed json returned by the server.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

```
http_request(verb: str, path: str, query_data: Optional[Dict[str, Any]] = None, post_data:  
            Optional[Union[Dict[str, Any], bytes]] = None, raw: bool = False, streamed: bool = False,  
            files: Optional[Dict[str, Any]] = None, timeout: Optional[float] = None, obey_rate_limit:  
            bool = True, retry_transient_errors: Optional[bool] = None, max_retries: int = 10,  
            **kwargs: Any) → Response
```

Make an HTTP request to the Gitlab server.

Parameters

- **verb (str)** – The HTTP method to call ('get', 'post', 'put', 'delete')
- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projecs')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **post_data (Optional[Union[Dict[str, Any], bytes]])** – Data to send in the body (will be converted to json by default)
- **raw (bool)** – If True, do not convert post_data to json
- **streamed (bool)** – Whether the data should be streamed
- **files (Optional[Dict[str, Any]])** – The files to send to the server
- **timeout (Optional[float])** – The timeout, in seconds, for the request
- **obey_rate_limit (bool)** – Whether to obey 429 Too Many Requests responses. Defaults to True.
- **retry_transient_errors (Optional[bool])** – Whether to retry after 500, 502, 503, 504 or 52x responses. Defaults to False.
- **max_retries (int)** – Max retries after 429 or transient errors, set to -1 to retry forever. Defaults to 10.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

A requests result object.

Raises

GitlabHttpError – When the return code is not 2xx

Return type

Response

issues

See [IssueManager](#)

issues_statistics

See [IssuesStatisticsManager](#)

keys

See [KeyManager](#)

ldapgroups

See [LDAPGroupManager](#)

licenses

See [LicenseManager](#)

lint(*content*: str, ***kwargs*: Any) → Tuple[bool, List[str]]

Validate a gitlab CI configuration.

Parameters

- **content** (str) – The .gitlab-ci.yml content
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabVerifyError** – If the validation could not be done

Returns

(True, []) if the file is valid, (False, errors(list)) otherwise

Return type

Tuple[bool, List[str]]

markdown(*text*: str, *gfm*: bool = False, *project*: Optional[str] = None, ***kwargs*: Any) → str

Render an arbitrary Markdown document.

Parameters

- **text** (str) – The markdown text to render
- **gfm** (bool) – Render text using GitLab Flavored Markdown. Default is False
- **project** (Optional[str]) – Full path of a project used a context when *gfm* is True
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMarkdownError** – If the server cannot perform the request

Returns

The HTML rendering of the markdown text.

Return type

str

classmethod merge_config(*options*: Dict[str, Any], *gitlab_id*: Optional[str] = None, *config_files*: Optional[List[str]] = None) → [Gitlab](#)

Create a Gitlab connection by merging configuration with the following precedence:

1. Explicitly provided CLI arguments,
2. Environment variables,
3. Configuration files:
 - a. explicitly defined config files:

- i. via the `-config-file` CLI argument,
 - ii. via the `PYTHON_GITLAB_CFG` environment variable,
- b. user-specific config file,
 - c. system-level config file,
4. Environment variables always present in CI (`CI_SERVER_URL`, `CI_JOB_TOKEN`).

Parameters

- **options** (`Dict[str, Any]`) – A dictionary of explicitly provided key-value options.
- **gitlab_id** (`Optional[str]`) – ID of the configuration section.
- **config_files** (`Optional[List[str]]`) – List of paths to configuration files.

Returns

A Gitlab connection.

Return type

`(gitlab.Gitlab)`

Raises

`gitlab.config.GitlabDataError` – If the configuration is not correct.

mergerequests

See `MergeRequestManager`

namespaces

See `NamespaceManager`

notificationsettings

See `NotificationSettingsManager`

pagesdomains

See `PagesDomainManager`

personal_access_tokens

See `PersonalAccessTokenManager`

projects

See `ProjectManager`

registry_repositories

See `RegistryRepositoryManager`

runners

See `RunnerManager`

runners_all

See `RunnerManager`

search(`scope: str, search: str, **kwargs: Any`) → Union[`GitlabList`, `List[Dict[str, Any]]`]

Search GitLab resources matching the provided string.'

Parameters

- **scope** (`str`) – Scope of the search
- **search** (`str`) – Search string
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSearchError** – If the server failed to perform the request

Returns

A list of dicts describing the resources found.

Return type

Union[GitlabList, List[Dict[str, Any]]]

session

Create a session object for requests

set_license(license: str, **kwargs: Any) → Dict[str, Any]

Add a new license.

Parameters

- **license (str)** – The license string
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPostError** – If the server cannot perform the request

Returns

The new license information

Return type

Dict[str, Any]

settings

See [ApplicationSettingsManager](#)

sidekiq

See [SidekiqManager](#)

snippets

See [SnippetManager](#)

ssl_verify

Whether SSL certificates should be validated

timeout

Timeout to use for requests to gitlab server

todos

See [TodoManager](#)

topics

See [TopicManager](#)

property url: str

The user-provided server URL.

user_activities

See [UserActivitiesManager](#)

users

See [UserManager](#)

variables

See [VariableManager](#)

version() → Tuple[str, str]

Returns the version and revision of the gitlab server.

Note that self.version and self.revision will be set on the gitlab object.

Returns**The server version and server revision.**

(‘unknown’, ‘unknown’) if the server doesn’t perform as expected.

Return type

Tuple[str, str]

exception `gitlab.GitlabActivateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabAttachFileError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabAuthenticationError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: [GitlabError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabBanError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabBlockError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabBuildCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabCancelError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabBuildEraseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabRetryError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabBuildPlayError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabRetryError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabBuildRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabCherryPickError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabCiLintError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabConnectionError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabCreateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabDeactivateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabDeleteError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabDeploymentApprovalError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *Exception*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabFollowError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabGetError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabGroupTransferError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: `GitlabOperationError`

Parameters

- `error_message` (`Union[str, bytes]`) –
- `response_code` (`Optional[int]`) –
- `response_body` (`Optional[bytes]`) –

Return type

`None`

exception `gitlab.GitlabHeadError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- `error_message` (`Union[str, bytes]`) –
- `response_code` (`Optional[int]`) –
- `response_body` (`Optional[bytes]`) –

Return type

`None`

exception `gitlab.GitlabHousekeepingError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- `error_message` (`Union[str, bytes]`) –
- `response_code` (`Optional[int]`) –
- `response_body` (`Optional[bytes]`) –

Return type

`None`

exception `gitlab.GitlabHttpError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabError`

Parameters

- `error_message` (`Union[str, bytes]`) –
- `response_code` (`Optional[int]`) –
- `response_body` (`Optional[bytes]`) –

Return type

`None`

exception `gitlab.GitlabImportError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabInvitationError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabJobCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabCancelError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabJobEraseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabJobPlayError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabJobRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabRetryError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabLicenseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
class gitlab.GitlabList(gl: Gitlab, url: str, query_data: Dict[str, Any], get_next: bool = True, **kwargs: Any)
```

Bases: [object](#)

Generator representing a list of remote objects.

The object handles the links returned by a query to the API, and will call the API again when needed.

Parameters

- **gl** ([Gitlab](#)) –
- **url** (*str*) –
- **query_data** (*Dict[str, Any]*) –
- **get_next** (*bool*) –
- **kwargs** (*Any*) –

property current_page: int

The current page number.

next() → *Dict[str, Any]*

Return type
Dict[str, Any]

property next_page: Optional[int]

The next page number.

If None, the current page is the last.

property per_page: Optional[int]

The number of items per page.

property prev_page: Optional[int]

The previous page number.

If None, the current page is the first.

property total: Optional[int]

The total number of items.

property total_pages: Optional[int]

The total number of pages.

exception gitlab.GitlabListError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception gitlab.GitlabMRApprovalError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception gitlab.GitlabMRClosedError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception gitlab.GitlabMRForbiddenError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabMROnBuildSuccessError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabMRRebaseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabMRResetApprovalError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabMarkdownError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: `GitlabOperationError`

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –

- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabOperationError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabOwnershipError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabParsingError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabPipelineCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabCancelError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabPipelinePlayError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabRetryError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabPipelineRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabRetryError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabProjectDeployKeyError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabPromoteError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

`None`

```
exception gitlab.GitlabProtectError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabRenderError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabRepairError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabRestoreError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabRevertError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabSearchError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabSetError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

exception `gitlab.GitlabStopError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)`

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabSubscribeError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabTimeTrackingError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabTodoError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabTransferProjectError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUnbanError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUnblockError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUnfollowError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUnsubscribeError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUpdateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUploadError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUserApproveError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabUserRejectError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.GitlabVerifyError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.RedirectError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
class gitlab.Gitlab(url: Optional[str] = None, private_token: Optional[str] = None, oauth_token: Optional[str] = None, job_token: Optional[str] = None, ssl_verify: Union[bool, str] = True, http_username: Optional[str] = None, http_password: Optional[str] = None, timeout: Optional[float] = None, api_version: str = '4', session: Optional[Session] = None, per_page: Optional[int] = None, pagination: Optional[str] = None, order_by: Optional[str] = None, user_agent: str = 'python-gitlab/3.10.0', retry_transient_errors: bool = False, keep_base_url: bool = False)
```

Bases: [object](#)

Represents a GitLab server connection.

Parameters

- **url** (*Optional[str]*) – The URL of the GitLab server (defaults to <https://gitlab.com>).
- **private_token** (*Optional[str]*) – The user private token
- **oauth_token** (*Optional[str]*) – An oauth token
- **job_token** (*Optional[str]*) – A CI job token
- **ssl_verify** (*Union[bool, str]*) – Whether SSL certificates should be validated. If the value is a string, it is the path to a CA file used for certificate validation.
- **timeout** (*Optional[float]*) – Timeout to use for requests to the GitLab server.
- **http_username** (*Optional[str]*) – Username for HTTP authentication
- **http_password** (*Optional[str]*) – Password for HTTP authentication
- **api_version** (*str*) – Gitlab API version to use (support for 4 only)
- **pagination** (*Optional[str]*) – Can be set to ‘keyset’ to use keyset pagination
- **order_by** (*Optional[str]*) – Set order_by globally
- **user_agent** (*str*) – A custom user agent to use for making HTTP requests.
- **retry_transient_errors** (*bool*) – Whether to retry after 500, 502, 503, 504 or 52x responses. Defaults to False.
- **keep_base_url** (*bool*) – keep user-provided base URL for pagination if it differs from response headers
- **session** (*Optional[Session]*) –
- **per_page** (*Optional[int]*) –

property api_url: str

The computed API base URL.

property api_version: str

The API version used (4 only).

appearance

See [ApplicationAppearanceManager](#)

applications

See [ApplicationManager](#)

audit_events

See [AuditEventManager](#)

auth() → None

Performs an authentication using private token. Warns the user if a potentially misconfigured URL is detected on the client or server side.

The *user* attribute will hold a *gitlab.objects.CurrentUser* object on success.

Return type

None

broadcastmessages

See [BroadcastMessageManager](#)

ci_lint

See [CiLintManager](#)

deploykeys

See [DeployKeyManager](#)

deploytokens

See [DeployTokenManager](#)

dockerfiles

See [DockerfileManager](#)

static enable_debug() → None**Return type**

None

events

See [EventManager](#)

features

See [FeatureManager](#)

classmethod from_config(gitlab_id: Optional[str] = None, config_files: Optional[List[str]] = None) → Gitlab

Create a Gitlab connection from configuration files.

Parameters

- **gitlab_id** (*Optional[str]*) – ID of the configuration section.
- **list[str]** (*config_files*) – List of paths to configuration files.
- **config_files** (*Optional[List[str]]*) –

Returns

A Gitlab connection.

Raises

`gitlab.config.GitlabDataError` – If the configuration is not correct.

Return type

`Gitlab`

geonodes

See [GeoNodeManager](#)

get_license(kwargs: Any) → Dict[str, Any]**

Retrieve information about the current license.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Returns

The current license information

Return type

`Dict[str, Any]`

gitignores

See [GitignoreManager](#)

gitlabciymls

See [GitlabciymlManager](#)

groups

See [GroupManager](#)

headers

Headers that will be used in request to GitLab

hooks

See [HookManager](#)

http_delete(path: str, **kwargs: Any) → Response

Make a DELETE request to the Gitlab server.

Parameters

- `path (str)` – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The requests object.

Raises

`GitlabHttpError` – When the return code is not 2xx

Return type

`Response`

http_get(path: str, query_data: Optional[Dict[str, Any]] = None, streamed: bool = False, raw: bool = False, **kwargs: Any) → Union[Dict[str, Any], Response]

Make a GET request to the Gitlab server.

Parameters

- **path** (str) – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data** (Optional[Dict[str, Any]]) – Data to send as query parameters
- **streamed** (bool) – Whether the data should be streamed
- **raw** (bool) – If True do not try to parse the output as json
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

A requests result object is streamed is True or the content type is not json. The parsed json data otherwise.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

http_head(path: str, query_data: Optional[Dict[str, Any]] = None, **kwargs: Any) → requests.structures.CaseInsensitiveDict[Any]

Make a HEAD request to the Gitlab server.

Parameters

- **path** (str) – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data** (Optional[Dict[str, Any]]) – Data to send as query parameters
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo, page, per_page)

Returns

A requests.header object

Raises

GitlabHttpError – When the return code is not 2xx

Return type

requests.structures.CaseInsensitiveDict[Any]

http_list(path: str, query_data: Optional[Dict[str, Any]] = None, *, as_list: Optional[bool] = None, iterator: Optional[bool] = None, **kwargs: Any) → Union[[GitlabList](#), List[Dict[str, Any]]]

Make a GET request to the Gitlab server for list-oriented queries.

Parameters

- **path** (str) – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data** (Optional[Dict[str, Any]]) – Data to send as query parameters
- **iterator** (Optional[bool]) – Indicate if should return a generator (True)

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo, page, per_page)
- **as_list (Optional[bool])** –

Returns

A list of the objects returned by the server. If *iterator* is True and no pagination-related arguments (*page*, *per_page*, *get_all*) are defined then a GitlabList object (generator) is returned instead. This object will make API calls when needed to fetch the next items from the server.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[GitlabList, List[Dict[str, Any]]]

http_post(*path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Dict[str, Any]] = None, raw: bool = False, files: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *Union[Dict[str, Any], Response]*

Make a POST request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters
- **post_data (Optional[Dict[str, Any]])** – Data to send in the body (will be converted to json by default)
- **raw (bool)** – If True, do not convert post_data to json
- **files (Optional[Dict[str, Any]])** – The files to send to the server
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The parsed json returned by the server if json is return, else the raw content

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

http_put(*path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Union[Dict[str, Any], bytes]] = None, raw: bool = False, files: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *Union[Dict[str, Any], Response]*

Make a PUT request to the Gitlab server.

Parameters

- **path (str)** – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data (Optional[Dict[str, Any]])** – Data to send as query parameters

- **post_data** (*Optional[Union[Dict[str, Any], bytes]]*) – Data to send in the body (will be converted to json by default)
- **raw** (*bool*) – If True, do not convert post_data to json
- **files** (*Optional[Dict[str, Any]]*) – The files to send to the server
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The parsed json returned by the server.

Raises

- **GitlabHttpError** – When the return code is not 2xx
- **GitlabParsingError** – If the json data could not be parsed

Return type

Union[Dict[str, Any], Response]

http_request(*verb: str, path: str, query_data: Optional[Dict[str, Any]] = None, post_data: Optional[Union[Dict[str, Any], bytes]] = None, raw: bool = False, streamed: bool = False, files: Optional[Dict[str, Any]] = None, timeout: Optional[float] = None, obey_rate_limit: bool = True, retry_transient_errors: Optional[bool] = None, max_retries: int = 10, **kwargs: Any*) → Response

Make an HTTP request to the Gitlab server.

Parameters

- **verb** (*str*) – The HTTP method to call ('get', 'post', 'put', 'delete')
- **path** (*str*) – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')
- **query_data** (*Optional[Dict[str, Any]]*) – Data to send as query parameters
- **post_data** (*Optional[Union[Dict[str, Any], bytes]]*) – Data to send in the body (will be converted to json by default)
- **raw** (*bool*) – If True, do not convert post_data to json
- **streamed** (*bool*) – Whether the data should be streamed
- **files** (*Optional[Dict[str, Any]]*) – The files to send to the server
- **timeout** (*Optional[float]*) – The timeout, in seconds, for the request
- **obey_rate_limit** (*bool*) – Whether to obey 429 Too Many Requests responses. Defaults to True.
- **retry_transient_errors** (*Optional[bool]*) – Whether to retry after 500, 502, 503, 504 or 52x responses. Defaults to False.
- **max_retries** (*int*) – Max retries after 429 or transient errors, set to -1 to retry forever. Defaults to 10.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

A requests result object.

Raises

GitlabHttpError – When the return code is not 2xx

Return type

Response

issues

See [IssueManager](#)

issues_statistics

See [IssuesStatisticsManager](#)

keys

See [KeyManager](#)

ldapgroups

See [LDAPGroupManager](#)

licenses

See [LicenseManager](#)

lint(*content*: str, *kwargs*: Any) → Tuple[bool, List[str]]**

Validate a gitlab CI configuration.

Parameters

- **content (str)** – The .gitlab-ci.yml content
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabVerifyError** – If the validation could not be done

Returns

(True, []) if the file is valid, (False, errors(list)) otherwise

Return type

Tuple[bool, List[str]]

markdown(*text*: str, *gfm*: bool = False, *project*: Optional[str] = None, *kwargs*: Any) → str**

Render an arbitrary Markdown document.

Parameters

- **text (str)** – The markdown text to render
- **gfm (bool)** – Render text using GitLab Flavored Markdown. Default is False
- **project (Optional[str])** – Full path of a project used a context when *gfm* is True
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMarkdownError** – If the server cannot perform the request

Returns

The HTML rendering of the markdown text.

Return type

str

```
classmethod merge_config(options: Dict[str, Any], gitlab_id: Optional[str] = None, config_files: Optional[List[str]] = None) → Gitlab
```

Create a Gitlab connection by merging configuration with the following precedence:

1. Explicitly provided CLI arguments,
2. Environment variables,
3. **Configuration files:**
 - a. **explicitly defined config files:**
 - i. via the `-config-file` CLI argument,
 - ii. via the `PYTHON_GITLAB_CFG` environment variable,
 - b. user-specific config file,
 - c. system-level config file,
4. Environment variables always present in CI (`CI_SERVER_URL`, `CI_JOB_TOKEN`).

Parameters

- **options** (`Dict[str, Any]`) – A dictionary of explicitly provided key-value options.
- **gitlab_id** (`Optional[str]`) – ID of the configuration section.
- **config_files** (`Optional[List[str]]`) – List of paths to configuration files.

Returns

A Gitlab connection.

Return type

`(gitlab.Gitlab)`

Raises

`gitlab.config.GitlabDataError` – If the configuration is not correct.

mergerequests

See `MergeRequestManager`

namespaces

See `NamespaceManager`

notificationsettings

See `NotificationSettingsManager`

pagesdomains

See `PagesDomainManager`

personal_access_tokens

See `PersonalAccessTokenManager`

projects

See `ProjectManager`

registry_repositories

See `RegistryRepositoryManager`

runners

See `RunnerManager`

runners_all

See [RunnerManager](#)

search(scope: str, search: str, **kwargs: Any) → Union[GitlabList, List[Dict[str, Any]]]

Search GitLab resources matching the provided string.'

Parameters

- **scope (str)** – Scope of the search
- **search (str)** – Search string
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSearchError** – If the server failed to perform the request

Returns

A list of dicts describing the resources found.

Return type

Union[GitlabList, List[Dict[str, Any]]]

session

Create a session object for requests

set_license(license: str, **kwargs: Any) → Dict[str, Any]

Add a new license.

Parameters

- **license (str)** – The license string
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPostError** – If the server cannot perform the request

Returns

The new license information

Return type

Dict[str, Any]

settings

See [ApplicationSettingsManager](#)

sidekiq

See [SidekiqManager](#)

snippets

See [SnippetManager](#)

ssl_verify

Whether SSL certificates should be validated

timeout

Timeout to use for requests to gitlab server

todos

See [TodoManager](#)

topics

See [TopicManager](#)

property url: str

The user-provided server URL.

user: Optional[objects.CurrentUser]**user_activities**

See [UserActivitiesManager](#)

users

See [UserManager](#)

variables

See [VariableManager](#)

version() → Tuple[str, str]

Returns the version and revision of the gitlab server.

Note that self.version and self.revision will be set on the gitlab object.

Returns**The server version and server revision.**

('unknown', 'unknown') if the server doesn't perform as expected.

Return type

Tuple[str, str]

```
class gitlab.GitlabList(gl: Gitlab, url: str, query_data: Dict[str, Any], get_next: bool = True, **kwargs: Any)
```

Bases: *object*

Generator representing a list of remote objects.

The object handles the links returned by a query to the API, and will call the API again when needed.

Parameters

- **gl (Gitlab) –**
- **url (str) –**
- **query_data (Dict[str, Any]) –**
- **get_next (bool) –**
- **kwargs (Any) –**

property current_page: int

The current page number.

next() → Dict[str, Any]**Return type**

Dict[str, Any]

```
property next_page: Optional[int]
    The next page number.
    If None, the current page is the last.
property per_page: Optional[int]
    The number of items per page.
property prev_page: Optional[int]
    The previous page number.
    If None, the current page is the first.
property total: Optional[int]
    The total number of items.
property total_pages: Optional[int]
    The total number of pages.
```

6.6.2 Subpackages

gitlab.v4 package

Submodules

gitlab.v4.objects module

```
class gitlab.v4.objects.Application(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:
    bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ApplicationAppearance(manager: RESTManager, attrs: Dict[str, Any], *,
    created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ApplicationAppearanceManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin*, *UpdateMixin*, *RESTManager*

Object Creation

Object update

Optional attributes for object update:

- title
- description
- logo
- header_logo
- favicon
- new_project_guidelines
- header_message
- footer_message
- message_background_color
- message_font_color
- email_header_and_footer_enabled

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(***kwargs: Any*) → *ApplicationAppearance*

Retrieve a single object.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ApplicationAppearance

gitlab: *Gitlab*

update(*id: Optional[Union[int, str]] = None*, *new_data: Optional[Dict[str, Any]] = None*, ***kwargs: Any*) → *Dict[str, Any]*

Update an object on the server.

Parameters

- **id** (*Optional[Union[int, str]]*) – ID of the object to update (can be None if not required)

- **new_data** (*Optional[Dict[str, Any]]*) – the update data for the object
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The new object data (*not* a RESTObject)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server cannot perform the request

Return type

Dict[str, Any]

class gitlab.v4.objects.ApplicationManager(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: *ListMixin, CreateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- **name**
- **redirect_uri**
- **scopes**

Optional attributes for object create:

- **confidential**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

class gitlab.v4.objects.ApplicationSettings(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *SaveMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

class gitlab.v4.objects.ApplicationSettingsManager(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: *GetWithoutIdMixin, UpdateMixin, RESTManager*

Object Creation

Object update

Optional attributes for object update:

- `id`
- `default_projects_limit`
- `signup_enabled`
- `password_authentication_enabled_for_web`
- `gravatar_enabled`
- `sign_in_text`
- `created_at`
- `updated_at`
- `home_page_url`
- `default_branch_protection`
- `restricted_visibility_levels`
- `max_attachment_size`
- `session_expire_delay`
- `default_project_visibility`
- `default_snippet_visibility`
- `default_group_visibility`
- `outbound_local_requests_whitelist`
- `disabled_oauth_sign_in_sources`
- `domain_whitelist`
- `domain_blacklist_enabled`
- `domain_blacklist`
- `domain_allowlist`
- `domain_denylist_enabled`
- `domain_denylist`
- `external_authorization_service_enabled`
- `external_authorization_service_url`
- `external_authorization_service_default_label`
- `external_authorization_service_timeout`
- `import_sources`
- `user_oauth_applications`
- `after_sign_out_path`
- `container_registry_token_expire_delay`
- `repository_storages`
- `plantuml_enabled`
- `plantuml_url`
- `terminal_max_session_time`

- `polling_interval_multiplier`
- `rsa_key_restriction`
- `dsa_key_restriction`
- `ecdsa_key_restriction`
- `ed25519_key_restriction`
- `first_day_of_week`
- `enforce_terms`
- `terms`
- `performance_bar_allowed_group_id`
- `instance_statistics_visibility_private`
- `user_show_add_ssh_key_message`
- `file_template_project_id`
- `local_markdown_version`
- `asset_proxy_enabled`
- `asset_proxy_url`
- `asset_proxy_whitelist`
- `asset_proxy_allowlist`
- `geo_node_allowed_ips`
- `allow_local_requests_from_hooks_and_services`
- `allow_local_requests_from_web_hooks_and_services`
- `allow_local_requests_from_system_hooks`

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`get(**kwargs: Any) → ApplicationSettings`

Retrieve a single object.

Parameters

`**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ApplicationSettings`

`gitlab: Gitlab`

```
update(id: Optional[Union[int, str]] = None, new_data: Optional[Dict[str, Any]] = None, **kwargs: Any)  
    → Dict[str, Any]
```

Update an object on the server.

Parameters

- ***id*** (*Optional[Union[int, str]]*) – ID of the object to update (can be *None* if not required)
- ***new_data*** (*Optional[Dict[str, Any]]*) – the update data for the object
- *****kwargs*** (*Any*) – Extra options to send to the server (e.g. *sudo*)

Returns

The new object data (*not* a *RESTObject*)

Raises

- ***GitlabAuthenticationError*** – If authentication is not correct
- ***GitlabUpdateError*** – If the server cannot perform the request

Return type

Dict[str, Any]

```
class gitlab.v4.objects.AuditEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
    bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- ***manager*** (*RESTManager*) –
- ***attrs*** (*Dict[str, Any]*) –
- ***created_from_list*** (*bool*) –
- ***lazy*** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.AuditEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin*, *RESTManager*

Object listing filters

- *created_after*
- *created_before*
- *entity_type*
- *entity_id*

Object Creation

Object update

Parameters

- ***gl*** (*Gitlab*) –
- ***parent*** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → AuditEvent
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`AuditEvent`

gitlab: `Gitlab`

```
class gitlab.v4.objects.BroadcastMessage(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.BroadcastMessageManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `message`

Optional attributes for object create:

- `starts_at`
- `ends_at`
- `color`
- `font`
- `target_access_levels`

Object update

Optional attributes for object update:

- `message`

- `starts_at`
- `ends_at`
- `color`
- `font`
- `target_access_levels`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → BroadcastMessage`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`BroadcastMessage`

`gitlab: Gitlab`

`class gitlab.v4.objects.CiLint(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.CiLintManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CreateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `content`

Optional attributes for object create:

- `include_merged_yaml`
- `include_jobs`

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`gitlab: Gitlab`

`validate(*args: Any, **kwargs: Any) → None`

Raise an error if the CI Lint results are not valid.

This is a custom python-gitlab method to wrap lint endpoints.

Parameters

- `args (Any) –`
- `kwargs (Any) –`

Return type

`None`

`class gitlab.v4.objects.CurrentUser(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

`emails: CurrentUserEmailManager`

`gpgkeys: CurrentUserGPGKeyManager`

`keys: CurrentUserKeyManager`

`status: CurrentUserStatusManager`

`class gitlab.v4.objects.CurrentUserEmail(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

manager: `RESTManager`

class `gitlab.v4.objects.CurrentUserEmailManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)
Bases: `RetrieveMixin, CreateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- `email`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(`id: Union[str, int], lazy: bool = False, **kwargs: Any`) → `CurrentUserEmail`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`CurrentUserEmail`

gitlab: `Gitlab`

class `gitlab.v4.objects.CurrentUserGPGKey`(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

manager: `RESTManager`

class `gitlab.v4.objects.CurrentUserGPGKeyManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)
Bases: `RetrieveMixin, CreateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- key

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → CurrentUserGPGKey`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`CurrentUserGPGKey`

`gitlab: Gitlab`

`class gitlab.v4.objects.CurrentUserKey(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.CurrentUserKeyManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, CreateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- `title`
- `key`

Object update

Parameters

- `gl (Gitlab)` –

- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *CurrentUserKey*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

CurrentUserKey

gitlab: *Gitlab*

class *gitlab.v4.objects.CurrentUserManager*(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)

Bases: *GetWithoutIdMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(***kwargs: Any*) → *CurrentUser*

Retrieve a single object.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

CurrentUser

gitlab: *Gitlab*

class *gitlab.v4.objects.CurrentUserStatus*(*manager: RESTManager*, *attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *SaveMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.CurrentUserStatusManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `GetWithoutIdMixin, UpdateMixin, RESTManager`

Object Creation

Object update

Optional attributes for object update:

- `emoji`
- `message`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(kwargs: Any) → CurrentUserStatus**

Retrieve a single object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`CurrentUserStatus`

gitlab: `Gitlab`

class `gitlab.v4.objects.DeployKey`(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.DeployKeyManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, RESTManager
```

Object Creation

Object update

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.DeployToken(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:
    bool = False, lazy: bool = False)
```

Bases: ObjectDeleteMixin, RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: *RESTManager*

```
class gitlab.v4.objects.DeployTokenManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: ListMixin, RESTManager

Object Creation

Object update

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.Dockerfile(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:
    bool = False, lazy: bool = False)
```

Bases: RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: *RESTManager*

```
class gitlab.v4.objects.DockerfileManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** ([Optional\[RESTObject\]](#)) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → Dockerfile
```

Retrieve a single object.

Parameters

- **id** ([Union\[str, int\]](#)) – ID of the object to retrieve
- **lazy** ([bool](#)) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** ([Any](#)) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[Dockerfile](#)

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.Event(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** ([Dict\[str, Any\]](#)) –
- **created_from_list** ([bool](#)) –
- **lazy** ([bool](#)) –

manager: [RESTManager](#)

```
class gitlab.v4.objectsEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- **action**
- **target_type**
- **before**
- **after**

- `sort`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.Feature(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.FeatureManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `ListMixin, DeleteMixin, RESTManager`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
set(name: str, value: Union[bool, int], feature_group: Optional[str] = None, user: Optional[str] = None, group: Optional[str] = None, project: Optional[str] = None, **kwargs: Any) → Feature
```

Create or update the object.

Parameters

- `name (str)` – The value to set for the object
- `value (Union[bool, int])` – The value to set for the object
- `feature_group (Optional[str])` – A feature group name
- `user (Optional[str])` – A GitLab username
- `group (Optional[str])` – A GitLab group
- `project (Optional[str])` – A GitLab project in form group/project
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct

- **GitlabSetError** – If an error occurred

Returns

The created/updated attribute

Return type

Feature

```
class gitlab.v4.objects.GenericPackage(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GenericPackageManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
download(package_name: str, package_version: str, file_name: str, streamed: bool = False, action:  
        Optional[Callable[[bytes], None]] = None, chunk_size: int = 1024, *, iterator: bool = False,  
        **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]
```

Download a generic package.

Parameters

- **package_name** (*str*) – The package name.
- **package_version** (*str*) – The package version.
- **file_name** (*str*) – The name of the file in the registry
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[[bytes], None]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The package content if streamed is False, None otherwise

Return type

Optional[Union[bytes, Iterator[Any]]]

gitlab: `Gitlab`

upload(*package_name*: str, *package_version*: str, *file_name*: str, *path*: Union[str, Path], ***kwargs*: Any) → `GenericPackage`

Upload a file as a generic package.

Parameters

- **package_name** (str) – The package name. Must follow generic package name regex rules
- **package_version** (str) – The package version. Must follow semantic version regex rules
- **file_name** (str) – The name of the file as uploaded in the registry
- **path** (Union[str, Path]) – The path to a local file to upload
- **kwargs** (Any) –

Raises

- **GitlabConnectionError** – If the server cannot be reached
- **GitlabUploadError** – If the file upload fails
- **GitlabUploadError** – If `filepath` cannot be read

Returns

An object storing the metadata of the uploaded package.

Return type

`GenericPackage`

https://docs.gitlab.com/ee/user/packages/generic_packages/

class `gitlab.v4.objects.GeoNode`(*manager*: RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False, *lazy*: bool = False)

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: `RESTManager`

repair(***kwargs*: Any) → None

Repair the OAuth authentication of the geo node.

Parameters

****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabRepairError** – If the server failed to perform the request

Return type

None

status(kwargs: Any) → Dict[str, Any]**

Get the status of the geo node.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The status of the geo node

Return type

Dict[str, Any]

class gitlab.v4.objects.GeoNodeManager(gl: Gitlab, parent: Optional[RESTObject] = None)

Bases: *RetrieveMixin, UpdateMixin, DeleteMixin, RESTManager*

Object Creation

Object update

Optional attributes for object update:

- enabled
- url
- files_max_capacity
- repos_max_capacity

Parameters

- **gl (Gitlab)** –
- **parent (Optional[RESTObject])** –

current_failures(kwargs: Any) → List[Dict[str, Any]]**

Get the list of failures on the current geo node.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The list of failures

Return type

List[Dict[str, Any]]

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *GeoNode*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GeoNode

gitlab: *Gitlab*

status(***kwargs: Any*) → *List[Dict[str, Any]]*

Get the status of all the geo nodes.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The status of all the geo nodes

Return type

List[Dict[str, Any]]

class gitlab.v4.objects.Gitignore(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

class gitlab.v4.objects.GitignoreManager(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)

Bases: *RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [Gitignore](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[Gitignore](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.Gitlabciyml](#)(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)

Bases: [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: [RESTManager](#)

class [gitlab.v4.objects.GitlabciymlManager](#)(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)

Bases: [RetrieveMixin](#), [RESTManager](#)

Object Creation

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [Gitlabciyml](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Gitlabciyml

gitlab: *Gitlab*

class `gitlab.v4.objects.Group(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

access_tokens: *GroupAccessTokenManager*

accessrequests: *GroupAccessRequestManager*

add_ldap_group_link(*cn: str, group_access: int, provider: str, **kwargs: Any*) → None

Add an LDAP group link.

Parameters

- **cn** (*str*) – CN of the LDAP group
- **group_access** (*int*) – Minimum access level for members of the LDAP group
- **provider** (*str*) – LDAP provider for the LDAP group
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Return type

None

audit_events: *GroupAuditEventManager*

badges: *GroupBadgeManager*

billable_members: *GroupBillableMemberManager*

boards: *GroupBoardManager*
clusters: *GroupClusterManager*
customattributes: *GroupCustomAttributeManager*
delete_ldap_group_link(*cn: str, provider: Optional[str] = None, **kwargs: Any*) → None
Delete an LDAP group link.

Parameters

- **cn** (*str*) – CN of the LDAP group
- **provider** (*Optional[str]*) – LDAP provider for the LDAP group
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

None

deploytokens: *GroupDeployTokenManager*
descendant_groups: *GroupDescendantGroupManager*
epics: *GroupEpicManager*
exports: *GroupExportManager*
hooks: *GroupHookManager*
imports: *GroupImportManager*
invitations: *GroupInvitationManager*
issues: *GroupIssueManager*
issues_statistics: *GroupIssuesStatisticsManager*
iterations: *GroupIterationManager*
labels: *GroupLabelManager*
ldap_sync(***kwargs: Any*) → None
Sync LDAP groups.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Return type

None

members: *GroupMemberManager*

```
members_all: GroupMemberAllManager
mergerequests: GroupMergeRequestManager
milestones: GroupMilestoneManager
notificationsettings: GroupNotificationSettingsManager
packages: GroupPackageManager
projects: GroupProjectManager
pushrules: GroupPushRulesManager
registry_repositories: GroupRegistryRepositoryManager
runners: GroupRunnerManager
search(scope: str, search: str, **kwargs: Any) → Union[GitlabList, List[Dict[str, Any]]]
```

Search the group resources matching the provided string.

Parameters

- **scope (str)** – Scope of the search
- **search (str)** – Search string
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSearchError** – If the server failed to perform the request

Returns

A list of dicts describing the resources found.

Return type

Union[GitlabList, List[Dict[str, Any]]]

```
share(group_id: int, group_access: int, expires_at: Optional[str] = None, **kwargs: Any) → None
```

Share the group with a group.

Parameters

- **group_id (int)** – ID of the group.
- **group_access (int)** – Access level for the group.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)
- **expires_at (Optional[str])** –
- ****kwargs** –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server failed to perform the request

Returns

Group

Return type

None

shared_projects: *SharedProjectManager*

subgroups: *GroupSubgroupManager*

transfer(*group_id*: *Optional[int]* = *None*, ***kwargs*: *Any*) → None

Transfer the group to a new parent group or make it a top-level group.

Requires GitLab 14.6.

Parameters

- **group_id** (*Optional[int]*) – ID of the new parent group. When not specified, the group to transfer is instead turned into a top-level group.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGroupTransferError** – If the group could not be transferred

Return type

None

transfer_project(*project_id*: *int*, ***kwargs*: *Any*) → None

Transfer a project to this group.

Parameters

- **to_project_id** – ID of the project to transfer
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)
- **project_id** (*int*) –
- ****kwargs** –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTransferProjectError** – If the project could not be transferred

Return type

None

unshare(*group_id*: *int*, ***kwargs*: *Any*) → None

Delete a shared group link within a group.

Parameters

- **group_id** (*int*) – ID of the group.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server failed to perform the request

Return type

None

```
variables: GroupVariableManager
wikis: GroupWikiManager

class gitlab.v4.objects.GroupAccessRequest(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
Bases: AccessRequestMixin, ObjectDeleteMixin, RESTObject

    Parameters
        • manager (RESTManager) –
        • attrs (Dict[str, Any]) –
        • created_from_list (bool) –
        • lazy (bool) –

    manager: RESTManager

class gitlab.v4.objects.GroupAccessRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, CreateMixin, DeleteMixin, RESTManager

Object Creation
Object update

    Parameters
        • gl (Gitlab) –
        • parent (Optional[RESTObject]) –

    gitlab: Gitlab

class gitlab.v4.objects.GroupAccessToken(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
Bases: ObjectDeleteMixin, RESTObject

    Parameters
        • manager (RESTManager) –
        • attrs (Dict[str, Any]) –
        • created_from_list (bool) –
        • lazy (bool) –

    manager: RESTManager

class gitlab.v4.objects.GroupAccessTokenManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, CreateMixin, DeleteMixin, RESTManager

Object Creation

Required attributes for object create:
    • name
    • scopes

Optional attributes for object create:
    • access_level
    • expires_at
```

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

```
class gitlab.v4.objects.GroupAuditEvent(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.GroupAuditEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, RESTManager`

Object listing filters

- `created_after`
- `created_before`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `GroupAuditEvent`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`GroupAuditEvent`

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupBadge(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupBadgeManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *BadgeRenderMixin, CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- `link_url`
- `image_url`

Object update

Optional attributes for object update:

- `link_url`
- `image_url`

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *GroupBadge*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupBadge

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupBillableMember(manager: RESTManager, attrs: Dict[str, Any], *,  
                                             created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

memberships: *GroupBillableMemberMembershipManager*

```
class gitlab.v4.objects.GroupBillableMemberManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                 None)
```

Bases: *ListMixin, DeleteMixin, RESTManager*

Object listing filters

- `search`
- `sort`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupBillableMemberMembership(manager: RESTManager, attrs: Dict[str,  
                                         Any], *, created_from_list: bool = False, lazy:  
                                         bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupBillableMemberMembershipManager(gl: Gitlab, parent:  
                                                               Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional[RESTObject]*) –

gitlab: `Gitlab`

class `gitlab.v4.objects.GroupBoard`(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

lists: `GroupBoardListManager`

class `gitlab.v4.objects.GroupBoardList`(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.GroupBoardListManager`(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: *CRUDMixin, RESTManager*

Object Creation

Mutually exclusive attributes for object create:

- `label_id`
- `assignee_id`
- `milestone_id`

Object update

Required attributes for object update:

- `position`

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional[RESTObject]*) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupBoardList`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`GroupBoardList`

gitlab: `Gitlab`

`class gitlab.v4.objects.GroupBoardManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupBoard`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`GroupBoard`

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupCluster(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupClusterManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- `name`
- `platform_kubernetes_attributes`

Optional attributes for object create:

- `domain`
- `enabled`
- `managed`
- `environment_scope`

Object update

Optional attributes for object update:

- `name`
- `domain`
- `management_project_id`
- `platform_kubernetes_attributes`
- `environment_scope`

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

create(*data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *GroupCluster*

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – Parameters to send to the server to create the resource

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo or ‘ref_name’, ‘stage’, ‘name’, ‘all’)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Returns

A new instance of the `manage` object class build with
the data sent by the server

Return type

`GroupCluster`

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → `GroupCluster`

Retrieve a single object.

Parameters

- **id (Union[str, int])** – ID of the object to retrieve
- **lazy (bool)** – If True, don’t request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`GroupCluster`

gitlab: `Gitlab`

class `gitlab.v4.objects.GroupCustomAttribute`(*manager*: RESTManager, *attrs*: Dict[str, Any], *,
created_from_list: bool = False, *lazy*: bool = False)

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

manager: `RESTManager`

class `gitlab.v4.objects.GroupCustomAttributeManager`(*gl*: Gitlab, *parent*: Optional[RESTObject] = None)

Bases: `RetrieveMixin, SetMixin, DeleteMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional*[[RESTObject](#)]) –

get(*id*: *Union*[*str*, *int*], **lazy**: *bool* = *False*, ****kwargs**: *Any*) → [GroupCustomAttribute](#)

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[GroupCustomAttribute](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.GroupDeployToken](#)(*manager*: [RESTManager](#), *attrs*: *Dict*[*str*, *Any*], *, *created_from_list*: *bool* = *False*, **lazy**: *bool* = *False*)

Bases: [ObjectDeleteMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: [RESTManager](#)

class [gitlab.v4.objects.GroupDeployTokenManager](#)(*gl*: [Gitlab](#), **parent**: *Optional*[[RESTObject](#)] = *None*)

Bases: [RetrieveMixin](#), [CreateMixin](#), [DeleteMixin](#), [RESTManager](#)

Object listing filters

- **scopes**

Object Creation

Required attributes for object create:

- **name**
- **scopes**

Optional attributes for object create:

- **expires_at**
- **username**

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupDeployToken`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupDeployToken`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupDescendantGroup(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

`manager: RESTManager`

`class gitlab.v4.objects.GroupDescendantGroupManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `GroupSubgroupManager`

This manager inherits from `GroupSubgroupManager` as descendant groups share all attributes with subgroups, except the path and object class.

Object listing filters

- `skip_groups`
- `all_available`
- `search`
- `order_by`

- `sort`
- `statistics`
- `owned`
- `with_custom_attributes`
- `min_access_level`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

```
class gitlab.v4.objects.GroupEpic(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, SaveMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`issues: GroupEpicIssueManager`

`notes: GroupEpicNoteManager`

`resourcelabelevents: GroupEpicResourceLabelEventManager`

```
class gitlab.v4.objects.GroupEpicAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.GroupEpicAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `NoUpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `name`

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional*[[RESTObject](#)]) –

get(*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) → [GroupEpicAwardEmoji](#)

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[GroupEpicAwardEmoji](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.GroupEpicDiscussionNote](#)(*manager*: [RESTManager](#), *attrs*: *Dict*[*str*, *Any*], *, *created_from_list*: *bool* = *False*, *lazy*: *bool* = *False*)

Bases: [SaveMixin](#), [ObjectDeleteMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: [RESTManager](#)

class [gitlab.v4.objects.GroupEpicDiscussionNoteManager](#)(*gl*: [Gitlab](#), *parent*: *Optional*[[RESTObject](#)] = *None*)

Bases: [GetMixin](#), [CreateMixin](#), [UpdateMixin](#), [DeleteMixin](#), [RESTManager](#)

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at

Object update

Required attributes for object update:

- body

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional* [[RESTObject](#)]) –

get(*id*: *Union*[*str*, *int*], **lazy**: *bool* = *False*, ****kwargs**: *Any*) → [GroupEpicDiscussionNote](#)

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[GroupEpicDiscussionNote](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.GroupEpicIssue](#)(*manager*: [RESTManager](#), *attrs*: *Dict*[*str*, *Any*], *, *created_from_list*: *bool* = *False*, **lazy**: *bool* = *False*)

Bases: [ObjectDeleteMixin](#), [SaveMixin](#), [RESTObject](#)

Parameters

- **manager** ([GroupEpicIssueManager](#)) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: [GroupEpicIssueManager](#)

save(****kwargs**: *Any*) → None

Save the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server cannot perform the request

Return type

None

```
class gitlab.v4.objects.GroupEpicIssueManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager
```

Object Creation

Required attributes for object create:

- issue_id

Object update

Optional attributes for object update:

- move_before_id
- move_after_id

Parameters

- gl (Gitlab) –
- parent (Optional[RESTObject]) –

create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → GroupEpicIssue

Create a new object.

Parameters

- data (Optional[Dict[str, Any]]) – Parameters to send to the server to create the resource
- **kwargs (Any) – Extra options to send to the server (e.g. sudo)

Raises

- GitlabAuthenticationError – If authentication is not correct
- GitlabCreateError – If the server cannot perform the request

Returns

A new instance of the manage object class build with
the data sent by the server

Return type

GroupEpicIssue

gitlab: Gitlab

```
class gitlab.v4.objects.GroupEpicManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: CRUDMixin, RESTManager
```

Object listing filters

- author_id
- labels
- order_by
- sort
- search

Object Creation

Required attributes for object create:

- `title`

Optional attributes for object create:

- `labels`
- `description`
- `start_date`
- `end_date`

Object update

Optional attributes for object update:

- `title`
- `labels`
- `description`
- `start_date`
- `end_date`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupEpic`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupEpic`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupEpicNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –

- `created_from_list (bool) –`
- `lazy (bool) –`

`awardemojis: GroupEpicNoteAwardEmojiManager`

`class gitlab.v4.objects.GroupEpicNoteAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

`manager: RESTManager`

`class gitlab.v4.objects.GroupEpicNoteAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `NoUpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `name`

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupEpicNoteAwardEmoji`

Retrieve a single object.

Parameters

- `id (Union[str, int]) –` ID of the object to retrieve
- `lazy (bool) –` If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupEpicNoteAwardEmoji`

`gitlab: Gitlab`

```
class gitlab.v4.objects.GroupEpicNoteManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: CRUDMixin, RESTManager
```

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at

Object update

Required attributes for object update:

- body

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → GroupEpicNote

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupEpicNote

gitlab: Gitlab

```
class gitlab.v4.objects.GroupEpicResourceLabelEvent(manager: RESTManager, attrs: Dict[str, Any],
*, created_from_list: bool = False, lazy: bool = False)
```

Bases: RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

`manager: RESTManager`

`class gitlab.v4.objects.GroupEpicResourceLabelEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, RESTManager`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupEpicResourceLabelEvent`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupEpicResourceLabelEvent`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupExport(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `DownloadMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.GroupExportManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `GetWithoutIdMixin, CreateMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional[RESTObject]*) –

get(***kwargs: Any*) → `GroupExport`
Retrieve a single object.

Parameters
****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns
The generated RESTObject

Raises
• `GitlabAuthenticationError` – If authentication is not correct
• `GitlabGetError` – If the server cannot perform the request

Return type
`GroupExport`

gitlab: `Gitlab`

class `gitlab.v4.objects.GroupHook`(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)
Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.GroupHookManager`(*gl: Gitlab, parent: Optional[RESTObject] = None*)
Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `url`

Optional attributes for object create:

- `push_events`
- `issues_events`
- `confidential_issues_events`
- `merge_requests_events`
- `tag_push_events`
- `note_events`
- `confidential_note_events`
- `job_events`
- `pipeline_events`

- `wiki_page_events`
- `deployment_events`
- `releases_events`
- `subgroup_events`
- `enable_ssl_verification`
- `token`

Object update

Required attributes for object update:

- `url`

Optional attributes for object update:

- `push_events`
- `issues_events`
- `confidential_issues_events`
- `merge_requests_events`
- `tag_push_events`
- `note_events`
- `confidential_note_events`
- `job_events`
- `pipeline_events`
- `wiki_page_events`
- `deployment_events`
- `releases_events`
- `subgroup_events`
- `enable_ssl_verification`
- `token`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupHook`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupHook

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupImport(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
    bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupImportManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin, RESTManager*

Object Creation**Object update****Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → GroupImport**

Retrieve a single object.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupImport

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupInvitation(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin`, `ObjectDeleteMixin`, `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.GroupInvitationManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `InvitationMixin`, `RESTManager`

Object listing filters

- `query`

Object Creation

Required attributes for object create:

- `access_level`

Optional attributes for object create:

- `expires_at`
- `invite_source`
- `tasks_to_be_done`
- `tasks_project_id`

Mutually exclusive attributes for object create:

- `email`
- `user_id`

Object update

Optional attributes for object update:

- `access_level`
- `expires_at`

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `GroupInvitation`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupInvitation

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupIssue(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
    bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupIssueManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- state
- labels
- milestone
- order_by
- sort
- iids
- author_id
- assignee_id
- my_reaction_emoji
- search
- created_after
- created_before
- updated_after
- updated_before

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional[RESTObject]*) –

gitlab: `Gitlab`

```
class gitlab.v4.objects.GroupIssuesStatistics(manager: RESTManager, attrs: Dict[str, Any], *,  
                                              created_from_list: bool = False, lazy: bool = False)
```

Bases: `RefreshMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.GroupIssuesStatisticsManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                    None)
```

Bases: `GetWithoutIdMixin, RESTManager`

Object listing filters

- `iids`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → GroupIssuesStatistics**

Retrieve a single object.

Parameters

****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`GroupIssuesStatistics`

gitlab: `Gitlab`

```
class gitlab.v4.objects.GroupIteration(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupIterationManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- **state**
- **search**
- **include_ancestors**

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupLabel(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                         bool = False, lazy: bool = False)
```

Bases: *SubscribableMixin, SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*GroupLabelManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *GroupLabelManager*

save(kwargs: Any) → None**

Saves the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct.

- **GitlabUpdateError** – If the server cannot perform the request.

Return type

None

`class gitlab.v4.objects.GroupLabelManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- name
- color

Optional attributes for object create:

- description
- priority

Object update

Required attributes for object update:

- name

Optional attributes for object update:

- new_name
- color
- description
- priority

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupLabel`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`GroupLabel`

gitlab: Gitlab

update(name: Optional[str], new_data: Optional[Dict[str, Any]] = None, **kwargs: Any) → Dict[str, Any]
Update a Label on the server.

Parameters

- **name** (*Optional[str]*) – The name of the label
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)
- **new_data** (*Optional[Dict[str, Any]]*) –
- ****kwargs** –

Return type

Dict[str, Any]

class gitlab.v4.objects.GroupManager(gl: Gitlab, parent: Optional[RESTObject] = None)

Bases: *CRUDMixin, RESTManager*

Object listing filters

- `skip_groups`
- `all_available`
- `search`
- `order_by`
- `sort`
- `statistics`
- `owned`
- `with_custom_attributes`
- `min_access_level`
- `top_level_only`

Object Creation

Required attributes for object create:

- `name`
- `path`

Optional attributes for object create:

- `description`
- `membership_lock`
- `visibility`
- `share_with_group_lock`
- `require_two_factor_authentication`
- `two_factor_grace_period`
- `project_creation_level`
- `auto_devops_enabled`
- `subgroup_creation_level`

- emails_disabled
- avatar
- mentions_disabled
- lfs_enabled
- request_access_enabled
- parent_id
- default_branch_protection
- shared_runners_minutes_limit
- extra_shared_runners_minutes_limit

Object update

Optional attributes for object update:

- name
- path
- description
- membership_lock
- share_with_group_lock
- visibility
- require_two_factor_authentication
- two_factor_grace_period
- project_creation_level
- auto_devops_enabled
- subgroup_creation_level
- emails_disabled
- avatar
- mentions_disabled
- lfs_enabled
- request_access_enabled
- default_branch_protection
- file_template_project_id
- shared_runners_minutes_limit
- extra_shared_runners_minutes_limit
- prevent_forking_outside_group
- shared_runners_setting

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *Group*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Group

gitlab: *Gitlab*

import_group(*file: BinaryIO*, *path: str*, *name: str*, *parent_id: Optional[str] = None*, ***kwargs: Any*) → *Union[Dict[str, Any], Response]*

Import a group from an archive file.

Parameters

- **file** (*BinaryIO*) – Data or file object containing the group
- **path** (*str*) – The path for the new group to be imported.
- **name** (*str*) – The name for the new group.
- **parent_id** (*Optional[str]*) – ID of a parent group that the group will be imported into.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabImportError** – If the server failed to perform the request

Returns

A representation of the import status.

Return type

Union[Dict[str, Any], Response]

class gitlab.v4.objects.GroupMember(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –

- **lazy (bool) –**

manager: `RESTManager`

class `gitlab.v4.objects.GroupMemberAll(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- **manager (RESTManager) –**
- **attrs (Dict[str, Any]) –**
- **created_from_list (bool) –**
- **lazy (bool) –**

manager: `RESTManager`

class `gitlab.v4.objects.GroupMemberAllManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl (Gitlab) –**
- **parent (Optional[RESTObject]) –**

get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupMemberAll

Retrieve a single object.

Parameters

- **id (Union[str, int]) –** ID of the object to retrieve
- **lazy (bool) –** If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs (Any) –** Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`GroupMemberAll`

gitlab: `Gitlab`

class `gitlab.v4.objects.GroupMemberManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `access_level`

- `user_id`

Optional attributes for object create:

- `expires_at`
- `tasks_to_be_done`

Object update

Required attributes for object update:

- `access_level`

Optional attributes for object update:

- `expires_at`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupMember`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupMember`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupMergeRequest(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.GroupMergeRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, RESTManager
```

Object listing filters

- state
- order_by
- sort
- milestone
- view
- labels
- created_after
- created_before
- updated_after
- updated_before
- scope
- author_id
- assignee_id
- approver_ids
- approved_by_ids
- my_reaction_emoji
- source_branch
- target_branch
- search
- wip

Object Creation

Object update

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

gitlab: Gitlab

```
class gitlab.v4.objects.GroupMilestone(manager: RESTManager, attrs: Dict[str, Any], *,
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: SaveMixin, ObjectDeleteMixin, RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

issues(kwargs: Any) → RESTObjectList**

List issues related to this milestone.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

The list of issues

Return type

RESTObjectList

manager: RESTManager**merge_requests(**kwargs: Any) → RESTObjectList**

List the merge requests related to this milestone.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

The list of merge requests

Return type

RESTObjectList

class gitlab.v4.objects.GroupMilestoneManager(gl: Gitlab, parent: Optional[RESTObject] = None)

Bases: *CRUDMixin, RESTManager*

Object listing filters

- **iids**
- **state**
- **search**

Object Creation

Required attributes for object create:

- **title**

Optional attributes for object create:

- `description`
- `due_date`
- `start_date`

Object update

Optional attributes for object update:

- `title`
- `description`
- `due_date`
- `start_date`
- `state_event`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupMilestone`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupMilestone`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupNotificationSettings(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `NotificationSettings`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –

- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupNotificationSettingsManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NotificationSettingsManager*

Object Creation

Object update

Optional attributes for object update:

- level
- notification_email
- new_note
- new_issue
- reopen_issue
- close_issue
- reassign_issue
- new_merge_request
- reopen_merge_request
- close_merge_request
- reassign_merge_request
- merge_merge_request

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(***kwargs*: Any) → *GroupNotificationSettings*

Retrieve a single object.

Parameters

****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

GroupNotificationSettings

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupPackage(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
    bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupPackageManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- `exclude_subgroups`
- `order_by`
- `sort`
- `package_type`
- `package_name`

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupProject(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
    bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupProjectManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- `archived`
- `visibility`

- `order_by`
- `sort`
- `search`
- `simple`
- `owned`
- `starred`
- `with_custom_attributes`
- `include_subgroups`
- `with_issues_enabled`
- `with_merge_requests_enabled`
- `with_shared`
- `min_access_level`
- `with_security_reports`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.GroupPushRules(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.GroupPushRulesManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `GetWithoutIdMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager`

Object Creation

Optional attributes for object create:

- `deny_delete_tag`
- `member_check`
- `prevent_secrets`
- `commit_message_regex`

- `commit_message_negative_regex`
- `branch_name_regex`
- `author_email_regex`
- `file_name_regex`
- `max_file_size`
- `commit_committer_check`
- `reject_unsigned_commits`

Object update

Optional attributes for object update:

- `deny_delete_tag`
- `member_check`
- `prevent_secrets`
- `commit_message_regex`
- `commit_message_negative_regex`
- `branch_name_regex`
- `author_email_regex`
- `file_name_regex`
- `max_file_size`
- `commit_committer_check`
- `reject_unsigned_commits`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → GroupPushRules`

Retrieve a single object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupPushRules`

`gitlab: Gitlab`

```
class gitlab.v4.objects.GroupRegistryRepositoryManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin*, *RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupRunner(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.GroupRunnerManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin*, *RESTManager*

Object listing filters

- scope
- tag_list

Object Creation

Required attributes for object create:

- runner_id

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.GroupSubgroup(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –

- `created_from_list (bool) –`
- `lazy (bool) –`

`manager: RESTManager`

`class gitlab.v4.objects.GroupSubgroupManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `ListMixin, RESTManager`

Object listing filters

- `skip_groups`
- `all_available`
- `search`
- `order_by`
- `sort`
- `statistics`
- `owned`
- `with_custom_attributes`
- `min_access_level`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`class gitlab.v4.objects.GroupVariable(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

`manager: RESTManager`

`class gitlab.v4.objects.GroupVariableManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `key`
- `value`

Optional attributes for object create:

- `protected`

- `variable_type`
- `masked`

Object update

Required attributes for object update:

- `key`
- `value`

Optional attributes for object update:

- `protected`
- `variable_type`
- `masked`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → GroupVariable`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupVariable`

`gitlab: Gitlab`

`class gitlab.v4.objects.GroupWiki(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

manager: `RESTManager`

class `gitlab.v4.objects.GroupWikiManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)
Bases: `CRUDMixin, RESTManager`

Object listing filters

- `with_content`

Object Creation

Required attributes for object create:

- `title`
- `content`

Optional attributes for object create:

- `format`

Object update

Optional attributes for object update:

- `title`
- `content`
- `format`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(`id: Union[str, int], lazy: bool = False, **kwargs: Any`) → `GroupWiki`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`GroupWiki`

gitlab: `Gitlab`

```
class gitlab.v4.objects.Hook(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin*, *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.HookManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin*, *RESTManager*

Object Creation

Required attributes for object create:

- *url*

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *Hook*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated *RESTObject*.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Hook

gitlab: *Gitlab*

```
class gitlab.v4.objects.Issue(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –

```
    • attrs (Dict[str, Any]) –
    • created_from_list (bool) –
    • lazy (bool) –

manager: RESTManager

class gitlab.v4.objects.IssueManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: RetrieveMixin, RESTManager
```

Object listing filters

- state
- labels
- milestone
- scope
- author_id
- assignee_id
- my_reaction_emoji
- iids
- order_by
- sort
- search
- created_after
- created_before
- updated_after
- updated_before

Object Creation

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → Issue
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Issue

gitlab: *Gitlab*

```
class gitlab.v4.objects.IssuesStatistics(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *RefreshMixin, RESTObject***Parameters**

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.IssuesStatisticsManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin, RESTManager***Object listing filters**

- iids

Object Creation**Object update****Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → *IssuesStatistics***

Retrieve a single object.

Parameters****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)**Returns**

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

IssuesStatistics

gitlab: *Gitlab*

```
class gitlab.v4.objects.Key(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool =  
                           False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.KeyManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `GetMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Optional[Union[int, str]] = None, lazy: bool = False, **kwargs: Any`) → `Key`

Retrieve a single object.

Parameters

- **id** (`Optional[Union[int, str]]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`Key`

gitlab: `Gitlab`

class `gitlab.v4.objects.LDAPGroup`(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.LDAPGroupManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RESTManager*

Object listing filters

- `search`
- `provider`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
list(**kwargs: Any) → Union[List[LDAPGroup], RESTObjectList]
```

Retrieve a list of objects.

Parameters

- `all` – If True, return all the items, without pagination
- `per_page` – Number of items to retrieve per request
- `page` – ID of the page to return (starts with page 1)
- `iterator` – If set to True and no pagination option is defined, return a generator instead of a list
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The list of objects, or a generator if `iterator` is True

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the server cannot perform the request

Return type

`Union[List[LDAPGroup], RESTObjectList]`

```
class gitlab.v4.objects.License(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool  
                                = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.LicenseManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, RESTManager*

Object listing filters

- popular

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → License
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

License

gitlab: *Gitlab*

```
class gitlab.v4.objects.MergeRequest(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.MergeRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- state
- order_by

- sort
- milestone
- view
- labels
- with_labels_details
- with_merge_status_recheck
- created_after
- created_before
- updated_after
- updated_before
- scope
- author_id
- author_username
- assignee_id
- approver_ids
- approved_by_ids
- reviewer_id
- reviewer_username
- my_reaction_emoji
- source_branch
- target_branch
- search
- in
- wip
- not
- environment
- deployed_before
- deployed_after

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.Namespace(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.NamespaceManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, RESTManager`

Object listing filters

- `search`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

exists(`namespace: str, **kwargs: Any`) → `Namespace`

Get existence of a namespace by path.

Parameters

- **namespace** (`str`) – The path to the namespace.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

Data on namespace existence returned from the server.

Return type

`Namespace`

get(`id: Union[str, int], lazy: bool = False, **kwargs: Any`) → `Namespace`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Namespace

gitlab: `Gitlab`

```
class gitlab.v4.objects.NotificationSettings(manager: RESTManager, attrs: Dict[str, Any], *,  
                                              created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.NotificationSettingsManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                   None)
```

Bases: `GetWithoutIdMixin, UpdateMixin, RESTManager`

Object Creation**Object update**

Optional attributes for object update:

- `level`
- `notification_email`
- `new_note`
- `new_issue`
- `reopen_issue`
- `close_issue`
- `reassign_issue`
- `new_merge_request`
- `reopen_merge_request`
- `close_merge_request`
- `reassign_merge_request`
- `merge_merge_request`

Parameters

- **gl** (`Gitlab`) –

- **parent** (*Optional[RESTObject]*) –

get(***kwargs: Any*) → *NotificationSettings*

Retrieve a single object.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

NotificationSettings

gitlab: *Gitlab*

class `gitlab.v4.objects.PagesDomain(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

class `gitlab.v4.objects.PagesDomainManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: *ListMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

class `gitlab.v4.objects.PersonalAccessToken(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

```
manager: RESTManager

class gitlab.v4.objects.PersonalAccessTokenManager(gl: Gitlab, parent: Optional[RESTObject] = None)

Bases: DeleteMixin, ListMixin, RESTManager

Object listing filters

- user_id

Object Creation
Object update
    Parameters

- gl (Gitlab) –
- parent (Optional[RESTObject]) –

gitlab: Gitlab

class gitlab.v4.objects.Project(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)

Bases: RefreshMixin, SaveMixin, ObjectDeleteMixin, RepositoryMixin, RESTObject

    Parameters

- manager (RESTManager) –
- attrs (Dict[str, Any]) –
- created_from_list (bool) –
- lazy (bool) –

access_tokens: ProjectAccessTokenManager
accessrequests: ProjectAccessRequestManager
additionalstatistics: ProjectAdditionalStatisticsManager
approvalrules: ProjectApprovalRuleManager
approvals: ProjectApprovalManager
archive(**kwargs: Any) → None
    Archive a project.

    Parameters

- **kwargs (Any) – Extra options to send to the server (e.g. sudo)

Raises

- GitlabAuthenticationError – If authentication is not correct
- GitlabCreateError – If the server failed to perform the request

Return type
    None

artifact(*args: Any, **kwargs: Any) → Optional[bytes]
    Parameters

- args (Any) –

```

- **kwargs (Any)** –

Return type

Optional[bytes]

artifacts: *ProjectArtifactManager*

audit_events: *ProjectAuditEventManager*

badges: *ProjectBadgeManager*

boards: *ProjectBoardManager*

branches: *ProjectBranchManager*

ci_lint: *ProjectCiLintManager*

clusters: *ProjectClusterManager*

commits: *ProjectCommitManager*

create_fork_relation(*forked_from_id*: int, **kwargs: Any) → None

Create a forked from/to relation between existing projects.

Parameters

- **forked_from_id (int)** – The ID of the project that was forked from
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the relation could not be created

Return type

None

customattributes: *ProjectCustomAttributeManager*

delete_fork_relation(**kwargs: Any) → None

Delete a forked relation between existing projects.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server failed to perform the request

Return type

None

deployments: *ProjectDeploymentManager*

deploytokens: *ProjectDeployTokenManager*

environments: *ProjectEnvironmentManager*

events: *ProjectEventManager*

```
exports: ProjectExportManager
files: ProjectFileManager
forks: ProjectForkManager
generic_packages: GenericPackageManager
groups: ProjectGroupManager
hooks: ProjectHookManager
housekeeping(**kwargs: Any) → None
    Start the housekeeping task.

    Parameters
        **kwargs (Any) – Extra options to send to the server (e.g. sudo)

    Raises
        • GitlabAuthenticationError – If authentication is not correct
        • GitlabHousekeepingError – If the server failed to perform the request

    Return type
        None

imports: ProjectImportManager
integrations: ProjectIntegrationManager
invitations: ProjectInvitationManager
issues: ProjectIssueManager
issues_statistics: ProjectIssuesStatisticsManager
iterations: GroupIterationManager
jobs: ProjectJobManager
keys: ProjectKeyManager
labels: ProjectLabelManager
languages(**kwargs: Any) → Union[Dict[str, Any], Response]
    Get languages used in the project with percentage value.

    Parameters
        **kwargs (Any) – Extra options to send to the server (e.g. sudo)

    Raises
        • GitlabAuthenticationError – If authentication is not correct
        • GitlabGetError – If the server failed to perform the request

    Return type
        Union[Dict[str, Any], Response]

members: ProjectMemberManager
members_all: ProjectMemberAllManager
```

```
merge_trains: ProjectMergeTrainManager
mergerequests: ProjectMergeRequestManager
milestones: ProjectMilestoneManager
mirror_pull(**kwargs: Any) → None
    Start the pull mirroring process for the project.

    Parameters
        **kwargs (Any) – Extra options to send to the server (e.g. sudo)

    Raises
        • GitlabAuthenticationError – If authentication is not correct
        • GitlabCreateError – If the server failed to perform the request

    Return type
        None

notes: ProjectNoteManager
notificationsettings: ProjectNotificationSettingsManager
packages: ProjectPackageManager
pagesdomains: ProjectPagesDomainManager
pipelines: ProjectPipelineManager
pipelineschedules: ProjectPipelineScheduleManager
protected_environments: ProjectProtectedEnvironmentManager
protectedbranches: ProjectProtectedBranchManager
protectedtags: ProjectProtectedTagManager
pushrules: ProjectPushRulesManager
releases: ProjectReleaseManager
remote_mirrors: ProjectRemoteMirrorManager
repositories: ProjectRegistryRepositoryManager
restore(**kwargs: Any) → None
    Restore a project marked for deletion.

    Parameters
        **kwargs (Any) – Extra options to send to the server (e.g. sudo)

    Raises
        • GitlabAuthenticationError – If authentication is not correct
        • GitlabRestoreError – If the server failed to perform the request

    Return type
        None

runners: ProjectRunnerManager
```

search(*scope: str, search: str, **kwargs: Any*) → Union[*GitlabList*, *List[Dict[str, Any]]*]

Search the project resources matching the provided string.'

Parameters

- **scope (str)** – Scope of the search
- **search (str)** – Search string
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSearchError** – If the server failed to perform the request

Returns

A list of dicts describing the resources found.

Return type

Union[GitlabList, List[Dict[str, Any]]]

services: *ProjectServiceManager*

share(*group_id: int, group_access: int, expires_at: Optional[str] = None, **kwargs: Any*) → None

Share the project with a group.

Parameters

- **group_id (int)** – ID of the group.
- **group_access (int)** – Access level for the group.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)
- **expires_at (Optional[str])** –
- ****kwargs** –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server failed to perform the request

Return type

None

snapshot(*wiki = False, streamed: bool = False, action: Optional[Callable[[bytes], None]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any*) → Optional[Union[bytes, Iterator[Any]]]

Return a snapshot of the repository.

Parameters

- **wiki (bool)** – If True return the wiki repository
- **streamed (bool)** – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment.
- **iterator (bool)** – If True directly return the underlying response iterator
- **action (Optional[Callable[[bytes], None]])** – Callable responsible of dealing with chunk of data
- **chunk_size (int)** – Size of each chunk

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the content could not be retrieved

Returns

The uncompressed tar archive of the repository

Return type

Optional[Union[bytes, Iterator[Any]]]

snippets: *ProjectSnippetManager*

star(kwargs: Any) → None**

Star a project.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server failed to perform the request

Return type

None

storage: *ProjectStorageManager*

tags: *ProjectTagManager*

transfer(to_namespace: Union[int, str], **kwargs: Any) → None

Transfer a project to the given namespace ID

Parameters

- **to_namespace (Union[int, str])** – ID or path of the namespace to transfer the project to
- **to (project)** –
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTransferProjectError** – If the project could not be transferred

Return type

None

transfer_project(*args: Any, **kwargs: Any) → None

Parameters

- **args (Any)** –
- **kwargs (Any)** –

Return type

None

trigger_pipeline(*ref: str, token: str, variables: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *ProjectPipeline*

Trigger a CI build.

See <https://gitlab.com/help/ci/triggers/README.md#trigger-a-build>

Parameters

- **ref** (*str*) – Commit to build; can be a branch name or a tag
- **token** (*str*) – The trigger token
- **variables** (*Optional[Dict[str, Any]]*) – Variables passed to the build script
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server failed to perform the request

Return type

ProjectPipeline

triggers: *ProjectTriggerManager*

unarchive(***kwargs: Any*) → None

Unarchive a project.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server failed to perform the request

Return type

None

unshare(*group_id: int, **kwargs: Any*) → None

Delete a shared project link within a group.

Parameters

- **group_id** (*int*) – ID of the group.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server failed to perform the request

Return type

None

unstar(***kwargs: Any*) → None

Unstar a project.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server failed to perform the request

Return type

None

upload(filename: str, filedata: Optional[bytes] = None, filepath: Optional[str] = None, **kwargs: Any) → Dict[str, Any]

Upload the specified file into the project.

Note: Either `filedata` or `filepath` *MUST* be specified.

Parameters

- **filename (str)** – The name of the file being uploaded
- **filedata (Optional[bytes])** – The raw data of the file being uploaded
- **filepath (Optional[str])** – The path to a local file to upload (optional)
- **kwargs (Any)** –

Raises

- **GitlabConnectionError** – If the server cannot be reached
- **GitlabUploadError** – If the file upload fails
- **GitlabUploadError** – If `filedata` and `filepath` are not specified
- **GitlabUploadError** – If both `filedata` and `filepath` are specified

Returns

- `alt` - The alternate text for the upload
- `url` - The direct url to the uploaded file
- `markdown` - Markdown for the uploaded file

Return type

A dict with the keys

users: `ProjectUserManager`

variables: `ProjectVariableManager`

wikis: `ProjectWikiManager`

class gitlab.v4.objects.ProjectAccessRequest(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)

Bases: `AccessRequestMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

```
manager: RESTManager

class gitlab.v4.objects.ProjectAccessRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, CreateMixin, DeleteMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectAccessToken(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectAccessTokenManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, CreateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- `name`
- `scopes`

Optional attributes for object create:

- `access_level`
- `expires_at`

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectAdditionalStatistics(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RefreshMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectAdditionalStatisticsManager(gl: Gitlab, parent:  
Optional[RESTObject] = None)
```

Bases: `GetWithoutIdMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(kwargs: Any) → ProjectAdditionalStatistics**

Retrieve a single object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectAdditionalStatistics`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectApproval(manager: RESTManager, attrs: Dict[str, Any], *,  
created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectApprovalManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: GetWithoutIdMixin, UpdateMixin, RESTManager
```

Object Creation

Object update

Optional attributes for object update:

- approvals_before_merge
- reset_approvals_on_push
- disable_overriding_approvers_per_merge_request
- merge_requests_author_approval
- merge_requests_disable_committers_approval

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

```
get(**kwargs: Any) → ProjectApproval
```

Retrieve a single object.

Parameters

**kwargs (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectApproval

```
gitlab: Gitlab
```

```
set获批者(approver_ids: Optional[List[int]] = None, approver_group_ids: Optional[List[int]] = None, **kwargs: Any) → Dict[str, Any]
```

Change project-level allowed approvers and approver groups.

Parameters

- **approver_ids** (Optional[List[int]]) – User IDs that can approve MRs
- **approver_group_ids** (Optional[List[int]]) – Group IDs whose members can approve MRs
- **kwargs** (Any) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server failed to perform the request

Returns

A dict value of the result

Return type

Dict[str, Any]

```
class gitlab.v4.objects.ProjectApprovalRule(manager: RESTManager, attrs: Dict[str, Any], *,  
                                             created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectApprovalRuleManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                 None)
```

Bases: *ListMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- `name`
- `approvals_required`

Optional attributes for object create:

- `user_ids`
- `group_ids`
- `protected_branch_ids`

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectArtifact(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Dummy object to manage custom actions on artifacts

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectArtifactManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
delete(**kwargs: Any) → None
```

Delete the project's artifacts on the server.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

None

```
download(ref_name: str, job: str, streamed: bool = False, action: Optional[Callable[[bytes], None]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]
```

Get the job artifacts archive from a specific tag or branch.

Parameters

- **ref_name** (*str*) – Branch or tag name in repository. HEAD or SHA references
- **supported.** (*are not*) –
- **job** (*str*) – The name of the job.
- **job_token** – Job token for multi-project pipeline triggers.
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[[bytes], None]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns

The artifacts if *streamed* is False, None otherwise.

Return type

Optional[Union[bytes, Iterator[Any]]]

gitlab: *Gitlab*

```
raw(ref_name: str, artifact_path: str, job: str, streamed: bool = False, action: Optional[Callable[[bytes], None]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]
```

Download a single artifact file from a specific tag or branch from within the job's artifacts archive.

Parameters

- **ref_name** (*str*) – Branch or tag name in repository. HEAD or SHA references are not supported.
- **artifact_path** (*str*) – Path to a file inside the artifacts archive.
- **job** (*str*) – The name of the job.
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[[bytes], None]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns

The artifact if *streamed* is False, None otherwise.

Return type

Optional[Union[bytes, Iterator[Any]]]

```
class gitlab.v4.objects.ProjectAudit(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ProjectAuditEvent*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectAuditEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –

- `created_from_list (bool) –`
- `lazy (bool) –`

manager: `RESTManager`

class `gitlab.v4.objects.ProjectAuditEventManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `RetrieveMixin, RESTManager`

Object listing filters

- `created_after`
- `created_before`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

get(`id: Union[str, int], lazy: bool = False, **kwargs: Any`) → `ProjectAuditEvent`

Retrieve a single object.

Parameters

- `id (Union[str, int]) –` ID of the object to retrieve
- `lazy (bool) –` If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectAuditEvent`

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectAuditManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `ProjectAuditEventManager`

Object listing filters

- `created_after`
- `created_before`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`

- **parent** (*Optional[RESTObject]*) –

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectBadge`(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectBadgeManager`(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: `BadgeRenderMixin, CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `link_url`
- `image_url`

Object update

Optional attributes for object update:

- `link_url`
- `image_url`

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → `ProjectBadge`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type
ProjectBadge

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectBoard`(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

lists: `ProjectBoardListManager`

class `gitlab.v4.objects.ProjectBoardList`(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectBoardListManager`(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: `CRUDMixin, RESTManager`

Object Creation

Mutually exclusive attributes for object create:

- `label_id`
- `assignee_id`
- `milestone_id`

Object update

Required attributes for object update:

- `position`

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectBoardList`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectBoardList`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectBoardManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectBoard`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectBoard`

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectBranch(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectBranchManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- **branch**
- **ref**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectBranch*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectBranch

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectCiLint(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectCiLintManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin*, *CreateMixin*, *RESTManager*

Object Creation

Required attributes for object create:

- **content**

Optional attributes for object create:

- **dry_run**
- **include_jobs**
- **ref**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(kwargs: Any) → ProjectCiLint**

Retrieve a single object.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectCiLint

gitlab: Gitlab

validate(*args: Any, **kwargs: Any) → None

Raise an error if the Project CI Lint results are not valid.

This is a custom python-gitlab method to wrap lint endpoints.

Parameters

- **args** (*Any*) –
- **kwargs** (*Any*) –

Return type

None

```
class gitlab.v4.objects.ProjectCluster(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectClusterManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- `name`
- `platform_kubernetes_attributes`

Optional attributes for object create:

- `domain`
- `enabled`
- `managed`
- `environment_scope`

Object update

Optional attributes for object update:

- `name`
- `domain`
- `management_project_id`
- `platform_kubernetes_attributes`
- `environment_scope`

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

create(*data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *ProjectCluster*

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – Parameters to send to the server to create the resource
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo or ‘ref_name’, ‘stage’, ‘name’, ‘all’)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Returns

A new instance of the manage object class build with
the data sent by the server

Return type

ProjectCluster

get(*id: Union[str, int], lazy: bool = False, **kwargs: Any*) → *ProjectCluster*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don’t request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectCluster

gitlab: *Gitlab*

class gitlab.v4.objects.ProjectCommit(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

cherry_pick(*branch: str, **kwargs: Any*) → None

Cherry-pick a commit into a branch.

Parameters

- **branch (str)** – Name of target branch
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCherryPickError** – If the cherry-pick could not be performed

Return type

None

comments: *ProjectCommitCommentManager*

diff(***kwargs: Any*) → Union[*GitlabList*, List[Dict[str, Any]]]

Generate the commit diff.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the diff could not be retrieved

Returns

The changes done in this commit

Return type

Union[*GitlabList*, List[Dict[str, Any]]]

discussions: *ProjectCommitDiscussionManager*

merge_requests(***kwargs: Any*) → Union[*GitlabList*, List[Dict[str, Any]]]

List the merge requests related to the commit.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the references could not be retrieved

Returns

The merge requests related to the commit.

Return type

Union[*GitlabList*, List[Dict[str, Any]]]

refs(*type: str = 'all', **kwargs: Any*) → Union[*GitlabList*, List[Dict[str, Any]]]

List the references the commit is pushed to.

Parameters

- **type (str)** – The scope of references ('branch', 'tag' or 'all')
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the references could not be retrieved

Returns

The references the commit is pushed to.

Return type

Union[GitlabList, List[Dict[str, Any]]]

revert(*branch: str, **kwargs: Any*) → *Union[Dict[str, Any], Response]*

Revert a commit on a given branch.

Parameters

- **branch (str)** – Name of target branch
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabRevertError** – If the revert could not be performed

Returns

The new commit data (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

signature(***kwargs: Any*) → *Union[Dict[str, Any], Response]*

Get the signature of the commit.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the signature could not be retrieved

Returns

The commit's signature data

Return type

Union[Dict[str, Any], Response]

statuses: *ProjectCommitStatusManager*

class *gitlab.v4.objects.ProjectCommitComment*(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *RESTObject*

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

```
manager: RESTManager

class gitlab.v4.objects.ProjectCommitCommentManager(gl: Gitlab, parent: Optional[RESTObject] = None)

Bases: ListMixin, CreateMixin, RESTManager
```

Object Creation

Required attributes for object create:

- note

Optional attributes for object create:

- path
- line
- line_type

Object update

Parameters

- gl (Gitlab) –
- parent (Optional[RESTObject]) –

gitlab: Gitlab

```
class gitlab.v4.objects.ProjectCommitDiscussion(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: RESTObject

Parameters

- manager (RESTManager) –
- attrs (Dict[str, Any]) –
- created_from_list (bool) –
- lazy (bool) –

notes: ProjectCommitDiscussionNoteManager

```
class gitlab.v4.objects.ProjectCommitDiscussionManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: RetrieveMixin, CreateMixin, RESTManager

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at

Object update

Parameters

- gl (Gitlab) –
- parent (Optional[RESTObject]) –

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → ProjectCommitDiscussion

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve
- **lazy** (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectCommitDiscussion

gitlab: Gitlab

class gitlab.v4.objects.ProjectCommitDiscussionNote(*manager*: RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False, *lazy*: bool = False)

Bases: SaveMixin, ObjectDeleteMixin, RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: RESTManager

class gitlab.v4.objects.ProjectCommitDiscussionNoteManager(*gl*: Gitlab, *parent*: Optional[RESTObject] = None)

Bases: GetMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at
- position

Object update

Required attributes for object update:

- body

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectCommitDiscussionNote`

Retrieve a single object.

Parameters

- `id (Union[str, int]) –` ID of the object to retrieve
- `lazy (bool) –` If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectCommitDiscussionNote`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectCommitManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, CreateMixin, RESTManager`

Object listing filters

- `ref_name`
- `since`
- `until`
- `path`
- `with_stats`
- `first_parent`
- `order`
- `trailers`

Object Creation

Required attributes for object create:

- `branch`
- `commit_message`
- `actions`

Optional attributes for object create:

- `author_email`
- `author_name`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectCommit`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectCommit`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectCommitStatus(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RefreshMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectCommitStatusManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `ListMixin, CreateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `state`

Optional attributes for object create:

- `description`
- `name`
- `context`
- `ref`

- `target_url`
- `coverage`

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → ProjectCommitStatus`

Create a new object.

Parameters

- `data (Optional[Dict[str, Any]]) –` Parameters to send to the server to create the resource
- `**kwargs (Any) –` Extra options to send to the server (e.g. `sudo` or `'ref_name'`, `'stage'`, `'name'`, `'all'`)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

Returns

A new instance of the `manage` object class build with the data sent by the server

Return type

`ProjectCommitStatus`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectCustomAttribute(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager) –`
- `attrs (Dict[str, Any]) –`
- `created_from_list (bool) –`
- `lazy (bool) –`

`manager: RESTManager`

`class gitlab.v4.objects.ProjectCustomAttributeManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, SetMixin, DeleteMixin, RESTManager`

Object Creation

Object update

Parameters

- `gl (Gitlab) –`

- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectCustomAttribute*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectCustomAttribute

gitlab: *Gitlab*

class *gitlab.v4.objects.ProjectDeployToken*(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

class *gitlab.v4.objects.ProjectDeployTokenManager*(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)

Bases: *RetrieveMixin, CreateMixin, DeleteMixin, RESTManager*

Object listing filters

- **scopes**

Object Creation

Required attributes for object create:

- **name**
- **scopes**

Optional attributes for object create:

- **expires_at**
- **username**

Object update

Parameters

- **g1 (Gitlab) –**
 - **parent (Optional[RESTObject]) –**
- get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectDeployToken**
- Retrieve a single object.
- Parameters**
- **id (Union[str, int]) –** ID of the object to retrieve
 - **lazy (bool) –** If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
 - ****kwargs (Any) –** Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectDeployToken

gitlab: Gitlab

class gitlab.v4.objects.ProjectDeployment(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)

Bases: *SaveMixin, RESTObject*

Parameters

- **manager (RESTManager) –**
- **attrs (Dict[str, Any]) –**
- **created_from_list (bool) –**
- **lazy (bool) –**

approval(status: str, comment: Optional[str] = None, represented_as: Optional[str] = None, **kwargs: Any) → Dict[str, Any]

Approve or reject a blocked deployment.

Parameters

- **status (str) –** Either “approved” or “rejected”
- **comment (Optional[str]) –** A comment to go with the approval
- **represented_as (Optional[str]) –** The name of the User/Group/Role to use for the approval, when the user belongs to multiple approval rules.
- ****kwargs (Any) –** Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMRAApprovalError** – If the approval failed

Returns

A dict containing the result.

Return type

Dict[str, Any]

<https://docs.gitlab.com/ee/api/deployments.html#approve-or-reject-a-blocked-deployment>

mergerequests: *ProjectDeploymentMergeRequestManager*

```
class gitlab.v4.objects.ProjectDeploymentManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: RetrieveMixin, CreateMixin, UpdateMixin, RESTManager
```

Object listing filters

- `order_by`
- `sort`
- `updated_after`
- `updated_before`
- `environment`
- `status`

Object Creation

Required attributes for object create:

- `sha`
- `ref`
- `tag`
- `status`
- `environment`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → *ProjectDeployment*

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

ProjectDeployment

```
gitlab: Gitlab

class gitlab.v4.objects.ProjectDeploymentMergeRequest(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
    Bases: MergeRequest

    Parameters
        • manager (RESTManager) –
        • attrs (Dict[str, Any]) –
        • created_from_list (bool) –
        • lazy (bool) –

    manager: RESTManager

class gitlab.v4.objects.ProjectDeploymentMergeRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)
    Bases: MergeRequestManager

    Object listing filters
        • state
        • order_by
        • sort
        • milestone
        • view
        • labels
        • with_labels_details
        • with_merge_status_recheck
        • created_after
        • created_before
        • updated_after
        • updated_before
        • scope
        • author_id
        • author_username
        • assignee_id
        • approver_ids
        • approved_by_ids
        • reviewer_id
        • reviewer_username
        • my_reaction_emoji
        • source_branch
```

- `target_branch`
- `search`
- `in`
- `wip`
- `not`
- `environment`
- `deployed_before`
- `deployed_after`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectEnvironment(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`stop(**kwargs: Any) → Union[Dict[str, Any], Response]`

Stop the environment.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabStopError` – If the operation failed

Returns

A dict of the result.

Return type

`Union[Dict[str, Any], Response]`

```
class gitlab.v4.objects.ProjectEnvironmentManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager`

Object listing filters

- `name`

- `search`
- `states`

Object Creation

Required attributes for object create:

- `name`

Optional attributes for object create:

- `external_url`

Object update

Optional attributes for object update:

- `name`
- `external_url`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectEnvironment`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectEnvironment`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `Event`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectEventManager`(`gl: Gitlab`, `parent: Optional[RESTObject] = None`)

Bases: `EventManager`

Object listing filters

- `action`
- `target_type`
- `before`
- `after`
- `sort`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectExport`(`manager: RESTManager`, `attrs: Dict[str, Any]`, *, `created_from_list: bool = False`, `lazy: bool = False`)

Bases: `DownloadMixin`, `RefreshMixin`, `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectExportManager`(`gl: Gitlab`, `parent: Optional[RESTObject] = None`)

Bases: `GetWithoutIdMixin`, `CreateMixin`, `RESTManager`

Object Creation

Optional attributes for object create:

- `description`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(kwargs: Any) → ProjectExport**

Retrieve a single object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectExport

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectFile(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*ProjectFileManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

branch: str

commit_message: str

decode() → bytes

Returns the decoded content of the file.

Returns

The decoded content.

Return type

bytes

delete(*branch: str, commit_message: str, **kwargs: Any*) → None

Delete the file from the server.

Parameters

- **branch** (*str*) – Branch from which the file will be removed
- **commit_message** (*str*) – Commit message for the deletion
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

None

file_path: str

manager: *ProjectFileManager*

save(*branch: str, commit_message: str, **kwargs: Any*) → None

Save the changes made to the file to the server.

The object is updated to match what the server returns.

Parameters

- **branch (str)** – Branch in which the file will be updated
- **commit_message (str)** – Message to send with the commit
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server cannot perform the request

Return type

None

class gitlab.v4.objects.ProjectFileManager(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: *GetMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- `file_path`
- `branch`
- `content`
- `commit_message`

Optional attributes for object create:

- `encoding`
- `author_email`
- `author_name`

Object update

Required attributes for object update:

- `file_path`
- `branch`
- `content`
- `commit_message`

Optional attributes for object update:

- `encoding`
- `author_email`
- `author_name`

Parameters

- `gl (Gitlab)` –

- **parent** (*Optional[RESTObject]*) –

blame(*file_path: str, ref: str, **kwargs: Any*) → *List[Dict[str, Any]]*

Return the content of a file for a commit.

Parameters

- **file_path** (*str*) – Path of the file to retrieve
- **ref** (*str*) – Name of the branch, tag or commit
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns

A list of commits/lines matching the file

Return type

List[Dict[str, Any]]

create(*data: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *ProjectFile*

Create a new object.

Parameters

- **data** (*Optional[Dict[str, Any]]*) – parameters to send to the server to create the resource
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

a new instance of the managed object class built with
the data sent by the server

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Return type

ProjectFile

delete(*file_path: str, branch: str, commit_message: str, **kwargs: Any*) → *None*

Delete a file on the server.

Parameters

- **file_path** (*str*) – Path of the file to remove
- **branch** (*str*) – Branch from which the file will be removed
- **commit_message** (*str*) – Commit message for the deletion
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

None

get(*file_path*: str, *ref*: str, ***kwargs*: Any) → [ProjectFile](#)

Retrieve a single file.

Parameters

- **file_path** (str) – Path of the file to retrieve
- **ref** (str) – Name of the branch, tag or commit
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the file could not be retrieved

Returns

The generated RESTObject

Return type

[ProjectFile](#)

gitlab: [Gitlab](#)

raw(*file_path*: str, *ref*: str, *streamed*: bool = False, *action*: Optional[Callable[[], Any]] = None, *chunk_size*: int = 1024, *, *iterator*: bool = False, ***kwargs*: Any) → Optional[Union[bytes, Iterator[Any]]]

Return the content of a file for a commit.

Parameters

- **ref** (str) – ID of the commit
- **filepath** – Path of the file to return
- **streamed** (bool) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (bool) – If True directly return the underlying response iterator
- **action** (Optional[Callable[[], Any]]) – Callable responsible of dealing with chunk of data
- **chunk_size** (int) – Size of each chunk
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)
- **file_path** (str) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the file could not be retrieved

Returns

The file content

Return type

Optional[Union[bytes, Iterator[Any]]]

update(*file_path*: str, *new_data*: Optional[Dict[str, Any]] = None, ***kwargs*: Any) → Dict[str, Any]

Update an object on the server.

Parameters

- **id** – ID of the object to update (can be None if not required)
- **new_data** (*Optional[Dict[str, Any]]*) – the update data for the object
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)
- **file_path** (*str*) –

Returns

The new object data (*not* a RESTObject)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server cannot perform the request

Return type

Dict[str, Any]

class gitlab.v4.objects.ProjectFork(*manager*: RESTManager, *attrs*: Dict[str, Any], *, *created_from_list*: bool = False, *lazy*: bool = False)

Bases: *RESTObject*

Parameters

- **manager** (RESTManager) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: RESTManager

class gitlab.v4.objects.ProjectForkManager(*gl*: Gitlab, *parent*: *Optional[RESTObject]* = None)

Bases: *CreateMixin, ListMixin, RESTManager*

Object listing filters

- **archived**
- **visibility**
- **order_by**
- **sort**
- **search**
- **simple**
- **owned**
- **membership**
- **starred**
- **statistics**
- **with_custom_attributes**

- `with_issues_enabled`
- `with_merge_requests_enabled`

Object Creation

Optional attributes for object create:

- `namespace`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → ProjectFork`

Creates a new object.

Parameters

- `data (Optional[Dict[str, Any]])` – Parameters to send to the server to create the resource
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

Returns

A new instance of the managed object class build with the data sent by the server

Return type

`ProjectFork`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectHook(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectHookManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `url`

Optional attributes for object create:

- `push_events`
- `issues_events`
- `confidential_issues_events`
- `merge_requests_events`
- `tag_push_events`
- `note_events`
- `job_events`
- `pipeline_events`
- `wiki_page_events`
- `enable_ssl_verification`
- `token`

Object update

Required attributes for object update:

- `url`

Optional attributes for object update:

- `push_events`
- `issues_events`
- `confidential_issues_events`
- `merge_requests_events`
- `tag_push_events`
- `note_events`
- `job_events`
- `pipeline_events`
- `wiki_events`
- `enable_ssl_verification`
- `token`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectHook`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.

- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectHook

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectImport`(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)

Bases: `RefreshMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectImportManager`(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)

Bases: `GetWithoutIdMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(kwargs: Any) → ProjectImport**

Retrieve a single object.

Parameters

- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectImport

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectIntegration(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin*, *ObjectDeleteMixin*, *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectIntegrationManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetMixin*, *UpdateMixin*, *DeleteMixin*, *ListMixin*, *RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

available() → *List[str]*

List the services known by python-gitlab.

Returns

The list of service code names.

Return type

List[str]

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectIntegration*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIntegration

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectInvitation(manager: RESTManager, attrs: Dict[str, Any], *,  
    created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin`, `ObjectDeleteMixin`, `RESTObject`

Parameters

- `manager` (`RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –
- `lazy` (`bool`) –

`manager:` `RESTManager`

```
class gitlab.v4.objects.ProjectInvitationManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `InvitationMixin`, `RESTManager`

Object listing filters

- `query`

Object Creation

Required attributes for object create:

- `access_level`

Optional attributes for object create:

- `expires_at`
- `invite_source`
- `tasks_to_be_done`
- `tasks_project_id`

Mutually exclusive attributes for object create:

- `email`
- `user_id`

Object update

Optional attributes for object update:

- `access_level`
- `expires_at`

Parameters

- `gl` (`Gitlab`) –
- `parent` (`Optional[RESTObject]`) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectInvitation
```

Retrieve a single object.

Parameters

- `id` (`Union[str, int]`) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectInvitation

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectIssue(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                     bool = False, lazy: bool = False)  
  
Bases:     UserAgentDetailMixin, SubscribableMixin, TodoMixin, TimeTrackingMixin,  
           ParticipantsMixin, SaveMixin, ObjectDeleteMixin, RESTObject
```

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

awardemojis: *ProjectIssueAwardEmojiManager*

closed_by(**kwargs: Any) → Dict[str, Any]

List merge requests that will close the issue when merged.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the merge requests could not be retrieved

Returns

The list of merge requests.

Return type

Dict[str, Any]

discussions: *ProjectIssueDiscussionManager*

links: *ProjectIssueLinkManager*

move(to_project_id: int, **kwargs: Any) → None

Move the issue to another project.

Parameters

- **to_project_id** (*int*) – ID of the target project
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the issue could not be moved

Return type

None

notes: *ProjectIssueNoteManager*

related_merge_requests(kwargs: Any) → Dict[str, Any]**

List merge requests related to the issue.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the merge requests could not be retrieved

Returns

The list of merge requests.

Return type

Dict[str, Any]

reorder(move_after_id: Optional[int] = None, move_before_id: Optional[int] = None, **kwargs: Any) → None

Reorder an issue on a board.

Parameters

- **move_after_id (Optional[int])** – ID of an issue that should be placed after this issue
- **move_before_id (Optional[int])** – ID of an issue that should be placed before this issue
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the issue could not be reordered

Return type

None

resourcelabelevents: ProjectIssueResourceLabelEventManager

resourcemilestoneevents: ProjectIssueResourceMilestoneEventManager

resourcestateevents: ProjectIssueResourceStateEventManager

class gitlab.v4.objects.ProjectIssueAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager (RESTManager)** –

- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectIssueAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `NoUpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `name`

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectIssueAwardEmoji
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectIssueAwardEmoji`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectIssueDiscussion(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

notes: *ProjectIssueDiscussionNoteManager*

```
class gitlab.v4.objects.ProjectIssueDiscussionManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, CreateMixin, RESTManager*

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectIssueDiscussion
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIssueDiscussion

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectIssueDiscussionNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectIssueDiscussionNoteManager(gl: Gitlab, parent:  
Optional[RESTObject] = None)
```

Bases: `GetMixin`, `CreateMixin`, `UpdateMixin`, `DeleteMixin`, `RESTManager`

Object Creation

Required attributes for object create:

- `body`

Optional attributes for object create:

- `created_at`

Object update

Required attributes for object update:

- `body`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectIssueDiscussionNote`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectIssueDiscussionNote`

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectIssueLink(manager: RESTManager, attrs: Dict[str, Any], *,  
created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin`, `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectIssueLinkManager(gl: Gitlab, parent: Optional[RESTObject] = None)`
Bases: `ListMixin, CreateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- `target_project_id`
- `target_issue_iid`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

create(`data: Dict[str, Any]`, `**kwargs: Any`) → `Tuple[RESTObject, RESTObject]`

Create a new object.

Parameters

- `data (Dict[str, Any])` – parameters to send to the server to create the resource
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The source and target issues

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

Return type

`Tuple[RESTObject, RESTObject]`

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectIssueManager(gl: Gitlab, parent: Optional[RESTObject] = None)`
Bases: `CRUDMixin, RESTManager`

Object listing filters

- `iids`
- `state`
- `labels`
- `milestone`
- `scope`
- `author_id`
- `assignee_id`
- `my_reaction_emoji`
- `order_by`
- `sort`

- `search`
- `created_after`
- `created_before`
- `updated_after`
- `updated_before`

Object Creation

Required attributes for object create:

- `title`

Optional attributes for object create:

- `description`
- `confidential`
- `assignee_ids`
- `assignee_id`
- `milestone_id`
- `labels`
- `created_at`
- `due_date`
- `merge_request_to_resolve_discussions_of`
- `discussion_to_resolve`

Object update

Optional attributes for object update:

- `title`
- `description`
- `confidential`
- `assignee_ids`
- `assignee_id`
- `milestone_id`
- `labels`
- `state_event`
- `updated_at`
- `due_date`
- `discussion_locked`

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectIssue`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectIssue`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectIssueNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`awardemojis: ProjectIssueNoteAwardEmojiManager`

`class gitlab.v4.objects.ProjectIssueNoteAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `NoUpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [ProjectIssueNoteAwardEmoji](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[ProjectIssueNoteAwardEmoji](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.ProjectIssueNoteManager](#)(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: [CRUDMixin](#), [RESTManager](#)

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- created_at

Object update

Required attributes for object update:

- body

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [ProjectIssueNote](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIssueNote

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectIssueResourceLabelEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectIssueResourceEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectIssueResourceLabelEvent*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIssueResourceLabelEvent

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectIssueResourceMilestoneEvent(manager: RESTManager, attrs:  
    Dict[str, Any], *, created_from_list:  
    bool = False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager(gl: Gitlab, parent:  
    Optional[RESTObject] =  
    None)
```

Bases: `RetrieveMixin, RESTManager`

Object Creation**Object update****Parameters**

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `ProjectIssueResourceMilestoneEvent`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIssueResourceMilestoneEvent

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectIssueResourceStateEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectIssueResourceStateManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin*, *RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectIssueResourceStateEvent*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectIssueResourceStateEvent

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectIssuesStatistics(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RefreshMixin*, *RESTObject*

Parameters

- **manager** (*RESTManager*) –

```
    • attrs (Dict[str, Any]) –
    • created_from_list (bool) –
    • lazy (bool) –

manager: RESTManager

class gitlab.v4.objects.ProjectIssuesStatisticsManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: GetWithoutIdMixin, RESTManager

Object listing filters
    • iids

Object Creation

Object update
    Parameters
        • gl (Gitlab) –
        • parent (Optional[RESTObject]) –
get(**kwargs: Any) → ProjectIssuesStatistics
    Retrieve a single object.

    Parameters
        • **kwargs (Any) – Extra options to send to the server (e.g. sudo)

    Returns
        The generated RESTObject

    Raises
        • GitlabAuthenticationError – If authentication is not correct
        • GitlabGetError – If the server cannot perform the request

    Return type
        ProjectIssuesStatistics

gitlab: Gitlab

class gitlab.v4.objects.ProjectIterationManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, RESTManager

Object listing filters
    • state
    • search
    • include_ancestors

Object Creation

Object update
    Parameters
        • gl (Gitlab) –
        • parent (Optional[RESTObject]) –
```

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectJob(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RefreshMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

```
artifact(path: str, streamed: bool = False, action: Optional[Callable[..., Any]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]
```

Get a single artifact file from within the job's artifacts archive.

Parameters

- **path** (*str*) – Path of the artifact
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[..., Any]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns

The artifacts if *streamed* is False, None otherwise.

Return type

Optional[Union[bytes, Iterator[Any]]]

```
artifacts(streamed: bool = False, action: Optional[Callable[..., Any]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]
```

Get the job artifacts.

Parameters

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[..., Any]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns

The artifacts if *streamed* is False, None otherwise.

Return type

Optional[Union[bytes, Iterator[Any]]]

cancel(kwargs: Any) → Dict[str, Any]**

Cancel the job.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabJobCancelError** – If the job could not be canceled

Return type

Dict[str, Any]

delete_artifacts(kwargs: Any) → None**

Delete artifacts of a job.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the request could not be performed

Return type

None

erase(kwargs: Any) → None**

Erase the job (remove job artifacts and trace).

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabJobEraseError** – If the job could not be erased

Return type

None

keep_artifacts(kwargs: Any) → None**

Prevent artifacts from being deleted when expiration is set.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabCreateError** – If the request could not be performed

Return type

None

manager: *RESTManager*

play(kwargs: Any) → None**

Trigger a job explicitly.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabJobPlayError** – If the job could not be triggered

Return type

None

retry(kwargs: Any) → Dict[str, Any]**

Retry the job.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabJobRetryError** – If the job could not be retried

Return type

Dict[str, Any]

trace(streamed: bool = False, action: Optional[Callable[..., Any]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Dict[str, Any]

Get the job trace.

Parameters

- **streamed (bool)** – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator (bool)** – If True directly return the underlying response iterator
- **action (Optional[Callable[..., Any]])** – Callable responsible of dealing with chunk of data
- **chunk_size (int)** – Size of each chunk
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the artifacts could not be retrieved

Returns

The trace

Return type

Dict[str, Any]

```
class gitlab.v4.objects.ProjectJobManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin*, *RESTManager*

Object listing filters

- scope

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectJob
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectJob

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectKey(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin*, *ObjectDeleteMixin*, *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectKeyManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin*, *RESTManager*

Object Creation

Required attributes for object create:

- title

- `key`

Optional attributes for object create:

- `can_push`

Object update

Optional attributes for object update:

- `title`
- `can_push`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`enable(key_id: int, **kwargs: Any) → Union[Dict[str, Any], Response]`

Enable a deploy key for a project.

Parameters

- `key_id (int)` – The ID of the key to enable
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabProjectDeployKeyError` – If the key could not be enabled

Returns

A dict of the result.

Return type

`Union[Dict[str, Any], Response]`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectKey`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectKey`

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectLabel(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
    bool = False, lazy: bool = False)
```

Bases: PromoteMixin, SubscribableMixin, SaveMixin, ObjectDeleteMixin, RESTObject

Parameters

- **manager** (`ProjectLabelManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `ProjectLabelManager`

save(kwargs: Any) → None**

Saves the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct.
- **GitlabUpdateError** – If the server cannot perform the request.

Return type

None

```
class gitlab.v4.objects.ProjectLabelManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: RetrieveMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager

Object Creation

Required attributes for object create:

- name
- color

Optional attributes for object create:

- description
- priority

Object update

Required attributes for object update:

- name

Optional attributes for object update:

- new_name
- color
- description
- priority

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectLabel`

Retrieve a single object.

Parameters

- `id (Union[str, int]) –` ID of the object to retrieve
- `lazy (bool) –` If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectLabel`

`gitlab: Gitlab`

`update(name: Optional[str], new_data: Optional[Dict[str, Any]] = None, **kwargs: Any) → Dict[str, Any]`

Update a Label on the server.

Parameters

- `name (Optional[str]) –` The name of the label
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)
- `new_data (Optional[Dict[str, Any]]) –`
- `**kwargs –`

Return type

`Dict[str, Any]`

`class gitlab.v4.objects.ProjectManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object listing filters

- `archived`
- `id_after`
- `id_before`
- `last_activity_after`
- `last_activity_before`
- `membership`
- `min_access_level`
- `order_by`

- owned
- repository_checksum_failed
- repository_storage
- search_namespaces
- search
- simple
- sort
- starred
- statistics
- topic
- visibility
- wiki_checksum_failed
- with_custom_attributes
- with_issues_enabled
- with_merge_requests_enabled
- with_programming_language

Object Creation

Optional attributes for object create:

- name
- path
- allow_merge_on_skipped_pipeline
- analytics_access_level
- approvals_before_merge
- auto_cancel_pending_pipelines
- auto_devops_deploy_strategy
- auto_devops_enabled
- autoclose_referenced_issues
- avatar
- build_coverage_regex
- build_git_strategy
- build_timeout
- builds_access_level
- ci_config_path
- container_expiration_policy_attributes
- container_registry_enabled
- default_branch

- `description`
- `emails_disabled`
- `external_authorization_classification_label`
- `forking_access_level`
- `group_with_project_templates_id`
- `import_url`
- `initialize_with_readme`
- `issues_access_level`
- `issues_enabled`
- `jobs_enabled`
- `lfs_enabled`
- `merge_method`
- `merge_pipelines_enabled`
- `merge_requests_access_level`
- `merge_requests_enabled`
- `mirror_trigger_builds`
- `mirror`
- `namespace_id`
- `operations_access_level`
- `only_allow_merge_if_all_discussions_are_resolved`
- `only_allow_merge_if_pipeline_succeeds`
- `packages_enabled`
- `pages_access_level`
- `requirements_access_level`
- `printing_merge_request_link_enabled`
- `public_builds`
- `remove_source_branch_after_merge`
- `repository_access_level`
- `repository_storage`
- `request_access_enabled`
- `resolve_outdated_diff_discussions`
- `shared_runners_enabled`
- `show_default_award_emojis`
- `snippets_access_level`
- `snippets_enabled`
- `squash_option`

- `tag_list`
- `topics`
- `template_name`
- `template_project_id`
- `use_custom_template`
- `visibility`
- `wiki_access_level`
- `wiki_enabled`

Object update

Optional attributes for object update:

- `allow_merge_on_skipped_pipeline`
- `analytics_access_level`
- `approvals_before_merge`
- `auto_cancel_pending_pipelines`
- `auto_devops_deploy_strategy`
- `auto_devops_enabled`
- `autoclose_referenced_issues`
- `avatar`
- `build_coverage_regex`
- `build_git_strategy`
- `build_timeout`
- `builds_access_level`
- `ci_config_path`
- `ci_default_git_depth`
- `ci_forward_deployment_enabled`
- `container_expiration_policy_attributes`
- `container_registry_enabled`
- `default_branch`
- `description`
- `emails_disabled`
- `external_authorization_classification_label`
- `forking_access_level`
- `import_url`
- `issues_access_level`
- `issues_enabled`
- `jobs_enabled`

- lfs_enabled
- merge_method
- merge_pipelines_enabled
- merge_requests_access_level
- merge_requests_enabled
- mirror_overwrites_diverged_branches
- mirror_trigger_builds
- mirror_user_id
- mirror
- name
- operations_access_level
- only_allow_merge_if_all_discussions_are_resolved
- only_allow_merge_if_pipeline_succeeds
- only_mirror_protected_branches
- packages_enabled
- pages_access_level
- requirements_access_level
- restrict_user_defined_variables
- path
- public_builds
- remove_source_branch_after_merge
- repository_access_level
- repository_storage
- request_access_enabled
- resolve_outdated_diff_discussions
- service_desk_enabled
- shared_runners_enabled
- show_default_award_emojis
- snippets_access_level
- snippets_enabled
- squash_option
- suggestion_commit_message
- tag_list
- topics
- visibility
- wiki_access_level

- `wiki_enabled`
- `issues_template`
- `merge_requests_template`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → Project`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`Project`

`gitlab: Gitlab`

`import_bitbucket_server(bitbucket_server_url: str, bitbucket_server_username: str, personal_access_token: str, bitbucket_server_project: str, bitbucket_server_repo: str, new_name: Optional[str] = None, target_namespace: Optional[str] = None, **kwargs: Any) → Union[Dict[str, Any], Response]`

Import a project from BitBucket Server to Gitlab (schedule the import)

This method will return when an import operation has been safely queued, or an error has occurred. After triggering an import, check the `import_status` of the newly created project to detect when the import operation has completed.

Note: This request may take longer than most other API requests. So this method will specify a 60 second default timeout if none is specified. A timeout can be specified via kwargs to override this functionality.

Parameters

- `bitbucket_server_url (str)` – Bitbucket Server URL
- `bitbucket_server_username (str)` – Bitbucket Server Username
- `personal_access_token (str)` – Bitbucket Server personal access token/password
- `bitbucket_server_project (str)` – Bitbucket Project Key

- **bitbucket_server_repo** (*str*) – Bitbucket Repository Name
- **new_name** (*Optional[str]*) – New repository name (Optional)
- **target_namespace** (*Optional[str]*) – Namespace to import repository into. Supports subgroups like /namespace/subgroup (Optional)
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns

A representation of the import status.

Return type

Union[Dict[str, Any], Response]

Example:

```
gl = gitlab.Gitlab_from_config()
print("Triggering import")
result = gl.projects.import_bitbucket_server(
    bitbucket_server_url="https://some.server.url",
    bitbucket_server_username="some_bitbucket_user",
    personal_access_token="my_password_or_access_token",
    bitbucket_server_project="my_project",
    bitbucket_server_repo="my_repo",
    new_name="gl_project_name",
    target_namespace="gl_project_path"
)
project = gl.projects.get(ret['id'])
print("Waiting for import to complete")
while project.import_status == u'started':
    time.sleep(1.0)
    project = gl.projects.get(project.id)
print("BitBucket import complete")
```

import_github(*personal_access_token: str, repo_id: int, target_namespace: str, new_name: Optional[str] = None, **kwargs: Any*) → *Union[Dict[str, Any], Response]*

Import a project from Github to Gitlab (schedule the import)

This method will return when an import operation has been safely queued, or an error has occurred. After triggering an import, check the `import_status` of the newly created project to detect when the import operation has completed.

Note: This request may take longer than most other API requests. So this method will specify a 60 second default timeout if none is specified. A timeout can be specified via kwargs to override this functionality.

Parameters

- **personal_access_token** (*str*) – GitHub personal access token
- **repo_id** (*int*) – Github repository ID

- **target_namespace** (*str*) – Namespace to import repo into
- **new_name** (*Optional[str]*) – New repo name (Optional)
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns

A representation of the import status.

Return type

Union[Dict[str, Any], Response]

Example:

```
gl = gitlab.Gitlab_from_config()
print("Triggering import")
result = gl.projects.import_github(ACCESS_TOKEN,
                                   123456,
                                   "my-group/my-subgroup")
project = gl.projects.get(ret['id'])
print("Waiting for import to complete")
while project.import_status == u'started':
    time.sleep(1.0)
    project = gl.projects.get(project.id)
print("Github import complete")
```

import_project(*file: str, path: str, name: Optional[str] = None, namespace: Optional[str] = None, overwrite: bool = False, override_params: Optional[Dict[str, Any]] = None, **kwargs: Any*) → *Union[Dict[str, Any], Response]*

Import a project from an archive file.

Parameters

- **file** (*str*) – Data or file object containing the project
- **path** (*str*) – Name and path for the new project
- **namespace** (*Optional[str]*) – The ID or path of the namespace that the project will be imported to
- **overwrite** (*bool*) – If True overwrite an existing project with the same path
- **override_params** (*Optional[Dict[str, Any]]*) – Set the specific settings for the project
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)
- **name** (*Optional[str]*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns

A representation of the import status.

Return type

Union[Dict[str, Any], Response]

```
class gitlab.v4.objects.ProjectMember(manager: RESTManager, attrs: Dict[str, Any], *,  
created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectMemberAll(manager: RESTManager, attrs: Dict[str, Any], *,  
created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectMemberAllManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectMemberAll*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMemberAll

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectMemberManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: CRUDMixin, RESTManager
```

Object Creation

Required attributes for object create:

- access_level
- user_id

Optional attributes for object create:

- expires_at
- tasks_to_be_done

Object update

Required attributes for object update:

- access_level

Optional attributes for object update:

- expires_at

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMember
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMember

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequest(manager: RESTManager, attrs: Dict[str, Any], *,  
                                             created_from_list: bool = False, lazy: bool = False)  
Bases: SubscribableMixin, TodoMixin, TimeTrackingMixin, ParticipantsMixin, SaveMixin,  
ObjectDeleteMixin, RESTObject
```

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

approval_rules: ProjectMergeRequestApprovalRuleManager

approval_state: ProjectMergeRequestApprovalStateManager

approvals: ProjectMergeRequestApprovalManager

approve(sha: Optional[str] = None, **kwargs: Any) → Dict[str, Any]

Approve the merge request.

Parameters

- **sha** (Optional[str]) – Head SHA of MR
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMRApiApprovalError** – If the approval failed

Returns

A dict containing the result.

Return type

Dict[str, Any]

https://docs.gitlab.com/ee/api/merge_request_approvals.html#approve-merge-request

awardemojis: ProjectMergeRequestAwardEmojiManager

cancel_merge_when_pipeline_succeeds(**kwargs: Any) → ProjectMergeRequest

Cancel merge when the pipeline succeeds.

Parameters

- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMROnBuildSuccessError** – If the server could not handle the request

Returns

ProjectMergeRequest

Return type

ProjectMergeRequest

changes(**kwargs: Any) → Union[Dict[str, Any], Response]

List the merge request changes.

Parameters

**kwargs (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

List of changes

Return type

Union[Dict[str, Any], Response]

closes_issues(**kwargs: Any) → RESTObjectList

List issues that will close on merge.”

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **kwargs (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

List of issues

Return type

RESTObjectList

commits(**kwargs: Any) → RESTObjectList

List the merge request commits.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **kwargs (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

The list of commits

Return type

RESTObjectList

diffs: *ProjectMergeRequestDiffManager*
discussions: *ProjectMergeRequestDiscussionManager*
merge(*merge_commit_message: Optional[str] = None*, *should_remove_source_branch: Optional[bool] = None*, *merge_when_pipeline_succeeds: Optional[bool] = None*, ***kwargs: Any*) → *Dict[str, Any]*
Accept the merge request.

Parameters

- **merge_commit_message** (*Optional[str]*) – Commit message
- **should_remove_source_branch** (*Optional[bool]*) – If True, removes the source branch
- **merge_when_pipeline_succeeds** (*Optional[bool]*) – Wait for the build to succeed, then merge
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMRClosedError** – If the merge failed

Return type

Dict[str, Any]

merge_ref(***kwargs: Any*) → *Union[Dict[str, Any], Response]*

**Attempt to merge changes between source and target branches into
refs/merge-requests/:iid/merge.**

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabGetError** – If cannot be merged

Return type

Union[Dict[str, Any], Response]

notes: *ProjectMergeRequestNoteManager*

pipelines: *ProjectMergeRequestPipelineManager*

rebase(***kwargs: Any*) → *Union[Dict[str, Any], Response]*

Attempt to rebase the source branch onto the target branch

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabMRRebaseError** – If rebasing failed

Return type

Union[Dict[str, Any], Response]

`reset_approvals(**kwargs: Any) → Union[Dict[str, Any], Response]`

Clear all approvals of the merge request.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct

- `GitlabMRResetApprovalError` – If reset approval failed

Return type

`Union[Dict[str, Any], Response]`

`resource_label_events: ProjectMergeRequestResourceLabelEventManager`

`resource_milestone_events: ProjectMergeRequestResourceMilestoneEventManager`

`resource_state_events: ProjectMergeRequestResourceStateEventManager`

`unapprove(**kwargs: Any) → None`

Unapprove the merge request.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct

- `GitlabMRApprovalError` – If the unapproval failed

Return type

`None`

https://docs.gitlab.com/ee/api/merge_request_approvals.html#unapprove-merge-request

`class gitlab.v4.objects.ProjectMergeRequestApproval(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectMergeRequestApprovalManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `GetWithoutIdMixin, UpdateMixin, RESTManager`

Object Creation

Object update

Required attributes for object update:

- `approvals_required`

Parameters

- `g1 (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → ProjectMergeRequestApproval`

Retrieve a single object.

Parameters

- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectMergeRequestApproval`

`gitlab: Gitlab`

`set_approvers(approvals_required: int, approver_ids: Optional[List[int]] = None, approver_group_ids: Optional[List[int]] = None, approval_rule_name: str = 'name', **kwargs: Any) → RESTObject`

Change MR-level allowed approvers and approver groups.

Parameters

- `approvals_required (int)` – The number of required approvals for this rule
- `approver_ids (Optional[List[int]])` – User IDs that can approve MRs
- `approver_group_ids (Optional[List[int]])` – Group IDs whose members can approve MRs
- `approval_rule_name (str)` –
- `kwargs (Any)` –

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server failed to perform the request

Return type

`RESTObject`

`class gitlab.v4.objects.ProjectMergeRequestApprovalRule(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –

- `created_from_list (bool) –`
- `lazy (bool) –`

`approval_rule_id: int`

`id: int`

`merge_request_iid: int`

`save(**kwargs: Any) → None`

Save the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server cannot perform the request

Return type

None

`class gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `id`
- `merge_request_iid`
- `name`
- `approvals_required`

Optional attributes for object create:

- `approval_project_rule_id`
- `user_ids`
- `group_ids`

Object update

Required attributes for object update:

- `id`
- `merge_request_iid`
- `approval_rule_id`
- `name`
- `approvals_required`

Optional attributes for object update:

- `user_ids`

- `group_ids`

Parameters

- `g1 (Gitlab)` –
- `parent (Optional[RESTObject])` –

`create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → RESTObject`

Create a new object.

Parameters

- `data (Optional[Dict[str, Any]])` – Parameters to send to the server to create the resource
- `**kwargs (Any)` – Extra options to send to the server (e.g. `sudo` or `'ref_name'`, `'stage'`, `'name'`, `'all'`)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

Returns

A new instance of the `manage` object class build with
the data sent by the server

Return type

`RESTObject`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestApprovalRule`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. `sudo`)

Returns

The generated `RESTObject`.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectMergeRequestApprovalRule`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectMergeRequestApprovalState(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectMergeRequestApprovalStateManager`(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `GetWithoutIdMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(kwargs: Any) → ProjectMergeRequestApprovalState**

Retrieve a single object.

Parameters

- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectMergeRequestApprovalState`

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectMergeRequestAwardEmoji`(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager(gl: Gitlab, parent:  
                           Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestAwardEmoji
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[ProjectMergeRequestAwardEmoji](#)

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.ProjectMergeRequestDiff(manager: RESTManager, attrs: Dict[str, Any], *,  
                                               created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: [RESTManager](#)

```
class gitlab.v4.objects.ProjectMergeRequestDiffManager(gl: Gitlab, parent: Optional[RESTObject] =  
                           None)
```

Bases: *RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (*Optional*[`RESTObject`]) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestDiff`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectMergeRequestDiff`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectMergeRequestDiscussion(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

`notes: ProjectMergeRequestDiscussionNoteManager`

`class gitlab.v4.objects.ProjectMergeRequestDiscussionManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, CreateMixin, UpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- `created_at`
- `position`

Object update

Required attributes for object update:

- resolved

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestDiscussion`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectMergeRequestDiscussion`

gitlab: `Gitlab`

`class gitlab.v4.objects.ProjectMergeRequestDiscussionNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

`class gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `GetMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- `created_at`

Object update

Required attributes for object update:

- `body`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestDiscussionNote`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectMergeRequestDiscussionNote`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectMergeRequestManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object listing filters

- `state`
- `order_by`
- `sort`
- `milestone`
- `view`
- `labels`
- `created_after`
- `created_before`
- `updated_after`
- `updated_before`

- scope
- iids
- author_id
- assignee_id
- approver_ids
- approved_by_ids
- my_reaction_emoji
- source_branch
- target_branch
- search
- wip

Object Creation

Required attributes for object create:

- source_branch
- target_branch
- title

Optional attributes for object create:

- allow_collaboration
- allow_maintainer_to_push
- approvals_before_merge
- assignee_id
- assignee_ids
- description
- labels
- milestone_id
- remove_source_branch
- reviewer_ids
- squash
- target_project_id

Object update

Optional attributes for object update:

- target_branch
- assignee_id
- title
- description
- state_event

- labels
- milestone_id
- remove_source_branch
- discussion_locked
- allow_maintainer_to_push
- squash
- reviewer_ids

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional*[[RESTObject](#)]) –

get(*id*: *Union*[*str*, *int*], *lazy*: *bool* = *False*, ***kwargs*: *Any*) → [ProjectMergeRequest](#)

Retrieve a single object.

Parameters

- **id** (*Union*[*str*, *int*]) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[ProjectMergeRequest](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.ProjectMergeRequestNote](#)(*manager*: [RESTManager](#), *attrs*: *Dict*[*str*, *Any*], *, *created_from_list*: *bool* = *False*, *lazy*: *bool* = *False*)

Bases: [SaveMixin](#), [ObjectDeleteMixin](#), [RESTObject](#)

Parameters

- **manager** ([RESTManager](#)) –
- **attrs** (*Dict*[*str*, *Any*]) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

awardemojis: [ProjectMergeRequestNoteAwardEmojiManager](#)

```
class gitlab.v4.objects.ProjectMergeRequestNoteAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → *ProjectMergeRequestNoteAwardEmoji*

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectMergeRequestNoteAwardEmoji`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectMergeRequestNoteManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin*, *RESTManager*

Object Creation

Required attributes for object create:

- body

Object update

Required attributes for object update:

- body

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectMergeRequestNote
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMergeRequestNote

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestPipeline(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectMergeRequestPipelineManager(gl: Gitlab, parent:  
Optional[RESTObject] = None)
```

Bases: *CreateMixin, ListMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestResourceLabelEvent(manager: RESTManager, attrs:  
Dict[str, Any], *, created_from_list:  
bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager(gl: Gitlab, parent:  
Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectMergeRequestResourceLabelEvent*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMergeRequestResourceLabelEvent

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEvent(manager: RESTManager,  
                     attrs: Dict[str, Any], *,  
                     created_from_list: bool =  
                         False, lazy: bool = False)
```

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager(gl: Gitlab, parent:  
                           Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, RESTManager`

Object Creation**Object update****Parameters**

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `ProjectMergeRequestResourceMilestoneEvent`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMergeRequestResourceMilestoneEvent

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectMergeRequestResourceStateEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectMergeRequestResourceEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectMergeRequestResourceStateEvent*
Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated *RESTObject*.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectMergeRequestResourceStateEvent

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectMergeTrain(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

gitlab.v4.objects.ProjectMergeTrainManager(`gl: Gitlab, parent: Optional[RESTObject] = None`)
Bases: `ListMixin, RESTManager`

Object listing filters

- `scope`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

gitlab.v4.objects.ProjectMilestone(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)
Bases: `PromoteMixin, SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

issues(kwargs: Any) → RESTObjectList**

List issues related to this milestone.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

The list of issues

Return type
`RESTObjectList`

`manager: RESTManager`

`merge_requests(**kwargs: Any) → RESTObjectList`

List the merge requests related to this milestone.

Parameters

- `all` – If True, return all the items, without pagination
- `per_page` – Number of items to retrieve per request
- `page` – ID of the page to return (starts with page 1)
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the list could not be retrieved

Returns

The list of merge requests

Return type

`RESTObjectList`

`class gitlab.v4.objects.ProjectMilestoneManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `CRUDMixin, RESTManager`

Object listing filters

- `iids`
- `state`
- `search`

Object Creation

Required attributes for object create:

- `title`

Optional attributes for object create:

- `description`
- `due_date`
- `start_date`
- `state_event`

Object update

Optional attributes for object update:

- `title`
- `description`
- `due_date`
- `start_date`
- `state_event`

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, ***kwargs*: `Any`) → `ProjectMilestone`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectMilestone`

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectNote`(*manager*: `RESTManager`, *attrs*: `Dict[str, Any]`, *, *created_from_list*: `bool = False`, *lazy*: `bool = False`)

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

class `gitlab.v4.objects.ProjectNoteManager`(*gl*: `Gitlab`, *parent*: `Optional[RESTObject] = None`)

Bases: `RetrieveMixin, RESTManager`

Object Creation

Required attributes for object create:

- body

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectNote`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectNote`

gitlab: `Gitlab`

`class gitlab.v4.objects.ProjectNotificationSettings(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `NotificationSettings`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

`class gitlab.v4.objects.ProjectNotificationSettingsManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `NotificationSettingsManager`

Object Creation

Object update

Optional attributes for object update:

- `level`
- `notification_email`
- `new_note`
- `new_issue`
- `reopen_issue`
- `close_issue`
- `reassign_issue`

- `new_merge_request`
- `reopen_merge_request`
- `close_merge_request`
- `reassign_merge_request`
- `merge_merge_request`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → ProjectNotificationSettings`

Retrieve a single object.

Parameters

- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectNotificationSettings`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectPackage(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`package_files: ProjectPackageManager`

`class gitlab.v4.objects.ProjectPackageFile(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

```
manager: RESTManager

class gitlab.v4.objects.ProjectPackageManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: DeleteMixin, ListMixin, RESTManager

Object Creation
Object update

    Parameters
        • gl (Gitlab) –
        • parent (Optional[RESTObject]) –

gitlab: Gitlab

class gitlab.v4.objects.ProjectPackageManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, GetMixin, DeleteMixin, RESTManager

Object listing filters
    • order_by
    • sort
    • package_type
    • package_name

Object Creation
Object update

    Parameters
        • gl (Gitlab) –
        • parent (Optional[RESTObject]) –

get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectPackage
Retrieve a single object.

    Parameters
        • id (Union[str, int]) – ID of the object to retrieve
        • lazy (bool) – If True, don't request the server, but create a shallow object giving
                      access to the managers. This is useful if you want to avoid useless calls to the API.
        • **kwargs (Any) – Extra options to send to the server (e.g. sudo)

    Returns
        The generated RESTObject.

    Raises
        • GitlabAuthenticationError – If authentication is not correct
        • GitlabGetError – If the server cannot perform the request

    Return type
        ProjectPackage

gitlab: Gitlab
```

```
class gitlab.v4.objects.ProjectPagesDomain(manager: RESTManager, attrs: Dict[str, Any], *,  
    created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin`, `ObjectDeleteMixin`, `RESTObject`

Parameters

- `manager` (`RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –
- `lazy` (`bool`) –

`manager:` `RESTManager`

```
class gitlab.v4.objects.ProjectPagesDomainManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `CRUDMixin`, `RESTManager`

Object Creation

Required attributes for object create:

- `domain`

Optional attributes for object create:

- `certificate`
- `key`

Object update

Optional attributes for object update:

- `certificate`
- `key`

Parameters

- `gl` (`Gitlab`) –
- `parent` (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectPagesDomain`

Retrieve a single object.

Parameters

- `id` (`Union[str, int]`) – ID of the object to retrieve
- `lazy` (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectPagesDomain`

gitlab: `Gitlab`

class `gitlab.v4.objects.ProjectPipeline(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RefreshMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

bridges: `ProjectPipelineBridgeManager`

cancel(kwargs: Any) → Union[Dict[str, Any], Response]**

Cancel the job.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPipelineCancelError** – If the request failed

Return type

`Union[Dict[str, Any], Response]`

jobs: `ProjectPipelineJobManager`

retry(kwargs: Any) → Union[Dict[str, Any], Response]**

Retry the job.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPipelineRetryError** – If the request failed

Return type

`Union[Dict[str, Any], Response]`

test_report: `ProjectPipelineTestReportManager`

test_report_summary: `ProjectPipelineTestReportSummaryManager`

variables: `ProjectPipelineVariableManager`

class `gitlab.v4.objects.ProjectPipelineBridge(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

gitlab.v4.objects.ProjectPipelineBridgeManager(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `ListMixin, RESTManager`

Object listing filters

- `scope`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

gitlab.v4.objects.ProjectPipelineJob(`manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)

Bases: `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

gitlab.v4.objects.ProjectPipelineJobManager(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `ListMixin, RESTManager`

Object listing filters

- `scope`
- `include_retried`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectPipelineManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: RetrieveMixin, CreateMixin, DeleteMixin, RESTManager
```

Object listing filters

- scope
- status
- ref
- sha
- yaml_errors
- name
- username
- order_by
- sort

Object Creation

Required attributes for object create:

- ref

Object update

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

```
create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → ProjectPipeline
```

Creates a new object.

Parameters

- **data** (Optional[Dict[str, Any]]) – Parameters to send to the server to create the resource
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabCreateError** – If the server cannot perform the request

Returns

A new instance of the managed object class build with the data sent by the server

Return type

ProjectPipeline

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectPipeline
```

Retrieve a single object.

Parameters

- **id** (Union[str, int]) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectPipeline

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectPipelineSchedule(manager: RESTManager, attrs: Dict[str, Any], *,  
                                               created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

play(kwargs: Any) → Dict[str, Any]**

Trigger a new scheduled pipeline, which runs immediately. The next scheduled run of this pipeline is not affected.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPipelinePlayError** – If the request failed

Return type

Dict[str, Any]

take_ownership(kwargs: Any) → None**

Update the owner of a pipeline schedule.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabOwnershipError** – If the request failed

Return type

None

variables: *ProjectPipelineScheduleVariableManager*

```
class gitlab.v4.objects.ProjectPipelineScheduleManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- `description`
- `ref`
- `cron`

Optional attributes for object create:

- `cron_timezone`
- `active`

Object update

Optional attributes for object update:

- `description`
- `ref`
- `cron`
- `cron_timezone`
- `active`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectPipelineSchedule`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectPipelineSchedule`

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectPipelineScheduleVariable(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectPipelineScheduleVariableManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CreateMixin, UpdateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- key
- value

Object update

Required attributes for object update:

- key
- value

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectPipelineTestReport(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectPipelineTestReportManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(**`kwargs`: Any) → *ProjectPipelineTestReport*

Retrieve a single object.

Parameters

****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectPipelineTestReport`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectPipelineTestReportSummary(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectPipelineTestReportSummaryManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

```
get(**kwargs: Any) → ProjectPipelineTestReportSummary
```

Retrieve a single object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectPipelineTestReportSummary

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.ProjectPipelineVariable(manager: RESTManager, attrs: Dict[str, Any], *,  
                                               created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

manager: [RESTManager](#)

```
class gitlab.v4.objects.ProjectPipelineVariableManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                     None)
```

Bases: *ListMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl (Gitlab)** –
- **parent (Optional[RESTObject])** –

gitlab: [Gitlab](#)

```
class gitlab.v4.objects.ProjectProtectedBranch(manager: RESTManager, attrs: Dict[str, Any], *,  
                                                created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

`manager: RESTManager`

```
class gitlab.v4.objects.ProjectProtectedBranchManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `NoUpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `name`

Optional attributes for object create:

- `push_access_level`
- `merge_access_level`
- `unprotect_access_level`
- `allowed_to_push`
- `allowed_to_merge`
- `allowed_to_unprotect`
- `code_owner_approval_required`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectProtectedBranch
```

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectProtectedBranch`

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectProtectedEnvironment(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectProtectedEnvironmentManager(gl: Gitlab, parent:  
Optional[RESTObject] = None)
```

Bases: `RetrieveMixin, CreateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- `name`
- `deploy_access_levels`

Optional attributes for object create:

- `required_approval_count`
- `approval_rules`

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `ProjectProtectedEnvironment`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectProtectedEnvironment`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectProtectedTag(manager: RESTManager, attrs: Dict[str, Any], *,  
    created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectProtectedTagManager(gl: Gitlab, parent: Optional[RESTObject] =  
    None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- **name**

Optional attributes for object create:

- **create_access_level**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectProtectedTag*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectProtectedTag

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectPushRules(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin*, *ObjectDeleteMixin*, *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectPushRulesManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin*, *CreateMixin*, *UpdateMixin*, *DeleteMixin*, *RESTManager*

Object Creation

Optional attributes for object create:

- `author_email_regex`
- `branch_name_regex`
- `commit_committer_check`
- `commit_message_negative_regex`
- `commit_message_regex`
- `deny_delete_tag`
- `file_name_regex`
- `max_file_size`
- `member_check`
- `prevent_secrets`
- `reject_unsigned_commits`

Object update

Optional attributes for object update:

- `author_email_regex`
- `branch_name_regex`
- `commit_committer_check`
- `commit_message_negative_regex`
- `commit_message_regex`
- `deny_delete_tag`
- `file_name_regex`
- `max_file_size`
- `member_check`
- `prevent_secrets`
- `reject_unsigned_commits`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(**kwargs: Any) → ProjectPushRules`

Retrieve a single object.

Parameters

- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectPushRules`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectRegistryRepository(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`tags: ProjectRegistryTagManager`

`class gitlab.v4.objects.ProjectRegistryRepositoryManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `DeleteMixin, ListMixin, RESTManager`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectRegistryTag(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

gitlab.v4.objects.ProjectRegistryTagManager(`gl: Gitlab, parent: Optional[RESTObject] = None`)

Bases: `DeleteMixin, RetrieveMixin, RESTManager`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

delete_in_bulk(`name_regex_delete: str, **kwargs: Any`) → `None`

Delete Tag in bulk

Parameters

- **name_regex_delete** (`str`) – The regex of the name to delete. To delete all tags specify `.*`.
- **keep_n** – The amount of latest tags of given name to keep.
- **name_regex_keep** – The regex of the name to keep. This value overrides any matches from `name_regex`.
- **older_than** – Tags to delete that are older than the given time, written in human readable form `1h, 1d, 1month`.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. `sudo`)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

`None`

get(`id: Union[str, int], lazy: bool = False, **kwargs: Any`) → `ProjectRegistryTag`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. `sudo`)

Returns

The generated `RESTObject`.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectRegistryTag`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectRelease(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

links: `ProjectReleaseLinkManager`

```
class gitlab.v4.objects.ProjectReleaseLink(manager: RESTManager, attrs: Dict[str, Any], *,  
                                            created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, SaveMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectReleaseLinkManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `CRUDMixin, RESTManager`

Object Creation

Required attributes for object create:

- `name`
- `url`

Optional attributes for object create:

- `filepath`
- `link_type`

Object update

Optional attributes for object update:

- `name`
- `url`
- `filepath`

- `link_type`

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectReleaseLink`

Retrieve a single object.

Parameters

- `id (Union[str, int]) –` ID of the object to retrieve
- `lazy (bool) –` If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any) –` Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectReleaseLink`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectReleaseManager(gl: Gitlab, parent: Optional[RESTObject] = None)`
Bases: `CRUDMixin, RESTManager`

Object listing filters

- `order_by`
- `sort`
- `include_html_description`

Object Creation

Required attributes for object create:

- `tag_name`
- `description`

Optional attributes for object create:

- `name`
- `ref`
- `assets`

Object update

Optional attributes for object update:

- `name`
- `description`

- `milestones`
- `released_at`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectRelease`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectRelease`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectRemoteMirror(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectRemoteMirrorManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `ListMixin, CreateMixin, UpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- `url`

Optional attributes for object create:

- `enabled`

- `only_protected_branches`

Object update

Optional attributes for object update:

- `enabled`
- `only_protected_branches`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectRunner(manager: RESTManager, attrs: Dict[str, Any], *,  
                                      created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.ProjectRunnerManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `CreateMixin, DeleteMixin, ListMixin, RESTManager`

Object listing filters

- `scope`
- `tag_list`

Object Creation

Required attributes for object create:

- `runner_id`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.ProjectService(manager: RESTManager, attrs: Dict[str, Any], *,  
                                       created_from_list: bool = False, lazy: bool = False)
```

Bases: `ProjectIntegration`

Parameters

- `manager (RESTManager)` –

```
    • attrs (Dict[str, Any]) –
    • created_from_list (bool) –
    • lazy (bool) –

manager: RESTManager

class gitlab.v4.objects.ProjectServiceManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ProjectIntegrationManager

Object Creation
Object update

    Parameters
        • gl (Gitlab) –
        • parent (Optional[RESTObject]) –

get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectService
    Retrieve a single object.

    Parameters
        • id (Union[str, int]) – ID of the object to retrieve
        • lazy (bool) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
        • **kwargs (Any) – Extra options to send to the server (e.g. sudo)

    Returns
        The generated RESTObject.

    Raises
        • GitlabAuthenticationError – If authentication is not correct
        • GitlabGetError – If the server cannot perform the request

    Return type
        ProjectService

gitlab: Gitlab

class gitlab.v4.objects.ProjectSnippet(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
Bases: UserAgentDetailMixin, SaveMixin, ObjectDeleteMixin, RESTObject

    Parameters
        • manager (RESTManager) –
        • attrs (Dict[str, Any]) –
        • created_from_list (bool) –
        • lazy (bool) –

awardemojis: ProjectSnippetAwardEmojiManager
```

```
content(streamed: bool = False, action: Optional[Callable[..., Any]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]
```

Return the content of a snippet.

Parameters

- **streamed** (bool) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment.
- **iterator** (bool) – If True directly return the underlying response iterator
- **action** (Optional[Callable[..., Any]]) – Callable responsible of dealing with chunk of data
- **chunk_size** (int) – Size of each chunk
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the content could not be retrieved

Returns

The snippet content

Return type

Optional[Union[bytes, Iterator[Any]]]

discussions: *ProjectSnippetDiscussionManager*

notes: *ProjectSnippetNoteManager*

```
class gitlab.v4.objects.ProjectSnippetAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectSnippetAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** (Gitlab) –

- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectSnippetAwardEmoji*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectSnippetAwardEmoji

gitlab: *Gitlab*

class *gitlab.v4.objects.ProjectSnippetDiscussion*(*manager: RESTManager*, *attrs: Dict[str, Any]*, *, *created_from_list: bool = False*, *lazy: bool = False*)

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

notes: *ProjectSnippetDiscussionNoteManager*

class *gitlab.v4.objects.ProjectSnippetDiscussionManager*(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)

Bases: *RetrieveMixin, CreateMixin, RESTManager*

Object Creation

Required attributes for object create:

- **body**

Optional attributes for object create:

- **created_at**

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectSnippetDiscussion
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectSnippetDiscussion`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectSnippetDiscussionNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectSnippetDiscussionNoteManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `GetMixin, CreateMixin, UpdateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- body

Optional attributes for object create:

- `created_at`

Object update

Required attributes for object update:

- body

Parameters

- **gl** (`Gitlab`) –

- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectSnippetDiscussionNote*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectSnippetDiscussionNote

gitlab: *Gitlab*

class *gitlab.v4.objects.ProjectSnippetManager*(*gl: Gitlab*, *parent: Optional[RESTObject] = None*)

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- **title**
- **file_name**
- **content**
- **visibility**

Optional attributes for object create:

- **description**

Object update

Optional attributes for object update:

- **title**
- **file_name**
- **content**
- **visibility**
- **description**

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectSnippet`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectSnippet`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectSnippetNote(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`awardemojis: ProjectSnippetNoteAwardEmojiManager`

`class gitlab.v4.objects.ProjectSnippetNoteAwardEmoji(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `NoUpdateMixin, RESTManager`

Object Creation

Required attributes for object create:

- name

Object update

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [ProjectSnippetNoteAwardEmoji](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

[ProjectSnippetNoteAwardEmoji](#)

gitlab: [Gitlab](#)

class [gitlab.v4.objects.ProjectSnippetNoteManager](#)(*gl: Gitlab, parent: Optional[RESTObject] = None*)

Bases: [CRUDMixin](#), [RESTManager](#)

Object Creation

Required attributes for object create:

- body

Object update

Required attributes for object update:

- body

Parameters

- **gl** ([Gitlab](#)) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → [ProjectSnippetNote](#)

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectSnippetNote

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectStorage(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RefreshMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectStorageManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin, RESTManager*

Object Creation**Object update****Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(***kwargs: Any*) → *ProjectStorage*

Retrieve a single object.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectStorage

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectTag(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.ProjectTagManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object Creation

Required attributes for object create:

- `tag_name`
- `ref`

Optional attributes for object create:

- `message`

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(*id*: Union[str, int], *lazy*: bool = False, ***kwargs*: Any) → *ProjectTag*

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

`ProjectTag`

gitlab: `Gitlab`

```
class gitlab.v4.objects.ProjectTrigger(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin*, *ObjectDeleteMixin*, *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectTriggerManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin*, *RESTManager*

Object Creation

Required attributes for object create:

- **description**

Object update

Required attributes for object update:

- **description**

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *ProjectTrigger*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

ProjectTrigger

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectUser(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectUserManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- `search`
- `skip_users`

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.ProjectVariable(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.ProjectVariableManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- `key`
- `value`

Optional attributes for object create:

- `protected`

- `variable_type`
- `masked`
- `environment_scope`

Object update

Required attributes for object update:

- `key`
- `value`

Optional attributes for object update:

- `protected`
- `variable_type`
- `masked`
- `environment_scope`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectVariable`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectVariable`

`gitlab: Gitlab`

`class gitlab.v4.objects.ProjectWiki(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `SaveMixin, ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –

- **lazy (bool)** –
manager: `RESTManager`

```
class gitlab.v4.objects.ProjectWikiManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: CRUDMixin, RESTManager
```

Object listing filters

- `with_content`

Object Creation

Required attributes for object create:

- `title`
- `content`

Optional attributes for object create:

- `format`

Object update

Optional attributes for object update:

- `title`
- `content`
- `format`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → ProjectWiki
```

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`ProjectWiki`

```
gitlab: Gitlab
```

```
class gitlab.v4.objects.RegistryRepository(manager: RESTManager, attrs: Dict[str, Any], *,  
    created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.RegistryRepositoryManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetMixin, RESTManager*

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *RegistryRepository*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

RegistryRepository

gitlab: *Gitlab*

```
class gitlab.v4.objects.RepositoryMixin
```

Bases: *object*

delete_merged_branches(***kwargs: Any*) → None

Delete merged branches.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server failed to perform the request

Return type

None

repository_archive(*sha: Optional[str] = None, streamed: bool = False, action: Optional[Callable[[...], Any]] = None, chunk_size: int = 1024, format: Optional[str] = None, path: Optional[str] = None, *, iterator: bool = False, **kwargs: Any*) → *Optional[Union[bytes, Iterator[Any]]]*

Return an archive of the repository.

Parameters

- **sha** (*Optional[str]*) – ID of the commit (default branch by default)
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[[...], Any]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- **format** (*Optional[str]*) – file format (tar.gz by default)
- **path** (*Optional[str]*) – The subpath of the repository to download (all files by default)
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns

The binary data of the archive

Return type

Optional[Union[bytes, Iterator[Any]]]

repository_blob(*sha: str, **kwargs: Any*) → *Union[Dict[str, Any], Response]*

Return a file by blob SHA.

Parameters

- **sha** (*str*) – ID of the blob
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The blob content and metadata

Return type

Union[Dict[str, Any], Response]

repository_compare(*from_*: str, *to*: str, **kwargs: Any) → Union[Dict[str, Any], Response]

Return a diff between two branches/commits.

Parameters

- **from** – Source branch/SHA
- **to (str)** – Destination branch/SHA
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)
- **from_ (str)** –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The diff

Return type

Union[Dict[str, Any], Response]

repository_contributors(**kwargs: Any) → Union[*GitlabList*, List[Dict[str, Any]]]

Return a list of contributors for the project.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **iterator** – If set to True and no pagination option is defined, return a generator instead of a list
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The contributors

Return type

Union[*GitlabList*, List[Dict[str, Any]]]

repository_merge_base(refs: List[str], **kwargs: Any) → Union[Dict[str, Any], Response]

Return a diff between two branches/commits.

Parameters

- **refs** (List[str]) – The refs to find the common ancestor of. Multiple refs can be passed.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The common ancestor commit (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

repository_raw_blob(*sha: str, streamed: bool = False, action: Optional[Callable[..., Any]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any*) → *Optional[Union[bytes, Iterator[Any]]]*

Return the raw file contents for a blob.

Parameters

- **sha** (*str*) – ID of the blob
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[..., Any]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The blob content if *streamed* is False, None otherwise

Return type

Optional[Union[bytes, Iterator[Any]]]

repository_tree(*path: str = '/', ref: str = '', recursive: bool = False, **kwargs: Any*) → *Union[GitlabList, List[Dict[str, Any]]]*

Return a list of files in the repository.

Parameters

- **path** (*str*) – Path of the top folder (/ by default)
- **ref** (*str*) – Reference to a commit or branch
- **recursive** (*bool*) – Whether to get the tree recursively
- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- **iterator** – If set to True and no pagination option is defined, return a generator instead of a list
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The representation of the tree

Return type

Union[GitlabList, List[Dict[str, Any]]]

update_submodule(*submodule: str, branch: str, commit_sha: str, **kwargs: Any*) → *Union[Dict[str, Any], Response]*

Update a project submodule

Parameters

- **submodule** (*str*) – Full path to the submodule
- **branch** (*str*) – Name of the branch to commit into
- **commit_sha** (*str*) – Full commit SHA to update the submodule to
- **commit_message** – Commit message. If no message is provided, a default one will be set (optional)
- **kwargs** (*Any*) –

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabPutError** – If the submodule could not be updated

Return type

Union[Dict[str, Any], Response]

class gitlab.v4.objects.Runner(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

jobs: *RunnerJobManager*

class gitlab.v4.objects.RunnerAll(*manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False*)

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.RunnerAllManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- scope
- type
- status
- paused
- tag_list

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.RunnerJob(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.RunnerJobManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- status

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.RunnerManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object listing filters

- scope

- type
- status
- paused
- tag_list

Object Creation

Required attributes for object create:

- token

Optional attributes for object create:

- description
- info
- active
- locked
- run_untagged
- tag_list
- access_level
- maximum_timeout

Object update

Optional attributes for object update:

- description
- active
- tag_list
- run_untagged
- locked
- access_level
- maximum_timeout

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`all(scope: Optional[str] = None, **kwargs: Any) → List[Runner]`

List all the runners.

Parameters

- `scope (Optional[str])` – The scope of runners to show, one of: specific, shared, active, paused, online
- `all` – If True, return all the items, without pagination
- `per_page` – Number of items to retrieve per request
- `page` – ID of the page to return (starts with page 1)

- **iterator** – If set to True and no pagination option is defined, return a generator instead of a list
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server failed to perform the request

Returns

A list of runners matching the scope.

Return type

List[Runner]

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *Runner*

Retrieve a single object.

Parameters

- **id (Union[str, int])** – ID of the object to retrieve
- **lazy (bool)** – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Runner

gitlab: Gitlab

verify(*token: str*, ***kwargs: Any*) → None

Validates authentication credentials for a registered Runner.

Parameters

- **token (str)** – The runner's authentication token
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabVerifyError** – If the server failed to verify the token

Return type

None

class gitlab.v4.objects.SharedProject(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)

Bases: *RESTObject*

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.SharedProjectManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: ListMixin, RESTManager
```

Object listing filters

- `archived`
- `visibility`
- `order_by`
- `sort`
- `search`
- `simple`
- `starred`
- `with_issues_enabled`
- `with_merge_requests_enabled`
- `min_access_level`
- `with_custom_attributes`

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

gitlab: `Gitlab`

```
class gitlab.v4.objects.SidekiqManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: RESTManager
```

Manager for the Sidekiq methods.

This manager doesn't actually manage objects but provides helper function for the sidekiq metrics API.

Object Creation

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

compound_metrics(kwargs: Any) → Union[Dict[str, Any], Response]**

Return all available metrics and statistics.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the information couldn't be retrieved

Returns

All available Sidekiq metrics and statistics

Return type

Union[Dict[str, Any], Response]

gitlab: Gitlab

job_stats(kwargs: Any) → Union[Dict[str, Any], Response]**

Return statistics about the jobs performed.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the information couldn't be retrieved

Returns

Statistics about the Sidekiq jobs performed

Return type

Union[Dict[str, Any], Response]

process_metrics(kwargs: Any) → Union[Dict[str, Any], Response]**

Return the registered sidekiq workers.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the information couldn't be retrieved

Returns

Information about the register Sidekiq worker

Return type

Union[Dict[str, Any], Response]

queue_metrics(kwargs: Any) → Union[Dict[str, Any], Response]**

Return the registered queues information.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabGetError** – If the information couldn't be retrieved

Returns

Information about the Sidekiq queues

Return type

Union[Dict[str, Any], Response]

```
class gitlab.v4.objects.Snippet(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *UserAgentDetailMixin, SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

content (*streamed: bool = False, action: Optional[Callable[..., Any]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any*) → *Optional[Union[bytes, Iterator[Any]]]*

Return the content of a snippet.

Parameters

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk_size* and each chunk is passed to *action* for treatment.
- **iterator** (*bool*) – If True directly return the underlying response iterator
- **action** (*Optional[Callable[..., Any]]*) – Callable responsible of dealing with chunk of data
- **chunk_size** (*int*) – Size of each chunk
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the content could not be retrieved

Returns

The snippet content

Return type

Optional[Union[bytes, Iterator[Any]]]

manager: *RESTManager*

```
class gitlab.v4.objects.SnippetManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- **title**
- **file_name**
- **content**

Optional attributes for object create:

- `lifetime`
- `visibility`

Object update

Optional attributes for object update:

- `title`
- `file_name`
- `content`
- `visibility`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → Snippet`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`Snippet`

`gitlab: Gitlab`

`public(**kwargs: Any) → Union[RESTObjectList, List[RESTObject]]`

List all the public snippets.

Parameters

- `all` – If True the returned object will be a list
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

`GitlabListError` – If the list could not be retrieved

Returns

A generator for the snippets list

Return type

`Union[RESTObjectList, List[RESTObject]]`

```
class gitlab.v4.objects.StarredProject(manager: RESTManager, attrs: Dict[str, Any], *,  
                                         created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.StarredProjectManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin, RESTManager*

Object listing filters

- `archived`
- `membership`
- `min_access_level`
- `order_by`
- `owned`
- `search`
- `simple`
- `sort`
- `starred`
- `statistics`
- `visibility`
- `with_custom_attributes`
- `with_issues_enabled`
- `with_merge_requests_enabled`

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.Todo(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool =  
                                         False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –

- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

mark_as_done (**kwargs: `Any`) → `Dict[str, Any]`

Mark the todo as done.

Parameters

**kwargs (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTodoError** – If the server failed to perform the request

Returns

A dict with the result

Return type

`Dict[str, Any]`

class `gitlab.v4.objects.TodoManager`(`gl: Gitlab`, `parent: Optional[RESTObject] = None`)

Bases: `ListMixin, DeleteMixin, RESTManager`

Object listing filters

- `action`
- `author_id`
- `project_id`
- `state`
- `type`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

gitlab: `Gitlab`

mark_all_as_done (**kwargs: `Any`) → `None`

Mark all the todos as done.

Parameters

**kwargs (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTodoError** – If the server failed to perform the request

Returns

The number of todos marked done

Return type

None

```
class gitlab.v4.objects.Topic(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.TopicManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *CRUDMixin, RESTManager*

Object Creation

Required attributes for object create:

- name

Optional attributes for object create:

- avatar
- description
- title

Object update

Optional attributes for object update:

- avatar
- description
- name

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → Topic
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Topic

gitlab: *Gitlab*

```
class gitlab.v4.objects.User(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *SaveMixin, ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

activate(kwargs: Any) → Union[Dict[str, Any], Response]**

Activate the user.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabActivateError** – If the user could not be activated

Returns

Whether the user status has been changed

Return type

Union[Dict[str, Any], Response]

approve(kwargs: Any) → Union[Dict[str, Any], Response]**

Approve a user creation request.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUserApproveError** – If the user could not be activated

Returns

The new object data (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

ban(kwargs: Any) → Union[Dict[str, Any], Response]**

Ban the user.

Parameters

****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabBanError** – If the user could not be banned

Returns

Whether the user has been banned

Return type

Union[Dict[str, Any], Response]

block(kwargs: Any) → Optional[bool]**

Block the user.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabBlockError** – If the user could not be blocked

Returns

Whether the user status has been changed

Return type

Optional[bool]

customattributes: UserCustomAttributeManager

deactivate(kwargs: Any) → Union[Dict[str, Any], Response]**

Deactivate the user.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeactivateError** – If the user could not be deactivated

Returns

Whether the user status has been changed

Return type

Union[Dict[str, Any], Response]

emails: UserEmailManager

events: UserEventManager

follow(kwargs: Any) → Union[Dict[str, Any], Response]**

Follow the user.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabFollowError** – If the user could not be followed

Returns

The new object data (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

followers_users: *UserFollowersManager*

following_users: *UserFollowingManager*

gpgkeys: *UserGPGKeyManager*

identityproviders: *UserIdentityProviderManager*

impersonationtokens: *UserImpersonationTokenManager*

keys: *UserKeyManager*

memberships: *UserMembershipManager*

personal_access_tokens: *UserPersonalAccessTokenManager*

projects: *UserProjectManager*

reject(kwargs: Any) → Union[Dict[str, Any], Response]**

Reject a user creation request.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabUserRejectError** – If the user could not be rejected

Returns

The new object data (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

starred_projects: *StarredProjectManager*

status: *UserStatusManager*

unban(kwargs: Any) → Union[Dict[str, Any], Response]**

Unban the user.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabUnbanError** – If the user could not be unbanned

Returns

Whether the user has been unbanned

Return type

Union[Dict[str, Any], Response]

unblock(**kwargs: Any) → Optional[bool]

Unblock the user.

Parameters

**kwargs (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUnblockError** – If the user could not be unblocked

Returns

Whether the user status has been changed

Return type

Optional[bool]

unfollow(**kwargs: Any) → Union[Dict[str, Any], Response]

Unfollow the user.

Parameters

**kwargs (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUnfollowError** – If the user could not be followed

Returns

The new object data (*not* a RESTObject)

Return type

Union[Dict[str, Any], Response]

class gitlab.v4.objects.UserActivities(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)

Bases: RESTObject

Parameters

- **manager** (RESTManager) –
- **attrs** (Dict[str, Any]) –
- **created_from_list** (bool) –
- **lazy** (bool) –

manager: RESTManager

class gitlab.v4.objects.UserActivitiesManager(gl: Gitlab, parent: Optional[RESTObject] = None)

Bases: ListMixin, RESTManager

Object Creation

Object update

Parameters

- **gl** (Gitlab) –
- **parent** (Optional[RESTObject]) –

`gitlab: Gitlab`

```
class gitlab.v4.objects.UserCustomAttribute(manager: RESTManager, attrs: Dict[str, Any], *,  
                                             created_from_list: bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager` (`RESTManager`) –
- `attrs` (`Dict[str, Any]`) –
- `created_from_list` (`bool`) –
- `lazy` (`bool`) –

`manager: RESTManager`

```
class gitlab.v4.objects.UserCustomAttributeManager(gl: Gitlab, parent: Optional[RESTObject] =  
                                                 None)
```

Bases: `RetrieveMixin, SetMixin, DeleteMixin, RESTManager`

Object Creation

Object update

Parameters

- `gl` (`Gitlab`) –
- `parent` (`Optional[RESTObject]`) –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → UserCustomAttribute`

Retrieve a single object.

Parameters

- `id` (`Union[str, int]`) – ID of the object to retrieve
- `lazy` (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs` (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`UserCustomAttribute`

`gitlab: Gitlab`

```
class gitlab.v4.objects.UserEmail(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                    bool = False, lazy: bool = False)
```

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager` (`RESTManager`) –

```
    • attrs (Dict[str, Any]) –
    • created_from_list (bool) –
    • lazy (bool) –

manager: RESTManager

class gitlab.v4.objects.UserEmailManager(gl: Gitlab, parent: Optional[RESTObject] = None)
Bases: RetrieveMixin, CreateMixin, DeleteMixin, RESTManager
```

Object Creation

Required attributes for object create:

- `email`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → UserEmail
```

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`UserEmail`

gitlab: *Gitlab*

```
class gitlab.v4.objects.UserEvent(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *Event*

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

manager: *RESTManager*

```
class gitlab.v4.objects.UserEventManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *EventManager*

Object listing filters

- action
- target_type
- before
- after
- sort

Object Creation

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.UserGPGKey(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list:  
                                bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.UserGPGKeyManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *RetrieveMixin, CreateMixin, DeleteMixin, RESTManager*

Object Creation

Required attributes for object create:

- key

Object update

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

get(*id: Union[str, int]*, *lazy: bool = False*, ***kwargs: Any*) → *UserGPGKey*

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve

- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

UserGPGKey

gitlab: *Gitlab*

```
class gitlab.v4.objects.UserIdentityProviderManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *DeleteMixin, RESTManager*

Manager for user identities.

This manager does not actually manage objects but enables functionality for deletion of user identities by provider.

Object Creation**Object update****Parameters**

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

gitlab: *Gitlab*

```
class gitlab.v4.objects.UserImpersonationToken(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *ObjectDeleteMixin, RESTObject*

Parameters

- **manager** (*RESTManager*) –
- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

manager: *RESTManager*

```
class gitlab.v4.objects.UserImpersonationTokenManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *NoUpdateMixin, RESTManager*

Object listing filters

- state

Object Creation

Required attributes for object create:

- name
- scopes

Optional attributes for object create:

- expires_at

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → UserImpersonationToken`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`UserImpersonationToken`

`gitlab: Gitlab`

`class gitlab.v4.objects.UserKey(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `ObjectDeleteMixin, RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

`class gitlab.v4.objects.UserKeyManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: `RetrieveMixin, CreateMixin, DeleteMixin, RESTManager`

Object Creation

Required attributes for object create:

- title
- key

Object update

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

get(*id*: `Union[str, int]`, *lazy*: `bool = False`, `**kwargs`: `Any`) → `UserKey`

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`UserKey`

gitlab: `Gitlab`

class `gitlab.v4.objects.UserManager`(*gl*: `Gitlab`, *parent*: `Optional[RESTObject] = None`)

Bases: `CRUDMixin, RESTManager`

Object listing filters

- `active`
- `blocked`
- `username`
- `extern_uid`
- `provider`
- `external`
- `search`
- `custom_attributes`
- `status`
- `two_factor`

Object Creation

Optional attributes for object create:

- `email`
- `username`
- `name`

- password
- reset_password
- skype
- linkedin
- twitter
- projects_limit
- extern_uid
- provider
- bio
- admin
- can_create_group
- website_url
- skip_confirmation
- external
- organization
- location
- avatar
- public_email
- private_profile
- color_scheme_id
- theme_id

Object update

Required attributes for object update:

- email
- username
- name

Optional attributes for object update:

- password
- skype
- linkedin
- twitter
- projects_limit
- extern_uid
- provider
- bio
- admin

- `can_create_group`
- `website_url`
- `skip_reconfirmation`
- `external`
- `organization`
- `location`
- `avatar`
- `public_email`
- `private_profile`
- `color_scheme_id`
- `theme_id`

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → User`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

User

`gitlab: Gitlab`

`class gitlab.v4.objects.UserMembership(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

manager: `RESTManager`

class `gitlab.v4.objects.UserMembershipManager`(`gl: Gitlab`, `parent: Optional[RESTObject] = None`)

Bases: `RetrieveMixin, RESTManager`

Object listing filters

- `type`

Object Creation

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

get(`id: Union[str, int]`, `lazy: bool = False`, `**kwargs: Any`) → `UserMembership`

Retrieve a single object.

Parameters

- `id (Union[str, int])` – ID of the object to retrieve
- `lazy (bool)` – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- `**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

Return type

`UserMembership`

gitlab: `Gitlab`

class `gitlab.v4.objects.UserPersonalAccessToken`(`manager: RESTManager`, `attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False`)

Bases: `RESTObject`

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

manager: `RESTManager`

class `gitlab.v4.objects.UserPersonalAccessTokenManager`(`gl: Gitlab`, `parent: Optional[RESTObject] = None`)

Bases: *CreateMixin*, *RESTManager*

Object Creation

Required attributes for object create:

- `name`
- `scopes`

Optional attributes for object create:

- `expires_at`

Object update

Parameters

- `gl (Gitlab)` –
- `parent (Optional[RESTObject])` –

`gitlab: Gitlab`

```
class gitlab.v4.objects.UserProject(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- `manager (RESTManager)` –
- `attrs (Dict[str, Any])` –
- `created_from_list (bool)` –
- `lazy (bool)` –

`manager: RESTManager`

```
class gitlab.v4.objects.UserProjectManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *ListMixin*, *CreateMixin*, *RESTManager*

Object listing filters

- `archived`
- `visibility`
- `order_by`
- `sort`
- `search`
- `simple`
- `owned`
- `membership`
- `starred`
- `statistics`
- `with_issues_enabled`
- `with_merge_requests_enabled`

- `with_custom_attributes`
- `with_programming_language`
- `wiki_checksum_failed`
- `repository_checksum_failed`
- `min_access_level`
- `id_after`
- `id_before`

Object Creation

Required attributes for object create:

- `name`

Optional attributes for object create:

- `default_branch`
- `issues_enabled`
- `wall_enabled`
- `merge_requests_enabled`
- `wiki_enabled`
- `snippets_enabled`
- `squash_option`
- `public`
- `visibility`
- `description`
- `builds_enabled`
- `public_builds`
- `import_url`
- `only_allow_merge_if_build_succeeds`

Object update

Parameters

- `gl (Gitlab) –`
- `parent (Optional[RESTObject]) –`

`gitlab: Gitlab`

`list(**kwargs: Any) → Union[RESTObjectList, List[RESTObject]]`

Retrieve a list of objects.

Parameters

- `all` – If True, return all the items, without pagination
- `per_page` – Number of items to retrieve per request
- `page` – ID of the page to return (starts with page 1)

- **iterator** – If set to True and no pagination option is defined, return a generator instead of a list
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The list of objects, or a generator if *iterator* is True

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server cannot perform the request

Return type

Union[RESTObjectList, List[RESTObject]]

```
class gitlab.v4.objects.UserStatus(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: *RESTObject*

Parameters

- **manager (RESTManager)** –
- **attrs (Dict[str, Any])** –
- **created_from_list (bool)** –
- **lazy (bool)** –

manager: *RESTManager*

```
class gitlab.v4.objects.UserStatusManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: *GetWithoutIdMixin, RESTManager*

Object Creation**Object update****Parameters**

- **gl (Gitlab)** –
- **parent (Optional[RESTObject])** –

get(kwargs: Any) → UserStatus**

Retrieve a single object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

UserStatus

gitlab: *Gitlab*

```
class gitlab.v4.objects.Variable(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)
```

Bases: `SaveMixin`, `ObjectDeleteMixin`, `RESTObject`

Parameters

- **manager** (`RESTManager`) –
- **attrs** (`Dict[str, Any]`) –
- **created_from_list** (`bool`) –
- **lazy** (`bool`) –

manager: `RESTManager`

```
class gitlab.v4.objects.VariableManager(gl: Gitlab, parent: Optional[RESTObject] = None)
```

Bases: `CRUDMixin`, `RESTManager`

Object Creation

Required attributes for object create:

- `key`
- `value`

Optional attributes for object create:

- `protected`
- `variable_type`
- `masked`

Object update

Required attributes for object update:

- `key`
- `value`

Optional attributes for object update:

- `protected`
- `variable_type`
- `masked`

Parameters

- **gl** (`Gitlab`) –
- **parent** (`Optional[RESTObject]`) –

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → Variable
```

Retrieve a single object.

Parameters

- **id** (`Union[str, int]`) – ID of the object to retrieve
- **lazy** (`bool`) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Variable

`gitlab: Gitlab`

Module contents

6.6.3 Submodules

6.6.4 gitlab.base module

`class gitlab.base.RESTManager(gl: Gitlab, parent: Optional[RESTObject] = None)`

Bases: object

Base class for CRUD operations on objects.

Derived class must define `_path` and `_obj_cls`.

`_path`: Base URL path on which requests will be sent (e.g. '/projects') `_obj_cls`: The class of objects that will be created

Parameters

- **gl** (*Gitlab*) –
- **parent** (*Optional[RESTObject]*) –

`gitlab: Gitlab`

`property parent_attrs: Optional[Dict[str, Any]]`

`property path: Optional[str]`

`class gitlab.base.RESTObject(manager: RESTManager, attrs: Dict[str, Any], *, created_from_list: bool = False, lazy: bool = False)`

Bases: object

Represents an object built from server data.

It holds the attributes known from the server, and the updated attributes in another. This allows smart updates, if the object allows it.

You can redefine `_id_attr` in child classes to specify which attribute must be used as the unique ID. `None` means that the object can be updated without ID in the url.

Likewise, you can define a `_repr_attr` in subclasses to specify which attribute should be added as a human-readable identifier when called in the object's `__repr__()` method.

Parameters

- **manager** (*RESTManager*) –

- **attrs** (*Dict[str, Any]*) –
- **created_from_list** (*bool*) –
- **lazy** (*bool*) –

asdict(*, *with_parent_attrs: bool = False*) → *Dict[str, Any]*

Parameters

- with_parent_attrs** (*bool*) –

Return type

Dict[str, Any]

property attributes: Dict[str, Any]

property encoded_id: Optional[Union[int, str]]

Ensure that the ID is url-encoded so that it can be safely used in a URL path

get_id() → *Optional[Union[int, str]]*

Returns the id of the resource.

Return type

Optional[Union[int, str]]

manager: [RESTManager](#)

pformat() → *str*

Return type

str

pprint() → *None*

Return type

None

to_json(*, *with_parent_attrs: bool = False*, ***kwargs: Any*) → *str*

Parameters

- **with_parent_attrs** (*bool*) –
- **kwargs** (*Any*) –

Return type

str

class gitlab.base.RESTObjectList(*manager: RESTManager*, *obj_cls: Type[RESTObject]*, *_list: GitlabList*)

Bases: *object*

Generator object representing a list of RESTObject's.

This generator uses the Gitlab pagination system to fetch new data when required.

Note: you should not instantiate such objects, they are returned by calls to RESTManager.list()

Parameters

- **manager** ([RESTManager](#)) – Manager to attach to the created objects
- **obj_cls** (*Type[RESTObject]*) – Type of objects to create from the json data
- **_list** ([GitlabList](#)) – A GitlabList object

```
property current_page: int
    The current page number.

next() → RESTObject

    Return type
        RESTObject

property next_page: Optional[int]
    The next page number.

    If None, the current page is the last.

property per_page: Optional[int]
    The number of items per page.

property prev_page: Optional[int]
    The previous page number.

    If None, the current page is the first.

property total: Optional[int]
    The total number of items.

property total_pages: Optional[int]
    The total number of pages.
```

6.6.5 gitlab.cli module

```
class gitlab.cli.VerticalHelpFormatter(prog, indent_increment=2, max_help_position=24, width=None)
    Bases: HelpFormatter

    format_help() → str

        Return type
            str

gitlab.cli.cls_to_gitlab_resource(cls: RESTObject) → str

    Parameters
        cls (RESTObject) –

    Return type
        str

gitlab.cli.die(msg: str, e: Optional[Exception] = None) → None

    Parameters
        • msg (str) –
        • e (Optional[Exception]) –

    Return type
        None

gitlab.cli.docs() → ArgumentParser

    Provide a statically generated parser for sphinx only, so we don't need to provide dummy gitlab config for readthe-
    docs.
```

Return type

ArgumentParser

`gitlab.cli.gitlab_resource_to_cls(gitlab_resource: str, namespace: module) → Type[RESTObject]`

Parameters

- **gitlab_resource** (*str*) –
- **namespace** (*module*) –

Return type

Type[RESTObject]

`gitlab.cli.main() → None`

Return type

None

`gitlab.cli.register_custom_action(cls_names: Union[str, Tuple[str, ...]], mandatory: Tuple[str, ...] = (), optional: Tuple[str, ...] = (), custom_action: Optional[str] = None) → Callable[[__F], __F]`

Parameters

- **cls_names** (*Union[str, Tuple[str, ...]]*) –
- **mandatory** (*Tuple[str, ...]*) –
- **optional** (*Tuple[str, ...]*) –
- **custom_action** (*Optional[str]*) –

Return type

Callable[[__F], __F]

6.6.6 gitlab.config module

`exception gitlab.config.ConfigError`

Bases: *Exception*

`exception gitlab.config.GitlabConfigHelperError`

Bases: *ConfigError*

`exception gitlab.config.GitlabConfigMissingError`

Bases: *ConfigError*

`class gitlab.config.GitlabConfigParser(gitlab_id: Optional[str] = None, config_files: Optional[List[str]] = None)`

Bases: *object*

Parameters

- **gitlab_id** (*Optional[str]*) –
- **config_files** (*Optional[List[str]]*) –

`exception gitlab.config.GitlabDataError`

Bases: *ConfigError*

`exception gitlab.config.GitlabIDError`

Bases: *ConfigError*

6.6.7 gitlab.const module

```
class gitlab.const.AccessLevel(value)
    Bases: IntEnum

    An enumeration.

    ADMIN: int = 60
    DEVELOPER: int = 30
    GUEST: int = 10
    MAINTAINER: int = 40
    MINIMAL_ACCESS: int = 5
    NO_ACCESS: int = 0
    OWNER: int = 50
    REPORTER: int = 20

class gitlab.const.NotificationLevel(value)
    Bases: GitlabEnum

    An enumeration.

    CUSTOM: str = 'custom'
    DISABLED: str = 'disabled'
    GLOBAL: str = 'global'
    MENTION: str = 'mention'
    PARTICIPATING: str = 'participating'
    WATCH: str = 'watch'

class gitlab.const.SearchScope(value)
    Bases: GitlabEnum

    An enumeration.

    BLOBS: str = 'blobs'
    COMMITS: str = 'commits'
    GLOBAL_SNIPPET_TITLES: str = 'snippet_titles'
    ISSUES: str = 'issues'
    MERGE_REQUESTS: str = 'merge_requests'
    MILESTONES: str = 'milestones'
    PROJECTS: str = 'projects'
    PROJECT_NOTES: str = 'notes'
```

```
USERS: str = 'users'

WIKI_BLOBS: str = 'wiki_blobs'

class gitlab.const.Visibility(value)

Bases: GitlabEnum

An enumeration.

INTERNAL: str = 'internal'

PRIVATE: str = 'private'

PUBLIC: str = 'public'
```

6.6.8 gitlab.exceptions module

```
exception gitlab.exceptions.GitlabActivateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabAttachFileError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabAuthenticationError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBanError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBlockError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBuildCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabCancelError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBuildEraseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBuildPlayError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabBuildRetryError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabCancelError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes]  
                                              = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabCherryPickError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabCiLintError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabConnectionError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabCreateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabDeactivateError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabDeleteError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabDeploymentApprovalError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [Exception](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabFollowError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabGetError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabGroupTransferError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabHeadError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabHousekeepingError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabHttpError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabImportError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabInvitationError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabJobCancelError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabCancelError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabJobEraseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabJobPlayError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabJobRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabLicenseError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabListError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabMRApiApprovalError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabMRClosedError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabMRForbiddenError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabMROnBuildSuccessError(error_message: Union[str, bytes] = "",  
                                                       response_code: Optional[int] = None,  
                                                       response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabMRRebaseError(error_message: Union[str, bytes] = "", response_code:  
                                               Optional[int] = None, response_body:  
                                               Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabMRResetApprovalError(error_message: Union[str, bytes] = "",  
                                                       response_code: Optional[int] = None,  
                                                       response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabMarkdownError(error_message: Union[str, bytes] = "", response_code:  
                                               Optional[int] = None, response_body:  
                                               Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabOperationError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: [GitlabError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabOwnershipError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabParsingError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes]  
                                              = None)
```

Bases: [GitlabError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabPipelineCancelError(error_message: Union[str, bytes] = "",  
                                                       response_code: Optional[int] = None,  
                                                       response_body: Optional[bytes] = None)
```

Bases: [GitlabCancelError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabPipelinePlayError(error_message: Union[str, bytes] = "",  
                                                 response_code: Optional[int] = None,  
                                                 response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabPipelineRetryError(error_message: Union[str, bytes] = "",  
                                                 response_code: Optional[int] = None,  
                                                 response_body: Optional[bytes] = None)
```

Bases: *GitlabRetryError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabProjectDeployKeyError(error_message: Union[str, bytes] = "",  
                                                 response_code: Optional[int] = None,  
                                                 response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabPromoteError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes]  
                                              = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabProtectError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabRenderError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabRepairError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabRestoreError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (`Union[str, bytes]`) –
- **response_code** (`Optional[int]`) –
- **response_body** (`Optional[bytes]`) –

Return type

None

```
exception gitlab.exceptions.GitlabRetryError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabRevertError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabSearchError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabSetError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabStopError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabSubscribeError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabTimeTrackingError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabTodoError(error_message: Union[str, bytes] = "", response_code: Optional[int] = None, response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError*

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabTransferProjectError(error_message: Union[str, bytes] = "",  
                                                     response_code: Optional[int] = None,  
                                                     response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUnbanError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes] =  
                                              None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUnblockError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes] =  
                                              None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUnfollowError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body:  
                                              Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUnsubscribeError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUpdateError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes]  
                                              = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUploadError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes]  
                                              = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUserApproveError(error_message: Union[str, bytes] = "",  
                                                 response_code: Optional[int] = None,  
                                                 response_body: Optional[bytes] = None)
```

Bases: [GitlabOperationError](#)

Parameters

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabUserRejectError(error_message: Union[str, bytes] = "",  
                                                response_code: Optional[int] = None,  
                                                response_body: Optional[bytes] = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.GitlabVerifyError(error_message: Union[str, bytes] = "", response_code:  
                                              Optional[int] = None, response_body: Optional[bytes]  
                                              = None)
```

Bases: *GitlabOperationError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

```
exception gitlab.exceptions.RedirectError(error_message: Union[str, bytes] = "", response_code:  
                                         Optional[int] = None, response_body: Optional[bytes] =  
                                         None)
```

Bases: *GitlabError***Parameters**

- **error_message** (*Union[str, bytes]*) –
- **response_code** (*Optional[int]*) –
- **response_body** (*Optional[bytes]*) –

Return type

None

6.6.9 `gitlab.mixins` module

```
class gitlab.mixins.AccessRequestMixin
```

Bases: *object*

```
approve(access_level: int = 30, **kwargs: Any) → None
```

Approve an access request.

Parameters

- **access_level** (*int*) – The access level for the user

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server fails to perform the request

Return type

None

manager: [RESTManager](#)

class gitlab.mixins.BadgeRenderMixin

Bases: `object`

render(link_url: str, image_url: str, **kwargs: Any) → Dict[str, Any]

Preview link_url and image_url after interpolation.

Parameters

- **link_url (str)** – URL of the badge link
- **image_url (str)** – URL of the badge image
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabRenderError** – If the rendering failed

Returns

The rendering properties

Return type

`Dict[str, Any]`

class gitlab.mixins.CRUDMixin

Bases: `GetMixin, ListMixin, CreateMixin, UpdateMixin, DeleteMixin`

gitlab: [Gitlab](#)

class gitlab.mixins.CreateMixin

Bases: `object`

create(data: Optional[Dict[str, Any]] = None, **kwargs: Any) → RESTObject

Create a new object.

Parameters

- **data (Optional[Dict[str, Any]])** – parameters to send to the server to create the resource
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

A new instance of the managed object class built with
the data sent by the server

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabCreateError** – If the server cannot perform the request

Return type

`RESTObject`

`gitlab: Gitlab`

`class gitlab.mixins.DeleteMixin`

Bases: `object`

`delete(id: Optional[Union[int, str]] = None, **kwargs: Any) → None`

Delete an object on the server.

Parameters

- **id** (`Optional[Union[int, str]]`) – ID of the object to delete
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

`None`

`gitlab: Gitlab`

`class gitlab.mixins.DownloadMixin`

Bases: `object`

`download(streamed: bool = False, action: Optional[Callable[[bytes], None]] = None, chunk_size: int = 1024, *, iterator: bool = False, **kwargs: Any) → Optional[Union[bytes, Iterator[Any]]]`

Download the archive of a resource export.

Parameters

- **streamed** (`bool`) – If True the data will be processed by chunks of `chunk_size` and each chunk is passed to `action` for treatment
- **iterator** (`bool`) – If True directly return the underlying response iterator
- **action** (`Optional[Callable[[bytes], None]]`) – Callable responsible of dealing with chunk of data
- **chunk_size** (`int`) – Size of each chunk
- ****kwargs** (`Any`) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server failed to perform the request

Returns

The blob content if `streamed` is False, `None` otherwise

Return type

`Optional[Union[bytes, Iterator[Any]]]`

`manager: RESTManager`

```
class gitlab.mixins.GetMixin
```

Bases: HeadMixin, object

```
get(id: Union[str, int], lazy: bool = False, **kwargs: Any) → RESTObject
```

Retrieve a single object.

Parameters

- **id** (*Union[str, int]*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject.

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

RESTObject

gitlab: *Gitlab*

```
class gitlab.mixins.GetWithoutIdMixin
```

Bases: HeadMixin, object

```
get(**kwargs: Any) → RESTObject
```

Retrieve a single object.

Parameters

- ****kwargs** (*Any*) – Extra options to send to the server (e.g. sudo)

Returns

The generated RESTObject

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

RESTObject

gitlab: *Gitlab*

```
class gitlab.mixins.ListMixin
```

Bases: HeadMixin, object

gitlab: *Gitlab*

```
list(**kwargs: Any) → Union[RESTObjectList, List[RESTObject]]
```

Retrieve a list of objects.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request

- **page** – ID of the page to return (starts with page 1)
- **iterator** – If set to True and no pagination option is defined, return a generator instead of a list
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The list of objects, or a generator if *iterator* is True

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the server cannot perform the request

Return type

Union[RESTObjectList, List[RESTObject]]

class gitlab.mixins.NoUpdateMixin

Bases: *GetMixin, ListMixin, CreateMixin, DeleteMixin*

gitlab: *Gitlab*

class gitlab.mixins.ObjectDeleteMixin

Bases: *object*

Mixin for RESTObject's that can be deleted.

delete(kwargs: Any) → None**

Delete the object from the server.

Parameters

- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabDeleteError** – If the server cannot perform the request

Return type

None

manager: *RESTManager*

class gitlab.mixins.ParticipantsMixin

Bases: *object*

manager: *RESTManager*

participants(kwargs: Any) → Dict[str, Any]**

List the participants.

Parameters

- **all** – If True, return all the items, without pagination
- **per_page** – Number of items to retrieve per request
- **page** – ID of the page to return (starts with page 1)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabListError** – If the list could not be retrieved

Returns

The list of participants

Return type

Dict[str, Any]

class gitlab.mixins.RefreshMixin

Bases: *object*

manager: *RESTManager*

refresh(kwargs: Any) → None**

Refresh a single object from server.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Return type

None

Returns *None* (updates the object)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Parameters

kwargs (Any) –

Return type

None

class gitlab.mixins.RetrieveMixin

Bases: *ListMixin, GetMixin*

gitlab: *Gitlab*

class gitlab.mixins.SaveMixin

Bases: *object*

Mixin for RESTObject's that can be updated.

manager: *RESTManager*

save(kwargs: Any) → Optional[Dict[str, Any]]**

Save the changes made to the object to the server.

The object is updated to match what the server returns.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The new object data (*not* a RESTObject)

Raises

- **GitlabAuthenticationError** – If authentication is not correct

- **GitlabUpdateError** – If the server cannot perform the request

Return type

Optional[Dict[str, Any]]

class `gitlab.mixins.SetMixin`

Bases: `object`

gitlab: `Gitlab`

set(*key*: str, *value*: str, ***kwargs*: Any) → RESTObject

Create or update the object.

Parameters

- **key** (str) – The key of the object to create/update
- **value** (str) – The value to set for the object
- ****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSetError** – If an error occurred

Returns

The created/updated attribute

Return type

`RESTObject`

class `gitlab.mixins.SubscribableMixin`

Bases: `object`

manager: `RESTManager`

subscribe(***kwargs*: Any) → None

Subscribe to the object notifications.

Parameters

****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabSubscribeError** – If the subscription cannot be done

Return type

`None`

unsubscribe(***kwargs*: Any) → None

Unsubscribe from the object notifications.

Parameters

****kwargs** (Any) – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUnsubscribeError** – If the unsubscription cannot be done

Return type

None

`class gitlab.mixins.TimeTrackingMixin`

Bases: `object`

`add_spent_time(duration: str, **kwargs: Any) → Dict[str, Any]`

Add time spent working on the object.

Parameters

- **duration (str)** – Duration in human format (e.g. 3h30)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTimeTrackingError** – If the time tracking update cannot be done

Return type

`Dict[str, Any]`

`manager: RESTManager`

`reset_spent_time(**kwargs: Any) → Dict[str, Any]`

Resets the time spent working on the object.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTimeTrackingError** – If the time tracking update cannot be done

Return type

`Dict[str, Any]`

`reset_time_estimate(**kwargs: Any) → Dict[str, Any]`

Resets estimated time for the object to 0 seconds.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTimeTrackingError** – If the time tracking update cannot be done

Return type

`Dict[str, Any]`

`time_estimate(duration: str, **kwargs: Any) → Dict[str, Any]`

Set an estimated time of work for the object.

Parameters

- **duration (str)** – Duration in human format (e.g. 3h30)
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTimeTrackingError** – If the time tracking update cannot be done

Return type

Dict[str, Any]

time_stats(kwargs: Any) → Dict[str, Any]**

Get time stats for the object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTimeTrackingError** – If the time tracking update cannot be done

Return type

Dict[str, Any]

class gitlab.mixins.TodoMixin

Bases: `object`

manager: RESTManager

todo(kwargs: Any) → None**

Create a todo associated to the object.

Parameters

****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabTodoError** – If the todo cannot be set

Return type

`None`

class gitlab.mixins.UpdateMixin

Bases: `object`

gitlab: Gitlab

update(id: Optional[Union[int, str]] = None, new_data: Optional[Dict[str, Any]] = None, **kwargs: Any) → Dict[str, Any]

Update an object on the server.

Parameters

- **id (Optional[Union[int, str]])** – ID of the object to update (can be `None` if not required)
- **new_data (Optional[Dict[str, Any]])** – the update data for the object
- ****kwargs (Any)** – Extra options to send to the server (e.g. sudo)

Returns

The new object data (*not* a RESTObject)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabUpdateError** – If the server cannot perform the request

Return type

Dict[str, Any]

`class gitlab.mixins.UserAgentDetailMixin`

Bases: `object`

`manager: RESTManager`

`user_agent_detail(**kwargs: Any) → Dict[str, Any]`

Get the user agent detail.

Parameters

`**kwargs (Any)` – Extra options to send to the server (e.g. sudo)

Raises

- **GitlabAuthenticationError** – If authentication is not correct
- **GitlabGetError** – If the server cannot perform the request

Return type

Dict[str, Any]

6.6.10 `gitlab.utils` module

`class gitlab.utils.EncodedId(value: Union[str, int, EncodedId])`

Bases: `str`

A custom `str` class that will return the URL-encoded value of the string.

- Using it recursively will only url-encode the value once.
- Can accept either `str` or `int` as input value.
- Can be used in an f-string and output the URL-encoded string.

Reference to documentation on why this is necessary.

See:

<https://docs.gitlab.com/ee/api/index.html#namespaced-path-encoding>
<https://docs.gitlab.com/ee/api/index.html#path-parameters>

Parameters

`value(Union[str, int, EncodedId])` –

Return type

`EncodedId`

`gitlab.utils.copy_dict(*, src: Dict[str, Any], dest: Dict[str, Any]) → None`

Parameters

- `src (Dict[str, Any])` –
- `dest (Dict[str, Any])` –

Return type

None

`gitlab.utils.remove_none_from_dict(data: Dict[str, Any]) → Dict[str, Any]`**Parameters**`data (Dict[str, Any]) –`**Return type**`Dict[str, Any]``gitlab.utils.response_content(response: Response, streamed: bool, action: Optional[Callable[[bytes], None]], chunk_size: int, *, iterator: bool) → Optional[Union[bytes, Iterator[Any]]]`**Parameters**

- `response (Response)` –
- `streamed (bool)` –
- `action (Optional[Callable[[bytes], None]])` –
- `chunk_size (int)` –
- `iterator (bool)` –

Return type`Optional[Union[bytes, Iterator[Any]]]``gitlab.utils.warn(message: str, *, category: Optional[Type[Warning]] = None, source: Optional[Any] = None) → None`

This `warnings.warn` wrapper function attempts to show the location causing the warning in the user code that called the library.

It does this by walking up the stack trace to find the first frame located outside the `gitlab/` directory. This is helpful to users as it shows them their code that is causing the warning.

Parameters

- `message (str)` –
- `category (Optional[Type[Warning]])` –
- `source (Optional[Any])` –

Return type

None

6.7 CLI reference (gitlab command)

Warning: The following is a complete, auto-generated list of subcommands available via the `gitlab` command-line tool. Some of the actions may currently not work as expected or lack functionality available via the API.

Please see the existing [list of CLI related issues](#), or open a new one if it is not already listed there.

6.7.1 gitlab

GitLab API Command Line Interface

```
usage: gitlab [-h] [--version] [-v] [-d] [-c CONFIG_FILE] [-g GITLAB]
              [-o {json,legacy,yaml}] [-f FIELDS] [--server-url SERVER_URL]
              [--ssl-verify SSL_VERIFY] [--timeout TIMEOUT]
              [--api-version API_VERSION] [--per-page PER_PAGE]
              [--pagination PAGINATION] [--order-by ORDER_BY]
              [--user-agent USER_AGENT]
              [--private-token PRIVATE_TOKEN | --oauth-token OAUTH_TOKEN | --job-token_
JOB_TOKEN]
application
application-appearance
application-settings
audit-event
broadcast-message
ci-lint
current-user
current-user-email
current-user-gpg-key
current-user-key
current-user-status
deploy-key
deploy-token
dockerfile
event
feature
generic-package
geo-node
gitignore
gitlabciyml
group
group-access-request
group-access-token
group-audit-event
group-badge
group-billable-member
group-billable-member-membership
group-board
group-board-list
group-cluster
group-custom-attribute
group-deploy-token
group-descendant-group
group-epic
group-epic-award-emoji
group-epic-discussion-note
group-epic-issue
group-epic-note
group-epic-note-award-emoji
group-epic-resource-label-event
group-export
group-hook
group-import
group-invitation
group-issue
```

(continues on next page)

(continued from previous page)

```
group-issues-statistics
group-iteration
group-label
group-member
group-member-all
group-merge-request
group-milestone
group-notification-settings
group-package
group-project
group-push-rules
group-runner
group-subgroup
group-variable
group-wiki
hook
issue
issues-statistics
key
ldap-group
license
merge-request
namespace
notification-settings
pages-domain
personal-access-token
project
project-access-request
project-access-token
project-additional-statistics
project-approval
project-approval-rule
project-artifact
project-audit-event
project-badge
project-board
project-board-list
project-branch
project-ci-lint
project-cluster
project-commit
project-commit-comment
project-commit-discussion
project-commit-discussion-note
project-commit-status
project-custom-attribute
project-deploy-token
project-deployment
project-deployment-merge-request
project-environment
project-event
project-export
```

(continues on next page)

(continued from previous page)

```
project-file
project-fork
project-hook
project-import
project-integration
project-invitation
project-issue
project-issue-award-emoji
project-issue-discussion
project-issue-discussion-note
project-issue-link
project-issue-note
project-issue-note-award-emoji
project-issue-resource-label-event
project-issue-resource-milestone-event
project-issue-resource-state-event
project-issues-statistics
project-job
project-key
project-label
project-member
project-member-all
project-merge-request
project-merge-request-approval
project-merge-request-approval-rule
project-merge-request-approval-state
project-merge-request-award-emoji
project-merge-request-diff
project-merge-request-discussion
project-merge-request-discussion-note
project-merge-request-note
project-merge-request-note-award-emoji
project-merge-request-pipeline
project-merge-request-resource-label-event
project-merge-request-resource-milestone-event
project-merge-request-resource-state-event
project-merge-train
project-milestone
project-note
project-notification-settings
project-package
project-package-file
project-pages-domain
project-pipeline
project-pipeline-bridge
project-pipeline-job
project-pipeline-schedule
project-pipeline-schedule-variable
project-pipeline-test-report
project-pipeline-test-report-summary
project-pipeline-variable
project-protected-branch
```

(continues on next page)

(continued from previous page)

```
project-protected-environment
project-protected-tag
project-push-rules
project-registry-repository
project-registry-tag
project-release
project-release-link
project-remote-mirror
project-runner
project-service
project-snippet
project-snippet-award-emoji
project-snippet-discussion
project-snippet-discussion-note
project-snippet-note
project-snippet-note-award-emoji
project-storage
project-tag
project-trigger
project-user
project-variable
project-wiki
registry-repository
runner
runner-all
runner-job
shared-project
snippet
starred-project
todo
topic
user
user-activities
user-custom-attribute
user-email
user-event
user-gpg-key
user-impersonation-token
user-key
user-membership
user-personal-access-token
user-project
user-status
variable
...
...
```

-h, --help

show this help message and exit

--version

Display the version.

-v, --verbose, --fancy

Verbose mode (legacy format only) [env var: GITLAB_VERBOSE]
-d, --debug
 Debug mode (display HTTP requests) [env var: GITLAB_DEBUG]
-c <config_file>, --config-file <config_file>
 Configuration file to use. Can be used multiple times. [env var: PYTHON_GITLAB_CFG]
-g <gitlab>, --gitlab <gitlab>
 Which configuration section should be used. If not defined, the default selection will be used.
-o {json,legacy,yaml}, --output {json,legacy,yaml}
 Output format (v4 only): json|legacy|yaml
-f <fields>, --fields <fields>
 Fields to display in the output (comma separated). Not used with legacy output
--server-url <server_url>
 GitLab server URL [env var: GITLAB_URL]
--ssl-verify <ssl_verify>
 Whether SSL certificates should be validated. [env var: GITLAB_SSL_VERIFY]
--timeout <timeout>
 Timeout to use for requests to the GitLab server. [env var: GITLAB_TIMEOUT]
--api-version <api_version>
 GitLab API version [env var: GITLAB_API_VERSION]
--per-page <per_page>
 Number of entries to return per page in the response. [env var: GITLAB_PER_PAGE]
--pagination <pagination>
 Whether to use keyset or offset pagination [env var: GITLAB_PAGINATION]
--order-by <order_by>
 Set order_by globally [env var: GITLAB_ORDER_BY]
--user-agent <user_agent>
 The user agent to send to GitLab with the HTTP request. [env var: GITLAB_USER_AGENT]
--private-token <private_token>
 GitLab private access token [env var: GITLAB_PRIVATE_TOKEN]
--oauth-token <oauth_token>
 GitLab OAuth token [env var: GITLAB_OAUTH_TOKEN]
--job-token <job_token>
 GitLab CI job token [env var: CI_JOB_TOKEN]

gitlab application

```
usage: gitlab application [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab application create

```
usage: gitlab application create [-h] [--sudo SUDO] --name NAME --redirect-uri  
                                REDIRECT_URI --scopes SCOPES  
                                [--confidential CONFIDENTIAL]
```

-h, --help

show this help message and exit

--sudo <sudo>

--name <name>

--redirect-uri <redirect_uri>

--scopes <scopes>

--confidential <confidential>

gitlab application delete

```
usage: gitlab application delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab application list

```
usage: gitlab application list [-h] [--sudo SUDO] [--page PAGE]  
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab application-appearance

```
usage: gitlab application-appearance [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab application-appearance get

```
usage: gitlab application-appearance get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab application-appearance update

```
usage: gitlab application-appearance update [-h] [--sudo SUDO] [--title TITLE]
                                             [--description DESCRIPTION]
                                             [--logo LOGO]
                                             [--header-logo HEADER_LOGO]
                                             [--favicon FAVICON]
                                             [--new-project-guidelines NEW_PROJECT_
                                             ↵GUIDELINES]
                                             [--header-message HEADER_MESSAGE]
                                             [--footer-message FOOTER_MESSAGE]
                                             [--message-background-color MESSAGE_
                                             ↵BACKGROUND_COLOR]
                                             [--message-font-color MESSAGE_FONT_COLOR]
                                             [--email-header-and-footer-enabled EMAIL_
                                             ↵HEADER_AND_FOOTER_ENABLED]
```

-h, --help

show this help message and exit

--sudo <sudo>

--title <title>

--description <description>

--logo <logo>

--header-logo <header_logo>

```
--favicon <favicon>
--new-project-guidelines <new_project_guidelines>
--header-message <header_message>
--footer-message <footer_message>
--message-background-color <message_background_color>
--message-font-color <message_font_color>
--email-header-and-footer-enabled <email_header_and_footer_enabled>
```

gitlab application-settings

```
usage: gitlab application-settings [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab application-settings get

```
usage: gitlab application-settings get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab application-settings update

```
usage: gitlab application-settings update [-h] [--sudo SUDO] [--id ID]
                                         [--default-projects-limit DEFAULT_PROJECTS_
                                         ↵LIMIT]
                                         [--signup-enabled SIGNUP_ENABLED]
                                         [--password-authentication-enabled-for-web_
                                         ↵PASSWORD_AUTHENTICATION_ENABLED_FOR_WEB]
                                         [--gravatar-enabled GRAVATAR_ENABLED]
                                         [--sign-in-text SIGN_IN_TEXT]
                                         [--created-at CREATED_AT]
                                         [--updated-at UPDATED_AT]
                                         [--home-page-url HOME_PAGE_URL]
                                         [--default-branch-protection DEFAULT_BRANCH_
                                         ↵PROTECTION]
                                         [--restricted-visibility-levels RESTRICTED_
                                         ↵VISIBILITY_LEVELS]
                                         [--max-attachment-size MAX_ATTACHMENT_SIZE]
                                         [--session-expire-delay SESSION_EXPIRE_DELAY]
                                         [--default-project-visibility DEFAULT_PROJECT_
                                         ↵VISIBILITY]
```

(continues on next page)

(continued from previous page)

↳ VVISIBILITY]	[--default-snippet-visibility DEFAULT_SNIPPET_
↳ VVISIBILITY]	[--default-group-visibility DEFAULT_GROUP_
↳ LOCAL_REQUESTS_WHITELIST]	[--outbound-local-requests-whitelist OUTBOUND_
↳ OAUTH_SIGN_IN_SOURCES]	[--disabled-oauth-sign-in-sources DISABLED_
↳ VENABLED]	[--domain-whitelist DOMAIN_WHITELIST] [--domain-blacklist-enabled DOMAIN_BLACKLIST_
↳ VENABLED]	[--domain-blacklist DOMAIN_BLACKLIST] [--domain-allowlist DOMAIN_ALLOWLIST] [--domain-denylist-enabled DOMAIN_DENYLIST_
↳ VEXTERNAL_AUTHORIZATION_SERVICE_ENABLED]	[--domain-denylist DOMAIN_DENYLIST] [--external-authorization-service-enabled_
↳ VAUTHORIZATION_SERVICE_URL]	[--external-authorization-service-url EXTERNAL_
↳ Vlabel EXTERNAL_AUTHORIZATION_SERVICE_DEFAULT_LABEL]	[--external-authorization-service-default-
↳ VEXTERNAL_AUTHORIZATION_SERVICE_TIMEOUT]	[--external-authorization-service-timeout_
↳ VAPPLICATIONS]	[--import-sources IMPORT_SOURCES] [--user-oauth-applications USER_OAUTH_
↳ VCONTAINER_REGISTRY_TOKEN_EXPIRE_DELAY]	[--after-sign-out-path AFTER_SIGN_OUT_PATH] [--container-registry-token-expire-delay_
↳ VSESSION_TIME]	[--repository-storages REPOSITORY_STORAGES] [--plantuml-enabled PLANTUML_ENABLED] [--plantuml-url PLANTUML_URL] [--terminal-max-session-time TERMINAL_MAX_
↳ VINTERVAL_MULTIPLIER]	[--polling-interval-multiplier POLLING_
↳ VRESTRICTION]	[--rsa-key-restriction RSA_KEY_RESTRICTION] [--dsa-key-restriction DSA_KEY_RESTRICTION] [--ecdsa-key-restriction ECDSA_KEY_RESTRICTION] [--ed25519-key-restriction ED25519_KEY_
↳ VPERFORMANCE_BAR_ALLOWED_GROUP_ID]	[--first-day-of-week FIRST_DAY_OF_WEEK] [--enforce-terms ENFORCE_TERMS] [--terms TERMS] [--performance-bar-allowed-group-id_
↳ VINSTANCE_STATISTICS_VISIBILITY_PRIVATE]	[--instance-statistics-visibility-private_
↳ VSSH_KEY_MESSAGE]	[--user-show-add-ssh-key-message USER_SHOW_ADD_
	[--file-template-project-id FILE_TEMPLATE_

(continues on next page)

(continued from previous page)

```

→PROJECT_ID]
[--local-markdown-version LOCAL_MARKDOWN_]

→VERSION]
[--asset-proxy-enabled ASSET_PROXY_ENABLED]
[--asset-proxy-url ASSET_PROXY_URL]
[--asset-proxy-whitelist ASSET_PROXY_WHITELIST]
[--asset-proxy-allowlist ASSET_PROXY_ALLOWLIST]
[--geo-node-allowed-ips GEO_NODE_ALLOWED_IPS]
[--allow-local-requests-from-hooks-and-
→services ALLOW_LOCAL_REQUESTS_FROM_HOOKS_AND_SERVICES]
[--allow-local-requests-from-web-hooks-and-
→services ALLOW_LOCAL_REQUESTS_FROM_WEB_HOOKS_AND_SERVICES]
[--allow-local-requests-from-system-hooks_
→ALLOW_LOCAL_REQUESTS_FROM_SYSTEM_HOOKS]

```

-h, --help

show this help message and exit

--sudo <sudo>**--id <id>****--default-projects-limit <default_projects_limit>****--signup-enabled <signup_enabled>****--password-authentication-enabled-for-web <password_authentication_enabled_for_web>****--gravatar-enabled <gravatar_enabled>****--sign-in-text <sign_in_text>****--created-at <created_at>****--updated-at <updated_at>****--home-page-url <home_page_url>****--default-branch-protection <default_branch_protection>****--restricted-visibility-levels <restricted_visibility_levels>****--max-attachment-size <max_attachment_size>****--session-expire-delay <session_expire_delay>****--default-project-visibility <default_project_visibility>****--default-snippet-visibility <default_snippet_visibility>****--default-group-visibility <default_group_visibility>****--outbound-local-requests-whitelist <outbound_local_requests_whitelist>****--disabled-oauth-sign-in-sources <disabled_oauth_sign_in_sources>****--domain-whitelist <domain_whitelist>**

```
--domain-blacklist-enabled <domain_blacklist_enabled>
--domain-blacklist <domain_blacklist>
--domain-allowlist <domain_allowlist>
--domain-denylist-enabled <domain_denylist_enabled>
--domain-denylist <domain_denylist>
--external-authorization-service-enabled <external_authorization_service_enabled>
--external-authorization-service-url <external_authorization_service_url>
--external-authorization-service-default-label <external_authorization_service_default_label>
--external-authorization-service-timeout <external_authorization_service_timeout>
--import-sources <import_sources>
--user-oauth-applications <user_oauth_applications>
--after-sign-out-path <after_sign_out_path>
--container-registry-token-expire-delay <container_registry_token_expire_delay>
--repository-storages <repository_storages>
--plantuml-enabled <plantuml_enabled>
--plantuml-url <plantuml_url>
--terminal-max-session-time <terminal_max_session_time>
--polling-interval-multiplier <polling_interval_multiplier>
--rsa-key-restriction <rsa_key_restriction>
--dsa-key-restriction <dsa_key_restriction>
--ecdsa-key-restriction <ecdsa_key_restriction>
--ed25519-key-restriction <ed25519_key_restriction>
--first-day-of-week <first_day_of_week>
--enforce-terms <enforce_terms>
--terms <terms>
--performance-bar-allowed-group-id <performance_bar_allowed_group_id>
--instance-statistics-visibility-private <instance_statistics_visibility_private>
--user-show-add-ssh-key-message <user_show_add_ssh_key_message>
--file-template-project-id <file_template_project_id>
--local-markdown-version <local_markdown_version>
--asset-proxy-enabled <asset_proxy_enabled>
```

```
--asset-proxy-url <asset_proxy_url>
--asset-proxy-whitelist <asset_proxy_whitelist>
--asset-proxy-allowlist <asset_proxy_allowlist>
--geo-node-allowed-ips <geo_node_allowed_ips>
--allow-local-requests-from-hooks-and-services <allow_local_requests_from_hooks_and_services>
--allow-local-requests-from-web-hooks-and-services <allow_local_requests_from_web_hooks_and_services>
--allow-local-requests-from-system-hooks <allow_local_requests_from_system_hooks>
```

gitlab audit-event

```
usage: gitlab audit-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab audit-event get

```
usage: gitlab audit-event get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab audit-event list

```
usage: gitlab audit-event list [-h] [--sudo SUDO]
                               [--created-after CREATED_AFTER]
                               [--created-before CREATED_BEFORE]
                               [--entity-type ENTITY_TYPE]
                               [--entity-id ENTITY_ID] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--created-after <created_after>

--created-before <created_before>

--entity-type <entity_type>

--entity-id <entity_id>

```
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab broadcast-message

```
usage: gitlab broadcast-message [-h] {list,get,create,update,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab broadcast-message create

```
usage: gitlab broadcast-message create [-h] [--sudo SUDO] --message MESSAGE
                                       [--starts-at STARTS_AT]
                                       [--ends-at ENDS_AT] [--color COLOR]
                                       [--font FONT]
                                       [--target-access-levels TARGET_ACCESS_LEVELS]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--message <message>
--starts-at <starts_at>
--ends-at <ends_at>
--color <color>
--font <font>
--target-access-levels <target_access_levels>
```

gitlab broadcast-message delete

```
usage: gitlab broadcast-message delete [-h] [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>
```

gitlab broadcast-message get

```
usage: gitlab broadcast-message get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab broadcast-message list

```
usage: gitlab broadcast-message list [-h] [--sudo SUDO] [--page PAGE]
                                     [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab broadcast-message update

```
usage: gitlab broadcast-message update [-h] [--sudo SUDO] --id ID
                                         [--message MESSAGE]
                                         [--starts-at STARTS_AT]
                                         [--ends-at ENDS_AT] [--color COLOR]
                                         [--font FONT]
                                         [--target-access-levels TARGET_ACCESS_LEVELS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

--message <message>

--starts-at <starts_at>

--ends-at <ends_at>

--color <color>

```
--font <font>
--target-access-levels <target_access_levels>
```

gitlab ci-lint

```
usage: gitlab ci-lint [-h] {create,validate} ...
```

-h, --help

show this help message and exit

gitlab ci-lint create

```
usage: gitlab ci-lint create [-h] [--sudo SUDO] --content CONTENT
                             [--include-merged-yaml INCLUDE_MERGED_YAML]
                             [--include-jobs INCLUDE_JOBS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--content <content>

--include-merged-yaml <include_merged_yaml>

--include-jobs <include_jobs>

gitlab ci-lint validate

```
usage: gitlab ci-lint validate [-h] --content CONTENT
                               [--include-merged-yaml INCLUDE_MERGED_YAML]
                               [--include-jobs INCLUDE_JOBS]
```

-h, --help

show this help message and exit

--content <content>

--include-merged-yaml <include_merged_yaml>

--include-jobs <include_jobs>

gitlab current-user

```
usage: gitlab current-user [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab current-user get

```
usage: gitlab current-user get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>**gitlab current-user-email**

```
usage: gitlab current-user-email [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab current-user-email create

```
usage: gitlab current-user-email create [-h] [--sudo SUDO] --email EMAIL
```

-h, --help

show this help message and exit

--sudo <sudo>**--email <email>****gitlab current-user-email delete**

```
usage: gitlab current-user-email delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--id <id>**

gitlab current-user-email get

```
usage: gitlab current-user-email get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-email list

```
usage: gitlab current-user-email list [-h] [--sudo SUDO] [--page PAGE]
                                      [--per-page PER_PAGE] [--get-all]
                                      [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab current-user-gpg-key

```
usage: gitlab current-user-gpg-key [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab current-user-gpg-key create

```
usage: gitlab current-user-gpg-key create [-h] [--sudo SUDO] --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

gitlab current-user-gpg-key delete

```
usage: gitlab current-user-gpg-key delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-gpg-key get

```
usage: gitlab current-user-gpg-key get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-gpg-key list

```
usage: gitlab current-user-gpg-key list [-h] [--sudo SUDO] [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab current-user-key

```
usage: gitlab current-user-key [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab current-user-key create

```
usage: gitlab current-user-key create [-h] [--sudo SUDO] --title TITLE --key  
KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--title <title>

--key <key>

gitlab current-user-key delete

```
usage: gitlab current-user-key delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-key get

```
usage: gitlab current-user-key get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab current-user-key list

```
usage: gitlab current-user-key list [-h] [--sudo SUDO] [--page PAGE]  
[--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab current-user-status

```
usage: gitlab current-user-status [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab current-user-status get

```
usage: gitlab current-user-status get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>**gitlab current-user-status update**

```
usage: gitlab current-user-status update [-h] [--sudo SUDO] [--emoji EMOJI]
                                         [--message MESSAGE]
```

-h, --help

show this help message and exit

--sudo <sudo>**--emoji <emoji>****--message <message>****gitlab deploy-key**

```
usage: gitlab deploy-key [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab deploy-key list

```
usage: gitlab deploy-key list [-h] [--sudo SUDO] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab deploy-token

```
usage: gitlab deploy-token [-h] {list} ...
```

```
-h, --help
    show this help message and exit
```

gitlab deploy-token list

```
usage: gitlab deploy-token list [-h] [--sudo SUDO] [--page PAGE]
                                [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab dockerfile

```
usage: gitlab dockerfile [-h] {list,get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab dockerfile get

```
usage: gitlab dockerfile get [-h] [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--name <name>

gitlab dockerfile list

```
usage: gitlab dockerfile list [-h] [--sudo SUDO] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab event

```
usage: gitlab event [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab event list

```
usage: gitlab event list [-h] [--sudo SUDO] [--action ACTION]
                           [--target-type TARGET_TYPE] [--before BEFORE]
                           [--after AFTER] [--sort SORT] [--page PAGE]
                           [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--action <action>

```
--target-type <target_type>
--before <before>
--after <after>
--sort <sort>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab feature

```
usage: gitlab feature [-h] {list,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab feature delete

```
usage: gitlab feature delete [-h] [--sudo SUDO] --name NAME
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--name <name>
```

gitlab feature list

```
usage: gitlab feature list [-h] [--sudo SUDO] [--page PAGE]
                           [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab generic-package

```
usage: gitlab generic-package [-h] {upload,download} ...
```

-h, --help

show this help message and exit

gitlab generic-package download

```
usage: gitlab generic-package download [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --package-name
                                       PACKAGE_NAME --package-version
                                       PACKAGE_VERSION --file-name FILE_NAME
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--package-name <package_name>

--package-version <package_version>

--file-name <file_name>

gitlab generic-package upload

```
usage: gitlab generic-package upload [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --package-name PACKAGE_NAME
                                       --package-version PACKAGE_VERSION
                                       --file-name FILE_NAME --path PATH
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--package-name <package_name>

--package-version <package_version>

--file-name <file_name>

--path <path>

gitlab geo-node

```
usage: gitlab geo-node [-h]
  list
  get
  update
  delete
  repair
  status
  current-failures
  ...
```

-h, --help

show this help message and exit

gitlab geo-node current-failures

```
usage: gitlab geo-node current-failures [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab geo-node delete

```
usage: gitlab geo-node delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab geo-node get

```
usage: gitlab geo-node get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab geo-node list

```
usage: gitlab geo-node list [-h] [--sudo SUDO] [--page PAGE]
                            [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab geo-node repair

```
usage: gitlab geo-node repair [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab geo-node status

```
usage: gitlab geo-node status [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab geo-node update

```
usage: gitlab geo-node update [-h] [--sudo SUDO] --id ID [--enabled ENABLED]
                               [--url URL]
                               [--files-max-capacity FILES_MAX_CAPACITY]
                               [--repos-max-capacity REPOS_MAX_CAPACITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

```
--enabled <enabled>
--url <url>
--files-max-capacity <files_max_capacity>
--repos-max-capacity <repos_max_capacity>
```

gitlab gitignore

```
usage: gitlab gitignore [-h] {list,get} ...
```

-h, --help
show this help message and exit

gitlab gitignore get

```
usage: gitlab gitignore get [-h] [--sudo SUDO] --name NAME
```

-h, --help
show this help message and exit
--sudo <sudo>
--name <name>

gitlab gitignore list

```
usage: gitlab gitignore list [-h] [--sudo SUDO] [--page PAGE]
                             [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help
show this help message and exit
--sudo <sudo>
--page <page>
--per-page <per_page>
--get-all
Return all items from the server, without pagination.
--all
Deprecated. Use --get-all instead.

gitlab gitlabciyml

```
usage: gitlab gitlabciyml [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab gitlabciyml get

```
usage: gitlab gitlabciyml get [-h] [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>**--name <name>****gitlab gitlabciyml list**

```
usage: gitlab gitlabciyml list [-h] [--sudo SUDO] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab group

```
usage: gitlab group [-h]
    list
    get
    create
    update
    delete
    transfer-project
    transfer
    search
    add-ldap-group-link
    delete-ldap-group-link
```

(continues on next page)

(continued from previous page)

```
ldap-sync  
share  
unshare  
...
```

-h, --help

show this help message and exit

gitlab group add-ldap-group-link

```
usage: gitlab group add-ldap-group-link [-h] --id ID --cn CN --group-access  
GROUP_ACCESS --provider PROVIDER
```

-h, --help

show this help message and exit

```
--id <id>
```

```
--cn <cn>
```

```
--group-access <group_access>
```

```
--provider <provider>
```

gitlab group create

```
usage: gitlab group create [-h] [--sudo SUDO] --name NAME --path PATH  
[--description DESCRIPTION]  
[--membership-lock MEMBERSHIP_LOCK]  
[--visibility VISIBILITY]  
[--share-with-group-lock SHARE_WITH_GROUP_LOCK]  
[--require-two-factor-authentication REQUIRE_TWO_FACTOR  
→AUTHENTICATION]  
[--two-factor-grace-period TWO_FACTOR_GRACE_PERIOD]  
[--project-creation-level PROJECT_CREATION_LEVEL]  
[--auto-devops-enabled AUTO_DEVOPS_ENABLED]  
[--subgroup-creation-level SUBGROUP_CREATION_LEVEL]  
[--emails-disabled EMAILS_DISABLED]  
[--avatar AVATAR]  
[--mentions-disabled MENTIONS_DISABLED]  
[--lfs-enabled LFS_ENABLED]  
[--request-access-enabled REQUEST_ACCESS_ENABLED]  
[--parent-id PARENT_ID]  
[--default-branch-protection DEFAULT_BRANCH_PROTECTION]  
[--shared-runners-minutes-limit SHARED_RUNNERS_MINUTES_LIMIT]  
[--extra-shared-runners-minutes-limit EXTRA_SHARED_RUNNERS  
→MINUTES_LIMIT]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--name <name>
--path <path>
--description <description>
--membership-lock <membership_lock>
--visibility <visibility>
--share-with-group-lock <share_with_group_lock>
--require-two-factor-authentication <require_two_factor_authentication>
--two-factor-grace-period <two_factor_grace_period>
--project-creation-level <project_creation_level>
--auto-devops-enabled <auto_devops_enabled>
--subgroup-creation-level <subgroup_creation_level>
--emails-disabled <emails_disabled>
--avatar <avatar>
--mentions-disabled <mentions_disabled>
--lfs-enabled <lfs_enabled>
--request-access-enabled <request_access_enabled>
--parent-id <parent_id>
--default-branch-protection <default_branch_protection>
--shared-runners-minutes-limit <shared_runners_minutes_limit>
--extra-shared-runners-minutes-limit <extra_shared_runners_minutes_limit>
```

gitlab group delete

```
usage: gitlab group delete [-h] [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>
```

gitlab group delete-ldap-group-link

```
usage: gitlab group delete-ldap-group-link [-h] --id ID --cn CN  
                                         [--provider PROVIDER]
```

-h, --help

show this help message and exit

--id <id>

--cn <cn>

--provider <provider>

gitlab group get

```
usage: gitlab group get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab group ldap-sync

```
usage: gitlab group ldap-sync [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab group list

```
usage: gitlab group list [-h] [--sudo SUDO] [--skip-groups SKIP_GROUPS]  
                         [--all-available ALL_AVAILABLE] [--search SEARCH]  
                         [--order-by ORDER_BY] [--sort SORT]  
                         [--statistics STATISTICS] [--owned OWNED]  
                         [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]  
                         [--min-access-level MIN_ACCESS_LEVEL]  
                         [--top-level-only TOP_LEVEL_ONLY] [--page PAGE]  
                         [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--skip-groups <skip_groups>

```
--all-available <all_available>
--search <search>
--order-by <order_by>
--sort <sort>
--statistics <statistics>
--owned <owned>
--with-custom-attributes <with_custom_attributes>
--min-access-level <min_access_level>
--top-level-only <top_level_only>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group search

```
usage: gitlab group search [-h] --id ID --scope SCOPE --search SEARCH
```

```
-h, --help
    show this help message and exit
--id <id>
--scope <scope>
--search <search>
```

gitlab group share

```
usage: gitlab group share [-h] --id ID --group-id GROUP_ID --group-access
                           GROUP_ACCESS [--expires-at EXPIRES_AT]
```

```
-h, --help
    show this help message and exit
--id <id>
--group-id <group_id>
--group-access <group_access>
--expires-at <expires_at>
```

gitlab group transfer

```
usage: gitlab group transfer [-h] --id ID [--group-id GROUP_ID]
```

-h, --help

show this help message and exit

--id <id>

--group-id <group_id>

gitlab group transfer-project

```
usage: gitlab group transfer-project [-h] --id ID --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--id <id>

--project-id <project_id>

gitlab group unshare

```
usage: gitlab group unshare [-h] --id ID --group-id GROUP_ID
```

-h, --help

show this help message and exit

--id <id>

--group-id <group_id>

gitlab group update

```
usage: gitlab group update [-h] [--sudo SUDO] --id ID [--name NAME]
                           [--path PATH] [--description DESCRIPTION]
                           [--membership-lock MEMBERSHIP_LOCK]
                           [--share-with-group-lock SHARE_WITH_GROUP_LOCK]
                           [--visibility VISIBILITY]
                           [--require-two-factor-authentication REQUIRE_TWO_FACTOR_
                           ↵AUTHENTICATION]
                           [--two-factor-grace-period TWO_FACTOR_GRACE_PERIOD]
                           [--project-creation-level PROJECT_CREATION_LEVEL]
                           [--auto-devops-enabled AUTO_DEVOPS_ENABLED]
                           [--subgroup-creation-level SUBGROUP_CREATION_LEVEL]
                           [--emails-disabled EMAILS_DISABLED]
                           [--avatar AVATAR]
                           [--mentions-disabled MENTIONS_DISABLED]
                           [--lfs-enabled LFS_ENABLED]
                           [--request-access-enabled REQUEST_ACCESS_ENABLED]
```

(continues on next page)

(continued from previous page)

<pre> [--default-branch-protection DEFAULT_BRANCH_PROTECTION] [--file-template-project-id FILE_TEMPLATE_PROJECT_ID] [--shared-runners-minutes-limit SHARED_RUNNERS_MINUTES_LIMIT] [--extra-shared-runners-minutes-limit EXTRA_SHARED_RUNNERS_ MINUTES_LIMIT] </pre>	<pre> [--prevent-forking-outside-group PREVENT_FORKING_OUTSIDE_ GROUP] </pre>
	<pre> [--shared-runners-setting SHARED_RUNNERS_SETTING] </pre>

-h, --help
show this help message and exit

--sudo <sudo>

--id <id>

--name <name>

--path <path>

--description <description>

--membership-lock <membership_lock>

--share-with-group-lock <share_with_group_lock>

--visibility <visibility>

--require-two-factor-authentication <require_two_factor_authentication>

--two-factor-grace-period <two_factor_grace_period>

--project-creation-level <project_creation_level>

--auto-devops-enabled <auto_devops_enabled>

--subgroup-creation-level <subgroup_creation_level>

--emails-disabled <emails_disabled>

--avatar <avatar>

--mentions-disabled <mentions_disabled>

--lfs-enabled <lfs_enabled>

--request-access-enabled <request_access_enabled>

--default-branch-protection <default_branch_protection>

--file-template-project-id <file_template_project_id>

--shared-runners-minutes-limit <shared_runners_minutes_limit>

--extra-shared-runners-minutes-limit <extra_shared_runners_minutes_limit>

--prevent-forking-outside-group <prevent_forking_outside_group>

--shared-runners-setting <shared_runners_setting>

gitlab group-access-request

```
usage: gitlab group-access-request [-h] {list,create,delete,approve} ...
```

-h, --help

show this help message and exit

gitlab group-access-request approve

```
usage: gitlab group-access-request approve [-h] --group-id GROUP_ID
                                            [--sudo SUDO] --id ID
                                            [--access-level ACCESS_LEVEL]
```

-h, --help

show this help message and exit

--group-id <group_id>

--sudo <sudo>

--id <id>

--access-level <access_level>

gitlab group-access-request create

```
usage: gitlab group-access-request create [-h] [--sudo SUDO] --group-id
                                           GROUP_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-access-request delete

```
usage: gitlab group-access-request delete [-h] [--sudo SUDO] --group-id
                                           GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-access-request list

```
usage: gitlab group-access-request list [-h] [--sudo SUDO] --group-id GROUP_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-access-token

```
usage: gitlab group-access-token [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab group-access-token create

```
usage: gitlab group-access-token create [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --name NAME --scopes SCOPES
                                         [--access-level ACCESS_LEVEL]
                                         [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

--scopes <scopes>

--access-level <access_level>

--expires-at <expires_at>

gitlab group-access-token delete

```
usage: gitlab group-access-token delete [-h] [--sudo SUDO] --group-id GROUP_ID  
                                      --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-access-token list

```
usage: gitlab group-access-token list [-h] [--sudo SUDO] --group-id GROUP_ID  
                                      [--page PAGE] [--per-page PER_PAGE]  
                                      [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-audit-event

```
usage: gitlab group-audit-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab group-audit-event get

```
usage: gitlab group-audit-event get [-h] [--sudo SUDO] --group-id GROUP_ID  
                                  --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-audit-event list

```
usage: gitlab group-audit-event list [-h] [--sudo SUDO] --group-id GROUP_ID  
                                     [--created-after CREATED_AFTER]  
                                     [--created-before CREATED_BEFORE]  
                                     [--page PAGE] [--per-page PER_PAGE]  
                                     [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--created-after <created_after>

--created-before <created_before>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-badge

```
usage: gitlab group-badge [-h] {list,get,create,update,delete,render} ...
```

-h, --help

show this help message and exit

gitlab group-badge create

```
usage: gitlab group-badge create [-h] [--sudo SUDO] --group-id GROUP_ID  
                                --link-url LINK_URL --image-url IMAGE_URL
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--link-url <link_url>

--image-url <image_url>

gitlab group-badge delete

```
usage: gitlab group-badge delete [-h] [--sudo SUDO] --group-id GROUP_ID --id  
                                 ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-badge get

```
usage: gitlab group-badge get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-badge list

```
usage: gitlab group-badge list [-h] [--sudo SUDO] --group-id GROUP_ID  
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]  
                               [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-badge render

```
usage: gitlab group-badge render [-h] --group-id GROUP_ID [--sudo SUDO] --id
                                 ID --link-url LINK_URL --image-url IMAGE_URL
```

```
-h, --help
    show this help message and exit
--group-id <group_id>
--sudo <sudo>
--id <id>
--link-url <link_url>
--image-url <image_url>
```

gitlab group-badge update

```
usage: gitlab group-badge update [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                 ID [--link-url LINK_URL]
                                 [--image-url IMAGE_URL]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
--link-url <link_url>
--image-url <image_url>
```

gitlab group-billable-member

```
usage: gitlab group-billable-member [-h] {list,delete} ...
```

-h, --help

show this help message and exit

gitlab group-billable-member delete

```
usage: gitlab group-billable-member delete [-h] [--sudo SUDO] --group-id
                                             GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-billable-member list

```
usage: gitlab group-billable-member list [-h] [--sudo SUDO] --group-id
                                         GROUP_ID [--search SEARCH]
                                         [--sort SORT] [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--search <search>

--sort <sort>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-billable-member-membership

```
usage: gitlab group-billable-member-membership [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-billable-member-membership list

```
usage: gitlab group-billable-member-membership list [-h] [--sudo SUDO]
                                                    --group-id GROUP_ID
                                                    --user-id USER_ID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--user-id <user_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-board

```
usage: gitlab group-board [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-board create

```
usage: gitlab group-board create [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                 NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--group-id <group_id>  
--name <name>
```

gitlab group-board delete

```
usage: gitlab group-board delete [-h] [--sudo SUDO] --group-id GROUP_ID --id  
                                 ID
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--group-id <group_id>  
--id <id>
```

gitlab group-board get

```
usage: gitlab group-board get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--group-id <group_id>  
--id <id>
```

gitlab group-board list

```
usage: gitlab group-board list [-h] [--sudo SUDO] --group-id GROUP_ID  
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]  
                               [--all]
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--group-id <group_id>  
--page <page>  
--per-page <per_page>  
--get-all  
    Return all items from the server, without pagination.  
--all  
    Deprecated. Use --get-all instead.
```

gitlab group-board update

```
usage: gitlab group-board update [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                  ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-board-list

```
usage: gitlab group-board-list [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-board-list create

```
usage: gitlab group-board-list create [-h] [--sudo SUDO] --group-id GROUP_ID
                                       --board-id BOARD_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

gitlab group-board-list delete

```
usage: gitlab group-board-list delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                       --board-id BOARD_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--id <id>

gitlab group-board-list get

```
usage: gitlab group-board-list get [-h] [--sudo SUDO] --group-id GROUP_ID
                                  --board-id BOARD_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--id <id>

gitlab group-board-list list

```
usage: gitlab group-board-list list [-h] [--sudo SUDO] --group-id GROUP_ID
                                    --board-id BOARD_ID [--page PAGE]
                                    [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--board-id <board_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-board-list update

```
usage: gitlab group-board-list update [-h] [--sudo SUDO] --group-id GROUP_ID
                                       --board-id BOARD_ID --id ID --position
                                       POSITION
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

```
--board-id <board_id>
--id <id>
--position <position>
```

gitlab group-cluster

```
usage: gitlab group-cluster [-h] {list,get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab group-cluster create

```
usage: gitlab group-cluster create [-h] [--sudo SUDO] --group-id GROUP_ID
                                  --name NAME
                                  --platform-kubernetes-attributes
                                  PLATFORM_KUBERNETES_ATTRIBUTES
                                  [--domain DOMAIN] [--enabled ENABLED]
                                  [--managed MANAGED]
                                  [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--name <name>
--platform-kubernetes-attributes <platform_kubernetes_attributes>
--domain <domain>
--enabled <enabled>
--managed <managed>
--environment-scope <environment_scope>
```

gitlab group-cluster delete

```
usage: gitlab group-cluster delete [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID
```

-h, --help
show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-cluster get

```
usage: gitlab group-cluster get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-cluster list

```
usage: gitlab group-cluster list [-h] [--sudo SUDO] --group-id GROUP_ID  
                                 [--page PAGE] [--per-page PER_PAGE]  
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-cluster update

```
usage: gitlab group-cluster update [-h] [--sudo SUDO] --group-id GROUP_ID --id  
                                   ID [--name NAME] [--domain DOMAIN]  
                                   [--management-project-id MANAGEMENT_PROJECT_ID]  
                                   [--platform-kubernetes-attributes PLATFORM_KUBERNETES_  
                                     ↵ATTRIBUTES]  
                                   [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

```
--name <name>
--domain <domain>
--management-project-id <management_project_id>
--platform-kubernetes-attributes <platform_kubernetes_attributes>
--environment-scope <environment_scope>
```

gitlab group-custom-attribute

```
usage: gitlab group-custom-attribute [-h] {list,get,delete} ...
```

-h, --help

show this help message and exit

gitlab group-custom-attribute delete

```
usage: gitlab group-custom-attribute delete [-h] [--sudo SUDO] --group-id
                                             GROUP_ID --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

gitlab group-custom-attribute get

```
usage: gitlab group-custom-attribute get [-h] [--sudo SUDO] --group-id
                                         GROUP_ID --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--key <key>

gitlab group-custom-attribute list

```
usage: gitlab group-custom-attribute list [-h] [--sudo SUDO] --group-id
                                         GROUP_ID [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-deploy-token

```
usage: gitlab group-deploy-token [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab group-deploy-token create

```
usage: gitlab group-deploy-token create [-h] [--sudo SUDO] --group-id GROUP_ID
                                         --name NAME --scopes SCOPES
                                         [--expires-at EXPIRES_AT]
                                         [--username USERNAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

--scopes <scopes>

--expires-at <expires_at>

--username <username>

gitlab group-deploy-token delete

```
usage: gitlab group-deploy-token delete [-h] [--sudo SUDO] --group-id GROUP_ID  
                                         --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-deploy-token get

```
usage: gitlab group-deploy-token get [-h] [--sudo SUDO] --group-id GROUP_ID  
                                         --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-deploy-token list

```
usage: gitlab group-deploy-token list [-h] [--sudo SUDO] --group-id GROUP_ID  
                                         [--scopes SCOPES] [--page PAGE]  
                                         [--per-page PER_PAGE] [--get-all]  
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--scopes <scopes>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-descendant-group

```
usage: gitlab group-descendant-group [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-descendant-group list

```
usage: gitlab group-descendant-group list [-h] [--sudo SUDO] --group-id
                                         GROUP_ID [--skip-groups SKIP_GROUPS]
                                         [--all-available ALL_AVAILABLE]
                                         [--search SEARCH]
                                         [--order-by ORDER_BY] [--sort SORT]
                                         [--statistics STATISTICS]
                                         [--owned OWNED]
                                         [--with-custom-attributes WITH_CUSTOM_
                                         ↵ATTRIBUTES]
                                         [--min-access-level MIN_ACCESS_LEVEL]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--skip-groups <skip_groups>

--all-available <all_available>

--search <search>

--order-by <order_by>

--sort <sort>

--statistics <statistics>

--owned <owned>

--with-custom-attributes <with_custom_attributes>

--min-access-level <min_access_level>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-epic

```
usage: gitlab group-epic [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-epic create

```
usage: gitlab group-epic create [-h] [--sudo SUDO] --group-id GROUP_ID --title
                                TITLE [--labels LABELS]
                                [--description DESCRIPTION]
                                [--start-date START_DATE]
                                [--end-date END_DATE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--title <title>

--labels <labels>

--description <description>

--start-date <start_date>

--end-date <end_date>

gitlab group-epic delete

```
usage: gitlab group-epic delete [-h] [--sudo SUDO] --group-id GROUP_ID --iid
                                 IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--iid <iid>

gitlab group-epic get

```
usage: gitlab group-epic get [-h] [--sudo SUDO] --group-id GROUP_ID --iid IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--iid <iid>

gitlab group-epic list

```
usage: gitlab group-epic list [-h] [--sudo SUDO] --group-id GROUP_ID
                               [--author-id AUTHOR_ID] [--labels LABELS]
                               [--order-by ORDER_BY] [--sort SORT]
                               [--search SEARCH] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--author-id <author_id>

--labels <labels>

--order-by <order_by>

--sort <sort>

--search <search>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-epic update

```
usage: gitlab group-epic update [-h] [--sudo SUDO] --group-id GROUP_ID --iid
                                IID [--title TITLE] [--labels LABELS]
                                [--description DESCRIPTION]
                                [--start-date START_DATE]
                                [--end-date END_DATE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--iid <iid>

--title <title>

--labels <labels>

--description <description>

--start-date <start_date>

--end-date <end_date>

gitlab group-epic-award-emoji

```
usage: gitlab group-epic-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab group-epic-award-emoji create

```
usage: gitlab group-epic-award-emoji create [-h] [--sudo SUDO] --group-id
                                              GROUP_ID --epic-iid EPIC_IID
                                              --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--name <name>

gitlab group-epic-award-emoji delete

```
usage: gitlab group-epic-award-emoji delete [-h] [--sudo SUDO] --group-id
                                             GROUP_ID --epic-iid EPIC_IID --id
                                             ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--id <id>

gitlab group-epic-award-emoji get

```
usage: gitlab group-epic-award-emoji get [-h] [--sudo SUDO] --group-id
                                         GROUP_ID --epic-iid EPIC_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--id <id>

gitlab group-epic-award-emoji list

```
usage: gitlab group-epic-award-emoji list [-h] [--sudo SUDO] --group-id
                                            GROUP_ID --epic-iid EPIC_IID
                                            [--page PAGE] [--per-page PER_PAGE]
                                            [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-epic-discussion-note

```
usage: gitlab group-epic-discussion-note [-h] {get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-epic-discussion-note create

```
usage: gitlab group-epic-discussion-note create [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --discussion-id DISCUSSION_ID
                                                --body BODY
                                                [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--epic-iid <epic_iid>****--discussion-id <discussion_id>****--body <body>****--created-at <created_at>****gitlab group-epic-discussion-note delete**

```
usage: gitlab group-epic-discussion-note delete [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --discussion-id DISCUSSION_ID
                                                --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--epic-iid <epic_iid>**

```
--discussion-id <discussion_id>  
--id <id>
```

gitlab group-epic-discussion-note get

```
usage: gitlab group-epic-discussion-note get [-h] [--sudo SUDO] --group-id  
      GROUP_ID --epic-iid EPIC_IID  
      --discussion-id DISCUSSION_ID  
      --id ID
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--group-id <group_id>  
--epic-iid <epic_iid>  
--discussion-id <discussion_id>  
--id <id>
```

gitlab group-epic-discussion-note update

```
usage: gitlab group-epic-discussion-note update [-h] [--sudo SUDO] --group-id  
      GROUP_ID --epic-iid EPIC_IID  
      --discussion-id DISCUSSION_ID  
      --id ID --body BODY
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--group-id <group_id>  
--epic-iid <epic_iid>  
--discussion-id <discussion_id>  
--id <id>  
--body <body>
```

gitlab group-epic-issue

```
usage: gitlab group-epic-issue [-h] {list,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-epic-issue create

```
usage: gitlab group-epic-issue create [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --epic-iid EPIC_IID --issue-id ISSUE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--issue-id <issue_id>

gitlab group-epic-issue delete

```
usage: gitlab group-epic-issue delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                       --epic-iid EPIC_IID --epic-issue-id
                                       EPIC_ISSUE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--epic-issue-id <epic_issue_id>

gitlab group-epic-issue list

```
usage: gitlab group-epic-issue list [-h] [--sudo SUDO] --group-id GROUP_ID
                                     --epic-iid EPIC_IID [--page PAGE]
                                     [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

```
--epic-iid <epic_iid>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-epic-issue update

```
usage: gitlab group-epic-issue update [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --epic-iid EPIC_IID --epic-issue-id
                                      EPIC_ISSUE_ID
                                      [--move-before-id MOVE_BEFORE_ID]
                                      [--move-after-id MOVE_AFTER_ID]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--epic-iid <epic_iid>
--epic-issue-id <epic_issue_id>
--move-before-id <move_before_id>
--move-after-id <move_after_id>
```

gitlab group-epic-note

```
usage: gitlab group-epic-note [-h] {list,get,create,update,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-epic-note create

```
usage: gitlab group-epic-note create [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --epic-iid EPIC_IID --body BODY
                                      [--created-at CREATED_AT]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
```

```
--group-id <group_id>
--epic-iid <epic_iid>
--body <body>
--created-at <created_at>
```

gitlab group-epic-note delete

```
usage: gitlab group-epic-note delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --epic-iid EPIC_IID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--epic-iid <epic_iid>
--id <id>
```

gitlab group-epic-note get

```
usage: gitlab group-epic-note get [-h] [--sudo SUDO] --group-id GROUP_ID
                                    --epic-iid EPIC_IID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--epic-iid <epic_iid>
--id <id>
```

gitlab group-epic-note list

```
usage: gitlab group-epic-note list [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --epic-iid EPIC_IID [--page PAGE]
                                      [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

```
--epic-iid <epic_iid>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-epic-note update

```
usage: gitlab group-epic-note update [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --epic-iid EPIC_IID --id ID --body BODY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--epic-iid <epic_iid>
--id <id>
--body <body>
```

gitlab group-epic-note-award-emoji

```
usage: gitlab group-epic-note-award-emoji [-h] {list,get,create,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-epic-note-award-emoji create

```
usage: gitlab group-epic-note-award-emoji create [-h] [--sudo SUDO] --group-id
                                                 GROUP_ID --epic-iid EPIC_IID
                                                 --note-id NOTE_ID --name NAME
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--epic-iid <epic_iid>
--note-id <note_id>
--name <name>
```

gitlab group-epic-note-award-emoji delete

```
usage: gitlab group-epic-note-award-emoji delete [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --note-id NOTE_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--note-id <note_id>

--id <id>

gitlab group-epic-note-award-emoji get

```
usage: gitlab group-epic-note-award-emoji get [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --note-id NOTE_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

--note-id <note_id>

--id <id>

gitlab group-epic-note-award-emoji list

```
usage: gitlab group-epic-note-award-emoji list [-h] [--sudo SUDO] --group-id
                                                GROUP_ID --epic-iid EPIC_IID
                                                --note-id NOTE_ID [--page PAGE]
                                                [--per-page PER_PAGE]
                                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--epic-iid <epic_iid>

```
--note-id <note_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-epic-resource-label-event

```
usage: gitlab group-epic-resource-label-event [-h] {list,get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-epic-resource-label-event get

```
usage: gitlab group-epic-resource-label-event get [-h] [--sudo SUDO]
                                                --group-id GROUP_ID
                                                --epic-id EPIC_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--epic-id <epic_id>
--id <id>
```

gitlab group-epic-resource-label-event list

```
usage: gitlab group-epic-resource-label-event list [-h] [--sudo SUDO]
                                                 --group-id GROUP_ID
                                                 --epic-id EPIC_ID
                                                 [--page PAGE]
                                                 [--per-page PER_PAGE]
                                                 [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

```
--epic-id <epic_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-export

```
usage: gitlab group-export [-h] {get,create,download} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-export create

```
usage: gitlab group-export create [-h] [--sudo SUDO] --group-id GROUP_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

gitlab group-export download

```
usage: gitlab group-export download [-h] --group-id GROUP_ID [--sudo SUDO]
```

```
-h, --help
    show this help message and exit
--group-id <group_id>
--sudo <sudo>
```

gitlab group-export get

```
usage: gitlab group-export get [-h] [--sudo SUDO] --group-id GROUP_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

gitlab group-hook

```
usage: gitlab group-hook [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-hook create

```
usage: gitlab group-hook create [-h] [--sudo SUDO] --group-id GROUP_ID --url
                                URL [--push-events PUSH_EVENTS]
                                [--issues-events ISSUES_EVENTS]
                                [--confidential-issues-events CONFIDENTIAL_ISSUES_EVENTS]
                                [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                [--tag-push-events TAG_PUSH_EVENTS]
                                [--note-events NOTE_EVENTS]
                                [--confidential-note-events CONFIDENTIAL_NOTE_EVENTS]
                                [--job-events JOB_EVENTS]
                                [--pipeline-events PIPELINE_EVENTS]
                                [--wiki-page-events WIKI_PAGE_EVENTS]
                                [--deployment-events DEPLOYMENT_EVENTS]
                                [--releases-events RELEASES_EVENTS]
                                [--subgroup-events SUBGROUP_EVENTS]
                                [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                [--token TOKEN]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--url <url>

--push-events <push_events>

--issues-events <issues_events>

--confidential-issues-events <confidential_issues_events>

--merge-requests-events <merge_requests_events>

--tag-push-events <tag_push_events>

--note-events <note_events>

--confidential-note-events <confidential_note_events>

--job-events <job_events>

--pipeline-events <pipeline_events>

--wiki-page-events <wiki_page_events>

```
--deployment-events <deployment_events>
--releases-events <releases_events>
--subgroup-events <subgroup_events>
--enable-ssl-verification <enable_ssl_verification>
--token <token>
```

gitlab group-hook delete

```
usage: gitlab group-hook delete [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-hook get

```
usage: gitlab group-hook get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
```

gitlab group-hook list

```
usage: gitlab group-hook list [-h] [--sudo SUDO] --group-id GROUP_ID
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]
                               [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--page <page>
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-hook update

```
usage: gitlab group-hook update [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
                                --url URL [--push-events PUSH_EVENTS]
                                [--issues-events ISSUES_EVENTS]
                                [--confidential-issues-events CONFIDENTIAL_ISSUES_EVENTS]
                                [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                [--tag-push-events TAG_PUSH_EVENTS]
                                [--note-events NOTE_EVENTS]
                                [--confidential-note-events CONFIDENTIAL_NOTE_EVENTS]
                                [--job-events JOB_EVENTS]
                                [--pipeline-events PIPELINE_EVENTS]
                                [--wiki-page-events WIKI_PAGE_EVENTS]
                                [--deployment-events DEPLOYMENT_EVENTS]
                                [--releases-events RELEASES_EVENTS]
                                [--subgroup-events SUBGROUP_EVENTS]
                                [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                [--token TOKEN]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

--url <url>

--push-events <push_events>

--issues-events <issues_events>

--confidential-issues-events <confidential_issues_events>

--merge-requests-events <merge_requests_events>

--tag-push-events <tag_push_events>

--note-events <note_events>

--confidential-note-events <confidential_note_events>

--job-events <job_events>

--pipeline-events <pipeline_events>

--wiki-page-events <wiki_page_events>

```
--deployment-events <deployment_events>
--releases-events <releases_events>
--subgroup-events <subgroup_events>
--enable-ssl-verification <enable_ssl_verification>
--token <token>
```

gitlab group-import

```
usage: gitlab group-import [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab group-import get

```
usage: gitlab group-import get [-h] [--sudo SUDO] --group-id GROUP_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-invitation

```
usage: gitlab group-invitation [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-invitation create

```
usage: gitlab group-invitation create [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --access-level ACCESS_LEVEL
                                      [--expires-at EXPIRES_AT]
                                      [--invite-source INVITE_SOURCE]
                                      [--tasks-to-be-done TASKS_TO_BE_DONE]
                                      [--tasks-project-id TASKS_PROJECT_ID]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

```
--access-level <access_level>
--expires-at <expires_at>
--invite-source <invite_source>
--tasks-to-be-done <tasks_to_be_done>
--tasks-project-id <tasks_project_id>
```

gitlab group-invitation delete

```
usage: gitlab group-invitation delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --email EMAIL
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--email <email>

gitlab group-invitation get

```
usage: gitlab group-invitation get [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --email EMAIL
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--email <email>

gitlab group-invitation list

```
usage: gitlab group-invitation list [-h] [--sudo SUDO] --group-id GROUP_ID
                                      [--query QUERY] [--page PAGE]
                                      [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--group-id <group_id>

--query <query>

```
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-invitation update

```
usage: gitlab group-invitation update [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --email EMAIL
                                      [--access-level ACCESS_LEVEL]
                                      [--expires-at EXPIRES_AT]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--email <email>
--access-level <access_level>
--expires-at <expires_at>
```

gitlab group-issue

```
usage: gitlab group-issue [-h] {list} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-issue list

```
usage: gitlab group-issue list [-h] [--sudo SUDO] --group-id GROUP_ID
                               [--state STATE] [--labels LABELS]
                               [--milestone MILESTONE] [--order-by ORDER_BY]
                               [--sort SORT] [--iids IIDS]
                               [--author-id AUTHOR_ID]
                               [--assignee-id ASSIGNEE_ID]
                               [--my-reaction-emoji MY_REACTION_EMOJI]
                               [--search SEARCH]
                               [--created-after CREATED_AFTER]
                               [--created-before CREATED_BEFORE]
                               [--updated-after UPDATED_AFTER]
                               [--updated-before UPDATED_BEFORE] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--state <state>
--labels <labels>
--milestone <milestone>
--order-by <order_by>
--sort <sort>
--iids <iids>
--author-id <author_id>
--assignee-id <assignee_id>
--my-reaction-emoji <my_reaction_emoji>
--search <search>
--created-after <created_after>
--created-before <created_before>
--updated-after <updated_after>
--updated-before <updated_before>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-issues-statistics

```
usage: gitlab group-issues-statistics [-h] {get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-issues-statistics get

```
usage: gitlab group-issues-statistics get [-h] [--sudo SUDO] --group-id GROUP_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

gitlab group-iteration

```
usage: gitlab group-iteration [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-iteration list

```
usage: gitlab group-iteration list [-h] [--sudo SUDO] --group-id GROUP_ID  
                                  [--state STATE] [--search SEARCH]  
                                  [--include-ancestors INCLUDE_ANCESTORS]  
                                  [--page PAGE] [--per-page PER_PAGE]  
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--state <state>

--search <search>

--include-ancestors <include_ancestors>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-label

```
usage: gitlab group-label [-h]
  list
  get
  create
  update
  delete
  subscribe
  unsubscribe
  ...
```

-h, --help

show this help message and exit

gitlab group-label create

```
usage: gitlab group-label create [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                 NAME --color COLOR
                                 [--description DESCRIPTION]
                                 [--priority PRIORITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

--color <color>

--description <description>

--priority <priority>

gitlab group-label delete

```
usage: gitlab group-label delete [-h] [--sudo SUDO] --group-id GROUP_ID --name
                                 NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

gitlab group-label get

```
usage: gitlab group-label get [-h] [--sudo SUDO] --group-id GROUP_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

gitlab group-label list

```
usage: gitlab group-label list [-h] [--sudo SUDO] --group-id GROUP_ID  
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]  
                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-label subscribe

```
usage: gitlab group-label subscribe [-h] --group-id GROUP_ID [--sudo SUDO]  
                                   --name NAME
```

-h, --help

show this help message and exit

--group-id <group_id>

--sudo <sudo>

--name <name>

gitlab group-label unsubscribe

```
usage: gitlab group-label unsubscribe [-h] --group-id GROUP_ID [--sudo SUDO]
--name NAME
```

-h, --help

show this help message and exit

--group-id <group_id>

--sudo <sudo>

--name <name>

gitlab group-label update

```
usage: gitlab group-label update [-h] [--sudo SUDO] --group-id GROUP_ID --name
NAME [--new-name NEW_NAME] [--color COLOR]
[--description DESCRIPTION]
[--priority PRIORITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--name <name>

--new-name <new_name>

--color <color>

--description <description>

--priority <priority>

gitlab group-member

```
usage: gitlab group-member [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-member create

```
usage: gitlab group-member create [-h] [--sudo SUDO] --group-id GROUP_ID
                                  --access-level ACCESS_LEVEL --user-id
                                  USER_ID [--expires-at EXPIRES_AT]
                                  [--tasks-to-be-done TASKS_TO_BE_DONE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--access-level <access_level>

--user-id <user_id>

--expires-at <expires_at>

--tasks-to-be-done <tasks_to_be_done>

gitlab group-member delete

```
usage: gitlab group-member delete [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-member get

```
usage: gitlab group-member get [-h] [--sudo SUDO] --group-id GROUP_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-member list

```
usage: gitlab group-member list [-h] [--sudo SUDO] --group-id GROUP_ID
                                 [--page PAGE] [--per-page PER_PAGE]
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-member update

```
usage: gitlab group-member update [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID --access-level ACCESS_LEVEL
                                   [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

--access-level <access_level>

--expires-at <expires_at>

gitlab group-member-all

```
usage: gitlab group-member-all [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab group-member-all get

```
usage: gitlab group-member-all get [-h] [--sudo SUDO] --group-id GROUP_ID --id
                                   ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-member-all list

```
usage: gitlab group-member-all list [-h] [--sudo SUDO] --group-id GROUP_ID
                                    [--page PAGE] [--per-page PER_PAGE]
                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-merge-request

```
usage: gitlab group-merge-request [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-merge-request list

```
usage: gitlab group-merge-request list [-h] [--sudo SUDO] --group-id GROUP_ID
                                         [--state STATE] [--order-by ORDER_BY]
                                         [--sort SORT] [--milestone MILESTONE]
                                         [--view VIEW] [--labels LABELS]
                                         [--created-after CREATED_AFTER]
                                         [--created-before CREATED_BEFORE]
                                         [--updated-after UPDATED_AFTER]
                                         [--updated-before UPDATED_BEFORE]
                                         [--scope SCOPE] [--author-id AUTHOR_ID]
                                         [--assignee-id ASSIGNEE_ID]
                                         [--approver-ids APPROVER_IDS]
                                         [--approved-by-ids APPROVED_BY_IDS]
                                         [--my-reaction-emoji MY_REACTION_EMOJI]
                                         [--source-branch SOURCE_BRANCH]
                                         [--target-branch TARGET_BRANCH]
                                         [--search SEARCH] [--wip WIP]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--state <state>

--order-by <order_by>

--sort <sort>

--milestone <milestone>

--view <view>

--labels <labels>

--created-after <created_after>

--created-before <created_before>

--updated-after <updated_after>

--updated-before <updated_before>

--scope <scope>

--author-id <author_id>

--assignee-id <assignee_id>

--approver-ids <approver_ids>

--approved-by-ids <approved_by_ids>

```
--my-reaction-emoji <my_reaction_emoji>
--source-branch <source_branch>
--target-branch <target_branch>
--search <search>
--wip <wip>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-milestone

```
usage: gitlab group-milestone [-h]
  list
  get
  create
  update
  delete
  issues
  merge-requests
  ...
  
```

-h, --help

show this help message and exit

gitlab group-milestone create

```
usage: gitlab group-milestone create [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --title TITLE [--description DESCRIPTION]
                                      [--due-date DUE_DATE]
                                      [--start-date START_DATE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--title <title>

--description <description>

--due-date <due_date>

--start-date <start_date>

gitlab group-milestone delete

```
usage: gitlab group-milestone delete [-h] [--sudo SUDO] --group-id GROUP_ID  
                                     --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-milestone get

```
usage: gitlab group-milestone get [-h] [--sudo SUDO] --group-id GROUP_ID --id  
                                   ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--id <id>

gitlab group-milestone issues

```
usage: gitlab group-milestone issues [-h] --group-id GROUP_ID [--sudo SUDO]  
                                     --id ID
```

-h, --help

show this help message and exit

--group-id <group_id>

--sudo <sudo>

--id <id>

gitlab group-milestone list

```
usage: gitlab group-milestone list [-h] [--sudo SUDO] --group-id GROUP_ID  
                                     [--iids IIDS] [--state STATE]  
                                     [--search SEARCH] [--page PAGE]  
                                     [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--group-id <group_id>
--iids <iids>
--state <state>
--search <search>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-milestone merge-requests

```
usage: gitlab group-milestone merge-requests [-h] --group-id GROUP_ID
                                              [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--group-id <group_id>
--sudo <sudo>
--id <id>
```

gitlab group-milestone update

```
usage: gitlab group-milestone update [-h] [--sudo SUDO] --group-id GROUP_ID
                                      --id ID [--title TITLE]
                                      [--description DESCRIPTION]
                                      [--due-date DUE_DATE]
                                      [--start-date START_DATE]
                                      [--state-event STATE_EVENT]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--id <id>
--title <title>
--description <description>
```

```
--due-date <due_date>
--start-date <start_date>
--state-event <state_event>
```

gitlab group-notification-settings

```
usage: gitlab group-notification-settings [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab group-notification-settings get

```
usage: gitlab group-notification-settings get [-h] [--sudo SUDO] --group-id
                                              GROUP_ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--group-id <group_id>
```

gitlab group-notification-settings update

```
usage: gitlab group-notification-settings update [-h] [--sudo SUDO] --group-id
                                                 GROUP_ID [--level LEVEL]
                                                 [--notification-email NOTIFICATION_
                                                 ↵EMAIL]
                                                 [--new-note NEW_NOTE]
                                                 [--new-issue NEW_ISSUE]
                                                 [--reopen-issue REOPEN_ISSUE]
                                                 [--close-issue CLOSE_ISSUE]
                                                 [--reassign-issue REASSIGN_ISSUE]
                                                 [--new-merge-request NEW_MERGE_REQUEST]
                                                 [--reopen-merge-request REOPEN_MERGE_
                                                 ↵REQUEST]
                                                 [--close-merge-request CLOSE_MERGE_
                                                 ↵REQUEST]
                                                 [--reassign-merge-request REASSIGN_
                                                 ↵MERGE_REQUEST]
                                                 [--merge-merge-request MERGE_MERGE_
                                                 ↵REQUEST]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--group-id <group_id>
--level <level>
--notification-email <notification_email>
--new-note <new_note>
--new-issue <new_issue>
--reopen-issue <reopen_issue>
--close-issue <close_issue>
--reassign-issue <reassign_issue>
--new-merge-request <new_merge_request>
--reopen-merge-request <reopen_merge_request>
--close-merge-request <close_merge_request>
--reassign-merge-request <reassign_merge_request>
--merge-merge-request <merge_merge_request>
```

gitlab group-package

```
usage: gitlab group-package [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-package list

```
usage: gitlab group-package list [-h] [--sudo SUDO] --group-id GROUP_ID
                                  [--exclude-subgroups EXCLUDE_SUBGROUPS]
                                  [--order-by ORDER_BY] [--sort SORT]
                                  [--package-type PACKAGE_TYPE]
                                  [--package-name PACKAGE_NAME] [--page PAGE]
                                  [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--exclude-subgroups <exclude_subgroups>

--order-by <order_by>

--sort <sort>

```
--package-type <package_type>
--package-name <package_name>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-project

```
usage: gitlab group-project [-h] {list} ...
```

```
-h, --help
    show this help message and exit
```

gitlab group-project list

```
usage: gitlab group-project list [-h] [--sudo SUDO] --group-id GROUP_ID
    [--archived ARCHIVED]
    [--visibility VISIBILITY]
    [--order-by ORDER_BY] [--sort SORT]
    [--search SEARCH] [--simple SIMPLE]
    [--owned OWNED] [--starred STARRED]
    [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
    [--include-subgroups INCLUDE_SUBGROUPS]
    [--with-issues-enabled WITH_ISSUES_ENABLED]
    [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
    ↵ENABLED]
    [--with-shared WITH_SHARED]
    [--min-access-level MIN_ACCESS_LEVEL]
    [--with-security-reports WITH_SECURITY_REPORTS]
    [--page PAGE] [--per-page PER_PAGE]
    [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--archived <archived>
--visibility <visibility>
--order-by <order_by>
```

```
--sort <sort>
--search <search>
--simple <simple>
--owned <owned>
--starred <starred>
--with-custom-attributes <with_custom_attributes>
--include-subgroups <include_subgroups>
--with-issues-enabled <with_issues_enabled>
--with-merge-requests-enabled <with_merge_requests_enabled>
--with-shared <with_shared>
--min-access-level <min_access_level>
--with-security-reports <with_security_reports>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab group-push-rules

```
usage: gitlab group-push-rules [-h] {get,create,update,delete} ...
```

-h, --help
show this help message and exit

gitlab group-push-rules create

```
usage: gitlab group-push-rules create [-h] [--sudo SUDO] --group-id GROUP_ID
                                      [--deny-delete-tag DENY_DELETE_TAG]
                                      [--member-check MEMBER_CHECK]
                                      [--prevent-secrets PREVENT_SECRETS]
                                      [--commit-message-regex COMMIT_MESSAGE_REGEX]
                                      [--commit-message-negative-regex COMMIT_MESSAGE_
                                       NEGATIVE_REGEX]
                                      [--branch-name-regex BRANCH_NAME_REGEX]
                                      [--author-email-regex AUTHOR_EMAIL_REGEX]
                                      [--file-name-regex FILE_NAME_REGEX]
                                      [--max-file-size MAX_FILE_SIZE]
                                      [--commit-committer-check COMMIT_COMMITTER_CHECK]
                                      [--reject-unsigned-commits REJECT_UNSIGNED_COMMITS]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--deny-delete-tag <deny_delete_tag>
--member-check <member_check>
--prevent-secrets <prevent_secrets>
--commit-message-regex <commit_message_regex>
--commit-message-negative-regex <commit_message_negative_regex>
--branch-name-regex <branch_name_regex>
--author-email-regex <author_email_regex>
--file-name-regex <file_name_regex>
--max-file-size <max_file_size>
--commit-committer-check <commit_committer_check>
--reject-unsigned-commits <reject_unsigned_commits>
```

gitlab group-push-rules delete

```
usage: gitlab group-push-rules delete [-h] [--sudo SUDO] --group-id GROUP_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

gitlab group-push-rules get

```
usage: gitlab group-push-rules get [-h] [--sudo SUDO] --group-id GROUP_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
```

gitlab group-push-rules update

```
usage: gitlab group-push-rules update [-h] [--sudo SUDO] --group-id GROUP_ID
                                      [--deny-delete-tag DENY_DELETE_TAG]
                                      [--member-check MEMBER_CHECK]
                                      [--prevent-secrets PREVENT_SECRETS]
                                      [--commit-message-regex COMMIT_MESSAGE_REGEX]
                                      [--commit-message-negative-regex COMMIT_MESSAGE_
                                       NEGATIVE_REGEX]
                                      [--branch-name-regex BRANCH_NAME_REGEX]
                                      [--author-email-regex AUTHOR_EMAIL_REGEX]
                                      [--file-name-regex FILE_NAME_REGEX]
                                      [--max-file-size MAX_FILE_SIZE]
                                      [--commit-committer-check COMMIT_COMMITTER_CHECK]
                                      [--reject-unsigned-commits REJECT_UNSIGNED_COMMITS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--deny-delete-tag <deny_delete_tag>

--member-check <member_check>

--prevent-secrets <prevent_secrets>

--commit-message-regex <commit_message_regex>

--commit-message-negative-regex <commit_message_negative_regex>

--branch-name-regex <branch_name_regex>

--author-email-regex <author_email_regex>

--file-name-regex <file_name_regex>

--max-file-size <max_file_size>

--commit-committer-check <commit_committer_check>

--reject-unsigned-commits <reject_unsigned_commits>

gitlab group-runner

```
usage: gitlab group-runner [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-runner list

```
usage: gitlab group-runner list [-h] [--sudo SUDO] --group-id GROUP_ID
                                [--scope SCOPE] [--tag-list TAG_LIST]
                                [--page PAGE] [--per-page PER_PAGE]
                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--scope <scope>

--tag-list <tag_list>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-subgroup

```
usage: gitlab group-subgroup [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab group-subgroup list

```
usage: gitlab group-subgroup list [-h] [--sudo SUDO] --group-id GROUP_ID
                                    [--skip-groups SKIP_GROUPS]
                                    [--all-available ALL_AVAILABLE]
                                    [--search SEARCH] [--order-by ORDER_BY]
                                    [--sort SORT] [--statistics STATISTICS]
                                    [--owned OWNED]
                                    [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                    [--min-access-level MIN_ACCESS_LEVEL]
                                    [--page PAGE] [--per-page PER_PAGE]
                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--group-id <group_id>
--skip-groups <skip_groups>
--all-available <all_available>
--search <search>
--order-by <order_by>
--sort <sort>
--statistics <statistics>
--owned <owned>
--with-custom-attributes <with_custom_attributes>
--min-access-level <min_access_level>
--page <page>
--per-page <per_page>
--get-all
```

Return all items from the server, without pagination.

```
--all
```

Deprecated. Use --get-all instead.

gitlab group-variable

```
usage: gitlab group-variable [-h] {list,get,create,update,delete} ...
```

```
-h, --help
```

show this help message and exit

gitlab group-variable create

```
usage: gitlab group-variable create [-h] [--sudo SUDO] --group-id GROUP_ID
                                    --key KEY --value VALUE
                                    [--protected PROTECTED]
                                    [--variable-type VARIABLE_TYPE]
                                    [--masked MASKED]
```

```
-h, --help
```

show this help message and exit

```
--sudo <sudo>
```

```
--group-id <group_id>
```

```
--key <key>
```

```
--value <value>
```

```
--protected <protected>
--variable-type <variable_type>
--masked <masked>
```

gitlab group-variable delete

```
usage: gitlab group-variable delete [-h] [--sudo SUDO] --group-id GROUP_ID
                                   --key KEY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--key <key>
```

gitlab group-variable get

```
usage: gitlab group-variable get [-h] [--sudo SUDO] --group-id GROUP_ID --key
                                 KEY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--key <key>
```

gitlab group-variable list

```
usage: gitlab group-variable list [-h] [--sudo SUDO] --group-id GROUP_ID
                                   [--page PAGE] [--per-page PER_PAGE]
                                   [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--group-id <group_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
```

--all

Deprecated. Use --get-all instead.

gitlab group-variable update

```
usage: gitlab group-variable update [-h] [--sudo SUDO] --group-id GROUP_ID
                                   --key KEY --value VALUE
                                   [--protected PROTECTED]
                                   [--variable-type VARIABLE_TYPE]
                                   [--masked MASKED]
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--key <key>****--value <value>****--protected <protected>****--variable-type <variable_type>****--masked <masked>****gitlab group-wiki**

```
usage: gitlab group-wiki [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab group-wiki create

```
usage: gitlab group-wiki create [-h] [--sudo SUDO] --group-id GROUP_ID --title
                                 TITLE --content CONTENT [--format FORMAT]
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--title <title>****--content <content>****--format <format>**

gitlab group-wiki delete

```
usage: gitlab group-wiki delete [-h] [--sudo SUDO] --group-id GROUP_ID --slug
                                SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--slug <slug>

gitlab group-wiki get

```
usage: gitlab group-wiki get [-h] [--sudo SUDO] --group-id GROUP_ID --slug
                             SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--slug <slug>

gitlab group-wiki list

```
usage: gitlab group-wiki list [-h] [--sudo SUDO] --group-id GROUP_ID
                               [--with-content WITH_CONTENT] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--with-content <with_content>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab group-wiki update

```
usage: gitlab group-wiki update [-h] [--sudo SUDO] --group-id GROUP_ID --slug
                                SLUG [--title TITLE] [--content CONTENT]
                                [--format FORMAT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--group-id <group_id>

--slug <slug>

--title <title>

--content <content>

--format <format>

gitlab hook

```
usage: gitlab hook [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab hook create

```
usage: gitlab hook create [-h] [--sudo SUDO] --url URL
```

-h, --help

show this help message and exit

--sudo <sudo>

--url <url>

gitlab hook delete

```
usage: gitlab hook delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab hook get

```
usage: gitlab hook get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab hook list

```
usage: gitlab hook list [-h] [--sudo SUDO] [--page PAGE] [--per-page PER_PAGE]
                        [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab issue

```
usage: gitlab issue [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab issue get

```
usage: gitlab issue get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab issue list

```
usage: gitlab issue list [-h] [--sudo SUDO] [--state STATE] [--labels LABELS]
                         [--milestone MILESTONE] [--scope SCOPE]
                         [--author-id AUTHOR_ID] [--assignee-id ASSIGNEE_ID]
                         [--my-reaction-emoji MY_REACTION_EMOJI] [--iids IIDS]
                         [--order-by ORDER_BY] [--sort SORT] [--search SEARCH]
                         [--created-after CREATED_AFTER]
                         [--created-before CREATED_BEFORE]
                         [--updated-after UPDATED_AFTER]
                         [--updated-before UPDATED_BEFORE] [--page PAGE]
                         [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--state <state>

--labels <labels>

--milestone <milestone>

--scope <scope>

--author-id <author_id>

--assignee-id <assignee_id>

--my-reaction-emoji <my_reaction_emoji>

--iids <iids>

--order-by <order_by>

--sort <sort>

--search <search>

--created-after <created_after>

--created-before <created_before>

--updated-after <updated_after>

--updated-before <updated_before>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab issues-statistics

```
usage: gitlab issues-statistics [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab issues-statistics get

```
usage: gitlab issues-statistics get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab key

```
usage: gitlab key [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab key get

```
usage: gitlab key get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab ldap-group

```
usage: gitlab ldap-group [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab ldap-group list

```
usage: gitlab ldap-group list [-h] [--sudo SUDO] [--search SEARCH]
                               [--provider PROVIDER] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--search <search>

--provider <provider>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab license

```
usage: gitlab license [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab license get

```
usage: gitlab license get [-h] [--sudo SUDO] --key KEY [--project PROJECT]
                           [--fullname FULLNAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

--project <project>

--fullname <fullname>

gitlab license list

```
usage: gitlab license list [-h] [--sudo SUDO] [--popular POPULAR]
                           [--page PAGE] [--per-page PER_PAGE] [--get-all]
                           [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--popular <popular>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab merge-request

```
usage: gitlab merge-request [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab merge-request list

```
usage: gitlab merge-request list [-h] [--sudo SUDO] [--state STATE]
                                 [--order-by ORDER_BY] [--sort SORT]
                                 [--milestone MILESTONE] [--view VIEW]
                                 [--labels LABELS]
                                 [--with-labels-details WITH_LABELS_DETAILS]
                                 [--with-merge-status-recheck WITH_MERGE_STATUS_RECHECK]
                                 [--created-after CREATED_AFTER]
                                 [--created-before CREATED_BEFORE]
                                 [--updated-after UPDATED_AFTER]
                                 [--updated-before UPDATED_BEFORE]
                                 [--scope SCOPE] [--author-id AUTHOR_ID]
                                 [--author-username AUTHOR_USERNAME]
                                 [--assignee-id ASSIGNEE_ID]
                                 [--approver-ids APPROVER_IDS]
                                 [--approved-by-ids APPROVED_BY_IDS]
                                 [--reviewer-id REVIEWER_ID]
                                 [--reviewer-username REVIEWER_USERNAME]
                                 [--my-reaction-emoji MY_REACTION_EMOJI]
                                 [--source-branch SOURCE_BRANCH]
                                 [--target-branch TARGET_BRANCH]
```

(continues on next page)

(continued from previous page)

```
[--search SEARCH] [--in IN] [--wip WIP]
[--not NOT] [--environment ENVIRONMENT]
[--deployed-before DEPLOYED_BEFORE]
[--deployed-after DEPLOYED_AFTER]
[--page PAGE] [--per-page PER_PAGE]
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--state <state>****--order-by <order_by>****--sort <sort>****--milestone <milestone>****--view <view>****--labels <labels>****--with-labels-details <with_labels_details>****--with-merge-status-recheck <with_merge_status_recheck>****--created-after <created_after>****--created-before <created_before>****--updated-after <updated_after>****--updated-before <updated_before>****--scope <scope>****--author-id <author_id>****--author-username <author_username>****--assignee-id <assignee_id>****--approver-ids <approver_ids>****--approved-by-ids <approved_by_ids>****--reviewer-id <reviewer_id>****--reviewer-username <reviewer_username>****--my-reaction-emoji <my_reaction_emoji>****--source-branch <source_branch>****--target-branch <target_branch>**

```
--search <search>
--in <in>
--wip <wip>
--not <not>
--environment <environment>
--deployed-before <deployed_before>
--deployed-after <deployed_after>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab namespace

```
usage: gitlab namespace [-h] {list,get,exists} ...
```

```
-h, --help
    show this help message and exit
```

gitlab namespace exists

```
usage: gitlab namespace exists [-h] --id ID --namespace NAMESPACE --parent-id
                                PARENT_ID
```

```
-h, --help
    show this help message and exit
--id <id>
--namespace <namespace>
--parent-id <parent_id>
```

gitlab namespace get

```
usage: gitlab namespace get [-h] [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>
```

gitlab namespace list

```
usage: gitlab namespace list [-h] [--sudo SUDO] [--search SEARCH]
                             [--page PAGE] [--per-page PER_PAGE] [--get-all]
                             [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--search <search>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab notification-settings

```
usage: gitlab notification-settings [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab notification-settings get

```
usage: gitlab notification-settings get [-h] [--sudo SUDO]
```

-h, --help

show this help message and exit

--sudo <sudo>

gitlab notification-settings update

```
usage: gitlab notification-settings update [-h] [--sudo SUDO] [--level LEVEL]
                                            [--notification-email NOTIFICATION_EMAIL]
                                            [--new-note NEW_NOTE]
                                            [--new-issue NEW_ISSUE]
                                            [--reopen-issue REOPEN_ISSUE]
                                            [--close-issue CLOSE_ISSUE]
                                            [--reassign-issue REASSIGN_ISSUE]
                                            [--new-merge-request NEW_MERGE_REQUEST]
                                            [--reopen-merge-request REOPEN_MERGE_REQUEST]
                                            [--close-merge-request CLOSE_MERGE_REQUEST]
```

(continues on next page)

(continued from previous page)

```
[--reassign-merge-request REASSIGN_MERGE_  
↪REQUEST]  
[--merge-merge-request MERGE_MERGE_REQUEST]
```

-h, --help

show this help message and exit

--sudo <sudo>

--level <level>

--notification-email <notification_email>

--new-note <new_note>

--new-issue <new_issue>

--reopen-issue <reopen_issue>

--close-issue <close_issue>

--reassign-issue <reassign_issue>

--new-merge-request <new_merge_request>

--reopen-merge-request <reopen_merge_request>

--close-merge-request <close_merge_request>

--reassign-merge-request <reassign_merge_request>

--merge-merge-request <merge_merge_request>

gitlab pages-domain

```
usage: gitlab pages-domain [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab pages-domain list

```
usage: gitlab pages-domain list [-h] [--sudo SUDO] [--page PAGE]  
                                [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab personal-access-token

```
usage: gitlab personal-access-token [-h] {list,delete} ...
```

-h, --help

show this help message and exit

gitlab personal-access-token delete

```
usage: gitlab personal-access-token delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--id <id>****gitlab personal-access-token list**

```
usage: gitlab personal-access-token list [-h] [--sudo SUDO]
                                         [--user-id USER_ID] [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--user-id <user_id>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project

```
usage: gitlab project [-h]
  list
  get
  create
  update
  delete
  artifacts
  update-submodule
  repository-tree
  repository-blob
  repository-raw-blob
  repository-compare
  repository-contributors
  repository-archive
  repository-merge-base
  delete-merged-branches
  create-fork-relation
  delete-fork-relation
  languages
  star
  unstar
  archive
  unarchive
  share
  unshare
  trigger-pipeline
  housekeeping
  upload
  restore
  snapshot
  search
  mirror-pull
  transfer
  transfer-project
  artifact
  ...
  ...
```

-h, --help

show this help message and exit

gitlab project archive

```
usage: gitlab project archive [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project artifact

```
usage: gitlab project artifact [-h] --id ID --ref-name REF_NAME
                               --artifact-path ARTIFACT_PATH --job JOB
```

-h, --help

show this help message and exit

--id <id>

--ref-name <ref_name>

--artifact-path <artifact_path>

--job <job>

gitlab project artifacts

```
usage: gitlab project artifacts [-h] --id ID --ref-name REF_NAME --job JOB
                               [--job-token JOB_TOKEN]
```

-h, --help

show this help message and exit

--id <id>

--ref-name <ref_name>

--job <job>

--job-token <job_token>

gitlab project create

```
usage: gitlab project create [-h] [--sudo SUDO] [--name NAME] [--path PATH]
                            [--allow-merge-on-skipped-pipeline ALLOW_MERGE_ON_SKIPPED_
                            PIPELINE]
                            [--analytics-access-level ANALYTICS_ACCESS_LEVEL]
                            [--approvals-before-merge APPROVALS_BEFORE_MERGE]
                            [--auto-cancel-pending-pipelines AUTO_CANCEL_PENDING_
                            PIPELINES]
                            [--auto-devops-deploy-strategy AUTO_DEVOPS_DEPLOY_STRATEGY]
                            [--auto-devops-enabled AUTO_DEVOPS_ENABLED]
                            [--autoclose-referenced-issues AUTOCLOSE_REFERENCED_ISSUES]
                            [--avatar AVATAR]
                            [--build-coverage-regex BUILD_COVERAGE_REGEX]
                            [--build-git-strategy BUILD_GIT_STRATEGY]
                            [--build-timeout BUILD_TIMEOUT]
                            [--builds-access-level BUILDS_ACCESS_LEVEL]
                            [--ci-config-path CI_CONFIG_PATH]
                            [--container-expiration-policy-attributes CONTAINER_
                            EXPIRATION_POLICY_ATTRIBUTES]
```

(continues on next page)

(continued from previous page)

```
[--container-registry-enabled CONTAINER_REGISTRY_ENABLED]
[--default-branch DEFAULT_BRANCH]
[--description DESCRIPTION]
[--emails-disabled EMAILS_DISABLED]
[--external-authorization-classification-label EXTERNAL_
˓→AUTHORIZATION_CLASSIFICATION_LABEL]
[--forking-access-level FORKING_ACCESS_LEVEL]
[--group-with-project-templates-id GROUP_WITH_PROJECT_
˓→TEMPLATES_ID]
[--import-url IMPORT_URL]
[--initialize-with-readme INITIALIZE_WITH_README]
[--issues-access-level ISSUES_ACCESS_LEVEL]
[--issues-enabled ISSUES_ENABLED]
[--jobs-enabled JOBS_ENABLED]
[--lfs-enabled LFS_ENABLED]
[--merge-method MERGE_METHOD]
[--merge-pipelines-enabled MERGE_PIPELINES_ENABLED]
[--merge-requests-access-level MERGE_REQUESTS_ACCESS_LEVEL]
[--merge-requests-enabled MERGE_REQUESTS_ENABLED]
[--mirror-trigger-builds MIRROR_TRIGGER_BUILDUPS]
[--mirror MIRROR] [--namespace-id NAMESPACE_ID]
[--operations-access-level OPERATIONS_ACCESS_LEVEL]
[--only-allow-merge-if-all-discussions-are-resolved ONLY_
˓→ALLOW_MERGE_IF_ALL_DISCUSSIONS_ARE_RESOLVED]
[--only-allow-merge-if-pipeline-succeeds ONLY_ALLOW_MERGE_
˓→IF_PIPELINE_SUCCEEDS]
[--packages-enabled PACKAGES_ENABLED]
[--pages-access-level PAGES_ACCESS_LEVEL]
[--requirements-access-level REQUIREMENTS_ACCESS_LEVEL]
[--printing-merge-request-link-enabled PRINTING_MERGE_
˓→REQUEST_LINK_ENABLED]
[--public-builds PUBLIC_BUILDUPS]
[--remove-source-branch-after-merge REMOVE_SOURCE_BRANCH_
˓→AFTER_MERGE]
[--repository-access-level REPOSITORY_ACCESS_LEVEL]
[--repository-storage REPOSITORY_STORAGE]
[--request-access-enabled REQUEST_ACCESS_ENABLED]
[--resolve-outdated-diff-discussions RESOLVE_OUTDATED_DIFF_
˓→DISCUSSIONS]
[--shared-runners-enabled SHARED_RUNNERS_ENABLED]
[--show-default-award-emojis SHOW_DEFAULT_AWARD_EMOJIS]
[--snippets-access-level SNIPPETS_ACCESS_LEVEL]
[--snippets-enabled SNIPPETS_ENABLED]
[--squash-option SQUASH_OPTION]
[--tag-list TAG_LIST] [--topics TOPICS]
[--template-name TEMPLATE_NAME]
[--template-project-id TEMPLATE_PROJECT_ID]
[--use-custom-template USE_CUSTOM_TEMPLATE]
[--visibility VISIBILITY]
[--wiki-access-level WIKI_ACCESS_LEVEL]
[--wiki-enabled WIKI_ENABLED]
```

-h, --help

```
show this help message and exit

--sudo <sudo>

--name <name>

--path <path>

--allow-merge-on-skipped-pipeline <allow_merge_on_skipped_pipeline>

--analytics-access-level <analytics_access_level>

--approvals-before-merge <approvals_before_merge>

--auto-cancel-pending-pipelines <auto_cancel_pending_pipelines>

--auto-devops-deploy-strategy <auto_devops_deploy_strategy>

--auto-devops-enabled <auto_devops_enabled>

--autoclose-referenced-issues <autoclose_referenced_issues>

--avatar <avatar>

--build-coverage-regex <build_coverage_regex>

--build-git-strategy <build_git_strategy>

--build-timeout <build_timeout>

--builds-access-level <builds_access_level>

--ci-config-path <ci_config_path>

--container-expiration-policy-attributes <container_expiration_policy_attributes>

--container-registry-enabled <container_registry_enabled>

--default-branch <default_branch>

--description <description>

--emails-disabled <emails_disabled>

--external-authorization-classification-label <external_authorization_classification_label>

--forking-access-level <forking_access_level>

--group-with-project-templates-id <group_with_project_templates_id>

--import-url <import_url>

--initialize-with-readme <initialize_with_readme>

--issues-access-level <issues_access_level>

--issues-enabled <issues_enabled>

--jobs-enabled <jobs_enabled>
```

```
--lfs-enabled <lfs_enabled>
--merge-method <merge_method>
--merge-pipelines-enabled <merge_pipelines_enabled>
--merge-requests-access-level <merge_requests_access_level>
--merge-requests-enabled <merge_requests_enabled>
--mirror-trigger-builds <mirror_trigger_builds>
--mirror <mirror>
--namespace-id <namespace_id>
--operations-access-level <operations_access_level>
--only-allow-merge-if-all-discussions-are-resolved <only_allow_merge_if_all_discussions_are_resolved>
--only-allow-merge-if-pipeline-succeeds <only_allow_merge_if_pipeline_succeeds>
--packages-enabled <packages_enabled>
--pages-access-level <pages_access_level>
--requirements-access-level <requirements_access_level>
--printing-merge-request-link-enabled <printing_merge_request_link_enabled>
--public-builds <public_builds>
--remove-source-branch-after-merge <remove_source_branch_after_merge>
--repository-access-level <repository_access_level>
--repository-storage <repository_storage>
--request-access-enabled <request_access_enabled>
--resolve-outdated-diff-discussions <resolve_outdated_diff_discussions>
--shared-runners-enabled <shared_runners_enabled>
--show-default-award-emojis <show_default_award_emojis>
--snippets-access-level <snippets_access_level>
--snippets-enabled <snippets_enabled>
--squash-option <squash_option>
--tag-list <tag_list>
--topics <topics>
--template-name <template_name>
--template-project-id <template_project_id>
--use-custom-template <use_custom_template>
```

```
--visibility <visibility>
--wiki-access-level <wiki_access_level>
--wiki-enabled <wiki_enabled>
```

gitlab project create-fork-relation

```
usage: gitlab project create-fork-relation [-h] --id ID --forked-from-id
                                         FORKED_FROM_ID
```

```
-h, --help
    show this help message and exit
--id <id>
--forked-from-id <forked_from_id>
```

gitlab project delete

```
usage: gitlab project delete [-h] [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>
```

gitlab project delete-fork-relation

```
usage: gitlab project delete-fork-relation [-h] --id ID
```

```
-h, --help
    show this help message and exit
--id <id>
```

gitlab project delete-merged-branches

```
usage: gitlab project delete-merged-branches [-h] --id ID
```

```
-h, --help
    show this help message and exit
--id <id>
```

gitlab project get

```
usage: gitlab project get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab project housekeeping

```
usage: gitlab project housekeeping [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project languages

```
usage: gitlab project languages [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project list

```
usage: gitlab project list [-h] [--sudo SUDO] [--archived ARCHIVED]
                           [--id-after ID_AFTER] [--id-before ID_BEFORE]
                           [--last-activity-after LAST_ACTIVITY_AFTER]
                           [--last-activity-before LAST_ACTIVITY_BEFORE]
                           [--membership MEMBERSHIP]
                           [--min-access-level MIN_ACCESS_LEVEL]
                           [--order-by ORDER_BY] [--owned OWNED]
                           [--repository-checksum-failed REPOSITORY_CHECKSUM_FAILED]
                           [--repository-storage REPOSITORY_STORAGE]
                           [--search-namespaces SEARCH_NAMESPACES]
                           [--search SEARCH] [--simple SIMPLE] [--sort SORT]
                           [--starred STARRED] [--statistics STATISTICS]
                           [--topic TOPIC] [--visibility VISIBILITY]
                           [--wiki-checksum-failed WIKI_CHECKSUM_FAILED]
                           [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                           [--with-issues-enabled WITH_ISSUES_ENABLED]
                           [--with-merge-requests-enabled WITH_MERGE_REQUESTS_ENABLED]
                           [--with-programming-language WITH_PROGRAMMING_LANGUAGE]
                           [--page PAGE] [--per-page PER_PAGE] [--get-all]
                           [--all]
```

```
-h, --help
    show this help message and exit

--sudo <sudo>

--archived <archived>

--id-after <id_after>

--id-before <id_before>

--last-activity-after <last_activity_after>

--last-activity-before <last_activity_before>

--membership <membership>

--min-access-level <min_access_level>

--order-by <order_by>

--owned <owned>

--repository-checksum-failed <repository_checksum_failed>

--repository-storage <repository_storage>

--search-namespaces <search_namespaces>

--search <search>

--simple <simple>

--sort <sort>

--starred <starred>

--statistics <statistics>

--topic <topic>

--visibility <visibility>

--wiki-checksum-failed <wiki_checksum_failed>

--with-custom-attributes <with_custom_attributes>

--with-issues-enabled <with_issues_enabled>

--with-merge-requests-enabled <with_merge_requests_enabled>

--with-programming-language <with_programming_language>

--page <page>

--per-page <per_page>

--get-all
    Return all items from the server, without pagination.

--all
    Deprecated. Use --get-all instead.
```

gitlab project mirror-pull

```
usage: gitlab project mirror-pull [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project repository-archive

```
usage: gitlab project repository-archive [-h] --id ID [--sha SHA]
                                         [--format FORMAT]
```

-h, --help

show this help message and exit

--id <id>

--sha <sha>

--format <format>

gitlab project repository-blob

```
usage: gitlab project repository-blob [-h] --id ID --sha SHA
```

-h, --help

show this help message and exit

--id <id>

--sha <sha>

gitlab project repository-compare

```
usage: gitlab project repository-compare [-h] --id ID --from- FROM_ --to TO
```

-h, --help

show this help message and exit

--id <id>

--from- <from_>

--to <to>

gitlab project repository-contributors

```
usage: gitlab project repository-contributors [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project repository-merge-base

```
usage: gitlab project repository-merge-base [-h] --id ID --refs REFS
```

-h, --help

show this help message and exit

--id <id>

--refs <refs>

gitlab project repository-raw-blob

```
usage: gitlab project repository-raw-blob [-h] --id ID --sha SHA
```

-h, --help

show this help message and exit

--id <id>

--sha <sha>

gitlab project repository-tree

```
usage: gitlab project repository-tree [-h] --id ID [--path PATH] [--ref REF]
                                     [--recursive RECURSIVE]
```

-h, --help

show this help message and exit

--id <id>

--path <path>

--ref <ref>

--recursive <recursive>

gitlab project restore

```
usage: gitlab project restore [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project search

```
usage: gitlab project search [-h] --id ID --scope SCOPE --search SEARCH
```

-h, --help

show this help message and exit

--id <id>

--scope <scope>

--search <search>

gitlab project share

```
usage: gitlab project share [-h] --id ID --group-id GROUP_ID --group-access
                           GROUP_ACCESS [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--id <id>

--group-id <group_id>

--group-access <group_access>

--expires-at <expires_at>

gitlab project snapshot

```
usage: gitlab project snapshot [-h] --id ID [--wiki WIKI]
```

-h, --help

show this help message and exit

--id <id>

--wiki <wiki>

gitlab project star

```
usage: gitlab project star [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project transfer

```
usage: gitlab project transfer [-h] --id ID --to-namespace TO_NAMESPACE
```

-h, --help

show this help message and exit

--id <id>

--to-namespace <to_namespace>

gitlab project transfer-project

```
usage: gitlab project transfer-project [-h] --id ID --to-namespace  
                                     TO_NAMESPACE
```

-h, --help

show this help message and exit

--id <id>

--to-namespace <to_namespace>

gitlab project trigger-pipeline

```
usage: gitlab project trigger-pipeline [-h] --id ID --ref REF --token TOKEN
```

-h, --help

show this help message and exit

--id <id>

--ref <ref>

--token <token>

gitlab project unarchive

```
usage: gitlab project unarchive [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project unshare

```
usage: gitlab project unshare [-h] --id ID --group-id GROUP_ID
```

-h, --help

show this help message and exit

--id <id>

--group-id <group_id>

gitlab project unstar

```
usage: gitlab project unstar [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab project update

```
usage: gitlab project update [-h] [--sudo SUDO] --id ID
                             [--allow-merge-on-skipped-pipeline ALLOW_MERGE_ON_SKIPPED_
                             ↵PIPELINE]
                             [--analytics-access-level ANALYTICS_ACCESS_LEVEL]
                             [--approvals-before-merge APPROVALS_BEFORE_MERGE]
                             [--auto-cancel-pending-pipelines AUTO_CANCEL_PENDING_
                             ↵PIPELINES]
                             [--auto-devops-deploy-strategy AUTO_DEVOPS_DEPLOY_STRATEGY]
                             [--auto-devops-enabled AUTO_DEVOPS_ENABLED]
                             [--autoclose-referenced-issues AUTOCLOSE_REFERENCED_ISSUES]
                             [--avatar AVATAR]
                             [--build-coverage-regex BUILD_COVERAGE_REGEX]
                             [--build-git-strategy BUILD_GIT_STRATEGY]
                             [--build-timeout BUILD_TIMEOUT]
                             [--builds-access-level BUILDS_ACCESS_LEVEL]
                             [--ci-config-path CI_CONFIG_PATH]
                             [--ci-default-git-depth CI_DEFAULT_GIT_DEPTH]
                             [--ci-forward-deployment-enabled CI_FORWARD_DEPLOYMENT_
                             ↵ENABLED]
```

(continues on next page)

(continued from previous page)

```

[--container-expiration-policy-attributes CONTAINER_
˓→EXPIRATION_POLICY_ATTRIBUTES]
    [--container-registry-enabled CONTAINER_REGISTRY_ENABLED]
    [--default-branch DEFAULT_BRANCH]
    [--description DESCRIPTION]
    [--emails-disabled EMAILS_DISABLED]
    [--external-authorization-classification-label EXTERNAL_
˓→AUTHORIZATION_CLASSIFICATION_LABEL]
        [--forking-access-level FORKING_ACCESS_LEVEL]
        [--import-url IMPORT_URL]
        [--issues-access-level ISSUES_ACCESS_LEVEL]
        [--issues-enabled ISSUES_ENABLED]
        [--jobs-enabled JOBS_ENABLED]
        [--lfs-enabled LFS_ENABLED]
        [--merge-method MERGE_METHOD]
        [--merge-pipelines-enabled MERGE_PIPELINES_ENABLED]
        [--merge-requests-access-level MERGE_REQUESTS_ACCESS_LEVEL]
        [--merge-requests-enabled MERGE_REQUESTS_ENABLED]
        [--mirror-overwrites-diverged-branches MIRROR_OVERWRITES_
˓→DIVERGED_BRANCHES]
            [--mirror-trigger-builds MIRROR_TRIGGER_BUILDS]
            [--mirror-user-id MIRROR_USER_ID]
            [--mirror MIRROR] [--name NAME]
            [--operations-access-level OPERATIONS_ACCESS_LEVEL]
            [--only-allow-merge-if-all-discussions-are-resolved ONLY_
˓→ALLOW_MERGE_IF_ALL_DISCUSSIONS_ARE_RESOLVED]
                [--only-allow-merge-if-pipeline-succeeds ONLY_ALLOW_MERGE_
˓→IF_PIPELINE_SUCCEEDS]
                    [--only-mirror-protected-branches ONLY_MIRROR_PROTECTED_
˓→BRANCHES]
                        [--packages-enabled PACKAGES_ENABLED]
                        [--pages-access-level PAGES_ACCESS_LEVEL]
                        [--requirements-access-level REQUIREMENTS_ACCESS_LEVEL]
                        [--restrict-user-defined-variables RESTRICT_USER_DEFINED_
˓→VARIABLES]
                            [--path PATH] [--public-builds PUBLIC_BUILD]
                            [--remove-source-branch-after-merge REMOVE_SOURCE_BRANCH_
˓→AFTER_MERGE]
                                [--repository-access-level REPOSITORY_ACCESS_LEVEL]
                                [--repository-storage REPOSITORY_STORAGE]
                                [--request-access-enabled REQUEST_ACCESS_ENABLED]
                                [--resolve-outdated-diff-discussions RESOLVE_OUTDATED_DIFF_
˓→DISCUSSIONS]
                                    [--service-desk-enabled SERVICE_DESK_ENABLED]
                                    [--shared-runners-enabled SHARED_RUNNERS_ENABLED]
                                    [--show-default-award-emojis SHOW_DEFAULT_AWARD_EMOJIS]
                                    [--snippets-access-level SNIPPETS_ACCESS_LEVEL]
                                    [--snippets-enabled SNIPPETS_ENABLED]
                                    [--squash-option SQUASH_OPTION]
                                    [--suggestion-commit-message SUGGESTION_COMMIT_MESSAGE]
                                    [--tag-list TAG_LIST] [--topics TOPICS]
                                    [--visibility VISIBILITY]

```

(continues on next page)

(continued from previous page)

```
[--wiki-access-level WIKI_ACCESS_LEVEL]
[--wiki-enabled WIKI_ENABLED]
[--issues-template ISSUES_TEMPLATE]
[--merge-requests-template MERGE_REQUESTS_TEMPLATE]
```

-h, --help

show this help message and exit

--sudo <sudo>**--id <id>****--allow-merge-on-skipped-pipeline <allow_merge_on_skipped_pipeline>****--analytics-access-level <analytics_access_level>****--approvals-before-merge <approvals_before_merge>****--auto-cancel-pending-pipelines <auto_cancel_pending_pipelines>****--auto-devops-deploy-strategy <auto_devops_deploy_strategy>****--auto-devops-enabled <auto_devops_enabled>****--autoclose-referenced-issues <autoclose_referenced_issues>****--avatar <avatar>****--build-coverage-regex <build_coverage_regex>****--build-git-strategy <build_git_strategy>****--build-timeout <build_timeout>****--builds-access-level <builds_access_level>****--ci-config-path <ci_config_path>****--ci-default-git-depth <ci_default_git_depth>****--ci-forward-deployment-enabled <ci_forward_deployment_enabled>****--container-expiration-policy-attributes <container_expiration_policy_attributes>****--container-registry-enabled <container_registry_enabled>****--default-branch <default_branch>****--description <description>****--emails-disabled <emails_disabled>****--external-authorization-classification-label <external_authorization_classification_label>****--forking-access-level <forking_access_level>****--import-url <import_url>****--issues-access-level <issues_access_level>**

```
--issues-enabled <issues_enabled>
--jobs-enabled <jobs_enabled>
--lfs-enabled <lfs_enabled>
--merge-method <merge_method>
--merge-pipelines-enabled <merge_pipelines_enabled>
--merge-requests-access-level <merge_requests_access_level>
--merge-requests-enabled <merge_requests_enabled>
--mirror-overwrites-diverged-branches <mirror_overwrites_diverged_branches>
--mirror-trigger-builds <mirror_trigger_builds>
--mirror-user-id <mirror_user_id>
--mirror <mirror>
--name <name>
--operations-access-level <operations_access_level>
--only-allow-merge-if-all-discussions-are-resolved <only_allow_merge_if_all_discussions_are_resolved>
--only-allow-merge-if-pipeline-succeeds <only_allow_merge_if_pipeline_succeeds>
--only-mirror-protected-branches <only_mirror_protected_branches>
--packages-enabled <packages_enabled>
--pages-access-level <pages_access_level>
--requirements-access-level <requirements_access_level>
--restrict-user-defined-variables <restrict_user_defined_variables>
--path <path>
--public-builds <public_builds>
--remove-source-branch-after-merge <remove_source_branch_after_merge>
--repository-access-level <repository_access_level>
--repository-storage <repository_storage>
--request-access-enabled <request_access_enabled>
--resolve-outdated-diff-discussions <resolve_outdated_diff_discussions>
--service-desk-enabled <service_desk_enabled>
--shared-runners-enabled <shared_runners_enabled>
--show-default-award-emojis <show_default_award_emojis>
--snippets-access-level <snippets_access_level>
```

```
--snippets-enabled <snippets_enabled>
--squash-option <squash_option>
--suggestion-commit-message <suggestion_commit_message>
--tag-list <tag_list>
--topics <topics>
--visibility <visibility>
--wiki-access-level <wiki_access_level>
--wiki-enabled <wiki_enabled>
--issues-template <issues_template>
--merge-requests-template <merge_requests_template>
```

gitlab project update-submodule

```
usage: gitlab project update-submodule [-h] --id ID --submodule SUBMODULE
                                         --branch BRANCH --commit-sha COMMIT_SHA
```

-h, --help

show this help message and exit

--id <id>

--submodule <submodule>

--branch <branch>

--commit-sha <commit_sha>

gitlab project upload

```
usage: gitlab project upload [-h] --id ID --filename FILENAME --filepath
                             FILEPATH
```

-h, --help

show this help message and exit

--id <id>

--filename <filename>

--filepath <filepath>

gitlab project-access-request

```
usage: gitlab project-access-request [-h] {list,create,delete,approve} ...
```

-h, --help

show this help message and exit

gitlab project-access-request approve

```
usage: gitlab project-access-request approve [-h] --project-id PROJECT_ID
                                              [--sudo SUDO] --id ID
                                              [--access-level ACCESS_LEVEL]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--access-level <access_level>

gitlab project-access-request create

```
usage: gitlab project-access-request create [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-access-request delete

```
usage: gitlab project-access-request delete [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-access-request list

```
usage: gitlab project-access-request list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID [--page PAGE]  
                                         [--per-page PER_PAGE] [--get-all]  
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-access-token

```
usage: gitlab project-access-token [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-access-token create

```
usage: gitlab project-access-token create [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --name NAME --scopes  
                                         SCOPES [--access-level ACCESS_LEVEL]  
                                         [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--scopes <scopes>

--access-level <access_level>

--expires-at <expires_at>

gitlab project-access-token delete

```
usage: gitlab project-access-token delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--id <id>****gitlab project-access-token list**

```
usage: gitlab project-access-token list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID [--page PAGE]  
                                         [--per-page PER_PAGE] [--get-all]  
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-additional-statistics

```
usage: gitlab project-additional-statistics [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-additional-statistics get

```
usage: gitlab project-additional-statistics get [-h] [--sudo SUDO]
                                               --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-approval

```
usage: gitlab project-approval [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab project-approval get

```
usage: gitlab project-approval get [-h] [--sudo SUDO] --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-approval update

```
usage: gitlab project-approval update [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID
                                      [--approvals-before-merge APPROVALS_BEFORE_MERGE]
                                      [--reset-approvals-on-push RESET_APPROVALS_ON_PUSH]
                                      [--disable-overriding-approvers-per-merge-request
                                       ↵DISABLE_OVERRIDING_APPROVERS_PER_MERGE_REQUEST]
                                      [--merge-requests-author-approval MERGE_REQUESTS_
                                       ↵AUTHOR_APPROVAL]
                                      [--merge-requests-disable-committers-approval
                                       ↵MERGE_REQUESTS_DISABLE_COMMITTERS_APPROVAL]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--approvals-before-merge <approvals_before_merge>

```
--reset-approvals-on-push <reset_approvals_on_push>
--disable-overriding-approvers-per-merge-request <disable_overriding_approvers_per_merge_request>
--merge-requests-author-approval <merge_requests_author_approval>
--merge-requests-disable-committers-approval <merge_requests_disable_committers_approval>
```

gitlab project-approval-rule

```
usage: gitlab project-approval-rule [-h] {list,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-approval-rule create

```
usage: gitlab project-approval-rule create [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --name NAME
                                             --approvals-required
                                             APPROVALS_REQUIRED
                                             [--user-ids USER_IDS]
                                             [--group-ids GROUP_IDS]
                                             [--protected-branch-ids PROTECTED_BRANCH_IDS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--approvals-required <approvals_required>

--user-ids <user_ids>

--group-ids <group_ids>

--protected-branch-ids <protected_branch_ids>

gitlab project-approval-rule delete

```
usage: gitlab project-approval-rule delete [-h] [--sudo SUDO] --project-id
                                            PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-approval-rule list

```
usage: gitlab project-approval-rule list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID [--page PAGE]  
                                         [--per-page PER_PAGE] [--get-all]  
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-approval-rule update

```
usage: gitlab project-approval-rule update [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-artifact

```
usage: gitlab project-artifact [-h] {delete,download,raw} ...
```

-h, --help

show this help message and exit

gitlab project-artifact delete

```
usage: gitlab project-artifact delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --ref-name REF_NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--ref-name <ref_name>

gitlab project-artifact download

```
usage: gitlab project-artifact download [-h] --project-id PROJECT_ID  
[--sudo SUDO] --ref-name REF_NAME  
--job JOB [--job-token JOB_TOKEN]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--ref-name <ref_name>

--job <job>

--job-token <job_token>

gitlab project-artifact raw

```
usage: gitlab project-artifact raw [-h] --project-id PROJECT_ID [--sudo SUDO]  
--ref-name REF_NAME --artifact-path  
ARTIFACT_PATH --job JOB
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--ref-name <ref_name>

--artifact-path <artifact_path>

--job <job>

gitlab project-audit-event

```
usage: gitlab project-audit-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-audit-event get

```
usage: gitlab project-audit-event get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-audit-event list

```
usage: gitlab project-audit-event list [-h] [--sudo SUDO] --project-id  
PROJECT_ID  
[--created-after CREATED_AFTER]  
[--created-before CREATED_BEFORE]  
[--page PAGE] [--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--created-after <created_after>

--created-before <created_before>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-badge

```
usage: gitlab project-badge [-h] {list,get,create,update,delete,render} ...
```

-h, --help

show this help message and exit

gitlab project-badge create

```
usage: gitlab project-badge create [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  --link-url LINK_URL --image-url IMAGE_URL
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--link-url <link_url>

--image-url <image_url>

gitlab project-badge delete

```
usage: gitlab project-badge delete [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-badge get

```
usage: gitlab project-badge get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-badge list

```
usage: gitlab project-badge list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 [--page PAGE] [--per-page PER_PAGE]
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-badge render

```
usage: gitlab project-badge render [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID --link-url LINK_URL --image-url
                                   IMAGE_URL
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--link-url <link_url>

--image-url <image_url>

gitlab project-badge update

```
usage: gitlab project-badge update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID [--link-url LINK_URL]
                                   [--image-url IMAGE_URL]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--id <id>
--link-url <link_url>
--image-url <image_url>
```

gitlab project-board

```
usage: gitlab project-board [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-board create

```
usage: gitlab project-board create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-board delete

```
usage: gitlab project-board delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-board get

```
usage: gitlab project-board get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>  
--id <id>
```

gitlab project-board list

```
usage: gitlab project-board list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 [--page PAGE] [--per-page PER_PAGE]  
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-board update

```
usage: gitlab project-board update [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-board-list

```
usage: gitlab project-board-list [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-board-list create

```
usage: gitlab project-board-list create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --board-id BOARD_ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--board-id <board_id>****gitlab project-board-list delete**

```
usage: gitlab project-board-list delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --board-id BOARD_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--board-id <board_id>****--id <id>****gitlab project-board-list get**

```
usage: gitlab project-board-list get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --board-id BOARD_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--board-id <board_id>****--id <id>**

gitlab project-board-list list

```
usage: gitlab project-board-list list [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --board-id BOARD_ID
                                      [--page PAGE] [--per-page PER_PAGE]
                                      [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-board-list update

```
usage: gitlab project-board-list update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --board-id BOARD_ID --id ID
                                         --position POSITION
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--board-id <board_id>

--id <id>

--position <position>

gitlab project-branch

```
usage: gitlab project-branch [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-branch create

```
usage: gitlab project-branch create [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   --branch BRANCH --ref REF
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--branch <branch>

--ref <ref>

gitlab project-branch delete

```
usage: gitlab project-branch delete [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-branch get

```
usage: gitlab project-branch get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-branch list

```
usage: gitlab project-branch list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  [--page PAGE] [--per-page PER_PAGE]
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab project-ci-lint

```
usage: gitlab project-ci-lint [-h] {get,create,validate} ...
```

-h, --help

show this help message and exit

gitlab project-ci-lint create

```
usage: gitlab project-ci-lint create [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --content CONTENT
                                      [--dry-run DRY_RUN]
                                      [--include-jobs INCLUDE_JOBS] [--ref REF]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--content <content>

--dry-run <dry_run>

--include-jobs <include_jobs>

--ref <ref>

gitlab project-ci-lint get

```
usage: gitlab project-ci-lint get [-h] [--sudo SUDO] --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-ci-lint validate

```
usage: gitlab project-ci-lint validate [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --content CONTENT
                                         [--dry-run DRY_RUN]
                                         [--include-jobs INCLUDE_JOBS]
                                         [--ref REF]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--content <content>

--dry-run <dry_run>

--include-jobs <include_jobs>

--ref <ref>

gitlab project-cluster

```
usage: gitlab project-cluster [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-cluster create

```
usage: gitlab project-cluster create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --name NAME
                                         --platform-kubernetes-attributes
                                         PLATFORM_KUBERNETES_ATTRIBUTES
                                         [--domain DOMAIN] [--enabled ENABLED]
                                         [--managed MANAGED]
                                         [--environment-scope ENVIRONMENT_SCOPE]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--name <name>
--platform-kubernetes-attributes <platform_kubernetes_attributes>
--domain <domain>
--enabled <enabled>
--managed <managed>
--environment-scope <environment_scope>
```

gitlab project-cluster delete

```
usage: gitlab project-cluster delete [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-cluster get

```
usage: gitlab project-cluster get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-cluster list

```
usage: gitlab project-cluster list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  [--page PAGE] [--per-page PER_PAGE]
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab project-cluster update

```
usage: gitlab project-cluster update [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --id ID [--name NAME]
                                     [--domain DOMAIN]
                                     [--management-project-id MANAGEMENT_PROJECT_ID]
                                     [--platform-kubernetes-attributes PLATFORM_
                                     ↵KUBERNETES_ATTRIBUTES]
                                     [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--name <name>

--domain <domain>

--management-project-id <management_project_id>

--platform-kubernetes-attributes <platform_kubernetes_attributes>

--environment-scope <environment_scope>

gitlab project-commit

```
usage: gitlab project-commit [-h]
  list
  get
  create
  diff
  cherry-pick
  refs
  merge-requests
  revert
  signature
  ...
  ...
```

-h, --help

show this help message and exit

gitlab project-commit cherry-pick

```
usage: gitlab project-commit cherry-pick [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --id ID --branch BRANCH
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--branch <branch>

gitlab project-commit create

```
usage: gitlab project-commit create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                    --branch BRANCH --commit-message
                                    COMMIT_MESSAGE --actions ACTIONS
                                    [--author-email AUTHOR_EMAIL]
                                    [--author-name AUTHOR_NAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--branch <branch>

--commit-message <commit_message>

--actions <actions>

```
--author-email <author_email>  
--author-name <author_name>
```

gitlab project-commit diff

```
usage: gitlab project-commit diff [-h] --project-id PROJECT_ID [--sudo SUDO]  
                                 --id ID
```

```
-h, --help  
    show this help message and exit  
--project-id <project_id>  
--sudo <sudo>  
--id <id>
```

gitlab project-commit get

```
usage: gitlab project-commit get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 --id ID
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>  
--id <id>
```

gitlab project-commit list

```
usage: gitlab project-commit list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 [--ref-name REF_NAME] [--since SINCE]  
                                 [--until UNTIL] [--path PATH]  
                                 [--with-stats WITH_STATS]  
                                 [--first-parent FIRST_PARENT]  
                                 [--order ORDER] [--trailers TRAILERS]  
                                 [--page PAGE] [--per-page PER_PAGE]  
                                 [--get-all] [--all]
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>  
--ref-name <ref_name>
```

```
--since <since>
--until <until>
--path <path>
--with-stats <with_stats>
--first-parent <first_parent>
--order <order>
--trailers <trailers>
--page <page>
--per-page <per_page>
--get-all
```

Return all items from the server, without pagination.

```
--all
```

Deprecated. Use --get-all instead.

gitlab project-commit merge-requests

```
usage: gitlab project-commit merge-requests [-h] --project-id PROJECT_ID
                                            [--sudo SUDO] --id ID
```

```
-h, --help
```

show this help message and exit

```
--project-id <project_id>
```

```
--sudo <sudo>
```

```
--id <id>
```

gitlab project-commit refs

```
usage: gitlab project-commit refs [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID [--type TYPE]
```

```
-h, --help
```

show this help message and exit

```
--project-id <project_id>
```

```
--sudo <sudo>
```

```
--id <id>
```

```
--type <type>
```

gitlab project-commit revert

```
usage: gitlab project-commit revert [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID --branch BRANCH
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--branch <branch>

gitlab project-commit signature

```
usage: gitlab project-commit signature [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-commit-comment

```
usage: gitlab project-commit-comment [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab project-commit-comment create

```
usage: gitlab project-commit-comment create [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --commit-id COMMIT_ID
                                             --note NOTE [--path PATH]
                                             [--line LINE]
                                             [--line-type LINE_TYPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--commit-id <commit_id>
--note <note>
--path <path>
--line <line>
--line-type <line_type>
```

gitlab project-commit-comment list

```
usage: gitlab project-commit-comment list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --commit-id COMMIT_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-commit-discussion

```
usage: gitlab project-commit-discussion [-h] {list,get,create} ...
```

-h, --help

show this help message and exit

gitlab project-commit-discussion create

```
usage: gitlab project-commit-discussion create [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --commit-id
                                               COMMIT_ID --body BODY
                                               [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--commit-id <commit_id>
--body <body>
--created-at <created_at>
```

gitlab project-commit-discussion get

```
usage: gitlab project-commit-discussion get [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --commit-id COMMIT_ID
                                             --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--commit-id <commit_id>
--id <id>
```

gitlab project-commit-discussion list

```
usage: gitlab project-commit-discussion list [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --commit-id COMMIT_ID
                                              [--page PAGE]
                                              [--per-page PER_PAGE] [--get-all]
                                              [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--commit-id <commit_id>
--page <page>
--per-page <per_page>
--get-all
      Return all items from the server, without pagination.
--all
      Deprecated. Use --get-all instead.
```

gitlab project-commit-discussion-note

```
usage: gitlab project-commit-discussion-note [-h]
  get
  create
  update
  delete} ...
```

-h, --help

show this help message and exit

gitlab project-commit-discussion-note create

```
usage: gitlab project-commit-discussion-note create [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --commit-id COMMIT_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --body BODY
                                                    [--created-at CREATED_AT]
                                                    [--position POSITION]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--discussion-id <discussion_id>

--body <body>

--created-at <created_at>

--position <position>

gitlab project-commit-discussion-note delete

```
usage: gitlab project-commit-discussion-note delete [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --commit-id COMMIT_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--commit-id <commit_id>
--discussion-id <discussion_id>
--id <id>
```

gitlab project-commit-discussion-note get

```
usage: gitlab project-commit-discussion-note get [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --commit-id COMMIT_ID
                                                --discussion-id DISCUSSION_ID
                                                --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--commit-id <commit_id>
```

```
--discussion-id <discussion_id>
```

```
--id <id>
```

gitlab project-commit-discussion-note update

```
usage: gitlab project-commit-discussion-note update [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --commit-id COMMIT_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --id ID
                                                    --body BODY
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--commit-id <commit_id>
```

```
--discussion-id <discussion_id>
```

```
--id <id>
```

```
--body <body>
```

gitlab project-commit-status

```
usage: gitlab project-commit-status [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab project-commit-status create

```
usage: gitlab project-commit-status create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --commit-id COMMIT_ID
                                         --state STATE
                                         [--description DESCRIPTION]
                                         [--name NAME] [--context CONTEXT]
                                         [--ref REF]
                                         [--target-url TARGET_URL]
                                         [--coverage COVERAGE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--commit-id <commit_id>

--state <state>

--description <description>

--name <name>

--context <context>

--ref <ref>

--target-url <target_url>

--coverage <coverage>

gitlab project-commit-status list

```
usage: gitlab project-commit-status list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --commit-id COMMIT_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--commit-id <commit_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-custom-attribute

```
usage: gitlab project-custom-attribute [-h] {list,get,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-custom-attribute delete

```
usage: gitlab project-custom-attribute delete [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --key KEY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--key <key>
```

gitlab project-custom-attribute get

```
usage: gitlab project-custom-attribute get [-h] [--sudo SUDO] --project-id
                                            PROJECT_ID --key KEY
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--key <key>
```

gitlab project-custom-attribute list

```
usage: gitlab project-custom-attribute list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-deploy-token

```
usage: gitlab project-deploy-token [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-deploy-token create

```
usage: gitlab project-deploy-token create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --name NAME --scopes  
SCOPES [--expires-at EXPIRES_AT]  
[--username USERNAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--scopes <scopes>

--expires-at <expires_at>

--username <username>

gitlab project-deploy-token delete

```
usage: gitlab project-deploy-token delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-deploy-token get

```
usage: gitlab project-deploy-token get [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-deploy-token list

```
usage: gitlab project-deploy-token list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID [--scopes SCOPES]  
                                         [--page PAGE] [--per-page PER_PAGE]  
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--scopes <scopes>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-deployment

```
usage: gitlab project-deployment [-h] {list,get,create,update,approval} ...
```

-h, --help

show this help message and exit

gitlab project-deployment approval

```
usage: gitlab project-deployment approval [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --id ID --status
                                         STATUS [--comment COMMENT]
                                         [--represented-as REPRESENTED_AS]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--status <status>

--comment <comment>

--represented-as <represented_as>

gitlab project-deployment create

```
usage: gitlab project-deployment create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --sha SHA --ref REF --tag
                                         TAG --status STATUS --environment
                                         ENVIRONMENT
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--sha <sha>

--ref <ref>

--tag <tag>

--status <status>

--environment <environment>

gitlab project-deployment get

```
usage: gitlab project-deployment get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-deployment list

```
usage: gitlab project-deployment list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--order-by ORDER_BY]  
[--sort SORT]  
[--updated-after UPDATED_AFTER]  
[--updated-before UPDATED_BEFORE]  
[--environment ENVIRONMENT]  
[--status STATUS] [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--order-by <order_by>

--sort <sort>

--updated-after <updated_after>

--updated-before <updated_before>

--environment <environment>

--status <status>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-deployment update

```
usage: gitlab project-deployment update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-deployment-merge-request

```
usage: gitlab project-deployment-merge-request [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-deployment-merge-request list

```
usage: gitlab project-deployment-merge-request list [-h] [--sudo SUDO]  
--deployment-id  
DEPLOYMENT_ID --project-id  
PROJECT_ID [--state STATE]  
[--order-by ORDER_BY]  
[--sort SORT]  
[--milestone MILESTONE]  
[--view VIEW]  
[--labels LABELS]  
[--with-labels-details WITH_LABELS_  
↳ DETAILS]  
[--with-merge-status-recheck WITH_  
↳ MERGE_STATUS_RECHECK]  
[--created-after CREATED_AFTER]  
[--created-before CREATED_BEFORE]  
[--updated-after UPDATED_AFTER]  
[--updated-before UPDATED_BEFORE]  
[--scope SCOPE]  
[--author-id AUTHOR_ID]  
[--author-username AUTHOR_USERNAME]  
[--assignee-id ASSIGNEE_ID]  
[--approver-ids APPROVER_IDS]  
[--approved-by-ids APPROVED_BY_IDS]  
[--reviewer-id REVIEWER_ID]  
[--reviewer-username REVIEWER_  
↳ USERNAME]  
[--my-reaction-emoji MY_REACTION_  
↳ EMOJI]
```

(continues on next page)

(continued from previous page)

```
[--source-branch SOURCE_BRANCH]
[--target-branch TARGET_BRANCH]
[--search SEARCH]
[--in IN] [--wip WIP]
[--not NOT]
[--environment ENVIRONMENT]
[--deployed-before DEPLOYED_BEFORE]
[--deployed-after DEPLOYED_AFTER]
[--page PAGE]
[--per-page PER_PAGE]
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--deployment-id <deployment_id>****--project-id <project_id>****--state <state>****--order-by <order_by>****--sort <sort>****--milestone <milestone>****--view <view>****--labels <labels>****--with-labels-details <with_labels_details>****--with-merge-status-recheck <with_merge_status_recheck>****--created-after <created_after>****--created-before <created_before>****--updated-after <updated_after>****--updated-before <updated_before>****--scope <scope>****--author-id <author_id>****--author-username <author_username>****--assignee-id <assignee_id>****--approver-ids <approver_ids>****--approved-by-ids <approved_by_ids>****--reviewer-id <reviewer_id>**

```
--reviewer-username <reviewer_username>
--my-reaction-emoji <my_reaction_emoji>
--source-branch <source_branch>
--target-branch <target_branch>
--search <search>
--in <in>
--wip <wip>
--not <not>
--environment <environment>
--deployed-before <deployed_before>
--deployed-after <deployed_after>
--page <page>
--per-page <per_page>
--get-all
```

Return all items from the server, without pagination.

```
--all
```

Deprecated. Use --get-all instead.

gitlab project-environment

```
usage: gitlab project-environment [-h]
    list
    get
    create
    update
    delete
    stop} ...
```

```
-h, --help
```

show this help message and exit

gitlab project-environment create

```
usage: gitlab project-environment create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --name NAME
                                         [--external-url EXTERNAL_URL]
```

```
-h, --help
```

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--name <name>
--external-url <external_url>
```

gitlab project-environment delete

```
usage: gitlab project-environment delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-environment get

```
usage: gitlab project-environment get [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
```

gitlab project-environment list

```
usage: gitlab project-environment list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--name NAME]
                                         [--search SEARCH] [--states STATES]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--name <name>
```

```
--search <search>
--states <states>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-environment stop

```
usage: gitlab project-environment stop [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>
```

gitlab project-environment update

```
usage: gitlab project-environment update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --id ID [--name NAME]
                                         [--external-url EXTERNAL_URL]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
--name <name>
--external-url <external_url>
```

gitlab project-event

```
usage: gitlab project-event [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-event list

```
usage: gitlab project-event list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 [--action ACTION] [--target-type TARGET_TYPE]
                                 [--before BEFORE] [--after AFTER]
                                 [--sort SORT] [--page PAGE]
                                 [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--action <action>

--target-type <target_type>

--before <before>

--after <after>

--sort <sort>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-export

```
usage: gitlab project-export [-h] {get,create,download} ...
```

-h, --help

show this help message and exit

gitlab project-export create

```
usage: gitlab project-export create [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  [--description DESCRIPTION]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--description <description>

gitlab project-export download

```
usage: gitlab project-export download [-h] --project-id PROJECT_ID  
                                     [--sudo SUDO]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

gitlab project-export get

```
usage: gitlab project-export get [-h] [--sudo SUDO] --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-file

```
usage: gitlab project-file [-h] {get,create,update,delete,raw,blame} ...
```

-h, --help

show this help message and exit

gitlab project-file blame

```
usage: gitlab project-file blame [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --file-path FILE_PATH --ref REF
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--ref <ref>

gitlab project-file create

```
usage: gitlab project-file create [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --file-path FILE_PATH --branch BRANCH
                                 --content CONTENT --commit-message
                                 COMMIT_MESSAGE [--encoding ENCODING]
                                 [--author-email AUTHOR_EMAIL]
                                 [--author-name AUTHOR_NAME]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--branch <branch>

--content <content>

--commit-message <commit_message>

--encoding <encoding>

--author-email <author_email>

--author-name <author_name>

gitlab project-file delete

```
usage: gitlab project-file delete [-h] --project-id PROJECT_ID [--sudo SUDO]
                                  --file-path FILE_PATH --branch BRANCH
                                  --commit-message COMMIT_MESSAGE
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--branch <branch>

--commit-message <commit_message>

gitlab project-file get

```
usage: gitlab project-file get [-h] --project-id PROJECT_ID [--sudo SUDO]
                               --file-path FILE_PATH --ref REF
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--ref <ref>

gitlab project-file raw

```
usage: gitlab project-file raw [-h] --project-id PROJECT_ID [--sudo SUDO]
                               --file-path FILE_PATH --ref REF
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--file-path <file_path>

--ref <ref>

gitlab project-file update

```
usage: gitlab project-file update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --file-path FILE_PATH --branch BRANCH
                                  --content CONTENT --commit-message
                                  COMMIT_MESSAGE [--encoding ENCODING]
                                  [--author-email AUTHOR_EMAIL]
                                  [--author-name AUTHOR_NAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--file-path <file_path>

--branch <branch>

--content <content>

--commit-message <commit_message>

--encoding <encoding>

--author-email <author_email>

--author-name <author_name>

gitlab project-fork

```
usage: gitlab project-fork [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab project-fork create

```
usage: gitlab project-fork create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  [--namespace NAMESPACE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--namespace <namespace>

gitlab project-fork list

```
usage: gitlab project-fork list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                [--archived ARCHIVED]
                                [--visibility VISIBILITY]
                                [--order-by ORDER_BY] [--sort SORT]
                                [--search SEARCH] [--simple SIMPLE]
                                [--owned OWNED] [--membership MEMBERSHIP]
                                [--starred STARRED] [--statistics STATISTICS]
                                [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                [--with-issues-enabled WITH_ISSUES_ENABLED]
                                [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
                                ↵ENABLED]
                                [--page PAGE] [--per-page PER_PAGE]
                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--archived <archived>

--visibility <visibility>

--order-by <order_by>

--sort <sort>

--search <search>

--simple <simple>

--owned <owned>

--membership <membership>

--starred <starred>

--statistics <statistics>

--with-custom-attributes <with_custom_attributes>

--with-issues-enabled <with_issues_enabled>

--with-merge-requests-enabled <with_merge_requests_enabled>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-hook

```
usage: gitlab project-hook [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-hook create

```
usage: gitlab project-hook create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --url URL [--push-events PUSH_EVENTS]
                                  [--issues-events ISSUES_EVENTS]
                                  [--confidential-issues-events CONFIDENTIAL_ISSUES_
                                  EVENTS]
                                  [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                  [--tag-push-events TAG_PUSH_EVENTS]
                                  [--note-events NOTE_EVENTS]
                                  [--job-events JOB_EVENTS]
                                  [--pipeline-events PIPELINE_EVENTS]
                                  [--wiki-page-events WIKI_PAGE_EVENTS]
                                  [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                  [--token TOKEN]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--url <url>

--push-events <push_events>

--issues-events <issues_events>

--confidential-issues-events <confidential_issues_events>

--merge-requests-events <merge_requests_events>

--tag-push-events <tag_push_events>

--note-events <note_events>

--job-events <job_events>

--pipeline-events <pipeline_events>

--wiki-page-events <wiki_page_events>

--enable-ssl-verification <enable_ssl_verification>

--token <token>

gitlab project-hook delete

```
usage: gitlab project-hook delete [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-hook get

```
usage: gitlab project-hook get [-h] [--sudo SUDO] --project-id PROJECT_ID --id  
                               ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-hook list

```
usage: gitlab project-hook list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                [--page PAGE] [--per-page PER_PAGE]  
                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-hook update

```
usage: gitlab project-hook update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --id ID --url URL
                                  [--push-events PUSH_EVENTS]
                                  [--issues-events ISSUES_EVENTS]
                                  [--confidential-issues-events CONFIDENTIAL_ISSUES_
←EVENTS]
                                  [--merge-requests-events MERGE_REQUESTS_EVENTS]
                                  [--tag-push-events TAG_PUSH_EVENTS]
                                  [--note-events NOTE_EVENTS]
                                  [--job-events JOB_EVENTS]
                                  [--pipeline-events PIPELINE_EVENTS]
                                  [--wiki-events WIKI_EVENTS]
                                  [--enable-ssl-verification ENABLE_SSL_VERIFICATION]
                                  [--token TOKEN]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--url <url>

--push-events <push_events>

--issues-events <issues_events>

--confidential-issues-events <confidential_issues_events>

--merge-requests-events <merge_requests_events>

--tag-push-events <tag_push_events>

--note-events <note_events>

--job-events <job_events>

--pipeline-events <pipeline_events>

--wiki-events <wiki_events>

--enable-ssl-verification <enable_ssl_verification>

--token <token>

gitlab project-import

```
usage: gitlab project-import [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-import get

```
usage: gitlab project-import get [-h] [--sudo SUDO] --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-integration

```
usage: gitlab project-integration [-h] {list,get,update,delete,available} ...
```

-h, --help

show this help message and exit

gitlab project-integration available

```
usage: gitlab project-integration available [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --slug SLUG
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--slug <slug>

gitlab project-integration delete

```
usage: gitlab project-integration delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-integration get

```
usage: gitlab project-integration get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-integration list

```
usage: gitlab project-integration list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-integration update

```
usage: gitlab project-integration update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-invitation

```
usage: gitlab project-invitation [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-invitation create

```
usage: gitlab project-invitation create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --access-level ACCESS_LEVEL
                                         [--expires-at EXPIRES_AT]
                                         [--invite-source INVITE_SOURCE]
                                         [--tasks-to-be-done TASKS_TO_BE_DONE]
                                         [--tasks-project-id TASKS_PROJECT_ID]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--access-level <access_level>

--expires-at <expires_at>

--invite-source <invite_source>

--tasks-to-be-done <tasks_to_be_done>

--tasks-project-id <tasks_project_id>

gitlab project-invitation delete

```
usage: gitlab project-invitation delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --email EMAIL
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--email <email>

gitlab project-invitation get

```
usage: gitlab project-invitation get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --email EMAIL
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--email <email>

gitlab project-invitation list

```
usage: gitlab project-invitation list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--query QUERY] [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--query <query>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-invitation update

```
usage: gitlab project-invitation update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --email EMAIL  
[--access-level ACCESS_LEVEL]  
[--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--email <email>
--access-level <access_level>
--expires-at <expires_at>
```

gitlab project-issue

```
usage: gitlab project-issue [-h]
    list
    get
    create
    update
    delete
    user-agent-detail
    subscribe
    unsubscribe
    todo
    time-stats
    time-estimate
    reset-time-estimate
    add-spent-time
    reset-spent-time
    participants
    move
    reorder
    related-merge-requests
    closed-by
    ...
    ...
```

-h, --help

show this help message and exit

gitlab project-issue add-spent-time

```
usage: gitlab project-issue add-spent-time [-h] --project-id PROJECT_ID
                                            [--sudo SUDO] --iid IID --duration
                                            DURATION
```

-h, --help

show this help message and exit

```
--project-id <project_id>
--sudo <sudo>
--iid <iid>
--duration <duration>
```

gitlab project-issue closed-by

```
usage: gitlab project-issue closed-by [-h] --project-id PROJECT_ID  
                                     [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue create

```
usage: gitlab project-issue create [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                   --title TITLE [--description DESCRIPTION]  
                                   [--confidential CONFIDENTIAL]  
                                   [--assignee-ids ASSIGNEE_IDS]  
                                   [--assignee-id ASSIGNEE_ID]  
                                   [--milestone-id MILESTONE_ID]  
                                   [--labels LABELS] [--created-at CREATED_AT]  
                                   [--due-date DUE_DATE]  
                                   [--merge-request-to-resolve-discussions-of MERGE_  
→REQUEST_TO_RESOLVE_DISCUSSIONS_OF]  
                                   [--discussion-to-resolve DISCUSSION_TO_RESOLVE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--title <title>

--description <description>

--confidential <confidential>

--assignee-ids <assignee_ids>

--assignee-id <assignee_id>

--milestone-id <milestone_id>

--labels <labels>

--created-at <created_at>

--due-date <due_date>

--merge-request-to-resolve-discussions-of <merge_request_to_resolve_discussions_of>

--discussion-to-resolve <discussion_to_resolve>

gitlab project-issue delete

```
usage: gitlab project-issue delete [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  --iid IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iid <iid>

gitlab project-issue get

```
usage: gitlab project-issue get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 --iid IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iid <iid>

gitlab project-issue list

```
usage: gitlab project-issue list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 [--iids IIDS] [--state STATE]  
                                 [--labels LABELS] [--milestone MILESTONE]  
                                 [--scope SCOPE] [--author-id AUTHOR_ID]  
                                 [--assignee-id ASSIGNEE_ID]  
                                 [--my-reaction-emoji MY_REACTION_EMOJI]  
                                 [--order-by ORDER_BY] [--sort SORT]  
                                 [--search SEARCH]  
                                 [--created-after CREATED_AFTER]  
                                 [--created-before CREATED_BEFORE]  
                                 [--updated-after UPDATED_AFTER]  
                                 [--updated-before UPDATED_BEFORE]  
                                 [--page PAGE] [--per-page PER_PAGE]  
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iids <iids>

```
--state <state>
--labels <labels>
--milestone <milestone>
--scope <scope>
--author-id <author_id>
--assignee-id <assignee_id>
--my-reaction-emoji <my_reaction_emoji>
--order-by <order_by>
--sort <sort>
--search <search>
--created-after <created_after>
--created-before <created_before>
--updated-after <updated_after>
--updated-before <updated_before>
--page <page>
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issue move

```
usage: gitlab project-issue move [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --iid IID --to-project-id TO_PROJECT_ID
```

-h, --help

show this help message and exit

--project-id <project_id>**--sudo <sudo>****--iid <iid>****--to-project-id <to_project_id>**

gitlab project-issue participants

```
usage: gitlab project-issue participants [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue related-merge-requests

```
usage: gitlab project-issue related-merge-requests [-h] --project-id  
                                                 PROJECT_ID [--sudo SUDO]  
                                                 --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue reorder

```
usage: gitlab project-issue reorder [-h] --project-id PROJECT_ID [--sudo SUDO]  
                                    --iid IID --move-after-id MOVE_AFTER_ID  
                                    --move-before-id MOVE_BEFORE_ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--move-after-id <move_after_id>

--move-before-id <move_before_id>

gitlab project-issue reset-spent-time

```
usage: gitlab project-issue reset-spent-time [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue reset-time-estimate

```
usage: gitlab project-issue reset-time-estimate [-h] --project-id PROJECT_ID  
                                                [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue subscribe

```
usage: gitlab project-issue subscribe [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-issue time-estimate

```
usage: gitlab project-issue time-estimate [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --iid IID --duration  
                                         DURATION
```

-h, --help

show this help message and exit

--project-id <project_id>

```
--sudo <sudo>
--iid <iid>
--duration <duration>
```

gitlab project-issue time-stats

```
usage: gitlab project-issue time-stats [-h] --project-id PROJECT_ID
                                       [--sudo SUDO] --iid IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-issue todo

```
usage: gitlab project-issue todo [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --iid IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-issue unsubscribe

```
usage: gitlab project-issue unsubscribe [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --iid IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-issue update

```
usage: gitlab project-issue update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --iid IID [--title TITLE]
                                  [--description DESCRIPTION]
                                  [--confidential CONFIDENTIAL]
                                  [--assignee-ids ASSIGNEE_IDS]
                                  [--assignee-id ASSIGNEE_ID]
                                  [--milestone-id MILESTONE_ID]
                                  [--labels LABELS]
                                  [--state-event STATE_EVENT]
                                  [--updated-at UPDATED_AT]
                                  [--due-date DUE_DATE]
                                  [--discussion-locked DISCUSSION_LOCKED]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iid <iid>

--title <title>

--description <description>

--confidential <confidential>

--assignee-ids <assignee_ids>

--assignee-id <assignee_id>

--milestone-id <milestone_id>

--labels <labels>

--state-event <state_event>

--updated-at <updated_at>

--due-date <due_date>

--discussion-locked <discussion_locked>

gitlab project-issue user-agent-detail

```
usage: gitlab project-issue user-agent-detail [-h] --project-id PROJECT_ID
                                              [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

```
--sudo <sudo>
--iid <iid>
```

gitlab project-issue-award-emoji

```
usage: gitlab project-issue-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-issue-award-emoji create

```
usage: gitlab project-issue-award-emoji create [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --issue-iid
                                               ISSUE_IID --name NAME
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--issue-iid <issue_iid>
```

```
--name <name>
```

gitlab project-issue-award-emoji delete

```
usage: gitlab project-issue-award-emoji delete [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --issue-iid
                                               ISSUE_IID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--issue-iid <issue_iid>
```

```
--id <id>
```

gitlab project-issue-award-emoji get

```
usage: gitlab project-issue-award-emoji get [-h] [--sudo SUDO] --project-id  
                                PROJECT_ID --issue-iid ISSUE_IID  
                                --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-award-emoji list

```
usage: gitlab project-issue-award-emoji list [-h] [--sudo SUDO] --project-id  
                                PROJECT_ID --issue-iid ISSUE_IID  
                                [--page PAGE]  
                                [--per-page PER_PAGE] [--get-all]  
                                [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issue-discussion

```
usage: gitlab project-issue-discussion [-h] {list,get,create} ...
```

-h, --help

show this help message and exit

gitlab project-issue-discussion create

```
usage: gitlab project-issue-discussion create [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --issue-iid ISSUE_IID
                                              --body BODY
                                              [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--body <body>

--created-at <created_at>

gitlab project-issue-discussion get

```
usage: gitlab project-issue-discussion get [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --issue-iid ISSUE_IID
                                             --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-discussion list

```
usage: gitlab project-issue-discussion list [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --issue-iid ISSUE_IID
                                              [--page PAGE]
                                              [--per-page PER_PAGE] [--get-all]
                                              [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

```
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-issue-discussion-note

```
usage: gitlab project-issue-discussion-note [-h]
  get
  create
  update
  delete} ...
```

-h, --help
show this help message and exit

gitlab project-issue-discussion-note create

```
usage: gitlab project-issue-discussion-note create [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --discussion-id
                                                 DISCUSSION_ID --body BODY
                                                 [--created-at CREATED_AT]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--discussion-id <discussion_id>

--body <body>

--created-at <created_at>

gitlab project-issue-discussion-note delete

```
usage: gitlab project-issue-discussion-note delete [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --discussion-id
                                                 DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--discussion-id <discussion_id>

--id <id>

gitlab project-issue-discussion-note get

```
usage: gitlab project-issue-discussion-note get [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --discussion-id DISCUSSION_ID
                                                 --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--discussion-id <discussion_id>

--id <id>

gitlab project-issue-discussion-note update

```
usage: gitlab project-issue-discussion-note update [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --discussion-id
                                                 DISCUSSION_ID --id ID
                                                 --body BODY
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--discussion-id <discussion_id>
--id <id>
--body <body>
```

gitlab project-issue-link

```
usage: gitlab project-issue-link [-h] {list,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-issue-link create

```
usage: gitlab project-issue-link create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --issue-iid ISSUE_IID
                                         --target-project-id TARGET_PROJECT_ID
                                         --target-issue-iid TARGET_ISSUE_IID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--target-project-id <target_project_id>
--target-issue-iid <target_issue_iid>
```

gitlab project-issue-link delete

```
usage: gitlab project-issue-link delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --issue-iid ISSUE_IID
                                         --issue-link-id ISSUE_LINK_ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--issue-link-id <issue_link_id>
```

gitlab project-issue-link list

```
usage: gitlab project-issue-link list [-h] [--sudo SUDO] --project-id  
PROJECT_ID --issue-iid ISSUE_IID  
[--page PAGE] [--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issue-note

```
usage: gitlab project-issue-note [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-issue-note create

```
usage: gitlab project-issue-note create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --issue-iid ISSUE_IID  
--body BODY [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--body <body>

--created-at <created_at>

gitlab project-issue-note delete

```
usage: gitlab project-issue-note delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --issue-iid ISSUE_IID --id  
                                         ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-note get

```
usage: gitlab project-issue-note get [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --issue-iid ISSUE_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-note list

```
usage: gitlab project-issue-note list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --issue-iid ISSUE_IID  
                                         [--page PAGE] [--per-page PER_PAGE]  
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issue-note update

```
usage: gitlab project-issue-note update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --issue-iid ISSUE_IID --id
                                         ID --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

--body <body>

gitlab project-issue-note-award-emoji

```
usage: gitlab project-issue-note-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-issue-note-award-emoji create

```
usage: gitlab project-issue-note-award-emoji create [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --note-id NOTE_ID --name
                                                 NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--note-id <note_id>

--name <name>

gitlab project-issue-note-award-emoji delete

```
usage: gitlab project-issue-note-award-emoji delete [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --note-id NOTE_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--note-id <note_id>

--id <id>

gitlab project-issue-note-award-emoji get

```
usage: gitlab project-issue-note-award-emoji get [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --note-id NOTE_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--note-id <note_id>

--id <id>

gitlab project-issue-note-award-emoji list

```
usage: gitlab project-issue-note-award-emoji list [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --issue-iid ISSUE_IID
                                                 --note-id NOTE_ID
                                                 [--page PAGE]
                                                 [--per-page PER_PAGE]
                                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--note-id <note_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-issue-resource-label-event

```
usage: gitlab project-issue-resource-label-event [-h] {list,get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-issue-resource-label-event get

```
usage: gitlab project-issue-resource-label-event get [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--issue-iid <issue_iid>
--id <id>
```

gitlab project-issue-resource-label-event list

```
usage: gitlab project-issue-resource-label-event list [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --issue-iid ISSUE_IID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--issue-iid <issue_iid>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issue-resource-milestone-event

```
usage: gitlab project-issue-resource-milestone-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-issue-resource-milestone-event get

```
usage: gitlab project-issue-resource-milestone-event get [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID
                                                       --issue-iid ISSUE_IID
                                                       --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--issue-iid <issue_iid>****--id <id>**

gitlab project-issue-resource-milestone-event list

```
usage: gitlab project-issue-resource-milestone-event list [-h] [--sudo SUDO]
                           --project-id
                           PROJECT_ID
                           --issue-iid
                           ISSUE_IID
                           [--page PAGE]
                           [--per-page PER_PAGE]
                           [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab project-issue-resource-state-event

```
usage: gitlab project-issue-resource-state-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-issue-resource-state-event get

```
usage: gitlab project-issue-resource-state-event get [-h] [--sudo SUDO]
                           --project-id PROJECT_ID
                           --issue-iid ISSUE_IID
                           --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--id <id>

gitlab project-issue-resource-state-event list

```
usage: gitlab project-issue-resource-state-event list [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --issue-iid ISSUE_IID
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--issue-iid <issue_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-issues-statistics

```
usage: gitlab project-issues-statistics [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-issues-statistics get

```
usage: gitlab project-issues-statistics get [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

gitlab project-job

```
usage: gitlab project-job [-h]
  list
  get
  cancel
  retry
  play
  erase
  keep-artifacts
  delete-artifacts
  artifacts
  artifact
  trace
  ...
  ...
```

-h, --help

show this help message and exit

gitlab project-job artifact

```
usage: gitlab project-job artifact [-h] --project-id PROJECT_ID [--sudo SUDO]
                                   --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job artifacts

```
usage: gitlab project-job artifacts [-h] --project-id PROJECT_ID [--sudo SUDO]
                                    --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job cancel

```
usage: gitlab project-job cancel [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job delete-artifacts

```
usage: gitlab project-job delete-artifacts [-h] --project-id PROJECT_ID
                                            [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job erase

```
usage: gitlab project-job erase [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job get

```
usage: gitlab project-job get [-h] [--sudo SUDO] --project-id PROJECT_ID --id
                               ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--id <id>
```

gitlab project-job keep-artifacts

```
usage: gitlab project-job keep-artifacts [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>
```

gitlab project-job list

```
usage: gitlab project-job list [-h] [--sudo SUDO] --project-id PROJECT_ID
                               [--scope SCOPE] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--scope <scope>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-job play

```
usage: gitlab project-job play [-h] --project-id PROJECT_ID [--sudo SUDO] --id
                               ID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
```

```
--sudo <sudo>  
--id <id>
```

gitlab project-job retry

```
usage: gitlab project-job retry [-h] --project-id PROJECT_ID [--sudo SUDO]  
                                --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-job trace

```
usage: gitlab project-job trace [-h] --project-id PROJECT_ID [--sudo SUDO]  
                                --id ID
```

-h, --help
show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-key

```
usage: gitlab project-key [-h] {list,get,create,update,delete,enable} ...
```

-h, --help
show this help message and exit

gitlab project-key create

```
usage: gitlab project-key create [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                --title TITLE --key KEY [--can-push CAN_PUSH]
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--title <title>
--key <key>
--can-push <can_push>
```

gitlab project-key delete

```
usage: gitlab project-key delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-key enable

```
usage: gitlab project-key enable [-h] --project-id PROJECT_ID [--sudo SUDO]
                                 --id ID --key-id KEY_ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

--key-id <key_id>

gitlab project-key get

```
usage: gitlab project-key get [-h] [--sudo SUDO] --project-id PROJECT_ID --id
                               ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-key list

```
usage: gitlab project-key list [-h] [--sudo SUDO] --project-id PROJECT_ID
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]
                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-key update

```
usage: gitlab project-key update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --id ID [--title TITLE] [--can-push CAN_PUSH]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--title <title>

--can-push <can_push>

gitlab project-label

```
usage: gitlab project-label [-h]
    list
    get
    create
    update
    delete
    subscribe
    unsubscribe
    ...
```

-h, --help

show this help message and exit

gitlab project-label create

```
usage: gitlab project-label create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --name NAME --color COLOR
                                  [--description DESCRIPTION]
                                  [--priority PRIORITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--color <color>

--description <description>

--priority <priority>

gitlab project-label delete

```
usage: gitlab project-label delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-label get

```
usage: gitlab project-label get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-label list

```
usage: gitlab project-label list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 [--page PAGE] [--per-page PER_PAGE]
                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-label subscribe

```
usage: gitlab project-label subscribe [-h] --project-id PROJECT_ID
                                      [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--name <name>

gitlab project-label unsubscribe

```
usage: gitlab project-label unsubscribe [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --name NAME
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--name <name>

gitlab project-label update

```
usage: gitlab project-label update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --name NAME [--new-name NEW_NAME]
                                  [--color COLOR] [--description DESCRIPTION]
                                  [--priority PRIORITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--new-name <new_name>

--color <color>

--description <description>

--priority <priority>

gitlab project-member

```
usage: gitlab project-member [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-member create

```
usage: gitlab project-member create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                    --access-level ACCESS_LEVEL --user-id
                                    USER_ID [--expires-at EXPIRES_AT]
                                    [--tasks-to-be-done TASKS_TO_BE_DONE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--access-level <access_level>

--user-id <user_id>

--expires-at <expires_at>

--tasks-to-be-done <tasks_to_be_done>

gitlab project-member delete

```
usage: gitlab project-member delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-member get

```
usage: gitlab project-member get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-member list

```
usage: gitlab project-member list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   [--page PAGE] [--per-page PER_PAGE]
                                   [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-member update

```
usage: gitlab project-member update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --id ID --access-level ACCESS_LEVEL
                                   [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--access-level <access_level>

--expires-at <expires_at>

gitlab project-member-all

```
usage: gitlab project-member-all [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-member-all get

```
usage: gitlab project-member-all get [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-member-all list

```
usage: gitlab project-member-all list [-h] [--sudo SUDO] --project-id
                                       PROJECT_ID [--page PAGE]
                                       [--per-page PER_PAGE] [--get-all]
                                       [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-merge-request

```
usage: gitlab project-merge-request [-h]
  list
  get
  create
  update
  delete
  subscribe
  unsubscribe
  todo
  time-stats
  time-estimate
  reset-time-estimate
  add-spent-time
  reset-spent-time
  participants
  cancel-merge-when-pipeline-succeeds
  closes-issues
  commits
  changes
  approve
  unapprove
  rebase
  reset-approvals
  merge-ref
  merge
  ...
  
```

-h, --help

show this help message and exit

gitlab project-merge-request add-spent-time

```
usage: gitlab project-merge-request add-spent-time [-h] --project-id
                                                 PROJECT_ID [--sudo SUDO]
                                                 --iid IID --duration
                                                 DURATION
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--duration <duration>

gitlab project-merge-request approve

```
usage: gitlab project-merge-request approve [-h] --project-id PROJECT_ID
                                             [--sudo SUDO] --iid IID
                                             [--sha SHA]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--sha <sha>

gitlab project-merge-request cancel-merge-when-pipeline-succeeds

```
usage: gitlab project-merge-request cancel-merge-when-pipeline-succeeds
      [-h] --project-id PROJECT_ID [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request changes

```
usage: gitlab project-merge-request changes [-h] --project-id PROJECT_ID
                                            [--sudo SUDO] --iid IID
                                            [--access-raw-diffs ACCESS_RAW_DIFFS]
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

--access-raw-diffs <access_raw_diffs>

gitlab project-merge-request closes-issues

```
usage: gitlab project-merge-request closes-issues [-h] --project-id PROJECT_ID
                                                 [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request commits

```
usage: gitlab project-merge-request commits [-h] --project-id PROJECT_ID
                                             [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request create

```
usage: gitlab project-merge-request create [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --source-branch
                                             SOURCE_BRANCH --target-branch
                                             TARGET_BRANCH --title TITLE
                                             [--allow-collaboration ALLOW_COLLABORATION]
                                             [--allow-maintainer-to-push ALLOW_MAINTAINER_
                                             ↵TO_PUSH]
                                             [--approvals-before-merge APPROVALS_BEFORE_
                                             ↵MERGE]
                                             [--assignee-id ASSIGNEE_ID]
                                             [--assignee-ids ASSIGNEE_IDS]
                                             [--description DESCRIPTION]
                                             [--labels LABELS]
                                             [--milestone-id MILESTONE_ID]
                                             [--remove-source-branch REMOVE_SOURCE_BRANCH]
                                             [--reviewer-ids REVIEWER_IDS]
                                             [--squash SQUASH]
                                             [--target-project-id TARGET_PROJECT_ID]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--source-branch <source_branch>

--target-branch <target_branch>

--title <title>

--allow-collaboration <allow_collaboration>

--allow-maintainer-to-push <allow_maintainer_to_push>

--approvals-before-merge <approvals_before_merge>

--assignee-id <assignee_id>

--assignee-ids <assignee_ids>

--description <description>

--labels <labels>

--milestone-id <milestone_id>

--remove-source-branch <remove_source_branch>

--reviewer-ids <reviewer_ids>

--squash <squash>

--target-project-id <target_project_id>

gitlab project-merge-request delete

```
usage: gitlab project-merge-request delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --iid IID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--iid <iid>****gitlab project-merge-request get**

```
usage: gitlab project-merge-request get [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --iid IID
                                         [--render-html RENDER_HTML]
                                         [--include-diverged-commits-count INCLUDE_
                                         ↵DIVERGED_COMMITS_COUNT]
                                         [--include-rebase-in-progress INCLUDE_REBASE_IN_
                                         ↵PROGRESS]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--iid <iid>****--render-html <render_html>****--include-diverged-commits-count <include_diverged_commits_count>****--include-rebase-in-progress <include_rebase_in_progress>****gitlab project-merge-request list**

```
usage: gitlab project-merge-request list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--state STATE]
                                         [--order-by ORDER_BY] [--sort SORT]
                                         [--milestone MILESTONE] [--view VIEW]
                                         [--labels LABELS]
                                         [--created-after CREATED_AFTER]
                                         [--created-before CREATED_BEFORE]
                                         [--updated-after UPDATED_AFTER]
                                         [--updated-before UPDATED_BEFORE]
                                         [--scope SCOPE] [-iids IIDS]
                                         [--author-id AUTHOR_ID]
                                         [--assignee-id ASSIGNEE_ID]
```

(continues on next page)

(continued from previous page)

```
[--approver-ids APPROVER_IDS]
[--approved-by-ids APPROVED_BY_IDS]
[--my-reaction-emoji MY_REACTION_EMOJI]
[--source-branch SOURCE_BRANCH]
[--target-branch TARGET_BRANCH]
[--search SEARCH] [--wip WIP]
[--page PAGE] [--per-page PER_PAGE]
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--state <state>****--order-by <order_by>****--sort <sort>****--milestone <milestone>****--view <view>****--labels <labels>****--created-after <created_after>****--created-before <created_before>****--updated-after <updated_after>****--updated-before <updated_before>****--scope <scope>****--iids <iids>****--author-id <author_id>****--assignee-id <assignee_id>****--approver-ids <approver_ids>****--approved-by-ids <approved_by_ids>****--my-reaction-emoji <my_reaction_emoji>****--source-branch <source_branch>****--target-branch <target_branch>****--search <search>****--wip <wip>**

```
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-merge-request merge

```
usage: gitlab project-merge-request merge [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --iid IID
                                         [--merge-commit-message MERGE_COMMIT_MESSAGE]
                                         [--should-remove-source-branch SHOULD_REMOVE_
                                         ↵SOURCE_BRANCH]
                                         [--merge-when-pipeline-succeeds MERGE_WHEN_
                                         ↵PIPELINE_SUCCEEDS]
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
--merge-commit-message <merge_commit_message>
--should-remove-source-branch <should_remove_source_branch>
--merge-when-pipeline-succeeds <merge_when_pipeline_succeeds>
```

gitlab project-merge-request merge-ref

```
usage: gitlab project-merge-request merge-ref [-h] --project-id PROJECT_ID
                                              [--sudo SUDO] --iid IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-merge-request participants

```
usage: gitlab project-merge-request participants [-h] --project-id PROJECT_ID  
                                                [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request rebase

```
usage: gitlab project-merge-request rebase [-h] --project-id PROJECT_ID  
                                            [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request reset-approvals

```
usage: gitlab project-merge-request reset-approvals [-h] --project-id  
                                                 PROJECT_ID [--sudo SUDO]  
                                                 --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request reset-spent-time

```
usage: gitlab project-merge-request reset-spent-time [-h] --project-id  
                                                 PROJECT_ID [--sudo SUDO]  
                                                 --iid IID
```

-h, --help

show this help message and exit

```
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-merge-request reset-time-estimate

```
usage: gitlab project-merge-request reset-time-estimate [-h] --project-id
                                                       PROJECT_ID
                                                       [--sudo SUDO] --iid
                                                       IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-merge-request subscribe

```
usage: gitlab project-merge-request subscribe [-h] --project-id PROJECT_ID
                                               [--sudo SUDO] --iid IID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
```

gitlab project-merge-request time-estimate

```
usage: gitlab project-merge-request time-estimate [-h] --project-id PROJECT_ID
                                                 [--sudo SUDO] --iid IID
                                                 --duration DURATION
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--iid <iid>
--duration <duration>
```

gitlab project-merge-request time-stats

```
usage: gitlab project-merge-request time-stats [-h] --project-id PROJECT_ID  
                                              [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request todo

```
usage: gitlab project-merge-request todo [-h] --project-id PROJECT_ID  
                                         [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request unapprove

```
usage: gitlab project-merge-request unapprove [-h] --project-id PROJECT_ID  
                                              [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--iid <iid>

gitlab project-merge-request unsubscribe

```
usage: gitlab project-merge-request unsubscribe [-h] --project-id PROJECT_ID  
                                                 [--sudo SUDO] --iid IID
```

-h, --help

show this help message and exit

--project-id <project_id>

```
--sudo <sudo>  
--iid <iid>
```

gitlab project-merge-request update

```
usage: gitlab project-merge-request update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --iid IID  
[--target-branch TARGET_BRANCH]  
[--assignee-id ASSIGNEE_ID]  
[--title TITLE]  
[--description DESCRIPTION]  
[--state-event STATE_EVENT]  
[--labels LABELS]  
[--milestone-id MILESTONE_ID]  
[--remove-source-branch REMOVE_SOURCE_BRANCH]  
[--discussion-locked DISCUSSION_LOCKED]  
[--allow-maintainer-to-push ALLOW_MAINTAINER_  
→ TO_PUSH]  
[--squash SQUASH]  
[--reviewer-ids REVIEWER_IDS]
```

-h, --help

show this help message and exit

```
--sudo <sudo>  
--project-id <project_id>  
--iid <iid>  
--target-branch <target_branch>  
--assignee-id <assignee_id>  
--title <title>  
--description <description>  
--state-event <state_event>  
--labels <labels>  
--milestone-id <milestone_id>  
--remove-source-branch <remove_source_branch>  
--discussion-locked <discussion_locked>  
--allow-maintainer-to-push <allow_maintainer_to_push>  
--squash <squash>  
--reviewer-ids <reviewer_ids>
```

gitlab project-merge-request-approval

```
usage: gitlab project-merge-request-approval [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-approval get

```
usage: gitlab project-merge-request-approval get [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --mr-iid MR_IID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

gitlab project-merge-request-approval update

```
usage: gitlab project-merge-request-approval update [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID
                                                    --approvals-required
                                                    APPROVALS_REQUIRED
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--approvals-required <approvals_required>

gitlab project-merge-request-approval-rule

```
usage: gitlab project-merge-request-approval-rule [-h]
  list
  get
  create
  update
  delete
  ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-approval-rule create

```
usage: gitlab project-merge-request-approval-rule create [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID --id ID
                                                       --merge-request-iid
                                                       MERGE_REQUEST_IID
                                                       --name NAME
                                                       --approvals-required
                                                       APPROVALS_REQUIRED
                                                       [--approval-project-rule-id,
                                                       APPROPAL_PROJECT_RULE_ID]
                                                       [--user-ids USER_IDS]
                                                       [--group-ids GROUP_IDS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

--merge-request-iid <merge_request_iid>

--name <name>

--approvals-required <approvals_required>

--approval-project-rule-id <approval_project_rule_id>

--user-ids <user_ids>

--group-ids <group_ids>

gitlab project-merge-request-approval-rule delete

```
usage: gitlab project-merge-request-approval-rule delete [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--mr-iid <mr_iid>
--id <id>
```

gitlab project-merge-request-approval-rule get

```
usage: gitlab project-merge-request-approval-rule get [-h] [--sudo SUDO]
                                                     --project-id PROJECT_ID
                                                     --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--mr-iid <mr_iid>
```

```
--id <id>
```

gitlab project-merge-request-approval-rule list

```
usage: gitlab project-merge-request-approval-rule list [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--mr-iid <mr_iid>
```

```
--page <page>
```

```
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-approval-rule update

```
usage: gitlab project-merge-request-approval-rule update [-h] [--sudo SUDO]
                                         --project-id
                                         PROJECT_ID --mr-iid
                                         MR_IID --id ID
                                         --merge-request-iid
                                         MERGE_REQUEST_IID
                                         --approval-rule-id
                                         APPROVAL_RULE_ID
                                         --name NAME
                                         --approvals-required
                                         APPROVALS_REQUIRED
                                         [--user-ids USER_IDS]
                                         [--group-ids GROUP_IDS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

--merge-request-iid <merge_request_iid>

--approval-rule-id <approval_rule_id>

--name <name>

--approvals-required <approvals_required>

--user-ids <user_ids>

--group-ids <group_ids>

gitlab project-merge-request-approval-state

```
usage: gitlab project-merge-request-approval-state [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-approval-state get

```
usage: gitlab project-merge-request-approval-state get [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-award-emoji

```
usage: gitlab project-merge-request-award-emoji [-h]
                                              list
                                              get
                                              create
                                              delete} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-award-emoji create

```
usage: gitlab project-merge-request-award-emoji create [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --name
                                                       NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--name <name>

gitlab project-merge-request-award-emoji delete

```
usage: gitlab project-merge-request-award-emoji delete [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-award-emoji get

```
usage: gitlab project-merge-request-award-emoji get [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-award-emoji list

```
usage: gitlab project-merge-request-award-emoji list [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

```
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-merge-request-diff

```
usage: gitlab project-merge-request-diff [-h] {list,get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-merge-request-diff get

```
usage: gitlab project-merge-request-diff get [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --mr-iid MR_IID --id
                                              ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--id <id>
```

gitlab project-merge-request-diff list

```
usage: gitlab project-merge-request-diff list [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --mr-iid MR_IID
                                               [--page PAGE]
                                               [--per-page PER_PAGE]
                                               [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--page <page>
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-discussion

```
usage: gitlab project-merge-request-discussion [-h]
  list
  get
  create
  update} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-discussion create

```
usage: gitlab project-merge-request-discussion create [-h] [--sudo SUDO]
                                                      --project-id PROJECT_ID
                                                      --mr-iid MR_IID --body
                                                      BODY
                                                      [--created-at CREATED_AT]
                                                      [--position POSITION]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--mr-iid <mr_iid>****--body <body>****--created-at <created_at>****--position <position>****gitlab project-merge-request-discussion get**

```
usage: gitlab project-merge-request-discussion get [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--mr-iid <mr_iid>
--id <id>
```

gitlab project-merge-request-discussion list

```
usage: gitlab project-merge-request-discussion list [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --mr-iid MR_IID
                                                    [--page PAGE]
                                                    [--per-page PER_PAGE]
                                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-discussion update

```
usage: gitlab project-merge-request-discussion update [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --mr-iid MR_IID --id ID
                                                       --resolved RESOLVED
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

--resolved <resolved>

gitlab project-merge-request-discussion-note

```
usage: gitlab project-merge-request-discussion-note [-h]
  get
  create
  update
  delete
  ...
  
```

-h, --help

show this help message and exit

gitlab project-merge-request-discussion-note create

```
usage: gitlab project-merge-request-discussion-note create [-h] [--sudo SUDO]
                           --project-id
                           PROJECT_ID --mr-iid
                           MR_IID
                           --discussion-id
                           DISCUSSION_ID
                           --body BODY
                           [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--mr-iid <mr_iid>****--discussion-id <discussion_id>****--body <body>****--created-at <created_at>****gitlab project-merge-request-discussion-note delete**

```
usage: gitlab project-merge-request-discussion-note delete [-h] [--sudo SUDO]
                           --project-id
                           PROJECT_ID --mr-iid
                           MR_IID
                           --discussion-id
                           DISCUSSION_ID --id
                           ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--mr-iid <mr_iid>
--discussion-id <discussion_id>
--id <id>
```

gitlab project-merge-request-discussion-note get

```
usage: gitlab project-merge-request-discussion-note get [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID --discussion-id
                                                       DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--discussion-id <discussion_id>
--id <id>
```

gitlab project-merge-request-discussion-note update

```
usage: gitlab project-merge-request-discussion-note update [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID
                                                       --discussion-id
                                                       DISCUSSION_ID --id
                                                       ID --body BODY
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--discussion-id <discussion_id>
--id <id>
--body <body>
```

gitlab project-merge-request-note

```
usage: gitlab project-merge-request-note [-h]
  list
  get
  create
  update
  delete} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-note create

```
usage: gitlab project-merge-request-note create [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --mr-iid MR_IID --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--mr-iid <mr_iid>****--body <body>****gitlab project-merge-request-note delete**

```
usage: gitlab project-merge-request-note delete [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID
                                                --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--mr-iid <mr_iid>****--id <id>**

gitlab project-merge-request-note get

```
usage: gitlab project-merge-request-note get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --mr-iid MR_IID --id  
ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-note list

```
usage: gitlab project-merge-request-note list [-h] [--sudo SUDO] --project-id  
PROJECT_ID --mr-iid MR_IID  
[--page PAGE]  
[--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-note update

```
usage: gitlab project-merge-request-note update [-h] [--sudo SUDO]  
--project-id PROJECT_ID  
--mr-iid MR_IID --id ID --body  
BODY
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--id <id>
--body <body>
```

gitlab project-merge-request-note-award-emoji

```
usage: gitlab project-merge-request-note-award-emoji [-h]
    list
    get
    create
    delete
    ...
    ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-note-award-emoji create

```
usage: gitlab project-merge-request-note-award-emoji create
    [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --note-id
    NOTE_ID --name NAME
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--mr-iid <mr_iid>
--note-id <note_id>
--name <name>
```

gitlab project-merge-request-note-award-emoji delete

```
usage: gitlab project-merge-request-note-award-emoji delete
    [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --note-id
    NOTE_ID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
--mr-iid <mr_iid>
--note-id <note_id>
--id <id>
```

gitlab project-merge-request-note-award-emoji get

```
usage: gitlab project-merge-request-note-award-emoji get [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID --note-id
                                                       NOTE_ID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--mr-iid <mr_iid>
```

```
--note-id <note_id>
```

```
--id <id>
```

gitlab project-merge-request-note-award-emoji list

```
usage: gitlab project-merge-request-note-award-emoji list [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID --mr-iid
                                                       MR_IID --note-id
                                                       NOTE_ID
                                                       [--page PAGE]
                                                       [--per-page PER_PAGE]
                                                       [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--mr-iid <mr_iid>
```

```
--note-id <note_id>
```

```
--page <page>
```

```
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-pipeline

```
usage: gitlab project-merge-request-pipeline [-h] {list,create} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-pipeline create

```
usage: gitlab project-merge-request-pipeline create [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --mr-iid MR_IID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--mr-iid <mr_iid>****gitlab project-merge-request-pipeline list**

```
usage: gitlab project-merge-request-pipeline list [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --mr-iid MR_IID
                                                 [--page PAGE]
                                                 [--per-page PER_PAGE]
                                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--mr-iid <mr_iid>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-resource-label-event

```
usage: gitlab project-merge-request-resource-label-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-resource-label-event get

```
usage: gitlab project-merge-request-resource-label-event get
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-resource-label-event list

```
usage: gitlab project-merge-request-resource-label-event list
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID
      [--page PAGE] [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-resource-milestone-event

```
usage: gitlab project-merge-request-resource-milestone-event
      [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-resource-milestone-event get

```
usage: gitlab project-merge-request-resource-milestone-event get
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-resource-milestone-event list

```
usage: gitlab project-merge-request-resource-milestone-event list
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID
      [--page PAGE] [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-request-resource-state-event

```
usage: gitlab project-merge-request-resource-state-event [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab project-merge-request-resource-state-event get

```
usage: gitlab project-merge-request-resource-state-event get
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--id <id>

gitlab project-merge-request-resource-state-event list

```
usage: gitlab project-merge-request-resource-state-event list
      [-h] [--sudo SUDO] --project-id PROJECT_ID --mr-iid MR_IID
      [--page PAGE] [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--mr-iid <mr_iid>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-merge-train

```
usage: gitlab project-merge-train [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-merge-train list

```
usage: gitlab project-merge-train list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--scope SCOPE]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--scope <scope>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-milestone

```
usage: gitlab project-milestone [-h]
    list
    get
    create
    update
    delete
    issues
    merge-requests
    ...

```

-h, --help

show this help message and exit

gitlab project-milestone create

```
usage: gitlab project-milestone create [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --title TITLE
                                      [--description DESCRIPTION]
                                      [--due-date DUE_DATE]
                                      [--start-date START_DATE]
                                      [--state-event STATE_EVENT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--title <title>

--description <description>

--due-date <due_date>

--start-date <start_date>

--state-event <state_event>

gitlab project-milestone delete

```
usage: gitlab project-milestone delete [-h] [--sudo SUDO] --project-id
                                       PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-milestone get

```
usage: gitlab project-milestone get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                    --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-milestone issues

```
usage: gitlab project-milestone issues [-h] --project-id PROJECT_ID  
                                     [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-milestone list

```
usage: gitlab project-milestone list [-h] [--sudo SUDO] --project-id  
                                     PROJECT_ID [--iids IIDS] [--state STATE]  
                                     [--search SEARCH] [--page PAGE]  
                                     [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--iids <iids>

--state <state>

--search <search>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-milestone merge-requests

```
usage: gitlab project-milestone merge-requests [-h] --project-id PROJECT_ID  
                                              [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

```
--sudo <sudo>  
--id <id>
```

gitlab project-milestone update

```
usage: gitlab project-milestone update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID [--title TITLE]  
[--description DESCRIPTION]  
[--due-date DUE_DATE]  
[--start-date START_DATE]  
[--state-event STATE_EVENT]
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>  
--id <id>  
--title <title>  
--description <description>  
--due-date <due_date>  
--start-date <start_date>  
--state-event <state_event>
```

gitlab project-note

```
usage: gitlab project-note [-h] {list,get} ...
```

```
-h, --help  
    show this help message and exit
```

gitlab project-note get

```
usage: gitlab project-note get [-h] [--sudo SUDO] --project-id PROJECT_ID --id  
ID
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>  
--id <id>
```

gitlab project-note list

```
usage: gitlab project-note list [-h] [--sudo SUDO] --project-id PROJECT_ID
                               [--page PAGE] [--per-page PER_PAGE]
                               [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-notification-settings

```
usage: gitlab project-notification-settings [-h] {get,update} ...
```

-h, --help

show this help message and exit

gitlab project-notification-settings get

```
usage: gitlab project-notification-settings get [-h] [--sudo SUDO]
                                               --project-id PROJECT_ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****gitlab project-notification-settings update**

```
usage: gitlab project-notification-settings update [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 [--level LEVEL]
                                                 [--notification-email NOTIFICATION_
                                                 ↪EMAIL]
                                                 [--new-note NEW_NOTE]
                                                 [--new-issue NEW_ISSUE]
```

(continues on next page)

(continued from previous page)

↳ REQUEST]	[--reopen-issue REOPEN_ISSUE] [--close-issue CLOSE_ISSUE] [--reassign-issue REASSIGN_ISSUE] [--new-merge-request NEW_MERGE_
↳ REQUEST]	[--reopen-merge-request REOPEN_MERGE_
↳ REQUEST]	[--close-merge-request CLOSE_MERGE_
↳ MERGE_REQUEST]	[--reassign-merge-request REASSIGN_
↳ REQUEST]	[--merge-merge-request MERGE_MERGE_

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--level <level>****--notification-email <notification_email>****--new-note <new_note>****--new-issue <new_issue>****--reopen-issue <reopen_issue>****--close-issue <close_issue>****--reassign-issue <reassign_issue>****--new-merge-request <new_merge_request>****--reopen-merge-request <reopen_merge_request>****--close-merge-request <close_merge_request>****--reassign-merge-request <reassign_merge_request>****--merge-merge-request <merge_merge_request>****gitlab project-package**

usage: gitlab project-package [-h] {list,get,delete} ...

-h, --help

show this help message and exit

gitlab project-package delete

```
usage: gitlab project-package delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-package get

```
usage: gitlab project-package get [-h] [--sudo SUDO] --project-id PROJECT_ID  
--id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-package list

```
usage: gitlab project-package list [-h] [--sudo SUDO] --project-id PROJECT_ID  
[--order-by ORDER_BY] [--sort SORT]  
[--package-type PACKAGE_TYPE]  
[--package-name PACKAGE_NAME] [--page PAGE]  
[--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--order-by <order_by>

--sort <sort>

--package-type <package_type>

--package-name <package_name>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-package-file

```
usage: gitlab project-package-file [-h] {list,delete} ...
```

-h, --help

show this help message and exit

gitlab project-package-file delete

```
usage: gitlab project-package-file delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --package-id PACKAGE_ID
                                         --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--package-id <package_id>

--id <id>

gitlab project-package-file list

```
usage: gitlab project-package-file list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --package-id PACKAGE_ID
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--package-id <package_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-pages-domain

```
usage: gitlab project-pages-domain [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-pages-domain create

```
usage: gitlab project-pages-domain create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --domain DOMAIN
                                         [--certificate CERTIFICATE]
                                         [--key KEY]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--domain <domain>****--certificate <certificate>****--key <key>****gitlab project-pages-domain delete**

```
usage: gitlab project-pages-domain delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --domain DOMAIN
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--domain <domain>**

gitlab project-pages-domain get

```
usage: gitlab project-pages-domain get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --domain DOMAIN
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--domain <domain>

gitlab project-pages-domain list

```
usage: gitlab project-pages-domain list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-pages-domain update

```
usage: gitlab project-pages-domain update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --domain DOMAIN  
[--certificate CERTIFICATE]  
[--key KEY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--domain <domain>

```
--certificate <certificate>
--key <key>
```

gitlab project-pipeline

```
usage: gitlab project-pipeline [-h] {list,get,create,delete,cancel,retry} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline cancel

```
usage: gitlab project-pipeline cancel [-h] --project-id PROJECT_ID
                                      [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-pipeline create

```
usage: gitlab project-pipeline create [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --ref REF
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--ref <ref>

gitlab project-pipeline delete

```
usage: gitlab project-pipeline delete [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-pipeline get

```
usage: gitlab project-pipeline get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-pipeline list

```
usage: gitlab project-pipeline list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                    [--scope SCOPE] [--status STATUS]  
                                    [--ref REF] [--sha SHA]  
                                    [--yaml-errors YAML_ERRORS] [--name NAME]  
                                    [--username USERNAME]  
                                    [--order-by ORDER_BY] [--sort SORT]  
                                    [--page PAGE] [--per-page PER_PAGE]  
                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--scope <scope>

--status <status>

--ref <ref>

--sha <sha>

--yaml-errors <yaml_errors>

--name <name>

--username <username>

--order-by <order_by>

--sort <sort>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-pipeline retry

```
usage: gitlab project-pipeline retry [-h] --project-id PROJECT_ID  
                                     [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>**--sudo <sudo>****--id <id>****gitlab project-pipeline-bridge**

```
usage: gitlab project-pipeline-bridge [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-bridge list

```
usage: gitlab project-pipeline-bridge list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --pipeline-id  
                                         PIPELINE_ID [--scope SCOPE]  
                                         [--page PAGE] [--per-page PER_PAGE]  
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--pipeline-id <pipeline_id>****--scope <scope>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-pipeline-job

```
usage: gitlab project-pipeline-job [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-job list

```
usage: gitlab project-pipeline-job list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --pipeline-id PIPELINE_ID
                                         [--scope SCOPE]
                                         [--include-retried INCLUDE_RETRIED]
                                         [--page PAGE] [--per-page PER_PAGE]
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-id <pipeline_id>

--scope <scope>

--include-retried <include_retried>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-pipeline-schedule

```
usage: gitlab project-pipeline-schedule [-h]
  list
  get
  create
  update
  delete
  take-ownership
  play
  ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-schedule create

```
usage: gitlab project-pipeline-schedule create [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --description
                                               DESCRIPTION --ref REF --cron
                                               CRON
                                               [--cron-timezone CRON_TIMEZONE]
                                               [--active ACTIVE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--description <description>

--ref <ref>

--cron <cron>

--cron-timezone <cron_timezone>

--active <active>

gitlab project-pipeline-schedule delete

```
usage: gitlab project-pipeline-schedule delete [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-pipeline-schedule get

```
usage: gitlab project-pipeline-schedule get [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-pipeline-schedule list

```
usage: gitlab project-pipeline-schedule list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-pipeline-schedule play

```
usage: gitlab project-pipeline-schedule play [-h] --project-id PROJECT_ID  
[--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-pipeline-schedule take-ownership

```
usage: gitlab project-pipeline-schedule take-ownership [-h] --project-id  
PROJECT_ID  
[--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-pipeline-schedule update

```
usage: gitlab project-pipeline-schedule update [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --id ID
                                               [--description DESCRIPTION]
                                               [--ref REF] [--cron CRON]
                                               [--cron-timezone CRON_TIMEZONE]
                                               [--active ACTIVE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--description <description>

--ref <ref>

--cron <cron>

--cron-timezone <cron_timezone>

--active <active>

gitlab project-pipeline-schedule-variable

```
usage: gitlab project-pipeline-schedule-variable [-h]
  create
  update
  delete} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-schedule-variable create

```
usage: gitlab project-pipeline-schedule-variable create [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID
                                                       --pipeline-schedule-id
                                                       PIPELINE_SCHEDULE_ID
                                                       --key KEY --value
                                                       VALUE
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--pipeline-schedule-id <pipeline_schedule_id>
--key <key>
--value <value>
```

gitlab project-pipeline-schedule-variable delete

```
usage: gitlab project-pipeline-schedule-variable delete [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID
                                                       --pipeline-schedule-id
                                                       PIPELINE_SCHEDULE_ID
                                                       --key KEY
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-schedule-id <pipeline_schedule_id>

--key <key>

gitlab project-pipeline-schedule-variable update

```
usage: gitlab project-pipeline-schedule-variable update [-h] [--sudo SUDO]
                                                       --project-id
                                                       PROJECT_ID
                                                       --pipeline-schedule-id
                                                       PIPELINE_SCHEDULE_ID
                                                       --key KEY --value
                                                       VALUE
```

-h, --help
show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-schedule-id <pipeline_schedule_id>

--key <key>

--value <value>

gitlab project-pipeline-test-report

```
usage: gitlab project-pipeline-test-report [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-test-report get

```
usage: gitlab project-pipeline-test-report get [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --pipeline-id
                                               PIPELINE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-id <pipeline_id>

gitlab project-pipeline-test-report-summary

```
usage: gitlab project-pipeline-test-report-summary [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-test-report-summary get

```
usage: gitlab project-pipeline-test-report-summary get [-h] [--sudo SUDO]
                                                       --project-id PROJECT_ID
                                                       --pipeline-id
                                                       PIPELINE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-id <pipeline_id>

gitlab project-pipeline-variable

```
usage: gitlab project-pipeline-variable [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-pipeline-variable list

```
usage: gitlab project-pipeline-variable list [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --pipeline-id
                                             PIPELINE_ID [--page PAGE]
                                             [--per-page PER_PAGE] [--get-all]
                                             [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--pipeline-id <pipeline_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-protected-branch

```
usage: gitlab project-protected-branch [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-protected-branch create

```
usage: gitlab project-protected-branch create [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --name NAME
                                              [--push-access-level PUSH_ACCESS_LEVEL]
                                              [--merge-access-level MERGE_ACCESS_LEVEL]
                                              [--unprotect-access-level UNPROTECT_ACCESS_
                                              ↵LEVEL]
                                              [--allowed-to-push ALLOWED_TO_PUSH]
                                              [--allowed-to-merge ALLOWED_TO_MERGE]
```

(continues on next page)

(continued from previous page)

<code>↳UNPROTECT]</code> <code>↳APPROVAL_REQUIRED]</code>	<code>[--allowed-to-unprotect ALLOWED_TO_</code> <code>[--code-owner-approval-required CODE_OWNER_</code>
--	--

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--name <name>****--push-access-level <push_access_level>****--merge-access-level <merge_access_level>****--unprotect-access-level <unprotect_access_level>****--allowed-to-push <allowed_to_push>****--allowed-to-merge <allowed_to_merge>****--allowed-to-unprotect <allowed_to_unprotect>****--code-owner-approval-required <code_owner_approval_required>****gitlab project-protected-branch delete**

```
usage: gitlab project-protected-branch delete [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--name <name>****gitlab project-protected-branch get**

```
usage: gitlab project-protected-branch get [-h] [--sudo SUDO] --project-id
                                            PROJECT_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--name <name>**

gitlab project-protected-branch list

```
usage: gitlab project-protected-branch list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-protected-environment

```
usage: gitlab project-protected-environment [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-protected-environment create

```
usage: gitlab project-protected-environment create [-h] [--sudo SUDO]  
--project-id PROJECT_ID  
--name NAME  
--deploy-access-levels  
DEPLOY_ACCESS_LEVELS  
[--required-approval-count REQUIRED_  
APPROVAL_COUNT]  
[--approval-rules APPROVAL_RULES]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--deploy-access-levels <deploy_access_levels>

```
--required-approval-count <required_approval_count>
--approval-rules <approval_rules>
```

gitlab project-protected-environment delete

```
usage: gitlab project-protected-environment delete [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --name NAME
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--name <name>
```

gitlab project-protected-environment get

```
usage: gitlab project-protected-environment get [-h] [--sudo SUDO]
                                                --project-id PROJECT_ID --name
                                                NAME
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--name <name>
```

gitlab project-protected-environment list

```
usage: gitlab project-protected-environment list [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 [--page PAGE]
                                                 [--per-page PER_PAGE]
                                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--page <page>
```

```
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-protected-tag

```
usage: gitlab project-protected-tag [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-protected-tag create

```
usage: gitlab project-protected-tag create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --name NAME
                                         [--create-access-level CREATE_ACCESS_LEVEL]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

--create-access-level <create_access_level>

gitlab project-protected-tag delete

```
usage: gitlab project-protected-tag delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-protected-tag get

```
usage: gitlab project-protected-tag get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--name <name>****gitlab project-protected-tag list**

```
usage: gitlab project-protected-tag list [-h] [--sudo SUDO] --project-id  
PROJECT_ID [--page PAGE]  
[--per-page PER_PAGE] [--get-all]  
[--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-push-rules

```
usage: gitlab project-push-rules [-h] {get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-push-rules create

```
usage: gitlab project-push-rules create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID
                                         [--author-email-regex AUTHOR_EMAIL_REGEX]
                                         [--branch-name-regex BRANCH_NAME_REGEX]
                                         [--commit-committer-check COMMIT_COMMITTER_CHECK]
                                         [--commit-message-negative-regex COMMIT_MESSAGE_
                                         ↵NEGATIVE_REGEX]
                                         [--commit-message-regex COMMIT_MESSAGE_REGEX]
                                         [--deny-delete-tag DENY_DELETE_TAG]
                                         [--file-name-regex FILE_NAME_REGEX]
                                         [--max-file-size MAX_FILE_SIZE]
                                         [--member-check MEMBER_CHECK]
                                         [--prevent-secrets PREVENT_SECRETS]
                                         [--reject-unsigned-commits REJECT_UNSIGNED_
                                         ↵COMMITS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--author-email-regex <author_email_regex>

--branch-name-regex <branch_name_regex>

--commit-committer-check <commit_committer_check>

--commit-message-negative-regex <commit_message_negative_regex>

--commit-message-regex <commit_message_regex>

--deny-delete-tag <deny_delete_tag>

--file-name-regex <file_name_regex>

--max-file-size <max_file_size>

--member-check <member_check>

--prevent-secrets <prevent_secrets>

--reject-unsigned-commits <reject_unsigned_commits>

gitlab project-push-rules delete

```
usage: gitlab project-push-rules delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>  
--project-id <project_id>
```

gitlab project-push-rules get

```
usage: gitlab project-push-rules get [-h] [--sudo SUDO] --project-id  
PROJECT_ID
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>
```

gitlab project-push-rules update

```
usage: gitlab project-push-rules update [-h] [--sudo SUDO] --project-id  
PROJECT_ID  
[--author-email-regex AUTHOR_EMAIL_REGEX]  
[--branch-name-regex BRANCH_NAME_REGEX]  
[--commit-committer-check COMMIT_COMMITTER_CHECK]  
[--commit-message-negative-regex COMMIT_MESSAGE_  
NEGATIVE_REGEX]  
[--commit-message-regex COMMIT_MESSAGE_REGEX]  
[--deny-delete-tag DENY_DELETE_TAG]  
[--file-name-regex FILE_NAME_REGEX]  
[--max-file-size MAX_FILE_SIZE]  
[--member-check MEMBER_CHECK]  
[--prevent-secrets PREVENT_SECRETS]  
[--reject-unsigned-commits REJECT_UNSIGNED_  
COMMITTS]
```

```
-h, --help  
    show this help message and exit  
--sudo <sudo>  
--project-id <project_id>  
--author-email-regex <author_email_regex>  
--branch-name-regex <branch_name_regex>  
--commit-committer-check <commit_committer_check>  
--commit-message-negative-regex <commit_message_negative_regex>  
--commit-message-regex <commit_message_regex>  
--deny-delete-tag <deny_delete_tag>  
--file-name-regex <file_name_regex>
```

```
--max-file-size <max_file_size>
--member-check <member_check>
--prevent-secrets <prevent_secrets>
--reject-unsigned-commits <reject_unsigned_commits>
```

gitlab project-registry-repository

```
usage: gitlab project-registry-repository [-h] {list,delete} ...
```

-h, --help

show this help message and exit

gitlab project-registry-repository delete

```
usage: gitlab project-registry-repository delete [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID --id
                                                 ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-registry-repository list

```
usage: gitlab project-registry-repository list [-h] [--sudo SUDO] --project-id
                                                PROJECT_ID [--page PAGE]
                                                [--per-page PER_PAGE]
                                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-registry-tag

```
usage: gitlab project-registry-tag [-h] {list,get,delete,delete-in-bulk} ...
```

-h, --help

show this help message and exit

gitlab project-registry-tag delete

```
usage: gitlab project-registry-tag delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --repository-id
                                         REPOSITORY_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--repository-id <repository_id>

--name <name>

gitlab project-registry-tag delete-in-bulk

```
usage: gitlab project-registry-tag delete-in-bulk [-h] --project-id PROJECT_ID
                                                 --repository-id
                                                 REPOSITORY_ID [--sudo SUDO]
                                                 --name NAME
                                                 --name-regex-delete
                                                 NAME_REGEX_DELETE
                                                 [--keep-n KEEP_N]
                                                 [--name-regex-keep NAME_REGEX_KEEP]
                                                 [--older-than OLDER_THAN]
```

-h, --help

show this help message and exit

--project-id <project_id>

--repository-id <repository_id>

--sudo <sudo>

--name <name>

--name-regex-delete <name_regex_delete>

--keep-n <keep_n>

--name-regex-keep <name_regex_keep>

--older-than <older_than>

gitlab project-registry-tag get

```
usage: gitlab project-registry-tag get [-h] [--sudo SUDO] --project-id  
                                      PROJECT_ID --repository-id  
                                      REPOSITORY_ID --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--repository-id <repository_id>

--name <name>

gitlab project-registry-tag list

```
usage: gitlab project-registry-tag list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --repository-id  
                                         REPOSITORY_ID [--page PAGE]  
                                         [--per-page PER_PAGE] [--get-all]  
                                         [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--repository-id <repository_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-release

```
usage: gitlab project-release [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-release create

```
usage: gitlab project-release create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --tag-name TAG_NAME  
--description DESCRIPTION [--name NAME]  
[--ref REF] [--assets ASSETS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--description <description>

--name <name>

--ref <ref>

--assets <assets>

gitlab project-release delete

```
usage: gitlab project-release delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --tag-name TAG_NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

gitlab project-release get

```
usage: gitlab project-release get [-h] [--sudo SUDO] --project-id PROJECT_ID  
--tag-name TAG_NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

gitlab project-release list

```
usage: gitlab project-release list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  [--order-by ORDER_BY] [--sort SORT]
                                  [--include-html-description INCLUDE_HTML_DESCRIPTION]
                                  [--page PAGE] [--per-page PER_PAGE]
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--order-by <order_by>

--sort <sort>

--include-html-description <include_html_description>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-release update

```
usage: gitlab project-release update [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --tag-name TAG_NAME
                                      [--name NAME] [--description DESCRIPTION]
                                      [--milestones MILESTONES]
                                      [--released-at RELEASED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--name <name>

--description <description>

--milestones <milestones>

--released-at <released_at>

gitlab project-release-link

```
usage: gitlab project-release-link [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-release-link create

```
usage: gitlab project-release-link create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --tag-name TAG_NAME
                                         --name NAME --url URL
                                         [--filepath FILEPATH]
                                         [--link-type LINK_TYPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--name <name>

--url <url>

--filepath <filepath>

--link-type <link_type>

gitlab project-release-link delete

```
usage: gitlab project-release-link delete [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --tag-name TAG_NAME --id
                                         ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--id <id>

gitlab project-release-link get

```
usage: gitlab project-release-link get [-h] [--sudo SUDO] --project-id  
PROJECT_ID --tag-name TAG_NAME --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--id <id>

gitlab project-release-link list

```
usage: gitlab project-release-link list [-h] [--sudo SUDO] --project-id  
PROJECT_ID --tag-name TAG_NAME  
[--page PAGE] [--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-release-link update

```
usage: gitlab project-release-link update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --tag-name TAG_NAME --id  
ID [--name NAME] [--url URL]  
[--filepath FILEPATH]  
[--link-type LINK_TYPE]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--tag-name <tag_name>
--id <id>
--name <name>
--url <url>
--filepath <filepath>
--link-type <link_type>
```

gitlab project-remote-mirror

```
usage: gitlab project-remote-mirror [-h] {list,create,update} ...
```

-h, --help

show this help message and exit

gitlab project-remote-mirror create

```
usage: gitlab project-remote-mirror create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --url URL
                                         [--enabled ENABLED]
                                         [--only-protected-branches ONLY_PROTECTED_
                                         BRANCHES]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--url <url>

--enabled <enabled>

--only-protected-branches <only_protected_branches>

gitlab project-remote-mirror list

```
usage: gitlab project-remote-mirror list [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID [--page PAGE]
                                         [--per-page PER_PAGE] [--get-all]
                                         [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--project-id <project_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-remote-mirror update

```
usage: gitlab project-remote-mirror update [-h] [--sudo SUDO] --project-id
                                             PROJECT_ID --id ID
                                             [--enabled ENABLED]
                                             [--only-protected-branches ONLY_PROTECTED_
                                             BRANCHES]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--id <id>
--enabled <enabled>
--only-protected-branches <only_protected_branches>
```

gitlab project-runner

```
usage: gitlab project-runner [-h] {list,create,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-runner create

```
usage: gitlab project-runner create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                    --runner-id RUNNER_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--runner-id <runner_id>
```

gitlab project-runner delete

```
usage: gitlab project-runner delete [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-runner list

```
usage: gitlab project-runner list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  [--scope SCOPE] [--tag-list TAG_LIST]  
                                  [--page PAGE] [--per-page PER_PAGE]  
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--scope <scope>

--tag-list <tag_list>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-service

```
usage: gitlab project-service [-h] {list,get,update,delete,available} ...
```

-h, --help

show this help message and exit

gitlab project-service available

```
usage: gitlab project-service available [-h] --project-id PROJECT_ID  
                                      [--sudo SUDO] --slug SLUG
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--slug <slug>

gitlab project-service delete

```
usage: gitlab project-service delete [-h] [--sudo SUDO] --project-id  
                                     PROJECT_ID --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-service get

```
usage: gitlab project-service get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                 --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-service list

```
usage: gitlab project-service list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                    [--page PAGE] [--per-page PER_PAGE]  
                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab project-service update

```
usage: gitlab project-service update [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --slug SLUG
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--project-id <project_id>
--slug <slug>
```

gitlab project-snippet

```
usage: gitlab project-snippet [-h]
  list
  get
  create
  update
  delete
  user-agent-detail
  content
  ...
```

```
-h, --help
    show this help message and exit
```

gitlab project-snippet content

```
usage: gitlab project-snippet content [-h] --project-id PROJECT_ID
                                         [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--project-id <project_id>
--sudo <sudo>
--id <id>
```

gitlab project-snippet create

```
usage: gitlab project-snippet create [-h] [--sudo SUDO] --project-id  
PROJECT_ID --title TITLE --file-name  
FILE_NAME --content CONTENT --visibility  
VISIBILITY [--description DESCRIPTION]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--title <title>

--file-name <file_name>

--content <content>

--visibility <visibility>

--description <description>

gitlab project-snippet delete

```
usage: gitlab project-snippet delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-snippet get

```
usage: gitlab project-snippet get [-h] [--sudo SUDO] --project-id PROJECT_ID  
--id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-snippet list

```
usage: gitlab project-snippet list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  [--page PAGE] [--per-page PER_PAGE]
                                  [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab project-snippet update

```
usage: gitlab project-snippet update [-h] [--sudo SUDO] --project-id
                                      PROJECT_ID --id ID [--title TITLE]
                                      [--file-name FILE_NAME]
                                      [--content CONTENT]
                                      [--visibility VISIBILITY]
                                      [--description DESCRIPTION]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--title <title>

--file-name <file_name>

--content <content>

--visibility <visibility>

--description <description>

gitlab project-snippet user-agent-detail

```
usage: gitlab project-snippet user-agent-detail [-h] --project-id PROJECT_ID  
                                              [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--project-id <project_id>

--sudo <sudo>

--id <id>

gitlab project-snippet-award-emoji

```
usage: gitlab project-snippet-award-emoji [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-snippet-award-emoji create

```
usage: gitlab project-snippet-award-emoji create [-h] [--sudo SUDO]  
                                               --project-id PROJECT_ID  
                                               --snippet-id SNIPPET_ID  
                                               --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--name <name>

gitlab project-snippet-award-emoji delete

```
usage: gitlab project-snippet-award-emoji delete [-h] [--sudo SUDO]  
                                              --project-id PROJECT_ID  
                                              --snippet-id SNIPPET_ID --id  
                                              ID
```

-h, --help

show this help message and exit

--sudo <sudo>

```
--project-id <project_id>
--snippet-id <snippet_id>
--id <id>
```

gitlab project-snippet-award-emoji get

```
usage: gitlab project-snippet-award-emoji get [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --snippet-id
                                              SNIPPET_ID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--snippet-id <snippet_id>
```

```
--id <id>
```

gitlab project-snippet-award-emoji list

```
usage: gitlab project-snippet-award-emoji list [-h] [--sudo SUDO] --project-id
                                               PROJECT_ID --snippet-id
                                               SNIPPET_ID [--page PAGE]
                                               [--per-page PER_PAGE]
                                               [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--snippet-id <snippet_id>
```

```
--page <page>
```

```
--per-page <per_page>
```

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-snippet-discussion

```
usage: gitlab project-snippet-discussion [-h] {list,get,create} ...
```

-h, --help

show this help message and exit

gitlab project-snippet-discussion create

```
usage: gitlab project-snippet-discussion create [-h] [--sudo SUDO]
                                               --project-id PROJECT_ID
                                               --snippet-id SNIPPET_ID --body
                                               BODY [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--body <body>

--created-at <created_at>

gitlab project-snippet-discussion get

```
usage: gitlab project-snippet-discussion get [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --snippet-id
                                              SNIPPET_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--id <id>

gitlab project-snippet-discussion list

```
usage: gitlab project-snippet-discussion list [-h] [--sudo SUDO] --project-id
                                              PROJECT_ID --snippet-id
                                              SNIPPET_ID [--page PAGE]
                                              [--per-page PER_PAGE]
                                              [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--snippet-id <snippet_id>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-snippet-discussion-note

```
usage: gitlab project-snippet-discussion-note [-h]
      get
      create
      update
      delete} ...
```

-h, --help

show this help message and exit

gitlab project-snippet-discussion-note create

```
usage: gitlab project-snippet-discussion-note create [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --snippet-id SNIPPET_ID
                                                 --discussion-id
                                                 DISCUSSION_ID --body BODY
                                                 [--created-at CREATED_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>**

```
--snippet-id <snippet_id>
--discussion-id <discussion_id>
--body <body>
--created-at <created_at>
```

gitlab project-snippet-discussion-note delete

```
usage: gitlab project-snippet-discussion-note delete [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--discussion-id <discussion_id>

--id <id>

gitlab project-snippet-discussion-note get

```
usage: gitlab project-snippet-discussion-note get [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--discussion-id <discussion_id>

--id <id>

gitlab project-snippet-discussion-note update

```
usage: gitlab project-snippet-discussion-note update [-h] [--sudo SUDO]
                                                    --project-id PROJECT_ID
                                                    --snippet-id SNIPPET_ID
                                                    --discussion-id
                                                    DISCUSSION_ID --id ID
                                                    --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--discussion-id <discussion_id>

--id <id>

--body <body>

gitlab project-snippet-note

```
usage: gitlab project-snippet-note [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-snippet-note create

```
usage: gitlab project-snippet-note create [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --snippet-id SNIPPET_ID
                                         --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--body <body>

gitlab project-snippet-note delete

```
usage: gitlab project-snippet-note delete [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --snippet-id SNIPPET_ID  
                                         --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--id <id>

gitlab project-snippet-note get

```
usage: gitlab project-snippet-note get [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --snippet-id SNIPPET_ID --id  
                                         ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--id <id>

gitlab project-snippet-note list

```
usage: gitlab project-snippet-note list [-h] [--sudo SUDO] --project-id  
                                         PROJECT_ID --snippet-id SNIPPET_ID  
                                         [--page PAGE] [--per-page PER_PAGE]  
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-snippet-note update

```
usage: gitlab project-snippet-note update [-h] [--sudo SUDO] --project-id
                                         PROJECT_ID --snippet-id SNIPPET_ID
                                         --id ID --body BODY
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--snippet-id <snippet_id>****--id <id>****--body <body>****gitlab project-snippet-note-award-emoji**

```
usage: gitlab project-snippet-note-award-emoji [-h]
      list
      get
      create
      delete} ...
```

-h, --help

show this help message and exit

gitlab project-snippet-note-award-emoji create

```
usage: gitlab project-snippet-note-award-emoji create [-h] [--sudo SUDO]
                                         --project-id PROJECT_ID
                                         --snippet-id SNIPPET_ID
                                         --note-id NOTE_ID --name
                                         NAME
```

-h, --help

show this help message and exit

--sudo <sudo>**--project-id <project_id>****--snippet-id <snippet_id>**

```
--note-id <note_id>  
--name <name>
```

gitlab project-snippet-note-award-emoji delete

```
usage: gitlab project-snippet-note-award-emoji delete [-h] [--sudo SUDO]  
          --project-id PROJECT_ID  
          --snippet-id SNIPPET_ID  
          --note-id NOTE_ID --id  
          ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--snippet-id <snippet_id>
```

```
--note-id <note_id>
```

```
--id <id>
```

gitlab project-snippet-note-award-emoji get

```
usage: gitlab project-snippet-note-award-emoji get [-h] [--sudo SUDO]  
          --project-id PROJECT_ID  
          --snippet-id SNIPPET_ID  
          --note-id NOTE_ID --id ID
```

-h, --help

show this help message and exit

```
--sudo <sudo>
```

```
--project-id <project_id>
```

```
--snippet-id <snippet_id>
```

```
--note-id <note_id>
```

```
--id <id>
```

gitlab project-snippet-note-award-emoji list

```
usage: gitlab project-snippet-note-award-emoji list [-h] [--sudo SUDO]
                                                 --project-id PROJECT_ID
                                                 --snippet-id SNIPPET_ID
                                                 --note-id NOTE_ID
                                                 [--page PAGE]
                                                 [--per-page PER_PAGE]
                                                 [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--snippet-id <snippet_id>

--note-id <note_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-storage

```
usage: gitlab project-storage [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab project-storage get

```
usage: gitlab project-storage get [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-tag

```
usage: gitlab project-tag [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab project-tag create

```
usage: gitlab project-tag create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --tag-name TAG_NAME --ref REF
                                 [--message MESSAGE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--tag-name <tag_name>

--ref <ref>

--message <message>

gitlab project-tag delete

```
usage: gitlab project-tag delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-tag get

```
usage: gitlab project-tag get [-h] [--sudo SUDO] --project-id PROJECT_ID
                               --name NAME
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--name <name>

gitlab project-tag list

```
usage: gitlab project-tag list [-h] [--sudo SUDO] --project-id PROJECT_ID
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]
                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-trigger

```
usage: gitlab project-trigger [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-trigger create

```
usage: gitlab project-trigger create [-h] [--sudo SUDO] --project-id
                                     PROJECT_ID --description DESCRIPTION
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--description <description>

gitlab project-trigger delete

```
usage: gitlab project-trigger delete [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-trigger get

```
usage: gitlab project-trigger get [-h] [--sudo SUDO] --project-id PROJECT_ID  
--id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

gitlab project-trigger list

```
usage: gitlab project-trigger list [-h] [--sudo SUDO] --project-id PROJECT_ID  
[--page PAGE] [--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-trigger update

```
usage: gitlab project-trigger update [-h] [--sudo SUDO] --project-id  
PROJECT_ID --id ID --description  
DESCRIPTION
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--id <id>

--description <description>

gitlab project-user

```
usage: gitlab project-user [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab project-user list

```
usage: gitlab project-user list [-h] [--sudo SUDO] --project-id PROJECT_ID  
[--search SEARCH] [--skip-users SKIP_USERS]  
[--page PAGE] [--per-page PER_PAGE]  
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--search <search>

--skip-users <skip_users>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-variable

```
usage: gitlab project-variable [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-variable create

```
usage: gitlab project-variable create [-h] [--sudo SUDO] --project-id
PROJECT_ID --key KEY --value VALUE
[--protected PROTECTED]
[--variable-type VARIABLE_TYPE]
[--masked MASKED]
[--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--key <key>

--value <value>

--protected <protected>

--variable-type <variable_type>

--masked <masked>

--environment-scope <environment_scope>

gitlab project-variable delete

```
usage: gitlab project-variable delete [-h] [--sudo SUDO] --project-id
PROJECT_ID --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--key <key>

gitlab project-variable get

```
usage: gitlab project-variable get [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                  --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--key <key>

gitlab project-variable list

```
usage: gitlab project-variable list [-h] [--sudo SUDO] --project-id PROJECT_ID  
                                    [--page PAGE] [--per-page PER_PAGE]  
                                    [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-variable update

```
usage: gitlab project-variable update [-h] [--sudo SUDO] --project-id  
                                      PROJECT_ID --key KEY --value VALUE  
                                      [--protected PROTECTED]  
                                      [--variable-type VARIABLE_TYPE]  
                                      [--masked MASKED]  
                                      [--environment-scope ENVIRONMENT_SCOPE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

```
--key <key>
--value <value>
--protected <protected>
--variable-type <variable_type>
--masked <masked>
--environment-scope <environment_scope>
```

gitlab project-wiki

```
usage: gitlab project-wiki [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab project-wiki create

```
usage: gitlab project-wiki create [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --title TITLE --content CONTENT
                                  [--format FORMAT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--title <title>

--content <content>

--format <format>

gitlab project-wiki delete

```
usage: gitlab project-wiki delete [-h] [--sudo SUDO] --project-id PROJECT_ID
                                  --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-wiki get

```
usage: gitlab project-wiki get [-h] [--sudo SUDO] --project-id PROJECT_ID
                               --slug SLUG
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

gitlab project-wiki list

```
usage: gitlab project-wiki list [-h] [--sudo SUDO] --project-id PROJECT_ID
                                 [--with-content WITH_CONTENT] [--page PAGE]
                                 [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--with-content <with_content>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab project-wiki update

```
usage: gitlab project-wiki update [-h] [--sudo SUDO] --project-id PROJECT_ID
                                   --slug SLUG [--title TITLE]
                                   [--content CONTENT] [--format FORMAT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--project-id <project_id>

--slug <slug>

```
--title <title>
--content <content>
--format <format>
```

gitlab registry-repository

```
usage: gitlab registry-repository [-h] {get} ...
```

-h, --help

show this help message and exit

gitlab registry-repository get

```
usage: gitlab registry-repository get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab runner

```
usage: gitlab runner [-h] {list,get,create,update,delete,all,verify} ...
```

-h, --help

show this help message and exit

gitlab runner all

```
usage: gitlab runner all [-h] --id ID [--scope SCOPE]
```

-h, --help

show this help message and exit

--id <id>

--scope <scope>

gitlab runner create

```
usage: gitlab runner create [-h] [--sudo SUDO] --token TOKEN
                            [--description DESCRIPTION] [--info INFO]
                            [--active ACTIVE] [--locked LOCKED]
                            [--run-untagged RUN_UNTAGGED]
                            [--tag-list TAG_LIST]
                            [--access-level ACCESS_LEVEL]
                            [--maximum-timeout MAXIMUM_TIMEOUT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--token <token>

--description <description>

--info <info>

--active <active>

--locked <locked>

--run-untagged <run_untagged>

--tag-list <tag_list>

--access-level <access_level>

--maximum-timeout <maximum_timeout>

gitlab runner delete

```
usage: gitlab runner delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab runner get

```
usage: gitlab runner get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab runner list

```
usage: gitlab runner list [-h] [--sudo SUDO] [--scope SCOPE] [--type TYPE]
                          [--status STATUS] [--paused PAUSED]
                          [--tag-list TAG_LIST] [--page PAGE]
                          [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--scope <scope>

--type <type>

--status <status>

--paused <paused>

--tag-list <tag_list>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab runner update

```
usage: gitlab runner update [-h] [--sudo SUDO] --id ID
                            [--description DESCRIPTION] [--active ACTIVE]
                            [--tag-list TAG_LIST]
                            [--run-untagged RUN_UNTAGGED] [--locked LOCKED]
                            [--access-level ACCESS_LEVEL]
                            [--maximum-timeout MAXIMUM_TIMEOUT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

--description <description>

--active <active>

--tag-list <tag_list>

--run-untagged <run_untagged>

```
--locked <locked>
--access-level <access_level>
--maximum-timeout <maximum_timeout>
```

gitlab runner verify

```
usage: gitlab runner verify [-h] --id ID --token TOKEN
```

```
-h, --help
    show this help message and exit
--id <id>
--token <token>
```

gitlab runner-all

```
usage: gitlab runner-all [-h] {list} ...
```

```
-h, --help
    show this help message and exit
```

gitlab runner-all list

```
usage: gitlab runner-all list [-h] [--sudo SUDO] [--scope SCOPE] [--type TYPE]
                               [--status STATUS] [--paused PAUSED]
                               [--tag-list TAG_LIST] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--scope <scope>
--type <type>
--status <status>
--paused <paused>
--tag-list <tag_list>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab runner-job

```
usage: gitlab runner-job [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab runner-job list

```
usage: gitlab runner-job list [-h] [--sudo SUDO] --runner-id RUNNER_ID
                               [--status STATUS] [--page PAGE]
                               [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--runner-id <runner_id>

--status <status>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab shared-project

```
usage: gitlab shared-project [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab shared-project list

```
usage: gitlab shared-project list [-h] [--sudo SUDO] --group-id GROUP_ID
                                   [--archived ARCHIVED]
                                   [--visibility VISIBILITY]
                                   [--order-by ORDER_BY] [--sort SORT]
                                   [--search SEARCH] [--simple SIMPLE]
                                   [--starred STARRED]
                                   [--with-issues-enabled WITH_ISSUES_ENABLED]
                                   [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
                                   ↵ENABLED]
                                   [--min-access-level MIN_ACCESS_LEVEL]
```

(continues on next page)

(continued from previous page)

```
[--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
[--page PAGE] [--per-page PER_PAGE]
[--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--group-id <group_id>****--archived <archived>****--visibility <visibility>****--order-by <order_by>****--sort <sort>****--search <search>****--simple <simple>****--starred <starred>****--with-issues-enabled <with_issues_enabled>****--with-merge-requests-enabled <with_merge_requests_enabled>****--min-access-level <min_access_level>****--with-custom-attributes <with_custom_attributes>****--page <page>****--per-page <per_page>****--get-all**

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab snippet

```
usage: gitlab snippet [-h]
  list
  get
  create
  update
  delete
  user-agent-detail
  content
  public
  ...
```

-h, --help

show this help message and exit

gitlab snippet content

```
usage: gitlab snippet content [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab snippet create

```
usage: gitlab snippet create [-h] [--sudo SUDO] --title TITLE --file-name  
                           FILE_NAME --content CONTENT [--lifetime LIFETIME]  
                           [--visibility VISIBILITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--title <title>

--file-name <file_name>

--content <content>

--lifetime <lifetime>

--visibility <visibility>

gitlab snippet delete

```
usage: gitlab snippet delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab snippet get

```
usage: gitlab snippet get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab snippet list

```
usage: gitlab snippet list [-h] [--sudo SUDO] [--page PAGE]
                           [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab snippet public

```
usage: gitlab snippet public [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab snippet update

```
usage: gitlab snippet update [-h] [--sudo SUDO] --id ID [--title TITLE]
                             [--file-name FILE_NAME] [--content CONTENT]
                             [--visibility VISIBILITY]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

```
--title <title>
--file-name <file_name>
--content <content>
--visibility <visibility>
```

gitlab snippet user-agent-detail

```
usage: gitlab snippet user-agent-detail [-h] --id ID
```

-h, --help
show this help message and exit

--id <id>

gitlab starred-project

```
usage: gitlab starred-project [-h] {list} ...
```

-h, --help
show this help message and exit

gitlab starred-project list

```
usage: gitlab starred-project list [-h] [--sudo SUDO] --user-id USER_ID
                                   [--archived ARCHIVED]
                                   [--membership MEMBERSHIP]
                                   [--min-access-level MIN_ACCESS_LEVEL]
                                   [--order-by ORDER_BY] [--owned OWNED]
                                   [--search SEARCH] [--simple SIMPLE]
                                   [--sort SORT] [--starred STARRED]
                                   [--statistics STATISTICS]
                                   [--visibility VISIBILITY]
                                   [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                   [--with-issues-enabled WITH_ISSUES_ENABLED]
                                   [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
                                   ↵ENABLED]
                                   [--page PAGE] [--per-page PER_PAGE]
                                   [--get-all] [--all]
```

-h, --help
show this help message and exit

--sudo <sudo>

--user-id <user_id>

--archived <archived>

```
--membership <membership>
--min-access-level <min_access_level>
--order-by <order_by>
--owned <owned>
--search <search>
--simple <simple>
--sort <sort>
--starred <starred>
--statistics <statistics>
--visibility <visibility>
--with-custom-attributes <with_custom_attributes>
--with-issues-enabled <with_issues_enabled>
--with-merge-requests-enabled <with_merge_requests_enabled>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab todo

```
usage: gitlab todo [-h] {list,delete,mark-as-done,mark-all-as-done} ...
```

```
-h, --help
    show this help message and exit
```

gitlab todo delete

```
usage: gitlab todo delete [-h] [--sudo SUDO] --id ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--id <id>
```

gitlab todo list

```
usage: gitlab todo list [-h] [--sudo SUDO] [--action ACTION]
                        [--author-id AUTHOR_ID] [--project-id PROJECT_ID]
                        [--state STATE] [--type TYPE] [--page PAGE]
                        [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--action <action>

--author-id <author_id>

--project-id <project_id>

--state <state>

--type <type>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab todo mark-all-as-done

```
usage: gitlab todo mark-all-as-done [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab todo mark-as-done

```
usage: gitlab todo mark-as-done [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab topic

```
usage: gitlab topic [-h] {list,get,create,update,delete} ...
```

-h, --help

show this help message and exit

gitlab topic create

```
usage: gitlab topic create [-h] [--sudo SUDO] --name NAME [--avatar AVATAR]
                           [--description DESCRIPTION] [--title TITLE]
```

-h, --help

show this help message and exit

--sudo <sudo>

--name <name>

--avatar <avatar>

--description <description>

--title <title>

gitlab topic delete

```
usage: gitlab topic delete [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab topic get

```
usage: gitlab topic get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab topic list

```
usage: gitlab topic list [-h] [--sudo SUDO] [--page PAGE]
                         [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab topic update

```
usage: gitlab topic update [-h] [--sudo SUDO] --id ID [--avatar AVATAR]
                           [--description DESCRIPTION] [--name NAME]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

--avatar <avatar>

--description <description>

--name <name>

gitlab user

```
usage: gitlab user [-h]
    list
    get
    create
    update
    delete
    block
    follow
    unfollow
    unblock
    deactivate
    activate
    approve
```

(continues on next page)

(continued from previous page)

```
reject  
ban  
unban  
...
```

-h, --help

show this help message and exit

gitlab user activate

```
usage: gitlab user activate [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>**gitlab user approve**

```
usage: gitlab user approve [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>**gitlab user ban**

```
usage: gitlab user ban [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>**gitlab user block**

```
usage: gitlab user block [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user create

```
usage: gitlab user create [-h] [--sudo SUDO] [--email EMAIL]
                          [--username USERNAME] [--name NAME]
                          [--password PASSWORD]
                          [--reset-password RESET_PASSWORD] [--skype SKYPE]
                          [--linkedin LINKEDIN] [--twitter TWITTER]
                          [--projects-limit PROJECTS_LIMIT]
                          [--extern-uid EXTERN_UID] [--provider PROVIDER]
                          [--bio BIO] [--admin ADMIN]
                          [--can-create-group CAN_CREATE_GROUP]
                          [--website-url WEBSITE_URL]
                          [--skip-confirmation SKIP_CONFIRMATION]
                          [--external EXTERNAL] [--organization ORGANIZATION]
                          [--location LOCATION] [--avatar AVATAR]
                          [--public-email PUBLIC_EMAIL]
                          [--private-profile PRIVATE_PROFILE]
                          [--color-scheme-id COLOR_SCHEME_ID]
                          [--theme-id THEME_ID]
```

-h, --help

show this help message and exit

--sudo <sudo>

--email <email>

--username <username>

--name <name>

--password <password>

--reset-password <reset_password>

--skype <skype>

--linkedin <linkedin>

--twitter <twitter>

--projects-limit <projects_limit>

--extern-uid <extern_uid>

--provider <provider>

--bio <bio>

--admin <admin>

--can-create-group <can_create_group>

--website-url <website_url>

--skip-confirmation <skip_confirmation>

```
--external <external>
--organization <organization>
--location <location>
--avatar <avatar>
--public-email <public_email>
--private-profile <private_profile>
--color-scheme-id <color_scheme_id>
--theme-id <theme_id>
```

gitlab user deactivate

```
usage: gitlab user deactivate [-h] --id ID
```

-h, --help
show this help message and exit
--id <id>

gitlab user delete

```
usage: gitlab user delete [-h] [--sudo SUDO] --id ID
```

-h, --help
show this help message and exit
--sudo <sudo>
--id <id>

gitlab user follow

```
usage: gitlab user follow [-h] --id ID
```

-h, --help
show this help message and exit
--id <id>

gitlab user get

```
usage: gitlab user get [-h] [--sudo SUDO] --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

gitlab user list

```
usage: gitlab user list [-h] [--sudo SUDO] [--active ACTIVE]
                        [--blocked BLOCKED] [--username USERNAME]
                        [--extern-uid EXTERN_UID] [--provider PROVIDER]
                        [--external EXTERNAL] [--search SEARCH]
                        [--custom-attributes CUSTOM_ATTRIBUTES]
                        [--status STATUS] [--two-factor TWO_FACTOR]
                        [--page PAGE] [--per-page PER_PAGE] [--get-all]
                        [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--active <active>

--blocked <blocked>

--username <username>

--extern-uid <extern_uid>

--provider <provider>

--external <external>

--search <search>

--custom-attributes <custom_attributes>

--status <status>

--two-factor <two_factor>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab user reject

```
usage: gitlab user reject [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user unban

```
usage: gitlab user unban [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user unblock

```
usage: gitlab user unblock [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user unfollow

```
usage: gitlab user unfollow [-h] --id ID
```

-h, --help

show this help message and exit

--id <id>

gitlab user update

```
usage: gitlab user update [-h] [--sudo SUDO] --id ID --email EMAIL --username  
    USERNAME --name NAME [--password PASSWORD]  
    [--skype SKYPE] [--linkedin LINKEDIN]  
    [--twitter TWITTER]  
    [--projects-limit PROJECTS_LIMIT]  
    [--extern-uid EXTERN_UID] [--provider PROVIDER]  
    [--bio BIO] [--admin ADMIN]  
    [--can-create-group CAN_CREATE_GROUP]  
    [--website-url WEBSITE_URL]  
    [--skip-reconfirmation SKIP_RECONFIRMATION]  
    [--external EXTERNAL] [--organization ORGANIZATION]
```

(continues on next page)

(continued from previous page)

```
[--location LOCATION] [--avatar AVATAR]
[--public-email PUBLIC_EMAIL]
[--private-profile PRIVATE_PROFILE]
[--color-scheme-id COLOR_SCHEME_ID]
[--theme-id THEME_ID]
```

-h, --help

show this help message and exit

--sudo <sudo>

--id <id>

--email <email>

--username <username>

--name <name>

--password <password>

--skype <skype>

--linkedin <linkedin>

--twitter <twitter>

--projects-limit <projects_limit>

--extern-uid <extern_uid>

--provider <provider>

--bio <bio>

--admin <admin>

--can-create-group <can_create_group>

--website-url <website_url>

--skip-reconfirmation <skip_reconfirmation>

--external <external>

--organization <organization>

--location <location>

--avatar <avatar>

--public-email <public_email>

--private-profile <private_profile>

--color-scheme-id <color_scheme_id>

--theme-id <theme_id>

gitlab user-activities

```
usage: gitlab user-activities [-h] {list} ...
```

-h, --help

show this help message and exit

gitlab user-activities list

```
usage: gitlab user-activities list [-h] [--sudo SUDO] [--page PAGE]
                                   [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab user-custom-attribute

```
usage: gitlab user-custom-attribute [-h] {list,get,delete} ...
```

-h, --help

show this help message and exit

gitlab user-custom-attribute delete

```
usage: gitlab user-custom-attribute delete [-h] [--sudo SUDO] --user-id
                                            USER_ID --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--key <key>

gitlab user-custom-attribute get

```
usage: gitlab user-custom-attribute get [-h] [--sudo SUDO] --user-id USER_ID  
                                      --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--key <key>

gitlab user-custom-attribute list

```
usage: gitlab user-custom-attribute list [-h] [--sudo SUDO] --user-id USER_ID  
                                         [--page PAGE] [--per-page PER_PAGE]  
                                         [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab user-email

```
usage: gitlab user-email [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab user-email create

```
usage: gitlab user-email create [-h] [--sudo SUDO] --user-id USER_ID --email  
                                EMAIL
```

-h, --help

show this help message and exit

--sudo <sudo>**--user-id <user_id>****--email <email>****gitlab user-email delete**

```
usage: gitlab user-email delete [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--user-id <user_id>****--id <id>****gitlab user-email get**

```
usage: gitlab user-email get [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>**--user-id <user_id>****--id <id>****gitlab user-email list**

```
usage: gitlab user-email list [-h] [--sudo SUDO] --user-id USER_ID  
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]  
                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>**--user-id <user_id>**

```
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab user-event

```
usage: gitlab user-event [-h] {list} ...
```

```
-h, --help
    show this help message and exit
```

gitlab user-event list

```
usage: gitlab user-event list [-h] [--sudo SUDO] --user-id USER_ID
                               [--action ACTION] [--target-type TARGET_TYPE]
                               [--before BEFORE] [--after AFTER] [--sort SORT]
                               [--page PAGE] [--per-page PER_PAGE] [--get-all]
                               [--all]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--user-id <user_id>
--action <action>
--target-type <target_type>
--before <before>
--after <after>
--sort <sort>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab user-gpg-key

```
usage: gitlab user-gpg-key [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab user-gpg-key create

```
usage: gitlab user-gpg-key create [-h] [--sudo SUDO] --user-id USER_ID --key  
                                  KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--key <key>

gitlab user-gpg-key delete

```
usage: gitlab user-gpg-key delete [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-gpg-key get

```
usage: gitlab user-gpg-key get [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-gpg-key list

```
usage: gitlab user-gpg-key list [-h] [--sudo SUDO] --user-id USER_ID
                                [--page PAGE] [--per-page PER_PAGE]
                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use –get-all instead.

gitlab user-impersonation-token

```
usage: gitlab user-impersonation-token [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab user-impersonation-token create

```
usage: gitlab user-impersonation-token create [-h] [--sudo SUDO] --user-id
                                                USER_ID --name NAME --scopes
                                                SCOPES [--expires-at EXPIRES_AT]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--name <name>

--scopes <scopes>

--expires-at <expires_at>

gitlab user-impersonation-token delete

```
usage: gitlab user-impersonation-token delete [-h] [--sudo SUDO] --user-id
                                               USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-impersonation-token get

```
usage: gitlab user-impersonation-token get [-h] [--sudo SUDO] --user-id
                                              USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-impersonation-token list

```
usage: gitlab user-impersonation-token list [-h] [--sudo SUDO] --user-id
                                               USER_ID [--state STATE]
                                               [--page PAGE]
                                               [--per-page PER_PAGE] [--get-all]
                                               [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--state <state>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab user-key

```
usage: gitlab user-key [-h] {list,get,create,delete} ...
```

-h, --help

show this help message and exit

gitlab user-key create

```
usage: gitlab user-key create [-h] [--sudo SUDO] --user-id USER_ID --title
                               TITLE --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--title <title>

--key <key>

gitlab user-key delete

```
usage: gitlab user-key delete [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-key get

```
usage: gitlab user-key get [-h] [--sudo SUDO] --user-id USER_ID --id ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--id <id>

gitlab user-key list

```
usage: gitlab user-key list [-h] [--sudo SUDO] --user-id USER_ID [--page PAGE]
                            [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab user-membership

```
usage: gitlab user-membership [-h] {list,get} ...
```

-h, --help

show this help message and exit

gitlab user-membership get

```
usage: gitlab user-membership get [-h] [--sudo SUDO] --user-id USER_ID
                                  --source-id SOURCE_ID
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--source-id <source_id>

gitlab user-membership list

```
usage: gitlab user-membership list [-h] [--sudo SUDO] --user-id USER_ID
                                   [--type TYPE] [--page PAGE]
                                   [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

```
--sudo <sudo>
--user-id <user_id>
--type <type>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab user-personal-access-token

```
usage: gitlab user-personal-access-token [-h] {create} ...
```

```
-h, --help
    show this help message and exit
```

gitlab user-personal-access-token create

```
usage: gitlab user-personal-access-token create [-h] [--sudo SUDO] --user-id
                                                USER_ID --name NAME --scopes
                                                SCOPES
                                                [--expires-at EXPIRES_AT]
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--user-id <user_id>
--name <name>
--scopes <scopes>
--expires-at <expires_at>
```

gitlab user-project

```
usage: gitlab user-project [-h] {list,create} ...
```

```
-h, --help
    show this help message and exit
```

gitlab user-project create

```
usage: gitlab user-project create [-h] [--sudo SUDO] --user-id USER_ID --name
                                  NAME [--default-branch DEFAULT_BRANCH]
                                  [--issues-enabled ISSUES_ENABLED]
                                  [--wall-enabled WALL_ENABLED]
                                  [--merge-requests-enabled MERGE_REQUESTS_ENABLED]
                                  [--wiki-enabled WIKI_ENABLED]
                                  [--snippets-enabled SNIPPETS_ENABLED]
                                  [--squash-option SQUASH_OPTION]
                                  [--public PUBLIC] [--visibility VISIBILITY]
                                  [--description DESCRIPTION]
                                  [--builds-enabled BUILDS_ENABLED]
                                  [--public-builds PUBLIC_BUILDS]
                                  [--import-url IMPORT_URL]
                                  [--only-allow-merge-if-build-succeeds ONLY_ALLOW_MERGE_
                                  ↪IF_BUILD_SUCCEEDS]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--name <name>

--default-branch <default_branch>

--issues-enabled <issues_enabled>

--wall-enabled <wall_enabled>

--merge-requests-enabled <merge_requests_enabled>

--wiki-enabled <wiki_enabled>

--snippets-enabled <snippets_enabled>

--squash-option <squash_option>

--public <public>

--visibility <visibility>

--description <description>

--builds-enabled <builds_enabled>

--public-builds <public_builds>

--import-url <import_url>

--only-allow-merge-if-build-succeeds <only_allow_merge_if_build_succeeds>

gitlab user-project list

```
usage: gitlab user-project list [-h] [--sudo SUDO] --user-id USER_ID
                                [--archived ARCHIVED]
                                [--visibility VISIBILITY]
                                [--order-by ORDER_BY] [--sort SORT]
                                [--search SEARCH] [--simple SIMPLE]
                                [--owned OWNED] [--membership MEMBERSHIP]
                                [--starred STARRED] [--statistics STATISTICS]
                                [--with-issues-enabled WITH_ISSUES_ENABLED]
                                [--with-merge-requests-enabled WITH_MERGE_REQUESTS_
                                ↪ENABLED]
                                [--with-custom-attributes WITH_CUSTOM_ATTRIBUTES]
                                [--with-programming-language WITH_PROGRAMMING_LANGUAGE]
                                [--wiki-checksum-failed WIKI_CHECKSUM_FAILED]
                                [--repository-checksum-failed REPOSITORY_CHECKSUM_FAILED]
                                [--min-access-level MIN_ACCESS_LEVEL]
                                [--id-after ID_AFTER] [--id-before ID_BEFORE]
                                [--page PAGE] [--per-page PER_PAGE]
                                [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--user-id <user_id>

--archived <archived>

--visibility <visibility>

--order-by <order_by>

--sort <sort>

--search <search>

--simple <simple>

--owned <owned>

--membership <membership>

--starred <starred>

--statistics <statistics>

--with-issues-enabled <with_issues_enabled>

--with-merge-requests-enabled <with_merge_requests_enabled>

--with-custom-attributes <with_custom_attributes>

--with-programming-language <with_programming_language>

--wiki-checksum-failed <wiki_checksum_failed>

```
--repository-checksum-failed <repository_checksum_failed>
--min-access-level <min_access_level>
--id-after <id_after>
--id-before <id_before>
--page <page>
--per-page <per_page>
--get-all
    Return all items from the server, without pagination.
--all
    Deprecated. Use --get-all instead.
```

gitlab user-status

```
usage: gitlab user-status [-h] {get} ...
```

```
-h, --help
    show this help message and exit
```

gitlab user-status get

```
usage: gitlab user-status get [-h] [--sudo SUDO] --user-id USER_ID
```

```
-h, --help
    show this help message and exit
--sudo <sudo>
--user-id <user_id>
```

gitlab variable

```
usage: gitlab variable [-h] {list,get,create,update,delete} ...
```

```
-h, --help
    show this help message and exit
```

gitlab variable create

```
usage: gitlab variable create [-h] [--sudo SUDO] --key KEY --value VALUE
                               [--protected PROTECTED]
                               [--variable-type VARIABLE_TYPE]
                               [--masked MASKED]
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

--value <value>

--protected <protected>

--variable-type <variable_type>

--masked <masked>

gitlab variable delete

```
usage: gitlab variable delete [-h] [--sudo SUDO] --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

gitlab variable get

```
usage: gitlab variable get [-h] [--sudo SUDO] --key KEY
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

gitlab variable list

```
usage: gitlab variable list [-h] [--sudo SUDO] [--page PAGE]
                           [--per-page PER_PAGE] [--get-all] [--all]
```

-h, --help

show this help message and exit

--sudo <sudo>

--page <page>

--per-page <per_page>

--get-all

Return all items from the server, without pagination.

--all

Deprecated. Use --get-all instead.

gitlab variable update

```
usage: gitlab variable update [-h] [--sudo SUDO] --key KEY --value VALUE
                               [--protected PROTECTED]
                               [--variable-type VARIABLE_TYPE]
                               [--masked MASKED]
```

-h, --help

show this help message and exit

--sudo <sudo>

--key <key>

--value <value>

--protected <protected>

--variable-type <variable_type>

--masked <masked>

6.8 Changelog

6.8.1 v3.10.0 (2022-09-28)

Feature

- Add reset_approvals api (88693ff)
- Add support for deployment approval endpoint (9c9eeb9)

Fix

- **cli:** Add missing attributes for creating MRs ([1714d0a](#))
- **cli:** Add missing attribute for MR changes ([20c46a0](#))

6.8.2 v3.9.0 (2022-08-28)

Feature

- Add support for merge_base API ([dd4fdbd5](#))

6.8.3 v3.8.1 (2022-08-10)

Fix

- **client:** Do not assume user attrs returned for auth() ([a07547c](#))

6.8.4 v3.8.0 (2022-08-04)

Feature

- **client:** Warn user on misconfigured URL in auth() ([0040b43](#))
- Support downloading archive subpaths ([cadb0e5](#))

Fix

- **client:** Ensure encoded query params are never duplicated ([1398426](#))
- Optionally keep user-provided base URL for pagination ([#2149](#)) ([e2ea8b8](#))

Documentation

- Describe self-revoking personal access tokens ([5ea48fc](#))

6.8.5 v3.7.0 (2022-07-28)

Feature

- Allow sort/ordering for project releases ([b1dd284](#))
- **cli:** Add a custom help formatter ([005ba93](#))
- Add support for iterations API ([194ee01](#))
- **groups:** Add support for shared projects API ([66461ba](#))
- **issues:** Add support for issue reorder API ([8703324](#))
- **namespaces:** Add support for namespace existence API ([4882cb2](#))
- Add support for group and project invitations API ([7af3d340](#))

- **projects:** Add support for project restore API ([4794ecc](#))
- Add support for filtering jobs by scope ([0e1c0dd](#))
- Add `asdict()` and `to_json()` methods to Gitlab Objects ([08ac071](#))
- **api:** Add support for instance-level registry repositories ([284d739](#))
- **groups:** Add support for group-level registry repositories ([70148c6](#))
- Add ‘merge_pipelines_enabled’ project attribute ([fc33c93](#))
- Support validating CI lint results ([3b1ede4](#))
- **cli:** Add support for global CI lint ([3f67c4b](#))
- **objects:** Add Project CI Lint support ([b213dd3](#))
- Add support for group push rules ([b5cdc09](#))
- **api:** Add support for get for a MR approval rule ([89c18c6](#))

Fix

- Support array types for most resources ([d9126cd](#))
- Use the [] after key names for array variables in `params` ([1af44ce](#))
- **runners:** Fix listing for /runners/all ([c6dd57c](#))
- **config:** Raise error when gitlab id provided but no config section found ([1ef7018](#))
- **config:** Raise error when gitlab id provided but no config file found ([ac46c1c](#))
- Add `get_all` param (and `--get-all`) to allow passing all to API ([7c71d5d](#))
- Results returned by `attributes` property to show updates ([e5afffc8](#))
- Enable epic notes ([5fc3216](#))
- **cli:** Remove irrelevant MR approval rule list filters ([0daec5f](#))
- Ensure path elements are escaped ([5d9c198](#))

Documentation

- **cli:** Showcase use of token scopes ([4a6f8d6](#))
- **projects:** Document export with upload to URL ([03f5484](#))
- Describe fetching existing export status ([9c5b8d5](#))
- **authors:** Add John ([e2afb84](#))
- Document CI Lint usage ([d5de4b1](#))
- **users:** Add docs about listing a user’s projects ([065a1a5](#))
- Update return type of pushrules ([53cbecc](#))
- Describe ROPC flow in place of password authentication ([91c17b7](#))
- **readme:** Remove redundant -v that breaks the command ([c523e18](#))

6.8.6 v3.6.0 (2022-06-28)

Feature

- **downloads:** Allow streaming downloads access to response iterator (#1956) ([b644721](#))
- **api:** Support head() method for get and list endpoints ([ce9216c](#))
- **api:** Implement HEAD method ([90635a7](#))
- **users:** Add approve and reject methods to User ([f57139d](#))
- **api:** Convert gitlab.const to Enums ([c3c6086](#))
- Add support for Protected Environments ([1dc9d0f](#))
- **users:** Add ban and unban methods ([0d44b11](#))
- **docker:** Provide a Debian-based slim image ([384031c](#))
- Support mutually exclusive attributes and consolidate validation to fix board lists (#2037) ([3fa330c](#))
- **client:** Introduce iterator=True and deprecate as_list=False in list() ([cdc6605](#))

Fix

- **base:** Do not fail repr() on lazy objects ([1efb123](#))
- **cli:** Project-merge-request-approval-rule ([15a242c](#))
- **cli:** Fix project export download for CLI ([5d14867](#))

Documentation

- **api:** Add separate section for advanced usage ([22ae101](#))
- **api:** Document usage of head() methods ([f555bfb](#))
- **projects:** Provide more detailed import examples ([8f8611a](#))
- **projects:** Document 404 gotcha with unactivated integrations ([522ecff](#))
- **variables:** Instruct users to follow GitLab rules for values ([194b6be](#))
- **api:** Stop linking to python-requests.org ([49c7e83](#))
- **api:** Fix incorrect docs for merge_request_approvals (#2094) ([5583eaa](#))
- **api-usage:** Add import os in example ([2194a44](#))
- Drop deprecated setuptools build_sphinx ([048d66a](#))
- **usage:** Refer to upstream docs instead of custom attributes ([ae7d3b0](#))
- **ext:** Fix rendering for RequiredOptional dataclass ([4d431e5](#))
- Documentation updates to reflect addition of mutually exclusive attributes ([24b720e](#))
- Use as_list=False or all=True in Getting started ([de8c6e8](#))

6.8.7 v3.5.0 (2022-05-28)

Feature

- **objects:** Support get project storage endpoint ([8867ee5](#))
- Display human-readable attribute in `repr()` if present ([6b47c26](#))
- **ux:** Display project.name_with_namespace on project repr ([e598762](#))

Fix

- **cli:** Changed default `allow_abbrev` value to fix arguments collision problem ([#2013](#)) ([d68cacf](#))
- Duplicate subparsers being added to argparse ([f553fd3](#))

Documentation

- Update issue example and extend API usage docs ([aad71d2](#))
- **CONTRIBUTING.rst:** Fix link to conventional-changelog commit format documentation ([2373a4f](#))
- Add missing Admin access const value ([3e0d4d9](#))
- **merge_requests:** Add new possible merge request state and link to the upstream docs ([e660fa8](#))

6.8.8 v3.4.0 (2022-04-28)

Feature

- Emit a warning when using a `list()` method returns max ([1339d64](#))
- **objects:** Support getting project/group deploy tokens by id ([fcd37fe](#))
- **user:** Support getting user SSH key by id ([6f93c05](#))
- **api:** Re-add topic delete endpoint ([d1d96bd](#))

Fix

- Add `ChunkedEncodingError` to list of retryable exceptions ([7beb20f](#))
- Avoid passing redundant arguments to API ([3431887](#))
- **cli:** Add missing filters for project commit list ([149d244](#))
- Add 52x range to retry transient failures and tests ([c3ef1b5](#))
- Also retry HTTP-based transient errors ([3b49e4d](#))

Documentation

- **api-docs:** Docs fix for application scopes ([e1ad93d](#))

6.8.9 v3.3.0 (2022-03-28)

Feature

- **object:** Add pipeline test report summary support ([a97e0cf](#))

Fix

- Support RateLimit-Reset header ([4060146](#))

Documentation

- Fix typo and incorrect style ([2828b10](#))
- Add pipeline test report summary support ([d78afb3](#))
- **chore:** Include docs .js files in sdist ([3010b40](#))

6.8.10 v3.2.0 (2022-02-28)

Feature

- **merge_request_approvals:** Add support for deleting MR approval rules ([85a734f](#))
- **artifacts:** Add support for project artifacts delete API ([c01c034](#))
- **mixins:** Allow deleting resources without IDs ([0717517](#))
- **objects:** Add a complete artifacts manager ([c8c2fa7](#))

Fix

- **services:** Use slug for id_attr instead of custom methods ([e30f39d](#))
- Remove custom delete method for labels ([0841a2a](#))

Documentation

- Enable gitter chat directly in docs ([bd1ecdd](#))
- Add delete methods for runners and project artifacts ([5e711fd](#))
- Add retry_transient infos ([bb1f054](#))
- Add transient errors retry info ([b7a1266](#))
- **artifacts:** Deprecate artifacts() and artifact() methods ([64d01ef](#))
- Revert “chore: add temporary banner for v3” (#1864) ([7a13b9b](#))

6.8.11 v3.1.1 (2022-01-28)

Fix

- **cli:** Make ‘per_page’ and ‘page’ type explicit ([d493a5e](#))
- **cli:** Make ‘timeout’ type explicit ([bbb7df5](#))
- **cli:** Allow custom methods in managers ([8dfed0c](#))
- **objects:** Make resource access tokens and repos available in CLI ([e0a3a41](#))

Documentation

- Enhance release docs for CI_JOB_TOKEN usage ([5d973de](#))
- **changelog:** Add missing changelog items ([01755fb](#))

6.8.12 v3.1.0 (2022-01-14)

Feature

- add support for Group Access Token API ([c01b7c4](#))
- Add support for Groups API method `transfer()` ([0007006](#))
- **api:** Add `project.transfer()` and deprecate `transfer_project()` ([259668a](#))
- **api:** Return result from `SaveMixin.save()` ([e6258a4](#))

Fix

- **cli:** Add missing list filters for environments ([6f64d40](#))
- Use url-encoded ID in all paths ([12435d7](#))
- **members:** Use new *All objects for *AllManager managers ([755e0a3](#))
- **api:** Services: add missing `lazy` parameter ([888f332](#))
- broken URL for FAQ about attribute-error-list ([1863f30](#))
- remove default arguments for `mergerequests.merge()` ([8e589c4](#))
- remove custom URL encoding ([3d49e5e](#))

Documentation

- **cli:** make examples more easily navigable by generating TOC ([f33c523](#))
- update project access token API reference link ([73ae955](#))

6.8.13 v3.0.0 (2022-01-05)

Feature

- **docker:** Remove custom entrypoint from image (80754a1)
- **cli:** Allow options from args and environment variables (ca58008)
- **api:** Support file format for repository archive (83dcabf)
- Add support for `squash_option` in Projects (a246ce8)
- **cli:** Do not require config file to run CLI (92a893b)
- **api:** Add support for Topics API (e7559bf)
- Add delete on `package_file` object (124667b)
- Add support for `projects.groups.list()` (68ff595)
- **api:** Add support for epic notes (7f4edb5)
- Remove support for Python 3.6, require 3.7 or higher (414009d)
- **api:** Add project milestone promotion (f068520)
- **api:** Add merge trains (fd73a73)
- **api:** Add merge request approval state (f41b093)
- **api:** Add project label promotion (6d7c88a)
- **objects:** Support delete package files API (4518046)
- **objects:** List starred projects of a user (47a5606)
- **build:** Officially support and test python 3.10 (c042ddc)
- **objects:** Support Create and Revoke personal access token API (e19314d)
- Default to gitlab.com if no URL given (8236281)
- Allow global `retry_transient_errors` setup (3b1d3a4)

Fix

- Handle situation where GitLab does not return values (cb824a4)
- Stop encoding ‘.’ to ‘%2E’ (702e41d)
- **build:** Do not include docs in wheel package (68a97ce)
- **api:** Delete invalid ‘project-runner get’ command (#1628) (905781b)
- **api:** Replace deprecated attribute in `delete_in_bulk()` (#1536) (c59fbdb)
- **objects:** Rename confusing `to_project_id` argument (ce4bc0d)
- Raise error if there is a 301/302 redirection (d56a434)
- **build:** Do not package tests in wheel (969dccc)

Breaking

- The gitlab CLI will now accept CLI arguments and environment variables for its global options in addition to configuration file options. This may change behavior for some workflows such as running inside GitLab CI and with certain environment variables configured. ([ca58008](#))
- stop encoding ‘.’ to ‘%2E’. This could potentially be a breaking change for users who have incorrectly configured GitLab servers which don’t handle period ‘.’ characters correctly. ([702e41d](#))
- A config file is no longer needed to run the CLI. python-gitlab will default to https://gitlab.com with no authentication if there is no config file provided. python-gitlab will now also only look for configuration in the provided PYTHON_GITLAB_CFG path, instead of merging it with user- and system-wide config files. If the environment variable is defined and the file cannot be opened, python-gitlab will now explicitly fail. ([92a893b](#))
- As of python-gitlab 3.0.0, Python 3.6 is no longer supported. Python 3.7 or higher is required. ([414009d](#))
- As of python-gitlab 3.0.0, the default branch for development has changed from `master` to `main`. ([545f8ed](#))
- remove deprecated branch protect methods in favor of the more complete protected branches API. ([9656a16](#))
- The deprecated `name_regex` attribute has been removed in favor of `name_regex_delete`. (see <https://gitlab.com/gitlab-org/gitlab/-/commit/ce99813cf54>) ([c59fbdb](#))
- rename confusing `to_project_id` argument in `transfer_project` to `project_id` (`--project-id` in CLI). This is used for the source project, not for the target namespace. ([ce4bc0d](#))
- remove deprecated constants defined in `gitlab.v4.objects`, and use only `gitlab.const` module ([3f320af](#))
- remove deprecated tag release API. This was removed in GitLab 14.0 ([2b8a94a](#))
- remove deprecated `project.issuesstatistics` in favor of `project.issues_statistics` ([ca777e](#))
- remove deprecated `members.all()` method in favor of `members_all.list()` ([4d7b848](#))
- remove deprecated `pipelines()` methods in favor of `pipelines.list()` ([c4f5ec6](#))
- python-gitlab will now default to `gitlab.com` if no URL is given ([8236281](#))
- raise error if there is a 301/302 redirection ([d56a434](#))

Documentation

- Switch to Furo and refresh introduction pages ([ee6b024](#))
- Correct documentation for updating discussion note ([ee66f4a](#))
- Rename documentation files to match names of code files ([ee3f865](#))
- **project:** Remove redundant encoding parameter ([fed613f](#))
- Use annotations for return types ([79e785e](#))
- Update docs to use `gitlab.const` for constants ([b3b0b5f](#))
- Only use type annotations for documentation ([b7dde0d](#))
- Add links to the GitLab API docs ([e3b5d27](#))
- Fix API delete key example ([b31bb05](#))
- **pipelines:** Document `take_ownership` method ([69461f6](#))
- **api:** Document the update method for project variables ([7992911](#))
- **api:** Clarify job token usage with `auth()` ([3f423ef](#))

- Fix a few typos ([7ea4ddc](#))
- Consolidate changelogs and remove v3 API docs ([90da8ba](#))
- Correct documented return type ([acabf63](#))

6.8.14 v2.10.1 (2021-08-28)

Fix

- **mixins:** Improve deprecation warning ([57e0187](#))
- **deps:** Upgrade requests to 2.25.0 (see CVE-2021-33503) ([ce995b2](#))

Documentation

- **mergequests:** Gl.mergequests.list documentation was missleading ([5b5a7bc](#))

6.8.15 v2.10.0 (2021-07-28)

Feature

- **api:** Add merge_ref for merge requests ([1e24ab2](#))
- **api:** Add name_regex_keep attribute in delete_in_bulk() ([e49ff3f](#))

Fix

- **api:** Do not require Release name for creation ([98cd03b](#))

Documentation

- **readme:** Move contributing docs to CONTRIBUTING.rst ([edf49a3](#))
- Add example for mr.merge_ref ([b30b8ac](#))
- **project:** Add example on getting a single project using name with namespace ([ef16a97](#))

6.8.16 v2.9.0 (2021-06-28)

Feature

- **release:** Allow to update release ([b4c4787](#))
- **api:** Add group hooks ([4a7e9b8](#))
- **api:** Remove responsibility for API inconsistencies for MR reviewers ([3d985ee](#))
- **api:** Add MR pipeline manager and deprecate pipelines() method ([954357c](#))
- **api:** Add support for creating/editing reviewers in project merge requests ([676d1f6](#))

Documentation

- **tags:** Remove deprecated functions ([1b1a827](#))
- **release:** Add update example ([6254a5f](#))
- Make Gitlab class usable for intersphinx ([8753add](#))

6.8.17 v2.8.0 (2021-06-10)

Feature

- Add keys endpoint ([a81525a](#))
- **objects:** Add support for Group wikis (#[1484](#)) ([74f5e62](#))
- **objects:** Add support for generic packages API ([79d88bd](#))
- **api:** Add deployment mergerequests interface ([fbbc0d4](#))
- **objects:** Support all issues statistics endpoints ([f731707](#))
- **objects:** Add support for descendant groups API ([1b70580](#))
- **objects:** Add pipeline test report support ([ee9f96e](#))
- **objects:** Add support for billable members ([fb0b083](#))
- Add feature to get inherited member for project/group ([e444b39](#))
- Add code owner approval as attribute ([fdc46ba](#))
- Indicate that we are a typed package ([e4421ca](#))
- Add support for lists of integers to ListAttribute ([115938b](#))

Fix

- Catch invalid type used to initialize RESTObject ([c7bcc25](#))
- Functional project service test (#[1500](#)) ([093db9d](#))
- Ensure kwargs are passed appropriately for ObjectDeleteMixin ([4e690c2](#))
- **cli:** Add missing list filter for jobs ([b3d1c26](#))
- Change mr.merge() to use ‘post_data’ ([cb6a3c6](#))
- **cli:** Fix parsing CLI objects to classnames ([4252070](#))
- **objects:** Return server data in cancel/retry methods ([9fed061](#))
- **objects:** Add missing group attributes ([d20ff4f](#))
- **objects:** Allow lists for filters for in all objects ([603a351](#))
- Iids not working as a list in projects.issues.list() ([45f806c](#))
- Add a check to ensure the MRO is correct ([565d548](#))

Documentation

- Fix typo in http_delete docstring ([5226f09](#))
- **api:** Add behavior in local attributes when updating objects ([38f65e8](#))
- Fail on warnings during sphinx build ([cbd4d52](#))

6.8.18 v2.7.1 (2021-04-26)

- fix(files): do not url-encode file paths twice

6.8.19 v2.7.0 (2021-04-25)

Bug Fixes

- update user's bool data and avatar ([3ba27ffb](#))
- argument type was not a tuple as expected ([062f8f6a](#))
- correct some type-hints in gitlab/mixins.py ([8bd31240](#))
- only append kwargs as query parameters ([b9ecc9a8](#))
- only add query_parameters to GitlabList once ([1386](#))
- checking if RESTManager._from_parentAttrs is set ([8224b406](#))
- handling config value in _get_values_from_helper ([9dfb4cd9](#))
- let the homedir be expanded in path of helper ([fc7387a0](#))
- make secret helper more user friendly ([fc2798fc](#))
- linting issues and test ([b04dd2c0](#))
- handle tags like debian/2%2.6-21 as identifiers ([b4dac5ce](#))
- remove duplicate class definitions in v4/objects/users.py ([7c4e6259](#))
- wrong variable name ([15ec41ca](#))
- tox pep8 target, so that it can run ([f518e87b](#))
- undefined name errors ([48ec9e0f](#))
- extend wait timeout for test_delete_user() ([19fde8ed](#))
- test_update_group() dependency on ordering ([e78a8d63](#))
- honor parameter value passed ([c2f8f0e7](#))
- **objects:** add single get endpoint for instance audit events ([c3f0a6f1](#))
- **types:** prevent **dir** from producing duplicates ([5bf7525d](#))

Features

- add ProjectPackageFile (#1372)
- add option to add a helper to lookup token (8ecf5592)
- add project audit endpoint (6660dbef)
- add personal access token API (2bb16fac)
- add import from bitbucket server (ff3013a2)
- **api,cli:** make user agent configurable (4bb201b9)
- **issues:** add missing get verb to IssueManager (f78ebe06)
- **objects:**
 - add support for resource state events API (d4799c40)
 - add support for group audit events API (2a0fbdf9)
 - add Release Links API support (28d75181)
- **projects:** add project access token api (1becef02)
- **users:** add follow/unfollow API (e456869d)

Documentation

- correct ProjectFile.decode() documentation (b180bafd)
- update doc for token helper (3ac6fa12)
- better real life token lookup example (9ef83118)

6.8.20 v2.6.0 (2021-01-29)

Features

- support multipart uploads (2fa3004d)
- add MINIMAL_ACCESS constant (49eb3ca7)
- unit tests added (f37ebf5f)
- added support for pipeline bridges (05cbdc22)
- adds support for project merge request approval rules (#1199) (c6fbf399)
- **api:**
 - added wip filter param for merge requests (d6078f80)
 - added wip filter param for merge requests (aa6e80d5)
 - add support for user identity provider deletion (e78e1215)
- **tests:** test label getter (a41af902)

Bug Fixes

- docs changed using the consts (650b65c3)
- typo (9baa9053)
- **api:**
 - use RetrieveMixin for ProjectLabelManager (1a143952)
 - add missing runner access_level param (92669f2e)
- **base:** really refresh object (e1e0d8cb), closes (#1155)
- **cli:**
 - write binary data to stdout buffer (0733ec6c)
 - add missing args for project lists (c73e2374)

6.8.21 v2.5.0 (2020-09-01)

Features

- add support to resource milestone events (88f8cc78), closes #1154
- add share/unshare group with group (7c6e541d)
- add support for instance variables (4492fc42)
- add support for Packages API (71495d12)
- add endpoint for latest ref artifacts (b7a07fca)

Bug Fixes

- wrong reconfirmation parameter when updating user's email (b5c267e1)
- tests fail when using REUSE_CONTAINER option ([0078f899](#), closes #1146)
- implement Gitlab's behavior change for owned=True (99777991)

6.8.22 v2.4.0 (2020-07-09)

Bug Fixes

- do not check if kwargs is none (a349b90e)
- make query kwargs consistent between call in init and next (72ffa016)
- pass kwargs to subsequent queries in gitlab list (1d011ac7)
- **merge:** parse arguments as query_data (878098b7)

Features

- add NO_ACCESS const (dab4d0a1)
- add masked parameter for variables command (b6339bf8)

6.8.23 v2.3.1 (2020-06-09)

- revert keyset pagination by default

6.8.24 v2.3.0 (2020-06-08)

Features

- add group runners api (49439916)
- add play command to project pipeline schedules (07b99881)
- allow an environment variable to specify config location (401e702a)
- **api:** added support in the GroupManager to upload Group avatars (28eb7eab)
- **services:** add project service list API (fc522218)
- **types:** add **dir** to RESTObject to expose attributes (cad134c0)

Bug Fixes

- use keyset pagination by default for /projects > 50000 (f86ef3bb)
- **config:** fix duplicate code (ee2df6f1), closes (#1094)
- **project:** add missing project parameters (ad8c67d6)

6.8.25 v2.2.0 (2020-04-07)

Bug Fixes

- add missing import_project param (9b16614b)
- **types:** do not split single value string in ListAttribute (a26e5858)

Features

- add commit GPG signature API (da7a8097)
- add create from template args to ProjectManager (f493b73e)
- add remote mirrors API (#1056) (4cfaa2fd)
- add Gitlab Deploy Token API (01de524c)
- add Group Import/Export API (#1037) (6cb9d923)

6.8.26 v2.1.2 (2020-03-09)

Bug Fixes

- Fix regression, when using keyset pagination with merge requests. Related to <https://github.com/python-gitlab/python-gitlab/issues/1044>

6.8.27 v2.1.1 (2020-03-09)

Bug Fixes

users: update user attributes

This change was made to mitigate an issue in Gitlab (again). Fix available in: https://gitlab.com/gitlab-org/gitlab-/merge_requests/26792

6.8.28 v2.1.0 (2020-03-08)

Bug Fixes

- do not require empty data dict for create() (99d959f7)
- remove trailing slashes from base URL (#913) (2e396e4a)
- return response with commit data (b77b945c)
- remove null values from features POST data, because it fails with HTTP 500 (1ec1816d)
- **docs:**
 - fix typo in user memberships example (33889bcb)
 - update to new set approvers call for # of approvers (8e0c5262)
 - update docs and tests for set_approvers (2cf12c79)
- **objects:**
 - add default name data and use http post (70c0cfb6)
 - update set_approvers function call (65ecadcf)
 - update to new gitlab api for path, and args (e512cddd)

Features

- add support for user memberships API (#1009) (c313c2b0)
- add support for commit revert API (#991) (5298964e)
- add capability to control GitLab features per project or group (7f192b4f)
- use keyset pagination by default for all=True (99b4484d)
- add support for GitLab OAuth Applications API (4e12356d)

6.8.29 v2.0.1 (2020-02-05)

Changes

- **users:** update user attributes

This change was made to mitigate an issue in Gitlab. See: <https://gitlab.com/gitlab-org/gitlab/issues/202070>

6.8.30 v2.0.0 (2020-01-26)

This release drops support for python < 3.6

Bug Fixes

- **projects:** adjust snippets to match the API (e104e213)

Features

- add global order_by option to ease pagination (d1879253)
- support keyset pagination globally (0b71ba4d)
- add appearance API (4c4ac5ca)
- add autocompletion support (973cb8b9)

6.8.31 v1.15.0 (2019-12-16)

Bug Fixes

- ignore all parameter, when as_list=True 137d72b3, closes #962

Features

- allow cfg timeout to be overridden via kwargs e9a8289a
- add support for /import/github aa4d41b7
- nicer stacktrace 697cda24
- retry transient HTTP errors 59fe2714, closes #970
- access project's issues statistics 482e57ba, closes #966
- adding project stats db0b00a9, closes #967
- add variable_type/protected to projects ci variables 4724c50e
- add variable_type to groups ci variables 0986c931

6.8.32 v1.14.0 (2019-12-07)

Bug Fixes

- added missing attributes for project approvals 460ed63c
- **labels:** ensure label.save() works 727f5361
- **project-fork:**
 - copy create fix from ProjectPipelineManager 516307f1
 - correct path computation for project-fork list 44a7c278

Features

- add audit endpoint 2534020b
- add project and group clusters ebd053e7
- add support for include_subgroups filter adbcd83f

6.8.33 v1.13.0 (2019-11-02)

Features

- add users activate, deactivate functionality (32ad6692)
- send python-gitlab version as user-agent (c22d49d0)
- add deployment creation (ca256a07), closes [#917]
- **auth:** remove deprecated session auth (b751cdf4)
- **doc:** remove refs to api v3 in docs (6beeaa99)
- **test:** unused unittest2, type -> isinstance (33b18012)

Bug Fixes

- **projects:** support approval_rules endpoint for projects (2cef2bb4)

6.8.34 v1.12.1 (2019-10-07)

Bug Fixes

fix: fix not working without auth provided

6.8.35 v1.12.0 (2019-10-06)

Features

- add support for job token
- **project:**
 - implement update_submodule
 - add file blame api
- **user:** add status api

Bug Fixes

- **cli:** fix cli command user-project list
- **labels:** don't mangle label name on update
- **todo:** mark_all_as_done doesn't return anything

6.8.36 v1.11.0 (2019-08-31)

Features

- add methods to retrieve an individual project environment
- group labels with subscriptable mixin

Bug Fixes

- projects: avatar uploading for projects
- remove empty list default arguments
- remove empty dict default arguments
- add project and group label update without id to fix cli

6.8.37 v1.10.0 (2019-07-22)

Features

- add mr rebase method bc4280c2
- get artifact by ref and job cda11745
- add support for board update 908d79fa, closes #801
- add support for issue.related_merge_requests 90a36315, closes #794

Bug Fixes

- improve pickle support b4b5decb
- cli:
 - allow –recursive parameter in repository tree 7969a78c, closes #718, #731
 - don't fail when the short print attr value is None 8d1552a0, closes #717, #727
 - fix update value for key not working b7662039

6.8.38 v1.9.0 (2019-06-19)

Features

- implement artifacts deletion
- add endpoint to get the variables of a pipeline
- delete ProjectPipeline
- implement **eq** and **hash** methods
- Allow runpy invocation of CLI tool (python -m gitlab)
- add project releases api
- merged new release & registry apis

Bug Fixes

- convert # to %23 in URLs
- pep8 errors
- use python2 compatible syntax for super
- Make MemberManager.all() return a list of objects
-
- Re-enable command specific help messages
- dont ask for id attr if this is *Manager originating custom action
- fix -/_ replacament for *Manager custom actions
- fix repository_id marshaling in cli
- register cli action for delete_in_bulk

6.8.39 v1.8.0 (2019-02-22)

- docs(setup): use proper readme on PyPI
- docs(readme): provide commit message guidelines
- fix(api): make reset_time_estimate() work again
- fix: handle empty ‘Retry-After’ header from GitLab
- fix: remove decode() on error_message string
- chore: release tags to PyPI automatically
- fix(api): avoid parameter conflicts with python and gitlab
- fix(api): Don’t try to parse raw downloads
- feat: Added approve & unapprove method for Mergerequests
- fix all kwarg behaviour

6.8.40 v1.7.0 (2018-12-09)

- **docs:** Fix the owned/starred usage documentation
- **docs:** Add a warning about http to https redirects
- Fix the https redirection test
- **docs:** Add a note about GroupProject limited API
- Add missing comma in ProjectIssueManager _create_attrs
- More flexible docker image
- Add project protected tags management
- **cli:** Print help and usage without config file
- Rename MASTER_ACCESS to MAINTAINER_ACCESS
- **docs:** Add docs build information
- Use docker image with current sources
- **docs:** Add PyYAML requirement notice
- Add Gitter badge to README
- **docs:** Add an example of pipeline schedule vars listing
- **cli:** Exit on config parse error, instead of crashing
- Add support for resource label events
- **docs:** Fix the milestone filetring doc (iid -> iids)
- **docs:** Fix typo in custom attributes example
- Improve error message handling in exceptions
- Add support for members all() method
- Add access control options to protected branch creation

6.8.41 v1.6.0 (2018-08-25)

- **docs:** Don't use hardcoded values for ids
- **docs:** Improve the snippets examples
- **cli:** Output: handle bytes in API responses
- **cli:** Fix the case where we have nothing to print
- Project import: fix the override_params parameter
- Support group and global MR listing
- Implement MR.pipelines()
- MR: add the squash attribute for create/update
- Added support for listing forks of a project
- **docs:** Add/update notes about read-only objects
- Raise an exception on https redirects for PUT/POST
- **docs:** Add a FAQ
- **cli:** Fix the project-export download

6.8.42 v1.5.1 (2018-06-23)

- Fix the ProjectPipelineJob base class (regression)

6.8.43 v1.5.0 (2018-06-22)

- Drop API v3 support
- Drop GetFromListMixin
- Update the sphinx extension for v4 objects
- Add support for user avatar upload
- Add support for project import/export
- Add support for the search API
- Add a global per_page config option
- Add support for the discussions API
- Add support for merged branches deletion
- Add support for Project badges
- Implement user_agent_detail for snippets
- Implement commit.refs()
- Add commit.merge_requests() support
- Deployment: add list filters
- Deploy key: add missing attributes
- Add support for environment stop()

- Add feature flags deletion support
- Update some group attributes
- Issues: add missing attributes and methods
- Fix the participants() decorator
- Add support for group boards
- Implement the markdown rendering API
- Update MR attributes
- Add pipeline listing filters
- Add missing project attributes
- Implement runner jobs listing
- Runners can be created (registered)
- Implement runner token validation
- Update the settings attributes
- Add support for the gitlab CI lint API
- Add support for group badges
- Fix the IssueManager path to avoid redirections
- time_stats(): use an existing attribute if available
- Make ProjectCommitStatus.create work with CLI
- Tests: default to python 3
- ProjectPipelineJob was defined twice
- Silence logs/warnings in unittests
- Add support for MR approval configuration (EE)
- Change post_data default value to None
- Add geo nodes API support (EE)
- Add support for issue links (EE)
- Add support for LDAP groups (EE)
- Add support for board creation/deletion (EE)
- Add support for Project.pull_mirror (EE)
- Add project push rules configuration (EE)
- Add support for the EE license API
- Add support for the LDAP groups API (EE)
- Add support for epics API (EE)
- Fix the non-verbose output of ProjectCommitComment

6.8.44 v1.4.0 (2018-05-19)

- Require requests>=2.4.2
- ProjectKeys can be updated
- Add support for unsharing projects (v3/v4)
- **cli:** fix listing for json and yaml output
- Fix typos in documentation
- Introduce RefreshMixin
- **docs:** Fix the time tracking examples
- **docs:** Commits: add an example of binary file creation
- **cli:** Allow to read args from files
- Add support for recursive tree listing
- **cli:** Restore the –help option behavior
- Add basic unit tests for v4 CLI
- **cli:** Fix listing of strings
- Support downloading a single artifact file
- Update docs copyright years
- Implement attribute types to handle special cases
- **docs:** fix GitLab reference for notes
- Expose additional properties for Gitlab objects
- Fix the impersonation token deletion example
- **feat:** obey the rate limit
- Fix URL encoding on branch methods
- **docs:** add a code example for listing commits of a MR
- **docs:** update service.available() example for API v4
- **tests:** fix functional tests for python3
- **api-usage:** bit more detail for listing with all
- More efficient .get() for group members
- Add docs for the `files` arg in `http_*`
- Deprecate GetFromListMixin

6.8.45 v1.3.0 (2018-02-18)

- Add support for pipeline schedules and schedule variables
- Clarify information about supported python version
- Add manager for jobs within a pipeline
- Fix wrong tag example
- Update the groups documentation
- Add support for MR participants API
- Add support for getting list of user projects
- Add Gitlab and User events support
- Make trigger_pipeline return the pipeline
- Config: support api_version in the global section
- Gitlab can be used as context manager
- Default to API v4
- Add a simplified example for streamed artifacts
- Add documentation about labels update

6.8.46 v1.2.0 (2018-01-01)

- Add mattermost service support
- Add users custom attributes support
- **doc:** Fix project.triggers.create example with v4 API
- Oauth token support
- Remove deprecated objects/methods
- Rework authentication args handling
- Add support for oauth and anonymous auth in config/CLI
- Add support for impersonation tokens API
- Add support for user activities
- Update user docs with gitlab URLs
- **docs:** Bad arguments in projects file documentation
- Add support for user_agent_detail (issues)
- Add a SetMixin
- Add support for project housekeeping
- Expected HTTP response for subscribe is 201
- Update pagination docs for ProjectCommit
- Add doc to get issue from iid
- Make todo() raise GitlabTodoError on error

- Add support for award emojis
- Update project services docs for v4
- Avoid sending empty update data to issue.save
- **docstrings:** Explicitly document pagination arguments
- **docs:** Add a note about password auth being removed from GitLab
- Submanagers: allow having undefined parameters
- ProjectFile.create(): don't modify the input data
- Update testing tools for /session removal
- Update groups tests
- Allow per_page to be used with generators
- Add groups listing attributes
- Add support for subgroups listing
- Add supported python versions in setup.py
- Add support for pagesdomains
- Add support for features flags
- Add support for project and group custom variables
- Add support for user/group/project filter by custom attribute
- Respect content of REQUESTS_CA_BUNDLE and *_proxy envvars

6.8.47 v1.1.0 (2017-11-03)

- Fix trigger variables in v4 API
- Make the delete() method handle / in ids
- **docs:** update the file upload samples
- Tags release description: support / in tag names
- **docs:** improve the labels usage documentation
- Add support for listing project users
- ProjectFileManager.create: handle / in file paths
- Change ProjectUser and GroupProject base class
- **docs:** document `get_create_attrs` in the API tutorial
- Document the Gitlab session parameter
- ProjectFileManager: custom update() method
- Project: add support for printing_merge_request_link_enabled attr
- Update the ssl_verify docstring
- Add support for group milestones
- Add support for GPG keys
- Add support for wiki pages

- Update the repository_blob documentation
- Fix the CLI for objects without ID (API v4)
- Add a contributed Dockerfile
- Pagination generators: expose more information
- Module's base objects serialization
- **doc:** Add sample code for client-side certificates

6.8.48 v1.0.2 (2017-09-29)

- **docs:** remove example usage of submanagers
- Properly handle the labels attribute in ProjectMergeRequest
- ProjectFile: handle / in path for delete() and save()

6.8.49 v1.0.1 (2017-09-21)

- Tags can be retrieved by ID
- Add the server response in GitlabError exceptions
- Add support for project file upload
- Minor typo fix in “Switching to v4” documentation
- Fix password authentication for v4
- Fix the labels attrs on MR and issues
- Exceptions: use a proper error message
- Fix http_get method in get artifacts and job trace
- CommitStatus: sha is parent attribute
- Fix a couple listing calls to allow proper pagination
- Add missing doc file

6.8.50 v1.0.0 (2017-09-08)

- Support for API v4. See <http://python-gitlab.readthedocs.io/en/master/switching-to-v4.html>
- Support SSL verification via internal CA bundle
- Docs: Add link to gitlab docs on obtaining a token
- Added dependency injection support for Session
- Fixed repository_compare examples
- Fix changelog and release notes inclusion in sdist
- Missing expires_at in GroupMembers update
- Add lower-level methods for Gitlab()

6.8.51 v0.21.2 (2017-06-11)

- Install doc: use sudo for system commands
- **v4:** Make MR work properly
- Remove extra_attrs argument from _raw_list
- **v4:** Make project issues work properly
- Fix urlencode() usage (python 2/3) (#268)
- Fixed spelling mistake (#269)
- Add new event types to ProjectHook

6.8.52 v0.21.1 (2017-05-25)

- Fix the manager name for jobs in the Project class
- Fix the docs

6.8.53 v0.21 (2017-05-24)

- Add time_stats to ProjectMergeRequest
- Update User options for creation and update (#246)
- Add milestone.merge_requests() API
- Fix docs typo (s/correspdning/corresponding/)
- Support milestone start date (#251)
- Add support for priority attribute in labels (#256)
- Add support for nested groups (#257)
- Make GroupProjectManager a subclass of ProjectManager (#255)
- Available services: return a list instead of JSON (#258)
- MR: add support for time tracking features (#248)
- Fixed repository_tree and repository_blob path encoding (#265)
- Add ‘search’ attribute to projects.list()
- Initial gitlab API v4 support
- Reorganise the code to handle v3 and v4 objects
- Allow 202 as delete return code
- Deprecate parameter related methods in gitlab.Gitlab

6.8.54 v0.20 (2017-03-25)

- Add time tracking support (#222)
- Improve changelog (#229, #230)
- Make sure that manager objects are never overwritten (#209)
- Include chanlog and release notes in docs
- Add DeployKey{,Manager} classes (#212)
- Add support for merge request notes deletion (#227)
- Properly handle extra args when listing with all=True (#233)
- Implement pipeline creation API (#237)
- Fix spent_time methods
- Add ‘delete source branch’ option when creating MR (#241)
- Provide API wrapper for cherry picking commits (#236)
- Stop listing if recursion limit is hit (#234)

6.8.55 v0.19 (2017-02-21)

- Update project.archive() docs
- Support the scope attribute in runners.list()
- Add support for project runners
- Add support for commit creation
- Fix install doc
- Add builds-email and pipelines-email services
- Deploy keys: rework enable/disable
- Document the dynamic aspect of objects
- Add pipeline_events to ProjectHook attrs
- Add due_date attribute to ProjectIssue
- Handle settings.domain_whitelist, partly
- {Project,Group}Member: support expires_at attribute

6.8.56 v0.18 (2016-12-27)

- Fix JIRA service editing for GitLab 8.14+
- Add jira_issue_transition_id to the JIRA service optional fields
- Added support for Snippets (new API in Gitlab 8.15)
- **docs:** update pagination section
- **docs:** artifacts example: open file in wb mode
- **CLI:** ignore empty arguments

- **CLI:** Fix wrong use of arguments
- **docs:** Add doc for snippets
- Fix duplicated data in API docs
- Update known attributes for projects
- sudo: always use strings

6.8.57 v0.17 (2016-12-02)

- README: add badges for pypi and RTD
- Fix ProjectBuild.play (raised error on success)
- Pass kwargs to the object factory
- Add .tox to ignore to respect default tox settings
- Convert response list to single data source for iid requests
- Add support for boards API
- Add support for Gitlab.version()
- Add support for broadcast messages API
- Add support for the notification settings API
- Don't overwrite attributes returned by the server
- Fix bug when retrieving changes for merge request
- Feature: enable / disable the deploy key in a project
- Docs: add a note for python 3.5 for file content update
- ProjectHook: support the token attribute
- Rework the API documentation
- Fix docstring for http_{username,password}
- Build managers on demand on GitlabObject's
- API docs: add managers doc in GitlabObject's
- Sphinx ext: factorize the build methods
- Implement __repr__ for gitlab objects
- Add a ‘report a bug’ link on doc
- Remove deprecated methods
- Implement merge requests diff support
- Make the manager objects creation more dynamic
- Add support for templates API
- Add attr ‘created_at’ to ProjectIssueNote
- Add attr ‘updated_at’ to ProjectIssue
- CLI: add support for project all –all
- Add support for triggering a new build

- Rework requests arguments (support latest requests release)
- Fix `should_remove_source_branch`

6.8.58 v0.16 (2016-10-16)

- Add the ability to fork to a specific namespace
- JIRA service - add `api_url` to optional attributes
- Fix bug: Missing coma concatenates array values
- docs: branch protection notes
- Create a project in a group
- Add `only_allow_merge_if_build_succeeds` option to project objects
- Add support for `-all` in CLI
- Fix examples for file modification
- Use the plural `merge_requests` URL everywhere
- Rework travis and tox setup
- Workaround gitlab setup failure in tests
- Add `ProjectBuild.erase()`
- Implement `ProjectBuild.play()`

6.8.59 v0.15.1 (2016-10-16)

- docs: improve the pagination section
- Fix and test pagination
- ‘path’ is an existing gitlab attr, don’t use it as method argument

6.8.60 v0.15 (2016-08-28)

- Add a basic HTTP debug method
- Run more tests in travis
- Fix fork creation documentation
- Add more API examples in docs
- Update the `ApplicationSettings` attributes
- Implement the todo API
- Add sidekiq metrics support
- Move the constants at the gitlab root level
- Remove methods marked as deprecated 7 months ago
- Refactor the `Gitlab` class
- Remove `_get_list_or_object()` and its tests

- Fix canGet attribute (typo)
- Remove unused ProjectTagReleaseManager class
- Add support for project services API
- Add support for project pipelines
- Add support for access requests
- Add support for project deployments

6.8.61 v0.14 (2016-08-07)

- Remove ‘next_url’ from kwargs before passing it to the cls constructor.
- List projects under group
- Add support for subscribe and unsubscribe in issues
- Project issue: doc and CLI for (un)subscribe
- Added support for HTTP basic authentication
- Add support for build artifacts and trace
- –title is a required argument for ProjectMilestone
- Commit status: add optional context url
- Commit status: optional get attrs
- Add support for commit comments
- Issues: add optional listing parameters
- Issues: add missing optional listing parameters
- Project issue: proper update attributes
- Add support for project-issue move
- Update ProjectLabel attributes
- Milestone: optional listing attrs
- Add support for namespaces
- Add support for label (un)subscribe
- MR: add (un)subscribe support
- Add note_events to project hooks attributes
- Add code examples for a bunch of resources
- Implement user emails support
- Project: add VISIBILITY_* constants
- Fix the Project.archive call
- Implement archive/unarchive for a project
- Update ProjectSnippet attributes
- Fix ProjectMember update
- Implement sharing project with a group

- Implement CLI for project archive/unarchive/share
- Implement runners global API
- Gitlab: add managers for build-related resources
- Implement ProjectBuild.keep_artifacts
- Allow to stream the downloads when appropriate
- Groups can be updated
- Replace Snippet.Content() with a new content() method
- CLI: refactor _die()
- Improve commit statuses and comments
- Add support from listing group issues
- Added a new project attribute to enable the container registry.
- Add a contributing section in README
- Add support for global deploy key listing
- Add support for project environments
- MR: get list of changes and commits
- Fix the listing of some resources
- MR: fix updates
- Handle empty messages from server in exceptions
- MR (un)subscribe: don't fail if state doesn't change
- MR merge(): update the object

6.8.62 v0.13 (2016-05-16)

- Add support for MergeRequest validation
- MR: add support for cancel_merge_when_build_succeeds
- MR: add support for closes_issues
- Add “external” parameter for users
- Add deletion support for issues and MR
- Add missing group creation parameters
- Add a Session instance for all HTTP requests
- Enable updates on ProjectIssueNotes
- Add support for Project raw_blob
- Implement project compare
- Implement project contributors
- Drop the next_url attribute when listing
- Remove unnecessary canUpdate property from ProjectIssuesNote
- Add new optional attributes for projects

- Enable deprecation warnings for gitlab only
- Rework merge requests update
- Rework the Gitlab.delete method
- ProjectFile: file_path is required for deletion
- Rename some methods to better match the API URLs
- Deprecate the file_* methods in favor of the files manager
- Implement star/unstar for projects
- Implement list/get licenses
- Manage optional parameters for list() and get()

6.8.63 v0.12.2 (2016-03-19)

- Add new ProjectHook attributes
- Add support for user block/unblock
- Fix GitlabObject creation in _custom_list
- Add support for more CLI subcommands
- Add some unit tests for CLI
- Add a coverage tox env
- Define GitlabObject.as_dict() to dump object as a dict
- Define GitlabObject.__eq__() and __ne__() equivalence methods
- Define UserManager.search() to search for users
- Define UserManager.get_by_username() to get a user by username
- Implement “user search” CLI
- Improve the doc for UserManager
- CLI: implement user get-by-username
- Re-implement _custom_list in the Gitlab class
- Fix the ‘invalid syntax’ error on Python 3.2
- Gitlab.update(): use the proper attributes if defined

6.8.64 v0.12.1 (2016-02-03)

- Fix a broken upload to pypi

6.8.65 v0.12 (2016-02-03)

- Improve documentation
- Improve unit tests
- Improve test scripts
- Skip BaseManager attributes when encoding to JSON
- Fix the json() method for python 3
- Add Travis CI support
- Add a decode method for ProjectFile
- Make connection exceptions more explicit
- Fix ProjectLabel get and delete
- Implement ProjectMilestone.issues()
- ProjectTag supports deletion
- Implement setting release info on a tag
- Implement project triggers support
- Implement project variables support
- Add support for application settings
- Fix the ‘password’ requirement for User creation
- Add sudo support
- Fix project update
- Fix Project.tree()
- Add support for project builds

6.8.66 v0.11.1 (2016-01-17)

- Fix discovery of parents object attrs for managers
- Support setting commit status
- Support deletion without getting the object first
- Improve the documentation

6.8.67 v0.11 (2016-01-09)

- functional_tests.sh: support python 2 and 3
- Add a get method for GitlabObject
- CLI: Add the -g short option for --gitlab
- Provide a create method for GitlabObject’s
- Rename the _created attribute _from_api
- More unit tests

- CLI: fix error when arguments are missing (python 3)
- Remove deprecated methods
- Implement managers to get access to resources
- Documentation improvements
- Add fork project support
- Deprecate the “old” Gitlab methods
- Add support for groups search

6.8.68 v0.10 (2015-12-29)

- Implement pagination for list() (#63)
- Fix url when fetching a single MergeRequest
- Add support to update MergeRequestNotes
- API: Provide a Gitlab.from_config method
- setup.py: require requests>=1 (#69)
- Fix deletion of object not using ‘id’ as ID (#68)
- Fix GET/POST for project files
- Make ‘confirm’ an optional attribute for user creation
- Python 3 compatibility fixes
- Add support for group members update (#73)

6.8.69 v0.9.2 (2015-07-11)

- CLI: fix the update and delete subcommands (#62)

6.8.70 v0.9.1 (2015-05-15)

- Fix the setup.py script

6.8.71 v0.9 (2015-05-15)

- Implement argparse library for parsing argument on CLI
- Provide unit tests and (a few) functional tests
- Provide PEP8 tests
- Use tox to run the tests
- CLI: provide a –config-file option
- Turn the gitlab module into a proper package
- Allow projects to be updated
- Use more pythonic names for some methods

- Deprecate some Gitlab object methods:
 - `raw*` methods should never have been exposed; replace them with `_raw_*` methods
 - `setCredentials` and `setToken` are replaced with `set_credentials` and `set_token`
- Sphinx: don't hardcode the version in `conf.py`

6.8.72 v0.8 (2014-10-26)

- Better python 2.6 and python 3 support
- Timeout support in HTTP requests
- `Gitlab.get()` raised `GitlabListError` instead of `GitlabGetError`
- Support api-objects which don't have id in api response
- Add `ProjectLabel` and `ProjectFile` classes
- Moved url attributes to separate list
- Added list for delete attributes

6.8.73 v0.7 (2014-08-21)

- Fix license classifier in `setup.py`
- Fix encoding error when printing to redirected output
- Fix encoding error when updating with redirected output
- Add support for `UserKey` listing and deletion
- Add support for branches creation and deletion
- Support `state_event` in `ProjectMilestone` (#30)
- Support namespace/name for project id (#28)
- Fix handling of boolean values (#22)

6.8.74 v0.6 (2014-01-16)

- IDs can be unicode (#15)
- `ProjectMember`: constructor should not create a `User` object
- Add support for extra parameters when listing all projects (#12)
- Projects listing: explicitly define arguments for pagination

6.8.75 v0.5 (2013-12-26)

- Add SSH key for user
- Fix comments
- Add support for project events
- Support creation of projects for users
- Project: add methods for create/update/delete files
- Support projects listing: search, all, owned
- System hooks can't be updated
- Project.archive(): download tarball of the project
- Define new optional attributes for user creation
- Provide constants for access permissions in groups

6.8.76 v0.4 (2013-09-26)

- Fix strings encoding (Closes #6)
- Allow to get a project commit (GitLab 6.1)
- ProjectMergeRequest: fix Note() method
- Gitlab 6.1 methods: diff, blob (commit), tree, blob (project)
- Add support for Gitlab 6.1 group members

6.8.77 v0.3 (2013-08-27)

- Use PRIVATE-TOKEN header for passing the auth token
- provide an AUTHORS file
- cli: support ssl_verify config option
- Add ssl_verify option to Gitlab object. Defaults to True
- Correct url for merge requests API.

6.8.78 v0.2 (2013-08-08)

- provide a pip requirements.txt
- drop some debug statements

6.8.79 v0.1 (2013-07-08)

- Initial release

6.9 Release notes

Prior to version 2.0.0 and GitHub Releases, a summary of changes was maintained in release notes. They are available below for historical purposes. For the list of current releases, including breaking changes, please see the [changelog](#).

6.9.1 Changes from 1.8 to 1.9

- `ProjectMemberManager.all()` and `GroupMemberManager.all()` now return a list of `ProjectMember` and `GroupMember` objects respectively, instead of a list of dicts.

6.9.2 Changes from 1.7 to 1.8

- You can now use the `query_parameters` argument in method calls to define arguments to send to the GitLab server. This allows to avoid conflicts between python-gitlab and GitLab server variables, and allows to use the python reserved keywords as GitLab arguments.

The following examples make the same GitLab request with the 2 syntaxes:

```
projects = gl.projects.list(owned=True, starred=True)
projects = gl.projects.list(query_parameters={'owned': True, 'starred': True})
```

The following example only works with the new parameter:

```
activities = gl.user_activities.list(
    query_parameters={'from': '2019-01-01'},
    all=True)
```

- Additionally the `all` parameter is not sent to the GitLab anymore.

6.9.3 Changes from 1.5 to 1.6

- When python-gitlab detects HTTP redirections from http to https it will raise a `RedirectionError` instead of a cryptic error.

Make sure to use an `https://` protocol in your GitLab URL parameter if the server requires it.

6.9.4 Changes from 1.4 to 1.5

- APIv3 support has been removed. Use the 1.4 release/branch if you need v3 support.
- GitLab EE features are now supported: Geo nodes, issue links, LDAP groups, project/group boards, project mirror pulling, project push rules, EE license configuration, epics.
- The `GetFromListMixin` class has been removed. The `get()` method is not available anymore for the following managers:
 - `UserKeyManager`

- DeployKeyManager
 - GroupAccessRequestManager
 - GroupIssueManager
 - GroupProjectManager
 - GroupSubgroupManager
 - IssueManager
 - ProjectCommitStatusManager
 - ProjectEnvironmentManager
 - ProjectLabelManager
 - ProjectPipelineJobManager
 - ProjectAccessRequestManager
 - TodoManager
- ProjectPipelineJob do not heritate from ProjectJob anymore and thus can only be listed.

6.9.5 Changes from 1.3 to 1.4

- 1.4 is the last release supporting the v3 API, and the related code will be removed in the 1.5 version.

If you are using a Gitlab server version that does not support the v4 API you can:

- upgrade the server (recommended)
- make sure to use version 1.4 of python-gitlab (`pip install python-gitlab==1.4`)

See also the [Switching to GitLab API v4 documentation](#).

- python-gitlab now handles the server rate limiting feature. It will pause for the required time when reaching the limit ([documentation](#))
- The `GetFromListMixin.get()` method is deprecated and will be removed in the next python-gitlab version. The goal of this mixin/method is to provide a way to get an object by looping through a list for GitLab objects that don't support the GET method. The method [is broken](#) and conflicts with the GET method now supported by some GitLab objects.

You can implement your own method with something like:

```
def get_from_list(self, id):  
    for obj in self.list(as_list=False):  
        if obj.get_id() == id:  
            return obj
```

- The `GroupMemberManager`, `NamespaceManager` and `ProjectBoardManager` managers now use the GET API from GitLab instead of the `GetFromListMixin.get()` method.

6.9.6 Changes from 1.2 to 1.3

- `gitlab.Gitlab` objects can be used as context managers in a `with` block.

6.9.7 Changes from 1.1 to 1.2

- python-gitlab now respects the `*_proxy`, `REQUESTS_CA_BUNDLE` and `CURL_CA_BUNDLE` environment variables (#352)
- The following deprecated methods and objects have been removed:
 - `gitlab.v3.object` `Key` and `KeyManager` objects: use `DeployKey` and `DeployKeyManager` instead
 - `gitlab.v3.objects`.`Project` `archive_` and `unarchive_` methods
 - `gitlab.Gitlab` `credentials_auth`, `token_auth`, `set_url`, `set_token` and `set_credentials` methods. Once a `Gitlab` object has been created its URL and authentication information cannot be updated: create a new `Gitlab` object if you need to use new information
- The `todo()` method raises a `GitlabTodoError` exception on error

6.9.8 Changes from 1.0.2 to 1.1

- The `ProjectUser` class doesn't inherit from `User` anymore, and the `GroupProject` class doesn't inherit from `Project` anymore. The Gitlab API doesn't provide the same set of features for these objects, so python-gitlab objects shouldn't try to workaround that.

You can create `User` or `Project` objects from `ProjectUser` and `GroupProject` objects using the `id` attribute:

```
for gr_project in group.projects.list():
    # lazy object creation avoids a Gitlab API request
    project = gl.projects.get(gr_project.id, lazy=True)
    project.default_branch = 'develop'
    project.save()
```

6.9.9 Changes from 0.21 to 1.0.0

1.0.0 brings a stable python-gitlab API for the v4 Gitlab API. v3 is still used by default.

v4 is mostly compatible with the v3, but some important changes have been introduced. Make sure to read [Switching to GitLab API v4](#).

The development focus will be v4 from now on. v3 has been deprecated by GitLab and will disappear from python-gitlab at some point.

6.9.10 Changes from 0.20 to 0.21

- Initial support for the v4 API (experimental)

The support for v4 is stable enough to be tested, but some features might be broken. Please report issues to <https://github.com/python-gitlab/python-gitlab/issues/>

Be aware that the python-gitlab API for v4 objects might change in the next releases.

Warning: Consider defining explicitly which API version you want to use in the configuration files or in your `gitlab.Gitlab` instances. The default will change from v3 to v4 soon.

- Several methods have been deprecated in the `gitlab.Gitlab` class:
 - `credentials_auth()` is deprecated and will be removed. Call `auth()`.
 - `token_auth()` is deprecated and will be removed. Call `auth()`.
 - `set_url()` is deprecated, create a new `Gitlab` instance if you need an updated URL.
 - `set_token()` is deprecated, use the `private_token` argument of the `Gitlab` constructor.
 - `set_credentials()` is deprecated, use the `email` and `password` arguments of the `Gitlab` constructor.
- The service listing method (`ProjectServiceManager.list()`) now returns a python list instead of a JSON string.

6.9.11 Changes from 0.19 to 0.20

- The `projects` attribute of `Group` objects is not a list of `Project` objects anymore. It is a `Manager` object giving access to `GroupProject` objects. To get the list of projects use:

```
group.projects.list()
```

Documentation: http://python-gitlab.readthedocs.io/en/stable/gl_objects/groups.html#examples

Related issue: <https://github.com/python-gitlab/python-gitlab/issues/209>

- The `Key` objects are deprecated in favor of the new `DeployKey` objects. They are exactly the same but the name makes more sense.

Documentation: http://python-gitlab.readthedocs.io/en/stable/gl_objects/deploy_keys.html

Related issue: <https://github.com/python-gitlab/python-gitlab/issues/212>

6.10 FAQ

I cannot edit the merge request / issue I've just retrieved

It is likely that you used a `MergeRequest`, `GroupMergeRequest`, `Issue` or `GroupIssue` object. These objects cannot be edited. But you can create a new `ProjectMergeRequest` or `ProjectIssue` object to apply changes. For example:

```
issue = gl.issues.list()[0]
project = gl.projects.get(issue.project_id, lazy=True)
editable_issue = project.issues.get(issue.iid, lazy=True)
# you can now edit the object
```

See the [merge requests example](#) and the [issues examples](#).

I get an `AttributeError` when accessing attributes of an object retrieved via a `list()` call.

Fetching a list of objects, doesn't always include all attributes in the objects. To retrieve an object with all attributes use a `get()` call.

Example with projects:

```
for projects in gl.projects.list():
    # Retrieve project object with all attributes
    project = gl.projects.get(project.id)
```

How can I clone the repository of a project?

python-gitlab doesn't provide an API to clone a project. You have to use a git library or call the `git` command.

The git URI is exposed in the `ssh_url_to_repo` attribute of `Project` objects.

Example:

```
import subprocess

project = gl.projects.create(data) # or gl.projects.get(project_id)
print(project.attributes) # displays all the attributes
git_url = project.ssh_url_to_repo
subprocess.call(['git', 'clone', git_url])
```

I get an `AttributeError` when accessing attributes after `save()` or `refresh()`.

You are most likely trying to access an attribute that was not returned by the server on the second request. Please look at the documentation in [Attributes in updated objects](#) to see how to avoid this.

I passed `all=True` (or `--all` via the CLI) to the API and I still cannot see all items returned.

Use `get_all=True` (or `--get-all` via the CLI). See [Pagination](#) for more details.

CHAPTER
SEVEN

INDICES AND TABLES

- genindex
- modindex
- search

PYTHON MODULE INDEX

g

`gitlab.base`, 423
`gitlab.cli`, 425
`gitlab.config`, 426
`gitlab.const`, 427
`gitlab.exceptions`, 428
`gitlab.mixins`, 445
`gitlab.utils`, 454
`gitlab.v4`, 423
`gitlab.v4.objects`, 182

INDEX

Symbols

--access-level
 gitlab-group-access-request-approve
 command line option, 490
 gitlab-group-access-token-create
 command line option, 491
 gitlab-group-invitation-create command
 line option, 523
 gitlab-group-invitation-update command
 line option, 525
 gitlab-group-member-create command line
 option, 531
 gitlab-group-member-update command line
 option, 532
 gitlab-project-access-request-approve
 command line option, 577
 gitlab-project-access-token-create
 command line option, 578
 gitlab-project-invitation-create
 command line option, 626
 gitlab-project-invitation-update
 command line option, 628
 gitlab-project-member-create command
 line option, 658
 gitlab-project-member-update command
 line option, 660
 gitlab-runner-create command line
 option, 751
 gitlab-runner-update command line
 option, 753

--access-raw-diffs
 gitlab-project-merge-request-changes
 command line option, 663

--action
 gitlab-event-list command line option,
 477
 gitlab-project-event-list command line
 option, 615
 gitlab-todo-list command line option, 760
 gitlab-user-event-list command line
 option, 772

--actions

--active
 gitlab-project-pipeline-schedule-create
 command line option, 705
 gitlab-project-pipeline-schedule-update
 command line option, 707
 gitlab-runner-create command line
 option, 751
 gitlab-runner-update command line
 option, 752
 gitlab-user-list command line option, 766

--admin
 gitlab-user-create command line option,
 764
 gitlab-user-update command line option,
 768

--after
 gitlab-event-list command line option,
 478
 gitlab-project-event-list command line
 option, 615
 gitlab-user-event-list command line
 option, 772

--after-sign-out-path
 gitlab-application-settings-update
 command line option, 466

--all
 gitlab-application-list command line
 option, 462
 gitlab-audit-event-list command line
 option, 468
 gitlab-broadcast-message-list command
 line option, 469
 gitlab-current-user-email-list command
 line option, 472
 gitlab-current-user-gpg-key-list
 command line option, 473
 gitlab-current-user-key-list command
 line option, 474
 gitlab-deploy-key-list command line
 option, 476

gitlab-deploy-token-list command line option, 476
gitlab-dockerfile-list command line option, 477
gitlab-event-list command line option, 478
gitlab-feature-list command line option, 478
gitlab-geo-node-list command line option, 481
gitlab-gitignore-list command line option, 482
gitlab-gitlabciyml-list command line option, 483
gitlab-group-access-request-list command line option, 491
gitlab-group-access-token-list command line option, 492
gitlab-group-audit-event-list command line option, 493
gitlab-group-badge-list command line option, 495
gitlab-group-billable-member-list command line option, 496
gitlab-group-billable-member-membership-list command line option, 497
gitlab-group-board-list command line option, 498
gitlab-group-board-list-list command line option, 500
gitlab-group-cluster-list command line option, 502
gitlab-group-custom-attribute-list command line option, 504
gitlab-group-deploy-token-list command line option, 505
gitlab-group-descendant-group-list command line option, 506
gitlab-group-emoji-list command line option, 511
gitlab-group-epic-issue-list command line option, 514
gitlab-group-epic-list command line option, 508
gitlab-group-epic-note-award-emoji-list command line option, 518
gitlab-group-epic-note-list command line option, 516
gitlab-group-epic-resource-label-event-list command line option, 519
gitlab-group-hook-list command line option, 522
gitlab-group-invitation-list command line option, 525
gitlab-group-issue-list command line option, 526
gitlab-group-iteration-list command line option, 527
gitlab-group-label-list command line option, 529
gitlab-group-list command line option, 487
gitlab-group-member-all-list command line option, 533
gitlab-group-member-list command line option, 532
gitlab-group-merge-request-list command line option, 535
gitlab-group-milestone-list command line option, 537
gitlab-group-package-list command line option, 540
gitlab-group-project-list command line option, 541
gitlab-group-runner-list command line option, 544
gitlab-group-subgroup-list command line option, 545
gitlab-group-variable-list command line option, 546
gitlab-group-wiki-list command line option, 548
gitlab-hook-list command line option, 550
gitlab-issue-list command line option, 551
gitlab-ldap-group-list command line option, 553
gitlab-license-list command line option, 554
gitlab-merge-request-list command line option, 556
gitlab-namespace-list command line option, 557
gitlab-pages-domain-list command line option, 559
gitlab-personal-access-token-list command line option, 559
gitlab-project-access-request-list command line option, 578
gitlab-project-access-token-list command line option, 579
gitlab-project-approval-rule-list command line option, 582
gitlab-project-audit-event-list command line option, 584
gitlab-project-badge-list command line option, 586
gitlab-project-board-list command line

```

    option, 588
gitlab-project-board-list-list command
    line option, 590
gitlab-project-branch-list command line
    option, 592
gitlab-project-cluster-list command
    line option, 595
gitlab-project-commit-comment-list
    command line option, 600
gitlab-project-commit-discussion-list
    command line option, 601
gitlab-project-commit-list command line
    option, 598
gitlab-project-commit-status-list
    command line option, 605
gitlab-project-custom-attribute-list
    command line option, 606
gitlab-project-deploy-token-list
    command line option, 607
gitlab-project-deployment-list command
    line option, 609
gitlab-project-deployment-merge-request-list
    command line option, 612
gitlab-project-environment-list command
    line option, 614
gitlab-project-event-list command line
    option, 615
gitlab-project-fork-list command line
    option, 620
gitlab-project-hook-list command line
    option, 622
gitlab-project-integration-list command
    line option, 625
gitlab-project-invitation-list command
    line option, 627
gitlab-project-issue-award-emoji-list
    command line option, 637
gitlab-project-issue-discussion-list
    command line option, 639
gitlab-project-issue-link-list command
    line option, 642
gitlab-project-issue-list command line
    option, 631
gitlab-project-issue-note-award-emoji-list
    command line option, 646
gitlab-project-issue-note-list command
    line option, 644
gitlab-project-issue-resource-label-event-list
    command line option, 647
gitlab-project-issue-resource-milestone-event-dgit
    command line option, 648
gitlab-project-issue-resource-state-event-list
    command line option, 649
gitlab-project-job-list command line
    option, 652
gitlab-project-key-list command line
    option, 655
gitlab-project-label-list command line
    option, 657
gitlab-project-list command line option,
    567
gitlab-project-member-all-list command
    line option, 661
gitlab-project-member-list command line
    option, 659
gitlab-project-merge-request-approval-rule-list
    command line option, 674
gitlab-project-merge-request-award-emoji-list
    command line option, 678
gitlab-project-merge-request-diff-list
    command line option, 679
gitlab-project-merge-request-discussion-list
    command line option, 680
gitlab-project-merge-request-list
    command line option, 667
gitlab-project-merge-request-note-award-emoji-list
    command line option, 687
gitlab-project-merge-request-note-list
    command line option, 684
gitlab-project-merge-request-pipeline-list
    command line option, 687
gitlab-project-merge-request-resource-label-event-list
    command line option, 688
gitlab-project-merge-request-resource-milestone-event-
    command line option, 689
gitlab-project-merge-request-resource-state-event-list
    command line option, 690
gitlab-project-merge-train-list command
    line option, 691
gitlab-project-milestone-list command
    line option, 693
gitlab-project-note-list command line
    option, 695
gitlab-project-package-file-list
    command line option, 698
gitlab-project-package-list command
    line option, 698
gitlab-project-pages-domain-list
    command line option, 700
gitlab-project-pipeline-bridge-list
    command line option, 703
gitlab-project-pipeline-job-list
    command line option, 704
gitlab-project-pipeline-list command
    line option, 702
gitlab-project-pipeline-schedule-list
    command line option, 706
gitlab-project-pipeline-variable-list

```

command line option, 710
gitlab-project-protected-branch-list command line option, 712
gitlab-project-protected-environment-list command line option, 714
gitlab-project-protected-tag-list command line option, 715
gitlab-project-registry-repository-list command line option, 718
gitlab-project-registry-tag-list command line option, 720
gitlab-project-release-link-list command line option, 724
gitlab-project-release-list command line option, 722
gitlab-project-remote-mirror-list command line option, 726
gitlab-project-runner-list command line option, 727
gitlab-project-service-list command line option, 729
gitlab-project-snippet-award-emoji-list command line option, 733
gitlab-project-snippet-discussion-list command line option, 735
gitlab-project-snippet-list command line option, 731
gitlab-project-snippet-note-award-emoji-list command line option, 741
gitlab-project-snippet-note-list command line option, 739
gitlab-project-tag-list command line option, 743
gitlab-project-trigger-list command line option, 744
gitlab-project-user-list command line option, 745
gitlab-project-variable-list command line option, 747
gitlab-project-wiki-list command line option, 749
gitlab-runner-all-list command line option, 753
gitlab-runner-job-list command line option, 754
gitlab-runner-list command line option, 752
gitlab-shared-project-list command line option, 755
gitlab-snippet-list command line option, 757
gitlab-starred-project-list command line option, 759
gitlab-todo-list command line option, 760
gitlab-topic-list command line option, 762
gitlab-user-activities-list command line option, 769
gitlab-user-custom-attribute-list command line option, 770
gitlab-user-email-list command line option, 772
gitlab-user-event-list command line option, 772
gitlab-user-gpg-key-list command line option, 774
gitlab-user-impersonation-token-list command line option, 775
gitlab-user-key-list command line option, 777
gitlab-user-list command line option, 766
gitlab-user-membership-list command line option, 778
gitlab-user-project-list command line option, 781
gitlab-variable-list command line option, 783
--all-available
gitlab-group-descendant-group-list command line option, 506
gitlab-group-list command line option, 486
gitlab-group-subgroup-list command line option, 545
--allow-collaboration
gitlab-project-merge-request-create command line option, 664
--allow-local-requests-from-hooks-and-services
gitlab-application-settings-update command line option, 467
--allow-local-requests-from-system-hooks
gitlab-application-settings-update command line option, 467
--allow-local-requests-from-web-hooks-and-services
gitlab-application-settings-update command line option, 467
--allow-maintainer-to-push
gitlab-project-merge-request-create command line option, 664
gitlab-project-merge-request-update command line option, 671
--allow-merge-on-skipped-pipeline
gitlab-project-create command line option, 563
gitlab-project-update command line option, 574
--allowed-to-merge
gitlab-project-protected-branch-create

```

    command line option, 711
--allowed-to-push
    gitlab-project-protected-branch-create
        command line option, 711
--allowed-to-unprotect
    gitlab-project-protected-branch-create
        command line option, 711
--analytics-access-level
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 574
--api-version
    gitlab command line option, 460
--approval-project-rule-id
    gitlab-project-merge-request-approval-rule-create
        command line option, 673
--approval-rule-id
    gitlab-project-merge-request-approval-rule-update
        command line option, 675
--approval-rules
    gitlab-project-protected-environment-create
        command line option, 713
--approvals-before-merge
    gitlab-project-approval-update command
        line option, 580
    gitlab-project-create command line
        option, 563
    gitlab-project-merge-request-create
        command line option, 664
    gitlab-project-update command line
        option, 574
--approvals-required
    gitlab-project-approval-rule-create
        command line option, 581
    gitlab-project-merge-request-approval-rule-create
        command line option, 673
    gitlab-project-merge-request-approval-rule-update
        command line option, 675
    gitlab-project-merge-request-approval-update
        command line option, 672
--approved-by-ids
    gitlab-group-merge-request-list command
        line option, 534
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-deployment-merge-request-list
        command line option, 611
    gitlab-project-merge-request-list
        command line option, 666
--approver-ids
    gitlab-group-merge-request-list command
        line option, 534
    gitlab-merge-request-list command line
        option, 555
option, 555
gitlab-project-deployment-merge-request-list
    command line option, 611
gitlab-project-merge-request-list
    command line option, 666
--archived
    gitlab-group-project-list command line
        option, 540
    gitlab-project-fork-list command line
        option, 620
    gitlab-project-list command line option,
        567
    gitlab-shared-project-list command line
        option, 755
    gitlab-starred-project-list command
        line option, 758
    gitlab-user-project-list command line
        option, 780
gitlab-project-artifact command line
        option, 561
gitlab-project-artifact-raw command
    line option, 583
--asset-proxy-allowlist
    gitlab-application-settings-update
        command line option, 467
--asset-proxy-enabled
    gitlab-application-settings-update
        command line option, 466
--asset-proxy-url
    gitlab-application-settings-update
        command line option, 466
--asset-proxy-whitelist
    gitlab-application-settings-update
        command line option, 467
gitlab-project-release-create command
    line option, 721
--assignee-id
    gitlab-group-issue-list command line
        option, 526
    gitlab-group-merge-request-list command
        line option, 534
    gitlab-issue-list command line option,
        551
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-deployment-merge-request-list
        command line option, 611
    gitlab-project-issue-create command
        line option, 629
    gitlab-project-issue-list command line
        option, 631
    gitlab-project-issue-update command

```

```
    line option, 635
gitlab-project-merge-request-create
    command line option, 664
gitlab-project-merge-request-list
    command line option, 666
gitlab-project-merge-request-update
    command line option, 671
--assignee-ids
gitlab-project-issue-create command
    line option, 629
gitlab-project-issue-update command
    line option, 635
gitlab-project-merge-request-create
    command line option, 664
--author-email
gitlab-project-commit-create command
    line option, 596
gitlab-project-file-create command line
    option, 617
gitlab-project-file-update command line
    option, 619
--author-email-regex
gitlab-group-push-rules-create command
    line option, 542
gitlab-group-push-rules-update command
    line option, 543
gitlab-project-push-rules-create
    command line option, 716
gitlab-project-push-rules-update
    command line option, 717
--author-id
gitlab-group-epic-list command line
    option, 508
gitlab-group-issue-list command line
    option, 526
gitlab-group-merge-request-list command
    line option, 534
gitlab-issue-list command line option,
    551
gitlab-merge-request-list command line
    option, 555
gitlab-project-deployment-merge-request-list
    command line option, 611
gitlab-project-issue-list command line
    option, 631
gitlab-project-merge-request-list
    command line option, 666
gitlab-todo-list command line option, 760
--author-name
gitlab-project-commit-create command
    line option, 597
gitlab-project-file-create command line
    option, 617
gitlab-project-file-update command line
    option, 619
--author-username
gitlab-merge-request-list command line
    option, 555
gitlab-project-deployment-merge-request-list
    command line option, 611
--auto-cancel-pending-pipelines
gitlab-project-create command line
    option, 563
gitlab-project-update command line
    option, 574
--auto-devops-deploy-strategy
gitlab-project-create command line
    option, 563
gitlab-project-update command line
    option, 574
--auto-devops-enabled
gitlab-group-create command line option,
    485
gitlab-group-update command line option,
    489
gitlab-project-create command line
    option, 563
gitlab-project-update command line
    option, 574
--autoclose-referenced-issues
gitlab-project-create command line
    option, 563
gitlab-project-update command line
    option, 574
--avatar
gitlab-group-create command line option,
    485
gitlab-group-update command line option,
    489
gitlab-project-create command line
    option, 563
gitlab-project-update command line
    option, 574
gitlab-topic-create command line option,
    761
gitlab-topic-update command line option,
    762
gitlab-user-create command line option,
    765
gitlab-user-update command line option,
    768
--before
gitlab-event-list command line option,
    478
gitlab-project-event-list command line
    option, 615
gitlab-user-event-list command line
    option, 772
```

```
--bio
    gitlab-user-create command line option, 764
    gitlab-user-update command line option, 768
--blocked
    gitlab-user-list command line option, 766
--board-id
    gitlab-group-board-list-create command
        line option, 499
    gitlab-group-board-list-delete command
        line option, 499
    gitlab-group-board-list-get command
        line option, 500
    gitlab-group-board-list-list command
        line option, 500
    gitlab-group-board-list-update command
        line option, 500
    gitlab-project-board-list-create
        command line option, 589
    gitlab-project-board-list-delete
        command line option, 589
    gitlab-project-board-list-get command
        line option, 589
    gitlab-project-board-list-list command
        line option, 590
    gitlab-project-board-list-update
        command line option, 590
--body
    gitlab-group-epic-discussion-note-create
        command line option, 511
    gitlab-group-epic-discussion-note-update
        command line option, 512
    gitlab-group-epic-note-create command
        line option, 515
    gitlab-group-epic-note-update command
        line option, 516
    gitlab-project-commit-discussion-create
        command line option, 601
    gitlab-project-commit-discussion-note-create
        command line option, 602
    gitlab-project-commit-discussion-note-update
        command line option, 603
    gitlab-project-issue-discussion-create
        command line option, 638
    gitlab-project-issue-discussion-note-create-build-coverage-regex
        command line option, 639
    gitlab-project-issue-discussion-note-update
        command line option, 641
    gitlab-project-issue-note-create
        command line option, 642
    gitlab-project-issue-note-update
        command line option, 644
    gitlab-project-merge-request-discussion-create
        command line option, 679
    gitlab-project-merge-request-discussion-note-create
        command line option, 681
    gitlab-project-merge-request-discussion-note-update
        command line option, 682
    gitlab-project-merge-request-note-create
        command line option, 683
    gitlab-project-merge-request-note-update
        command line option, 685
    gitlab-project-snippet-discussion-create
        command line option, 734
    gitlab-project-snippet-discussion-note-create
        command line option, 736
    gitlab-project-snippet-discussion-note-update
        command line option, 737
    gitlab-project-snippet-note-create
        command line option, 737
    gitlab-project-snippet-note-update
        command line option, 739
--branch
    gitlab-project-branch-create command
        line option, 591
    gitlab-project-commit-cherry-pick
        command line option, 596
    gitlab-project-commit-create command
        line option, 596
    gitlab-project-commit-revert command
        line option, 599
    gitlab-project-file-create command line
        option, 617
    gitlab-project-file-delete command line
        option, 618
    gitlab-project-file-update command line
        option, 619
    gitlab-project-update-submodule command
        line option, 576
--branch-name-regex
    gitlab-group-push-rules-create command
        line option, 542
    gitlab-group-push-rules-update command
        line option, 543
    gitlab-project-push-rules-create
        command line option, 716
    gitlab-project-push-rules-update
        command line option, 717
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 574
--build-git-strategy
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
```

```
    option, 574
--build-timeout
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 574
--builds-access-level
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 574
--builds-enabled
    gitlab-user-project-create command line
        option, 779
--can-create-group
    gitlab-user-create command line option,
        764
    gitlab-user-update command line option,
        768
--can-push
    gitlab-project-key-create command line
        option, 654
    gitlab-project-key-update command line
        option, 655
--certificate
    gitlab-project-pages-domain-create
        command line option, 699
    gitlab-project-pages-domain-update
        command line option, 700
--ci-config-path
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 574
--ci-default-git-depth
    gitlab-project-update command line
        option, 574
--ci-forward-deployment-enabled
    gitlab-project-update command line
        option, 574
--close-issue
    gitlab-group-notification-settings-update
        command line option, 539
    gitlab-notification-settings-update
        command line option, 558
    gitlab-project-notification-settings-update
        command line option, 696
--close-merge-request
    gitlab-group-notification-settings-update
        command line option, 539
    gitlab-notification-settings-update
        command line option, 558
    gitlab-project-notification-settings-update
        command line option, 696
--cn
    gitlab-group-add-ldap-group-link
        command line option, 484
    gitlab-group-delete-ldap-group-link
        command line option, 486
--code-owner-approval-required
    gitlab-project-protected-branch-create
        command line option, 711
--color
    gitlab-broadcast-message-create command
        line option, 468
    gitlab-broadcast-message-update command
        line option, 469
    gitlab-group-label-create command line
        option, 528
    gitlab-group-label-update command line
        option, 530
    gitlab-project-label-create command
        line option, 656
    gitlab-project-label-update command
        line option, 658
--color-scheme-id
    gitlab-user-create command line option,
        765
    gitlab-user-update command line option,
        768
--comment
    gitlab-project-deployment-approval
        command line option, 608
--commit-committer-check
    gitlab-group-push-rules-create command
        line option, 542
    gitlab-group-push-rules-update command
        line option, 543
    gitlab-project-push-rules-create
        command line option, 716
    gitlab-project-push-rules-update
        command line option, 717
--commit-id
    gitlab-project-commit-comment-create
        command line option, 599
    gitlab-project-commit-comment-list
        command line option, 600
    gitlab-project-commit-discussion-create
        command line option, 601
    gitlab-project-commit-discussion-get
        command line option, 601
    gitlab-project-commit-discussion-list
        command line option, 601
    gitlab-project-commit-discussion-note-create
        command line option, 602
    gitlab-project-commit-discussion-note-delete
        command line option, 602
    gitlab-project-commit-discussion-note-get
```

```

    command line option, 603
gitlab-project-commit-discussion-note-update
    command line option, 603
gitlab-project-commit-status-create
    command line option, 604
gitlab-project-commit-status-list
    command line option, 605
--commit-message
gitlab-project-commit-create command
    line option, 596
gitlab-project-file-create command line
    option, 617
gitlab-project-file-delete command line
    option, 618
gitlab-project-file-update command line
    option, 619
--commit-message-negative-regex
gitlab-group-push-rules-create command
    line option, 542
gitlab-group-push-rules-update command
    line option, 543
gitlab-project-push-rules-create
    command line option, 716
gitlab-project-push-rules-update
    command line option, 717
--commit-message-regex
gitlab-group-push-rules-create command
    line option, 542
gitlab-group-push-rules-update command
    line option, 543
gitlab-project-push-rules-create
    command line option, 716
gitlab-project-push-rules-update
    command line option, 717
--commit-sha
gitlab-project-update-submodule command
    line option, 576
--confidential
gitlab-application-create command line
    option, 461
gitlab-project-issue-create command
    line option, 629
gitlab-project-issue-update command
    line option, 635
--confidential-issues-events
gitlab-group-hook-create command line
    option, 520
gitlab-group-hook-update command line
    option, 522
gitlab-project-hook-create command line
    option, 621
gitlab-project-hook-update command line
    option, 623
--confidential-note-events
gitlab-group-hook-create command line
    option, 520
gitlab-group-hook-update command line
    option, 522
--config-file
gitlab command line option, 460
--container-expiration-policy-attributes
gitlab-project-create command line
    option, 563
gitlab-project-update command line
    option, 574
--container-registry-enabled
gitlab-project-create command line
    option, 563
gitlab-project-update command line
    option, 574
--container-registry-token-expire-delay
gitlab-application-settings-update
    command line option, 466
--content
gitlab-ci-lint-create command line
    option, 470
gitlab-ci-lint-validate command line
    option, 470
gitlab-group-wiki-create command line
    option, 547
gitlab-group-wiki-update command line
    option, 549
gitlab-project-ci-lint-create command
    line option, 592
gitlab-project-ci-lint-validate command
    line option, 593
gitlab-project-file-create command line
    option, 617
gitlab-project-file-update command line
    option, 619
gitlab-project-snippet-create command
    line option, 730
gitlab-project-snippet-update command
    line option, 731
gitlab-project-wiki-create command line
    option, 748
gitlab-project-wiki-update command line
    option, 750
gitlab-snippet-create command line
    option, 756
gitlab-snippet-update command line
    option, 758
--context
gitlab-project-commit-status-create
    command line option, 604
--coverage
gitlab-project-commit-status-create
    command line option, 604

```

```
--create-access-level
    gitlab-project-protected-tag-create
        command line option, 714
--created-after
    gitlab-audit-event-list command line
        option, 467
    gitlab-group-audit-event-list command
        line option, 493
    gitlab-group-issue-list command line
        option, 526
    gitlab-group-merge-request-list command
        line option, 534
    gitlab-issue-list command line option,
        551
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-audit-event-list command
        line option, 584
    gitlab-project-deployment-merge-request-list
        command line option, 611
    gitlab-project-issue-list command line
        option, 631
    gitlab-project-merge-request-list
        command line option, 666
--created-at
    gitlab-application-settings-update
        command line option, 465
    gitlab-group-epic-discussion-note-create
        command line option, 511
    gitlab-group-epic-note-create command
        line option, 515
    gitlab-project-commit-discussion-create
        command line option, 601
    gitlab-project-commit-discussion-note-create
        command line option, 602
    gitlab-project-issue-create command
        line option, 629
    gitlab-project-issue-discussion-create
        command line option, 638
    gitlab-project-issue-discussion-note-create
        command line option, 639
    gitlab-project-issue-note-create
        command line option, 642
    gitlab-project-merge-request-discussion-create
        command line option, 679
    gitlab-project-merge-request-discussion-note-create
        command line option, 681
    gitlab-project-snippet-discussion-create
        command line option, 734
    gitlab-project-snippet-discussion-note-create
        command line option, 736
--created-before
    gitlab-audit-event-list command line
        option, 467
gitlab-group-audit-event-list command
    line option, 493
gitlab-group-issue-list command line
    option, 526
gitlab-group-merge-request-list command
    line option, 534
gitlab-issue-list command line option,
    551
gitlab-merge-request-list command line
    option, 555
gitlab-project-audit-event-list command
    line option, 584
gitlab-project-deployment-merge-request-list
    command line option, 611
gitlab-project-issue-list command line
    option, 631
gitlab-project-merge-request-list
    command line option, 666
gitlab-project-pipeline-schedule-create
    command line option, 705
gitlab-project-pipeline-schedule-update
    command line option, 707
--cron-timezone
    gitlab-project-pipeline-schedule-create
        command line option, 705
    gitlab-project-pipeline-schedule-update
        command line option, 707
--custom-attributes
    gitlab-user-list command line option, 766
--debug
    gitlab command line option, 460
--default-branch
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 574
    gitlab-user-project-create command line
        option, 779
gitlab-application-settings-update
    command line option, 465
gitlab-group-create command line option,
    485
gitlab-group-update command line option,
    489
--default-group-visibility
    gitlab-application-settings-update
        command line option, 465
default-project-visibility
    gitlab-application-settings-update
        command line option, 465
--default-projects-limit
    gitlab-application-settings-update
```

```

    command line option, 465
--default-snippet-visibility
    gitlab-application-settings-update
        command line option, 465
--deny-delete-tag
    gitlab-group-push-rules-create command
        line option, 542
    gitlab-group-push-rules-update command
        line option, 543
    gitlab-project-push-rules-create
        command line option, 716
    gitlab-project-push-rules-update
        command line option, 717
--deploy-access-levels
    gitlab-project-protected-environment-create
        command line option, 712
--deployed-after
    gitlab-merge-request-list command line
        option, 556
    gitlab-project-deployment-merge-request-list
        command line option, 612
--deployed-before
    gitlab-merge-request-list command line
        option, 556
    gitlab-project-deployment-merge-request-list
        command line option, 612
--deployment-events
    gitlab-group-hook-create command line
        option, 520
    gitlab-group-hook-update command line
        option, 522
--deployment-id
    gitlab-project-deployment-merge-request-list
        command line option, 611
--description
    gitlab-application-appearance-update
        command line option, 462
    gitlab-group-create command line option,
        485
    gitlab-group-epic-create command line
        option, 507
    gitlab-group-epic-update command line
        option, 509
    gitlab-group-label-create command line
        option, 528
    gitlab-group-label-update command line
        option, 530
    gitlab-group-milestone-create command
        line option, 535
    gitlab-group-milestone-update command
        line option, 537
    gitlab-group-update command line option,
        489
    gitlab-project-commit-status-create
        command line option, 604
gitlab-project-create command line
    option, 563
gitlab-project-export-create command
    line option, 616
gitlab-project-issue-create command
    line option, 629
gitlab-project-issue-update command
    line option, 635
gitlab-project-label-create command
    line option, 656
gitlab-project-label-update command
    line option, 658
gitlab-project-merge-request-create
    command line option, 664
gitlab-project-merge-request-update
    command line option, 671
gitlab-project-milestone-create command
    line option, 692
gitlab-project-milestone-update command
    line option, 694
gitlab-project-pipeline-schedule-create
    command line option, 705
gitlab-project-pipeline-schedule-update
    command line option, 707
gitlab-project-release-create command
    line option, 721
gitlab-project-release-update command
    line option, 722
gitlab-project-snippet-create command
    line option, 730
gitlab-project-snippet-update command
    line option, 731
gitlab-project-trigger-create command
    line option, 743
gitlab-project-trigger-update command
    line option, 745
gitlab-project-update command line
    option, 574
gitlab-runner-create command line
    option, 751
gitlab-runner-update command line
    option, 752
gitlab-topic-create command line option,
    761
gitlab-topic-update command line option,
    762
gitlab-user-project-create command line
    option, 779
--disable-overriding-approvers-per-merge-request
    gitlab-project-approval-update command
        line option, 581
--disabled-oauth-sign-in-sources
    gitlab-application-settings-update

```

command line option, 465
--discussion-id
gitlab-group-epic-discussion-note-create command line option, 511
gitlab-group-epic-discussion-note-delete command line option, 511
gitlab-group-epic-discussion-note-get command line option, 512
gitlab-group-epic-discussion-note-update command line option, 512
gitlab-project-commit-discussion-note-create command line option, 602
gitlab-project-commit-discussion-note-delete command line option, 603
gitlab-project-commit-discussion-note-get command line option, 603
gitlab-project-commit-discussion-note-updatedomain-blacklist
command line option, 603
gitlab-project-issue-discussion-note-create command line option, 639
gitlab-project-issue-discussion-note-delete command line option, 640
gitlab-project-issue-discussion-note-get command line option, 640
gitlab-project-issue-discussion-note-update command line option, 641
gitlab-project-merge-request-discussion-note-create command line option, 681
gitlab-project-merge-request-discussion-note-delete
command line option, 682
gitlab-project-merge-request-discussion-note-get command line option, 682
gitlab-project-merge-request-discussion-note-updatedomain-whitelist
command line option, 682
gitlab-project-snippet-discussion-note-create command line option, 736
gitlab-project-snippet-discussion-note-delete
command line option, 736
gitlab-project-snippet-discussion-note-get command line option, 736
gitlab-project-snippet-discussion-note-update command line option, 737
--discussion-locked
gitlab-project-issue-update command line option, 635
gitlab-project-merge-request-update command line option, 671
--discussion-to-resolve
gitlab-project-issue-create command line option, 629
--domain
gitlab-group-cluster-create command line option, 501
gitlab-group-cluster-update command line option, 501
line option, 503
gitlab-project-cluster-create command line option, 594
gitlab-project-cluster-update command line option, 595
gitlab-project-pages-domain-create command line option, 699
gitlab-project-pages-domain-delete command line option, 699
gitlab-project-pages-domain-get command line option, 700
gitlab-project-pages-domain-update command line option, 700
--domain-allowlist
gitlab-application-settings-update command line option, 466
gitlab-application-settings-update command line option, 466
--domain-blacklist
gitlab-application-settings-update command line option, 465
--domain-blacklist-enabled
gitlab-application-settings-update command line option, 465
--domain-denylist
gitlab-application-settings-update command line option, 466
--domain-denylist-enabled
gitlab-application-settings-update command line option, 466
gitlab-project-ci-lint-create command line option, 592
gitlab-project-ci-lint-validate command line option, 593
gitlab-project-milestone-create command line option, 535
gitlab-project-milestone-update command line option, 537
gitlab-project-issue-create command line option, 629
gitlab-project-issue-update command line option, 635
gitlab-project-milestone-create command line option, 692
gitlab-project-milestone-update command line option, 694
--duration
gitlab-project-issue-add-spent-time

```

        command line option, 628
gitlab-project-issue-time-estimate
    command line option, 634
gitlab-project-merge-request-add-spent-time
    command line option, 662
gitlab-project-merge-request-time-estimate
    command line option, 669
--ecdsa-key-restriction
    gitlab-application-settings-update
        command line option, 466
--ed25519-key-restriction
    gitlab-application-settings-update
        command line option, 466
--email
    gitlab-current-user-email-create
        command line option, 471
    gitlab-group-invitation-delete command
        line option, 524
    gitlab-group-invitation-get command
        line option, 524
    gitlab-group-invitation-update command
        line option, 525
    gitlab-project-invitation-delete
        command line option, 626
    gitlab-project-invitation-get command
        line option, 627
    gitlab-project-invitation-update
        command line option, 627
    gitlab-user-create command line option,
        764
    gitlab-user-email-create command line
        option, 771
    gitlab-user-update command line option,
        768
--email-header-and-footer-enabled
    gitlab-application-appearance-update
        command line option, 463
--emails-disabled
    gitlab-group-create command line option,
        485
    gitlab-group-update command line option,
        489
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 574
--emoji
    gitlab-current-user-status-update
        command line option, 475
--enable-ssl-verification
    gitlab-group-hook-create command line
        option, 521
    gitlab-group-hook-update command line
        option, 523
gitlab-project-hook-create command line
    option, 621
gitlab-project-hook-update command line
    option, 623
--enabled
gitlab-geo-node-update command line
    option, 481
gitlab-group-cluster-create command
    line option, 501
gitlab-project-cluster-create command
    line option, 594
gitlab-project-remote-mirror-create
    command line option, 725
gitlab-project-remote-mirror-update
    command line option, 726
--encoding
    gitlab-project-file-create command line
        option, 617
    gitlab-project-file-update command line
        option, 619
--end-date
    gitlab-group-epic-create command line
        option, 507
    gitlab-group-epic-update command line
        option, 509
--ends-at
    gitlab-broadcast-message-create command
        line option, 468
    gitlab-broadcast-message-update command
        line option, 469
--enforce-terms
    gitlab-application-settings-update
        command line option, 466
--entity-id
    gitlab-audit-event-list command line
        option, 467
--entity-type
    gitlab-audit-event-list command line
        option, 467
--environment
    gitlab-merge-request-list command line
        option, 556
    gitlab-project-deployment-create
        command line option, 608
    gitlab-project-deployment-list command
        line option, 609
    gitlab-project-deployment-merge-request-list
        command line option, 612
--environment-scope
    gitlab-group-cluster-create command
        line option, 501
    gitlab-group-cluster-update command
        line option, 503
    gitlab-project-cluster-create command

```

```
    line option, 594
gitlab-project-cluster-update command
    line option, 595
gitlab-project-variable-create command
    line option, 746
gitlab-project-variable-update command
    line option, 748
--epic-id
    gitlab-group-epic-resource-label-event-get
        command line option, 518
    gitlab-group-epic-resource-label-event-list
        command line option, 518
--epic-iid
    gitlab-group-epic-award-emoji-create
        command line option, 509
    gitlab-group-epic-award-emoji-delete
        command line option, 510
    gitlab-group-epic-award-emoji-get
        command line option, 510
    gitlab-group-epic-award-emoji-list
        command line option, 510
    gitlab-group-epic-discussion-note-create
        command line option, 511
    gitlab-group-epic-discussion-note-delete
        command line option, 511
    gitlab-group-epic-discussion-note-get
        command line option, 512
    gitlab-group-epic-discussion-note-update
        command line option, 512
    gitlab-group-epic-issue-create command
        line option, 513
    gitlab-group-epic-issue-delete command
        line option, 513
    gitlab-group-epic-issue-list command
        line option, 513
    gitlab-group-epic-issue-update command
        line option, 514
    gitlab-group-epic-note-award-emoji-create
        command line option, 516
    gitlab-group-epic-note-award-emoji-delete
        command line option, 517
    gitlab-group-epic-note-award-emoji-get
        command line option, 517
    gitlab-group-epic-note-award-emoji-list
        command line option, 517
    gitlab-group-epic-note-create command
        line option, 515
    gitlab-group-epic-note-delete command
        line option, 515
    gitlab-group-epic-note-get command line
        option, 515
    gitlab-group-epic-note-list command
        line option, 515
    gitlab-group-epic-note-update command
        line option, 516
--epic-issue-id
    gitlab-group-epic-issue-delete command
        line option, 513
    gitlab-group-epic-issue-update command
        line option, 514
--exclude-subgroups
    gitlab-group-package-list command line
        option, 539
--expires-at
    gitlab-group-access-token-create
        command line option, 491
gitlab-group-deploy-token-create
    command line option, 504
gitlab-group-invitation-create command
    line option, 524
gitlab-group-invitation-update command
    line option, 525
gitlab-group-member-create command line
    option, 531
gitlab-group-member-update command line
    option, 532
gitlab-group-share command line option,
    487
gitlab-project-access-token-create
    command line option, 578
gitlab-project-deploy-token-create
    command line option, 606
gitlab-project-invitation-create
    command line option, 626
gitlab-project-invitation-update
    command line option, 628
gitlab-project-member-create command
    line option, 658
gitlab-project-member-update command
    line option, 660
gitlab-project-share command line
    option, 570
gitlab-user-impersonation-token-create
    command line option, 774
gitlab-user-personal-access-token-create
    command line option, 778
--extern-uid
    gitlab-user-create command line option,
    764
    gitlab-user-list command line option, 766
    gitlab-user-update command line option,
    768
--external
    gitlab-user-create command line option,
    764
    gitlab-user-list command line option, 766
    gitlab-user-update command line option,
    768
```

```
--external-authorization-classification-label
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 574
--external-authorization-service-default-label
    gitlab-application-settings-update
        command line option, 466
--external-authorization-service-enabled
    gitlab-application-settings-update
        command line option, 466
--external-authorization-service-timeout
    gitlab-application-settings-update
        command line option, 466
--external-authorization-service-url
    gitlab-application-settings-update
        command line option, 466
--external-url
    gitlab-project-environment-create
        command line option, 613
    gitlab-project-environment-update
        command line option, 614
--extra-shared-runners-minutes-limit
    gitlab-group-create command line option,
        485
    gitlab-group-update command line option,
        489
--fancy
    gitlab command line option, 459
--favicon
    gitlab-application-appearance-update
        command line option, 462
--fields
    gitlab command line option, 460
--file-name
    gitlab-generic-package-download command
        line option, 479
    gitlab-generic-package-upload command
        line option, 479
    gitlab-project-snippet-create command
        line option, 730
    gitlab-project-snippet-update command
        line option, 731
    gitlab-snippet-create command line
        option, 756
    gitlab-snippet-update command line
        option, 758
--file-name-regex
    gitlab-group-push-rules-create command
        line option, 542
    gitlab-group-push-rules-update command
        line option, 543
    gitlab-project-push-rules-create
        command line option, 716
gitlab-project-push-rules-update
    command line option, 717
--file-path
    gitlab-project-file-blame command line
        option, 617
    gitlab-project-file-create command line
        option, 617
    gitlab-project-file-delete command line
        option, 618
    gitlab-project-file-get command line
        option, 618
    gitlab-project-file-raw command line
        option, 618
    gitlab-project-file-update command line
        option, 619
--file-template-project-id
    gitlab-application-settings-update
        command line option, 466
    gitlab-group-update command line option,
        489
--filename
    gitlab-project-upload command line
        option, 576
--filepath
    gitlab-project-release-link-create
        command line option, 723
    gitlab-project-release-link-update
        command line option, 725
    gitlab-project-upload command line
        option, 576
--files-max-capacity
    gitlab-geo-node-update command line
        option, 482
--first-day-of-week
    gitlab-application-settings-update
        command line option, 466
--first-parent
    gitlab-project-commit-list command line
        option, 598
--font
    gitlab-broadcast-message-create command
        line option, 468
    gitlab-broadcast-message-update command
        line option, 469
--footer-message
    gitlab-application-appearance-update
        command line option, 463
--forked-from-id
    gitlab-project-create-fork-relation
        command line option, 565
--forking-access-level
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
```

```
    option, 574
--format
    gitlab-group-wiki-create command line
        option, 547
    gitlab-group-wiki-update command line
        option, 549
    gitlab-project-repository-archive
        command line option, 568
    gitlab-project-wiki-create command line
        option, 748
    gitlab-project-wiki-update command line
        option, 750
--from-
    gitlab-project-repository-compare
        command line option, 568
--fullname
    gitlab-license-get command line option,
        553
--geo-node-allowed-ips
    gitlab-application-settings-update
        command line option, 467
--get-all
    gitlab-application-list command line
        option, 461
    gitlab-audit-event-list command line
        option, 468
    gitlab-broadcast-message-list command
        line option, 469
    gitlab-current-user-email-list command
        line option, 472
    gitlab-current-user-gpg-key-list
        command line option, 473
    gitlab-current-user-key-list command
        line option, 474
    gitlab-deploy-key-list command line
        option, 476
    gitlab-deploy-token-list command line
        option, 476
    gitlab-dockerfile-list command line
        option, 477
    gitlab-event-list command line option,
        478
    gitlab-feature-list command line option,
        478
    gitlab-geo-node-list command line
        option, 481
    gitlab-gitignore-list command line
        option, 482
    gitlab-gitlabciyml-list command line
        option, 483
    gitlab-group-access-request-list
        command line option, 491
    gitlab-group-access-token-list command
        line option, 492
gitlab-group-audit-event-list command
    line option, 493
gitlab-group-badge-list command line
    option, 495
gitlab-group-billable-member-list
    command line option, 496
gitlab-group-billable-member-membership-list
    command line option, 497
gitlab-group-board-list command line
    option, 498
gitlab-group-board-list-list command
    line option, 500
gitlab-group-cluster-list command line
    option, 502
gitlab-group-custom-attribute-list
    command line option, 504
gitlab-group-deploy-token-list command
    line option, 505
gitlab-group-descendant-group-list
    command line option, 506
gitlab-group-epic-award-emoji-list
    command line option, 510
gitlab-group-epic-issue-list command
    line option, 514
gitlab-group-epic-list command line
    option, 508
gitlab-group-epic-note-award-emoji-list
    command line option, 518
gitlab-group-epic-note-list command
    line option, 516
gitlab-group-epic-resource-label-event-list
    command line option, 519
gitlab-group-hook-list command line
    option, 521
gitlab-group-invitation-list command
    line option, 525
gitlab-group-issue-list command line
    option, 526
gitlab-group-iteration-list command
    line option, 527
gitlab-group-label-list command line
    option, 529
gitlab-group-list command line option,
    487
gitlab-group-member-all-list command
    line option, 533
gitlab-group-member-list command line
    option, 532
gitlab-group-merge-request-list command
    line option, 535
gitlab-group-milestone-list command
    line option, 537
gitlab-group-package-list command line
    option, 540
```

gitlab-group-project-list command line
 option, 541

gitlab-group-runner-list command line
 option, 544

gitlab-group-subgroup-list command line
 option, 545

gitlab-group-variable-list command line
 option, 546

gitlab-group-wiki-list command line
 option, 548

gitlab-hook-list command line option, 550

gitlab-issue-list command line option,
 551

gitlab-ldap-group-list command line
 option, 553

gitlab-license-list command line option,
 554

gitlab-merge-request-list command line
 option, 556

gitlab-namespace-list command line
 option, 557

gitlab-pages-domain-list command line
 option, 558

gitlab-personal-access-token-list
 command line option, 559

gitlab-project-access-request-list
 command line option, 578

gitlab-project-access-token-list
 command line option, 579

gitlab-project-approval-rule-list
 command line option, 582

gitlab-project-audit-event-list command
 line option, 584

gitlab-project-badge-list command line
 option, 586

gitlab-project-board-list command line
 option, 588

gitlab-project-board-list-list command
 line option, 590

gitlab-project-branch-list command line
 option, 592

gitlab-project-cluster-list command
 line option, 595

gitlab-project-commit-comment-list
 command line option, 600

gitlab-project-commit-discussion-list
 command line option, 601

gitlab-project-commit-list command line
 option, 598

gitlab-project-commit-status-list
 command line option, 605

gitlab-project-custom-attribute-list
 command line option, 606

gitlab-project-deploy-token-list
 command line option, 607

gitlab-project-deployment-list command
 line option, 609

gitlab-project-deployment-merge-request-list
 command line option, 612

gitlab-project-environment-list command
 line option, 614

gitlab-project-event-list command line
 option, 615

gitlab-project-fork-list command line
 option, 620

gitlab-project-hook-list command line
 option, 622

gitlab-project-integration-list command
 line option, 625

gitlab-project-invitation-list command
 line option, 627

gitlab-project-issue-award-emoji-list
 command line option, 637

gitlab-project-issue-discussion-list
 command line option, 639

gitlab-project-issue-link-list command
 line option, 642

gitlab-project-issue-list command line
 option, 631

gitlab-project-issue-note-award-emoji-list
 command line option, 646

gitlab-project-issue-note-list command
 line option, 643

gitlab-project-issue-resource-label-event-list
 command line option, 647

gitlab-project-issue-resource-milestone-event-list
 command line option, 648

gitlab-project-issue-resource-state-event-list
 command line option, 649

gitlab-project-job-list command line
 option, 652

gitlab-project-key-list command line
 option, 655

gitlab-project-label-list command line
 option, 657

gitlab-project-list command line option,
 567

gitlab-project-member-all-list command
 line option, 661

gitlab-project-member-list command line
 option, 659

gitlab-project-merge-request-approval-rule-list
 command line option, 674

gitlab-project-merge-request-award-emoji-list
 command line option, 678

gitlab-project-merge-request-diff-list
 command line option, 678

gitlab-project-merge-request-discussion-list

```
    command line option, 680
gitlab-project-merge-request-list           option, 727
    command line option, 667
gitlab-project-merge-request-note-award-emoji-ditab-project-snippet-award-emoji-list
    command line option, 686                   command line option, 733
gitlab-project-merge-request-note-list      gitlab-project-snippet-discussion-list
    command line option, 684                   command line option, 735
gitlab-project-merge-request-pipeline-list   gitlab-project-snippet-list command
    command line option, 687                   line option, 731
gitlab-project-merge-request-resource-label-eventlist-project-snippet-note-award-emoji-list
    command line option, 688                   command line option, 741
gitlab-project-merge-request-resource-milestone-project-snippet-note-list
    command line option, 689                   command line option, 738
gitlab-project-merge-request-resource-state-eventlist-project-tag-list command line
    command line option, 690                   option, 743
gitlab-project-merge-train-list command     gitlab-project-trigger-list command
    line option, 691                         line option, 744
gitlab-project-milestone-list command        gitlab-project-user-list command line
    line option, 693                         option, 745
gitlab-project-note-list command line       gitlab-project-variable-list command
    option, 695                           line option, 747
gitlab-project-package-file-list            gitlab-project-wiki-list command line
    command line option, 698                   option, 749
gitlab-project-package-list command         gitlab-runner-all-list command line
    line option, 697                         option, 753
gitlab-project-pages-domain-list          gitlab-runner-job-list command line
    command line option, 700                   option, 754
gitlab-project-pipeline-bridge-list        gitlab-runner-list command line option,
    command line option, 703                   752
gitlab-project-pipeline-job-list          gitlab-shared-project-list command line
    command line option, 704                   option, 755
gitlab-project-pipeline-list command       gitlab-snippet-list command line option,
    line option, 702                         757
gitlab-project-pipeline-schedule-list     gitlab-starred-project-list command
    command line option, 706                   line option, 759
gitlab-project-pipeline-variable-list     gitlab-todo-list command line option, 760
    command line option, 710
gitlab-project-protected-branch-list      gitlab-topic-list command line option,
    command line option, 712                   762
gitlab-project-protected-environment-list  gitlab-user-activities-list command
    command line option, 713                   line option, 769
gitlab-project-protected-tag-list         gitlab-user-custom-attribute-list
    command line option, 715                   command line option, 770
gitlab-project-registry-repository-list   gitlab-user-email-list command line
    command line option, 718                   option, 772
gitlab-project-registry-tag-list         gitlab-user-event-list command line
    command line option, 720                   option, 772
gitlab-project-release-link-list         gitlab-user-gpg-key-list command line
    command line option, 724                   option, 774
gitlab-project-release-list command       gitlab-user-impersonation-token-list
    line option, 722                         command line option, 775
gitlab-project-remote-mirror-list        gitlab-user-key-list command line
    command line option, 726                   option, 777
gitlab-project-runner-list command line   gitlab-user-list command line option, 766
                                         gitlab-user-membership-list command
```

```

    line option, 778
gitlab-user-project-list command line
    option, 781
gitlab-variable-list command line
    option, 783
--gitlab
    gitlab command line option, 460
--gravatar-enabled
    gitlab-application-settings-update
        command line option, 465
--group-access
    gitlab-group-add-ldap-group-link
        command line option, 484
    gitlab-group-share command line option,
        487
    gitlab-project-share command line
        option, 570
--group-id
    gitlab-group-access-request-approve
        command line option, 490
    gitlab-group-access-request-create
        command line option, 490
    gitlab-group-access-request-delete
        command line option, 490
    gitlab-group-access-request-list
        command line option, 491
    gitlab-group-access-token-create
        command line option, 491
    gitlab-group-access-token-delete
        command line option, 492
    gitlab-group-access-token-list command
        line option, 492
    gitlab-group-audit-event-get command
        line option, 493
    gitlab-group-audit-event-list command
        line option, 493
    gitlab-group-badge-create command line
        option, 494
    gitlab-group-badge-delete command line
        option, 494
    gitlab-group-badge-get command line
        option, 494
    gitlab-group-badge-list command line
        option, 495
    gitlab-group-badge-render command line
        option, 495
    gitlab-group-badge-update command line
        option, 495
    gitlab-group-billable-member-delete
        command line option, 496
    gitlab-group-billable-member-list
        command line option, 496
    gitlab-group-billable-member-membership-list
        command line option, 497
gitlab-group-board-create command line
    option, 497
gitlab-group-board-delete command line
    option, 498
gitlab-group-board-get command line
    option, 498
gitlab-group-board-list command line
    option, 498
gitlab-group-board-list-create command
    line option, 499
gitlab-group-board-list-delete command
    line option, 499
gitlab-group-board-list-get command
    line option, 500
gitlab-group-board-list-list command
    line option, 500
gitlab-group-board-list-update command
    line option, 500
gitlab-group-board-update command line
    option, 499
gitlab-group-cluster-create command
    line option, 501
gitlab-group-cluster-delete command
    line option, 501
gitlab-group-cluster-get command line
    option, 502
gitlab-group-cluster-list command line
    option, 502
gitlab-group-cluster-update command
    line option, 502
gitlab-group-custom-attribute-delete
    command line option, 503
gitlab-group-custom-attribute-get
    command line option, 503
gitlab-group-custom-attribute-list
    command line option, 504
gitlab-group-deploy-token-create
    command line option, 504
gitlab-group-deploy-token-delete
    command line option, 505
gitlab-group-deploy-token-get command
    line option, 505
gitlab-group-deploy-token-list command
    line option, 505
gitlab-group-descendant-group-list
    command line option, 506
gitlab-group-epic-award-emoji-create
    command line option, 509
gitlab-group-epic-award-emoji-delete
    command line option, 510
gitlab-group-epic-award-emoji-get
    command line option, 510
gitlab-group-epic-award-emoji-list
    command line option, 510

```

gitlab-group-epic-create command line
 option, 507
gitlab-group-epic-delete command line
 option, 507
gitlab-group-epic-discussion-note-create
 command line option, 511
gitlab-group-epic-discussion-note-delete
 command line option, 511
gitlab-group-epic-discussion-note-get
 command line option, 512
gitlab-group-epic-discussion-note-update
 command line option, 512
gitlab-group-epic-get command line
 option, 508
gitlab-group-epic-issue-create command
 line option, 513
gitlab-group-epic-issue-delete command
 line option, 513
gitlab-group-epic-issue-list command
 line option, 513
gitlab-group-epic-issue-update command
 line option, 514
gitlab-group-epic-list command line
 option, 508
gitlab-group-epic-note-award-emoji-create
 command line option, 516
gitlab-group-epic-note-award-emoji-delete
 command line option, 517
gitlab-group-epic-note-award-emoji-get
 command line option, 517
gitlab-group-epic-note-award-emoji-list
 command line option, 517
gitlab-group-epic-note-create command
 line option, 514
gitlab-group-epic-note-delete command
 line option, 515
gitlab-group-epic-note-get command line
 option, 515
gitlab-group-epic-note-list command
 line option, 515
gitlab-group-epic-note-update command
 line option, 516
gitlab-group-epic-resource-label-event-get
 command line option, 518
gitlab-group-epic-resource-label-event-list
 command line option, 518
gitlab-group-epic-update command line
 option, 509
gitlab-group-export-create command line
 option, 519
gitlab-group-export-download command
 line option, 519
gitlab-group-export-get command line
 option, 519

gitlab-group-hook-create command line
 option, 520
gitlab-group-hook-delete command line
 option, 521
gitlab-group-hook-get command line
 option, 521
gitlab-group-hook-list command line
 option, 521
gitlab-group-hook-update command line
 option, 522
gitlab-group-import-get command line
 option, 523
gitlab-group-invitation-create command
 line option, 523
gitlab-group-invitation-delete command
 line option, 524
gitlab-group-invitation-get command
 line option, 524
gitlab-group-invitation-list command
 line option, 524
gitlab-group-invitation-update command
 line option, 525
gitlab-group-issue-list command line
 option, 526
gitlab-group-issues-statistics-get
 command line option, 527
gitlab-group-iteration-list command
 line option, 527
gitlab-group-label-create command line
 option, 528
gitlab-group-label-delete command line
 option, 528
gitlab-group-label-get command line
 option, 529
gitlab-group-label-list command line
 option, 529
gitlab-group-label-subscribe command
 line option, 529
gitlab-group-label-unsubscribe command
 line option, 530
gitlab-group-label-update command line
 option, 530
gitlab-group-member-all-get command
 line option, 533
gitlab-group-member-all-list command
 line option, 533
gitlab-group-member-create command line
 option, 531
gitlab-group-member-delete command line
 option, 531
gitlab-group-member-get command line
 option, 531
gitlab-group-member-list command line
 option, 532

```
gitlab-group-member-update command line
    option, 532
gitlab-group-merge-request-list command
    line option, 534
gitlab-group-milestone-create command
    line option, 535
gitlab-group-milestone-delete command
    line option, 536
gitlab-group-milestone-get command line
    option, 536
gitlab-group-milestone-issues command
    line option, 536
gitlab-group-milestone-list command
    line option, 537
gitlab-group-milestone-merge-requests
    command line option, 537
gitlab-group-milestone-update command
    line option, 537
gitlab-group-notification-settings-get
    command line option, 538
gitlab-group-notification-settings-update
    command line option, 538
gitlab-group-package-list command line
    option, 539
gitlab-group-project-list command line
    option, 540
gitlab-group-push-rules-create command
    line option, 542
gitlab-group-push-rules-delete command
    line option, 542
gitlab-group-push-rules-get command
    line option, 542
gitlab-group-push-rules-update command
    line option, 543
gitlab-group-runner-list command line
    option, 544
gitlab-group-share command line option,
    487
gitlab-group-subgroup-list command line
    option, 544
gitlab-group-transfer command line
    option, 488
gitlab-group-unshare command line
    option, 488
gitlab-group-variable-create command
    line option, 545
gitlab-group-variable-delete command
    line option, 546
gitlab-group-variable-get command line
    option, 546
gitlab-group-variable-list command line
    option, 546
gitlab-group-variable-update command
    line option, 547
gitlab-group-wiki-create command line
    option, 547
gitlab-group-wiki-delete command line
    option, 548
gitlab-group-wiki-get command line
    option, 548
gitlab-group-wiki-list command line
    option, 548
gitlab-group-wiki-update command line
    option, 549
gitlab-project-share command line
    option, 570
gitlab-project-unshare command line
    option, 572
gitlab-shared-project-list command line
    option, 755
--group-ids
    gitlab-project-approval-rule-create
        command line option, 581
    gitlab-project-merge-request-approval-rule-create
        command line option, 673
    gitlab-project-merge-request-approval-rule-update
        command line option, 675
--group-with-project-templates-id
    gitlab-project-create command line
        option, 563
--header-logo
    gitlab-application-appearance-update
        command line option, 462
--header-message
    gitlab-application-appearance-update
        command line option, 463
--help
    gitlab command line option, 459
    gitlab-application command line option,
        461
    gitlab-application-appearance command
        line option, 462
    gitlab-application-appearance-get
        command line option, 462
    gitlab-application-appearance-update
        command line option, 462
    gitlab-application-create command line
        option, 461
    gitlab-application-delete command line
        option, 461
    gitlab-application-list command line
        option, 461
    gitlab-application-settings command
        line option, 463
    gitlab-application-settings-get command
        line option, 463
    gitlab-application-settings-update
        command line option, 465
```

gitlab-audit-event command line option, 467
gitlab-audit-event-get command line option, 467
gitlab-audit-event-list command line option, 467
gitlab-broadcast-message command line option, 468
gitlab-broadcast-message-create command line option, 468
gitlab-broadcast-message-delete command line option, 468
gitlab-broadcast-message-get command line option, 469
gitlab-broadcast-message-list command line option, 469
gitlab-broadcast-message-update command line option, 469
gitlab-ci-lint command line option, 470
gitlab-ci-lint-create command line option, 470
gitlab-ci-lint-validate command line option, 470
gitlab-current-user command line option, 471
gitlab-current-user-email command line option, 471
gitlab-current-user-email-create command line option, 471
gitlab-current-user-email-delete command line option, 471
gitlab-current-user-email-get command line option, 472
gitlab-current-user-email-list command line option, 472
gitlab-current-user-get command line option, 471
gitlab-current-user-gpg-key command line option, 472
gitlab-current-user-gpg-key-create command line option, 472
gitlab-current-user-gpg-key-delete command line option, 473
gitlab-current-user-gpg-key-get command line option, 473
gitlab-current-user-gpg-key-list command line option, 473
gitlab-current-user-key command line option, 473
gitlab-current-user-key-create command line option, 474
gitlab-current-user-key-delete command line option, 474
gitlab-current-user-key-get command line option, 474
gitlab-current-user-key-list command line option, 474
gitlab-current-user-key-status command line option, 475
gitlab-current-user-key-update command line option, 475
gitlab-current-user-key-delete command line option, 475
gitlab-current-user-key-get command line option, 475
gitlab-current-user-key-list command line option, 475
gitlab-current-user-key-status command line option, 475
gitlab-current-user-key-update command line option, 475
gitlab-current-user-status command line option, 475
gitlab-current-user-status-get command line option, 475
gitlab-current-user-status-update command line option, 475
gitlab-deploy-key command line option, 475
gitlab-deploy-key-list command line option, 475
gitlab-deploy-token command line option, 476
gitlab-deploy-token-list command line option, 476
gitlab-dockerfile command line option, 476
gitlab-dockerfile-get command line option, 477
gitlab-dockerfile-list command line option, 477
gitlab-event command line option, 477
gitlab-event-list command line option, 477
gitlab-feature command line option, 478
gitlab-feature-delete command line option, 478
gitlab-feature-list command line option, 478
gitlab-generic-package command line option, 479
gitlab-generic-package-download command line option, 479
gitlab-generic-package-upload command line option, 479
gitlab-geo-node command line option, 480
gitlab-geo-node-current-failures command line option, 480
gitlab-geo-node-delete command line option, 480
gitlab-geo-node-get command line option, 480
gitlab-geo-node-list command line option, 481
gitlab-geo-node-repair command line option, 481
gitlab-geo-node-status command line option, 481
gitlab-geo-node-update command line option, 481
gitlab-gitignore command line option, 482
gitlab-gitignore-get command line option, 482

```
    option, 482
gitlab-gitignore-list command line
    option, 482
gitlab-gitlabciyml command line option,
    483
gitlab-gitlabciyml-get command line
    option, 483
gitlab-gitlabciyml-list command line
    option, 483
gitlab-group command line option, 484
gitlab-group-access-request command
    line option, 490
gitlab-group-access-request-approve
    command line option, 490
gitlab-group-access-request-create
    command line option, 490
gitlab-group-access-request-delete
    command line option, 490
gitlab-group-access-request-list
    command line option, 491
gitlab-group-access-token command line
    option, 491
gitlab-group-access-token-create
    command line option, 491
gitlab-group-access-token-delete
    command line option, 492
gitlab-group-access-token-list command
    line option, 492
gitlab-group-add-ldap-group-link
    command line option, 484
gitlab-group-audit-event command line
    option, 492
gitlab-group-audit-event-get command
    line option, 493
gitlab-group-audit-event-list command
    line option, 493
gitlab-group-badge command line option,
    493
gitlab-group-badge-create command line
    option, 494
gitlab-group-badge-delete command line
    option, 494
gitlab-group-badge-get command line
    option, 494
gitlab-group-badge-list command line
    option, 494
gitlab-group-badge-render command line
    option, 495
gitlab-group-badge-update command line
    option, 495
gitlab-group-billable-member command
    line option, 496
gitlab-group-billable-member-delete
    command line option, 496
gitlab-group-billable-member-list
    command line option, 496
gitlab-group-billable-member-membership
    command line option, 497
gitlab-group-billable-member-membership-list
    command line option, 497
gitlab-group-board command line option,
    497
gitlab-group-board-create command line
    option, 497
gitlab-group-board-delete command line
    option, 498
gitlab-group-board-get command line
    option, 498
gitlab-group-board-list command line
    option, 498, 499
gitlab-group-board-list-create command
    line option, 499
gitlab-group-board-list-delete command
    line option, 499
gitlab-group-board-list-get command
    line option, 500
gitlab-group-board-list-list command
    line option, 500
gitlab-group-board-list-update command
    line option, 500
gitlab-group-board-update command line
    option, 499
gitlab-group-cluster command line
    option, 501
gitlab-group-cluster-create command
    line option, 501
gitlab-group-cluster-delete command
    line option, 501
gitlab-group-cluster-get command line
    option, 502
gitlab-group-cluster-list command line
    option, 502
gitlab-group-cluster-update command
    line option, 502
gitlab-group-create command line option,
    484
gitlab-group-custom-attribute command
    line option, 503
gitlab-group-custom-attribute-delete
    command line option, 503
gitlab-group-custom-attribute-get
    command line option, 503
gitlab-group-custom-attribute-list
    command line option, 504
gitlab-group-delete command line option,
    485
gitlab-group-delete-ldap-group-link
    command line option, 486
```

gitlab-group-deploy-token command line
option, 504
gitlab-group-deploy-token-create
command line option, 504
gitlab-group-deploy-token-delete
command line option, 505
gitlab-group-deploy-token-get command
line option, 505
gitlab-group-deploy-token-list command
line option, 505
gitlab-group-descendant-group command
line option, 506
gitlab-group-descendant-group-list
command line option, 506
gitlab-group-epic command line option,
507
gitlab-group-epic-award-emoji command
line option, 509
gitlab-group-epic-award-emoji-create
command line option, 509
gitlab-group-epic-award-emoji-delete
command line option, 510
gitlab-group-epic-award-emoji-get
command line option, 510
gitlab-group-epic-award-emoji-list
command line option, 510
gitlab-group-epic-create command line
option, 507
gitlab-group-epic-delete command line
option, 507
gitlab-group-epic-discussion-note
command line option, 511
gitlab-group-epic-discussion-note-create
command line option, 511
gitlab-group-epic-discussion-note-delete
command line option, 511
gitlab-group-epic-discussion-note-get
command line option, 512
gitlab-group-epic-discussion-note-update
command line option, 512
gitlab-group-epic-get command line
option, 508
gitlab-group-epic-issue command line
option, 513
gitlab-group-epic-issue-create command
line option, 513
gitlab-group-epic-issue-delete command
line option, 513
gitlab-group-epic-issue-list command
line option, 513
gitlab-group-epic-issue-update command
line option, 514
gitlab-group-epic-list command line
option, 508

gitlab-group-epic-note command line
option, 514
gitlab-group-epic-note-award-emoji
command line option, 516
gitlab-group-epic-note-award-emoji-create
command line option, 516
gitlab-group-epic-note-award-emoji-delete
command line option, 517
gitlab-group-epic-note-award-emoji-get
command line option, 517
gitlab-group-epic-note-award-emoji-list
command line option, 517
gitlab-group-epic-note-create command
line option, 514
gitlab-group-epic-note-delete command
line option, 515
gitlab-group-epic-note-get command line
option, 515
gitlab-group-epic-note-list command
line option, 515
gitlab-group-epic-note-update command
line option, 516
gitlab-group-epic-resource-label-event
command line option, 518
gitlab-group-epic-resource-label-event-get
command line option, 518
gitlab-group-epic-resource-label-event-list
command line option, 518
gitlab-group-epic-update command line
option, 509
gitlab-group-export command line option,
519
gitlab-group-export-create command line
option, 519
gitlab-group-export-download command
line option, 519
gitlab-group-export-get command line
option, 519
gitlab-group-get command line option, 486
gitlab-group-hook command line option,
520
gitlab-group-hook-create command line
option, 520
gitlab-group-hook-delete command line
option, 521
gitlab-group-hook-get command line
option, 521
gitlab-group-hook-list command line
option, 521
gitlab-group-hook-update command line
option, 522
gitlab-group-import command line option,
523
gitlab-group-import-get command line

```
    option, 523
gitlab-group-invitation command line
    option, 523
gitlab-group-invitation-create command
    line option, 523
gitlab-group-invitation-delete command
    line option, 524
gitlab-group-invitation-get command
    line option, 524
gitlab-group-invitation-list command
    line option, 524
gitlab-group-invitation-update command
    line option, 525
gitlab-group-issue command line option,
    525
gitlab-group-issue-list command line
    option, 525
gitlab-group-issues-statistics command
    line option, 526
gitlab-group-issues-statistics-get
    command line option, 527
gitlab-group-iteration command line
    option, 527
gitlab-group-iteration-list command
    line option, 527
gitlab-group-label command line option,
    528
gitlab-group-label-create command line
    option, 528
gitlab-group-label-delete command line
    option, 528
gitlab-group-label-get command line
    option, 529
gitlab-group-label-list command line
    option, 529
gitlab-group-label-subscribe command
    line option, 529
gitlab-group-label-unsubscribe command
    line option, 530
gitlab-group-label-update command line
    option, 530
gitlab-group-ldap-sync command line
    option, 486
gitlab-group-list command line option,
    486
gitlab-group-member command line option,
    530
gitlab-group-member-all command line
    option, 532
gitlab-group-member-all-get command
    line option, 533
gitlab-group-member-all-list command
    line option, 533
gitlab-group-member-create command line
    option, 531
gitlab-group-member-delete command line
    option, 531
gitlab-group-member-get command line
    option, 531
gitlab-group-member-list command line
    option, 532
gitlab-group-member-update command line
    option, 532
gitlab-group-merge-request command line
    option, 533
gitlab-group-merge-request-list command
    line option, 534
gitlab-group-milestone command line
    option, 535
gitlab-group-milestone-create command
    line option, 535
gitlab-group-milestone-delete command
    line option, 536
gitlab-group-milestone-get command line
    option, 536
gitlab-group-milestone-issues command
    line option, 536
gitlab-group-milestone-list command
    line option, 536
gitlab-group-milestone-merge-requests
    command line option, 537
gitlab-group-milestone-update command
    line option, 537
gitlab-group-notification-settings
    command line option, 538
gitlab-group-notification-settings-get
    command line option, 538
gitlab-group-notification-settings-update
    command line option, 538
gitlab-group-package command line
    option, 539
gitlab-group-package-list command line
    option, 539
gitlab-group-project command line
    option, 540
gitlab-group-project-list command line
    option, 540
gitlab-group-push-rules command line
    option, 541
gitlab-group-push-rules-create command
    line option, 541
gitlab-group-push-rules-delete command
    line option, 542
gitlab-group-push-rules-get command
    line option, 542
gitlab-group-push-rules-update command
    line option, 543
gitlab-group-runner command line option,
```

543
gitlab-group-runner-list command line
option, 544
gitlab-group-search command line option,
487
gitlab-group-share command line option,
487
gitlab-group-subgroup command line
option, 544
gitlab-group-subgroup-list command line
option, 544
gitlab-group-transfer command line
option, 488
gitlab-group-transfer-project command
line option, 488
gitlab-group-unshare command line
option, 488
gitlab-group-update command line option,
489
gitlab-group-variable command line
option, 545
gitlab-group-variable-create command
line option, 545
gitlab-group-variable-delete command
line option, 546
gitlab-group-variable-get command line
option, 546
gitlab-group-variable-list command line
option, 546
gitlab-group-variable-update command
line option, 547
gitlab-group-wiki command line option,
547
gitlab-group-wiki-create command line
option, 547
gitlab-group-wiki-delete command line
option, 548
gitlab-group-wiki-get command line
option, 548
gitlab-group-wiki-list command line
option, 548
gitlab-group-wiki-update command line
option, 549
gitlab-hook command line option, 549
gitlab-hook-create command line option,
549
gitlab-hook-delete command line option,
549
gitlab-hook-get command line option, 550
gitlab-hook-list command line option, 550
gitlab-issue command line option, 550
gitlab-issue-get command line option, 550
gitlab-issue-list command line option,
551
gitlab-issues-statistics command line
option, 552
gitlab-issues-statistics-get command
line option, 552
gitlab-key command line option, 552
gitlab-key-get command line option, 552
gitlab-ldap-group command line option,
552
gitlab-ldap-group-list command line
option, 553
gitlab-license command line option, 553
gitlab-license-get command line option,
553
gitlab-license-list command line option,
554
gitlab-merge-request command line
option, 554
gitlab-merge-request-list command line
option, 555
gitlab-namespace command line option, 556
gitlab-namespace-exists command line
option, 556
gitlab-namespace-get command line
option, 556
gitlab-namespace-list command line
option, 557
gitlab-notification-settings command
line option, 557
gitlab-notification-settings-get
command line option, 557
gitlab-notification-settings-update
command line option, 558
gitlab-pages-domain command line option,
558
gitlab-pages-domain-list command line
option, 558
gitlab-personal-access-token command
line option, 559
gitlab-personal-access-token-delete
command line option, 559
gitlab-personal-access-token-list
command line option, 559
gitlab-project command line option, 560
gitlab-project-access-request command
line option, 577
gitlab-project-access-request-approve
command line option, 577
gitlab-project-access-request-create
command line option, 577
gitlab-project-access-request-delete
command line option, 577
gitlab-project-access-request-list
command line option, 578
gitlab-project-access-token command

```
    line option, 578
gitlab-project-access-token-create
    command line option, 578
gitlab-project-access-token-delete
    command line option, 579
gitlab-project-access-token-list
    command line option, 579
gitlab-project-additional-statistics
    command line option, 579
gitlab-project-additional-statistics-get
    command line option, 580
gitlab-project-approval command line
    option, 580
gitlab-project-approval-get command
    line option, 580
gitlab-project-approval-rule command
    line option, 581
gitlab-project-approval-rule-create
    command line option, 581
gitlab-project-approval-rule-delete
    command line option, 581
gitlab-project-approval-rule-list
    command line option, 582
gitlab-project-approval-rule-update
    command line option, 582
gitlab-project-approval-update command
    line option, 580
gitlab-project-archive command line
    option, 560
gitlab-project-artifact command line
    option, 561, 582
gitlab-project-artifact-delete command
    line option, 583
gitlab-project-artifact-download
    command line option, 583
gitlab-project-artifact-raw command
    line option, 583
gitlab-project-artifacts command line
    option, 561
gitlab-project-audit-event command line
    option, 584
gitlab-project-audit-event-get command
    line option, 584
gitlab-project-audit-event-list command
    line option, 584
gitlab-project-badge command line
    option, 585
gitlab-project-badge-create command
    line option, 585
gitlab-project-badge-delete command
    line option, 585
gitlab-project-badge-get command line
    option, 585
gitlab-project-badge-list command line
    option, 586
gitlab-project-badge-render command
    line option, 586
gitlab-project-badge-update command
    line option, 586
gitlab-project-board command line
    option, 587
gitlab-project-board-create command
    line option, 587
gitlab-project-board-delete command
    line option, 587
gitlab-project-board-get command line
    option, 587
gitlab-project-board-list command line
    option, 588
gitlab-project-board-list-create
    command line option, 589
gitlab-project-board-list-delete
    command line option, 589
gitlab-project-board-list-get command
    line option, 589
gitlab-project-board-list-list command
    line option, 590
gitlab-project-board-list-update
    command line option, 590
gitlab-project-board-update command
    line option, 588
gitlab-project-branch command line
    option, 590
gitlab-project-branch-create command
    line option, 591
gitlab-project-branch-delete command
    line option, 591
gitlab-project-branch-get command line
    option, 591
gitlab-project-branch-list command line
    option, 592
gitlab-project-ci-lint command line
    option, 592
gitlab-project-ci-lint-create command
    line option, 592
gitlab-project-ci-lint-get command line
    option, 593
gitlab-project-ci-lint-validate command
    line option, 593
gitlab-project-cluster command line
    option, 593
gitlab-project-cluster-create command
    line option, 593
gitlab-project-cluster-delete command
    line option, 594
gitlab-project-cluster-get command line
    option, 594
gitlab-project-cluster-list command
```

```
    line option, 595
gitlab-project-cluster-update command
    line option, 595
gitlab-project-commit command line
    option, 596
gitlab-project-commit-cherry-pick
    command line option, 596
gitlab-project-commit-comment command
    line option, 599
gitlab-project-commit-comment-create
    command line option, 599
gitlab-project-commit-comment-list
    command line option, 600
gitlab-project-commit-create command
    line option, 596
gitlab-project-commit-diff command line
    option, 597
gitlab-project-commit-discussion
    command line option, 600
gitlab-project-commit-discussion-create
    command line option, 600
gitlab-project-commit-discussion-get
    command line option, 601
gitlab-project-commit-discussion-list
    command line option, 601
gitlab-project-commit-discussion-note
    command line option, 602
gitlab-project-commit-discussion-note-create
    command line option, 602
gitlab-project-commit-discussion-note-delete
    command line option, 602
gitlab-project-commit-discussion-note-get
    command line option, 603
gitlab-project-commit-discussion-note-update
    command line option, 603
gitlab-project-commit-get command line
    option, 597
gitlab-project-commit-list command line
    option, 597
gitlab-project-commit-merge-requests
    command line option, 598
gitlab-project-commit-refs command line
    option, 598
gitlab-project-commit-revert command
    line option, 599
gitlab-project-commit-signature command
    line option, 599
gitlab-project-commit-status command
    line option, 604
gitlab-project-commit-status-create
    command line option, 604
gitlab-project-commit-status-list
    command line option, 604
gitlab-project-create command line
    option, 562
gitlab-project-create-fork-relation
    command line option, 565
gitlab-project-custom-attribute command
    line option, 605
gitlab-project-custom-attribute-delete
    command line option, 605
gitlab-project-custom-attribute-get
    command line option, 605
gitlab-project-custom-attribute-list
    command line option, 606
gitlab-project-delete command line
    option, 565
gitlab-project-delete-fork-relation
    command line option, 565
gitlab-project-delete-merged-branches
    command line option, 565
gitlab-project-deploy-token command
    line option, 606
gitlab-project-deploy-token-create
    command line option, 606
gitlab-project-deploy-token-delete
    command line option, 607
gitlab-project-deploy-token-get command
    line option, 607
gitlab-project-deploy-token-list
    command line option, 607
gitlab-project-deployment command line
    option, 608
gitlab-project-deployment-approval
    command line option, 608
gitlab-project-deployment-create
    command line option, 608
gitlab-project-deployment-get command
    line option, 609
gitlab-project-deployment-list command
    line option, 609
gitlab-project-deployment-merge-request
    command line option, 610
gitlab-project-deployment-merge-request-list
    command line option, 611
gitlab-project-deployment-update
    command line option, 610
gitlab-project-environment command line
    option, 612
gitlab-project-environment-create
    command line option, 612
gitlab-project-environment-delete
    command line option, 613
gitlab-project-environment-get command
    line option, 613
gitlab-project-environment-list command
    line option, 613
gitlab-project-environment-stop command
```

```
    line option, 614
gitlab-project-environment-update
    command line option, 614
gitlab-project-event command line
    option, 615
gitlab-project-event-list command line
    option, 615
gitlab-project-export command line
    option, 615
gitlab-project-export-create command
    line option, 616
gitlab-project-export-download command
    line option, 616
gitlab-project-export-get command line
    option, 616
gitlab-project-file command line option,
    616
gitlab-project-file-blame command line
    option, 617
gitlab-project-file-create command line
    option, 617
gitlab-project-file-delete command line
    option, 618
gitlab-project-file-get command line
    option, 618
gitlab-project-file-raw command line
    option, 618
gitlab-project-file-update command line
    option, 619
gitlab-project-fork command line option,
    619
gitlab-project-fork-create command line
    option, 619
gitlab-project-fork-list command line
    option, 620
gitlab-project-get command line option,
    566
gitlab-project-hook command line option,
    621
gitlab-project-hook-create command line
    option, 621
gitlab-project-hook-delete command line
    option, 622
gitlab-project-hook-get command line
    option, 622
gitlab-project-hook-list command line
    option, 622
gitlab-project-hook-update command line
    option, 623
gitlab-project-housekeeping command
    line option, 566
gitlab-project-import command line
    option, 624
gitlab-project-import-get command line
    option, 624
gitlab-project-integration command line
    option, 624
gitlab-project-integration-available
    command line option, 624
gitlab-project-integration-delete
    command line option, 624
gitlab-project-integration-get command
    line option, 625
gitlab-project-integration-list command
    line option, 625
gitlab-project-integration-update
    command line option, 625
gitlab-project-invitation command line
    option, 626
gitlab-project-invitation-create
    command line option, 626
gitlab-project-invitation-delete
    command line option, 626
gitlab-project-invitation-get command
    line option, 627
gitlab-project-invitation-list command
    line option, 627
gitlab-project-invitation-update
    command line option, 627
gitlab-project-issue command line
    option, 628
gitlab-project-issue-add-spent-time
    command line option, 628
gitlab-project-issue-award-emoji
    command line option, 636
gitlab-project-issue-award-emoji-create
    command line option, 636
gitlab-project-issue-award-emoji-delete
    command line option, 636
gitlab-project-issue-award-emoji-get
    command line option, 637
gitlab-project-issue-award-emoji-list
    command line option, 637
gitlab-project-issue-closed-by command
    line option, 629
gitlab-project-issue-create command
    line option, 629
gitlab-project-issue-delete command
    line option, 630
gitlab-project-issue-discussion command
    line option, 637
gitlab-project-issue-discussion-create
    command line option, 638
gitlab-project-issue-discussion-get
    command line option, 638
gitlab-project-issue-discussion-list
    command line option, 638
gitlab-project-issue-discussion-note
```

```
    command line option, 639
gitlab-project-issue-discussion-note-create
    command line option, 639
gitlab-project-issue-discussion-note-delete
    command line option, 640
gitlab-project-issue-discussion-note-get
    command line option, 640
gitlab-project-issue-discussion-note-update
    command line option, 640
gitlab-project-issue-get command line
    option, 630
gitlab-project-issue-link command line
    option, 641
gitlab-project-issue-link-create
    command line option, 641
gitlab-project-issue-link-delete
    command line option, 641
gitlab-project-issue-link-list command
    line option, 642
gitlab-project-issue-list command line
    option, 630
gitlab-project-issue-move command line
    option, 631
gitlab-project-issue-note command line
    option, 642
gitlab-project-issue-note-award-emoji
    command line option, 644
gitlab-project-issue-note-award-emoji-create
    command line option, 644
gitlab-project-issue-note-award-emoji-delete
    command line option, 645
gitlab-project-issue-note-award-emoji-get
    command line option, 645
gitlab-project-issue-note-award-emoji-list
    command line option, 645
gitlab-project-issue-note-create
    command line option, 642
gitlab-project-issue-note-delete
    command line option, 643
gitlab-project-issue-note-get command
    line option, 643
gitlab-project-issue-note-list command
    line option, 643
gitlab-project-issue-note-update
    command line option, 644
gitlab-project-issue-participants
    command line option, 632
gitlab-project-issue-related-merge-requests
    command line option, 632
gitlab-project-issue-reorder command
    line option, 632
gitlab-project-issue-reset-spent-time
    command line option, 633
gitlab-project-issue-reset-time-estimate
```

```
    command line option, 633
gitlab-project-issue-resource-label-event
    command line option, 646
gitlab-project-issue-resource-label-event-get
    command line option, 646
gitlab-project-issue-resource-label-event-list
    command line option, 646
gitlab-project-issue-resource-milestone-event
    command line option, 647
gitlab-project-issue-resource-milestone-event-get
    command line option, 647
gitlab-project-issue-resource-milestone-event-list
    command line option, 648
gitlab-project-issue-resource-state-event
    command line option, 648
gitlab-project-issue-resource-state-event-get
    command line option, 648
gitlab-project-issue-resource-state-event-list
    command line option, 649
gitlab-project-issue-subscribe command
    line option, 633
gitlab-project-issue-time-estimate
    command line option, 633
gitlab-project-issue-time-stats command
    line option, 634
gitlab-project-issue-todo command line
    option, 634
gitlab-project-issue-unsubscribe
    command line option, 634
gitlab-project-issue-update command
    line option, 635
gitlab-project-issue-user-agent-detail
    command line option, 635
gitlab-project-issues-statistics
    command line option, 649
gitlab-project-issues-statistics-get
    command line option, 649
gitlab-project-job command line option,
    650
gitlab-project-job-artifact command
    line option, 650
gitlab-project-job-artifacts command
    line option, 650
gitlab-project-job-cancel command line
    option, 651
gitlab-project-job-delete-artifacts
    command line option, 651
gitlab-project-job-erase command line
    option, 651
gitlab-project-job-get command line
    option, 651
gitlab-project-job-keep-artifacts
    command line option, 652
gitlab-project-job-list command line
```

```
    option, 652
gitlab-project-job-play command line
    option, 652
gitlab-project-job-retry command line
    option, 653
gitlab-project-job-trace command line
    option, 653
gitlab-project-key command line option,
    653
gitlab-project-key-create command line
    option, 653
gitlab-project-key-delete command line
    option, 654
gitlab-project-key-enable command line
    option, 654
gitlab-project-key-get command line
    option, 654
gitlab-project-key-list command line
    option, 655
gitlab-project-key-update command line
    option, 655
gitlab-project-label command line
    option, 655
gitlab-project-label-create command
    line option, 656
gitlab-project-label-delete command
    line option, 656
gitlab-project-label-get command line
    option, 656
gitlab-project-label-list command line
    option, 657
gitlab-project-label-subscribe command
    line option, 657
gitlab-project-label-unsubscribe
    command line option, 657
gitlab-project-label-update command
    line option, 658
gitlab-project-languages command line
    option, 566
gitlab-project-list command line option,
    566
gitlab-project-member command line
    option, 658
gitlab-project-member-all command line
    option, 660
gitlab-project-member-all-get command
    line option, 660
gitlab-project-member-all-list command
    line option, 660
gitlab-project-member-create command
    line option, 658
gitlab-project-member-delete command
    line option, 659
gitlab-project-member-get command line
    option, 659
gitlab-project-member-list command line
    option, 659
gitlab-project-member-update command
    line option, 660
gitlab-project-merge-request command
    line option, 661
gitlab-project-merge-request-add-spent-time
    command line option, 662
gitlab-project-merge-request-approval
    command line option, 672
gitlab-project-merge-request-approval-get
    command line option, 672
gitlab-project-merge-request-approval-rule
    command line option, 672
gitlab-project-merge-request-approval-rule-create
    command line option, 673
gitlab-project-merge-request-approval-rule-delete
    command line option, 673
gitlab-project-merge-request-approval-rule-get
    command line option, 674
gitlab-project-merge-request-approval-rule-list
    command line option, 674
gitlab-project-merge-request-approval-rule-update
    command line option, 675
gitlab-project-merge-request-approval-state
    command line option, 675
gitlab-project-merge-request-approval-state-get
    command line option, 676
gitlab-project-merge-request-approval-update
    command line option, 672
gitlab-project-merge-request-approve
    command line option, 662
gitlab-project-merge-request-award-emoji
    command line option, 676
gitlab-project-merge-request-award-emoji-create
    command line option, 676
gitlab-project-merge-request-award-emoji-delete
    command line option, 677
gitlab-project-merge-request-award-emoji-get
    command line option, 677
gitlab-project-merge-request-award-emoji-list
    command line option, 677
gitlab-project-merge-request-cancel-merge-when-pipeline
    command line option, 662
gitlab-project-merge-request-changes
    command line option, 663
gitlab-project-merge-request-closes-issues
    command line option, 663
gitlab-project-merge-request-commits
    command line option, 663
gitlab-project-merge-request-create
    command line option, 664
gitlab-project-merge-request-delete
```

```
    command line option, 665
gitlab-project-merge-request-diff
    command line option, 678
gitlab-project-merge-request-diff-get
    command line option, 678
gitlab-project-merge-request-diff-list
    command line option, 678
gitlab-project-merge-request-discussion
    command line option, 679
gitlab-project-merge-request-discussion-creategitlab-project-merge-request-pipeline-list
    command line option, 679
gitlab-project-merge-request-discussion-get
    command line option, 679
gitlab-project-merge-request-discussion-list
    command line option, 680
gitlab-project-merge-request-discussion-note
    command line option, 681
gitlab-project-merge-request-discussion-note-createlab-project-merge-request-reset-time-estimate
    command line option, 681
gitlab-project-merge-request-discussion-note-deltalab-project-merge-request-resource-label-event
    command line option, 681
gitlab-project-merge-request-discussion-note-gittab-project-merge-request-resource-label-event-get
    command line option, 682
gitlab-project-merge-request-discussion-note-updatelab-project-merge-request-resource-label-event-list
    command line option, 682
gitlab-project-merge-request-discussion-updategitlab-project-merge-request-resource-milestone-event
    command line option, 680
gitlab-project-merge-request-get
    command line option, 665
gitlab-project-merge-request-list
    command line option, 666
gitlab-project-merge-request-merge
    command line option, 667
gitlab-project-merge-request-merge-ref
    command line option, 667
gitlab-project-merge-request-note
    command line option, 683
gitlab-project-merge-request-note-award-emoji gitlab-project-merge-request-subscribe
    command line option, 685
gitlab-project-merge-request-note-award-emoji-createlab-project-merge-request-time-estimate
    command line option, 685
gitlab-project-merge-request-note-award-emoji-deltab-project-merge-request-time-stats
    command line option, 685
gitlab-project-merge-request-note-award-emoji-gittab-project-merge-request-todo
    command line option, 686
gitlab-project-merge-request-note-award-emoji-deltab-project-merge-request-unapprove
    command line option, 686
gitlab-project-merge-request-note-create
    command line option, 683
gitlab-project-merge-request-note-delete
    command line option, 683
gitlab-project-merge-request-note-get
    command line option, 684
gitlab-project-merge-request-note-list
    command line option, 684
gitlab-project-merge-request-note-update
    command line option, 684
gitlab-project-merge-request-participants
    command line option, 668
gitlab-project-merge-request-pipeline
    command line option, 687
gitlab-project-merge-request-pipeline-create
    command line option, 687
gitlab-project-merge-request-rebase
    command line option, 668
gitlab-project-merge-request-reset-approvals
    command line option, 668
gitlab-project-merge-request-reset-spent-time
    command line option, 668
gitlab-project-merge-request-reset-time-estimate
    command line option, 669
gitlab-project-merge-request-resource-label-event
    command line option, 688
gitlab-project-merge-request-resource-label-event-get
    command line option, 688
gitlab-project-merge-request-resource-label-event-list
    command line option, 688
gitlab-project-merge-request-resource-milestone-event
    command line option, 689
gitlab-project-merge-request-resource-milestone-event-
    command line option, 689
gitlab-project-merge-request-resource-state-event
    command line option, 690
gitlab-project-merge-request-resource-state-event-get
    command line option, 690
gitlab-project-merge-request-resource-state-event-list
    command line option, 690
gitlab-project-merge-request-subscribe
    command line option, 669
gitlab-project-merge-request-time-estimate
    command line option, 669
gitlab-project-merge-request-time-stats
    command line option, 670
gitlab-project-merge-request-todo
    command line option, 670
gitlab-project-merge-request-unapprove
    command line option, 670
gitlab-project-merge-request-unsubscribe
    command line option, 670
gitlab-project-merge-request-update
    command line option, 671
gitlab-project-merge-train command line
    option, 691
gitlab-project-merge-train-list command
```

```
    line option, 691
gitlab-project-milestone command line
    option, 691
gitlab-project-milestone-create command
    line option, 692
gitlab-project-milestone-delete command
    line option, 692
gitlab-project-milestone-get command
    line option, 692
gitlab-project-milestone-issues command
    line option, 693
gitlab-project-milestone-list command
    line option, 693
gitlab-project-milestone-merge-requests
    command line option, 693
gitlab-project-milestone-update command
    line option, 694
gitlab-project-mirror-pull command line
    option, 568
gitlab-project-note command line option,
    694
gitlab-project-note-get command line
    option, 694
gitlab-project-note-list command line
    option, 695
gitlab-project-notification-settings
    command line option, 695
gitlab-project-notification-settings-get
    command line option, 695
gitlab-project-notification-settings-update
    command line option, 696
gitlab-project-package command line
    option, 696
gitlab-project-package-delete command
    line option, 697
gitlab-project-package-file command
    line option, 698
gitlab-project-package-file-delete
    command line option, 698
gitlab-project-package-file-list
    command line option, 698
gitlab-project-package-get command line
    option, 697
gitlab-project-package-list command
    line option, 697
gitlab-project-pages-domain command
    line option, 699
gitlab-project-pages-domain-create
    command line option, 699
gitlab-project-pages-domain-delete
    command line option, 699
gitlab-project-pages-domain-get command
    line option, 700
gitlab-project-pages-domain-list
    command line option, 700
gitlab-project-pipeline command line
    option, 701
gitlab-project-pipeline-bridge command
    line option, 703
gitlab-project-pipeline-bridge-list
    command line option, 703
gitlab-project-pipeline-cancel command
    line option, 701
gitlab-project-pipeline-create command
    line option, 701
gitlab-project-pipeline-delete command
    line option, 701
gitlab-project-pipeline-get command
    line option, 702
gitlab-project-pipeline-job command
    line option, 704
gitlab-project-pipeline-job-list
    command line option, 704
gitlab-project-pipeline-list command
    line option, 702
gitlab-project-pipeline-retry command
    line option, 703
gitlab-project-pipeline-schedule
    command line option, 704
gitlab-project-pipeline-schedule-create
    command line option, 705
gitlab-project-pipeline-schedule-delete
    command line option, 705
gitlab-project-pipeline-schedule-get
    command line option, 705
gitlab-project-pipeline-schedule-list
    command line option, 706
gitlab-project-pipeline-schedule-play
    command line option, 706
gitlab-project-pipeline-schedule-take-ownership
    command line option, 706
gitlab-project-pipeline-schedule-update
    command line option, 707
gitlab-project-pipeline-schedule-variable
    command line option, 707
gitlab-project-pipeline-schedule-variable-create
    command line option, 707
gitlab-project-pipeline-schedule-variable-delete
    command line option, 708
gitlab-project-pipeline-schedule-variable-update
    command line option, 708
gitlab-project-pipeline-test-report
    command line option, 709
gitlab-project-pipeline-test-report-get
    command line option, 709
gitlab-project-pipeline-test-report-summary
```

command line option, 709
gitlab-project-pipeline-test-report-summary command line option, 709
gitlab-project-pipeline-variable command line option, 710
gitlab-project-pipeline-variable-list command line option, 710
gitlab-project-protected-branch command line option, 710
gitlab-project-protected-branch-create command line option, 711
gitlab-project-protected-branch-delete command line option, 711
gitlab-project-protected-branch-get command line option, 711
gitlab-project-protected-branch-list command line option, 712
gitlab-project-protected-environment command line option, 712
gitlab-project-protected-environment-create command line option, 712
gitlab-project-protected-environment-delete command line option, 713
gitlab-project-protected-environment-get command line option, 713
gitlab-project-protected-environment-list command line option, 713
gitlab-project-protected-tag command line option, 714
gitlab-project-protected-tag-create command line option, 714
gitlab-project-protected-tag-delete command line option, 714
gitlab-project-protected-tag-get command line option, 715
gitlab-project-protected-tag-list command line option, 715
gitlab-project-push-rules command line option, 715
gitlab-project-push-rules-create command line option, 716
gitlab-project-push-rules-delete command line option, 716
gitlab-project-push-rules-get command line option, 717
gitlab-project-push-rules-update command line option, 717
gitlab-project-registry-repository command line option, 718
gitlab-project-registry-repository-delete command line option, 718
gitlab-project-registry-repository-list command line option, 718
gitlab-project-registry-tag command line option, 719
gitlab-project-registry-tag-delete command line option, 719
gitlab-project-registry-tag-delete-in-bulk command line option, 719
gitlab-project-registry-tag-get command line option, 720
gitlab-project-registry-tag-list command line option, 720
gitlab-project-release command line option, 720
gitlab-project-release-create command line option, 721
gitlab-project-release-delete command line option, 721
gitlab-project-release-get command line option, 721
gitlab-project-release-link command line option, 723
gitlab-project-release-link-create command line option, 723
gitlab-project-release-link-delete command line option, 723
gitlab-project-release-link-get command line option, 724
gitlab-project-release-link-list command line option, 724
gitlab-project-release-link-update command line option, 724
gitlab-project-release-list command line option, 722
gitlab-project-release-update command line option, 722
gitlab-project-remote-mirror command line option, 725
gitlab-project-remote-mirror-create command line option, 725
gitlab-project-remote-mirror-list command line option, 725
gitlab-project-remote-mirror-update command line option, 726
gitlab-project-repository-archive command line option, 568
gitlab-project-repository-blob command line option, 568
gitlab-project-repository-compare command line option, 568
gitlab-project-repository-contributors command line option, 569
gitlab-project-repository-merge-base command line option, 569
gitlab-project-repository-raw-blob command line option, 569
gitlab-project-repository-tree command

```
    line option, 569
gitlab-project-restore command line
    option, 570
gitlab-project-runner command line
    option, 726
gitlab-project-runner-create command
    line option, 726
gitlab-project-runner-delete command
    line option, 727
gitlab-project-runner-list command line
    option, 727
gitlab-project-search command line
    option, 570
gitlab-project-service command line
    option, 727
gitlab-project-service-available
    command line option, 728
gitlab-project-service-delete command
    line option, 728
gitlab-project-service-get command line
    option, 728
gitlab-project-service-list command
    line option, 728
gitlab-project-service-update command
    line option, 729
gitlab-project-share command line
    option, 570
gitlab-project-snapshot command line
    option, 570
gitlab-project-snippet command line
    option, 729
gitlab-project-snippet-award-emoji
    command line option, 732
gitlab-project-snippet-award-emoji-create
    command line option, 732
gitlab-project-snippet-award-emoji-delete
    command line option, 732
gitlab-project-snippet-award-emoji-get
    command line option, 733
gitlab-project-snippet-award-emoji-list
    command line option, 733
gitlab-project-snippet-content command
    line option, 729
gitlab-project-snippet-create command
    line option, 730
gitlab-project-snippet-delete command
    line option, 730
gitlab-project-snippet-discussion
    command line option, 734
gitlab-project-snippet-discussion-create
    command line option, 734
gitlab-project-snippet-discussion-get
    command line option, 734
gitlab-project-snippet-discussion-list
    command line option, 735
gitlab-project-snippet-discussion-note
    command line option, 735
gitlab-project-snippet-discussion-note-create
    command line option, 735
gitlab-project-snippet-discussion-note-delete
    command line option, 736
gitlab-project-snippet-discussion-note-get
    command line option, 736
gitlab-project-snippet-discussion-note-update
    command line option, 737
gitlab-project-snippet-get command line
    option, 730
gitlab-project-snippet-list command
    line option, 731
gitlab-project-snippet-note command
    line option, 737
gitlab-project-snippet-note-award-emoji
    command line option, 739
gitlab-project-snippet-note-award-emoji-create
    command line option, 739
gitlab-project-snippet-note-award-emoji-delete
    command line option, 740
gitlab-project-snippet-note-award-emoji-get
    command line option, 740
gitlab-project-snippet-note-award-emoji-list
    command line option, 741
gitlab-project-snippet-note-create
    command line option, 737
gitlab-project-snippet-note-delete
    command line option, 738
gitlab-project-snippet-note-get command
    line option, 738
gitlab-project-snippet-note-list
    command line option, 738
gitlab-project-snippet-note-update
    command line option, 739
gitlab-project-snippet-update command
    line option, 731
gitlab-project-snippet-user-agent-detail
    command line option, 732
gitlab-project-star command line option,
    571
gitlab-project-storage command line
    option, 741
gitlab-project-storage-get command line
    option, 741
gitlab-project-tag command line option,
    742
gitlab-project-tag-create command line
    option, 742
gitlab-project-tag-delete command line
    option, 742
gitlab-project-tag-get command line
```

```
    option, 742
gitlab-project-tag-list command line
    option, 743
gitlab-project-transfer command line
    option, 571
gitlab-project-transfer-project command
    line option, 571
gitlab-project-trigger command line
    option, 743
gitlab-project-trigger-create command
    line option, 743
gitlab-project-trigger-delete command
    line option, 744
gitlab-project-trigger-get command line
    option, 744
gitlab-project-trigger-list command
    line option, 744
gitlab-project-trigger-pipeline command
    line option, 571
gitlab-project-trigger-update command
    line option, 745
gitlab-project-unarchive command line
    option, 572
gitlab-project-unshare command line
    option, 572
gitlab-project-unstar command line
    option, 572
gitlab-project-update command line
    option, 574
gitlab-project-update-submodule command
    line option, 576
gitlab-project-upload command line
    option, 576
gitlab-project-user command line option,
    745
gitlab-project-user-list command line
    option, 745
gitlab-project-variable command line
    option, 746
gitlab-project-variable-create command
    line option, 746
gitlab-project-variable-delete command
    line option, 746
gitlab-project-variable-get command
    line option, 747
gitlab-project-variable-list command
    line option, 747
gitlab-project-variable-update command
    line option, 747
gitlab-project-wiki command line option,
    748
gitlab-project-wiki-create command line
    option, 748
gitlab-project-wiki-delete command line
    option, 748
gitlab-project-wiki-get command line
    option, 749
gitlab-project-wiki-list command line
    option, 749
gitlab-project-wiki-update command line
    option, 749
gitlab-registry-repository command line
    option, 750
gitlab-registry-repository-get command
    line option, 750
gitlab-runner command line option, 750
gitlab-runner-all command line option,
    750, 753
gitlab-runner-all-list command line
    option, 753
gitlab-runner-create command line
    option, 751
gitlab-runner-delete command line
    option, 751
gitlab-runner-get command line option,
    751
gitlab-runner-job command line option,
    754
gitlab-runner-job-list command line
    option, 754
gitlab-runner-list command line option,
    752
gitlab-runner-update command line
    option, 752
gitlab-runner-verify command line
    option, 753
gitlab-shared-project command line
    option, 754
gitlab-shared-project-list command line
    option, 755
gitlab-snippet command line option, 755
gitlab-snippet-content command line
    option, 756
gitlab-snippet-create command line
    option, 756
gitlab-snippet-delete command line
    option, 756
gitlab-snippet-get command line option,
    757
gitlab-snippet-list command line option,
    757
gitlab-snippet-public command line
    option, 757
gitlab-snippet-update command line
    option, 757
gitlab-snippet-user-agent-detail
    command line option, 758
gitlab-starred-project command line
```

option, 758
gitlab-starred-project-list command line option, 758
gitlab-todo command line option, 759
gitlab-todo-delete command line option, 759
gitlab-todo-list command line option, 760
gitlab-todo-mark-all-as-done command line option, 760
gitlab-todo-mark-as-done command line option, 760
gitlab-topic command line option, 761
gitlab-topic-create command line option, 761
gitlab-topic-delete command line option, 761
gitlab-topic-get command line option, 761
gitlab-topic-list command line option, 762
gitlab-topic-update command line option, 762
gitlab-user command line option, 763
gitlab-user-activate command line option, 763
gitlab-user-activities command line option, 769
gitlab-user-activities-list command line option, 769
gitlab-user-approve command line option, 763
gitlab-user-ban command line option, 763
gitlab-user-block command line option, 763
gitlab-user-create command line option, 764
gitlab-user-custom-attribute command line option, 769
gitlab-user-custom-attribute-delete command line option, 769
gitlab-user-custom-attribute-get command line option, 770
gitlab-user-custom-attribute-list command line option, 770
gitlab-user-deactivate command line option, 765
gitlab-user-delete command line option, 765
gitlab-user-email command line option, 770
gitlab-user-email-create command line option, 771
gitlab-user-email-delete command line option, 771
gitlab-user-email-get command line option, 771
gitlab-user-email-list command line option, 771
gitlab-user-event command line option, 772
gitlab-user-event-list command line option, 772
gitlab-user-follow command line option, 765
gitlab-user-get command line option, 766
gitlab-user-gpg-key command line option, 773
gitlab-user-gpg-key-create command line option, 773
gitlab-user-gpg-key-delete command line option, 773
gitlab-user-gpg-key-get command line option, 773
gitlab-user-gpg-key-list command line option, 774
gitlab-user-impersonation-token command line option, 774
gitlab-user-impersonation-token-create command line option, 774
gitlab-user-impersonation-token-delete command line option, 775
gitlab-user-impersonation-token-get command line option, 775
gitlab-user-impersonation-token-list command line option, 775
gitlab-user-key command line option, 776
gitlab-user-key-create command line option, 776
gitlab-user-key-delete command line option, 776
gitlab-user-key-get command line option, 776
gitlab-user-key-list command line option, 777
gitlab-user-list command line option, 766
gitlab-user-membership command line option, 777
gitlab-user-membership-get command line option, 777
gitlab-user-membership-list command line option, 777
gitlab-user-personal-access-token command line option, 778
gitlab-user-personal-access-token-create command line option, 778
gitlab-user-project command line option, 778
gitlab-user-project-create command line option, 779

```
gitlab-user-project-list command line
    option, 780
gitlab-user-reject command line option,
    767
gitlab-user-status command line option,
    781
gitlab-user-status-get command line
    option, 781
gitlab-user-unban command line option,
    767
gitlab-user-unblock command line option,
    767
gitlab-user-unfollow command line
    option, 767
gitlab-user-update command line option,
    768
gitlab-variable command line option, 781
gitlab-variable-create command line
    option, 782
gitlab-variable-delete command line
    option, 782
gitlab-variable-get command line option,
    782
gitlab-variable-list command line
    option, 783
gitlab-variable-update command line
    option, 783
--home-page-url
    gitlab-application-settings-update
        command line option, 465
--id
    gitlab-application-delete command line
        option, 461
    gitlab-application-settings-update
        command line option, 465
    gitlab-audit-event-get command line
        option, 467
    gitlab-broadcast-message-delete command
        line option, 468
    gitlab-broadcast-message-get command
        line option, 469
    gitlab-broadcast-message-update command
        line option, 469
    gitlab-current-user-email-delete
        command line option, 471
    gitlab-current-user-email-get command
        line option, 472
    gitlab-current-user-gpg-key-delete
        command line option, 473
    gitlab-current-user-gpg-key-get command
        line option, 473
    gitlab-current-user-key-delete command
        line option, 474
    gitlab-current-user-key-get command
        line option, 474
gitlab-geo-node-current-failures
    command line option, 480
gitlab-geo-node-delete command line
    option, 480
gitlab-geo-node-get command line option,
    480
gitlab-geo-node-repair command line
    option, 481
gitlab-geo-node-status command line
    option, 481
gitlab-geo-node-update command line
    option, 481
gitlab-group-access-request-approve
    command line option, 490
gitlab-group-access-request-delete
    command line option, 490
gitlab-group-access-token-delete
    command line option, 492
gitlab-group-add-ldap-group-link
    command line option, 484
gitlab-group-audit-event-get command
    line option, 493
gitlab-group-badge-delete command line
    option, 494
gitlab-group-badge-get command line
    option, 494
gitlab-group-badge-render command line
    option, 495
gitlab-group-badge-update command line
    option, 495
gitlab-group-billable-member-delete
    command line option, 496
gitlab-group-board-delete command line
    option, 498
gitlab-group-board-get command line
    option, 498
gitlab-group-board-list-delete command
    line option, 499
gitlab-group-board-list-get command
    line option, 500
gitlab-group-board-list-update command
    line option, 501
gitlab-group-board-update command line
    option, 499
gitlab-group-cluster-delete command
    line option, 501
gitlab-group-cluster-get command line
    option, 502
gitlab-group-cluster-update command
    line option, 502
gitlab-group-delete command line option,
    485
gitlab-group-delete-ldap-group-link
```

```
    command line option, 486
gitlab-group-deploy-token-delete
    command line option, 505
gitlab-group-deploy-token-get command
    line option, 505
gitlab-group-emoji-award-delete
    command line option, 510
gitlab-group-emoji-award-get
    command line option, 510
gitlab-group-emoji-discussion-note-delete
    command line option, 512
gitlab-group-emoji-discussion-note-get
    command line option, 512
gitlab-group-emoji-discussion-note-update
    command line option, 512
gitlab-group-emoji-note-award-delete
    command line option, 517
gitlab-group-emoji-note-award-get
    command line option, 517
gitlab-group-emoji-note-delete command
    line option, 515
gitlab-group-emoji-note-get command line
    option, 515
gitlab-group-emoji-note-update command
    line option, 516
gitlab-group-epic-resource-label-event-get
    command line option, 518
gitlab-group-get command line option, 486
gitlab-group-hook-delete command line
    option, 521
gitlab-group-hook-get command line
    option, 521
gitlab-group-hook-update command line
    option, 522
gitlab-group-ldap-sync command line
    option, 486
gitlab-group-member-all-get command
    line option, 533
gitlab-group-member-delete command line
    option, 531
gitlab-group-member-get command line
    option, 531
gitlab-group-member-update command line
    option, 532
gitlab-group-milestone-delete command
    line option, 536
gitlab-group-milestone-get command line
    option, 536
gitlab-group-milestone-issues command
    line option, 536
gitlab-group-milestone-merge-requests
    command line option, 537
gitlab-group-milestone-update command
    line option, 537
gitlab-group-search command line option,
    487
gitlab-group-share command line option,
    487
gitlab-group-transfer command line
    option, 488
gitlab-group-transfer-project command
    line option, 488
gitlab-group-unshare command line
    option, 488
gitlab-group-update command line option,
    489
gitlab-hook-delete command line option,
    549
gitlab-hook-get command line option, 550
gitlab-issue-get command line option, 550
gitlab-key-get command line option, 552
gitlab-namespace-exists command line
    option, 556
gitlab-namespace-get command line
    option, 556
gitlab-personal-access-token-delete
    command line option, 559
gitlab-project-access-request-approve
    command line option, 577
gitlab-project-access-request-delete
    command line option, 577
gitlab-project-access-token-delete
    command line option, 579
gitlab-project-approval-rule-delete
    command line option, 581
gitlab-project-approval-rule-update
    command line option, 582
gitlab-project-archive command line
    option, 560
gitlab-project-artifact command line
    option, 561
gitlab-project-artifacts command line
    option, 561
gitlab-project-audit-event-get command
    line option, 584
gitlab-project-badge-delete command
    line option, 585
gitlab-project-badge-get command line
    option, 585
gitlab-project-badge-render command
    line option, 586
gitlab-project-badge-update command
    line option, 586
gitlab-project-board-delete command
    line option, 587
gitlab-project-board-get command line
    option, 588
gitlab-project-board-list-delete
```

```
    command line option, 589
gitlab-project-board-list-get command
    line option, 589
gitlab-project-board-list-update
    command line option, 590
gitlab-project-board-update command
    line option, 588
gitlab-project-cluster-delete command
    line option, 594
gitlab-project-cluster-get command line
    option, 594
gitlab-project-cluster-update command
    line option, 595
gitlab-project-commit-cherry-pick
    command line option, 596
gitlab-project-commit-diff command line
    option, 597
gitlab-project-commit-discussion-get
    command line option, 601
gitlab-project-commit-discussion-note-delete
    command line option, 603
gitlab-project-commit-discussion-note-get
    command line option, 603
gitlab-project-commit-discussion-note-update
    command line option, 603
gitlab-project-commit-get command line
    option, 597
gitlab-project-commit-merge-requests
    command line option, 598
gitlab-project-commit-refs command line
    option, 598
gitlab-project-commit-revert command
    line option, 599
gitlab-project-commit-signature command
    line option, 599
gitlab-project-create-fork-relation
    command line option, 565
gitlab-project-delete command line
    option, 565
gitlab-project-delete-fork-relation
    command line option, 565
gitlab-project-delete-merged-branches
    command line option, 565
gitlab-project-deploy-token-delete
    command line option, 607
gitlab-project-deploy-token-get command
    line option, 607
gitlab-project-deployment-approval
    command line option, 608
gitlab-project-deployment-get command
    line option, 609
gitlab-project-deployment-update
    command line option, 610
gitlab-project-environment-delete
    command line option, 613
gitlab-project-environment-get command
    line option, 613
gitlab-project-environment-stop command
    line option, 614
gitlab-project-environment-update
    command line option, 614
gitlab-project-get command line option,
    566
gitlab-project-hook-delete command line
    option, 622
gitlab-project-hook-get command line
    option, 622
gitlab-project-hook-update command line
    option, 623
gitlab-project-housekeeping command
    line option, 566
gitlab-project-issue-award-emoji-delete
    command line option, 636
gitlab-project-issue-award-emoji-get
    command line option, 637
gitlab-project-issue-discussion-get
    command line option, 638
gitlab-project-issue-discussion-note-delete
    command line option, 640
gitlab-project-issue-discussion-note-get
    command line option, 640
gitlab-project-issue-discussion-note-update
    command line option, 641
gitlab-project-issue-note-award-emoji-delete
    command line option, 645
gitlab-project-issue-note-award-emoji-get
    command line option, 645
gitlab-project-issue-note-delete
    command line option, 643
gitlab-project-issue-note-get command
    line option, 643
gitlab-project-issue-note-update
    command line option, 644
gitlab-project-issue-resource-label-event-get
    command line option, 646
gitlab-project-issue-resource-milestone-event-get
    command line option, 647
gitlab-project-issue-resource-state-event-get
    command line option, 648
gitlab-project-job-artifact command
    line option, 650
gitlab-project-job-artifacts command
    line option, 650
gitlab-project-job-cancel command line
    option, 651
gitlab-project-job-delete-artifacts
    command line option, 651
gitlab-project-job-erase command line
```

```
    option, 651
gitlab-project-job-get command line
    option, 652
gitlab-project-job-keep-artifacts
    command line option, 652
gitlab-project-job-play command line
    option, 653
gitlab-project-job-retry command line
    option, 653
gitlab-project-job-trace command line
    option, 653
gitlab-project-key-delete command line
    option, 654
gitlab-project-key-enable command line
    option, 654
gitlab-project-key-get command line
    option, 654
gitlab-project-key-update command line
    option, 655
gitlab-project-languages command line
    option, 566
gitlab-project-member-all-get command
    line option, 660
gitlab-project-member-delete command
    line option, 659
gitlab-project-member-get command line
    option, 659
gitlab-project-member-update command
    line option, 660
gitlab-project-merge-request-approval-rule-create
    command line option, 673
gitlab-project-merge-request-approval-rule-delete
    command line option, 674
gitlab-project-merge-request-approval-rule-get
    command line option, 674
gitlab-project-merge-request-approval-rule-update
    command line option, 675
gitlab-project-merge-request-approval-state-get
    command line option, 676
gitlab-project-merge-request-award-emoji-delete
    command line option, 677
gitlab-project-merge-request-award-emoji-get
    command line option, 677
gitlab-project-merge-request-diff-get
    command line option, 678
gitlab-project-merge-request-discussion-get
    command line option, 680
gitlab-project-merge-request-discussion-note-delete
    command line option, 682
gitlab-project-merge-request-discussion-note-get
    command line option, 682
gitlab-project-merge-request-discussion-note-update
    command line option, 682
gitlab-project-merge-request-discussion-update
    command line option, 682
    command line option, 680
gitlab-project-merge-request-note-award-emoji-delete
    command line option, 686
gitlab-project-merge-request-note-award-emoji-get
    command line option, 686
gitlab-project-merge-request-note-delete
    command line option, 683
gitlab-project-merge-request-note-get
    command line option, 684
gitlab-project-merge-request-note-update
    command line option, 685
gitlab-project-merge-request-resource-label-event-get
    command line option, 688
gitlab-project-merge-request-resource-milestone-event-
    command line option, 689
gitlab-project-merge-request-resource-state-event-get
    command line option, 690
gitlab-project-milestone-delete command
    line option, 692
gitlab-project-milestone-get command
    line option, 692
gitlab-project-milestone-issues command
    line option, 693
gitlab-project-milestone-merge-requests
    command line option, 694
gitlab-project-milestone-update command
    line option, 694
gitlab-project-mirror-pull command line
    option, 568
gitlab-project-note-get command line
    option, 694
gitlab-project-package-delete command
    line option, 697
gitlab-project-package-file-delete
    command line option, 698
gitlab-project-package-get command line
    option, 697
gitlab-project-pipeline-cancel command
    line option, 701
gitlab-project-pipeline-delete command
    line option, 701
gitlab-project-pipeline-get command
    line option, 702
gitlab-project-pipeline-retry command
    line option, 703
gitlab-project-pipeline-schedule-delete
    command line option, 705
gitlab-project-pipeline-schedule-get
    command line option, 705
gitlab-project-pipeline-schedule-play
    command line option, 706
gitlab-project-pipeline-schedule-take-ownership
    command line option, 706
gitlab-project-pipeline-schedule-update
```

```
    command line option, 707
gitlab-project-registry-repository-delete
    command line option, 718
gitlab-project-release-link-delete
    command line option, 723
gitlab-project-release-link-get command
    line option, 724
gitlab-project-release-link-update
    command line option, 725
gitlab-project-remote-mirror-update
    command line option, 726
gitlab-project-repository-archive
    command line option, 568
gitlab-project-repository-blob command
    line option, 568
gitlab-project-repository-compare
    command line option, 568
gitlab-project-repository-contributors
    command line option, 569
gitlab-project-repository-merge-base
    command line option, 569
gitlab-project-repository-raw-blob
    command line option, 569
gitlab-project-repository-tree command
    line option, 569
gitlab-project-restore command line
    option, 570
gitlab-project-runner-delete command
    line option, 727
gitlab-project-search command line
    option, 570
gitlab-project-share command line
    option, 570
gitlab-project-snapshot command line
    option, 570
gitlab-project-snippet-award-emoji-delete
    command line option, 733
gitlab-project-snippet-award-emoji-get
    command line option, 733
gitlab-project-snippet-content command
    line option, 729
gitlab-project-snippet-delete command
    line option, 730
gitlab-project-snippet-discussion-get
    command line option, 734
gitlab-project-snippet-discussion-note-delete gitlab-runner-delete command line
    command line option, 736
gitlab-project-snippet-discussion-note-get
    command line option, 736
gitlab-project-snippet-discussion-note-update gitlab-runner-update command line
    command line option, 737
gitlab-project-snippet-get command line
    option, 730
gitlab-project-snippet-note-award-emoji-deletegitlab-snippet-content command line
    command line option, 740
gitlab-project-snippet-note-award-emoji-get
    command line option, 740
gitlab-project-snippet-note-delete
    command line option, 738
gitlab-project-snippet-note-get command
    line option, 738
gitlab-project-snippet-note-update
    command line option, 739
gitlab-project-snippet-update command
    line option, 731
gitlab-project-snippet-user-agent-detail
    command line option, 732
gitlab-project-star command line option,
    571
gitlab-project-storage-get command line
    option, 741
gitlab-project-transfer command line
    option, 571
gitlab-project-transfer-project command
    line option, 571
gitlab-project-trigger-delete command
    line option, 744
gitlab-project-trigger-get command line
    option, 744
gitlab-project-trigger-pipeline command
    line option, 571
gitlab-project-trigger-update command
    line option, 745
gitlab-project-unarchive command line
    option, 572
gitlab-project-unshare command line
    option, 572
gitlab-project-unstar command line
    option, 572
gitlab-project-update command line
    option, 574
gitlab-project-update-submodule command
    line option, 576
gitlab-project-upload command line
    option, 576
gitlab-registry-repository-get command
    line option, 750
gitlab-runner-all command line option,
    750
gitlab-runner-delete command line
    option, 751
gitlab-runner-get command line option,
    751
gitlab-runner-update command line
    option, 752
gitlab-runner-verify command line
    option, 753
gitlab-snippet-content command line
```

```

    option, 756
gitlab-snippet-delete command line
    option, 756
gitlab-snippet-get command line option,
    757
gitlab-snippet-public command line
    option, 757
gitlab-snippet-update command line
    option, 757
gitlab-snippet-user-agent-detail
    command line option, 758
gitlab-todo-delete command line option,
    759
gitlab-todo-mark-all-as-done command
    line option, 760
gitlab-todo-mark-as-done command line
    option, 760
gitlab-topic-delete command line option,
    761
gitlab-topic-get command line option, 761
gitlab-topic-update command line option,
    762
gitlab-user-activate command line
    option, 763
gitlab-user-approve command line option,
    763
gitlab-user-ban command line option, 763
gitlab-user-block command line option,
    763
gitlab-user-deactivate command line
    option, 765
gitlab-user-delete command line option,
    765
gitlab-user-email-delete command line
    option, 771
gitlab-user-email-get command line
    option, 771
gitlab-user-follow command line option,
    765
gitlab-user-get command line option, 766
gitlab-user-gpg-key-delete command line
    option, 773
gitlab-user-gpg-key-get command line
    option, 773
gitlab-user-impersonation-token-delete
    command line option, 775
gitlab-user-impersonation-token-get
    command line option, 775
gitlab-user-key-delete command line
    option, 776
gitlab-user-key-get command line option,
    776
gitlab-user-reject command line option,
    767
gitlab-user-unban command line option,
    767
gitlab-user-unblock command line option,
    767
gitlab-user-unfollow command line
    option, 767
gitlab-user-update command line option,
    768
--id-after
gitlab-project-list command line option,
    567
gitlab-user-project-list command line
    option, 781
--id-before
gitlab-project-list command line option,
    567
gitlab-user-project-list command line
    option, 781
--iid
gitlab-group-epic-delete command line
    option, 507
gitlab-group-epic-get command line
    option, 508
gitlab-group-epic-update command line
    option, 509
gitlab-project-issue-add-spent-time
    command line option, 628
gitlab-project-issue-closed-by command
    line option, 629
gitlab-project-issue-delete command
    line option, 630
gitlab-project-issue-get command line
    option, 630
gitlab-project-issue-move command line
    option, 631
gitlab-project-issue-participants
    command line option, 632
gitlab-project-issue-related-merge-requests
    command line option, 632
gitlab-project-issue-reorder command
    line option, 632
gitlab-project-issue-reset-spent-time
    command line option, 633
gitlab-project-issue-reset-time-estimate
    command line option, 633
gitlab-project-issue-subscribe command
    line option, 633
gitlab-project-issue-time-estimate
    command line option, 634
gitlab-project-issue-time-stats command
    line option, 634
gitlab-project-issue-todo command line
    option, 634
gitlab-project-issue-unsubscribe

```

```
    command line option, 634
gitlab-project-issue-update command
    line option, 635
gitlab-project-issue-user-agent-detail
    command line option, 636
gitlab-project-merge-request-add-spent-time
    command line option, 662
gitlab-project-merge-request-approve
    command line option, 662
gitlab-project-merge-request-cancel-merge-when-pending-updates
    command line option, 662
gitlab-project-merge-request-changes
    command line option, 663
gitlab-project-merge-request-closes-issues
    command line option, 663
gitlab-project-merge-request-commits
    command line option, 663
gitlab-project-merge-request-delete
    command line option, 665
gitlab-project-merge-request-get
    command line option, 665
gitlab-project-merge-request-merge
    command line option, 667
gitlab-project-merge-request-merge-ref
    command line option, 667
gitlab-project-merge-request-participants
    command line option, 668
gitlab-project-merge-request-rebase
    command line option, 668
gitlab-project-merge-request-reset-approvals
    command line option, 668
gitlab-project-merge-request-reset-spent-time
    command line option, 669
gitlab-project-merge-request-reset-time-estimate
    command line option, 669
gitlab-project-merge-request-subscribe
    command line option, 669
gitlab-project-merge-request-time-estimate
    command line option, 669
gitlab-project-merge-request-time-stats
    command line option, 670
gitlab-project-merge-request-todo
    command line option, 670
gitlab-project-merge-request-unapprove
    command line option, 670
gitlab-project-merge-request-unsubscribe
    command line option, 671
gitlab-project-merge-request-update
    command line option, 671
--iids
    gitlab-group-issue-list command line
        option, 526
    gitlab-group-milestone-list command
        line option, 537
gitlab-issue-list command line option,
    551
gitlab-project-issue-list command line
    option, 630
gitlab-project-merge-request-list
    command line option, 666
gitlab-project-milestone-list command
    line option, 693
--image-url
    gitlab-project-updates-create command line
        option, 494
gitlab-group-badge-render command line
    option, 495
gitlab-group-badge-update command line
    option, 495
gitlab-project-badge-create command
    line option, 585
gitlab-project-badge-render command
    line option, 586
gitlab-project-badge-update command
    line option, 587
--import-sources
    gitlab-application-settings-update
        command line option, 466
--import-url
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 574
gitlab-user-project-create command line
    option, 779
gitlab-merge-request-list command line
    option, 556
gitlab-project-deployment-merge-request-list
    command line option, 612
--include-ancestors
    gitlab-group-iteration-list command
        line option, 527
--include-diverged-commits-count
    gitlab-project-merge-request-get
        command line option, 665
--include-html-description
    gitlab-project-release-list command
        line option, 722
--include-jobs
    gitlab-ci-lint-create command line
        option, 470
    gitlab-ci-lint-validate command line
        option, 470
gitlab-project-ci-lint-create command
    line option, 592
gitlab-project-ci-lint-validate command
    line option, 593
```

```
--include-merged-yaml
    gitlab-ci-lint-create command line
        option, 470
    gitlab-ci-lint-validate command line
        option, 470
--include-rebase-in-progress
    gitlab-project-merge-request-get
        command line option, 665
--include-retried
    gitlab-project-pipeline-job-list
        command line option, 704
--include-subgroups
    gitlab-group-project-list command line
        option, 541
--info
    gitlab-runner-create command line
        option, 751
--initialize-with-readme
    gitlab-project-create command line
        option, 563
--instance-statistics-visibility-private
    gitlab-application-settings-update
        command line option, 466
--invite-source
    gitlab-group-invitation-create command
        line option, 524
    gitlab-project-invitation-create
        command line option, 626
--issue-id
    gitlab-group-epic-issue-create command
        line option, 513
--issue-iid
    gitlab-project-issue-award-emoji-create
        command line option, 636
    gitlab-project-issue-award-emoji-delete
        command line option, 636
    gitlab-project-issue-award-emoji-get
        command line option, 637
    gitlab-project-issue-award-emoji-list
        command line option, 637
    gitlab-project-issue-discussion-create
        command line option, 638
    gitlab-project-issue-discussion-get
        command line option, 638
    gitlab-project-issue-discussion-list
        command line option, 638
    gitlab-project-issue-discussion-note-create
        command line option, 639
    gitlab-project-issue-discussion-note-delete
        command line option, 640
    gitlab-project-issue-discussion-note-get
        command line option, 640
    gitlab-project-issue-discussion-note-update
        command line option, 641
gitlab-project-issue-link-create
    command line option, 641
gitlab-project-issue-link-delete
    command line option, 641
gitlab-project-issue-link-list command
    line option, 642
gitlab-project-issue-note-award-emoji-create
    command line option, 644
gitlab-project-issue-note-award-emoji-delete
    command line option, 645
gitlab-project-issue-note-award-emoji-get
    command line option, 645
gitlab-project-issue-note-award-emoji-list
    command line option, 646
gitlab-project-issue-note-create
    command line option, 642
gitlab-project-issue-note-delete
    command line option, 643
gitlab-project-issue-note-get command
    line option, 643
gitlab-project-issue-note-list command
    line option, 643
gitlab-project-issue-note-update
    command line option, 644
gitlab-project-issue-resource-label-event-get
    command line option, 646
gitlab-project-issue-resource-label-event-list
    command line option, 647
gitlab-project-issue-resource-milestone-event-get
    command line option, 647
gitlab-project-issue-resource-milestone-event-list
    command line option, 648
gitlab-project-issue-resource-state-event-get
    command line option, 648
gitlab-project-issue-resource-state-event-list
    command line option, 649
--issue-link-id
    gitlab-project-issue-link-delete
        command line option, 641
--issues-access-level
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 574
--issues-enabled
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 574
    gitlab-user-project-create command line
        option, 779
--issues-events
    gitlab-group-hook-create command line
        option, 520
```

```
gitlab-group-hook-update command line
    option, 522
gitlab-project-hook-create command line
    option, 621
gitlab-project-hook-update command line
    option, 623
--issues-template
    gitlab-project-update command line
        option, 576
--job
    gitlab-project-artifact command line
        option, 561
    gitlab-project-artifact-download
        command line option, 583
    gitlab-project-artifact-raw command
        line option, 583
    gitlab-project-artifacts command line
        option, 561
--job-events
    gitlab-group-hook-create command line
        option, 520
    gitlab-group-hook-update command line
        option, 522
    gitlab-project-hook-create command line
        option, 621
    gitlab-project-hook-update command line
        option, 623
--job-token
    gitlab command line option, 460
    gitlab-project-artifact-download
        command line option, 583
    gitlab-project-artifacts command line
        option, 561
--jobs-enabled
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 575
--keep-n
    gitlab-project-registry-tag-delete-in-bulk
        command line option, 719
--key
    gitlab-current-user-gpg-key-create
        command line option, 472
    gitlab-current-user-key-create command
        line option, 474
    gitlab-group-custom-attribute-delete
        command line option, 503
    gitlab-group-custom-attribute-get
        command line option, 503
    gitlab-group-variable-create command
        line option, 545
    gitlab-group-variable-delete command
        line option, 546
gitlab-group-variable-get command line
    option, 546
gitlab-group-variable-update command
    line option, 547
gitlab-license-get command line option,
    553
gitlab-project-custom-attribute-delete
    command line option, 605
gitlab-project-custom-attribute-get
    command line option, 605
gitlab-project-key-create command line
    option, 654
gitlab-project-pages-domain-create
    command line option, 699
gitlab-project-pages-domain-update
    command line option, 701
gitlab-project-pipeline-schedule-variable-create
    command line option, 708
gitlab-project-pipeline-schedule-variable-delete
    command line option, 708
gitlab-project-pipeline-schedule-variable-update
    command line option, 708
gitlab-project-variable-create command
    line option, 746
gitlab-project-variable-delete command
    line option, 746
gitlab-project-variable-get command
    line option, 747
gitlab-project-variable-update command
    line option, 747
gitlab-user-custom-attribute-delete
    command line option, 769
gitlab-user-custom-attribute-get
    command line option, 770
gitlab-user-gpg-key-create command line
    option, 773
gitlab-user-key-create command line
    option, 776
gitlab-variable-create command line
    option, 782
gitlab-variable-delete command line
    option, 782
gitlab-variable-get command line option,
    782
gitlab-variable-update command line
    option, 783
--key-id
    gitlab-project-key-enable command line
        option, 654
--labels
    gitlab-group-epic-create command line
        option, 507
    gitlab-group-epic-list command line
        option, 508
```

```

gitlab-group-epic-update command line
    option, 509
gitlab-group-issue-list command line
    option, 526
gitlab-group-merge-request-list command
    line option, 534
gitlab-issue-list command line option,
    551
gitlab-merge-request-list command line
    option, 555
gitlab-project-deployment-merge-request-list
    command line option, 611
gitlab-project-issue-create command
    line option, 629
gitlab-project-issue-list command line
    option, 631
gitlab-project-issue-update command
    line option, 635
gitlab-project-merge-request-create
    command line option, 664
gitlab-project-merge-request-list
    command line option, 666
gitlab-project-merge-request-update
    command line option, 671
--last-activity-after
    gitlab-project-list command line option,
        567
--last-activity-before
    gitlab-project-list command line option,
        567
--level
    gitlab-group-notification-settings-update
        command line option, 539
    gitlab-notification-settings-update
        command line option, 558
    gitlab-project-notification-settings-update
        command line option, 696
--lfs-enabled
    gitlab-group-create command line option,
        485
    gitlab-group-update command line option,
        489
    gitlab-project-create command line
        option, 563
    gitlab-project-update command line
        option, 575
--lifetime
    gitlab-snippet-create command line
        option, 756
--line
    gitlab-project-commit-comment-create
        command line option, 600
--line-type
    gitlab-project-commit-comment-create
        command line option, 600
--link-type
    gitlab-project-release-link-create
        command line option, 723
    gitlab-project-release-link-update
        command line option, 725
--link-url
    gitlab-group-badge-create command line
        option, 494
    gitlab-group-badge-render command line
        option, 495
    gitlab-group-badge-update command line
        option, 495
    gitlab-project-badge-create command
        line option, 585
    gitlab-project-badge-render command
        line option, 586
    gitlab-project-badge-update command
        line option, 587
--linkedin
    gitlab-user-create command line option,
        764
    gitlab-user-update command line option,
        768
--local-markdown-version
    gitlab-application-settings-update
        command line option, 466
--location
    gitlab-user-create command line option,
        765
    gitlab-user-update command line option,
        768
--locked
    gitlab-runner-create command line
        option, 751
    gitlab-runner-update command line
        option, 752
--logo
    gitlab-application-appearance-update
        command line option, 462
--managed
    gitlab-group-cluster-create command
        line option, 501
    gitlab-project-cluster-create command
        line option, 594
--management-project-id
    gitlab-group-cluster-update command
        line option, 503
    gitlab-project-cluster-update command
        line option, 595
--masked
    gitlab-group-variable-create command
        line option, 546
    gitlab-group-variable-update command
        line option, 546

```

line option, 547
gitlab-project-variable-create command line option, 746
gitlab-project-variable-update command line option, 748
gitlab-variable-create command line option, 782
gitlab-variable-update command line option, 783
--max-attachment-size
 gitlab-application-settings-update command line option, 465
--max-file-size
 gitlab-group-push-rules-create command line option, 542
 gitlab-group-push-rules-update command line option, 543
 gitlab-project-push-rules-create command line option, 716
 gitlab-project-push-rules-update command line option, 717
--maximum-timeout
 gitlab-runner-create command line option, 751
 gitlab-runner-update command line option, 753
--member-check
 gitlab-group-push-rules-create command line option, 542
 gitlab-group-push-rules-update command line option, 543
 gitlab-project-push-rules-create command line option, 716
 gitlab-project-push-rules-update command line option, 718
--membership
 gitlab-project-fork-list command line option, 620
 gitlab-project-list command line option, 567
 gitlab-starred-project-list command line option, 758
 gitlab-user-project-list command line option, 780
--membership-lock
 gitlab-group-create command line option, 485
 gitlab-group-update command line option, 489
--mentions-disabled
 gitlab-group-create command line option, 485
 gitlab-group-update command line option, 489
--merge-access-level
 gitlab-project-protected-branch-create command line option, 711
--merge-commit-message
 gitlab-project-merge-request-merge command line option, 667
--merge-merge-request
 gitlab-group-notification-settings-update command line option, 539
 gitlab-notification-settings-update command line option, 558
 gitlab-project-notification-settings-update command line option, 696
--merge-method
 gitlab-project-create command line option, 564
 gitlab-project-update command line option, 575
--merge-pipelines-enabled
 gitlab-project-create command line option, 564
 gitlab-project-update command line option, 575
--merge-request-iid
 gitlab-project-merge-request-approval-rule-create command line option, 673
 gitlab-project-merge-request-approval-rule-update command line option, 675
--merge-request-to-resolve-discussions-of
 gitlab-project-issue-create command line option, 629
--merge-requests-access-level
 gitlab-project-create command line option, 564
 gitlab-project-update command line option, 575
--merge-requests-author-approval
 gitlab-project-approval-update command line option, 581
--merge-requests-disable-committers-approval
 gitlab-project-approval-update command line option, 581
--merge-requests-enabled
 gitlab-project-create command line option, 564
 gitlab-project-update command line option, 575
 gitlab-user-project-create command line option, 779
--merge-requests-events
 gitlab-group-hook-create command line option, 520
 gitlab-group-hook-update command line option, 522

```

gitlab-project-hook-create command line
    option, 621
gitlab-project-hook-update command line
    option, 623
--merge-requests-template
    gitlab-project-update command line
        option, 576
--merge-when-pipeline-succeeds
    gitlab-project-merge-request-merge
        command line option, 667
--message
    gitlab-broadcast-message-create command
        line option, 468
    gitlab-broadcast-message-update command
        line option, 469
    gitlab-current-user-status-update
        command line option, 475
    gitlab-project-tag-create command line
        option, 742
--message-background-color
    gitlab-application-appearance-update
        command line option, 463
--message-font-color
    gitlab-application-appearance-update
        command line option, 463
--milestone
    gitlab-group-issue-list command line
        option, 526
    gitlab-group-merge-request-list command
        line option, 534
    gitlab-issue-list command line option,
        551
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-deployment-merge-request-list
        command line option, 611
    gitlab-project-issue-list command line
        option, 631
    gitlab-project-merge-request-list
        command line option, 666
--milestone-id
    gitlab-project-issue-create command
        line option, 629
    gitlab-project-issue-update command
        line option, 635
    gitlab-project-merge-request-create
        command line option, 664
    gitlab-project-merge-request-update
        command line option, 671
--milestones
    gitlab-project-release-update command
        line option, 722
--min-access-level
    gitlab-group-descendant-group-list
        command line option, 506
gitlab-group-list command line option,
    487
gitlab-group-project-list command line
    option, 541
gitlab-group-subgroup-list command line
    option, 545
gitlab-project-list command line option,
    567
gitlab-shared-project-list command line
    option, 755
gitlab-starred-project-list command
    line option, 759
gitlab-user-project-list command line
    option, 781
--mirror
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 575
--mirror-overwrites-diverged-branches
    gitlab-project-update command line
        option, 575
--mirror-trigger-builds
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 575
--mirror-user-id
    gitlab-project-update command line
        option, 575
--move-after-id
    gitlab-group-epic-issue-update command
        line option, 514
    gitlab-project-issue-reorder command
        line option, 632
--move-before-id
    gitlab-group-epic-issue-update command
        line option, 514
    gitlab-project-issue-reorder command
        line option, 632
--mr-iid
    gitlab-project-merge-request-approval-get
        command line option, 672
    gitlab-project-merge-request-approval-rule-create
        command line option, 673
    gitlab-project-merge-request-approval-rule-delete
        command line option, 674
    gitlab-project-merge-request-approval-rule-get
        command line option, 674
    gitlab-project-merge-request-approval-rule-list
        command line option, 674
    gitlab-project-merge-request-approval-rule-update
        command line option, 675

```

```
gitlab-project-merge-request-approval-state-get gitlab-project-merge-request-resource-label-event-get
    command line option, 676                               command line option, 688
gitlab-project-merge-request-approval-update gitlab-project-merge-request-resource-label-event-list
    command line option, 672                               command line option, 688
gitlab-project-merge-request-award-emoji-create gitlab-project-merge-request-resource-milestone-event
    command line option, 676                               command line option, 689
gitlab-project-merge-request-award-emoji-delete gitlab-project-merge-request-resource-milestone-event
    command line option, 677                               command line option, 689
gitlab-project-merge-request-award-emoji-get gitlab-project-merge-request-resource-state-event-get
    command line option, 677                               command line option, 690
gitlab-project-merge-request-award-emoji-list gitlab-project-merge-request-resource-state-event-list
    command line option, 677                               command line option, 690
gitlab-project-merge-request-diff-get      --my-reaction-emoji
    command line option, 678                               gitlab-group-issue-list command line
gitlab-project-merge-request-diff-list      option, 526
    command line option, 678                               gitlab-group-merge-request-list command
gitlab-project-merge-request-discussion-create      line option, 534
    command line option, 679                               gitlab-issue-list command line option,
gitlab-project-merge-request-discussion-get      551
    command line option, 680                               gitlab-merge-request-list command line
gitlab-project-merge-request-discussion-list      option, 555
    command line option, 680                               gitlab-project-deployment-merge-request-list
gitlab-project-merge-request-discussion-note-create      command line option, 612
    command line option, 681                               gitlab-project-issue-list command line
gitlab-project-merge-request-discussion-note-delete      option, 631
    command line option, 682                               gitlab-project-merge-request-list
gitlab-project-merge-request-discussion-note-get      command line option, 666
    command line option, 682                               --name
gitlab-project-merge-request-discussion-note-update      gitlab-application-create command line
    command line option, 682                               option, 461
gitlab-project-merge-request-discussion-update gitlab-dockerfile-get command line
    command line option, 680                               option, 477
gitlab-project-merge-request-note-award-emoji-delete gitlab-feature-delete command line
    command line option, 685                               option, 478
gitlab-project-merge-request-note-award-emoji-ignore gitlab-gitignore-get command line
    command line option, 686                               option, 482
gitlab-project-merge-request-note-award-emoji-gitlababcyaml-get command line
    command line option, 686                               option, 483
gitlab-project-merge-request-note-award-emoji-group gitlab-group-access-token-create
    command line option, 686                               command line option, 491
gitlab-project-merge-request-note-create      gitlab-group-board-create command line
    command line option, 683                               option, 498
gitlab-project-merge-request-note-delete      gitlab-group-cluster-create command
    command line option, 683                               line option, 501
gitlab-project-merge-request-note-get       gitlab-group-cluster-update command
    command line option, 684                               line option, 502
gitlab-project-merge-request-note-list      gitlab-group-create command line option,
    command line option, 684                               485
gitlab-project-merge-request-note-update      gitlab-group-deploy-token-create
    command line option, 685                               command line option, 504
gitlab-project-merge-request-pipeline-create      gitlab-group-epic-award-emoji-create
    command line option, 687                               command line option, 509
gitlab-project-merge-request-pipeline-list      gitlab-group-epic-note-award-emoji-create
    command line option, 687                               command line option, 516
```

gitlab-group-label-create command line option, 528
gitlab-group-label-delete command line option, 528
gitlab-group-label-get command line option, 529
gitlab-group-label-subscribe command line option, 529
gitlab-group-label-unsubscribe command line option, 530
gitlab-group-label-update command line option, 530
gitlab-group-update command line option, 489
gitlab-project-access-token-create command line option, 578
gitlab-project-approval-rule-create command line option, 581
gitlab-project-board-create command line option, 587
gitlab-project-branch-delete command line option, 591
gitlab-project-branch-get command line option, 591
gitlab-project-cluster-create command line option, 594
gitlab-project-cluster-update command line option, 595
gitlab-project-commit-status-create command line option, 604
gitlab-project-create command line option, 563
gitlab-project-deploy-token-create command line option, 606
gitlab-project-environment-create command line option, 613
gitlab-project-environment-list command line option, 613
gitlab-project-environment-update command line option, 614
gitlab-project-issue-award-emoji-create command line option, 636
gitlab-project-issue-note-award-emoji-create command line option, 644
gitlab-project-label-create command line option, 656
gitlab-project-label-delete command line option, 656
gitlab-project-label-get command line option, 656
gitlab-project-label-subscribe command line option, 657
gitlab-project-label-unsubscribe command line option, 657
gitlab-project-label-update command line option, 658
gitlab-project-merge-request-approval-rule-create command line option, 673
gitlab-project-merge-request-approval-rule-update command line option, 675
gitlab-project-merge-request-award-emoji-create command line option, 676
gitlab-project-merge-request-note-award-emoji-create command line option, 685
gitlab-project-pipeline-list command line option, 702
gitlab-project-protected-branch-create command line option, 711
gitlab-project-protected-branch-delete command line option, 711
gitlab-project-protected-branch-get command line option, 711
gitlab-project-protected-environment-create command line option, 712
gitlab-project-protected-environment-delete command line option, 713
gitlab-project-protected-environment-get command line option, 713
gitlab-project-protected-tag-create command line option, 714
gitlab-project-protected-tag-delete command line option, 714
gitlab-project-protected-tag-get command line option, 715
gitlab-project-registry-tag-delete command line option, 719
gitlab-project-registry-tag-delete-in-bulk command line option, 719
gitlab-project-registry-tag-get command line option, 720
gitlab-project-release-create command line option, 721
gitlab-project-release-link-create command line option, 723
gitlab-project-release-link-update command line option, 725
gitlab-project-release-update command line option, 722
gitlab-project-snippet-award-emoji-create command line option, 732
gitlab-project-snippet-note-award-emoji-create command line option, 740
gitlab-project-tag-delete command line option, 742
gitlab-project-tag-get command line option, 742
gitlab-project-update command line option, 575

```
gitlab-topic-create command line option,      --new-project-guidelines
    761                                         gitlab-application-appearance-update
gitlab-topic-update command line option,      command line option, 463
    762                                         --not
gitlab-user-create command line option,       gitlab-merge-request-list command line
    764                                         option, 556
gitlab-user-impersonation-token-create      gitlab-project-deployment-merge-request-list
    command line option, 774                     command line option, 612
gitlab-user-personal-access-token-create     --note
    command line option, 778                     gitlab-project-commit-comment-create
gitlab-user-project-create command line      command line option, 600
    option, 779                     --note-events
                                         gitlab-group-hook-create command line
                                         option, 520
                                         gitlab-group-hook-update command line
                                         option, 522
                                         gitlab-project-hook-create command line
                                         option, 621
                                         gitlab-project-hook-update command line
                                         option, 623
--name-regex-delete                         --note-id
                                         gitlab-group-epic-note-award-emoji-create
                                         command line option, 516
                                         gitlab-group-epic-note-award-emoji-delete
                                         command line option, 517
                                         gitlab-group-epic-note-award-emoji-get
                                         command line option, 517
                                         gitlab-group-epic-note-award-emoji-list
                                         command line option, 517
                                         gitlab-project-issue-note-award-emoji-create
                                         command line option, 644
                                         gitlab-project-issue-note-award-emoji-delete
                                         command line option, 645
                                         gitlab-project-issue-note-award-emoji-get
                                         command line option, 645
                                         gitlab-project-issue-note-award-emoji-list
                                         command line option, 646
                                         gitlab-project-merge-request-note-award-emoji-create
                                         command line option, 685
                                         gitlab-project-merge-request-note-award-emoji-delete
                                         command line option, 686
                                         gitlab-project-merge-request-note-award-emoji-get
                                         command line option, 686
                                         gitlab-project-merge-request-note-award-emoji-list
                                         command line option, 686
                                         gitlab-project-snippet-note-award-emoji-create
                                         command line option, 739
                                         gitlab-project-snippet-note-award-emoji-delete
                                         command line option, 740
                                         gitlab-project-snippet-note-award-emoji-get
                                         command line option, 740
                                         gitlab-project-snippet-note-award-emoji-list
                                         command line option, 741
--name-regex-keep                           --notification-email
```

```

gitlab-group-notification-settings-update command line option, 539
gitlab-notification-settings-update command line option, 558
gitlab-project-notification-settings-update command line option, 696
--oauth-token gitlab command line option, 460
--older-than gitlab-project-registry-tag-delete-in-bulk command line option, 719
--only-allow-merge-if-all-discussions-are-resolved gitlab-project-create command line option, 564
gitlab-project-update command line option, 575
--only-allow-merge-if-build-succeeds gitlab-user-project-create command line option, 779
--only-allow-merge-if-pipeline-succeeds gitlab-project-create command line option, 564
gitlab-project-update command line option, 575
--only-mirror-protected-branches gitlab-project-update command line option, 575
--only-protected-branches gitlab-project-remote-mirror-create command line option, 725
gitlab-project-remote-mirror-update command line option, 726
--operations-access-level gitlab-project-create command line option, 564
gitlab-project-update command line option, 575
--order gitlab-project-commit-list command line option, 598
--order-by gitlab command line option, 460
gitlab-group-descendant-group-list command line option, 506
gitlab-group-epic-list command line option, 508
gitlab-group-issue-list command line option, 526
gitlab-group-list command line option, 487
gitlab-group-merge-request-list command line option, 534
gitlab-group-package-list command line option, 539
gitlab-group-project-list command line option, 540
gitlab-group-subgroup-list command line option, 545
gitlab-issue-list command line option, 551
gitlab-merge-request-list command line option, 555
gitlab-project-deployment-list command line option, 609
gitlab-project-deployment-merge-request-list command line option, 611
gitlab-project-fork-list command line option, 620
gitlab-project-issue-list command line option, 631
gitlab-project-list command line option, 567
gitlab-project-merge-request-list command line option, 666
gitlab-project-package-list command line option, 697
gitlab-project-pipeline-list command line option, 702
gitlab-project-release-list command line option, 722
gitlab-shared-project-list command line option, 755
gitlab-starred-project-list command line option, 759
gitlab-user-project-list command line option, 780
--organization gitlab-user-create command line option, 765
gitlab-user-update command line option, 768
--outbound-local-requests-whitelist gitlab-application-settings-update command line option, 465
--output gitlab command line option, 460
--owned gitlab-group-descendant-group-list command line option, 506
gitlab-group-list command line option, 487
gitlab-group-project-list command line option, 541
gitlab-group-subgroup-list command line option, 545
gitlab-project-fork-list command line option, 620
gitlab-project-list command line option,

```

567
gitlab-starred-project-list command
line option, 759
gitlab-user-project-list command line
option, 780
--package-id
gitlab-project-package-file-delete
command line option, 698
gitlab-project-package-file-list
command line option, 698
--package-name
gitlab-generic-package-download command
line option, 479
gitlab-generic-package-upload command
line option, 479
gitlab-group-package-list command line
option, 540
gitlab-project-package-list command
line option, 697
--package-type
gitlab-group-package-list command line
option, 539
gitlab-project-package-list command
line option, 697
--package-version
gitlab-generic-package-download command
line option, 479
gitlab-generic-package-upload command
line option, 479
--packages-enabled
gitlab-project-create command line
option, 564
gitlab-project-update command line
option, 575
--page
gitlab-application-list command line
option, 461
gitlab-audit-event-list command line
option, 467
gitlab-broadcast-message-list command
line option, 469
gitlab-current-user-email-list command
line option, 472
gitlab-current-user-gpg-key-list
command line option, 473
gitlab-current-user-key-list command
line option, 474
gitlab-deploy-key-list command line
option, 476
gitlab-deploy-token-list command line
option, 476
gitlab-dockerfile-list command line
option, 477
gitlab-event-list command line option,
478
gitlab-feature-list command line option,
478
gitlab-geo-node-list command line
option, 481
gitlab-gitignore-list command line
option, 482
gitlab-gitlabciyml-list command line
option, 483
gitlab-group-access-request-list
command line option, 491
gitlab-group-access-token-list command
line option, 492
gitlab-group-audit-event-list command
line option, 493
gitlab-group-badge-list command line
option, 495
gitlab-group-billable-member-list
command line option, 496
gitlab-group-billable-member-membership-list
command line option, 497
gitlab-group-board-list command line
option, 498
gitlab-group-board-list-list command
line option, 500
gitlab-group-cluster-list command line
option, 502
gitlab-group-custom-attribute-list
command line option, 504
gitlab-group-deploy-token-list command
line option, 505
gitlab-group-descendant-group-list
command line option, 506
gitlab-group-epic-award-emoji-list
command line option, 510
gitlab-group-epic-issue-list command
line option, 514
gitlab-group-epic-list command line
option, 508
gitlab-group-epic-note-award-emoji-list
command line option, 518
gitlab-group-epic-note-list command
line option, 516
gitlab-group-epic-resource-label-event-list
command line option, 519
gitlab-group-hook-list command line
option, 521
gitlab-group-invitation-list command
line option, 524
gitlab-group-issue-list command line
option, 526
gitlab-group-iteration-list command
line option, 527
gitlab-group-label-list command line

option, 529
gitlab-group-list command line option, 487
gitlab-group-member-all-list command line option, 533
gitlab-group-member-list command line option, 532
gitlab-group-merge-request-list command line option, 535
gitlab-group-milestone-list command line option, 537
gitlab-group-package-list command line option, 540
gitlab-group-project-list command line option, 541
gitlab-group-runner-list command line option, 544
gitlab-group-subgroup-list command line option, 545
gitlab-group-variable-list command line option, 546
gitlab-group-wiki-list command line option, 548
gitlab-hook-list command line option, 550
gitlab-issue-list command line option, 551
gitlab-ldap-group-list command line option, 553
gitlab-license-list command line option, 554
gitlab-merge-request-list command line option, 556
gitlab-namespace-list command line option, 557
gitlab-pages-domain-list command line option, 558
gitlab-personal-access-token-list command line option, 559
gitlab-project-access-request-list command line option, 578
gitlab-project-access-token-list command line option, 579
gitlab-project-approval-rule-list command line option, 582
gitlab-project-audit-event-list command line option, 584
gitlab-project-badge-list command line option, 586
gitlab-project-board-list command line option, 588
gitlab-project-board-list-list command line option, 590
gitlab-project-branch-list command line option, 592
gitlab-project-cluster-list command line option, 595
gitlab-project-commit-comment-list command line option, 600
gitlab-project-commit-discussion-list command line option, 601
gitlab-project-commit-list command line option, 598
gitlab-project-commit-status-list command line option, 605
gitlab-project-custom-attribute-list command line option, 606
gitlab-project-deploy-token-list command line option, 607
gitlab-project-deployment-list command line option, 609
gitlab-project-deployment-merge-request-list command line option, 612
gitlab-project-environment-list command line option, 614
gitlab-project-event-list command line option, 615
gitlab-project-fork-list command line option, 620
gitlab-project-hook-list command line option, 622
gitlab-project-integration-list command line option, 625
gitlab-project-invitation-list command line option, 627
gitlab-project-issue-award-emoji-list command line option, 637
gitlab-project-issue-discussion-list command line option, 638
gitlab-project-issue-link-list command line option, 642
gitlab-project-issue-list command line option, 631
gitlab-project-issue-note-award-emoji-list command line option, 646
gitlab-project-issue-note-list command line option, 643
gitlab-project-issue-resource-label-event-list command line option, 647
gitlab-project-issue-resource-milestone-event-list command line option, 648
gitlab-project-issue-resource-state-event-list command line option, 649
gitlab-project-job-list command line option, 652
gitlab-project-key-list command line option, 655
gitlab-project-label-list command line option, 657

gitlab-project-list command line option, 567
gitlab-project-member-all-list command line option, 661
gitlab-project-member-list command line option, 659
gitlab-project-merge-request-approval-rule-list command line option, 674
gitlab-project-merge-request-award-emoji-list command line option, 677
gitlab-project-merge-request-diff-list command line option, 678
gitlab-project-merge-request-discussion-list command line option, 680
gitlab-project-merge-request-list command line option, 666
gitlab-project-merge-request-note-award-emoji-list command line option, 686
gitlab-project-merge-request-note-list command line option, 684
gitlab-project-merge-request-pipeline-list command line option, 687
gitlab-project-merge-request-resource-label-event command line option, 688
gitlab-project-merge-request-resource-milestone-command line option, 689
gitlab-project-merge-request-resource-state-event command line option, 690
gitlab-project-merge-train-list command line option, 691
gitlab-project-milestone-list command line option, 693
gitlab-project-note-list command line option, 695
gitlab-project-package-file-list command line option, 698
gitlab-project-package-list command line option, 697
gitlab-project-pages-domain-list command line option, 700
gitlab-project-pipeline-bridge-list command line option, 703
gitlab-project-pipeline-job-list command line option, 704
gitlab-project-pipeline-list command line option, 702
gitlab-project-pipeline-schedule-list command line option, 706
gitlab-project-pipeline-variable-list command line option, 710
gitlab-project-protected-branch-list command line option, 712
gitlab-project-protected-environment-list command line option, 713
gitlab-project-protected-tag-list command line option, 715
gitlab-project-registry-repository-list command line option, 718
gitlab-project-registry-tag-list command line option, 720
gitlab-project-release-link-list command line option, 724
gitlab-project-release-list command line option, 722
gitlab-project-remote-mirror-list command line option, 726
gitlab-project-runner-list command line option, 727
gitlab-project-service-list command line option, 729
gitlab-project-snippet-award-emoji-list command line option, 733
gitlab-project-snippet-discussion-list command line option, 735
gitlab-project-snippet-list command line option, 731
gitlab-project-snippet-note-award-emoji-list command line option, 741
gitlab-project-snippet-note-list command line option, 738
gitlab-project-tag-list command line option, 743
gitlab-project-trigger-list command line option, 744
gitlab-project-user-list command line option, 745
gitlab-project-variable-list command line option, 747
gitlab-project-wiki-list command line option, 749
gitlab-runner-all-list command line option, 753
gitlab-runner-job-list command line option, 754
gitlab-runner-list command line option, 752
gitlab-shared-project-list command line option, 755
gitlab-snippet-list command line option, 757
gitlab-starred-project-list command line option, 759
gitlab-todo-list command line option, 760
gitlab-topic-list command line option, 762
gitlab-user-activities-list command line option, 769
gitlab-user-custom-attribute-list

```

    command line option, 770
gitlab-user-email-list command line
    option, 771
gitlab-user-event-list command line
    option, 772
gitlab-user-gpg-key-list command line
    option, 774
gitlab-user-impersonation-token-list
    command line option, 775
gitlab-user-key-list command line
    option, 777
gitlab-user-list command line option, 766
gitlab-user-membership-list command
    line option, 778
gitlab-user-project-list command line
    option, 781
gitlab-variable-list command line
    option, 783
--pages-access-level
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 575
--pagination
    gitlab command line option, 460
--parent-id
    gitlab-group-create command line option,
        485
    gitlab-namespace-exists command line
        option, 556
--password
    gitlab-user-create command line option,
        764
    gitlab-user-update command line option,
        768
--password-authentication-enabled-for-web
    gitlab-application-settings-update
        command line option, 465
--path
    gitlab-generic-package-upload command
        line option, 479
    gitlab-group-create command line option,
        485
    gitlab-group-update command line option,
        489
    gitlab-project-commit-comment-create
        command line option, 600
    gitlab-project-commit-list command line
        option, 598
    gitlab-project-create command line
        option, 563
    gitlab-project-repository-tree command
        line option, 569
    gitlab-project-update command line
        option, 575
--paused
    gitlab-runner-all-list command line
        option, 753
    gitlab-runner-list command line option,
        752
--per-page
    gitlab command line option, 460
    gitlab-application-list command line
        option, 461
    gitlab-audit-event-list command line
        option, 468
    gitlab-broadcast-message-list command
        line option, 469
    gitlab-current-user-email-list command
        line option, 472
    gitlab-current-user-gpg-key-list
        command line option, 473
    gitlab-current-user-key-list command
        line option, 474
    gitlab-deploy-key-list command line
        option, 476
    gitlab-deploy-token-list command line
        option, 476
    gitlab-dockerfile-list command line
        option, 477
    gitlab-event-list command line option,
        478
    gitlab-feature-list command line option,
        478
    gitlab-geo-node-list command line
        option, 481
    gitlab-gitignore-list command line
        option, 482
    gitlab-gitlabciyml-list command line
        option, 483
    gitlab-group-access-request-list
        command line option, 491
    gitlab-group-access-token-list command
        line option, 492
    gitlab-group-audit-event-list command
        line option, 493
    gitlab-group-badge-list command line
        option, 495
    gitlab-group-billable-member-list
        command line option, 496
    gitlab-group-billable-member-membership-list
        command line option, 497
    gitlab-group-board-list command line
        option, 498
    gitlab-group-board-list-list command
        line option, 500
    gitlab-group-cluster-list command line
        option, 502

```

gitlab-group-custom-attribute-list
 command line option, 504
gitlab-group-deploy-token-list command
 line option, 505
gitlab-group-descendant-group-list
 command line option, 506
gitlab-group-emoji-award-emoji-list
 command line option, 510
gitlab-group-epic-issue-list command
 line option, 514
gitlab-group-epic-list command line
 option, 508
gitlab-group-epic-note-award-emoji-list
 command line option, 518
gitlab-group-epic-note-list command
 line option, 516
gitlab-group-epic-resource-label-event-list
 command line option, 519
gitlab-group-hook-list command line
 option, 521
gitlab-group-invitation-list command
 line option, 525
gitlab-group-issue-list command line
 option, 526
gitlab-group-iteration-list command
 line option, 527
gitlab-group-label-list command line
 option, 529
gitlab-group-list command line option,
 487
gitlab-group-member-all-list command
 line option, 533
gitlab-group-member-list command line
 option, 532
gitlab-group-merge-request-list command
 line option, 535
gitlab-group-milestone-list command
 line option, 537
gitlab-group-package-list command line
 option, 540
gitlab-group-project-list command line
 option, 541
gitlab-group-runner-list command line
 option, 544
gitlab-group-subgroup-list command line
 option, 545
gitlab-group-variable-list command line
 option, 546
gitlab-group-wiki-list command line
 option, 548
gitlab-hook-list command line option, 550
gitlab-issue-list command line option,
 551
gitlab-ldap-group-list command line
 option, 553
gitlab-license-list command line option,
 554
gitlab-merge-request-list command line
 option, 556
gitlab-namespace-list command line
 option, 557
gitlab-pages-domain-list command line
 option, 558
gitlab-personal-access-token-list
 command line option, 559
gitlab-project-access-request-list
 command line option, 578
gitlab-project-access-token-list
 command line option, 579
gitlab-project-approval-rule-list
 command line option, 582
gitlab-project-audit-event-list command
 line option, 584
gitlab-project-badge-list command line
 option, 586
gitlab-project-board-list command line
 option, 588
gitlab-project-board-list-list command
 line option, 590
gitlab-project-branch-list command line
 option, 592
gitlab-project-cluster-list command
 line option, 595
gitlab-project-commit-comment-list
 command line option, 600
gitlab-project-commit-discussion-list
 command line option, 601
gitlab-project-commit-list command line
 option, 598
gitlab-project-commit-status-list
 command line option, 605
gitlab-project-custom-attribute-list
 command line option, 606
gitlab-project-deploy-token-list
 command line option, 607
gitlab-project-deployment-list command
 line option, 609
gitlab-project-deployment-merge-request-list
 command line option, 612
gitlab-project-environment-list command
 line option, 614
gitlab-project-event-list command line
 option, 615
gitlab-project-fork-list command line
 option, 620
gitlab-project-hook-list command line
 option, 622
gitlab-project-integration-list command

```

    line option, 625
gitlab-project-invitation-list command
    line option, 627
gitlab-project-issue-award-emoji-list
    command line option, 637
gitlab-project-issue-discussion-list
    command line option, 639
gitlab-project-issue-link-list command
    line option, 642
gitlab-project-issue-list command line
    option, 631
gitlab-project-issue-note-award-emoji-list
    command line option, 646
gitlab-project-issue-note-list command
    line option, 643
gitlab-project-issue-resource-label-event-list
    command line option, 647
gitlab-project-issue-resource-milestone-event-list
    command line option, 648
gitlab-project-issue-resource-state-event-list
    command line option, 649
gitlab-project-job-list command line
    option, 652
gitlab-project-key-list command line
    option, 655
gitlab-project-label-list command line
    option, 657
gitlab-project-list command line option,
    567
gitlab-project-member-all-list command
    line option, 661
gitlab-project-member-list command line
    option, 659
gitlab-project-merge-request-approval-rule-list
    command line option, 674
gitlab-project-merge-request-award-emoji-list
    command line option, 677
gitlab-project-merge-request-diff-list
    command line option, 678
gitlab-project-merge-request-discussion-list
    command line option, 680
gitlab-project-merge-request-list
    command line option, 667
gitlab-project-merge-request-note-award-emoji-list
    command line option, 686
gitlab-project-merge-request-note-list
    command line option, 684
gitlab-project-merge-request-pipeline-list
    command line option, 687
gitlab-project-merge-request-resource-label-event-list
    command line option, 688
gitlab-project-merge-request-resource-milestone-list
    command line option, 689
gitlab-project-merge-request-resource-state-event-list
    command line option, 690
gitlab-project-merge-train-list command
    line option, 691
gitlab-project-milestone-list command
    line option, 693
gitlab-project-note-list command line
    option, 695
gitlab-project-package-file-list
    command line option, 698
gitlab-project-package-list command
    line option, 697
gitlab-project-pages-domain-list
    command line option, 700
gitlab-project-pipeline-bridge-list
    command line option, 703
gitlab-project-pipeline-job-list
    command line option, 704
gitlab-project-pipeline-list command
    line option, 702
gitlab-project-pipeline-schedule-list
    command line option, 706
gitlab-project-pipeline-variable-list
    command line option, 710
gitlab-project-protected-branch-list
    command line option, 712
gitlab-project-protected-environment-list
    command line option, 713
gitlab-project-protected-tag-list
    command line option, 715
gitlab-project-registry-repository-list
    command line option, 718
gitlab-project-registry-tag-list
    command line option, 720
gitlab-project-release-link-list
    command line option, 724
gitlab-project-release-list command
    line option, 722
gitlab-project-remote-mirror-list
    command line option, 726
gitlab-project-runner-list command line
    option, 727
gitlab-project-service-list command
    line option, 729
gitlab-project-snippet-award-emoji-list
    command line option, 733
gitlab-project-snippet-discussion-list
    command line option, 735
gitlab-project-snippet-list command
    line option, 731
gitlab-project-snippet-note-award-emoji-list
    command line option, 741
gitlab-project-snippet-note-list
    command line option, 738
gitlab-project-tag-list command line
    
```

```
    option, 743
gitlab-project-trigger-list command
    line option, 744
gitlab-project-user-list command line
    option, 745
gitlab-project-variable-list command
    line option, 747
gitlab-project-wiki-list command line
    option, 749
gitlab-runner-all-list command line
    option, 753
gitlab-runner-job-list command line
    option, 754
gitlab-runner-list command line option,
    752
gitlab-shared-project-list command line
    option, 755
gitlab-snippet-list command line option,
    757
gitlab-starred-project-list command
    line option, 759
gitlab-todo-list command line option, 760
gitlab-topic-list command line option,
    762
gitlab-user-activities-list command
    line option, 769
gitlab-user-custom-attribute-list
    command line option, 770
gitlab-user-email-list command line
    option, 772
gitlab-user-event-list command line
    option, 772
gitlab-user-gpg-key-list command line
    option, 774
gitlab-user-impersonation-token-list
    command line option, 775
gitlab-user-key-list command line
    option, 777
gitlab-user-list command line option, 776
gitlab-user-membership-list command
    line option, 778
gitlab-user-project-list command line
    option, 781
gitlab-variable-list command line
    option, 783
--performance-bar-allowed-group-id
    gitlab-application-settings-update
        command line option, 466
--pipeline-events
    gitlab-group-hook-create command line
        option, 520
    gitlab-group-hook-update command line
        option, 522
    gitlab-project-hook-create command line
        option, 621
gitlab-project-hook-update command line
    option, 623
--pipeline-id
    gitlab-project-pipeline-bridge-list
        command line option, 703
    gitlab-project-pipeline-job-list
        command line option, 704
    gitlab-project-pipeline-test-report-get
        command line option, 709
    gitlab-project-pipeline-test-report-summary-get
        command line option, 709
    gitlab-project-pipeline-variable-list
        command line option, 710
--pipeline-schedule-id
    gitlab-project-pipeline-schedule-variable-create
        command line option, 708
    gitlab-project-pipeline-schedule-variable-delete
        command line option, 708
    gitlab-project-pipeline-schedule-variable-update
        command line option, 708
--plantuml-enabled
    gitlab-application-settings-update
        command line option, 466
--plantuml-url
    gitlab-application-settings-update
        command line option, 466
--platform-kubernetes-attributes
    gitlab-group-cluster-create command
        line option, 501
    gitlab-group-cluster-update command
        line option, 503
    gitlab-project-cluster-create command
        line option, 594
    gitlab-project-cluster-update command
        line option, 595
--polling-interval-multiplier
    gitlab-application-settings-update
        command line option, 466
--popular
    gitlab-license-list command line option,
    554
--position
    gitlab-group-board-list-update command
        line option, 501
    gitlab-project-board-list-update
        command line option, 590
    gitlab-project-commit-discussion-note-create
        command line option, 602
    gitlab-project-merge-request-discussion-create
        command line option, 679
--prevent-forking-outside-group
    gitlab-group-update command line option,
    489
```

```
--prevent-secrets
    gitlab-group-push-rules-create command
        line option, 542
    gitlab-group-push-rules-update command
        line option, 543
    gitlab-project-push-rules-create
        command line option, 716
    gitlab-project-push-rules-update
        command line option, 718
--printing-merge-request-link-enabled
    gitlab-project-create command line
        option, 564
--priority
    gitlab-group-label-create command line
        option, 528
    gitlab-group-label-update command line
        option, 530
    gitlab-project-label-create command
        line option, 656
    gitlab-project-label-update command
        line option, 658
--private-profile
    gitlab-user-create command line option,
        765
    gitlab-user-update command line option,
        768
--private-token
    gitlab command line option, 460
--project
    gitlab-license-get command line option,
        553
--project-creation-level
    gitlab-group-create command line option,
        485
    gitlab-group-update command line option,
        489
--project-id
    gitlab-generic-package-download command
        line option, 479
    gitlab-generic-package-upload command
        line option, 479
    gitlab-group-transfer-project command
        line option, 488
    gitlab-project-access-request-approve
        command line option, 577
    gitlab-project-access-request-create
        command line option, 577
    gitlab-project-access-request-delete
        command line option, 577
    gitlab-project-access-request-list
        command line option, 578
    gitlab-project-access-token-create
        command line option, 578
    gitlab-project-access-token-delete
        command line option, 579
gitlab-project-access-token-list
        command line option, 579
gitlab-project-additional-statistics-get
        command line option, 580
gitlab-project-approval-get command
        line option, 580
gitlab-project-approval-rule-create
        command line option, 581
gitlab-project-approval-rule-delete
        command line option, 581
gitlab-project-approval-rule-list
        command line option, 582
gitlab-project-approval-rule-update
        command line option, 582
gitlab-project-approval-update command
        line option, 580
gitlab-project-artifact-delete command
        line option, 583
gitlab-project-artifact-download
        command line option, 583
gitlab-project-artifact-raw command
        line option, 583
gitlab-project-audit-event-get command
        line option, 584
gitlab-project-audit-event-list command
        line option, 584
gitlab-project-badge-create command
        line option, 585
gitlab-project-badge-delete command
        line option, 585
gitlab-project-badge-get command line
        option, 585
gitlab-project-badge-list command line
        option, 586
gitlab-project-badge-render command
        line option, 586
gitlab-project-badge-update command
        line option, 586
gitlab-project-board-create command
        line option, 587
gitlab-project-board-delete command
        line option, 587
gitlab-project-board-get command line
        option, 587
gitlab-project-board-list command line
        option, 588
gitlab-project-board-list-create
        command line option, 589
gitlab-project-board-list-delete
        command line option, 589
gitlab-project-board-list-get command
        line option, 589
gitlab-project-board-list-list command
```

```
    line option, 590
gitlab-project-board-list-update
    command line option, 590
gitlab-project-board-update command
    line option, 588
gitlab-project-branch-create command
    line option, 591
gitlab-project-branch-delete command
    line option, 591
gitlab-project-branch-get command line
    option, 591
gitlab-project-branch-list command line
    option, 592
gitlab-project-ci-lint-create command
    line option, 592
gitlab-project-ci-lint-get command line
    option, 593
gitlab-project-ci-lint-validate command
    line option, 593
gitlab-project-cluster-create command
    line option, 594
gitlab-project-cluster-delete command
    line option, 594
gitlab-project-cluster-get command line
    option, 594
gitlab-project-cluster-list command
    line option, 595
gitlab-project-cluster-update command
    line option, 595
gitlab-project-commit-cherry-pick
    command line option, 596
gitlab-project-commit-comment-create
    command line option, 599
gitlab-project-commit-comment-list
    command line option, 600
gitlab-project-commit-create command
    line option, 596
gitlab-project-commit-diff command line
    option, 597
gitlab-project-commit-discussion-create
    command line option, 601
gitlab-project-commit-discussion-get
    command line option, 601
gitlab-project-commit-discussion-list
    command line option, 601
gitlab-project-commit-discussion-note-create
    command line option, 602
gitlab-project-commit-discussion-note-delete
    command line option, 602
gitlab-project-commit-discussion-note-get
    command line option, 603
gitlab-project-commit-discussion-note-update
    command line option, 603
gitlab-project-commit-get command line
    option, 597
gitlab-project-commit-list command line
    option, 597
gitlab-project-commit-merge-requests
    command line option, 598
gitlab-project-commit-refs command line
    option, 598
gitlab-project-commit-revert command
    line option, 599
gitlab-project-commit-signature command
    line option, 599
gitlab-project-commit-status-create
    command line option, 604
gitlab-project-commit-status-list
    command line option, 604
gitlab-project-custom-attribute-delete
    command line option, 605
gitlab-project-custom-attribute-get
    command line option, 605
gitlab-project-custom-attribute-list
    command line option, 606
gitlab-project-deploy-token-create
    command line option, 606
gitlab-project-deploy-token-delete
    command line option, 607
gitlab-project-deploy-token-get command
    line option, 607
gitlab-project-deploy-token-list
    command line option, 607
gitlab-project-deployment-approval
    command line option, 608
gitlab-project-deployment-create
    command line option, 608
gitlab-project-deployment-get command
    line option, 609
gitlab-project-deployment-list command
    line option, 609
gitlab-project-deployment-merge-request-list
    command line option, 611
gitlab-project-deployment-update
    command line option, 610
gitlab-project-environment-create
    command line option, 613
gitlab-project-environment-delete
    command line option, 613
gitlab-project-environment-get command
    line option, 613
gitlab-project-environment-list command
    line option, 613
gitlab-project-environment-stop command
    line option, 614
gitlab-project-environment-update
    command line option, 614
gitlab-project-event-list command line
```

```
    option, 615
gitlab-project-export-create command
    line option, 616
gitlab-project-export-download command
    line option, 616
gitlab-project-export-get command line
    option, 616
gitlab-project-file-blame command line
    option, 617
gitlab-project-file-create command line
    option, 617
gitlab-project-file-delete command line
    option, 618
gitlab-project-file-get command line
    option, 618
gitlab-project-file-raw command line
    option, 618
gitlab-project-file-update command line
    option, 619
gitlab-project-fork-create command line
    option, 619
gitlab-project-fork-list command line
    option, 620
gitlab-project-hook-create command line
    option, 621
gitlab-project-hook-delete command line
    option, 622
gitlab-project-hook-get command line
    option, 622
gitlab-project-hook-list command line
    option, 622
gitlab-project-hook-update command line
    option, 623
gitlab-project-import-get command line
    option, 624
gitlab-project-integration-available
    command line option, 624
gitlab-project-integration-delete
    command line option, 624
gitlab-project-integration-get command
    line option, 625
gitlab-project-integration-list command
    line option, 625
gitlab-project-integration-update
    command line option, 625
gitlab-project-invitation-create
    command line option, 626
gitlab-project-invitation-delete
    command line option, 626
gitlab-project-invitation-get command
    line option, 627
gitlab-project-invitation-list command
    line option, 627
gitlab-project-invitation-update
```

```
    command line option, 627
gitlab-project-issue-add-spent-time
    command line option, 628
gitlab-project-issue-award-emoji-create
    command line option, 636
gitlab-project-issue-award-emoji-delete
    command line option, 636
gitlab-project-issue-award-emoji-get
    command line option, 637
gitlab-project-issue-award-emoji-list
    command line option, 637
gitlab-project-issue-closed-by command
    line option, 629
gitlab-project-issue-create command
    line option, 629
gitlab-project-issue-delete command
    line option, 630
gitlab-project-issue-discussion-create
    command line option, 638
gitlab-project-issue-discussion-get
    command line option, 638
gitlab-project-issue-discussion-list
    command line option, 638
gitlab-project-issue-discussion-note-create
    command line option, 639
gitlab-project-issue-discussion-note-delete
    command line option, 640
gitlab-project-issue-discussion-note-get
    command line option, 640
gitlab-project-issue-discussion-note-update
    command line option, 641
gitlab-project-issue-get command line
    option, 630
gitlab-project-issue-link-create
    command line option, 641
gitlab-project-issue-link-delete
    command line option, 641
gitlab-project-issue-link-list command
    line option, 642
gitlab-project-issue-list command line
    option, 630
gitlab-project-issue-move command line
    option, 631
gitlab-project-issue-note-award-emoji-create
    command line option, 644
gitlab-project-issue-note-award-emoji-delete
    command line option, 645
gitlab-project-issue-note-award-emoji-get
    command line option, 645
gitlab-project-issue-note-award-emoji-list
    command line option, 646
gitlab-project-issue-note-create
    command line option, 642
gitlab-project-issue-note-delete
```

```
    command line option, 643
gitlab-project-issue-note-get command
    line option, 643
gitlab-project-issue-note-list command
    line option, 643
gitlab-project-issue-note-update
    command line option, 644
gitlab-project-issue-participants
    command line option, 632
gitlab-project-issue-related-merge-requests
    command line option, 632
gitlab-project-issue-reorder command
    line option, 632
gitlab-project-issue-reset-spent-time
    command line option, 633
gitlab-project-issue-reset-time-estimate
    command line option, 633
gitlab-project-issue-resource-label-event-get gitlab-project-key-enable command line
    command line option, 646
gitlab-project-issue-resource-label-event-listgitlab-project-key-get command line
    command line option, 647
gitlab-project-issue-resource-milestone-event-gitlab-project-key-list command line
    command line option, 647
gitlab-project-issue-resource-milestone-event-gitlab-project-key-update command line
    command line option, 648
gitlab-project-issue-resource-state-event-get gitlab-project-label-create command
    command line option, 648
gitlab-project-issue-resource-state-event-listgitlab-project-label-delete command
    command line option, 649
gitlab-project-issue-subscribe command
    line option, 633
gitlab-project-issue-time-estimate
    command line option, 633
gitlab-project-issue-time-stats command
    line option, 634
gitlab-project-issue-todo command line
    option, 634
gitlab-project-issue-unsubscribe
    command line option, 634
gitlab-project-issue-update command
    line option, 635
gitlab-project-issue-user-agent-detail
    command line option, 635
gitlab-project-issues-statistics-get
    command line option, 649
gitlab-project-job-artifact command
    line option, 650
gitlab-project-job-artifacts command
    line option, 650
gitlab-project-job-cancel command line
    option, 651
gitlab-project-job-delete-artifacts
    command line option, 651
gitlab-project-job-erase command line
    option, 651
gitlab-project-job-get command line
    option, 651
gitlab-project-job-keep-artifacts
    command line option, 652
gitlab-project-job-list command line
    option, 652
gitlab-project-job-play command line
    option, 652
gitlab-project-job-retry command line
    option, 653
gitlab-project-job-trace command line
    option, 653
gitlab-project-key-create command line
    option, 653
gitlab-project-key-delete command line
    option, 654
gitlab-project-key-enable command line
    option, 654
gitlab-project-key-get command line
    option, 654
gitlab-project-key-list command line
    option, 655
gitlab-project-key-update command line
    option, 655
gitlab-project-label-create command
    line option, 656
gitlab-project-label-delete command
    line option, 656
gitlab-project-label-get command line
    option, 656
gitlab-project-label-list command line
    option, 657
gitlab-project-label-subscribe command
    line option, 657
gitlab-project-label-unsubscribe
    command line option, 657
gitlab-project-label-update command
    line option, 658
gitlab-project-member-all-get command
    line option, 660
gitlab-project-member-all-list command
    line option, 660
gitlab-project-member-create command
    line option, 658
gitlab-project-member-delete command
    line option, 659
gitlab-project-member-get command line
    option, 659
gitlab-project-member-list command line
    option, 659
gitlab-project-member-update command
    line option, 660
gitlab-project-merge-request-add-spent-time
```

```

    command line option, 662
gitlab-project-merge-request-approval-get    command line option, 682
    command line option, 672
gitlab-project-merge-request-approval-rule-create    command line option, 682
    command line option, 673
gitlab-project-merge-request-approval-rule-delete    command line option, 680
    command line option, 673
gitlab-project-merge-request-approval-rule-getgitlab-project-merge-request-list    command line option, 680
    command line option, 674
gitlab-project-merge-request-approval-rule-listgitlab-project-merge-request-merge    command line option, 665
    command line option, 674
gitlab-project-merge-request-approval-rule-updategitlab-project-merge-request-ref    command line option, 667
    command line option, 675
gitlab-project-merge-request-approval-state-getgitlab-project-merge-request-note-award-emoji-create    command line option, 685
    command line option, 676
gitlab-project-merge-request-approval-updategitlab-project-merge-request-note-award-emoji-delete    command line option, 685
    command line option, 672
gitlab-project-merge-request-approvegitlab-project-merge-request-note-award-emoji-get    command line option, 686
    command line option, 662
gitlab-project-merge-request-award-emoji-creategitlab-project-merge-request-note-award-emoji-list    command line option, 686
    command line option, 676
gitlab-project-merge-request-award-emoji-deletgitlab-project-merge-request-note-create    command line option, 683
    command line option, 677
gitlab-project-merge-request-award-emoji-getgitlab-project-merge-request-note-delete    command line option, 683
    command line option, 677
gitlab-project-merge-request-award-emoji-list gitlab-project-merge-request-note-get    command line option, 684
    command line option, 677
gitlab-project-merge-request-cancel-merge-whengitlab-project-merge-request-note-list    command line option, 684
    command line option, 662
gitlab-project-merge-request-changesgitlab-project-merge-request-note-update    command line option, 685
    command line option, 663
gitlab-project-merge-request-closes-issuesgitlab-project-merge-request-participants    command line option, 668
    command line option, 663
gitlab-project-merge-request-commitsgitlab-project-merge-request-pipeline-create    command line option, 687
    command line option, 663
gitlab-project-merge-request-creategitlab-project-merge-request-pipeline-list    command line option, 687
    command line option, 664
gitlab-project-merge-request-deletegitlab-project-merge-request-rebase    command line option, 668
    command line option, 665
gitlab-project-merge-request-diff-getgitlab-project-merge-request-reset-approvals    command line option, 668
    command line option, 678
gitlab-project-merge-request-diff-listgitlab-project-merge-request-reset-spent-time    command line option, 668
    command line option, 678
gitlab-project-merge-request-discussion-creategitlab-project-merge-request-reset-time-estimate    command line option, 669
    command line option, 679
gitlab-project-merge-request-discussion-getgitlab-project-merge-request-resource-label-event-get    command line option, 688
    command line option, 679
gitlab-project-merge-request-discussion-listgitlab-project-merge-request-resource-label-event-list    command line option, 688
    command line option, 680
gitlab-project-merge-request-discussion-note-creategitlab-project-merge-request-resource-milestone-event    command line option, 689
    command line option, 681
gitlab-project-merge-request-discussion-note-deletegitlab-project-merge-request-resource-milestone-event    command line option, 689
    command line option, 681
gitlab-project-merge-request-discussion-note-getgitlab-project-merge-request-resource-state-event-get

```

```
    command line option, 690
gitlab-project-merge-request-resource-state-event command
    command line option, 690
gitlab-project-merge-request-subscribe
    command line option, 669
gitlab-project-merge-request-time-estimate
    command line option, 669
gitlab-project-merge-request-time-stats
    command line option, 670
gitlab-project-merge-request-todo
    command line option, 670
gitlab-project-merge-request-unapprove
    command line option, 670
gitlab-project-merge-request-unsubscribe
    command line option, 670
gitlab-project-merge-request-update
    command line option, 671
gitlab-project-merge-train-list command
    line option, 691
gitlab-project-milestone-create command
    line option, 692
gitlab-project-milestone-delete command
    line option, 692
gitlab-project-milestone-get command
    line option, 692
gitlab-project-milestone-issues command
    line option, 693
gitlab-project-milestone-list command
    line option, 693
gitlab-project-milestone-merge-requests
    command line option, 693
gitlab-project-milestone-update command
    line option, 694
gitlab-project-note-get command line
    option, 694
gitlab-project-note-list command line
    option, 695
gitlab-project-notification-settings-get
    command line option, 695
gitlab-project-notification-settings-update
    command line option, 696
gitlab-project-package-delete command
    line option, 697
gitlab-project-package-file-delete
    command line option, 698
gitlab-project-package-file-list
    command line option, 698
gitlab-project-package-get command line
    option, 697
gitlab-project-package-list command
    line option, 697
gitlab-project-pages-domain-create
    command line option, 699
gitlab-project-pages-domain-delete
    command line option, 699
gitlab-project-project-pages-domain-get command
    line option, 700
gitlab-project-pages-domain-list
    command line option, 700
gitlab-project-pages-domain-update
    command line option, 700
gitlab-project-pipeline-bridge-list
    command line option, 703
gitlab-project-pipeline-cancel command
    line option, 701
gitlab-project-pipeline-create command
    line option, 701
gitlab-project-pipeline-delete command
    line option, 701
gitlab-project-pipeline-get command
    line option, 702
gitlab-project-pipeline-job-list
    command line option, 704
gitlab-project-pipeline-list command
    line option, 702
gitlab-project-pipeline-retry command
    line option, 703
gitlab-project-pipeline-schedule-create
    command line option, 705
gitlab-project-pipeline-schedule-delete
    command line option, 705
gitlab-project-pipeline-schedule-get
    command line option, 705
gitlab-project-pipeline-schedule-list
    command line option, 706
gitlab-project-pipeline-schedule-play
    command line option, 706
gitlab-project-pipeline-schedule-take-ownership
    command line option, 706
gitlab-project-pipeline-schedule-update
    command line option, 707
gitlab-project-pipeline-schedule-variable-create
    command line option, 707
gitlab-project-pipeline-schedule-variable-delete
    command line option, 708
gitlab-project-pipeline-schedule-variable-update
    command line option, 708
gitlab-project-pipeline-test-report-get
    command line option, 709
gitlab-project-pipeline-test-report-summary-get
    command line option, 709
gitlab-project-pipeline-variable-list
    command line option, 710
gitlab-project-protected-branch-create
    command line option, 711
gitlab-project-protected-branch-delete
    command line option, 711
gitlab-project-protected-branch-get
```

```
    command line option, 711
gitlab-project-protected-branch-list
    command line option, 712
gitlab-project-protected-environment-create
    command line option, 712
gitlab-project-protected-environment-delete
    command line option, 713
gitlab-project-protected-environment-get
    command line option, 713
gitlab-project-protected-environment-list
    command line option, 713
gitlab-project-protected-tag-create
    command line option, 714
gitlab-project-protected-tag-delete
    command line option, 714
gitlab-project-protected-tag-get
    command line option, 715
gitlab-project-protected-tag-list
    command line option, 715
gitlab-project-push-rules-create
    command line option, 716
gitlab-project-push-rules-delete
    command line option, 717
gitlab-project-push-rules-get command
    line option, 717
gitlab-project-push-rules-update
    command line option, 717
gitlab-project-registry-repository-delete
    command line option, 718
gitlab-project-registry-repository-list
    command line option, 718
gitlab-project-registry-tag-delete
    command line option, 719
gitlab-project-registry-tag-delete-in-bulk
    command line option, 719
gitlab-project-registry-tag-get command
    line option, 720
gitlab-project-registry-tag-list
    command line option, 720
gitlab-project-release-create command
    line option, 721
gitlab-project-release-delete command
    line option, 721
gitlab-project-release-get command line
    option, 721
gitlab-project-release-link-create
    command line option, 723
gitlab-project-release-link-delete
    command line option, 723
gitlab-project-release-link-get command
    line option, 724
gitlab-project-release-link-list
    command line option, 724
gitlab-project-release-link-update
    command line option, 725
gitlab-project-release-list command
    line option, 722
gitlab-project-release-update command
    line option, 722
gitlab-project-remote-mirror-create
    command line option, 725
gitlab-project-remote-mirror-list
    command line option, 726
gitlab-project-remote-mirror-update
    command line option, 726
gitlab-project-runner-create command
    line option, 726
gitlab-project-runner-delete command
    line option, 727
gitlab-project-runner-list command line
    option, 727
gitlab-project-service-available
    command line option, 728
gitlab-project-service-delete command
    line option, 728
gitlab-project-service-get command line
    option, 728
gitlab-project-service-list command
    line option, 728
gitlab-project-service-update command
    line option, 729
gitlab-project-snippet-award-emoji-create
    command line option, 732
gitlab-project-snippet-award-emoji-delete
    command line option, 732
gitlab-project-snippet-award-emoji-get
    command line option, 733
gitlab-project-snippet-award-emoji-list
    command line option, 733
gitlab-project-snippet-content command
    line option, 729
gitlab-project-snippet-create command
    line option, 730
gitlab-project-snippet-delete command
    line option, 730
gitlab-project-snippet-discussion-create
    command line option, 734
gitlab-project-snippet-discussion-get
    command line option, 734
gitlab-project-snippet-discussion-list
    command line option, 735
gitlab-project-snippet-discussion-note-create
    command line option, 735
gitlab-project-snippet-discussion-note-delete
    command line option, 736
gitlab-project-snippet-discussion-note-get
    command line option, 736
gitlab-project-snippet-discussion-note-update
```

```
    command line option, 737
gitlab-project-snippet-get command line
    option, 730
gitlab-project-snippet-list command
    line option, 731
gitlab-project-snippet-note-award-emoji-creategitlab-project-wiki-create command line
    command line option, 739
gitlab-project-snippet-note-award-emoji-deletegitlab-project-wiki-delete command line
    command line option, 740
gitlab-project-snippet-note-award-emoji-get    gitlab-project-wiki-get command line
    command line option, 740
gitlab-project-snippet-note-award-emoji-list   gitlab-project-wiki-list command line
    command line option, 741
gitlab-project-snippet-note-create            gitlab-project-wiki-update command line
    command line option, 737
gitlab-project-snippet-note-delete           gitlab-todo-list command line option, 760
    command line option, 738
gitlab-project-snippet-note-get command
    line option, 738
gitlab-project-snippet-note-list            --projects-limit
    command line option, 738
gitlab-project-snippet-note-update          gitlab-user-create command line option,
    command line option, 739
    764
gitlab-project-snippet-update command
    line option, 731
gitlab-project-snippet-user-agent-detail   gitlab-user-update command line option,
    command line option, 732
    768
--protected
gitlab-project-storage-get command line
    option, 741
gitlab-project-tag-create command line
    option, 742
gitlab-project-tag-delete command line
    option, 742
gitlab-project-tag-get command line
    option, 742
gitlab-project-tag-list command line
    option, 743
gitlab-project-trigger-create command
    line option, 743
gitlab-project-trigger-delete command
    line option, 744
gitlab-project-trigger-get command line
    option, 744
gitlab-project-trigger-list command
    line option, 744
gitlab-project-trigger-update command
    line option, 745
gitlab-project-user-list command line
    option, 745
gitlab-project-variable-create command
    line option, 746
gitlab-project-variable-delete command
    line option, 746
gitlab-project-variable-get command
    line option, 747
gitlab-project-variable-list command
    line option, 747
gitlab-project-variable-update command
    line option, 747
gitlab-project-wiki-create command line
    option, 748
gitlab-project-wiki-delete command line
    option, 748
gitlab-project-wiki-get command line
    option, 749
gitlab-project-wiki-list command line
    option, 749
gitlab-project-wiki-update command line
    option, 749
gitlab-todo-list command line option, 760
--protected
gitlab-group-variable-create command
    line option, 545
gitlab-group-variable-update command
    line option, 547
gitlab-project-variable-create command
    line option, 746
gitlab-project-variable-update command
    line option, 748
gitlab-variable-create command line
    option, 782
gitlab-variable-update command line
    option, 783
--protected-branch-ids
gitlab-project-approval-rule-create
    command line option, 581
--provider
gitlab-group-add-ldap-group-link
    command line option, 484
gitlab-group-delete-ldap-group-link
    command line option, 486
gitlab-ldap-group-list command line
    option, 553
gitlab-user-create command line option,
    764
gitlab-user-list command line option, 766
gitlab-user-update command line option,
    768
--public
gitlab-user-project-create command line
    option, 779
--public-builds
gitlab-project-create command line
```

```

        option, 564
gitlab-project-update command line
    option, 575
gitlab-user-project-create command line
    option, 779
--public-email
    gitlab-user-create command line option,
        765
    gitlab-user-update command line option,
        768
--push-access-level
    gitlab-project-protected-branch-create
        command line option, 711
--push-events
    gitlab-group-hook-create command line
        option, 520
    gitlab-group-hook-update command line
        option, 522
    gitlab-project-hook-create command line
        option, 621
    gitlab-project-hook-update command line
        option, 623
--query
    gitlab-group-invitation-list command
        line option, 524
    gitlab-project-invitation-list command
        line option, 627
--reassign-issue
    gitlab-group-notification-settings-update
        command line option, 539
    gitlab-notification-settings-update
        command line option, 558
    gitlab-project-notification-settings-update
        command line option, 696
--reassign-merge-request
    gitlab-group-notification-settings-update
        command line option, 539
    gitlab-notification-settings-update
        command line option, 558
    gitlab-project-notification-settings-update-refs
        command line option, 696
--recursive
    gitlab-project-repository-tree command
        line option, 569
--redirect-uri
    gitlab-application-create command line
        option, 461
--ref
    gitlab-project-branch-create command
        line option, 591
    gitlab-project-ci-lint-create command
        line option, 592
    gitlab-project-ci-lint-validate command
        line option, 593
gitlab-project-commit-status-create
    command line option, 604
gitlab-project-deployment-create
    command line option, 608
gitlab-project-file-blame command line
    option, 617
gitlab-project-file-get command line
    option, 618
gitlab-project-file-raw command line
    option, 618
gitlab-project-pipeline-create command
    line option, 701
gitlab-project-pipeline-list command
    line option, 702
gitlab-project-pipeline-schedule-create
    command line option, 705
gitlab-project-pipeline-schedule-update
    command line option, 707
gitlab-project-release-create command
    line option, 721
gitlab-project-repository-tree command
    line option, 569
gitlab-project-tag-create command line
    option, 742
gitlab-project-trigger-pipeline command
    line option, 571
--ref-name
    gitlab-project-artifact command line
        option, 561
    gitlab-project-artifact-delete command
        line option, 583
    gitlab-project-artifact-download
        command line option, 583
    gitlab-project-artifact-raw command
        line option, 583
    gitlab-project-artifacts command line
        option, 561
    gitlab-project-commit-list command line
        option, 597
gitlab-project-repository-merge-base
    command line option, 569
--reject-unsigned-commits
    gitlab-group-push-rules-create command
        line option, 542
    gitlab-group-push-rules-update command
        line option, 543
    gitlab-project-push-rules-create
        command line option, 716
    gitlab-project-push-rules-update
        command line option, 718
--released-at
    gitlab-project-release-update command
        line option, 722

```

```
--releases-events
    gitlab-group-hook-create command line
        option, 521
    gitlab-group-hook-update command line
        option, 523
--remove-source-branch
    gitlab-project-merge-request-create
        command line option, 664
    gitlab-project-merge-request-update
        command line option, 671
--remove-source-branch-after-merge
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 575
--render-html
    gitlab-project-merge-request-get
        command line option, 665
--reopen-issue
    gitlab-group-notification-settings-update
        command line option, 539
    gitlab-notification-settings-update
        command line option, 558
    gitlab-project-notification-settings-update
        command line option, 696
--reopen-merge-request
    gitlab-group-notification-settings-update
        command line option, 539
    gitlab-notification-settings-update
        command line option, 558
    gitlab-project-notification-settings-update
        command line option, 696
--repos-max-capacity
    gitlab-geo-node-update command line
        option, 482
--repository-access-level
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 575
--repository-checksum-failed
    gitlab-project-list command line option,
        567
    gitlab-user-project-list command line
        option, 780
--repository-id
    gitlab-project-registry-tag-delete
        command line option, 719
    gitlab-project-registry-tag-delete-in-bulk
        command line option, 719
    gitlab-project-registry-tag-get command
        line option, 720
    gitlab-project-registry-tag-list
        command line option, 720
--repository-storage
    gitlab-project-create command line
        option, 564
    gitlab-project-list command line option,
        567
    gitlab-project-update command line
        option, 575
--repository-storages
    gitlab-application-settings-update
        command line option, 466
--represented-as
    gitlab-project-deployment-approval
        command line option, 608
--request-access-enabled
    gitlab-group-create command line option,
        485
    gitlab-group-update command line option,
        489
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 575
--require-two-factor-authentication
    gitlab-group-create command line option,
        485
    gitlab-group-update command line option,
        489
--required-approval-count
    gitlab-project-protected-environment-create
        command line option, 712
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 575
--reset-approvals-on-push
    gitlab-project-approval-update command
        line option, 580
--reset-password
    gitlab-user-create command line option,
        764
--resolve-outdated-diff-discussions
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 575
--resolved
    gitlab-project-merge-request-discussion-update
        command line option, 680
--restrict-user-defined-variables
    gitlab-project-update command line
        option, 575
--restricted-visibility-levels
    gitlab-application-settings-update
```

```

    command line option, 465
--reviewer-id
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-deployment-merge-request-list
        command line option, 611
--reviewer-ids
    gitlab-project-merge-request-create
        command line option, 664
    gitlab-project-merge-request-update
        command line option, 671
--reviewer-username
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-deployment-merge-request-list
        command line option, 611
--rsa-key-restriction
    gitlab-application-settings-update
        command line option, 466
--run-untagged
    gitlab-runner-create command line
        option, 751
    gitlab-runner-update command line
        option, 752
--runner-id
    gitlab-project-runner-create command
        line option, 726
    gitlab-runner-job-list command line
        option, 754
--scope
    gitlab-group-merge-request-list command
        line option, 534
    gitlab-group-runner-list command line
        option, 544
    gitlab-group-search command line option,
        487
    gitlab-issue-list command line option,
        551
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-deployment-merge-request-list
        command line option, 611
    gitlab-project-issue-list command line
        option, 631
    gitlab-project-job-list command line
        option, 652
    gitlab-project-merge-request-list
        command line option, 666
    gitlab-project-merge-train-list command
        line option, 691
    gitlab-project-pipeline-bridge-list
        command line option, 703
    gitlab-project-pipeline-job-list
        command line option, 704
gitlab-project-pipeline-list command
    line option, 702
gitlab-project-runner-list command line
    option, 727
gitlab-project-search command line
    option, 570
gitlab-runner-all command line option,
    750
gitlab-runner-all-list command line
    option, 753
gitlab-runner-list command line option,
    752
--scopes
    gitlab-application-create command line
        option, 461
    gitlab-group-access-token-create
        command line option, 491
    gitlab-group-deploy-token-create
        command line option, 504
    gitlab-group-deploy-token-list command
        line option, 505
    gitlab-project-access-token-create
        command line option, 578
    gitlab-project-deploy-token-create
        command line option, 606
    gitlab-project-deploy-token-list
        command line option, 607
    gitlab-user-impersonation-token-create
        command line option, 774
    gitlab-user-personal-access-token-create
        command line option, 778
--search
    gitlab-group-billable-member-list
        command line option, 496
    gitlab-group-descendant-group-list
        command line option, 506
    gitlab-group-epic-list command line
        option, 508
    gitlab-group-issue-list command line
        option, 526
    gitlab-group-iteration-list command
        line option, 527
    gitlab-group-list command line option,
        487
    gitlab-group-merge-request-list command
        line option, 535
    gitlab-group-milestone-list command
        line option, 537
    gitlab-group-project-list command line
        option, 541
    gitlab-group-search command line option,
        487
    gitlab-group-subgroup-list command line
        option, 545

```

```
gitlab-issue-list command line option,  
    551  
gitlab-ldap-group-list command line  
    option, 553  
gitlab-merge-request-list command line  
    option, 555  
gitlab-namespace-list command line  
    option, 557  
gitlab-project-deployment-merge-request-list  
    command line option, 612  
gitlab-project-environment-list command  
    line option, 613  
gitlab-project-fork-list command line  
    option, 620  
gitlab-project-issue-list command line  
    option, 631  
gitlab-project-list command line option,  
    567  
gitlab-project-merge-request-list  
    command line option, 666  
gitlab-project-milestone-list command  
    line option, 693  
gitlab-project-search command line  
    option, 570  
gitlab-project-user-list command line  
    option, 745  
gitlab-shared-project-list command line  
    option, 755  
gitlab-starred-project-list command  
    line option, 759  
gitlab-user-list command line option, 766  
gitlab-user-project-list command line  
    option, 780  
--search-namespaces  
    gitlab-project-list command line option,  
        567  
--server-url  
    gitlab command line option, 460  
--service-desk-enabled  
    gitlab-project-update command line  
    option, 575  
--session-expire-delay  
    gitlab-application-settings-update  
    command line option, 465  
--sha  
    gitlab-project-deployment-create  
    command line option, 608  
    gitlab-project-merge-request-approve  
    command line option, 662  
    gitlab-project-pipeline-list command  
    line option, 702  
    gitlab-project-repository-archive  
    command line option, 568  
    gitlab-project-repository-blob command  
        line option, 568  
    gitlab-project-repository-raw-blob  
        command line option, 569  
--share-with-group-lock  
    gitlab-group-create command line option,  
        485  
    gitlab-group-update command line option,  
        489  
shared-runners-enabled  
    gitlab-project-create command line  
    option, 564  
    gitlab-project-update command line  
    option, 575  
--shared-runners-minutes-limit  
    gitlab-group-create command line option,  
        485  
    gitlab-group-update command line option,  
        489  
--shared-runners-setting  
    gitlab-group-update command line option,  
        489  
--should-remove-source-branch  
    gitlab-project-merge-request-merge  
    command line option, 667  
--show-default-award-emojis  
    gitlab-project-create command line  
    option, 564  
    gitlab-project-update command line  
    option, 575  
--sign-in-text  
    gitlab-application-settings-update  
    command line option, 465  
--signup-enabled  
    gitlab-application-settings-update  
    command line option, 465  
--simple  
    gitlab-group-project-list command line  
    option, 541  
    gitlab-project-fork-list command line  
    option, 620  
    gitlab-project-list command line option,  
        567  
    gitlab-shared-project-list command line  
    option, 755  
    gitlab-starred-project-list command  
    line option, 759  
    gitlab-user-project-list command line  
    option, 780  
--since  
    gitlab-project-commit-list command line  
    option, 597  
--skip-confirmation  
    gitlab-user-create command line option,  
        764
```

```
--skip-groups
    gitlab-group-descendant-group-list
        command line option, 506
    gitlab-group-list command line option,
        486
    gitlab-group-subgroup-list command line
        option, 545
--skip-reconfirmation
    gitlab-user-update command line option,
        768
--skip-users
    gitlab-project-user-list command line
        option, 745
--skype
    gitlab-user-create command line option,
        764
    gitlab-user-update command line option,
        768
--slug
    gitlab-group-wiki-delete command line
        option, 548
    gitlab-group-wiki-get command line
        option, 548
    gitlab-group-wiki-update command line
        option, 549
    gitlab-project-integration-available
        command line option, 624
    gitlab-project-integration-delete
        command line option, 624
    gitlab-project-integration-get command
        line option, 625
    gitlab-project-integration-update
        command line option, 625
    gitlab-project-service-available
        command line option, 728
    gitlab-project-service-delete command
        line option, 728
    gitlab-project-service-get command line
        option, 728
    gitlab-project-service-update command
        line option, 729
    gitlab-project-wiki-delete command line
        option, 748
    gitlab-project-wiki-get command line
        option, 749
    gitlab-project-wiki-update command line
        option, 749
--snippet-id
    gitlab-project-snippet-award-emoji-create
        command line option, 732
    gitlab-project-snippet-award-emoji-delete
        command line option, 733
    gitlab-project-snippet-award-emoji-get
        command line option, 733
gitlab-project-snippet-award-emoji-list
    command line option, 733
gitlab-project-snippet-discussion-create
    command line option, 734
gitlab-project-snippet-discussion-get
    command line option, 734
gitlab-project-snippet-discussion-list
    command line option, 735
gitlab-project-snippet-discussion-note-create
    command line option, 735
gitlab-project-snippet-discussion-note-delete
    command line option, 736
gitlab-project-snippet-discussion-note-get
    command line option, 736
gitlab-project-snippet-discussion-note-update
    command line option, 737
gitlab-project-snippet-note-award-emoji-create
    command line option, 739
gitlab-project-snippet-note-award-emoji-delete
    command line option, 740
gitlab-project-snippet-note-award-emoji-get
    command line option, 740
gitlab-project-snippet-note-award-emoji-list
    command line option, 741
gitlab-project-snippet-note-create
    command line option, 737
gitlab-project-snippet-note-delete
    command line option, 738
gitlab-project-snippet-note-get command
    line option, 738
gitlab-project-snippet-note-list
    command line option, 738
gitlab-project-snippet-note-update
    command line option, 739
--snippets-access-level
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 575
--snippets-enabled
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 575
    gitlab-user-project-create command line
        option, 779
--sort
    gitlab-event-list command line option,
        478
    gitlab-group-billable-member-list
        command line option, 496
    gitlab-group-descendant-group-list
        command line option, 506
    gitlab-group-epic-list command line
```

```
    option, 508
gitlab-group-issue-list command line
    option, 526
gitlab-group-list command line option,
    487
gitlab-group-merge-request-list command
    line option, 534
gitlab-group-package-list command line
    option, 539
gitlab-group-project-list command line
    option, 540
gitlab-group-subgroup-list command line
    option, 545
gitlab-issue-list command line option,
    551
gitlab-merge-request-list command line
    option, 555
gitlab-project-deployment-list command
    line option, 609
gitlab-project-deployment-merge-request-liststarred
    command line option, 611
gitlab-project-event-list command line
    option, 615
gitlab-project-fork-list command line
    option, 620
gitlab-project-issue-list command line
    option, 631
gitlab-project-list command line option,
    567
gitlab-project-merge-request-list
    command line option, 666
gitlab-project-package-list command
    line option, 697
gitlab-project-pipeline-list command
    line option, 702
gitlab-project-release-list command
    line option, 722
gitlab-shared-project-list command line
    option, 755
gitlab-starred-project-list command
    line option, 759
gitlab-user-event-list command line
    option, 772
gitlab-user-project-list command line
    option, 780
--source-branch
    gitlab-group-merge-request-list command
        line option, 535
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-deployment-merge-request-liststate
        command line option, 612
    gitlab-project-merge-request-create
        command line option, 664
gitlab-project-merge-request-list
    command line option, 666
--source-id
    gitlab-user-membership-get command line
        option, 777
--squash
    gitlab-project-merge-request-create
        command line option, 664
    gitlab-project-merge-request-update
        command line option, 671
--squash-option
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 576
    gitlab-user-project-create command line
        option, 779
--ssl-verify
    gitlab command line option, 460
gitlab-project-list
    gitlab-group-project-list command line
        option, 541
    gitlab-project-fork-list command line
        option, 620
    gitlab-project-list command line option,
        567
    gitlab-shared-project-list command line
        option, 755
    gitlab-starred-project-list command
        line option, 759
    gitlab-user-project-list command line
        option, 780
--start-date
    gitlab-group-epic-create command line
        option, 507
    gitlab-group-epic-update command line
        option, 509
    gitlab-group-milestone-create command
        line option, 535
    gitlab-group-milestone-update command
        line option, 538
    gitlab-project-milestone-create command
        line option, 692
    gitlab-project-milestone-update command
        line option, 694
--starts-at
    gitlab-broadcast-message-create command
        line option, 468
    gitlab-broadcast-message-update command
        line option, 469
gitlab-group-issue-list
    gitlab-group-iteration-list command
```

```

    line option, 527
gitlab-group-merge-request-list command
    line option, 534
gitlab-group-milestone-list command
    line option, 537
gitlab-issue-list command line option,
    551
gitlab-merge-request-list command line
    option, 555
gitlab-project-commit-status-create
    command line option, 604
gitlab-project-deployment-merge-request-list
    command line option, 611
gitlab-project-issue-list command line
    option, 630
gitlab-project-merge-request-list
    command line option, 666
gitlab-project-milestone-list command
    line option, 693
gitlab-todo-list command line option, 760
gitlab-user-impersonation-token-list
    command line option, 775
--state-event
    gitlab-group-milestone-update command
        line option, 538
    gitlab-project-issue-update command
        line option, 635
    gitlab-project-merge-request-update
        command line option, 671
    gitlab-project-milestone-create command
        line option, 692
    gitlab-project-milestone-update command
        line option, 694
--states
    gitlab-project-environment-list command
        line option, 614
--statistics
    gitlab-group-descendant-group-list
        command line option, 506
    gitlab-group-list command line option,
        487
    gitlab-group-subgroup-list command line
        option, 545
    gitlab-project-fork-list command line
        option, 620
    gitlab-project-list command line option,
        567
    gitlab-starred-project-list command
        line option, 759
    gitlab-user-project-list command line
        option, 780
--status
    gitlab-project-deployment-approval
        command line option, 608
gitlab-project-deployment-create
    command line option, 608
gitlab-project-deployment-list command
    line option, 609
gitlab-project-pipeline-list command
    line option, 702
gitlab-runner-all-list command line
    option, 753
gitlab-runner-job-list command line
    option, 754
gitlab-runner-list command line option,
    752
gitlab-user-list command line option, 766
--subgroup-creation-level
    gitlab-group-create command line option,
        485
    gitlab-group-update command line option,
        489
--subgroup-events
    gitlab-group-hook-create command line
        option, 521
    gitlab-group-hook-update command line
        option, 523
--submodule
    gitlab-project-update-submodule command
        line option, 576
--sudo
    gitlab-application-appearance-get
        command line option, 462
    gitlab-application-appearance-update
        command line option, 462
    gitlab-application-create command line
        option, 461
    gitlab-application-delete command line
        option, 461
    gitlab-application-list command line
        option, 461
    gitlab-application-settings-get command
        line option, 463
    gitlab-application-settings-update
        command line option, 465
    gitlab-audit-event-get command line
        option, 467
    gitlab-audit-event-list command line
        option, 467
    gitlab-broadcast-message-create command
        line option, 468
    gitlab-broadcast-message-delete command
        line option, 468
    gitlab-broadcast-message-get command
        line option, 469
    gitlab-broadcast-message-list command
        line option, 469
    gitlab-broadcast-message-update command

```

line option, 469
gitlab-ci-lint-create command line option, 470
gitlab-current-user-email-create command line option, 471
gitlab-current-user-email-delete command line option, 471
gitlab-current-user-email-get command line option, 472
gitlab-current-user-email-list command line option, 472
gitlab-current-user-get command line option, 471
gitlab-current-user-gpg-key-create command line option, 472
gitlab-current-user-gpg-key-delete command line option, 473
gitlab-current-user-gpg-key-get command line option, 473
gitlab-current-user-gpg-key-list command line option, 473
gitlab-current-user-key-create command line option, 474
gitlab-current-user-key-delete command line option, 474
gitlab-current-user-key-get command line option, 474
gitlab-current-user-key-list command line option, 474
gitlab-current-user-status-get command line option, 475
gitlab-current-user-status-update command line option, 475
gitlab-deploy-key-list command line option, 475
gitlab-deploy-token-list command line option, 476
gitlab-dockerfile-get command line option, 477
gitlab-dockerfile-list command line option, 477
gitlab-event-list command line option, 477
gitlab-feature-delete command line option, 478
gitlab-feature-list command line option, 478
gitlab-generic-package-download command line option, 479
gitlab-generic-package-upload command line option, 479
gitlab-geo-node-delete command line option, 480
gitlab-geo-node-get command line option, 480
gitlab-geo-node-list command line option, 481
gitlab-geo-node-update command line option, 481
gitlab-gitignore-get command line option, 482
gitlab-gitignore-list command line option, 482
gitlab-gitlabciyaml-get command line option, 483
gitlab-gitlabciyaml-list command line option, 483
gitlab-group-access-request-approve command line option, 490
gitlab-group-access-request-create command line option, 490
gitlab-group-access-request-delete command line option, 490
gitlab-group-access-request-list command line option, 491
gitlab-group-access-token-create command line option, 491
gitlab-group-access-token-delete command line option, 492
gitlab-group-access-token-list command line option, 492
gitlab-group-audit-event-get command line option, 493
gitlab-group-audit-event-list command line option, 493
gitlab-group-badge-create command line option, 494
gitlab-group-badge-delete command line option, 494
gitlab-group-badge-get command line option, 494
gitlab-group-badge-list command line option, 494
gitlab-group-badge-render command line option, 495
gitlab-group-badge-update command line option, 495
gitlab-group-billable-member-delete command line option, 496
gitlab-group-billable-member-list command line option, 496
gitlab-group-billable-member-membership-list command line option, 497
gitlab-group-board-create command line option, 497
gitlab-group-board-delete command line option, 498
gitlab-group-board-get command line

```
    option, 498
gitlab-group-board-list command line
    option, 498
gitlab-group-board-list-create command
    line option, 499
gitlab-group-board-list-delete command
    line option, 499
gitlab-group-board-list-get command
    line option, 500
gitlab-group-board-list-list command
    line option, 500
gitlab-group-board-list-update command
    line option, 500
gitlab-group-board-update command line
    option, 499
gitlab-group-cluster-create command
    line option, 501
gitlab-group-cluster-delete command
    line option, 501
gitlab-group-cluster-get command line
    option, 502
gitlab-group-cluster-list command line
    option, 502
gitlab-group-cluster-update command
    line option, 502
gitlab-group-create command line option,
    484
gitlab-group-custom-attribute-delete
    command line option, 503
gitlab-group-custom-attribute-get
    command line option, 503
gitlab-group-custom-attribute-list
    command line option, 504
gitlab-group-delete command line option,
    485
gitlab-group-deploy-token-create
    command line option, 504
gitlab-group-deploy-token-delete
    command line option, 505
gitlab-group-deploy-token-get command
    line option, 505
gitlab-group-deploy-token-list command
    line option, 505
gitlab-group-descendant-group-list
    command line option, 506
gitlab-group-epic-award-emoji-create
    command line option, 509
gitlab-group-epic-award-emoji-delete
    command line option, 510
gitlab-group-epic-award-emoji-get
    command line option, 510
gitlab-group-epic-award-emoji-list
    command line option, 510
gitlab-group-epic-create command line
    option, 507
gitlab-group-epic-delete command line
    option, 507
gitlab-group-epic-discussion-note-create
    command line option, 511
gitlab-group-epic-discussion-note-delete
    command line option, 511
gitlab-group-epic-discussion-note-get
    command line option, 512
gitlab-group-epic-discussion-note-update
    command line option, 512
gitlab-group-epic-get command line
    option, 508
gitlab-group-epic-issue-create command
    line option, 513
gitlab-group-epic-issue-delete command
    line option, 513
gitlab-group-epic-issue-list command
    line option, 513
gitlab-group-epic-issue-update command
    line option, 514
gitlab-group-epic-list command line
    option, 508
gitlab-group-epic-note-award-emoji-create
    command line option, 516
gitlab-group-epic-note-award-emoji-delete
    command line option, 517
gitlab-group-epic-note-award-emoji-get
    command line option, 517
gitlab-group-epic-note-award-emoji-list
    command line option, 517
gitlab-group-epic-note-create command
    line option, 514
gitlab-group-epic-note-delete command
    line option, 515
gitlab-group-epic-note-get command line
    option, 515
gitlab-group-epic-note-list command
    line option, 515
gitlab-group-epic-note-update command
    line option, 516
gitlab-group-epic-resource-label-event-get
    command line option, 518
gitlab-group-epic-resource-label-event-list
    command line option, 518
gitlab-group-epic-update command line
    option, 509
gitlab-group-export-create command line
    option, 519
gitlab-group-export-download command
    line option, 519
gitlab-group-export-get command line
    option, 519
gitlab-group-get command line option, 486
```

gitlab-group-hook-create command line option, 520
gitlab-group-hook-delete command line option, 521
gitlab-group-hook-get command line option, 521
gitlab-group-hook-list command line option, 521
gitlab-group-hook-update command line option, 522
gitlab-group-import-get command line option, 523
gitlab-group-invitation-create command line option, 523
gitlab-group-invitation-delete command line option, 524
gitlab-group-invitation-get command line option, 524
gitlab-group-invitation-list command line option, 524
gitlab-group-invitation-update command line option, 525
gitlab-group-issue-list command line option, 526
gitlab-group-issues-statistics-get command line option, 527
gitlab-group-iteration-list command line option, 527
gitlab-group-label-create command line option, 528
gitlab-group-label-delete command line option, 528
gitlab-group-label-get command line option, 529
gitlab-group-label-list command line option, 529
gitlab-group-label-subscribe command line option, 529
gitlab-group-label-unsubscribe command line option, 530
gitlab-group-label-update command line option, 530
gitlab-group-list command line option, 486
gitlab-group-member-all-get command line option, 533
gitlab-group-member-all-list command line option, 533
gitlab-group-member-create command line option, 531
gitlab-group-member-delete command line option, 531
gitlab-group-member-get command line option, 531
gitlab-group-member-list command line option, 532
gitlab-group-member-update command line option, 532
gitlab-group-merge-request-list command line option, 534
gitlab-group-milestone-create command line option, 535
gitlab-group-milestone-delete command line option, 536
gitlab-group-milestone-get command line option, 536
gitlab-group-milestone-issues command line option, 536
gitlab-group-milestone-list command line option, 536
gitlab-group-milestone-merge-requests command line option, 537
gitlab-group-milestone-update command line option, 537
gitlab-group-notification-settings-get command line option, 538
gitlab-group-notification-settings-update command line option, 538
gitlab-group-package-list command line option, 539
gitlab-group-project-list command line option, 540
gitlab-group-push-rules-create command line option, 542
gitlab-group-push-rules-delete command line option, 542
gitlab-group-push-rules-get command line option, 542
gitlab-group-push-rules-update command line option, 543
gitlab-group-runner-list command line option, 544
gitlab-group-subgroup-list command line option, 544
gitlab-group-update command line option, 489
gitlab-group-variable-create command line option, 545
gitlab-group-variable-delete command line option, 546
gitlab-group-variable-get command line option, 546
gitlab-group-variable-list command line option, 546
gitlab-group-variable-update command line option, 547
gitlab-group-wiki-create command line option, 547

gitlab-group-wiki-delete command line option, 548
gitlab-group-wiki-get command line option, 548
gitlab-group-wiki-list command line option, 548
gitlab-group-wiki-update command line option, 549
gitlab-hook-create command line option, 549
gitlab-hook-delete command line option, 549
gitlab-hook-get command line option, 550
gitlab-hook-list command line option, 550
gitlab-issue-get command line option, 550
gitlab-issue-list command line option, 551
gitlab-issues-statistics-get command line option, 552
gitlab-key-get command line option, 552
gitlab-ldap-group-list command line option, 553
gitlab-license-get command line option, 553
gitlab-license-list command line option, 554
gitlab-merge-request-list command line option, 555
gitlab-namespace-get command line option, 556
gitlab-namespace-list command line option, 557
gitlab-notification-settings-get command line option, 557
gitlab-notification-settings-update command line option, 558
gitlab-pages-domain-list command line option, 558
gitlab-personal-access-token-delete command line option, 559
gitlab-personal-access-token-list command line option, 559
gitlab-project-access-request-approve command line option, 577
gitlab-project-access-request-create command line option, 577
gitlab-project-access-request-delete command line option, 577
gitlab-project-access-request-list command line option, 578
gitlab-project-access-token-create command line option, 578
gitlab-project-access-token-delete command line option, 579
gitlab-project-access-token-list command line option, 579
gitlab-project-access-token-list-create command line option, 580
gitlab-project-access-token-list-delete command line option, 580
gitlab-project-access-token-list-get command line option, 580
gitlab-project-access-token-list-list command line option, 580
gitlab-project-access-token-list-option command line option, 580
gitlab-project-access-token-list-set command line option, 580
gitlab-project-access-token-list-unset command line option, 580
gitlab-project-access-token-list-update command line option, 580
gitlab-project-access-token-list-validate command line option, 580
gitlab-project-access-token-validate command line option, 580
gitlab-project-additional-statistics-get command line option, 580
gitlab-project-approval-get command line option, 580
gitlab-project-approval-rule-create command line option, 581
gitlab-project-approval-rule-delete command line option, 581
gitlab-project-approval-rule-list command line option, 582
gitlab-project-approval-rule-update command line option, 582
gitlab-project-approval-update command line option, 580
gitlab-project-artifact-delete command line option, 583
gitlab-project-artifact-download command line option, 583
gitlab-project-artifact-raw command line option, 583
gitlab-project-audit-event-get command line option, 584
gitlab-project-audit-event-list command line option, 584
gitlab-project-badge-create command line option, 585
gitlab-project-badge-delete command line option, 585
gitlab-project-badge-get command line option, 585
gitlab-project-badge-list command line option, 586
gitlab-project-badge-render command line option, 586
gitlab-project-badge-update command line option, 586
gitlab-project-board-create command line option, 587
gitlab-project-board-delete command line option, 587
gitlab-project-board-get command line option, 587
gitlab-project-board-list command line option, 588
gitlab-project-board-list-create command line option, 589
gitlab-project-board-list-delete command line option, 589
gitlab-project-board-list-get command line option, 589
gitlab-project-board-list-list command line option, 590

gitlab-project-board-list-update command line option, 590
gitlab-project-board-update command line option, 588
gitlab-project-branch-create command line option, 591
gitlab-project-branch-delete command line option, 591
gitlab-project-branch-get command line option, 591
gitlab-project-branch-list command line option, 592
gitlab-project-ci-lint-create command line option, 592
gitlab-project-ci-lint-get command line option, 593
gitlab-project-ci-lint-validate command line option, 593
gitlab-project-cluster-create command line option, 594
gitlab-project-cluster-delete command line option, 594
gitlab-project-cluster-get command line option, 594
gitlab-project-cluster-list command line option, 595
gitlab-project-cluster-update command line option, 595
gitlab-project-commit-cherry-pick command line option, 596
gitlab-project-commit-comment-create command line option, 599
gitlab-project-commit-comment-list command line option, 600
gitlab-project-commit-create command line option, 596
gitlab-project-commit-diff command line option, 597
gitlab-project-commit-discussion-create command line option, 600
gitlab-project-commit-discussion-get command line option, 601
gitlab-project-commit-discussion-list command line option, 601
gitlab-project-commit-discussion-note-create command line option, 602
gitlab-project-commit-discussion-note-delete command line option, 602
gitlab-project-commit-discussion-note-get command line option, 603
gitlab-project-commit-discussion-note-update command line option, 603
gitlab-project-commit-get command line option, 597
gitlab-project-commit-list command line option, 597
gitlab-project-commit-merge-requests command line option, 598
gitlab-project-commit-refs command line option, 598
gitlab-project-commit-revert command line option, 599
gitlab-project-commit-signature command line option, 599
gitlab-project-commit-status-create command line option, 604
gitlab-project-commit-status-list command line option, 604
gitlab-project-create command line option, 563
gitlab-project-custom-attribute-delete command line option, 605
gitlab-project-custom-attribute-get command line option, 605
gitlab-project-custom-attribute-list command line option, 606
gitlab-project-delete command line option, 565
gitlab-project-deploy-token-create command line option, 606
gitlab-project-deploy-token-delete command line option, 607
gitlab-project-deploy-token-get command line option, 607
gitlab-project-deploy-token-list command line option, 607
gitlab-project-deployment-approval command line option, 608
gitlab-project-deployment-create command line option, 608
gitlab-project-deployment-get command line option, 609
gitlab-project-deployment-list command line option, 609
gitlab-project-deployment-merge-request-list command line option, 611
gitlab-project-deployment-update command line option, 610
gitlab-project-environment-create command line option, 612
gitlab-project-environment-delete command line option, 613
gitlab-project-environment-get command line option, 613
gitlab-project-environment-list command line option, 613
gitlab-project-environment-stop command line option, 614

```
gitlab-project-environment-update
    command line option, 614
gitlab-project-event-list command line
    option, 615
gitlab-project-export-create command
    line option, 616
gitlab-project-export-download command
    line option, 616
gitlab-project-export-get command line
    option, 616
gitlab-project-file-blame command line
    option, 617
gitlab-project-file-create command line
    option, 617
gitlab-project-file-delete command line
    option, 618
gitlab-project-file-get command line
    option, 618
gitlab-project-file-raw command line
    option, 618
gitlab-project-file-update command line
    option, 619
gitlab-project-fork-create command line
    option, 619
gitlab-project-fork-list command line
    option, 620
gitlab-project-get command line option,
    566
gitlab-project-hook-create command line
    option, 621
gitlab-project-hook-delete command line
    option, 622
gitlab-project-hook-get command line
    option, 622
gitlab-project-hook-list command line
    option, 622
gitlab-project-hook-update command line
    option, 623
gitlab-project-import-get command line
    option, 624
gitlab-project-integration-available
    command line option, 624
gitlab-project-integration-delete
    command line option, 624
gitlab-project-integration-get command
    line option, 625
gitlab-project-integration-list command
    line option, 625
gitlab-project-integration-update
    command line option, 625
gitlab-project-invitation-create
    command line option, 626
gitlab-project-invitation-delete
    command line option, 626
gitlab-project-invitation-get command
    line option, 627
gitlab-project-invitation-list command
    line option, 627
gitlab-project-invitation-update
    command line option, 627
gitlab-project-issue-add-spent-time
    command line option, 628
gitlab-project-issue-award-emoji-create
    command line option, 636
gitlab-project-issue-award-emoji-delete
    command line option, 636
gitlab-project-issue-award-emoji-get
    command line option, 637
gitlab-project-issue-award-emoji-list
    command line option, 637
gitlab-project-issue-closed-by command
    line option, 629
gitlab-project-issue-create command
    line option, 629
gitlab-project-issue-delete command
    line option, 630
gitlab-project-issue-discussion-create
    command line option, 638
gitlab-project-issue-discussion-get
    command line option, 638
gitlab-project-issue-discussion-list
    command line option, 638
gitlab-project-issue-discussion-note-create
    command line option, 639
gitlab-project-issue-discussion-note-delete
    command line option, 640
gitlab-project-issue-discussion-note-get
    command line option, 640
gitlab-project-issue-discussion-note-update
    command line option, 640
gitlab-project-issue-get command line
    option, 630
gitlab-project-issue-link-create
    command line option, 641
gitlab-project-issue-link-delete
    command line option, 641
gitlab-project-issue-link-list command
    line option, 642
gitlab-project-issue-list command line
    option, 630
gitlab-project-issue-move command line
    option, 631
gitlab-project-issue-note-award-emoji-create
    command line option, 644
gitlab-project-issue-note-award-emoji-delete
    command line option, 645
gitlab-project-issue-note-award-emoji-get
    command line option, 645
```

gitlab-project-issue-note-award-emoji-list
 command line option, 645
gitlab-project-issue-note-create
 command line option, 642
gitlab-project-issue-note-delete
 command line option, 643
gitlab-project-issue-note-get command
 line option, 643
gitlab-project-issue-note-list command
 line option, 643
gitlab-project-issue-note-update
 command line option, 644
gitlab-project-issue-participants
 command line option, 632
gitlab-project-issue-related-merge-requests
 command line option, 632
gitlab-project-issue-reorder command
 line option, 632
gitlab-project-issue-reset-spent-time
 command line option, 633
gitlab-project-issue-reset-time-estimate
 command line option, 633
gitlab-project-issue-resource-label-event-get gitlab-project-key-enable command line
 option, 646
gitlab-project-issue-resource-label-event-listgitlab-project-key-get command line
 option, 647
gitlab-project-issue-resource-milestone-eventgitlab-project-key-list command line
 option, 647
gitlab-project-issue-resource-milestone-eventgitlab-project-key-update command line
 option, 648
gitlab-project-issue-resource-state-event-get gitlab-project-label-create command
 line option, 648
gitlab-project-issue-resource-state-event-listgitlab-project-label-delete command
 line option, 649
gitlab-project-issue-subscribe command
 line option, 633
gitlab-project-issue-time-estimate
 command line option, 633
gitlab-project-issue-time-stats command
 line option, 634
gitlab-project-issue-todo command line
 option, 634
gitlab-project-issue-unsubscribe
 command line option, 634
gitlab-project-issue-update command
 line option, 635
gitlab-project-issue-user-agent-detail
 command line option, 635
gitlab-project-issues-statistics-get
 command line option, 649
gitlab-project-job-artifact command
 line option, 650
gitlab-project-job-artifacts command
 line option, 650
gitlab-project-job-cancel command line
 option, 651
gitlab-project-job-delete-artifacts
 command line option, 651
gitlab-project-job-erase command line
 option, 651
gitlab-project-job-get command line
 option, 651
gitlab-project-job-keep-artifacts
 command line option, 652
gitlab-project-job-list command line
 option, 652
gitlab-project-job-play command line
 option, 652
gitlab-project-job-retry command line
 option, 653
gitlab-project-job-trace command line
 option, 653
gitlab-project-key-create command line
 option, 653
gitlab-project-key-delete command line
 option, 654
gitlab-project-key-enable command line
 option, 654
gitlab-project-key-get command line
 option, 654
gitlab-project-key-list command line
 option, 655
gitlab-project-key-update command line
 option, 655
gitlab-project-label-create command
 line option, 656
gitlab-project-label-delete command
 line option, 656
gitlab-project-label-get command line
 option, 656
gitlab-project-label-list command line
 option, 657
gitlab-project-label-subscribe command
 line option, 657
gitlab-project-label-unsubscribe
 command line option, 657
gitlab-project-label-update command
 line option, 658
gitlab-project-list command line option,
 567
gitlab-project-member-all-get command
 line option, 660
gitlab-project-member-all-list command
 line option, 660
gitlab-project-member-create command
 line option, 658
gitlab-project-member-delete command
 line option, 659

```

gitlab-project-member-get command line
    option, 659
gitlab-project-member-list command line
    option, 659
gitlab-project-member-update command
    line option, 660
gitlab-project-merge-request-add-spent-time
    command line option, 662
gitlab-project-merge-request-approval-get
    command line option, 672
gitlab-project-merge-request-approval-rule-create
    command line option, 673
gitlab-project-merge-request-approval-rule-delete
    command line option, 673
gitlab-project-merge-request-approval-rule-get
    command line option, 674
gitlab-project-merge-request-approval-rule-list
    command line option, 674
gitlab-project-merge-request-approval-rule-list
    command line option, 674
gitlab-project-merge-request-approval-rule-update
    command line option, 675
gitlab-project-merge-request-approval-state-get
    command line option, 676
gitlab-project-merge-request-approval-update
    command line option, 672
gitlab-project-merge-request-approve
    command line option, 662
gitlab-project-merge-request-award-emoji-create
    command line option, 676
gitlab-project-merge-request-award-emoji-delete
    command line option, 677
gitlab-project-merge-request-award-emoji-get
    command line option, 677
gitlab-project-merge-request-award-emoji-list
    command line option, 676
gitlab-project-merge-request-cancel-merge-whengitlab-project-merge-request-note-create
    command line option, 662
gitlab-project-merge-request-changes
    command line option, 663
gitlab-project-merge-request-closes-issues
    command line option, 663
gitlab-project-merge-request-commits
    command line option, 663
gitlab-project-merge-request-create
    command line option, 664
gitlab-project-merge-request-delete
    command line option, 665
gitlab-project-merge-request-diff-get
    command line option, 678
gitlab-project-merge-request-diff-list
    command line option, 678
gitlab-project-merge-request-discussion-create
    command line option, 679
gitlab-project-merge-request-discussion-get
    command line option, 679
gitlab-project-merge-request-discussion-list
    command line option, 680
gitlab-project-merge-request-discussion-note-create
    command line option, 681
gitlab-project-merge-request-discussion-note-delete
    command line option, 681
gitlab-project-merge-request-discussion-note-get
    command line option, 682
gitlab-project-merge-request-discussion-note-update
    command line option, 682
gitlab-project-merge-request-discussion-update
    command line option, 680
gitlab-project-merge-request-get
    command line option, 665
gitlab-project-merge-request-list
    command line option, 666
gitlab-project-merge-request-merge
    command line option, 667
gitlab-project-merge-request-merge-ref
    command line option, 667
gitlab-project-merge-request-note-award-emoji-create
    command line option, 685
gitlab-project-merge-request-note-award-emoji-delete
    command line option, 685
gitlab-project-merge-request-note-award-emoji-get
    command line option, 686
gitlab-project-merge-request-note-award-emoji-list
    command line option, 686
gitlab-project-merge-request-note-create
    command line option, 683
gitlab-project-merge-request-note-delete
    command line option, 683
gitlab-project-merge-request-note-list
    command line option, 684
gitlab-project-merge-request-note-update
    command line option, 684
gitlab-project-merge-request-participants
    command line option, 668
gitlab-project-merge-request-pipeline-create
    command line option, 687
gitlab-project-merge-request-pipeline-list
    command line option, 687
gitlab-project-merge-request-rebase
    command line option, 668
gitlab-project-merge-request-reset-approvals
    command line option, 668
gitlab-project-merge-request-reset-spent-time
    command line option, 669
gitlab-project-merge-request-reset-time-estimate
    command line option, 669
gitlab-project-merge-request-resource-label-event-get
    command line option, 688

```

```
gitlab-project-merge-request-resource-label-event-list-project-package-get command line
    command line option, 688
gitlab-project-merge-request-resource-milestone-event-list-project-package-list command
    command line option, 689
gitlab-project-merge-request-resource-milestone-event-list-project-pages-domain-create
    command line option, 689
gitlab-project-merge-request-resource-state-event-list-project-pages-domain-delete
    command line option, 690
gitlab-project-merge-request-resource-state-event-list-project-pages-domain-get command
    command line option, 690
gitlab-project-merge-request-subscribe
    command line option, 669
gitlab-project-merge-request-time-estimate
    command line option, 669
gitlab-project-merge-request-time-stats
    command line option, 670
gitlab-project-merge-request-todo
    command line option, 670
gitlab-project-merge-request-unapprove
    command line option, 670
gitlab-project-merge-request-unsubscribe
    command line option, 670
gitlab-project-merge-request-update
    command line option, 671
gitlab-project-merge-train-list command
    line option, 691
gitlab-project-milestone-create command
    line option, 692
gitlab-project-milestone-delete command
    line option, 692
gitlab-project-milestone-get command
    line option, 692
gitlab-project-milestone-issues command
    line option, 693
gitlab-project-milestone-list command
    line option, 693
gitlab-project-milestone-merge-requests
    command line option, 693
gitlab-project-milestone-update command
    line option, 694
gitlab-project-note-get command line
    option, 694
gitlab-project-note-list command line
    option, 695
gitlab-project-notification-settings-get
    command line option, 695
gitlab-project-notification-settings-update
    command line option, 696
gitlab-project-package-delete command
    line option, 697
gitlab-project-package-file-delete
    command line option, 698
gitlab-project-package-file-list
    command line option, 698
gitlab-project-project-package-get command line
    option, 697
gitlab-project-project-package-list command
    line option, 697
gitlab-project-project-pages-domain-create
    command line option, 699
gitlab-project-project-pages-domain-delete
    command line option, 699
gitlab-project-project-pages-domain-get command
    line option, 700
gitlab-project-project-pages-domain-list
    command line option, 700
gitlab-project-project-pages-domain-update
    command line option, 700
gitlab-project-pipeline-bridge-list
    command line option, 703
gitlab-project-pipeline-cancel command
    line option, 701
gitlab-project-pipeline-create command
    line option, 701
gitlab-project-pipeline-delete command
    line option, 701
gitlab-project-pipeline-get command
    line option, 702
gitlab-project-pipeline-job-list
    command line option, 704
gitlab-project-pipeline-list command
    line option, 702
gitlab-project-pipeline-retry command
    line option, 703
gitlab-project-pipeline-schedule-create
    command line option, 705
gitlab-project-pipeline-schedule-delete
    command line option, 705
gitlab-project-pipeline-schedule-get
    command line option, 705
gitlab-project-pipeline-schedule-list
    command line option, 706
gitlab-project-pipeline-schedule-play
    command line option, 706
gitlab-project-pipeline-schedule-take-ownership
    command line option, 706
gitlab-project-pipeline-schedule-update
    command line option, 707
gitlab-project-pipeline-schedule-variable-create
    command line option, 707
gitlab-project-pipeline-schedule-variable-delete
    command line option, 708
gitlab-project-pipeline-schedule-variable-update
    command line option, 708
gitlab-project-pipeline-test-report-get
    command line option, 709
gitlab-project-pipeline-test-report-summary-get
    command line option, 709
```

gitlab-project-pipeline-variable-list
 command line option, 710

gitlab-project-protected-branch-create
 command line option, 711

gitlab-project-protected-branch-delete
 command line option, 711

gitlab-project-protected-branch-get
 command line option, 711

gitlab-project-protected-branch-list
 command line option, 712

gitlab-project-protected-environment-create
 command line option, 712

gitlab-project-protected-environment-delete
 command line option, 713

gitlab-project-protected-environment-get
 command line option, 713

gitlab-project-protected-environment-list
 command line option, 713

gitlab-project-protected-tag-create
 command line option, 714

gitlab-project-protected-tag-delete
 command line option, 714

gitlab-project-protected-tag-get
 command line option, 715

gitlab-project-protected-tag-list
 command line option, 715

gitlab-project-push-rules-create
 command line option, 716

gitlab-project-push-rules-delete
 command line option, 716

gitlab-project-push-rules-get command
 line option, 717

gitlab-project-push-rules-update
 command line option, 717

gitlab-project-registry-repository-delete
 command line option, 718

gitlab-project-registry-repository-list
 command line option, 718

gitlab-project-registry-tag-delete
 command line option, 719

gitlab-project-registry-tag-delete-in-bulk
 command line option, 719

gitlab-project-registry-tag-get command
 line option, 720

gitlab-project-registry-tag-list
 command line option, 720

gitlab-project-release-create command
 line option, 721

gitlab-project-release-delete command
 line option, 721

gitlab-project-release-get command line
 option, 721

gitlab-project-release-link-create
 command line option, 723

gitlab-project-release-link-delete
 command line option, 723

gitlab-project-release-link-get command
 line option, 724

gitlab-project-release-link-list
 command line option, 724

gitlab-project-release-link-update
 command line option, 724

gitlab-project-release-list command
 line option, 722

gitlab-project-release-update command
 line option, 722

gitlab-project-remote-mirror-create
 command line option, 725

gitlab-project-remote-mirror-list
 command line option, 725

gitlab-project-remote-mirror-update
 command line option, 726

gitlab-project-runner-create command
 line option, 726

gitlab-project-runner-delete command
 line option, 727

gitlab-project-runner-list command line
 option, 727

gitlab-project-service-available
 command line option, 728

gitlab-project-service-delete command
 line option, 728

gitlab-project-service-get command line
 option, 728

gitlab-project-service-list command
 line option, 728

gitlab-project-service-update command
 line option, 729

gitlab-project-snippet-award-emoji-create
 command line option, 732

gitlab-project-snippet-award-emoji-delete
 command line option, 732

gitlab-project-snippet-award-emoji-get
 command line option, 733

gitlab-project-snippet-award-emoji-list
 command line option, 733

gitlab-project-snippet-content command
 line option, 729

gitlab-project-snippet-create command
 line option, 730

gitlab-project-snippet-delete command
 line option, 730

gitlab-project-snippet-discussion-create
 command line option, 734

gitlab-project-snippet-discussion-get
 command line option, 734

gitlab-project-snippet-discussion-list
 command line option, 735

```
gitlab-project-snippet-discussion-note-create gitlab-project-update command line
    command line option, 735                                option, 574
gitlab-project-snippet-discussion-note-delete gitlab-project-user-list command line
    command line option, 736                                option, 745
gitlab-project-snippet-discussion-note-get    gitlab-project-variable-create command
    command line option, 736                                line option, 746
gitlab-project-snippet-discussion-note-update gitlab-project-variable-delete command
    command line option, 737                                line option, 746
gitlab-project-snippet-get command line
    option, 730
gitlab-project-snippet-list command
    line option, 731
gitlab-project-snippet-note-award-emoji-create gitlab-project-variable-update command
    command line option, 739                                line option, 747
gitlab-project-snippet-note-award-emoji-delete gitlab-project-wiki-create command line
    command line option, 740                                option, 748
gitlab-project-snippet-note-award-emoji-get    gitlab-project-wiki-delete command line
    command line option, 740                                option, 748
gitlab-project-snippet-note-award-emoji-list  gitlab-project-wiki-get command line
    command line option, 741                                option, 749
gitlab-project-snippet-note-create
    command line option, 737
gitlab-project-snippet-note-delete
    command line option, 738
gitlab-project-snippet-note-get command
    line option, 738
gitlab-project-snippet-note-list
    command line option, 738
gitlab-project-snippet-note-update
    command line option, 739
gitlab-project-snippet-update command
    line option, 731
gitlab-project-snippet-user-agent-detail
    command line option, 732
gitlab-project-storage-get command line
    option, 741
gitlab-project-tag-create command line
    option, 742
gitlab-project-tag-delete command line
    option, 742
gitlab-project-tag-get command line
    option, 742
gitlab-project-tag-list command line
    option, 743
gitlab-project-trigger-create command
    line option, 743
gitlab-project-trigger-delete command
    line option, 744
gitlab-project-trigger-get command line
    option, 744
gitlab-project-trigger-list command
    line option, 744
gitlab-project-trigger-update command
    line option, 745
```

```

gitlab-todo-delete command line option,
    759
gitlab-todo-list command line option, 760
gitlab-topic-create command line option,
    761
gitlab-topic-delete command line option,
    761
gitlab-topic-get command line option, 761
gitlab-topic-list command line option,
    762
gitlab-topic-update command line option,
    762
gitlab-user-activities-list command
    line option, 769
gitlab-user-create command line option,
    764
gitlab-user-custom-attribute-delete
    command line option, 769
gitlab-user-custom-attribute-get
    command line option, 770
gitlab-user-custom-attribute-list
    command line option, 770
gitlab-user-delete command line option,
    765
gitlab-user-email-create command line
    option, 771
gitlab-user-email-delete command line
    option, 771
gitlab-user-email-get command line
    option, 771
gitlab-user-email-list command line
    option, 771
gitlab-user-event-list command line
    option, 772
gitlab-user-get command line option, 766
gitlab-user-gpg-key-create command line
    option, 773
gitlab-user-gpg-key-delete command line
    option, 773
gitlab-user-gpg-key-get command line
    option, 773
gitlab-user-gpg-key-list command line
    option, 774
gitlab-user-impersonation-token-create
    command line option, 774
gitlab-user-impersonation-token-delete
    command line option, 775
gitlab-user-impersonation-token-get
    command line option, 775
gitlab-user-impersonation-token-list
    command line option, 775
gitlab-user-key-create command line
    option, 776
gitlab-user-key-delete command line
    option, 776
gitlab-user-key-get command line option,
    776
gitlab-user-key-list command line
    option, 777
gitlab-user-list command line option, 766
gitlab-user-membership-get command line
    option, 777
gitlab-user-membership-list command
    line option, 777
gitlab-user-personal-access-token-create
    command line option, 778
gitlab-user-project-create command line
    option, 779
gitlab-user-project-list command line
    option, 780
gitlab-user-status-get command line
    option, 781
gitlab-user-update command line option,
    768
gitlab-variable-create command line
    option, 782
gitlab-variable-delete command line
    option, 782
gitlab-variable-get command line option,
    782
gitlab-variable-list command line
    option, 783
gitlab-variable-update command line
    option, 783
--suggestion-commit-message
gitlab-project-update command line
    option, 576
--tag
gitlab-project-deployment-create
    command line option, 608
--tag-list
gitlab-group-runner-list command line
    option, 544
gitlab-project-create command line
    option, 564
gitlab-project-runner-list command line
    option, 727
gitlab-project-update command line
    option, 576
gitlab-runner-all-list command line
    option, 753
gitlab-runner-create command line
    option, 751
gitlab-runner-list command line option,
    752
gitlab-runner-update command line
    option, 752
--tag-name

```

```
gitlab-project-release-create command
    line option, 721
gitlab-project-release-delete command
    line option, 721
gitlab-project-release-get command line
    option, 721
gitlab-project-release-link-create
    command line option, 723
gitlab-project-release-link-delete
    command line option, 723
gitlab-project-release-link-get command
    line option, 724
gitlab-project-release-link-list
    command line option, 724
gitlab-project-release-link-update
    command line option, 725
gitlab-project-release-update command
    line option, 722
gitlab-project-tag-create command line
    option, 742
--tag-push-events
    gitlab-group-hook-create command line
        option, 520
    gitlab-group-hook-update command line
        option, 522
    gitlab-project-hook-create command line
        option, 621
    gitlab-project-hook-update command line
        option, 623
--target-access-levels
    gitlab-broadcast-message-create command
        line option, 468
    gitlab-broadcast-message-update command
        line option, 470
--target-branch
    gitlab-group-merge-request-list command
        line option, 535
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-deployment-merge-request-list
        command line option, 612
    gitlab-project-merge-request-create
        command line option, 664
    gitlab-project-merge-request-list
        command line option, 666
    gitlab-project-merge-request-update
        command line option, 671
--target-issue-iid
    gitlab-project-issue-link-create
        command line option, 641
--target-project-id
    gitlab-project-issue-link-create
        command line option, 641
    gitlab-project-merge-request-create
        command line option, 664
    gitlab-project-release-create command
        command line option, 664
--target-type
    gitlab-event-list command line option,
        477
    gitlab-project-event-list command line
        option, 615
    gitlab-user-event-list command line
        option, 772
--target-url
    gitlab-project-commit-status-create
        command line option, 604
--tasks-project-id
    gitlab-group-invitation-create command
        line option, 524
    gitlab-project-invitation-create
        command line option, 626
--tasks-to-be-done
    gitlab-group-invitation-create command
        line option, 524
    gitlab-group-member-create command line
        option, 531
    gitlab-project-invitation-create
        command line option, 626
    gitlab-project-member-create command
        line option, 658
--template-name
    gitlab-project-create command line
        option, 564
--template-project-id
    gitlab-project-create command line
        option, 564
--terminal-max-session-time
    gitlab-application-settings-update
        command line option, 466
--terms
    gitlab-application-settings-update
        command line option, 466
--theme-id
    gitlab-user-create command line option,
        765
    gitlab-user-update command line option,
        768
--timeout
    gitlab command line option, 460
--title
    gitlab-application-appearance-update
        command line option, 462
    gitlab-current-user-key-create command
        line option, 474
    gitlab-group-epic-create command line
        option, 507
    gitlab-group-epic-update command line
        option, 509
    gitlab-group-milestone-create command
```

```

    line option, 535
gitlab-group-milestone-update command
    line option, 537
gitlab-group-wiki-create command line
    option, 547
gitlab-group-wiki-update command line
    option, 549
gitlab-project-issue-create command
    line option, 629
gitlab-project-issue-update command
    line option, 635
gitlab-project-key-create command line
    option, 653
gitlab-project-key-update command line
    option, 655
gitlab-project-merge-request-create
    command line option, 664
gitlab-project-merge-request-update
    command line option, 671
gitlab-project-milestone-create command
    line option, 692
gitlab-project-milestone-update command
    line option, 694
gitlab-project-snippet-create command
    line option, 730
gitlab-project-snippet-update command
    line option, 731
gitlab-project-wiki-create command line
    option, 748
gitlab-project-wiki-update command line
    option, 749
gitlab-snippet-create command line
    option, 756
gitlab-snippet-update command line
    option, 757
gitlab-topic-create command line option,
    761
gitlab-user-key-create command line
    option, 776
--to
    gitlab-project-repository-compare
        command line option, 568
--to-namespace
    gitlab-project-transfer command line
        option, 571
    gitlab-project-transfer-project command
        line option, 571
--to-project-id
    gitlab-project-issue-move command line
        option, 631
--token
    gitlab-group-hook-create command line
        option, 521
    gitlab-group-hook-update command line
        option, 523
gitlab-project-hook-create command line
    option, 621
gitlab-project-hook-update command line
    option, 623
gitlab-project-trigger-pipeline command
    line option, 571
gitlab-runner-create command line
    option, 751
gitlab-runner-verify command line
    option, 753
--top-level-only
    gitlab-group-list command line option,
        487
--topic
    gitlab-project-list command line option,
        567
--topics
    gitlab-project-create command line
        option, 564
    gitlab-project-update command line
        option, 576
--trailers
    gitlab-project-commit-list command line
        option, 598
--twitter
    gitlab-user-create command line option,
        764
    gitlab-user-update command line option,
        768
--two-factor
    gitlab-user-list command line option, 766
--two-factor-grace-period
    gitlab-group-create command line option,
        485
    gitlab-group-update command line option,
        489
--type
    gitlab-project-commit-refs command line
        option, 598
    gitlab-runner-all-list command line
        option, 753
    gitlab-runner-list command line option,
        752
    gitlab-todo-list command line option, 760
    gitlab-user-membership-list command
        line option, 778
--unprotect-access-level
    gitlab-project-protected-branch-create
        command line option, 711
--until
    gitlab-project-commit-list command line
        option, 598
--updated-after

```

```
gitlab-group-issue-list command line
    option, 526
gitlab-group-merge-request-list command
    line option, 534
gitlab-issue-list command line option,
    551
gitlab-merge-request-list command line
    option, 555
gitlab-project-deployment-list command
    line option, 609
gitlab-project-deployment-merge-request-list
    command line option, 611
gitlab-project-issue-list command line
    option, 631
gitlab-project-merge-request-list
    command line option, 666
--updated-at
    gitlab-application-settings-update
        command line option, 465
    gitlab-project-issue-update command
        line option, 635
--updated-before
    gitlab-group-issue-list command line
        option, 526
    gitlab-group-merge-request-list command
        line option, 534
    gitlab-issue-list command line option,
        551
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-deployment-list command
        line option, 609
    gitlab-project-deployment-merge-request-list
        command line option, 611
    gitlab-project-issue-list command line
        option, 631
    gitlab-project-merge-request-list
        command line option, 666
--url
    gitlab-geo-node-update command line
        option, 482
    gitlab-group-hook-create command line
        option, 520
    gitlab-group-hook-update command line
        option, 522
    gitlab-hook-create command line option,
        549
    gitlab-project-hook-create command line
        option, 621
    gitlab-project-hook-update command line
        option, 623
    gitlab-project-release-link-create
        command line option, 723
    gitlab-project-release-link-update
        command line option, 725
gitlab-project-remote-mirror-create
    command line option, 725
--use-custom-template
    gitlab-project-create command line
        option, 564
--user-agent
    gitlab command line option, 460
--user-id
    gitlab-group-billable-member-membership-list
        command line option, 497
    gitlab-group-member-create command line
        option, 531
    gitlab-personal-access-token-list
        command line option, 559
    gitlab-project-member-create command
        line option, 658
    gitlab-starred-project-list command
        line option, 758
    gitlab-user-custom-attribute-delete
        command line option, 769
    gitlab-user-custom-attribute-get
        command line option, 770
    gitlab-user-custom-attribute-list
        command line option, 770
    gitlab-user-email-create command line
        option, 771
    gitlab-user-email-delete command line
        option, 771
    gitlab-user-email-get command line
        option, 771
    gitlab-user-email-list command line
        option, 771
    gitlab-user-event-list command line
        option, 772
    gitlab-user-gpg-key-create command line
        option, 773
    gitlab-user-gpg-key-delete command line
        option, 773
    gitlab-user-gpg-key-get command line
        option, 773
    gitlab-user-gpg-key-list command line
        option, 774
    gitlab-user-impersonation-token-create
        command line option, 774
    gitlab-user-impersonation-token-delete
        command line option, 775
    gitlab-user-impersonation-token-get
        command line option, 775
    gitlab-user-impersonation-token-list
        command line option, 775
    gitlab-user-key-create command line
        option, 776
    gitlab-user-key-delete command line
```

```

    option, 776
gitlab-user-key-get command line option,
    776
gitlab-user-key-list command line
    option, 777
gitlab-user-membership-get command line
    option, 777
gitlab-user-membership-list command
    line option, 778
gitlab-user-personal-access-token-create
    command line option, 778
gitlab-user-project-create command line
    option, 779
gitlab-user-project-list command line
    option, 780
gitlab-user-status-get command line
    option, 781
--user-ids
    gitlab-project-approval-rule-create
        command line option, 581
    gitlab-project-merge-request-approval-rule-creation
        command line option, 673
    gitlab-project-merge-request-approval-rule-update
        command line option, 675
--user-oauth-applications
    gitlab-application-settings-update
        command line option, 466
--user-show-add-ssh-key-message
    gitlab-application-settings-update
        command line option, 466
--username
    gitlab-group-deploy-token-create
        command line option, 504
    gitlab-project-deploy-token-create
        command line option, 606
    gitlab-project-pipeline-list command
        line option, 702
    gitlab-user-create command line option,
        764
    gitlab-user-list command line option, 766
    gitlab-user-update command line option,
        768
--value
    gitlab-group-variable-create command
        line option, 545
    gitlab-group-variable-update command
        line option, 547
    gitlab-project-pipeline-schedule-variable-create
        command line option, 708
    gitlab-project-pipeline-schedule-variable-update
        command line option, 708
    gitlab-project-variable-create command
        line option, 746
    gitlab-project-variable-update command
        line option, 748
gitlab-variable-create command line
    option, 782
gitlab-variable-update command line
    option, 783
--variable-type
    gitlab-group-variable-create command
        line option, 546
    gitlab-group-variable-update command
        line option, 547
    gitlab-project-variable-create command
        line option, 746
    gitlab-project-variable-update command
        line option, 748
    gitlab-variable-create command line
        option, 782
    gitlab-variable-update command line
        option, 783
--verbose
    gitlab command line option, 459
gitlab command line option, 459
gitlab command line option, 459
gitlab-group-merge-request-list command
    line option, 534
gitlab-merge-request-list command line
    option, 555
gitlab-project-deployment-merge-request-list
    command line option, 611
gitlab-project-merge-request-list
    command line option, 666
--visibility
    gitlab-group-create command line option,
        485
    gitlab-group-project-list command line
        option, 540
    gitlab-group-update command line option,
        489
    gitlab-project-create command line
        option, 564
    gitlab-project-fork-list command line
        option, 620
    gitlab-project-list command line option,
        567
    gitlab-project-snippet-create command
        line option, 730
    gitlab-project-snippet-update command
        line option, 731
    gitlab-project-update command line
        option, 576
    gitlab-shared-project-list command line
        option, 755
    gitlab-snippet-create command line
        option, 756

```

```
gitlab-snippet-update command line
    option, 758
gitlab-starred-project-list command
    line option, 759
gitlab-user-project-create command line
    option, 779
gitlab-user-project-list command line
    option, 780
--wall-enabled
    gitlab-user-project-create command line
        option, 779
--website-url
    gitlab-user-create command line option,
        764
    gitlab-user-update command line option,
        768
--wiki
    gitlab-project-snapshot command line
        option, 570
--wiki-access-level
    gitlab-project-create command line
        option, 565
    gitlab-project-update command line
        option, 576
--wiki-checksum-failed
    gitlab-project-list command line option,
        567
    gitlab-user-project-list command line
        option, 780
--wiki-enabled
    gitlab-project-create command line
        option, 565
    gitlab-project-update command line
        option, 576
    gitlab-user-project-create command line
        option, 779
--wiki-events
    gitlab-project-hook-update command line
        option, 623
--wiki-page-events
    gitlab-group-hook-create command line
        option, 520
    gitlab-group-hook-update command line
        option, 522
    gitlab-project-hook-create command line
        option, 621
--wip
    gitlab-group-merge-request-list command
        line option, 535
    gitlab-merge-request-list command line
        option, 556
    gitlab-project-deployment-merge-request-list
        command line option, 612
    gitlab-project-merge-request-list
        command line option, 666
--with-content
    gitlab-group-wiki-list command line
        option, 548
    gitlab-project-wiki-list command line
        option, 749
--with-custom-attributes
    gitlab-group-descendant-group-list
        command line option, 506
    gitlab-group-list command line option,
        487
    gitlab-group-project-list command line
        option, 541
    gitlab-group-subgroup-list command line
        option, 545
    gitlab-project-fork-list command line
        option, 620
    gitlab-project-list command line option,
        567
    gitlab-shared-project-list command line
        option, 755
    gitlab-starred-project-list command
        line option, 759
    gitlab-user-project-list command line
        option, 780
--with-issues-enabled
    gitlab-group-project-list command line
        option, 541
    gitlab-project-fork-list command line
        option, 620
    gitlab-project-list command line option,
        567
    gitlab-shared-project-list command line
        option, 755
    gitlab-starred-project-list command
        line option, 759
    gitlab-user-project-list command line
        option, 780
--with-labels-details
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-deployment-merge-request-list
        command line option, 611
--with-merge-requests-enabled
    gitlab-group-project-list command line
        option, 541
    gitlab-project-fork-list command line
        option, 620
    gitlab-project-list command line option,
        567
    gitlab-shared-project-list command line
        option, 755
    gitlab-starred-project-list command
        line option, 759
```

```

gitlab-user-project-list command line
    option, 780
--with-merge-status-recheck
    gitlab-merge-request-list command line
        option, 555
    gitlab-project-deployment-merge-request-list
        command line option, 611
--with-programming-language
    gitlab-project-list command line option,
        567
    gitlab-user-project-list command line
        option, 780
--with-security-reports
    gitlab-group-project-list command line
        option, 541
--with-shared
    gitlab-group-project-list command line
        option, 541
--with-stats
    gitlab-project-commit-list command line
        option, 598
--yaml-errors
    gitlab-project-pipeline-list command
        line option, 702
-c
    gitlab command line option, 460
-d
    gitlab command line option, 460
-f
    gitlab command line option, 460
-g
    gitlab command line option, 460
-h
    gitlab command line option, 459
    gitlab-application command line option,
        461
    gitlab-application-appearance command
        line option, 462
    gitlab-application-appearance-get
        command line option, 462
    gitlab-application-appearance-update
        command line option, 462
    gitlab-application-create command line
        option, 461
    gitlab-application-delete command line
        option, 461
    gitlab-application-list command line
        option, 461
    gitlab-application-settings command
        line option, 463
    gitlab-application-settings-get command
        line option, 463
    gitlab-application-settings-update
        command line option, 465
gitlab-audit-event command line option,
    467
gitlab-audit-event-get command line
    option, 467
gitlab-audit-event-list command line
    option, 467
gitlab-broadcast-message command line
    option, 468
gitlab-broadcast-message-create command
    line option, 468
gitlab-broadcast-message-delete command
    line option, 468
gitlab-broadcast-message-get command
    line option, 469
gitlab-broadcast-message-list command
    line option, 469
gitlab-broadcast-message-update command
    line option, 469
gitlab-ci-lint command line option, 470
gitlab-ci-lint-create command line
    option, 470
gitlab-ci-lint-validate command line
    option, 470
gitlab-current-user command line option,
    471
gitlab-current-user-email command line
    option, 471
gitlab-current-user-email-create
    command line option, 471
gitlab-current-user-email-delete
    command line option, 471
gitlab-current-user-email-get command
    line option, 472
gitlab-current-user-email-list command
    line option, 472
gitlab-current-user-get command line
    option, 471
gitlab-current-user-gpg-key command
    line option, 472
gitlab-current-user-gpg-key-create
    command line option, 472
gitlab-current-user-gpg-key-delete
    command line option, 473
gitlab-current-user-gpg-key-get command
    line option, 473
gitlab-current-user-gpg-key-list
    command line option, 473
gitlab-current-user-key command line
    option, 473
gitlab-current-user-key-create command
    line option, 474
gitlab-current-user-key-delete command
    line option, 474
gitlab-current-user-key-get command

```

line option, 474
gitlab-current-user-key-list command line option, 474
gitlab-current-user-status command line option, 475
gitlab-current-user-status-get command line option, 475
gitlab-current-user-status-update command line option, 475
gitlab-deploy-key command line option, 475
gitlab-deploy-key-list command line option, 475
gitlab-deploy-token command line option, 476
gitlab-deploy-token-list command line option, 476
gitlab-dockerfile command line option, 476
gitlab-dockerfile-get command line option, 477
gitlab-dockerfile-list command line option, 477
gitlab-event command line option, 477
gitlab-event-list command line option, 477
gitlab-feature command line option, 478
gitlab-feature-delete command line option, 478
gitlab-feature-list command line option, 478
gitlab-generic-package command line option, 479
gitlab-generic-package-download command line option, 479
gitlab-generic-package-upload command line option, 479
gitlab-geo-node command line option, 480
gitlab-geo-node-current-failures command line option, 480
gitlab-geo-node-delete command line option, 480
gitlab-geo-node-get command line option, 480
gitlab-geo-node-list command line option, 481
gitlab-geo-node-repair command line option, 481
gitlab-geo-node-status command line option, 481
gitlab-geo-node-update command line option, 481
gitlab-gitignore command line option, 482
gitlab-gitignore-get command line option, 482
gitlab-gitignore-list command line option, 482
gitlab-gitlabciyml command line option, 483
gitlab-gitlabciyml-get command line option, 483
gitlab-gitlabciyml-list command line option, 483
gitlab-group command line option, 484
gitlab-group-access-request command line option, 490
gitlab-group-access-request-approve command line option, 490
gitlab-group-access-request-create command line option, 490
gitlab-group-access-request-delete command line option, 490
gitlab-group-access-request-list command line option, 491
gitlab-group-access-token command line option, 491
gitlab-group-access-token-create command line option, 491
gitlab-group-access-token-delete command line option, 492
gitlab-group-access-token-list command line option, 492
gitlab-group-add-ldap-group-link command line option, 484
gitlab-group-audit-event command line option, 492
gitlab-group-audit-event-get command line option, 493
gitlab-group-audit-event-list command line option, 493
gitlab-group-badge command line option, 493
gitlab-group-badge-create command line option, 494
gitlab-group-badge-delete command line option, 494
gitlab-group-badge-get command line option, 494
gitlab-group-badge-list command line option, 494
gitlab-group-badge-render command line option, 495
gitlab-group-badge-update command line option, 495
gitlab-group-billable-member command line option, 496
gitlab-group-billable-member-delete command line option, 496

gitlab-group-billable-member-list
 command line option, 496
gitlab-group-billable-member-membership
 command line option, 497
gitlab-group-billable-member-membership-list
 command line option, 497
gitlab-group-board command line option,
 497
gitlab-group-board-create command line
 option, 497
gitlab-group-board-delete command line
 option, 498
gitlab-group-board-get command line
 option, 498
gitlab-group-board-list command line
 option, 498, 499
gitlab-group-board-list-create command
 line option, 499
gitlab-group-board-list-delete command
 line option, 499
gitlab-group-board-list-get command
 line option, 500
gitlab-group-board-list-list command
 line option, 500
gitlab-group-board-list-update command
 line option, 500
gitlab-group-board-update command line
 option, 499
gitlab-group-cluster command line
 option, 501
gitlab-group-cluster-create command
 line option, 501
gitlab-group-cluster-delete command
 line option, 501
gitlab-group-cluster-get command line
 option, 502
gitlab-group-cluster-list command line
 option, 502
gitlab-group-cluster-update command
 line option, 502
gitlab-group-create command line option,
 484
gitlab-group-custom-attribute command
 line option, 503
gitlab-group-custom-attribute-delete
 command line option, 503
gitlab-group-custom-attribute-get
 command line option, 503
gitlab-group-custom-attribute-list
 command line option, 504
gitlab-group-delete command line option,
 485
gitlab-group-delete-ldap-group-link
 command line option, 486

gitlab-group-deploy-token command line
 option, 504
gitlab-group-deploy-token-create
 command line option, 504
gitlab-group-deploy-token-delete
 command line option, 505
gitlab-group-deploy-token-get command
 line option, 505
gitlab-group-deploy-token-list command
 line option, 505
gitlab-group-descendant-group command
 line option, 506
gitlab-group-descendant-group-list
 command line option, 506
gitlab-group-epic command line option,
 507
gitlab-group-epic-award-emoji command
 line option, 509
gitlab-group-epic-award-emoji-create
 command line option, 509
gitlab-group-epic-award-emoji-delete
 command line option, 510
gitlab-group-epic-award-emoji-get
 command line option, 510
gitlab-group-epic-award-emoji-list
 command line option, 510
gitlab-group-epic-create command line
 option, 507
gitlab-group-epic-delete command line
 option, 507
gitlab-group-epic-discussion-note
 command line option, 511
gitlab-group-epic-discussion-note-create
 command line option, 511
gitlab-group-epic-discussion-note-delete
 command line option, 511
gitlab-group-epic-discussion-note-get
 command line option, 512
gitlab-group-epic-discussion-note-update
 command line option, 512
gitlab-group-epic-get command line
 option, 508
gitlab-group-epic-issue command line
 option, 513
gitlab-group-epic-issue-create command
 line option, 513
gitlab-group-epic-issue-delete command
 line option, 513
gitlab-group-epic-issue-list command
 line option, 513
gitlab-group-epic-issue-update command
 line option, 514
gitlab-group-epic-list command line
 option, 508

```
gitlab-group-epic-note command line
    option, 514
gitlab-group-epic-note-award-emoji
    command line option, 516
gitlab-group-epic-note-award-emoji-create
    command line option, 516
gitlab-group-epic-note-award-emoji-delete
    command line option, 517
gitlab-group-epic-note-award-emoji-get
    command line option, 517
gitlab-group-epic-note-award-emoji-list
    command line option, 517
gitlab-group-epic-note-create command
    line option, 514
gitlab-group-epic-note-delete command
    line option, 515
gitlab-group-epic-note-get command line
    option, 515
gitlab-group-epic-note-list command
    line option, 515
gitlab-group-epic-note-update command
    line option, 516
gitlab-group-epic-resource-label-event
    command line option, 518
gitlab-group-epic-resource-label-event-get
    command line option, 518
gitlab-group-epic-resource-label-event-list
    command line option, 518
gitlab-group-export command line option,
    519
gitlab-group-export-create command line
    option, 519
gitlab-group-export-download command
    line option, 519
gitlab-group-export-get command line
    option, 519
gitlab-group-get command line option, 486
gitlab-group-hook command line option,
    520
gitlab-group-hook-create command line
    option, 520
gitlab-group-hook-delete command line
    option, 521
gitlab-group-hook-get command line
    option, 521
gitlab-group-hook-list command line
    option, 521
gitlab-group-hook-update command line
    option, 522
gitlab-group-import command line option,
    523
gitlab-group-import-get command line
    option, 523
gitlab-group-invitation command line
    option, 523
gitlab-group-invitation-create command
    line option, 523
gitlab-group-invitation-delete command
    line option, 524
gitlab-group-invitation-get command
    line option, 524
gitlab-group-invitation-list command
    line option, 524
gitlab-group-invitation-update command
    line option, 525
gitlab-group-issue command line option,
    525
gitlab-group-issue-list command line
    option, 525
gitlab-group-issues-statistics command
    line option, 526
gitlab-group-issues-statistics-get
    command line option, 527
gitlab-group-iteration command line
    option, 527
gitlab-group-iteration-list command
    line option, 527
gitlab-group-label command line option,
    528
gitlab-group-label-create command line
    option, 528
gitlab-group-label-delete command line
    option, 528
gitlab-group-label-get command line
    option, 529
gitlab-group-label-list command line
    option, 529
gitlab-group-label-subscribe command
    line option, 529
gitlab-group-label-unsubscribe command
    line option, 530
gitlab-group-label-update command line
    option, 530
gitlab-group-ldap-sync command line
    option, 486
gitlab-group-list command line option,
    486
gitlab-group-member command line option,
    530
gitlab-group-member-all command line
    option, 532
gitlab-group-member-all-get command
    line option, 533
gitlab-group-member-all-list command
    line option, 533
gitlab-group-member-create command line
```

option, 531
gitlab-group-member-delete command line
option, 531
gitlab-group-member-get command line
option, 531
gitlab-group-member-list command line
option, 532
gitlab-group-member-update command line
option, 532
gitlab-group-merge-request command line
option, 533
gitlab-group-merge-request-list command
line option, 534
gitlab-group-milestone command line
option, 535
gitlab-group-milestone-create command
line option, 535
gitlab-group-milestone-delete command
line option, 536
gitlab-group-milestone-get command line
option, 536
gitlab-group-milestone-issues command
line option, 536
gitlab-group-milestone-list command
line option, 536
gitlab-group-milestone-merge-requests
command line option, 537
gitlab-group-milestone-update command
line option, 537
gitlab-group-notification-settings
command line option, 538
gitlab-group-notification-settings-get
command line option, 538
gitlab-group-notification-settings-update
command line option, 538
gitlab-group-package command line
option, 539
gitlab-group-package-list command line
option, 539
gitlab-group-project command line
option, 540
gitlab-group-project-list command line
option, 540
gitlab-group-push-rules command line
option, 541
gitlab-group-push-rules-create command
line option, 541
gitlab-group-push-rules-delete command
line option, 542
gitlab-group-push-rules-get command
line option, 542
gitlab-group-push-rules-update command
line option, 543
gitlab-group-runner command line option,
543
gitlab-group-runner-list command line
option, 544
gitlab-group-search command line option,
487
gitlab-group-share command line option,
487
gitlab-group-subgroup command line
option, 544
gitlab-group-subgroup-list command line
option, 544
gitlab-group-transfer command line
option, 488
gitlab-group-transfer-project command
line option, 488
gitlab-group-unshare command line
option, 488
gitlab-group-update command line option,
489
gitlab-group-variable command line
option, 545
gitlab-group-variable-create command
line option, 545
gitlab-group-variable-delete command
line option, 546
gitlab-group-variable-get command line
option, 546
gitlab-group-variable-list command line
option, 546
gitlab-group-variable-update command
line option, 547
gitlab-group-wiki command line option,
547
gitlab-group-wiki-create command line
option, 547
gitlab-group-wiki-delete command line
option, 548
gitlab-group-wiki-get command line
option, 548
gitlab-group-wiki-list command line
option, 548
gitlab-group-wiki-update command line
option, 549
gitlab-hook command line option, 549
gitlab-hook-create command line option,
549
gitlab-hook-delete command line option,
549
gitlab-hook-get command line option, 550
gitlab-hook-list command line option, 550
gitlab-issue command line option, 550
gitlab-issue-get command line option, 550
gitlab-issue-list command line option,
551

gitlab-issues-statistics command line
 option, 552
gitlab-issues-statistics-get command
 line option, 552
gitlab-key command line option, 552
gitlab-key-get command line option, 552
gitlab-ldap-group command line option,
 552
gitlab-ldap-group-list command line
 option, 553
gitlab-license command line option, 553
gitlab-license-get command line option,
 553
gitlab-license-list command line option,
 554
gitlab-merge-request command line
 option, 554
gitlab-merge-request-list command line
 option, 555
gitlab-namespace command line option, 556
gitlab-namespace-exists command line
 option, 556
gitlab-namespace-get command line
 option, 556
gitlab-namespace-list command line
 option, 557
gitlab-notification-settings command
 line option, 557
gitlab-notification-settings-get
 command line option, 557
gitlab-notification-settings-update
 command line option, 558
gitlab-pages-domain command line option,
 558
gitlab-pages-domain-list command line
 option, 558
gitlab-personal-access-token command
 line option, 559
gitlab-personal-access-token-delete
 command line option, 559
gitlab-personal-access-token-list
 command line option, 559
gitlab-project command line option, 560
gitlab-project-access-request command
 line option, 577
gitlab-project-access-request-approve
 command line option, 577
gitlab-project-access-request-create
 command line option, 577
gitlab-project-access-request-delete
 command line option, 577
gitlab-project-access-request-list
 command line option, 578
gitlab-project-access-token command
 line option, 578
gitlab-project-access-token-create
 command line option, 578
gitlab-project-access-token-delete
 command line option, 579
gitlab-project-access-token-list
 command line option, 579
gitlab-project-additional-statistics
 command line option, 579
gitlab-project-additional-statistics-get
 command line option, 580
gitlab-project-approval command line
 option, 580
gitlab-project-approval-get command
 line option, 580
gitlab-project-approval-rule command
 line option, 581
gitlab-project-approval-rule-create
 command line option, 581
gitlab-project-approval-rule-delete
 command line option, 581
gitlab-project-approval-rule-list
 command line option, 582
gitlab-project-approval-rule-update
 command line option, 582
gitlab-project-approval-update command
 line option, 580
gitlab-project-archive command line
 option, 560
gitlab-project-artifact command line
 option, 561, 582
gitlab-project-artifact-delete command
 line option, 583
gitlab-project-artifact-download
 command line option, 583
gitlab-project-artifact-raw command
 line option, 583
gitlab-project-artifacts command line
 option, 561
gitlab-project-audit-event command line
 option, 584
gitlab-project-audit-event-get command
 line option, 584
gitlab-project-audit-event-list command
 line option, 584
gitlab-project-badge command line
 option, 585
gitlab-project-badge-create command
 line option, 585
gitlab-project-badge-delete command
 line option, 585
gitlab-project-badge-get command line
 option, 585
gitlab-project-badge-list command line

```
    option, 586
gitlab-project-badge-render command
    line option, 586
gitlab-project-badge-update command
    line option, 586
gitlab-project-board command line
    option, 587
gitlab-project-board-create command
    line option, 587
gitlab-project-board-delete command
    line option, 587
gitlab-project-board-get command line
    option, 587
gitlab-project-board-list command line
    option, 588
gitlab-project-board-list-create
    command line option, 589
gitlab-project-board-list-delete
    command line option, 589
gitlab-project-board-list-get command
    line option, 589
gitlab-project-board-list-list command
    line option, 590
gitlab-project-board-list-update
    command line option, 590
gitlab-project-board-update command
    line option, 588
gitlab-project-branch command line
    option, 590
gitlab-project-branch-create command
    line option, 591
gitlab-project-branch-delete command
    line option, 591
gitlab-project-branch-get command line
    option, 591
gitlab-project-branch-list command line
    option, 592
gitlab-project-ci-lint command line
    option, 592
gitlab-project-ci-lint-create command
    line option, 592
gitlab-project-ci-lint-get command line
    option, 593
gitlab-project-ci-lint-validate command
    line option, 593
gitlab-project-cluster command line
    option, 593
gitlab-project-cluster-create command
    line option, 593
gitlab-project-cluster-delete command
    line option, 594
gitlab-project-cluster-get command line
    option, 594
gitlab-project-cluster-list command
    line option, 595
gitlab-project-cluster-update command
    line option, 595
gitlab-project-commit command line
    option, 596
gitlab-project-commit-cherry-pick
    command line option, 596
gitlab-project-commit-comment command
    line option, 599
gitlab-project-commit-comment-create
    command line option, 599
gitlab-project-commit-comment-list
    command line option, 600
gitlab-project-commit-create command
    line option, 596
gitlab-project-commit-diff command line
    option, 597
gitlab-project-commit-discussion
    command line option, 600
gitlab-project-commit-discussion-create
    command line option, 600
gitlab-project-commit-discussion-get
    command line option, 601
gitlab-project-commit-discussion-list
    command line option, 601
gitlab-project-commit-discussion-note
    command line option, 602
gitlab-project-commit-discussion-note-create
    command line option, 602
gitlab-project-commit-discussion-note-delete
    command line option, 602
gitlab-project-commit-discussion-note-get
    command line option, 603
gitlab-project-commit-discussion-note-update
    command line option, 603
gitlab-project-commit-get command line
    option, 597
gitlab-project-commit-list command line
    option, 597
gitlab-project-commit-merge-requests
    command line option, 598
gitlab-project-commit-refs command line
    option, 598
gitlab-project-commit-revert command
    line option, 599
gitlab-project-commit-signature command
    line option, 599
gitlab-project-commit-status command
    line option, 604
gitlab-project-commit-status-create
    command line option, 604
gitlab-project-commit-status-list
    command line option, 604
gitlab-project-create command line
```

```
    option, 562
gitlab-project-create-fork-relation
    command line option, 565
gitlab-project-custom-attribute command
    line option, 605
gitlab-project-custom-attribute-delete
    command line option, 605
gitlab-project-custom-attribute-get
    command line option, 605
gitlab-project-custom-attribute-list
    command line option, 606
gitlab-project-delete command line
    option, 565
gitlab-project-delete-fork-relation
    command line option, 565
gitlab-project-delete-merged-branches
    command line option, 565
gitlab-project-deploy-token command
    line option, 606
gitlab-project-deploy-token-create
    command line option, 606
gitlab-project-deploy-token-delete
    command line option, 607
gitlab-project-deploy-token-get command
    line option, 607
gitlab-project-deploy-token-list
    command line option, 607
gitlab-project-deployment command line
    option, 608
gitlab-project-deployment-approval
    command line option, 608
gitlab-project-deployment-create
    command line option, 608
gitlab-project-deployment-get command
    line option, 609
gitlab-project-deployment-list command
    line option, 609
gitlab-project-deployment-merge-request
    command line option, 610
gitlab-project-deployment-merge-request-list
    command line option, 611
gitlab-project-deployment-update
    command line option, 610
gitlab-project-environment command line
    option, 612
gitlab-project-environment-create
    command line option, 612
gitlab-project-environment-delete
    command line option, 613
gitlab-project-environment-get command
    line option, 613
gitlab-project-environment-list command
    line option, 613
gitlab-project-environment-stop command
    line option, 614
gitlab-project-environment-update
    command line option, 614
gitlab-project-event command line
    option, 615
gitlab-project-event-list command line
    option, 615
gitlab-project-export command line
    option, 615
gitlab-project-export-create command
    line option, 616
gitlab-project-export-download command
    line option, 616
gitlab-project-export-get command line
    option, 616
gitlab-project-file command line option,
    616
gitlab-project-file-blame command line
    option, 617
gitlab-project-file-create command line
    option, 617
gitlab-project-file-delete command line
    option, 618
gitlab-project-file-get command line
    option, 618
gitlab-project-file-raw command line
    option, 618
gitlab-project-file-update command line
    option, 619
gitlab-project-fork command line option,
    619
gitlab-project-fork-create command line
    option, 619
gitlab-project-fork-list command line
    option, 620
gitlab-project-get command line option,
    566
gitlab-project-hook command line option,
    621
gitlab-project-hook-create command line
    option, 621
gitlab-project-hook-delete command line
    option, 622
gitlab-project-hook-get command line
    option, 622
gitlab-project-hook-list command line
    option, 622
gitlab-project-hook-update command line
    option, 623
gitlab-project-housekeeping command
    line option, 566
gitlab-project-import command line
    option, 624
gitlab-project-import-get command line
```

```
    option, 624
gitlab-project-integration command line
    option, 624
gitlab-project-integration-available
    command line option, 624
gitlab-project-integration-delete
    command line option, 624
gitlab-project-integration-get command
    line option, 625
gitlab-project-integration-list command
    line option, 625
gitlab-project-integration-update
    command line option, 625
gitlab-project-invitation command line
    option, 626
gitlab-project-invitation-create
    command line option, 626
gitlab-project-invitation-delete
    command line option, 626
gitlab-project-invitation-get command
    line option, 627
gitlab-project-invitation-list command
    line option, 627
gitlab-project-invitation-update
    command line option, 627
gitlab-project-issue command line
    option, 628
gitlab-project-issue-add-spent-time
    command line option, 628
gitlab-project-issue-award-emoji
    command line option, 636
gitlab-project-issue-award-emoji-create
    command line option, 636
gitlab-project-issue-award-emoji-delete
    command line option, 636
gitlab-project-issue-award-emoji-get
    command line option, 637
gitlab-project-issue-award-emoji-list
    command line option, 637
gitlab-project-issue-closed-by command
    line option, 629
gitlab-project-issue-create command
    line option, 629
gitlab-project-issue-delete command
    line option, 630
gitlab-project-issue-discussion command
    line option, 637
gitlab-project-issue-discussion-create
    command line option, 638
gitlab-project-issue-discussion-get
    command line option, 638
gitlab-project-issue-discussion-list
    command line option, 638
gitlab-project-issue-discussion-note
    command line option, 639
gitlab-project-issue-discussion-note-create
    command line option, 639
gitlab-project-issue-discussion-note-delete
    command line option, 640
gitlab-project-issue-discussion-note-get
    command line option, 640
gitlab-project-issue-discussion-note-update
    command line option, 640
gitlab-project-issue-get command line
    option, 630
gitlab-project-issue-link command line
    option, 641
gitlab-project-issue-link-create
    command line option, 641
gitlab-project-issue-link-delete
    command line option, 641
gitlab-project-issue-link-list command
    line option, 642
gitlab-project-issue-list command line
    option, 630
gitlab-project-issue-move command line
    option, 631
gitlab-project-issue-note command line
    option, 642
gitlab-project-issue-note-award-emoji
    command line option, 644
gitlab-project-issue-note-award-emoji-create
    command line option, 644
gitlab-project-issue-note-award-emoji-delete
    command line option, 645
gitlab-project-issue-note-award-emoji-get
    command line option, 645
gitlab-project-issue-note-award-emoji-list
    command line option, 645
gitlab-project-issue-note-create
    command line option, 642
gitlab-project-issue-note-delete
    command line option, 643
gitlab-project-issue-note-get command
    line option, 643
gitlab-project-issue-note-list command
    line option, 643
gitlab-project-issue-note-update
    command line option, 644
gitlab-project-issue-participants
    command line option, 632
gitlab-project-issue-related-merge-requests
    command line option, 632
gitlab-project-issue-reorder command
    line option, 632
gitlab-project-issue-reset-spent-time
    command line option, 633
gitlab-project-issue-reset-time-estimate
```

```
    command line option, 633
gitlab-project-issue-resource-label-event      option, 652
    command line option, 646
gitlab-project-issue-resource-label-event-get gitlab-project-job-play command line
    command line option, 646
gitlab-project-issue-resource-label-event-list gitlab-project-job-retry command line
    command line option, 646
gitlab-project-issue-resource-milestone-event gitlab-project-key command line option,
    command line option, 647
gitlab-project-issue-resource-milestone-event gitlab-project-key-create command line
    command line option, 647
gitlab-project-issue-resource-milestone-event gitlab-project-key-delete command line
    command line option, 648
gitlab-project-issue-resource-state-event      gitlab-project-key-enable command line
    command line option, 648
gitlab-project-issue-resource-state-event-get gitlab-project-key-get command line
    command line option, 648
gitlab-project-issue-resource-state-event-list gitlab-project-key-list command line
    command line option, 649
gitlab-project-issue-subscribe command
    line option, 633
gitlab-project-issue-time-estimate
    command line option, 633
gitlab-project-issue-time-stats command
    line option, 634
gitlab-project-issue-todo command line
    option, 634
gitlab-project-issue-unsubscribe
    command line option, 634
gitlab-project-issue-update command
    line option, 635
gitlab-project-issue-user-agent-detail
    command line option, 635
gitlab-project-issues-statistics
    command line option, 649
gitlab-project-issues-statistics-get
    command line option, 649
gitlab-project-job command line option,
    650
gitlab-project-job-artifact command
    line option, 650
gitlab-project-job-artifacts command
    line option, 650
gitlab-project-job-cancel command line
    option, 651
gitlab-project-job-delete-artifacts
    command line option, 651
gitlab-project-job-erase command line
    option, 651
gitlab-project-job-get command line
    option, 651
gitlab-project-job-keep-artifacts
    command line option, 652
gitlab-project-job-list command line
```

```
    option, 652
gitlab-project-job-play command line
    option, 652
gitlab-project-job-retry command line
    option, 653
gitlab-project-job-trace command line
    option, 653
gitlab-project-key command line option,
    653
gitlab-project-key-create command line
    option, 653
gitlab-project-key-delete command line
    option, 654
gitlab-project-key-enable command line
    option, 654
gitlab-project-key-get command line
    option, 654
gitlab-project-key-list command line
    option, 655
gitlab-project-key-update command line
    option, 655
gitlab-project-label command line
    option, 655
gitlab-project-label-create command
    line option, 656
gitlab-project-label-delete command
    line option, 656
gitlab-project-label-get command line
    option, 656
gitlab-project-label-list command line
    option, 657
gitlab-project-label-subscribe command
    line option, 657
gitlab-project-label-unsubscribe
    command line option, 657
gitlab-project-label-update command
    line option, 658
gitlab-project-languages command line
    option, 566
gitlab-project-list command line option,
    566
gitlab-project-member command line
    option, 658
gitlab-project-member-all command line
    option, 660
gitlab-project-member-all-get command
    line option, 660
gitlab-project-member-all-list command
    line option, 660
gitlab-project-member-create command
    line option, 658
gitlab-project-member-delete command
    line option, 659
gitlab-project-member-get command line
```

```

    option, 659
gitlab-project-member-list command line
    option, 659
gitlab-project-member-update command
    line option, 660
gitlab-project-merge-request command
    line option, 661
gitlab-project-merge-request-add-spent-time
    command line option, 662
gitlab-project-merge-request-approval
    command line option, 672
gitlab-project-merge-request-approval-get
    command line option, 672
gitlab-project-merge-request-approval-rule
    command line option, 672
gitlab-project-merge-request-approval-rule-create
    command line option, 673
gitlab-project-merge-request-approval-rule-delete
    command line option, 673
gitlab-project-merge-request-approval-rule-get
    command line option, 674
gitlab-project-merge-request-approval-rule-list
    command line option, 674
gitlab-project-merge-request-approval-rule-update
    command line option, 675
gitlab-project-merge-request-approval-state
    command line option, 675
gitlab-project-merge-request-approval-state-get
    command line option, 676
gitlab-project-merge-request-approval-update
    command line option, 672
gitlab-project-merge-request-approve
    command line option, 662
gitlab-project-merge-request-award-emoji
    command line option, 676
gitlab-project-merge-request-award-emoji-create
    command line option, 676
gitlab-project-merge-request-award-emoji-delete
    command line option, 677
gitlab-project-merge-request-award-emoji-get
    command line option, 677
gitlab-project-merge-request-award-emoji-list
    command line option, 677
gitlab-project-merge-request-cancel-merge-when-pushed-to-branch
    command line option, 662
gitlab-project-merge-request-changes
    command line option, 663
gitlab-project-merge-request-closes-issues
    command line option, 663
gitlab-project-merge-request-commits
    command line option, 663
gitlab-project-merge-request-create
    command line option, 664
gitlab-project-merge-request-delete
    command line option, 665
gitlab-project-merge-request-diff
    command line option, 665
gitlab-project-merge-request-diff-get
    command line option, 678
gitlab-project-merge-request-diff-list
    command line option, 678
gitlab-project-merge-request-discussion
    command line option, 679
gitlab-project-merge-request-discussion-create
    command line option, 679
gitlab-project-merge-request-discussion-get
    command line option, 679
gitlab-project-merge-request-discussion-list
    command line option, 680
gitlab-project-merge-request-discussion-note
    command line option, 681
gitlab-project-merge-request-discussion-note-create
    command line option, 681
gitlab-project-merge-request-discussion-note-delete
    command line option, 681
gitlab-project-merge-request-discussion-note-get
    command line option, 682
gitlab-project-merge-request-discussion-note-update
    command line option, 682
gitlab-project-merge-request-discussion-update
    command line option, 680
gitlab-project-merge-request-merge
    command line option, 667
gitlab-project-merge-request-merge-ref
    command line option, 667
gitlab-project-merge-request-note
    command line option, 683
gitlab-project-merge-request-note-award-emoji
    command line option, 685
gitlab-project-merge-request-note-award-emoji-create
    command line option, 685
gitlab-project-merge-request-note-award-emoji-delete
    command line option, 685
gitlab-project-merge-request-note-award-emoji-get
    command line option, 686
gitlab-project-merge-request-note-award-emoji-list
    command line option, 686
gitlab-project-merge-request-note-create
    command line option, 683
gitlab-project-merge-request-note-delete
    command line option, 683
gitlab-project-merge-request-note-get
    command line option, 684
gitlab-project-merge-request-note-list
    command line option, 685

```

```
    command line option, 684
gitlab-project-merge-request-note-update
    command line option, 684
gitlab-project-merge-request-participants
    command line option, 668
gitlab-project-merge-request-pipeline
    command line option, 687
gitlab-project-merge-request-pipeline-create
    command line option, 687
gitlab-project-merge-request-pipeline-list
    command line option, 687
gitlab-project-merge-request-rebase
    command line option, 668
gitlab-project-merge-request-reset-approvals
    command line option, 668
gitlab-project-merge-request-reset-spent-time
    command line option, 668
gitlab-project-merge-request-reset-time-estimate
    command line option, 669
gitlab-project-merge-request-resource-label-event
    command line option, 688
gitlab-project-merge-request-resource-label-event
    command line option, 688
gitlab-project-merge-request-resource-label-event
    command line option, 688
gitlab-project-merge-request-resource-milestone
    command line option, 689
gitlab-project-merge-request-resource-state-event
    command line option, 690
gitlab-project-merge-request-resource-state-event
    command line option, 690
gitlab-project-merge-request-subscribe
    command line option, 669
gitlab-project-merge-request-time-estimate
    command line option, 669
gitlab-project-merge-request-time-stats
    command line option, 670
gitlab-project-merge-request-todo
    command line option, 670
gitlab-project-merge-request-unapprove
    command line option, 670
gitlab-project-merge-request-unsubscribe
    command line option, 670
gitlab-project-merge-request-update
    command line option, 671
gitlab-project-merge-train command line
    option, 691
gitlab-project-merge-train-list command
    line option, 691
gitlab-project-milestone command line
    option, 691
gitlab-project-milestone-create command
    line option, 692
gitlab-project-milestone-delete command
    line option, 692
gitlab-project-milestone-get command
    line option, 692
gitlab-project-milestone-issues command
    line option, 693
gitlab-project-milestone-list command
    line option, 693
gitlab-project-milestone-merge-requests
    command line option, 693
gitlab-project-milestone-update command
    line option, 694
gitlab-project-mirror-pull command line
    option, 568
gitlab-project-note command line option,
    694
gitlab-project-note-get command line
    option, 694
gitlab-project-note-list command line
    option, 695
gitlab-project-notification-settings
    command line option, 695
gitlab-project-notification-settings-get
    command line option, 695
gitlab-project-notification-settings-update
    command line option, 696
gitlab-project-package command line
    option, 696
gitlab-project-package-delete command
    line option, 697
gitlab-project-package-file command
    line option, 698
gitlab-project-package-file-delete
    command line option, 698
gitlab-project-package-file-list
    command line option, 698
gitlab-project-package-get command line
    option, 697
gitlab-project-package-list command
    line option, 697
gitlab-project-pages-domain command
    line option, 699
gitlab-project-pages-domain-create
    command line option, 699
gitlab-project-pages-domain-delete
    command line option, 699
gitlab-project-pages-domain-get command
    line option, 700
gitlab-project-pages-domain-list
```

```
    command line option, 700
gitlab-project-pages-domain-update
    command line option, 700
gitlab-project-pipeline command line
    option, 701
gitlab-project-pipeline-bridge command
    line option, 703
gitlab-project-pipeline-bridge-list
    command line option, 703
gitlab-project-pipeline-cancel command
    line option, 701
gitlab-project-pipeline-create command
    line option, 701
gitlab-project-pipeline-delete command
    line option, 701
gitlab-project-pipeline-get command
    line option, 702
gitlab-project-pipeline-job command
    line option, 704
gitlab-project-pipeline-job-list
    command line option, 704
gitlab-project-pipeline-list command
    line option, 702
gitlab-project-pipeline-retry command
    line option, 703
gitlab-project-pipeline-schedule
    command line option, 704
gitlab-project-pipeline-schedule-create
    command line option, 705
gitlab-project-pipeline-schedule-delete
    command line option, 705
gitlab-project-pipeline-schedule-get
    command line option, 705
gitlab-project-pipeline-schedule-list
    command line option, 706
gitlab-project-pipeline-schedule-play
    command line option, 706
gitlab-project-pipeline-schedule-take-ownership
    command line option, 706
gitlab-project-pipeline-schedule-update
    command line option, 707
gitlab-project-pipeline-schedule-variable
    command line option, 707
gitlab-project-pipeline-schedule-variable-create
    command line option, 707
gitlab-project-pipeline-schedule-variable-delete
    command line option, 708
gitlab-project-pipeline-schedule-variable-update
    command line option, 708
gitlab-project-pipeline-test-report
    command line option, 709
gitlab-project-pipeline-test-report-get
    command line option, 709
gitlab-project-pipeline-test-report-summary
    command line option, 709
gitlab-project-pipeline-test-report-summary-get
    command line option, 709
gitlab-project-pipeline-variable
    command line option, 710
gitlab-project-pipeline-variable-list
    command line option, 710
gitlab-project-protected-branch command
    line option, 710
gitlab-project-protected-branch-create
    command line option, 711
gitlab-project-protected-branch-delete
    command line option, 711
gitlab-project-protected-branch-get
    command line option, 711
gitlab-project-protected-branch-list
    command line option, 712
gitlab-project-protected-environment
    command line option, 712
gitlab-project-protected-environment-create
    command line option, 712
gitlab-project-protected-environment-delete
    command line option, 713
gitlab-project-protected-environment-get
    command line option, 713
gitlab-project-protected-environment-list
    command line option, 713
gitlab-project-protected-tag command
    line option, 714
gitlab-project-protected-tag-create
    command line option, 714
gitlab-project-protected-tag-delete
    command line option, 714
gitlab-project-protected-tag-get
    command line option, 715
gitlab-project-protected-tag-list
    command line option, 715
gitlab-project-push-rules command line
    option, 715
gitlab-project-push-rules-create
    command line option, 716
gitlab-project-push-rules-delete
    command line option, 716
gitlab-project-push-rules-get command
    line option, 717
gitlab-project-push-rules-update
    command line option, 717
gitlab-project-registry-repository
    command line option, 718
gitlab-project-registry-repository-delete
    command line option, 718
gitlab-project-registry-repository-list
    command line option, 718
gitlab-project-registry-tag command
```

line option, 719
gitlab-project-registry-tag-delete command line option, 719
gitlab-project-registry-tag-delete-in-bulk command line option, 719
gitlab-project-registry-tag-get command line option, 720
gitlab-project-registry-tag-list command line option, 720
gitlab-project-release command line option, 720
gitlab-project-release-create command line option, 721
gitlab-project-release-delete command line option, 721
gitlab-project-release-get command line option, 721
gitlab-project-release-link command line option, 723
gitlab-project-release-link-create command line option, 723
gitlab-project-release-link-delete command line option, 723
gitlab-project-release-link-get command line option, 724
gitlab-project-release-link-list command line option, 724
gitlab-project-release-link-update command line option, 724
gitlab-project-release-list command line option, 722
gitlab-project-release-update command line option, 722
gitlab-project-remote-mirror command line option, 725
gitlab-project-remote-mirror-create command line option, 725
gitlab-project-remote-mirror-list command line option, 725
gitlab-project-remote-mirror-update command line option, 726
gitlab-project-repository-archive command line option, 568
gitlab-project-repository-blob command line option, 568
gitlab-project-repository-compare command line option, 568
gitlab-project-repository-contributors command line option, 569
gitlab-project-repository-merge-base command line option, 569
gitlab-project-repository-raw-blob command line option, 569
gitlab-project-repository-tree command line option, 569
gitlab-project-restore command line option, 570
gitlab-project-runner command line option, 726
gitlab-project-runner-create command line option, 726
gitlab-project-runner-delete command line option, 727
gitlab-project-runner-list command line option, 727
gitlab-project-search command line option, 570
gitlab-project-service command line option, 727
gitlab-project-service-available command line option, 728
gitlab-project-service-delete command line option, 728
gitlab-project-service-get command line option, 728
gitlab-project-service-list command line option, 728
gitlab-project-service-update command line option, 729
gitlab-project-share command line option, 570
gitlab-project-snapshot command line option, 570
gitlab-project-snippet command line option, 729
gitlab-project-snippet-award-emoji command line option, 732
gitlab-project-snippet-award-emoji-create command line option, 732
gitlab-project-snippet-award-emoji-delete command line option, 732
gitlab-project-snippet-award-emoji-get command line option, 733
gitlab-project-snippet-award-emoji-list command line option, 733
gitlab-project-snippet-content command line option, 729
gitlab-project-snippet-create command line option, 730
gitlab-project-snippet-delete command line option, 730
gitlab-project-snippet-discussion command line option, 734
gitlab-project-snippet-discussion-create command line option, 734
gitlab-project-snippet-discussion-get command line option, 734
gitlab-project-snippet-discussion-list command line option, 734

```
    command line option, 735
gitlab-project-snippet-discussion-note      option, 742
    command line option, 735
gitlab-project-snippet-discussion-note-create gitlab-project-transfer command line
    command line option, 735
gitlab-project-snippet-discussion-note-delete gitlab-project-transfer-project command
    command line option, 736
gitlab-project-snippet-discussion-note-get   gitlab-project-trigger command line
    command line option, 736
gitlab-project-snippet-discussion-note-update gitlab-project-trigger-create command
    command line option, 737
gitlab-project-snippet-get command line
    option, 730
gitlab-project-snippet-list command
    line option, 731
gitlab-project-snippet-note command
    line option, 737
gitlab-project-snippet-note-award-emoji      gitlab-project-trigger-delete command
    command line option, 739
gitlab-project-snippet-note-award-emoji-create gitlab-project-trigger-command line
    command line option, 739
gitlab-project-snippet-note-award-emoji-delete gitlab-project-unarchive command line
    command line option, 740
gitlab-project-snippet-note-award-emoji-get   gitlab-project-unshare command line
    command line option, 740
gitlab-project-snippet-note-award-emoji-list  gitlab-project-unstar command line
    command line option, 741
gitlab-project-snippet-note-create           gitlab-project-update command line
    command line option, 737
gitlab-project-snippet-note-delete           gitlab-project-update-submodule command
    command line option, 738
gitlab-project-snippet-note-get command line
    option, 738
gitlab-project-snippet-note-list            gitlab-project-upload command line
    command line option, 738
gitlab-project-snippet-note-update          gitlab-project-user command line option,
    command line option, 739
    745
gitlab-project-snippet-update command line
    option, 731
gitlab-project-snippet-user-agent-detail    gitlab-project-user-list command line
    command line option, 732
    option, 745
gitlab-project-star command line option,
    571
gitlab-project-storage command line
    option, 741
gitlab-project-storage-get command line
    option, 741
gitlab-project-tag command line option,
    742
gitlab-project-tag-create command line
    option, 742
gitlab-project-tag-delete command line
    option, 742
gitlab-project-tag-get command line
    option, 743
gitlab-project-tag-list command line
    option, 743
gitlab-project-transfer command line
    option, 571
gitlab-project-transfer-project command
    line option, 571
gitlab-project-trigger command line
    option, 743
gitlab-project-trigger-create command
    line option, 743
gitlab-project-trigger-delete command
    line option, 744
gitlab-project-trigger-get command line
    option, 744
gitlab-project-trigger-list command
    line option, 744
gitlab-project-trigger-pipeline command
    line option, 571
gitlab-project-trigger-update command
    line option, 745
gitlab-project-unarchive command line
    option, 572
gitlab-project-unshare command line
    option, 572
gitlab-project-unstar command line
    option, 572
gitlab-project-update command line
    option, 574
gitlab-project-update-submodule command
    line option, 576
gitlab-project-upload command line
    option, 576
gitlab-project-user command line option,
    745
gitlab-project-user-list command line
    option, 745
gitlab-project-variable command line
    option, 746
gitlab-project-variable-create command
    line option, 746
gitlab-project-variable-delete command
    line option, 746
gitlab-project-variable-get command
    line option, 747
gitlab-project-variable-list command
    line option, 747
gitlab-project-variable-update command
    line option, 747
gitlab-project-wiki command line option,
    748
gitlab-project-wiki-create command line
    option, 748
gitlab-project-wiki-delete command line
```

```
    option, 748
gitlab-project-wiki-get command line
    option, 749
gitlab-project-wiki-list command line
    option, 749
gitlab-project-wiki-update command line
    option, 749
gitlab-registry-repository command line
    option, 750
gitlab-registry-repository-get command
    line option, 750
gitlab-runner command line option, 750
gitlab-runner-all command line option,
    750, 753
gitlab-runner-all-list command line
    option, 753
gitlab-runner-create command line
    option, 751
gitlab-runner-delete command line
    option, 751
gitlab-runner-get command line option,
    751
gitlab-runner-job command line option,
    754
gitlab-runner-job-list command line
    option, 754
gitlab-runner-list command line option,
    752
gitlab-runner-update command line
    option, 752
gitlab-runner-verify command line
    option, 753
gitlab-shared-project command line
    option, 754
gitlab-shared-project-list command line
    option, 755
gitlab-snippet command line option, 755
gitlab-snippet-content command line
    option, 756
gitlab-snippet-create command line
    option, 756
gitlab-snippet-delete command line
    option, 756
gitlab-snippet-get command line option,
    757
gitlab-snippet-list command line option,
    757
gitlab-snippet-public command line
    option, 757
gitlab-snippet-update command line
    option, 757
gitlab-snippet-user-agent-detail
    command line option, 758
gitlab-starred-project command line
    option, 758
gitlab-starred-project-list command
    line option, 758
gitlab-todo command line option, 759
gitlab-todo-delete command line option,
    759
gitlab-todo-list command line option, 760
gitlab-todo-mark-all-as-done command
    line option, 760
gitlab-todo-mark-as-done command line
    option, 760
gitlab-topic command line option, 761
gitlab-topic-create command line option,
    761
gitlab-topic-delete command line option,
    761
gitlab-topic-get command line option, 761
gitlab-topic-list command line option,
    762
gitlab-topic-update command line option,
    762
gitlab-user command line option, 763
gitlab-user-activate command line
    option, 763
gitlab-user-activities command line
    option, 769
gitlab-user-activities-list command
    line option, 769
gitlab-user-approve command line option,
    763
gitlab-user-ban command line option, 763
gitlab-user-block command line option,
    763
gitlab-user-create command line option,
    764
gitlab-user-custom-attribute command
    line option, 769
gitlab-user-custom-attribute-delete
    command line option, 769
gitlab-user-custom-attribute-get
    command line option, 770
gitlab-user-custom-attribute-list
    command line option, 770
gitlab-user-deactivate command line
    option, 765
gitlab-user-delete command line option,
    765
gitlab-user-email command line option,
    770
gitlab-user-email-create command line
    option, 771
gitlab-user-email-delete command line
    option, 771
gitlab-user-email-get command line
```

```

        option, 771
gitlab-user-email-list command line
    option, 771
gitlab-user-event command line option,
    772
gitlab-user-event-list command line
    option, 772
gitlab-user-follow command line option,
    765
gitlab-user-get command line option, 766
gitlab-user-gpg-key command line option,
    773
gitlab-user-gpg-key-create command line
    option, 773
gitlab-user-gpg-key-delete command line
    option, 773
gitlab-user-gpg-key-get command line
    option, 773
gitlab-user-gpg-key-list command line
    option, 774
gitlab-user-impersonation-token command
    line option, 774
gitlab-user-impersonation-token-create
    command line option, 774
gitlab-user-impersonation-token-delete
    command line option, 775
gitlab-user-impersonation-token-get
    command line option, 775
gitlab-user-impersonation-token-list
    command line option, 775
gitlab-user-key command line option, 776
gitlab-user-key-create command line
    option, 776
gitlab-user-key-delete command line
    option, 776
gitlab-user-key-get command line option,
    776
gitlab-user-key-list command line
    option, 777
gitlab-user-list command line option, 766
gitlab-user-membership command line
    option, 777
gitlab-user-membership-get command line
    option, 777
gitlab-user-membership-list command
    line option, 777
gitlab-user-personal-access-token
    command line option, 778
gitlab-user-personal-access-token-create
    command line option, 778
gitlab-user-project command line option,
    778
gitlab-user-project-create command line
    option, 779
gitlab-user-project-list command line
    option, 780
gitlab-user-reject command line option,
    767
gitlab-user-status command line option,
    781
gitlab-user-status-get command line
    option, 781
gitlab-user-unban command line option,
    767
gitlab-user-unblock command line option,
    767
gitlab-user-unfollow command line
    option, 767
gitlab-user-update command line option,
    768
gitlab-variable command line option, 781
gitlab-variable-create command line
    option, 782
gitlab-variable-delete command line
    option, 782
gitlab-variable-get command line option,
    782
gitlab-variable-list command line
    option, 783
gitlab-variable-update command line
    option, 783
-o gitlab command line option, 460
-v gitlab command line option, 459

```

A

access_tokens (*gitlab.v4.objects.Group attribute*), 203
access_tokens (*gitlab.v4.objects.Project attribute*), 259
AccessLevel (*class in gitlab.const*), 427
AccessRequestMixin (*class in gitlab.mixins*), 445
accessrequests (*gitlab.v4.objects.Group attribute*), 203
accessrequests (*gitlab.v4.objects.Project attribute*), 259
activate() (*gitlab.v4.objects.User method*), 406
add_ldap_group_link() (*gitlab.v4.objects.Group method*), 203
add_spent_time() (*gitlab.mixins.TimeTrackingMixin method*), 452
additionalstatistics (*gitlab.v4.objects.Project attribute*), 259
ADMIN (*gitlab.const.AccessLevel attribute*), 427
all() (*gitlab.v4.objects.RunnerManager method*), 397
api_url (*gitlab.Gitlab property*), 172
api_version (*gitlab.Gitlab property*), 173
appearance (*gitlab.Gitlab attribute*), 173
Application (*class in gitlab.v4.objects*), 182

ApplicationAppearance (*class in gitlab.v4.objects*), 182
ApplicationAppearanceManager (*class in gitlab.v4.objects*), 182
ApplicationManager (*class in gitlab.v4.objects*), 184
applications (*gitlab.Gitlab attribute*), 173
ApplicationSettings (*class in gitlab.v4.objects*), 184
ApplicationSettingsManager (*class in gitlab.v4.objects*), 184
approval() (*gitlab.v4.objects.ProjectDeployment method*), 289
approval_rule_id (*gitlab.v4.objects.ProjectMergeRequestApprovalRule attribute*), 339
approval_rules (*gitlab.v4.objects.ProjectMergeRequest attribute*), 334
approval_state (*gitlab.v4.objects.ProjectMergeRequest attribute*), 334
approvalrules (*gitlab.v4.objects.Project attribute*), 259
approvals (*gitlab.v4.objects.Project attribute*), 259
approvals (*gitlab.v4.objects.ProjectMergeRequest attribute*), 334
approve() (*gitlab.mixins.AccessRequestMixin method*), 445
approve() (*gitlab.v4.objects.ProjectMergeRequest method*), 334
approve() (*gitlab.v4.objects.User method*), 406
archive() (*gitlab.v4.objects.Project method*), 259
artifact() (*gitlab.v4.objects.Project method*), 259
artifact() (*gitlab.v4.objects.ProjectJob method*), 318
artifacts (*gitlab.v4.objects.Project attribute*), 260
artifacts() (*gitlab.v4.objects.ProjectJob method*), 318
asdict() (*gitlab.base.RESTObject method*), 424
attributes (*gitlab.base.RESTObject property*), 424
audit_events (*gitlab.Gitlab attribute*), 173
audit_events (*gitlab.v4.objects.Group attribute*), 203
audit_events (*gitlab.v4.objects.Project attribute*), 260
AuditEvent (*class in gitlab.v4.objects*), 187
AuditEventManager (*class in gitlab.v4.objects*), 187
auth() (*gitlab.Gitlab method*), 173
available() (*gitlab.v4.objects.ProjectIntegrationManager method*), 303
awardemojis (*gitlab.v4.objects.GroupEpicNote attribute*), 222
awardemojis (*gitlab.v4.objects.ProjectIssue attribute*), 305
awardemojis (*gitlab.v4.objects.ProjectIssueNote attribute*), 312
awardemojis (*gitlab.v4.objects.ProjectMergeRequest attribute*), 334
awardemojis (*gitlab.v4.objects.ProjectMergeRequestNote attribute*), 347
awardemojis (*gitlab.v4.objects.ProjectSnippet attribute*), 378
awardemojis (*gitlab.v4.objects.ProjectSnippetNote attribute*), 383

B

BadgeRenderMixin (*class in gitlab.mixins*), 446
badges (*gitlab.v4.objects.Group attribute*), 203
badges (*gitlab.v4.objects.Project attribute*), 260
ban() (*gitlab.v4.objects.User method*), 406
billable_members (*gitlab.v4.objects.Group attribute*), 203
blame() (*gitlab.v4.objects.ProjectFileManager method*), 297
BLOBS (*gitlab.const.SearchScope attribute*), 427
block() (*gitlab.v4.objects.User method*), 407
boards (*gitlab.v4.objects.Group attribute*), 203
boards (*gitlab.v4.objects.Project attribute*), 260
branch (*gitlab.v4.objects.ProjectFile attribute*), 295
branches (*gitlab.v4.objects.Project attribute*), 260
bridges (*gitlab.v4.objects.ProjectPipeline attribute*), 360
BroadcastMessage (*class in gitlab.v4.objects*), 188
BroadcastMessageManager (*class in gitlab.v4.objects*), 188
broadcastmessages (*gitlab.Gitlab attribute*), 173

C

cancel() (*gitlab.v4.objects.ProjectJob method*), 319
cancel() (*gitlab.v4.objects.ProjectPipeline method*), 360
cancel_merge_when_pipeline_succeeds() (*gitlab.v4.objects.ProjectMergeRequest method*), 334
changes() (*gitlab.v4.objects.ProjectMergeRequest method*), 334
cherry_pick() (*gitlab.v4.objects.ProjectCommit method*), 280
ci_lint (*gitlab.Gitlab attribute*), 173
ci_lint (*gitlab.v4.objects.Project attribute*), 260
CiLint (*class in gitlab.v4.objects*), 189
CiLintManager (*class in gitlab.v4.objects*), 189
closed_by() (*gitlab.v4.objects.ProjectIssue method*), 305
closes_issues() (*gitlab.v4.objects.ProjectMergeRequest method*), 335
cls_to_gitlab_resource() (*in module gitlab.cli*), 425
clusters (*gitlab.v4.objects.Group attribute*), 204
clusters (*gitlab.v4.objects.Project attribute*), 260
comments (*gitlab.v4.objects.ProjectCommit attribute*), 281
commit_message (*gitlab.v4.objects.ProjectFile attribute*), 295
COMMITS (*gitlab.const.SearchScope attribute*), 427

commits (*gitlab.v4.objects.Project attribute*), 260
commits() (*gitlab.v4.objects.ProjectMergeRequest method*), 335
compound_metrics() (*gitlab.v4.objects.SidekiqManager method*), 399
ConfigError, 426
content() (*gitlab.v4.objects.ProjectSnippet method*), 378
content() (*gitlab.v4.objects.Snippet method*), 401
copy_dict() (*in module gitlab.utils*), 454
create() (*gitlab.mixins.CreateMixin method*), 446
create() (*gitlab.v4.objects.GroupClusterManager method*), 213
create() (*gitlab.v4.objects.GroupEpicIssueManager method*), 220
create() (*gitlab.v4.objects.ProjectClusterManager method*), 279
create() (*gitlab.v4.objects.ProjectCommitStatusManager method*), 287
create() (*gitlab.v4.objects.ProjectFileManager method*), 297
create() (*gitlab.v4.objects.ProjectForkManager method*), 300
create() (*gitlab.v4.objects.ProjectIssueLinkManager method*), 310
create() (*gitlab.v4.objects.ProjectMergeRequestApproval method*), 340
create() (*gitlab.v4.objects.ProjectPipelineManager method*), 362
create_fork_relation() (*gitlab.v4.objects.Project method*), 260
CreateMixin (*class in gitlab.mixins*), 446
CRUDMixin (*class in gitlab.mixins*), 446
current_failures() (*gitlab.v4.objects.GeoNodeManager method*), 200
current_page (*gitlab.base.RESTObjectList property*), 424
current_page (*gitlab.GitlabList property*), 181
CurrentUser (*class in gitlab.v4.objects*), 190
CurrentUserEmail (*class in gitlab.v4.objects*), 190
CurrentUserEmailManager (*class in gitlab.v4.objects*), 191
CurrentUserGPGKey (*class in gitlab.v4.objects*), 191
CurrentUserGPGKeyManager (*class in gitlab.v4.objects*), 191
CurrentUserKey (*class in gitlab.v4.objects*), 192
CurrentUserKeyManager (*class in gitlab.v4.objects*), 192
CurrentUserManager (*class in gitlab.v4.objects*), 193
CurrentUserStatus (*class in gitlab.v4.objects*), 193
CurrentUserStatusManager (*class in gitlab.v4.objects*), 194
CUSTOM (*gitlab.const.NotificationLevel attribute*), 427
custom_attributes (*gitlab.v4.objects.Group attribute*), 204
custom_attributes (*gitlab.v4.objects.Project attribute*), 260
custom_attributes (*gitlab.v4.objects.User attribute*), 407

D

deactivate() (*gitlab.v4.objects.User method*), 407
decode() (*gitlab.v4.objects.ProjectFile method*), 295
delete() (*gitlab.mixins.DeleteMixin method*), 447
delete() (*gitlab.mixins.ObjectDeleteMixin method*), 449
delete() (*gitlab.v4.objects.ProjectArtifactManager method*), 271
delete() (*gitlab.v4.objects.ProjectFile method*), 295
delete() (*gitlab.v4.objects.ProjectFileManager method*), 297
delete_artifacts() (*gitlab.v4.objects.ProjectJob method*), 319
delete_fork_relation() (*gitlab.v4.objects.Project method*), 260
delete_in_bulk() (*gitlab.v4.objects.ProjectRegistryTagManager method*), 373
del_member_group_link() (*gitlab.v4.objects.Group method*), 204
delete_merged_branches() (*gitlab.v4.objects.RepositoryMixin method*), 391
DeleteMixin (*class in gitlab.mixins*), 447
DeployKey (*class in gitlab.v4.objects*), 194
DeployKeyManager (*class in gitlab.v4.objects*), 194
deploykeys (*gitlab.Gitlab attribute*), 173
deployments (*gitlab.v4.objects.Project attribute*), 260
DeployToken (*class in gitlab.v4.objects*), 195
DeployTokenManager (*class in gitlab.v4.objects*), 195
deploytokens (*gitlab.Gitlab attribute*), 173
deploytokens (*gitlab.v4.objects.Group attribute*), 204
deploytokens (*gitlab.v4.objects.Project attribute*), 260
descendant_groups (*gitlab.v4.objects.Group attribute*), 204
DEVELOPER (*gitlab.const.AccessLevel attribute*), 427
die() (*in module gitlab.cli*), 425
diff() (*gitlab.v4.objects.ProjectCommit method*), 281
diffs (*gitlab.v4.objects.ProjectMergeRequest attribute*), 335
DISABLED (*gitlab.const.NotificationLevel attribute*), 427
discussions (*gitlab.v4.objects.ProjectCommit attribute*), 281
discussions (*gitlab.v4.objects.ProjectIssue attribute*), 305

`discussions` (*gitlab.v4.objects.ProjectMergeRequest attribute*), 336
`discussions` (*gitlab.v4.objects.ProjectSnippet attribute*), 379

`Dockerfile` (*class in gitlab.v4.objects*), 195
`DockerfileManager` (*class in gitlab.v4.objects*), 195
`dockerfiles` (*gitlab.Gitlab attribute*), 173
`docs()` (*in module gitlab.cli*), 425
`download()` (*gitlab.mixins.DownloadMixin method*), 447
`download()` (*gitlab.v4.objects.GenericPackageManager method*), 198
`download()` (*gitlab.v4.objects.ProjectArtifactManager method*), 271
`DownloadMixin` (*class in gitlab.mixins*), 447

E

`emails` (*gitlab.v4.objects.CurrentUser attribute*), 190
`emails` (*gitlab.v4.objects.User attribute*), 407
`enable()` (*gitlab.v4.objects.ProjectKeyManager method*), 322
`enable_debug()` (*gitlab.Gitlab static method*), 173
`encoded_id` (*gitlab.base.RESTObject property*), 424
`EncodedId` (*class in gitlab.utils*), 454
`environments` (*gitlab.v4.objects.Project attribute*), 260
`epics` (*gitlab.v4.objects.Group attribute*), 204
`erase()` (*gitlab.v4.objects.ProjectJob method*), 319
`Event` (*class in gitlab.v4.objects*), 196
`EventManager` (*class in gitlab.v4.objects*), 196
`events` (*gitlab.Gitlab attribute*), 173
`events` (*gitlab.v4.objects.Project attribute*), 260
`events` (*gitlab.v4.objects.User attribute*), 407
`exists()` (*gitlab.v4.objects.NamespaceManager method*), 256
`exports` (*gitlab.v4.objects.Group attribute*), 204
`exports` (*gitlab.v4.objects.Project attribute*), 260

F

`Feature` (*class in gitlab.v4.objects*), 197
`FeatureManager` (*class in gitlab.v4.objects*), 197
`features` (*gitlab.Gitlab attribute*), 173
`file_path` (*gitlab.v4.objects.ProjectFile attribute*), 295
`files` (*gitlab.v4.objects.Project attribute*), 261
`follow()` (*gitlab.v4.objects.User method*), 407
`followers_users` (*gitlab.v4.objects.User attribute*), 408
`following_users` (*gitlab.v4.objects.User attribute*), 408
`forks` (*gitlab.v4.objects.Project attribute*), 261
`format_help()` (*gitlab.cli.VerticalHelpFormatter method*), 425
`from_config()` (*gitlab.Gitlab class method*), 173

G

`generic_packages` (*gitlab.v4.objects.Project attribute*), 261
`GenericPackage` (*class in gitlab.v4.objects*), 198
`GenericPackageManager` (*class in gitlab.v4.objects*), 198
`GeoNode` (*class in gitlab.v4.objects*), 199
`GeoNodeManager` (*class in gitlab.v4.objects*), 200
`geonodes` (*gitlab.Gitlab attribute*), 174
`get()` (*gitlab.mixins.GetMixin method*), 448
`get()` (*gitlab.mixins.GetWithoutIdMixin method*), 448
`get()` (*gitlab.v4.objects.ApplicationAppearanceManager method*), 183
`get()` (*gitlab.v4.objects.ApplicationSettingsManager method*), 186
`get()` (*gitlab.v4.objects.AuditEventManager method*), 187
`get()` (*gitlab.v4.objects.BroadcastMessageManager method*), 189
`get()` (*gitlab.v4.objects.CurrentUserEmailManager method*), 191
`get()` (*gitlab.v4.objects.CurrentUserGPGKeyManager method*), 192
`get()` (*gitlab.v4.objects.CurrentUserKeyManager method*), 193
`get()` (*gitlab.v4.objects.CurrentUserManager method*), 193
`get()` (*gitlab.v4.objects.CurrentUserStatusManager method*), 194
`get()` (*gitlab.v4.objects.DockerfileManager method*), 196
`get()` (*gitlab.v4.objects.GeoNodeManager method*), 200
`get()` (*gitlab.v4.objects.IgnoreManager method*), 202
`get()` (*gitlab.v4.objects.GitlabciymlManager method*), 202
`get()` (*gitlab.v4.objects.GroupAuditEventManager method*), 208
`get()` (*gitlab.v4.objects.GroupBadgeManager method*), 209
`get()` (*gitlab.v4.objects.GroupBoardListManager method*), 211
`get()` (*gitlab.v4.objects.GroupBoardManager method*), 212
`get()` (*gitlab.v4.objects.GroupClusterManager method*), 214
`get()` (*gitlab.v4.objects.GroupCustomAttributeManager method*), 215
`get()` (*gitlab.v4.objects.GroupDeployTokenManager method*), 216
`get()` (*gitlab.v4.objects.GroupEpicAwardEmojiManager method*), 218
`get()` (*gitlab.v4.objects.GroupEpicDiscussionNoteManager method*), 219

get()	(gitlab.v4.objects.GroupEpicManager method),	method), 275
221		
get()	(gitlab.v4.objects.GroupEpicNoteAwardEmojiManager method),	276
222		
get()	(gitlab.v4.objects.GroupEpicNoteManager method),	277
223		
get()	(gitlab.v4.objects.GroupEpicResourceLabelEventManager method),	278
224		
get()	(gitlab.v4.objects.GroupExportManager method),	279
225		
get()	(gitlab.v4.objects.GroupHookManager method),	280
226		
get()	(gitlab.v4.objects.GroupImportManager method),	281
227		
get()	(gitlab.v4.objects.GroupInvitationManager method),	282
228		
get()	(gitlab.v4.objects.GroupIssuesStatisticsManager method),	283
230		
get()	(gitlab.v4.objects.GroupLabelManager method),	284
232		
get()	(gitlab.v4.objects.GroupManager method),	285
get()	(gitlab.v4.objects.GroupMemberAllManager method),	286
get()	(gitlab.v4.objects.GroupMemberManager method),	287
get()	(gitlab.v4.objects.GroupMilestoneManager method),	288
get()	(gitlab.v4.objects.GroupNotificationSettingsManager method),	289
get()	(gitlab.v4.objects.GroupPushRulesManager method),	290
get()	(gitlab.v4.objects.GroupVariableManager method),	291
get()	(gitlab.v4.objects.GroupWikiManager method),	292
get()	(gitlab.v4.objects.HookManager method),	293
get()	(gitlab.v4.objects.IssueManager method),	294
get()	(gitlab.v4.objects.IssuesStatisticsManager method),	295
get()	(gitlab.v4.objects.KeyManager method),	296
get()	(gitlab.v4.objects.LicenseManager method),	297
get()	(gitlab.v4.objects.NamespaceManager method),	298
get()	(gitlab.v4.objects.NotificationSettingsManager method),	299
get()	(gitlab.v4.objects.ProjectAdditionalStatisticsManager method),	300
get()	(gitlab.v4.objects.ProjectApprovalManager method),	301
get()	(gitlab.v4.objects.ProjectAuditEventManager method),	302
get()	(gitlab.v4.objects.ProjectBadgeManager method),	303
get()	(gitlab.v4.objects.ProjectBoardListManager	

```
        method), 317
get() (gitlab.v4.objects.ProjectJobManager method),
      321
get() (gitlab.v4.objects.ProjectKeyManager method),
      322
get() (gitlab.v4.objects.ProjectLabelManager method),
      324
get() (gitlab.v4.objects.ProjectManager method), 329
get() (gitlab.v4.objects.ProjectMemberAllManager
      method), 332
get() (gitlab.v4.objects.ProjectMemberManager
      method), 333
get() (gitlab.v4.objects.ProjectMergeRequestApprovalManager
      method), 338
get() (gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager
      method), 340
get() (gitlab.v4.objects.ProjectMergeRequestApprovalStateManager
      method), 341
get() (gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager
      method), 342
get() (gitlab.v4.objects.ProjectMergeRequestDiffManager
      method), 343
get() (gitlab.v4.objects.ProjectMergeRequestDiscussionManager
      method), 344
get() (gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager
      method), 345
get() (gitlab.v4.objects.ProjectMergeRequestManager
      method), 347
get() (gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager
      method), 348
get() (gitlab.v4.objects.ProjectMergeRequestNoteManager
      method), 349
get() (gitlab.v4.objects.ProjectMergeRequestResourceLabelManager
      method), 350
get() (gitlab.v4.objects.ProjectMergeRequestResourceMilestoneManager
      method), 351
get() (gitlab.v4.objects.ProjectMergeRequestResourceStateManager
      method), 352
get() (gitlab.v4.objects.ProjectMilestoneManager
      method), 355
get() (gitlab.v4.objects.ProjectNoteManager method),
      355
get() (gitlab.v4.objects.ProjectNotificationSettingsManager
      method), 357
get() (gitlab.v4.objects.ProjectPackageManager
      method), 358
get() (gitlab.v4.objects.ProjectPagesDomainManager
      method), 359
get() (gitlab.v4.objects.ProjectPipelineManager
      method), 362
get() (gitlab.v4.objects.ProjectPipelineScheduleManager
      method), 364
get() (gitlab.v4.objects.ProjectPipelineTestReportManager
      method), 366
get() (gitlab.v4.objects.ProjectProtectedBranchManager
      method), 368
get() (gitlab.v4.objects.ProjectProtectedEnvironmentManager
      method), 369
get() (gitlab.v4.objects.ProjectProtectedTagManager
      method), 370
get() (gitlab.v4.objects.ProjectPushRulesManager
      method), 372
get() (gitlab.v4.objects.ProjectRegistryTagManager
      method), 373
get() (gitlab.v4.objects.ProjectReleaseLinkManager
      method), 375
get() (gitlab.v4.objects.ProjectReleaseManager
      method), 376
get() (gitlab.v4.objects.ProjectServiceManager
      method), 378
get() (gitlab.v4.objects.ProjectSnippetAwardEmojiManager
      method), 380
get() (gitlab.v4.objects.ProjectSnippetDiscussionManager
      method), 380
get() (gitlab.v4.objects.ProjectSnippetDiscussionNoteManager
      method), 382
get() (gitlab.v4.objects.ProjectSnippetManager
      method), 382
get() (gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager
      method), 384
get() (gitlab.v4.objects.ProjectSnippetNoteManager
      method), 384
get() (gitlab.v4.objects.ProjectStorageManager
      method), 385
get() (gitlab.v4.objects.ProjectTagManager
      method), 386
get() (gitlab.v4.objects.ProjectTriggerManager
      method), 387
get() (gitlab.v4.objects.ProjectVariableManager
      method), 389
get() (gitlab.v4.objects.ProjectWikiManager
      method), 390
get() (gitlab.v4.objects.RegistryRepositoryManager
      method), 391
get() (gitlab.v4.objects.RunnerManager method), 398
get() (gitlab.v4.objects.SnippetManager method), 402
get() (gitlab.v4.objects.TopicManager method), 405
get() (gitlab.v4.objects.UserCustomAttributeManager
      method), 410
get() (gitlab.v4.objects.UserEmailManager method),
      411
get() (gitlab.v4.objects.UserGPGKeyManager method),
      412
get() (gitlab.v4.objects.UserImpersonationTokenManager
      method), 414
get() (gitlab.v4.objects.UserKeyManager method), 415
```

get()	(gitlab.v4.objects.UserManager method),	417		
get()	(gitlab.v4.objects.UserMembershipManager method),	418	gitlab	(gitlab.v4.objects.GenericPackageManager attribute),
get()	(gitlab.v4.objects.UserStatusManager method),	421	gitlab	(gitlab.v4.objects.GeoNodeManager attribute),
get()	(gitlab.v4.objects.VariableManager method),	422	gitlab	(gitlab.v4.objects.GitignoreManager attribute),
get_id()	(gitlab.base.RESTObject method),	424	gitlab	(gitlab.v4.objects.GitlabcimlManager attribute),
get_license()	(gitlab.Gitlab method),	174	gitlab	(gitlab.v4.objects.GroupAccessRequestManager attribute),
GetMixin	(class in gitlab.mixins),	447	gitlab	(gitlab.v4.objects.GroupAccessTokenManager attribute),
GetWithoutIdMixin	(class in gitlab.mixins),	448	gitlab	(gitlab.v4.objects.GroupAuditEventManager attribute),
Gitignore	(class in gitlab.v4.objects),	201	gitlab	(gitlab.v4.objects.GroupBadgeManager attribute),
GitignoreManager	(class in gitlab.v4.objects),	201	gitlab	(gitlab.v4.objects.GroupBillableMemberManager attribute),
gitignores	(gitlab.Gitlab attribute),	174	gitlab	(gitlab.v4.objects.GroupBillableMemberMembershipManager attribute),
Gitlab	(class in gitlab),	172	gitlab	(gitlab.v4.objects.GroupBoardListManager attribute),
gitlab	(gitlab.base.RESTManager attribute),	423	gitlab	(gitlab.v4.objects.GroupBoardManager attribute),
gitlab	(gitlab.mixins.CreateMixin attribute),	447	gitlab	(gitlab.v4.objects.GroupClusterManager attribute),
gitlab	(gitlab.mixins.CRUDMixin attribute),	446	gitlab	(gitlab.v4.objects.GroupCustomAttributeManager attribute),
gitlab	(gitlab.mixins.DeleteMixin attribute),	447	gitlab	(gitlab.v4.objects.GroupDeployTokenManager attribute),
gitlab	(gitlab.mixins.GetMixin attribute),	448	gitlab	(gitlab.v4.objects.GroupEpicAwardEmojiManager attribute),
gitlab	(gitlab.mixins.GetWithoutIdMixin attribute),	448	gitlab	(gitlab.v4.objects.GroupEpicDiscussionNoteManager attribute),
gitlab	(gitlab.mixins.ListMixin attribute),	448	gitlab	(gitlab.v4.objects.GroupEpicIssueManager attribute),
gitlab	(gitlab.mixins.NoUpdateMixin attribute),	449	gitlab	(gitlab.v4.objects.GroupEpicManager attribute),
gitlab	(gitlab.mixins.RetrieveMixin attribute),	450	gitlab	(gitlab.v4.objects.GroupEpicNoteAwardEmojiManager attribute),
gitlab	(gitlab.mixins.SetMixin attribute),	451	gitlab	(gitlab.v4.objects.GroupEpicNoteManager attribute),
gitlab	(gitlab.mixins.UpdateMixin attribute),	453	gitlab	(gitlab.v4.objects.GroupEpicResourceLabelEventManager attribute),
gitlab	(gitlab.v4.objects.ApplicationAppearanceManager attribute),	183	gitlab	(gitlab.v4.objects.GroupExportManager attribute),
gitlab	(gitlab.v4.objects.ApplicationManager attribute),	184	gitlab	(gitlab.v4.objects.GroupHookManager attribute),
gitlab	(gitlab.v4.objects.ApplicationSettingsManager attribute),	186	gitlab	(gitlab.v4.objects.GroupImportManager attribute),
gitlab	(gitlab.v4.objects.AuditEventManager attribute),	188	gitlab	(gitlab.v4.objects.GroupInvitationManager attribute),
gitlab	(gitlab.v4.objects.BroadcastMessageManager attribute),	189	gitlab	(gitlab.v4.objects.GroupIssueManager attribute),
gitlab	(gitlab.v4.objects.CiLintManager attribute),	190		
gitlab	(gitlab.v4.objects.CurrentUserEmailManager attribute),	191		
gitlab	(gitlab.v4.objects.CurrentUserGPGKeyManager attribute),	192		
gitlab	(gitlab.v4.objects.CurrentUserKeyManager attribute),	193		
gitlab	(gitlab.v4.objects.CurrentUserManager attribute),	193		
gitlab	(gitlab.v4.objects.CurrentUserStatusManager attribute),	194		
gitlab	(gitlab.v4.objects.DeployKeyManager attribute),	195		
gitlab	(gitlab.v4.objects.DeployTokenManager attribute),	195		
gitlab	(gitlab.v4.objects.DockerfileManager attribute),	196		
gitlab	(gitlab.v4.objects.EventManager attribute),	197		
gitlab	(gitlab.v4.objects.FeatureManager attribute),			

230
gitlab (*gitlab.v4.objects.GroupIssuesStatisticsManager attribute*), 230
gitlab (*gitlab.v4.objects.GroupIterationManager attribute*), 231
gitlab (*gitlab.v4.objects.GroupLabelManager attribute*), 232
gitlab (*gitlab.v4.objects.GroupManager attribute*), 235
gitlab (*gitlab.v4.objects.GroupMemberAllManager attribute*), 236
gitlab (*gitlab.v4.objects.GroupMemberManager attribute*), 237
gitlab (*gitlab.v4.objects.GroupMergeRequestManager attribute*), 238
gitlab (*gitlab.v4.objects.GroupMilestoneManager attribute*), 240
gitlab (*gitlab.v4.objects.GroupNotificationSettingsManager attribute*), 241
gitlab (*gitlab.v4.objects.GroupPackageManager attribute*), 242
gitlab (*gitlab.v4.objects.GroupProjectManager attribute*), 243
gitlab (*gitlab.v4.objects.GroupPushRulesManager attribute*), 244
gitlab (*gitlab.v4.objects.GroupRegistryRepositoryManager attribute*), 245
gitlab (*gitlab.v4.objects.GroupRunnerManager attribute*), 245
gitlab (*gitlab.v4.objects.GroupVariableManager attribute*), 247
gitlab (*gitlab.v4.objects.GroupWikiManager attribute*), 248
gitlab (*gitlab.v4.objects.HookManager attribute*), 249
gitlab (*gitlab.v4.objects.IssueManager attribute*), 251
gitlab (*gitlab.v4.objects.IssuesStatisticsManager attribute*), 251
gitlab (*gitlab.v4.objects.KeyManager attribute*), 252
gitlab (*gitlab.v4.objects.LDAPGroupManager attribute*), 253
gitlab (*gitlab.v4.objects.LicenseManager attribute*), 254
gitlab (*gitlab.v4.objects.MergeRequestManager attribute*), 255
gitlab (*gitlab.v4.objects.NamespaceManager attribute*), 257
gitlab (*gitlab.v4.objects.NotificationSettingsManager attribute*), 258
gitlab (*gitlab.v4.objects.PagesDomainManager attribute*), 258
gitlab (*gitlab.v4.objects.PersonalAccessTokenManager attribute*), 259
gitlab (*gitlab.v4.objects.ProjectAccessRequestManager attribute*), 267
gitlab (*gitlab.v4.objects.ProjectAccessTokenManager attribute*), 267
gitlab (*gitlab.v4.objects.ProjectAdditionalStatisticsManager attribute*), 268
gitlab (*gitlab.v4.objects.ProjectApprovalManager attribute*), 269
gitlab (*gitlab.v4.objects.ProjectApprovalRuleManager attribute*), 270
gitlab (*gitlab.v4.objects.ProjectArtifactManager attribute*), 271
gitlab (*gitlab.v4.objects.ProjectAuditEventManager attribute*), 273
gitlab (*gitlab.v4.objects.ProjectAuditManager attribute*), 274
gitlab (*gitlab.v4.objects.ProjectBadgeManager attribute*), 275
gitlab (*gitlab.v4.objects.ProjectBoardListManager attribute*), 276
gitlab (*gitlab.v4.objects.ProjectBoardManager attribute*), 276
gitlab (*gitlab.v4.objects.ProjectBranchManager attribute*), 277
gitlab (*gitlab.v4.objects.ProjectCiLintManager attribute*), 278
gitlab (*gitlab.v4.objects.ProjectClusterManager attribute*), 280
gitlab (*gitlab.v4.objects.ProjectCommitCommentManager attribute*), 283
gitlab (*gitlab.v4.objects.ProjectCommitDiscussionManager attribute*), 284
gitlab (*gitlab.v4.objects.ProjectCommitDiscussionNoteManager attribute*), 285
gitlab (*gitlab.v4.objects.ProjectCommitManager attribute*), 286
gitlab (*gitlab.v4.objects.ProjectCommitStatusManager attribute*), 287
gitlab (*gitlab.v4.objects.ProjectCustomAttributeManager attribute*), 288
gitlab (*gitlab.v4.objects.ProjectDeploymentManager attribute*), 291
gitlab (*gitlab.v4.objects.ProjectDeploymentMergeRequestManager attribute*), 292
gitlab (*gitlab.v4.objects.ProjectDeployTokenManager attribute*), 289
gitlab (*gitlab.v4.objects.ProjectEnvironmentManager attribute*), 293
gitlab (*gitlab.v4.objects.ProjectEventManager attribute*), 294
gitlab (*gitlab.v4.objects.ProjectExportManager attribute*), 295
gitlab (*gitlab.v4.objects.ProjectFileManager attribute*), 298
gitlab (*gitlab.v4.objects.ProjectForkManager attribute*), 300
gitlab (*gitlab.v4.objects.ProjectHookManager attribute*), 300

tribute), 302
`gitlab` (`gitlab.v4.objects.ProjectImportManager` attribute), 302
`gitlab` (`gitlab.v4.objects.ProjectIntegrationManager` attribute), 303
`gitlab` (`gitlab.v4.objects.ProjectInvitationManager` attribute), 305
`gitlab` (`gitlab.v4.objects.ProjectIssueAwardEmojiManager` attribute), 307
`gitlab` (`gitlab.v4.objects.ProjectIssueDiscussionManager` attribute), 308
`gitlab` (`gitlab.v4.objects.ProjectIssueDiscussionNoteManager` attribute), 309
`gitlab` (`gitlab.v4.objects.ProjectIssueLinkManager` attribute), 310
`gitlab` (`gitlab.v4.objects.ProjectIssueManager` attribute), 312
`gitlab` (`gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager` attribute), 313
`gitlab` (`gitlab.v4.objects.ProjectIssueNoteManager` attribute), 314
`gitlab` (`gitlab.v4.objects.ProjectIssueResourceLabelEventManager` attribute), 315
`gitlab` (`gitlab.v4.objects.ProjectIssueResourceMilestoneEventManager` attribute), 315
`gitlab` (`gitlab.v4.objects.ProjectIssueResourceStateEventManager` attribute), 316
`gitlab` (`gitlab.v4.objects.ProjectIssuesStatisticsManager` attribute), 317
`gitlab` (`gitlab.v4.objects.ProjectIterationManager` attribute), 317
`gitlab` (`gitlab.v4.objects.ProjectJobManager` attribute), 321
`gitlab` (`gitlab.v4.objects.ProjectKeyManager` attribute), 322
`gitlab` (`gitlab.v4.objects.ProjectLabelManager` attribute), 324
`gitlab` (`gitlab.v4.objects.ProjectManager` attribute), 329
`gitlab` (`gitlab.v4.objects.ProjectMemberAllManager` attribute), 333
`gitlab` (`gitlab.v4.objects.ProjectMemberManager` attribute), 333
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestApprovalManager` attribute), 338
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestApprovalRuleManager` attribute), 340
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestApprovalStatusManager` attribute), 341
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager` attribute), 342
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestDiffManager` attribute), 343
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestDiscussionManager` attribute), 344
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager` attribute), 345
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestManager` attribute), 347
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager` attribute), 348
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestNoteManager` attribute), 349
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestPipelineManager` attribute), 350
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestResourceLabelEventManager` attribute), 351
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEventManager` attribute), 351
`gitlab` (`gitlab.v4.objects.ProjectMergeRequestResourceStateEventManager` attribute), 352
`gitlab` (`gitlab.v4.objects.ProjectMergeTrainManager` attribute), 353
`gitlab` (`gitlab.v4.objects.ProjectMilestoneManager` attribute), 355
`gitlab` (`gitlab.v4.objects.ProjectNoteManager` attribute), 356
`gitlab` (`gitlab.v4.objects.ProjectNotificationSettingsManager` attribute), 357
`gitlab` (`gitlab.v4.objects.ProjectPackageFileManager` attribute), 358
`gitlab` (`gitlab.v4.objects.ProjectPackageManager` attribute), 358
`gitlab` (`gitlab.v4.objects.ProjectPagesDomainManager` attribute), 360
`gitlab` (`gitlab.v4.objects.ProjectPipelineBridgeManager` attribute), 361
`gitlab` (`gitlab.v4.objects.ProjectPipelineJobManager` attribute), 361
`gitlab` (`gitlab.v4.objects.ProjectPipelineManager` attribute), 363
`gitlab` (`gitlab.v4.objects.ProjectPipelineScheduleManager` attribute), 364
`gitlab` (`gitlab.v4.objects.ProjectPipelineScheduleVariableManager` attribute), 365
`gitlab` (`gitlab.v4.objects.ProjectPipelineTestReportManager` attribute), 366
`gitlab` (`gitlab.v4.objects.ProjectPipelineTestReportSummaryManager` attribute), 367
`gitlab` (`gitlab.v4.objects.ProjectPipelineVariableManager` attribute), 367
`gitlab` (`gitlab.v4.objects.ProjectProtectedBranchManager` attribute), 368
`gitlab` (`gitlab.v4.objects.ProjectProtectedEnvironmentManager` attribute), 369
`gitlab` (`gitlab.v4.objects.ProjectProtectedTagManager` attribute), 370
`gitlab` (`gitlab.v4.objects.ProjectPushRulesManager` attribute), 372

gitlab (*gitlab.v4.objects.ProjectRegistryRepositoryManager attribute*), 372
gitlab (*gitlab.v4.objects.ProjectRegistryTagManager attribute*), 374
gitlab (*gitlab.v4.objects.ProjectReleaseLinkManager attribute*), 375
gitlab (*gitlab.v4.objects.ProjectReleaseManager attribute*), 376
gitlab (*gitlab.v4.objects.ProjectRemoteMirrorManager attribute*), 377
gitlab (*gitlab.v4.objects.ProjectRunnerManager attribute*), 377
gitlab (*gitlab.v4.objects.ProjectServiceManager attribute*), 378
gitlab (*gitlab.v4.objects.ProjectSnippetAwardEmojiManager attribute*), 380
gitlab (*gitlab.v4.objects.ProjectSnippetDiscussionManager attribute*), 381
gitlab (*gitlab.v4.objects.ProjectSnippetDiscussionNoteManager attribute*), 382
gitlab (*gitlab.v4.objects.ProjectSnippetManager attribute*), 383
gitlab (*gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager attribute*), 384
gitlab (*gitlab.v4.objects.ProjectSnippetNoteManager attribute*), 385
gitlab (*gitlab.v4.objects.ProjectStorageManager attribute*), 385
gitlab (*gitlab.v4.objects.ProjectTagManager attribute*), 386
gitlab (*gitlab.v4.objects.ProjectTriggerManager attribute*), 387
gitlab (*gitlab.v4.objects.ProjectUserManager attribute*), 388
gitlab (*gitlab.v4.objects.ProjectVariableManager attribute*), 389
gitlab (*gitlab.v4.objects.ProjectWikiManager attribute*), 390
gitlab (*gitlab.v4.objects.RegistryRepositoryManager attribute*), 391
gitlab (*gitlab.v4.objects.RunnerAllManager attribute*), 396
gitlab (*gitlab.v4.objects.RunnerJobManager attribute*), 396
gitlab (*gitlab.v4.objects.RunnerManager attribute*), 398
gitlab (*gitlab.v4.objects.SharedProjectManager attribute*), 399
gitlab (*gitlab.v4.objects.SidekiqManager attribute*), 400
gitlab (*gitlab.v4.objects.SnippetManager attribute*), 402
gitlab (*gitlab.v4.objects.StarredProjectManager attribute*), 403
gitlab (*gitlab.v4.objects.TodoManager attribute*), 404
gitlab (*gitlab.v4.objects.TopicManager attribute*), 406
gitlab (*gitlab.v4.objects.UserActivitiesManager attribute*), 409
gitlab (*gitlab.v4.objects.UserCustomAttributeManager attribute*), 410
gitlab (*gitlab.v4.objects.UserEmailManager attribute*), 411
gitlab (*gitlab.v4.objects.UserEventManager attribute*), 412
gitlab (*gitlab.v4.objects.UserGPGKeyManager attribute*), 413
gitlab (*gitlab.v4.objects.UserIdentityProviderManager attribute*), 413
gitlab (*gitlab.v4.objects.UserImpersonationTokenManager attribute*), 414
gitlab (*gitlab.v4.objects.UserKeyManager attribute*), 415
gitlab (*gitlab.v4.objects.UserManager attribute*), 417
gitlab (*gitlab.v4.objects.UserMembershipManager attribute*), 418
gitlab (*gitlab.v4.objects.UserPersonalAccessTokenManager attribute*), 419
gitlab (*gitlab.v4.objects.UserProjectManager attribute*), 420
gitlab (*gitlab.v4.objects.UserStatusManager attribute*), 421
gitlab (*gitlab.v4.objects.VariableManager attribute*), 423
gitlab command line option
 --api-version, 460
 --config-file, 460
 --debug, 460
 --fancy, 459
 --fields, 460
 --gitlab, 460
 --help, 459
 --job-token, 460
 --oauth-token, 460
 --order-by, 460
 --output, 460
 --pagination, 460
 --per-page, 460
 --private-token, 460
 --server-url, 460
 --ssl-verify, 460
 --timeout, 460
 --user-agent, 460
 --verbose, 459
 --version, 459
 -c, 460
 -d, 460
 -f, 460
 -g, 460
 -h, 459
 -o, 460
 -v, 459

```

gitlab.base
    module, 423
gitlab.cli
    module, 425
gitlab.config
    module, 426
gitlab.const
    module, 427
gitlab.exceptions
    module, 428
gitlab.mixins
    module, 445
gitlab.utils
    module, 454
gitlab.v4
    module, 423
gitlab.v4.objects
    module, 182
gitlab_resource_to_cls() (in module gitlab.cli),
    426
gitlab-application command line option
    --help, 461
    -h, 461
gitlab-application-appearance command line
    option
    --help, 462
    -h, 462
gitlab-application-appearance-get command
    line option
    --help, 462
    --sudo, 462
    -h, 462
gitlab-application-appearance-update
    command line option
    --description, 462
    --email-header-and-footer-enabled, 463
    --favicon, 462
    --footer-message, 463
    --header-logo, 462
    --header-message, 463
    --help, 462
    --logo, 462
    --message-background-color, 463
    --message-font-color, 463
    --new-project-guidelines, 463
    --sudo, 462
    --title, 462
    -h, 462
gitlab-application-create command line
    option
    --confidential, 461
    --help, 461
    --name, 461
    --redirect-uri, 461
    --scopes, 461
    --sudo, 461
    -h, 461
gitlab-application-delete command line
    option
    --help, 461
    --id, 461
    --sudo, 461
    -h, 461
gitlab-application-list command line option
    --all, 462
    --get-all, 461
    --help, 461
    --page, 461
    --per-page, 461
    --sudo, 461
    -h, 461
gitlab-application-settings command line
    option
    --help, 463
    -h, 463
gitlab-application-settings-get command
    line option
    --help, 463
    --sudo, 463
    -h, 463
gitlab-application-settings-update command
    line option
    --after-sign-out-path, 466
    --allow-local-requests-from-hooks-and-services,
        467
    --allow-local-requests-from-system-hooks,
        467
    --allow-local-requests-from-web-hooks-and-services,
        467
    --asset-proxy-allowlist, 467
    --asset-proxy-enabled, 466
    --asset-proxy-url, 466
    --asset-proxy-whitelist, 467
    --container-registry-token-expire-delay,
        466
    --created-at, 465
    --default-branch-protection, 465
    --default-group-visibility, 465
    --default-project-visibility, 465
    --default-projects-limit, 465
    --default-snippet-visibility, 465
    --disabled-oauth-sign-in-sources, 465
    --domain-allowlist, 466
    --domain-blacklist, 466
    --domain-blacklist-enabled, 465
    --domain-denylist, 466
    --domain-denylist-enabled, 466
    --domain-whitelist, 465

```

```
--dsa-key-restriction, 466
--ecdsa-key-restriction, 466
--ed25519-key-restriction, 466
--enforce-terms, 466
--external-authorization-service-default-label, -h, 466
--external-authorization-service-enabled, 466
--external-authorization-service-timeout, 466
--external-authorization-service-url, 466
--file-template-project-id, 466
--first-day-of-week, 466
--geo-node-allowed-ips, 467
--gravatar-enabled, 465
--help, 465
--home-page-url, 465
--id, 465
--import-sources, 466
--instance-statistics-visibility-private, 466
--local-markdown-version, 466
--max-attachment-size, 465
--outbound-local-requests-whitelist, 465
--password-authentication-enabled-for-web, gitlab-broadcast-message-delete command line option
--performance-bar-allowed-group-id, 466
--plantuml-enabled, 466
--plantuml-url, 466
--polling-interval-multiplier, 466
--repository-storages, 466
--restricted-visibility-levels, 465
--rsa-key-restriction, 466
--session-expire-delay, 465
--sign-in-text, 465
--signup-enabled, 465
--sudo, 465
--terminal-max-session-time, 466
--terms, 466
--updated-at, 465
--user-oauth-applications, 466
--user-show-add-ssh-key-message, 466
-h, 465
gitlab-audit-event command line option
--help, 467
-h, 467
gitlab-audit-event-get command line option
--help, 467
--id, 467
--sudo, 467
-h, 467
gitlab-audit-event-list command line option
--all, 468
--created-after, 467
--created-before, 467
--entity-id, 467
--entity-type, 467
--get-all, 468
--page, 467
--per-page, 468
--sudo, 467
-h, 467
gitlab-broadcast-message command line option
--help, 468
-h, 468
gitlab-broadcast-message-create command line option
--color, 468
--ends-at, 468
--font, 468
--help, 468
--message, 468
--starts-at, 468
--sudo, 468
--target-access-levels, 468
-h, 468
gitlab-broadcast-message-delete command line option
--help, 468
--id, 468
--sudo, 468
-h, 468
gitlab-broadcast-message-get command line option
--help, 469
--id, 469
--sudo, 469
-h, 469
gitlab-broadcast-message-list command line option
--all, 469
--get-all, 469
--help, 469
--page, 469
--per-page, 469
--sudo, 469
-h, 469
gitlab-broadcast-message-update command line option
--color, 469
--ends-at, 469
--font, 469
--help, 469
--id, 469
--message, 469
--starts-at, 469
```

```

--sudo, 469
--target-access-levels, 470
-h, 469
gitlab-ci-lint command line option
--help, 470
-h, 470
gitlab-ci-lint-create command line option
--content, 470
--help, 470
--include-jobs, 470
--include-merged-yaml, 470
--sudo, 470
-h, 470
gitlab-ci-lint-validate command line option
--content, 470
--help, 470
--include-jobs, 470
--include-merged-yaml, 470
-h, 470
gitlab-current-user command line option
--help, 471
-h, 471
gitlab-current-user-email command line
    option
--help, 471
-h, 471
gitlab-current-user-email-create command
    line option
--email, 471
--help, 471
--sudo, 471
-h, 471
gitlab-current-user-email-delete command
    line option
--help, 471
--id, 471
--sudo, 471
-h, 471
gitlab-current-user-email-get command line
    option
--help, 472
--id, 472
--sudo, 472
-h, 472
gitlab-current-user-email-list command line
    option
--all, 472
--get-all, 472
--help, 472
--page, 472
--per-page, 472
--sudo, 472
-h, 472
gitlab-current-user-get command line option
--help, 471
--sudo, 471
-h, 471
gitlab-current-user-gpg-key command line
    option
--help, 472
-h, 472
gitlab-current-user-gpg-key-create command
    line option
--help, 472
--key, 472
--sudo, 472
-h, 472
gitlab-current-user-gpg-key-delete command
    line option
--help, 473
--id, 473
--sudo, 473
-h, 473
gitlab-current-user-gpg-key-get command
    line option
--help, 473
--id, 473
--sudo, 473
-h, 473
gitlab-current-user-gpg-key-list command
    line option
--all, 473
--get-all, 473
--help, 473
--page, 473
--per-page, 473
--sudo, 473
-h, 473
gitlab-current-user-key command line option
--help, 473
-h, 473
gitlab-current-user-key-create command line
    option
--help, 474
--key, 474
--sudo, 474
--title, 474
-h, 474
gitlab-current-user-key-delete command line
    option
--help, 474
--id, 474
--sudo, 474
-h, 474
gitlab-current-user-key-get command line
    option
--help, 474
--id, 474

```

```
--sudo, 474
-h, 474
gitlab-current-user-key-list command line
    option
    --all, 474
    --get-all, 474
    --help, 474
    --page, 474
    --per-page, 474
    --sudo, 474
    -h, 474
gitlab-current-user-status command line
    option
    --help, 475
    -h, 475
gitlab-current-user-status-get command line
    option
    --help, 475
    --sudo, 475
    -h, 475
gitlab-current-user-status-update command
    line option
    --emoji, 475
    --help, 475
    --message, 475
    --sudo, 475
    -h, 475
gitlab-deploy-key command line option
    --help, 475
    -h, 475
gitlab-deploy-key-list command line option
    --all, 476
    --get-all, 476
    --help, 475
    --page, 476
    --per-page, 476
    --sudo, 475
    -h, 475
gitlab-deploy-token command line option
    --help, 476
    -h, 476
gitlab-deploy-token-list command line
    option
    --all, 476
    --get-all, 476
    --help, 476
    --page, 476
    --per-page, 476
    --sudo, 476
    -h, 476
gitlab-dockerfile command line option
    --help, 476
    -h, 476
gitlab-dockerfile-get command line option
    --help, 477
    --name, 477
    --sudo, 477
    -h, 477
gitlab-dockerfile-list command line option
    --all, 477
    --get-all, 477
    --help, 477
    --page, 477
    --per-page, 477
    --sudo, 477
    -h, 477
gitlab-event command line option
    --help, 477
    -h, 477
gitlab-event-list command line option
    --action, 477
    --after, 478
    --all, 478
    --before, 478
    --get-all, 478
    --help, 477
    --page, 478
    --per-page, 478
    --sort, 478
    --sudo, 477
    --target-type, 477
    -h, 477
gitlab-feature command line option
    --help, 478
    -h, 478
gitlab-feature-delete command line option
    --help, 478
    --name, 478
    --sudo, 478
    -h, 478
gitlab-feature-list command line option
    --all, 478
    --get-all, 478
    --help, 478
    --page, 478
    --per-page, 478
    --sudo, 478
    -h, 478
gitlab-generic-package command line option
    --help, 479
    -h, 479
gitlab-generic-package-download command
    line option
    --file-name, 479
    --help, 479
    --package-name, 479
    --package-version, 479
    --project-id, 479
```

```

--sudo, 479
-h, 479
gitlab-generic-package-upload command line
    option
--file-name, 479
--help, 479
--package-name, 479
--package-version, 479
--path, 479
--project-id, 479
--sudo, 479
-h, 479
gitlab-geo-node command line option
--help, 480
-h, 480
gitlab-geo-node-current-failures command
    line option
--help, 480
--id, 480
-h, 480
gitlab-geo-node-delete command line option
--help, 480
--id, 480
--sudo, 480
-h, 480
gitlab-geo-node-get command line option
--help, 480
--id, 480
--sudo, 480
-h, 480
gitlab-geo-node-list command line option
--all, 481
--get-all, 481
--help, 481
--page, 481
--per-page, 481
--sudo, 481
-h, 481
gitlab-geo-node-repair command line option
--help, 481
--id, 481
-h, 481
gitlab-geo-node-status command line option
--help, 481
--id, 481
-h, 481
gitlab-geo-node-update command line option
--enabled, 481
--files-max-capacity, 482
--help, 481
--id, 481
--repos-max-capacity, 482
--sudo, 481
--url, 482
-h, 481
gitlab-gitignore command line option
--help, 482
-h, 482
gitlab-gitignore-get command line option
--help, 482
--name, 482
--sudo, 482
-h, 482
gitlab-gitignore-list command line option
--all, 482
--get-all, 482
--help, 482
--page, 482
--per-page, 482
--sudo, 482
-h, 482
gitlab-gitlabciyml command line option
--help, 483
-h, 483
gitlab-gitlabciyml-get command line option
--help, 483
--name, 483
--sudo, 483
-h, 483
gitlab-gitlabciyml-list command line option
--all, 483
--get-all, 483
--help, 483
--page, 483
--per-page, 483
--sudo, 483
-h, 483
gitlab-group command line option
--help, 484
-h, 484
gitlab-group-access-request command line
    option
--help, 490
-h, 490
gitlab-group-access-request-approve command
    line option
--access-level, 490
--group-id, 490
--help, 490
--id, 490
--sudo, 490
-h, 490
gitlab-group-access-request-create command
    line option
--group-id, 490
--help, 490
--sudo, 490
-h, 490

```

```
gitlab-group-access-request-delete command
    line option
    --group-id, 490
    --help, 490
    --id, 490
    --sudo, 490
    -h, 490
gitlab-group-access-request-list command
    line option
    --all, 491
    --get-all, 491
    --group-id, 491
    --help, 491
    --page, 491
    --per-page, 491
    --sudo, 491
    -h, 491
gitlab-group-access-token command line
    option
    --help, 491
    -h, 491
gitlab-group-access-token-create command
    line option
    --access-level, 491
    --expires-at, 491
    --group-id, 491
    --help, 491
    --name, 491
    --scopes, 491
    --sudo, 491
    -h, 491
gitlab-group-access-token-delete command
    line option
    --group-id, 492
    --help, 492
    --id, 492
    --sudo, 492
    -h, 492
gitlab-group-access-token-list command line
    option
    --all, 492
    --get-all, 492
    --group-id, 492
    --help, 492
    --page, 492
    --per-page, 492
    --sudo, 492
    -h, 492
gitlab-group-add-ldap-group-link command
    line option
    --cn, 484
    --group-access, 484
    --help, 484
    --id, 484
    --provider, 484
    -h, 484
gitlab-group-audit-event command line
    option
    --help, 492
    -h, 492
gitlab-group-audit-event-get command line
    option
    --group-id, 493
    --help, 493
    --id, 493
    --sudo, 493
    -h, 493
gitlab-group-audit-event-list command line
    option
    --all, 493
    --created-after, 493
    --created-before, 493
    --get-all, 493
    --group-id, 493
    --help, 493
    --page, 493
    --per-page, 493
    --sudo, 493
    -h, 493
gitlab-group-badge command line option
    --help, 493
    -h, 493
gitlab-group-badge-create command line
    option
    --group-id, 494
    --help, 494
    --image-url, 494
    --link-url, 494
    --sudo, 494
    -h, 494
gitlab-group-badge-delete command line
    option
    --group-id, 494
    --help, 494
    --id, 494
    --sudo, 494
    -h, 494
gitlab-group-badge-get command line option
    --group-id, 494
    --help, 494
    --id, 494
    --sudo, 494
    -h, 494
gitlab-group-badge-list command line option
    --all, 495
    --get-all, 495
    --group-id, 495
    --help, 494
```

```

--page, 495
--per-page, 495
--sudo, 494
-h, 494
gitlab-group-badge-render command line
    option
    --group-id, 495
    --help, 495
    --id, 495
    --image-url, 495
    --link-url, 495
    --sudo, 495
    -h, 495
gitlab-group-badge-update command line
    option
    --group-id, 495
    --help, 495
    --id, 495
    --image-url, 495
    --link-url, 495
    --sudo, 495
    -h, 495
gitlab-group-billable-member command line
    option
    --help, 496
    -h, 496
gitlab-group-billable-member-delete command
    line option
    --group-id, 496
    --help, 496
    --id, 496
    --sudo, 496
    -h, 496
gitlab-group-billable-member-list command
    line option
    --all, 496
    --get-all, 496
    --group-id, 496
    --help, 496
    --page, 496
    --per-page, 496
    --search, 496
    --sort, 496
    --sudo, 496
    -h, 496
gitlab-group-billable-member-membership
    command line option
    --help, 497
    -h, 497
gitlab-group-billable-member-membership-list
    command line option
    --all, 497
    --get-all, 497
    --group-id, 497
    --help, 497
    --id, 497
    --page, 497
    --per-page, 497
    --sudo, 497
    -h, 497
gitlab-group-board command line option
    --help, 497
    -h, 497
gitlab-group-board-create command line
    option
    --group-id, 497
    --help, 497
    --name, 498
    --sudo, 497
    -h, 497
gitlab-group-board-delete command line
    option
    --group-id, 498
    --help, 498
    --id, 498
    --sudo, 498
    -h, 498
gitlab-group-board-get command line option
    --group-id, 498
    --help, 498
    --id, 498
    --sudo, 498
    -h, 498
gitlab-group-board-list command line option
    --all, 498
    --get-all, 498
    --group-id, 498
    --help, 498, 499
    --page, 498
    --per-page, 498
    --sudo, 498
    -h, 498, 499
gitlab-group-board-list-create command line
    option
    --board-id, 499
    --group-id, 499
    --help, 499
    --sudo, 499
    -h, 499
gitlab-group-board-list-delete command line
    option
    --board-id, 499
    --group-id, 499
    --help, 499
    --id, 499
    --sudo, 499
    -h, 499

```

```
gitlab-group-board-list-get command line
    option
    --board-id, 500
    --group-id, 500
    --help, 500
    --id, 500
    --sudo, 500
    -h, 500
gitlab-group-board-list-list command line
    option
    --all, 500
    --board-id, 500
    --get-all, 500
    --group-id, 500
    --help, 500
    --page, 500
    --per-page, 500
    --sudo, 500
    -h, 500
gitlab-group-board-list-update command line
    option
    --board-id, 500
    --group-id, 500
    --help, 500
    --id, 501
    --position, 501
    --sudo, 500
    -h, 500
gitlab-group-board-update command line
    option
    --group-id, 499
    --help, 499
    --id, 499
    --sudo, 499
    -h, 499
gitlab-group-cluster command line option
    --help, 501
    -h, 501
gitlab-group-cluster-create command line
    option
    --domain, 501
    --enabled, 501
    --environment-scope, 501
    --group-id, 501
    --help, 501
    --managed, 501
    --name, 501
    --platform-kubernetes-attributes, 501
    --sudo, 501
    -h, 501
gitlab-group-cluster-delete command line
    option
    --group-id, 501
    --help, 501
    --id, 501
    --sudo, 501
    -h, 501
gitlab-group-cluster-get command line
    option
    --group-id, 502
    --help, 502
    --id, 502
    --sudo, 502
    -h, 502
gitlab-group-cluster-list command line
    option
    --all, 502
    --get-all, 502
    --group-id, 502
    --help, 502
    --page, 502
    --per-page, 502
    --sudo, 502
    -h, 502
gitlab-group-cluster-update command line
    option
    --domain, 503
    --environment-scope, 503
    --group-id, 502
    --help, 502
    --id, 502
    --management-project-id, 503
    --name, 502
    --platform-kubernetes-attributes, 503
    --sudo, 502
    -h, 502
gitlab-group-create command line option
    --auto-devops-enabled, 485
    --avatar, 485
    --default-branch-protection, 485
    --description, 485
    --emails-disabled, 485
    --extra-shared-runners-minutes-limit, 485
    --help, 484
    --lfs-enabled, 485
    --membership-lock, 485
    --mentions-disabled, 485
    --name, 485
    --parent-id, 485
    --path, 485
    --project-creation-level, 485
    --request-access-enabled, 485
    --require-two-factor-authentication, 485
    --share-with-group-lock, 485
    --shared-runners-minutes-limit, 485
    --subgroup-creation-level, 485
    --sudo, 484
    --two-factor-grace-period, 485
```

```

--visibility, 485
-h, 484
gitlab-group-custom-attribute command line
    option
    --help, 503
    -h, 503
gitlab-group-custom-attribute-delete
    command line option
    --group-id, 503
    --help, 503
    --key, 503
    --sudo, 503
    -h, 503
gitlab-group-custom-attribute-get command
    line option
    --group-id, 503
    --help, 503
    --key, 503
    --sudo, 503
    -h, 503
gitlab-group-custom-attribute-list command
    line option
    --all, 504
    --get-all, 504
    --group-id, 504
    --help, 504
    --page, 504
    --per-page, 504
    --sudo, 504
    -h, 504
gitlab-group-delete command line option
    --help, 485
    --id, 485
    --sudo, 485
    -h, 485
gitlab-group-delete-ldap-group-link command
    line option
    --cn, 486
    --help, 486
    --id, 486
    --provider, 486
    -h, 486
gitlab-group-deploy-token command line
    option
    --help, 504
    -h, 504
gitlab-group-deploy-token-create command
    line option
    --expires-at, 504
    --group-id, 504
    --help, 504
    --name, 504
    --scopes, 504
    --sudo, 504
    --username, 504
    -h, 504
gitlab-group-deploy-token-delete command
    line option
    --group-id, 505
    --help, 505
    --id, 505
    --sudo, 505
    -h, 505
gitlab-group-deploy-token-get command line
    option
    --group-id, 505
    --help, 505
    --id, 505
    --sudo, 505
    -h, 505
gitlab-group-deploy-token-list command line
    option
    --all, 505
    --get-all, 505
    --group-id, 505
    --help, 505
    --page, 505
    --per-page, 505
    --scopes, 505
    --sudo, 505
    -h, 505
gitlab-group-descendant-group command line
    option
    --help, 506
    -h, 506
gitlab-group-descendant-group-list command
    line option
    --all, 506
    --all-available, 506
    --get-all, 506
    --group-id, 506
    --help, 506
    --min-access-level, 506
    --order-by, 506
    --owned, 506
    --page, 506
    --per-page, 506
    --search, 506
    --skip-groups, 506
    --sort, 506
    --statistics, 506
    --sudo, 506
    --with-custom-attributes, 506
    -h, 506
gitlab-group-epic command line option
    --help, 507
    -h, 507

```

```
gitlab-group-epic-award-emoji command line
    option
    --help, 509
    -h, 509
gitlab-group-epic-award-emoji-create
    command line option
    --epic-iid, 509
    --group-id, 509
    --help, 509
    --name, 509
    --sudo, 509
    -h, 509
gitlab-group-epic-award-emoji-delete
    command line option
    --epic-iid, 510
    --group-id, 510
    --help, 510
    --id, 510
    --sudo, 510
    -h, 510
gitlab-group-epic-award-emoji-get command
    line option
    --epic-iid, 510
    --group-id, 510
    --help, 510
    --id, 510
    --sudo, 510
    -h, 510
gitlab-group-epic-award-emoji-list command
    line option
    --all, 511
    --epic-iid, 510
    --get-all, 510
    --group-id, 510
    --help, 510
    --page, 510
    --per-page, 510
    --sudo, 510
    -h, 510
gitlab-group-epic-create command line
    option
    --description, 507
    --end-date, 507
    --group-id, 507
    --help, 507
    --labels, 507
    --start-date, 507
    --sudo, 507
    --title, 507
    -h, 507
gitlab-group-epic-delete command line
    option
    --group-id, 507
    --help, 507
    --iid, 507
    --sudo, 507
    -h, 507
gitlab-group-epic-discussion-note command
    line option
    --help, 511
    -h, 511
gitlab-group-epic-discussion-note-create
    command line option
    --body, 511
    --created-at, 511
    --discussion-id, 511
    --epic-iid, 511
    --group-id, 511
    --help, 511
    --sudo, 511
    -h, 511
gitlab-group-epic-discussion-note-delete
    command line option
    --discussion-id, 511
    --epic-iid, 511
    --group-id, 511
    --help, 511
    --id, 512
    --sudo, 511
    -h, 511
gitlab-group-epic-discussion-note-get
    command line option
    --discussion-id, 512
    --epic-iid, 512
    --group-id, 512
    --help, 512
    --id, 512
    --sudo, 512
    -h, 512
gitlab-group-epic-discussion-note-update
    command line option
    --body, 512
    --discussion-id, 512
    --epic-iid, 512
    --group-id, 512
    --help, 512
    --id, 512
    --sudo, 512
    -h, 512
gitlab-group-epic-get command line option
    --group-id, 508
    --help, 508
    --iid, 508
    --sudo, 508
    -h, 508
gitlab-group-epic-issue command line option
    --help, 513
    -h, 513
```

```

gitlab-group-epic-issue-create command line      gitlab-group-epic-note-award-emoji command
    option                                         line option
    --epic-iid, 513
    --group-id, 513
    --help, 513
    --issue-id, 513
    --sudo, 513
    -h, 513
gitlab-group-epic-issue-delete command line      gitlab-group-epic-note-award-emoji-create
    option                                         command line option
    --epic-iid, 513
    --epic-issue-id, 513
    --group-id, 513
    --help, 513
    --sudo, 513
    -h, 513
gitlab-group-epic-issue-list command line        gitlab-group-epic-note-award-emoji-delete
    option                                         command line option
    --all, 514
    --epic-iid, 513
    --get-all, 514
    --group-id, 513
    --help, 513
    --page, 514
    --per-page, 514
    --sudo, 513
    -h, 513
gitlab-group-epic-issue-update command line       gitlab-group-epic-note-award-emoji-get
    option                                         command line option
    --epic-iid, 514
    --epic-issue-id, 514
    --group-id, 514
    --help, 514
    --move-after-id, 514
    --move-before-id, 514
    --sudo, 514
    -h, 514
gitlab-group-epic-list command line option        gitlab-group-epic-note-award-emoji-list
    --all, 508
    --author-id, 508
    --get-all, 508
    --group-id, 508
    --help, 508
    --labels, 508
    --order-by, 508
    --page, 508
    --per-page, 508
    --search, 508
    --sort, 508
    --sudo, 508
    -h, 508
gitlab-group-epic-note command line option        gitlab-group-epic-note-create command line
    --help, 514
    -h, 514
                                            option
                                            --body, 515
                                            --created-at, 515
                                            --epic-iid, 515
                                            --group-id, 514
                                            --help, 514
                                            --sudo, 514
                                            -h, 514
gitlab-group-epic-note-delete command line        gitlab-group-epic-note-delete command line
    option                                         option

```

```
--epic-iid, 515
--group-id, 515
--help, 515
--id, 515
--sudo, 515
-h, 515
gitlab-group-epic-note-get command line
    option
    --epic-iid, 515
    --group-id, 515
    --help, 515
    --id, 515
    --sudo, 515
    -h, 515
gitlab-group-epic-note-list command line
    option
    --all, 516
    --epic-iid, 515
    --get-all, 516
    --group-id, 515
    --help, 515
    --page, 516
    --per-page, 516
    --sudo, 515
    -h, 515
gitlab-group-epic-note-update command line
    option
    --body, 516
    --epic-iid, 516
    --group-id, 516
    --help, 516
    --id, 516
    --sudo, 516
    -h, 516
gitlab-group-epic-resource-label-event
    command line option
    --help, 518
    -h, 518
gitlab-group-epic-resource-label-event-get
    command line option
    --epic-id, 518
    --group-id, 518
    --help, 518
    --id, 518
    --sudo, 518
    -h, 518
gitlab-group-epic-resource-label-event-list
    command line option
    --all, 519
    --epic-id, 518
    --get-all, 519
    --group-id, 518
    --help, 518
    --page, 519
    --per-page, 519
    --sudo, 519
    -h, 519
gitlab-group-epic-update command line
    option
    --description, 509
    --end-date, 509
    --group-id, 509
    --help, 509
    --iid, 509
    --labels, 509
    --start-date, 509
    --sudo, 509
    --title, 509
    -h, 509
gitlab-group-export command line option
    --help, 519
    -h, 519
gitlab-group-export-create command line
    option
    --group-id, 519
    --help, 519
    --sudo, 519
    -h, 519
gitlab-group-export-download command line
    option
    --group-id, 519
    --help, 519
    --sudo, 519
    -h, 519
gitlab-group-export-get command line option
    --group-id, 519
    --help, 519
    --sudo, 519
    -h, 519
gitlab-group-get command line option
    --help, 486
    --id, 486
    --sudo, 486
    -h, 486
gitlab-group-hook command line option
    --help, 520
    -h, 520
gitlab-group-hook-create command line
    option
    --confidential-issues-events, 520
    --confidential-note-events, 520
    --deployment-events, 520
    --enable-ssl-verification, 521
    --group-id, 520
    --help, 520
    --issues-events, 520
    --job-events, 520
    --merge-requests-events, 520
```

```

--note-events, 520
--pipeline-events, 520
--push-events, 520
--releases-events, 521
--subgroup-events, 521
--sudo, 520
--tag-push-events, 520
--token, 521
--url, 520
--wiki-page-events, 520
-h, 520

gitlab-group-hook-delete command line
    option
        --group-id, 521
        --help, 521
        --id, 521
        --sudo, 521
        -h, 521
gitlab-group-hook-get command line option
        --group-id, 521
        --help, 521
        --id, 521
        --sudo, 521
        -h, 521
gitlab-group-hook-list command line option
        --all, 522
        --get-all, 521
        --group-id, 521
        --help, 521
        --page, 521
        --per-page, 521
        --sudo, 521
        -h, 521
gitlab-group-hook-update command line
    option
        --confidential-issues-events, 522
        --confidential-note-events, 522
        --deployment-events, 522
        --enable-ssl-verification, 523
        --group-id, 522
        --help, 522
        --id, 522
        --issues-events, 522
        --job-events, 522
        --merge-requests-events, 522
        --note-events, 522
        --pipeline-events, 522
        --push-events, 522
        --releases-events, 523
        --subgroup-events, 523
        --sudo, 522
        --tag-push-events, 522
        --token, 523
        --url, 522
        --wiki-page-events, 522
        -h, 522
gitlab-group-import command line option
        --help, 523
        -h, 523
gitlab-group-import-get command line option
        --group-id, 523
        --help, 523
        --sudo, 523
        -h, 523
gitlab-group-invitation command line option
        --help, 523
        -h, 523
gitlab-group-invitation-create command line
    option
        --access-level, 523
        --expires-at, 524
        --group-id, 523
        --help, 523
        --invite-source, 524
        --sudo, 523
        --tasks-project-id, 524
        --tasks-to-be-done, 524
        -h, 523
gitlab-group-invitation-delete command line
    option
        --email, 524
        --group-id, 524
        --help, 524
        --sudo, 524
        -h, 524
gitlab-group-invitation-get command line
    option
        --email, 524
        --group-id, 524
        --help, 524
        --sudo, 524
        -h, 524
gitlab-group-invitation-list command line
    option
        --all, 525
        --get-all, 525
        --group-id, 524
        --help, 524
        --page, 524
        --per-page, 525
        --query, 524
        --sudo, 524
        -h, 524
gitlab-group-invitation-update command line
    option
        --access-level, 525
        --email, 525
        --expires-at, 525

```

```
--group-id, 525
--help, 525
--sudo, 525
-h, 525
gitlab-group-issue command line option
--help, 525
-h, 525
gitlab-group-issue-list command line option
--all, 526
--assignee-id, 526
--author-id, 526
--created-after, 526
--created-before, 526
--get-all, 526
--group-id, 526
--help, 525
--iids, 526
--labels, 526
--milestone, 526
--my-reaction-emoji, 526
--order-by, 526
--page, 526
--per-page, 526
--search, 526
--sort, 526
--state, 526
--sudo, 526
--updated-after, 526
--updated-before, 526
-h, 525
gitlab-group-issues-statistics command line
    option
--help, 526
-h, 526
gitlab-group-issues-statistics-get command
    line option
--group-id, 527
--help, 527
--sudo, 527
-h, 527
gitlab-group-iteration command line option
--help, 527
-h, 527
gitlab-group-iteration-list command line
    option
--all, 527
--get-all, 527
--group-id, 527
--help, 527
--include-ancestors, 527
--page, 527
--per-page, 527
--search, 527
--state, 527
--sudo, 527
--name, 528
--password, 528
--path, 528
--sudo, 528
--token, 528
--username, 528
--version, 528
--help, 528
-h, 528
gitlab-group-label command line option
--help, 528
-h, 528
gitlab-group-label-create command line
    option
--color, 528
--description, 528
--group-id, 528
--help, 528
--name, 528
--priority, 528
--sudo, 528
-h, 528
gitlab-group-label-delete command line
    option
--group-id, 528
--help, 528
--name, 528
--sudo, 528
-h, 528
gitlab-group-label-get command line option
--group-id, 529
--help, 529
--name, 529
--sudo, 529
-h, 529
gitlab-group-label-list command line option
--all, 529
--get-all, 529
--group-id, 529
--help, 529
--page, 529
--per-page, 529
--sudo, 529
-h, 529
gitlab-group-label-subscribe command line
    option
--group-id, 529
--help, 529
--name, 529
--sudo, 529
-h, 529
gitlab-group-label-unsubscribe command line
    option
--group-id, 530
--help, 530
--name, 530
--sudo, 530
-h, 530
gitlab-group-label-update command line
    option
--color, 530
```

```

--description, 530
--group-id, 530
--help, 530
--name, 530
--new-name, 530
--priority, 530
--sudo, 530
-h, 530
gitlab-group-ldap-sync command line option
--help, 486
--id, 486
-h, 486
gitlab-group-list command line option
--all, 487
--all-available, 486
--get-all, 487
--help, 486
--min-access-level, 487
--order-by, 487
--owned, 487
--page, 487
--per-page, 487
--search, 487
--skip-groups, 486
--sort, 487
--statistics, 487
--sudo, 486
--top-level-only, 487
--with-custom-attributes, 487
-h, 486
gitlab-group-member command line option
--help, 530
-h, 530
gitlab-group-member-all command line option
--help, 532
-h, 532
gitlab-group-member-all-get command line
    option
--group-id, 533
--help, 533
--id, 533
--sudo, 533
-h, 533
gitlab-group-member-all-list command line
    option
--all, 533
--get-all, 533
--group-id, 533
--help, 533
--page, 533
--per-page, 533
--sudo, 533
-h, 533
gitlab-group-member-create command line
    option
--access-level, 531
--expires-at, 531
--group-id, 531
--help, 531
--sudo, 531
--tasks-to-be-done, 531
--user-id, 531
-h, 531
gitlab-group-member-delete command line
    option
--group-id, 531
--help, 531
--id, 531
--sudo, 531
-h, 531
gitlab-group-member-get command line option
--group-id, 531
--help, 531
--id, 531
--sudo, 531
-h, 531
gitlab-group-member-list command line
    option
--all, 532
--get-all, 532
--group-id, 532
--help, 532
--page, 532
--per-page, 532
--sudo, 532
-h, 532
gitlab-group-member-update command line
    option
--access-level, 532
--expires-at, 532
--group-id, 532
--help, 532
--id, 532
--sudo, 532
-h, 532
gitlab-group-merge-request command line
    option
--help, 533
-h, 533
gitlab-group-merge-request-list command
    line option
--all, 535
--approved-by-ids, 534
--approver-ids, 534
--assignee-id, 534
--author-id, 534
--created-after, 534

```

```
--created-before, 534
--get-all, 535
--group-id, 534
--help, 534
--labels, 534
--milestone, 534
--my-reaction-emoji, 534
--order-by, 534
--page, 535
--per-page, 535
--scope, 534
--search, 535
--sort, 534
--source-branch, 535
--state, 534
--sudo, 534
--target-branch, 535
--updated-after, 534
--updated-before, 534
--view, 534
--wip, 535
-h, 534

gitlab-group-milestone command line option
--help, 535
-h, 535

gitlab-group-milestone-create command line
    option
--description, 535
--due-date, 535
--group-id, 535
--help, 535
--start-date, 535
--sudo, 535
--title, 535
-h, 535

gitlab-group-milestone-delete command line
    option
--group-id, 536
--help, 536
--id, 536
--sudo, 536
-h, 536

gitlab-group-milestone-get command line
    option
--group-id, 536
--help, 536
--id, 536
--sudo, 536
-h, 536

gitlab-group-milestone-issues command line
    option
--group-id, 536
--help, 536
--id, 536

--sudo, 536
-h, 536

gitlab-group-milestone-list command line
    option
--all, 537
--get-all, 537
--group-id, 537
--help, 536
--iids, 537
--page, 537
--per-page, 537
--search, 537
--state, 537
--sudo, 536
-h, 536

gitlab-group-milestone-merge-requests
    command line option
--group-id, 537
--help, 537
--id, 537
--sudo, 537
-h, 537

gitlab-group-milestone-update command line
    option
--description, 537
--due-date, 537
--group-id, 537
--help, 537
--id, 537
--start-date, 538
--state-event, 538
--sudo, 537
--title, 537
-h, 537

gitlab-group-notification-settings command
    line option
--help, 538
-h, 538

gitlab-group-notification-settings-get
    command line option
--group-id, 538
--help, 538
--sudo, 538
-h, 538

gitlab-group-notification-settings-update
    command line option
--close-issue, 539
--close-merge-request, 539
--group-id, 538
--help, 538
--level, 539
--merge-merge-request, 539
--new-issue, 539
--new-merge-request, 539
```

```

--new-note, 539
--notification-email, 539
--reassign-issue, 539
--reassign-merge-request, 539
--reopen-issue, 539
--reopen-merge-request, 539
--sudo, 538
-h, 538
gitlab-group-package command line option
--help, 539
-h, 539
gitlab-group-package-list command line
    option
--all, 540
--exclude-subgroups, 539
--get-all, 540
--group-id, 539
--help, 539
--order-by, 539
--package-name, 540
--package-type, 539
--page, 540
--per-page, 540
--sort, 539
--sudo, 539
-h, 539
gitlab-group-project command line option
--help, 540
-h, 540
gitlab-group-project-list command line
    option
--all, 541
--archived, 540
--get-all, 541
--group-id, 540
--help, 540
--include-subgroups, 541
--min-access-level, 541
--order-by, 540
--owned, 541
--page, 541
--per-page, 541
--search, 541
--simple, 541
--sort, 540
--starred, 541
--sudo, 540
--visibility, 540
--with-custom-attributes, 541
--with-issues-enabled, 541
--with-merge-requests-enabled, 541
--with-security-reports, 541
--with-shared, 541
-h, 540
gitlab-group-push-rules command line option
--help, 541
-h, 541
gitlab-group-push-rules-create command line
    option
--author-email-regex, 542
--branch-name-regex, 542
--commit-committer-check, 542
--commit-message-negative-regex, 542
--commit-message-regex, 542
--deny-delete-tag, 542
--file-name-regex, 542
--group-id, 542
--help, 541
--max-file-size, 542
--member-check, 542
--prevent-secrets, 542
--reject-unsigned-commits, 542
--sudo, 542
-h, 541
gitlab-group-push-rules-delete command line
    option
--group-id, 542
--help, 542
--sudo, 542
-h, 542
gitlab-group-push-rules-get command line
    option
--group-id, 542
--help, 542
--sudo, 542
-h, 542
gitlab-group-push-rules-update command line
    option
--author-email-regex, 543
--branch-name-regex, 543
--commit-committer-check, 543
--commit-message-negative-regex, 543
--commit-message-regex, 543
--deny-delete-tag, 543
--file-name-regex, 543
--group-id, 543
--help, 543
--max-file-size, 543
--member-check, 543
--prevent-secrets, 543
--reject-unsigned-commits, 543
--sudo, 543
-h, 543
gitlab-group-runner command line option
--help, 543
-h, 543
gitlab-group-runner-list command line
    option

```

```
--all, 544
--get-all, 544
--group-id, 544
--help, 544
--page, 544
--per-page, 544
--scope, 544
--sudo, 544
--tag-list, 544
-h, 544
gitlab-group-search command line option
--help, 487
--id, 487
--scope, 487
--search, 487
-h, 487
gitlab-group-share command line option
--expires-at, 487
--group-access, 487
--group-id, 487
--help, 487
--id, 487
-h, 487
gitlab-group-subgroup command line option
--help, 544
-h, 544
gitlab-group-subgroup-list command line
    option
--all, 545
--all-available, 545
--get-all, 545
--group-id, 544
--help, 544
--min-access-level, 545
--order-by, 545
--owned, 545
--page, 545
--per-page, 545
--search, 545
--skip-groups, 545
--sort, 545
--statistics, 545
--sudo, 544
--with-custom-attributes, 545
-h, 544
gitlab-group-transfer command line option
--group-id, 488
--help, 488
--id, 488
-h, 488
gitlab-group-transfer-project command line
    option
--help, 488
--id, 488
--project-id, 488
-h, 488
gitlab-group-unshare command line option
--group-id, 488
--help, 488
--id, 488
-h, 488
gitlab-group-update command line option
--auto-devops-enabled, 489
--avatar, 489
--default-branch-protection, 489
--description, 489
--emails-disabled, 489
--extra-shared-runners-minutes-limit, 489
--file-template-project-id, 489
--help, 489
--id, 489
--lfs-enabled, 489
--membership-lock, 489
--mentions-disabled, 489
--name, 489
--path, 489
--prevent-forking-outside-group, 489
--project-creation-level, 489
--request-access-enabled, 489
--require-two-factor-authentication, 489
--share-with-group-lock, 489
--shared-runners-minutes-limit, 489
--shared-runners-setting, 489
--subgroup-creation-level, 489
--sudo, 489
--two-factor-grace-period, 489
--visibility, 489
-h, 489
gitlab-group-variable command line option
--help, 545
-h, 545
gitlab-group-variable-create command line
    option
--group-id, 545
--help, 545
--key, 545
--masked, 546
--protected, 545
--sudo, 545
--value, 545
--variable-type, 546
-h, 545
gitlab-group-variable-delete command line
    option
--group-id, 546
--help, 546
--key, 546
--sudo, 546
```

```

-h, 546
gitlab-group-variable-get command line
    option
    --group-id, 546
    --help, 546
    --key, 546
    --sudo, 546
    -h, 546
gitlab-group-variable-list command line
    option
    --all, 546
    --get-all, 546
    --group-id, 546
    --help, 546
    --page, 546
    --per-page, 546
    --sudo, 546
    -h, 546
gitlab-group-variable-update command line
    option
    --group-id, 547
    --help, 547
    --key, 547
    --masked, 547
    --protected, 547
    --sudo, 547
    --value, 547
    --variable-type, 547
    -h, 547
gitlab-group-wiki command line option
    --help, 547
    -h, 547
gitlab-group-wiki-create command line
    option
    --content, 547
    --format, 547
    --group-id, 547
    --help, 547
    --sudo, 547
    --title, 547
    -h, 547
gitlab-group-wiki-delete command line
    option
    --group-id, 548
    --help, 548
    --slug, 548
    --sudo, 548
    -h, 548
gitlab-group-wiki-get command line option
    --group-id, 548
    --help, 548
    --slug, 548
    --sudo, 548
    -h, 548
gitlab-group-wiki-list command line option
    --all, 548
    --get-all, 548
    --group-id, 548
    --help, 548
    --page, 548
    --per-page, 548
    --sudo, 548
    --with-content, 548
    -h, 548
gitlab-group-wiki-update command line
    option
    --content, 549
    --format, 549
    --group-id, 549
    --help, 549
    --slug, 549
    --sudo, 549
    --title, 549
    -h, 549
gitlab-hook command line option
    --help, 549
    -h, 549
gitlab-hook-create command line option
    --help, 549
    --sudo, 549
    --url, 549
    -h, 549
gitlab-hook-delete command line option
    --help, 549
    --id, 549
    --sudo, 549
    -h, 549
gitlab-hook-get command line option
    --help, 550
    --id, 550
    --sudo, 550
    -h, 550
gitlab-hook-list command line option
    --all, 550
    --get-all, 550
    --help, 550
    --page, 550
    --per-page, 550
    --sudo, 550
    -h, 550
gitlab-issue command line option
    --help, 550
    -h, 550
gitlab-issue-get command line option
    --help, 550
    --id, 550
    --sudo, 550
    -h, 550

```

```
gitlab-issue-list command line option
  --all, 551
  --assignee-id, 551
  --author-id, 551
  --created-after, 551
  --created-before, 551
  --get-all, 551
  --help, 551
  --iids, 551
  --labels, 551
  --milestone, 551
  --my-reaction-emoji, 551
  --order-by, 551
  --page, 551
  --per-page, 551
  --scope, 551
  --search, 551
  --sort, 551
  --state, 551
  --sudo, 551
  --updated-after, 551
  --updated-before, 551
  -h, 551
gitlab-issues-statistics command line
    option
  --help, 552
  -h, 552
gitlab-issues-statistics-get command line
    option
  --help, 552
  --sudo, 552
  -h, 552
gitlab-key command line option
  --help, 552
  -h, 552
gitlab-key-get command line option
  --help, 552
  --id, 552
  --sudo, 552
  -h, 552
gitlab-ldap-group command line option
  --help, 552
  -h, 552
gitlab-ldap-group-list command line option
  --all, 553
  --get-all, 553
  --help, 553
  --page, 553
  --per-page, 553
  --provider, 553
  --search, 553
  --sudo, 553
  -h, 553
gitlab-license command line option
  --help, 553
  -h, 553
gitlab-license-get command line option
  --fullname, 553
  --help, 553
  --key, 553
  --project, 553
  --sudo, 553
  -h, 553
gitlab-license-list command line option
  --all, 554
  --get-all, 554
  --help, 554
  --page, 554
  --per-page, 554
  --popular, 554
  --sudo, 554
  -h, 554
gitlab-merge-request command line option
  --help, 554
  -h, 554
gitlab-merge-request-list command line
    option
  --all, 556
  --approved-by-ids, 555
  --approver-ids, 555
  --assignee-id, 555
  --author-id, 555
  --author-username, 555
  --created-after, 555
  --created-before, 555
  --deployed-after, 556
  --deployed-before, 556
  --environment, 556
  --get-all, 556
  --help, 555
  --in, 556
  --labels, 555
  --milestone, 555
  --my-reaction-emoji, 555
  --not, 556
  --order-by, 555
  --page, 556
  --per-page, 556
  --reviewer-id, 555
  --reviewer-username, 555
  --scope, 555
  --search, 555
  --sort, 555
  --source-branch, 555
  --state, 555
  --sudo, 555
  --target-branch, 555
  --updated-after, 555
```

```

--updated-before, 555
--view, 555
--wip, 556
--with-labels-details, 555
--with-merge-status-recheck, 555
-h, 555
gitlab-namespace command line option
--help, 556
-h, 556
gitlab-namespace-exists command line option
--help, 556
--id, 556
--namespace, 556
--parent-id, 556
-h, 556
gitlab-namespace-get command line option
--help, 556
--id, 556
--sudo, 556
-h, 556
gitlab-namespace-list command line option
--all, 557
--get-all, 557
--help, 557
--page, 557
--per-page, 557
--search, 557
--sudo, 557
-h, 557
gitlab-notification-settings command line
    option
--help, 557
-h, 557
gitlab-notification-settings-get command
    line option
--help, 557
--sudo, 557
-h, 557
gitlab-notification-settings-update command
    line option
--close-issue, 558
--close-merge-request, 558
--help, 558
--level, 558
--merge-merge-request, 558
--new-issue, 558
--new-merge-request, 558
--new-note, 558
--notification-email, 558
--reassign-issue, 558
--reassign-merge-request, 558
--reopen-issue, 558
--reopen-merge-request, 558
--sudo, 558
-h, 558
gitlab-pages-domain command line option
--help, 558
-h, 558
gitlab-pages-domain-list command line
    option
--all, 559
--get-all, 558
--help, 558
--page, 558
--per-page, 558
--sudo, 558
-h, 558
gitlab-personal-access-token command line
    option
--help, 559
-h, 559
gitlab-personal-access-token-delete command
    line option
--help, 559
--id, 559
--sudo, 559
-h, 559
gitlab-personal-access-token-list command
    line option
--all, 559
--get-all, 559
--help, 559
--page, 559
--per-page, 559
--sudo, 559
--user-id, 559
-h, 559
gitlab-project command line option
--help, 560
-h, 560
gitlab-project-access-request command line
    option
--help, 577
-h, 577
gitlab-project-access-request-approve
    command line option
--access-level, 577
--help, 577
--id, 577
--project-id, 577
--sudo, 577
-h, 577
gitlab-project-access-request-create
    command line option
--help, 577
--project-id, 577
--sudo, 577
-h, 577

```

```
gitlab-project-access-request-delete
    command line option
    --help, 577
    --id, 577
    --project-id, 577
    --sudo, 577
    -h, 577
gitlab-project-access-request-list command
    line option
    --all, 578
    --get-all, 578
    --help, 578
    --page, 578
    --per-page, 578
    --project-id, 578
    --sudo, 578
    -h, 578
gitlab-project-access-token command line
    option
    --help, 578
    -h, 578
gitlab-project-access-token-create command
    line option
    --access-level, 578
    --expires-at, 578
    --help, 578
    --name, 578
    --project-id, 578
    --scopes, 578
    --sudo, 578
    -h, 578
gitlab-project-access-token-delete command
    line option
    --help, 579
    --id, 579
    --project-id, 579
    --sudo, 579
    -h, 579
gitlab-project-access-token-list command
    line option
    --all, 579
    --get-all, 579
    --help, 579
    --page, 579
    --per-page, 579
    --project-id, 579
    --sudo, 579
    -h, 579
gitlab-project-additional-statistics
    command line option
    --help, 579
    -h, 579
gitlab-project-additional-statistics-get
    command line option
    --help, 580
    --project-id, 580
    --sudo, 580
    -h, 580
gitlab-project-approval command line option
    --help, 580
    -h, 580
gitlab-project-approval-get command line
    option
    --help, 580
    --project-id, 580
    --sudo, 580
    -h, 580
gitlab-project-approval-rule command line
    option
    --help, 581
    -h, 581
gitlab-project-approval-rule-create command
    line option
    --approvals-required, 581
    --group-ids, 581
    --help, 581
    --name, 581
    --project-id, 581
    --protected-branch-ids, 581
    --sudo, 581
    --user-ids, 581
    -h, 581
gitlab-project-approval-rule-delete command
    line option
    --help, 581
    --id, 581
    --project-id, 581
    --sudo, 581
    -h, 581
gitlab-project-approval-rule-list command
    line option
    --all, 582
    --get-all, 582
    --help, 582
    --page, 582
    --per-page, 582
    --project-id, 582
    --sudo, 582
    -h, 582
gitlab-project-approval-rule-update command
    line option
    --help, 582
    --id, 582
    --project-id, 582
    --sudo, 582
    -h, 582
gitlab-project-update command line
    option
```

```

--approvals-before-merge, 580
--disable-overriding-approvers-per-merge-request, 581
--help, 580
--merge-requests-author-approval, 581
--merge-requests-disable-committers-approval, 581
--project-id, 580
--reset-approvals-on-push, 580
--sudo, 580
-h, 580
gitlab-project-archive command line option
--help, 560
--id, 560
-h, 560
gitlab-project-artifact command line option
--artifact-path, 561
--help, 561, 582
--id, 561
--job, 561
--ref-name, 561
-h, 561, 582
gitlab-project-artifact-delete command line
    option
--help, 583
--project-id, 583
--ref-name, 583
--sudo, 583
-h, 583
gitlab-project-artifact-download command
    line option
--help, 583
--job, 583
--job-token, 583
--project-id, 583
--ref-name, 583
--sudo, 583
-h, 583
gitlab-project-artifact-raw command line
    option
--artifact-path, 583
--help, 583
--job, 583
--project-id, 583
--ref-name, 583
--sudo, 583
-h, 583
gitlab-project-artifacts command line
    option
--help, 561
--id, 561
--job, 561
--job-token, 561
--ref-name, 561
-h, 561
gitlab-project-audit-event command line
    option
--help, 584
--id, 584
--project-id, 584
--sudo, 584
-h, 584
gitlab-project-audit-event-get command line
    option
--help, 584
--id, 584
--project-id, 584
--sudo, 584
-h, 584
gitlab-project-audit-event-list command
    line option
--all, 584
--created-after, 584
--created-before, 584
--get-all, 584
--help, 584
--page, 584
--per-page, 584
--project-id, 584
--sudo, 584
-h, 584
gitlab-project-badge command line option
--help, 585
-h, 585
gitlab-project-badge-create command line
    option
--help, 585
--image-url, 585
--link-url, 585
--project-id, 585
--sudo, 585
-h, 585
gitlab-project-badge-delete command line
    option
--help, 585
--id, 585
--project-id, 585
--sudo, 585
-h, 585
gitlab-project-badge-get command line
    option
--help, 585
--id, 585
--project-id, 585
--sudo, 585
-h, 585
gitlab-project-badge-list command line
    option
--all, 586
--get-all, 586
--help, 586

```

```
--page, 586
--per-page, 586
--project-id, 586
--sudo, 586
-h, 586
gitlab-project-badge-render command line
    option
--help, 586
--id, 586
--image-url, 586
--link-url, 586
--project-id, 586
--sudo, 586
-h, 586
gitlab-project-badge-update command line
    option
--help, 586
--id, 586
--image-url, 587
--link-url, 587
--project-id, 586
--sudo, 586
-h, 586
gitlab-project-board command line option
--help, 587
-h, 587
gitlab-project-board-create command line
    option
--help, 587
--name, 587
--project-id, 587
--sudo, 587
-h, 587
gitlab-project-board-delete command line
    option
--help, 587
--id, 587
--project-id, 587
--sudo, 587
-h, 587
gitlab-project-board-get command line
    option
--help, 587
--id, 588
--project-id, 587
--sudo, 587
-h, 587
gitlab-project-board-list command line
    option
--all, 588
--get-all, 588
--help, 588
--page, 588
--per-page, 588
--project-id, 588
--sudo, 588
-h, 588
gitlab-project-board-list-create command
    line option
--board-id, 589
--help, 589
--project-id, 589
--sudo, 589
-h, 589
gitlab-project-board-list-delete command
    line option
--board-id, 589
--help, 589
--id, 589
--project-id, 589
--sudo, 589
-h, 589
gitlab-project-board-list-get command line
    option
--board-id, 589
--help, 589
--id, 589
--project-id, 589
--sudo, 589
-h, 589
gitlab-project-board-list-list command line
    option
--all, 590
--board-id, 590
--get-all, 590
--help, 590
--page, 590
--per-page, 590
--project-id, 590
--sudo, 590
-h, 590
gitlab-project-board-list-update command
    line option
--board-id, 590
--help, 590
--id, 590
--position, 590
--project-id, 590
--sudo, 590
-h, 590
gitlab-project-board-update command line
    option
--help, 588
--id, 588
--project-id, 588
--sudo, 588
-h, 588
gitlab-project-branch command line option
```

```

--help, 590
-h, 590
gitlab-project-branch-create command line
    option
    --branch, 591
    --help, 591
    --project-id, 591
    --ref, 591
    --sudo, 591
    -h, 591
gitlab-project-branch-delete command line
    option
    --help, 591
    --name, 591
    --project-id, 591
    --sudo, 591
    -h, 591
gitlab-project-branch-get command line
    option
    --help, 591
    --name, 591
    --project-id, 591
    --sudo, 591
    -h, 591
gitlab-project-branch-list command line
    option
    --all, 592
    --get-all, 592
    --help, 592
    --page, 592
    --per-page, 592
    --project-id, 592
    --sudo, 592
    -h, 592
gitlab-project-ci-lint command line option
    --help, 592
    -h, 592
gitlab-project-ci-lint-create command line
    option
    --content, 592
    --dry-run, 592
    --help, 592
    --include-jobs, 592
    --project-id, 592
    --ref, 592
    --sudo, 592
    -h, 592
gitlab-project-ci-lint-get command line
    option
    --help, 593
    --project-id, 593
    --sudo, 593
    -h, 593
gitlab-project-ci-lint-validate command
    line option
    --content, 593
    --dry-run, 593
    --help, 593
    --include-jobs, 593
    --project-id, 593
    --ref, 593
    --sudo, 593
    -h, 593
gitlab-project-cluster command line option
    --help, 593
    -h, 593
gitlab-project-cluster-create command line
    option
    --domain, 594
    --enabled, 594
    --environment-scope, 594
    --help, 593
    --managed, 594
    --name, 594
    --platform-kubernetes-attributes, 594
    --project-id, 594
    --sudo, 594
    -h, 593
gitlab-project-cluster-delete command line
    option
    --help, 594
    --id, 594
    --project-id, 594
    --sudo, 594
    -h, 594
gitlab-project-cluster-get command line
    option
    --help, 594
    --id, 594
    --project-id, 594
    --sudo, 594
    -h, 594
gitlab-project-cluster-list command line
    option
    --all, 595
    --get-all, 595
    --help, 595
    --page, 595
    --per-page, 595
    --project-id, 595
    --sudo, 595
    -h, 595
gitlab-project-cluster-update command line
    option
    --domain, 595
    --environment-scope, 595
    --help, 595

```

```
--id, 595
--management-project-id, 595
--name, 595
--platform-kubernetes-attributes, 595
--project-id, 595
--sudo, 595
-h, 595
gitlab-project-commit command line option
--help, 596
-h, 596
gitlab-project-commit-cherry-pick command
    line option
--branch, 596
--help, 596
--id, 596
--project-id, 596
--sudo, 596
-h, 596
gitlab-project-commit-comment command line
    option
--help, 599
-h, 599
gitlab-project-commit-comment-create
    command line option
--commit-id, 599
--help, 599
--line, 600
--line-type, 600
--note, 600
--path, 600
--project-id, 599
--sudo, 599
-h, 599
gitlab-project-commit-comment-list command
    line option
--all, 600
--commit-id, 600
--get-all, 600
--help, 600
--page, 600
--per-page, 600
--project-id, 600
--sudo, 600
-h, 600
gitlab-project-commit-create command line
    option
--actions, 596
--author-email, 596
--author-name, 597
--branch, 596
--commit-message, 596
--help, 596
--project-id, 596
--sudo, 596
-h, 596
gitlab-project-commit-diff command line
    option
--help, 597
--id, 597
--project-id, 597
--sudo, 597
-h, 597
gitlab-project-commit-discussion command
    line option
--help, 600
-h, 600
gitlab-project-commit-discussion-create
    command line option
--body, 601
--commit-id, 601
--created-at, 601
--help, 600
--project-id, 601
--sudo, 600
-h, 600
gitlab-project-commit-discussion-get
    command line option
--commit-id, 601
--help, 601
--id, 601
--project-id, 601
--sudo, 601
-h, 601
gitlab-project-commit-discussion-list
    command line option
--all, 601
--commit-id, 601
--get-all, 601
--help, 601
--page, 601
--per-page, 601
--project-id, 601
--sudo, 601
-h, 601
gitlab-project-commit-discussion-note
    command line option
--help, 602
-h, 602
gitlab-project-commit-discussion-note-create
    command line option
--body, 602
--commit-id, 602
--created-at, 602
--discussion-id, 602
--help, 602
--position, 602
--project-id, 602
--sudo, 602
```

```

-h, 602
gitlab-project-commit-discussion-note-delete
    command line option
--commit-id, 602
--discussion-id, 603
--help, 602
--id, 603
--project-id, 602
--sudo, 602
-h, 602
gitlab-project-commit-discussion-note-get
    command line option
--commit-id, 603
--discussion-id, 603
--help, 603
--id, 603
--project-id, 603
--sudo, 603
-h, 603
gitlab-project-commit-discussion-note-update
    command line option
--body, 603
--commit-id, 603
--discussion-id, 603
--help, 603
--id, 603
--project-id, 603
--sudo, 603
-h, 603
gitlab-project-commit-get command line
    option
--help, 597
--id, 597
--project-id, 597
--sudo, 597
-h, 597
gitlab-project-commit-list command line
    option
--all, 598
--first-parent, 598
--get-all, 598
--help, 597
--order, 598
--page, 598
--path, 598
--per-page, 598
--project-id, 597
--ref-name, 597
--since, 597
--sudo, 597
--trailers, 598
--until, 598
--with-stats, 598
-h, 597
gitlab-project-commit-merge-requests
    command line option
--help, 598
--id, 598
--project-id, 598
--sudo, 598
-h, 598
gitlab-project-commit-refs command line
    option
--help, 598
--id, 598
--project-id, 598
--sudo, 598
--type, 598
-h, 598
gitlab-project-commit-revert command line
    option
--branch, 599
--help, 599
--id, 599
--project-id, 599
--sudo, 599
-h, 599
gitlab-project-commit-signature command
    line option
--help, 599
--id, 599
--project-id, 599
--sudo, 599
-h, 599
gitlab-project-commit-status command line
    option
--help, 604
-h, 604
gitlab-project-commit-status-create command
    line option
--commit-id, 604
--context, 604
--coverage, 604
--description, 604
--help, 604
--name, 604
--project-id, 604
--ref, 604
--state, 604
--sudo, 604
--target-url, 604
-h, 604
gitlab-project-commit-status-list command
    line option
--all, 605
--commit-id, 605
--get-all, 605
--help, 604

```

```
--page, 605
--per-page, 605
--project-id, 604
--sudo, 604
-h, 604
gitlab-project-create command line option
--allow-merge-on-skipped-pipeline, 563
--analytics-access-level, 563
--approvals-before-merge, 563
--auto-cancel-pending-pipelines, 563
--auto-devops-deploy-strategy, 563
--auto-devops-enabled, 563
--autoclose-referenced-issues, 563
--avatar, 563
--build-coverage-regex, 563
--build-git-strategy, 563
--build-timeout, 563
--builds-access-level, 563
--ci-config-path, 563
--container-expiration-policy-attributes,
    563
--container-registry-enabled, 563
--default-branch, 563
--description, 563
--emails-disabled, 563
--external-authorization-classification-label,
    563
--forking-access-level, 563
--group-with-project-templates-id, 563
--help, 562
--import-url, 563
--initialize-with-readme, 563
--issues-access-level, 563
--issues-enabled, 563
--jobs-enabled, 563
--lfs-enabled, 563
--merge-method, 564
--merge-pipelines-enabled, 564
--merge-requests-access-level, 564
--merge-requests-enabled, 564
--mirror, 564
--mirror-trigger-builds, 564
--name, 563
--namespace-id, 564
--only-allow-merge-if-all-discussions-are-resolved,
    564
--only-allow-merge-if-pipeline-succeeds, 564
--operations-access-level, 564
--packages-enabled, 564
--pages-access-level, 564
--path, 563
--printing-merge-request-link-enabled,
    564
--public-builds, 564
--remove-source-branch-after-merge, 564
--repository-access-level, 564
--repository-storage, 564
--request-access-enabled, 564
--requirements-access-level, 564
--resolve-outdated-diff-discussions, 564
--shared-runners-enabled, 564
--show-default-award-emojis, 564
--snippets-access-level, 564
--snippets-enabled, 564
--squash-option, 564
--sudo, 563
--tag-list, 564
--template-name, 564
--template-project-id, 564
--topics, 564
--use-custom-template, 564
--visibility, 564
--wiki-access-level, 565
--wiki-enabled, 565
-h, 562
gitlab-project-create-fork-relation command
    line option
--forked-from-id, 565
--id, 565
-h, 565
gitlab-project-custom-attribute command
    line option
--help, 605
-h, 605
gitlab-project-custom-attribute-delete
    command line option
--help, 605
--key, 605
--project-id, 605
--sudo, 605
-h, 605
gitlab-project-custom-attribute-get command
    line option
--help, 605
--key, 605
--project-id, 605
-h, 605
gitlab-project-custom-attribute-list command line option
--all, 606
--get-all, 606
--help, 606
--page, 606
--per-page, 606
--project-id, 606
```

```

--sudo, 606
-h, 606
gitlab-project-delete command line option
--help, 565
--id, 565
--sudo, 565
-h, 565
gitlab-project-delete-fork-relation command
    line option
--help, 565
--id, 565
-h, 565
gitlab-project-delete-merged-branches
    command line option
--help, 565
--id, 565
-h, 565
gitlab-project-deploy-token command line
    option
--help, 606
-h, 606
gitlab-project-deploy-token-create command
    line option
--expires-at, 606
--help, 606
--name, 606
--project-id, 606
--scopes, 606
--sudo, 606
--username, 606
-h, 606
gitlab-project-deploy-token-delete command
    line option
--help, 607
--id, 607
--project-id, 607
--sudo, 607
-h, 607
gitlab-project-deploy-token-get command
    line option
--help, 607
--id, 607
--project-id, 607
--sudo, 607
-h, 607
gitlab-project-deploy-token-list command
    line option
--all, 607
--get-all, 607
--help, 607
--page, 607
--per-page, 607
--project-id, 607
--scopes, 607
--sudo, 607
--status, 607
--tag, 608
-h, 608
gitlab-project-deployment command line
    option
--help, 608
-h, 608
gitlab-project-deployment-approval command
    line option
--comment, 608
--help, 608
--id, 608
--project-id, 608
--represented-as, 608
--status, 608
--sudo, 608
-h, 608
gitlab-project-deployment-create command
    line option
--environment, 608
--help, 608
--project-id, 608
--ref, 608
--sha, 608
--status, 608
--sudo, 608
--tag, 608
-h, 608
gitlab-project-deployment-get command line
    option
--help, 609
--id, 609
--project-id, 609
--sudo, 609
-h, 609
gitlab-project-deployment-list command line
    option
--all, 609
--environment, 609
--get-all, 609
--help, 609
--order-by, 609
--page, 609
--per-page, 609
--project-id, 609
--sort, 609
--status, 609
--sudo, 609
--updated-after, 609
--updated-before, 609
-h, 609
gitlab-project-deployment-merge-request
    command line option
--help, 610
-h, 610

```

```
gitlab-project-deployment-merge-request-list
    command line option
    --all, 612
    --approved-by-ids, 611
    --approver-ids, 611
    --assignee-id, 611
    --author-id, 611
    --author-username, 611
    --created-after, 611
    --created-before, 611
    --deployed-after, 612
    --deployed-before, 612
    --deployment-id, 611
    --environment, 612
    --get-all, 612
    --help, 611
    --in, 612
    --labels, 611
    --milestone, 611
    --my-reaction-emoji, 612
    --not, 612
    --order-by, 611
    --page, 612
    --per-page, 612
    --project-id, 611
    --reviewer-id, 611
    --reviewer-username, 611
    --scope, 611
    --search, 612
    --sort, 611
    --source-branch, 612
    --state, 611
    --sudo, 611
    --target-branch, 612
    --updated-after, 611
    --updated-before, 611
    --view, 611
    --wip, 612
    --with-labels-details, 611
    --with-merge-status-recheck, 611
    -h, 611
gitlab-project-deployment-update command
    line option
    --help, 610
    --id, 610
    --project-id, 610
    --sudo, 610
    -h, 610
gitlab-project-environment command line
    option
    --help, 612
    -h, 612
gitlab-project-environment-create command
    line option
    --external-url, 613
    --help, 612
    --name, 613
    --project-id, 613
    --sudo, 612
    -h, 612
gitlab-project-environment-delete command
    line option
    --help, 613
    --id, 613
    --project-id, 613
    --sudo, 613
    -h, 613
gitlab-project-environment-get command line
    option
    --help, 613
    --id, 613
    --project-id, 613
    --sudo, 613
    -h, 613
gitlab-project-environment-list command
    line option
    --all, 614
    --get-all, 614
    --help, 613
    --name, 613
    --page, 614
    --per-page, 614
    --project-id, 613
    --search, 613
    --states, 614
    --sudo, 613
    -h, 613
gitlab-project-environment-stop command
    line option
    --help, 614
    --id, 614
    --project-id, 614
    --sudo, 614
    -h, 614
gitlab-project-environment-update command
    line option
    --external-url, 614
    --help, 614
    --id, 614
    --name, 614
    --project-id, 614
    --sudo, 614
    -h, 614
gitlab-project-event command line option
    --help, 615
    -h, 615
gitlab-project-event-list command line
    option
```

```
--action, 615
--after, 615
--all, 615
--before, 615
--get-all, 615
--help, 615
--page, 615
--per-page, 615
--project-id, 615
--sort, 615
--sudo, 615
--target-type, 615
-h, 615
gitlab-project-export command line option
--help, 615
-h, 615
gitlab-project-export-create command line
    option
--description, 616
--help, 616
--project-id, 616
--sudo, 616
-h, 616
gitlab-project-export-download command line
    option
--help, 616
--project-id, 616
--sudo, 616
-h, 616
gitlab-project-export-get command line
    option
--help, 616
--project-id, 616
--sudo, 616
-h, 616
gitlab-project-file command line option
--help, 616
-h, 616
gitlab-project-file-blame command line
    option
--file-path, 617
--help, 617
--project-id, 617
--ref, 617
--sudo, 617
-h, 617
gitlab-project-file-create command line
    option
--author-email, 617
--author-name, 617
--branch, 617
--commit-message, 617
--content, 617
--encoding, 617
--file-path, 617
--help, 617
--project-id, 617
--ref, 617
--sudo, 617
--target-type, 617
-h, 617
gitlab-project-file-delete command line
    option
--branch, 618
--commit-message, 618
--file-path, 618
--help, 618
--project-id, 618
--sudo, 618
-h, 618
gitlab-project-file-get command line option
--file-path, 618
--help, 618
--project-id, 618
--ref, 618
--sudo, 618
-h, 618
gitlab-project-file-raw command line option
--file-path, 618
--help, 618
--project-id, 618
--ref, 618
--sudo, 618
-h, 618
gitlab-project-file-update command line
    option
--author-email, 619
--author-name, 619
--branch, 619
--commit-message, 619
--content, 619
--encoding, 619
--file-path, 619
--help, 619
--project-id, 619
--sudo, 619
-h, 619
gitlab-project-fork command line option
--help, 619
-h, 619
gitlab-project-fork-create command line
    option
--help, 619
--namespace, 619
--project-id, 619
--sudo, 619
-h, 619
gitlab-project-fork-list command line
    option
--all, 620
```

```
--archived, 620
--get-all, 620
--help, 620
--membership, 620
--order-by, 620
--owned, 620
--page, 620
--per-page, 620
--project-id, 620
--search, 620
--simple, 620
--sort, 620
--starred, 620
--statistics, 620
--sudo, 620
--visibility, 620
--with-custom-attributes, 620
--with-issues-enabled, 620
--with-merge-requests-enabled, 620
-h, 620
gitlab-project-get command line option
--help, 566
--id, 566
--sudo, 566
-h, 566
gitlab-project-hook command line option
--help, 621
-h, 621
gitlab-project-hook-create command line
    option
--confidential-issues-events, 621
--enable-ssl-verification, 621
--help, 621
--issues-events, 621
--job-events, 621
--merge-requests-events, 621
--note-events, 621
--pipeline-events, 621
--project-id, 621
--push-events, 621
--sudo, 621
--tag-push-events, 621
--token, 621
--url, 621
--wiki-page-events, 621
-h, 621
gitlab-project-hook-delete command line
    option
--help, 622
--id, 622
--project-id, 622
--sudo, 622
-h, 622
gitlab-project-hook-get command line option
--help, 622
--id, 622
--project-id, 622
--sudo, 622
-h, 622
gitlab-project-hook-list command line
    option
--all, 622
--get-all, 622
--help, 622
--page, 622
--per-page, 622
--project-id, 622
--sudo, 622
-h, 622
gitlab-project-hook-update command line
    option
--confidential-issues-events, 623
--enable-ssl-verification, 623
--help, 623
--id, 623
--issues-events, 623
--job-events, 623
--merge-requests-events, 623
--note-events, 623
--pipeline-events, 623
--project-id, 623
--push-events, 623
--sudo, 623
--tag-push-events, 623
--token, 623
--url, 623
--wiki-events, 623
-h, 623
gitlab-project-housekeeping command line
    option
--help, 566
--id, 566
-h, 566
gitlab-project-import command line option
--help, 624
-h, 624
gitlab-project-import-get command line
    option
--help, 624
--project-id, 624
--sudo, 624
-h, 624
gitlab-project-integration command line
    option
--help, 624
-h, 624
gitlab-project-integration-available
    command line option
```

```
--help, 624
--project-id, 624
--slug, 624
--sudo, 624
-h, 624
gitlab-project-integration-delete command
    line option
--help, 624
--project-id, 624
--slug, 624
--sudo, 624
-h, 624
gitlab-project-integration-get command line
    option
--help, 625
--project-id, 625
--slug, 625
--sudo, 625
-h, 625
gitlab-project-integration-list command
    line option
--all, 625
--get-all, 625
--help, 625
--page, 625
--per-page, 625
--project-id, 625
--sudo, 625
-h, 625
gitlab-project-integration-update command
    line option
--help, 625
--project-id, 625
--slug, 625
--sudo, 625
-h, 625
gitlab-project-invitation command line
    option
--help, 626
-h, 626
gitlab-project-invitation-create command
    line option
--access-level, 626
--expires-at, 626
--help, 626
--invite-source, 626
--project-id, 626
--sudo, 626
--tasks-project-id, 626
--tasks-to-be-done, 626
-h, 626
gitlab-project-invitation-delete command
    line option
--email, 626
--help, 626
--project-id, 626
--sudo, 626
-h, 626
gitlab-project-invitation-get command line
    option
--email, 627
--help, 627
--project-id, 627
--sudo, 627
-h, 627
gitlab-project-invitation-list command line
    option
--all, 627
--get-all, 627
--help, 627
--page, 627
--per-page, 627
--project-id, 627
--query, 627
--sudo, 627
-h, 627
gitlab-project-invitation-update command
    line option
--access-level, 628
--email, 628
--expires-at, 628
--help, 627
--project-id, 627
--sudo, 627
-h, 627
gitlab-project-issue command line option
--help, 628
-h, 628
gitlab-project-issue-add-spent-time command
    line option
--duration, 628
--help, 628
--iid, 628
--project-id, 628
--sudo, 628
-h, 628
gitlab-project-issue-award-emoji command
    line option
--help, 636
-h, 636
gitlab-project-issue-award-emoji-create
    command line option
--help, 636
--issue-iid, 636
--name, 636
--project-id, 636
--sudo, 636
-h, 636
```

```
gitlab-project-issue-award-emoji-delete
    command line option
    --help, 636
    --id, 636
    --issue-iid, 636
    --project-id, 636
    --sudo, 636
    -h, 636
gitlab-project-issue-award-emoji-get
    command line option
    --help, 637
    --id, 637
    --issue-iid, 637
    --project-id, 637
    --sudo, 637
    -h, 637
gitlab-project-issue-award-emoji-list
    command line option
    --all, 637
    --get-all, 637
    --help, 637
    --issue-iid, 637
    --page, 637
    --per-page, 637
    --project-id, 637
    --sudo, 637
    -h, 637
gitlab-project-issue-closed-by command line
    option
    --help, 629
    --iid, 629
    --project-id, 629
    --sudo, 629
    -h, 629
gitlab-project-issue-create command line
    option
    --assignee-id, 629
    --assignee-ids, 629
    --confidential, 629
    --created-at, 629
    --description, 629
    --discussion-to-resolve, 629
    --due-date, 629
    --help, 629
    --labels, 629
    --merge-request-to-resolve-discussions-of,
        629
    --milestone-id, 629
    --project-id, 629
    --sudo, 629
    --title, 629
    -h, 629
gitlab-project-issue-delete command line
    option
    --help, 630
    --iid, 630
    --project-id, 630
    --sudo, 630
    -h, 630
gitlab-project-issue-discussion command
    line option
    --help, 637
    -h, 637
gitlab-project-issue-discussion-create
    command line option
    --body, 638
    --created-at, 638
    --help, 638
    --issue-iid, 638
    --project-id, 638
    --sudo, 638
    -h, 638
gitlab-project-issue-discussion-get command
    line option
    --help, 638
    --id, 638
    --issue-iid, 638
    --project-id, 638
    --sudo, 638
    -h, 638
gitlab-project-issue-discussion-list
    command line option
    --all, 639
    --get-all, 639
    --help, 638
    --issue-iid, 638
    --page, 638
    --per-page, 639
    --project-id, 638
    --sudo, 638
    -h, 638
gitlab-project-issue-discussion-note
    command line option
    --help, 639
    -h, 639
gitlab-project-issue-discussion-note-create
    command line option
    --body, 639
    --created-at, 639
    --discussion-id, 639
    --help, 639
    --issue-iid, 639
    --project-id, 639
    --sudo, 639
    -h, 639
gitlab-project-issue-discussion-note-delete
    command line option
    --discussion-id, 640
```

```

--help, 640
--id, 640
--issue-iid, 640
--project-id, 640
--sudo, 640
-h, 640
gitlab-project-issue-discussion-note-get
    command line option
--discussion-id, 640
--help, 640
--id, 640
--issue-iid, 640
--project-id, 640
--sudo, 640
-h, 640
gitlab-project-issue-discussion-note-update
    command line option
--body, 641
--discussion-id, 641
--help, 640
--id, 641
--issue-iid, 641
--project-id, 641
--sudo, 640
-h, 640
gitlab-project-issue-get command line
    option
--help, 630
--iid, 630
--project-id, 630
--sudo, 630
-h, 630
gitlab-project-issue-link command line
    option
--help, 641
-h, 641
gitlab-project-issue-link-create command
    line option
--help, 641
--issue-iid, 641
--project-id, 641
--sudo, 641
--target-issue-iid, 641
--target-project-id, 641
-h, 641
gitlab-project-issue-link-delete command
    line option
--help, 641
--issue-iid, 641
--issue-link-id, 641
--project-id, 641
--sudo, 641
-h, 641
gitlab-project-issue-link-list command line
    option
--all, 642
--get-all, 642
--help, 642
--issue-iid, 642
--page, 642
--per-page, 642
--project-id, 642
--sudo, 642
-h, 642
gitlab-project-issue-list command line
    option
--all, 631
--assignee-id, 631
--author-id, 631
--created-after, 631
--created-before, 631
--get-all, 631
--help, 630
--iids, 630
--labels, 631
--milestone, 631
--my-reaction-emoji, 631
--order-by, 631
--page, 631
--per-page, 631
--project-id, 630
--scope, 631
--search, 631
--sort, 631
--state, 630
--sudo, 630
--updated-after, 631
--updated-before, 631
-h, 630
gitlab-project-issue-move command line
    option
--help, 631
--iid, 631
--project-id, 631
--sudo, 631
--to-project-id, 631
-h, 631
gitlab-project-issue-note command line
    option
--help, 642
-h, 642
gitlab-project-issue-note-award-emoji
    command line option
--help, 644
-h, 644
gitlab-project-issue-note-award-emoji-create
    command line option

```

```
--help, 644
--issue-iid, 644
--name, 644
--note-id, 644
--project-id, 644
--sudo, 644
-h, 644
gitlab-project-issue-note-award-emoji-delete
    command line option
--help, 645
--id, 645
--issue-iid, 645
--note-id, 645
--project-id, 645
--sudo, 645
-h, 645
gitlab-project-issue-note-award-emoji-get
    command line option
--help, 645
--id, 645
--issue-iid, 645
--note-id, 645
--project-id, 645
--sudo, 645
-h, 645
gitlab-project-issue-note-award-emoji-list
    command line option
--all, 646
--get-all, 646
--help, 645
--issue-iid, 646
--note-id, 646
--page, 646
--per-page, 646
--project-id, 646
--sudo, 645
-h, 645
gitlab-project-issue-note-create command
    line option
--body, 642
--created-at, 642
--help, 642
--issue-iid, 642
--project-id, 642
--sudo, 642
-h, 642
gitlab-project-issue-note-delete command
    line option
--help, 643
--id, 643
--issue-iid, 643
--project-id, 643
--sudo, 643
-h, 643
gitlab-project-issue-note-get command line
    option
--help, 643
--id, 643
--issue-iid, 643
--project-id, 643
--sudo, 643
-h, 643
gitlab-project-issue-note-list command line
    option
--all, 644
--get-all, 643
--help, 643
--issue-iid, 643
--page, 643
--per-page, 643
--project-id, 643
--sudo, 643
-h, 643
gitlab-project-issue-note-update command
    line option
--body, 644
--help, 644
--id, 644
--issue-iid, 644
--project-id, 644
--sudo, 644
-h, 644
gitlab-project-issue-participants command
    line option
--help, 632
--iid, 632
--project-id, 632
--sudo, 632
-h, 632
gitlab-project-issue-related-merge-requests
    command line option
--help, 632
--iid, 632
--project-id, 632
--sudo, 632
-h, 632
gitlab-project-issue-reorder command line
    option
--help, 632
--iid, 632
--move-after-id, 632
--move-before-id, 632
--project-id, 632
--sudo, 632
-h, 632
gitlab-project-issue-reset-spent-time
    command line option
--help, 633
```

```

--iid, 633
--project-id, 633
--sudo, 633
-h, 633
gitlab-project-issue-reset-time-estimate
    command line option
--help, 633
--iid, 633
--project-id, 633
--sudo, 633
-h, 633
gitlab-project-issue-resource-label-event
    command line option
--help, 646
-h, 646
gitlab-project-issue-resource-label-event-get gitlab-project-issue-resource-state-event-list
    command line option
--help, 646
--id, 646
--issue-iid, 646
--project-id, 646
--sudo, 646
-h, 646
gitlab-project-issue-resource-label-event-list
    command line option
--all, 647
--get-all, 647
--help, 646
--issue-iid, 647
--page, 647
--per-page, 647
--project-id, 647
--sudo, 647
-h, 646
gitlab-project-issue-resource-milestone-event
    command line option
--help, 647
-h, 647
gitlab-project-issue-resource-milestone-event-get --project-id, 633
    command line option
--help, 647
--id, 647
--issue-iid, 647
--project-id, 647
--sudo, 647
-h, 647
gitlab-project-issue-resource-milestone-event-list-sudo, 634
    command line option
--all, 648
--get-all, 648
--help, 648
--issue-iid, 648
--page, 648
--per-page, 648
--project-id, 648
--sudo, 648
--duration, 634
--help, 633
--iid, 634
--project-id, 633
--sudo, 633
-h, 633
gitlab-project-issue-time-estimate command
    line option
--duration, 634
--help, 633
--iid, 634
--project-id, 633
--sudo, 633
-h, 633
gitlab-project-issue-time-stats command
    line option
--help, 634
--iid, 634
--project-id, 634
--duration, 634
--help, 634
--iid, 634
--project-id, 634
--sudo, 634
gitlab-project-issue-todo command line
    option
--help, 634
--iid, 634
--project-id, 634
--sudo, 634

```

```
-h, 634
gitlab-project-issue-unsubscribe command
    line option
    --help, 634
    --iid, 634
    --project-id, 634
    --sudo, 634
    -h, 634
gitlab-project-issue-update command line
    option
    --assignee-id, 635
    --assignee-ids, 635
    --confidential, 635
    --description, 635
    --discussion-locked, 635
    --due-date, 635
    --help, 635
    --iid, 635
    --labels, 635
    --milestone-id, 635
    --project-id, 635
    --state-event, 635
    --sudo, 635
    --title, 635
    --updated-at, 635
    -h, 635
gitlab-project-issue-user-agent-detail
    command line option
    --help, 635
    --iid, 636
    --project-id, 635
    --sudo, 635
    -h, 635
gitlab-project-issues-statistics command
    line option
    --help, 649
    -h, 649
gitlab-project-issues-statistics-get
    command line option
    --help, 649
    --project-id, 649
    --sudo, 649
    -h, 649
gitlab-project-job command line option
    --help, 650
    -h, 650
gitlab-project-job-artifact command line
    option
    --help, 650
    --id, 650
    --project-id, 650
    --sudo, 650
    -h, 650
gitlab-project-job-artifacts command line
    option
    --help, 650
    --id, 650
    --project-id, 650
    --sudo, 650
    -h, 650
gitlab-project-job-cancel command line
    option
    --help, 651
    --id, 651
    --project-id, 651
    --sudo, 651
    -h, 651
gitlab-project-job-delete-artifacts command
    line option
    --help, 651
    --id, 651
    --project-id, 651
    --sudo, 651
    -h, 651
gitlab-project-job-erase command line
    option
    --help, 651
    --id, 651
    --project-id, 651
    --sudo, 651
    -h, 651
gitlab-project-job-get command line option
    --help, 651
    --id, 652
    --project-id, 651
    --sudo, 651
    -h, 651
gitlab-project-job-keep-artifacts command
    line option
    --help, 652
    --id, 652
    --project-id, 652
    --sudo, 652
    -h, 652
gitlab-project-job-list command line option
    --all, 652
    --get-all, 652
    --help, 652
    --page, 652
    --per-page, 652
    --project-id, 652
    --scope, 652
    --sudo, 652
    -h, 652
gitlab-project-job-play command line option
    --help, 652
    --id, 653
```

```

--project-id, 652
--sudo, 652
-h, 652
gitlab-project-job-retry command line
    option
    --help, 653
    --id, 653
    --project-id, 653
    --sudo, 653
    -h, 653
gitlab-project-job-trace command line
    option
    --help, 653
    --id, 653
    --project-id, 653
    --sudo, 653
    -h, 653
gitlab-project-key command line option
    --help, 653
    -h, 653
gitlab-project-key-create command line
    option
    --can-push, 654
    --help, 653
    --key, 654
    --project-id, 653
    --sudo, 653
    --title, 653
    -h, 653
gitlab-project-key-delete command line
    option
    --help, 654
    --id, 654
    --project-id, 654
    --sudo, 654
    -h, 654
gitlab-project-key-enable command line
    option
    --help, 654
    --id, 654
    --key-id, 654
    --project-id, 654
    --sudo, 654
    -h, 654
gitlab-project-key-get command line option
    --help, 654
    --id, 654
    --project-id, 654
    --sudo, 654
    -h, 654
gitlab-project-key-list command line option
    --all, 655
    --get-all, 655
    --help, 655
    --page, 655
    --per-page, 655
    --project-id, 655
    --sudo, 655
    -h, 655
gitlab-project-key-update command line
    option
    --can-push, 655
    --help, 655
    --id, 655
    --project-id, 655
    --sudo, 655
    --title, 655
    -h, 655
gitlab-project-label command line option
    --help, 655
    -h, 655
gitlab-project-label-create command line
    option
    --color, 656
    --description, 656
    --help, 656
    --name, 656
    --priority, 656
    --project-id, 656
    --sudo, 656
    -h, 656
gitlab-project-label-delete command line
    option
    --help, 656
    --name, 656
    --project-id, 656
    --sudo, 656
    -h, 656
gitlab-project-label-get command line
    option
    --help, 656
    --name, 656
    --project-id, 656
    --sudo, 656
    -h, 656
gitlab-project-label-list command line
    option
    --all, 657
    --get-all, 657
    --help, 657
    --page, 657
    --per-page, 657
    --project-id, 657
    --sudo, 657
    -h, 657
gitlab-project-label-subscribe command line
    option
    --help, 657

```

```
--name, 657
--project-id, 657
--sudo, 657
-h, 657
gitlab-project-label-unsubscribe command
    line option
--help, 657
--name, 657
--project-id, 657
--sudo, 657
-h, 657
gitlab-project-label-update command line
    option
--color, 658
--description, 658
--help, 658
--name, 658
--new-name, 658
--priority, 658
--project-id, 658
--sudo, 658
-h, 658
gitlab-project-languages command line
    option
--help, 566
--id, 566
-h, 566
gitlab-project-list command line option
--all, 567
--archived, 567
--get-all, 567
--help, 566
--id-after, 567
--id-before, 567
--last-activity-after, 567
--last-activity-before, 567
--membership, 567
--min-access-level, 567
--order-by, 567
--owned, 567
--page, 567
--per-page, 567
--repository-checksum-failed, 567
--repository-storage, 567
--search, 567
--search-namespaces, 567
--simple, 567
--sort, 567
--starred, 567
--statistics, 567
--sudo, 567
--topic, 567
--visibility, 567
--wiki-checksum-failed, 567
--with-custom-attributes, 567
--with-issues-enabled, 567
--with-merge-requests-enabled, 567
--with-programming-language, 567
-h, 566
gitlab-project-member command line option
--help, 658
-h, 658
gitlab-project-member-all command line
    option
--help, 660
-h, 660
gitlab-project-member-all-get command line
    option
--help, 660
--id, 660
--project-id, 660
--sudo, 660
-h, 660
gitlab-project-member-all-list command line
    option
--all, 661
--get-all, 661
--help, 660
--page, 661
--per-page, 661
--project-id, 660
--sudo, 660
-h, 660
gitlab-project-member-create command line
    option
--access-level, 658
--expires-at, 658
--help, 658
--project-id, 658
--sudo, 658
--tasks-to-be-done, 658
--user-id, 658
-h, 658
gitlab-project-member-delete command line
    option
--help, 659
--id, 659
--project-id, 659
--sudo, 659
-h, 659
gitlab-project-member-get command line
    option
--help, 659
--id, 659
--project-id, 659
--sudo, 659
-h, 659
```

```

gitlab-project-member-list command line
    option
    --all, 659
    --get-all, 659
    --help, 659
    --page, 659
    --per-page, 659
    --project-id, 659
    --sudo, 659
    -h, 659
gitlab-project-member-update command line
    option
    --access-level, 660
    --expires-at, 660
    --help, 660
    --id, 660
    --project-id, 660
    --sudo, 660
    -h, 660
gitlab-project-merge-request command line
    option
    --help, 661
    -h, 661
gitlab-project-merge-request-add-spent-time
    command line option
    --duration, 662
    --help, 662
    --iid, 662
    --project-id, 662
    --sudo, 662
    -h, 662
gitlab-project-merge-request-approval
    command line option
    --help, 672
    -h, 672
gitlab-project-merge-request-approval-get
    command line option
    --help, 672
    --mr-iid, 672
    --project-id, 672
    --sudo, 672
    -h, 672
gitlab-project-merge-request-approval-rule
    command line option
    --help, 672
    -h, 672
gitlab-project-merge-request-approval-rule-create -h, 675
    command line option
    --approval-project-rule-id, 673
    --approvals-required, 673
    --group-ids, 673
    --help, 673
    --id, 673
    --merge-request-iid, 673
    --mr-iid, 673
    --name, 673
    --project-id, 673
    --sudo, 673
    --user-ids, 673
gitlab-project-merge-request-approval-rule-delete
    command line option
    --help, 673
    --id, 674
    --mr-iid, 674
    --project-id, 673
    --sudo, 673
    -h, 673
gitlab-project-merge-request-approval-rule-get
    command line option
    --help, 674
    --id, 674
    --mr-iid, 674
    --project-id, 674
    --sudo, 674
    -h, 674
gitlab-project-merge-request-approval-rule-list
    command line option
    --all, 674
    --get-all, 674
    --help, 674
    --mr-iid, 674
    --page, 674
    --per-page, 674
    --project-id, 674
    --sudo, 674
    -h, 674
gitlab-project-merge-request-approval-rule-update
    command line option
    --approval-rule-id, 675
    --approvals-required, 675
    --group-ids, 675
    --help, 675
    --id, 675
    --merge-request-iid, 675
    --mr-iid, 675
    --name, 675
    --project-id, 675
    --sudo, 675
    --user-ids, 675
gitlab-project-merge-request-approval-state
    command line option
    --help, 675
    -h, 675
gitlab-project-merge-request-approval-state-get
    command line option
    --help, 676

```

```
--id, 676
--mr-iid, 676
--project-id, 676
--sudo, 676
-h, 676
gitlab-project-merge-request-approval-update
    command line option
--approvals-required, 672
--help, 672
--mr-iid, 672
--project-id, 672
--sudo, 672
-h, 672
gitlab-project-merge-request-approve
    command line option
--help, 662
--iid, 662
--project-id, 662
--sha, 662
--sudo, 662
-h, 662
gitlab-project-merge-request-award-emoji
    command line option
--help, 676
-h, 676
gitlab-project-merge-request-award-emoji-create
    command line option
--help, 676
--mr-iid, 676
--name, 676
--project-id, 676
--sudo, 676
-h, 676
gitlab-project-merge-request-award-emoji-delete
    command line option
--help, 677
--id, 677
--mr-iid, 677
--project-id, 677
--sudo, 677
-h, 677
gitlab-project-merge-request-award-emoji-get
    command line option
--help, 677
--id, 677
--mr-iid, 677
--project-id, 677
--sudo, 677
-h, 677
gitlab-project-merge-request-award-emoji-list
    command line option
--all, 678
--get-all, 678
--help, 677
--mr-iid, 677
--page, 677
--per-page, 677
--project-id, 677
--sudo, 677
-h, 677
gitlab-project-merge-request-cancel-merge-when-pipeline-su
    command line option
--help, 662
--iid, 662
--project-id, 662
--sudo, 662
-h, 662
gitlab-project-merge-request-changes
    command line option
--access-raw-diffs, 663
--help, 663
--iid, 663
--project-id, 663
--sudo, 663
-h, 663
gitlab-project-merge-request-closes-issues
    command line option
--help, 663
--iid, 663
--project-id, 663
--sudo, 663
-h, 663
gitlab-project-merge-request-commits
    command line option
--help, 663
--iid, 663
--project-id, 663
--sudo, 663
-h, 663
gitlab-project-merge-request-create command
    line option
--allow-collaboration, 664
--allow-maintainer-to-push, 664
--approvals-before-merge, 664
--assignee-id, 664
--assignee-ids, 664
--description, 664
--help, 664
--labels, 664
--milestone-id, 664
--project-id, 664
--remove-source-branch, 664
--reviewer-ids, 664
--source-branch, 664
--squash, 664
--sudo, 664
--target-branch, 664
--target-project-id, 664
```

```

--title, 664
-h, 664
gitlab-project-merge-request-delete command
    line option
--help, 665
--iid, 665
--project-id, 665
--sudo, 665
-h, 665
gitlab-project-merge-request-diff command
    line option
--help, 678
-h, 678
gitlab-project-merge-request-diff-get
    command line option
--help, 678
--id, 678
--mr-iid, 678
--project-id, 678
--sudo, 678
-h, 678
gitlab-project-merge-request-diff-list
    command line option
--all, 679
--get-all, 678
--help, 678
--mr-iid, 678
--page, 678
--per-page, 678
--project-id, 678
--sudo, 678
-h, 678
gitlab-project-merge-request-discussion
    command line option
--help, 679
-h, 679
gitlab-project-merge-request-discussion-create
    command line option
--body, 679
--created-at, 679
--help, 679
--mr-iid, 679
--position, 679
--project-id, 679
--sudo, 679
-h, 679
gitlab-project-merge-request-discussion-get
    command line option
--help, 679
--id, 680
--mr-iid, 680
--project-id, 679
--sudo, 679
-h, 679
gitlab-project-merge-request-discussion-list
    command line option
--all, 680
--get-all, 680
--help, 680
--mr-iid, 680
--page, 680
--per-page, 680
--project-id, 680
--sudo, 680
-h, 680
gitlab-project-merge-request-discussion-note
    command line option
--help, 681
-h, 681
gitlab-project-merge-request-discussion-note-create
    command line option
--body, 681
--created-at, 681
--discussion-id, 681
--help, 681
--mr-iid, 681
--project-id, 681
--sudo, 681
-h, 681
gitlab-project-merge-request-discussion-note-delete
    command line option
--discussion-id, 682
--help, 681
--id, 682
--mr-iid, 682
--project-id, 681
--sudo, 681
-h, 681
gitlab-project-merge-request-discussion-note-get
    command line option
--discussion-id, 682
--help, 682
--id, 682
--mr-iid, 682
--project-id, 682
--sudo, 682
-h, 682
gitlab-project-merge-request-discussion-note-update
    command line option
--body, 682
--discussion-id, 682
--help, 682
--id, 682
--mr-iid, 682
--project-id, 682
--sudo, 682
-h, 682

```

```
gitlab-project-merge-request-discussion-update
    command line option
    --help, 680
    --id, 680
    --mr-iid, 680
    --project-id, 680
    --resolved, 680
    --sudo, 680
    -h, 680
gitlab-project-merge-request-get command
    line option
    --help, 665
    --iid, 665
    --include-diverged-commits-count, 665
    --include-rebase-in-progress, 665
    --project-id, 665
    --render-html, 665
    --sudo, 665
    -h, 665
gitlab-project-merge-request-list command
    line option
    --all, 667
    --approved-by-ids, 666
    --approver-ids, 666
    --assignee-id, 666
    --author-id, 666
    --created-after, 666
    --created-before, 666
    --get-all, 667
    --help, 666
    --iids, 666
    --labels, 666
    --milestone, 666
    --my-reaction-emoji, 666
    --order-by, 666
    --page, 666
    --per-page, 667
    --project-id, 666
    --scope, 666
    --search, 666
    --sort, 666
    --source-branch, 666
    --state, 666
    --sudo, 666
    --target-branch, 666
    --updated-after, 666
    --updated-before, 666
    --view, 666
    --wip, 666
    -h, 666
gitlab-project-merge-request-merge command
    line option
    --help, 667
    --iid, 667
    --merge-commit-message, 667
    --merge-when-pipeline-succeeds, 667
    --project-id, 667
    --should-remove-source-branch, 667
    --sudo, 667
    -h, 667
gitlab-project-merge-request-merge-ref
    command line option
    --help, 667
    --iid, 667
    --project-id, 667
    --sudo, 667
    -h, 667
gitlab-project-merge-request-note command
    line option
    --help, 683
    -h, 683
gitlab-project-merge-request-note-award-emoji
    command line option
    --help, 685
    -h, 685
gitlab-project-merge-request-note-award-emoji-create
    command line option
    --help, 685
    --mr-iid, 685
    --name, 685
    --note-id, 685
    --project-id, 685
    --sudo, 685
    -h, 685
gitlab-project-merge-request-note-award-emoji-delete
    command line option
    --help, 685
    --id, 686
    --mr-iid, 686
    --note-id, 686
    --project-id, 685
    --sudo, 685
    -h, 685
gitlab-project-merge-request-note-award-emoji-get
    command line option
    --help, 686
    --id, 686
    --mr-iid, 686
    --note-id, 686
    --project-id, 686
    --sudo, 686
    -h, 686
gitlab-project-merge-request-note-award-emoji-list
    command line option
    --all, 687
    --get-all, 686
    --help, 686
    --mr-iid, 686
```

```
--note-id, 686
--page, 686
--per-page, 686
--project-id, 686
--sudo, 686
-h, 686
gitlab-project-merge-request-note-create
    command line option
--body, 683
--help, 683
--mr-iid, 683
--project-id, 683
--sudo, 683
-h, 683
gitlab-project-merge-request-note-delete
    command line option
--help, 683
--id, 683
--mr-iid, 683
--project-id, 683
--sudo, 683
-h, 683
gitlab-project-merge-request-note-get
    command line option
--help, 684
--id, 684
--mr-iid, 684
--project-id, 684
--sudo, 684
-h, 684
gitlab-project-merge-request-note-list
    command line option
--all, 684
--get-all, 684
--help, 684
--mr-iid, 684
--page, 684
--per-page, 684
--project-id, 684
--sudo, 684
-h, 684
gitlab-project-merge-request-note-update
    command line option
--body, 685
--help, 684
--id, 685
--mr-iid, 685
--project-id, 685
--sudo, 684
-h, 684
gitlab-project-merge-request-participants
    command line option
--help, 668
--iid, 668
--project-id, 668
--sudo, 668
-h, 668
--project-id, 668
--sudo, 668
-h, 668
gitlab-project-merge-request-pipeline
    command line option
--help, 687
-h, 687
gitlab-project-merge-request-pipeline-create
    command line option
--help, 687
--mr-iid, 687
--project-id, 687
--sudo, 687
-h, 687
gitlab-project-merge-request-pipeline-list
    command line option
--all, 687
--get-all, 687
--help, 687
--mr-iid, 687
--page, 687
--per-page, 687
--project-id, 687
--sudo, 687
-h, 687
gitlab-project-merge-request-rebase command
    line option
--help, 668
--iid, 668
--project-id, 668
--sudo, 668
-h, 668
gitlab-project-merge-request-reset-approvals
    command line option
--help, 668
--iid, 668
--project-id, 668
--sudo, 668
-h, 668
gitlab-project-merge-request-reset-spent-time
    command line option
--help, 668
--iid, 669
--project-id, 668
--sudo, 669
-h, 668
gitlab-project-merge-request-reset-time-estimate
    command line option
--help, 669
--iid, 669
--project-id, 669
--sudo, 669
-h, 669
```

```
gitlab-project-merge-request-resource-label-event --mr-iid, 690
    command line option
--help, 688
-h, 688
gitlab-project-merge-request-resource-label-event --project-id, 690
    command line option
--all, 690
--get-all, 690
--help, 690
--mr-iid, 690
--page, 690
--per-page, 690
gitlab-project-merge-request-resource-label-event --sudo, 690
--h, 690
gitlab-project-merge-request-resource-label-event --project-id, 690
    command line option
--all, 688
--get-all, 688
--help, 688
--mr-iid, 688
--page, 688
--per-page, 688
--project-id, 688
--sudo, 688
--h, 688
gitlab-project-merge-request-resource-label-event --project-id, 690
    command line option
--all, 688
--get-all, 688
--help, 688
--mr-iid, 688
--page, 688
--per-page, 688
--project-id, 688
--sudo, 688
--h, 688
gitlab-project-merge-request-time-estimate
gitlab-project-merge-request-resource-milestone-event --project-id, 669
    command line option
--duration, 669
--help, 669
--iid, 669
gitlab-project-merge-request-resource-milestone-event --project-id, 669
    command line option
--duration, 669
--help, 669
--iid, 669
gitlab-project-merge-request-time-stats
gitlab-project-merge-request-time-stats --project-id, 670
    command line option
--duration, 670
--help, 670
--iid, 670
--project-id, 670
--sudo, 670
--h, 670
gitlab-project-merge-request-milestone-list --project-id, 670
    command line option
--all, 670
--get-all, 670
--help, 670
--mr-iid, 670
--page, 670
--per-page, 670
--project-id, 670
--sudo, 670
--h, 670
gitlab-project-merge-request-todo --project-id, 670
    command line option
--all, 670
--get-all, 670
--help, 670
--mr-iid, 670
--page, 670
--per-page, 670
--project-id, 670
--sudo, 670
--h, 670
gitlab-project-merge-request-unapprove
gitlab-project-merge-request-unapprove --project-id, 670
    command line option
--all, 670
--get-all, 670
--help, 670
--mr-iid, 670
--page, 670
--per-page, 670
--project-id, 670
--sudo, 670
--h, 670
gitlab-project-merge-request-resource-state-event --help, 670
    command line option
--all, 670
--get-all, 670
--help, 670
--mr-iid, 670
--page, 670
--per-page, 670
--project-id, 670
--sudo, 670
--h, 670
gitlab-project-merge-request-resource-state-event --project-id, 670
    command line option
--all, 670
--get-all, 670
--help, 670
--mr-iid, 670
--page, 670
--per-page, 670
--project-id, 670
--sudo, 670
--h, 670
gitlab-project-merge-request-unsubscribe
gitlab-project-merge-request-unsubscribe --project-id, 670
    command line option
--all, 670
--get-all, 670
--help, 670
--mr-iid, 670
--page, 670
--per-page, 670
--project-id, 670
--sudo, 670
--h, 670
```

```

--iid, 671
--project-id, 670
--sudo, 670
-h, 670
gitlab-project-merge-request-update command
    line option
    --allow-maintainer-to-push, 671
    --assignee-id, 671
    --description, 671
    --discussion-locked, 671
    --help, 671
    --iid, 671
    --labels, 671
    --milestone-id, 671
    --project-id, 671
    --remove-source-branch, 671
    --reviewer-ids, 671
    --squash, 671
    --state-event, 671
    --sudo, 671
    --target-branch, 671
    --title, 671
    -h, 671
gitlab-project-merge-train command line
    option
    --help, 691
    -h, 691
gitlab-project-merge-train-list command
    line option
    --all, 691
    --get-all, 691
    --help, 691
    --page, 691
    --per-page, 691
    --project-id, 691
    --scope, 691
    --sudo, 691
    -h, 691
gitlab-project-milestone command line
    option
    --help, 691
    -h, 691
gitlab-project-milestone-create command
    line option
    --description, 692
    --due-date, 692
    --help, 692
    --project-id, 692
    --start-date, 692
    --state-event, 692
    --sudo, 692
    --title, 692
    -h, 692
gitlab-project-milestone-delete command
    line option
    --help, 692
    --id, 692
    --project-id, 692
    --sudo, 692
    -h, 692
gitlab-project-milestone-get command line
    option
    --help, 692
    --id, 692
    --project-id, 692
    --sudo, 692
    -h, 692
gitlab-project-milestone-issues command
    line option
    --help, 693
    --id, 693
    --project-id, 693
    --sudo, 693
    -h, 693
gitlab-project-milestone-list command line
    option
    --all, 693
    --get-all, 693
    --help, 693
    --iids, 693
    --page, 693
    --per-page, 693
    --project-id, 693
    --search, 693
    --state, 693
    --sudo, 693
    -h, 693
gitlab-project-milestone-merge-requests
    command line option
    --help, 693
    --id, 694
    --project-id, 693
    --sudo, 693
    -h, 693
gitlab-project-milestone-update command
    line option
    --description, 694
    --due-date, 694
    --help, 694
    --id, 694
    --project-id, 694
    --start-date, 694
    --state-event, 694
    --sudo, 694
    --title, 694
    -h, 694

```

```
gitlab-project-mirror-pull command line
    option
        --help, 698
        --id, 698
        -h, 698
gitlab-project-note command line option
    --help, 694
    -h, 694
gitlab-project-note-get command line option
    --help, 694
    --id, 694
    --project-id, 694
    --sudo, 694
    -h, 694
gitlab-project-note-list command line
    option
        --all, 695
        --get-all, 695
        --help, 695
        --page, 695
        --per-page, 695
        --project-id, 695
        --sudo, 695
        -h, 695
gitlab-project-notification-settings
    command line option
        --help, 695
        -h, 695
gitlab-project-notification-settings-get
    command line option
        --help, 695
        --project-id, 695
        --sudo, 695
        -h, 695
gitlab-project-notification-settings-update
    command line option
        --close-issue, 696
        --close-merge-request, 696
        --help, 696
        --level, 696
        --merge-merge-request, 696
        --new-issue, 696
        --new-merge-request, 696
        --new-note, 696
        --notification-email, 696
        --project-id, 696
        --reassign-issue, 696
        --reassign-merge-request, 696
        --reopen-issue, 696
        --reopen-merge-request, 696
        --sudo, 696
        -h, 696
gitlab-project-package command line option
    --help, 696
                    -h, 696
gitlab-project-package-delete command line
    option
        --help, 697
        --id, 697
        --project-id, 697
        --sudo, 697
        -h, 697
gitlab-project-package-file command line
    option
        --help, 698
        -h, 698
gitlab-project-package-file-delete command
    line option
        --help, 698
        --id, 698
        --package-id, 698
        --project-id, 698
        --sudo, 698
        -h, 698
gitlab-project-package-file-list command
    line option
        --all, 698
        --get-all, 698
        --help, 698
        --package-id, 698
        --page, 698
        --per-page, 698
        --project-id, 698
        --sudo, 698
        -h, 698
gitlab-project-package-get command line
    option
        --help, 697
        --id, 697
        --project-id, 697
        --sudo, 697
        -h, 697
gitlab-project-package-list command line
    option
        --all, 698
        --get-all, 697
        --help, 697
        --order-by, 697
        --package-name, 697
        --package-type, 697
        --page, 697
        --per-page, 697
        --project-id, 697
        --sort, 697
        --sudo, 697
        -h, 697
gitlab-project-pages-domain command line
    option
```

```

--help, 699
-h, 699
gitlab-project-pages-domain-create command
    line option
--certificate, 699
--domain, 699
--help, 699
--key, 699
--project-id, 699
--sudo, 699
-h, 699
gitlab-project-pages-domain-delete command
    line option
--domain, 699
--help, 699
--project-id, 699
--sudo, 699
-h, 699
gitlab-project-pages-domain-get command
    line option
--domain, 700
--help, 700
--project-id, 700
--sudo, 700
-h, 700
gitlab-project-pages-domain-list command
    line option
--all, 700
--get-all, 700
--help, 700
--page, 700
--per-page, 700
--project-id, 700
--sudo, 700
-h, 700
gitlab-project-pages-domain-update command
    line option
--certificate, 700
--domain, 700
--help, 700
--key, 701
--project-id, 700
--sudo, 700
-h, 700
gitlab-project-pipeline command line option
--help, 701
-h, 701
gitlab-project-pipeline-bridge command line
    option
--help, 703
-h, 703
gitlab-project-pipeline-bridge-list command
    line option
--all, 703
--get-all, 703
--help, 703
--id, 703
--page, 703
--per-page, 703
--pipeline-id, 703
--project-id, 703
--scope, 703
--sudo, 703
-h, 703
gitlab-project-pipeline-cancel command line
    option
--help, 701
--id, 701
--project-id, 701
--sudo, 701
-h, 701
gitlab-project-pipeline-create command line
    option
--help, 701
--project-id, 701
--ref, 701
--sudo, 701
-h, 701
gitlab-project-pipeline-delete command line
    option
--help, 701
--id, 701
--project-id, 701
--sudo, 701
-h, 701
gitlab-project-pipeline-get command line
    option
--help, 702
--id, 702
--project-id, 702
--sudo, 702
-h, 702
gitlab-project-pipeline-job command line
    option
--help, 704
-h, 704
gitlab-project-pipeline-job-list command
    line option
--all, 704
--get-all, 704
--help, 704
--include-retried, 704
--page, 704
--per-page, 704
--pipeline-id, 704
--project-id, 704
--scope, 704
--sudo, 704
-h, 704

```

```
gitlab-project-pipeline-list command line
    option
    --all, 702
    --get-all, 702
    --help, 702
    --name, 702
    --order-by, 702
    --page, 702
    --per-page, 702
    --project-id, 702
    --ref, 702
    --scope, 702
    --sha, 702
    --sort, 702
    --status, 702
    --sudo, 702
    --username, 702
    --yaml-errors, 702
    -h, 702
gitlab-project-pipeline-retry command line
    option
    --help, 703
    --id, 703
    --project-id, 703
    --sudo, 703
    -h, 703
gitlab-project-pipeline-schedule command
    line option
    --help, 704
    -h, 704
gitlab-project-pipeline-schedule-create
    command line option
    --active, 705
    --cron, 705
    --cron-timezone, 705
    --description, 705
    --help, 705
    --project-id, 705
    --ref, 705
    --sudo, 705
    -h, 705
gitlab-project-pipeline-schedule-delete
    command line option
    --help, 705
    --id, 705
    --project-id, 705
    --sudo, 705
    -h, 705
gitlab-project-pipeline-schedule-get
    command line option
    --help, 705
    --id, 705
    --project-id, 705
    --sudo, 705
    -h, 705
    -h, 705
gitlab-project-pipeline-schedule-list
    command line option
    --all, 706
    --get-all, 706
    --help, 706
    --page, 706
    --per-page, 706
    --project-id, 706
    --sudo, 706
    -h, 706
gitlab-project-pipeline-schedule-play
    command line option
    --help, 706
    --id, 706
    --project-id, 706
    --sudo, 706
    -h, 706
gitlab-project-pipeline-schedule-take-ownership
    command line option
    --help, 706
    --id, 706
    --project-id, 706
    --sudo, 706
    -h, 706
gitlab-project-pipeline-schedule-update
    command line option
    --active, 707
    --cron, 707
    --cron-timezone, 707
    --description, 707
    --help, 707
    --id, 707
    --project-id, 707
    --ref, 707
    --sudo, 707
    -h, 707
gitlab-project-pipeline-schedule-variable
    command line option
    --help, 707
    -h, 707
gitlab-project-pipeline-schedule-variable-create
    command line option
    --help, 707
    --key, 708
    --pipeline-schedule-id, 708
    --project-id, 707
    --sudo, 707
    --value, 708
    -h, 707
gitlab-project-pipeline-schedule-variable-delete
    command line option
    --help, 708
    --key, 708
```

```

--pipeline-schedule-id, 708
--project-id, 708
--sudo, 708
-h, 708
gitlab-project-pipeline-schedule-variable-update command line option
--help, 708
--key, 708
--pipeline-schedule-id, 708
--project-id, 708
--sudo, 708
--value, 708
-h, 708
gitlab-project-pipeline-test-report command line option
--help, 709
-h, 709
gitlab-project-pipeline-test-report-get command line option
--help, 709
--pipeline-id, 709
--project-id, 709
--sudo, 709
-h, 709
gitlab-project-pipeline-test-report-summary command line option
--help, 709
-h, 709
gitlab-project-pipeline-test-report-summary-ge gitlab-project-protected-branch-list command line option
--all, 712
--get-all, 712
--help, 712
--page, 712
--per-page, 712
--project-id, 712
--sudo, 712
-h, 712
gitlab-project-pipeline-variable command line option
--help, 710
-h, 710
gitlab-project-pipeline-variable-list command line option
--all, 710
--get-all, 710
--help, 710
--page, 710
--per-page, 710
--pipeline-id, 710
--project-id, 710
--sudo, 710
-h, 710
gitlab-project-protected-branch command line option
--help, 710
-h, 710
gitlab-project-protected-branch-create command line option
--allowed-to-merge, 711
--allowed-to-push, 711
--allowed-to-unprotect, 711
--code-owner-approval-required, 711
--help, 711
--merge-access-level, 711
--name, 711
--project-id, 711
--push-access-level, 711
--sudo, 711
--unprotect-access-level, 711
-h, 711
gitlab-project-protected-branch-delete command line option
--help, 711
--name, 711
--project-id, 711
--sudo, 711
-h, 711
gitlab-project-protected-branch-get command line option
--help, 711
--name, 711
--project-id, 711
--sudo, 711
-h, 711
gitlab-project-protected-environment command line option
--help, 712
-h, 712
gitlab-project-protected-environment-create command line option
--approval-rules, 713
--deploy-access-levels, 712
--help, 712
--name, 712
--project-id, 712
--required-approval-count, 712
--sudo, 712
-h, 712
gitlab-project-protected-environment-delete command line option

```

```
--help, 713
--name, 713
--project-id, 713
--sudo, 713
-h, 713
gitlab-project-protected-environment-get
    command line option
--help, 713
--name, 713
--project-id, 713
--sudo, 713
-h, 713
gitlab-project-protected-environment-list
    command line option
--all, 714
--get-all, 713
--help, 713
--page, 713
--per-page, 713
--project-id, 713
--sudo, 713
-h, 713
gitlab-project-protected-tag command line
    option
--help, 714
-h, 714
gitlab-project-protected-tag-create command
    line option
--create-access-level, 714
--help, 714
--name, 714
--project-id, 714
--sudo, 714
-h, 714
gitlab-project-protected-tag-delete command
    line option
--help, 714
--name, 714
--project-id, 714
--sudo, 714
-h, 714
gitlab-project-protected-tag-get command
    line option
--help, 715
--name, 715
--project-id, 715
--sudo, 715
-h, 715
gitlab-project-protected-tag-list command
    line option
--all, 715
--get-all, 715
--help, 715
--page, 715
--per-page, 715
--project-id, 715
--sudo, 715
-h, 715
gitlab-project-push-rules command line
    option
--help, 715
-h, 715
gitlab-project-push-rules-create command
    line option
--author-email-regex, 716
--branch-name-regex, 716
--commit-committer-check, 716
--commit-message-negative-regex, 716
--commit-message-regex, 716
--deny-delete-tag, 716
--file-name-regex, 716
--help, 716
--max-file-size, 716
--member-check, 716
--prevent-secrets, 716
--project-id, 716
--reject-unsigned-commits, 716
--sudo, 716
-h, 716
gitlab-project-push-rules-delete command
    line option
--help, 716
--project-id, 717
--sudo, 716
-h, 716
gitlab-project-push-rules-get command line
    option
--help, 717
--project-id, 717
--sudo, 717
-h, 717
gitlab-project-push-rules-update command
    line option
--author-email-regex, 717
--branch-name-regex, 717
--commit-committer-check, 717
--commit-message-negative-regex, 717
--commit-message-regex, 717
--deny-delete-tag, 717
--file-name-regex, 717
--help, 717
--max-file-size, 717
--member-check, 718
--prevent-secrets, 718
--project-id, 717
--reject-unsigned-commits, 718
--sudo, 717
-h, 717
```

```

gitlab-project-registry-repository command
    line option
    --help, 718
    -h, 718
gitlab-project-registry-repository-delete
    command line option
    --help, 718
    --id, 718
    --project-id, 718
    --sudo, 718
    -h, 718
gitlab-project-registry-repository-list
    command line option
    --all, 718
    --get-all, 718
    --help, 718
    --page, 718
    --per-page, 718
    --project-id, 718
    --sudo, 718
    -h, 718
gitlab-project-registry-tag command line
    option
    --help, 719
    -h, 719
gitlab-project-registry-tag-delete command
    line option
    --help, 719
    --name, 719
    --project-id, 719
    --repository-id, 719
    --sudo, 719
    -h, 719
gitlab-project-registry-tag-delete-in-bulk
    command line option
    --help, 719
    --keep-n, 719
    --name, 719
    --name-regex-delete, 719
    --name-regex-keep, 719
    --older-than, 719
    --project-id, 719
    --repository-id, 719
    --sudo, 719
    -h, 719
gitlab-project-registry-tag-get command
    line option
    --help, 720
    --name, 720
    --project-id, 720
    --repository-id, 720
    --sudo, 720
    -h, 720
gitlab-project-registry-tag-list command
    line option
    --all, 720
    --get-all, 720
    --help, 720
    --page, 720
    --per-page, 720
    --project-id, 720
    --repository-id, 720
    --sudo, 720
    -h, 720
gitlab-project-release command line option
    --help, 720
    -h, 720
gitlab-project-release-create command line
    option
    --assets, 721
    --description, 721
    --help, 721
    --name, 721
    --project-id, 721
    --ref, 721
    --sudo, 721
    --tag-name, 721
    -h, 721
gitlab-project-release-delete command line
    option
    --help, 721
    --project-id, 721
    --sudo, 721
    --tag-name, 721
    -h, 721
gitlab-project-release-get command line
    option
    --help, 721
    --project-id, 721
    --sudo, 721
    --tag-name, 721
    -h, 721
gitlab-project-release-link command line
    option
    --help, 723
    -h, 723
gitlab-project-release-link-create command
    line option
    --filepath, 723
    --help, 723
    --link-type, 723
    --name, 723
    --project-id, 723
    --sudo, 723
    --tag-name, 723
    --url, 723
    -h, 723

```

```
gitlab-project-release-link-delete command
    line option
    --help, 723
    --id, 723
    --project-id, 723
    --sudo, 723
    --tag-name, 723
    -h, 723
gitlab-project-release-link-get command
    line option
    --help, 724
    --id, 724
    --project-id, 724
    --sudo, 724
    --tag-name, 724
    -h, 724
gitlab-project-release-link-list command
    line option
    --all, 724
    --get-all, 724
    --help, 724
    --page, 724
    --per-page, 724
    --project-id, 724
    --sudo, 724
    --tag-name, 724
    -h, 724
gitlab-project-release-link-update command
    line option
    --filepath, 725
    --help, 724
    --id, 725
    --link-type, 725
    --name, 725
    --project-id, 725
    --sudo, 724
    --tag-name, 725
    --url, 725
    -h, 724
gitlab-project-release-list command line
    option
    --all, 722
    --get-all, 722
    --help, 722
    --include-html-description, 722
    --order-by, 722
    --page, 722
    --per-page, 722
    --project-id, 722
    --sort, 722
    --sudo, 722
    -h, 722
gitlab-project-release-update command line
    option
    --description, 722
    --help, 722
    --milestones, 722
    --name, 722
    --project-id, 722
    --released-at, 722
    --sudo, 722
    --tag-name, 722
    -h, 722
gitlab-project-remote-mirror command line
    option
    --help, 725
    -h, 725
gitlab-project-remote-mirror-create command
    line option
    --enabled, 725
    --help, 725
    --only-protected-branches, 725
    --project-id, 725
    --sudo, 725
    --url, 725
    -h, 725
gitlab-project-remote-mirror-list command
    line option
    --all, 726
    --get-all, 726
    --help, 725
    --page, 726
    --per-page, 726
    --project-id, 726
    --sudo, 725
    -h, 725
gitlab-project-remote-mirror-update command
    line option
    --enabled, 726
    --help, 726
    --id, 726
    --only-protected-branches, 726
    --project-id, 726
    --sudo, 726
    -h, 726
gitlab-project-repository-archive command
    line option
    --format, 568
    --help, 568
    --id, 568
    --sha, 568
    -h, 568
gitlab-project-repository-blob command line
    option
    --help, 568
    --id, 568
    --sha, 568
    -h, 568
```

```

gitlab-project-repository-compare command
    line option
    --from-, 568
    --help, 568
    --id, 568
    --to, 568
    -h, 568
gitlab-project-repository-contributors
    command line option
    --help, 569
    --id, 569
    -h, 569
gitlab-project-repository-merge-base
    command line option
    --help, 569
    --id, 569
    --refs, 569
    -h, 569
gitlab-project-repository-raw-blob command
    line option
    --help, 569
    --id, 569
    --sha, 569
    -h, 569
gitlab-project-repository-tree command line
    option
    --help, 569
    --id, 569
    --path, 569
    --recursive, 569
    --ref, 569
    -h, 569
gitlab-project-restore command line option
    --help, 570
    --id, 570
    -h, 570
gitlab-project-runner command line option
    --help, 726
    -h, 726
gitlab-project-runner-create command line
    option
    --help, 726
    --project-id, 726
    --runner-id, 726
    --sudo, 726
    -h, 726
gitlab-project-runner-delete command line
    option
    --help, 727
    --id, 727
    --project-id, 727
    --sudo, 727
    -h, 727
gitlab-project-runner-list command line
    option
    --all, 727
    --get-all, 727
    --help, 727
    --page, 727
    --per-page, 727
    --project-id, 727
    --scope, 727
    --sudo, 727
    --tag-list, 727
    -h, 727
gitlab-project-search command line option
    --help, 570
    --id, 570
    --scope, 570
    --search, 570
    -h, 570
gitlab-project-service command line option
    --help, 727
    -h, 727
gitlab-project-service-available command
    line option
    --help, 728
    --project-id, 728
    --slug, 728
    --sudo, 728
    -h, 728
gitlab-project-service-delete command line
    option
    --help, 728
    --project-id, 728
    --slug, 728
    --sudo, 728
    -h, 728
gitlab-project-service-get command line
    option
    --help, 728
    --project-id, 728
    --slug, 728
    --sudo, 728
    -h, 728
gitlab-project-service-list command line
    option
    --all, 729
    --get-all, 729
    --help, 728
    --page, 729
    --per-page, 729
    --project-id, 728
    --sudo, 728
    -h, 728
gitlab-project-service-update command line
    option

```

```
--help, 729
--project-id, 729
--slug, 729
--sudo, 729
-h, 729
gitlab-project-share command line option
--expires-at, 570
--group-access, 570
--group-id, 570
--help, 570
--id, 570
-h, 570
gitlab-project-snapshot command line option
--help, 570
--id, 570
--wiki, 570
-h, 570
gitlab-project-snippet command line option
--help, 729
-h, 729
gitlab-project-snippet-award-emoji command
    line option
--help, 732
-h, 732
gitlab-project-snippet-award-emoji-create
    command line option
--help, 732
--name, 732
--project-id, 732
--snippet-id, 732
--sudo, 732
-h, 732
gitlab-project-snippet-award-emoji-delete
    command line option
--help, 732
--id, 733
--project-id, 732
--snippet-id, 733
--sudo, 732
-h, 732
gitlab-project-snippet-award-emoji-get
    command line option
--help, 733
--id, 733
--project-id, 733
--snippet-id, 733
--sudo, 733
-h, 733
gitlab-project-snippet-award-emoji-list
    command line option
--all, 733
--get-all, 733
--help, 733
--page, 733
--per-page, 733
--project-id, 733
--snippet-id, 733
--sudo, 733
-h, 733
gitlab-project-snippet-content command line
    option
--help, 729
--id, 729
--project-id, 729
--sudo, 729
-h, 729
gitlab-project-snippet-create command line
    option
--content, 730
--description, 730
--file-name, 730
--help, 730
--project-id, 730
--sudo, 730
--title, 730
--visibility, 730
-h, 730
gitlab-project-snippet-delete command line
    option
--help, 730
--id, 730
--project-id, 730
--sudo, 730
-h, 730
gitlab-project-snippet-discussion command
    line option
--help, 734
-h, 734
gitlab-project-snippet-discussion-create
    command line option
--body, 734
--created-at, 734
--help, 734
--project-id, 734
--snippet-id, 734
--sudo, 734
-h, 734
gitlab-project-snippet-discussion-get
    command line option
--help, 734
--id, 734
--project-id, 734
--snippet-id, 734
--sudo, 734
-h, 734
gitlab-project-snippet-discussion-list
    command line option
--all, 735
```

```

--get-all, 735
--help, 735
--page, 735
--per-page, 735
--project-id, 735
--snippet-id, 735
--sudo, 735
-h, 735
gitlab-project-snippet-discussion-note
    command line option
--help, 735
-h, 735
gitlab-project-snippet-discussion-note-create
    command line option
--body, 736
--created-at, 736
--discussion-id, 736
--help, 735
--project-id, 735
--snippet-id, 735
--sudo, 735
-h, 735
gitlab-project-snippet-discussion-note-delete
    command line option
--discussion-id, 736
--help, 736
--id, 736
--project-id, 736
--snippet-id, 736
--sudo, 736
-h, 736
gitlab-project-snippet-discussion-note-get
    command line option
--discussion-id, 736
--help, 736
--id, 736
--project-id, 736
--snippet-id, 736
--sudo, 736
-h, 736
gitlab-project-snippet-discussion-note-update
    command line option
--body, 737
--discussion-id, 737
--help, 737
--id, 737
--project-id, 737
--snippet-id, 737
--sudo, 737
-h, 737
gitlab-project-snippet-get command line
    option
--help, 730
--id, 730
--project-id, 730
--sudo, 730
--all, 730
--get-all, 730
--help, 730
--h, 730
gitlab-project-snippet-list command line
    option
--all, 731
--get-all, 731
--help, 731
--h, 731
--page, 731
--per-page, 731
--project-id, 731
--sudo, 731
-h, 731
gitlab-project-snippet-note command line
    option
--help, 737
-h, 737
gitlab-project-snippet-note-award-emoji
    command line option
--help, 739
-h, 739
gitlab-project-snippet-note-award-emoji-create
    command line option
--help, 739
--name, 740
--note-id, 739
--project-id, 739
--snippet-id, 739
--sudo, 739
-h, 739
gitlab-project-snippet-note-award-emoji-delete
    command line option
--help, 740
--id, 740
--note-id, 740
--project-id, 740
--snippet-id, 740
--sudo, 740
-h, 740
gitlab-project-snippet-note-award-emoji-get
    command line option
--help, 740
--id, 740
--note-id, 740
--project-id, 740
--snippet-id, 740
--sudo, 740
-h, 740
gitlab-project-snippet-note-award-emoji-list
    command line option
--all, 741
--get-all, 741
--help, 741
--note-id, 741

```

```
--page, 741
--per-page, 741
--project-id, 741
--snippet-id, 741
--sudo, 741
-h, 741
gitlab-project-snippet-note-create command
    line option
--body, 737
--help, 737
--project-id, 737
--snippet-id, 737
--sudo, 737
-h, 737
gitlab-project-snippet-note-delete command
    line option
--help, 738
--id, 738
--project-id, 738
--snippet-id, 738
--sudo, 738
-h, 738
gitlab-project-snippet-note-get command
    line option
--help, 738
--id, 738
--project-id, 738
--snippet-id, 738
--sudo, 738
-h, 738
gitlab-project-snippet-note-list command
    line option
--all, 739
--get-all, 738
--help, 738
--page, 738
--per-page, 738
--project-id, 738
--snippet-id, 738
--sudo, 738
-h, 738
gitlab-project-snippet-note-update command
    line option
--body, 739
--help, 739
--id, 739
--project-id, 739
--snippet-id, 739
--sudo, 739
-h, 739
gitlab-project-snippet-update command line
    option
--content, 731
--description, 731
--file-name, 731
--help, 731
--id, 731
--project-id, 731
--sudo, 731
--title, 731
--visibility, 731
-h, 731
gitlab-project-snippet-user-agent-detail
    command line option
--help, 732
--id, 732
--project-id, 732
--sudo, 732
-h, 732
gitlab-project-star command line option
--help, 571
--id, 571
-h, 571
gitlab-project-storage command line option
--help, 741
-h, 741
gitlab-project-storage-get command line
    option
--help, 741
--id, 741
--project-id, 741
--sudo, 741
-h, 741
gitlab-project-tag command line option
--help, 742
-h, 742
gitlab-project-tag-create command line
    option
--help, 742
--message, 742
--project-id, 742
--ref, 742
--sudo, 742
--tag-name, 742
-h, 742
gitlab-project-tag-delete command line
    option
--help, 742
--name, 742
--project-id, 742
--sudo, 742
-h, 742
gitlab-project-tag-get command line option
--help, 742
--name, 742
--project-id, 742
--sudo, 742
-h, 742
```

```

gitlab-project-tag-list command line option      gitlab-project-trigger-pipeline command
    --all, 743                                     line option
    --get-all, 743
    --help, 743
    --page, 743
    --per-page, 743
    --project-id, 743
    --sudo, 743
    -h, 743
gitlab-project-transfer command line option     gitlab-project-trigger-update command line
    --help, 571                                     option
    --id, 571
    --to-namespace, 571
    -h, 571
gitlab-project-transfer-project command          gitlab-project-unarchive command line
    line option                                     option
    --help, 571
    --id, 571
    --to-namespace, 571
    -h, 571
gitlab-project-trigger command line option       gitlab-project-unshare command line option
    --help, 743
    -h, 743
gitlab-project-trigger-create command line        gitlab-project-unstar command line option
    option                                         --help, 572
    --description, 743
    --help, 743
    --project-id, 743
    --sudo, 743
    -h, 743
gitlab-project-trigger-delete command line        gitlab-project-update command line option
    option                                         --allow-merge-on-skipped-pipeline, 574
    --help, 744
    --id, 744
    --project-id, 744
    --sudo, 744
    -h, 744
gitlab-project-trigger-get command line          --analytics-access-level, 574
    option                                         --approvals-before-merge, 574
    --help, 744
    --id, 744
    --project-id, 744
    --sudo, 744
    -h, 744
gitlab-project-trigger-list command line          --auto-cancel-pending-pipelines, 574
    option                                         --auto-devops-deploy-strategy, 574
    --all, 744
    --get-all, 744
    --help, 744
    --page, 744
    --per-page, 744
    --project-id, 744
    --sudo, 744
    -h, 744

```

```
--help, 574
--id, 574
--import-url, 574
--issues-access-level, 574
--issues-enabled, 574
--issues-template, 576
--jobs-enabled, 575
--lfs-enabled, 575
--merge-method, 575
--merge-pipelines-enabled, 575
--merge-requests-access-level, 575
--merge-requests-enabled, 575
--merge-requests-template, 576
--mirror, 575
--mirror-overwrites-diverged-branches,
    575
--mirror-trigger-builds, 575
--mirror-user-id, 575
--name, 575
--only-allow-merge-if-all-discussions-are-resolved,
    575
--only-allow-merge-if-pipeline-succeeds,
    575
--only-mirror-protected-branches, 575
--operations-access-level, 575
--packages-enabled, 575
--pages-access-level, 575
--path, 575
--public-builds, 575
--remove-source-branch-after-merge, 575
--repository-access-level, 575
--repository-storage, 575
--request-access-enabled, 575
--requirements-access-level, 575
--resolve-outdated-diff-discussions, 575
--restrict-user-defined-variables, 575
--service-desk-enabled, 575
--shared-runners-enabled, 575
--show-default-award-emojis, 575
--snippets-access-level, 575
--snippets-enabled, 575
--squash-option, 576
--sudo, 574
--suggestion-commit-message, 576
--tag-list, 576
--topics, 576
--visibility, 576
--wiki-access-level, 576
--wiki-enabled, 576
-h, 574
gitlab-project-update-submodule command
    line option
    --branch, 576
    --commit-sha, 576
--help, 576
--id, 576
--submodule, 576
-h, 576
gitlab-project-upload command line option
    --filename, 576
    --filepath, 576
    --help, 576
    --id, 576
    -h, 576
gitlab-project-user command line option
    --help, 745
    -h, 745
gitlab-project-user-list command line
    option
    --all, 745
    --get-all, 745
    --help, 745
    --page, 745
    --per-page, 745
    --project-id, 745
    --search, 745
    --skip-users, 745
    --sudo, 745
    -h, 745
gitlab-project-variable command line option
    --help, 746
    -h, 746
gitlab-project-variable-create command line
    option
    --environment-scope, 746
    --help, 746
    --key, 746
    --masked, 746
    --project-id, 746
    --protected, 746
    --sudo, 746
    --value, 746
    --variable-type, 746
    -h, 746
gitlab-project-variable-delete command line
    option
    --help, 746
    --key, 746
    --project-id, 746
    --sudo, 746
    -h, 746
gitlab-project-variable-get command line
    option
    --help, 747
    --key, 747
    --project-id, 747
    --sudo, 747
    -h, 747
```

```
gitlab-project-variable-list command line
    option
    --all, 747
    --get-all, 747
    --help, 747
    --page, 747
    --per-page, 747
    --project-id, 747
    --sudo, 747
    -h, 747
gitlab-project-variable-update command line
    option
    --environment-scope, 748
    --help, 747
    --key, 747
    --masked, 748
    --project-id, 747
    --protected, 748
    --sudo, 747
    --value, 748
    --variable-type, 748
    -h, 747
gitlab-project-wiki command line option
    --help, 748
    -h, 748
gitlab-project-wiki-create command line
    option
    --content, 748
    --format, 748
    --help, 748
    --project-id, 748
    --sudo, 748
    --title, 748
    -h, 748
gitlab-project-wiki-delete command line
    option
    --help, 748
    --project-id, 748
    --slug, 748
    --sudo, 748
    -h, 748
gitlab-project-wiki-get command line option
    --help, 749
    --project-id, 749
    --slug, 749
    --sudo, 749
    -h, 749
gitlab-project-wiki-list command line
    option
    --all, 749
    --get-all, 749
    --help, 749
    --page, 749
    --per-page, 749
    --project-id, 749
    --sudo, 749
    -h, 749
    --with-content, 749
    -h, 749
gitlab-project-wiki-update command line
    option
    --content, 750
    --format, 750
    --help, 749
    --project-id, 749
    --slug, 749
    --sudo, 749
    --title, 749
    -h, 749
gitlab-registry-repository command line
    option
    --help, 750
    -h, 750
gitlab-registry-repository-get command line
    option
    --help, 750
    --id, 750
    --sudo, 750
    -h, 750
gitlab-runner command line option
    --help, 750
    -h, 750
gitlab-runner-all command line option
    --help, 750, 753
    --id, 750
    --scope, 750
    -h, 750, 753
gitlab-runner-all-list command line option
    --all, 753
    --get-all, 753
    --help, 753
    --page, 753
    --paused, 753
    --per-page, 753
    --scope, 753
    --status, 753
    --sudo, 753
    --tag-list, 753
    --type, 753
    -h, 753
gitlab-runner-create command line option
    --access-level, 751
    --active, 751
    --description, 751
    --help, 751
    --info, 751
    --locked, 751
    --maximum-timeout, 751
    --run-untagged, 751
```

```
--sudo, 751
--tag-list, 751
--token, 751
-h, 751
gitlab-runner-delete command line option
--help, 751
--id, 751
--sudo, 751
-h, 751
gitlab-runner-get command line option
--help, 751
--id, 751
--sudo, 751
-h, 751
gitlab-runner-job command line option
--help, 754
-h, 754
gitlab-runner-job-list command line option
--all, 754
--get-all, 754
--help, 754
--page, 754
--per-page, 754
--runner-id, 754
--status, 754
--sudo, 754
-h, 754
gitlab-runner-list command line option
--all, 752
--get-all, 752
--help, 752
--page, 752
--paused, 752
--per-page, 752
--scope, 752
--status, 752
--sudo, 752
--tag-list, 752
--type, 752
-h, 752
gitlab-runner-update command line option
--access-level, 753
--active, 752
--description, 752
--help, 752
--id, 752
--locked, 752
--maximum-timeout, 753
--run-untagged, 752
--sudo, 752
--tag-list, 752
-h, 752
gitlab-runner-verify command line option
--help, 753
--id, 753
--token, 753
-h, 753
gitlab-shared-project command line option
--help, 754
-h, 754
gitlab-shared-project-list command line
option
--all, 755
--archived, 755
--get-all, 755
--group-id, 755
--help, 755
--min-access-level, 755
--order-by, 755
--page, 755
--per-page, 755
--search, 755
--simple, 755
--sort, 755
--starred, 755
--sudo, 755
--visibility, 755
--with-custom-attributes, 755
--with-issues-enabled, 755
--with-merge-requests-enabled, 755
-h, 755
gitlab-snippet command line option
--help, 755
-h, 755
gitlab-snippet-content command line option
--help, 756
--id, 756
-h, 756
gitlab-snippet-create command line option
--content, 756
--file-name, 756
--help, 756
--lifetime, 756
--sudo, 756
--title, 756
--visibility, 756
-h, 756
gitlab-snippet-delete command line option
--help, 756
--id, 756
--sudo, 756
-h, 756
gitlab-snippet-get command line option
--help, 757
--id, 757
--sudo, 757
-h, 757
gitlab-snippet-list command line option
```

```

--all, 757
--get-all, 757
--help, 757
--page, 757
--per-page, 757
--sudo, 757
-h, 757
gitlab-snippet-public command line option
--help, 757
--id, 757
-h, 757
gitlab-snippet-update command line option
--content, 758
--file-name, 758
--help, 757
--id, 757
--sudo, 757
--title, 757
--visibility, 758
-h, 757
gitlab-snippet-user-agent-detail command
    line option
--help, 758
--id, 758
-h, 758
gitlab-starred-project command line option
--help, 758
-h, 758
gitlab-starred-project-list command line
    option
--all, 759
--archived, 758
--get-all, 759
--help, 758
--membership, 758
--min-access-level, 759
--order-by, 759
--owned, 759
--page, 759
--per-page, 759
--search, 759
--simple, 759
--sort, 759
--starred, 759
--statistics, 759
--sudo, 758
--user-id, 758
--visibility, 759
--with-custom-attributes, 759
--with-issues-enabled, 759
--with-merge-requests-enabled, 759
-h, 758
gitlab-todo command line option
--help, 759
gitlab-todo-delete command line option
--help, 759
--id, 759
--sudo, 759
-h, 759
gitlab-todo-list command line option
--action, 760
--all, 760
--author-id, 760
--get-all, 760
--help, 760
--page, 760
--per-page, 760
--project-id, 760
--state, 760
--sudo, 760
--type, 760
-h, 760
gitlab-todo-mark-all-as-done command line
    option
--help, 760
--id, 760
-h, 760
gitlab-todo-mark-as-done command line
    option
--help, 760
--id, 760
-h, 760
gitlab-topic command line option
--help, 761
-h, 761
gitlab-topic-create command line option
--avatar, 761
--description, 761
--help, 761
--name, 761
--sudo, 761
--title, 761
-h, 761
gitlab-topic-delete command line option
--help, 761
--id, 761
--sudo, 761
-h, 761
gitlab-topic-get command line option
--help, 761
--id, 761
--sudo, 761
-h, 761
gitlab-topic-list command line option
--all, 762
--get-all, 762
--help, 762

```

```
--page, 762
--per-page, 762
--sudo, 762
-h, 762
gitlab-topic-update command line option
--avatar, 762
--description, 762
--help, 762
--id, 762
--name, 762
--sudo, 762
-h, 762
gitlab-user command line option
--help, 763
-h, 763
gitlab-user-activate command line option
--help, 763
--id, 763
-h, 763
gitlab-user-activities command line option
--help, 769
-h, 769
gitlab-user-activities-list command line
    option
--all, 769
--get-all, 769
--help, 769
--page, 769
--per-page, 769
--sudo, 769
-h, 769
gitlab-user-approve command line option
--help, 763
--id, 763
-h, 763
gitlab-user-ban command line option
--help, 763
--id, 763
-h, 763
gitlab-user-block command line option
--help, 763
--id, 763
-h, 763
gitlab-user-create command line option
--admin, 764
--avatar, 765
--bio, 764
--can-create-group, 764
--color-scheme-id, 765
--email, 764
--extern-uid, 764
--external, 764
--help, 764
--linkedin, 764
--location, 765
--name, 764
--organization, 765
--password, 764
--private-profile, 765
--projects-limit, 764
--provider, 764
--public-email, 765
--reset-password, 764
--skip-confirmation, 764
--skype, 764
--sudo, 764
--theme-id, 765
--twitter, 764
--username, 764
--website-url, 764
-h, 764
gitlab-user-custom-attribute command line
    option
--help, 769
-h, 769
gitlab-user-custom-attribute-delete command
    line option
--help, 769
--key, 769
--sudo, 769
--user-id, 769
-h, 769
gitlab-user-custom-attribute-get command
    line option
--help, 770
--key, 770
--sudo, 770
--user-id, 770
-h, 770
gitlab-user-custom-attribute-list command
    line option
--all, 770
--get-all, 770
--help, 770
--page, 770
--per-page, 770
--sudo, 770
--user-id, 770
-h, 770
gitlab-user-deactivate command line option
--help, 765
--id, 765
-h, 765
gitlab-user-delete command line option
--help, 765
--id, 765
--sudo, 765
-h, 765
```

```
gitlab-user-email command line option
  --help, 770
  -h, 770
gitlab-user-email-create command line
  option
  --email, 771
  --help, 771
  --sudo, 771
  --user-id, 771
  -h, 771
gitlab-user-email-delete command line
  option
  --help, 771
  --id, 771
  --sudo, 771
  --user-id, 771
  -h, 771
gitlab-user-email-get command line option
  --help, 771
  --id, 771
  --sudo, 771
  --user-id, 771
  -h, 771
gitlab-user-email-list command line option
  --all, 772
  --get-all, 772
  --help, 771
  --page, 771
  --per-page, 772
  --sudo, 771
  --user-id, 771
  -h, 771
gitlab-user-event command line option
  --help, 772
  -h, 772
gitlab-user-event-list command line option
  --action, 772
  --after, 772
  --all, 772
  --before, 772
  --get-all, 772
  --help, 772
  --page, 772
  --per-page, 772
  --sort, 772
  --sudo, 772
  --target-type, 772
  --user-id, 772
  -h, 772
gitlab-user-follow command line option
  --help, 765
  --id, 765
  -h, 765
gitlab-user-get command line option
  --help, 766
  --id, 766
  --sudo, 766
  -h, 766
gitlab-user-gpg-key command line option
  --help, 773
  -h, 773
gitlab-user-gpg-key-create command line
  option
  --help, 773
  --key, 773
  --sudo, 773
  --user-id, 773
  -h, 773
gitlab-user-gpg-key-delete command line
  option
  --help, 773
  --id, 773
  --sudo, 773
  --user-id, 773
  -h, 773
gitlab-user-gpg-key-get command line option
  --help, 773
  --id, 773
  --sudo, 773
  --user-id, 773
  -h, 773
gitlab-user-gpg-key-list command line
  option
  --all, 774
  --get-all, 774
  --help, 774
  --page, 774
  --per-page, 774
  --sudo, 774
  --user-id, 774
  -h, 774
gitlab-user-impersonation-token command
  line option
  --help, 774
  -h, 774
gitlab-user-impersonation-token-create
  command line option
  --expires-at, 774
  --help, 774
  --name, 774
  --scopes, 774
  --sudo, 774
  --user-id, 774
  -h, 774
gitlab-user-impersonation-token-delete
  command line option
  --help, 775
  --id, 775
```

```
--sudo, 775
--user-id, 775
-h, 775
gitlab-user-impersonation-token-get command
    line option
--help, 775
--id, 775
--sudo, 775
--user-id, 775
-h, 775
gitlab-user-impersonation-token-list
    command line option
--all, 775
--get-all, 775
--help, 775
--page, 775
--per-page, 775
--state, 775
--sudo, 775
--user-id, 775
-h, 775
gitlab-user-key command line option
--help, 776
-h, 776
gitlab-user-key-create command line option
--help, 776
--key, 776
--sudo, 776
--title, 776
--user-id, 776
-h, 776
gitlab-user-key-delete command line option
--help, 776
--id, 776
--sudo, 776
--user-id, 776
-h, 776
gitlab-user-key-get command line option
--help, 776
--id, 776
--sudo, 776
--user-id, 776
-h, 776
gitlab-user-key-list command line option
--all, 777
--get-all, 777
--help, 777
--page, 777
--per-page, 777
--sudo, 777
--user-id, 777
-h, 777
gitlab-user-list command line option
--active, 766
--all, 766
--blocked, 766
--custom-attributes, 766
--extern-uid, 766
--external, 766
--get-all, 766
--help, 766
--page, 766
--per-page, 766
--provider, 766
--search, 766
--status, 766
--sudo, 766
--two-factor, 766
--username, 766
-h, 766
gitlab-user-membership command line option
--help, 777
-h, 777
gitlab-user-membership-get command line
    option
--help, 777
--source-id, 777
--sudo, 777
--user-id, 777
-h, 777
gitlab-user-membership-list command line
    option
--all, 778
--get-all, 778
--help, 777
--page, 778
--per-page, 778
--sudo, 777
--type, 778
--user-id, 778
-h, 777
gitlab-user-personal-access-token command
    line option
--help, 778
-h, 778
gitlab-user-personal-access-token-create
    command line option
--expires-at, 778
--help, 778
--name, 778
--scopes, 778
--sudo, 778
--user-id, 778
-h, 778
gitlab-user-project command line option
--help, 778
-h, 778
```

```

gitlab-user-project-create command line
    option
    --builds-enabled, 779
    --default-branch, 779
    --description, 779
    --help, 779
    --import-url, 779
    --issues-enabled, 779
    --merge-requests-enabled, 779
    --name, 779
    --only-allow-merge-if-build-succeeds, 779
    --public, 779
    --public-builds, 779
    --snippets-enabled, 779
    --squash-option, 779
    --sudo, 779
    --user-id, 779
    --visibility, 779
    --wall-enabled, 779
    --wiki-enabled, 779
    -h, 779

gitlab-user-project-list command line
    option
    --all, 781
    --archived, 780
    --get-all, 781
    --help, 780
    --id-after, 781
    --id-before, 781
    --membership, 780
    --min-access-level, 781
    --order-by, 780
    --owned, 780
    --page, 781
    --per-page, 781
    --repository-checksum-failed, 780
    --search, 780
    --simple, 780
    --sort, 780
    --starred, 780
    --statistics, 780
    --sudo, 780
    --user-id, 780
    --visibility, 780
    --wiki-checksum-failed, 780
    --with-custom-attributes, 780
    --with-issues-enabled, 780
    --with-merge-requests-enabled, 780
    --with-programming-language, 780
    -h, 780

gitlab-user-reject command line option
    --help, 767
    --id, 767
    -h, 767

gitlab-user-status command line option
    --help, 781
    -h, 781

gitlab-user-status-get command line option
    --help, 781
    --sudo, 781
    --user-id, 781
    -h, 781

gitlab-user-unban command line option
    --help, 767
    --id, 767
    -h, 767

gitlab-user-unblock command line option
    --help, 767
    --id, 767
    -h, 767

gitlab-user-unfollow command line option
    --help, 767
    --id, 767
    -h, 767

gitlab-user-update command line option
    --admin, 768
    --avatar, 768
    --bio, 768
    --can-create-group, 768
    --color-scheme-id, 768
    --email, 768
    --extern-uid, 768
    --external, 768
    --help, 768
    --id, 768
    --linkedin, 768
    --location, 768
    --name, 768
    --organization, 768
    --password, 768
    --private-profile, 768
    --projects-limit, 768
    --provider, 768
    --public-email, 768
    --skip-reconfirmation, 768
    --skype, 768
    --sudo, 768
    --theme-id, 768
    --twitter, 768
    --username, 768
    --website-url, 768
    -h, 768

gitlab-variable command line option
    --help, 781
    -h, 781

gitlab-variable-create command line option
    --help, 782
    --key, 782

```

```
--masked, 782
--protected, 782
--sudo, 782
--value, 782
--variable-type, 782
-h, 782
gitlab-variable-delete command line option
--help, 782
--key, 782
--sudo, 782
-h, 782
gitlab-variable-get command line option
--help, 782
--key, 782
--sudo, 782
-h, 782
gitlab-variable-list command line option
--all, 783
--get-all, 783
--help, 783
--page, 783
--per-page, 783
--sudo, 783
-h, 783
gitlab-variable-update command line option
--help, 783
--key, 783
--masked, 783
--protected, 783
--sudo, 783
--value, 783
--variable-type, 783
-h, 783
GitlabActivateError, 428
GitlabAttachFileError, 428
GitlabAuthenticationError, 428
GitlabBanError, 429
GitlabBlockError, 429
GitlabBuildCancelError, 429
GitlabBuildEraseError, 429
GitlabBuildPlayError, 430
GitlabBuildRetryError, 430
GitlabCancelError, 430
GitlabCherryPickError, 430
GitlabCiLintError, 431
Gitlabciyml (class in gitlab.v4.objects), 202
GitlabciymlManager (class in gitlab.v4.objects), 202
gitlabciymls (gitlab.Gitlab attribute), 174
GitlabConfigHelperError, 426
GitlabConfigMissingError, 426
GitlabConfigParser (class in gitlab.config), 426
GitlabConnectionError, 431
GitlabCreateError, 431
GitlabDataError, 426
GitlabDeactivateError, 431
GitlabDeleteError, 432
GitlabDeploymentApprovalError, 432
GitlabError, 432
GitlabFollowError, 432
GitlabGetError, 433
GitlabGroupTransferError, 433
GitlabHeadError, 433
GitlabHousekeepingError, 433
GitlabHttpError, 434
GitlabIDError, 426
GitlabImportError, 434
GitlabInvitationError, 434
GitlabJobCancelError, 434
GitlabJobEraseError, 435
GitlabJobPlayError, 435
GitlabJobRetryError, 435
GitlabLicenseError, 435
GitlabList (class in gitlab), 181
GitlabListError, 436
GitlabMarkdownError, 437
GitlabMRApprovalError, 436
GitlabMRClosedError, 436
GitlabMRForbiddenError, 436
GitlabMROnBuildSuccessError, 437
GitlabMRRebaseError, 437
GitlabMRResetApprovalError, 437
GitlabOperationError, 438
GitlabOwnershipError, 438
GitlabParsingError, 438
GitlabPipelineCancelError, 438
GitlabPipelinePlayError, 439
GitlabPipelineRetryError, 439
GitlabProjectDeployKeyError, 439
GitlabPromoteError, 439
GitlabProtectError, 440
GitlabRenderError, 440
GitlabRepairError, 440
GitlabRestoreError, 440
GitlabRetryError, 441
GitlabRevertError, 441
GitlabSearchError, 441
GitlabSetError, 441
GitlabStopError, 442
GitlabSubscribeError, 442
GitlabTimeTrackingError, 442
GitlabTodoError, 442
GitlabTransferProjectError, 443
GitlabUnbanError, 443
GitlabUnblockError, 443
GitlabUnfollowError, 443
GitlabUnsubscribeError, 444
GitlabUpdateError, 444
GitlabUploadError, 444
```

`GitlabUserApproveError`, 444
`GitlabUserRejectError`, 445
`GitlabVerifyError`, 445
`GLOBAL` (`gitlab.const.NotificationLevel` attribute), 427
`GLOBAL_SNIPPET_TITLES` (`gitlab.const.SearchScope` attribute), 427
`gpgkeys` (`gitlab.v4.objects.CurrentUser` attribute), 190
`gpgkeys` (`gitlab.v4.objects.User` attribute), 408
`Group` (`class in gitlab.v4.objects`), 203
`GroupAccessRequest` (`class in gitlab.v4.objects`), 207
`GroupAccessRequestManager` (`class in gitlab.v4.objects`), 207
`GroupAccessToken` (`class in gitlab.v4.objects`), 207
`GroupAccessTokenManager` (`class in gitlab.v4.objects`), 207
`GroupAuditEvent` (`class in gitlab.v4.objects`), 208
`GroupAuditEventManager` (`class in gitlab.v4.objects`), 208
`GroupBadge` (`class in gitlab.v4.objects`), 209
`GroupBadgeManager` (`class in gitlab.v4.objects`), 209
`GroupBillableMember` (`class in gitlab.v4.objects`), 210
`GroupBillableMemberManager` (`class in gitlab.v4.objects`), 210
`GroupBillableMemberMembership` (`class in gitlab.v4.objects`), 210
`GroupBillableMemberMembershipManager` (`class in gitlab.v4.objects`), 210
`GroupBoard` (`class in gitlab.v4.objects`), 211
`GroupBoardList` (`class in gitlab.v4.objects`), 211
`GroupBoardListManager` (`class in gitlab.v4.objects`), 211
`GroupBoardManager` (`class in gitlab.v4.objects`), 212
`GroupCluster` (`class in gitlab.v4.objects`), 213
`GroupClusterManager` (`class in gitlab.v4.objects`), 213
`GroupCustomAttribute` (`class in gitlab.v4.objects`), 214
`GroupCustomAttributeManager` (`class in gitlab.v4.objects`), 214
`GroupDeployToken` (`class in gitlab.v4.objects`), 215
`GroupDeployTokenManager` (`class in gitlab.v4.objects`), 215
`GroupDescendantGroup` (`class in gitlab.v4.objects`), 216
`GroupDescendantGroupManager` (`class in gitlab.v4.objects`), 216
`GroupEpic` (`class in gitlab.v4.objects`), 217
`GroupEpicAwardEmoji` (`class in gitlab.v4.objects`), 217
`GroupEpicAwardEmojiManager` (`class in gitlab.v4.objects`), 217
`GroupEpicDiscussionNote` (`class in gitlab.v4.objects`), 218
`GroupEpicDiscussionNoteManager` (`class in gitlab.v4.objects`), 218
`GroupEpicIssue` (`class in gitlab.v4.objects`), 219
`GroupEpicIssueManager` (`class in gitlab.v4.objects`), 219
`GroupEpicManager` (`class in gitlab.v4.objects`), 220
`GroupEpicNote` (`class in gitlab.v4.objects`), 221
`GroupEpicNoteAwardEmoji` (`class in gitlab.v4.objects`), 222
`GroupEpicNoteAwardEmojiManager` (`class in gitlab.v4.objects`), 222
`GroupEpicNoteManager` (`class in gitlab.v4.objects`), 222
`GroupEpicResourceLabelEvent` (`class in gitlab.v4.objects`), 223
`GroupEpicResourceLabelEventManager` (`class in gitlab.v4.objects`), 224
`GroupExport` (`class in gitlab.v4.objects`), 224
`GroupExportManager` (`class in gitlab.v4.objects`), 224
`GroupHook` (`class in gitlab.v4.objects`), 225
`GroupHookManager` (`class in gitlab.v4.objects`), 225
`GroupImport` (`class in gitlab.v4.objects`), 227
`GroupImportManager` (`class in gitlab.v4.objects`), 227
`GroupInvitation` (`class in gitlab.v4.objects`), 227
`GroupInvitationManager` (`class in gitlab.v4.objects`), 228
`GroupIssue` (`class in gitlab.v4.objects`), 229
`GroupIssueManager` (`class in gitlab.v4.objects`), 229
`GroupIssuesStatistics` (`class in gitlab.v4.objects`), 230
`GroupIssuesStatisticsManager` (`class in gitlab.v4.objects`), 230
`GroupIteration` (`class in gitlab.v4.objects`), 230
`GroupIterationManager` (`class in gitlab.v4.objects`), 231
`GroupLabel` (`class in gitlab.v4.objects`), 231
`GroupLabelManager` (`class in gitlab.v4.objects`), 232
`GroupManager` (`class in gitlab.v4.objects`), 233
`GroupMember` (`class in gitlab.v4.objects`), 235
`GroupMemberAll` (`class in gitlab.v4.objects`), 236
`GroupMemberAllManager` (`class in gitlab.v4.objects`), 236
`GroupMemberManager` (`class in gitlab.v4.objects`), 236
`GroupMergeRequest` (`class in gitlab.v4.objects`), 237
`GroupMergeRequestManager` (`class in gitlab.v4.objects`), 237
`GroupMilestone` (`class in gitlab.v4.objects`), 238
`GroupMilestoneManager` (`class in gitlab.v4.objects`), 239
`GroupNotificationSettings` (`class in gitlab.v4.objects`), 240
`GroupNotificationSettingsManager` (`class in gitlab.v4.objects`), 241
`GroupPackage` (`class in gitlab.v4.objects`), 241
`GroupPackageManager` (`class in gitlab.v4.objects`), 242
`GroupProject` (`class in gitlab.v4.objects`), 242
`GroupProjectManager` (`class in gitlab.v4.objects`), 242

GroupPushRules (*class in gitlab.v4.objects*), 243
GroupPushRulesManager (*class in gitlab.v4.objects*), 243
GroupRegistryRepositoryManager (*class in gitlab.v4.objects*), 244
GroupRunner (*class in gitlab.v4.objects*), 245
GroupRunnerManager (*class in gitlab.v4.objects*), 245
groups (*gitlab.Gitlab attribute*), 174
groups (*gitlab.v4.objects.Project attribute*), 261
GroupSubgroup (*class in gitlab.v4.objects*), 245
GroupSubgroupManager (*class in gitlab.v4.objects*), 246
GroupVariable (*class in gitlab.v4.objects*), 246
GroupVariableManager (*class in gitlab.v4.objects*), 246
GroupWiki (*class in gitlab.v4.objects*), 247
GroupWikiManager (*class in gitlab.v4.objects*), 248
GUEST (*gitlab.const.AccessLevel attribute*), 427

H

headers (*gitlab.Gitlab attribute*), 174
Hook (*class in gitlab.v4.objects*), 248
HookManager (*class in gitlab.v4.objects*), 249
hooks (*gitlab.Gitlab attribute*), 174
hooks (*gitlab.v4.objects.Group attribute*), 204
hooks (*gitlab.v4.objects.Project attribute*), 261
housekeeping() (*gitlab.v4.objects.Project method*), 261
http_delete() (*gitlab.Gitlab method*), 174
http_get() (*gitlab.Gitlab method*), 174
http_head() (*gitlab.Gitlab method*), 175
http_list() (*gitlab.Gitlab method*), 175
http_post() (*gitlab.Gitlab method*), 176
http_put() (*gitlab.Gitlab method*), 176
http_request() (*gitlab.Gitlab method*), 177

I

id (*gitlab.v4.objects.ProjectMergeRequestApprovalRule attribute*), 339
identityproviders (*gitlab.v4.objects.User attribute*), 408
impersonationtokens (*gitlab.v4.objects.User attribute*), 408
import_bitbucket_server() (*gitlab.v4.objects.ProjectManager method*), 329
import_github() (*gitlab.v4.objects.ProjectManager method*), 330
import_group() (*gitlab.v4.objects.GroupManager method*), 235
import_project() (*gitlab.v4.objects.ProjectManager method*), 331
imports (*gitlab.v4.objects.Group attribute*), 204
imports (*gitlab.v4.objects.Project attribute*), 261

J

integrations (*gitlab.v4.objects.Project attribute*), 261
INTERNAL (*gitlab.const.Visibility attribute*), 428
invitations (*gitlab.v4.objects.Group attribute*), 204
invitations (*gitlab.v4.objects.Project attribute*), 261
Issue (*class in gitlab.v4.objects*), 249
IssueManager (*class in gitlab.v4.objects*), 250
ISSUES (*gitlab.const.SearchScope attribute*), 427
issues (*gitlab.Gitlab attribute*), 178
issues (*gitlab.v4.objects.Group attribute*), 204
issues (*gitlab.v4.objects.GroupEpic attribute*), 217
issues (*gitlab.v4.objects.Project attribute*), 261
issues() (*gitlab.v4.objects.GroupMilestone method*), 239
issues() (*gitlab.v4.objects.ProjectMilestone method*), 353
issues_statistics (*gitlab.Gitlab attribute*), 178
issues_statistics (*gitlab.v4.objects.Group attribute*), 204
issues_statistics (*gitlab.v4.objects.Project attribute*), 261
IssuesStatistics (*class in gitlab.v4.objects*), 251
IssuesStatisticsManager (*class in gitlab.v4.objects*), 251
iterations (*gitlab.v4.objects.Group attribute*), 204
iterations (*gitlab.v4.objects.Project attribute*), 261

K

job_stats() (*gitlab.v4.objects.SidekiqManager method*), 400
jobs (*gitlab.v4.objects.Project attribute*), 261
jobs (*gitlab.v4.objects.ProjectPipeline attribute*), 360
jobs (*gitlab.v4.objects.Runner attribute*), 395

L

keep_artifacts() (*gitlab.v4.objects.ProjectJob method*), 319
Key (*class in gitlab.v4.objects*), 251
KeyManager (*class in gitlab.v4.objects*), 252
keys (*gitlab.Gitlab attribute*), 178
keys (*gitlab.v4.objects.CurrentUser attribute*), 190
keys (*gitlab.v4.objects.Project attribute*), 261
keys (*gitlab.v4.objects.User attribute*), 408

M

languages() (*gitlab.v4.objects.Project method*), 261
ldap_sync() (*gitlab.v4.objects.Group method*), 204
LDAPGroup (*class in gitlab.v4.objects*), 252
LDAPGroupManager (*class in gitlab.v4.objects*), 252
ldapgroups (*gitlab.Gitlab attribute*), 178
License (*class in gitlab.v4.objects*), 253
LicenseManager (*class in gitlab.v4.objects*), 253

licenses (*gitlab.Gitlab attribute*), 178
 links (*gitlab.v4.objects.ProjectIssue attribute*), 305
 links (*gitlab.v4.objects.ProjectRelease attribute*), 374
 lint() (*gitlab.Gitlab method*), 178
 list() (*gitlab.mixins.ListMixin method*), 448
 list() (*gitlab.v4.objects.LDAPGroupManager method*), 253
 list() (*gitlab.v4.objects.UserProjectManager method*), 420
ListMixin (*class in gitlab.mixins*), 448
 lists (*gitlab.v4.objects.GroupBoard attribute*), 211
 lists (*gitlab.v4.objects.ProjectBoard attribute*), 275

M

main() (*in module gitlab.cli*), 426
 MAINTAINER (*gitlab.const.AccessLevel attribute*), 427
 manager (*gitlab.base.RESTObject attribute*), 424
 manager (*gitlab.mixins.AccessRequestMixin attribute*), 446
 manager (*gitlab.mixins.DownloadMixin attribute*), 447
 manager (*gitlab.mixins.ObjectDeleteMixin attribute*), 449
 manager (*gitlab.mixins.ParticipantsMixin attribute*), 449
 manager (*gitlab.mixins.RefreshMixin attribute*), 450
 manager (*gitlab.mixins.SaveMixin attribute*), 450
 manager (*gitlab.mixins.SubscribableMixin attribute*), 451
 manager (*gitlab.mixins.TimeTrackingMixin attribute*), 452
 manager (*gitlab.mixins.TodoMixin attribute*), 453
 manager (*gitlab.mixins.UserAgentDetailMixin attribute*), 454
 manager (*gitlab.v4.objects.Application attribute*), 182
 manager (*gitlab.v4.objects.ApplicationAppearance attribute*), 182
 manager (*gitlab.v4.objects.ApplicationSettings attribute*), 184
 manager (*gitlab.v4.objects.AuditEvent attribute*), 187
 manager (*gitlab.v4.objects.BroadcastMessage attribute*), 188
 manager (*gitlab.v4.objects.CiLint attribute*), 189
 manager (*gitlab.v4.objects.CurrentUserEmail attribute*), 190
 manager (*gitlab.v4.objects.CurrentUserGPGKey attribute*), 191
 manager (*gitlab.v4.objects.CurrentUserKey attribute*), 192
 manager (*gitlab.v4.objects.CurrentUserStatus attribute*), 194
 manager (*gitlab.v4.objects.DeployKey attribute*), 194
 manager (*gitlab.v4.objects.DeployToken attribute*), 195
 manager (*gitlab.v4.objects.Dockerfile attribute*), 195
 manager (*gitlab.v4.objects.Event attribute*), 196
 manager (*gitlab.v4.objects.Feature attribute*), 197
 manager (*gitlab.v4.objects.GenericPackage attribute*), 198
 manager (*gitlab.v4.objects.GeoNode attribute*), 199
 manager (*gitlab.v4.objects.Gitignore attribute*), 201
 manager (*gitlab.v4.objects.Gitlabciyml attribute*), 202
 manager (*gitlab.v4.objects.GroupAccessRequest attribute*), 207
 manager (*gitlab.v4.objects.GroupAccessToken attribute*), 207
 manager (*gitlab.v4.objects.GroupAuditEvent attribute*), 208
 manager (*gitlab.v4.objects.GroupBadge attribute*), 209
 manager (*gitlab.v4.objects.GroupBillableMemberMembership attribute*), 210
 manager (*gitlab.v4.objects.GroupBoardList attribute*), 211
 manager (*gitlab.v4.objects.GroupCluster attribute*), 213
 manager (*gitlab.v4.objects.GroupCustomAttribute attribute*), 214
 manager (*gitlab.v4.objects.GroupDeployToken attribute*), 215
 manager (*gitlab.v4.objects.GroupDescendantGroup attribute*), 216
 manager (*gitlab.v4.objects.GroupEpicAwardEmoji attribute*), 217
 manager (*gitlab.v4.objects.GroupEpicDiscussionNote attribute*), 218
 manager (*gitlab.v4.objects.GroupEpicIssue attribute*), 219
 manager (*gitlab.v4.objects.GroupEpicNoteAwardEmoji attribute*), 222
 manager (*gitlab.v4.objects.GroupEpicResourceLabelEvent attribute*), 223
 manager (*gitlab.v4.objects.GroupExport attribute*), 224
 manager (*gitlab.v4.objects.GroupHook attribute*), 225
 manager (*gitlab.v4.objects.GroupImport attribute*), 227
 manager (*gitlab.v4.objects.GroupInvitation attribute*), 228
 manager (*gitlab.v4.objects.GroupIssue attribute*), 229
 manager (*gitlab.v4.objects.GroupIssuesStatistics attribute*), 230
 manager (*gitlab.v4.objects.GroupIteration attribute*), 231
 manager (*gitlab.v4.objects.GroupLabel attribute*), 231
 manager (*gitlab.v4.objects.GroupMember attribute*), 236
 manager (*gitlab.v4.objects.GroupMemberAll attribute*), 236
 manager (*gitlab.v4.objects.GroupMergeRequest attribute*), 237
 manager (*gitlab.v4.objects.GroupMilestone attribute*), 239
 manager (*gitlab.v4.objects.GroupNotificationSettings attribute*), 241
 manager (*gitlab.v4.objects.GroupPackage attribute*), 242
 manager (*gitlab.v4.objects.GroupProject attribute*), 242

manager (`gitlab.v4.objects.GroupPushRules` attribute), 243
manager (`gitlab.v4.objects.GroupRunner` attribute), 245
manager (`gitlab.v4.objects.GroupSubgroup` attribute), 246
manager (`gitlab.v4.objects.GroupVariable` attribute), 246
manager (`gitlab.v4.objects.GroupWiki` attribute), 247
manager (`gitlab.v4.objects.Hook` attribute), 249
manager (`gitlab.v4.objects.Issue` attribute), 250
manager (`gitlab.v4.objects.IssuesStatistics` attribute), 251
manager (`gitlab.v4.objects.Key` attribute), 252
manager (`gitlab.v4.objects.LDAPGroup` attribute), 252
manager (`gitlab.v4.objects.License` attribute), 253
manager (`gitlab.v4.objects.MergeRequest` attribute), 254
manager (`gitlab.v4.objects.Namespace` attribute), 256
manager (`gitlab.v4.objects.NotificationSettings` attribute), 257
manager (`gitlab.v4.objects.PagesDomain` attribute), 258
manager (`gitlab.v4.objects.PersonalAccessToken` attribute), 259
manager (`gitlab.v4.objects.ProjectAccessRequest` attribute), 266
manager (`gitlab.v4.objects.ProjectAccessToken` attribute), 267
manager (`gitlab.v4.objects.ProjectAdditionalStatistics` attribute), 268
manager (`gitlab.v4.objects.ProjectApproval` attribute), 268
manager (`gitlab.v4.objects.ProjectApprovalRule` attribute), 270
manager (`gitlab.v4.objects.ProjectArtifact` attribute), 270
manager (`gitlab.v4.objects.ProjectAudit` attribute), 272
manager (`gitlab.v4.objects.ProjectAuditEvent` attribute), 273
manager (`gitlab.v4.objects.ProjectBadge` attribute), 274
manager (`gitlab.v4.objects.ProjectBoardList` attribute), 275
manager (`gitlab.v4.objects.ProjectBranch` attribute), 277
manager (`gitlab.v4.objects.ProjectCiLint` attribute), 278
manager (`gitlab.v4.objects.ProjectCluster` attribute), 279
manager (`gitlab.v4.objects.ProjectCommitComment` attribute), 282
manager (`gitlab.v4.objects.ProjectCommitDiscussionNote` attribute), 284
manager (`gitlab.v4.objects.ProjectCommitStatus` attribute), 286
manager (`gitlab.v4.objects.ProjectCustomAttribute` attribute), 287
manager (`gitlab.v4.objects.ProjectDeploymentMergeRequest` attribute), 291
manager (`gitlab.v4.objects.ProjectDeployToken` attribute), 288
manager (`gitlab.v4.objects.ProjectEnvironment` attribute), 292
manager (`gitlab.v4.objects.ProjectEvent` attribute), 293
manager (`gitlab.v4.objects.ProjectExport` attribute), 294
manager (`gitlab.v4.objects.ProjectFile` attribute), 295
manager (`gitlab.v4.objects.ProjectFork` attribute), 299
manager (`gitlab.v4.objects.ProjectHook` attribute), 300
manager (`gitlab.v4.objects.ProjectImport` attribute), 302
manager (`gitlab.v4.objects.ProjectIntegration` attribute), 303
manager (`gitlab.v4.objects.ProjectInvitation` attribute), 304
manager (`gitlab.v4.objects.ProjectIssueAwardEmoji` attribute), 307
manager (`gitlab.v4.objects.ProjectIssueDiscussionNote` attribute), 308
manager (`gitlab.v4.objects.ProjectIssueLink` attribute), 309
manager (`gitlab.v4.objects.ProjectIssueNoteAwardEmoji` attribute), 312
manager (`gitlab.v4.objects.ProjectIssueResourceLabelEvent` attribute), 314
manager (`gitlab.v4.objects.ProjectIssueResourceMilestoneEvent` attribute), 315
manager (`gitlab.v4.objects.ProjectIssueResourceStateEvent` attribute), 316
manager (`gitlab.v4.objects.ProjectIssuesStatistics` attribute), 317
manager (`gitlab.v4.objects.ProjectJob` attribute), 320
manager (`gitlab.v4.objects.ProjectKey` attribute), 321
manager (`gitlab.v4.objects.ProjectLabel` attribute), 323
manager (`gitlab.v4.objects.ProjectMember` attribute), 332
manager (`gitlab.v4.objects.ProjectMemberAll` attribute), 332
manager (`gitlab.v4.objects.ProjectMergeRequestApproval` attribute), 337
manager (`gitlab.v4.objects.ProjectMergeRequestApprovalState` attribute), 341
manager (`gitlab.v4.objects.ProjectMergeRequestAwardEmoji` attribute), 341
manager (`gitlab.v4.objects.ProjectMergeRequestDiff` attribute), 342
manager (`gitlab.v4.objects.ProjectMergeRequestDiscussionNote` attribute), 344
manager (`gitlab.v4.objects.ProjectMergeRequestNoteAwardEmoji` attribute), 348
manager (`gitlab.v4.objects.ProjectMergeRequestPipeline` attribute), 349
manager (`gitlab.v4.objects.ProjectMergeRequestResourceLabelEvent` attribute), 350
manager (`gitlab.v4.objects.ProjectMergeRequestResourceMilestoneEvent` attribute), 351
manager (`gitlab.v4.objects.ProjectMergeRequestResourceStateEvent` attribute), 352
manager (`gitlab.v4.objects.ProjectMergeTrain` attribute),

manager (*gitlab.v4.objects.ProjectMilestone attribute*), 353
 manager (*gitlab.v4.objects.ProjectNote attribute*), 355
 manager (*gitlab.v4.objects.ProjectNotificationSettings attribute*), 356
 manager (*gitlab.v4.objects.ProjectPackageFile attribute*), 357
 manager (*gitlab.v4.objects.ProjectPagesDomain attribute*), 359
 manager (*gitlab.v4.objects.ProjectPipelineBridge attribute*), 361
 manager (*gitlab.v4.objects.ProjectPipelineJob attribute*), 361
 manager (*gitlab.v4.objects.ProjectPipelineScheduleVariable attribute*), 365
 manager (*gitlab.v4.objects.ProjectPipelineTestReport attribute*), 365
 manager (*gitlab.v4.objects.ProjectPipelineTestReportSummary attribute*), 366
 manager (*gitlab.v4.objects.ProjectPipelineVariable attribute*), 367
 manager (*gitlab.v4.objects.ProjectProtectedBranch attribute*), 367
 manager (*gitlab.v4.objects.ProjectProtectedEnvironment attribute*), 369
 manager (*gitlab.v4.objects.ProjectProtectedTag attribute*), 370
 manager (*gitlab.v4.objects.ProjectPushRules attribute*), 371
 manager (*gitlab.v4.objects.ProjectRegistryTag attribute*), 373
 manager (*gitlab.v4.objects.ProjectReleaseLink attribute*), 374
 manager (*gitlab.v4.objects.ProjectRemoteMirror attribute*), 376
 manager (*gitlab.v4.objects.ProjectRunner attribute*), 377
 manager (*gitlab.v4.objects.ProjectService attribute*), 378
 manager (*gitlab.v4.objects.ProjectSnippetAwardEmoji attribute*), 379
 manager (*gitlab.v4.objects.ProjectSnippetDiscussionNote attribute*), 381
 manager (*gitlab.v4.objects.ProjectSnippetNoteAwardEmoji attribute*), 383
 manager (*gitlab.v4.objects.ProjectStorage attribute*), 385
 manager (*gitlab.v4.objects.ProjectTag attribute*), 386
 manager (*gitlab.v4.objects.ProjectTrigger attribute*), 387
 manager (*gitlab.v4.objects.ProjectUser attribute*), 388
 manager (*gitlab.v4.objects.ProjectVariable attribute*), 388
 manager (*gitlab.v4.objects.ProjectWiki attribute*), 390
 manager (*gitlab.v4.objects.RegistryRepository attribute*), 391
 manager (*gitlab.v4.objects.RunnerAll attribute*), 395
 manager (*gitlab.v4.objects.RunnerJob attribute*), 396
 manager (*gitlab.v4.objects.SharedProject attribute*), 399
 manager (*gitlab.v4.objects.Snippet attribute*), 401
 manager (*gitlab.v4.objects.StarredProject attribute*), 403
 manager (*gitlab.v4.objects.Todo attribute*), 404
 manager (*gitlab.v4.objects.Topic attribute*), 405
 manager (*gitlab.v4.objects.UserActivities attribute*), 409
 manager (*gitlab.v4.objects.UserCustomAttribute attribute*), 410
 manager (*gitlab.v4.objects.UserEmail attribute*), 411
 manager (*gitlab.v4.objects.UserEvent attribute*), 411
 manager (*gitlab.v4.objects.UserGPGKey attribute*), 412
 manager (*gitlab.v4.objects.UserImpersonationToken attribute*), 413
 manager (*gitlab.v4.objects.UserKey attribute*), 414
 manager (*gitlab.v4.objects.UserMembership attribute*), 417
 manager (*gitlab.v4.objects.UserPersonalAccessToken attribute*), 418
 manager (*gitlab.v4.objects.UserProject attribute*), 419
 manager (*gitlab.v4.objects.UserStatus attribute*), 421
 manager (*gitlab.v4.objects.Variable attribute*), 422
 mark_all_as_done() (*gitlab.v4.objects.TodoManager method*), 404
 mark_as_done() (*gitlab.v4.objects.Todo method*), 404
 markdown() (*gitlab.Gitlab method*), 178
 members (*gitlab.v4.objects.Group attribute*), 204
 members (*gitlab.v4.objects.Project attribute*), 261
 members_all (*gitlab.v4.objects.Group attribute*), 204
 members_all (*gitlab.v4.objects.Project attribute*), 261
 memberships (*gitlab.v4.objects.GroupBillableMember attribute*), 210
 memberships (*gitlab.v4.objects.User attribute*), 408
 MENTION (*gitlab.const.NotificationLevel attribute*), 427
 merge() (*gitlab.v4.objects.ProjectMergeRequest method*), 336
 merge_config() (*gitlab.Gitlab class method*), 178
 merge_ref() (*gitlab.v4.objects.ProjectMergeRequest method*), 336
 merge_request_iid (*gitlab.v4.objects.ProjectMergeRequestApprovalRule attribute*), 339
 MERGE_REQUESTS (*gitlab.const.SearchScope attribute*), 427
 merge_requests() (*gitlab.v4.objects.GroupMilestone method*), 239
 merge_requests() (*gitlab.v4.objects.ProjectCommit method*), 281
 merge_requests() (*gitlab.v4.objects.ProjectMilestone method*), 354
 merge_trains (*gitlab.v4.objects.Project attribute*), 261
 MergeRequest (*class in gitlab.v4.objects*), 254
 MergeRequestManager (*class in gitlab.v4.objects*), 254
 mergerequests (*gitlab.Gitlab attribute*), 179

mergerequests (*gitlab.v4.objects.Group attribute*), 205
mergerequests (*gitlab.v4.objects.Project attribute*), 262
mergerequests (*gitlab.v4.objects.ProjectDeployment attribute*), 290
MILESTONES (*gitlab.const.SearchScope attribute*), 427
milestones (*gitlab.v4.objects.Group attribute*), 205
milestones (*gitlab.v4.objects.Project attribute*), 262
MINIMAL_ACCESS (*gitlab.const.AccessLevel attribute*), 427
mirror_pull() (*gitlab.v4.objects.Project method*), 262
module
 gitlab.base, 423
 gitlab.cli, 425
 gitlab.config, 426
 gitlab.const, 427
 gitlab.exceptions, 428
 gitlab.mixins, 445
 gitlab.utils, 454
 gitlab.v4, 423
 gitlab.v4.objects, 182
move() (*gitlab.v4.objects.ProjectIssue method*), 305

N

Namespace (*class in gitlab.v4.objects*), 255
NamespaceManager (*class in gitlab.v4.objects*), 256
namespaces (*gitlab.Gitlab attribute*), 179
next() (*gitlab.base.RESTObjectList method*), 425
next() (*gitlab.GitlabList method*), 181
next_page (*gitlab.base.RESTObjectList property*), 425
next_page (*gitlab.GitlabList property*), 181
NO_ACCESS (*gitlab.const.AccessLevel attribute*), 427
notes (*gitlab.v4.objects.GroupEpic attribute*), 217
notes (*gitlab.v4.objects.Project attribute*), 262
notes (*gitlab.v4.objects.ProjectCommitDiscussion attribute*), 283
notes (*gitlab.v4.objects.ProjectIssue attribute*), 306
notes (*gitlab.v4.objects.ProjectIssueDiscussion attribute*), 307
notes (*gitlab.v4.objects.ProjectMergeRequest attribute*), 336
notes (*gitlab.v4.objects.ProjectMergeRequestDiscussion attribute*), 343
notes (*gitlab.v4.objects.ProjectSnippet attribute*), 379
notes (*gitlab.v4.objects.ProjectSnippetDiscussion attribute*), 380
NotificationLevel (*class in gitlab.const*), 427
NotificationSettings (*class in gitlab.v4.objects*), 257
notificationsettings (*gitlab.Gitlab attribute*), 179
notificationsettings (*gitlab.v4.objects.Group attribute*), 205
notificationsettings (*gitlab.v4.objects.Project attribute*), 262

NotificationSettingsManager (*class in gitlab.v4.objects*), 257
NoUpdateMixin (*class in gitlab.mixins*), 449

O

ObjectDeleteMixin (*class in gitlab.mixins*), 449
OWNER (*gitlab.const.AccessLevel attribute*), 427

P

package_files (*gitlab.v4.objects.ProjectPackage attribute*), 357
packages (*gitlab.v4.objects.Group attribute*), 205
packages (*gitlab.v4.objects.Project attribute*), 262
PagesDomain (*class in gitlab.v4.objects*), 258
PagesDomainManager (*class in gitlab.v4.objects*), 258
pagesdomains (*gitlab.Gitlab attribute*), 179
pagesdomains (*gitlab.v4.objects.Project attribute*), 262
parent_attrs (*gitlab.base.RESTManager property*), 423
participants() (*gitlab.mixins.ParticipantsMixin method*), 449
ParticipantsMixin (*class in gitlab.mixins*), 449
PARTICIPATING (*gitlab.const.NotificationLevel attribute*), 427
path (*gitlab.base.RESTManager property*), 423
per_page (*gitlab.base.RESTObjectList property*), 425
per_page (*gitlab.GitlabList property*), 182
personal_access_tokens (*gitlab.Gitlab attribute*), 179
personal_access_tokens (*gitlab.v4.objects.User attribute*), 408
PersonalAccessToken (*class in gitlab.v4.objects*), 258
PersonalAccessTokenManager (*class in gitlab.v4.objects*), 259
pformat() (*gitlab.base.RESTObject method*), 424
pipelines (*gitlab.v4.objects.Project attribute*), 262
pipelines (*gitlab.v4.objects.ProjectMergeRequest attribute*), 336
pipelineschedules (*gitlab.v4.objects.Project attribute*), 262
play() (*gitlab.v4.objects.ProjectJob method*), 320
play() (*gitlab.v4.objects.ProjectPipelineSchedule method*), 363
pprint() (*gitlab.base.RESTObject method*), 424
prev_page (*gitlab.base.RESTObjectList property*), 425
prev_page (*gitlab.GitlabList property*), 182
PRIVATE (*gitlab.const.Visibility attribute*), 428
process_metrics() (*gitlab.v4.objects.SidekiqManager method*), 400
Project (*class in gitlab.v4.objects*), 259
PROJECT_NOTES (*gitlab.const.SearchScope attribute*), 427
ProjectAccessRequest (*class in gitlab.v4.objects*), 266

ProjectAccessRequestManager (class in gitlab.v4.objects), 267
ProjectAccessToken (class in gitlab.v4.objects), 267
ProjectAccessTokenManager (class in gitlab.v4.objects), 267
ProjectAdditionalStatistics (class in gitlab.v4.objects), 267
ProjectAdditionalStatisticsManager (class in gitlab.v4.objects), 268
ProjectApproval (class in gitlab.v4.objects), 268
ProjectApprovalManager (class in gitlab.v4.objects), 268
ProjectApprovalRule (class in gitlab.v4.objects), 270
ProjectApprovalRuleManager (class in gitlab.v4.objects), 270
ProjectArtifact (class in gitlab.v4.objects), 270
ProjectArtifactManager (class in gitlab.v4.objects), 270
ProjectAudit (class in gitlab.v4.objects), 272
ProjectAuditEvent (class in gitlab.v4.objects), 272
ProjectAuditEventManager (class in gitlab.v4.objects), 273
ProjectAuditManager (class in gitlab.v4.objects), 273
ProjectBadge (class in gitlab.v4.objects), 274
ProjectBadgeManager (class in gitlab.v4.objects), 274
ProjectBoard (class in gitlab.v4.objects), 275
ProjectBoardList (class in gitlab.v4.objects), 275
ProjectBoardListManager (class in gitlab.v4.objects), 275
ProjectBoardManager (class in gitlab.v4.objects), 276
ProjectBranch (class in gitlab.v4.objects), 277
ProjectBranchManager (class in gitlab.v4.objects), 277
ProjectCiLint (class in gitlab.v4.objects), 277
ProjectCiLintManager (class in gitlab.v4.objects), 278
ProjectCluster (class in gitlab.v4.objects), 279
ProjectClusterManager (class in gitlab.v4.objects), 279
ProjectCommit (class in gitlab.v4.objects), 280
ProjectCommitComment (class in gitlab.v4.objects), 282
ProjectCommitCommentManager (class in gitlab.v4.objects), 283
ProjectCommitDiscussion (class in gitlab.v4.objects), 283
ProjectCommitDiscussionManager (class in gitlab.v4.objects), 283
ProjectCommitDiscussionNote (class in gitlab.v4.objects), 284
ProjectCommitDiscussionNoteManager (class in gitlab.v4.objects), 284
ProjectCommitManager (class in gitlab.v4.objects), 285
ProjectCommitStatus (class in gitlab.v4.objects), 286
ProjectCommitStatusManager (class in gitlab.v4.objects), 286
ProjectCustomAttribute (class in gitlab.v4.objects), 287
ProjectCustomAttributeManager (class in gitlab.v4.objects), 287
ProjectDeployment (class in gitlab.v4.objects), 289
ProjectDeploymentManager (class in gitlab.v4.objects), 290
ProjectDeploymentMergeRequest (class in gitlab.v4.objects), 291
ProjectDeploymentMergeRequestManager (class in gitlab.v4.objects), 291
ProjectDeployToken (class in gitlab.v4.objects), 288
ProjectDeployTokenManager (class in gitlab.v4.objects), 288
ProjectEnvironment (class in gitlab.v4.objects), 292
ProjectEnvironmentManager (class in gitlab.v4.objects), 292
ProjectEvent (class in gitlab.v4.objects), 293
ProjectEventManager (class in gitlab.v4.objects), 294
ProjectExport (class in gitlab.v4.objects), 294
ProjectExportManager (class in gitlab.v4.objects), 294
ProjectFile (class in gitlab.v4.objects), 295
ProjectFileManager (class in gitlab.v4.objects), 296
ProjectFork (class in gitlab.v4.objects), 299
ProjectForkManager (class in gitlab.v4.objects), 299
ProjectHook (class in gitlab.v4.objects), 300
ProjectHookManager (class in gitlab.v4.objects), 300
ProjectImport (class in gitlab.v4.objects), 302
ProjectImportManager (class in gitlab.v4.objects), 302
ProjectIntegration (class in gitlab.v4.objects), 302
ProjectIntegrationManager (class in gitlab.v4.objects), 303
ProjectInvitation (class in gitlab.v4.objects), 303
ProjectInvitationManager (class in gitlab.v4.objects), 304
ProjectIssue (class in gitlab.v4.objects), 305
ProjectIssueAwardEmoji (class in gitlab.v4.objects), 306
ProjectIssueAwardEmojiManager (class in gitlab.v4.objects), 307
ProjectIssueDiscussion (class in gitlab.v4.objects), 307
ProjectIssueDiscussionManager (class in gitlab.v4.objects), 308
ProjectIssueDiscussionNote (class in gitlab.v4.objects), 308
ProjectIssueDiscussionNoteManager (class in gitlab.v4.objects), 308
ProjectIssueLink (class in gitlab.v4.objects), 309

ProjectIssueLinkManager (*class in gitlab.v4.objects*), 310
ProjectIssueManager (*class in gitlab.v4.objects*), 310
ProjectIssueNote (*class in gitlab.v4.objects*), 312
ProjectIssueNoteAwardEmoji (*class in gitlab.v4.objects*), 312
ProjectIssueNoteAwardEmojiManager (*class in gitlab.v4.objects*), 312
ProjectIssueNoteManager (*class in gitlab.v4.objects*), 313
ProjectIssueResourceLabelEvent (*class in gitlab.v4.objects*), 314
ProjectIssueResourceLabelEventManager (*class in gitlab.v4.objects*), 314
ProjectIssueResourceMilestoneEvent (*class in gitlab.v4.objects*), 315
ProjectIssueResourceMilestoneEventManager (*class in gitlab.v4.objects*), 315
ProjectIssueResourceStateEvent (*class in gitlab.v4.objects*), 316
ProjectIssueResourceStateManager (*class in gitlab.v4.objects*), 316
ProjectIssuesStatistics (*class in gitlab.v4.objects*), 316
ProjectIssuesStatisticsManager (*class in gitlab.v4.objects*), 317
ProjectIterationManager (*class in gitlab.v4.objects*), 317
ProjectJob (*class in gitlab.v4.objects*), 318
ProjectJobManager (*class in gitlab.v4.objects*), 320
ProjectKey (*class in gitlab.v4.objects*), 321
ProjectKeyManager (*class in gitlab.v4.objects*), 321
ProjectLabel (*class in gitlab.v4.objects*), 322
ProjectLabelManager (*class in gitlab.v4.objects*), 323
ProjectManager (*class in gitlab.v4.objects*), 324
ProjectMember (*class in gitlab.v4.objects*), 332
ProjectMemberAll (*class in gitlab.v4.objects*), 332
ProjectMemberAllManager (*class in gitlab.v4.objects*), 332
ProjectMemberManager (*class in gitlab.v4.objects*), 333
ProjectMergeRequest (*class in gitlab.v4.objects*), 333
ProjectMergeRequestApproval (*class in gitlab.v4.objects*), 337
ProjectMergeRequestApprovalManager (*class in gitlab.v4.objects*), 337
ProjectMergeRequestApprovalRule (*class in gitlab.v4.objects*), 338
ProjectMergeRequestApprovalRuleManager (*class in gitlab.v4.objects*), 339
ProjectMergeRequestApprovalState (*class in gitlab.v4.objects*), 340
ProjectMergeRequestApprovalStateManager (*class in gitlab.v4.objects*), 341
ProjectMergeRequestAwardEmoji (*class in gitlab.v4.objects*), 341
ProjectMergeRequestAwardEmojiManager (*class in gitlab.v4.objects*), 341
ProjectMergeRequestDiff (*class in gitlab.v4.objects*), 342
ProjectMergeRequestDiffManager (*class in gitlab.v4.objects*), 342
ProjectMergeRequestDiscussion (*class in gitlab.v4.objects*), 343
ProjectMergeRequestDiscussionManager (*class in gitlab.v4.objects*), 343
ProjectMergeRequestDiscussionNote (*class in gitlab.v4.objects*), 344
ProjectMergeRequestDiscussionNoteManager (*class in gitlab.v4.objects*), 344
ProjectMergeRequestManager (*class in gitlab.v4.objects*), 345
ProjectMergeRequestNote (*class in gitlab.v4.objects*), 347
ProjectMergeRequestNoteAwardEmoji (*class in gitlab.v4.objects*), 347
ProjectMergeRequestNoteAwardEmojiManager (*class in gitlab.v4.objects*), 348
ProjectMergeRequestNoteManager (*class in gitlab.v4.objects*), 348
ProjectMergeRequestPipeline (*class in gitlab.v4.objects*), 349
ProjectMergeRequestPipelineManager (*class in gitlab.v4.objects*), 349
ProjectMergeRequestResourceLabelEvent (*class in gitlab.v4.objects*), 350
ProjectMergeRequestResourceLabelEventManager (*class in gitlab.v4.objects*), 350
ProjectMergeRequestResourceMilestoneEvent (*class in gitlab.v4.objects*), 351
ProjectMergeRequestResourceMilestoneEventManager (*class in gitlab.v4.objects*), 351
ProjectMergeRequestResourceStateEvent (*class in gitlab.v4.objects*), 352
ProjectMergeRequestResourceStateManager (*class in gitlab.v4.objects*), 352
ProjectMergeTrain (*class in gitlab.v4.objects*), 352
ProjectMergeTrainManager (*class in gitlab.v4.objects*), 353
ProjectMilestone (*class in gitlab.v4.objects*), 353
ProjectMilestoneManager (*class in gitlab.v4.objects*), 354
ProjectNote (*class in gitlab.v4.objects*), 355
ProjectNoteManager (*class in gitlab.v4.objects*), 355
ProjectNotificationSettings (*class in gitlab.v4.objects*), 356
ProjectNotificationSettingsManager (*class in gitlab.v4.objects*), 356

ProjectPackage (*class in gitlab.v4.objects*), 357
ProjectPackageFile (*class in gitlab.v4.objects*), 357
ProjectPackageManager (*class in gitlab.v4.objects*), 358
ProjectPackageManager (*class in gitlab.v4.objects*), 358
ProjectPagesDomain (*class in gitlab.v4.objects*), 358
ProjectPagesDomainManager (*class in gitlab.v4.objects*), 359
ProjectPipeline (*class in gitlab.v4.objects*), 360
ProjectPipelineBridge (*class in gitlab.v4.objects*), 360
ProjectPipelineBridgeManager (*class in gitlab.v4.objects*), 361
ProjectPipelineJob (*class in gitlab.v4.objects*), 361
ProjectPipelineJobManager (*class in gitlab.v4.objects*), 361
ProjectPipelineManager (*class in gitlab.v4.objects*), 361
ProjectPipelineSchedule (*class in gitlab.v4.objects*), 363
ProjectPipelineScheduleManager (*class in gitlab.v4.objects*), 363
ProjectPipelineScheduleVariable (*class in gitlab.v4.objects*), 364
ProjectPipelineScheduleVariableManager (*class in gitlab.v4.objects*), 365
ProjectPipelineTestReport (*class in gitlab.v4.objects*), 365
ProjectPipelineTestReportManager (*class in gitlab.v4.objects*), 365
ProjectPipelineTestReportSummary (*class in gitlab.v4.objects*), 366
ProjectPipelineTestReportSummaryManager (*class in gitlab.v4.objects*), 366
ProjectPipelineVariable (*class in gitlab.v4.objects*), 367
ProjectPipelineVariableManager (*class in gitlab.v4.objects*), 367
ProjectProtectedBranch (*class in gitlab.v4.objects*), 367
ProjectProtectedBranchManager (*class in gitlab.v4.objects*), 368
ProjectProtectedEnvironment (*class in gitlab.v4.objects*), 368
ProjectProtectedEnvironmentManager (*class in gitlab.v4.objects*), 369
ProjectProtectedTag (*class in gitlab.v4.objects*), 369
ProjectProtectedTagManager (*class in gitlab.v4.objects*), 370
ProjectPushRules (*class in gitlab.v4.objects*), 370
ProjectPushRulesManager (*class in gitlab.v4.objects*), 371
ProjectRegistryRepository (*class in gitlab.v4.objects*), 372
ProjectRegistryRepositoryManager (*class in gitlab.v4.objects*), 372
ProjectRegistryTag (*class in gitlab.v4.objects*), 372
ProjectRegistryTagManager (*class in gitlab.v4.objects*), 373
ProjectRelease (*class in gitlab.v4.objects*), 374
ProjectReleaseLink (*class in gitlab.v4.objects*), 374
ProjectReleaseLinkManager (*class in gitlab.v4.objects*), 374
ProjectReleaseManager (*class in gitlab.v4.objects*), 375
ProjectRemoteMirror (*class in gitlab.v4.objects*), 376
ProjectRemoteMirrorManager (*class in gitlab.v4.objects*), 376
ProjectRunner (*class in gitlab.v4.objects*), 377
ProjectRunnerManager (*class in gitlab.v4.objects*), 377
PROJECTS (*gitlab.const.SearchScope attribute*), 427
projects (*gitlab.Gitlab attribute*), 179
projects (*gitlab.v4.objects.Group attribute*), 205
projects (*gitlab.v4.objects.User attribute*), 408
ProjectService (*class in gitlab.v4.objects*), 377
ProjectServiceManager (*class in gitlab.v4.objects*), 378
ProjectSnippet (*class in gitlab.v4.objects*), 378
ProjectSnippetAwardEmoji (*class in gitlab.v4.objects*), 379
ProjectSnippetAwardEmojiManager (*class in gitlab.v4.objects*), 379
ProjectSnippetDiscussion (*class in gitlab.v4.objects*), 380
ProjectSnippetDiscussionManager (*class in gitlab.v4.objects*), 380
ProjectSnippetDiscussionNote (*class in gitlab.v4.objects*), 381
ProjectSnippetDiscussionNoteManager (*class in gitlab.v4.objects*), 381
ProjectSnippetManager (*class in gitlab.v4.objects*), 382
ProjectSnippetNote (*class in gitlab.v4.objects*), 383
ProjectSnippetNoteAwardEmoji (*class in gitlab.v4.objects*), 383
ProjectSnippetNoteAwardEmojiManager (*class in gitlab.v4.objects*), 383
ProjectSnippetNoteManager (*class in gitlab.v4.objects*), 384
ProjectStorage (*class in gitlab.v4.objects*), 385
ProjectStorageManager (*class in gitlab.v4.objects*), 385
ProjectTag (*class in gitlab.v4.objects*), 385
ProjectTagManager (*class in gitlab.v4.objects*), 386
ProjectTrigger (*class in gitlab.v4.objects*), 386
ProjectTriggerManager (*class in gitlab.v4.objects*),

387
ProjectUser (*class in gitlab.v4.objects*), 387
ProjectUserManager (*class in gitlab.v4.objects*), 388
ProjectVariable (*class in gitlab.v4.objects*), 388
ProjectVariableManager (*class in gitlab.v4.objects*), 388
ProjectWiki (*class in gitlab.v4.objects*), 389
ProjectWikiManager (*class in gitlab.v4.objects*), 390
protected_environments (*gitlab.v4.objects.Project attribute*), 262
protectedbranches (*gitlab.v4.objects.Project attribute*), 262
protectedtags (*gitlab.v4.objects.Project attribute*), 262
PUBLIC (*gitlab.const.Visibility attribute*), 428
public() (*gitlab.v4.objects.SnippetManager method*), 402
pushrules (*gitlab.v4.objects.Group attribute*), 205
pushrules (*gitlab.v4.objects.Project attribute*), 262

Q

queue_metrics() (*gitlab.v4.objects.SidekiqManager method*), 400

R

raw() (*gitlab.v4.objects.ProjectArtifactManager method*), 272
raw() (*gitlab.v4.objects.ProjectFileManager method*), 298
rebase() (*gitlab.v4.objects.ProjectMergeRequest method*), 336
RedirectError, 445
refresh() (*gitlab.mixins.RefreshMixin method*), 450
RefreshMixin (*class in gitlab.mixins*), 450
refs() (*gitlab.v4.objects.ProjectCommit method*), 281
register_custom_action() (*in module gitlab.cli*), 426
registry_repositories (*gitlab.Gitlab attribute*), 179
registry_repositories (*gitlab.v4.objects.Group attribute*), 205
RegistryRepository (*class in gitlab.v4.objects*), 390
RegistryRepositoryManager (*class in gitlab.v4.objects*), 391
reject() (*gitlab.v4.objects.User method*), 408
related_merge_requests() (*gitlab.v4.objects.ProjectIssue method*), 306
remove_none_from_dict() (*in module gitlab.utils*), 455
render() (*gitlab.mixins.BadgeRenderMixin method*), 446
reorder() (*gitlab.v4.objects.ProjectIssue method*), 306
repair() (*gitlab.v4.objects.GeoNode method*), 199

REPORTER (*gitlab.const.AccessLevel attribute*), 427
repositories (*gitlab.v4.objects.Project attribute*), 262
repository_archive() (*gitlab.v4.objects.RepositoryMixin method*), 392
repository_blob() (*gitlab.v4.objects.RepositoryMixin method*), 392
repository_compare() (*gitlab.v4.objects.RepositoryMixin method*), 392
repository_contributors() (*gitlab.v4.objects.RepositoryMixin method*), 393
repository_merge_base() (*gitlab.v4.objects.RepositoryMixin method*), 393
repository_raw_blob() (*gitlab.v4.objects.RepositoryMixin method*), 394
repository_tree() (*gitlab.v4.objects.RepositoryMixin method*), 394
RepositoryMixin (*class in gitlab.v4.objects*), 391
reset_approvals() (*gitlab.v4.objects.ProjectMergeRequest method*), 336
reset_spent_time() (*gitlab.mixins.TimeTrackingMixin method*), 452
reset_time_estimate() (*gitlab.mixins.TimeTrackingMixin method*), 452
resource_label_events (*gitlab.v4.objects.GroupEpic attribute*), 217
resource_label_events (*gitlab.v4.objects.ProjectIssue attribute*), 306
resource_label_events (*gitlab.v4.objects.ProjectMergeRequest attribute*), 337
resource_milestone_events (*gitlab.v4.objects.ProjectIssue attribute*), 306
resource_milestone_events (*gitlab.v4.objects.ProjectMergeRequest attribute*), 337
resource_state_events (*gitlab.v4.objects.ProjectIssue attribute*), 306
resource_state_events (*gitlab.v4.objects.ProjectMergeRequest attribute*), 337
response_content() (*in module gitlab.utils*), 455
RESTManager (*class in gitlab.base*), 423
RESTObject (*class in gitlab.base*), 423
RESTObjectList (*class in gitlab.base*), 424
restore() (*gitlab.v4.objects.Project method*), 262
RetrieveMixin (*class in gitlab.mixins*), 450

retry() (*gitlab.v4.objects.ProjectJob method*), 320
retry() (*gitlab.v4.objects.ProjectPipeline method*), 360
revert() (*gitlab.v4.objects.ProjectCommit method*), 282
Runner (*class in gitlab.v4.objects*), 395
RunnerAll (*class in gitlab.v4.objects*), 395
RunnerAllManager (*class in gitlab.v4.objects*), 395
RunnerJob (*class in gitlab.v4.objects*), 396
RunnerJobManager (*class in gitlab.v4.objects*), 396
RunnerManager (*class in gitlab.v4.objects*), 396
runners (*gitlab.Gitlab attribute*), 179
runners (*gitlab.v4.objects.Group attribute*), 205
runners (*gitlab.v4.objects.Project attribute*), 262
runners_all (*gitlab.Gitlab attribute*), 179

S

save() (*gitlab.mixins.SaveMixin method*), 450
save() (*gitlab.v4.objects.GroupEpicIssue method*), 219
save() (*gitlab.v4.objects.GroupLabel method*), 231
save() (*gitlab.v4.objects.ProjectFile method*), 295
save() (*gitlab.v4.objects.ProjectLabel method*), 323
save() (*gitlab.v4.objects.ProjectMergeRequestApprovalRule method*), 339
SaveMixin (*class in gitlab.mixins*), 450
search() (*gitlab.Gitlab method*), 180
search() (*gitlab.v4.objects.Group method*), 205
search() (*gitlab.v4.objects.Project method*), 262
SearchScope (*class in gitlab.const*), 427
services (*gitlab.v4.objects.Project attribute*), 263
session (*gitlab.Gitlab attribute*), 180
set() (*gitlab.mixins.SetMixin method*), 451
set() (*gitlab.v4.objects.FeatureManager method*), 197
set_approvers() (*gitlab.v4.objects.ProjectApprovalManager method*), 269
set_approvers() (*gitlab.v4.objects.ProjectMergeRequestApprovalManager method*), 338
set_license() (*gitlab.Gitlab method*), 180
SetMixin (*class in gitlab.mixins*), 451
settings (*gitlab.Gitlab attribute*), 180
share() (*gitlab.v4.objects.Group method*), 205
share() (*gitlab.v4.objects.Project method*), 263
shared_projects (*gitlab.v4.objects.Group attribute*), 206
SharedProject (*class in gitlab.v4.objects*), 398
SharedProjectManager (*class in gitlab.v4.objects*), 399
sidekiq (*gitlab.Gitlab attribute*), 180
SidekiqManager (*class in gitlab.v4.objects*), 399
signature() (*gitlab.v4.objects.ProjectCommit method*), 282
snapshot() (*gitlab.v4.objects.Project method*), 263
Snippet (*class in gitlab.v4.objects*), 401
SnippetManager (*class in gitlab.v4.objects*), 401
snippets (*gitlab.Gitlab attribute*), 180
snippets (*gitlab.v4.objects.Project attribute*), 264
ssl_verify (*gitlab.Gitlab attribute*), 180
star() (*gitlab.v4.objects.Project method*), 264
starred_projects (*gitlab.v4.objects.User attribute*), 408
StarredProject (*class in gitlab.v4.objects*), 403
StarredProjectManager (*class in gitlab.v4.objects*), 403
status (*gitlab.v4.objects.CurrentUser attribute*), 190
status (*gitlab.v4.objects.User attribute*), 408
status() (*gitlab.v4.objects.GeoNode method*), 200
status() (*gitlab.v4.objects.GeoNodeManager method*), 201
statuses (*gitlab.v4.objects.ProjectCommit attribute*), 282
stop() (*gitlab.v4.objects.ProjectEnvironment method*), 292
storage (*gitlab.v4.objects.Project attribute*), 264
subgroups (*gitlab.v4.objects.Group attribute*), 206
SubscribableMixin (*class in gitlab.mixins*), 451
subscribe() (*gitlab.mixins.SubscribableMixin method*), 451

T

tags (*gitlab.v4.objects.Project attribute*), 264
tags (*gitlab.v4.objects.ProjectRegistryRepository attribute*), 372
take_ownership() (*gitlab.v4.objects.ProjectPipelineSchedule method*), 363
test_report (*gitlab.v4.objects.ProjectPipeline attribute*), 360
test_report_summary (*gitlab.v4.objects.ProjectPipeline attribute*), 360
time_estimate() (*gitlab.mixins.TimeTrackingMixin method*), 452
time_stats() (*gitlab.mixins.TimeTrackingMixin method*), 453
timeout (*gitlab.Gitlab attribute*), 180
TimeTrackingMixin (*class in gitlab.mixins*), 452
to_json() (*gitlab.base.RESTObject method*), 424
Todo (*class in gitlab.v4.objects*), 403
todo() (*gitlab.mixins.TodoMixin method*), 453
TodoManager (*class in gitlab.v4.objects*), 404
TodoMixin (*class in gitlab.mixins*), 453
todos (*gitlab.Gitlab attribute*), 180
Topic (*class in gitlab.v4.objects*), 405
TopicManager (*class in gitlab.v4.objects*), 405
topics (*gitlab.Gitlab attribute*), 181
total (*gitlab.base.RESTObjectList property*), 425
total (*gitlab.GitlabList property*), 182

total_pages (*gitlab.base.RESTObjectList* property), 425
total_pages (*gitlab.GitlabList* property), 182
trace() (*gitlab.v4.objects.ProjectJob* method), 320
transfer() (*gitlab.v4.objects.Group* method), 206
transfer() (*gitlab.v4.objects.Project* method), 264
transfer_project() (*gitlab.v4.objects.Group* method), 206
transfer_project() (*gitlab.v4.objects.Project* method), 264
trigger_pipeline() (*gitlab.v4.objects.Project* method), 264
triggers (*gitlab.v4.objects.Project* attribute), 265

U

unapprove() (*gitlab.v4.objects.ProjectMergeRequest* method), 337
unarchive() (*gitlab.v4.objects.Project* method), 265
unban() (*gitlab.v4.objects.User* method), 408
unblock() (*gitlab.v4.objects.User* method), 408
unfollow() (*gitlab.v4.objects.User* method), 409
unshare() (*gitlab.v4.objects.Group* method), 206
unshare() (*gitlab.v4.objects.Project* method), 265
unstar() (*gitlab.v4.objects.Project* method), 265
unsubscribe() (*gitlab.mixins.SubscribableMixin* method), 451
update() (*gitlab.mixins.UpdateMixin* method), 453
update() (*gitlab.v4.objects.ApplicationAppearanceManager* method), 183
update() (*gitlab.v4.objects.ApplicationSettingsManager* method), 186
update() (*gitlab.v4.objects.GroupLabelManager* method), 233
update() (*gitlab.v4.objects.ProjectFileManager* method), 298
update() (*gitlab.v4.objects.ProjectLabelManager* method), 324
update_submodule() (*gitlab.v4.objects.RepositoryMixin* method), 395
UpdateMixin (*class in gitlab.mixins*), 453
upload() (*gitlab.v4.objects.GenericPackageManager* method), 199
upload() (*gitlab.v4.objects.Project* method), 266
url (*gitlab.Gitlab* property), 181
User (*class in gitlab.v4.objects*), 406
user (*gitlab.Gitlab* attribute), 181
user_activities (*gitlab.Gitlab* attribute), 181
user_agent_detail() (*gitlab.mixins.UserAgentDetailMixin* method), 454
UserActivities (*class in gitlab.v4.objects*), 409
UserActivitiesManager (*class in gitlab.v4.objects*), 409

UserAgentDetailMixin (*class in gitlab.mixins*), 454
UserCustomAttribute (*class in gitlab.v4.objects*), 410
UserCustomAttributeManager (*class in gitlab.v4.objects*), 410
UserEmail (*class in gitlab.v4.objects*), 410
UserEmailManager (*class in gitlab.v4.objects*), 411
UserEvent (*class in gitlab.v4.objects*), 411
UserEventManager (*class in gitlab.v4.objects*), 411
UserGPGKey (*class in gitlab.v4.objects*), 412
UserGPGKeyManager (*class in gitlab.v4.objects*), 412
UserIdentityProviderManager (*class in gitlab.v4.objects*), 413
UserImpersonationToken (*class in gitlab.v4.objects*), 413
UserImpersonationTokenManager (*class in gitlab.v4.objects*), 413
UserKey (*class in gitlab.v4.objects*), 414
UserKeyManager (*class in gitlab.v4.objects*), 414
UserManager (*class in gitlab.v4.objects*), 415
UserMembership (*class in gitlab.v4.objects*), 417
UserMembershipManager (*class in gitlab.v4.objects*), 418
UserPersonalAccessToken (*class in gitlab.v4.objects*), 418
UserPersonalAccessTokenManager (*class in gitlab.v4.objects*), 418
UserProject (*class in gitlab.v4.objects*), 419
UserProjectManager (*class in gitlab.v4.objects*), 419
USERS (*gitlab.const.SearchScope* attribute), 427
users (*gitlab.Gitlab* attribute), 181
users (*gitlab.v4.objects.Project* attribute), 266
UserStatus (*class in gitlab.v4.objects*), 421
UserStatusManager (*class in gitlab.v4.objects*), 421

V

validate() (*gitlab.v4.objects.CiLintManager* method), 190
validate() (*gitlab.v4.objects.ProjectCiLintManager* method), 278
Variable (*class in gitlab.v4.objects*), 421
VariableManager (*class in gitlab.v4.objects*), 422
variables (*gitlab.Gitlab* attribute), 181
variables (*gitlab.v4.objects.Group* attribute), 206
variables (*gitlab.v4.objects.Project* attribute), 266
variables (*gitlab.v4.objects.ProjectPipeline* attribute), 360
variables (*gitlab.v4.objects.ProjectPipelineSchedule* attribute), 363
verify() (*gitlab.v4.objects.RunnerManager* method), 398
version() (*gitlab.Gitlab* method), 181
VerticalHelpFormatter (*class in gitlab.cli*), 425
Visibility (*class in gitlab.const*), 428

W

`warn()` (*in module gitlab.utils*), [455](#)

`WATCH` (*gitlab.const.NotificationLevel attribute*), [427](#)

`WIKI_BLOBS` (*gitlab.const.SearchScope attribute*), [428](#)

`wikis` (*gitlab.v4.objects.Group attribute*), [207](#)

`wikis` (*gitlab.v4.objects.Project attribute*), [266](#)